



SPONSOR PLATINUM



SPONSOR GOLD



SPONSOR SILVER



Security Protocols

Alessandro Armando


Università di Genova

alessandro.armando@unige.it




- 1 Motivation
- 2 Basic notions
- 3 Needham-Schroeder Public Key Authentication Protocol
- 4 Needham-Schroeder Shared-Key Protocol
- 5 Kerberos

Example: Securing an e-banking application.



- How does *Bob* know the message originated from *Alice*?
- How does *Bob* know *Alice* just said it?

Example: Securing an e-banking application.



- How does *Bob* know the message originated from *Alice*?
- How does *Bob* know *Alice* just said it?

Other examples:

- Securing a sensor network.
- A micropayment scheme for a parking company.
- An access control system for area-wide ski lifts.

How would you build distributed algorithms for doing this?

Solutions involve protocols like: IPSec, SSH, PGP, SSL, Kerberos, etc.

We will focus on underlying ideas.

Other examples:

- Securing a sensor network.
- A micropayment scheme for a parking company.
- An access control system for area-wide ski lifts.

How would you build distributed algorithms for doing this?

Solutions involve protocols like: IPSec, SSH, PGP, SSL, Kerberos, etc.

We will focus on underlying ideas.

Other examples:

- Securing a sensor network.
- A micropayment scheme for a parking company.
- An access control system for area-wide ski lifts.

How would you build distributed algorithms for doing this?

Solutions involve protocols like: IPSec, SSH, PGP, SSL, Kerberos, etc.

We will focus on underlying ideas.

Other examples:

- Securing a sensor network.
- A micropayment scheme for a parking company.
- An access control system for area-wide ski lifts.

How would you build distributed algorithms for doing this?

Solutions involve protocols like: IPsec, SSH, PGP, SSL, Kerberos, etc.

We will focus on underlying ideas.

Other examples:

- Securing a sensor network.
- A micropayment scheme for a parking company.
- An access control system for area-wide ski lifts.

How would you build distributed algorithms for doing this?

Solutions involve protocols like: IPSec, SSH, PGP, SSL, Kerberos, etc.

We will focus on underlying ideas.

Other examples:

- Securing a sensor network.
- A micropayment scheme for a parking company.
- An access control system for area-wide ski lifts.

How would you build distributed algorithms for doing this?

Solutions involve protocols like: **IPSec**, **SSH**, **PGP**, **SSL**, **Kerberos**, etc.

We will focus on underlying ideas.

- 1 Motivation
- 2 Basic notions
- 3 Needham-Schroeder Public Key Authentication Protocol
- 4 Needham-Schroeder Shared-Key Protocol
- 5 Kerberos

- A **protocol** consists of a set of rules (conventions) that determine the exchange of messages between two or more principals.
In short, a **distributed algorithm** with emphasis on communication.
- **Security** (or **cryptographic**) protocols use cryptographic mechanisms to achieve security objectives.
Examples: Entity or message authentication, key establishment, integrity, timeliness, fair exchange, non-repudiation, ...
- Small recipes, but nontrivial to design and understand.

- A **protocol** consists of a set of rules (conventions) that determine the exchange of messages between two or more principals.
In short, a **distributed algorithm** with emphasis on communication.
- **Security** (or **cryptographic**) protocols use cryptographic mechanisms to achieve security objectives.
Examples: Entity or message authentication, key establishment, integrity, timeliness, fair exchange, non-repudiation, ...
- Small recipes, but nontrivial to design and understand.

- A **protocol** consists of a set of rules (conventions) that determine the exchange of messages between two or more principals.
In short, a **distributed algorithm** with emphasis on communication.
- **Security** (or **cryptographic**) protocols use cryptographic mechanisms to achieve security objectives.
Examples: Entity or message authentication, key establishment, integrity, timeliness, fair exchange, non-repudiation, ...
- Small recipes, but nontrivial to design and understand.

■ Message constructors are:

Names: A, B or *Alice, Bob, ...*

Keys: K and inverse keys K^{-1}

Encryption: $\{M\}_K$; Example: encryption with A 's public key: $\{M\}_{K_A}$

Signing: $\{M\}_{K^{-1}}$; Example: signing with A 's private key: $\{M\}_{K_A^{-1}}$

Symmetric keys: $\{M\}_{K_{AB}}$

Nonces: N_A , fresh data items used for challenge/response.

Timestamps: T , denote time, e.g., used for key expiration.

Message concatenation: $\{M_1, M_2\}$, $M_1 \parallel M_2$, or $[M_1, M_2]$.

■ Example: $\{A, T_A, K_{AB}\}_{K_B}$

- Message constructors are:

Names: A, B or *Alice, Bob, ...*

Keys: K and inverse keys K^{-1}

Encryption: $\{M\}_K$; Example: encryption with A 's public key: $\{M\}_{K_A}$

Signing: $\{M\}_{K^{-1}}$; Example: signing with A 's private key: $\{M\}_{K_A^{-1}}$

Symmetric keys: $\{M\}_{K_{AB}}$

Nonces: N_A , fresh data items used for challenge/response.

Timestamps: T , denote time, e.g., used for key expiration.

Message concatenation: $\{M_1, M_2\}$, $M_1 || M_2$, or $[M_1, M_2]$.

- Example: $\{A, T_A, K_{AB}\}_{K_B}$

- Message constructors are:

Names: A, B or *Alice, Bob, ...*

Keys: K and inverse keys K^{-1}

Encryption: $\{M\}_K$; Example: encryption with A 's public key: $\{M\}_{K_A}$

Signing: $\{M\}_{K^{-1}}$; Example: signing with A 's private key: $\{M\}_{K_A^{-1}}$

Symmetric keys: $\{M\}_{K_{AB}}$

Nonces: N_A , fresh data items used for challenge/response.

Timestamps: T , denote time, e.g., used for key expiration.

Message concatenation: $\{M_1, M_2\}$, $M_1 || M_2$, or $[M_1, M_2]$.

- Example: $\{A, T_A, K_{AB}\}_{K_B}$

- Message constructors are:

Names: A, B or *Alice, Bob, ...*

Keys: K and inverse keys K^{-1}

Encryption: $\{M\}_K$; Example: encryption with A 's public key: $\{M\}_{K_A}$

Signing: $\{M\}_{K^{-1}}$; Example: signing with A 's private key: $\{M\}_{K_A^{-1}}$

Symmetric keys: $\{M\}_{K_{AB}}$

Nonces: N_A , fresh data items used for challenge/response.

Timestamps: T , denote time, e.g., used for key expiration.

Message concatenation: $\{M_1, M_2\}$, $M_1 || M_2$, or $[M_1, M_2]$.

- Example: $\{A, T_A, K_{AB}\}_{K_B}$

- Message constructors are:

Names: A, B or *Alice, Bob, ...*

Keys: K and inverse keys K^{-1}

Encryption: $\{M\}_K$; Example: encryption with A 's public key: $\{M\}_{K_A}$

Signing: $\{M\}_{K^{-1}}$; Example: signing with A 's private key: $\{M\}_{K_A^{-1}}$

Symmetric keys: $\{M\}_{K_{AB}}$

Nonces: N_A , fresh data items used for challenge/response.

Timestamps: T , denote time, e.g., used for key expiration.

Message concatenation: $\{M_1, M_2\}$, $M_1 || M_2$, or $[M_1, M_2]$.

- Example: $\{A, T_A, K_{AB}\}_{K_B}$

- Message constructors are:

Names: A, B or *Alice, Bob*, ...

Keys: K and inverse keys K^{-1}

Encryption: $\{M\}_K$; Example: encryption with A 's public key: $\{M\}_{K_A}$

Signing: $\{M\}_{K^{-1}}$; Example: signing with A 's private key: $\{M\}_{K_A^{-1}}$

Symmetric keys: $\{M\}_{K_{AB}}$

Nonces: N_A , fresh data items used for challenge/response.

Timestamps: T , denote time, e.g., used for key expiration.

Message concatenation: $\{M_1, M_2\}$, $M_1 || M_2$, or $[M_1, M_2]$.

- Example: $\{A, T_A, K_{AB}\}_{K_B}$

- Message constructors are:

Names: A, B or *Alice, Bob*, ...

Keys: K and inverse keys K^{-1}

Encryption: $\{M\}_K$; Example: encryption with A 's public key: $\{M\}_{K_A}$

Signing: $\{M\}_{K^{-1}}$; Example: signing with A 's private key: $\{M\}_{K_A^{-1}}$

Symmetric keys: $\{M\}_{K_{AB}}$

Nonces: N_A , fresh data items used for challenge/response.

Timestamps: T , denote time, e.g., used for key expiration.

Message concatenation: $\{M_1, M_2\}$, $M_1 || M_2$, or $[M_1, M_2]$.

- Example: $\{A, T_A, K_{AB}\}_{K_B}$

- Message constructors are:

Names: A, B or *Alice, Bob*, ...

Keys: K and inverse keys K^{-1}

Encryption: $\{M\}_K$; Example: encryption with A 's public key: $\{M\}_{K_A}$

Signing: $\{M\}_{K^{-1}}$; Example: signing with A 's private key: $\{M\}_{K_A^{-1}}$

Symmetric keys: $\{M\}_{K_{AB}}$

Nonces: N_A , fresh data items used for challenge/response.

Timestamps: T , denote time, e.g., used for key expiration.

Message concatenation: $\{M_1, M_2\}$, $M_1 || M_2$, or $[M_1, M_2]$.

- Example: $\{A, T_A, K_{AB}\}_{K_B}$

- Message constructors are:

Names: A, B or *Alice, Bob*, ...

Keys: K and inverse keys K^{-1}

Encryption: $\{M\}_K$; Example: encryption with A 's public key: $\{M\}_{K_A}$

Signing: $\{M\}_{K^{-1}}$; Example: signing with A 's private key: $\{M\}_{K_A^{-1}}$

Symmetric keys: $\{M\}_{K_{AB}}$

Nonces: N_A , fresh data items used for challenge/response.

Timestamps: T , denote time, e.g., used for key expiration.

Message concatenation: $\{M_1, M_2\}$, $M_1 \parallel M_2$, or $[M_1, M_2]$.

- Example: $\{A, T_A, K_{AB}\}_{K_B}$

- Message constructors are:

Names: A, B or *Alice, Bob*, ...

Keys: K and inverse keys K^{-1}

Encryption: $\{M\}_K$; Example: encryption with A 's public key: $\{M\}_{K_A}$

Signing: $\{M\}_{K^{-1}}$; Example: signing with A 's private key: $\{M\}_{K_A^{-1}}$

Symmetric keys: $\{M\}_{K_{AB}}$

Nonces: N_A , fresh data items used for challenge/response.

Timestamps: T , denote time, e.g., used for key expiration.

Message concatenation: $\{M_1, M_2\}$, $M_1 \parallel M_2$, or $[M_1, M_2]$.

- Example: $\{A, T_A, K_{AB}\}_{K_B}$

Example: Remote Keyless System

Car Owner



Key Fob



Radio Link



Receiver




Actuator



Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.


Example: Remote Keyless System



Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.


Example: Remote Keyless System



Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.


Example: Remote Keyless System



Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.


Example: Remote Keyless System



Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.


Example: Remote Keyless System



Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.


Example: Remote Keyless System



Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.


Example: Remote Keyless System



Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.

Example: Remote Keyless System



Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.

Assume Serial Number (SN)
is a secret shared between KF and R.

KF sends SN to R:



1. $KF \rightarrow R$: *unlock, SN*

- Bad idea: Attacker can easily overhear SN and *replay* it subsequently.
- Problems:
 - Secrecy of SN compromised.
 - R cannot check authenticity of request

Assume Serial Number (SN)
is a secret shared between KF and R.

KF sends SN to R:



1. $KF \rightarrow R$: *unlock, SN*

■ Bad idea: Attacker can easily overhear SN and *replay* it subsequently.

■ Problems:

- Secrecy of SN compromised.
- R cannot check authenticity of request

Assume Serial Number (SN)
is a secret shared between KF and R.

KF sends SN to R:



1. $KF \rightarrow R$: *unlock, SN*

- Bad idea: Attacker can easily overhear SN and *replay* it subsequently.
- Problems:
 - Secrecy of SN compromised.
 - R cannot check authenticity of request


Idea: protect secrecy of SN

KF encrypts request with shared key (K)
and sends the results to R.



1. $KF \rightarrow R : \{lock, SN\}_K$

- Attacker can easily overhear encrypted request and **replay** it subsequently.
- Secrecy of SN ensured but attack possible anyway.
- R can check authenticity of request; but this is not enough...




Idea: protect secrecy of SN

KF encrypts request with shared key (K) and sends the results to R.



1. $KF \rightarrow R : \{lock, SN\}_K$

- Attacker can easily overhear encrypted request and **replay** it subsequently.
- Secrecy of SN ensured but attack possible anyway.
- R can check authenticity of request; but this is not enough...




Idea: protect secrecy of SN

KF encrypts request with shared key (K) and sends the results to R.



1. $KF \rightarrow R : \{lock, SN\}_K$

- Attacker can easily overhear encrypted request and **replay** it subsequently.
- Secrecy of SN ensured but attack possible anyway.
- R can check authenticity of request; but this is not enough...




Idea: protect secrecy of SN

KF encrypts request with shared key (K) and sends the results to R.



1. $KF \rightarrow R : \{lock, SN\}_K$


- Attacker can easily overhear encrypted request and **replay** it subsequently.
- Secrecy of SN ensured but attack possible anyway.
- R can check authenticity of request; but this is not enough...



The property:

Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.



is met by the protocol.

Yet, the protocol suffers from a *replay attack*.


Security Goal (revised)

Receiver sends unlock command to Actuator *only if* Car Owner *recently* pressed unlock button on Key Fob.

The property:

Security Goal (1st attempt)

Receiver sends unlock command to Actuator *only if* Car Owner *previously* pressed unlock button on Key Fob.



is met by the protocol.

Yet, the protocol suffers from a *replay attack*.

Security Goal (revised)

Receiver sends unlock command to Actuator *only if* Car Owner *recently* pressed unlock button on Key Fob.

KF encrypts a timestamp with shared key K and sends result to R .



1. $KF \rightarrow R : \{unlock, T\}_K$

KF encrypts a timestamp with shared key K and sends result to R .



$$1. KF \rightarrow R : \{unlock, T\}_K$$

- No need to send SN since KF can be identified by shared key.
- Timestamp prevents replay attack, but it requires synchronized clocks on KF and R .

KF encrypts a timestamp with shared key K and sends result to R .



$$1. KF \rightarrow R : \{unlock, T\}_K$$

- No need to send SN since KF can be identified by shared key.
- Timestamp prevents replay attack, but it requires synchronized clocks on KF and R .

Receiver (R) sends Key Fob (KF) a challenge (a nonce, N) and KF sends back N encrypted with shared key (K).



1. $KF \rightarrow R : \text{hello}$
2. $R \rightarrow KF : N$
3. $KF \rightarrow R : \{\text{unlock}, N\}_K$

Receiver (R) sends Key Fob (KF) a challenge (a nonce, N) and KF sends back N encrypted with shared key (K).



1. $KF \rightarrow R : \text{hello}$
2. $R \rightarrow KF : N$
3. $KF \rightarrow R : \{\text{unlock}, N\}_K$

- The usage of the nonce prevents replay attacks.
- Synchronized clocks on KF and R not needed, but additional steps are necessary.

Receiver (R) sends Key Fob (KF) a challenge (a nonce, N) and KF sends back N encrypted with shared key (K).



1. $KF \rightarrow R : \text{hello}$
2. $R \rightarrow KF : N$
3. $KF \rightarrow R : \{\text{unlock}, N\}_K$

- The usage of the nonce prevents replay attacks.
- Synchronized clocks on KF and R not needed, but additional steps are necessary.

- Fundamental events are communication between principals:

1. $A \rightarrow B : \{A, T_A, K\}_{K_B}$
2. $B \rightarrow A : \{B, A\}_K$

- A and B name **roles**.
Can be instantiated by any principal playing in the role.
- Communication is asynchronous
- Sender/receiver names " $A \rightarrow B$ " are not part of the message.
- Protocol specifies actions of principals.
Equivalently, protocol defines a set of event sequences (traces).

- Fundamental events are communication between principals:

$$\begin{aligned} 1. & A \rightarrow B : \{A, T_A, K\}_{K_B} \\ 2. & B \rightarrow A : \{B, A\}_K \end{aligned}$$

- A and B name **roles**.
Can be instantiated by any principal playing in the role.
- Communication is asynchronous
- Sender/receiver names " $A \rightarrow B$ " are not part of the message.
- Protocol specifies actions of principals.
Equivalently, protocol defines a set of event sequences (traces).

- Fundamental events are communication between principals:

$$\begin{aligned} 1. & A \rightarrow B : \{A, T_A, K\}_{K_B} \\ 2. & B \rightarrow A : \{B, A\}_K \end{aligned}$$

- A and B name **roles**.
Can be instantiated by any principal playing in the role.
- Communication is asynchronous
- Sender/receiver names " $A \rightarrow B$ " are not part of the message.
- Protocol specifies actions of principals.
Equivalently, protocol defines a set of event sequences (traces).

- Fundamental events are communication between principals:

$$\begin{aligned} 1. & A \rightarrow B : \{A, T_A, K\}_{K_B} \\ 2. & B \rightarrow A : \{B, A\}_K \end{aligned}$$

- A and B name **roles**.
Can be instantiated by any principal playing in the role.
- Communication is asynchronous
- Sender/receiver names " $A \rightarrow B$ " are not part of the message.
- Protocol specifies actions of principals.
Equivalently, protocol defines a set of event sequences (traces).

- Fundamental events are communication between principals:

$$\begin{aligned} 1. & A \rightarrow B : \{A, T_A, K\}_{K_B} \\ 2. & B \rightarrow A : \{B, A\}_K \end{aligned}$$

- A and B name **roles**.
Can be instantiated by any principal playing in the role.
- Communication is asynchronous
- Sender/receiver names " $A \rightarrow B$ " are not part of the message.
- Protocol specifies actions of principals.
Equivalently, protocol defines a set of event sequences (traces).

- Fundamental events are communication between principals:

$$\begin{aligned} 1. & A \rightarrow B : \{A, T_A, K\}_{K_B} \\ 2. & B \rightarrow A : \{B, A\}_K \end{aligned}$$

- A and B name **roles**.
Can be instantiated by any principal playing in the role.
- Communication is asynchronous
- Sender/receiver names " $A \rightarrow B$ " are not part of the message.
- Protocol specifies actions of principals.
Equivalently, protocol defines a set of event sequences (traces).

Assumptions (for principals):

- Principals know their private keys and public keys of others
- Principals can generate/check nonces and timestamps, encrypt and decrypt with known keys
- (Honest) Principals correctly implement the protocol
- The attacker controls the network, but cannot break crypto.

Goals: What the protocol should achieve. E.g.,

- **Authenticate** messages, binding them to their originator.
- Ensure **timeliness** of messages (recent, fresh, ...)
- Guarantee **secrecy** of certain items (e.g., generated keys).

Assumptions (for principals):

- Principals know their private keys and public keys of others
- Principals can generate/check nonces and timestamps, encrypt and decrypt with known keys
- (Honest) Principals correctly implement the protocol
- The attacker controls the network, but cannot break crypto.

Goals: What the protocol should achieve. E.g.,

- Authenticate messages, binding them to their originator.
- Ensure timeliness of messages (recent, fresh, ...)
- Guarantee secrecy of certain items (e.g., generated keys).

Assumptions (for principals):

- Principals know their private keys and public keys of others
- Principals can generate/check nonces and timestamps, encrypt and decrypt with known keys
- (Honest) Principals correctly implement the protocol
- The attacker controls the network, but cannot break crypto.

Goals: What the protocol should achieve. E.g.,

- Authenticate messages, binding them to their originator.
- Ensure timeliness of messages (recent, fresh, ...)
- Guarantee secrecy of certain items (e.g., generated keys).

Assumptions (for principals):

- Principals know their private keys and public keys of others
- Principals can generate/check nonces and timestamps, encrypt and decrypt with known keys
- (Honest) Principals correctly implement the protocol
- The attacker controls the network, but cannot break crypto.

Goals: What the protocol should achieve. E.g.,

- Authenticate messages, binding them to their originator.
- Ensure timeliness of messages (recent, fresh, ...)
- Guarantee secrecy of certain items (e.g., generated keys).

Assumptions (for principals):

- Principals know their private keys and public keys of others
- Principals can generate/check nonces and timestamps, encrypt and decrypt with known keys
- (Honest) Principals correctly implement the protocol
- The attacker controls the network, but cannot break crypto.

Goals: What the protocol should achieve. E.g.,

- Authenticate messages, binding them to their originator.
- Ensure timeliness of messages (recent, fresh, ...)
- Guarantee secrecy of certain items (e.g., generated keys).

Assumptions (for principals):

- Principals know their private keys and public keys of others
- Principals can generate/check nonces and timestamps, encrypt and decrypt with known keys
- (Honest) Principals correctly implement the protocol
- The attacker controls the network, but cannot break crypto.

Goals: What the protocol should achieve. E.g.,

- **Authenticate** messages, binding them to their originator.
- Ensure **timeliness** of messages (recent, fresh, ...)
- Guarantee **secrecy** of certain items (e.g., generated keys).

Assumptions (for principals):

- Principals know their private keys and public keys of others
- Principals can generate/check nonces and timestamps, encrypt and decrypt with known keys
- (Honest) Principals correctly implement the protocol
- The attacker controls the network, but cannot break crypto.

Goals: What the protocol should achieve. E.g.,

- **Authenticate** messages, binding them to their originator.
- Ensure **timeliness** of messages (recent, fresh, ...)
- Guarantee **secrecy** of certain items (e.g., generated keys).

Assumptions (for principals):

- Principals know their private keys and public keys of others
- Principals can generate/check nonces and timestamps, encrypt and decrypt with known keys
- (Honest) Principals correctly implement the protocol
- The attacker controls the network, but cannot break crypto.

Goals: What the protocol should achieve. E.g.,

- **Authenticate** messages, binding them to their originator.
- Ensure **timeliness** of messages (recent, fresh, ...)
- Guarantee **secrecy** of certain items (e.g., generated keys).

Assumptions (for principals):

- Principals know their private keys and public keys of others
- Principals can generate/check nonces and timestamps, encrypt and decrypt with known keys
- (Honest) Principals correctly implement the protocol
- The attacker controls the network, but cannot break crypto.

Goals: What the protocol should achieve. E.g.,

- **Authenticate** messages, binding them to their originator.
- Ensure **timeliness** of messages (recent, fresh, ...)
- Guarantee **secrecy** of certain items (e.g., generated keys).

How do we model the attacker? Possibilities:

- He knows the protocol but cannot break crypto. (Standard)
- He is **passive** but overhears all communications.
- He is **active** and can intercept and generate messages.
- He might even be one of the principals running the protocol!

How do we model the attacker? Possibilities:

- He knows the protocol but cannot break crypto. (Standard)
- He is **passive** but overhears all communications.
- He is **active** and can intercept and generate messages.
- He might even be one of the principals running the protocol!

How do we model the attacker? Possibilities:

- He knows the protocol but cannot break crypto. (Standard)
- He is **passive** but overhears all communications.
- He is **active** and can intercept and generate messages.
- He might even be one of the principals running the protocol!

How do we model the attacker? Possibilities:

- He knows the protocol but cannot break crypto. (Standard)
- He is **passive** but overhears all communications.
- He is **active** and can intercept and generate messages.
- He might even be one of the principals running the protocol!

- The attacker is active. Namely:
 - He can intercept and read all messages.
 - He can decompose messages into their parts.
But cryptography is secure: decryption requires inverse keys.
 - He can build new messages with the different constructors.
 - He can send messages at any time.
- Sometimes called the **Dolev-Yao** attacker model.
- Strongest possible assumptions about the attacker



correct protocols function in the largest range of environments.

- The attacker is active. Namely:
 - He can intercept and read all messages.
 - He can decompose messages into their parts.
But cryptography is secure: decryption requires inverse keys.
 - He can build new messages with the different constructors.
 - He can send messages at any time.
- Sometimes called the **Dolev-Yao** attacker model.
- Strongest possible assumptions about the attacker



correct protocols function in the largest range of environments.

- The attacker is active. Namely:
 - He can intercept and read all messages.
 - He can decompose messages into their parts.
But cryptography is secure: decryption requires inverse keys.
 - He can build new messages with the different constructors.
 - He can send messages at any time.
- Sometimes called the **Dolev-Yao** attacker model.
- Strongest possible assumptions about the attacker



correct protocols function in the largest range of environments.

- The attacker is active. Namely:
 - He can intercept and read all messages.
 - He can decompose messages into their parts.
But cryptography is secure: decryption requires inverse keys.
 - He can build new messages with the different constructors.
 - He can send messages at any time.
- Sometimes called the **Dolev-Yao** attacker model.
- Strongest possible assumptions about the attacker



correct protocols function in the largest range of environments.

- The attacker is active. Namely:
 - He can intercept and read all messages.
 - He can decompose messages into their parts.
But cryptography is secure: decryption requires inverse keys.
 - He can build new messages with the different constructors.
 - He can send messages at any time.
- Sometimes called the **Dolev-Yao** attacker model.
- Strongest possible assumptions about the attacker



correct protocols function in the largest range of environments.

- The attacker is active. Namely:
 - He can intercept and read all messages.
 - He can decompose messages into their parts.
But cryptography is secure: decryption requires inverse keys.
 - He can build new messages with the different constructors.
 - He can send messages at any time.
- Sometimes called the **Dolev-Yao** attacker model.
- Strongest possible assumptions about the attacker



correct protocols function in the largest range of environments.

- The attacker is active. Namely:
 - He can intercept and read all messages.
 - He can decompose messages into their parts.
But cryptography is secure: decryption requires inverse keys.
 - He can build new messages with the different constructors.
 - He can send messages at any time.
- Sometimes called the **Dolev-Yao** attacker model.
- Strongest possible assumptions about the attacker



correct protocols function in the largest range of environments.

- **Replay** (or **freshness**) **attack**: reuse parts of previous messages.
- **Man-in-the-middle** (or **parallel sessions**) **attack**: $A \leftrightarrow \mathcal{M} \leftrightarrow B$.
- **Reflection attack** send transmitted information back to originator.
- **Type flaw attack**: substitute a different type of message field. Example: use a name (or a key or ...) as a nonce.

- **Replay** (or **freshness**) **attack**: reuse parts of previous messages.
- **Man-in-the-middle** (or **parallel sessions**) **attack**: $A \leftrightarrow \mathcal{M} \leftrightarrow B$.
- **Reflection attack** send transmitted information back to originator.
- **Type flaw attack**: substitute a different type of message field. Example: use a name (or a key or ...) as a nonce.

- **Replay (or freshness) attack**: reuse parts of previous messages.
- **Man-in-the-middle (or parallel sessions) attack**: $A \leftrightarrow \mathcal{M} \leftrightarrow B$.
- **Reflection attack** send transmitted information back to originator.
- **Type flaw attack**: substitute a different type of message field. Example: use a name (or a key or ...) as a nonce.

- **Replay (or freshness) attack**: reuse parts of previous messages.
- **Man-in-the-middle (or parallel sessions) attack**: $A \leftrightarrow \mathcal{M} \leftrightarrow B$.
- **Reflection attack** send transmitted information back to originator.
- **Type flaw attack**: substitute a different type of message field. Example: use a name (or a key or ...) as a nonce.

- 1 Motivation
- 2 Basic notions
- 3 Needham-Schroeder Public Key Authentication Protocol
- 4 Needham-Schroeder Shared-Key Protocol
- 5 Kerberos

- **Goal:** mutual (entity) authentication.
- Correctness argument (informal).

- This is Alice and I have chosen a nonce N_{Alice} .
- Here is your Nonce N_{Alice} . Since I could read it, I must be Bob. I also have a challenge N_{Bob} for you.
- You sent me N_{Bob} . Since only Alice can read this and I sent it back, I must be Alice.

- Recall principals can be involved in multiple runs. Goal should hold in all interleaved protocol runs.

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$

Protocol proposed in 1970s and used for decades.

■ **Goal:** mutual (entity) authentication.

■ Correctness argument (informal).

- This is Alice and I have chosen a nonce N_{Alice} .
- Here is your Nonce N_{Alice} . Since I could read it, I must be Bob. I also have a challenge N_{Bob} for you.
- You sent me N_{Bob} . Since only Alice can read this and I sent it back, I must be Alice.

■ Recall principals can be involved in multiple runs. Goal should hold in all interleaved protocol runs.

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$

Protocol proposed in 1970s and used for decades.

- **Goal:** mutual (entity) authentication.
- Correctness argument (informal).

- 1 This is Alice and I have chosen a nonce N_{Alice} .
 - 2 Here is your Nonce N_{Alice} . Since I could read it, I must be Bob. I also have a challenge N_{Bob} for you.
 - 3 You sent me N_{Bob} . Since only Alice can read this and I sent it back, I must be Alice.
- Recall principals can be involved in multiple runs. Goal should hold in all interleaved protocol runs.

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$

Protocol proposed in 1970s and used for decades.

- **Goal:** mutual (entity) authentication.
- Correctness argument (informal).

- 1 This is Alice and I have chosen a nonce N_{Alice} .
 - 2 Here is your Nonce N_{Alice} . Since I could read it, I must be Bob. I also have a challenge N_{Bob} for you.
 - 3 You sent me N_{Bob} . Since only Alice can read this and I sent it back, I must be Alice.
- Recall principals can be involved in multiple runs. Goal should hold in all interleaved protocol runs.

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$

Protocol proposed in 1970s and used for decades.

- **Goal:** mutual (entity) authentication.
- Correctness argument (informal).

- 1 This is Alice and I have chosen a nonce N_{Alice} .
 - 2 Here is your Nonce N_{Alice} . Since I could read it, I must be Bob. I also have a challenge N_{Bob} for you.
 - 3 You sent me N_{Bob} . Since only Alice can read this and I sent it back, I must be Alice.
- Recall principals can be involved in multiple runs. Goal should hold in all interleaved protocol runs.

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$

Protocol proposed in 1970s and used for decades.

- **Goal:** mutual (entity) authentication.
- Correctness argument (informal).

- 1 This is Alice and I have chosen a nonce N_{Alice} .
- 2 Here is your Nonce N_{Alice} . Since I could read it, I must be Bob. I also have a challenge N_{Bob} for you.
- 3 You sent me N_{Bob} . Since only Alice can read this and I sent it back, I must be Alice.

- Recall principals can be involved in multiple runs. Goal should hold in all interleaved protocol runs.

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$

Protocol proposed in 1970s and used for decades.

- **Goal:** mutual (entity) authentication.
- Correctness argument (informal).


- 1 This is Alice and I have chosen a nonce N_{Alice} .
 - 2 Here is your Nonce N_{Alice} . Since I could read it, I must be Bob. I also have a challenge N_{Bob} for you.
 - 3 You sent me N_{Bob} . Since only Alice can read this and I sent it back, I must be Alice.
- Recall principals can be involved in multiple runs. Goal should hold in all interleaved protocol runs.

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$

Protocol proposed in 1970s and used for decades.


Attack on NSPK

21




Attack on NSPK


21




Attack on NSPK

21







1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$



1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$



1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$

B believes he is speaking with A!




1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$

B believes he is speaking with A!


How can we protect against the previous attack?

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B, B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




How can we protect against the previous attack?

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B, B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




How can we protect against the previous attack?

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B, B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




How can we protect against the previous attack?

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B, B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




How can we protect against the previous attack?

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B, B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




How can we protect against the previous attack?

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B, B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




How can we protect against the previous attack?

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B, B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




How can we protect against the previous attack?

1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B, B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




How can we protect against the previous attack?


1. $A \rightarrow B : \{A, N_A\}_{K_B}$
2. $B \rightarrow A : \{N_A, N_B, B\}_{K_A}$
3. $A \rightarrow B : \{N_B\}_{K_B}$




- 1 Motivation
- 2 Basic notions
- 3 Needham-Schroeder Public Key Authentication Protocol
- 4 Needham-Schroeder Shared-Key Protocol
- 5 Kerberos



Security Goal: Authenticated key exchange.



- If previous session key K_{AB} gets compromised, then the attacker makes B accept K_{AB} again by replaying $\{K_{AB}, A\}_{K_{BS}}$.
- This weakness can be fixed by the inclusion of a timestamp...



- If previous session key K_{AB} gets compromised, then the attacker makes B accept K_{AB} again by replaying $\{K_{AB}, A\}_{K_{BS}}$.
- This weakness can be fixed by the inclusion of a timestamp...

- 1 Motivation
- 2 Basic notions
- 3 Needham-Schroeder Public Key Authentication Protocol
- 4 Needham-Schroeder Shared-Key Protocol
- 5 Kerberos

- Protocol for authentication/access control for client/server applications.
- In Greek mythology, Kerberos is 3-headed dog guarding entrance to Hades. Modern Kerberos intended to have three components to guard a network's gate: authentication, accounting, and audit. Last two heads never implemented.
- Developed as part of Project Athena (MIT, 1980's).
 - Version V (1993) now standard.
 - Widely used, e.g., Microsoft Windows and Microsoft Active Directory.

- Protocol for authentication/access control for client/server applications.
- In Greek mythology, Kerberos is 3-headed dog guarding entrance to Hades. Modern Kerberos intended to have three components to guard a network's gate: authentication, accounting, and audit. Last two heads never implemented.
- Developed as part of Project Athena (MIT, 1980's).
 - Version V (1993) now standard.
 - Widely used, e.g., Microsoft Windows and Microsoft Active Directory.

- Protocol for authentication/access control for client/server applications.
- In Greek mythology, Kerberos is 3-headed dog guarding entrance to Hades. Modern Kerberos intended to have three components to guard a network's gate: authentication, accounting, and audit. Last two heads never implemented.
- Developed as part of Project Athena (MIT, 1980's).
 - Version V (1993) now standard.
 - Widely used, e.g., Microsoft Windows and Microsoft Active Directory.

- Protocol for authentication/access control for client/server applications.
- In Greek mythology, Kerberos is 3-headed dog guarding entrance to Hades. Modern Kerberos intended to have three components to guard a network's gate: authentication, accounting, and audit. Last two heads never implemented.
- Developed as part of Project Athena (MIT, 1980's).
 - Version V (1993) now standard.
 - Widely used, e.g., Microsoft Windows and Microsoft Active Directory.

- Protocol for authentication/access control for client/server applications.
- In Greek mythology, Kerberos is 3-headed dog guarding entrance to Hades. Modern Kerberos intended to have three components to guard a network's gate: authentication, accounting, and audit. Last two heads never implemented.
- Developed as part of Project Athena (MIT, 1980's).
 - Version V (1993) now standard.
 - Widely used, e.g., Microsoft Windows and Microsoft Active Directory.

(Taken from <https://www.kerberos.org/software/tutorial.html>)

- The user's password must never travel over the network;
- The user's password must never be stored in any form on the client machine: it must be immediately discarded after being used;
- The user's password should never be stored in an unencrypted form even in the authentication server database;
- Single Sign-On: The user is asked to enter a password only once per work session. Therefore users can transparently access all the services they are authorized for without having to re-enter the password during this session;

(Taken from <https://www.kerberos.org/software/tutorial.html>)

- The user's password must never travel over the network;
- The user's password must never be stored in any form on the client machine: it must be immediately discarded after being used;
- The user's password should never be stored in an unencrypted form even in the authentication server database;
- Single Sign-On: The user is asked to enter a password only once per work session. Therefore users can transparently access all the services they are authorized for without having to re-enter the password during this session;

(Taken from <https://www.kerberos.org/software/tutorial.html>)

- The user's password must never travel over the network;
- The user's password must never be stored in any form on the client machine: it must be immediately discarded after being used;
- The user's password should never be stored in an unencrypted form even in the authentication server database;
- Single Sign-On: The user is asked to enter a password only once per work session. Therefore users can transparently access all the services they are authorized for without having to re-enter the password during this session;

(Taken from <https://www.kerberos.org/software/tutorial.html>)

- The user's password must never travel over the network;
- The user's password must never be stored in any form on the client machine: it must be immediately discarded after being used;
- The user's password should never be stored in an unencrypted form even in the authentication server database;
- Single Sign-On: The user is asked to enter a password only once per work session. Therefore users can transparently access all the services they are authorized for without having to re-enter the password during this session;

- Authentication information resides on the authentication server only. The application servers must not contain the authentication information for their users. This is essential for obtaining the following results:
 - The administrator can disable the account of any user by acting in a single location without having to act on the several application servers;
 - When a user changes its password, it is changed for all services at the same time;
 - There is no redundancy of authentication information which would otherwise have to be safeguarded in various places;
- Mutual Authentication: not only do the users have to demonstrate that they are who they say, but, when requested, the application servers must prove their authenticity to the client as well.
- Following the completion of authentication and authorization, the client and server must be able to establish an encrypted connection.

- Authentication information resides on the authentication server only. The application servers must not contain the authentication information for their users. This is essential for obtaining the following results:
 - The administrator can disable the account of any user by acting in a single location without having to act on the several application servers;
 - When a user changes its password, it is changed for all services at the same time;
 - There is no redundancy of authentication information which would otherwise have to be safeguarded in various places;
- Mutual Authentication: not only do the users have to demonstrate that they are who they say, but, when requested, the application servers must prove their authenticity to the client as well.
- Following the completion of authentication and authorization, the client and server must be able to establish an encrypted connection.

- Authentication information resides on the authentication server only. The application servers must not contain the authentication information for their users. This is essential for obtaining the following results:
 - The administrator can disable the account of any user by acting in a single location without having to act on the several application servers;
 - When a user changes its password, it is changed for all services at the same time;
 - There is no redundancy of authentication information which would otherwise have to be safeguarded in various places;
- Mutual Authentication: not only do the users have to demonstrate that they are who they say, but, when requested, the application servers must prove their authenticity to the client as well.
- Following the completion of authentication and authorization, the client and server must be able to establish an encrypted connection.


- Authentication information resides on the authentication server only. The application servers must not contain the authentication information for their users. This is essential for obtaining the following results:
 - The administrator can disable the account of any user by acting in a single location without having to act on the several application servers;
 - When a user changes its password, it is changed for all services at the same time;
 - There is no redundancy of authentication information which would otherwise have to be safeguarded in various places;
- Mutual Authentication: not only do the users have to demonstrate that they are who they say, but, when requested, the application servers must prove their authenticity to the client as well.
- Following the completion of authentication and authorization, the client and server must be able to establish an encrypted connection.

- Authentication information resides on the authentication server only. The application servers must not contain the authentication information for their users. This is essential for obtaining the following results:
 - The administrator can disable the account of any user by acting in a single location without having to act on the several application servers;
 - When a user changes its password, it is changed for all services at the same time;
 - There is no redundancy of authentication information which would otherwise have to be safeguarded in various places;
- Mutual Authentication: not only do the users have to demonstrate that they are who they say, but, when requested, the application servers must prove their authenticity to the client as well.
- Following the completion of authentication and authorization, the client and server must be able to establish an encrypted connection.


- Authentication information resides on the authentication server only. The application servers must not contain the authentication information for their users. This is essential for obtaining the following results:
 - The administrator can disable the account of any user by acting in a single location without having to act on the several application servers;
 - When a user changes its password, it is changed for all services at the same time;
 - There is no redundancy of authentication information which would otherwise have to be safeguarded in various places;
- Mutual Authentication: not only do the users have to demonstrate that they are who they say, but, when requested, the application servers must prove their authenticity to the client as well.
- Following the completion of authentication and authorization, the client and server must be able to establish an encrypted connection.

■ Loosely based on the Needham-Schroeder Shared-Key Protocol:


- Timestamps instead of nonces to assure freshness of session keys.
- Removal of nested encryption.




- Loosely based on the Needham-Schroeder Shared-Key Protocol:
 - Timestamps instead of nonces to assure freshness of session keys.
 - Removal of nested encryption.



- Loosely based on the Needham-Schroeder Shared-Key Protocol:
 - Timestamps instead of nonces to assure freshness of session keys.
 - Removal of nested encryption.





Authentication
Authorization
Service

messages 1 and 2.
messages 3 and 4.
messages 5 and 6.

Once per user login session.
Once per type of service.
Once per service session.

We present the three parts below (slightly simplified).

1. $A \rightarrow KAS : A, TGS$
2. $KAS \rightarrow A : \{K_{A,TGS}, TGS, T_1\}_{K_{AS}}, \underbrace{\{A, TGS, K_{A,TGS}, T_1\}_{K_{KAS,TGS}}}_{AuthTicket}$

- A logs onto workstation and requests network resources.
- KAS accesses database and sends A a session key $K_{A,TGS}$ and an encrypted ticket *AuthTicket*.
- $K_{A,TGS}$ has lifetime of several hours (depending on application).
- K_{AS} is derived from the user's password, i.e. $K_{AS} = h(\text{Password}_A || A)$.
- Both user and server keys must be registered in database.
- A types password on client to decrypt results. The ticket and session key are saved. The user's password is forgotten. A is logged out when $K_{A,TGS}$ expires.

1. $A \rightarrow KAS : A, TGS$
2. $KAS \rightarrow A : \{K_{A,TGS}, TGS, T_1\}_{K_{AS}}, \underbrace{\{A, TGS, K_{A,TGS}, T_1\}_{K_{KAS,TGS}}}_{AuthTicket}$

- A logs onto workstation and requests network resources.
- KAS accesses database and sends A a session key $K_{A,TGS}$ and an encrypted ticket *AuthTicket*.
- $K_{A,TGS}$ has lifetime of several hours (depending on application).
- K_{AS} is derived from the user's password, i.e. $K_{AS} = h(\text{Password}_A || A)$.
- Both user and server keys must be registered in database.
- A types password on client to decrypt results. The ticket and session key are saved. The user's password is forgotten. A is logged out when $K_{A,TGS}$ expires.

1. $A \rightarrow KAS : A, TGS$
2. $KAS \rightarrow A : \{K_{A,TGS}, TGS, T_1\}_{K_{AS}}, \underbrace{\{A, TGS, K_{A,TGS}, T_1\}_{K_{KAS,TGS}}}_{AuthTicket}$

- A logs onto workstation and requests network resources.
- KAS accesses database and sends A a session key $K_{A,TGS}$ and an encrypted ticket *AuthTicket*.
- $K_{A,TGS}$ has lifetime of several hours (depending on application).
- K_{AS} is derived from the user's password, i.e. $K_{AS} = h(\text{Password}_A || A)$.
- Both user and server keys must be registered in database.
- A types password on client to decrypt results. The ticket and session key are saved. The user's password is forgotten. A is logged out when $K_{A,TGS}$ expires.

1. $A \rightarrow KAS : A, TGS$
2. $KAS \rightarrow A : \{K_{A,TGS}, TGS, T_1\}_{K_{AS}}, \underbrace{\{A, TGS, K_{A,TGS}, T_1\}_{K_{KAS,TGS}}}_{AuthTicket}$

- A logs onto workstation and requests network resources.
- KAS accesses database and sends A a session key $K_{A,TGS}$ and an encrypted ticket *AuthTicket*.
- $K_{A,TGS}$ has lifetime of several hours (depending on application).
- K_{AS} is derived from the user's password, i.e. $K_{AS} = h(\text{Password}_A || A)$.
- Both user and server keys must be registered in database.
- A types password on client to decrypt results. The ticket and session key are saved. The user's password is forgotten. A is logged out when $K_{A,TGS}$ expires.

1. $A \rightarrow KAS : A, TGS$
2. $KAS \rightarrow A : \{K_{A,TGS}, TGS, T_1\}_{K_{AS}}, \underbrace{\{A, TGS, K_{A,TGS}, T_1\}_{K_{KAS,TGS}}}_{AuthTicket}$

- A logs onto workstation and requests network resources.
- KAS accesses database and sends A a session key $K_{A,TGS}$ and an encrypted ticket *AuthTicket*.
- $K_{A,TGS}$ has lifetime of several hours (depending on application).
- K_{AS} is derived from the user's password, i.e. $K_{AS} = h(\text{Password}_A || A)$.
- Both user and server keys must be registered in database.
- A types password on client to decrypt results. The ticket and session key are saved. The user's password is forgotten. A is logged out when $K_{A,TGS}$ expires.

1. $A \rightarrow KAS : A, TGS$
2. $KAS \rightarrow A : \{K_{A,TGS}, TGS, T_1\}_{K_{AS}}, \underbrace{\{A, TGS, K_{A,TGS}, T_1\}_{K_{KAS,TGS}}}_{AuthTicket}$

- A logs onto workstation and requests network resources.
- KAS accesses database and sends A a session key $K_{A,TGS}$ and an encrypted ticket *AuthTicket*.
- $K_{A,TGS}$ has lifetime of several hours (depending on application).
- K_{AS} is derived from the user's password, i.e. $K_{AS} = h(\text{Password}_A || A)$.
- Both user and server keys must be registered in database.
- A types password on client to decrypt results. The ticket and session key are saved. The user's password is forgotten. A is logged out when $K_{A,TGS}$ expires.

3. $A \rightarrow TGS : \underbrace{\{A, TGS, K_{A,TGS}, \mathcal{T}_1\}_{K_{KAS,TGS}}}_{AuthTicket}, \underbrace{\{A, \mathcal{T}_2\}_{K_{A,TGS}}}_{authenticator}, B$

4. $TGS \rightarrow A : \{K_{AB}, B, \mathcal{T}_3\}_{K_{A,TGS}}, \underbrace{\{A, B, K_{AB}, \mathcal{T}_3\}_{K_{BS}}}_{ServTicket}$

Before A's first access of network resource B:

- A presents *AuthTicket* from message 2 to TGS together with a new *authenticator*, with short (seconds) lifetime.
 - Role of authenticator? Short validity prevent replay attacks.
 - Servers store recent authenticators to prevent immediate replay.
- TGS issues A a new session key K_{AB} (lifetime of few minutes) and a new ticket *ServTicket*. K_{BS} is key shared between TGS and network resource.

3. $A \rightarrow TGS : \underbrace{\{A, TGS, K_{A,TGS}, \mathcal{T}_1\}_{K_{KAS,TGS}}}_{AuthTicket}, \underbrace{\{A, \mathcal{T}_2\}_{K_{A,TGS}}}_{authenticator}, B$

4. $TGS \rightarrow A : \{K_{AB}, B, \mathcal{T}_3\}_{K_{A,TGS}}, \underbrace{\{A, B, K_{AB}, \mathcal{T}_3\}_{K_{BS}}}_{ServTicket}$

Before A's first access of network resource B:

- A presents *AuthTicket* from message 2 to TGS together with a new *authenticator*, with short (seconds) lifetime.
 - Role of authenticator? Short validity prevent replay attacks.
 - Servers store recent authenticators to prevent immediate replay.
- TGS issues A a new session key K_{AB} (lifetime of few minutes) and a new ticket *ServTicket*. K_{BS} is key shared between TGS and network resource.

3. $A \rightarrow TGS : \underbrace{\{A, TGS, K_{A,TGS}, \mathcal{T}_1\}_{K_{KAS,TGS}}}_{AuthTicket}, \underbrace{\{A, \mathcal{T}_2\}_{K_{A,TGS}}}_{authenticator}, B$

4. $TGS \rightarrow A : \{K_{AB}, B, \mathcal{T}_3\}_{K_{A,TGS}}, \underbrace{\{A, B, K_{AB}, \mathcal{T}_3\}_{K_{BS}}}_{ServTicket}$

Before A's first access of network resource B:

- A presents *AuthTicket* from message 2 to TGS together with a new *authenticator*, with short (seconds) lifetime.
 - Role of authenticator? Short validity prevent replay attacks.
 - Servers store recent authenticators to prevent immediate replay.
- TGS issues A a new session key K_{AB} (lifetime of few minutes) and a new ticket *ServTicket*. K_{BS} is key shared between TGS and network resource.

3. $A \rightarrow TGS : \underbrace{\{A, TGS, K_{A,TGS}, \mathcal{T}_1\}_{K_{KAS,TGS}}}_{AuthTicket}, \underbrace{\{A, \mathcal{T}_2\}_{K_{A,TGS}}}_{authenticator}, B$

4. $TGS \rightarrow A : \{K_{AB}, B, \mathcal{T}_3\}_{K_{A,TGS}}, \underbrace{\{A, B, K_{AB}, \mathcal{T}_3\}_{K_{BS}}}_{ServTicket}$

Before A's first access of network resource B:

- A presents *AuthTicket* from message 2 to TGS together with a new *authenticator*, with short (seconds) lifetime.
 - Role of authenticator? Short validity prevent replay attacks.
 - Servers store recent authenticators to prevent immediate replay.
- TGS issues A a new session key K_{AB} (lifetime of few minutes) and a new ticket *ServTicket*. K_{BS} is key shared between TGS and network resource.

3. $A \rightarrow TGS : \underbrace{\{A, TGS, K_{A,TGS}, \mathcal{T}_1\}_{K_{KAS,TGS}}}_{AuthTicket}, \underbrace{\{A, \mathcal{T}_2\}_{K_{A,TGS}}}_{authenticator}, B$

4. $TGS \rightarrow A : \{K_{AB}, B, \mathcal{T}_3\}_{K_{A,TGS}}, \underbrace{\{A, B, K_{AB}, \mathcal{T}_3\}_{K_{BS}}}_{ServTicket}$

Before A's first access of network resource B:

- A presents *AuthTicket* from message 2 to TGS together with a new *authenticator*, with short (seconds) lifetime.
 - Role of authenticator? Short validity prevent replay attacks.
 - Servers store recent authenticators to prevent immediate replay.
- TGS issues A a new session key K_{AB} (lifetime of few minutes) and a new ticket *ServTicket*. K_{BS} is key shared between TGS and network resource.

5. $A \rightarrow B : \underbrace{\{A, B, K_{AB}, \mathcal{T}_3\}_{K_{BS}}}_{\text{ServTicket}}, \underbrace{\{A, \mathcal{T}_4\}_{K_{AB}}}_{\text{authenticator}}$
6. $B \rightarrow A : \{\mathcal{T}_4 + 1\}_{K_{AB}}$

For A to access network resource B:

- A presents K_{AB} from 4 to B along with new *authenticator*.

In practice, other information for server might be sent too.

- B replies, authenticating service.

- $$\begin{aligned}
 5. A \rightarrow B : & \underbrace{\{A, B, K_{AB}, \mathcal{T}_3\}_{K_{BS}}}_{\text{ServTicket}}, \underbrace{\{A, \mathcal{T}_4\}_{K_{AB}}}_{\text{authenticator}} \\
 6. B \rightarrow A : & \{\mathcal{T}_4 + 1\}_{K_{AB}}
 \end{aligned}$$

For A to access network resource B:

- A presents K_{AB} from 4 to B along with new *authenticator*.

In practice, other information for server might be sent too.

- B replies, authenticating service.



SPONSOR PLATINUM



SPONSOR GOLD



SPONSOR SILVER

