

Chat Agent — Mind Map

YoMedia Dashboard · NovaAI · Luồng RAG & Supervisor · 2026-06-08

NovaAI Chat RAG

POST /api/trpc/rag.query · request/response

CLIENT

Chat.tsx — UI chat

- localStorage bubbles (UI only)
- Gemini / OpenAI selector
- File/folder → base64

api.rag.query

- sessionId = conversation.id
- BuildDemoProgress (UI)

L1 CONTROLLER

ragRouter.ts

- protectedProcedure
- Clerk Bearer auth

rag.schema Zod

- assertChatAccess(/chat)
- answerWithRag
- rag.clearSession

SUPERVISOR

runSupervisor

- guardrails
- shortMemory key
- resolveRoute
- runAgents (parallel)
- composeMultiResponse
- appendMemory + log

ROUTING

resolveRoute

- detectTool (Build Demo)
- detectAgentCandidates
- scoring.ts
- classifyIntentWithLlm
- classifyUserIntent (rule)

QA ưu tiên khi tool + rag

AGENTS

rag — knowledge_qa

actions — tools

- help · time_now
- upload_sftp_demo
- compress_demo_assets

free_chat

sql — MySQL

RAG NHÁNH

runRagAgent

- rag/docs/*.md|txt|json
- keyword scoring → top 3
- snippet ~2400 chars

callProvider

- + history (8 turns)
- fallback Gemini ↔ OpenAI
- sources[]

MEMORY

shortMemory server RAM

- key: email::sessionId
- TTL 2h · max 8 turns
- buildDemoAttachments

UI ≠ server memory

- Xóa phiên → clearSession

RESPONSE

answer — markdown text

- intent (knowledge_qa...)
- sources (doc names)
- provider + fallbackUsed
- toolCalled
- buildDemoProcessing
- trace (requestId, spans)

