SeedingMinds

Assessment Name

Java Coding_S2_100196

Module: Coding

Question 1:

Q2 - Print all Even Numbers From an Array

Write a Program to Print the all Even Elements from The Given Array?

Constraints:

Input :- First Line of Input Consists of One Integer Value (Array Size).

Second Line of Input Consists of few Integer Values Separated by Spaces (Array Elements).

Output :- Print All the Even Array Elements.

Constraints :- If there is no Even Elements in a Given Array then Print "**No Even Numbers.**".

Example:

Input 1 : 8

86 210 33 73 53 93 848 48

Output 1: 86 210 848 48

Input 2 : 6

1 2 3 4 5 6

Output 2: 2 4 6

Input 3 : 5

5 10 88 2 5

Output 3: 10 88 2

Explanation:

NA

Public Test Cases:

#	INPUT	EXPECTED OUTPUT
1	8 86 210 33 73 53 93 848 48	86 210 848 48
2	6 1 2 3 4 5 6	2 4 6
3	5 5 10 88 2 5	10 88 2

Question 2:

Vowels and Consonants

Write a Program to print the Number of Vowels and the Remaining Consonants(Not its Count).

Constraints:

Input must be a String.

Input can Contain both **Capital** and **Small Letters**.

If input contains any character other than Alphabets print **Invalid Input.**

Example:

Input 1 : Hmmm

Output 1 : No of Vowels : 0

Consonants : Hmmm

Input 2 : Lagaan

Output 2 : No of Vowels : 3

Consonants : Lgn

Input 3 : j@v@

Output 3 : Invalid Input

Explanation:

NA

Public Test Cases:

#	INPUT	EXPECTED OUTPUT
1	Hmmm	No of Vowels : 0 Consonants : Hmmm
2	Lagaan	No of Vowels : 3 Consonants : Lgn
3	j@v@	Invalid Input

Question 3:

Wildlife Rescue Operation

In a dedicated wildlife conservation center, a team of researchers is tasked with organizing a rescue operation for various endangered species. Each animal has a unique identification number and an associated urgency score based on their condition and the threats they face in the wild. The researchers need to prioritize which animals to rescue first, focusing on those with the highest urgency scores. Your task is to develop a program that collects data about the animals in need of rescue. The program should prompt the user to enter the total number of animals and their respective urgency scores. After collecting the data, the program must sort only the urgency scores while leaving the identification numbers unchanged. Finally, it should output the urgency scores in sorted order and indicate which urgency scores correspond to the animals that were prioritized for rescue.

Constraints:

- The number of animals can be up to 1,000.
- Urgency scores can be any integer value (positive or negative).
- Identification numbers are unique for each animal.

Example:

Example 1:

Input: 101 102 103 104 105
5 2 8 3 7
Output: 103:8, 105:7, 101:5, 104:3, 102:

Example 2:

Input: 801 802 803 804
0 0 0 0
Output: 801:0, 802:0, 803:0, 804:0

Explanation:

Your task is to create a program that efficiently manages and sorts the urgency of animal rescues based on their assigned IDs.Your objective is to sort the animal rescues primarily by their urgency scores in descending order. In cases where multiple animals share the same urgency score, their IDs should be displayed in ascending order. The output should provide a clear listing of each animal ID paired with its urgency score, formatted as ID:Score.

Public Test Cases:

#	INPUT	EXPECTED OUTPUT
1	901 902 903 904 905 4 2 1 4 1	901:4, 904:4, 902:2, 903:1, 905:1
2	1001 1002 1003 15 20 10	1002:20, 1001:15, 1003:10

Question 4:

Cosmic Order Challenge

In the cosmic kingdom of Astrophoria, the Celestial Guardians protect the order of the universe. Each guardian possesses a unique identity represented by a string of characters, signifying their
elemental properties. However, a celestial anomaly has caused the properties to become jumbled, and only
the chosen guardians can restore order through a mystical process called the Cosmic Shift. Each guardian can select up to k of their properties from the beginning of their identity string and shift any
one of them to the end. But here lies the challenge: they are limited to performing no more than m shifts.
The aim is to achieve a lexicographically smallest arrangement while adhering to a set of rules that
complicate the process.
However, there’s an additional requirement: Each time a guardian performs a shift, the string's properties
must maintain a specific order based on their original positions, and they cannot shift the

same character
more than once in a single operation.

Constraints:

- 1 <= k <= s.length <= 1000
- 1 <= m <= 100
- s consists of lowercase English letters.

Example:

Example 1:

Input: ecbda 3 2 2
Output: baecd

Example 2:

Input: apple 3 2
Output: ppeal

Explanation:

Given a string s, two integers k (the number of properties available for selection) and m (the
maximum number of shifts allowed), your task is to determine the smallest possible lexicographic
arrangement of the string after performing no more than m shifts while following the ordering rule

Public Test Cases:

#	INPUT	EXPECTED OUTPUT
1	helloworld 4 5	llwrldehoo
2	zxyw 3 1	zywx