



GW-1101-485 คือ ตัวแปลง RS485/RS422 to Ethernet Modbus Gateway

ตั้งค่าการใช้งานง่ายด้วยโปรแกรม เพียงกดปุ่ม Search

ตัวโปรแกรมจะค้นหาตัว GW-1101-485 อัตโนมัติ

แม้ IP จะอยู่คนละวงกับเครื่องคอมพิวเตอร์

และยังสามารถตั้งค่าต่างๆ ผ่านทาง Web base

และ Command line ได้อีกด้วย **New!**

Description

Features

- 1.Support Modbus TCP, Modbus RTU, Modbus ASCII, IP, ARP, DHCP and DNS protocol
- 2.Support 1 port 10/100M Ethernet
- 3.Support 1 Port RS-485/422
- 4.Support WEB and Telnet configuration
- 5.Convert between Modbus TCP and Modbus RTU/ASCII
- 6.Support RTU Slave, RTU Master, ASCII Slave, ASCII Master four operating modes
- 7.Support ID mapping function, to achieve the management of the host ID
- 8.300bps~115200bps baud rate and nonblocking communication
- 9.Support IP address and MAC address filtering function
- 10.Slave mode support 16 TCP master connections
- 11.Master mode support 32 slave TCP connection requests
- 12.Support Response Timeout and Interval Timeout setting
- 13.Support cross-gateway and cross-router communication
- 14.IP30 protection grade, metal shell, wall mounted installation
- 15.No fan, low consumption design
- 16.Working temperature: -40~75°C

Specification

Ethernet port

Standard: 10Base-T, 100Base-TX

Protocol: Support Modbus TCP, Modbus RTU, Modbus ASCII, IP, APR, ICMP, DNS and DHCP

Signal: Rx+, Rx-, Tx+, Tx-

Speed: 10/100Mbps

Working: Full-duplex and half duplex

Transfer distance: 100m

Connector: RJ45

Serial port

Serial port number: 1 ports RS-485/422

RS-485 signal: D+ (A), D- (B)

RS-422 signal: T+, T-, R+, R-

Parity bit: None, Even, Odd, Space, Mark

Data bit: 7bit, 8bit

Stop bit: 1bit, 2bit

Baud rate: 300bps~115200bps

RS-485/422 transfer distance: 1200m

RS-485/422 connector: 5 bits terminal block

Protection: class 3 static

Master mode: 32 TCP slaves

Slave mode: 16 TCP masters

Work mode: RTU Slave, RTU Master, ASCII Slave, and ASCII Master

LED Indicator

Power (PWR)

Ethernet port connect status (Link)

Serial port data indicator: TX, RX

Power requirements

Input voltage: 9~48VDC

No-load consumption: 0.90W@9VDC

Full-load consumption: 1.16W@9VDC

Environment limits

Working temperature: -40~75°C

Storage temperature: -40~85°C

Relative humidity: 5%~95% (non-condensing)

Mechanical

Shell: IP30 protection, metal shell

Installation: Wall mounting

Weight: 230g

Size (L×W×H): 100mm×69mm×22mm

Standard

EMI: EN 55022 Class A, FCC Part 15 Subpart B Class A

EMS: EN 61000-4-2 (ESD), Level 3

Shock: IEC 60068-2-27

Free fall: IEC 60068-2-32

Vibration: IEC 60068-2-6

Warranty

Warranty time: 3 years

Certificates

CE, FCC, RoHS, UL508 (pending)

Packing List

1. GW1101-1D(RS-485)-P(9~48VDC) ×1

2. User manual ×1

3. Straight network cable ×1

4. Power adapter ×1

5. CD ×1

Optional accessories:

DIN-Rail Mounting Kit (35mm) ×1

Product Support :

- [Modbus Gateway Quick Installation Guide](#)
- [Modbus Gateway user manual](#)
- [Series Modbus Gateway User Manual](#)