Supplementary Information
On The Conservation Laws and Pathway Realizability of Biochemical Reaction Networks

Thanh-An Pham[1] and Tieu-Long Phan[1,2*]

[1]Bioinformatics Group, Department of Computer Science & Interdisciplinary Center for Bioinformatics & School for Embedded and Composite Artificial Intelligence (SECAI), Leipzig University, Härtelstraße 16–18, D-04107, Leipzig, Germany.
[2]Department of Mathematics and Computer Science, University of Southern Denmark, DK-5230, Odense M, Denmark.

*Corresponding author(s). E-mail(s): tieu@bioinf.uni-leipzig.de;
Contributing authors: thanh-an.pham@uni-leipzig.de;

1 Software architecture and analysis interfaces

This supplement describes the chemical reaction network (CRN) submodule of `SynKit`. Figure S1 shows its input adapters and structural analyses built on the shared reaction-system representation. The supplementary examples specify their reaction equations and initial inventories, allowing their results to be interpreted separately from the reduced glycolysis model in the main text.




Fig. S1: Software architecture and data flow in the CRN submodule of `SynKit`. **(A)** Input adapters for `KEGG` pathways, `SBML` Core, and reaction rules. **(B)** Shared core records preserving reactant and product multiplicities. **(C)** Derived stoichiometric, Petri-net, and hypergraph representations. **(D)** Structural analyses: exact rational CRNT invariants, minimal conserved pools, Petri-net siphons/traps, and certified discrete pathway realizability (state/depth limits return `inconclusive`). Icons are schematic.

2 Reaction-network case studies

The two examples examine different substrate constraints: phosphoryl-donor availability in a listed glycolysis network and carbon-precursor multiplicity in a rule-generated formose network. The calculations use the equations and inventories reported below, and do not infer kinetic or physiological behaviour.

2.1 Phosphoryl-donor requirements in an extended glycolysis network

This explicitly listed network combines upper glycolysis with cofactor-coupled alternatives. It is distinct from the 14-species, currency-reduced `KEGG` module used in the main text. Its purpose is to compare qualitative reachability with execution from a finite ATP inventory.

The candidate routes share hexose phosphorylation and aldolase cleavage, but differ in whether the second phosphorylation consumes ATP or ADP. The following tables specify the reaction equations and putative species annotations.

2.1.1 Reaction stoichiometry and metabolite annotation

The `Structure` module constructs a `SynCRN` object from 34 directed reactions involving 40 species. Table S1 lists the complete equations, with identifiers $r1, \ldots, r34$. The biochemical names below are putative annotations, and the structural calculations do not independently validate these identities or enzyme assignments.

Table S1: Directed reaction stoichiometry for the 40-species, 34-reaction extended glycolysis network. Identifiers and coefficients correspond to species annotations in Table S2.

Rule	Reaction
r1	A + B → C + D
r2	E → B + F
r3	C + G → A + H
r4	I → J
r5	J + K + L → M + N + O
r6	J + K + P → M + O + Q
r7	H → J + I
r8	A + M → R + C
r9	R → E
r10	S + C → A + T
r11	S + U → T + V
r12	A + G → W + H
r13	J + 2X + F → 2O + R + 2Y

Continued on next page

Table S1 (continued from previous page)

Rule	Reaction
r14	A + S → T + W
r15	T → G
r16	Z + C → A + B + AA
r17	Z + AB → B + AA + AC
r18	B + F → E
r19	Z + AD → B + AA + AE
r20	F + H → K + G
r21	J → I
r22	M + N + O → J + K + L
r23	M + O + Q → J + K + P
r24	J + I → H
r25	R + C → A + M
r26	E → R
r27	AF + D → AA + AG
r28	L + AH + D → N + O + AA + AI
r29	P + AH + D → O + Q + AA + AI
r30	2X + AH + D → 2O + 2Y + AA + AI
r31	AH + AJ → AI + AK
r32	AG + AL → AF + AJ
r33	L + AK → N + O + AL
r34	AH + AM + D → AA + AI + AN

Species tokens are associated with putative biochemical names and SMILES in Table S2. Structural calculations use the listed reaction coefficients, while annotations aid interpretation and do not independently validate the chemistry.

Table S2: Species tokens, putative biochemical names, and SMILES strings for the extended glycolysis network (Table S1).

Token	Putative biochemical identity	SMILES
A	ADP	`Nc1ncnc2c1ncn2[C@@H]1O[C@H](COP(=O)(O)OP(=O)(O)O)[C@@H](O)[C@H]1O`
B	phosphoenolpyruvate	`C=C(OP(=O)(O)O)C(=O)O`
C	ATP	`Nc1ncnc2c1ncn2[C@@H]1O[C@H](COP(=O)(O)OP(=O)(O)OP(=O)(O)O)[C@@H](O)[C@H]1O`

Continued on next page

Table S2 (continued from previous page)

Token	Putative biochemical identity	SMILES
D	pyruvate	CC(=O)C(=O)O
E	2-phospho-D-glycerate	O=C(O)[C@@H](CO)OP(=O)(O)O
F	water	O
G	D-fructose-6-phosphate	O=P(O)(O)OC[C@H]1OC(O)(CO)[C@@H](O)[C@@H]1O
H	D-fructose-1,6-bisphosphate	O=P(O)(O)OC[C@H]1OC(O)(COP(=O)(O)O)[C@@H](O)[C@@H]1O
I	dihydroxyacetone phosphate	O=C(CO)COP(=O)(O)O
J	D-glyceraldehyde-3-phosphate	O=C[C@H](O)COP(=O)(O)O
K	orthophosphate	O=P(O)(O)O
L	NAD^+	NC(=O)c1ccc[n+]([C@@H]2O[C@H](COP(=O)(O)OP(=O)(O)OC[C@H]3O[C@@H](n4cnc5c(N)ncnc54)[C@H](O)[C@@H]3O)[C@@H](O)[C@H]2O)c1
M	1,3-bisphospho-D-glycerate	O=C(OP(=O)(O)O)[C@H](O)COP(=O)(O)O
N	NADH	NC(=O)C1=CN([C@@H]2O[C@H](COP(=O)(O)OP(=O)(O)OC[C@H]3O[C@@H](n4cnc5c(N)ncnc54)[C@H](O)[C@@H]3O)[C@@H](O)[C@H]2O)C=CC1
O	proton	[H+]
P	$NADP^+$	NC(=O)c1ccc[n+]([C@@H]2O[C@H](COP(=O)(O)OP(=O)(O)OC[C@H]3O[C@@H](n4cnc5c(N)ncnc54)[C@H](OP(=O)(O)O)[C@@H]3O)[C@@H](O)[C@H]2O)c1
Q	NADPH	NC(=O)C1=CN([C@@H]2O[C@H](COP(=O)(O)OP(=O)(O)OC[C@H]3O[C@@H](n4cnc5c(N)ncnc54)[C@H](OP(=O)(O)O)[C@@H]3O)[C@@H](O)[C@H]2O)C=CC1
R	3-phospho-D-glycerate	O=C(O)[C@H](O)COP(=O)(O)O
S	α-D-glucose	OC[C@H]1O[C@H](O)[C@H](O)[C@@H](O)[C@@H]1O
T	α-D-glucose-6-phosphate	O=P(O)(O)OC[C@H]1O[C@H](O)[C@H](O)[C@@H](O)[C@@H]1O
U	triphosphate	O=P(O)(O)OP(=O)(O)OP(=O)(O)O
V	pyrophosphate	O=P(O)(O)OP(=O)(O)O
W	AMP	Nc1ncnc2c1ncn2[C@@H]1O[C@H](COP(=O)(O)O)[C@@H](O)[C@H]1O
X	oxidized [2Fe-2S] ferredoxin	S1[Fe+]S[Fe+]1
Y	reduced [2Fe-2S] ferredoxin	S1[Fe]S[Fe+]1
Z	oxaloacetate	O=C(O)CC(=O)C(=O)O
AA	carbon dioxide	O=C=O
AB	GTP	Nc1nc2c(ncn2[C@@H]2O[C@H](COP(=O)(O)OP(=O)(O)OP(=O)(O)O)[C@@H](O)[C@H]2O)c(=O)[nH]1

Continued on next page

Table S2 (continued from previous page)

Token	Putative biochemical identity	SMILES
AC	GDP	`Nc1nc2c(ncn2[C@@H]2O[C@H](COP(=O)(O)OP(=O)(O)O)[C@@H](O)[C@H]2O)c(=O)[nH]1`
AD	ITP	`O=c1[nH]cnc2c1ncn2[C@@H]1O[C@H](COP(=O)(O)OP(=O)(O)OP(=O)(O)O)[C@@H](O)[C@H]1O`
AE	IDP	`O=c1[nH]cnc2c1ncn2[C@@H]1O[C@H](COP(=O)(O)OP(=O)(O)O)[C@@H](O)[C@H]1O`
AF	thiamine diphosphate (TPP/ThDP)	`Cc1ncc(C[n+]2csc(CCOP(=O)(O)OP(=O)(O)O)c2C)c(N)n1`
AG	2-(α-hydroxyethyl)thiamine diphosphate	`Cc1ncc(C[n+]2c(C(C)O)sc(CCOP(=O)(O)OP(=O)(O)O)c2C)c(N)n1`
AH	coenzyme A	`CC(C)(COP(=O)(O)OP(=O)(O)OC[C@H]1O[C@@H](n2cnc3c(N)ncnc32)[C@H](O)[C@@H]1OP(=O)(O)O)[C@@H](O)C(=O)NCCC(=O)NCCS`
AI	acetyl-CoA	`CC(=O)SCCNC(=O)CCNC(=O)[C@H](O)C(C)(C)COP(=O)(O)OP(=O)(O)OC[C@H]1O[C@@H](n2cnc3c(N)ncnc32)[C@H](O)[C@@H]1OP(=O)(O)O`
AJ	enzyme N^6-(S-acetyldihydrolipoyl)lysine	`*NC(=O)CCCC[C@@H](S)CCSC(C)=O`
AK	enzyme N^6-(dihydrolipoyl)lysine	`*NC(=O)CCCC[C@@H](S)CCS`
AL	enzyme N^6-(lipoyl)lysine	`*NC(=O)CCCC[C@@H]1CCSS1`
AM	oxidized flavodoxin	`CC2(C=C1(N=C3(C(=O)NC(=O)N=C(N(CC(O)C(O)C(O)COP([O-])(=O)[O-])C1=CC(C)=2)3)))`
AN	reduced flavodoxin	`CC2(C=C1(NC3(C(=O)NC(=O)NC(N(CC(O)C(O)C(O)COP([O-])(=O)[O-])C1=CC(C)=2)=3)))`

2.1.2 Automorphisms of the glycolysis reaction graph

Structural automorphism analysis of the species-reaction graph gives group order two. The paired orbits exchange GTP with ITP, GDP with IDP, and reactions r17 with r19. This is an equivalence of the unlabelled reaction structure, not chemical interchangeability of the nucleotide species.

2.1.3 Stoichiometric rank, conservation relations, and Jacobian constraints

We next performed structural diagnostics on the network via the `Props` module. For $|X| = 40$ species and $|\mathscr{R}| = 34$ reactions, the stoichiometric matrix $\mathbf{S} \in \mathbb{Z}^{40\times 34}$ yields:

$$\operatorname{rank}(\mathbf{S}) = 23, \qquad \dim\ker(\mathbf{S}^T) = 17, \qquad \dim\ker(\mathbf{S}) = 11. \tag{1}$$

The nullities count independent linear conservation relations and balanced reaction directions. A right-kernel basis need not be non-negative or executable.

The listed model is conservative and inconsistent under the package's feasibility diagnostics. A positive conservation vector bounds species inventories, while no strictly positive balanced flux involves every reaction. Balanced reaction cycles alone do not establish energy dissipation or thermodynamic infeasibility.

For any differentiable kinetic realization, $\operatorname{rank}(J) \leq \operatorname{rank}(\mathbf{S}) = 23$. A sparsity-pattern matching result can exceed this bound because it ignores algebraic dependencies imposed by $J = \mathbf{S}\,\partial v/\partial c$. Full-space Jacobian singularity therefore does not rule out isolated or stable equilibria within a stoichiometric compatibility class. We make no multistability claim from this diagnostic.

2.1.4 Qualitative reachability of ATP- and ADP-dependent glycolytic routes





Fig. S2: Key metabolite structures in the extended glycolysis network, drawn from the SMILES of Table S2. **(A)** ATP (C). **(B)** α-D-glucose (S). **(C)** D-fructose 1,6-bisphosphate (H). **(D)** D-glyceraldehyde 3-phosphate (J). Parenthesized tokens match Table S2. Sugars are Haworth projections (bold front bonds, substituents up or down), hydrogens on carbon are implicit, and phosphoryl groups are drawn in orange as in Figure S3. The anomeric centre of (C) is drawn without configuration because the listed SMILES leaves it unspecified.

The target is glyceraldehyde-3-phosphate (J), starting from glucose (S) and ATP (C). Both routes pass through fructose-1,6-bisphosphate (H). Figure S2 shows selected metabolite structures. The ADP-dependent phosphorylation in $r12$ corresponds to the reaction recorded as `KEGG R05805` [1].

The two candidate routes each contain four reactions. The ATP-dependent route uses $r10, r15, r3, r7$, whereas the ADP-dependent route replaces $r3$ with $r12$ (Figure S3). Qualitative search admits both because it retains a species in the reachable set after its first use. It therefore does not account for the two ATP molecules consumed by the ATP-dependent sequence.

A Two phosphoryl donors, two substrate requirements



B Checked reaction sequences

Initial inventory	ATP-dependent	ADP-dependent
1 glucose + 1 ATP	✗ Blocked	✓ 4 steps
1 glucose + 2 ATP	✓ 4 steps	✓ 4 steps
1 glucose + 1 ATP + 1 F6P	✗ Blocked	✓ 4 steps

Fig. S3: Phosphoryl-donor selectivity in ATP- versus ADP-dependent upper glycolysis. **(A)** Alternative phosphofructokinase steps: $r3$ (ATP-dependent) versus $r12$ (ADP-dependent) following glucose phosphorylation ($r10$) and isomerization ($r15$) to produce FBP, DHAP, and GAP (blue circles represent carbon count, orange P represents phosphate, and Ado represents adenosine). Branch colours denote realizability from $1 \times \text{Glc} + 1 \times \text{ATP}$. **(B)** Realizability under cofactor supplementation. The ADP-dependent route executes by recycling ADP formed in $r10$, whereas the ATP-dependent route requires a second ATP token (ticks show verified certificates, and crosses indicate exhaustive failure).

2.1.5 Glycolytic pathway realizability under ATP limitation

We next evaluated both candidates under discrete marking semantics using `PathwayRealizability`. For an initial marking of exactly one ATP and one glucose token:

$$m_0 = \{\text{ATP} : 1,\ \alpha\text{-D-glucose} : 1\} = \{C : 1, S : 1\}, \tag{2}$$

only the ADP-dependent route ($r10 \to r15 \to r12 \to r7$) has an executable certificate.

In the listed model, hexokinase ($r10$) consumes the available ATP and produces ADP and glucose 6-phosphate. After isomerization ($r15$), the ATP-dependent phosphorylation ($r3$) lacks its donor. The ADP-dependent reaction ($r12$) can instead consume the ADP formed in $r10$, yielding AMP and FBP. Aldolase ($r7$) then produces the two triose phosphates. All four steps of this sequence pass the independent inventory check.

Both routes were evaluated from the three inventories in Figure S3B: one glucose with one ATP, with two ATP, or with one ATP and one F6P. All positive sequences were independently replayed, and all negative results followed exhaustive searches for the prescribed reaction multiset.

Adding F6P does not make the prescribed ATP-dependent sequence executable: that sequence still consumes ATP in both $r10$ and $r3$. Supplying a second ATP enables it. This conclusion concerns the specified four reactions, rather than all possible routes in the larger network. It illustrates why a list of reachable metabolites cannot determine whether a finite phosphoryl-donor inventory suffices.

2.2 Precursor requirements in a rule-generated formose network

The formose example uses a finite rule-generated network to compare reachable species sets with executable reaction sequences.

Four rules for aldol addition, retro-aldol cleavage, and reversible keto-enol tautomerization expand formaldehyde and glycolaldehyde seeds. The fourth iteration contains 37 species and 44 reactions, where iteration is a graph-expansion depth rather than kinetic time.

The targets are an aldotetrose (T_4) and an aldohexose (T_6). Figure S4 shows their constitutional structures and the selected reactions that form them. Stereochemistry is not assigned in this example.

2.2.1 Network expansion under carbohydrate transformation rules

Table S3 reports counts and times directly from the archived formose evidence. The fourth iteration includes 31 species containing at least four carbons, and reaches ten carbons.

Table S3: Network size and generation time across four iterative formose rule-expansion steps from formaldehyde and glycolaldehyde.

Iteration	Species	Reactions	Generation time (s)
1	3	1	0.050
2	5	4	0.079
3	9	10	0.122
4	37	44	0.280

2.2.2 Automorphisms of the generated formose network

The nested iteration-four network has 81 bipartite nodes and 122 edges. Structural automorphism analysis reports group order 512 and 18 vertex orbits of size two. These symmetries refer to reaction incidence and the selected graph attributes.

Repeated rule application can create equivalent local reaction environments. Graph symmetry does not establish equal reaction rates, equal concentrations, or chemical equivalence of the associated molecules.

2.2.3 Conservation laws, semiflows, and siphon coverage

The stoichiometric matrix $\mathbf{S} \in \mathbb{Z}^{37\times 44}$ has rank $s = 36$, yielding the nullspace dimensions:

$$\dim\ker(\mathbf{S}^T) = 1, \qquad \dim\ker(\mathbf{S}) = 8. \tag{3}$$

The positive left-kernel vector bounds the non-negative compatibility class. Its primitive coefficients match molecular carbon counts in the archived evidence.

The network is conservative but inconsistent: it has a positive conservation vector, but no strictly positive balanced flux covering every reaction. This describes the finite generated network, as generation from seeds does not itself introduce inflow or outflow reactions.

Exact enumeration returns one minimal P-semiflow and seven minimal T-semiflows. There are 15 minimal traps and two minimal siphons. Neither siphon contains a P-semiflow support, so the sufficient persistence test does not certify this model. This does not prove that replenishment is necessary or that extinction occurs.

2.2.4 Qualitative reachability of tetrose and hexose targets

Both targets occur in the iteration-four network, including six constitutional $C_6H_{12}O_6$ isomers. Their presence records products generated by the selected rules.

Under qualitative set semantics (`PathwayFinder`), both targets are reachable from the minimal seed pool $M_{\text{min}} = \{\texttt{C=O}, \texttt{O=CCO}\}$ (Table S4):

- T_4 aldotetrose is reachable at depth 2 via glycolaldehyde enolization followed by aldol coupling with parent glycolaldehyde (Figure S4A, B).
- T_6 aldohexose is reachable at depth 3 via enolization followed by two successive aldol additions (Figure S4A, B, C).

Table S4: Qualitative reachability of aldotetrose (T_4) and aldohexose (T_6) targets from unquantified seeds $M_{\text{min}} = \{\text{formaldehyde}, \text{glycolaldehyde}\}$. Depth indicates the shortest reaction sequence under set reachability.

Target	Present?	Shortest qualitative depth	Reaction sequence
T_4 (aldotetrose)	Yes	2	Tautomerization → aldol addition
T_6 (aldohexose)	Yes	3	Tautomerization → aldol addition → aldol addition

2.2.5 Precursor-dependent realizability of tetrose and hexose routes

We evaluated exact discrete realizability across five initial precursor inventories (Table S5): M_1 (minimal seed), M_2 (carbon-exact for C_4, single glycolaldehyde), M_3 (carbon-exact for C_6, formaldehyde-rich), M_4 (two equivalents of each precursor), and M_5 (three glycolaldehyde molecules).

Pools M_4 and M_5 support the selected tetrose route, whereas only M_5 supports the selected hexose route. The tetrose sequence is:

$$\begin{aligned} \texttt{O=CCO} &\longrightarrow \texttt{OC=CO}, \\ \texttt{OC=CO} + \texttt{O=CCO} &\longrightarrow \texttt{O=CC(O)C(O)CO}. \end{aligned} \tag{4}$$




Fig. S4: Stoichiometry and precursor requirements of the selected formose routes. **(A)** Tautomerization (r_1) of glycolaldehyde to enediol. **(B)** Aldol coupling (r_3) to the aldotetrose (T_4). **(C)** Second aldol coupling (r_7) to the aldohexose (T_6). Firing counts are per route. Structures are constitutional: hydrogens on carbon are implicit, and no stereochemistry or atom mapping is asserted.

Table S5: Discrete pathway realizability of tetrose (T_4) and hexose (T_6) targets across initial precursor inventories. Total carbon denotes aggregate carbon tokens, Yes indicates a verified firing certificate, while No represents exhaustive failure for the prescribed reaction multiset.

Pool	Initial marking m_0	Total carbon	T_4 realizable?	T_6 realizable?
M_1	{`C=O` : 1, `O=CCO` : 1}	3	No	No
M_2	{`C=O` : 2, `O=CCO` : 1}	4	No	No
M_3	{`C=O` : 4, `O=CCO` : 1}	6	No	No
M_4	{`C=O` : 2, `O=CCO` : 2}	6	Yes	No
M_5	{`C=O` : 0, `O=CCO` : 3}	6	Yes	Yes

This sequence consumes two glycolaldehyde molecules. One forms the enediol (`OC=CO`), and the other reacts with that enediol in the aldol-addition step. Pool M_2 contains four carbon atoms but only one glycolaldehyde molecule, so it cannot supply both reactants of the selected route.

The T_4 certificate leaves formaldehyde unchanged. Two glycolaldehyde tokens suffice for this route. This is a route-specific requirement, as a global minimum across alternative pathways would require a separate optimization and completeness argument.

From M_5, the hexose certificate contains four firings: two glycolaldehyde-to-enediol conversions, followed by the tetrose-forming and hexose-forming aldol additions. Thus three glycolaldehyde molecules suffice for this selected sequence. The qualitative depth of three counts enolization only once, whereas execution must supply two enediol molecules. These results do not establish minimum seed inventories across unrestricted formose chemistry.

3 Reference networks and structural validation

Table S6 lists the twelve reference networks and the implementation properties they test. The examples target distinct edge cases rather than representing a random biological cohort.

Table S6: Reference reaction networks, literature sources, and targeted structural validation properties (invariants reported in main-text Figure 2A).

Network model	**Literature source**	**Targeted algebraic / topological property**
Reversible isomerization	Feinberg [2], Ch. 3	Minimal weakly reversible system, Deficiency Zero Theorem (positive branch)
Irreversible isomerization	Feinberg [2], Ch. 3	Deficiency Zero Theorem (negative branch)
Isomerization cycle	Feinberg [2], Ch. 3	Weak reversibility without individual reversible steps
Three disjoint reversible pairs	Synthetic regression	Linkage-class partitioning on disconnected graphs, where minimal semiflow supports must isolate disjoint pairs rather than their union
Disjoint pairs, non-unit stoichiometry	Synthetic regression	As above, with $E \rightleftharpoons 2F$: exact conservation $2E + F$, which naive coefficient rounding can corrupt
Michaelis-Menten	Michaelis & Menten, Feinberg [2]	Archetypal enzyme mechanism with two conserved moiety pools, deficiency $\delta = 0$, non-weakly reversible
Reversible Michaelis-Menten	Feinberg [2]	Identical deficiency ($\delta = 0$), weak reversibility restored
Edelstein bistable switch	Edelstein [3]	Minimal reversible deficiency-one network admitting multiple steady states
Futile cycle (single-site)	Wang & Sontag [4]	Distributive enzymatic cycle with three independent conservation pools
Futile cycle (two-site)	Wang & Sontag [4]	Multi-stationarity motif isolating failure of numerical left-kernel reconstruction
Shinar-Feinberg ACR motif	Shinar & Feinberg [5]	Absolute concentration robustness, with minimal siphon lacking P-semiflow support
Open reactor ($0 \to A \to B \to 0$)	Synthetic benchmark	Explicit zero-complex handling, where cycle closure changes weak reversibility

3.1 Algebraic consistency checks and implementation independence

The validation combines expected values, alternative algebraic formulations, checks on returned vectors, and exhaustive small-network enumeration. Some routes share parsing and matrix-construction helpers. For example, complex composition $\mathbf{Y}$ and complex-graph incidence $\mathbf{I}_a$ give $\mathbf{S} = \mathbf{Y}\mathbf{I}_a$, so the deficiency reported from complexes, linkage classes, and stoichiometric rank must agree with a rank difference computed on the complex graph alone:

$$\delta \;=\; n - \ell - \operatorname{rank}(\mathbf{S}) \;=\; \operatorname{rank}(\mathbf{I}_a) - \operatorname{rank}(\mathbf{Y}\mathbf{I}_a). \tag{5}$$

The two sides use different intermediate quantities, so a disagreement localizes the error to the complex graph, the rank routine, or the stoichiometric assembly. Because both sides are evaluated on the same parsed reaction records, the identity checks internal consistency rather than the parse itself, while the external `CRNT4SBML` comparison covers that step with an independent reader.

Two regression targets motivate these checks: rounding a floating-point kernel basis can violate the exact conservation identity, and inconsistent matrix-row and Petri-place ordering can attach a correct vector to the wrong species. These are reconstruction and indexing errors. They are not evidence that numerical nullspace methods generally fail to approximate the correct subspace.

3.2 Numerical nullspaces and exact integer conservation laws

We compared three operations on the same twelve reference networks: `SciPy`'s floating-point nullspace, the deliberately naive reconstruction round($1000B$) of that basis B, and `SynKit`'s exact integer conservation vectors. Table S7 reports maximum absolute residuals and invalid rounded-vector counts. The scale 1000 is fixed in advance for this illustration, so the result is sensitive to basis choice and is not a comparison against rational-reconstruction algorithms. The zero-dimensional left kernel of the open reactor has no vectors, so its zero residual is vacuous.

Table S7: Conservation residuals of numerical versus exact integer kernel vectors across the reference networks. SVD residual reports max $|\mathbf{S}^T B|$ for floating-point basis B, Rounded invalid counts columns of round($1000B$) with non-zero integer residuals, and Exact residual evaluates `SynKit`'s integer basis. The open reactor has a zero-dimensional conservation space.

Network	SVD residual	Rounded invalid	Exact residual
Reversible isomerization	1.1e-16	0	0
Irreversible isomerization	0.0e+00	0	0
Isomerization cycle	2.2e-16	0	0
Disjoint pairs	1.1e-16	0	0
Non-unit disjoint pairs	1.1e-16	0	0
Michaelis-Menten	2.2e-16	1	0
Reversible Michaelis-Menten	1.7e-16	1	0
Edelstein	0.0e+00	0	0
One-site futile cycle	3.3e-16	3	0
Two-site futile cycle	5.3e-16	0	0
Shinar-Feinberg	1.1e-16	0	0
Open reactor	0.0e+00	0	0

The supplementary audit reconstructs the printed 34-reaction network, verifies its species count and rank, checks ATP-dependent and ADP-dependent routes from one and two ATP tokens, and independently replays each positive certificate. It also verifies the selected formose reaction multisets for all five printed inventories, including the three-glycolaldehyde positive control. These are prescribed-flux tests, and alternative reaction multisets are outside their negative conclusions. Complete structural automorphism searches recover the reported orders two and 512.

4 Computational scaling across network families

The archived main sweep measures directed chains, reversible chains, and random sparse bimolecular networks at four size parameters, with one measurement per configuration and a 300-second per-task limit. The generator also supports cycles, but cycles are not part of that reported sweep. Timed-out measurements are censored, and larger sizes of the same failed task can be skipped.

A new paired study measures closure search and exhaustive subset enumeration at 11, 15, 19, and 21 species, with five repeats and alternating order. The evidence stores raw times, medians, and quartiles, and checks equality of every returned siphon set after aligning species identifiers. It supplies the main scaling panel without extrapolated timings.

In the archived random sparse family, siphons complete in 8.3 s at 197 species and 15.8 s at 395 species, while moiety enumeration exceeds 300 s at 197 species. These observations depend on topology, software, and hardware. They establish neither a polynomial bound for enumeration nor a universal network-size limit.

5 Supplementary structural analyses and runtime comparisons




Fig. S5: Conservation structure and deficiency-theorem diagnostics for the Edelstein network [3]. **(A)** Complex graph and its two linkage classes. **(B)** Stoichiometric matrix (green +1, vermillion −1) beside the primitive conservation vector y, whose product $y^{\mathsf{T}}\mathbf{S}$ vanishes over $\mathbb{Q}$ and certifies the conserved pool [B] + [C]. **(C)** Each classical deficiency theorem fails one hypothesis, leaving multistationarity undecided by deficiency alone.

References

[1] KEGG (2026) KEGG REACTION R05805: ADP:D-fructose-6-phosphate 1-phosphotransferase. https://www.kegg.jp/entry/R05805, accessed 6 September 2026

[2] Feinberg M (2019) Foundations of Chemical Reaction Network Theory, Applied Mathematical Sciences, vol 202. Springer, Cham, doi:10.1007/978-3-030-03858-8

[3] Edelstein BB (1970) Biochemical model with multiple steady states and hysteresis. Journal of Theoretical Biology 29(1):57–62, doi:10.1016/0022-5193(70)90118-9

[4] Wang L, Sontag ED (2008) On the number of steady states in a multiple futile cycle. Journal of Mathematical Biology 57(1):29–52, doi:10.1007/s00285-007-0145-z

[5] Shinar G, Feinberg M (2010) Structural sources of robustness in biochemical reaction networks. Science 327(5971):1389–1391, doi:10.1126/science.1183372




Fig. S6: Structural analysis runtimes across network sizes and topologies (directed chains, reversible chains, and random sparse networks). **(A)** Minimal-siphon enumeration. **(B)** Exact CRNT analysis. **(C)** Graph canonicalization. **(D)** Exact conserved-pool enumeration (triangle: 300 s timeout at 197 species). Points represent single-run timings, with lines as guides to the eye.




Fig. S7: Structural landscape of reference, `KEGG`, `BioModels`, and formose networks. **(A)** Directed reactions versus species (dashed line: $y = x$). **(B)** Complex-count decomposition $n = \ell + s + \delta$ (ℓ linkage classes, s rank, δ deficiency) by network cohort. **(C)** Normalized deficiency δ/n (ticks: cohort medians). **(D)** Weak reversibility (WR) and sufficient siphon persistence coverage (pers., Not assessed: conserved-pool timeout on `BIOMD0000000255`). Reaction-free `SBML-qual` models are omitted.