

Selector and Wait Review

Traceability summary

Feature	Before	Human-reviewed change	Remaining limitation
FR-02	form input <code>nth(0/1)</code> , CSS error class, <code>waitForTimeout(31000)</code>	fields anchored to stable label text and native input; error uses stable text; business window uses <code>expect.poll</code>	SUT labels lack <code>for/id</code> , so <code>getByLabel</code> is unavailable
FR-11	table <code>first()/nth()</code> , <code>tbody</code> CSS, row indexes	rows anchored by exact order-ID cells; status locators use exact text; route fulfillment awaited	UI fixture is mocked by design; API ownership case covers real isolation
FR-14	partial-text rows, raw evaluate click, 300 ms sleep	rows anchored by exact category-name cells; native click; state polling; category tab uses role + stable ASCII prefix	SUT renders mojibake Vietnamese text

No XPath remains. No `nth()` , `waitForTimeout` , click-through-`evaluate` , or arbitrary fixed UI delay remains in the three feature specs/support object. FR-02 retains a 31-second data value only as the requirement's business lock duration; it is not used as a Playwright fixed sleep.

The first FR-14 role locator used normalized Vietnamese and caused a TEST_DEFECT because the SUT actually renders mojibake. Trace evidence led to a role-based listitem locator filtered by the stable ASCII prefix `^Danh` , avoiding dependence on corrupt suffix bytes without changing SUT.

Tests are serial (`workers=1`) and use synthetic run IDs. FR-14 cleanup runs in `finally` for UI mutation cases. FR-11 rows no longer depend on presentation order for action assertions.