

Selecting

DATA MANIPULATION WITH DPLYR



Chris Cardillo

Data Scientist at DataCamp

Select

```
counties %>%  
  select(state, county, population, unemployment)
```

```
# A tibble: 3,138 x 4  
  state    county    population unemployment  
  <chr>   <chr>         <dbl>         <dbl>  
1 Alabama Autauga         55221           7.6  
2 Alabama Baldwin       195121          7.5  
3 Alabama Barbour        26932          17.6  
4 Alabama Bibb           22604           8.3  
5 Alabama Blount         57710           7.7  
6 Alabama Bullock        10678            18  
7 Alabama Butler         20354          10.9  
8 Alabama Calhoun       116648          12.3  
9 Alabama Chambers       34079           8.9  
10 Alabama Cherokee      26008           7.9  
# ... with 3,128 more rows
```

Select a range

```
counties %>%  
  select(state, county, drive:work_at_home)
```

```
# A tibble: 3,138 x 8  
  state    county    drive carpool transit  walk other_transp work_at_home  
  <chr>   <chr>   <dbl>  <dbl>  <dbl> <dbl>         <dbl>         <dbl>  
1 Alabama Autauga    87.5    8.8    0.1  0.5          1.3          1.8  
2 Alabama Baldwin   84.7    8.8    0.1  1           1.4          3.9  
3 Alabama Barbour   83.8   10.9    0.4  1.8          1.5          1.6  
4 Alabama Bibb      83.2   13.5    0.5  0.6          1.5          0.7  
5 Alabama Blount    84.9   11.2    0.4  0.9          0.4          2.3  
6 Alabama Bullock   74.9   14.9    0.7  5            1.7          2.8  
7 Alabama Butler    84.5   12.4    0    0.8          0.6          1.7  
8 Alabama Calhoun   85.3    9.4    0.2  1.2          1.2          2.7  
9 Alabama Chambers  85.1   11.9    0.2  0.3          0.4          2.1  
10 Alabama Cherokee 83.9   12.1    0.2  0.6          0.7          2.5  
# ... with 3,128 more rows
```

Select and arrange

```
counties %>%  
  select(state, county, drive:work_at_home) %>%  
  arrange(drive)
```

```
# A tibble: 3,138 x 8  
  state      county      drive carpool transit  walk other_transp work_at_home  
  <chr>    <chr>      <dbl>  <dbl>  <dbl> <dbl>      <dbl>      <dbl>  
1 New York New York      6.1    1.9   59.2  20.7      5.4      6.8  
2 Alaska  Northwest Arctic Borough 16.5   10.4    0.4  46.9     21.2     4.6  
3 Alaska  Aleutians East Borough  18.4    4.9    0.5  71.2     2.2     2.8  
4 New York Kings      18.6    4.4   61.7    8.8     2.5     3.9  
5 Alaska  North Slope Borough    20.1    17     2.8  37.9     7.9    14.3  
6 Alaska  Lake and Peninsula Borough 21.2    6.8    1.1  36.2    32.4     2.4  
7 New York Bronx      22.5    4.7   59.7    8      1.8     3.3  
8 Alaska  Nome Census Area      25.8   10     0.3  36.9    22.7     4.3  
9 Alaska  Bethel Census Area     26.5   12.7    0.5  33     22.6     4.8  
10 Alaska Yukon-Koyukuk Census Area 28.7    8.1    0.2  38.1    20.1     4.9  
# ... with 3,128 more rows
```

Contains

```
counties %>%  
  select(state, county, contains("work"))
```

```
# A tibble: 3,138 x 6  
  state    county work_at_home private_work public_work family_work  
  <chr>   <chr>         <dbl>         <dbl>         <dbl>         <dbl>  
1 Alabama Autauga          1.8           73.6           20.9           0  
2 Alabama Baldwin          3.9           81.5           12.3           0.4  
3 Alabama Barbour          1.6           71.8           20.8           0.1  
4 Alabama Bibb              0.7           76.8           16.1           0.4  
5 Alabama Blount           2.3           82            13.5           0.4  
6 Alabama Bullock          2.8           79.5           15.1           0  
7 Alabama Butler           1.7           77.4           16.2           0.2  
8 Alabama Calhoun          2.7           74.1           20.8           0.1  
9 Alabama Chambers         2.1           85.1           12.1           0  
10 Alabama Cherokee         2.5           73.1           18.5           0.5  
# ... with 3,128 more rows
```

Starts with

```
counties %>%  
  select(state, county, starts_with("income"))
```

```
# A tibble: 3,138 x 6  
  state    county    income income_err income_per_cap income_per_cap_err  
  <chr>   <chr>   <dbl>     <dbl>         <dbl>         <dbl>  
1 Alabama Autauga    51281      2391         24974          1080  
2 Alabama Baldwin    50254      1263         27317           711  
3 Alabama Barbour    32964      2973         16824           798  
4 Alabama Bibb       38678      3995         18431          1618  
5 Alabama Blount     45813      3141         20532           708  
6 Alabama Bullock    31938      5884         17580          2055  
7 Alabama Butler     32229      1793         18390           714  
8 Alabama Calhoun    41703       925         21374           489  
9 Alabama Chambers   34177      2949         21071          1366  
10 Alabama Cherokee  36296      1710         21811          1556  
# ... with 3,128 more rows
```

Other helpers

- `contains()`
- `starts_with()`
- `ends_with()`
- `last_col()`

For more:

```
?select_helpers
```

Removing a variable

```
counties %>%  
  select(-census_id)
```

```
# A tibble: 3,138 x 39  
  state county region metro population   men women hispanic white black native asian pacific citizens income  
  <chr> <chr>   <chr> <chr>      <dbl> <dbl> <dbl>   <dbl> <dbl> <dbl> <dbl> <dbl>   <dbl>   <dbl>  
1 Alab... Autau... South Metro    55221 26745 28476     2.6  75.8  18.5    0.4    1      0    40725  51281  
2 Alab... Baldw... South Metro   195121 95314 99807     4.5  83.1   9.5    0.6    0.7    0   147695  50254  
3 Alab... Barbo... South Nonm...    26932 14497 12435     4.6  46.2  46.7    0.2    0.4    0    20714  32964  
4 Alab... Bibb    South Metro    22604 12073 10531     2.2  74.5  21.4    0.4    0.1    0    17495  38678  
5 Alab... Blount South Metro    57710 28512 29198     8.6  87.9   1.5    0.3    0.1    0    42345  45813  
6 Alab... Bullo... South Nonm...    10678  5660  5018     4.4  22.2  70.7    1.2    0.2    0     8057  31938  
7 Alab... Butler South Nonm...    20354  9502 10852     1.2  53.3  43.8    0.1    0.4    0    15581  32229  
8 Alab... Calho... South Metro   116648 56274 60374     3.5   73    20.3    0.2    0.9    0    88612  41703  
9 Alab... Chamb... South Nonm...    34079 16258 17821     0.4  57.3  40.3    0.2    0.8    0    26462  34177  
10 Alab... Chero... South Nonm...    26008 12975 13033     1.5  91.7   4.8    0.6    0.3    0    20600  36296  
# ... with 3,128 more rows, and 24 more variables: income_err <dbl>, income_per_cap <dbl>,  
# income_per_cap_err <dbl>, poverty <dbl>, child_poverty <dbl>, professional <dbl>, service <dbl>,  
# office <dbl>, construction <dbl>, production <dbl>, drive <dbl>, carpool <dbl>, transit <dbl>, walk <dbl>,  
# other_transp <dbl>, work_at_home <dbl>, mean_commute <dbl>, employed <dbl>, private_work <dbl>,  
# public_work <dbl>, self_employed <dbl>, family_work <dbl>, unemployment <dbl>, land_area <dbl>
```


Let's practice!

DATA MANIPULATION WITH DPLYR

The rename verb

DATA MANIPULATION WITH DPLYR



Chris Cardillo

Data Scientist at DataCamp

Select columns

```
counties_selected <- counties %>%  
  select(state, county, population, unemployment)
```

```
counties_selected
```

```
# A tibble: 3,138 x 4  
  state  county  population unemployment  
  <chr>  <chr>      <dbl>      <dbl>  
1 Alabama Autauga      55221        7.6  
2 Alabama Baldwin    195121        7.5  
3 Alabama Barbour     26932       17.6  
4 Alabama Bibb        22604         8.3  
5 Alabama Blount      57710         7.7  
6 Alabama Bullock     10678         18  
7 Alabama Butler      20354       10.9  
8 Alabama Calhoun    116648       12.3  
9 Alabama Chambers    34079         8.9  
10 Alabama Cherokee   26008         7.9  
# ... with 3,128 more rows
```

Rename a column

```
counties_selected %>%  
  rename(unemployment_rate = unemployment)
```

```
# A tibble: 3,138 x 4  
  state    county    population unemployment_rate  
  <chr>   <chr>         <dbl>         <dbl>  
1 Alabama Autauga      55221          7.6  
2 Alabama Baldwin    195121         7.5  
3 Alabama Barbour    26932         17.6  
4 Alabama Bibb       22604          8.3  
5 Alabama Blount     57710          7.7  
6 Alabama Bullock    10678          18  
7 Alabama Butler     20354         10.9  
8 Alabama Calhoun    116648         12.3  
9 Alabama Chambers   34079          8.9  
10 Alabama Cherokee  26008          7.9  
# ... with 3,128 more rows
```

Combine verbs

```
counties_selected %>%  
  select(state, county, population, unemployment_rate = unemployment)
```

```
# A tibble: 3,138 x 4  
  state    county    population unemployment_rate  
  <chr>   <chr>         <dbl>         <dbl>  
1 Alabama Autauga         55221          7.6  
2 Alabama Baldwin       195121         7.5  
3 Alabama Barbour        26932        17.6  
4 Alabama Bibb           22604         8.3  
5 Alabama Blount         57710         7.7  
6 Alabama Bullock        10678         18  
7 Alabama Butler         20354        10.9  
8 Alabama Calhoun       116648        12.3  
9 Alabama Chambers       34079         8.9  
10 Alabama Cherokee      26008         7.9  
# ... with 3,128 more rows
```

Compare verbs

Select

```
counties %>%  
  select(state, county, population, unemployment_rate = unemployment)
```

Rename

```
counties %>%  
  select(state, county, population, unemployment) %>%  
  rename(unemployment_rate = unemployment)
```

Let's practice!

DATA MANIPULATION WITH DPLYR

The transmute verb

DATA MANIPULATION WITH DPLYR



Chris Cardillo

Data Scientist at DataCamp

Transmute

- Combination: select & mutate
- Returns a subset of columns that are transformed and changed

Select and calculate

```
counties %>%  
  transmute(state, county, fraction_men = men / population)
```

```
# A tibble: 3,138 x 3  
  state    county fraction_men  
  <chr>   <chr>         <dbl>  
1 Alabama Autauga      0.484  
2 Alabama Baldwin      0.488  
3 Alabama Barbour      0.538  
4 Alabama Bibb          0.534  
5 Alabama Blount        0.494  
6 Alabama Bullock       0.530  
7 Alabama Butler        0.467  
8 Alabama Calhoun        0.482  
9 Alabama Chambers      0.477  
10 Alabama Cherokee      0.499  
# ... with 3,128 more rows
```

Select and calculate

```
counties %>%  
  transmute(state, county, population, unemployed_people = population * unemployment / 100)
```

```
# A tibble: 3,138 x 4  
  state    county    population unemployed_people  
  <chr>   <chr>         <dbl>         <dbl>  
1 Alabama Autauga      55221          4197.  
2 Alabama Baldwin    195121        14634.  
3 Alabama Barbour     26932          4740.  
4 Alabama Bibb        22604          1876.  
5 Alabama Blount      57710          4444.  
6 Alabama Bullock     10678          1922.  
7 Alabama Butler      20354          2219.  
8 Alabama Calhoun    116648        14348.  
9 Alabama Chambers    34079          3033.  
10 Alabama Cherokee   26008          2055.  
# ... with 3,128 more rows
```

Summary

	Keeps only specified variables	Keeps other variables
Can't change values	select	rename
Can change values	transmute	mutate

Summary

	Keeps only specified variables	Keeps other variables
Can't change values	<code>select</code>	<code>rename</code>
Can change values	<code>transmute</code>	<code>mutate</code>

Summary

	Keeps only specified variables	Keeps other variables
Can't change values	select	rename
Can change values	transmute	mutate

Summary

	Keeps only specified variables	Keeps other variables
Can't change values	<code>select</code>	<code>rename</code>
Can change values	<code>transmute</code>	<code>mutate</code>

Summary

	Keeps only specified variables	Keeps other variables
Can't change values	select	rename
Can change values	transmute	mutate

Summary

	Keeps only specified variables	Keeps other variables
Can't change values	select	rename
Can change values	transmute	mutate

Let's practice!

DATA MANIPULATION WITH DPLYR