

systemctl: Mastering Linux Service Management

© Dan Mill Training

Ever wondered how to start, stop, or check the status of services in Linux? Meet **systemctl** - your command-line remote control for managing system services! Whether you need to restart a web server, check if SSH is running, or configure services to start at boot, systemctl is your go-to tool.

What is systemctl?

systemctl is the command-line interface for **systemd**, the modern Linux system and service manager. Think of it as the remote control for all the background services (daemons) running on your Linux system.

What Are Services?

Services are background programs that run continuously, such as:

- **SSH server** (sshd) - Remote access
- **Web server** (apache2/nginx) - Websites
- **Database** (mysql/postgresql) - Data storage
- **Network manager** - Internet connectivity
- **Firewall** (ufw/iptables) - Security

Essential systemctl Commands

Checking Service Status

```
bash

systemctl status [service-name]
```

Examples:

```
bash

systemctl status ssh      # Check SSH service
systemctl status apache2  # Check Apache web server
systemctl status mysql    # Check MySQL database
systemctl status networking # Check network service
```

Understanding Status Output:

- ssh.service - OpenBSD Secure Shell server
Loaded: loaded (/lib/systemd/system/ssh.service; enabled; vendor preset: enabled)
Active: active (running) since Mon 2024-01-15 10:30:15 UTC; 2h 15min ago
Docs: man:sshd(8)
Main PID: 1234 (sshd)
Tasks: 1 (limit: 4915)
Memory: 2.1M
CGroup: /system.slice/ssh.service
└─1234 /usr/sbin/sshd -D

Key indicators:

- **Active: active (running)** = Service is working 
- **Active: inactive (dead)** = Service is stopped 
- **Active: failed** = Service crashed 

Starting and Stopping Services

```
bash

sudo systemctl start [service-name]    # Start service
sudo systemctl stop [service-name]     # Stop service
sudo systemctl restart [service-name]  # Restart service
sudo systemctl reload [service-name]   # Reload config without restart
```

Examples:

```
bash

sudo systemctl start apache2    # Start web server
sudo systemctl stop mysql      # Stop database
sudo systemctl restart ssh      # Restart SSH service
sudo systemctl reload nginx     # Reload web server config
```

Enabling and Disabling Services (Boot Behavior)

```
bash

sudo systemctl enable [service-name]  # Start at boot
sudo systemctl disable [service-name] # Don't start at boot
```

Examples:

```
bash
```

```
sudo systemctl enable apache2    # Web server starts at boot
sudo systemctl disable bluetooth  # Bluetooth won't start at boot
```

Viewing All Services

List All Services

```
bash

systemctl list-units --type=service
```

List Only Running Services

```
bash

systemctl list-units --type=service --state=running
```

List Failed Services

```
bash

systemctl list-units --type=service --state=failed
```

List Enabled Services (Start at Boot)

```
bash

systemctl list-unit-files --type=service --state=enabled
```

Quick Reference Table

Task	Command
Check status	<code>systemctl status [service]</code>
Start service	<code>sudo systemctl start [service]</code>
Stop service	<code>sudo systemctl stop [service]</code>
Restart service	<code>sudo systemctl restart [service]</code>
Enable at boot	<code>sudo systemctl enable [service]</code>
Disable at boot	<code>sudo systemctl disable [service]</code>
View logs	<code>journalctl -u [service]</code>
List all services	<code>systemctl list-units --type=service</code>
List running	<code>systemctl list-units --type=service --state=running</code>
List failed	<code>systemctl list-units --failed</code>

Remember: systemctl is your Swiss Army knife for Linux service management - master these basics and you'll handle most system administration tasks with confidence!