

CORE



```
CORE#conf t
Enter configuration commands, one per line. End with CNTL/Z.
CORE(config)#vlan
*Sep 21 10:04:26.207: %SPAN TREE-2-UNBLOCK_CONSIST_PORT: Unblocking Ethernet0/0 on VLAN0001. Port consistency restored.
CORE(config)#vlan 10
CORE(config-vlan)#exit
CORE(config)#vlan 20
CORE(config-vlan)#exit
CORE(config)#int e0/0
CORE(config-if)#switchport trunk encapsulation dot1q
CORE(config-if)#switchport mode trunk
CORE(config-if)#exit
CORE(config)#
CORE(config)#
CORE(config)#
CORE(config)#
CORE(config)#int vlan 10
CORE(config-if)#ip add
*Sep 21 10:05:27.489: %LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan10, changed state to down
CORE(config-if)#ip add 10.0.0.1 255.0.0.0
CORE(config-if)#no sh
CORE(config-if)#exit
CORE(config)#
*Sep 21 10:05:39.048: %LINK-3-UPDOWN: Interface Vlan10, changed state to up
*Sep 21 10:05:40.049: %LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan10, changed state to up
CORE(config)#int vlan 20
CORE(config-if)#ip add
*Sep 21 10:05:45.136: %LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan20, changed state to down
CORE(config-if)#ip add 20.0.0.1 255.0.0.0
CORE(config-if)#no sh
CORE(config-if)#exit
CORE(config)#
CORE(config)#i
*Sep 21 10:05:59.319: %LINK-3-UPDOWN: Interface Vlan20, changed state to up
*Sep 21 10:06:00.320: %LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan20, changed state to up
CORE(config)#ip routing
CORE(config)#
CORE(config)#
CORE(config)#int e0/1
CORE(config-if)#no switchport
CORE(config-if)#ip add 1
*Sep 21 10:06:43.140: %LINK-3-UPDOWN: Interface Ethernet0/1, changed state to up
*Sep 21 10:06:44.140: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet0/1, changed state to up
CORE(config-if)#ip add 1.0.0.1 255.0.0.0
CORE(config-if)#no sh
CORE(config-if)#exit
CORE(config)#
CORE(config)#
```

Trying 49.204.127.18...

Connected to labs.surennetwork.com.

Escape character is '^']'.

L2-SW-1#

L2-SW-1#

L2-SW-1#conf t

Enter configuration commands, one per line. End with CNTL/Z.

L2-SW-1(config)#vlan 10

L2-SW-1(config-vlan)#name HR

L2-SW-1(config-vlan)#exit

L2-SW-1(config)#vlan 20

L2-SW-1(config-vlan)#name Sales

L2-SW-1(config-vlan)#exit

L2-SW-1(config)#int

*Sep 21 09:36:53.321: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)

L2-SW-1(config)#int e0/0

L2-SW-1(config-if)#switchport access vlan 10

L2-SW-1(config-if)#exit

L2-SW-1(config)#int e0/1

L2-SW-1(config-if)#switchport access vlan 20

L2-SW-1(config-if)#exit

L2-SW-1(config)#

L2-SW-1(config)#

L2-SW-1(config)#int e0/2

L2-SW-1(config-if)#switchport trunk encapsulation dot1q

L2-SW-1(config-if)#switchport access trunk

^

% Invalid input detected at '^' marker.

L2-SW-1(config-if)#switchport mode trunk

L2-SW-1(config-if)#exit

L2-SW-1(config)#exit

L2-SW-1#

L2-SW-1#

L2-SW-1#

L2-SW-1#

*Sep 21 09:39:02.499: %SYS-5-CONFIG_I: Configured from console by console

L2-SW-1#

ROUTER

```
ROUTER#
ROUTER#
ROUTER#
ROUTER#conf t
Enter configuration commands, one per line. End with CNTL/Z.
ROUTER(config)#int e0/
*Sep 21 09:52:38.909: %LINK-3-UPDOWN: Interface Ethernet0/2, changed state to down
*Sep 21 09:52:38.914: %LINK-3-UPDOWN: Interface Ethernet0/3, changed state to down
*Sep 21 09:52:39.909: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet0/2, changed state to down
*Sep 21 09:52:39.918: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet0/3, changed state to down
ROUTER(config)#int e0/1
ROUTER(config-if)#ip add 1.0.0.2 255.0.0.0
ROUTER(config-if)#no sh
ROUTER(config-if)#ex
ROUTER(config)#int e0/0
ROUTER(config-if)#no sh
ROUTER(config-if)#exit
ROUTER(config)#
ROUTER(config)#int e0/0.1
ROUTER(config-subif)#encapsulation dot1q 10
ROUTER(config-subif)#ip add 30.0.0.1 255.0.0.0
ROUTER(config-subif)#no sh
ROUTER(config-subif)#ex
ROUTER(config)#int e0/0.2
ROUTER(config-subif)#encapsulation dot1q 20
ROUTER(config-subif)#ip add 40.0.0.1 255.0.0.0
ROUTER(config-subif)#no sh
ROUTER(config-subif)#ex
ROUTER(config)#exit
ROUTER#
ROUTER#
ROUTER#
*Sep 21 09:54:11.335: %SYS-5-CONFIG_I: Configured from console by console
ROUTER#conf t
Enter configuration commands, one per line. End with CNTL/Z.
ROUTER(config)#ip route 0.0.0.0 0.0.0.0 1.0.0.1
ROUTER(config)#exit
ROUTER#
*Sep 21 09:56:12.892: %SYS-5-CONFIG_I: Configured from console by console
```

Connected to labs.surenetwork.com.
Escape character is '^']'.

L2-SW-2#

L2-SW-2#

L2-SW-2#

L2-SW-2#conf t

Enter configuration commands, one per line. End with CNTL/Z.

L2-SW-2(config)#vlan 10

L2-SW-2(config-vlan)#name Design

L2-SW-2(config-vlan)#exit

L2-SW-2(config)#vlan 20

L2-SW-2(config-vlan)#name Dev

L2-SW-2(config-vlan)#exit

L2-SW-2(config)#

L2-SW-2(config)#int e0/0

L2-SW-2(config-if)#switchport access vlan 10

L2-SW-2(config-if)#exit

L2-SW-2(config)#int e0/1

L2-SW-2(config-if)#switchport access vlan 20

L2-SW-2(config-if)#exit

L2-SW-2(config)#

L2-SW-2(config)#int e0/2

L2-SW-2(config-if)#switchport trunk encapsulation dot1q

L2-SW-2(config-if)#switchport mode trunk

L2-SW-2(config-if)#exit

L2-SW-2(config)#

L2-SW-2(config)#

L2-SW-2(config)#

L2-SW-2(config)#

*Sep 21 09:47:31.207: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet0/2, changed state to down

L2-SW-2(config)#

*Sep 21 09:47:33.036: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet0/2, changed state to up

L2-SW-2(config)#

*Sep 21 09:49:50.482: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)

L2-SW-2(config)#

VPC1



```
Trying 49.204.127.18...
Connected to labs.surennetwork.com.
Escape character is '^]'.
```

```
20.0.0.10 icmp_seq=3 timeout
20.0.0.10 icmp_seq=4 timeout
20.0.0.10 icmp_seq=5 timeout
```

```
VPC1> pipe2 failed
Bad command: "pipe2 failed". Use ? for help.
```

```
VPC1>
```

```
VPC1> ping 30.0.0.10
```

```
84 bytes from 30.0.0.10 icmp_seq=1 ttl=62 time=4.964 ms
84 bytes from 30.0.0.10 icmp_seq=2 ttl=62 time=5.094 ms
84 bytes from 30.0.0.10 icmp_seq=3 ttl=62 time=3.506 ms
84 bytes from 30.0.0.10 icmp_seq=4 ttl=62 time=3.031 ms
84 bytes from 30.0.0.10 icmp_seq=5 ttl=62 time=2.191 ms
```

```
VPC1> ping 40.0.0.10
```

```
84 bytes from 40.0.0.10 icmp_seq=1 ttl=62 time=5.319 ms
84 bytes from 40.0.0.10 icmp_seq=2 ttl=62 time=3.265 ms
84 bytes from 40.0.0.10 icmp_seq=3 ttl=62 time=2.721 ms
84 bytes from 40.0.0.10 icmp_seq=4 ttl=62 time=1.904 ms
84 bytes from 40.0.0.10 icmp_seq=5 ttl=62 time=2.776 ms
```

```
Trying 49.204.127.18...
Connected to labs.surennetwork.com.
Escape character is '^]'.
84 bytes from 10.0.0.10 icmp_seq=5 ttl=63 time=2.968 ms
```

```
VPC2> pipe2 failed
Bad command: "pipe2 failed". Use ? for help.
```

```
VPC2>
```

```
VPC2> ping 30.0.0.10
```

```
84 bytes from 30.0.0.10 icmp_seq=1 ttl=62 time=2.178 ms
84 bytes from 30.0.0.10 icmp_seq=2 ttl=62 time=3.583 ms
84 bytes from 30.0.0.10 icmp_seq=3 ttl=62 time=2.371 ms
84 bytes from 30.0.0.10 icmp_seq=4 ttl=62 time=2.019 ms
84 bytes from 30.0.0.10 icmp_seq=5 ttl=62 time=3.081 ms
```

```
VPC2> ping 40.0.0.10
```

```
84 bytes from 40.0.0.10 icmp_seq=1 ttl=62 time=3.035 ms
84 bytes from 40.0.0.10 icmp_seq=2 ttl=62 time=3.247 ms
84 bytes from 40.0.0.10 icmp_seq=3 ttl=62 time=2.114 ms
84 bytes from 40.0.0.10 icmp_seq=4 ttl=62 time=2.672 ms
84 bytes from 40.0.0.10 icmp_seq=5 ttl=62 time=3.392 ms
```

```
VPC2>
```

```
VPC2>
```