Setup Manual

Metro Ticket Generating System in ServiceNow | Recreation guide | 11 October 2026

Follow this order to recreate the catalog-based metro ticket demonstration in a ServiceNow Personal Developer Instance. Each step names the record, field, or script to configure and the result to check before moving on.

1 Prerequisites

- ServiceNow Personal Developer Instance with administrator access.
- Service Portal, Service Catalog, and catalog client scripting available.
- The supplied source snapshot files and a modern browser.
- A test account or approved role for checking portal and table access.

2 Create Station Reference Data

1. Open System Definition > Tables and create Metro Station Details with name u_metro_station_details.
2. Create a Station Name field with name u_station_name. Configure it as the display value.
3. Open the table list and add station records covering the 27-station Red Line order referenced in the fare script.
4. Check station spelling against the stationKeys array in fare-auto-calculation.js; the script normalizes punctuation and spaces but relies on the same station names.
5. Confirm that both station reference variables can display these records.

3 Create the Catalog Item

6. Open Service Catalog > Maintain Items and create a new catalog item.
7. Set Name to Book a Ticket, Catalog to Service Catalog, Category to Services, and Active to true.
8. Add the short description A metro ticketing system which allows users to buy metro ticket digitally.
9. Save the item and note its record identifier for links and screenshots.

4 Configure Variables in Order

Order	Question and name	Type and setting
100	Starting From starting_from	Reference; Required; references Metro Station Details
200	Going To going_to	Reference; Required; references Metro Station Details
300	Type of Jouney type_of_jouney	Multiple Choice; Single or return journey
400	Number of passengers number_of_passengers	Numeric Scale; Passenger count used by fare script
500	Amount for Single Journey amount_for_single_journey	Single Line Text; Calculated, read only display
600	Amount Including Return amount_including_return	Single Line Text; Calculated, read only display
700	Mode of Payment mode_of_payment	Multiple Choice; UPI, Card, Others
800	Enter Payment Mode enter_payment_mode	Single Line Text; Shown when Others is selected

The field label Type of Jouney is spelled this way in the current item. Keep its internal name type_of_jouney consistent with the stored script. Set the fare fields read only. The current passenger control offers 0 through 5; use 1 through 4 when demonstrating a calculated fare with the stored script.

5 Add Fare Auto Calculation

10. Under Catalog Client Scripts, create Fare auto Calculation for the Book a Ticket item.
11. Set Active to true, UI Type to All, Type to onChange, and Variable name to number_of_passengers.

12. Paste the exact saved code from 5. Project Development Phase/fare-auto-calculation.js.
13. Save the script and test a configured route using one passenger.

The script file is a snapshot of the current record. It includes the 27-station matrix and its fare mapping, so the station table must match its reference names. Its opening comment suggests four onChange triggers; the currently observed catalog item has one fare script bound to number_of_passengers. These instructions reproduce the configured item.

6 Configure the Payment UI Policy

14. Create a Catalog UI Policy named Fields Visibility for the item.
15. Set the condition to Mode of Payment is Others.
16. Add an action for Enter Payment Mode with Visible true and Mandatory true.
17. Enable On load and Reverse if false. Check the result in Service Portal.

7 Create the Metro QR Widget

18. Open Service Portal > Widgets and create Metro QR Widget.
19. Set its ID to metro_qr_widget.
20. Paste metro-qr-widget.html into Body HTML template.
21. Paste metro-qr-widget.server.js into Server script.
22. Save and confirm that the widget record is available by ID.

8 Add QRGeneration

23. Create an active Catalog Client Script named QRGeneration for Book a Ticket.
24. Set UI Type to All and Type to onSubmit.
25. Paste the exact exercise code from 5. Project Development Phase/qr-generation.js.
26. The exercise code intentionally uses an example.com ticket address for QR presentation. Its return false statement cancels the form submission; demonstrate the QR modal as the configured result.

9 Check Access and Run a Smoke Test

27. Review the table ACLs created with the custom table and check portal access using the intended user role.
28. Open the Service Portal item and confirm that the two station selectors load records.
29. Choose Miyapur to JNTU College, Single Journey, one passenger; the current fare mapping displays 11 for this example.
30. Choose Others and verify that Enter Payment Mode becomes visible and mandatory.
31. Inspect the QR widget preview without assuming a payment or gate validation took place.
32. Capture the final screenshots and UAT results in the Test Plan and UAT Record.