211x604 DSC

218727

PRO FORCE

Starting Fluid

For Gasoline, Diesel and Marine Engines

DANGER: EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED.

READ WARNINGS ON BACK PANEL.

Net. Wt. 11 oz. (312 gms)

STEEL

PRO FORCE Starting Fluid starts engines in any weather. Ensures fast and sure starts for all types of engines — automobiles, trucks, motorcycles, marine, 2 and 4 cycle and even diesel. Works at temperatures as low as 65°F (-52°C). Helps reduce cold weather wear on batteries.

DIRECTIONS FOR USE: Read entire label before use. Hold can upright and spray directly into carburetor air cleaner or air intake in short bursts of 2-3 seconds. Then start engine. Do not overspray. Only a small amount is needed. Do not use on flooded engines. Do not use spray when trying to crank engine over. Do not let can come in contact with battery or starter solenoid. Do not use to mount or seal tires.

CAUTION: Starting Fluids are not recommended in some glow plug equipped diesels. Consult your owners manual.

DANGER: EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. May be fatal if swallowed and enters air ways. Harmful in contact with skin. Causes skin irritation. Repeated exposure may cause skin dryness or cracking. Harmful if inha ed. May cause drowsiness and dizziness.

CONTAINS (CAS#): Heptane (64742-49-0), Diethyl Ether (60-29-7) and Carbon Dioxide (124-38-9).

Precautionary Statements – Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink, or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe dust, fume, gas, mist, vapors or spray. Wear eye/face protection. Keep away from heat/sparks/open flames/ hot surfaces - No smoking. Do not spray on an open flame or other ignition source. Pressurized container - Do not pierce or burn even after use.

Deliberate inhalation of the contents of this can is extremely dangerous. Death can occur without warning. Avoid breathing vapor or mist. Avoid contact with skin and eyes. Over-exposure to vapors may cause irritation to the eyes and may cause headaches, nausea, dizziness, drowsiness and general numbness. Inhalation of mist may cause irritation of the throat and lungs. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

FIRST AID SUMMARY: If exposed or concerned: Get medical advice/attention, have product container or label at hand. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists, get medical advice/attention. **IF ON SKIN:** Wash skin with plenty of soap and water. If skin irritation persists, get medical advice/attention. Take off contaminated clothing and wash it before reuse. **IF INHALED:** Increase fresh air circulation or leave area. **IF SWALLOWED:** Immediately call a **POISON CENTER/doctor.** Do **NOT** induce vomiting – Rinse mouth. Call a Poison Center or doctor/physician if you feel unwell.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50C/122°F. Store locked up. Disposal: Dispose of contents/container to an approved waste disposal plant.

WARNING: This product can expose you to chemicals including, Toluene, which is known to the State of California to cause developmental toxicity and Chloroethane, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

KEEP OUT OF REACH OF CHILDREN.

REV 06-15
#9123

J.D. Streett & Company, Inc.
144 Weldon Parkway • Maryland Heights, MO 63043 • 800-678-6600

Anchor™ 218727 00046 / 15650275.2 10/18

00046_PROFORCE_STARTING_FLUID R2.indd 1 MAGENTA BLACK

AnchorProof
FOR LAYOUT AND TEXT, NOT FOR COLOR MATCH.
ANCHOR
Flexible Packaging & Label Specialists
22790 Heslip
Novi, Michigan 48375
800/748-0209 • 248/335-7440
www.anchorprinting.com

Please read the proof and specifications carefully. Any errors that are not acknowledged by the customer are NOT the responsibility of Anchor Printing. Customer approval is required for print production.

☐ APPROVED
OK TO PROCEED

☐ NOT APPROVED
SEND NEW PROOF

CUSTOMER INITIALS

Specs:
Size: 16OZ 211X604 DSC
8.625" x 5.125"

Stock: 60# White C1S Litho ROLL

Coating: UV

Ink Colors
MAGENTA
YELLOW
BLACK

APPROVED
CUSTOMER
ART

Worthing

From: Cricket Blevens <Cricket@airosol.com>
Sent: Thursday, October 11, 2018 2:21 PM
To: Worthing
Subject: RE: 00046 / 15650275.2 Pro Force

This label is approved!

From: Worthing <Worthing@anchorprinting.com>
Sent: Thursday, October 11, 2018 9:29 AM
To: Cricket Blevens <Cricket@airosol.com>; Kim Willard <kim@airosol.com>; Carl Stratemeier <carls@airosol.com>
Subject: 00046 / 15650275.2 Pro Force