116984 PH_BRAKE CLNR R1.pdf 1 10/4/18 2:24 PM

222 mm Slit Width

2 mm Clear

4.5 mm Clear Seam Area

204.55 mm Print Length

209.55 mm Cut Length

Pro Honda

CONTACT/BRAKE CLEANER ULTRA LOW VOC NON-CHLORINATED

DIRECTIONS: Remove brake dust using approved techniques. If desired, attached extension tube for more precise cleaning. Spray disassembled metal parts liberally. Protect rubber brake parts and painted surfaces from product and overspray. Do not apply to hot surfaces or energized systems. Repeat if necessary. Allow parts to dry. Re-lubricate required areas with recommended lubricant per Service Manual when parts are re-assembled. Do not spray after lubricating - cleaner will remove lubricant. Always test brake system before riding in a normal manner.

CAUTION: Keep away from heat, sparks and open flame. Avoid contact with eyes and skin. Do not swallow. Use only in well ventilated areas. Do not breathe fumes or vapors. Do not puncture or incinerate this container. Intentional misuse by deliberate concentration and inhalation of this product may be harmful or fatal. Store in well ventilated area. Do not store above 120°F (49°C), near sources of heat, or in direct sunlight. Keep out of reach of children.

FIRST AID: In case of eye contact, immediately flush eyes with water for at least 15 minutes. In case of skin contact, wash affected area with mild soap and water. Remove contaminated clothing and launder before reuse. If swallowed, contact physician immediately. Do NOT induce vomiting unless directed to do so by medical personnel. If inhaled, remove to fresh air. In all cases, if symptoms develop or persist, seek medical attention.

INGREDIENTS: Acetone (67-64-1), toluene (108-88-3), carbon dioxide (124-38-9).

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

08732-CBCCA

Distributed By:
American Honda Motor Co., Inc.
Torrance, CA 90501
Made in USA

Pro Honda OILS AND CHEMICALS

NON-CHLORINATED

Contact/ Brake Cleaner

Ultra Low VOC

CLEANS BRAKE COMPONENTS AND ELECTRICAL CONNECTORS

- Dries fast with no residue.
- Quickly removes grease and oil.
- Safe for most plastics.
- Meets SCAQMD Rule 1171 requirements for unlimited use.

DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE.
Carefully read additional warnings on back panel.

NET WT. 15 OZ (425 g)

2 mm Clear

Fold

mm Layflat

25 mm to Fold

1 mm Clear

AnchorProof
ANCHOR
Flexible Packaging & Label Specialists

APPROVED OK TO PROCESS

NOT APPROVED READ NEW PROOF

Ink Colors

CUSTOMER INITIALS

90

APPROVED
CUSTOMER
ART

FG0521

Mike Dion

From: R Heckman <rheckman@customaerosol.com>
Sent: Wednesday, January 09, 2019 12:36 PM
To: Mike Dion
Cc: Hillebrand
Subject: Re: Acura SCAQMD Labels

Hi Mike,

They have been approved.

APPROVED
CUSTOMER
ART

Can you get me a date that I will have them.

Thanks,

Bob

On Wed, Jan 9, 2019 at 11:48 AM Mike Dion <dion@anchorprinting.com> wrote:

Hi Bob,

It appears that Eric sent you a press ready PDF proofs to get approvals on back on 10/8/18. We never received any approvals on these labels. Please forward these to your customer and get the approvals needed. Once approved production can be scheduled as per PO# 32600.

- 08700-SBPCB = ACURA 20oz DSC shrink sleeve (PDF 9201A) on PO# 32600
- 08732-CBCCA = HONDA 20oz DSC shrink sleeve (PDF 116984)

Please advise,

Michael R. Dion

Anchor Printing - Flexible Packaging & Label Specialists
22790 Heslip Dr.
Novi, Michigan 48375
TOLL-FREE: (800) 748-0209
Fax: (248) 335-6989
Web: www.anchorprinting.com
At Anchor: "We Manufacture Your Success"

From: Hillebrand
Sent: Tuesday, January 08, 2019 5:01 PM
To: R Heckman <rheckman@customaerosol.com>