Rajalakshmi Engineering College

Name: Tharunprakash G
Email: 241801298@rajalakshmi.edu.in
Roll no: 241801298
Phone: 9445307271
Branch: REC
Department: I AI & DS FD
Batch: 2028
Degree: B.E - AI & DS

Scan to verify results

NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

Input Format

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

Output Format

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
10 20 30 40 50
Output: 10 20 30 40 50

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

struct node {
    int data;
    struct node* prev;
    struct node* next;
};

struct node* start = NULL;

void insertAtEnd(int id) {
    struct node* new_node = (struct node*)malloc(sizeof(struct node));
    new_node->data = id;
    new_node->next = NULL;
    new_node->prev = NULL;

    if (start == NULL) {
        start = new_node;
    } else {
        struct node* temp = start;
        while (temp->next != NULL) {
            temp = temp->next;
```

```
        }
        temp->next = new_node;
        new_node->prev = temp;
    }
}

void traverse() {
    struct node* temp = start;
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}

int main() {
    int N, id;
    scanf("%d", &N);

    for (int i = 0; i < N; i++) {
        scanf("%d", &id);
        insertAtEnd(id);
    }

    traverse();

    return 0;
}
```

Status : Correct **Marks : 10/10**