



FOR PROFESSIONAL USE ONLY

# SPEC DATA SHEET

Alkaline Stone Cleaner is an all-purpose cleaner for removing stubborn deposits from many substrates. These would include stone, concrete, masonry, awnings, and common sidings. The deposits include lichens, algae, biological and environmental stains. Rinsing with a pressure washer is generally required.

#### **ADVANTAGES**

- Generally brushless application
- Biodegradable
- Fast rinsing
- · Friendly on most paint and glass

#### **LIMITATIONS**

- This is a mild but effective cleaner that may not accomplish all restoration challenges
- · Do not use in exceptional heat

#### TECHNICAL DATA

Appearance: Pale color
Odor: Mild odor
Physical State: Liquid
pH: 12.8
Boiling Point: >212° F
Specific Gravity (water=1): 1.11 @ 77° F

Evaporation Rate: N/D Solubility in Water: Complete

Flash Point: N/D Viscosity Water thin

Decomposition Temp: N/D
Oxidizing Properties: N/D

#### **PREPARATION**

Protect adjacent surfaces and surrounding building hardware not intended to be cleaned from exposure to the cleaning solution. Avoid direct contact with foliage. Cover landscape using plastic or wet the foliage with water before and after cleaning. Avoid wind drift on surrounding surfaces such as auto and pedestrian traffic.

#### SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results

are obtained when air and surface temperatures are above 40° Fahrenheit or less than 90° Fahrenheit. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for the surface to thaw. If air temperatures exceed 90° Fahrenheit, flash cool the surface with water before applying product. Do not allow products to dry on the surface. Always rinse thoroughly while still wet.

#### **Pre-Testing**

Always test prior to beginning full-scale cleaning operations. Pre-testing will determine suitability and effectiveness on each type of surface and stain designated to be cleaned. Pre-testing will also determine dwell times and number of applications required to achieve desired results. Pre-testing will show any potential or adverse reactions to adjacent surfaces. Allow test areas to thoroughly dry before evaluating final appearance and results.

#### **SAFETY INFORMATION**

Always wear goggles and chemical resistant gloves when handling this product. Read the Safety Data Sheet for additional safety and health hazard information prior to use. Do not get in eyes, on skin, or on clothing. Do not wear contact lenses when using this product. If material comes in contact with clothing, wash before re-use. Do not dilute this product with any other product except clean water. Do not use any other application other than specified in the application instructions. Keep container closed when not in use. Use with adequate ventilation. Use NIOSH/MSHA approved respiration devises when adequate ventilation is not available. Though the potential for fuming is minimal, take precautions to avoid exposing building occupants to fumes. Do not remove the label from the container. Dispose of empty containers in accordance with federal, state, and local requirements.

CAUTION: KEEP AWAY FROM CHILDREN





## FOR PROFESSIONAL USE ONLY

# DATA SHEET

### VELOCITY EHS 24 HOUR EMERGENCY RESPONSE RINSING **SERVICE NUMBER - 1-800-255-3294**

#### SUITABLE SUBSTRATES

The following substrates have been tested on and are deemed suitable under standard conditions. Pretesting is always recommended prior to full-scale cleaning.

√ Stone √ Concrete √ Vinyl Siding √ Stucco ✓ Awnings √ Wood √ EIFS √ Gutters

√ Glass √ Masonry Surfaces

While this list is extensive, there are other substrates that Alkaline Stone Cleaner may be suitable for that are not listed. Every cleaning situation is unique in its own way, so please follow all precaution, pre-testing and application instructions included in this Product Data Sheet.

#### **DILUTIONS**

Undiluted for extreme stains and soils

- (4:1) heavy stains and soils (Can us an ECJet)
- (10:1) for medium cleaning
- (20:1) for light soil

Note: Dilutions will vary based on the severity of stain and type of surface.

#### COVERAGE RATES

Coverage rates with Alkaline Stone Cleaner will vary from 100-250 sq. ft. per gallon depending on the surface porosity, texture, ambient temperature, craftsmanship, and severity of staining.

### **APPLICATION INSTRUCTIONS**

- 1. Pre-wet the surface (do not saturate) with water before applying ASC.
- 2. Apply two applications using a low pressure applicator. Do not rinse between applications.

Use a wide-angle nozzle when rinsing. Rinse pressure is determined by the skill set of the washer and sensitivity of the surface. When in doubt, consult substrate manufacture for recommended P.S.I. Pressures that mark or damage the surface should be avoided. Do not use a zero-degree nozzle.

Caution: Do not allow the product to dry on a surface.

#### SPILL OR LEAK PROCEDURES

Check with state, local, or federal regulation for waste disposal methods in the area. Wear proper protective equipment while doing clean-up. For large spills, dike and contain for intended use. For residual, use a chemical absorbent material. For small spills, use a chemical absorbent material and place in an approved container for disposal.

### CONTAINER HANDLING/STORAGE

Store product in a cool, dry place away from alkalibased materials. Vent the bung cap before opening. Keep container tightly closed when not in use. Wash thoroughly after handling. For best results, liquid should be 32° F or higher prior to use.

#### Instructions in Case of Contact or Exposure

**Eves:** Flood with water for 15 minutes. If irritation develops, seek medical attention.

Skin: Wash off with soap and water. Follow with a good emollient. If irritation develops, seek medical attention.

**Ingestion:** Drink lots of water to dilute. Do not induce vomiting. Seek immediate medical attention.

Inhalation: Move to fresh air. If irritation develops, seek medical attention.





FOR PROFESSIONAL USE ONLY

# SPEC DATA SHEET

#### NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

### **D**ISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot be sure or guarantee these are the only hazards which exist.

#### **CUSTOMER SERVICE**

Factory personnel are available for assistance Monday through Friday from 8am to 5pm EST at (724) 656-1055. Questions can also be sent to info@eacochem.com. A reply can be expected by the following business day or FaceTime and Call from the Wall is available while on jobsite.