

**FOR PROFESSIONAL USE ONLY**

SPEC DATA SHEET

Truckwash Supreme SC (TWS SC) is a one step brushless truck wash that is safe on painted surfaces and polished aluminum. TWS SC leaves a great shine and uses no petroleum solvents to achieve the clean; it is completely biodegradable when used as directed.

ADVANTAGES

- Concentrated for super strength cleaning action
- Versatile truck wash detergent
- Safe on polished aluminum
- No petroleum solvents
- One step brushless system

LIMITATIONS

- Not appropriate for most reclaim systems
- Contains D-Limonene (causes rubber to swell)

**For information about soft metals, please see our soft metal Issue Statement at our website for more complete guidance.*

TECHNICAL DATA

Appearance:	Amber color
Odor:	Mild odor
Physical State:	Liquid
pH:	13.5
Boiling Point:	>212° F
Specific Gravity (water=1):	1.13 @ 77° F
Evaporation Rate:	N/D
Solubility in Water:	Complete
Flash Point:	N/D
Viscosity	Water thin
Decomposition Temp:	N/D
Oxidizing Properties:	N/D

PREPARATION

Protect adjacent surfaces not intended to be cleaned from exposure to the cleaning solution. Avoid direct contact with foliage. Avoid wind drift on surrounding surfaces as well as auto and pedestrian traffic.

SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results are obtained when air and surface temperatures are above 40° Fahrenheit or less than 90° Fahrenheit. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for the surface to thaw. If air temperatures exceed 90° Fahrenheit, flash cool the surface with water before applying product. Do not allow products to dry on the surface. Always rinse thoroughly while still wet.

PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Pre-testing will determine suitability and effectiveness on each type of surface and stain designated to be cleaned. Pre-testing will also determine dwell times and number of applications required to achieve desired results. Pre-testing will show any potential or adverse reactions to adjacent surfaces. Allow test areas to thoroughly dry before evaluating final appearance and results.

SAFETY INFORMATION

Always wear goggles and chemical resistant gloves when handling this product. Read the Safety Data Sheet for additional safety and health hazard information prior to use. Do not get in eyes, on skin, or on clothing. Do not wear contact lenses when using this product. If material comes in contact with clothing, wash before re-use. Do not dilute this product with any other product except clean water. Do not use any other application other than specified in the application instructions. Keep container closed when not in use. Use with adequate ventilation. Use NIOSH/MSHA approved respiration devices when adequate ventilation is not available. Though the potential for fuming is minimal, take precautions to avoid exposing building occupants to fumes. Do not remove the label from the container. Dispose of empty containers in accordance with federal, state, and local requirements.

CAUTION: KEEP AWAY FROM CHILDREN

**VELOCITY EHS 24 HOUR EMERGENCY RESPONSE
SERVICE NUMBER - 1-800-255-3294**

**FOR PROFESSIONAL USE ONLY**

SPEC DATA SHEET

DILUTIONS

- 20 parts water to 1 part TWS SC for a quick, one application cleaning (including de-oxidizing aluminum); or dilute 1 part water to 1 part TWS SC then apply with a pressure washer at a 10 to 1 ratio
- 50 parts water to 1 part TWS SC for routine cleaning; or first dilute 4 parts water to 1 part TWS SC then apply with a pressure washer at a 10 to 1 ratio

Note: Dilutions will vary based on the severity of stain and type of surface.

APPLICATION INSTRUCTIONS

1. Pre-wet the surface with water before applying TWS SC.
2. For best brushless results, apply TWS SC with a pressure washer - upstream or downstream, or with a low pressure applicator.
3. TWS SC requires two quick applications, which leads to complete soil release most of the time. Do not rinse between applications. Dwell time should be no longer than 2 to 3 minutes.

RINSING

For brushless results, rinsing requires pressure washer impact. Proper rinsing techniques determine the final look and quality of the job. A thorough rinse job is always recommended. Pressures that mark the surface should be avoided. Water softeners are built into TWS SC; water re-treatment is generally not necessary. **Do not use a zero-degree nozzle.**

Caution: Do not allow the product to dry on a surface.

SPILL OR LEAK PROCEDURES

Check with state, local, or federal regulation for waste disposal methods in the area. Wear proper protective equipment while doing clean-up. For large spills, dike and contain for intended use. For residual, use a chemical absorbent material. For small spills, use a chemical absorbent material and place in an approved container for disposal.

CONTAINER HANDLING/STORAGE

Store product in a cool, dry place away from acid-based materials. Vent the bung cap before opening. Keep container tightly closed when not in use. Wash thoroughly after handling. For best results, liquid should be 32° F or higher prior to use.

INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flood with water for 15 minutes. If irritation develops, seek medical attention.

Skin: Wash off with soap and water. Follow with a good emollient. If irritation develops, seek medical attention.

Ingestion: Drink lots of water to dilute. Do not induce vomiting. Seek immediate medical attention.

Inhalation: Move to fresh air. If irritation develops, seek medical attention.

NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

DISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot be sure or guarantee these are the only hazards which exist.

CUSTOMER SERVICE

Factory personnel are available for assistance Monday through Friday from 8am to 5pm EST at (724) 656-1055. Questions can also be sent to info@eacochem.com. A reply can be expected by the following business day or FaceTime and Call from the Wall is available while on jobsite.