



BLEACH MAGIC

FOR PROFESSIONAL USE ONLY

SPEC DATA SHEET

Bleach Magic is an all-purpose alkaline cleaner designed for use on all common residential and commercial finishes, including fabric awnings, patio furniture, roofing materials, siding, wood, decking materials, and pavers. Bleach Magic is a brushless cleaner and works phenomenal in tandem with Heritage Restorer. Bleach Magic works equally well in hot or cold temperatures, but should not exceed 120° Fahrenheit. Testing should occur before use on all substrates.

ADVANTAGES

- Good splitting of oils and water, no emulsification of oils, low foam on rinsing.

TECHNICAL DATA

Appearance & Odor:	Pale yellow, mild odor.
Physical State:	Liquid
pH:	10.5
Vapor Pressure (mmHg):	As water
Vapor Density (air=1):	As water
Boiling Point:	212° F
Freezing/Melting Point:	N/A
Specific Gravity (water =1):	1.04
Evaporation Rate:	As water
Solubility in Water:	Complete

SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results are obtained when air and surface temperatures are between 40° and 90° Fahrenheit. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° Fahrenheit, flash cool the surface with water before applying product. Do not allow products to dry on the surface. Always rinse thoroughly while still wet.

PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness. Testing also determines the desired dwell time and any potential for adverse reactions with adjacent materials. Allow test area to dry thoroughly before evaluating final appearance and results.

DILUTION

- Undiluted for extreme stains and soil.
- 4 parts water: 1 part product for heavy stains and soils with pressure washer. EC Jet from EaCo Chem is designed to dilute 4:1.
- Dilute as testing indicates.

NOTE: DILUTIONS WILL VARY BASED ON THE SEVERITY OF THE STAIN AND TYPE OF SURFACE.

APPLICATION INSTRUCTIONS

Pre-wet the surface (do not saturate) with water before applying Bleach Magic. Apply two applications using a low-pressure applicator. Do not rinse between applications. Use a wide-angle nozzle when rinsing. Pressures that mark or damage the surface should be avoided.

SAFETY INFORMATION

Precautionary Measures: Always wear goggles and rubber gloves when handling this product. Keep off of skin and clothing. If material comes in contact with clothing, wash before reuse. Do not get in eyes, on skin or clothing. Keep container closed when not in use. Applicators should wear gloves and goggles to avoid splash to bare skin and eyes. Dispose of empty containers according to federal, state, and local requirements. Do not remove label. Read Safety Data Sheet for additional safety and health hazard information prior to use.

CONTAINER HANDLING/STORAGE

Store the product in a cool dry place. Keep container



BLEACH MAGIC

FOR PROFESSIONAL USE ONLY

SPEC DATA SHEET

product enter drains, waterways, or storm drains. Soak up with inert absorbant material for disposal. Keep in suitable, closed container for disposal.

SPILL OR LEAK PROCEDURES

Check with the state, local, or federal regulations for waste disposal methods in the area. Wear proper protective equipment while doing cleanup. For large spills, dike and contain for intended use. For small spills, use a chemical absorbent product and place in approved container for disposal.

FIRST AID

General advice:

Consult a physician. Show the Safety Data Sheet to the doctor in attendance. Never give anything by mouth to an unconscious person. Remove contaminated clothing.

INHALATION: Remove person to fresh air. Consult a physician if irritation develops.

SKIN CONTACT: Remove contaminated clothing. Wash clothing before reuse. Wash skin with soap and water. Consult a physician if irritation develops.

EYE CONTACT: Rinse eyes thoroughly for 15 minutes. Consult a physician.

INGESTION: Do NOT induce vomiting. Drink plenty of fluids. Do not give anything by mouth to an unconscious person. Consult a physician.

CAUTION

Please review our SDS, Product Data Sheet, and website issue statements before using this product. TESTING SHOULD OCCUR BEFORE USE ON ALL SUBSTRATES. Test area must be dry after rinsing and before evaluating final results.

NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

DISCLAIMER

The information herein is given in good faith but no warranty, expressed or implied is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot be sure or guarantee these are the only hazards which exist.

CUSTOMER SERVICE

Factory personnel are available for assistance at 724-656-1055 and will send you additional information on products as necessary.

**VELOCITY EHS 24 HOUR EMERGENCY RESPONSE
SERVICE NUMBER - 1-800-255-3294**