

Q1

```
mysql> select h.name, r.room_no, r.type, r.price
-> from room as r inner join hotel as h on h.hotel_no = r.hotel_no
-> where (r.type = 'Double' or r.type = 'Family') and r.price < 7500
-> order by r.price;
```

name	room_no	type	price
Rangiri Dambulla Resort	205	Double	4500
Rangiri Dambulla Resort	203	Double	4500
Rangiri Dambulla Resort	204	Double	4500
The Kingsbury	201	Double	4500
The Kingsbury	206	Double	4500
The Kingsbury	205	Double	4500
The Kingsbury	204	Double	4500
Rangiri Dambulla Resort	206	Double	4500
The Kingsbury	203	Double	4500
The Kingsbury	202	Double	4500
Rangiri Dambulla Resort	201	Double	4500
Rangiri Dambulla Resort	202	Double	4500
Ramada Colombo	206	Double	5000
Ramada Colombo	207	Double	5000
Ramada Colombo	208	Double	5000
Amaya Lake Hotel	208	Double	5000
Heritance Kandalama	201	Double	5000
Heritance Kandalama	202	Double	5000
Heritance Kandalama	203	Double	5000
Heritance Kandalama	204	Double	5000
Heritance Kandalama	205	Double	5000

Q2

```
mysql> select r.room_no, r.hotel_no, type, price, g.name
-> from ((room as r left join booking as b on r.room_no = b.room_no and r.ho
tel_no = b.hotel_no) left join guest as g on b.guest_no = g.guest_no)
-> where r.hotel_no in (
-> select hotel_no from hotel where name = 'Anilana Nilaveli'
-> );
```

room_no	hotel_no	type	price	name
102	00007	Single	3500	Ruvan Gamage
103	00007	Single	3500	Gihan Perera
101	00007	Single	3500	NULL
104	00007	Single	3500	NULL
105	00007	Single	3500	NULL
106	00007	Single	3500	NULL
107	00007	Single	3500	NULL
201	00007	Family	6500	NULL
202	00007	Family	6500	NULL
203	00007	Family	6500	NULL
204	00007	Family	6500	NULL
205	00007	Family	6500	NULL
206	00007	Family	6500	NULL
301	00007	Double	8500	NULL
302	00007	Double	8500	NULL
303	00007	Double	8500	NULL
304	00007	Double	8500	NULL
305	00007	Double	8500	NULL

18 rows in set (0.00 sec)

Q3

```
mysql> select sum(price) as total_revenue
-> from room
-> where type = 'Double' and hotel_no in (
-> select hotel_no from hotel where name = 'Anilana Nilaveli'
-> );
```

total_revenue
42500

1 row in set (0.00 sec)

Q4

```
mysql> select sum(price) as total_income_today
-> from room as r inner join booking as b on r.room_no = b.room_no and r.hotel_no = b.hotel_no
-> where r.hotel_no in (
-> select hotel_no from hotel where name = 'Anilana Nilaveli'
-> ) and date_from <= CURDATE() and date_to >= CURDATE();
+-----+
| total_income_today |
+-----+
|          7000      |
+-----+
1 row in set (0.00 sec)
```

Q5

```
mysql> select h.name, count(room_no) as no_of_rooms
-> from room as r inner join hotel as h on r.hotel_no = h.hotel_no
-> where h.address like '%Dambulla%'
-> group by r.hotel_no;
+-----+-----+
| name           | no_of_rooms |
+-----+-----+
| Arika Villa    | 17          |
| Sundaras Resort | 18          |
| Thilanka Resort and Spa | 7          |
| Rangiri Dambulla Resort | 11         |
| Amaya Lake Hotel | 21         |
+-----+-----+
5 rows in set (0.03 sec)
```

Q6

```
mysql> select name
-> from hotel
-> where address like '%Dambulla%' and hotel_no in (
-> select hotel_no from room where type = 'Double'
-> ) and hotel_no in (
-> select hotel_no from room where type = 'Family'
-> );
+-----+
| name           |
+-----+
| Arika Villa    |
| Sundaras Resort |
| Amaya Lake Hotel |
+-----+
3 rows in set (0.00 sec)
```

Q7

```
mysql> select h.name, h.address
-> from room as r inner join hotel as h on r.hotel_no = h.hotel_no
-> where r.type = 'Double' and address like '%Colombo%'
-> order by r.price DESC
-> limit 1;
+-----+-----+
| name           | address                                             |
+-----+-----+
| Taj Samudra    | 25, Galle Face Centre Road, 09411 Colombo, Sri Lanka |
+-----+-----+
1 row in set (0.00 sec)
```

Q8

```
mysql> select name
-> from hotel
-> where hotel_no not in (
->   select hotel_no from room where type = 'Double'
-> );
```

name
Thilanka Resort and Spa

```
1 row in set (0.03 sec)
```