



PERFORMANCE

**Easy Install**

Slide on and off a bushing without removing the bushing from the shaft

290 products

**Corrosion Resistant**

Won't rust when exposed to water

405 products

**Lightweight**

Cut weight with plastic or aluminum pulleys

405 products

**Finished**

Mount onto the shaft—no machining necessary

315 products

**Plain**

Machine to your exact shaft size, or add a set screw or keyway

215 products

**Bushing**

Pair with C or taper lock easy install

290 products

FOR SHAFT TYPE

**Round**

Secure to a round shaft with a set screw

288 products

**Keyed**

Comes machined with a keyway to lock onto a keyed shaft

27 products

**Flush**

No raised hub—best for tight spots

48 products

HUB TYPE

Timing Belt Pulleys



Finished Bore



Plain Bore



Bushing Bore

Keep your drive system in sync. Trapezoidal teeth mesh with matching belts to synchronize motion. With the original tooth profile, these pulleys handle enough torque for most applications. If you need high torque or precise starts and stops, consider curved tooth profiles, such as GT and HTD pulleys.

Steel and Iron—Strong but best for dry environments since moisture will cause them to rust.


Corrosion-Resistant Aluminum—Won't rust in wet environments and one-third the weight of steel and iron. However, aluminum pulleys are not as strong as iron and steel.

Finished Bore—Mount these pulleys onto the shaft and secure with a set screw—no machining required.

Plain Bore—Do it your way—machine the bore to your exact shaft size or add a set screw or keyway.

Bushing Bore—Quickly swap or service parts in tight spaces—no press-fitting or special tools required. Mount a bushing (sold separately) on your shaft and slide the pulley over it. As you tighten the included set screws, the bushing grips the shaft and draws it into the pulley, creating a final hold that is more secure than with set screws alone.

Flush Hub—Ideal in tight spots where a raised hub would get in the way.



For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	For Bushing		Keyway			Pitch Dia.	No. of Flanges	Hub Type	Each
					Type		Trade No.	Wd.	Dp.				
For MXL Trade Size													
Corrosion-Resistant Aluminum													
1/8"	0.080"	10	Finished	1/8"	—	—	—	—	0.255"	1	Standard	1375K11	\$10.42
1/8"	0.080"	11	Finished	1/8"	—	—	—	—	0.28"	1	Standard	1375K12	10.45
1/8"	0.080"	12	Finished	1/8"	—	—	—	—	0.306"	1	Standard	1375K13	10.47
1/8"	0.080"	14	Finished	1/8"	—	—	—	—	0.357"	1	Standard	1375K14	11.70
1/8"	0.080"	15	Finished	3/16"	—	—	—	—	0.382"	1	Standard	1375K15	10.55
1/8"	0.080"	16	Finished	3/16"	—	—	—	—	0.407"	1	Standard	1375K16	11.05
1/8"	0.080"	18	Finished	3/16"	—	—	—	—	0.458"	2	Standard	1375K17	11.12
1/8"	0.080"	20	Finished	1/4"	—	—	—	—	0.509"	1	Standard	1375K21	12.52
1/8"	0.080"	21	Finished	1/4"	—	—	—	—	0.535"	1	Standard	1375K23	12.62

For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	For Bushing		Keyway			Pitch Dia.	No. of Flanges	Hub Type		Each
					Type	Trade No.	Wd.	Dp.						
1/8"	0.080"	22	Finished	1/4"	—	—	—	—	0.56"	1	Standard	1375K25	12.97	
1/8"	0.080"	24	Finished	1/4"	—	—	—	—	0.611"	2	Standard	1375K26	11.85	
1/8"	0.080"	28	Finished	1/4"	—	—	—	—	0.713"	2	Standard	1375K27	12.80	
1/8"	0.080"	30	Finished	1/4"	—	—	—	—	0.764"	2	Standard	1375K28	13.32	
1/8"	0.080"	36	Finished	1/4"	—	—	—	—	0.917"	2	Standard	1375K49	14.05	
1/8"	0.080"	40	Finished	1/4"	—	—	—	—	1.019"	2	Standard	1375K51	14.92	
1/8"	0.080"	42	Finished	1/4"	—	—	—	—	1.07"	2	Standard	1375K52	16.30	
1/8"	0.080"	60	Finished	1/4"	—	—	—	—	1.53"	2	Standard	1375K53	20.38	
1/4"	0.080"	10	Finished	1/8"	—	—	—	—	0.255"	1	Standard	1375K29	10.42	
1/4"	0.080"	11	Finished	1/8"	—	—	—	—	0.28"	1	Standard	1375K31	10.60	
1/4"	0.080"	12	Finished	1/8"	—	—	—	—	0.306"	1	Standard	1375K32	10.80	
1/4"	0.080"	14	Finished	1/8"	—	—	—	—	0.357"	1	Standard	1375K33	10.92	
1/4"	0.080"	15	Finished	3/16"	—	—	—	—	0.382"	1	Standard	1375K34	11.25	
1/4"	0.080"	16	Finished	3/16"	—	—	—	—	0.407"	1	Standard	1375K35	11.32	
1/4"	0.080"	18	Finished	3/16"	—	—	—	—	0.458"	2	Standard	1375K36	11.40	
1/4"	0.080"	20	Finished	1/4"	—	—	—	—	0.509"	1	Standard	1375K39	12.97	
1/4"	0.080"	21	Finished	1/4"	—	—	—	—	0.535"	1	Standard	1375K42	13.17	
1/4"	0.080"	22	Finished	1/4"	—	—	—	—	0.56"	1	Standard	1375K44	13.35	
1/4"	0.080"	24	Finished	1/4"	—	—	—	—	0.611"	2	Standard	1375K45	11.85	
1/4"	0.080"	28	Finished	1/4"	—	—	—	—	0.713"	2	Standard	1375K47	12.40	
1/4"	0.080"	30	Finished	1/4"	—	—	—	—	0.764"	2	Standard	1375K48	12.92	
1/4"	0.080"	36	Finished	1/4"	—	—	—	—	0.917"	2	Standard	1375K54	14.90	
1/4"	0.080"	40	Finished	1/4"	—	—	—	—	1.019"	2	Standard	1375K55	15.70	
1/4"	0.080"	42	Finished	1/4"	—	—	—	—	1.07"	2	Standard	1375K56	16.55	
1/4"	0.080"	60	Finished	1/4"	—	—	—	—	1.53"	2	Standard	1375K57	19.68	
3 mm	0.080"	10	Finished	3 mm	—	—	—	—	6.5 mm	1	Standard	1375K171	13.92	
3 mm	0.080"	11	Finished	3 mm	—	—	—	—	7.1 mm	1	Standard	1375K172	14.17	
3 mm	0.080"	12	Finished	3 mm	—	—	—	—	7.8 mm	1	Standard	1375K173	14.39	
3 mm	0.080"	14	Finished	3 mm	—	—	—	—	9.1 mm	1	Standard	1375K174	15.60	
3 mm	0.080"	15	Finished	4 mm	—	—	—	—	9.7 mm	1	Standard	1375K175	14.44	
3 mm	0.080"	16	Finished	4 mm	—	—	—	—	10.3 mm	1	Standard	1375K176	15.23	
3 mm	0.080"	18	Finished	4 mm	—	—	—	—	11.6 mm	2	Standard	1375K177	14.17	
3 mm	0.080"	18	Finished	6 mm	—	—	—	—	11.6 mm	1	Standard	1375K178	15.60	
3 mm	0.080"	20	Finished	4 mm	—	—	—	—	12.9 mm	2	Standard	1375K179	14.54	
3 mm	0.080"	20	Finished	6 mm	—	—	—	—	12.9 mm	1	Standard	1375K181	16.13	
3 mm	0.080"	22	Finished	4 mm	—	—	—	—	14.2 mm	2	Standard	1375K184	15.01	
3 mm	0.080"	22	Finished	6 mm	—	—	—	—	14.2 mm	1	Standard	1375K185	16.52	
3 mm	0.080"	24	Finished	6 mm	—	—	—	—	15.5 mm	2	Standard	1375K186	15.32	
3 mm	0.080"	25	Finished	6 mm	—	—	—	—	16.2 mm	2	Standard	1375K187	15.57	
3 mm	0.080"	28	Finished	6 mm	—	—	—	—	18.1 mm	2	Standard	1375K188	16.13	
3 mm	0.080"	30	Finished	6 mm	—	—	—	—	19.4 mm	2	Standard	1375K189	16.46	
3 mm	0.080"	32	Finished	6 mm	—	—	—	—	20.7 mm	2	Standard	1375K191	16.78	
3 mm	0.080"	36	Finished	6 mm	—	—	—	—	23.3 mm	2	Standard	1375K192	17.83	
3 mm	0.080"	40	Finished	6 mm	—	—	—	—	25.9 mm	2	Standard	1375K193	18.94	
3 mm	0.080"	42	Finished	6 mm	—	—	—	—	27.2 mm	2	Standard	1375K194	19.59	
3 mm	0.080"	44	Finished	6 mm	—	—	—	—	28.5 mm	2	Standard	1375K195	20.07	
3 mm	0.080"	60	Finished	6 mm	—	—	—	—	38.8 mm	2	Standard	1375K197	24.02	
6 mm	0.080"	10	Finished	3 mm	—	—	—	—	6.5 mm	1	Standard	1375K101	14.36	
6 mm	0.080"	12	Finished	3 mm	—	—	—	—	7.8 mm	1	Standard	1375K105	14.89	
6 mm	0.080"	14	Finished	3 mm	—	—	—	—	9.1 mm	1	Standard	1375K107	15.32	
6 mm	0.080"	15	Finished	4 mm	—	—	—	—	9.7 mm	1	Standard	1375K109	15.53	
6 mm	0.080"	16	Finished	4 mm	—	—	—	—	10.3 mm	1	Standard	1375K112	15.53	
6 mm	0.080"	18	Finished	4 mm	—	—	—	—	11.6 mm	2	Standard	1375K114	15.70	
6 mm	0.080"	18	Finished	6 mm	—	—	—	—	11.6 mm	1	Standard	1375K115	14.54	
6 mm	0.080"	20	Finished	4 mm	—	—	—	—	12.9 mm	2	Standard	1375K118	14.83	
6 mm	0.080"	20	Finished	6 mm	—	—	—	—	12.9 mm	1	Standard	1375K119	15.08	
6 mm	0.080"	22	Finished	4 mm	—	—	—	—	14.2 mm	2	Standard	1375K127	16.86	
6 mm	0.080"	22	Finished	6 mm	—	—	—	—	14.2 mm	1	Standard	1375K128	15.49	
6 mm	0.080"	24	Finished	6 mm	—	—	—	—	15.5 mm	2	Standard	1375K132	17.11	
6 mm	0.080"	28	Finished	6 mm	—	—	—	—	18.1 mm	2	Standard	1375K136	17.22	
6 mm	0.080"	30	Finished	6 mm	—	—	—	—	19.4 mm	2	Standard	1375K138	17.27	
6 mm	0.080"	32	Finished	6 mm	—	—	—	—	20.7 mm	2	Standard	1375K141	17.32	
6 mm	0.080"	36	Finished	6 mm	—	—	—	—	23.3 mm	2	Standard	1375K143	17.37	
6 mm	0.080"	40	Finished	6 mm	—	—	—	—	25.9 mm	2	Standard	1375K145	18.03	
6 mm	0.080"	42	Finished	6 mm	—	—	—	—	27.2 mm	2	Standard	1375K147	19.38	
6 mm	0.080"	48	Finished	6 mm	—	—	—	—	31 mm	2	Standard	1375K153	21.39	
6 mm	0.080"	60	Finished	6 mm	—	—	—	—	38.8 mm	—	Standard	1375K157	16.84	
6 mm	0.080"	60	Finished	6 mm	—	—	—	—	38.8 mm	2	Standard	1375K155	22.06	
6 mm	0.080"	80	Finished	8 mm	—	—	—	—	51.7 mm	—	Standard	1375K162	29.36	
6 mm	0.080"	90	Finished	8 mm	—	—	—	—	58.2 mm	—	Standard	1375K164	30.58	
6 mm	0.080"	100	Finished	8 mm	—	—	—	—	64.7 mm	—	Standard	1375K166	33.33	
6 mm	0.080"	120	Finished	10 mm	—	—	—	—	77.6 mm	—	Standard	1375K168	86.90	

For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	For Bushing		Keyway			Pitch Dia.	No. of Flanges	Hub Type		Each
					Type	Trade No.	Wd.	Dp.						
9 mm	0.080"	10	Finished	3 mm	—	—	—	—	6.5 mm	1	Standard	1375K102	14.43	
9 mm	0.080"	14	Finished	3 mm	—	—	—	—	9.1 mm	1	Standard	1375K108	15.49	
9 mm	0.080"	15	Finished	4 mm	—	—	—	—	9.7 mm	1	Standard	1375K111	15.66	
9 mm	0.080"	16	Finished	4 mm	—	—	—	—	10.3 mm	1	Standard	1375K113	15.80	
9 mm	0.080"	18	Finished	6 mm	—	—	—	—	11.6 mm	1	Standard	1375K117	16.17	
9 mm	0.080"	20	Finished	6 mm	—	—	—	—	12.9 mm	1	Standard	1375K122	16.70	
9 mm	0.080"	21	Finished	6 mm	—	—	—	—	13.6 mm	1	Standard	1375K126	16.90	
9 mm	0.080"	22	Finished	6 mm	—	—	—	—	14.2 mm	1	Standard	1375K131	18.14	
9 mm	0.080"	30	Finished	6 mm	—	—	—	—	19.4 mm	2	Standard	1375K139	17.02	
9 mm	0.080"	32	Finished	6 mm	—	—	—	—	20.7 mm	2	Standard	1375K142	17.54	
9 mm	0.080"	48	Finished	6 mm	—	—	—	—	31 mm	2	Standard	1375K154	22.14	
9 mm	0.080"	60	Finished	6 mm	—	—	—	—	38.8 mm	—	Standard	1375K158	17.82	
9 mm	0.080"	60	Finished	6 mm	—	—	—	—	38.8 mm	2	Standard	1375K156	25.04	
9 mm	0.080"	72	Finished	6 mm	—	—	—	—	46.6 mm	—	Standard	1375K161	20.89	
9 mm	0.080"	80	Finished	8 mm	—	—	—	—	51.7 mm	—	Standard	1375K163	23.90	
9 mm	0.080"	90	Finished	8 mm	—	—	—	—	58.2 mm	—	Standard	1375K165	27.00	
9 mm	0.080"	100	Finished	8 mm	—	—	—	—	64.7 mm	—	Standard	1375K167	32.46	
9 mm	0.080"	120	Finished	10 mm	—	—	—	—	77.6 mm	—	Standard	1375K169	34.93	

For XL Trade Size

Steel

3/8"	0.200"	10	Finished	3/16"	—	—	—	—	0.637"	2	Standard	6495K711	18.62
3/8"	0.200"	10	Finished	1/4"	—	—	—	—	0.637"	2	Standard	6495K744	22.24
3/8"	0.200"	11	Finished	3/16"	—	—	—	—	0.7"	2	Standard	6495K712	20.44
3/8"	0.200"	12	Finished	3/16"	—	—	—	—	0.764"	2	Standard	6495K713	21.18
3/8"	0.200"	12	Finished	1/4"	—	—	—	—	0.764"	2	Standard	6495K745	29.98
3/8"	0.200"	12	Finished	5/16"	—	—	—	—	0.764"	2	Standard	6495K746	22.30
3/8"	0.200"	14	Finished	1/4"	—	—	—	—	0.891"	2	Standard	6495K714	24.98
3/8"	0.200"	15	Finished	1/4"	—	—	—	—	0.955"	2	Standard	6495K715	25.87
3/8"	0.200"	15	Finished	3/8"	—	—	—	—	0.955"	2	Standard	6495K747	22.40
3/8"	0.200"	16	Finished	1/4"	—	—	—	—	1.019"	2	Standard	6495K716	27.38
3/8"	0.200"	16	Finished	3/8"	—	—	—	—	1.019"	2	Standard	6495K748	30.36
3/8"	0.200"	18	Finished	1/4"	—	—	—	—	1.146"	2	Standard	6495K717	30.57
3/8"	0.200"	18	Finished	3/8"	—	—	—	—	1.146"	2	Standard	6495K751	30.60
3/8"	0.200"	18	Finished	1/2"	—	—	—	—	1.146"	2	Standard	6495K749	30.60
3/8"	0.200"	20	Finished	1/4"	—	—	—	—	1.273"	2	Standard	6495K718	32.54
3/8"	0.200"	20	Finished	1/2"	—	—	—	—	1.273"	2	Standard	6495K752	23.62
3/8"	0.200"	21	Finished	1/4"	—	—	—	—	1.337"	2	Standard	6495K719	34.31
3/8"	0.200"	22	Finished	1/4"	—	—	—	—	1.401"	2	Standard	6495K721	35.69
3/8"	0.200"	22	Finished	3/8"	—	—	—	—	1.401"	2	Standard	6495K753	37.80
3/8"	0.200"	24	Finished	1/4"	—	—	—	—	1.528"	2	Standard	6495K722	39.45
3/8"	0.200"	28	Finished	1/4"	—	—	—	—	1.783"	2	Standard	6495K723	45.28
3/8"	0.200"	30	Finished	5/16"	—	—	—	—	1.91"	2	Standard	6495K724	48.21
3/8"	0.200"	32	Finished	5/16"	—	—	—	—	2.037"	—	Standard	6495K725	48.88
3/8"	0.200"	36	Finished	5/16"	—	—	—	—	2.292"	—	Standard	6495K726	49.74
3/8"	0.200"	40	Finished	5/16"	—	—	—	—	2.546"	—	Standard	6495K727	54.16
3/8"	0.200"	42	Finished	5/16"	—	—	—	—	2.674"	—	Standard	6495K728	55.59
3/8"	0.200"	44	Finished	5/16"	—	—	—	—	2.801"	—	Standard	6495K729	52.40
3/8"	0.200"	48	Finished	5/16"	—	—	—	—	3.056"	—	Standard	6495K731	56.75
3/8"	0.200"	60	Finished	3/8"	—	—	—	—	3.82"	—	Standard	6495K732	68.62
3/8"	0.200"	72	Finished	3/8"	—	—	—	—	4.584"	—	Standard	6495K733	84.81

Corrosion-Resistant Aluminum

1/4"	0.200"	10	Finished	3/16"	—	—	—	—	0.637"	2	Standard	1277N11	14.51
1/4"	0.200"	12	Finished	3/16"	—	—	—	—	0.764"	2	Standard	1277N13	14.69
1/4"	0.200"	13	Finished	1/4"	—	—	—	—	0.828"	2	Standard	1277N14	14.82
1/4"	0.200"	14	Finished	1/4"	—	—	—	—	0.891"	2	Standard	1277N15	15.00
1/4"	0.200"	15	Finished	1/4"	—	—	—	—	0.955"	2	Standard	1277N16	16.51
1/4"	0.200"	16	Finished	1/4"	—	—	—	—	1.019"	2	Standard	1277N17	16.91
1/4"	0.200"	18	Finished	1/4"	—	—	—	—	1.146"	2	Standard	1277N18	17.16
1/4"	0.200"	20	Finished	1/4"	—	—	—	—	1.273"	2	Standard	1277N19	17.56
1/4"	0.200"	21	Finished	1/4"	—	—	—	—	1.337"	2	Standard	1277N21	18.22
1/4"	0.200"	22	Finished	5/16"	—	—	—	—	1.401"	2	Standard	1277N22	18.49
1/4"	0.200"	24	Finished	5/16"	—	—	—	—	1.528"	2	Standard	1277N23	18.56
1/4"	0.200"	26	Finished	5/16"	—	—	—	—	1.655"	2	Standard	1277N24	21.20
1/4"	0.200"	28	Finished	5/16"	—	—	—	—	1.783"	2	Standard	1277N25	24.67
1/4"	0.200"	30	Finished	5/8"	—	—	—	—	1.91"	2	Standard	1277N26	28.82
3/8"	0.200"	10	Finished	3/16"	—	—	—	—	0.637"	2	Flush	1277N735	15.16
3/8"	0.200"	10	Finished	3/16"	—	—	—	—	0.637"	2	Standard	1277N41	11.91
3/8"	0.200"	10	Finished	1/4"	—	—	—	—	0.637"	2	Flush	1277N736	15.16
3/8"	0.200"	10	Finished	6 mm	—	—	—	—	0.64"	2	Flush	1277N775	15.16
3/8"	0.200"	10	Finished	6 mm	—	—	—	—	0.64"	2	Standard	1277N711	14.96

For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	For Bushing		Keyway			Pitch Dia.	No. of Flanges	Hub Type		Each
					Type	Trade No.	Wd.	Dp.						
3/8"	0.200"	11	Finished	3/16"	—	—	—	—	0.7"	2	Standard	1277N42		11.93
3/8"	0.200"	11	Finished	1/4"	—	—	—	—	0.7"	2	Flush	1277N737		15.20
3/8"	0.200"	11	Finished	6 mm	—	—	—	—	0.7"	2	Flush	1277N776		15.20
3/8"	0.200"	11	Finished	6 mm	—	—	—	—	0.7"	2	Standard	1277N712		14.98
3/8"	0.200"	12	Finished	3/16"	—	—	—	—	0.764"	2	Flush	1277N738		15.40
3/8"	0.200"	12	Finished	3/16"	—	—	—	—	0.764"	2	Standard	1277N43		12.04
3/8"	0.200"	12	Finished	1/4"	—	—	—	—	0.764"	2	Flush	1277N739		15.40
3/8"	0.200"	12	Finished	6 mm	—	—	—	—	0.76"	2	Flush	1277N777		15.40
3/8"	0.200"	12	Finished	6 mm	—	—	—	—	0.76"	2	Standard	1277N713		15.13
3/8"	0.200"	14	Finished	1/4"	—	—	—	—	0.891"	2	Flush	1277N741		15.64
3/8"	0.200"	14	Finished	1/4"	—	—	—	—	0.891"	2	Standard	1277N44		12.36
3/8"	0.200"	14	Finished	5/16"	—	—	—	—	0.891"	2	Flush	1277N742		15.64
3/8"	0.200"	14	Finished	8 mm	—	—	—	—	0.89"	2	Flush	1277N778		15.64
3/8"	0.200"	14	Finished	8 mm	—	—	—	—	0.89"	2	Standard	1277N714		15.49
3/8"	0.200"	15	Finished	1/4"	—	—	—	—	0.955"	2	Flush	1277N27		15.71
3/8"	0.200"	15	Finished	1/4"	—	—	—	—	0.955"	2	Standard	1277N45		12.42
3/8"	0.200"	15	Finished	5/16"	—	—	—	—	0.955"	2	Flush	1277N744		15.71
3/8"	0.200"	15	Finished	8 mm	—	—	—	—	0.96"	2	Flush	1277N779		15.71
3/8"	0.200"	15	Finished	8 mm	—	—	—	—	0.96"	2	Standard	1277N715		15.58
3/8"	0.200"	16	Finished	1/4"	—	—	—	—	1.019"	2	Flush	1277N745		16.80
3/8"	0.200"	16	Finished	1/4"	—	—	—	—	1.019"	2	Standard	1277N46		13.24
3/8"	0.200"	16	Finished	5/16"	—	—	—	—	1.019"	2	Flush	1277N746		16.80
3/8"	0.200"	16	Finished	3/8"	—	—	—	—	1.019"	2	Flush	1277N747		18.40
3/8"	0.200"	16	Finished	8 mm	—	—	—	—	1.02"	2	Flush	1277N781		16.80
3/8"	0.200"	16	Finished	8 mm	—	—	—	—	1.02"	2	Standard	1277N716		16.64
3/8"	0.200"	18	Finished	1/4"	—	—	—	—	1.146"	2	Flush	1277N748		17.36
3/8"	0.200"	18	Finished	1/4"	—	—	—	—	1.146"	2	Standard	1277N47		13.76
3/8"	0.200"	18	Finished	5/16"	—	—	—	—	1.146"	2	Flush	1277N749		17.36
3/8"	0.200"	18	Finished	3/8"	—	—	—	—	1.146"	2	Flush	1277N751		19.91
3/8"	0.200"	18	Finished	1/2"	—	—	—	—	1.146"	2	Flush	1277N752		20.44
3/8"	0.200"	18	Finished	8 mm	—	—	—	—	1.15"	2	Flush	1277N782		17.36
3/8"	0.200"	18	Finished	8 mm	—	—	—	—	1.15"	2	Standard	1277N717		17.33
3/8"	0.200"	20	Finished	1/4"	—	—	—	—	1.273"	2	Flush	1277N753		17.51
3/8"	0.200"	20	Finished	1/4"	—	—	—	—	1.273"	2	Standard	1277N48		14.13
3/8"	0.200"	20	Finished	5/16"	—	—	—	—	1.273"	2	Flush	1277N754		17.51
3/8"	0.200"	20	Finished	3/8"	—	—	—	—	1.273"	2	Flush	1277N755		17.51
3/8"	0.200"	20	Finished	1/2"	—	—	—	—	1.273"	2	Flush	1277N756		20.00
3/8"	0.200"	20	Finished	8 mm	—	—	—	—	1.27"	2	Flush	1277N783		17.51
3/8"	0.200"	20	Finished	8 mm	—	—	—	—	1.27"	2	Standard	1277N718		17.76
3/8"	0.200"	21	Finished	1/4"	—	—	—	—	1.337"	2	Flush	1277N757		17.82
3/8"	0.200"	21	Finished	1/4"	—	—	—	—	1.337"	2	Standard	1277N49		14.91
3/8"	0.200"	22	Finished	1/4"	—	—	—	—	1.401"	2	Flush	1277N758		18.13
3/8"	0.200"	22	Finished	1/4"	—	—	—	—	1.401"	2	Standard	1277N5		15.96
3/8"	0.200"	22	Finished	5/16"	—	—	—	—	1.401"	2	Flush	1277N759		18.13
3/8"	0.200"	22	Finished	3/8"	—	—	—	—	1.401"	2	Flush	1277N761		20.67
3/8"	0.200"	22	Finished	8 mm	—	—	—	—	1.4"	2	Flush	1277N784		18.13
3/8"	0.200"	22	Finished	8 mm	—	—	—	—	1.4"	2	Standard	1277N719		18.53
3/8"	0.200"	24	Finished	1/4"	—	—	—	—	1.528"	2	Flush	1277N762		19.56
3/8"	0.200"	24	Finished	1/4"	—	—	—	—	1.528"	2	Standard	1277N51		16.64
3/8"	0.200"	24	Finished	5/16"	—	—	—	—	1.528"	2	Flush	1277N763		19.56
3/8"	0.200"	24	Finished	3/8"	—	—	—	—	1.528"	2	Flush	1277N764		19.56
3/8"	0.200"	24	Finished	3/8"	—	—	—	—	1.528"	2	Standard	1277N28		19.40
3/8"	0.200"	24	Finished	1/2"	—	—	—	—	1.528"	2	Flush	1277N765		19.93
3/8"	0.200"	24	Finished	8 mm	—	—	—	—	1.53"	2	Flush	1277N785		19.56
3/8"	0.200"	24	Finished	8 mm	—	—	—	—	1.53"	2	Standard	1277N721		19.40
3/8"	0.200"	26	Finished	1/4"	—	—	—	—	1.665"	2	Standard	1277N52		18.07
3/8"	0.200"	28	Finished	1/4"	—	—	—	—	1.783"	2	Flush	1277N766		24.20
3/8"	0.200"	28	Finished	1/4"	—	—	—	—	1.783"	2	Standard	1277N53		21.20
3/8"	0.200"	28	Finished	8 mm	—	—	—	—	1.78"	2	Flush	1277N786		24.20
3/8"	0.200"	28	Finished	8 mm	—	—	—	—	1.79"	2	Standard	1277N722		25.56
3/8"	0.200"	30	Finished	1/4"	—	—	—	—	1.91"	2	Flush	1277N767		24.73
3/8"	0.200"	30	Finished	1/4"	—	—	—	—	1.91"	2	Standard	1277N54		22.29
3/8"	0.200"	30	Finished	5/16"	—	—	—	—	1.91"	2	Flush	1277N768		32.53
3/8"	0.200"	30	Finished	3/8"	—	—	—	—	1.91"	2	Flush	1277N769		24.73
3/8"	0.200"	30	Finished	1/2"	—	—	—	—	1.91"	2	Flush	1277N771		32.53
3/8"	0.200"	30	Finished	8 mm	—	—	—	—	1.91"	2	Flush	1277N787		24.73
3/8"	0.200"	30	Finished	10 mm	—	—	—	—	1.91"	2	Standard	1277N723		26.42
3/8"	0.200"	32	Finished	1/4"	—	—	—	—	2.037"	2	Flush	1277N772		30.76
3/8"	0.200"	32	Finished	5/16"	—	—	—	—	2.037"	—	Standard	1277N55		23.78
3/8"	0.200"	32	Finished	5/16"	—	—	—	—	2.037"	2	Flush	1277N773		26.76
3/8"	0.200"	32	Finished	3/8"	—	—	—	—	2.037"	2	Flush	1277N774		26.76
3/8"	0.200"	32	Finished	8 mm	—	—	—	—	2.04"	2	Standard	1277N724		28.56

For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	For Bushing		Keyway			Pitch Dia.	No. of Flanges	Hub Type		Each
					Type	Trade No.	Wd.	Dp.						
3/8"	0.200"	32	Finished	12 mm	—	—	—	—	2.04"	2	Standard	1277N725	28.56	
3/8"	0.200"	36	Finished	5/16"	—	—	—	—	2.292"	—	Standard	1277N56	24.87	
3/8"	0.200"	36	Finished	10 mm	—	—	—	—	2.29"	—	Standard	1277N726	30.07	
3/8"	0.200"	40	Finished	5/16"	—	—	—	—	2.546"	—	Standard	1277N57	30.07	
3/8"	0.200"	40	Finished	12 mm	—	—	—	—	2.55"	—	Standard	1277N728	34.09	
3/8"	0.200"	42	Finished	5/16"	—	—	—	—	2.674"	—	Standard	1277N58	32.20	
3/8"	0.200"	44	Finished	5/16"	—	—	—	—	2.801"	—	Standard	1277N59	33.84	
3/8"	0.200"	45	Finished	3/8"	—	—	—	—	2.865"	—	Standard	1277N29	42.07	
3/8"	0.200"	48	Finished	5/16"	—	—	—	—	3.056"	—	Standard	1277N6	41.87	
3/8"	0.200"	48	Finished	12 mm	—	—	—	—	3.06"	—	Standard	1277N732	44.71	
3/8"	0.200"	50	Finished	3/8"	—	—	—	—	3.183"	—	Standard	1277N31	58.78	
3/8"	0.200"	60	Finished	3/8"	—	—	—	—	3.82"	—	Standard	1277N61	49.67	
3/8"	0.200"	60	Finished	12 mm	—	—	—	—	3.82"	—	Standard	1277N733	68.49	
3/8"	0.200"	72	Finished	12 mm	—	—	—	—	4.58"	—	Standard	1277N734	69.36	

For L Trade Size

Steel														
1/2"	0.375"	10	Finished	3/8"	—	—	—	—	1.194"	2	Standard	6495K23		30.62
1/2"	0.375"	12	Finished	3/8"	—	—	—	—	1.432"	2	Standard	6495K24		34.05
1/2"	0.375"	12	Finished	5/8"	—	—	3/16"	3/32"	1.432"	2	Standard	6495K251		26.62
1/2"	0.375"	14	Finished	3/8"	—	—	—	—	1.671"	2	Standard	6495K14		38.85
1/2"	0.375"	14	Finished	5/8"	—	—	3/16"	3/32"	1.671"	2	Standard	6495K252		30.24
1/2"	0.375"	15	Finished	5/8"	—	—	3/16"	3/32"	1.79"	2	Standard	6495K253		34.26
1/2"	0.375"	15	Finished	3/4"	—	—	3/16"	3/32"	1.79"	2	Standard	6495K254		34.26
1/2"	0.375"	16	Finished	1/2"	—	—	—	—	1.91"	2	Standard	6495K15		43.02
1/2"	0.375"	16	Finished	5/8"	—	—	3/16"	3/32"	1.91"	2	Standard	6495K255		34.26
1/2"	0.375"	16	Finished	3/4"	—	—	3/16"	3/32"	1.91"	2	Standard	6495K256		34.26
1/2"	0.375"	17	Finished	5/8"	—	—	3/16"	3/32"	2.029"	2	Standard	6495K257		37.56
1/2"	0.375"	17	Finished	3/4"	—	—	3/16"	3/32"	2.029"	2	Standard	6495K258		37.56
1/2"	0.375"	18	Finished	5/8"	—	—	3/16"	3/32"	2.149"	2	Standard	6495K259		77.44
1/2"	0.375"	18	Finished	3/4"	—	—	3/16"	3/32"	2.149"	2	Standard	6495K261		77.44
1/2"	0.375"	18	Plain	1/2"	—	—	—	—	2.149"	2	Standard	6495K16		45.31
1/2"	0.375"	18	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.149"	2	—	6495K211		58.51
1/2"	0.375"	19	Finished	5/8"	—	—	3/16"	3/32"	2.268"	2	Standard	6495K262		79.06
1/2"	0.375"	20	Plain	1/2"	—	—	—	—	2.387"	2	Standard	6495K17		55.45
1/2"	0.375"	20	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.387"	2	—	6495K212		59.76
1/2"	0.375"	22	Plain	1/2"	—	—	—	—	2.626"	2	Standard	6495K18		58.84
1/2"	0.375"	22	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.626"	2	—	6495K213		63.04
1/2"	0.375"	24	Plain	1/2"	—	—	—	—	2.865"	2	Standard	6495K19		60.93
1/2"	0.375"	24	Bushing	—	Quick Disconnect (QD)	SH	—	—	2.865"	2	—	6495K214		59.36
1/2"	0.375"	26	Plain	1/2"	—	—	—	—	3.104"	2	Standard	6495K106		86.00
1/2"	0.375"	26	Bushing	—	Quick Disconnect (QD)	SH	—	—	3.104"	2	—	6495K215		61.55
1/2"	0.375"	28	Plain	1/2"	—	—	—	—	3.342"	2	Standard	6495K107		92.38
1/2"	0.375"	28	Bushing	—	Quick Disconnect (QD)	SH	—	—	3.342"	2	—	6495K216		66.84
1/2"	0.375"	30	Plain	1/2"	—	—	—	—	3.581"	2	Standard	6495K108		103.62
1/2"	0.375"	30	Bushing	—	Quick Disconnect (QD)	SDS	—	—	3.581"	2	—	6495K217		67.82
1/2"	0.375"	32	Plain	1/2"	—	—	—	—	3.82"	2	Standard	6495K109		109.76
1/2"	0.375"	32	Bushing	—	Quick Disconnect (QD)	SDS	—	—	3.82"	2	—	6495K218		73.85
1/2"	0.375"	36	Bushing	—	Quick Disconnect (QD)	SDS	—	—	4.297"	2	—	6495K219		128.13
1/2"	0.375"	40	Bushing	—	Quick Disconnect (QD)	SDS	—	—	4.775"	2	—	6495K22		137.13
1/2"	0.375"	48	Bushing	—	Quick Disconnect (QD)	SDS	—	—	5.73"	2	—	6495K221		163.02
3/4"	0.375"	12	Finished	3/8"	—	—	—	—	1.432"	2	Standard	6495K101		50.87
3/4"	0.375"	12	Finished	5/8"	—	—	3/16"	3/32"	1.432"	2	Standard	6495K263		30.76
3/4"	0.375"	13	Finished	5/8"	—	—	3/16"	3/32"	1.552"	2	Standard	6495K264		33.36
3/4"	0.375"	14	Finished	3/8"	—	—	—	—	1.671"	2	Standard	6495K102		54.87
3/4"	0.375"	14	Finished	5/8"	—	—	3/16"	3/32"	1.671"	2	Standard	6495K265		33.36
3/4"	0.375"	15	Finished	5/8"	—	—	3/16"	3/32"	1.79"	2	Standard	6495K266		37.18
3/4"	0.375"	15	Finished	3/4"	—	—	3/16"	3/32"	1.79"	2	Standard	6495K267		37.18
3/4"	0.375"	16	Finished	1/2"	—	—	—	—	1.91"	2	Standard	6495K103		58.71
3/4"	0.375"	16	Finished	5/8"	—	—	3/16"	3/32"	1.91"	2	Standard	6495K268		37.68
3/4"	0.375"	16	Finished	3/4"	—	—	3/16"	3/32"	1.91"	2	Standard	6495K269		37.68
3/4"	0.375"	17	Finished	5/8"	—	—	3/16"	3/32"	2.029"	2	Standard	6495K271		41.28
3/4"	0.375"	17	Finished	3/4"	—	—	3/16"	3/32"	2.029"	2	Standard	6495K272		41.28
3/4"	0.375"	18	Plain	1/2"	—	—	—	—	2.149"	2	Standard	6495K882		69.60
3/4"	0.375"	18	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.149"	2	—	6495K311		61.55
3/4"	0.375"	20	Plain	1/2"	—	—	—	—	2.387"	2	Standard	6495K883		73.16
3/4"	0.375"	20	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.387"	2	—	6495K312		63.82
3/4"	0.375"	22	Plain	5/8"	—	—	—	—	2.626"	2	Standard	6495K881		92.09
3/4"	0.375"	22	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.626"	2	—	6495K313		69.09
3/4"	0.375"	24	Plain	5/8"	—	—	—	—	2.865"	2	Standard	6495K885		100.42
3/4"	0.375"	24	Bushing	—	Quick Disconnect (QD)	SH	—	—	2.865"	2	—	6495K314		65.35
3/4"	0.375"	26	Plain	5/8"	—	—	—	—	3.104"	2	Standard	6495K886		109.40

For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	For Bushing		Keyway			Pitch Dia.	No. of Flanges	Hub Type	Each
					Type	Trade No.	Wd.	Dr.					
3/4"	0.375"	26	Bushing	—	Quick Disconnect (QD)	SH	—	—	3.104"	2	—	6495K315	70.09
3/4"	0.375"	28	Plain	5/8"	—	—	—	—	3.342"	2	Standard	6495K887	114.85
3/4"	0.375"	28	Bushing	—	Quick Disconnect (QD)	SH	—	—	3.342"	2	—	6495K316	75.96
3/4"	0.375"	30	Plain	5/8"	—	—	—	—	3.581"	2	Standard	6495K878	126.11
3/4"	0.375"	30	Bushing	—	Quick Disconnect (QD)	SDS	—	—	3.581"	2	—	6495K317	79.91
3/4"	0.375"	32	Plain	5/8"	—	—	—	—	3.82"	2	Standard	6495K889	135.73
3/4"	0.375"	32	Bushing	—	Quick Disconnect (QD)	SDS	—	—	3.82"	2	—	6495K318	85.36
3/4"	0.375"	36	Bushing	—	Quick Disconnect (QD)	SDS	—	—	4.297"	2	—	6495K319	137.13
3/4"	0.375"	40	Bushing	—	Quick Disconnect (QD)	SDS	—	—	4.775"	2	—	6495K32	139.40
3/4"	0.375"	48	Bushing	—	Quick Disconnect (QD)	SDS	—	—	5.73"	2	—	6495K321	166.78
1"	0.375"	14	Finished	3/8"	—	—	—	—	1.671"	2	Standard	6495K104	52.65
1"	0.375"	14	Finished	5/8"	—	—	3/16"	3/32"	1.671"	2	Standard	6495K273	41.80
1"	0.375"	15	Finished	5/8"	—	—	3/16"	3/32"	1.79"	2	Standard	6495K274	42.84
1"	0.375"	15	Finished	3/4"	—	—	3/16"	3/32"	1.79"	2	Standard	6495K275	42.84
1"	0.375"	16	Finished	1/2"	—	—	—	—	1.91"	2	Standard	6495K105	56.47
1"	0.375"	16	Finished	5/8"	—	—	3/16"	3/32"	1.91"	2	Standard	6495K276	43.34
1"	0.375"	16	Finished	3/4"	—	—	3/16"	3/32"	1.91"	2	Standard	6495K277	43.34
1"	0.375"	17	Finished	5/8"	—	—	3/16"	3/32"	2.029"	2	Standard	6495K278	49.46
1"	0.375"	17	Finished	3/4"	—	—	3/16"	3/32"	2.029"	2	Standard	6495K279	49.46
1"	0.375"	18	Plain	1/2"	—	—	—	—	2.149"	2	Standard	6495K891	76.04
1"	0.375"	18	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.149"	2	—	6495K411	66.84
1"	0.375"	20	Plain	1/2"	—	—	—	—	2.387"	2	Standard	6495K892	80.85
1"	0.375"	20	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.387"	2	—	6495K412	70.09
1"	0.375"	22	Plain	5/8"	—	—	—	—	2.626"	2	Standard	6495K893	97.55
1"	0.375"	22	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.626"	2	—	6495K413	74.58
1"	0.375"	24	Plain	5/8"	—	—	—	—	2.865"	2	Standard	6495K894	105.56
1"	0.375"	24	Bushing	—	Quick Disconnect (QD)	SH	—	—	2.865"	2	—	6495K414	70.60
1"	0.375"	26	Plain	5/8"	—	—	—	—	3.104"	2	Standard	6495K895	113.58
1"	0.375"	26	Bushing	—	Quick Disconnect (QD)	SH	—	—	3.104"	2	—	6495K415	76.02
1"	0.375"	28	Plain	5/8"	—	—	—	—	3.342"	2	Standard	6495K896	117.71
1"	0.375"	28	Bushing	—	Quick Disconnect (QD)	SH	—	—	3.342"	2	—	6495K416	79.91
1"	0.375"	30	Plain	5/8"	—	—	—	—	3.581"	2	Standard	6495K897	117.71
1"	0.375"	30	Bushing	—	Quick Disconnect (QD)	SDS	—	—	3.581"	2	—	6495K417	86.89
1"	0.375"	32	Plain	5/8"	—	—	—	—	3.82"	2	Standard	6495K898	142.44
1"	0.375"	32	Bushing	—	Quick Disconnect (QD)	SDS	—	—	3.82"	2	—	6495K418	93.69
1"	0.375"	36	Bushing	—	Quick Disconnect (QD)	SDS	—	—	4.297"	2	—	6495K419	137.42
1"	0.375"	40	Bushing	—	Quick Disconnect (QD)	SDS	—	—	4.775"	2	—	6495K42	140.18
1"	0.375"	48	Bushing	—	Quick Disconnect (QD)	SDS	—	—	5.73"	2	—	6495K421	173.78
Iron													
1/2"	0.375"	60	Bushing	—	Quick Disconnect (QD)	SD	—	—	7.162"	—	—	6495K222	164.02
3/4"	0.375"	60	Bushing	—	Quick Disconnect (QD)	SD	—	—	7.162"	—	—	6495K322	172.36
1"	0.375"	60	Bushing	—	Quick Disconnect (QD)	SD	—	—	7.162"	—	—	6495K422	175.16
Corrosion-Resistant Aluminum													
1/2"	0.375"	10	Finished	10 mm	—	—	—	—	1.19"	2	Standard	3567N11	24.71
1/2"	0.375"	12	Finished	10 mm	—	—	—	—	1.43"	2	Standard	3567N12	27.42
1/2"	0.375"	13	Finished	10 mm	—	—	—	—	1.55"	2	Standard	3567N13	29.76
1/2"	0.375"	14	Finished	12 mm	—	—	—	—	1.67"	2	Standard	3567N14	31.82
1/2"	0.375"	15	Finished	12 mm	—	—	—	—	1.79"	2	Standard	3567N15	34.31
1/2"	0.375"	16	Finished	14 mm	—	—	—	—	1.91"	2	Standard	3567N16	33.84
1/2"	0.375"	17	Finished	14 mm	—	—	—	—	2.03"	2	Standard	3567N17	37.49
1/2"	0.375"	18	Finished	1/2"	—	—	—	—	2.149"	2	Standard	1304N11	26.72
1/2"	0.375"	18	Finished	14 mm	—	—	—	—	2.15"	2	Standard	3567N18	37.42
1/2"	0.375"	20	Finished	1/2"	—	—	—	—	2.387"	2	Standard	1304N12	30.25
1/2"	0.375"	20	Finished	14 mm	—	—	—	—	2.39"	2	Standard	3567N21	42.31
1/2"	0.375"	22	Finished	1/2"	—	—	—	—	2.626"	2	Standard	1304N13	38.85
1/2"	0.375"	22	Finished	14 mm	—	—	—	—	2.63"	2	Standard	3567N22	50.78
1/2"	0.375"	24	Finished	1/2"	—	—	—	—	2.865"	2	Standard	1304N14	47.70
1/2"	0.375"	24	Finished	14 mm	—	—	—	—	2.86"	2	Standard	3567N23	62.84
1/2"	0.375"	26	Finished	1/2"	—	—	—	—	3.104"	2	Standard	1304N15	69.60
1/2"	0.375"	26	Finished	14 mm	—	—	—	—	3.1"	2	Standard	3567N24	102.47
1/2"	0.375"	28	Finished	1/2"	—	—	—	—	3.342"	2	Standard	1304N16	76.55
1/2"	0.375"	30	Finished	1/2"	—	—	—	—	3.581"	2	Standard	1304N17	84.17
1/2"	0.375"	30	Finished	14 mm	—	—	—	—	3.58"	2	Standard	3567N26	104.78
1/2"	0.375"	32	Finished	1/2"	—	—	—	—	3.82"	2	Standard	1304N18	88.47
1/2"	0.375"	32	Finished	14 mm	—	—	—	—	3.82"	2	Standard	3567N27	117.35
1/2"	0.375"	36	Finished	1/2"	—	—	—	—	4.297"	2	Standard	1304N19	94.85
1/2"	0.375"	40	Finished	1/2"	—	—	—	—	4.775"	2	Standard	1304N2	103.87
1/2"	0.375"	40	Finished	14 mm	—	—	—	—	4.77"	2	Standard	3567N29	134.15
3/4"	0.375"	18	Finished	1/2"	—	—	—	—	2.149"	2	Standard	1304N21	52.91
3/4"	0.375"	20	Finished	1/2"	—	—	—	—	2.387"	2	Standard	1304N22	58.79
3/4"	0.375"	22	Finished	1/2"	—	—	—	—	2.626"	2	Standard	1304N23	64.66

		For Bushing				Keyway							
For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	Type	Trade No.	Wd.	Dp.	Pitch Dia.	No. of Flanges	Hub Type		Each
3/4"	0.375"	24	Finished	1/2"	—	—	—	—	2.865"	2	Standard	1304N24	70.53
3/4"	0.375"	26	Finished	1/2"	—	—	—	—	3.104"	2	Standard	1304N25	76.43
3/4"	0.375"	28	Finished	1/2"	—	—	—	—	3.342"	2	Standard	1304N26	82.30
3/4"	0.375"	30	Finished	1/2"	—	—	—	—	3.581"	2	Standard	1304N27	88.19
3/4"	0.375"	32	Finished	1/2"	—	—	—	—	3.82"	2	Standard	1304N28	94.06
3/4"	0.375"	36	Finished	1/2"	—	—	—	—	4.297"	2	Standard	1304N29	99.92
3/4"	0.375"	40	Finished	1/2"	—	—	—	—	4.775"	2	Standard	1304N3	105.83
1"	0.375"	18	Finished	1/2"	—	—	—	—	2.149"	2	Standard	1304N31	55.87
1"	0.375"	20	Finished	1/2"	—	—	—	—	2.387"	2	Standard	1304N32	61.72
1"	0.375"	22	Finished	1/2"	—	—	—	—	2.626"	2	Standard	1304N33	70.53
1"	0.375"	24	Finished	1/2"	—	—	—	—	2.865"	2	Standard	1304N34	73.49
1"	0.375"	26	Finished	1/2"	—	—	—	—	3.104"	2	Standard	1304N35	79.38
1"	0.375"	28	Finished	1/2"	—	—	—	—	3.342"	2	Standard	1304N36	85.23
1"	0.375"	30	Finished	1/2"	—	—	—	—	3.581"	2	Standard	1304N37	91.13
1"	0.375"	32	Finished	1/2"	—	—	—	—	3.82"	2	Standard	1304N38	96.98
1"	0.375"	36	Finished	1/2"	—	—	—	—	4.297"	2	Standard	1304N39	102.89
1"	0.375"	40	Finished	1/2"	—	—	—	—	4.775"	2	Standard	1304N4	117.19
For H Trade Size													
Steel													
1"	0.500"	14	Plain	5/8"	—	—	—	—	2.228"	2	Standard	6495K43	71.80
1"	0.500"	14	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.228"	2	—	6495K511	61.55
1"	0.500"	16	Plain	5/8"	—	—	—	—	2.546"	2	Standard	6495K44	81.09
1"	0.500"	16	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.546"	2	—	6495K512	70.58
1"	0.500"	18	Plain	5/8"	—	—	—	—	2.865"	2	Standard	6495K45	85.22
1"	0.500"	18	Bushing	—	Quick Disconnect (QD)	SH	—	—	2.865"	2	—	6495K513	67.05
1"	0.500"	20	Plain	5/8"	—	—	—	—	3.183"	2	Standard	6495K46	101.00
1"	0.500"	20	Bushing	—	Quick Disconnect (QD)	SH	—	—	3.183"	2	—	6495K514	83.18
1"	0.500"	21	Plain	3/4"	—	—	—	—	3.342"	2	Standard	6495K91	133.78
1"	0.500"	22	Plain	3/4"	—	—	—	—	3.501"	2	Standard	6495K92	134.11
1"	0.500"	22	Bushing	—	Quick Disconnect (QD)	SDS	—	—	3.501"	2	—	6495K515	92.16
1"	0.500"	24	Plain	3/4"	—	—	—	—	3.82"	2	Standard	6495K47	118.11
1"	0.500"	24	Bushing	—	Quick Disconnect (QD)	SDS	—	—	3.82"	2	—	6495K516	102.27
1"	0.500"	26	Plain	3/4"	—	—	—	—	4.138"	2	Standard	6495K93	162.36
1"	0.500"	26	Bushing	—	Quick Disconnect (QD)	SDS	—	—	4.138"	2	—	6495K517	116.87
1"	0.500"	28	Plain	3/4"	—	—	—	—	4.456"	2	Standard	6495K48	161.53
1"	0.500"	28	Bushing	—	Quick Disconnect (QD)	SDS	—	—	4.456"	2	—	6495K518	124.55
1 1/2"	0.500"	14	Plain	3/4"	—	—	—	—	2.228"	2	Standard	6495K94	110.04
1 1/2"	0.500"	14	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.228"	2	—	6495K611	81.38
1 1/2"	0.500"	16	Plain	3/4"	—	—	—	—	2.546"	2	Standard	6495K95	125.16
1 1/2"	0.500"	16	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.546"	2	—	6495K612	89.13
1 1/2"	0.500"	18	Plain	3/4"	—	—	—	—	2.865"	2	Standard	6495K96	134.11
1 1/2"	0.500"	18	Bushing	—	Quick Disconnect (QD)	SH	—	—	2.865"	2	—	6495K613	92.16
1 1/2"	0.500"	19	Plain	3/4"	—	—	—	—	3.024"	2	Standard	6495K97	146.33
1 1/2"	0.500"	20	Plain	3/4"	—	—	—	—	3.183"	2	Standard	6495K98	156.27
1 1/2"	0.500"	20	Bushing	—	Quick Disconnect (QD)	SH	—	—	3.183"	2	—	6495K614	103.00
1 1/2"	0.500"	21	Plain	3/4"	—	—	—	—	3.342"	2	Standard	6495K99	162.36
1 1/2"	0.500"	22	Plain	3/4"	—	—	—	—	3.501"	2	Standard	6495K161	170.69
1 1/2"	0.500"	22	Bushing	—	Quick Disconnect (QD)	SD	—	—	3.501"	2	—	6495K615	115.33
1 1/2"	0.500"	24	Plain	3/4"	—	—	—	—	3.82"	2	Standard	6495K162	182.87
1 1/2"	0.500"	24	Bushing	—	Quick Disconnect (QD)	SD	—	—	3.82"	2	—	6495K616	124.55
1 1/2"	0.500"	26	Plain	3/4"	—	—	—	—	4.138"	2	Standard	6495K163	198.95
1 1/2"	0.500"	26	Bushing	—	Quick Disconnect (QD)	SD	—	—	4.138"	2	—	6495K617	138.42
1 1/2"	0.500"	28	Bushing	—	Quick Disconnect (QD)	SD	—	—	4.456"	2	—	6495K618	145.95
2"	0.500"	14	Plain	3/4"	—	—	—	—	2.228"	2	Standard	6495K164	134.11
2"	0.500"	14	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.228"	2	—	6495K811	86.16
2"	0.500"	16	Plain	3/4"	—	—	—	—	2.546"	2	Standard	6495K165	150.18
2"	0.500"	16	Bushing	—	Quick Disconnect (QD)	JA	—	—	2.546"	2	—	6495K812	97.20
2"	0.500"	18	Plain	3/4"	—	—	—	—	2.865"	2	Standard	6495K166	162.36
2"	0.500"	18	Bushing	—	Quick Disconnect (QD)	SH	—	—	2.865"	2	—	6495K813	101.62
2"	0.500"	19	Plain	3/4"	—	—	—	—	3.024"	2	Standard	6495K167	170.69
2"	0.500"	20	Plain	3/4"	—	—	—	—	3.183"	2	Standard	6495K168	174.87
2"	0.500"	22	Plain	1"	—	—	—	—	3.501"	2	Standard	6495K169	186.71
2"	0.500"	24	Plain	1"	—	—	—	—	3.82"	2	Standard	6495K171	203.07
2"	0.500"	26	Plain	1"	—	—	—	—	4.138"	2	Standard	6495K172	238.73
3"	0.500"	16	Plain	3/4"	—	—	—	—	2.546"	2	Standard	6495K173	188.04
Iron													
1"	0.500"	30	Bushing	—	Quick Disconnect (QD)	SD	—	—	4.775"	2	—	6495K519	132.89
1"	0.500"	32	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.093"	2	—	6495K52	144.45
1"	0.500"	36	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.73"	2	—	6495K521	168.78
1"	0.500"	40	Bushing	—	Quick Disconnect (QD)	SK	—	—	6.366"	2	—	6495K522	191.60

For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	For Bushing	Keyway			Pitch Dia.	No. of Flanges	Hub Type	Each	
					Type	Trade No.	Wd.	Dp.					
1"	0.500"	48	Bushing	—	Quick Disconnect (QD)	SK	—	—	7.639"	2	—	6495K523	222.27
1"	0.500"	60	Bushing	—	Quick Disconnect (QD)	SF	—	—	9.549"	—	—	6495K524	230.55
1"	0.500"	120	Bushing	—	Quick Disconnect (QD)	SF	—	—	19.099"	—	—	6495K525	475.75
1 1/2"	0.500"	30	Bushing	—	Quick Disconnect (QD)	SD	—	—	4.775"	2	—	6495K619	154.60
1 1/2"	0.500"	32	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.093"	2	—	6495K62	169.04
1 1/2"	0.500"	36	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.73"	2	—	6495K621	194.18
1 1/2"	0.500"	40	Bushing	—	Quick Disconnect (QD)	SK	—	—	6.366"	2	—	6495K622	213.42
1 1/2"	0.500"	48	Bushing	—	Quick Disconnect (QD)	SK	—	—	7.639"	2	—	6495K623	248.11
1 1/2"	0.500"	60	Bushing	—	Quick Disconnect (QD)	SF	—	—	9.549"	—	—	6495K624	249.81
1 1/2"	0.500"	120	Bushing	—	Quick Disconnect (QD)	SF	—	—	19.099"	—	—	6495K625	533.18
2"	0.500"	20	Bushing	—	Quick Disconnect (QD)	SH	—	—	3.183"	2	—	6495K814	112.66
2"	0.500"	22	Bushing	—	Quick Disconnect (QD)	SD	—	—	3.501"	2	—	6495K815	114.88
2"	0.500"	24	Bushing	—	Quick Disconnect (QD)	SD	—	—	3.82"	2	—	6495K816	123.72
2"	0.500"	26	Bushing	—	Quick Disconnect (QD)	SD	—	—	4.138"	2	—	6495K817	134.74
2"	0.500"	28	Bushing	—	Quick Disconnect (QD)	SD	—	—	4.456"	2	—	6495K818	143.58
2"	0.500"	30	Bushing	—	Quick Disconnect (QD)	SD	—	—	4.775"	2	—	6495K819	154.64
2"	0.500"	32	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.093"	2	—	6495K82	161.26
2"	0.500"	36	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.73"	2	—	6495K821	209.88
2"	0.500"	40	Bushing	—	Quick Disconnect (QD)	SK	—	—	6.366"	2	—	6495K822	231.96
2"	0.500"	48	Bushing	—	Quick Disconnect (QD)	SF	—	—	7.639"	2	—	6495K823	290.94
2"	0.500"	60	Bushing	—	Quick Disconnect (QD)	SF	—	—	9.549"	—	—	6495K824	312.14
2"	0.500"	120	Bushing	—	Quick Disconnect (QD)	E	—	—	19.099"	—	—	6495K825	640.00

For XH Trade Size

Iron													
2"	0.875"	18	Plain	1"	—	—	—	—	5.013"	2	Standard	5728N11	300.09
2"	0.875"	18	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.013"	2	—	5732N11	281.30
2"	0.875"	20	Plain	1"	—	—	—	—	5.57"	2	Standard	5728N12	314.38
2"	0.875"	20	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.57"	2	—	5732N12	294.70
2"	0.875"	22	Bushing	—	Quick Disconnect (QD)	SK	—	—	6.127"	2	—	5732N13	311.96
2"	0.875"	23	Bushing	—	Quick Disconnect (QD)	SK	—	—	6.406"	2	—	5732N14	311.90
2"	0.875"	24	Bushing	—	Quick Disconnect (QD)	SF	—	—	6.685"	2	—	5732N15	322.84
2"	0.875"	26	Bushing	—	Quick Disconnect (QD)	SF	—	—	7.241"	2	—	5732N16	403.75
2"	0.875"	28	Bushing	—	Quick Disconnect (QD)	F	—	—	7.799"	2	—	5732N17	433.11
2"	0.875"	30	Bushing	—	Quick Disconnect (QD)	F	—	—	8.356"	2	—	5732N18	719.07
2"	0.875"	32	Bushing	—	Quick Disconnect (QD)	F	—	—	8.913"	2	—	5732N19	743.44
2"	0.875"	36	Bushing	—	Quick Disconnect (QD)	F	—	—	10.027"	2	—	5732N21	848.82
2"	0.875"	40	Bushing	—	Quick Disconnect (QD)	F	—	—	11.141"	2	—	5732N22	951.64
2"	0.875"	48	Bushing	—	Quick Disconnect (QD)	F	—	—	13.369"	—	—	5732N23	1,047.75
2"	0.875"	60	Bushing	—	Quick Disconnect (QD)	F	—	—	16.711"	—	—	5732N24	1,354.25
3"	0.875"	18	Plain	1"	—	—	—	—	5.013"	2	Standard	5728N13	321.53
3"	0.875"	18	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.013"	2	—	5732N25	301.40
3"	0.875"	20	Plain	1"	—	—	—	—	5.57"	2	Standard	5728N14	364.39
3"	0.875"	20	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.57"	2	—	5732N26	341.58
3"	0.875"	22	Bushing	—	Quick Disconnect (QD)	SK	—	—	6.127"	2	—	5732N27	384.40
3"	0.875"	24	Bushing	—	Quick Disconnect (QD)	SF	—	—	6.685"	2	—	5732N28	413.92
3"	0.875"	26	Bushing	—	Quick Disconnect (QD)	SF	—	—	7.241"	2	—	5732N29	512.09
3"	0.875"	28	Bushing	—	Quick Disconnect (QD)	E	—	—	7.799"	2	—	5732N31	545.99
3"	0.875"	30	Bushing	—	Quick Disconnect (QD)	E	—	—	8.356"	2	—	5732N32	899.60
3"	0.875"	36	Bushing	—	Quick Disconnect (QD)	E	—	—	10.027"	2	—	5732N33	1,047.49
3"	0.875"	40	Bushing	—	Quick Disconnect (QD)	F	—	—	11.141"	2	—	5732N34	1,166.69
3"	0.875"	48	Bushing	—	Quick Disconnect (QD)	F	—	—	13.369"	—	—	5732N35	1,281.05
4"	0.875"	18	Plain	1"	—	—	—	—	5.013"	2	Standard	5728N15	441.84
4"	0.875"	20	Plain	1"	—	—	—	—	5.57"	2	Standard	5728N16	450.14
4"	0.875"	20	Bushing	—	Quick Disconnect (QD)	SK	—	—	5.57"	2	—	5732N36	421.96
4"	0.875"	22	Bushing	—	Quick Disconnect (QD)	SK	—	—	6.127"	2	—	5732N37	475.52
4"	0.875"	24	Plain	1"	—	—	—	—	6.685"	2	Standard	5728N17	550.16
4"	0.875"	24	Bushing	—	Quick Disconnect (QD)	SF	—	—	6.685"	2	—	5732N38	515.72
4"	0.875"	26	Plain	1"	—	—	—	—	7.241"	2	Standard	5728N18	593.02
4"	0.875"	26	Bushing	—	Quick Disconnect (QD)	SF	—	—	7.241"	2	—	5732N39	632.91
4"	0.875"	28	Bushing	—	Quick Disconnect (QD)	E	—	—	7.799"	2	—	5732N41	661.87
4"	0.875"	30	Bushing	—	Quick Disconnect (QD)	E	—	—	8.356"	2	—	5732N42	1,047.75
4"	0.875"	32	Bushing	—	Quick Disconnect (QD)	E	—	—	8.913"	2	—	5732N43	1,104.91
4"	0.875"	36	Bushing	—	Quick Disconnect (QD)	E	—	—	10.027"	2	—	5732N44	1,240.11

For XXH Trade Size

Iron													
2"	1.25"	22	Bushing	—	Quick Disconnect (QD)	E	—	—	8.753"	2	—	5471N11	649.70
2"	1.25"	30	Bushing	—	Quick Disconnect (QD)	F	—	—	11.937"	2	—	5471N12	941.49
2"	1.25"	48	Bushing	—	Quick Disconnect (QD)	J	—	—	19.099"	—	—	5471N13	1,458.91
3"	1.25"	22	Bushing	—	Quick Disconnect (QD)	E	—	—	8.753"	2	—	5471N14	746.98
3"	1.25"	30	Bushing	—	Quick Disconnect (QD)	F	—	—	11.937"	2	—	5471N15	1,101.02

For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	For Bushings	Keyway			Pitch Dia.	No. of Flanges	Hub Type	Each
					Type	Trade No.	Wd.	Dp.				
4"	1.25"	22	Bushing	—	Quick Disconnect (QD)	E	—	—	8.753"	2	—	5471N16 981.63
4"	1.25"	34	Bushing	—	Quick Disconnect (QD)	J	—	—	13.528"	2	—	5471N17 1,458.91

For T2.5 Trade Size

Corrosion-Resistant Aluminum

6 mm	2.5 mm	15	Plain	—	—	—	—	—	12 mm	1	Standard	3568N101 19.90
6 mm	2.5 mm	20	Plain	—	—	—	—	—	16 mm	2	Standard	3568N102 22.71
6 mm	2.5 mm	28	Plain	—	—	—	—	—	22 mm	2	Standard	3568N103 23.25
6 mm	2.5 mm	44	Plain	—	—	—	—	—	35 mm	—	Standard	3568N104 24.85
6 mm	2.5 mm	48	Plain	—	—	—	—	—	38 mm	—	Standard	3568N105 25.42
6 mm	2.5 mm	60	Plain	—	—	—	—	—	48 mm	—	Standard	3568N106 29.50

For T5 Trade Size

Corrosion-Resistant Aluminum

10 mm	5 mm	10	Plain	—	—	—	—	—	16.1 mm	2	Standard	1428N2 12.94
10 mm	5 mm	12	Plain	—	—	—	—	—	19.3 mm	2	Standard	1428N21 14.64
10 mm	5 mm	14	Plain	—	—	—	—	—	22.5 mm	2	Standard	1428N22 14.82
10 mm	5 mm	15	Plain	—	—	—	—	—	24.1 mm	2	Standard	1428N23 14.98
10 mm	5 mm	16	Plain	—	—	—	—	—	25.6 mm	2	Standard	1428N24 15.50
10 mm	5 mm	18	Plain	—	—	—	—	—	28.8 mm	2	Standard	1428N25 16.02
10 mm	5 mm	19	Plain	—	—	—	—	—	30.4 mm	2	Standard	1428N26 17.24
10 mm	5 mm	20	Plain	—	—	—	—	—	32 mm	2	Standard	1428N27 17.38
10 mm	5 mm	22	Plain	—	—	—	—	—	35.3 mm	2	Standard	1428N28 18.08
10 mm	5 mm	24	Plain	—	—	—	—	—	38.4 mm	2	Standard	1428N29 18.42
10 mm	5 mm	25	Plain	—	—	—	—	—	40 mm	2	Standard	1428N3 18.60
10 mm	5 mm	26	Plain	—	—	—	—	—	41.6 mm	2	Standard	1428N31 18.96
10 mm	5 mm	27	Plain	—	—	—	—	—	43.2 mm	2	Standard	1428N32 19.64
10 mm	5 mm	30	Plain	—	—	—	—	—	47.8 mm	2	Standard	1428N33 19.82
10 mm	5 mm	32	Plain	—	—	—	—	—	50.9 mm	2	Standard	1428N34 22.38
10 mm	5 mm	36	Plain	—	—	—	—	—	57.3 mm	2	Standard	1428N35 23.78
10 mm	5 mm	40	Plain	—	—	—	—	—	63.7 mm	2	Standard	1428N36 31.00
10 mm	5 mm	48	Plain	—	—	—	—	—	76.4 mm	—	Standard	1428N37 36.16
10 mm	5 mm	60	Plain	—	—	—	—	—	95.5 mm	—	Standard	1428N38 44.78
16 mm	5 mm	10	Plain	—	—	—	—	—	16.1 mm	2	Standard	1428N4 16.28
16 mm	5 mm	12	Plain	—	—	—	—	—	19.3 mm	2	Standard	1428N41 16.84
16 mm	5 mm	14	Plain	—	—	—	—	—	22.5 mm	2	Standard	1428N42 17.40
16 mm	5 mm	15	Plain	—	—	—	—	—	24.1 mm	2	Standard	1428N43 17.76
16 mm	5 mm	16	Plain	—	—	—	—	—	25.6 mm	2	Standard	1428N44 19.54
16 mm	5 mm	18	Plain	—	—	—	—	—	28.8 mm	2	Standard	1428N45 19.74
16 mm	5 mm	19	Plain	—	—	—	—	—	30.4 mm	2	Standard	1428N46 20.18
16 mm	5 mm	20	Plain	—	—	—	—	—	32 mm	2	Standard	1428N47 21.02
16 mm	5 mm	22	Plain	—	—	—	—	—	35.3 mm	2	Standard	1428N48 22.92
16 mm	5 mm	24	Plain	—	—	—	—	—	38.4 mm	2	Standard	1428N49 24.12
16 mm	5 mm	25	Plain	—	—	—	—	—	40 mm	2	Standard	1428N5 24.46
16 mm	5 mm	26	Plain	—	—	—	—	—	41.6 mm	2	Standard	1428N51 25.44
16 mm	5 mm	27	Plain	—	—	—	—	—	43.2 mm	2	Standard	1428N52 25.78
16 mm	5 mm	30	Plain	—	—	—	—	—	48 mm	2	Standard	1428N53 26.20
16 mm	5 mm	32	Plain	—	—	—	—	—	51.1 mm	2	Standard	1428N54 26.76
16 mm	5 mm	36	Plain	—	—	—	—	—	57.5 mm	2	Standard	1428N55 27.86
16 mm	5 mm	40	Plain	—	—	—	—	—	63.9 mm	2	Standard	1428N56 31.80
16 mm	5 mm	48	Plain	—	—	—	—	—	76.6 mm	—	Standard	1428N57 35.90
16 mm	5 mm	60	Plain	—	—	—	—	—	95.7 mm	—	Standard	1428N58 48.88
25 mm	5 mm	10	Plain	—	—	—	—	—	16.1 mm	2	Standard	1428N6 17.40
25 mm	5 mm	14	Plain	—	—	—	—	—	22.5 mm	2	Standard	1428N62 18.88
25 mm	5 mm	15	Plain	—	—	—	—	—	24.1 mm	2	Standard	1428N63 19.44
25 mm	5 mm	16	Plain	—	—	—	—	—	25.6 mm	2	Standard	1428N64 20.74
25 mm	5 mm	18	Plain	—	—	—	—	—	28.8 mm	2	Standard	1428N65 21.36
25 mm	5 mm	20	Plain	—	—	—	—	—	32 mm	2	Standard	1428N67 22.80
25 mm	5 mm	22	Plain	—	—	—	—	—	35.3 mm	2	Standard	1428N68 25.18
25 mm	5 mm	24	Plain	—	—	—	—	—	38.4 mm	2	Standard	1428N69 26.32
25 mm	5 mm	25	Plain	—	—	—	—	—	40 mm	2	Standard	1428N7 27.74
25 mm	5 mm	26	Plain	—	—	—	—	—	41.6 mm	2	Standard	1428N71 28.12
25 mm	5 mm	27	Plain	—	—	—	—	—	43.2 mm	2	Standard	1428N72 28.64
25 mm	5 mm	30	Plain	—	—	—	—	—	48 mm	2	Standard	1428N73 29.20
25 mm	5 mm	32	Plain	—	—	—	—	—	51.1 mm	2	Standard	1428N74 29.72
25 mm	5 mm	36	Plain	—	—	—	—	—	57.5 mm	2	Standard	1428N75 32.68
25 mm	5 mm	40	Plain	—	—	—	—	—	63.9 mm	2	Standard	1428N76 36.12
25 mm	5 mm	48	Plain	—	—	—	—	—	76.6 mm	—	Standard	1428N77 44.76
25 mm	5 mm	60	Plain	—	—	—	—	—	95.7 mm	—	Standard	1428N78 58.54

For AT5 Trade Size

				For		Keyway								
For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	Type	Trade No.	Bushing		Pitch Dia.	No. of Flanges	Hub Type	Each		
							Wd.	Dp.						
Corrosion-Resistant Aluminum														
10 mm	5 mm	12	Plain	—	—	—	—	—	19.3 mm	2	Standard	3709N11	39.13	
10 mm	5 mm	15	Plain	—	—	—	—	—	24.1 mm	2	Standard	3709N13	41.69	
10 mm	5 mm	20	Plain	—	—	—	—	—	32 mm	2	Standard	3709N17	51.93	
10 mm	5 mm	22	Plain	—	—	—	—	—	35.3 mm	2	Standard	3709N18	53.77	
10 mm	5 mm	24	Plain	—	—	—	—	—	38.4 mm	2	Standard	3709N19	54.50	
10 mm	5 mm	27	Plain	—	—	—	—	—	43.2 mm	2	Standard	3709N23	55.95	
10 mm	5 mm	30	Plain	8 mm	—	—	—	—	48 mm	2	Standard	3709N25	57.42	
10 mm	5 mm	42	Plain	8 mm	—	—	—	—	67 mm	2	Standard	3709N29	76.08	
10 mm	5 mm	60	Plain	8 mm	—	—	—	—	95.7 mm	—	Standard	3709N33	97.30	
16 mm	5 mm	12	Plain	—	—	—	—	—	19.3 mm	2	Standard	3709N34	41.69	
16 mm	5 mm	18	Plain	—	—	—	—	—	28.8 mm	2	Standard	3709N38	51.93	
16 mm	5 mm	20	Plain	—	—	—	—	—	32 mm	2	Standard	3709N41	55.23	
16 mm	5 mm	22	Plain	—	—	—	—	—	35.3 mm	2	Standard	3709N42	55.95	
16 mm	5 mm	24	Plain	—	—	—	—	—	38.4 mm	2	Standard	3709N43	57.42	
16 mm	5 mm	25	Plain	—	—	—	—	—	40 mm	2	Standard	3709N44	58.52	
16 mm	5 mm	26	Plain	—	—	—	—	—	41.6 mm	2	Standard	3709N45	60.72	
16 mm	5 mm	27	Plain	8 mm	—	—	—	—	43.2 mm	2	Standard	3709N46	62.55	
16 mm	5 mm	28	Plain	8 mm	—	—	—	—	44.8 mm	2	Standard	3709N47	64.00	
16 mm	5 mm	30	Plain	8 mm	—	—	—	—	48 mm	2	Standard	3709N48	65.47	
16 mm	5 mm	32	Plain	8 mm	—	—	—	—	51.1 mm	2	Standard	3709N49	69.50	
16 mm	5 mm	36	Plain	8 mm	—	—	—	—	57.5 mm	2	Standard	3709N51	73.52	
16 mm	5 mm	40	Plain	8 mm	—	—	—	—	63.9 mm	2	Standard	3709N52	83.75	
16 mm	5 mm	42	Plain	8 mm	—	—	—	—	67 mm	2	Standard	3709N53	86.32	
16 mm	5 mm	44	Plain	8 mm	—	—	—	—	70.2 mm	—	Standard	3709N54	81.57	
16 mm	5 mm	60	Plain	8 mm	—	—	—	—	95.7 mm	—	Standard	3709N56	104.60	
25 mm	5 mm	16	Plain	—	—	—	—	—	25.6 mm	2	Standard	3709N61	57.42	
25 mm	5 mm	20	Plain	—	—	—	—	—	32 mm	2	Standard	3709N64	60.72	
25 mm	5 mm	22	Plain	—	—	—	—	—	35.3 mm	2	Standard	3709N65	64.00	
25 mm	5 mm	24	Plain	—	—	—	—	—	38.4 mm	2	Standard	3709N66	66.20	
25 mm	5 mm	25	Plain	—	—	—	—	—	40 mm	2	Standard	3709N67	68.77	
25 mm	5 mm	26	Plain	—	—	—	—	—	41.6 mm	2	Standard	3709N68	70.22	
25 mm	5 mm	27	Plain	8 mm	—	—	—	—	43.2 mm	2	Standard	3709N69	71.32	
25 mm	5 mm	30	Plain	8 mm	—	—	—	—	48 mm	2	Standard	3709N72	72.78	
25 mm	5 mm	32	Plain	8 mm	—	—	—	—	51.1 mm	2	Standard	3709N73	79.00	
25 mm	5 mm	40	Plain	8 mm	—	—	—	—	63.9 mm	2	Standard	3709N75	91.07	
25 mm	5 mm	48	Plain	8 mm	—	—	—	—	76.6 mm	—	Standard	3709N78	103.15	
For T10 Trade Size														
Corrosion-Resistant Aluminum														
16 mm	10 mm	12	Plain	—	—	—	—	—	38.4 mm	2	Standard	3568N11	37.67	
16 mm	10 mm	14	Plain	—	—	—	—	—	44.7 mm	2	Standard	3568N12	42.43	
25 mm	10 mm	12	Plain	—	—	—	—	—	38.4 mm	2	Standard	3568N33	40.97	
25 mm	10 mm	15	Plain	—	—	—	—	—	47.9 mm	2	Standard	3568N35	50.49	
25 mm	10 mm	18	Plain	—	—	—	—	—	57.5 mm	2	Standard	3568N37	63.27	
25 mm	10 mm	19	Plain	—	—	—	—	—	60.6 mm	2	Standard	3568N38	64.00	
25 mm	10 mm	20	Plain	—	—	—	—	—	63.8 mm	2	Standard	3568N39	67.30	
25 mm	10 mm	22	Plain	—	—	—	—	—	70.2 mm	2	Standard	3568N41	79.00	
25 mm	10 mm	24	Plain	—	—	—	—	—	76.6 mm	2	Standard	3568N42	86.32	
25 mm	10 mm	28	Plain	—	—	—	—	—	89.3 mm	2	Standard	3568N46	99.12	
25 mm	10 mm	30	Plain	—	—	—	—	—	96.7 mm	2	Standard	3568N47	103.87	
25 mm	10 mm	36	Plain	—	—	—	—	—	114.8 mm	2	Standard	3568N49	141.18	
50 mm	10 mm	18	Plain	—	—	—	—	—	57.5 mm	2	Standard	3568N73	86.32	
50 mm	10 mm	19	Plain	—	—	—	—	—	60.7 mm	2	Standard	3568N74	97.30	
50 mm	10 mm	24	Plain	—	—	—	—	—	76.6 mm	2	Standard	3568N77	109.37	
50 mm	10 mm	26	Plain	—	—	—	—	—	82.9 mm	2	Standard	3568N79	132.40	
50 mm	10 mm	30	Plain	—	—	—	—	—	95.7 mm	2	Standard	3568N83	155.82	
50 mm	10 mm	32	Plain	—	—	—	—	—	102 mm	2	Standard	3568N84	187.63	
50 mm	10 mm	36	Plain	—	—	—	—	—	114.8 mm	2	Standard	3568N85	203.35	
50 mm	10 mm	48	Plain	—	—	—	—	—	153 mm	—	Standard	3568N88	309.43	
For AT10 Trade Size														
Corrosion-Resistant Aluminum														
16 mm	10 mm	18	Plain	10 mm	—	—	—	—	57.3 mm	2	Standard	3709N801	44.11	
16 mm	10 mm	20	Plain	12 mm	—	—	—	—	63.7 mm	2	Standard	3709N802	52.89	
16 mm	10 mm	22	Plain	12 mm	—	—	—	—	70 mm	2	Standard	3709N803	56.40	
16 mm	10 mm	24	Plain	12 mm	—	—	—	—	76.4 mm	2	Standard	3709N804	57.49	
16 mm	10 mm	25	Plain	12 mm	—	—	—	—	79.6 mm	2	Standard	3709N805	58.04	
16 mm	10 mm	27	Plain	12 mm	—	—	—	—	86 mm	2	Standard	3709N806	59.33	
16 mm	10 mm	30	Plain	12 mm	—	—	—	—	95.5 mm	2	Standard	3709N807	67.29	
16 mm	10 mm	32	Plain	12 mm	—	—	—	—	101.9 mm	2	Standard	3709N808	86.85	

For Max. Belt Wd.	Pitch	No. of Teeth	Bore Type	For Shaft Dia.	For Bushing		Keyway		Pitch Dia.	No. of Flanges	Hub Type		Each
					Type	Trade No.	Wd.	Dp.					
16 mm	10 mm	36	Plain	16 mm	—	—	—	—	114.6 mm	2	Standard	3709N809	89.87
16 mm	10 mm	40	Plain	16 mm	—	—	—	—	127.3 mm	2	Standard	3709N811	106.96
16 mm	10 mm	44	Plain	16 mm	—	—	—	—	140.1 mm	2	Standard	3709N812	118.22
16 mm	10 mm	48	Plain	16 mm	—	—	—	—	152.8 mm	—	Standard	3709N813	130.56
16 mm	10 mm	60	Plain	16 mm	—	—	—	—	191 mm	—	Standard	3709N814	169.27
25 mm	10 mm	18	Plain	10 mm	—	—	—	—	57.3 mm	2	Standard	1326N51	50.79
25 mm	10 mm	20	Plain	12 mm	—	—	—	—	63.7 mm	2	Standard	1326N52	56.81
25 mm	10 mm	22	Plain	12 mm	—	—	—	—	70 mm	2	Standard	1326N53	59.74
25 mm	10 mm	24	Plain	12 mm	—	—	—	—	76.4 mm	2	Standard	1326N54	64.61
25 mm	10 mm	25	Plain	12 mm	—	—	—	—	79.6 mm	2	Standard	1326N55	68.00
25 mm	10 mm	27	Plain	12 mm	—	—	—	—	86 mm	2	Standard	1326N56	75.10
25 mm	10 mm	30	Plain	12 mm	—	—	—	—	95.5 mm	2	Standard	1326N57	83.87
25 mm	10 mm	32	Plain	12 mm	—	—	—	—	101.9 mm	2	Standard	1326N58	97.10
25 mm	10 mm	36	Plain	16 mm	—	—	—	—	114.6 mm	2	Standard	1326N59	108.75
25 mm	10 mm	40	Plain	16 mm	—	—	—	—	127.3 mm	2	Standard	1326N61	135.71
25 mm	10 mm	44	Plain	16 mm	—	—	—	—	140.1 mm	2	Standard	1326N62	145.40
25 mm	10 mm	48	Plain	16 mm	—	—	—	—	152.8 mm	—	Standard	1326N63	163.68
25 mm	10 mm	60	Plain	16 mm	—	—	—	—	191 mm	—	Standard	1326N64	217.65
50 mm	10 mm	18	Plain	10 mm	—	—	—	—	57.3 mm	2	Standard	3709N815	80.05
50 mm	10 mm	20	Plain	12 mm	—	—	—	—	63.7 mm	2	Standard	3709N816	86.62
50 mm	10 mm	22	Plain	12 mm	—	—	—	—	70 mm	2	Standard	3709N817	97.11
50 mm	10 mm	24	Plain	12 mm	—	—	—	—	76.4 mm	2	Standard	3709N818	102.36
50 mm	10 mm	25	Plain	12 mm	—	—	—	—	79.6 mm	2	Standard	3709N819	106.29
50 mm	10 mm	27	Plain	12 mm	—	—	—	—	86 mm	2	Standard	3709N821	108.93
50 mm	10 mm	30	Plain	12 mm	—	—	—	—	95.5 mm	2	Standard	3709N822	129.93
50 mm	10 mm	32	Plain	12 mm	—	—	—	—	101.9 mm	2	Standard	3709N823	133.85
50 mm	10 mm	36	Plain	16 mm	—	—	—	—	114.6 mm	2	Standard	3709N824	165.35
50 mm	10 mm	40	Plain	16 mm	—	—	—	—	127.3 mm	2	Standard	3709N825	194.20
50 mm	10 mm	44	Plain	16 mm	—	—	—	—	140.1 mm	2	Standard	3709N826	202.09
50 mm	10 mm	48	Plain	16 mm	—	—	—	—	152.8 mm	—	Standard	3709N827	249.33
50 mm	10 mm	60	Plain	16 mm	—	—	—	—	191 mm	—	Standard	3709N828	341.18

Bushings

Quick-Disconnect
Bushing

Type	Bushing		For Shaft Dia.	Each
	Trade No.			
Quick Disconnect (QD)	JA	1/2"	6086K111	\$20.41
Quick Disconnect (QD)	JA	9/16"	6086K118	20.41
Quick Disconnect (QD)	JA	5/8"	6086K112	20.41
Quick Disconnect (QD)	JA	3/4"	6086K113	20.41
Quick Disconnect (QD)	JA	13/16"	6086K119	20.41
Quick Disconnect (QD)	JA	7/8"	6086K114	20.41
Quick Disconnect (QD)	JA	15/16"	6086K115	20.41
Quick Disconnect (QD)	JA	1"	6086K116	20.41
Quick Disconnect (QD)	JA	1 1/16"	6086K845	20.41
Quick Disconnect (QD)	JA	1 1/8"	6086K846	20.41
Quick Disconnect (QD)	JA	1 3/16"	6086K847	20.41
Quick Disconnect (QD)	JA	1 1/4"	6086K117	20.41
Quick Disconnect (QD)	SH	1/2"	6086K211	27.97
Quick Disconnect (QD)	SH	5/8"	6086K212	27.97
Quick Disconnect (QD)	SH	11/16"	6086K226	27.97
Quick Disconnect (QD)	SH	3/4"	6086K213	27.97
Quick Disconnect (QD)	SH	7/8"	6086K214	27.97
Quick Disconnect (QD)	SH	15/16"	6086K215	27.97
Quick Disconnect (QD)	SH	1"	6086K216	27.97
Quick Disconnect (QD)	SH	1 1/16"	6086K217	27.97
Quick Disconnect (QD)	SH	1 1/8"	6086K218	27.97
Quick Disconnect (QD)	SH	1 3/16"	6086K219	27.97
Quick Disconnect (QD)	SH	1 1/4"	6086K221	27.97
Quick Disconnect (QD)	SH	1 5/16"	6086K848	27.97
Quick Disconnect (QD)	SH	1 3/8"	6086K222	27.97
Quick Disconnect (QD)	SH	1 7/16"	6086K849	27.97
Quick Disconnect (QD)	SH	1 1/2"	6086K223	27.97
Quick Disconnect (QD)	SH	1 5/8"	6086K224	27.97
Quick Disconnect (QD)	SH	1 11/16"	6086K225	27.97
Quick Disconnect (QD)	SH	22 mm	2344K71	37.24
Quick Disconnect (QD)	SH	24 mm	2344K11	32.46
Quick Disconnect (QD)	SH	25 mm	2344K12	32.47
Quick Disconnect (QD)	SH	28 mm	2344K13	32.47

Bushing		Trade	For Shaft	
Type	No.	Dia.		Each
Quick Disconnect (QD)	SH	30 mm	2344K14	32.46
Quick Disconnect (QD)	SH	32 mm	2344K15	32.46
Quick Disconnect (QD)	SH	35 mm	2344K16	32.46
Quick Disconnect (QD)	SDS	1/2"	6086K311	32.49
Quick Disconnect (QD)	SDS	9/16"	6086K131	32.49
Quick Disconnect (QD)	SDS	5/8"	6086K312	32.49
Quick Disconnect (QD)	SDS	3/4"	6086K313	32.49
Quick Disconnect (QD)	SDS	7/8"	6086K314	32.49
Quick Disconnect (QD)	SDS	15/16"	6086K315	32.49
Quick Disconnect (QD)	SDS	1"	6086K316	32.49
Quick Disconnect (QD)	SDS	1 1/16"	6086K317	32.49
Quick Disconnect (QD)	SDS	1 1/8"	6086K318	32.49
Quick Disconnect (QD)	SDS	1 3/16"	6086K319	32.49
Quick Disconnect (QD)	SDS	1 1/4"	6086K321	32.49
Quick Disconnect (QD)	SDS	1 5/16"	6086K851	32.49
Quick Disconnect (QD)	SDS	1 3/8"	6086K322	32.49
Quick Disconnect (QD)	SDS	1 7/16"	6086K323	32.49
Quick Disconnect (QD)	SDS	1 1/2"	6086K324	32.49
Quick Disconnect (QD)	SDS	1 9/16"	6086K132	32.49
Quick Disconnect (QD)	SDS	1 5/8"	6086K325	32.49
Quick Disconnect (QD)	SDS	1 11/16"	6086K852	32.49
Quick Disconnect (QD)	SDS	1 3/4"	6086K326	32.49
Quick Disconnect (QD)	SDS	1 7/8"	6086K853	32.49
Quick Disconnect (QD)	SDS	1 15/16"	6086K854	32.49
Quick Disconnect (QD)	SDS	2"	6086K327	32.49
Quick Disconnect (QD)	SDS	24 mm	2344K21	37.74
Quick Disconnect (QD)	SDS	25 mm	2344K22	37.74
Quick Disconnect (QD)	SDS	28 mm	2344K23	37.74
Quick Disconnect (QD)	SDS	30 mm	2344K24	37.74
Quick Disconnect (QD)	SDS	32 mm	2344K25	37.74
Quick Disconnect (QD)	SDS	35 mm	2344K26	37.74
Quick Disconnect (QD)	SDS	38 mm	2344K27	37.74
Quick Disconnect (QD)	SDS	40 mm	2344K28	37.74
Quick Disconnect (QD)	SDS	42 mm	2344K29	37.74
Quick Disconnect (QD)	SD	1/2"	6086K411	39.00
Quick Disconnect (QD)	SD	5/8"	6086K412	39.00
Quick Disconnect (QD)	SD	3/4"	6086K413	39.00
Quick Disconnect (QD)	SD	7/8"	6086K414	39.00
Quick Disconnect (QD)	SD	15/16"	6086K415	39.00
Quick Disconnect (QD)	SD	1"	6086K416	39.00
Quick Disconnect (QD)	SD	1 1/16"	6086K417	39.00
Quick Disconnect (QD)	SD	1 1/8"	6086K418	39.00
Quick Disconnect (QD)	SD	1 3/16"	6086K419	39.00
Quick Disconnect (QD)	SD	1 1/4"	6086K421	39.00
Quick Disconnect (QD)	SD	1 5/16"	6086K855	39.00
Quick Disconnect (QD)	SD	1 3/8"	6086K422	39.00
Quick Disconnect (QD)	SD	1 7/16"	6086K423	39.00
Quick Disconnect (QD)	SD	1 1/2"	6086K424	39.00
Quick Disconnect (QD)	SD	1 5/8"	6086K425	39.00
Quick Disconnect (QD)	SD	1 11/16"	6086K856	39.00
Quick Disconnect (QD)	SD	1 3/4"	6086K426	39.00
Quick Disconnect (QD)	SD	1 7/8"	6086K857	39.00
Quick Disconnect (QD)	SD	1 15/16"	6086K429	39.00
Quick Disconnect (QD)	SD	2"	6086K427	39.00
Quick Disconnect (QD)	SD	24 mm	2344K31	45.37
Quick Disconnect (QD)	SD	25 mm	2344K32	45.37
Quick Disconnect (QD)	SD	28 mm	2344K33	45.37
Quick Disconnect (QD)	SD	30 mm	2344K34	45.37
Quick Disconnect (QD)	SD	32 mm	2344K35	45.37
Quick Disconnect (QD)	SD	35 mm	2344K36	45.37
Quick Disconnect (QD)	SD	38 mm	2344K37	45.37
Quick Disconnect (QD)	SD	40 mm	2344K38	45.37
Quick Disconnect (QD)	SD	42 mm	2344K39	45.37
Quick Disconnect (QD)	SK	1/2"	6086K511	50.33
Quick Disconnect (QD)	SK	5/8"	6086K512	50.33
Quick Disconnect (QD)	SK	3/4"	6086K513	50.33
Quick Disconnect (QD)	SK	7/8"	6086K514	50.33
Quick Disconnect (QD)	SK	15/16"	6086K515	50.33
Quick Disconnect (QD)	SK	1"	6086K516	50.33
Quick Disconnect (QD)	SK	1 1/16"	6086K517	50.33
Quick Disconnect (QD)	SK	1 1/8"	6086K518	50.33
Quick Disconnect (QD)	SK	1 3/16"	6086K519	50.33
Quick Disconnect (QD)	SK	1 1/4"	6086K521	50.33

Bushing		Trade	For Shaft	
Type	No.	Dia.		Each
Quick Disconnect (QD)	SK	1 5/16"	6086K533	50.33
Quick Disconnect (QD)	SK	1 3/8"	6086K522	50.33
Quick Disconnect (QD)	SK	1 7/16"	6086K523	50.33
Quick Disconnect (QD)	SK	1 1/2"	6086K524	50.33
Quick Disconnect (QD)	SK	1 9/16"	6086K536	50.33
Quick Disconnect (QD)	SK	1 5/8"	6086K525	50.33
Quick Disconnect (QD)	SK	1 11/16"	6086K526	50.33
Quick Disconnect (QD)	SK	1 3/4"	6086K527	50.33
Quick Disconnect (QD)	SK	1 7/8"	6086K528	50.33
Quick Disconnect (QD)	SK	1 15/16"	6086K529	50.33
Quick Disconnect (QD)	SK	2"	6086K531	50.33
Quick Disconnect (QD)	SK	2 1/8"	6086K532	50.33
Quick Disconnect (QD)	SK	2 3/16"	6086K858	50.33
Quick Disconnect (QD)	SK	2 1/4"	6086K859	50.33
Quick Disconnect (QD)	SK	2 3/8"	6086K861	50.33
Quick Disconnect (QD)	SK	2 7/16"	6086K862	50.33
Quick Disconnect (QD)	SK	2 1/2"	6086K534	50.33
Quick Disconnect (QD)	SK	2 5/8"	6086K535	50.33
Quick Disconnect (QD)	SK	24 mm	2344K41	58.49
Quick Disconnect (QD)	SK	25 mm	2344K42	58.49
Quick Disconnect (QD)	SK	28 mm	2344K43	58.49
Quick Disconnect (QD)	SK	30 mm	2344K44	58.49
Quick Disconnect (QD)	SK	32 mm	2344K45	58.49
Quick Disconnect (QD)	SK	35 mm	2344K46	58.49
Quick Disconnect (QD)	SK	38 mm	2344K47	58.49
Quick Disconnect (QD)	SK	40 mm	2344K48	58.49
Quick Disconnect (QD)	SK	42 mm	2344K72	66.96
Quick Disconnect (QD)	SK	48 mm	2344K49	58.49
Quick Disconnect (QD)	SK	50 mm	2344K51	58.49
Quick Disconnect (QD)	SK	55 mm	2344K52	58.49
Quick Disconnect (QD)	SF	1/2"	6086K614	61.86
Quick Disconnect (QD)	SF	5/8"	6086K615	61.86
Quick Disconnect (QD)	SF	3/4"	6086K616	61.86
Quick Disconnect (QD)	SF	7/8"	6086K617	61.86
Quick Disconnect (QD)	SF	1"	6086K619	61.86
Quick Disconnect (QD)	SF	1 1/8"	6086K622	61.86
Quick Disconnect (QD)	SF	1 3/16"	6086K623	61.86
Quick Disconnect (QD)	SF	1 1/4"	6086K624	61.86
Quick Disconnect (QD)	SF	1 3/8"	6086K625	61.86
Quick Disconnect (QD)	SF	1 7/16"	6086K626	61.86
Quick Disconnect (QD)	SF	1 1/2"	6086K627	61.86
Quick Disconnect (QD)	SF	1 5/8"	6086K628	61.86
Quick Disconnect (QD)	SF	1 11/16"	6086K629	61.86
Quick Disconnect (QD)	SF	1 3/4"	6086K631	61.86
Quick Disconnect (QD)	SF	1 7/8"	6086K632	61.86
Quick Disconnect (QD)	SF	1 15/16"	6086K633	61.86
Quick Disconnect (QD)	SF	2"	6086K634	61.86
Quick Disconnect (QD)	SF	2 1/8"	6086K635	61.86
Quick Disconnect (QD)	SF	2 3/16"	6086K636	61.86
Quick Disconnect (QD)	SF	2 1/4"	6086K637	61.86
Quick Disconnect (QD)	SF	2 3/8"	6086K864	61.86
Quick Disconnect (QD)	SF	2 7/16"	6086K865	61.86
Quick Disconnect (QD)	SF	2 1/2"	6086K638	61.86
Quick Disconnect (QD)	SF	2 5/8"	6086K866	61.86
Quick Disconnect (QD)	SF	2 3/4"	6086K867	61.86
Quick Disconnect (QD)	SF	2 15/16"	6086K639	61.86
Quick Disconnect (QD)	SF	30 mm	2344K75	82.41
Quick Disconnect (QD)	SF	35 mm	2344K62	75.44
Quick Disconnect (QD)	SF	40 mm	2344K64	75.44
Quick Disconnect (QD)	SF	50 mm	2344K67	75.44
Quick Disconnect (QD)	SF	55 mm	2344K68	75.44
Quick Disconnect (QD)	SF	60 mm	2344K69	75.44
Quick Disconnect (QD)	E	35 mm	2344K82	153.98
Quick Disconnect (QD)	E	65 mm	2344K92	153.98
Quick Disconnect (QD)	E	75 mm	2344K94	153.98

