# Software Requirements Specification for Crazy 1-0s Game

Team #25, The Crazy Four

Ruida Chen
Ammar Sharbat
Alvin Qian
Jiaming Li

30.09.2025

# Contents


**1 Purpose of the Project** **vii**
- 1.1 User Business . . . vii
- 1.2 Goals of the Project . . . vii
  - 1.2.1 MVP Functional Goals . . . vii
  - 1.2.2 MVP Non-functional Goals . . . viii
  - 1.2.3 Stretch Goals . . . viii

**2 Stakeholders** **ix**
- 2.1 Client . . . ix
- 2.2 Customer . . . ix
- 2.3 Other Stakeholders . . . ix
- 2.4 Hands-On Users of the Product . . . x
- 2.5 Personas . . . xii
  - 2.5.1 Educators / Instructors . . . xii
  - 2.5.2 Students / Casual Learners . . . xiii
  - 2.5.3 Gamers / General Public . . . xiv
- 2.6 Priorities Assigned to Users . . . xiv
- 2.7 User Participation . . . xv
- 2.8 Maintenance Users and Service Technicians . . . xvi

**3 3. Mandated Constraints** **xvii**
- 3.1 3a. Solution Constraints . . . xvii
- 3.2 3b. Implementation Environment of the Current System . . . xvii
- 3.3 3c. Partner or Collaborative Applications . . . xviii
- 3.4 3d. Off-the-Shelf Software . . . xviii
- 3.5 3e. Anticipated Workplace Environment . . . xviii
- 3.6 3f. Schedule Constraints . . . xviii
- 3.7 3g. Budget Constraints . . . xix
- 3.8 3h. Enterprise Constraints . . . xix

**4 Naming Conventions and Terminology** **xix**
- 4.1 Glossary of All Terms, Including Acronyms, Used by Stakeholders involved in the Project . . . xix

**5 Relevant Facts and Assumptions** **xxi**
5.1 Relevant Facts . . . xxi
5.2 Business Rules . . . xxi
5.3 Assumptions . . . xxii

**6 The Scope of the Work** **xxii**
6.1 The Current Situation . . . xxii
6.2 The Context of the Work . . . xxii
6.3 Work Partitioning . . . xxiii
6.4 Specifying a Business Use Case (BUC) . . . xxiv

**7 Business Data Model and Data Dictionary** **xxv**
7.1 Business Data Model . . . xxv
7.2 Data Dictionary . . . xxvi

**8 The Scope of the Product** **xxvii**
8.1 Product Boundary . . . xxvii
8.2 Product Use Case Table . . . xxviii
8.3 Individual Product Use Cases (PUCs) . . . xxviii

**9 Functional Requirements** **xxxi**
9.1 Game Manager . . . xxxi
9.2 Score Manager . . . xxxii
9.3 Education Support . . . xxxiii
9.4 Login Manager . . . xxxiii
9.5 Data Manager . . . xxxiv

**10 Look and Feel Requirements** **xxxiv**
10.1 Appearance Requirements . . . xxxiv
10.2 Style Requirements . . . xxxv

**11 Usability and Humanity Requirements** **xxxv**
11.1 Ease of Use Requirements . . . xxxv
11.2 Personalization and Internationalization Requirements . . . xxxvi
11.3 Learning Requirements . . . xxxvi
11.4 Understandability and Politeness Requirements . . . xxxvi
11.5 Accessibility Requirements . . . xxxvi

**12 Performance Requirements** **xxxvi**
12.1 Speed and Latency Requirements . . . xxxvi
12.2 Safety-Critical Requirements . . . xxxvii
12.3 Precision or Accuracy Requirements . . . xxxvii
12.4 Robustness or Fault-Tolerance Requirements . . . xxxvii
12.5 Capacity Requirements . . . xxxvii
12.6 Scalability or Extensibility Requirements . . . xxxvii
12.7 Longevity Requirements . . . xxxvii

**13 Operational and Environmental Requirements** **xxxviii**
13.1 Expected Physical Environment . . . xxxviii
13.2 Requirements for Interfacing with Adjacent Systems . . . xxxviii
13.3 Productization Requirements . . . xxxviii
13.4 Release Requirements . . . xxxix

**14 Maintainability and Support Requirements** **xxxix**
14.1 Maintenance Requirements . . . xxxix
14.2 Supportability Requirements . . . xxxix
14.3 Adaptability Requirements . . . xl

**15 Security Requirements** **xl**
15.1 Access Requirements . . . xl
15.2 Integrity Requirements . . . xl
15.3 Privacy Requirements . . . xli
15.4 Audit Requirements . . . xli
15.5 Immunity Requirements . . . xli

**16 Cultural Requirements** **xli**
16.1 Cultural Requirements . . . xli

**17 Compliance Requirements** **xlii**
17.1 Legal Requirements . . . xlii
17.2 Standards Compliance Requirements . . . xlii

**18 Off-the-Shelf Solutions** **xliii**
18.1 Ready-Made Products . . . xliii
18.2 Reusable Components . . . xliii
18.3 Products That Can Be Copied . . . xliii

**19 New Problems** **xliii**
19.1 Effects on the Current Environment . . . xliii
19.2 Effects on the Installed Systems . . . xliii
19.3 Potential User Problems . . . xliv
19.4 Limitations in the Anticipated Implementation Environment That May Inhibit the New Product . . . xliv
19.5 Follow-Up Problems . . . xliv

**20 Tasks** **xliv**
20.1 Project Planning . . . xliv
20.2 Planning of the Development Phases . . . xliv

**21 Migration to the New Product** **xlv**

**22 Costs** **xlv**
22.1 Assumptions . . . xlv
22.2 One-time Costs . . . xlv
22.3 Recurring Costs . . . xlv
22.4 Total and Headroom . . . xlvi
22.5 Cost Control Plan . . . xlvi

**23 User Documentation and Training** **xlvi**
23.1 User Documentation Requirements . . . xlvi
23.2 Training Requirements . . . xlvi

**24 Waiting Room (Stretch Requirements)** **xlvii**
24.1 Purpose and scope . . . xlvii
24.2 Functional Stretch Requirements . . . xlvii
24.3 UI / Look-and-Feel Stretch Requirements (mapped to Section 10) . . . xlviii
24.4 Education / Learning Stretch Requirements (mapped to Section 11) . . . xlix
24.5 Internationalization and Language Stretch Requirements (mapped to Section 11.2) . . . l
24.6 Performance / Capacity Stretch Requirements (mapped to Section 12) . . . l
24.7 Integration / Deck Production Stretch Requirements . . . l
24.8 Urgency Ranking . . . li

24.9 Crazy10s v1.1 (Rank 1) — Priority stretch items . . . . . li
24.10 Crazy10s v1.2 (Rank 2) — Lower priority stretch items . . . . li

**25 Ideas for Solution** **li**
25.1 Architecture Overview . . . . . li
25.2 Implementation Options . . . . . lii
25.3 Recommended Path . . . . . lii
25.4 Key Non-functional Techniques . . . . . lii

# Revision History

Table 1: Revision History

| Date | Developer(s) | Change |
|---|---|---|
| 9.29 | Jiaming Li | 1 - Purpose of the Project |
| 9.30 | Ruida Chen | Section 3, 10 ,11, 12 |
| 9.30 | Jiaming Li | 8 - Scope of the Product |
| 9.30 | Jiaming Li | 9 - Functional Requirements |
| 9.30 | Alvin Qian | Section 4,6,7 |
| 10.1 | Alvin Qian | Section 14,16 |
| 10.9 | Ruida Chen | Section 20,21,22 |
| 10.9 | Jiaming Li | Section 17,18,19 |
| 10.9 | Alvin Qian | Appendix and Reflection |
| 10.12 | Ammar Sharbat | Section 1.1, 2, 5, 13, 15, 18 |
| 10.13 | Ammar Sharbat | Section 18, 19, 25 |
| 04.06 | Ammar Sharbat | Section 1, 11, Removed Section 18 |
| 04.07 | Ammar Sharbat | Section 2 |

# 1 Purpose of the Project

## 1.1 User Business

The purpose is to create an educational, game-based experience that introduces alternate number systems, especially dozenal, to learners who are currently more familiar with decimal arithmetic. The product will demonstrate the advantages of dozenal by embedding base-12 scoring and notation into a familiar card game structure, making abstract concepts concrete through gameplay.

We aim to accomplish the aforementioned by designing and implementing an educational card game based on the traditional *Crazy Eights* rule set, but with the following differences and additions:

- Switching the wild card from "8" to "10" to highlight that the game uses alternate numeric notation: "10" in base-12 represents twelve in decimal, not ten.
- Incorporating counting into the game so players learn base conversion and divisibility in context.
- Integrating the **Dozenal (base-12)** number system into scoring, display, and feedback.
- Using a special **Dozenal (base-12)** deck of cards (with 4 standard suits, ranks 0–9, ↊, ↋, 10 and face cards J, Q, K, C).

## 1.2 Goals of the Project

The Minimum Viable Product (MVP) introduces dozenal (base-12) concepts through an engaging Crazy Eights card game, while laying the foundation for future educational expansions.

### 1.2.1 MVP Functional Goals

- **Two-Player Core Loop:** Support a one-versus-one match with turn-taking, drawing, discarding, and win checks. Includes starter card, discard pile, and reshuffling the stock pile.

**Rationale:** Two players are the smallest playable unit; finishing this proves the core loop.

- **Classic Rules Engine:** Implement standard Crazy Eights: match by suit or rank; an "8" is wild and lets the player declare a suit; draw if no valid move exists.
  **Rationale:** Correct classic rules establish a solid baseline before adding variations.

- **Dozenal (Base-12) Scoring/Display:** Display scores, counters, or thresholds in base-12 notation while keeping classic rules unchanged.
  **Rationale:** Introduces dozenal in a simple, non-disruptive way that highlights novelty while retaining accessibility.

### 1.2.2 MVP Non-functional Goals

- **Move Validation and Feedback:** Provide immediate invalid-move feedback, clear suit selection UI after playing an "8," and real-time state indicators.
  **Rationale:** Reduces errors and learning curve; improves usability.

- **Testability and Determinism:** Support seeded shuffling and provide basic logs or replays for each session.
  **Rationale:** Enables reproducible unit/integration testing and debugging.

- **Stability and Performance:** Ensure responsive UI $< 200\,ms$, no crashes, no deadlocks, and correct reshuffling.
  **Rationale:** Reliability is the baseline for acceptance and live demonstration.

- **Minimal UI:** Provide a desktop or web interface showing hand, discard pile, current state, and a dozenal score tracker.
  **Rationale:** Covers essential interactions while limiting complexity at the MVP stage.

### 1.2.3 Stretch Goals

Stretch goals include extending the game to support more players, online multiplayer, AI opponents, advanced dozenal variants, and enhanced usability

features such as tutorials and cross-platform deployment. These are detailed in the Waiting Room section.

# 2 Stakeholders

## 2.1 Client

- **Professor Paul Rapoport, Mathematician** - paul.rapoport@mcmaster.ca. As a professor at McMaster University, he is responsible for the general direction, design decisions of the project, and concept mentorship.
- **Dr. Spencer Smith, Engineering Professor** - spencer.smith@mcmaster.ca. As a professor at McMaster University, he is responsible for project progress, deliverables, and development mentorship.

## 2.2 Customer

- **Mathematicians:** Responsible for conceptual design decisions, ensuring the game's mathematical accuracy and educational value.
- **Educators:** Responsible for teaching aspects of the game and gameplay, including how it integrates into curricula and learning outcomes.
- **Students:** Responsible for the UI/web-game design and gameplay feedback, focusing on usability and engagement for their age group.

## 2.3 Other Stakeholders

- **Other Scientists:** Provide expert input on alternative number systems and their applications, relating to use cases involving educational deployments and conceptual validation.
- **Parents and Children:** Offer feedback on family-friendly aspects, influencing deployments in home settings and casual learning scenarios.
- **Gamers:** Contribute to gameplay balance and fun factor, impacting use cases for recreational play and competitive modes.

- **Game Developers:** Advise on technical implementation and best practices, supporting deployments across different platforms and integrations.

- **General Public:** Represent broader societal interest, affecting use cases for public education and awareness campaigns.

## 2.4 Hands-On Users of the Product

- **User name/category:** Students (ages 10-30).
  **User role:** Players who engage with the game for fun and learning.
  **Subject matter experience:** Novice - little to no prior knowledge of dozenal or alternative bases.
  **Technological experience:** Novice - basic computer skills, comfortable with web browsers.
  **Other user characteristics:** Ages 10-30, motivated by curiosity; may need simple tutorials; prefer visual and interactive elements.

- **User name/category:** Educators (teachers or instructors).
  **User role:** Facilitators who use the game in classroom settings.
  **Subject matter experience:** Journeyman - familiar with math education but may not know dozenal deeply.
  **Technological experience:** Journeyman - regular use of educational software and online tools.
  **Other user characteristics:** Ages 25-55, focused on pedagogical value; need exportable results and session management; value ease of setup.

- **User name/category:** Gamers.
  **User role:** Players who enjoy strategic card games and challenges.
  **Subject matter experience:** Journeyman - interested in learning new concepts through play.
  **Technological experience:** Master - experienced with online games and interfaces.
  **Other user characteristics:** Ages 5-40, competitive; appreciate fair rules and replay features; tolerant of brief learning curves.

- **User name/category:** Capstone Evaluators (professors or experts).
  **User role:** Assessors who evaluate the project's technical and educa-

tional merits.
**Subject matter experience:** Master - deep expertise in software engineering and math education.
**Technological experience:** Master - proficient in various development tools and platforms.
**Other user characteristics:** Ages 30-60, analytical; focus on correctness, stability, and scalability; provide detailed feedback.

- **User name/category:** Parents.
  **User role:** Supervisors who introduce the game to children at home.
  **Subject matter experience:** Novice to journeyman - basic math knowledge, supportive of learning.
  **Technological experience:** Journeyman - regular internet users, comfortable with family apps.
  **Other user characteristics:** Ages 25-50, concerned with safety and appropriateness; prefer guided experiences for kids.

- **User name/category:** Children (young learners).
  **User role:** Young players exploring math through games.
  **Subject matter experience:** Novice - early math exposure, curious about numbers.
  **Technological experience:** Novice - learning to use devices, enjoy interactive content.
  **Other user characteristics:** Ages 8-14, playful; need simple, colorful interfaces; short attention spans.

## 2.5 Personas

### 2.5.1 Educators / Instructors

**Elena Ramirez, 42-year-old High School Math Teacher:** Elena is a dedicated educator at a local high school, passionate about making math engaging for her students. She discovered dozenal through a professional development workshop and sees it as a way to challenge traditional teaching methods. In her daily life, she spends hours planning lessons, grading papers, and attending parent-teacher meetings. Elena uses educational apps to supplement her classroom activities and is always looking for innovative tools to spark student interest. She dreams of inspiring the next generation of mathematicians and enjoys hiking and reading science fiction in her free time. For this project, Elena would provide feedback on how the game fits into curricula and helps students grasp alternative number systems.

### 2.5.2 Students / Casual Learners

**Alex Chen, 16-year-old High School Student:** Alex is a curious teenager who loves puzzles and games but finds traditional math classes boring. He stumbled upon dozenal while browsing online and became fascinated by how it could simplify fractions. As a student, Alex juggles schoolwork, extracurricular activities like the chess club, and hanging out with friends. He spends a lot of time on his phone playing mobile games and watching educational YouTube videos. Alex is tech-savvy, preferring intuitive apps over complicated software. He hopes to pursue engineering in college and sees learning dozenal as a fun way to build his problem-solving skills. For this project, Alex would test the game's usability and suggest improvements to make it more engaging for peers his age.

### 2.5.3 Gamers / General Public

**Mike Torres, 28-year-old Software Developer and Casual Gamer:** Mike works as a software developer by day, coding and debugging applications, but unwinds by playing card games and strategy titles online. He came across dozenal in a forum discussion about efficient number systems and thought it could make for an interesting game mechanic. In his life, Mike balances work deadlines, gym sessions, and gaming nights with friends. He's active in online gaming communities, sharing tips and reviewing new releases. Mike values fair gameplay and innovative features that add depth without complexity. He enjoys learning new concepts through entertainment and often researches game design. For this project, Mike would evaluate the game's balance, provide technical feedback, and suggest ways to appeal to the broader gaming audience.

## 2.6 Priorities Assigned to Users

- **Key users:**
  - Educators - they are the primary facilitators of the educational aspect and will integrate the game into learning environments.
  - Students - they are the main audience for the educational content and will provide critical feedback on usability and engagement.

- **Secondary users:**
  - Capstone evaluators - they provide expert feedback on conceptual validity and educational value, influencing design decisions and future enhancements.
  - Parents and children - they represent the family audience and provide insights on accessibility and appeal for younger users, impacting use cases for home learning and casual play.
  - Mathematicians and Scientists - they contribute to the broader scientific context and potential applications of dozenal, influencing use cases for public education and awareness.
  - Gamers - they offer feedback on gameplay mechanics and balance, affecting use cases for recreational play and competitive modes.

  These users are secondary as they provide valuable feedback during testing and demos, helping refine the product, but they are not the core audience for daily use.

- **Unimportant users:**
  - Educational Institutions - while they influence many of the other stakeholders, they are not directly involved in the design or feedback process.
  - Game Developers - they may provide technical advice but are not the end users or primary evaluators of the educational content.
  - General public / Anonymous spectators - they may have general interest but do not actively participate in the design or feedback process.

  These users are considered unimportant in terms of priority because, while they contribute to broader impact and family engagement, they have less direct involvement in the core functionality and decision-making processes.

## 2.7 User Participation

- **Educators:** Estimated 2-4 hours over the term for reviewing tutorial content and alignment with learning objectives; provide knowledge on pedagogical effectiveness and curriculum integration.

- **Students:** Estimated 3-5 sessions of 20-30 minutes for playtesting; provide knowledge on usability, engagement, and age-appropriate design.
- **Demonstration evaluators** Estimated 2-3 hours per month for feedback sessions; provide feedback on overall project / game progess and design and development.
- **Mathematicians Scientists:** Estimated 1-2 hours for content review; provide knowledge on mathematical accuracy and conceptual depth.
- **Parents and children:** Estimated 30 minutes - 1 hour for family testing; provide knowledge on accessibility and family-friendly features.
- **Gamers:** Estimated 10-20 minute sessions for gameplay testing; provide knowledge on game balance and competitive elements.
- **General Public and Anonymous spectators** Minimal participation; provide general impressions if surveyed.

## 2.8 Maintenance Users and Service Technicians

- **Computer Scientists:** Responsible for ongoing system maintenance, updates, and troubleshooting technical issues; they ensure the software remains functional and secure over time.
- **Game Developers:** Handle content updates, bug fixes, and feature enhancements; they maintain the game's integrity and adapt it to new platforms or user needs.

### Fit criterion

Stakeholder list and contact/role assignments exist in the project README and team Kanban; at least one named representative for each stakeholder category is recorded. Evidence: README / Team Roles section and meeting minutes indicating stakeholder reviews.

# 3 Mandated Constraints

## 3.1 Solution Constraints

**Description:** The system must be developed using a sound and scalable technology stack that supports web-based deployment. **Rationale:** Ensures the team gains proficiency in useful modern web development frameworks, aligning with the project's educational goals and contributing to long-term career growth. These technologies provide strong essential knowledge for building robust web applications. **Fit Criterion:** The frontend code is written in React (verified by package.json and component structure), and the backend is implemented in Node.js (verified by server files and runtime environment).

**Description:** All source code must be managed using version control, with frequent commits, issue tracking and project management. **Rationale:** Version control is essential for collaborative development, and maintaining a history of changes, which is critical for team coordination and project traceability. **Fit Criterion:** All code is stored in a GitHub repository, with commits made for each significant change and pull requests used for code reviews.

## 3.2 Implementation Environment of the Current System

**Server-hosting:** The backend must operate with a consistent server side connection. **Rationale:** A stable server environment is essential for hosting the game logic, managing user sessions, and ensuring real-time interactions between players. **Fit Criterion:** The application runs on Node.js LTS and connects to a relational database, as confirmed by deployment and testing in the specified environment.

**Data Management:** The system must sustain user data and game statistics. **Rationale:** Persistent data storage is essential for tracking user progress, game history, and providing a personalized experience. **Fit Criterion:** Using a relational database such as PostgreSQL or MySQL with defined schemas for users, games, and scores.

**Browser Compatibility:** The application must be deployable on modern web browsers (Chrome, Firefox, Edge). **Rationale:** Targeting modern browsers ensures broad accessibility and compatibility with standard web

technologies. **Fit Criterion:** The application loads and functions correctly in Chrome, Firefox, and Edge, verified through cross-browser testing.

## 3.3 Partner or Collaborative Applications

**Description:** The team must use GitHub for code collaboration and issue tracking. **Rationale:** GitHub facilitates distributed development and project management through its integrated tools. **Fit Criterion:** All team members use GitHub for code pushes, issue creation, and project tracking.

**Description:** Discord is required for real-time communication and coordination. **Rationale:** Discord provides efficient channels for quick updates, discussions, and meetings, supporting remote collaboration. **Fit Criterion:** Team communications occur via Discord channels, with records of key decisions logged.

## 3.4 Off-the-Shelf Software

**Description:** The system must rely primarily on open-source libraries. **Rationale:** Open-source libraries reduce costs and promote community-supported, reliable components. **Fit Criterion:** All third-party libraries used are open-source, as listed in package.json or equivalent dependency files.

**Description:** Proprietary software must not be required for end users to run the application. **Rationale:** Ensuring no proprietary dependencies allows free access and broad usability. **Fit Criterion:** The application runs without requiring any proprietary software installations, verified by user testing.

## 3.5 Anticipated Workplace Environment

**Description:** End users are expected to interact with the application primarily on web browsers. **Rationale:** Web-based deployment simplifies access and reduces platform-specific requirements. **Fit Criterion:** The application is fully functional within web browsers without additional software.

## 3.6 Schedule Constraints

**Description:** The project must be completed within the academic deadline. **Rationale:** Academic timelines ensure timely delivery and alignment with

course requirements. **Fit Criterion:** All deliverables are submitted by the specified deadlines, as per the project schedule.

**Description:** Progress reports and milestone check-ins with the TA are mandatory. **Rationale:** Regular check-ins provide oversight and feedback to maintain project quality. **Fit Criterion:** Check-ins occur as scheduled, with documented progress and TA approvals.

### 3.7 Budget Constraints

**Description:** Total financial budget is under 500 Canadian Dollars. **Rationale:** Limited budget enforces cost-effective development using free or low-cost tools. **Fit Criterion:** All project expenses remain under 500 CAD, tracked via receipts and logs.

**Description:** Open-source and free tools are primarily to be used. **Rationale:** Free tools minimize costs and promote sustainable development practices. **Fit Criterion:** All development tools and services are free or open-source, confirmed by usage logs.

### 3.8 Enterprise Constraints

**Description:** The project must comply with academic integrity and university policies. **Rationale:** Compliance ensures ethical development and avoids penalties. **Fit Criterion:** All work adheres to university policies, verified through self-assessment and TA review.

**Description:** Data collection and storage must follow privacy, security, and ethical guidelines. **Rationale:** Protecting user data builds trust and meets legal standards. **Fit Criterion:** Data handling complies with privacy laws (e.g., no unauthorized data collection), audited via code review.

## 4 Naming Conventions and Terminology

### 4.1 Glossary of All Terms, Including Acronyms, Used by Stakeholders involved in the Project

- **Base-10 (Decimal)**: The standard numerical system using ten digits (0–9), commonly used in arithmetic and everyday calculations.

- **Base-12 (Dozenal)**: A numerical system using twelve digits (0–9, ↊, ↋), where ↊ represents 10 and ↋ represents 11 in decimal. Has divisibility advantages (divisors: 2, 3, 4, 6).
- **Base-8 (Octal)**: A numerical system using eight digits (0–7). Each octal digit represents three binary digits (bits). Commonly used in computing and digital systems due to easy conversion with binary.
- **Base-16 (Hexadecimal)**: A numerical system using sixteen digits (0–9, A–F), where A through F represent decimal values 10 to 15. Widely used in programming and computer memory addressing for its compact binary representation.
- **Crazy Eights**: A classic card game where players match cards by suit or rank, with the "8" card acting as a wild card allowing the player to declare a new suit.
- **MVP**: Minimum Viable Product, the initial version of the Crazy Eights software with core functionality, including two-player gameplay, classic rules, and dozenal scoring.
- **Functional Goals**: Features and behaviors the software must implement, such as gameplay mechanics and dozenal score display.
- **Non-functional Goals**: Quality attributes of the software, such as usability, performance, and stability.
- **Stretch Goals**: Optional features or enhancements, such as multiplayer support or advanced dozenal rule variants, to be implemented if time permits.
- **GitHub**: The platform used for version control, issue tracking, and Kanban board management.
- **Discord**: The communication platform for team coordination, quick updates, and voice meetings.
- **Kanban Board**: A project management tool in GitHub Projects, divided into stages (Backlog, In Progress, Review, Done) to track tasks.
- **CI/CD**: Continuous Integration/Continuous Deployment, an automated process for testing and deploying code changes.

- **SRS**: Software Requirements Specification, this document outlining the requirements for the Crazy Eights project.
- **PoC**: Proof of Concept, a prototype demonstrating core gameplay mechanics to validate feasibility.
- **UI**: User Interface, the visual and interactive components of the software, such as the game board and score display.

# 5 Relevant Facts and Assumptions

## 5.1 Relevant Facts

- **Prevalence of decimal:** Users are overwhelmingly familiar with base-10; dozenal notation is novel for most.
- **Educational effectiveness:** Game-based learning improves numeracy engagement (backed by pedagogical literature).
- **Resource constraints:** Project budget is capped at 500 CAD and timeline is an academic term.
- **Technology stack:** Planned stack is React (frontend), Node.js (backend), PostgreSQL (data).
- **Browser target:** Modern desktop browsers (Chrome, Firefox, Edge) are the primary runtime environment.

## 5.2 Business Rules

- **Scoring rule:** Round score equals sum of opponents' remaining card values (displayed in both decimal and dozenal).
- **Account rule:** Registered usernames must be unique; guest mode creates impermanent sessions.
- **Open-source rule:** All deliverables must use appropriately licensed assets; avoid proprietary-only dependencies.

## 5.3 Assumptions

- **Connectivity:** Players typically have a stable internet connection for multiplayer sessions.
- **Device:** Primary devices are desktop/laptop; mobile support is a stretch-goal.
- **Play familiarity:** Players understand basic card game mechanics (matching suit or rank).
- **Team availability:** Team members will perform peer review before merges as per Development Plan.
- **Third-party components:** Standard open-source libraries (React, Socket.io, PG client) will be available and compatible.

# 6 The Scope of the Work

## 6.1 The Current Situation

No pre-existing educational card game exists that integrates Dozenal (Base-12) scoring and notation into gameplay to teach alternative number systems. Existing card games like Crazy Eights use decimal scoring, and educational tools for dozenal are limited to abstract calculators or texts, lacking interactive, gamified experiences that could engage learners and demonstrate practical advantages.

## 6.2 The Context of the Work

The work context focuses on the educational and recreational use of card games to teach alternative number systems. Adjacent systems include:

- Educational institutions (providing curriculum integration and student access). - Math communities and academics (supplying feedback on dozenal concepts). - Online desktop gaming platforms (providing gameplay data and engagement metrics). - Web browsers and devices (enabling access to the game).

Inputs: User login data, game start requests, move inputs. Outputs: Game states, scores in dozenal, educational feedback.

This context ensures the product fits into learning environments without disrupting existing workflows.

## 6.3 Work Partitioning

The work is partitioned into business events and their corresponding business use cases (BUCs):

- **BUC: Game Initiation** - Triggered by user request to start a game. Initialize Game Session. Outputs: Shuffled deck, dealt hands.
- **BUC: Player Move** - Triggered by player selecting a card. Process Move. Outputs: Updated game state, feedback.
- **BUC: Game End** - Triggered when a player empties their hand. Calculate and Display Score. Outputs: Final scores in dozenal.
- **BUC: Educational Query** - Triggered by user requesting dozenal explanations.
  Provide Learning Resources. Outputs: Tutorials or hints.

## 6.4 Specifying a Business Use Case (BUC)

**BUC: Play a Game of Crazy Eights with Dozenal Scoring**

- **Actors**: Two players, the software system.
- **Trigger**: A player creates a new game session using the UI.
- **Description**: Two players take turns matching cards by suit or rank, with the "10" card acting as a wild card that allows the player to declare a new suit. If no valid move can be made, the player draws from the stock pile. The game ends when one player discards all their cards, and the score is calculated and displayed in dozenal notation.
- **Preconditions**: The user is logged in. The software is running on a web interface, with a functional UI displaying the hand, discard pile, stock pile, and score tracker.

- **Postconditions**: The game concludes with a winner, points are displayed in dozenal and must be counted by the users to see the final score. The user can log Off or start a new game.
- **Basic Flow**:
  1. The system deals cards to both players and initializes the discard pile with a starter card.
  2. Players take turns, selecting a card to play (matching suit or rank) or drawing from the stock pile.
  3. If an "10" is played, the player selects a new suit via the UI.
  4. The system checks moves and gives immediate feedback for invalid moves.
  5. The game keeps going until one player has no cards left, triggering user score counting and calculation challenge in dozenal.
  6. The system displays the final score.
- **Exceptions**:
  - Invalid move attempted: The system highlights the error and prompts the player to select a valid card or draw.
  - Stock pile exhausted: The system reshuffles the discard pile to replenish the stock pile.
- **Assumptions**: Players are familiar with basic card game mechanics and the system supports a stable internet connection for play.

# 7 Business Data Model and Data Dictionary

## 7.1 Business Data Model

These are the key entities and relationships involved in the Crazy Eights game with dozenal scoring.

- **Entities**:
  - **Player**: Represents a game participant, holding a hand of cards and a score.

  - **Card**: Represents a single playing card with a suit and rank.
  - **Deck**: A collection of cards, divided into the stock pile and discard pile.
  - **Game Session**: Tracks the state of a single game, including players, current turn, discard pile, and scores.
  - **Score**: Tracks points in dozenal notation, calculated based on game rules.

- **Relationships**:
  - A **Game Session** has 2 **Players** (MVP) or 2–4 **Players** (stretch goal).
  - Each **Player** has a **Hand** (subset of **Cards**).
  - A **Deck** consists of 52 **Cards**, split into **Stock Pile** and **Discard Pile**.
  - A **Game Session** produces a **Score** for each **Player** in dozenal notation.
  - A **Card** played in a **Game Session** affects the **Discard Pile** and may trigger a suit change (if a "10").

## 7.2 Data Dictionary

- **Player**:
  - **ID**: Unique identifier for a player (integer).
  - **Name**: Display name for the player (string).
  - **Hand**: List of cards held by the player (array of Card objects).
  - **Score**: Player's cumulative score in dozenal notation (string, such as "1Ƹ" for 22 in decimal).

- **Card**:
  - **Suit**: One of four suits (Hearts, Diamonds, Clubs, Spades) (string).
  - **Rank**: Card value (2–10, J, Q, K, A) (string).
  - **IsWild**: Boolean indicating if the card is an "10" (true/false).

- **Deck**:
  - **Stock Pile**: List of cards available for drawing (array of Card objects).
  - **Discard Pile**: List of played cards (array of Card objects).
- **Game Session**:
  - **Session ID**: Unique identifier for the game session (string).
  - **Current Turn**: ID of the player whose turn it is (integer).
  - **Status**: Game state (Active, Completed) (string).
  - **Starter Card**: The first card in the discard pile (Card object).
  - **Last Played Suit**: The active suit after an "10" is played (string).
- **Score**:
  - **Player ID**: Links to the player (integer).
  - **Dozenal Value**: Score in base-12 notation (string, such as "14" for 16 in decimal).
  - **Calculation Method**: Rules for scoring (sum of remaining cards in the opponents hands) (string).

# 8 The Scope of the Product

## 8.1 Product Boundary

The product to be developed is a digital card game application based on the traditional *Crazy 8s* rules, modified to integrate the **Dozenal (base-12) number system**. The system boundary includes:

- A game engine that supports core Crazy 8s mechanics (drawing, discarding, turn-taking, winning conditions). Supported by BUC-2 (Play Card), BUC-3 (Draw Card), BUC-4 (Turn Handling)
- Adaptations of rules, card values, and scoring to incorporate Dozenal arithmetic and representations. Supported by BUC-5 (Score Calculation), BUC-6 (Dozenal Conversion)

- A user interface allowing players to interact with the game (play cards, view scores, receive feedback). Supported by BUC-1 (Join Game), BUC-7 (UI Rendering), BUC-8 (Real-time Updates)
- Educational prompts or visual aids to help players understand Dozenal concepts. Supported by BUC-9 (Educational Tips Display)

External systems not included in the boundary are: general learning platforms, multiplayer servers beyond basic peer-to-peer/local play, and integrations with unrelated educational tools.

## 8.2 Product Use Case Table

The following table summarizes the primary product use cases (PUCs):

| **PUC #** | **Description** |
|---|---|
| PUC-1 | Player logs into the system or creates a new account to enable personalized features and multiplayer access. |
| PUC-2 | Player views their personal profile, including gameplay history, win/loss record, and achievements. |
| PUC-3 | Player starts a new Crazy 1-0's game with Dozenal deck. |
| PUC-4 | Player takes a turn by drawing or discarding a card. |
| PUC-5 | System validates whether the played card is legal (wild card, same suit, same Dozenal value, or sum = 12). |
| PUC-6 | Player views scores and progress, displayed in Dozenal. |
| PUC-7 | System provides hints or resources to support Dozenal learning. |
| PUC-8 | Game ends when a player wins; final scores are calculated and displayed. |

## 8.3 Individual Product Use Cases (PUCs)

### UC1: Player Login

1. Player opens the game application and selects "Login" or "Create Account".
2. The system prompts the player to enter credentials (username and password) or choose guest mode.
3. The system validates login information against the stored database.

4. If credentials are valid, the player is granted access to personalized data (game progress, scores, and settings).
5. If the player selects guest mode, a temporary profile is generated for the session.
6. The system displays the main menu or lobby after login.

**UC2: See Player Profile**

1. The player selects "View Profile" from the main menu.
2. The system retrieves player data (username, past game records, win/loss ratio, and achievements) from the database.
3. The system displays profile information on screen.
4. If the player is logged in as a guest, the system displays a message such as "Profile unavailable for guest mode".
5. The player may choose to return to the main menu or edit available settings (if logged in).

**UC3: Start a New Game**

1. Player opens the application and selects "New Game".
2. The system initializes a Dozenal-enabled deck (0–9, ↊, ↋, 10, J, Q, K , C).
3. The system shuffles the deck.
4. The system deals cards to each player.
5. The game state is displayed on the interface.

**UC4: Take a Turn**

1. The system indicates that it is the player's turn.
2. The player chooses either to play a card or to draw from the deck.
3. If the player chooses a card, the system goes through **UC5** to check its validity against the discard pile.

4. If valid, the card is placed onto the discard pile.
5. If invalid, the system notifies the player and the card remains in the hand.
6. If the player chooses to draw, the system gives one card from the deck to the player.

**UC5: Validate Move**

1. The player selects a card to play.
2. The system retrieves the top card from the discard pile.
3. The system checks if the move is legal under Dozenal rules:
   (a) same suit, or
   (b) same Dozenal value, or
   (c) sum of the two values equals 12, or 1012, or
   (d) the card is a wild card "10" (for suit change) or "6" (for skip turn).
4. If the move is legal, the system accepts the card and updates the discard pile.
5. If not, the system rejects the move and notifies the player.

**UC6: View Scores**

1. A round ends or the player requests to view scores.
2. The system calculates points for each player.
3. The system displays and updates the scores in Dozenal.
4. The system displays the results on screen.

**UC7: Provide Hints**

1. The player hovers over or selects a card.
2. The system analyzes the current game state.

3. The system provides a hint (e.g., "This card is valid because its sum with the top card equals 1012.").

4. The hint is displayed as text or a visual highlight.

**UC8: End Game**

1. A player discards their last card.

2. The system checks if the game-ending condition is satisfied.

3. If satisfied, the system declares the winner.

4. The system calculates final scores in Dozenal.

5. The results are displayed on the final game screen.

# 9 Functional Requirements

## 9.1 Game Manager

1. **Start new game:** The system shall allow the player to start a new Crazy 8s game with a Dozenal-enabled deck. (FR-1)
   **Rationale:** Players need a way to initialize the game state; starting a new game is the basis for all other gameplay functions.
   **Fit Criterion:** The system initializes a new game state within 2 seconds, with deck, players, and discard pile correctly initialized.

2. **Turn management:** The system shall manage player turns, ensuring each player either discards a valid card or draws a card. (FR-2)
   **Rationale:** Turn-taking enforces fairness and ensures consistent game flow.
   **Fit Criterion:** In 20 consecutive turns, the system enforces correct turn order with zero invalid transitions.

3. **Rule validation:** The system shall validate that each played card is legal under Dozenal rules. A valid move is defined as either: (a) same suit, (b) same Dozenal value, (c) sum of the values equals 1012 in Dozenal, or (d) is a wild card "10" or "6". (FR-3)
   **Rationale:** Prevents illegal moves and integrates Dozenal arithmetic

as a core learning mechanic.
**Fit Criterion:** For 100 randomized test card pairs, the system correctly identifies valid/invalid moves with 100% accuracy.

4. **Special cards:** The system shall implement special wild cards ("10", "6") with all 4 of each being able to played anytime. Also the face cards ("J", "Q", "K", "C") are special mini-game wild cards, though are subject to rule validation (a) and (b) from (FR-3). The 6 wild cards can be played as such:

   - "10" allows the player to declare a new suit.
   - "6" forces the next player to skip their turn.
   - The face cards ("J", "Q", "K" and "C") trigger an arithmetic operation mini-game (called "MATH RACES") as follows:
     - "J", "Q", "K" (of any suit) will trigger a RANDOM "MATH RACE" (random operation from - addition, subtraction, multiplication, division).
     - "C" (of any suit) will trigger a CHOICE "MATH RACE" (player chooses the operation from - addition, subtraction, multiplication, division).
     - All "MATH RACES" result in an arithmetic operation popping upon both players screens. Whoever answers first receives 10 points!

   **Rationale:** Special cards improve gameplay depth, strategy, and user engagement.
   **Fit Criterion:** All 6 predefined special cards (10, 6, J, Q, K, C) behave correctly during system tests.

5. **End of game:** The system shall detect game-ending conditions (e.g., a player runs out of cards) and declare the winner. (FR-5)
   **Rationale:** A clear end condition is required for meaningful gameplay and learning outcomes.
   **Fit Criterion:** The system correctly detects the end-of-game and winner in 20/20 test rounds.

## 9.2 Score Manager

1. **Calculate score:** The system shall calculate scores for each round for both Decimal and Dozenal games. (FR-6)
   **Rationale:** Displaying both formats reinforces learning through system comparison.
   **Fit Criterion:** For 50 random hands, Decimal and Dozenal score calculations show zero errors.

2. **Display score:** The system shall display scores in both Decimal and Dozenal. (FR-7)
   **Rationale:** Visual feedback supports user understanding and helps internalize Dozenal values.
   **Fit Criterion:** Updated scores appear within 300ms of a scoring event and are identical across both formats.

## 9.3 Education Support

1. **Hints:** The system shall provide hints or explanations when a player performs an action involving Dozenal arithmetic. (FR-8)
   **Rationale:** On-demand guidance lowers the learning curve and supports players with varying familiarity.
   **Fit Criterion:** Hints appear within 500ms in at least 95% of test interactions.

2. **Highlight valid moves:** The system shall visually highlight valid moves based on Dozenal rules. (FR-9)
   **Rationale:** Reduces user frustration and reinforces learning through visual cues.
   **Fit Criterion:** Valid move highlighting is 100% correct across 30 test board configurations.

## 9.4 Login Manager

1. **Account creation:** The system shall allow players to create a new account with a unique username and password. (FR-10)
   **Rationale:** Enables persistent profiles for user progress tracking.
   **Fit Criterion:** Account creation completes within 3 seconds and stored credentials validate correctly in all test cases.

2. **Login/Logout:** The system shall allow players to log in and log out at any time without losing progress. (FR-11)
   **Rationale:** Ensures smooth user experience and session continuity.
   **Fit Criterion:** Login completes within 2 seconds with zero false accepts/rejects in 50 tests.

3. **Guest mode:** The system shall allow players to start a temporary session without login. (FR-12)
   **Rationale:** Reduces entry barriers and improves accessibility.
   **Fit Criterion:** Guest sessions start within 1 second and do not interact with persistent storage.

4. **Credential validation:** The system shall validate player credentials against stored records. (FR-13)
   **Rationale:** Prevents unauthorized access and ensures account security.
   **Fit Criterion:** Credential validation has 0 false positives and 0 false negatives in 50 trials.

## 9.5 Data Manager

1. **Data storage:** The system shall securely store user data, including usernames, game history, and Dozenal scores. (FR-14)
   **Rationale:** Persistence is required for progress tracking and analytics.
   **Fit Criterion:** User data remains uncorrupted across 200 consecutive write operations.

2. **Data retrieval:** The system shall allow retrieval of stored data when logging in or viewing profiles. (FR-15)
   **Rationale:** Enables personalized gameplay and profile review.
   **Fit Criterion:** Profile loading completes within 2 seconds with 0 data mismatches.

3. **Data update:** The system shall update stored data after each game or profile change. (FR-16)
   **Rationale:** Ensures player profiles remain accurate and up to date.
   **Fit Criterion:** Updates propagate to persistent storage within 2 seconds and remain consistent on reload.

4. **Data deletion:** The system shall allow players to permanently delete their data. (FR-17)

**Rationale:** Supports user privacy expectations and legal compliance. **Fit Criterion:** Deleted profiles cannot be recovered through UI or API in 100% of test attempts.

# 10 Look and Feel Requirements

## 10.1 Appearance Requirements

- **Layout**: The user interface must have a clean and minimalistic layout, ensuring readability and ease of navigation.
- **Responsiveness**: The system must be responsive, adapting automatically to different screen sizes.
- **Visual Hierarchy**: Key elements such as active player indicators, playable cards, and turn timers must be visually distinguishable using contrast, color, or animation.
- **Color Palette**: The color scheme should promote clarity and engagement.

## 10.2 Style Requirements

- **Consistency**: The application must follow a unified design language, maintaining consistent typography, iconography, and button styles across all screens.
- **Animations**: Smooth 2-D animations should be implemented for card movements, dealing, and discarding actions. These animations should be realistic but not distracting, maintaining short transition times. When a wild card is played, a distinct animation and color shift should visually emphasize its effect while maintaining overall style consistency.
- **In-Game Hints**: Hints should appear contextually (e.g., glowing borders, pulsing icons) rather than as intrusive pop-ups. They should guide the player without interrupting the flow of the game.

# 11 Usability and Humanity Requirements

## 11.1 Ease of Use Requirements

- **Simplicity**: The interface must minimize the number of steps needed to perform core tasks.
- **Intuitive Controls**: Card selection and game actions should be intuitive, with clear affordances (e.g., drag-and-drop or click-to-play).
- **Clear workflow**: Core gameplay and learning activities must be discoverable within two actions from the main menu.

## 11.2 Personalization and Internationalization Requirements

- **Language Options**: The system must support at least English and one additional language for international users.

## 11.3 Learning Requirements

- **Onboarding**: A short tutorial must explain the rules of the game and how counting in different bases works.

## 11.4 Understandability and Politeness Requirements

- **Friendly Wording**: Prompts like "Invalid Move" must be displayed as polite guidance.
- **Clear Instructions**: Rules and base-conversion explanations must be phrased in simple and non-technical terms.

## 11.5 Accessibility Requirements

- **Tactile Feedback**: All main actions must be accessible via buttons with clear labels, and easily clickable targets.
- **Contrast**: The UI must use accessible contrast ratios for text and interactive elements so they are easily read.

# 12 Performance Requirements

## 12.1 Speed and Latency Requirements

- **Low latency**: Game actions must update across all players' screens within 300 ms.
- **Fast loading**: The game lobby and first match must load within 5 seconds on a stable internet connection.

## 12.2 Safety-Critical Requirements

- **Cheat Prevention**: The system must prevent unauthorized manipulation (e.g., directly altering game state through client-side tools).
- **Data Integrity**: No game state (e.g. deck composition, player hand) should be lost or corrupted due to refresh or reconnect.

## 12.3 Precision or Accuracy Requirements

- **Card Rules**: Card-matching and counting rules must be enforced with 100% accuracy according to the chosen numeral base.

## 12.4 Robustness or Fault-Tolerance Requirements

- **Reconnection**: If a player disconnects, they must be able to rejoin within 30 seconds without losing progress.

## 12.5 Capacity Requirements

- **Concurrent Players**: The system must support at least 200 concurrent users during testing.

## 12.6 Scalability or Extensibility Requirements

- **Game Modes**: The system must allow for adding new rule variations (e.g., different numeral bases or wild card effects) with minimal code changes.

- **Server Scaling**: The backend must be deployable in a scalable environment (e.g., Docker, cloud hosting) to handle larger user bases.

### 12.7 Longevity Requirements

- **Maintainability**: The codebase must be modular and documented, so future developers can update rules easily.

## 13 Operational and Environmental Requirements

### 13.1 Expected Physical Environment

- The product will be used on desktop/laptop computers in classrooms, homes, and demo booths under normal indoor lighting and noise conditions.
- Typical input devices: keyboard and mouse; mouse will be primary input device; keyboard interaction considered a stretch goal.
- No special physical environment (temperature, humidity, dust) requirements are expected.

### 13.2 Requirements for Interfacing with Adjacent Systems

- **Authentication API:** Integrate with a simple backend-auth service (REST endpoints) for account creation and login.
- **Telemetry / Analytics (optional):** Provide an HTTP endpoint to export anonymized session metrics for research (GDPR-compliant).
- **Hosting / CI:** Integration with GitHub Actions for tests and deploy; target hosting platform must accept standard Docker containers or static web app hosting.

## 13.3 Productization Requirements

- Distribution as a web application (hosted) and a developer-local deployment (Docker-compose) for evaluation.
- Installation for in-person demos should require at most three documented steps (clone, install, run).

## 13.4 Release Requirements

- Release cadence: a demonstration-ready milestone (PoC) and a final-revision release for EXPO.
- Releases must be tagged in GitHub with release notes and a reproducible build artifact (Docker image or static bundle).
- **Fit Criterion:** Acceptance when: (a) core flows run on supported browsers; (b) documented REST endpoints respond to auth and telemetry; (c) dev deployment runs end-to-end using provided Docker-compose with README steps validated by at least one tester.

# 14 Maintainability and Support Requirements

## 14.1 Maintenance Requirements

- **Code Maintainability**: The codebase must be modular, with clear separation of concerns to facilitate updates and debugging. Inline comments for non-obvious logic and updated README/module documentation are required, as specified in the development plan.
- **Version Control**: All changes must be tracked via GitHub, with descriptive commit messages and pull requests requiring at least one peer review to ensure maintainability.
- **Extensibility**: The system must support adding new features without requiring significant refactoring. This is achieved by using a modular architecture and Object oriented Design principles.
- **Documentation Updates**: Any change in behavior, interfaces, or setup instructions must be reflected in the documentation to ensure

future developers can maintain the system. Local deployment instructions documented in the README to simplify setup for developers and maintainers.

### 14.2 Supportability Requirements

- **Error Reporting**: The system must provide clear, user-friendly feedback for invalid moves. Logs or replays of game sessions must be available for debugging, as specified in the non-functional goals.
- **User Support**: A tutorial or visual guidance (stretch goal) must be provided to assist new players in understanding gameplay and dozenal scoring. This reduces the need for extensive manual support.
- **Cross-Platform Support**: The software must run on different web environments (Windows, macOS, or browsers).

### 14.3 Adaptability Requirements

- **Rule Flexibility**: The system must support toggling house rules (e.g., draw-until-playable, stacking eights) via a rule configurator (stretch goal), allowing adaptation to different play styles without code changes.
- **Scalability for Players**: The architecture must accommodate extending from two-player (MVP) to 3–4 player games (stretch goal) by modifying session management and turn logic.
- **Numeric System Extensibility**: The scoring system must allow switching between dozenal and decimal displays, ensuring adaptability for users unfamiliar with base-12.

## 15 Security Requirements

### 15.1 Access Requirements

- Role model: **Guest**, **Registered Player**, and **Administrator/Team Maintainer**. Define permitted APIs for each role.

- Registered players may access persistent profile data and match history for their account only.
- Administrators may access system logs and anonymized telemetry; no arbitrary user personal data access without consent.

## 15.2 Integrity Requirements

- Server-authoritative game state: all moves validated server-side for any online session to prevent client tampering.
- Persistent data (user profiles, match results) must be stored atomically; partial writes are unacceptable.
- Backups: periodic DB snapshots for recovery as defined in deployment docs.

## 15.3 Privacy Requirements

- Collect minimal PII: username and optional display name; e-mail only if explicitly provided for account recovery.
- Users must be informed (privacy notice) before data collection; opt-out option for telemetry must be available.

## 15.4 Audit Requirements

- Maintain tamper-evident logs for administrative actions and system errors for at least 30 days.
- For online sessions, optionally retain replay logs (seed and sequence) to permit investigation of disputes; stored replays must be anonymized when used outside the originating account.

## 15.5 Immunity Requirements

- The product shall be resilient to basic web threats (e.g., injection, CSRF) by following standard secure-coding practices and OWASP guidance.

- External penetration testing is a stretch goal; at minimum, use linting and dependency-audit tools in CI.

# 16 Cultural Requirements

## 16.1 Cultural Requirements

- **Numeric System Accessibility**: The software must present dozenal (base-12) in an intuitive, non-disruptive way. This includes clear UI elements for dozenal scores (using ⅋ and Ɛ for 10 and 11) and optional tutorials (stretch goal) to explain dozenal notation to users unfamiliar with it.

- **Inclusivity**: The system must avoid cultural biases in its design, ensuring that gameplay and terminology (suits, ranks) are universally recognizable across cultures familiar with standard playing cards. No culturally specific references or imagery should be used in the UI to maintain broad accessibility.

- **Educational Alignment**: The software must align with educational goals by demonstrating the practical benefits of dozenal in a game context, making it appealing to students and educators. This supports the cultural shift toward exploring alternative numeric systems, as advocated by stakeholders like dozenal enthusiasts.

# 17 Compliance Requirements

## 17.1 Legal Requirements

- The game must comply with intellectual property laws and digital content distribution regulations.

- All assets (images, fonts, and sounds) used in the game must be open-source, royalty-free, or properly licensed.

## 17.2 Standards Compliance Requirements

- The software shall follow standard software development practices such as version control (Git), documentation standards (LaTeX-based SRS), and accessibility guidelines (WCAG 2.1 Level AA).
- The system must adhere to web standards for HTML5, CSS3, and JavaScript (ES6+) to ensure cross-browser compatibility and maintainability.

# 18 Off-the-Shelf Solutions

## 18.1 Ready-Made Products

Existing Crazy 8s card games (e.g., UNO or digital clones) offer partial gameplay models, but none integrate an educational Dozenal arithmetic component. No direct off-the-shelf solution currently fulfills both entertainment and mathematical learning objectives.

## 18.2 Reusable Components

- Card rendering engines from open-source projects such as *Pygame* or *Godot* assets.
- Math libraries for number-base conversion (decimal $\leftrightarrow$ Dozenal).
- UI component libraries for game menus, card animations, and scoreboards.

## 18.3 Products That Can Be Copied

Some structural aspects (turn management, shuffling algorithms) can be adapted from existing open-source card game repositories, provided licensing terms (e.g., MIT, GPL) are respected. However, educational Dozenal mechanics must be developed in-house to align with project-specific learning goals.

# 19 New Problems

## 19.1 Effects on the Current Environment

- The system is a newly devleoped web-based game and does not replace or interfere with any existing enviroment, minimal impact is expected aside from standard hosting and network usage.

## 19.2 Effects on the Installed Systems

- No existing software systems are modified or replaced by this product. The game operates independently on standard browsers and web servers.

## 19.3 Potential User Problems

- Users may experience confusion if base-conversion rules are misunderstood. These issues will be mitigated through clear feedback, tutorials, and consistent UI design.

## 19.4 Limitations in the Anticipated Implementation Environment That May Inhibit the New Product

- The main limitation is dependency on stable internet connectivity. Poor network conditions may degrade real-time synchronization or cause delayed responses.

## 19.5 Follow-Up Problems

- As the system evolves, maintaining compatibility with browser updates and third-party libraries (e.g., React, Socket.io) may introduce future maintenance challenges.

# 20 Tasks

## 20.1 Project Planning

- The project life cycle will follow the deliverable outline for SFWRENG 4G06: Capstone. By April the project must be completed in its entirety.

## 20.2 Planning of the Development Phases

- Requirements and Design Phase - Gather functional and non-functional requirements, identifying key components.
- Prototyping Phase - Develop an early functional prototype focusing on core interactions and user interface flow.
- MVP Phase - Implement the main gameplay logic, user authentication, and basic scoring system as our MVP.
- Finalize Phase - Polish the user interface, improve performance, deploy the final version to the hosting environment and prepare presentation.

# 21 Migration to the New Product

Not applicable.

# 22 Costs

## 22.1 Assumptions

- Academic, non-commercial deployment targeting a small user group during the term.
- Free tiers are acceptable for hosting and CI where reliability is sufficient for demos.
- Budget ceiling: 500 CAD (see Section "Budget Constraints").

## 22.2 One-time Costs

## 22.3 Recurring Costs

- App hosting utilize free tier where possible
- DB hosting and Free tier Postgres, small instance
- Domain name renweal cost could be recurring if we plan on hosting it longer term

## 22.4 Total and Headroom

Estimated total spend for the term: **100 CAD**. This stays within the 500 CAD cap and leaves headroom for risk mitigation or stretch features.

## 22.5 Cost Control Plan

- Prefer free tiers for hosting, CI, and CDN. Upgrade only if load or reliability requires it.
- Reuse open-source UI kits and icon packs with permissive licenses.
- Cap incentives to pre-approved number of sessions.

# 23 User Documentation and Training

## 23.1 User Documentation Requirements

- **In-app help**: Contextual tooltips for controls, hover help for Dozenal terms, and an always-available "How to play" panel.
- **Quick Start**: Setup, start a match, play a turn, view scores. Written for first-time users.
- **Rules and Dozenal guide**: Clear rules of Crazy Eights plus a simple Dozenal primer with examples for A and B, and conversions between base 10 and base 12.
- **FAQ**: Troubleshooting (cannot play a card, reconnect flow, what counts as a valid move).

## 23.2 Training Requirements

- **Onboarding tutorial**: 3 to 5 steps covering play a card, draw a card, wild eight, and reading Dozenal scores. Skippable and repeatable.
- **Practice mode**: Solo mode against a simple bot to learn pace and rules without pressure.

# 24 Waiting Room (Stretch Requirements)

## 24.1 Purpose and scope

This section lists unimplemented features (stretch goals) relating to the Crazy 10s game project. Each item below is intentionally classified as a post-MVP requirement; these will be considered for Crazy10s v1.1 (Rank 1) or v1.2 (Rank 2) per the urgency ranking in the very bottom of this section.

## 24.2 Functional Stretch Requirements

1. **Online Multiplayer (Stretch-L1)**
   **Description:** Create/join rooms and synchronize game state; provide basic reconnection.
   **Rationale:** Demonstrates system design capability and supports real usage.
   **Fit Criterion:** Players can create and join rooms, game state synchronizes across clients, and reconnection works after brief disconnections.

2. **AI Opponent (Stretch-L1)**
   **Description:** Computer-controlled players with simple heuristics for card choice and suit declaration.
   **Rationale:** Enables single-player testing and showcases extensibility.
   **Fit Criterion:** AI opponent plays valid moves, declares suits appropriately, and loses/wins matches against human players.

3. **Advanced Dozenal Variants (Stretch-L1)**
   **Description:** Optional rule packs (e.g., effects for 12-related cards; base-12 scoring thresholds such as $60_{12}$).
   **Rationale:** Deepens the dozenal theme while keeping the classic mode intact.

**Fit Criterion:** Variant rules can be enabled in lobby, affect gameplay as specified, and scores are computed in dozenal.

4. **Rule Configurator (Stretch-L1)**
   **Description:** Toggles for house rules (draw-until-playable, stacking eights, scoring methods in decimal or dozenal).
   **Rationale:** Shows variability management; supports experimentation and future product-line thinking.
   **Fit Criterion:** House rules can be toggled in lobby settings and correctly applied during gameplay.

5. **Save/Replay System (Stretch-L1)**
   **Description:** Save completed games and replay event sequences.
   **Rationale:** Aids debugging, user study, and documentation.
   **Fit Criterion:** Completed games can be saved and replayed with accurate event sequences.

6. **4-player match support (Stretch-L2)**
   **Description:** Extend session logic to allow 3–4 players, clear turn rotation, and UI to display additional hands.
   **Form (FR-style):** Add FR: "Multi-player session management must support up to 4 players with deterministic turn order and correct scoring."
   **Motivation:** Increased replayability and social gameplay.
   **Considerations:** Complexity in balancing learning vs. play-time; may increase server load.
   **Fit Criterion:** A 4-player match can be started, played to completion, and score computed correctly.

7. **Invite and classroom session tools (Stretch-L1)**
   **Description:** Teachers create class sessions, bulk-invite students, and view join status.
   **Form:** Teacher dashboard extension FR.
   **Motivation:** Simplify classroom management and improve adoption.
   **Fit Criterion:** Teacher creates a session and sees join statuses in real time in the lobby.

## 24.3 UI / Look-and-Feel Stretch Requirements (mapped to Section 10)

1. **In-game optional hints (Stretch-U1)**
   **Appearance / Style Form:** Hints shall be available as an opt-in toggle in the lobby settings (per-player or per-session). Visual hint styles: glowing border, subtle tooltip.
   **Motivation:** Supports novice players during early learning but avoid over-assistance for experienced users.
   **Considerations:** Hints must be accessible (ARIA) and optional; do not clutter the interface by default.
   **Fit Criterion:** A player toggles hints in the lobby and receives contextual, non-blocking hints during gameplay when enabled.

2. **Detailed onboarding preview in lobby (Stretch-U1)**
   **Appearance Form:** Lobby displays a short interactive primer about dozenal or the active base; includes a "Quick Try" button to demo the counting mechanic.
   **Motivation:** Lowers barrier to entry for classroom audiences.
   **Fit Criterion:** Primer launches from lobby and completes without entering a full match.

## 24.4 Education / Learning Stretch Requirements (mapped to Section 11)

1. **Tutorial and Visual Guidance (Stretch-E1)**
   **Description:** First-game tutorial, invalid-move highlights, and play suggestions.
   **Rationale:** Lowers the learning curve and improves usability.
   **Fit Criterion:** Tutorial guides new players through basic gameplay, highlights invalid moves, and provides suggestions during play.

2. **Advanced arithmetic mini-challenges (Stretch-E1)**
   **Description / Form:** When enabled in lobby, certain wild-card plays trigger short arithmetic mini-challenges (e.g., compute sum in active base). These are optional and configurable.
   **Motivation:** Deepen learning for engaged classes.
   **Considerations:** Must be skippable and have accessibility support;

avoid disrupting game flow.
**Fit Criterion:** When enabled, mini-challenges appear at correct trigger points and accept valid answers in the active base.

## 24.5 Internationalization and Language Stretch Requirements (mapped to Section 11.2)

1. **Optional language support (Stretch-I2)**
   **Description:** Add support for one additional language (e.g., French) as a stretch feature.
   **Form:** UI strings externalized; language selectable in lobby settings.
   **Motivation:** Broaden potential evaluators/users beyond English.
   **Considerations:** Translation quality is critical for pedagogical text; may require SME review.
   **Fit Criterion:** UI renders in selected language and sample dozenal primer is translated without truncation.

## 24.6 Performance / Capacity Stretch Requirements (mapped to Section 12)

1. **Higher concurrent capacity (Stretch-P2)**
   **Description:** Scale hosting to support ¿200 concurrent users for studies or demonstrations.
   **Form:** Performance requirement with load-test acceptance criteria.
   **Motivation:** Useful for large demo sessions or class-wide studies.
   **Considerations:** Higher cost and CI load-testing required.
   **Fit Criterion:** Simulated load test demonstrates system remains responsive per p95 latency target at target concurrency.

## 24.7 Integration / Deck Production Stretch Requirements

1. **Physical deck production workflow (Stretch-D2)**
   **Description:** Provide printable/print-on-demand assets and ordering instructions to create physical dozenal, octal, or hex decks.
   **Form:** Documentation and asset package in repo.
   **Motivation:** Supports tactile classroom use and outreach.

**Considerations:** Licensing and cost to be estimated.

2. **Fit Criterion:** Provided print assets produce a proof print and match on-screen representations.

## 24.8 Urgency Ranking

Each unimplemented stretch requirement above is assigned an urgency rank:

- **Rank 1 (v1.1)**: High-priority stretch items likely to be scheduled immediately after MVP if resources permit.
- **Rank 2 (v1.2)**: Lower-priority stretch items for later releases or exploratory work.

## 24.9 Crazy10s v1.1 (Rank 1) — Priority stretch items

- Invite & classroom session tools (Stretch-L1)
- In-game optional hints (Stretch-U1)
- Advanced arithmetic mini-challenges (Stretch-E1)
- Physical deck production workflow (Stretch-D2) — planning/asset creation phase

## 24.10 Crazy10s v1.2 (Rank 2) — Lower priority stretch items

- 4-player match support (Stretch-L2)
- Detailed onboarding preview in lobby (additional polish) (Stretch-U1)
- Optional language support (Stretch-I2)
- Higher concurrent capacity (Stretch-P2)

# 25 Ideas for Solution

## 25.1 Architecture Overview

- **Frontend**: React with TypeScript. State managed via a small store (Zustand or Redux Toolkit). WebSocket client for live turns. Component library and keyboard-first interactions.
- **Backend**: Node.js with TypeScript. HTTP API for auth and lobby. WebSocket for game sessions and events. Server-authoritative game state.
- **Data**: Postgres for user profiles, match history, and telemetry. In-memory room state with periodic snapshots to DB.
- **Game engine**: Pure TypeScript module with deterministic rules, validators, scoring, and base conversion utilities. No UI concerns.
- **CI/CD**: GitHub Actions for lint, tests, type-checks, and deploy to a free-tier host.

## 25.2 Implementation Options

| Option | Summary, Pros, Cons |
|---|---|
| A. Local-first 2P hot-seat | *Summary*: Single browser, two players, no backend. *Pros*: Fast MVP, minimal infra. *Cons*: No remote play, no persistence. |
| B. Server-authoritative WebSocket | *Summary*: Lobby, rooms, turns via WS. *Pros*: Fair play, replay logs, reconnect support. *Cons*: More code and testing. |

## 25.3 Recommended Path

1. Build the game engine as a pure library with full tests.
2. Ship Option A for fast validation and UI polish.
3. Upgrade to Option B for sessions, persistence, and reconnection.

## 25.4 Key Non-functional Techniques

- **Fairness**: Server-side validation for all moves. Shuffle with seeded RNG and record seed for audits.
- **Resilience**: Rejoin token and state rehydrate on reconnect.
- **Accessibility**: Semantic HTML, focus order, ARIA labels, and keyboard shortcuts for all core actions.

# Appendix — Reflection

The purpose of reflection questions is to give you a chance to assess your own learning and that of your group as a whole, and to find ways to improve in the future. Reflection is an important part of the learning process. Reflection is also an essential component of a successful software development process.

Reflections are most interesting and useful when they're honest, even if the stories they tell are imperfect. You will be marked based on your depth of thought and analysis, and not based on the content of the reflections themselves. Thus, for full marks we encourage you to answer openly and honestly and to avoid simply writing "what you think the evaluator wants to hear."

Please answer the following questions. Some questions can be answered on the team level, but where appropriate, each team member should write their own response:

1. What went well while writing this deliverable?

   - One thing that went well while writing the SRS was our team's ability to clearly define functional and non-functional requirements based on our project scope. We divided the document sections efficiently and maintained consistent formatting and terminology. Our discussions on user needs and system goals also helped refine the main features early, making later sections like use cases and functional requirements much easier to complete.

2. What pain points did you experience during this deliverable, and how did you resolve them?

   (a) Discussing and validating requirements with the Professor during the middle of midterm season.
   We resolved this by trusting the requirements and feedback from our previous meetings with the Professor, along with course lecture notes, the SRS-Volere template, and other stakeholders to aid us in generating appropriate and relevant requirements.

   (b) Reviewing SRS and ensuring all parts are consistent and complete.
   This is still unresolved, as many sections in the SRS are inconsistent and still incomplete (like the card game mechanics in Sections 8-9, which appear as complete, but are still being discussed among

the team and Project Supervisor Paul Rapoport).
One thing that worked to aid in resolving this pain point, was one of our team members (Ammar) doing an individual review of SRS (before he added all of his sections), to ensure the document is consistent and includes everything important. Upon review, Ammar found several missing subsections, inconsistencies, and suggested improvements, and created a GitHub issue for each one, which was then delegated to the appropriate team member, and resolved by each team member (as written in the created issue).
Another thing that helped was teammate Ammar getting a 3-day extension (which turned into a 4-day extension because of personal circumstances) on his Sections of the SRS. He used this extra time to schedule a meeting with Paul Rapoport and available team members to present our team's SRS, and open it for review to the Professor.
Shortly after the meeting, Supervisor Paul Rapoport sent us an email with his feedback on our SRS, in a written document. This document of Professor Rapoport's review was added to GitHub as an issue (see Project Issue 47). Teammate Ammar reviewed the document during his extension time, and tried to resolve what he could within the SRS document. The rest of the open issues that were there prior to the meeting, and the ones presented by Paul Rapoport in his review, were added to Section 18: Open Issues. These issues will eventually be added to the Project Repo as individual Issues, and resolved appropriately.

(c) Poor time management of teammate Ammar, last minute rush and missing GitHub skills to merge SRS and HA branch commits to main.
Teammate Ammar has apologized and stated any penalties for late submission should go to him and not other teammates. He also created pull requests for branches SRS and HA, as he was unable to merge these to main himself. To resolve the immediate issue of unmerged commits and branches, teammate Ruida stepped in the day after the deadline to fix branch diversions, resolve merge conflicts and merge teammate Ammar's commit history to main. This being said, the problem of constant late submission by team-

mate Ammar still persists, and requires resolution. The three clear options are:

- Teammate Ammar improves his time management and meets deadlines in the future.
- Teammate Ammar is penalized for the late submission for Deliverable 2 (SRS + HA), and the team continues as is.
- Professor Smith, Professor Rapoport and/or TA Chris come up with some other resolution/compromise for this pain point.

Written by Ammar Sharbat, 2024-10-15

3. How many of your requirements were inspired by speaking to your client(s) or their proxies (e.g. your peers, stakeholders, potential users)?

   - Most of our system requirements were influenced by feedback from peers and proxy users who represent our target audience—students learning numeral base conversions, additional requirements, such as real-time multiplayer functionality, clear in-game hints, and visual base conversion indicators are added.

4. Which of the courses you have taken, or are currently taking, will help your team to be successful with your capstone project.

   - SFWRENG 3A04: Software Design III - Large System Design (Git, designing software architecture, UML diagrams)
   - SFWRENG 4HC3: Human Computer Interfaces (User-Centered Design, Usability Testing)
   - SFWRENG 3RA3: Software Requirements (Git, Github Issues, Writing SRS, Requirements Elicitation)
   - SFWRENG 3S03: Software Testing (Test Case Design, Automated Testing Frameworks)
   - SFWRENG 4C03: Computer Networks and Security (Network Protocols, Security Best Practices)
   - SFWRENG 2AA4: Software Design I (Git, Kanban Board, Object-Oriented Design, Design Patterns)

5. What knowledge and skills will the team collectively need to acquire to successfully complete this capstone project? Examples of possible knowledge to acquire include domain specific knowledge from the domain of your application, or software engineering knowledge, mechatronics knowledge or computer science knowledge. Skills may be related to technology, or writing, or presentation, or team management, etc. You should look to identify at least one item for each team member.

    - Ruida: Frontend Development: Deepening our understanding of React component architecture, animation design, and state management.
    - Alvin: Backend Development: Gaining hands on experience in Node.js, Express, and database management.

6. For each of the knowledge areas and skills identified in the previous question, what are at least two approaches to acquiring the knowledge or mastering the skill? Of the identified approaches, which will each team member pursue, and why did they make this choice?

    - Ruida: Frontend Development (React & Animation) Approaches: (1) Following online React tutorials and official documentation; (2) Experimenting through prototype iterations and peer code reviews. I will choose the first approach - follow online react tutorials, since the official tutorial documentation of react is really straightfoward and easy to learn, lots of code examples are provided.

    - Alvin: Backend Development (Node.js, Express, Database Management) Approaches: (1) Completing online courses and tutorials on Node.js and Express (2) Reviewing course notes and project repositories from past relevant courses.

Table 2: One-time Purchases (CAD)

| **Item** | **Purpose** | **Unit** | **Total** |
|---|---|---|---|
| Domain name (1 year) | Simple memorable URL for demos | 1 | 20 |
| | | **Subtotal** | **20** |