

Computer Networks Lab Report- Assignment 4

TITLE:

Name: Debarghya Maitra

Class: BCSE 3 rd Year

Group: A3

Submission Date: 23/9/2022

PROBLEM STATEMENT: In this assignment you have to implement CDMA for multiple access of a common channel by n stations. Each sender uses a unique code word, given by the Walsh set, to encode its data, send it across the channel, and then perfectly reconstruct the data at n stations.

DESIGN:

For the simulation of the CDMA on n-stations the following design has been followed:

- i) **walshCode:** The walshcode module generates the walsh table for n stations network.
- ii) **Sender:** The sender module makes n threads for n stations and sends data to the channel via write file descriptor pipes.
- iii) **Channel:** The channel takes all the data from pipes encodes with respective walsh code and forms the channel data with $c1.d1+c2.d2+c3.d3+...+cndn$, where d_i = ith station data, c_i = ith station walsh code. Next it passes this formed data to all receiver threads.
- iv) **Receiver:** The receiver on receiving the encoded data, first it decodes it with respective codes and then stores the output in respective output files.




Fig: Design pattern

The outputs, data transfer at a particular time are all logged in analysis.txt and log.txt and not printed in stdout.

IMPLEMENTATION:

- i) **walsh table generating function:**

```

def generateWalshTable(wtable, length, x1, x2, y1, y2, compFlag: bool):
    if length == 2:
        if not compFlag:
            wtable[x1][y1] = 1
            wtable[x1][y2] = 1
            wtable[x2][y1] = 1
            wtable[x2][y2] = -1
        else:
            wtable[x1][y1] = -1
            wtable[x1][y2] = -1
            wtable[x2][y1] = -1
            wtable[x2][y2] = 1
        return
    midx = (x1+x2)//2
    midy = (y1+y2)//2
    generateWalshTable(wtable, length/2, x1, midx, y1, midy, compFlag)
    generateWalshTable(wtable, length/2, x1, midx, midy+1, y2, compFlag)
    generateWalshTable(wtable, length/2, midx+1, x2, y1, midy, compFlag)
    generateWalshTable(wtable, length/2, midx+1, x2, midy+1, y2, not compFlag)

```

Here the length argument must be a power of 2.

ii) **sender thread implementation:**

```

def send_data(self):
    curr_datetime = datetime.now().strftime("%d/%m/%Y %H:%M:%S")
    with open('logs/log.txt', 'a+', encoding='utf-8') as f:
        f.write(f"\n[{curr_datetime}] SENDER-{self.name+1} Started Sending To RECEIVER-
{self.name+1}")
    self.start = time.time()
    file = self.read_file(self.name)
    dataByte = file.read(1)
    while dataByte:
        dataBits = '{0:08b}'.format(ord(dataByte))
        for i in range(len(dataBits)):
            dataToSend = []
            bit = int(dataBits[i])
            if bit == 0:
                bit = -1
            for j in self.walshCode:
                dataToSend.append(j*bit)
            self.senderToChannel.send(dataToSend)
            self.bitcount += 1
        curr_datetime = datetime.now().strftime("%d/%m/%Y %H:%M:%S")
        with open('logs/log.txt', 'a+', encoding='utf-8') as f:
            f.write(f"\n[{curr_datetime}] SENDER-{self.name+1} Data Bit Sent {bit}")
        time.sleep(0.3)
        dataByte = file.read(1)
        self.delay = round((time.time()-self.start), 2)
    with open('logs/analysis.txt', 'a+', encoding='utf-8') as f:
        f.write()
    curr_datetime = datetime.now().strftime("%d/%m/%Y %H:%M:%S")
    with open('logs/log.txt', 'a+', encoding='utf-8') as f:
        f.write(f"\n[{curr_datetime}] SENDER-{self.name+1} Ended Sending Data")

```

iii)channel thread implementation:

```
def relayThread(self):
    while True:
        num = walshCode.nextPowerOf2(self.senderCount)
        for _ in range(self.senderCount):
            data = self.senderToChannel.recv()
            curr_datetime = datetime.now().strftime("%d/%m/%Y %H:%M:%S")
            with open('logs/log.txt', 'a+', encoding='utf-8') as f:
                f.write(f"\n[{curr_datetime}] CHANNEL Passed {data}")
            for j in range(num):
                #print(self.channelData, data, i, j)
                self.channelData[j] += data[j]
            self.syncVal += 1
            if self.syncVal == self.senderCount:
                for receiver in range(self.senderCount): # receiverCount = senderCount
                    self.channelToReceiver[receiver].send(self.channelData)
                self.syncVal = 0
                self.channelData = [0 for _ in range(walshCode.nextPowerOf2(self.senderCount))]
```

iv)receiver thread implementation:

```
def receive_data(self):
    curr_datetime = datetime.now().strftime("%d/%m/%Y %H:%M:%S")
    with open('logs/log.txt', 'a+', encoding='utf-8') as f:
        f.write(f"\n[{curr_datetime}] RECEIVER-{self.name+1} Receives Data from SENDER-
{self.senderToReceiver+1}")
    entiredata = []
    while True:
        channeldata = self.channelToReceiver.recv()
        sum = 0
        for i in range(len(channeldata)):
            sum += channeldata[i] * self.wTable[i]
        sum /= self.codeLength
        if sum == 1:
            bit = 1
        elif sum == -1:
            bit = 0
        else:
            bit = -1
        curr_datetime = datetime.now().strftime("%d/%m/%Y %H:%M:%S")
        with open('logs/log.txt', 'a+', encoding='utf-8') as f:
            f.write(f"\n[{curr_datetime}] RECEIVER-{self.name+1} Bit Received: {bit}")
        if len(entiredata) < 8 and bit != -1:
            entiredata.append(bit)
        if len(entiredata) == 8:
            byte = self.getByte(entiredata)
            output_file = self.read_file(self.senderToReceiver)
            output_file.write(byte)
            output_file.close()
            entiredata = []
```

v) Thread initialization and pipe implementation in main.py:

```

def simulate_environment(wTable, senderCount):
    writeRecvFd = [] #channel to receiver
    readRecvFd = [] #channel to receiver
    for _ in range(senderCount):
        readhead, writehead = multiprocessing.Pipe()
        readRecvFd.append(readhead) # file descriptor taken by receiver
        writeRecvFd.append(writehead) # file descriptor taken by channel
    readSendFd, writeSendFd = multiprocessing.Pipe() # sender to channel
    senderObjList = []
    receiverObjList = []
    senderThreads = []
    receiverThreads = []
    channel = Channel(senderCount, 0, readSendFd, writeRecvFd)
    for i in range(senderCount):
        sender = Sender(i, wTable[i], writeSendFd)
        senderObjList.append(sender)
        receiver = Receiver(i, wTable[i], readRecvFd[i])
        receiverObjList.append(receiver)
    channelThread = threading.Thread(target=channel.relayThread)
    for i in range(senderCount):
        sthread=threading.Thread(name="sender_thread"+str(i+1),
target=senderObjList[i].send_data)
        senderThreads.append(sthread)
    rthread=threading.Thread(name="receiver_thread"+str(i+1), target=receiverObjList[i].receive_data)
        receiverThreads.append(rthread)
    channelThread.start()
    for thread in receiverThreads:
        thread.start()
    for thread in senderThreads:
        thread.start()
    for thread in senderThreads:
        thread.join()
    for thread in receiverThreads:
        thread.join()
    channelThread.join()

```

RESULTS:

1) For 5 stations and data word as: “DEBARGHYAMAITRA”, the metrics for each sender was about:

[+] Total Bits Transferred: 120
 [+] Total Time Taken: 36.5 seconds
 [+] Throughput: 3.288 bps

2) For 6 stations and data word as “Debarghya Maitra test”, the metrics for each sender was about:

[+] Total Bits Transferred: 120
 [+] Total Time Taken: 36.5 seconds
 [+] Throughput: 3.288 bps

The below image shows the output in the file: analysis.txt:

```

+----- 20/10/2022 12:27:57 SENDER-3 Statistics -----+
[+] Total Bits Transferred: 168
[+] Total Time Taken: 51.06 seconds
[+] Throughput: 3.29 bps
+-----+

+----- 20/10/2022 12:27:57 SENDER-6 Statistics -----+
[+] Total Bits Transferred: 168
[+] Total Time Taken: 51.06 seconds
[+] Throughput: 3.29 bps
+-----+

+----- 20/10/2022 12:27:57 SENDER-2 Statistics -----+
[+] Total Bits Transferred: 168
[+] Total Time Taken: 51.07 seconds
[+] Throughput: 3.29 bps
+-----+

+----- 20/10/2022 12:27:57 SENDER-5 Statistics -----+
[+] Total Bits Transferred: 168
[+] Total Time Taken: 51.07 seconds
[+] Throughput: 3.29 bps
+-----+

```

ANALYSIS

- 1) No flow control protocol is considered here, hence the channel is assumed to be noise and disturbance free which isn't the practical scenario.
- 2) No particular packet format is considered, but again this is just a simulation environment.
- 3) All the outputs are taken in different files which makes the implementation very slow and also very resource intensive but on the other hand we get a cleaner and better analysis output well formatted in a file.

Though the above points can make a difference in the results in real world situations, the results are quite accurate otherwise.