

Home

Documentation

API Reference

Code Samples

Announcements

Models

Release Notes

FAQ

GitHub

Videos

Amazon Warehousing and Distribution API v2024-05-09 Reference

GET STARTED

- Welcome to SP-API Documentation
- What is the Selling Partner API?
- Selling Partner API Onboarding Overview

- Terminology
- Frequently Asked Questions

CHANGELOG

- SP-API Release Notes
- SP-API Deprecation Schedule
- SP-API Product Metadata Updates

Amazon Warehousing and Distribution API v2024-05-09 Reference

Retrieve and track AWD inbound shipments that contain items that are inbound to a distribution center.

The Selling Partner API for Amazon Warehousing and Distribution (AWD) provides programmatic access to information about AWD shipments and inventory.

Version information

Version : 2024-05-09

Contact information

Contact : Selling Partner API Developer Support

Contact URL : <https://sellercentral.amazon.com/gp/mws/contactus.html>

License information

License : Apache License 2.0

License URL : <https://www.apache.org/licenses/LICENSE-2.0>

URI scheme

Host : sellingpartnerapi-na.amazon.com

Schemes : HTTPS

Consumes

- application/json

Produces

- application/json

Operations

- [createInbound](#)
- [getInbound](#)
- [updateInbound](#)
- [cancelInbound](#)
- [confirmInbound](#)
- [getInboundShipment](#)
- [getInboundShipmentLabels](#)
- [updateInboundShipmentTransportDetails](#)

DIRECTORIES	
SP-API Models	
SP-API Seller Use Cases	
SP-API Vendor Use Cases	
Seller Central URLs	
Vendor Central URLs	
REGISTRATION	
SP-API Registration Overview	>
Developer Registration Request Status	
Third-Party Provider Registration	>
Service Provider Registration and Role Approval Process Overview	
Website Guidelines for Public Developers and Service Providers	
User Permissions for Service Providers	
Register your Application	
Update your Application Information	
Rotate your Application's LWA Credentials	>
View your Application Information and Credentials	
Learn How Sellers Authorize Service Providers	
Selling Partner API Roles	>
Policies and Agreements	
About Facial Data	
AUTHORIZATION	
Authorize Applications	>
Renew Authorizations	
Revoke Authorizations	
Authorization Limits	
Special Authorization Types	>

[checkInboundEligibility](#)
[listInboundShipments](#)
[listInventory](#)

Paths

POST /awd/2024-05-09/inboundOrders

Operation: createInbound

Description

Creates a draft AWD inbound order with a list of packages for inbound shipment. The operation creates one shipment per order.

Usage Plan:

Rate (requests per second)	Burst
1	1

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The preceding table indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may have higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Body	body <i>required</i>	Payload for creating an inbound order.	InboundOrderCreationData

Responses

HTTP Code	Description	Schema
201	<code>createInbound</code> 201 response. Headers : <code>Location</code> (string) : Location header with the order ID for the newly created inbound order. <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	InboundOrderReference

For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Consumes

- `application/json`

Produces

- `application/json`

Example HTTP request

Request body

JSON

```
{
  "externalReferenceId" : "TestReferenceId",
  "originAddress" : {
    "addressLine1" : "address_1",
    "addressLine2" : "address_2",
    "addressLine3" : "address_3",
    "city" : "City1",
    "countryCode" : "CC",
    "district" : "District1",
    "name" : "address_name",
    "postalCode" : "123456",
    "stateOrRegion" : "State1"
  },
  "packagesToInbound" : [ {
    "count" : 1,
    "distributionPackage" : {
      "contents" : {
        "products" : [ {
          "quantity" : 1,
          "sku" : "testPen"
        } ]
      }
    },
    "measurements" : {
      "dimensions" : {
        "height" : 1,
        "length" : 1,
        "unitOfMeasurement" : "INCHES",
        "width" : 1
      },
      "volume" : {
        "unitOfMeasurement" : "CUIN",
        "volume" : 1
      },
      "weight" : {
        "unitOfMeasurement" : "POUNDS",
        "weight" : 1
      }
    },
    "type" : "CASE"
  } ],
  "preferences" : {
    "destinationRegion" : "us-west"
  }
}
```

GET /awd/2024-05-09/inboundOrders/{orderId}

Operation: getInbound

Description

Retrieves an AWD inbound order.

Usage Plan:

Rate (requests per second)	Burst
2	2

INTEGRATION

Building Robust Amazon SP-API Applications

SP-API SDKs

Delete an Application From Your Developer Account

CALLING THE SP-API

Configuration Details

Call Structure

Development Tools

Performance Management

SOLUTION PROVIDER PORTAL

Manage Users in Solution Provider Portal

- Manage Your Business And Contact information in Solution Provider Portal
- Update Your Developer Profile in Solution Provider Portal
- Unify Your Developer Accounts
- Verify Your Identity in Solution Provider Portal
- API Usage Metrics in Solution Provider Portal

TUTORIALS

- Tutorial: Subscribe to the ORDER_CHANGE Notification
- Tutorial: Test Selling Partner API Endpoints
- Tutorial: Automate your SP-API Calls Using a C# SDK
- Tutorial: Automate your SP-API Calls Using a Java SDK
- Tutorial: Automate your SP-API Calls Using a JavaScript SDK for Node.js
- Tutorial: Automate your SP-API Calls Using a Python SDK
- Tutorial: Automate your SP-API Calls using a prebuilt C# SDK
- Tutorial: Automate your SP-API Calls using prebuilt Java SDK
- Tutorial: Automate your SP-API Calls using a prebuilt JavaScript SDK
- Tutorial: Automate your SP-API Calls using prebuilt PHP SDK
- Tutorial: Automate your SP-API calls using a prebuilt Python SDK
- Tutorial: Authorize Multiple Vendor Central Accounts with a Single SP-API Application
- Tutorial: Retrieve Merchant Shipping Templates
- Tutorial: Grant the SP-API Permission to an Amazon SQS Queue
- Tutorial: Retrieve and Pass a Purchase Order Number to a Carrier

TROUBLESHOOTING

- Troubleshoot SP-API Errors
- URL Encoding
- Resolve Common HTTP and Authorization Error Codes
- External Fulfillment Errors 
- Listings Items API Issues Troubleshooting 

SELLING PARTNER APPSTORE

- What is the Selling Partner Appstore?
- List Your App on the Selling Partner Appstore
- Edit Your Appstore Listing
- Check Listing Status
- Appstore Ratings and Reviews

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The preceding table indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may have higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Path	<code>orderId</code> <i>required</i>	The ID of the inbound order that you want to retrieve.	string

Responses

HTTP Code	Description	Schema
200	The 200 response for <code>getInbound</code> . Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	InboundOrder

For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Produces

- `application/json`

Example HTTP response

Response 200

JSON
<pre>{ "destinationDetails" : { "destinationAddress" : { "addressLine1" : "address_1", "addressLine2" : "address_2", "addressLine3" : "address_3", "city" : "Seattle", "countryCode" : "US", "county" : "Washington", "district" : "District1", "name" : "address_name", "phoneNumber" : "+14155552671", "postalCode" : "123456", "stateOrRegion" : "Washington" }, "destinationRegion" : "us-east", "shipmentId" : "TestShipmentId" }, "createdAt" : "2023-06-07T12:12:09.061Z", "externalReferenceId" : "TestReferenceId", "orderId" : "TestOrderId", "orderStatus" : "DRAFT", "originAddress" : { "addressLine1" : "address_1", "addressLine2" : "address_2",</pre>

Press Releases and Promotions	
SERVICE PROVIDER NETWORK	
List Your Service	
SECURITY AND COMPLIANCE	
SP-API Security and Compliance Overview	
Amazon Selling Partner API Guard Implementation Guide	>
VAT Calculation Service	>
Amazon Seller Data Access	
Best Practices	>
A+ CONTENT API	
A+ Content API	>

```
    "addressLine3" : "address_3",
    "city" : "Seattle",
    "countryCode" : "US",
    "county" : "Washington",
    "district" : "District1",
    "name" : "address_name",
    "phoneNumber" : "+14155552671",
    "postalCode" : "123456",
    "stateOrRegion" : "Washington"
  },
  "packagesToInbound" : [ {
    "count" : 1,
    "distributionPackage" : {
      "contents" : {
        "packages" : [ ],
        "products" : [ {
          "quantity" : 1,
          "sku" : "testPen",
          "expiration" : "2025-06-07T12:12:09.061Z",
          "prepDetails" : {
            "prepCategory" : "PERFORATED",
            "prepOwner" : "AMAZON",
            "labelOwner" : "SELF",
            "prepInstructions" : [ {
              "prepType" : "ITEM_POLYBAGGING",
              "prepOwner" : "AMAZON"
            } ]
          }
        } ]
      }
    } ]
  },
  "measurements" : {
    "dimensions" : {
      "height" : 2.54,
      "length" : 2.54,
      "width" : 2.54
    },
    "weight" : 0.453592
  }
}
```

PUT /awd/2024-05-09/inboundOrders/{orderId}

Operation: updateInbound

Description

Updates an AWD inbound order that is in `DRAFT` status and not yet confirmed. Use this operation to update the `packagesToInbound`, `originAddress` and `preferences` attributes.

Usage Plan:

Rate (requests per second)	Burst
1	1

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The preceding table indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may have higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Path	<code>orderId</code> <i>required</i>	The ID of the inbound order that you want to update.	string

A+ Content Examples

AMAZON WAREHOUSING AND DISTRIBUTION API

Amazon Warehousing and Distribution API >

Amazon Warehousing and Distribution API v2024-05-09 Reference

APP INTEGRATIONS API

App Integrations API v

- Create and onboard an app notification template
- Sample sandbox notification templates
- Send an app notification
- Record app notification feedback
- Delete app notifications

APPLICATION MANAGEMENT API

Application Management API >

CATALOG ITEMS API

Catalog Items API >

- Catalog Items API Rate Limits
- Catalog Items API v2022-04-01 Reference

CUSTOMER FEEDBACK API

Customer Feedback API >

Customer Feedback API Rate Limits

DATA KIOSK

Data Kiosk API >

Data Kiosk Schema Explorer User Guide

Type	Name	Description	Schema
Body	body required	Represents an AWD inbound order.	InboundOrder

Responses

HTTP Code	Description	Schema
204	The 204 response for updateInbound . Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	No Content

For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Consumes

- application/json

Produces

- application/json

Example HTTP request

Request body

JSON	<pre>{ "destinationDetails" : { "destinationAddress" : { "addressLine1" : "address_1", "addressLine2" : "address_2", "addressLine3" : "address_3", "city" : "Seattle", "countryCode" : "US", "county" : "Washington", "district" : "District1", "name" : "address_name", "phoneNumber" : "+14155552671", "postalCode" : "123456", "stateOrRegion" : "Washington" }, "destinationRegion" : "us-east", "shipmentId" : "TestShipmentId" }, "createdAt" : "2023-06-07T12:12:09.061Z", "externalReferenceId" : "TestReferenceId", "orderId" : "TestOrderId", "orderStatus" : "DRAFT", "originAddress" : { "addressLine1" : "address_1", "addressLine2" : "address_2", "addressLine3" : "address_3", "city" : "Seattle", "countryCode" : "US", "county" : "Washington", "district" : "District1",</pre>
------	---

Data Kiosk Query Processing Finished Notification

Building Data Kiosk workflows guide

Vendor Analytics Dataset Use Case Guide

Schedule Data Kiosk Queries

DELIVERY BY AMAZON API

Delivery by Amazon API

EASY SHIP API

Easy Ship API

EXTERNAL FULFILLMENT

External Fulfillment Inventory API

External Fulfillment Returns API

External Fulfillment Shipping API

External Fulfillment Errors

External Fulfillment APIs Rate Limits

FULFILLMENT BY AMAZON (FBA)

FBA Inventory API

FBA Inventory Dynamic Sandbox Guide

FEEDS API

Feeds API

Feed Type Values

```
"name" : "address_name",
"phoneNumber" : "+14155552671",
"postalCode" : "123456",
"stateOrRegion" : "Washington"
},
"packagesToInbound" : [ {
  "count" : 1,
  "distributionPackage" : {
    "contents" : {
      "packages" : [ ],
      "products" : [ {
        "quantity" : 1,
        "sku" : "testPen",
        "expiration" : "2025-06-07T12:12:09.061Z",
        "prepDetails" : {
          "prepCategory" : "PERFORATED",
          "prepOwner" : "AMAZON",
          "labelOwner" : "SELF",
          "prepInstructions" : [ {
            "prepType" : "ITEM_POLYBAGGING",
            "prepOwner" : "AMAZON"
          } ]
        }
      } ]
    }
  }
} ],
"measurements" : {
  "dimensions" : {
    "height" : 2.54,
    "length" : 2.54,
    "unitOfMeasurement" : "CENTIMETERS",
    "width" : 2.54
  },
  "weight" : {
    "unitOfMeasurement" : "KILOGRAMS",
    "weight" : 0.453592
  }
}
},
"updatedAt" : "2023-06-07T12:12:09.061Z",
"preferences" : {
  "destinationRegion" : "us-west"
}
```

POST /awd/2024-05-09/inboundOrders/{orderId}/cancellation

Operation: **cancelInbound**

Description:

Cancels an Amazon inbound order and its associated shipment.

Usage Plan:

Rate (requests per second)	Burst
1	1

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The preceding table indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may have higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Path	orderId <i>required</i>	The ID of the inbound order you want to cancel.	string

Responses

HTTP Code	Description	Schema
204	The 204 response for <code>cancelInbound</code> . Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit	No Content

Feeds JSON Schemas	↗
Feeds API Best Practices	
Feeds API FAQ	
Feeds API Rate Limits	
FINANCES	
Finances API	>

Transfers API	>
---------------	---

FULFILLMENT INBOUND API	
Fulfillment Inbound API	>

Fulfillment Inbound API FAQ	
Migrating Fulfillment Inbound workflows	
Fulfillment Inbound API Rate Limits	
FULFILLMENT OUTBOUND API	
Fulfillment Outbound Dynamic Sandbox Guide	
Fulfillment Outbound API	>

HTTP Code	Description	Schema
	(requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	

For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Produces

- `application/json`

POST /awd/2024-05-09/inboundOrders/{orderId}/confirmation

Operation: `confirmInbound`

Description

Confirms an AWD inbound order in `DRAFT` status.

Usage Plan:

Rate (requests per second)	Burst
1	1

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may see higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Path	<code>orderId</code> <i>required</i>	The ID of the inbound order that you want to confirm.	string

Responses

HTTP Code	Description	Schema
204	The 204 response for <code>confirmInbound</code> . Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	No Content

For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Produces

- `application/json`

GET /awd/2024-05-09/inboundShipments/{shipmentId}

Operation: `getInboundShipment`

Description

Retrieves an AWD inbound shipment.

Usage Plan:

Rate (requests per second)	Burst
2	2

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may see higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#)

Parameters

Type	Name	Description	Schema
Path	shipmentId <i>required</i>	ID for the shipment. A shipment contains the cases being inbounded. minLength : 1	string
Query	skuQuantities <i>optional</i>	If equal to <code>SHOW</code> , the response includes the shipment SKU quantity details. Defaults to <code>HIDE</code> , in which case the response does not contain SKU quantities	enum (SkuQuantities)

Responses

HTTP Code	Description	Schema
200	The 200 response for <code>getInboundShipment</code> . Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	InboundShipment

For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Produces

- `application/json`

GET /awd/2024-05-09/inboundShipments/{shipmentId}/labels

Operation: `getInboundShipmentLabels`

Description

Fulfillment Outbound API Rate Limits

MCF Best Practices

INVOICING

Invoices API

Invoices API FAQ

LISTINGS

Listings Items API

Listings Items API Rate Limits

Listings Restrictions API	>
Listings Restrictions API Rate Limits	
Manage Product Listings with the Selling Partner API	
Building Listings Management Workflows Guide	
Understanding Amazon listing status and seller-fulfilled inventory management	
Listings Management Workflow Migration	>
Manage Amazon Haul, Advanced Multiple-Offer, and Multiple-Fulfillment Use Cases	
Listings APIs FAQ	
Product Type Definitions API	>

Product Type Definitions API Rate Limits

MERCHANT FULFILLMENT API	
Merchant Fulfillment API	>

MESSAGING API	
Messaging API	>

NOTIFICATIONS API	
Notifications API	>

Notification Type Values

Retrieves the box labels for a shipment ID that you specify. This is an asynchronous operation. If the label status is `GENERATED` , then the label URL is available.

Usage Plan:

Rate (requests per second)	Burst
1	2

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The preceding table indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may have higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Path	shipmentId <i>required</i>	ID for the shipment. minLength : 1	string
Query	pageType <i>optional</i>	Page type for the generated labels. The default is <code>PLAIN_PAPER</code> .	enum (PageType)
Query	formatType <i>optional</i>	The format type of the output file that contains your labels. The default format type is <code>PDF</code> .	enum (FormatType)

Responses

HTTP Code	Description	Schema
200	The 200 response for <code>getInboundShipmentLabels</code> . Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ShipmentLabels

For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Produces

- `application/json`

PUT /awd/2024-05-09/inboundShipments/{shipmentId}/transport

Operation: `updateInboundShipmentTransportDetails`

Description

Updates transport details for an AWD shipment.

Usage Plan:

Tutorial: Subscribe to the ORDER_CHANGE Notification

ORDERS API

Orders API

Tutorial: Retrieve and Pass a Purchase Order Number to a Carrier

Orders API Migration Guide

Orders API Rate Limits

PRODUCT FEES API

Product Fees API

PRODUCT PRICING API

Product Pricing API

Product Pricing API and Notifications FAQ

Price Adjustment Automation Workflows Guide

Manage automated pricing rules with SP-API

REPLENISHMENT API

Replenishment API

↗

>

>

>

>

Rate (requests per second)	Burst
1	1

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may see higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Path	shipmentId <i>required</i>	The shipment ID. minLength : 1	string
Body	body <i>required</i>	Transportation details for the shipment.	TransportationDetails

Responses

HTTP Code	Description	Schema
204	The 204 response for <code>updateInboundShipmentTransportDetails</code> . Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	No Content

For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Consumes

- `application/json`

Produces

- `application/json`

Example HTTP request

Request body

```
JSON
{
  "trackingDetails" : [ {
    "carrierCode" : {
      "carrierCodeType" : "SCAC"
    },
    "bookingId" : "TRACKING_ID"
  } ]
}
```

POST /awd/2024-05-09/inboundEligibility

Operation: `checkInboundEligibility`

REPORTS API

Reports API

Report Type Values

Reports JSON Schemas

Reports API FAQ

SALES API

Sales API

SELLER WALLET API

Seller Wallet API

Seller Wallet API Rate Limits

SELLERS API

Sellers API

SERVICES API

Description

> Determines if the packages you specify are eligible for an AWD inbound order and contains error details for ineligible packages.

Usage Plan:

Rate (requests per second)	Burst
1	1

> The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The preceding table indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may have higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Body	<code>body</code> <i>required</i>	Represents the packages you want to inbound.	InboundPackages

Responses

HTTP Code	Description	Schema
200	The 200 response for <code>checkInboundEligibility</code> . Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	InboundEligibility

> For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Consumes

- >
 - `application/json`

Produces

- `application/json`

Example HTTP request

Request body

JSON
<pre>{ "packagesToInbound" : [{ "count" : 1, "distributionPackage" : { "contents" : { "products" : [{ "quantity" : 1, "sku" : "testPen" }] } }]</pre>

Services API	>
SHIPMENT INVOICING API	
Shipment Invoicing API	>
SHIPPING API	
Shipping API v2 Resources	↗
Shipping API v1 Reference	
SOLICITATIONS API	
Solicitations API	>
SUPPLY SOURCES API	
Supply Sources API	>
Multi-Location Inventory Integration Guide	
Supply Sources API Rate Limits	
TOKENS API	
Tokens API	>
UPLOADS API	
Uploads API	>

```
    } ]
  },
  "measurements" : {
    "dimensions" : {
      "height" : 1,
      "length" : 1,
      "unitOfMeasurement" : "INCHES",
      "width" : 1
    },
    "volume" : {
      "unitOfMeasurement" : "CUIN",
      "volume" : 1
    },
    "weight" : {
      "unitOfMeasurement" : "POUNDS",
      "weight" : 1
    }
  },
  "type" : "CASE"
}
} ]
}
```

GET /awd/2024-05-09/inboundShipments

Operation: listInboundShipments

Description

Retrieves a summary of all the inbound AWD shipments associated with a merchant, with the ability to apply optional filters.

Usage Plan:

Rate (requests per second)	Burst
1	1

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may see higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema	Default
Query	sortBy <i>optional</i>	Field to sort results by. By default, the response will be sorted by UPDATED_AT.	enum (SortBy)	-
Query	sortOrder <i>optional</i>	Sort the response in ASCENDING or DESCENDING order. By default, the response will	enum (SortOrder)	-

	Type	Name	Description	Schema	Default
VEHICLES API			be sorted in DESCENDING order.		
Vehicles API >	Query	shipmentStatus optional	Filter by inbound shipment status.	enum (ShipmentStatus)	-
Vehicles API Rate Limits					
VENDOR DIRECT FULFILLMENT APIS					
Vendor Direct Fulfillment Dynamic Sandbox Guide					
Vendor Direct Fulfillment Workflow Guide					
SP-API Bill-to-Party Addresses					
VENDOR DIRECT FULFILLMENT TRANSACTION STATUS API					
Vendor Direct Fulfillment Transaction Status API >	Query	updatedAfter optional	List the inbound shipments that were updated after a certain time (inclusive). The date must be in ISO 8601 format.	string (date-time)	-
VENDOR DIRECT FULFILLMENT INVENTORY API					
Vendor Direct Fulfillment Inventory API >	Query	updatedBefore optional	List the inbound shipments that were updated before a certain time (inclusive). The date must be in ISO 8601 format.	string (date-time)	-
VENDOR DIRECT FULFILLMENT ORDERS API					
Vendor Direct Fulfillment Orders API >					
VENDOR DIRECT FULFILLMENT SHIPPING API					
Vendor Direct Fulfillment Shipping API >	Query	maxResults optional	Maximum number of results to return. Minimum : 1 Maximum : 200	integer (int32)	25
VENDOR DIRECT FULFILLMENT PAYMENTS API					
Vendor Direct Fulfillment Payments API >	Query	nextToken optional	A token that is used to retrieve the next page of results. The response includes nextToken when the number of results exceeds the specified maxResults value. To get the next page of results, call the operation with this token and include	string	-
VENDOR RETAIL PROCUREMENT INVOICES API					

Vendor Retail Procurement Invoices API

>

VENDOR RETAIL PROCUREMENT ORDERS API

Vendor Retail Procurement Orders API

>

VENDOR RETAIL PROCUREMENT SHIPMENTS API

Vendor Retail Procurement Shipments API

>

VENDOR RETAIL PROCUREMENT TRANSACTION STATUS API

Vendor Retail Procurement Transaction Status API

>

Type	Name	Description	Schema	Default
		the same arguments as the call that produced the token. To get a complete list, call this operation until <code>nextToken</code> is null. Note that this operation can return empty pages.		

Responses

HTTP Code	Description	Schema
200	The 200 response for <code>listInboundShipments</code> . Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ShipmentListing

For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Produces

- `application/json`

GET /awd/2024-05-09/inventory

Operation: `listInventory`

Description

Lists AWD inventory associated with a merchant with the ability to apply optional filters.

Usage Plan:

Rate (requests per second)	Burst
2	2

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may see higher rate and burst values than those shown here. For more information, refer to [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters



Type	Name	Description	Schema	Default
Query	sku <i>optional</i>	Filter by seller or merchant SKU for the item.	string	-
Query	sortOrder <i>optional</i>	Sort the response in <code>ASC</code> <code>ENDING</code> or <code>DESCENDING</code> order.	enum (SortOrder)	-
Query	details <i>optional</i>	Set to <code>SHOW</code> to return summaries with additional inventory details. Defaults to <code>HIDE</code> , which returns only inventory summary totals.	enum (Details)	-
Query	nextToken <i>optional</i>	A token that is used to retrieve the next page of results. The response includes <code>nextToken</code> when the number of results exceeds the specified <code>maxResults</code> value. To get the next page of results, call the operation with this token and include the same arguments as the call that produced the token. To get a complete list, call this operation until <code>nextToken</code> is null. Note that this operation can return empty pages.	string	-
Query	maxResults <i>optional</i>	Maximum number of results to return. Minimum : 1 Maximum : 200	integer (int32)	25

Responses

HTTP Code	Description	Schema
200	The 200 response for <code>listInventory</code> . Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	InventoryListing

For error status codes, descriptions and schemas, see [Error responses and schemas](#).

Produces

- application/json

Error Responses and Schemas

This table contains HTTP status codes and associated information for error responses.

HTTP Code	Description	Schema
400	Request has missing or invalid parameters and cannot be parsed. Headers: <code>x-amzn-RateLimit-Limit</code> (string):Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList
403	Indicates that access to the resource is forbidden. Possible reasons include Access Denied, Unauthorized, Expired Token, or Invalid Signature. Headers: <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList
404	The resource specified does not exist. Headers: <code>x-amzn-RateLimit-Limit</code> (string):Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList
409	<code>ConflictException</code> 409 response. Headers: <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList
413	The request size exceeded the maximum accepted size. Headers: <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList
415	The request payload is in an unsupported format. Headers: <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList
429	The frequency of requests was greater than allowed. Headers: <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList
500	An unexpected condition occurred that prevented the server from fulfilling the request. Headers: <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList
503	Temporary overloading or maintenance of the server. Headers:	ErrorList

HTTP Code	Description	Schema
	<code>x-amzn-RequestId</code> (string):Unique request reference identifier.	

Definitions

Address

Shipping address that represents the origin or destination location.

Name	Description	Schema
addressLine1 <i>required</i>	First line of the address text.	string
addressLine2 <i>optional</i>	Optional second line of the address text.	string
addressLine3 <i>optional</i>	Optional third line of the address text.	string
city <i>optional</i>	Optional city where this address is located.	string
countryCode <i>required</i>	Two-digit, ISO 3166-1 alpha-2 formatted country code where this address is located.	string
county <i>optional</i>	Optional county where this address is located. Example : "Washington"	string
district <i>optional</i>	Optional district where this address is located.	string
name <i>required</i>	Name of the person, business, or institution at this address.	string
phoneNumber <i>optional</i>	Optional E.164-formatted phone number for an available contact at this address. Example : "+14155552671"	string
postalCode <i>optional</i>	Optional postal code where this address is located.	string
stateOrRegion <i>required</i>	State or region where this address is located. Note that this is contextual to the specified country code.	string

CarrierCode

Identifies the carrier that will deliver the shipment.

Name	Description	Schema
carrierCodeType <i>optional</i>	Denotes the carrier type.	CarrierCodeType
carrierCodeValue <i>optional</i>	Value of the carrier code. Example : "TestCarrierCode"	string

CarrierCodeType

Denotes the type for the carrier.

Type : enum

Value	Description
SCAC	Standard Carrier Alpha Code. Refer to What is a Standard Carrier Alpha Code for more information.

DestinationDetails

Destination details of an inbound order based on the assigned region and DC for the order.

Name	Description	Schema
destinationAddress <i>optional</i>	Destination address of the AWD facility where the shipment will be shipped to	Address
destinationRegion <i>optional</i>	Assigned region where the order will be shipped. This can differ from what was passed as preference. AWD currently supports following region IDs: [us-west, us-east, us-southcentral, us-southeast] Example : "us-west"	string
shipmentId <i>optional</i>	Unique ID of the confirmed shipment being shipped to the assigned destination. This will be available only after an inbound order is confirmed and can be used to track the shipment. minLength : 1	string

DimensionUnitOfMeasurement

Unit of measurement for package dimensions.

Type : enum

Value	Description
INCHES	Denotes package dimensions in inches.
CENTIMETERS	Denotes package dimensions in centimeters.

DistributionPackage

Represents an AWD distribution package.

Name	Description	Schema
contents <i>required</i>	The contents appropriate for the type.	DistributionPackageContents
measurements <i>required</i>	Measurements of a package, including weight, volume, and dimensions.	MeasurementData
type <i>required</i>	Type of distribution package.	DistributionPackageType

DistributionPackageContents

Represents the contents inside a package, which can be products or a nested package.

Name	Description	Schema
packages <i>optional</i>	This is required only when <code>DistributionPackageType=PALLET</code> .	< DistributionPackageQuantity > array
products <i>optional</i>	This is required only when <code>DistributionPackageType=CASE</code> .	< ProductQuantity > array

DistributionPackageQuantity

Represents a distribution package with its respective quantity.

Name	Description	Schema
count <i>required</i>	Number of cases or pallets with the same package configuration.	integer (int32)
distributionPackage <i>required</i>	Represents an AWD distribution package.	DistributionPackage

DistributionPackageType

Type of distribution packages.

Type : enum

Value	Description
CASE	Package type <code>CASE</code> .
PALLET	Package type <code>PALLET</code> . Currently, the <code>PALLET</code> package type is not supported.

Error

Error response returned when the request is unsuccessful.

Name	Description	Schema
code <i>required</i>	An error code that identifies the type of error that occurred.	string
details <i>optional</i>	Additional details that can help the caller understand or fix the issue.	string
message <i>required</i>	A message that describes the error condition.	string

ErrorList

This exception is thrown when client inputs are invalid.

Name	Description	Schema
errors <i>required</i>	A list of errors describing the failures.	< Error > array

InboundEligibility

Represents the eligibility status of the inbound packages.

Name	Description	Schema
ineligibilityReasons <i>optional</i>	If there are order level eligibility issues, then this list will contain those error codes and descriptions.	< OrderIneligibilityReason > array
packagesToInbound <i>required</i>	Details on SKU eligibility for each inbound package.	< SkuEligibility > array
previewedAt <i>required</i>	Timestamp when the eligibility check is performed.	string (date-time)
status <i>required</i>	Enum denoting the package inbound eligibility.	InboundEligibilityStatus

InboundEligibilityStatus

Enum denoting the package inbound eligibility.

Type : enum

Value	Description
ELIGIBLE	Eligible to inbound.
INELIGIBLE	Ineligible to inbound.

InboundOrder

Represents an AWD inbound order.

Name	Description	Schema
createdAt <i>required</i>	Date when this order was created.	string (date-time)
destinationDetails <i>optional</i>	Destination details of an inbound order based on the assigned region and DC for the order.	DestinationDetails
externalReferenceId <i>optional</i>	Reference ID that can be used to correlate the order with partner resources. Example : "TestReferenceId"	string
orderId <i>required</i>	Inbound order ID.	string

Name	Description	Schema
orderStatus <i>required</i>	Inbound order status.	InboundStatus
originAddress <i>required</i>	Origin address from where the inbound order will be shipped.	Address
packagesToInbound <i>required</i>	List of packages to be inbounded.	< DistributionPackageQuantity > array
preferences <i>optional</i>	Preferences that can be passed in context of an inbound order	InboundPreferences
updatedAt <i>optional</i>	Date when this order was last updated.	string (date-time)

InboundOrderCreationData

Payload for creating an inbound order.

Name	Description	Schema
externalReferenceId <i>optional</i>	Reference ID that can be used to correlate the order with partner resources. Example : "TestReferenceId"	string
originAddress <i>required</i>	Origin address from where the inbound order will be shipped.	Address
packagesToInbound <i>required</i>	List of packages to be inbounded. Example : [{ "count" : 1, "distributionPackage" : { "contents" : { "products" : [{ "quantity" : 1, "sku" : "testPen" }] }, "measurements" : { "dimensions" : { "height" : 1, "length" : 1, "unitOfMeasurement" : "INCHES", "width" : 1 }, "volume" : { "unitOfMeasureme	< DistributionPackageQuantity > array

Name	Description	Schema
	<pre>nt" : "CUIN", "volume" : 1 }, "weight" : { "unitOfMeasurement" : "POUNDS", "weight" : 1 }
 },
 "type" : "CASE"
 }
 }]</pre>	
preferences <i>optional</i>	Preferences that can be passed in context of an inbound order	InboundPreferences

InboundOrderReference

A response that contains the reference identifiers for the newly created or updated inbound order. Consists of an order ID and version.

Name	Description	Schema
orderId <i>required</i>	Order ID of the inbound order.	string

InboundPackages

Represents the packages to inbound.

Name	Description	Schema
packagesToInbound <i>required</i>	List of packages to be inbounded. Example : [{
 "count" : 1,
 "distributionPackage" : {
 "contents" : { "products" : [{"quantity" : 1,"sku" : "testPen" }]
 },
 "measurements" : { "dimensions" : {"height" : 1,"length" : 1,"unitOfMeasurement" : "INCHES","width" : 1 }, "volume" : {"unitOfMeasurement" : "CUIN","volume" : 1 }, "weight" : {"unitOfMeasurement" : "POUNDS","weight" : 1 }
 },
 "type" : "CASE"
 }
 }]	<pre>< DistributionPackageQuantity > array</pre>

InboundPreferences

Preferences that can be passed in context of an inbound order

Name	Description	Schema
destinationRegion <i>optional</i>	Pass a preferred region so that the inbound order can be shipped to an AWD warehouse located in that region. This doesn't guarantee the order to be assigned in the specified destination region as it depends on warehouse capacity availability. AWD currently supports following region IDs: [us-west, us-east, us-southcentral, us-southeast]	string

InboundShipment

Represents an AWD inbound shipment.

Name	Description	Schema
carrierCode <i>optional</i>	The shipment carrier code.	CarrierCode
createdAt <i>optional</i>	Timestamp when the shipment was created. The date is returned in ISO 8601 format.	string (date-time)
destinationAddress <i>required</i>	Destination address for this shipment.	Address
externalReferenceId <i>optional</i>	Client-provided reference ID that can correlate this shipment to client resources. For example, to map this shipment to an internal bookkeeping order record. Example : "TestReferenceId"	string
orderId <i>required</i>	The AWD inbound order ID that	string

Name	Description	Schema
	this inbound shipment belongs to. minLength : 1	
originAddress <i>required</i>	Origin address for this shipment.	Address
receivedQuantity <i>optional</i>	Quantity received (at the receiving end) as part of this shipment.	< InventoryQuantity > array
shipBy <i>optional</i>	Timestamp when the shipment will be shipped.	string (date-time)
shipmentContainerQuantities <i>required</i>	Packages that are part of this shipment.	< DistributionPackageQuantity > array
shipmentId <i>required</i>	Unique shipment ID. minLength : 1	string
shipmentSkuQuantities <i>optional</i>	Quantity details at SKU level for the shipment. This attribute will only appear if the skuQuantities parameter in the request is set to SHOW.	< SkuQuantity > array
destinationRegion <i>optional</i>	Assigned region where the order will be shipped. This can differ from what was passed as preference. AWD currently supports	string

Name	Description	Schema
	following region IDs: [us-west, us-east, us-southcentral, us-southeast] Example : "us-west"	
shipmentStatus <i>required</i>	Current status of this shipment.	InboundShipmentStatus
trackingId <i>optional</i>	Carrier-unique tracking ID for this shipment. minLength : 1	string
updatedAt <i>optional</i>	Timestamp when the shipment was updated. The date is returned in ISO 8601 format.	string (date-time)
warehouseReferenceId <i>optional</i>	An AWD-provided reference ID that you can use to interact with the warehouse. For example, a carrier appointment booking. Example : "TestWarehouseReferenceId"	string

InboundShipmentStatus

Possible shipment statuses used by shipments.

Type : enum

Value	Description
CREATED	Shipment is created but has not yet shipped.

Value	Description
SHIPPED	Shipment was picked up by the carrier or was dropped off with the carrier.
IN_TRANSIT	The carrier has notified AWD that the shipment is in transit between origin and destination node.
RECEIVING	The shipment has been partially received.
DELIVERED	The shipment has reached the destination node and has been delivered to the facility yard. The shipment receive process at the warehouse will start soon.
CLOSED	No more actions required on the shipment. This is a final state.
CANCELLED	Shipment has been cancelled. This is a final state.

InboundShipmentSummary

Summary for an AWD inbound shipment containing the shipment ID, which can be used to retrieve the actual shipment.

Name	Description	Schema
createdAt <i>optional</i>	Timestamp when the shipment was created.	string (date-time)
externalReferenceId <i>optional</i>	Optional client-provided reference ID that can be used to correlate this shipment with client resources. For example, to map this shipment to an internal bookkeeping order record. Example : "TestReferenceId"	string
orderId <i>required</i>	The AWD inbound order ID that this inbound shipment belongs to. minLength : 1	string
shipmentId <i>required</i>	A unique shipment ID. minLength : 1	string
shipmentStatus <i>required</i>	Possible shipment statuses used by shipments.	InboundShipmentStatus
updatedAt <i>optional</i>	Timestamp when the shipment was updated.	string (date-time)

InboundStatus

The supported statuses for an inbound order.

Type : enum

Value	Description
DRAFT	A newly created inbound order will start in this state.
VALIDATING	The order is in this state while being updated. Once updated, the order will enter the updated state.
CONFIRMED	The order enters this state as soon as the order is confirmed.
CLOSED	The order enters this state when all associated shipments are closed.
EXPIRED	The order enters this state if it is not confirmed within a time limit.
CANCELLED	The order enters this state when it is cancelled.

ExpirationDetails

The expiration details of the inventory. This object will only appear if the details parameter in the request is set to `SHOW`.

Name	Description	Schema
expiration <i>optional</i>	The expiration date of the SKU.	string (date-time)
onhandQuantity <i>optional</i>	The quantity that is present in AWD.	integer (int64)

InventoryDetails

Additional inventory details. This object is only displayed if the details parameter in the request is set to `SHOW`.

Name	Description	Schema
availableDistributableQuantity <i>optional</i>	Quantity that is available for downstream channel replenishment.	integer (int64)
replenishmentQuantity <i>optional</i>	Quantity that is in transit from AWD and has not yet been received at FBA.	integer (int64)
reservedDistributableQuantity <i>optional</i>	Quantity that is reserved for a downstream channel replenishment order that is being prepared for shipment.	integer (int64)

InventoryListing

AWD inventory payload.

Name	Description	Schema
inventory <i>required</i>	List of inventory summaries.	< InventorySummary > array
nextToken <i>optional</i>	A token that is used to retrieve the next page of results. The response includes <code>nextToken</code> when the number of	string

Name	Description	Schema
	results exceeds the specified <code>maxResults</code> value. To get the next page of results, call the operation with this token and include the same arguments as the call that produced the token. To get a complete list, call this operation until <code>nextToken</code> is null. Note that this operation can return empty pages. Example : "SampleToken"	

InventoryQuantity

Quantity of inventory with an associated measurement unit context.

Name	Description	Schema
quantity <i>required</i>	Quantity of the respective inventory.	number
unitOfMeasurement <i>required</i>	Unit of measurement for the inventory.	InventoryUnitOfMeasurement

InventorySummary

Summary of inventory per SKU.

Name	Description	Schema
expirationDetails <i>optional</i>	The expiration details of the inventory. This object will only appear if the <code>details</code> parameter in the request is set to <code>SHOW</code> .	< ExpirationDetails > array
inventoryDetails <i>optional</i>	Additional inventory details. This object is only displayed if the details parameter in the request is set to <code>SHOW</code> .	InventoryDetails
sku <i>required</i>	The seller or merchant SKU.	string
totalInboundQuantity <i>optional</i>	Total quantity that is in-transit from the seller and has not yet been received at an AWD Distribution Center	integer (int64)
totalOnhandQuantity <i>optional</i>	Total quantity that is present in AWD distribution centers.	integer (int64)

InventoryUnitOfMeasurement

Unit of measurement for the inventory.

Type : enum

Value	Description
PRODUCT_UNITS	Measures a discrete amount of product units.
CASES	Measures a discrete amount of cases.
PALLETS	Measures a discrete amount of pallets.

LabelOwner

The entity that labels the products.

Type : enum

Value	Description
AMAZON	Amazon labels the products.
SELF	The seller labels the products.

LabelStatus

The status of your label.

Type : enum

Value	Description
GENERATING	Labels are being generated.
GENERATED	Labels are generated.
GENERATION_FAILED	Label generation failed.
NOT_READY	Not yet ready to start label generation.

MeasurementData

Package weight and dimension.

Name	Description	Schema
dimensions <i>optional</i>	Dimensions of the package. Dimensions are required when creating an inbound or outbound order.	PackageDimensions
volume <i>optional</i>	Volume of the package.	PackageVolume
weight <i>required</i>	Weight of the package.	PackageWeight

OrderIneligibilityReason

Represents one ineligibility reason for the order (there can be multiple reasons).

Name	Description	Schema
code <i>required</i>	Code for the order ineligibility. Example : "INVALID_MSKU"	string
description <i>required</i>	Description detailing the ineligibility reason of the order. Example : "The MSKU passed as part of order is invalid"	string

PackageDimensions

Dimensions of the package.

Name	Description	Schema
height <i>required</i>	Height of the package.	number (double)
length <i>required</i>	Length of the package.	number (double)
unitOfMeasurement <i>required</i>	Unit of measurement for package dimensions.	DimensionUnitOfMeasurement
width <i>required</i>	Width of the package.	number (double)

PackageVolume

Represents the volume of the package with a unit of measurement.

Name	Description	Schema
unitOfMeasurement <i>required</i>	Unit of measurement for the package volume.	VolumeUnitOfMeasurement
volume <i>required</i>	The package volume value.	number (double)

PackageWeight

Represents the weight of the package with a unit of measurement.

Name	Description	Schema
unitOfMeasurement <i>required</i>	Unit of measurement for the package weight.	WeightUnitOfMeasurement
weight <i>required</i>	The package weight value.	number (double)

PrepDetails

The preparation details for a product. This contains the prep category, prep owner, and label owner.

Prep instructions are generated based on the specified category.

Name	Description	Schema
labelOwner <i>optional</i>	The entity that labels the products.	LabelOwner
prepCategory <i>optional</i>	The preparation category for shipping an item to Amazon's fulfillment network.	PrepCategory

Name	Description	Schema
prepInstructions <i>optional</i>	Contains information about the preparation of the inbound products. The system auto-generates this field with the use of the <code>prepCategory</code> , and if you attempt to pass a value for this field, the system will ignore it.	< PrepInstruction > array
prepOwner <i>optional</i>	The owner of the preparations, if special preparations are required.	PrepOwner

PrepCategory

The preparation category for shipping an item to Amazon's fulfillment network.

Type : enum

Value	Description
ADULT	Displays potentially offensive material such as profanity or nudity.
BABY	Made for a child aged three years or younger, packaging with cutouts greater than one square inch.
FC_PROVIDED	A prep type has been defined by the Fulfillment Center. This value is provided by Amazon and cannot be used as an input.
FRAGILE	Glass or otherwise fragile, or a liquid in a glass container.
GRANULAR	Made of powder, pellets, or granular material.
HANGER	Made of cloth or fabric and intended to be put on a hanger.
LIQUID	Liquid or viscous without a double seal.
PERFORATED	In packaging that has a perforated opening.
SET	Multiple items that are sold as one unit.
SHARP	Sharp and easily exposed, not already contained in protective packaging.
SMALL	Longest side less than 2 1/8 inches (width of a credit card).
TEXTILE	Made of cloth or fabric that could be damaged by dirt, dust, moisture, or liquid.
NO_PREP	Does not require prep.
UNKNOWN	An unknown prep category was found. This value is provided by Amazon and cannot be used as an input.

PrepInstruction

Information pertaining to the preparation of inbound products.

Name	Description	Schema
prepOwner <i>optional</i>	The owner of the preparations, if special preparations are required.	PrepOwner

Name	Description	Schema
prepType <i>optional</i>	The type of preparation to be done. For more information about preparing items, refer to Prep guidance on Seller Central.	string

PrepOwner

The owner of the preparations, if special preparations are required.

Type : enum

Value	Description
AMAZON	Amazon owns the preparation.
SELF	The seller owns the preparation

ProductAttribute

Product instance attribute that is not described at the SKU level in the catalog.

Name	Description	Schema
name <i>optional</i>	Product attribute name. Example : "TestAttribute"	string
value <i>optional</i>	Product attribute value. Example : "TestAttributeValue"	string

ProductQuantity

Represents a product with the SKU details and the corresponding quantity.

Name	Description	Schema
attributes <i>optional</i>	Contains attributes for this instance of the product. For example, item color, or other attributes that distinguish the product beyond the SKU. This is metadata for the product and Amazon does not process this data. Example : {"name" : "TestAttribute", "value" : "TestAttributeValue"}	< ProductAttribute > array
quantity <i>required</i>	Product quantity.	integer (int32)
sku <i>required</i>	The seller or merchant SKU.	string
expiration <i>optional</i>	The expiration date for the SKU. Values are in ISO 8601 date-time format.	string (date-time)
prepDetails <i>optional</i>	Preparation details of a product which contains the prep category, prep owner and the label owner. If not passed while creating an inbound order, NO_PREP will be used on the product by-default.	PrepDetails

Name	Description	Schema
	Prep instructions will be generated based on the category passed	

ShipmentLabels

Shipment labels.

Name	Description	Schema
labelDownloadURL <i>optional</i>	The URL to download shipment labels. The URL is active for 600 seconds from generation.	string
labelStatus <i>required</i>	Status of label generation.	LabelStatus

ShipmentListing

A list of inbound shipment summaries filtered by the attributes specified in the request.

Name	Description	Schema
nextToken <i>optional</i>	A token that is used to retrieve the next page of results. The response includes <code>nextToken</code> when the number of results exceeds the specified <code>maxResults</code> value. To get the next page of results, call the operation with this token and include the same arguments as the call that produced the token. To get a complete list, call this operation until <code>nextToken</code> is null. Note that this operation can return empty pages. Example : "SampleToken"	string
shipments <i>optional</i>	List of inbound shipment summaries.	< InboundShipmentSummary > array

SkuEligibility

Represents eligibility of one SKU.

Name	Description	Schema
ineligibilityReasons <i>optional</i>	If not eligible, these are list of error codes and descriptions.	< SkuIneligibilityReason > array
packageQuantity <i>required</i>	Represents a distribution package with its respective quantity.	DistributionPackageQuantity

Name	Description	Schema
status <i>required</i>	Enum denoting the package inbound eligibility.	InboundEligibilityStatus

SkulneligibilityReason

Represents the ineligibility reason for one SKU.

Name	Description	Schema
code <i>required</i>	Code for the SKU ineligibility.	string
description <i>required</i>	Detailed description of the SKU ineligibility.	string

SkuQuantity

Quantity details for a SKU as part of a shipment

Name	Description	Schema
expectedQuantity <i>required</i>	Quantity of inventory with an associated measurement unit context.	InventoryQuantity
receivedQuantity <i>optional</i>	Quantity of inventory with an associated measurement unit context.	InventoryQuantity
sku <i>required</i>	The merchant stock keeping unit	string

TrackingDetails

Tracking details for the shipment. If using SPD transportation, this can be for each case. If not using SPD transportation, this is a single tracking entry for the entire shipment.

Name	Description	Schema
carrierCode <i>optional</i>	Unique or identifying code for the carrier.	CarrierCode
bookingId <i>required</i>	The identifier that is received from transportation to uniquely identify a booking. minLength : 1	string

TransportationDetails

Transportation details for the shipment.

Name	Description	Schema
trackingDetails <i>required</i>	Tracking details for the shipment. If using SPD transportation, this can be for each case. If not using SPD transportation, this is a single tracking entry for the entire shipment.	< TrackingDetails > array

VolumeUnitOfMeasurement

Unit of measurement for the package volume.

Type : enum

Value	Description
CU_IN	Denotes volume measurement in cubic inches.
CBM	Denotes volume measurement in cubic meters.
CC	Denotes volume measurement in cubic centimeters.

WeightUnitOfMeasurement

Unit of measurement for the package weight.

Type : enum

Value	Description
POUNDS	Denotes weight measurement in pounds.
KILOGRAMS	Denotes weight measurement in kilograms.

SkuQuantities

If equal to `SHOW` , the response includes the shipment SKU quantity details.

Defaults to `HIDE` , in which case the response does not contain SKU quantities

Type : enum

Value	Description
SHOW	Show the additional SKU quantity details.
HIDE	Hide the additional SKU quantity details.

Details

Set to `SHOW` to return summaries with additional inventory details. Defaults to `HIDE`, which returns only inventory summary totals.

Type : enum

Value	Description
SHOW	Show the additional summarized inventory details.
HIDE	Hide the additional summarized inventory details.

ShipmentStatus

Filter by inbound shipment status.

Type : enum

Value	Description
CREATED	Shipment is created, but hasn't shipped.
SHIPPED	Shipment was picked up by the carrier or was dropped off with the carrier.

Value	Description
IN_TRANSIT	The carrier has notified AWD that the shipment is in transit between the origin and destination nodes.
RECEIVING	The shipment has been partially received.
DELIVERED	The shipment has reached the destination node and has been delivered to the facility yard. The shipment <code>receive</code> process at the warehouse will start soon.
CLOSED	No more actions are required for the shipment. This is a final state.
CANCELLED	The shipment is cancelled. This is a final state.

SortBy

Field to sort results by. By default, the response will be sorted by UPDATED_AT.

Type : enum

Value	Description
UPDATED_AT	Sort by the time of update.
CREATED_AT	Sort by the time of creation.

PageType

Page type for the generated labels. The default is `PLAIN_PAPER` .

Type : enum

Value	Description
PLAIN_PAPER	One label per sheet of US Letter paper. Only for non-Amazon-partnered shipments.

FormatType

The format type of the output file that contains your labels. The default format type is `PDF` .

Type : enum

Value	Description
PDF	PDF format.

SortOrder

Type : enum

For use with the operation(s): [listInboundShipments](#)

Sort the response in ASCENDING or DESCENDING order. By default, the response will be sorted in DESCENDING order.

Value	Description
ASCENDING	Sorts the collection in ascending order.
DESCENDING	Sorts the collection in descending order.

For use with the operation(s): [listInventory](#).

Sort the response in `ASCENDING` or `DESCENDING` order.

Value	Description
ASCENDING	Sorts the collection in ascending order.
DESCENDING	Sorts the collection in descending order.

 Updated 19 days ago

[← Track an inbound shipment with expected and received SKU details](#)

[App Integrations API →](#)

Did this page help you?  Yes  No