

Shipping API v1 Reference

⬆

GET STARTED

- Welcome to SP-API Documentation
- What is the Selling Partner API?
- Selling Partner API Onboarding Overview >

- Terminology
- Frequently Asked Questions >

CHANGELOG

- SP-API Release Notes
- SP-API Deprecation Schedule
- SP-API Product Metadata Updates

DIRECTORIES

Shipping API v1 Reference

Provides programmatic access to Amazon Shipping APIs.

Provides programmatic access to Amazon Shipping APIs.

Note: If you are new to the Amazon Shipping API, refer to the latest version of [Amazon Shipping API \(v2\)](#) on the [Amazon Shipping Developer Documentation](#) site.

Version information

Version : v1

Contact information

Contact : Selling Partner API Developer Support
Contact URL : <https://sellercentral.amazon.com/gp/mws/contactus.html>

License information

License : Apache License 2.0
License URL : <http://www.apache.org/licenses/LICENSE-2.0>

URI scheme

Host : sellingpartnerapi-na.amazon.com
Schemes : HTTPS

Consumes

- application/json

Produces

- application/json

Operations

- [createShipment](#)
- [getShipment](#)
- [cancelShipment](#)
- [purchaseLabels](#)
- [retrieveShippingLabel](#)
- [purchaseShipment](#)
- [getRates](#)
- [getAccount](#)
- [getTrackingInformation](#)

Paths

POST /shipping/v1/shipments

SP-API Models

SP-API Seller Use Cases

SP-API Vendor Use Cases

Seller Central URLs

Vendor Central URLs

REGISTRATION

SP-API Registration Overview >

Developer Registration Request Status

Third-Party Provider Registration >

Service Provider Registration and Role Approval Process Overview

Website Guidelines for Public Developers and Service Providers

User Permissions for Service Providers

Register your Application

Update your Application Information

Rotate your Application's LWA Credentials >

View your Application Information and Credentials

Learn How Sellers Authorize Service Providers

Selling Partner API Roles >

Policies and Agreements

About Facial Data

AUTHORIZATION

Authorize Applications >

Renew Authorizations

Revoke Authorizations

Authorization Limits

Special Authorization Types >

INTEGRATION

Building Robust Amazon SP-API Applications

Operation: createShipment

Description

Create a new shipment.

Usage Plan:

Rate (requests per second)	Burst
5	15

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate and burst values for this operation. Selling partners whose business demands require higher throughput may see higher rate and burst values than those shown here. For more information, see [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Body	body <i>required</i>	CreateShipmentRequest Body	CreateShipmentRequest

Responses

HTTP Code	Description	Schema
200	Success. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	CreateShipmentResponse
400	Request has missing or invalid parameters and cannot be parsed. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	CreateShipmentResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	CreateShipmentResponse
403	403 can be caused for reasons like Access Denied, Unauthorized, Expired Token, Invalid Signature or Resource Not Found. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	CreateShipmentResponse
404	The resource specified does not exist. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this	CreateShipmentResponse



HTTP Code	Description	Schema
	operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	
429	The frequency of requests was greater than allowed. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	CreateShipmentResponse
500	Encountered an unexpected condition which prevented the server from fulfilling the request. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	CreateShipmentResponse
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	CreateShipmentResponse

Delete an Application From Your Developer Account

CALLING THE SP-API

Configuration Details



GET /shipping/v1/shipments/{shipmentId}

Operation: getShipment

Description

Return the entire shipment object for the shipmentId.

Usage Plan:

Rate (requests per second)	Burst
5	15

Call Structure



For more information, see "Usage Plans and Rate Limits" in the Selling Partner API documentation.

Development Tools



Parameters

Type	Name	Description	Schema
Path	shipmentId <i>required</i>	Shipment id to return the entire shipment object	string

Performance Management



Responses

HTTP Code	Description	Schema
200	Success. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetShipmentResponse
400	Request has missing or invalid parameters and cannot be parsed. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate	GetShipmentResponse

SOLUTION PROVIDER PORTAL

Manage Users in Solution Provider Portal

Manage Your Business And Contact information in Solution Provider Portal

Update Your Developer Profile in Solution Provider Portal

Unify Your Developer Accounts

Verify Your Identity in Solution Provider Portal

API Usage Metrics in Solution Provider Portal

TUTORIALS

Tutorial: Subscribe to the ORDER_CHANGE Notification

Tutorial: Test Selling Partner API Endpoints

Tutorial: Automate your SP-API Calls Using a C# SDK

Tutorial: Automate your SP-API Calls Using a Java SDK

Tutorial: Automate your SP-API Calls Using a JavaScript SDK for Node.js

Tutorial: Automate your SP-API Calls Using a Python SDK

Tutorial: Automate your SP-API Calls using a prebuilt C# SDK

Tutorial: Automate your SP-API Calls using prebuilt Java SDK

Tutorial: Automate your SP-API Calls using a prebuilt JavaScript SDK

Tutorial: Automate your SP-API Calls using prebuilt PHP SDK

Tutorial: Automate your SP-API calls using a prebuilt Python SDK

Tutorial: Authorize Multiple Vendor Central Accounts with a Single SP-API Application

Tutorial: Retrieve Merchant Shipping Templates

Tutorial: Grant the SP-API Permission to an Amazon SQS Queue

Tutorial: Retrieve and Pass a Purchase Order Number to a Carrier

TROUBLESHOOTING

Troubleshoot SP-API Errors

URL Encoding

Resolve Common HTTP and Authorization Error Codes

External Fulfillment Errors 

Listings Items API Issues Troubleshooting 

SELLING PARTNER APPSTORE

What is the Selling Partner Appstore?

List Your App on the Selling Partner Appstore

Edit Your Appstore Listing

Check Listing Status

Appstore Ratings and Reviews

Press Releases and Promotions

SERVICE PROVIDER NETWORK

List Your Service

SECURITY AND COMPLIANCE

SP-API Security and Compliance Overview

Amazon Selling Partner API Guard Implementation Guide 

HTTP Code	Description	Schema
	limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetShipmentResponse
403	403 can be caused for reasons like Access Denied, Unauthorized, Expired Token, Invalid Signature or Resource Not Found. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetShipmentResponse
404	The resource specified does not exist. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	GetShipmentResponse
429	The frequency of requests was greater than allowed. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetShipmentResponse
500	Encountered an unexpected condition which prevented the server from fulfilling the request. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetShipmentResponse
503	Temporary overloading or maintenance of the server. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetShipmentResponse

POST /shipping/v1/shipments/{shipmentId}/cancel

Operation: cancelShipment

Description

Cancel a shipment by the given shipmentId.

Usage Plan:

Rate (requests per second)	Burst
5	15

For more information, see "Usage Plans and Rate Limits" in the Selling Partner API documentation.

Parameters

Type	Name	Description	Schema
Path	shipmentId <i>required</i>	Shipment Id to cancel a shipment	string

Responses

HTTP Code	Description	Schema
200	Success. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	CancelShipmentResponse
400	Request has missing or invalid parameters and cannot be parsed. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	CancelShipmentResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	CancelShipmentResponse
403	403 can be caused for reasons like Access Denied, Unauthorized, Expired Token, Invalid Signature or Resource Not Found. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	CancelShipmentResponse
404	The resource specified does not exist. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	CancelShipmentResponse
429	The frequency of requests was greater than allowed. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	CancelShipmentResponse
500	Encountered an unexpected condition which prevented the server from fulfilling the request. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	CancelShipmentResponse

VAT Calculation Service

>

Amazon Seller Data Access

Best Practices

>

A+ CONTENT API

A+ Content API

>

A+ Content Examples

AMAZON WAREHOUSING AND DISTRIBUTION API

Amazon Warehousing and Distribution API

>

Amazon Warehousing and Distribution API v2024-05-09 Reference

APP INTEGRATIONS API

App Integrations API

>

HTTP Code	Description	Schema
503	Temporary overloading or maintenance of the server. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	CancelShipmentResponse

APPLICATION MANAGEMENT API

Application Management API

>

POST /shipping/v1/shipments/{shipmentId}/purchaseLabels

Operation: purchaseLabels

Description

Purchase shipping labels based on a given rate.

Usage Plan:

Rate (requests per second)	Burst
5	15

For more information, see "Usage Plans and Rate Limits" in the Selling Partner API documentation.

Parameters

Type	Name	Description	Schema
Path	shipmentId <i>required</i>	Shipment id for purchase shipping label	string
Body	body <i>required</i>	PurchaseShippingLabelRequest body	PurchaseLabelsRequest

Responses

HTTP Code	Description	Schema
200	Success. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	PurchaseLabelsResponse
400	Request has missing or invalid parameters and cannot be parsed. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	PurchaseLabelsResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	PurchaseLabelsResponse
403	403 can be caused for reasons like Access Denied, Unauthorized, Expired Token, Invalid Signature or Resource Not Found.	PurchaseLabelsResponse

DATA KIOSK

Data Kiosk API

>

Data Kiosk Schema Explorer User Guide

Data Kiosk Query Processing Finished Notification

Building Data Kiosk workflows guide

Vendor Analytics Dataset Use Case Guide

Schedule Data Kiosk Queries

DELIVERY BY AMAZON API

Delivery by Amazon API

>

EASY SHIP API

Easy Ship API

>

EXTERNAL FULFILLMENT

External Fulfillment Inventory API

>

External Fulfillment Returns API

>

External Fulfillment Shipping API

>

External Fulfillment Errors

External Fulfillment APIs Rate Limits

FULFILLMENT BY AMAZON (FBA)

FBA Inventory API

>

FBA Inventory Dynamic Sandbox Guide

FEEDS API

Feeds API

>

Feed Type Values

>

HTTP Code

Description

Schema

Headers :
x-amzn-RequestId (string) : Unique request reference identifier.

404

The resource specified does not exist.
Headers :
x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation.
x-amzn-RequestId (string) : Unique request reference identifier.

[PurchaseLabelsResponse](#)

429

The frequency of requests was greater than allowed.
Headers :
x-amzn-RequestId (string) : Unique request reference identifier.

[PurchaseLabelsResponse](#)

500

Encountered an unexpected condition which prevented the server from fulfilling the request.
Headers :
x-amzn-RequestId (string) : Unique request reference identifier.

[PurchaseLabelsResponse](#)

503

Temporary overloading or maintenance of the server.
Headers :
x-amzn-RequestId (string) : Unique request reference identifier.

[PurchaseLabelsResponse](#)

POST

/shipping/v1/shipments/{shipmentId}/containers/{trackingId}/label

Operation: retrieveShippingLabel

Description

Retrieve shipping label based on the shipment id and tracking id.

Usage Plan:

Rate (requests per second)	Burst
5	15

For more information, see "Usage Plans and Rate Limits" in the Selling Partner API documentation.

Parameters

Type	Name	Description	Schema
Path	shipmentId required	Shipment Id to retrieve label	string
Path	trackingId required	Tracking Id	string
Body	body required	RetrieveShippingLabelRequest body	RetrieveShippingLabelRequest

Responses

FULFILLMENT INBOUND API

Fulfillment Inbound API

Fulfillment Inbound API FAQ

Migrating Fulfillment Inbound workflows

Fulfillment Inbound API Rate Limits

FULFILLMENT OUTBOUND API

Fulfillment Outbound Dynamic Sandbox Guide

Fulfillment Outbound API

Fulfillment Outbound API Rate Limits

MCF Best Practices

INVOICING

>

>

HTTP Code	Description	Schema
200	Success. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	RetrieveShippingLabelResponse
400	Request has missing or invalid parameters and cannot be parsed. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	RetrieveShippingLabelResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	RetrieveShippingLabelResponse
403	403 can be caused for reasons like Access Denied, Unauthorized, Expired Token, Invalid Signature or Resource Not Found. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	RetrieveShippingLabelResponse
404	The resource specified does not exist. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	RetrieveShippingLabelResponse
429	The frequency of requests was greater than allowed. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	RetrieveShippingLabelResponse
500	Encountered an unexpected condition which prevented the server from fulfilling the request. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	RetrieveShippingLabelResponse
503	Temporary overloading or maintenance of the server. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	RetrieveShippingLabelResponse

Invoices API

Invoices API FAQ

LISTINGS

Listings Items API

Listings Items API Rate Limits

Listings Restrictions API

Listings Restrictions API Rate Limits

Manage Product Listings with the Selling Partner API

Building Listings Management Workflows Guide

Understanding Amazon listing status and seller-fulfilled inventory management

Listings Management Workflow Migration

Manage Amazon Haul, Advanced Multiple-Offer, and Multiple-Fulfillment Use Cases

Listings APIs FAQ

Product Type Definitions API

Product Type Definitions API Rate Limits

>

POST /shipping/v1/purchaseShipment

Operation: purchaseShipment

Description

Purchase shipping labels.

Usage Plan:

>

Rate (requests per second)	Burst
5	15

For more information, see "Usage Plans and Rate Limits" in the Selling Partner API documentation.

Parameters

Type	Name	Description	Schema
Body	body <i>required</i>	PurchaseShipmentRequest body	PurchaseShipmentRequest

Responses

HTTP Code	Description	Schema
200	Success. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	PurchaseShipmentResponse
400	Request has missing or invalid parameters and cannot be parsed. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	PurchaseShipmentResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	PurchaseShipmentResponse
403	403 can be caused for reasons like Access Denied, Unauthorized, Expired Token, Invalid Signature or Resource Not Found. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	PurchaseShipmentResponse
404	The resource specified does not exist. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation.	PurchaseShipmentResponse

MERCHANT FULFILLMENT API

Merchant Fulfillment API



MESSAGING API

Messaging API



NOTIFICATIONS API

Notifications API



Notification Type Values

Tutorial: Subscribe to the ORDER_CHANGE Notification



ORDERS API

Orders API



HTTP Code	Description	Schema
	<code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	
429	The frequency of requests was greater than allowed. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	PurchaseShipmentResponse
500	Encountered an unexpected condition which prevented the server from fulfilling the request. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	PurchaseShipmentResponse
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	PurchaseShipmentResponse

POST /shipping/v1/rates

Operation: `getRates`

Description

Get service rates.

Usage Plan:

Rate (requests per second)	Burst
5	15

For more information, see "Usage Plans and Rate Limits" in the Selling Partner API documentation.

Parameters

Type	Name	Description	Schema
Body	<code>body</code> <i>required</i>	GetRatesRequest body	GetRatesRequest

Responses

HTTP Code	Description	Schema
200	Success. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetRatesResponse
400	Request is missing or has invalid parameters and cannot be parsed. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation.	GetRatesResponse

Tutorial: Retrieve and Pass a Purchase Order Number to a Carrier



Orders API Migration Guide

Orders API Rate Limits

PRODUCT FEES API

Product Fees API



PRODUCT PRICING API

Product Pricing API



Product Pricing API and Notifications FAQ

Price Adjustment Automation Workflows Guide

Manage automated pricing rules with SP-API

REPLENISHMENT API

Replenishment API



REPORTS API

Reports API



Report Type Values



HTTP Code	Description	Schema
	<code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetRatesResponse
403	403 can be caused for reasons like Access Denied, Unauthorized, Expired Token, Invalid Signature or Resource Not Found. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetRatesResponse
404	The resource specified does not exist. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetRatesResponse
429	The frequency of requests was greater than allowed. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetRatesResponse
500	Encountered an unexpected condition which prevented the server from fulfilling the request. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetRatesResponse
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetRatesResponse

GET /shipping/v1/account

Operation: `getAccount`

Description

Verify if the current account is valid.

Usage Plan:

Rate (requests per second)	Burst
5	15

Reports JSON Schemas



Reports API FAQ

SALES API

Sales API



Responses

For more information, see "Usage Plans and Rate Limits" in the Selling Partner API documentation.

SELLER WALLET API

Seller Wallet API

>

Seller Wallet API Rate Limits

SELLERS API

Sellers API

>

SERVICES API

Services API

>

SHIPMENT INVOICING API

Shipment Invoicing API

>

SHIPPING API

Shipping API v2 Resources

>

Shipping API v1 Reference

SOLICITATIONS API

Solicitations API

>

SUPPLY SOURCES API

Supply Sources API

>

Multi-Location Inventory Integration Guide

Supply Sources API Rate Limits

TOKENS API

Tokens API

>

HTTP Code	Description	Schema
200	The account was valid. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	GetAccountResponse
400	Request has missing or invalid parameters and cannot be parsed. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	GetAccountResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetAccountResponse
403	403 can be caused for reasons like Access Denied, Unauthorized, Expired Token, Invalid Signature or Resource Not Found. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetAccountResponse
404	The resource specified does not exist. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	GetAccountResponse
429	The frequency of requests was greater than allowed. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetAccountResponse
500	Encountered an unexpected condition which prevented the server from fulfilling the request. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetAccountResponse
503	Temporary overloading or maintenance of the server. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetAccountResponse

GET /shipping/v1/tracking/{trackingId}**Operation: getTrackingInformation****Description**

Return the tracking information of a shipment.

Usage Plan:

Rate (requests per second)	Burst
1	1

For more information, see "Usage Plans and Rate Limits" in the Selling Partner API documentation.

Parameters**UPLOADS API**

Uploads API >

Type	Name	Description	Schema
Path	trackingId <i>required</i>	Tracking Id	string

VEHICLES API

Vehicles API >

Vehicles API Rate Limits

VENDOR DIRECT FULFILLMENT APIS

Vendor Direct Fulfillment Dynamic Sandbox Guide

Vendor Direct Fulfillment Workflow Guide

SP-API Bill-to-Party Addresses

VENDOR DIRECT FULFILLMENT TRANSACTION STATUS API

Vendor Direct Fulfillment Transaction Status API >

VENDOR DIRECT FULFILLMENT INVENTORY API

Vendor Direct Fulfillment Inventory API >

VENDOR DIRECT FULFILLMENT ORDERS API

Vendor Direct Fulfillment Orders API >

VENDOR DIRECT FULFILLMENT SHIPPING API

Vendor Direct Fulfillment Shipping API >

Responses

HTTP Code	Description	Schema
200	Success. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	GetTrackingInformationResponse
400	Request has missing or invalid parameters and cannot be parsed. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	GetTrackingInformationResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetTrackingInformationResponse
403	403 can be caused for reasons like Access Denied, Unauthorized, Expired Token, Invalid Signature or Resource Not Found. Headers : x-amzn-RequestId (string) : Unique request reference identifier.	GetTrackingInformationResponse
404	The resource specified does not exist. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	GetTrackingInformationResponse
429	The frequency of requests was greater than allowed. Headers :	GetTrackingInformationResponse

VENDOR DIRECT FULFILLMENT PAYMENTS API	
Vendor Direct Fulfillment Payments API	>
VENDOR RETAIL PROCUREMENT INVOICES API	
Vendor Retail Procurement Invoices API	>
VENDOR RETAIL PROCUREMENT ORDERS API	
Vendor Retail Procurement Orders API	>

HTTP Code	Description	Schema
	<code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	
500	Encountered an unexpected condition which prevented the server from fulfilling the request. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetTrackingInformationResponse
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetTrackingInformationResponse

VENDOR RETAIL PROCUREMENT SHIPMENTS API	
Vendor Retail Procurement Shipments API	>
VENDOR RETAIL PROCUREMENT TRANSACTION STATUS API	
Vendor Retail Procurement Transaction Status API	>

Definitions

Error

Error response returned when the request is unsuccessful.

Name	Description	Schema
code <i>required</i>	An error code that identifies the type of error that occurred.	string
message <i>required</i>	A message that describes the error condition.	string
details <i>optional</i>	Additional details that can help the caller understand or fix the issue.	string

ErrorList

A list of error responses returned when a request is unsuccessful.

Type : < [Error](#) > array

AccountId

This is the Amazon Shipping account id generated during the Amazon Shipping onboarding process.

Type : string

maxLength : 10

ShipmentId

The unique shipment identifier.

Type : string

ClientReferenceId

Client reference id.

Type : string

maxLength : 40

ContainerReferenceId

Powered
by



An identifier for the container. This must be unique within all the containers in the same shipment.

Type : string

maxLength : 40

EventCode

The event code of a shipment, such as Departed, Received, and ReadyForReceive.

Type : string

minLength : 1

maxLength : 60

StateOrRegion

The state or region where the person, business or institution is located.

Type : string

City

The city where the person, business or institution is located.

Type : string

minLength : 1

maxLength : 50

CountryCode

The two digit country code. In ISO 3166-1 alpha-2 format.

Type : string

minLength : 2

maxLength : 2

PostalCode

The postal code of that address. It contains a series of letters or digits or both, sometimes including spaces or punctuation.

Type : string

minLength : 1

maxLength : 20

Location

The location where the person, business or institution is located.

Name	Description	Schema
stateOrRegion optional	The state or region where the person, business or institution is located.	StateOrRegion
city optional	The city where the person, business or institution is located.	City
countryCode optional	The two digit country code. In ISO 3166-1 alpha-2 format.	CountryCode
postalCode optional	The postal code of that address. It contains a series of letters or digits or both, sometimes including spaces or punctuation.	PostalCode

Event

An event of a shipment

Name	Description	Schema
eventCode <i>required</i>	The event code of a shipment, such as Departed, Received, and ReadyForReceive.	EventCode
eventTime <i>required</i>	The date and time of an event for a shipment.	string (date-time)
location <i>optional</i>	The location where the person, business or institution is located.	Location

EventList

A list of events of a shipment.

Type : < [Event](#) > array

TrackingId

The tracking id generated to each shipment. It contains a series of letters or digits or both.

Type : string

minLength : 1

maxLength : 60

TrackingSummary

The tracking summary.

Name	Description	Schema
status <i>optional</i>	The derived status based on the events in the eventHistory. minLength : 1 maxLength : 60	string

PromisedDeliveryDate

The promised delivery date and time of a shipment.

Type : string (date-time)

Address

The address.

Name	Description	Schema
name <i>required</i>	The name of the person, business or institution at that address. minLength : 1 maxLength : 50	string
addressLine1 <i>required</i>	First line of that address. minLength : 1 maxLength : 60	string
addressLine2 <i>optional</i>	Additional address information, if required. minLength : 1 maxLength : 60	string
addressLine3 <i>optional</i>	Additional address information, if required. minLength : 1 maxLength : 60	string

Name	Description	Schema
stateOrRegion <i>required</i>	The state or region where the person, business or institution is located.	StateOrRegion
city <i>required</i>	The city where the person, business or institution is located.	City
countryCode <i>required</i>	The two digit country code. In ISO 3166-1 alpha-2 format.	CountryCode
postalCode <i>required</i>	The postal code of that address. It contains a series of letters or digits or both, sometimes including spaces or punctuation.	PostalCode
email <i>optional</i>	The email address of the contact associated with the address. maxLength : 64	string
copyEmails <i>optional</i>	The email cc addresses of the contact associated with the address.	< string > array
phoneNumber <i>optional</i>	The phone number of the person, business or institution located at that address. minLength : 1 maxLength : 20	string

TimeRange

The time range.

Name	Description	Schema
start <i>optional</i>	The start date and time. This defaults to the current date and time.	string (date-time)
end <i>optional</i>	The end date and time. This must come after the value of start. This defaults to the next business day from the start.	string (date-time)

ShippingPromiseSet

The promised delivery time and pickup time.

Name	Description	Schema
deliveryWindow <i>optional</i>	The time window in which the shipment will be delivered.	TimeRange
receiveWindow <i>optional</i>	The time window in which Amazon Shipping will pick up the shipment.	TimeRange

ServiceType

The type of shipping service that will be used for the service offering.

Type : enum

Value	Description
Amazon Shipping Ground	Amazon Shipping Ground.
Amazon Shipping Standard	Amazon Shipping Standard.
Amazon Shipping Premium	Amazon Shipping Premium.

ServiceTypeList

A list of service types that can be used to send the shipment.

Type : < [ServiceType](#) > array

Rate

The available rate that can be used to send the shipment

Name	Description	Schema
rateId <i>optional</i>	An identifier for the rate.	string
totalCharge <i>optional</i>	The total charge that will be billed for the rate.	Currency
billedWeight <i>optional</i>	The weight that was used to calculate the totalCharge.	Weight
expirationTime <i>optional</i>	The time after which the offering will expire.	string (date-time)
serviceType <i>optional</i>	The type of shipping service that will be used for the service offering.	ServiceType
promise <i>optional</i>	The promised delivery time and pickup time.	ShippingPromiseSet

RateList

A list of all the available rates that can be used to send the shipment.

Type : < [Rate](#) > array

RateId

An identifier for the rating.

Type : string

AcceptedRate

The specific rate purchased for the shipment, or null if unpurchased.

Name	Description	Schema
totalCharge <i>optional</i>	The total charge that will be billed for the rate.	Currency
billedWeight <i>optional</i>	The weight that was used to calculate the totalCharge.	Weight
serviceType <i>optional</i>	The type of shipping service that will be used for the service offering.	ServiceType
promise <i>optional</i>	The promised delivery time and pickup time.	ShippingPromiseSet

ServiceRate

The specific rate for a shipping service, or null if no service available.

Name	Description	Schema
totalCharge <i>required</i>	The total charge that will be billed for the rate.	Currency
billableWeight <i>required</i>	The weight that was used to calculate the totalCharge.	Weight

Name	Description	Schema
serviceType <i>required</i>	The type of shipping service that will be used for the service offering.	ServiceType
promise <i>required</i>	The promised delivery time and pickup time.	ShippingPromiseSet

ServiceRateList

A list of service rates.

Type : < [ServiceRate](#) > array

Party

The account related with the shipment.

Name	Description	Schema
accountId <i>optional</i>	This is the Amazon Shipping account id generated during the Amazon Shipping onboarding process.	AccountId

Currency

The total value of all items in the container.

Name	Description	Schema
value <i>required</i>	The amount of currency.	number
unit <i>required</i>	A 3-character currency code. minLength : 3 maxLength : 3	string

Dimensions

A set of measurements for a three-dimensional object.

Name	Description	Schema
length <i>required</i>	The length of the container.	number
width <i>required</i>	The width of the container.	number
height <i>required</i>	The height of the container.	number
unit <i>required</i>	The unit of these measurements.	enum (Unit)

Weight

The weight.

Name	Description	Schema
unit <i>required</i>	The unit of measurement.	enum (Unit)
value <i>required</i>	The measurement value.	number

ContainerItem

Item in the container.

Name	Description	Schema
quantity <i>required</i>	The quantity of the items of this type in the container.	number
unitPrice <i>required</i>	The unit price of an item of this type (the total value of this item type in the container is unitPrice x quantity).	Currency
unitWeight <i>required</i>	The unit weight of an item of this type (the total weight of this item type in the container is unitWeight x quantity).	Weight
title <i>required</i>	A descriptive title of the item. maxLength : 30	string

Container

Container in the shipment.

Name	Description	Schema
containerType <i>optional</i>	The type of physical container being used. (always 'PACKAGE')	enum (ContainerType)
containerReferenceId <i>required</i>	An identifier for the container. This must be unique within all the containers in the same shipment.	ContainerReferenceId
value <i>required</i>	The total value of all items in the container.	Currency
dimensions <i>required</i>	The length, width, height, and weight of the container.	Dimensions
items <i>required</i>	A list of the items in the container.	< ContainerItem > array
weight <i>required</i>	The weight of the container.	Weight

ContainerList

A list of container.

Type : < [Container](#) > array

ContainerSpecification

Container specification for checking the service rate.

Name	Description	Schema
dimensions <i>required</i>	The length, width, and height of the container.	Dimensions
weight <i>required</i>	The weight of the container.	Weight

ContainerSpecificationList

A list of container specifications.

Type : < [ContainerSpecification](#) > array

Label

The label details of the container.

Name	Description	Schema
labelStream <i>optional</i>	Contains binary image data encoded as a base-64 string.	LabelStream
labelSpecification <i>optional</i>	The label specification info.	LabelSpecification

LabelResult

Label details including label stream, format, size.

Name	Description	Schema
containerReferenceId <i>optional</i>	An identifier for the container. This must be unique within all the containers in the same shipment.	ContainerReferenceId
trackingId <i>optional</i>	The tracking identifier assigned to the container.	string
label <i>optional</i>	The label details of the container.	Label

LabelResultList

A list of label results

Type : < [LabelResult](#) > array

LabelStream

Contains binary image data encoded as a base-64 string.

Type : string

LabelSpecification

The label specification info.

Name	Description	Schema
labelFormat <i>required</i>	The format of the label. Enum of PNG only for now.	enum (LabelFormat)
labelStockSize <i>required</i>	The label stock size specification in length and height. Enum of 4x6 only for now.	enum (LabelStockSize)

CreateShipmentRequest

The request schema for the createShipment operation.

Name	Description	Schema
clientReferenceId <i>required</i>	Client reference id.	ClientReferenceId
shipTo <i>required</i>	The address.	Address
shipFrom <i>required</i>	The address.	Address
containers <i>required</i>	A list of container.	ContainerList

PurchaseLabelsRequest

The request schema for the purchaseLabels operation.

Name	Description	Schema
ratelId <i>required</i>	An identifier for the rating.	RatelId
labelSpecification <i>required</i>	The label specification info.	LabelSpecification

RetrieveShippingLabelRequest

The request schema for the retrieveShippingLabel operation.

Name	Description	Schema
labelSpecification <i>required</i>	The label specification info.	LabelSpecification

GetRatesRequest

The payload schema for the getRates operation.

Name	Description	Schema
shipTo <i>required</i>	The address.	Address
shipFrom <i>required</i>	The address.	Address
serviceTypes <i>required</i>	A list of service types that can be used to send the shipment.	ServiceTypeList
shipDate <i>optional</i>	The start date and time. This defaults to the current date and time.	string (date-time)
containerSpecifications <i>required</i>	A list of container specifications.	ContainerSpecificationList

PurchaseShipmentRequest

The payload schema for the purchaseShipment operation.

Name	Description	Schema
clientReferenceId <i>required</i>	Client reference id.	ClientReferenceId
shipTo <i>required</i>	The address.	Address
shipFrom <i>required</i>	The address.	Address
shipDate <i>optional</i>	The start date and time. This defaults to the current date and time.	string (date-time)
serviceType <i>required</i>	The type of shipping service that will be used for the service offering.	ServiceType
containers <i>required</i>	A list of container.	ContainerList
labelSpecification <i>required</i>	The label specification info.	LabelSpecification

CreateShipmentResult

The payload schema for the createShipment operation.

Name	Description	Schema
shipmentId <i>required</i>	The unique shipment identifier.	ShipmentId
eligibleRates <i>required</i>	A list of all the available rates that can be used to send the shipment.	RateList

Shipment

The shipment related data.

Name	Description	Schema
shipmentId <i>required</i>	The unique shipment identifier.	ShipmentId
clientReferenceId <i>required</i>	Client reference id.	ClientReferenceId
shipFrom <i>required</i>	The address.	Address
shipTo <i>required</i>	The address.	Address
acceptedRate <i>optional</i>	The specific rate purchased for the shipment, or null if unpurchased.	AcceptedRate
shipper <i>optional</i>	The account related with the shipment.	Party
containers <i>required</i>	A list of container.	ContainerList

PurchaseLabelsResult

The payload schema for the purchaseLabels operation.

Name	Description	Schema
shipmentId <i>required</i>	The unique shipment identifier.	ShipmentId
clientReferenceId <i>optional</i>	Client reference id.	ClientReferenceId
acceptedRate <i>required</i>	The specific rate purchased for the shipment, or null if unpurchased.	AcceptedRate
labelResults <i>required</i>	A list of label results	LabelResultList

RetrieveShippingLabelResult

The payload schema for the retrieveShippingLabel operation.

Name	Description	Schema
labelStream <i>required</i>	Contains binary image data encoded as a base-64 string.	LabelStream
labelSpecification <i>required</i>	The label specification info.	LabelSpecification

Account

The account related data.

Name	Description	Schema
accountId <i>required</i>	This is the Amazon Shipping account id generated during the Amazon Shipping onboarding process.	AccountId

GetRatesResult

The payload schema for the getRates operation.

Name	Description	Schema
serviceRates <i>required</i>	A list of service rates.	ServiceRateList

PurchaseShipmentResult

The payload schema for the purchaseShipment operation.

Name	Description	Schema
shipmentId <i>required</i>	The unique shipment identifier.	ShipmentId
serviceRate <i>required</i>	The specific rate for a shipping service, or null if no service available.	ServiceRate
labelResults <i>required</i>	A list of label results	LabelResultList

TrackingInformation

The payload schema for the getTrackingInformation operation.

Name	Description	Schema
trackingId <i>required</i>	The tracking id generated to each shipment. It contains a series of letters or digits or both.	TrackingId
summary <i>required</i>	The tracking summary.	TrackingSummary
promisedDeliveryDate <i>required</i>	The promised delivery date and time of a shipment.	PromisedDeliveryDate
eventHistory <i>required</i>	A list of events of a shipment.	EventList

CreateShipmentResponse

The response schema for the createShipment operation.

Name	Description	Schema
payload <i>optional</i>	The payload for createShipment operation	CreateShipmentResult
errors <i>optional</i>	Encountered errors for the operation.	ErrorList

GetShipmentResponse

The response schema for the getShipment operation.

Name	Description	Schema
payload <i>optional</i>	The payload for getShipment operation	Shipment
errors <i>optional</i>	Encountered errors for the operation.	ErrorList

GetRatesResponse

The response schema for the getRates operation.

Name	Description	Schema
payload <i>optional</i>	The payload for getRates operation	GetRatesResult
errors <i>optional</i>	Encountered errors for the operation.	ErrorList

PurchaseShipmentResponse

The response schema for the purchaseShipment operation.

Name	Description	Schema
payload <i>optional</i>	The payload for purchaseShipment operation	PurchaseShipmentResult
errors <i>optional</i>	Encountered errors for the operation.	ErrorList

CancelShipmentResponse

The response schema for the cancelShipment operation.

Name	Description	Schema
errors <i>optional</i>	Encountered errors for the operation.	ErrorList

PurchaseLabelsResponse

The response schema for the purchaseLabels operation.

Name	Description	Schema
payload <i>optional</i>	The payload for purchaseLabels operation	PurchaseLabelsResult
errors <i>optional</i>	Encountered errors for the operation.	ErrorList

RetrieveShippingLabelResponse

The response schema for the retrieveShippingLabel operation.

Name	Description	Schema
payload <i>optional</i>	The payload for retrieveShippingLabel operation	RetrieveShippingLabelResult
errors <i>optional</i>	Encountered errors for the operation.	ErrorList

GetAccountResponse

The response schema for the getAccount operation.

Name	Description	Schema
payload <i>optional</i>	The payload for getAccount operation	Account
errors <i>optional</i>	Encountered errors for the operation.	ErrorList

GetTrackingInformationResponse

The response schema for the getTrackingInformation operation.

Name	Description	Schema
payload <i>optional</i>	The payload for getTrackingInformation operation	TrackingInformation
errors <i>optional</i>	Encountered errors for the operation.	ErrorList

LabelFormat

The format of the label. Enum of PNG only for now.

Type : enum

Value	Description
PNG	PNG

ContainerType

The type of physical container being used. (always 'PACKAGE')

Type : enum

Value	Description
PACKAGE	PACKAGE

LabelStockSize

The label stock size specification in length and height. Enum of 4x6 only for now.

Type : enum

Value	Description
4x6	4x6

Unit

Type : enum

For use with the definition(s): [Weight](#)

The unit of measurement.

Value	Description
g	Grams
kg	Kilograms
oz	Ounces
lb	Pounds

For use with the definition(s): [Dimensions](#)

The unit of these measurements.

Value	Description
IN	Inches
CM	Centimeters

 Updated over 1 year ago

[← Submit a shipment invoice](#)

[Solicitations API →](#)

Did this page help you?  Yes  No