

INTEGRATION GUIDES

Direct Integration with Amazon Shipping APIs (not an Amazon Marketplace Seller)

Direct Integration with Amazon Shipping APIs (Hybrid Sellers - Amazon Marketplace Seller and Other Sales Channel)

3rd Party Partner Integration (Enabling Amazon Marketplace Seller and Other Sales Channel Sellers)

3rd Party Partner Integrator (Enabling Other Sales Channel Sellers)

3P Website Authorization Workflow for Amazon Shipping API

SHIPPING API

Shipping API v2 Reference

Shipping API v2 Model

Workflow for creating a shipment

Push Notifications Setups



TUTORIALS

Tutorial: Purchase a Shipment From a Rate

Tutorial: Use the SmartPurchase API to Generate Amazon Shipping Labels

Tutorial: Retrieve Previously Generated Shipment Documents

Tutorial: Track a Shipment

Tutorial: Cancel a Shipment

Tutorial: Purchase a Limited Quantity Dangerous Goods Shipment From a Rate

Tutorial: Purchase a Dangerous Goods Shipment for an Item Containing a Lithium Ion Battery From a Rate

Tutorial: Purchase a Dangerous Goods Shipment for FRITES (France, Italy, Spain) marketplaces

Tutorial: Use the NDR Feedback API To Submit Non-Delivery Reports For Eligible Shipments

Tutorial: Integrate FBM Ship+ with ERPs and Multi-Channel Integrators

DOCS

What is the Selling Partner API?



Shipping API v2 Reference

Provides programmatic access to Amazon Shipping v2 APIs.

Overview

The Amazon Shipping API is designed to support outbound shipping use cases using [Amazon Shipping](#) and [Amazon Buy Shipping](#) for orders originating on Amazon-owned marketplaces as well as external channels/marketplaces. With these APIs, you can request shipping rates, create shipments, cancel shipments, and track shipments.

Carrier Support: Sellers enrolled in the [Fulfilled by Merchant \(FBM\) Program](#) can use this Shipping API V2 to purchase shipping labels for Amazon Shipping and/or third party shipping carriers like UPS, USPS, FedEx, DHL, etc. Complete list of supported carriers and shipping services can be found on [Seller Central](#).

- For Amazon marketplace orders (On-Amazon): Carrier labels for Amazon Shipping and third party carriers are available
- For other channels (Off-Amazon) e.g. Merchant website, eBay, Shopify etc: Only Amazon Shipping is available.

To indicate if the label you are purchasing is for On-Amazon or Off-Amazon, use [ChannelType](#).

Version information

Version : v2

URI scheme

Host : [available hosts for amazon shipping v2 apis](#)

Schemes : HTTPS

Consumes

- `application/json`

Produces

- `application/json`

Resources

Operations	Available Regions	Carrier Supported
getRates	WorldWide	Amazon Shipping and 3rd Party Carriers
purchaseShipment	WorldWide	Amazon Shipping and 3rd Party Carriers
oneClickShipment	WorldWide	Amazon Shipping
getTracking	WorldWide	Amazon Shipping and 3rd Party Carriers
getShipmentDocuments	WorldWide	Amazon Shipping and 3rd Party Carriers
cancelShipment	WorldWide	Amazon Shipping and 3rd Party Carriers
getAccessPoints	UK	Amazon Shipping
submitNdrFeedback	IN	Amazon Shipping
getAdditionalInputs	WorldWide	Amazon Shipping and 3rd Party Carriers

Paths

SP-API Endpoints	
Determine app type	
Registering as a developer	>

Registering your Application	
Rotating your application's LWA credentials	
Viewing your application information and credentials	
Authorizing Selling Partner API applications	>

The Selling Partner API sandbox	
Seller Central URLs	

USER GUIDES	
Amazon Shipping Roles	>

Usage Plans and Rate Limits in the Shipping API	
Amazon Shipping Label Guide	

POSTMAN SCRIPTS AND TEST CASE GUIDE	
Postman Collections For Amazon Shipping APIs	
Postman Environment Files for Amazon Shipping APIs	
API Integration Test Case Guide	

FAQS	
Frequently Asked Questions	
Seller Display Name	

MIGRATING TO AMAZON SHIPPING V2 API	
Amazon Shipping V2 Migration Guide	
Mapping APIs from previous versions to Amazon Shipping V2 API	

POST /shipping/v2/shipments/rates

Operation: `getRates`

Description

Returns the available shipping service offerings.

Usage Plan:

Default Quota	Unit
5	Requests Per Second

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate for this operation. For more information, see [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Body	body <i>required</i>	The request schema for the <code>getRates</code> operation. When the <code>channelType</code> is Amazon, the <code>shipTo</code> address is not required and will be ignored.	GetRatesRequest
Header	x-amz-access-token <i>required</i>	Amazon shipping request token	string
Header	x-amzn-shipping-business-id <i>optional</i>	Amazon shipping business to assume for this request. The default is <code>AmazonShipping_UK</code> .	enum (X-amzn-shipping-business-id)

Responses

HTTP Code	Description	Schema
200	Success. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetRatesResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
413	The request size exceeded the maximum accepted size. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
415	The request payload is in an unsupported format. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit	ErrorList

HTTP Code	Description	Schema
	(requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	
429	The frequency of requests was greater than allowed. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
500	An unexpected condition occurred that prevented the server from fulfilling the request. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList

For additional error status codes, descriptions and schemas, see [Error responses and schemas](#).

POST /shipping/v2/shipments

Operation: purchaseShipment

Description

Purchases a shipping service and returns purchase related details and documents.

Note: You must complete the purchase within **10 minutes** of rate creation by the shipping service provider for channelType as `EXTERNAL` which is for OFF-Amazon volume. If you make the request after the 10 minutes have expired, you will receive an error response with the error code equal to "TOKEN_EXPIRED". If you receive this error response, you must get the rates for the shipment again.

Usage Plan:

Default Quota	Unit
5	Requests Per Second

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate for this operation. For more information, see [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Body	body <i>required</i>	The request schema for the purchaseShipment operation.	PurchaseShipmentRequest

Type	Name	Description	Schema
Header	x-amz-access-token <i>required</i>	Amazon shipping request token	string
Header	x-amzn-shipping-business-id <i>optional</i>	Amazon shipping business to assume for this request. The default is AmazonShipping_UK.	enum (X-amzn-shipping-business-id)

Responses

HTTP Code	Description	Schema
200	Success. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	PurchaseShipmentResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. x-amzn-RequestId (string) : Unique request reference identifier.	ErrorList
413	The request size exceeded the maximum accepted size. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. x-amzn-RequestId (string) : Unique request reference identifier.	ErrorList
415	The request payload is in an unsupported format. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. x-amzn-RequestId (string) : Unique request reference identifier.	ErrorList
429	The frequency of requests was greater than allowed. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. x-amzn-RequestId (string) : Unique request reference identifier.	ErrorList
500	An unexpected condition occurred that prevented the server from fulfilling the request. Headers : x-amzn-RateLimit-Limit (string) : Your rate	ErrorList

HTTP Code	Description	Schema
	limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList

For additional error status codes, descriptions and schemas, see [Error responses and schemas](#).

POST /shipping/v2/oneClickShipment

Operation: oneClickShipment

Description

Purchases a shipping service identifier and returns purchase-related details and documents.

Note: Amazon Shipping labels generated for Amazon marketplace orders (On-Amazon) using the SmartPurchase API do not include [Amazon Buy Shipping protections](#). Therefore, it is important to consider this limitation when utilizing the API for your shipping requirements. If sellers wish to leverage Amazon Buy Shipping protection, it is recommended to use the [Tutorial: Purchase a Shipment From a Rate](#) instead.

Usage Plan:

Default Quota	Unit
5	Requests Per Second

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate for this operation. For more information, see [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Body	body <i>required</i>	The request schema for the OneClickShipment operation. When the channelType is not Amazon, shipTo is required and when channelType is Amazon shipTo is ignored.	OneClickShipmentRequest
Header	x-amz-access-token <i>required</i>	Amazon shipping request token	string
Header	x-amzn-shipping-business-id <i>optional</i>	Amazon shipping business to assume for this request. The default is AmazonShipping_UK.	enum (X-amzn-shipping-business-id)

Responses

HTTP Code	Description	Schema
200	Success. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	OneClickShipmentResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
413	The request size exceeded the maximum accepted size. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
415	The request payload is in an unsupported format. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
429	The frequency of requests was greater than allowed. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
500	An unexpected condition occurred that prevented the server from fulfilling the request. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned.	ErrorList

HTTP Code	Description	Schema
	<code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	

For additional error status codes, descriptions and schemas, see [Error responses and schemas](#).

GET /shipping/v2/tracking

Operation: `getTracking`

Description

Returns tracking information for a purchased shipment.

Usage Plan:

Default Quota	Unit
5	Requests Per Second

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate. For more information, see [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Query	<code>trackingId</code> <i>required</i>	A carrier-generated tracking identifier originally returned by the <code>purchaseShipment</code> operation.	string
Query	<code>carrierId</code> <i>required</i>	A carrier identifier originally returned by the <code>getRates</code> operation for the selected rate.	enum (carrier-id)
Header	<code>x-amz-access-token</code> <i>required</i>	Amazon shipping request token	string
Header	<code>x-amzn-shipping-business-id</code> <i>optional</i>	Amazon shipping business to assume for this request. The default is <code>AmazonShipping_UK</code> .	enum (X-amzn-shipping-business-id)

Responses

HTTP Code	Description	Schema
200	Success. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetTrackingResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
413	The request size exceeded the maximum accepted size. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit	ErrorList

HTTP Code	Description	Schema
	(requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	
415	The request payload is in an unsupported format. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
429	The frequency of requests was greater than allowed. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
500	An unexpected condition occurred that prevented the server from fulfilling the request. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList

For additional error status codes, descriptions and schemas, see [Error responses and schemas](#).

GET /shipping/v2/shipments/{shipmentId}/documents

Operation: `getShipmentDocuments`

Description

Returns the shipping documents associated with a package in a shipment.

Usage Plan:

Default Quota	Unit
5	Requests Per Second

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate for this operation. For more information, see [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Path	shipmentId <i>required</i>	The shipment identifier originally returned by the purchaseShipment operation.	string
Query	packageClientReferenceId <i>required</i>	The package client reference identifier originally provided in the request body parameter for the getRates operation.	string
Query	format <i>optional</i>	The file format of the document. Must be one of the supported formats returned by the getRates operation.	string
Query	dpi <i>optional</i>	The resolution of the document (for example, 300 means 300 dots per inch). Must be one of the supported resolutions returned in the response to the getRates operation.	number
Header	x-amz-access-token <i>required</i>	Amazon shipping request token	string
Header	x-amzn-shipping-business-id <i>optional</i>	Amazon shipping business to assume for this request. The default is AmazonShipping_UK.	enum (X- amzn- shipping- business- id)

Responses

HTTP Code	Description	Schema
200	Success. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetShipmentDocumentsResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList

HTTP Code	Description	Schema
413	The request size exceeded the maximum accepted size. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
415	The request payload is in an unsupported format. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
429	The frequency of requests was greater than allowed. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
500	An unexpected condition occurred that prevented the server from fulfilling the request. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList

For additional error status codes, descriptions and schemas, see [Error responses and schemas](#).

PUT /shipping/v2/shipments/{shipmentId}/cancel

Operation: cancelShipment**Description**

Cancels a purchased shipment. Returns an empty object if the shipment is successfully cancelled.

Usage Plan:

Default Quota	Unit
5	Requests Per Second

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate for this operation. For more information, see [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Path	shipmentId <i>required</i>	The shipment identifier originally returned by the purchaseShipment operation.	string
Header	x-amz-access-token <i>required</i>	Amazon shipping request token	string
Header	x-amzn-shipping-business-id <i>optional</i>	Amazon shipping business to assume for this request. The default is AmazonShipping_UK.	enum (X-amzn-shipping-business-id)

Responses

HTTP Code	Description	Schema
200	Success. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	CancelShipmentResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
413	The request size exceeded the maximum accepted size. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
415	The request payload is in an unsupported format. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned.	ErrorList

HTTP Code	Description	Schema
	<code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	
429	The frequency of requests was greater than allowed. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
500	An unexpected condition occurred that prevented the server from fulfilling the request. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList

For additional error status codes, descriptions and schemas, see [Error responses and schemas](#).

GET /shipping/v2/accessPoints

Operation: `getAccessPoints`

Description

Returns a list of access points in proximity of input postal code.

Usage Plan:

Default Quota	Unit
5	Requests Per Second

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate for this operation. For more information, see [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Query	<code>accessPointTypes</code> <i>required</i>	-	< enum (AccessPointTypes) > array(csv)
Query	<code>countryCode</code> <i>required</i>	-	string
Query	<code>postalCode</code> <i>required</i>	-	string

Type	Name	Description	Schema
Header	x-amz-access-token <i>required</i>	Amazon shipping request token	string
Header	x-amzn-shipping-business-id <i>optional</i>	Amazon shipping business to assume for this request. The default is AmazonShipping_UK.	enum (X-amzn-shipping-business-id)

Responses

HTTP Code	Description	Schema
200	Success. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. x-amzn-RequestId (string) : Unique request reference identifier.	GetAccessPointsResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. x-amzn-RequestId (string) : Unique request reference identifier.	ErrorList
413	The request size exceeded the maximum accepted size. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. x-amzn-RequestId (string) : Unique request reference identifier.	ErrorList
415	The request payload is in an unsupported format. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. x-amzn-RequestId (string) : Unique request reference identifier.	ErrorList
429	The frequency of requests was greater than allowed. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. x-amzn-RequestId (string) : Unique request reference identifier.	ErrorList
500	An unexpected condition occurred that prevented the server from fulfilling the request. Headers : x-amzn-RateLimit-Limit (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned.	ErrorList

HTTP Code	Description	Schema
	<code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList

For additional error status codes, descriptions and schemas, see [Error responses and schemas](#).

Consumes

- `application/json`

Produces

- `application/json`

POST /shipping/v2/ndrFeedback

Operation: `submitNdrFeedback`

Description

This API submits the NDR (Non-delivery Report) Feedback for any eligible shipment.

Usage Plan:

Default Quota	Unit
5	Requests Per Second

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate for this operation. For more information, see [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Body	body <i>required</i>	Request body for ndrFeedback operation	SubmitNdrFeedbackRequest
Header	x-amz-access-token <i>required</i>	Amazon shipping request token	string
Header	x-amzn-shipping-business-id <i>optional</i>	Amazon shipping business to assume for this request. The default is AmazonShipping_UK.	enum (X-amzn-shipping-business-id)

Responses

HTTP Code	Description	Schema
204	Success Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	No Content

HTTP Code	Description	Schema
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
413	The request size exceeded the maximum accepted size. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
415	The request payload is in an unsupported format. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
429	The frequency of requests was greater than allowed. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
500	An unexpected condition occurred that prevented the server from fulfilling the request. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList

For additional error status codes, descriptions and schemas, see [Error responses and schemas](#).

GET /shipping/v2/shipments/additionalInputs/schema

Operation: `getAdditionalInputs`

Description

Returns the JSON schema to use for providing additional inputs when needed to purchase a shipping offering. Call the `getAdditionalInputs` operation when the response to a previous call to the `getRates` operation indicates that additional inputs are required for the rate (shipping offering) that you want to purchase.

Usage Plan:

Default Quota	Unit
5	Requests Per Second

The `x-amzn-RateLimit-Limit` response header returns the usage plan rate limits that were applied to the requested operation, when available. The table above indicates the default rate for this operation. For more information, see [Usage Plans and Rate Limits in the Selling Partner API](#).

Parameters

Type	Name	Description	Schema
Query	<code>requestToken</code> <i>required</i>	The request token returned in the response to the <code>getRates</code> operation.	string
Query	<code>rateId</code> <i>required</i>	The rate identifier for the shipping offering (rate) returned in the response to the <code>getRates</code> operation.	string
Header	<code>x-amz-access-token</code> <i>required</i>	Amazon shipping request token	string
Header	<code>x-amzn-shipping-business-id</code> <i>optional</i>	Amazon shipping business to assume for this request. The default is <code>AmazonShipping_UK</code> .	enum (X-amzn-shipping-business-id)

Responses

HTTP Code	Description	Schema
200	Success. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	GetAdditionalInputsResponse
401	The request's Authorization header is not formatted correctly or does not contain a valid token. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
413	The request size exceeded the maximum accepted size. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
415	The request payload is in an unsupported format. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
429	The frequency of requests was greater than allowed. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
500	An unexpected condition occurred that prevented the server from fulfilling the request. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	ErrorList
503	Temporary overloading or maintenance of the server. Headers : <code>x-amzn-RateLimit-Limit</code> (string) : Your rate limit (requests per second) for this operation. <i>Note:</i> For this status code, the rate limit header is	ErrorList

HTTP Code	Description	Schema
	deprecated and no longer returned. <code>x-amzn-RequestId</code> (string) : Unique request reference identifier.	

For additional error status codes, descriptions and schemas, see [Error responses and schemas](#).

Error Responses and Schemas

This table contains HTTP status codes and associated information for error responses.

HTTP Code	Description	Schema
400	Request has missing or invalid parameters and cannot be parsed. Headers: <code>x-amzn-RateLimit-Limit</code> (string):Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList
403	Indicates that access to the resource is forbidden. Possible reasons include Access Denied, Unauthorized, Expired Token, or Invalid Signature. Headers: <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList
404	The resource specified does not exist. Headers: <code>x-amzn-RateLimit-Limit</code> (string):Your rate limit (requests per second) for this operation. <code>x-amzn-RequestId</code> (string):Unique request reference identifier.	ErrorList

Definitions

Error

Error response returned when the request is unsuccessful.

Name	Description	Schema
code <i>required</i>	An error code that identifies the type of error that occurred.	string
message <i>required</i>	A message that describes the error condition.	string
details <i>optional</i>	Additional details that can help the caller understand or fix the issue.	string

ErrorList

A list of error responses returned when a request is unsuccessful.

Name	Schema
errors <i>required</i>	< Error > array

Weight

The weight in the units indicated.

Name	Description	Schema
unit <i>required</i>	The unit of measurement.	enum (Unit)
value <i>required</i>	The measurement value.	number

LiquidVolume

Liquid Volume.

Name	Description	Schema
unit <i>required</i>	The unit of measurement.	enum (Unit)
value <i>required</i>	The measurement value.	number

InvoiceDetails

The invoice details for charges associated with the goods in the package. Only applies to certain regions.

Name	Description	Schema
invoiceNumber <i>optional</i>	The invoice number of the item.	string
invoiceDate <i>optional</i>	The invoice date of the item in ISO 8061 format.	string (date-time)

ChargeList

A list of charges based on the shipping service charges applied on a package.

Type : < [ChargeComponent](#) > array

ChargeComponent

The type and amount of a charge applied on a package.

Name	Description	Schema
amount <i>optional</i>	The monetary value in the currency indicated, in ISO 4217 standard format.	Currency .
chargeType <i>optional</i>	The type of charge.	enum (ChargeType)

Currency

The monetary value in the currency indicated, in ISO 4217 standard format.

Name	Description	Schema
value <i>required</i>	The monetary value.	number
unit <i>required</i>	The ISO 4217 format 3-character currency code. minLength : 3 maxLength : 3	string

Dimensions

A set of measurements for a three-dimensional object.

Name	Description	Schema
length <i>required</i>	The length of the package. This must be the longest side of the parcel. If dimensions are not submitted in descending order, they will be automatically reordered so that the largest value is assigned to length, the middle value to width, and the smallest value to height.	number
width <i>required</i>	The width of the package. After normalization, this will hold the middle dimension value.	number
height <i>required</i>	The height of the package. After normalization, this will hold the smallest dimension value.	number

Name	Description	Schema
unit <i>required</i>	The unit of measurement.	enum (Unit)

Note:

Amazon Shipping automatically normalizes package dimensions so that length ≥ width ≥ height (descending order).

The largest dimension value is assigned to length, the middle to width, and the smallest to height. Units are preserved.

This applies across all marketplaces. Submitted dimension field assignments may be reordered accordingly.

RequestToken

A unique token generated to identify a getRates operation.

Type : string

RateId

An identifier for the rate (shipment offering) provided by a shipping service provider.

Type : string

CarrierId

The carrier identifier for the offering, provided by the carrier.

Type : string

CarrierName

The carrier name for the offering.

Type : string

PackageClientReferenceId

A client provided unique identifier for a package being shipped. This value should be saved by the client to pass as a parameter to the getShipmentDocuments operation.

Type : string

AdditionalPackageInfo

Additional information about the package provided by Shipper

Type : < [AdditionalPackageInfo](#) > array

AdditionalPackageInfo

Name	Description	Schema
name <i>required</i>	The name of the information content being sent along with the package	enum (PURCHASE_ORDER_NUMBER)
value <i>required</i>	The value of the information content being sent along with the package	string

ShipmentId

The unique shipment identifier provided by a shipping service.

Type : string

DetailCodes

A list of codes used to provide additional shipment information.

Type : enum

Value	Description
BusinessClosed	Attempted delivery but the business was closed.
DeliveredWithOTP	Shipment was delivered with onetime passcode. OTP is currently only available in: UK, FR, IT, ES, IN.
ArrivedAtLocalFacility	Package arrived at the local facility.
RejectedByRecipientWithVerification	Recipient refused to accept the shipment and provided verification
CustomerUnavailable	Attempted delivery but the recipient was unavailable.
PaymentNotReady	Attempted delivery but cash was not available from recipient.
OtpNotAvailable	Attempted delivery but the recipient did not have the PIN available.
DeliveryAttempted	Delivery was attempted.
UnableToAccess	Attempted delivery but could not access the recipient location.
UnableToContactRecipient	Attempted delivery but unable to contact the recipient to coordinate delivery.
DeliveredToBehindWheelieBin	Shipment delivered behind wheelie bin.
DeliveredToPorch	Shipment delivered to front porch or front door.
DeliveredToGarage	Shipment delivered to garage.
DeliveredToGarden	Shipment delivered to garden.
DeliveredToGreenhouse	Shipment delivered to greenhouse.
DeliveredToMailSlot	Shipment delivered to letterbox/mail slot.
DeliveredToMailRoom	Shipment delivered to mail room.
DeliveredToNeighbor	Shipment delivered and signed for by neighbor.
DeliveredToRearDoor	Shipment delivered to rear porch or rear door.
DeliveredToReceptionist	Shipment delivered to reception.
DeliveredToShed	Shipment delivered to shed.
DeliveredWithOTP	Shipment delivered with onetime passcode.
Signed	Shipment delivered and signature received.
Damaged	Shipment was damaged. When paired with Rejected this indicates the recipient refused to accept the shipment because the shipment was damaged. When paired with UNDELIVERABLE it means the shipment was undeliverable due to being damaged and may be returned to the seller.
IncorrectItems	Recipient refused to accept the shipment because the shipment contains incorrect item/s.
NotRequired	Recipient refused to accept the shipment because the recipient did not want the shipment.
Rejected	Recipient refused to accept the shipment.
RejectedByRecipientWithVerification	Recipient refused to accept the shipment and provided verification.
CancelledByRecipient	Shipment was cancelled by the recipient. This tag is paired with the rejected shipment status.
AddressNotFound	Shipment is undeliverable and is returning to seller because the address was missing or incorrect.

Value	Description
HazmatShipment	Shipment is non-compliant Hazmat.
Undeliverable	Shipment is undeliverable and is returning to the seller.
ArrivedAtLocalFacility	Package arrived at the local facility.

TrackingDetailCodes

Contains detail codes that provide additional details related to the forward and return leg of the shipment.

Name	Description	Schema
forward <i>required</i>	Contains detail codes that provide additional details related to the forward leg of the shipment.	< DetailCodes > array
returns <i>required</i>	Contains detail codes that provide additional details related to the return leg of the shipment.	< DetailCodes > array

ProofOfDelivery

Contains the proof of delivery information for a package, if available and permitted.

Name	Description	Schema
deliveryLocationCoordinates <i>optional</i>	Contains detail codes that provide additional details related to the forward leg of the shipment.	Geocode
deliveryImageURL <i>optional</i>	This attribute exists only when available. A temporary URL that provides access to the image taken at the time of delivery. This URL is dynamically generated with each request, and remains valid for 72 hours before expiring. If the delivery image is needed again, another <code>getTracking</code> request can be made.	string
signatureImageURL <i>optional</i>	This attribute exists only when available. A temporary URL that provides access to the signature given at the time of delivery. This URL is dynamically generated with each request, and remains valid for 72 hours before expiring. If the signature image is needed again, another <code>getTracking</code> request can be made.	string
receivedBy <i>optional</i>	This attribute exists only when available. The recorded person or entity who received the package.	string

TrackingId

The carrier generated identifier for a package in a purchased shipment.

Type : string

AlternateLegTrackingId

The carrier generated reverse identifier for a returned package in a purchased shipment.

Type : string

ServiceId

An identifier for the shipping service.

Type : string

Please find the current list of service id [here](#).

ServiceName

The name of the shipping service.

Type : string

Please find the current list of service name [here](#).

AdditionalAddressNotes

Address notes to re-attempt delivery with.

Type : string

maxLength : 256

ShipperInstruction

The shipper instruction.

Name	Description	Schema
deliveryNotes <i>optional</i>	The delivery notes for the shipment maxLength : 256	string

Address

The address.

Name	Description	Schema
name <i>required</i>	The name of the person, business or institution at the address. minLength : 1 maxLength : 50	string
addressLine1 <i>required</i>	The first line of the address. minLength : 1 maxLength : 60	string
addressLine2 <i>optional</i>	Additional address information, if required. minLength : 1 maxLength : 60	string
addressLine3 <i>optional</i>	Additional address information, if required. minLength : 1 maxLength : 60	string
companyName <i>optional</i>	The name of the business or institution associated with the address.	string
stateOrRegion <i>Conditional</i>	The state, county or region where the person, business or institution is located. Note: This is required parameter for US, optional for EU and IN.	StateOrRegion
city <i>required</i>	The city or town where the person, business or institution is located.	City
countryCode <i>required</i>	The two digit country code. Follows ISO 3166-1 alpha-2 format.	CountryCode
postalCode <i>required</i>	The postal code of that address. It contains a series of letters or digits or both, sometimes including spaces or punctuation.	PostalCode
email <i>optional</i>	The email address of the contact associated with the address. maxLength : 64	string
phoneNumber <i>optional</i>	The phone number of the person, business or institution located at that address, including the country calling code. minLength : 1 maxLength : 20	string

Name	Description	Schema
geocode <i>optional</i>	Defines the latitude and longitude of the access point.	Geocode

Geocode

A representation of the geographical location. Currently only returns the geographic coordinate formatted in the ISO6709:2022 Decimal Degrees for longitude and latitude.

Name	Description	Schema
latitude <i>optional</i>	The latitude component of the location in ISO6709:2022 Decimal Degree format.	string
longitude <i>optional</i>	The longitude component of the location in ISO6709:2022 Decimal Degree format.	string
elevation <i>optional</i>	The height or depth component of the location in ISO6709:2022 Decimal Degree format. This is only present when the data is available.	string

StateOrRegion

The state, county or region where the person, business or institution is located.

Type : string

City

The city or town where the person, business or institution is located.

Type : string

CountryCode

The two digit country code. Follows ISO 3166-1 alpha-2 format.

Type : string

PostalCode

The postal code of that address. It contains a series of letters or digits or both, sometimes including spaces or punctuation.

Type : string

Location

The location where the person, business or institution is located.

Name	Description	Schema
stateOrRegion <i>optional</i>	The state, county or region where the person, business or institution is located.	StateOrRegion
city <i>optional</i>	The city or town where the person, business or institution is located.	City
countryCode <i>optional</i>	The two digit country code. Follows ISO 3166-1 alpha-2 format.	CountryCode
postalCode <i>optional</i>	The postal code of that address. It contains a series of letters or digits or both, sometimes including spaces or punctuation.	PostalCode

DocumentFormat

The file format of the document.

Type : enum

Value	Description
PDF	The Portable Document Format (PDF) file format. Used to present documents, including text formatting and images, in a manner independent of application software, hardware, and operating systems.
PNG	Portable Network Graphics (PNG) is a raster-graphics file format that supports lossless data compression.
ZPL	Zebra Programming Language (ZPL) format is from Zebra Technologies. It's used primarily for labeling applications and can only be used with ZPL compatible printers.

RequestAttributes

Specify the type of attributes to be added on a label.

Type : < [LabelAttribute](#) > array

LabelAttribute

Type : enum

Value	Description
PACKAGE_CLIENT_REFERENCE_ID	Prints client reference ID on the shipping label.
SELLER_DISPLAY_NAME	Prints seller name on the shipping label.
COLLECT_ON_DELIVERY_AMOUNT	Prints Collect On Delivery amount on the shipping label.

DocumentType

The type of shipping document.

Type : enum

Value	Description
PACKSLIP	A listing of the items packed within the shipment.
LABEL	The shipping label for the specific shipment.
RECEIPT	The receipt of the shipment.
CUSTOM_FORM	The customs documentation for a cross-border shipment.

Dpi

The dots per inch (DPI) value used in printing. This value represents a measure of the resolution of the document.

Type : integer

PageLayout

Indicates the position of the label on the paper. Should be the same value as returned in getRates response.

Type : string

NeedFileJoining

When true, files should be stitched together. Otherwise, files should be returned separately. Defaults to false.

Type : boolean

Contents

A Base64 encoded string of the file contents.

Type : string

PackageDocumentList

A list of documents related to a package.

Type : < [PackageDocument](#) > array

PackageDocument

A document related to a package.

Name	Description	Schema
type <i>required</i>	The type of shipping document.	DocumentType
format <i>required</i>	The file format of the document.	DocumentFormat
contents <i>required</i>	A Base64 encoded string of the file contents.	Contents

PrintOptionList

A list of the format options for a label.

Type : < [PrintOption](#) > array

PrintOption

The format options available for a label.

Name	Description	Schema
supportedDPIS <i>optional</i>	A list of the supported DPI options for a document.	< Dpi > array
supportedPageLayouts <i>required</i>	A list of the supported page layout options for a document.	< PageLayout > array
supportedFileJoiningOptions <i>required</i>	A list of the supported needFileJoining boolean values for a document.	< NeedFileJoining > array
supportedDocumentDetails <i>required</i>	A list of the supported documented details.	< SupportedDocumentDetail > array

DocumentSize

The size dimensions of the label.

Name	Description	Schema
width <i>required</i>	The width of the document measured in the units specified.	number
length <i>required</i>	The length of the document measured in the units specified.	number
unit <i>required</i>	The unit of measurement.	enum (Unit)

SupportedDocumentDetail

The supported document types for a service offering.

Name	Description	Schema
name <i>required</i>	The type of shipping document.	DocumentType
isMandatory <i>required</i>	When true, the supported document type is required.	boolean

RequestedDocumentSpecification

The document specifications requested. For calls to the purchaseShipment operation, the shipment purchase fails if the specified document specifications are not among those returned in the response to the getRates operation.

Name	Description	Schema
format <i>required</i>	The file format of the document.	DocumentFormat
size <i>required</i>	The size dimensions of the label.	DocumentSize
dpi <i>optional</i>	The dots per inch (DPI) value used in printing. This value represents a measure of the resolution of the document.	Dpi
pageLayout <i>optional</i>	Indicates the position of the label on the paper. Should be the same value as returned in getRates response.	PageLayout
needFileJoining <i>required</i>	When true, files should be stitched together. Otherwise, files should be returned separately. Defaults to false.	NeedFileJoining
requestedDocumentTypes <i>required</i>	A list of the document types requested.	< DocumentType > array
requestedLabelCustomization <i>optional</i>	Object contains customised data requested by a shipper to be printed on a shipping label.	< RequestAttributes > array

SupportedDocumentSpecificationList

A list of the document specifications supported for a shipment service offering.

Type : < [SupportedDocumentSpecification](#) > array

SupportedDocumentSpecification

Document specification that is supported for a service offering.

Name	Description	Schema
format <i>required</i>	The file format of the document.	DocumentFormat
size <i>required</i>	The size dimensions of the label.	DocumentSize
printOptions <i>required</i>	A list of the format options for a label.	PrintOptionList

Item

An item in a package.

Name	Description	Schema
itemValue <i>Conditional</i>	The monetary value in the currency indicated, in ISO 4217 standard format. <i>Note: This is Required field for Amazon Marketplace Orders (ON Amazon type of requests). And For Off Amazon</i>	Currency

Name	Description	Schema
	<i>type shipments to Northern Ireland, this field is mandatory and must accurately represent the invoiced amount for the item.</i>	
description <i>Conditional</i>	The product description of the item. <i>Note: It must accurately reflect the goods being shipped. For shipments to Northern Ireland, this field must also contain a six-digit <u>commodity code</u> (HS code) in the following format: HSCODE:XXXXXX (six digits without spaces or special characters).</i>	string
itemIdentifier <i>Conditional</i>	A unique identifier for an item provided by the client. Please use the Orders Selling Partner API and populate this field with the response parameter <code>OrderItemId</code>. <i>Note: This is Required field for Amazon Marketplace Orders (ON Amazon type of requests).</i>	string
quantity <i>required</i>	The number of units. This value is required.	integer
weight <i>required</i>	The weight in the units indicated.	Weight
liquidVolume <i>optional</i>	Liquid Volume.	LiquidVolume
isHazmat <i>optional</i>	When true, the item qualifies as hazardous materials (hazmat). Defaults to false.	boolean
dangerousGoodsDetails <i>optional</i>	Details related to any dangerous goods/items that are being shipped.	DangerousGoodsDetails
productType <i>optional</i>	The product type of the item.	string
invoiceDetails <i>optional</i>	The invoice details for charges associated with the goods in the package. Only applies to certain regions.	InvoiceDetails
serialNumbers <i>optional</i>	A list of unique serial numbers in an Amazon package that can be	< string > array

Name	Description	Schema
	used to guarantee non-fraudulent items. The number of serial numbers in the list must be less than or equal to the quantity of items being shipped. Only applicable when channel source is Amazon.	
directFulfillmentItemIdentifiers <i>optional</i>	Item identifiers for an item in a direct fulfillment shipment.	DirectFulfillmentItemIdentifiers

ItemList

A list of items.

Type : < [Item](#) > array

Package

A package to be shipped through a shipping service offering.

Name	Description	Schema
dimensions <i>required</i>	A set of measurements for a three-dimensional object.	Dimensions
weight <i>required</i>	The weight in the units indicated.	Weight
insuredValue <i>required</i>	The monetary value in the currency indicated, in ISO 4217 standard format.	Currency
isHazmat <i>optional</i>	When true, the package contains hazardous materials. Defaults to false.	boolean
sellerDisplayName <i>optional</i>	The seller name displayed on the label.	string
charges <i>optional</i>	A list of charges based on the shipping service charges applied on a package.	ChargeList
packageClientReferenceId <i>required</i>	A client provided unique identifier for a package being shipped. This value should be saved by the client to pass as a parameter to the getShipmentDocuments operation.	PackageClientReferenceId
additionalPackageInfo <i>optional</i>	Additional information about the package provided by Shipper	AdditionalPackageInfo
items <i>required</i>	A list of items.	ItemList

PackageList

A list of packages to be shipped through a shipping service offering.

Type : < [Package](#) > array

DirectFulfillmentItemIdentifiers

Item identifiers for an item in a direct fulfillment shipment.

Name	Description	Schema
lineItemID <i>required</i>	A unique identifier for an item provided by the client for a direct fulfillment shipment. This is only populated for direct fulfillment multi-piece shipments. It is required if a vendor wants to change the configuration of the packages in which the purchase order is shipped.	string
pieceNumber <i>optional</i>	A unique identifier for an item provided by the client for a direct fulfillment shipment. This is only populated if a single line item has multiple pieces. Defaults to 1.	string

PackageDocumentDetail

The post-purchase details of a package that will be shipped using a shipping service.

Name	Description	Schema
packageClientReferenceId <i>required</i>	A client provided unique identifier for a package being shipped. This value should be saved by the client to pass as a parameter to the getShipmentDocuments operation.	PackageClientReferenceId
packageDocuments <i>required</i>	A list of documents related to a package.	PackageDocumentList
trackingId <i>optional</i>	The carrier generated identifier for a package in a purchased shipment.	TrackingId

PackageDocumentDetailList

A list of post-purchase details about a package that will be shipped using a shipping service.

Type : < [PackageDocumentDetail](#) > array

TimeWindow

The start and end time that specifies the time interval of an event.

Name	Description	Schema
start <i>optional</i>	The start time of the time window.	string (date-time)
end <i>optional</i>	The end time of the time window.	string (date-time)

Promise

The time windows promised for pickup and delivery events.

Name	Description	Schema
deliveryWindow <i>optional</i>	The start and end time that specifies the time interval of an event.	TimeWindow
pickupWindow <i>optional</i>	The start and end time that specifies the time interval of an event.	TimeWindow

RequestedValueAddedServiceList

The value-added services to be added to a shipping service purchase.

Type : < [RequestedValueAddedService](#) > array

RequestedValueAddedService

A value-added service to be applied to a shipping service purchase.

Name	Description	Schema
id <i>required</i>	The identifier of the selected value-added service. Must be among those returned in the response to the getRates operation.	string

AvailableValueAddedServiceGroupList

A list of value-added services available for a shipping service offering.

Type : < [AvailableValueAddedServiceGroup](#) > array

AvailableValueAddedServiceGroup

The value-added services available for purchase with a shipping service offering.

Name	Description	Schema
groupId <i>required</i>	The type of the value-added service group.	string
groupDescription <i>required</i>	The name of the value-added service group.	string
isRequired <i>required</i>	When true, one or more of the value-added services listed must be specified.	boolean
valueAddedServices <i>optional</i>	A list of optional value-added services available for purchase with a shipping service offering.	< ValueAddedService > array

ValueAddedService

A value-added service available for purchase with a shipment service offering.

Name	Description	Schema
id <i>required</i>	The identifier for the value-added service.	string
name <i>required</i>	The name of the value-added service.	string
cost <i>required</i>	The cost of the value-added service.	Currency

CollectOnDelivery

The amount to collect on delivery.

Name	Description	Schema
amount <i>required</i>	The monetary value in the currency indicated, in ISO 4217 standard format.	Currency

SignatureOnDelivery

Setting this structure requests a service to confirm that the package has been delivered via signature at the time of delivery.

Type : object

OTPOnDelivery

Setting this structure requests a service to confirm that the package has been delivered via One Time Passcode at the time of delivery.

Type : object

ValueAddedServiceDetails

A collection of supported value-added services.

Name	Description	Schema
collectOnDelivery <i>optional</i>	The amount to collect on delivery.	CollectOnDelivery
signatureOnDelivery <i>optional</i>	Setting this structure requests a service to confirm that the package has been delivered via signature at the time of delivery.	SignatureOnDelivery
otpOnDelivery <i>optional</i>	Setting this structure requests a service to confirm that the package has been delivered via One Time Passcode at the time of delivery.	OTPOnDelivery

DangerousGoodsDetails

Details related to any dangerous goods/items that are being shipped.

Name	Description	Schema
unitedNationsRegulatoryId <i>optional</i>	The specific UNID of the item being shipped. Pattern : <code>"^(UN) [0-9] {4}\$"</code>	string
transportationRegulatoryClass <i>optional</i>	The specific regulatory class of the item being shipped. Pattern : <code>"^[1-9] (\\.[1-9]) ?\$"</code> Note if <code>transportationRegulatoryClass</code> is 2 or 3 then please populate LiquidVolume	string
packingGroup <i>optional</i>	The specific packaging group of the item being shipped.	enum (PackingGroup)
packingInstruction <i>optional</i>	The specific packing instruction of the item being shipped.	enum (PackingInstruction)

TaxType

Indicates the type of tax.

Type : enum

Value	Description
GST	Goods and Services Tax.

TaxDetail

Indicates the tax specifications associated with the shipment for customs compliance purposes in certain regions.

Name	Description	Schema
taxType <i>required</i>	Indicates the type of tax.	TaxType
taxRegistrationNumber <i>required</i>	The shipper's tax registration number associated with the shipment for customs compliance purposes in certain regions.	string

TaxDetailList

A list of tax detail information.

Type : < [TaxDetail](#) > array

MerchantId

merchant Id of provided merchant.

Type : string

ShipperNumber

A unique identifier for a shipper's 'Amazon Shipping' account.

Type : string

GoodsOwner

The seller owning the goods before handing them over to the carrier.

Name	Description	Schema
merchantId <i>required</i>	The Amazon Merchant Identifier (merchantId) of the seller owning the goods before handing them over to the carrier	MerchantId

EventCode

The tracking event type.

Type : enum

Value	Description
PickupDone	Package has been picked up by the service provider.
RecipientRequestedAlternateDeliveryTiming	Recipient has requested an update to their delivery date.
ReadyForReceive	Package has been created and is ready for pickup at the shippers location. This is a pre-transit status event code.
Delivered	Package has been delivered.
Departed	Package has departed from a particular location in carrier network.
DeliveryAttempted	Delivery was attempted, but was unsuccessful.
Lost	Package is lost.
OutForDelivery	Package is out for delivery.
ArrivedAtCarrierFacility	Package is in transit and has been received at a carrier location.
Rejected	Package was rejected by the recipient.
Undeliverable	Package is undeliverable.
PickupCancelled	Pickup scheduled for the package was cancelled.
ReturnInitiated	Return label has been generated.
AvailableForPickup	Package held for recipient pickup.
PackageReceivedByCarrier	Package has been received at a carrier location.

Event

A tracking event.

Name	Description	Schema
eventCode <i>required</i>	The tracking event type.	EventCode
location <i>optional</i>	The location where the person, business or institution is located.	Location
eventTime <i>required</i>	The ISO 8601 formatted timestamp of the event.	string (date-time)

Name	Description	Schema
shipmentType <i>optional</i>	Shipment type.	ShipmentType

TrackingSummary

A package status summary.

Name	Description	Schema
status <i>optional</i>	The status of the package being shipped.	Status
trackingDetailCodes <i>optional</i>	Contains detail codes that provide additional details related to the forward and return leg of the shipment.	TrackingDetailCodes
proofOfDelivery <i>optional</i>	Contains the proof of delivery information for a package, if available and permitted.	ProofOfDelivery

Status

The status of the package being shipped.

Type : enum

Value	Description
PreTransit	Package has been created but has not been picked up.
InTransit	Package has been picked up and is in transit.
Delivered	Package has has been delivered successfully.
Lost	Package is lost.
OutForDelivery	Package is out for delivery.
Rejected	Package has been rejected by the recipient.
Undeliverable	Package was undeliverable.
DeliveryAttempted	Delivery was attempted to the recipient location, but was not delivered.
PickupCancelled	Pickup was cancelled for the package.
AwaitingCustomerPickup	Package held at facility for the customer pickup.

AmazonOrderDetails

Amazon order information. This is required if the shipment source channel is Amazon.

Name	Description	Schema
orderId <i>required</i>	The Amazon order ID associated with the Amazon order fulfilled by this shipment.	string

AmazonShipmentDetails

Amazon shipment information.

Name	Description	Schema
shipmentId <i>required</i>	This attribute is required only for a Direct Fulfillment shipment. This is the encrypted shipment ID.	string

ChannelType

The shipment source channel type.

Type : enum

Value	Description
AMAZON	Indicates that the shipment originates from an Amazon order, eligible for Amazon Buy Shipping protections .
EXTERNAL	Indicates that the shipment originates from a non-Amazon channel, not eligible for Amazon Buy Shipping protections .

ChannelDetails

Shipment source channel related information.

Name	Description	Schema
channelType <i>required</i>	The shipment source channel type.	ChannelType
amazonOrderDetails <i>optional</i>	Amazon order information. This is required if the shipment source channel is Amazon.	AmazonOrderDetails
amazonShipmentDetails <i>optional</i>	Amazon shipment information.	AmazonShipmentDetails

RateList

A list of eligible shipping service offerings.

Type : < [Rate](#) > array

Rate

The details of a shipping service offering.

Name	Description	Schema
rateId <i>required</i>	An identifier for the rate (shipment offering) provided by a shipping service provider.	RateId
carrierId <i>required</i>	The carrier identifier for the offering, provided by the carrier.	CarrierId
carrierName <i>required</i>	The carrier name for the offering.	CarrierName
serviceId <i>required</i>	An identifier for the shipping service.	ServiceId
serviceName <i>required</i>	The name of the shipping service.	ServiceName
billedWeight <i>optional</i>	The weight in the units indicated.	Weight
totalCharge <i>required</i>	The monetary value in the currency indicated, in ISO 4217 standard format.	Currency
totalChargeWithAdjustments <i>optional</i>	The monetary value in the currency indicated, in ISO 4217 standard format.	Currency
promise <i>required</i>	The time windows promised for pickup and delivery events.	Promise

Name	Description	Schema
supportedDocumentSpecifications <i>required</i>	A list of the document specifications supported for a shipment service offering.	SupportedDocumentSpecification
availableValueAddedServiceGroups <i>optional</i>	A list of value-added services available for a shipping service offering.	AvailableValueAddedServiceGroups
requiresAdditionalInputs <i>required</i>	When true, indicates that additional inputs are required to purchase this shipment service. You must then call the <code>getAdditionalInputs</code> operation to return the JSON schema to use when providing the additional inputs to the <code>purchaseShipment</code> operation.	boolean
rateItemList <i>optional</i>	A list of <code>RateItem</code>	RateItemList
adjustmentItemList <i>optional</i>	A list of <code>RateItem</code>	AdjustmentItemList
paymentType <i>optional</i>	Payment type of the purchase.	PaymentType
benefits <i>optional</i>	Representing the included/excluded benefits that we offer for each <code>ShippingOffering/Rate</code> . Benefits being services provided by Amazon when sellers purchase shipping through Amazon.	Benefits

IneligibilityReasonCode

Reasons that make a shipment service offering ineligible.

Type : enum

Value	Description
NO_COVERAGE	The shipment is ineligible because there is no coverage to that address.
PICKUP_SLOT_RESTRICTION	The shipment is ineligible because there is an issue with the pickup slot.
UNSUPPORTED_VAS	The shipment is ineligible because the value-added service is invalid for this shipment.
VAS_COMBINATION_RESTRICTION	The shipment is ineligible because an invalid combination of value-added services were chosen.

Value	Description
SIZE_RESTRICTIONS	The shipment is ineligible because the package dimensions are unsupported.
WEIGHT_RESTRICTIONS	The shipment is ineligible because the weight is unsupported.
LATE_DELIVERY	The shipment is ineligible because delivery is too late.
PROGRAM_CONSTRAINTS	The shipment is ineligible because of program constraints.
TERMS_AND_CONDITIONS_NOT_ACCEPTED	The shipment is ineligible because terms and conditions have not been accepted by the carrier.
UNKNOWN	The ineligibility reason is unknown.

IneligibilityReason

The reason why a shipping service offering is ineligible.

Name	Description	Schema
code <i>required</i>	Reasons that make a shipment service offering ineligible.	IneligibilityReasonCode
message <i>required</i>	The ineligibility reason.	string

IneligibleRate

Detailed information for an ineligible shipping service offering.

Name	Description	Schema
serviceId <i>required</i>	An identifier for the shipping service.	ServiceId
serviceName <i>required</i>	The name of the shipping service.	ServiceName
carrierName <i>required</i>	The carrier name for the offering.	CarrierName
carrierId <i>required</i>	The carrier identifier for the offering, provided by the carrier.	CarrierId
ineligibilityReasons <i>required</i>	A list of reasons why a shipping service offering is ineligible.	< IneligibilityReason > array

IneligibleRateList

A list of ineligible shipping service offerings.

Type : < [IneligibleRate](#) > array

CancelShipmentResult

The payload for the cancelShipment operation.

Type : object

CancelShipmentResponse

Response schema for the cancelShipment operation.

Name	Description	Schema
payload <i>optional</i>	The payload for the cancelShipment operation.	CancelShipmentResult

GetRatesRequest

The request schema for the getRates operation. When the channelType is Amazon, the shipTo address is not required and will be ignored.

Name	Description	Schema
shipTo <i>optional</i>	The ship to address.	Address
shipFrom <i>required</i>	The ship from address.	Address
returnTo <i>optional</i>	The return to address.	Address
shipDate <i>optional</i>	The ship date and time (the requested pickup). This defaults to the current date and time.	string (date-time)
quoteForShipperNumber <i>optional</i>	The shipper's account number used to generate quoted price, which may be different from the requester's account number.	ShipperNumber
shipmentForShipperNumber <i>optional</i>	The Amazon Shipping Account ID responsible for managing and tracking the shipment.	ShipperNumber
shipperInstruction <i>optional</i>	This field describe shipper instruction.	ShipperInstruction
packages <i>required</i>	A list of packages to be shipped through a shipping service offering.	PackageList
valueAddedServices <i>optional</i>	A collection of supported value-added services.	ValueAddedServiceDetails
taxDetails <i>optional</i>	A list of tax detail information.	TaxDetailList
channelDetails <i>required</i>	Shipment source channel related information.	ChannelDetails
clientReferenceDetails <i>optional</i>	Object to pass additional information about the MCI Integrator shipperType: List of ClientReferenceDetail	ClientReferenceDetails
shipmentType <i>optional</i>	Shipment type.	ShipmentType
destinationAccessPointDetails <i>optional</i>	Accesspoint id for counter delivery	AccessPointDetails

Note: Package dimensions are normalized upon submission. The largest dimension value is assigned to length, the middle to width, and the smallest to height. Units are preserved.

AccessPointDetails

Name	Description	Schema
accessPointId <i>optional</i>	Unique identifier for the access point	AccessPointId

NdrAction

The type of NDR action shipper wants to take for a particular shipment.

Type : enum

Value	Description
RESCHEDULE	Seller wants to reschedule shipment delivery to a specific date.
REATTEMPT	Seller wants to re-attempt delivery with additional delivery notes.
RTO	Seller wants the shipment to return to the origin.

NdrRequestData

Additional information required for the NDR action that has been filed. If the NDR Action is RESCHEDULE, rescheduleDate is a required field. Otherwise, if the NDR Action is REATTEMPT, additionalAddressNotes is a required field.

Name	Description	Schema
rescheduleDate <i>optional</i>	The date on which the Seller wants to reschedule shipment delivery, in ISO-8601 date/time format Example : "2023-12-12T05:24:00.00Z"	string (date-time)
additionalAddressNotes <i>optional</i>	Address notes to re-attempt delivery with.	AdditionalAddressNotes

GetRatesResult

The payload for the getRates operation.

Name	Description	Schema
requestToken <i>required</i>	A unique token generated to identify a getRates operation.	RequestToken
rates <i>required</i>	A list of eligible shipping service offerings.	RateList
ineligibleRates <i>optional</i>	A list of ineligible shipping service offerings.	IneligibleRateList

GetRatesResponse

The response schema for the getRates operation.

Name	Description	Schema
payload <i>optional</i>	The payload for the getRates operation.	GetRatesResult

GetShipmentDocumentsResult

The payload for the getShipmentDocuments operation.

Name	Description	Schema
shipmentId <i>required</i>	The unique shipment identifier provided by a shipping service.	ShipmentId
packageDocumentDetail <i>required</i>	The post-purchase details of a package that will be shipped using a shipping service.	PackageDocumentDetail
benefits <i>optional</i>	Benefits that are included and excluded for each shipping offer.	Benefits

GetShipmentDocumentsResponse

The response schema for the the getShipmentDocuments operation.

Name	Description	Schema
payload <i>optional</i>	The payload for the getShipmentDocuments operation.	GetShipmentDocumentsResult

GetTrackingResult

The payload for the getTracking operation.

Name	Description	Schema
trackingId <i>required</i>	The carrier generated identifier for a package in a purchased shipment.	TrackingId
alternateLegTrackingId <i>required</i>	The carrier generated reverse identifier for a returned package in a purchased shipment.	AlternateLegTrackingId
eventHistory <i>required</i>	A list of tracking events.	< Event > array
promisedDeliveryDate <i>required</i>	The date and time by which the shipment is promised to be delivered.	string (date-time)
summary <i>required</i>	A package status summary.	TrackingSummary

SubmitNdrFeedbackRequest

The request schema for the NdrFeedback operation

Name	Description	Schema
trackingId <i>required</i>	The carrier generated identifier for a package in a purchased shipment.	TrackingId
ndrAction <i>required</i>	The type of NDR action shipper wants to take for a particular shipment.	NdrAction
ndrRequestData <i>optional</i>	Additional information required for the NDR action that has been filed. If the NDR Action is RESCHEDULE, rescheduleDate is a required field. Otherwise, if the NDR Action is REATTEMPT, additionalAddressNotes is a required field.	NdrRequestData

GetTrackingResponse

The response schema for the getTracking operation.

Name	Description	Schema
payload <i>optional</i>	The payload for the getTracking operation.	GetTrackingResult

PurchaseShipmentRequest

The request schema for the purchaseShipment operation.

Name	Description	Schema
requestToken <i>required</i>	A unique token generated to identify a getRates operation.	RequestToken
rateId <i>required</i>	An identifier for the rate (shipment offering) provided by a shipping service provider.	RateId
requestedDocumentSpecification <i>required</i>	The document specifications requested. For calls to	RequestedDocumentSpecification

Name	Description	Schema
	the purchaseShipment operation, the shipment purchase fails if the specified document specifications are not among those returned in the response to the getRates operation.	
requestedValueAddedServices <i>optional</i>	The value-added services to be added to a shipping service purchase.	RequestedValueAddedServiceList
additionalInputs <i>optional</i>	The additional inputs required to purchase a shipping offering, in JSON format. The JSON provided here must adhere to the JSON schema that is returned in the response to the getAdditionalInputs operation. Additional inputs are only required when indicated by the requiresAdditionalInputs property in the response to the getRates operation.	object

PurchaseShipmentResult

The payload for the purchaseShipment operation.

Name	Description	Schema
shipmentId <i>required</i>	The unique shipment identifier provided by a shipping service.	ShipmentId
packageDocumentDetails <i>required</i>	A list of post-purchase details about a package that will be shipped using a shipping service.	PackageDocumentDetailList
promise <i>required</i>	The time windows promised for pickup and delivery events.	Promise
benefits <i>optional</i>	Benefits that are included and excluded for each shipping offer.	Benefits
totalChargeWithAdjustments <i>optional</i>	The monetary value in the currency indicated, in ISO 4217 standard format.	Currency

PurchaseShipmentResponse

The response schema for the purchaseShipment operation.

Name	Description	Schema
payload <i>optional</i>	The payload for the purchaseShipment operation.	PurchaseShipmentResult

OneClickShipmentRequest

The request schema for the OneClickShipment operation. When the channelType is not Amazon, shipTo is required and when channelType is Amazon shipTo is ignored.

Name	Description	Schema
shipTo <i>optional</i>	The ship to address.	Address
shipFrom <i>required</i>	The ship from address.	Address
returnTo <i>optional</i>	The return to address.	Address
shipDate <i>optional</i>	The ship date and time (the requested pickup). This defaults to the current date and time.	string (date-time)
goodsOwner <i>optional</i>	The seller owning the goods before handing them over to the carrier	GoodsOwner
packages <i>required</i>	A list of packages to be shipped through a shipping service offering.	PackageList
valueAddedServicesDetails <i>optional</i>	This field is deprecated. This field only supports the Collect on Delivery (COD) value added service.	OneClickShipmentValueAddedServiceDet
valueAddedServices <i>optional</i>	A collection of supported value-added services.	ValueAddedServiceDetails
taxDetails <i>optional</i>	A list of tax detail information.	TaxDetailList
channelDetails <i>required</i>	Shipment source channel related information.	ChannelDetails
labelSpecifications <i>required</i>	The document specifications requested. For calls to the purchaseShipment operation, the shipment purchase fails if the specified document specifications are not among those returned in the	RequestedDocumentSpecification

Name	Description	Schema
	response to the getRates operation.	
serviceSelection <i>required</i>	Service Selection Criteria.	ServiceSelection
shipperInstruction <i>optional</i>	Optional field for shipper instruction.	ShipperInstruction
destinationAccessPointDetails <i>optional</i>	AccessPointDetails object	AccessPointDetails

Note: Package dimensions are normalized upon submission. The largest dimension value is assigned to length, the middle to width, and the smallest to height. Units are preserved.

OneClickShipmentResponse

The response schema for the OneClickShipment operation.

Name	Description	Schema
payload <i>optional</i>	The payload for the OneClickShipment API.	OneClickShipmentResult

OneClickShipmentResult

The payload for the OneClickShipment API.

Name	Description	Schema
shipmentId <i>required</i>	The unique shipment identifier provided by a shipping service.	ShipmentId
packageDocumentDetails <i>required</i>	A list of post-purchase details about a package that will be shipped using a shipping service.	PackageDocumentDetailList
promise <i>required</i>	The time windows promised for pickup and delivery events.	Promise
carrier <i>required</i>	Carrier Related Info	Carrier
service <i>required</i>	Service Related Info	Service
rateItems <i>optional</i>	A list of RateItem	RateItemList
totalCharge <i>required</i>	The monetary value in the currency indicated, in ISO 4217 standard format.	Currency

GetAccessPointsResponse

The response schema for the GetAccessPoints operation.

Name	Description	Schema
payload <i>optional</i>	The payload for the GetAccessPoints API.	GetAccessPointsResult

GetAccessPointsResult

The payload for the GetAccessPoints API.

Name	Description	Schema
accessPointsMap <i>required</i>	Map of type of access point to list of access points	AccessPointsMap

AccessPointsMap

Map of type of access point to list of access points

Type : < string, [AccessPointList](#) > map

AccessPointId

Unique identifier for the access point

Type : string

GetAdditionalInputsResult

The JSON schema to use to provide additional inputs when required to purchase a shipping offering.

Type : object

GetAdditionalInputsResponse

The response schema for the getAdditionalInputs operation.

Name	Description	Schema
payload <i>optional</i>	The JSON schema to use to provide additional inputs when required to purchase a shipping offering.	GetAdditionalInputsResult

ClientReferenceDetails

Object to pass additional information about the MCI Integrator shipperType: List of ClientReferenceDetail

Type : < [ClientReferenceDetail](#) > array

ClientReferenceDetail

Client Reference Details

Name	Description	Schema
clientReferenceType <i>required</i>	Client Reference type.	enum (ClientReferenceType)
clientReferenceId <i>required</i>	The Client Reference Id.	string

ShipmentType

Shipment type.

Type : enum

Value	Description
FORWARD	Additional information about shipment representing package journey from origin address to destination address in the transportation/shipping request.
RETURNS	Additional information about shipment representing package journey from destination address to origin/return address in the original transportation/shipping request.

PaymentType

Payment type of the purchase.

Type : enum

Value	Description
PAY_THROUGH_AMAZON	Payment Through Amazon.
PAY_DIRECT_TO_CARRIER	Payment Direct to Carrier.

AdjustmentItemList

A list of RateItem.

Type : < [RateItem](#) > array

RateItemList

A list of RateItem

Type : < [RateItem](#) > array

RateItem

Rate Item for shipping (base cost, transaction fee, confirmation, insurance, etc.) Data source definition:

Name	Description	Schema
rateItemID <i>optional</i>	Unique ID for the rateItem.	RateItemID
rateItemType <i>optional</i>	Type of the rateItem.	RateItemType
rateItemCharge <i>optional</i>	The monetary value in the currency indicated, in ISO 4217 standard format.	Currency
rateItemNameLocalization <i>optional</i>	Used for the localization.	string

RateItemID

Unique ID for the rateItem.

Type : enum

Value	Description
BASE_RATE	for Base Rate.
TRANSACTION_FEE	Charge for TransAction Fee.
ADULT_SIGNATURE_CONFIRMATION	Charge for Adult Signature Confirmation.
SIGNATURE_CONFIRMATION	Charge for signature confirmation.
NO_CONFIRMATION	Charge for No Confirmation.
WAIVE_SIGNATURE	Charge for Waive Signature.
IMPLIED_LIABILITY	Charge for Implied Liability.
HIDDEN_POSTAGE	Hidden Postage Charge.
DECLARED_VALUE	Declared Value Coverage Charge.
SUNDAY_HOLIDAY_DELIVERY	Sunday Holiday Delivery Charge.
DELIVERY_CONFIRMATION	Charge for Delivery Confirmation.
IMPORT_DUTY_CHARGE	Import Duty Charge.
VAT	Vat Charge.
NO_SATURDAY_DELIVERY	Charge for No Saturday Delivery.
INSURANCE	Insurance Charge.
COD	COD Charge.
FUEL_SURCHARGE	Fuel Surcharge.

Value	Description
INSPECTION_CHARGE	Inspection Charge.
DELIVERY_AREA_SURCHARGE	Delivery Area Surcharge.
WAYBILL_CHARGE	WayBill Charge.
AMAZON_SPONSORED_DISCOUNT	Amazon Sponsored Discount.
INTEGRATOR_SPONSORED_DISCOUNT	Integrator Sponsored Discount.
OVERSIZE_SURCHARGE	OverSize Surcharge.
CONGESTION_CHARGE	Congestion Charge.
RESIDENTIAL_SURCHARGE	Residential Surcharge.
ADDITIONAL_SURCHARGE	Additional Surcharge.
SURCHARGE	Surcharge.
REBATE	Rebate.
HIGH_CUBE_SURCHARGE	High Cube Surcharge.
HIGH_LENGTH_SURCHARGE	High Length Surcharge.
HIGH_WIDTH_SURCHARGE	High Width Surcharge.
DEMAND_SURCHARGE	A fee that is applied during specific periods of increased demand on the network as specified in the Amazon Shipping Service guide.
NONSTANDARD_FEE	A fee that applies for packages that are outside the standard size for processing and sorting as specified in the Amazon Shipping Service guide.
NON_CONVEYABLE_SURCHARGE	A handling surcharge which applies to a package, as defined in the Non-Conveyable Surcharge section of the Amazon Shipping Service guide.
OTP_ON_DELIVERY_FEE	A fee for one-time passcode on delivery value added service as defined in the Amazon Shipping Service Guide.
FBM_SHIP_PLUS_CREDIT	A charge adjustment for FBM Ship plus.

RateItemType

Type of the rateItem.

Type : enum

Value	Description
MANDATORY	Rate Item is mandatory.
OPTIONAL	Rate Item is Optional.
INCLUDED	Rate Item is included.

Benefits

Benefits that are included and excluded for each shipping offer. Benefits represents services provided by Amazon (eg. CLAIMS_PROTECTED, etc.) when sellers purchase shipping through Amazon. Benefit details will be made available for any shipment placed on or after January 1st 2024 00:00 UTC.

Name	Description	Schema
includedBenefits <i>required</i>	A list of included benefits.	IncludedBenefits
excludedBenefits <i>required</i>	A list of excluded benefit. Refer to the ExcludeBenefit object for further documentation	ExcludedBenefits

IncludedBenefits

A list of included benefits.

Type : < string > array

ExcludedBenefits

A list of excluded benefit. Refer to the ExcludeBenefit object for further documentation

Type : < [ExcludedBenefit](#) > array

ExcludedBenefit

Object representing a benefit that is excluded for a shipping offer or rate.

Name	Description	Schema
benefit <i>required</i>	Benefit that is being excluded from a shipment.	string
reasonCodes <i>optional</i>	List of reasons (eg. LATE_DELIVERY_RISK, etc.) indicating why a benefit is excluded for a shipping offer.	ExcludedBenefitReasonCodes

ExcludedBenefitReasonCodes

List of reasons (eg. LATE_DELIVERY_RISK, etc.) indicating why a benefit is excluded for a shipping offer.

Type : < string > array

Min items : 1

ServiceSelection

Service Selection Criteria.

Name	Description	Schema
serviceld <i>required</i>	A list of Serviceld.	Servicelds

Servicelds

A list of Serviceld.

Type : < string > array

Please find the current list of service id [here](#).

OneClickShipmentValueAddedServiceDetails

This field is deprecated. This field only supports the Collect on Delivery (COD) value added service.

Type : < [OneClickShipmentValueAddedService](#) > array

OneClickShipmentValueAddedService

A value-added service to be applied to a shipping service purchase.

Name	Description	Schema
id <i>required</i>	The identifier of the selected value-added service.	string
amount <i>optional</i>	The monetary value in the currency indicated, in ISO 4217 standard format.	Currency

Service

Service Related Info

Name	Description	Schema
id <i>required</i>	An identifier for the shipping service.	ServiceId
name <i>required</i>	The name of the shipping service.	ServiceName

Carrier

Carrier Related Info

Name	Description	Schema
id <i>required</i>	The carrier identifier for the offering, provided by the carrier.	CarrierId
name <i>required</i>	The carrier name for the offering.	CarrierName

PackingGroup

The specific packaging group of the item being shipped.

Type : enum

Value	Description
I	Packing group I indicates great danger.
II	Packing group II indicates medium danger.
III	Packing group III indicates minor danger.

ClientReferenceType

Client Reference type.

Type : enum

Value	Description
IntegratorShipperId	The unique identifier assigned to a 3P seller by the shipping integrator.
IntegratorMerchantId	The unique identifier assigned to a 3P shipping integrator by Amazon.

ChargeType

The type of charge.

Type : enum

Value	Description
TAX	A tax imposed on a package.
DISCOUNT	A discount deducted from the cost of a package.

PackingInstruction

The specific packing instruction of the item being shipped.

Type : enum

Value	Description
PI965_SECTION_IA	Ion PI965 Section IA (LiBa)
PI965_SECTION_IB	Ion PI965 Section IB (LiBa)
PI965_SECTION_II	Ion PI965 Section II (LiBa)
PI966_SECTION_I	Ion PI966 Section I (LiBa with equipment)

Value	Description
PI966_SECTION_II	Ion PI966 Section II (LiBa with equipment)
PI967_SECTION_I	Ion PI967 Section I (LiBa in equipment)
PI967_SECTION_II	Ion PI967 Section II (LiBa in equipment)
PI968_SECTION_IA	Metal PI968 Section IA (LiBa)
PI968_SECTION_IB	Metal PI968 Section IB (LiBa)
PI969_SECTION_I	Metal PI969 Section I (LiBa with equipment)
PI969_SECTION_II	Metal PI969 Section II (LiBa with equipment)
PI970_SECTION_I	Metal PI970 Section I (LiBa in equipment)
PI970_SECTION_II	Metal PI970 Section II (LiBa in equipment)

X-amzn-shipping-business-id

Amazon shipping business to assume for this request. The default is AmazonShipping_UK.

Type : enum

Value	Description
AmazonShipping_US	The United States Amazon shipping business.
AmazonShipping_IN	The India Amazon shipping business.
AmazonShipping_UK	The United Kingdom Amazon shipping business.
AmazonShipping_IT	The Italy Amazon shipping business.
AmazonShipping_ES	The Spain Amazon shipping business.
AmazonShipping_FR	The France Amazon shipping business.
AmazonShipping_JP	The Japan Amazon shipping business.

carrier-id

Amazon shipping carrier-id to be used for tracking api.

Type : enum

Value	Description
AMZN_US	The United States Amazon shipping carrier id.
ATS	The India Amazon shipping carrier id.
AMZN_UK	The United Kingdom Amazon shipping carrier id.
AMZN_IT	The Italy Amazon shipping carrier id.
AMZN_ES	The Spain Amazon shipping carrier id.
AMZN_FR	The France Amazon shipping carrier id.

AccessPointTypes

Type : enum

Value	Description
HELIX	Available now for AccessPoints APIs
CAMPUS_LOCKER	-
OMNI_LOCKER	-
ODIN_LOCKER	-
DOBBY_LOCKER	-

Value	Description
CORE_LOCKER	-
3P	-
CAMPUS_ROOM	-

Unit

Type : enum

For use with the definition(s): [LiquidVolume](#)

The unit of measurement.

Value	Description
ML	Milliliter - Metric unit of volume.
L	Liter - Metric unit of volume.
FL_OZ	Fluid Ounce - Imperial unit of volume.
GAL	Gallon - Imperial unit of volume.
PT	Pint - Imperial unit of volume.
QT	Quart - Imperial unit of volume.
C	Cup - Imperial unit of volume.

For use with the definition(s): [Dimensions](#), [DocumentSize](#)

The unit of measurement.

Value	Description
INCH	The imperial unit of length equal to one twelfth of a foot.
CENTIMETER	A metric unit of length, equal to one hundredth of a meter.

For use with the definition(s): [Weight](#)

The unit of measurement.

Value	Description
GRAM	Metric unit of mass equal to one thousandth of a kilogram.
KILOGRAM	Metric unit of mass.
OUNCE	The imperial unit of weight that is one sixteenth of a pound.
POUND	The imperial unit of weight.

 Updated 3 months ago