

1_Power

BUCK 12V – 4V5

C : X5R/X7R

BUCK 12V – 6V

C : X5R/X7R

BUCK 12V – 3V3

C : X5R/X7R

2_MCU

3_PERIPHERAL

The diagram shows four input channels for the 4_MPRLS0025PA00001A, each connected to a +3V3 supply and GND. The components and connections are as follows:

- VALVE1_IN:** Connected to VALVE1+IN. The signal path includes a 10k resistor (R16) and a 0.1μF/25V/0603/1% capacitor (C23) in parallel. The input is controlled by a switch (SW1).
- VALVE2_IN:** Connected to VALVE2+IN. The signal path includes a 10k resistor (R17) and a 0.1μF/25V/0603/1% capacitor (C24) in parallel. The input is controlled by a switch (SW2).
- PUMP1_IN:** Connected to PUMP1+IN. The signal path includes a 10k resistor (R18) and a 0.1μF/25V/0603/1% capacitor (C25) in parallel. The input is controlled by a switch (SW3).
- PUMP2_IN:** Connected to PUMP2+IN. The signal path includes a 10k resistor (R19) and a 0.1μF/25V/0603/1% capacitor (C26) in parallel. The input is controlled by a switch (SW4).

All input lines are labeled with a 10V/25V/0603/1% specification. The output of the device is labeled C : X5R/X7R.

