

TRANSMISSION OIL POWER STEERING OIL

Benefits of TIL Power Steering Fluids -

- Are made to keep up with power steering lubricant and for cars where Dexron@IID or Mercon performance is required.
- It is also suitable for light Commercial Vehicles (LCV's) trucks and buses where specified by the OEM.
- Compatible with other power steering fluids thus can be used for refilling existing systems.
- Assists in - reducing power steering "squeal", in reducing wear, in reducing corrosion and rust in power steering systems thus extending system life.

COOLANT

TIL Coolant Range are -

- Approved and latest technology products that are outstanding protection, maintaining performance under extreme conditions also.
- Fully formulated ethylene glycol base Coolant that has improved heat transferability.
- Organic Acid Technology provides superior corrosion and rust protection for reduced maintenance.
- Meets requirements of industry-leading specifications - JIS K 2234 Class 2, ASTM D3306, BS 6580:2010.

Our Sales Partners
Auto Corp Sales PTY Ltd. Australia
36/12 Crefden St Maidstone VIC3012,
Australia
Contact.: +91 721 929 1344 TIL
Our office Dhruvi Sales Corporation H-
15, Ambiance Aura, Near Madhuban
Society Sinhgad Road, Pune 411024
Email (for Sales)
Dhruvisales@theimperiallubricants.in
Email (Feedback)
info@theimperiallubricants.
in 2017 TIL, all trademarks used
herein are trademarks or registered
trademarks of TIL or one of its
subsidiaries.

WEBSITE

<http://www.theimperiallubricants.in/>



THE IMPERIAL LUBRICANTS



ENGINE OIL



TRANSMISSION OIL



GEAR OIL



INDUSTRIAL OIL



20W40

- Extends engine life.
- Keeps engines clean for smoother operation.
- Protects critical engine components.
- Year-round engine protection and performance Meets the requirements of SAE, API CK-4/SP, JASO MA-2 Suitable for petrol, diesel, and CNG engine up to 6,000kms - 8,000kms- (*in ideal conditions only) Available in synthetic and mineral.

20W50

- Extends engine life
- Keeps engines clean for smoother operation
- Protects critical engine components
- Year-round engine protection and performance Meets the requirements of SAE, API CK-4/SP, JASO MA-2 Suitable for petrol up to 8,000kms (*in ideal conditions only) Available in synthetic., diesel, and CNG engine

15W50

- Excellent acceleration
- Excellent protection
- Enduring performance
- Smooth riding
- Keeps engine cool Meets the requirements of SAE, API CK-4/SP, JASO MA-2 Suitable for petrol engine up to 6,000kms - 8,000kms- (*in ideal conditions only)

10W30

- Reduces engine noise and vibration
- Protects and prolongs engine life
- Synthetic 10W30 4 Stroke Engine Oil Meets the requirements of SAE, API CK-4/SP, JASO MA-2 Suitable for petrol engine up to 8,000kms(*in ideal conditions only) Available in synthetic.

20W50

- Less oil consumption, reduced engine internal friction, and extreme pressure performance, for more power and high shear stability offering increased gearbox reliability
- Jaso MA2 ensure optimum clutch performance at start-up, acceleration, and full speed
- API SP provide improved high-temperature deposit protection for more rigid sludge control
- Low oil film grip at low revolution speed offering increased torque
- Optimized friction control offering increased clutch grip for better motricity
- Use of non-fossil renewable materials meets the requirements of SAE, API CK-4/SP, JASO MA-2 Suitable for petrol engine up to 10,000kms (*in ideal conditions only) Available in synthetic.

15W50

- To maximize short and long term engine performance
- To sustain improved performance for longer, even when under pressure
- Enhanced fuel efficiency, independently qualified
- Excellent levels of protection across a variety of driving conditions and temperatures meet the requirements of SAE, API CK-4/SP, JASO MA-2 Suitable for petrol up to 12,000kms (*in ideal conditions only) Available in synthetic, diesel, and CNG engine

5W40

- Full synthetic engine oil for SUVs providing Non-Stop protection from start
- DUALOCK Technology gives 50% better protection from warm-up, stop-start and heavy load wear
- Suitable for use in SUVs with Petrol, Diesel and CNG powered engine meets the requirements of : SAE, API CK-4/SP, JASO MA-2 Suitable for petrol up to 22,000kms(*in ideal conditions only) Available in synthetic

5W40

- Universal use for petrol and diesel engines
- Good cold-start behavior
- High lubricating film stability and high wear protection
- Low evaporation losses
- High shear and aging stability Meet the requirements of SAE, API CK-4/SP, JASO MA-2 Suitable for petrol up to 10,000kms(*in ideal conditions only) Available in synthetic. , diesel and CNG engine

GEAR OIL

- Gear Oil: 75w-85, 80w-90, 90, 140
- Contains extreme pressure additives, that Deliver superior performance by reducing heat transmission in the gear set.
- Provides excellent gear protection for extreme and high load conditions.
- Prevents gear from pitting and hence minimizes wear.
- The high load-carrying capability ensures gears operating under high loads are protected, prolonging component life.
- Meets the requirements of SAE, API GL-4/5