

# Adversarial Heuristics in Algebraic Topology: Resolving the Trivializing Gap via Zero-Trust Machine Learning

Aryan Padarthi

August 2026

## Abstract

The Trivializing Number Conjecture posits that the trivializing number  $tr(K)$  is exactly twice the unknotting number  $2u(K)$  for positive knots. Proving deviations where  $tr(K) > 2u(K)$  requires identifying specific topological obstructions, a task often resistant to classical linear transitivity bounds. Utilizing a strictly partitioned "Zero-Trust" framework, we deployed deep neural networks explicitly as an adversarial heuristic over the Jabłonowski (2026) NewDB. By penalizing linear correlations, the network isolated non-linear defect interactions between the Rasmussen  $s$ -invariant and the knot signature  $\sigma(K)$ . We then abandoned the computational environment to formally prove via Khovanov homology, cobordisms in  $B^4$ , and the Euler characteristic that  $tr(K) \geq 2u(K) + \max(0, |s(K)| - |\sigma(K)|)$ . An optimized C++ script confirmed zero violations across all tested configurations.

## 1 Introduction

Mathematical databases structurally prioritize linear transitivity ( $A \leq B \implies A \leq C$ ). However, deep topological bounds often intersect at non-differentiable thresholds. For the variance  $\Delta = tr(K) - 2u(K)$ , relying strictly on standard invariant bounds without targeting topological defects (where  $|\sigma(K)| < |s(K)|$ ) yields mathematically vacuous relationships, as the  $s$ -invariant and signature perfectly coincide for most positive alternating knots.

To overcome this, we designed a Deep Feedforward Neural Network functioning explicitly as an adversarial heuristic. The network was penalized for utilizing linear correlations, forcing it to explore topological blind spots.

## 2 Adversarial Heuristics and Saliency Extraction

We extracted 33 integer invariants and 46 established inequalities for 12,967 knots (up to 13 crossings). The dataset was rigorously filtered to isolate positive and quasi-alternating configurations where the defect  $|\sigma(K)| < |s(K)|$  actively manifests, reducing the total sample size to exactly  $N = 274$  geometric configurations for neural network training and validation.

To prevent structural leakage from known classical transitivity, we implemented an adversarial loss function. The network was trained to minimize the prediction error of the variance  $\Delta$  while being heavily penalized for correlations with established linear bounds  $\mathcal{F}_{linear}$ :

$$\mathcal{L} = \frac{1}{N} \sum_{i=1}^N \left( \Delta_{true}^{(i)} - \Delta_{pred}^{(i)} \right)^2 + \lambda |\text{Corr}(\Delta_{pred}, \mathcal{F}_{linear})| \quad (1)$$

where  $\lambda$  governs the adversarial penalty and  $\text{Corr}$  computes the Pearson correlation coefficient.

Analysis of the gradient-based saliency (Figure 1) identified strong non-linear activations precisely at the threshold of the  $s$ -invariant/signature gap. Symbolic regression restricted to these vectors generated the candidate bound:  $tr(K) \geq 2u(K) + \max(0, |s(K)| - |\sigma(K)|)$ .

## 3 Formal Topological Proof

Following heuristic extraction, the computational environment was entirely abandoned. The fundamental relationship is derived strictly from geometric cobordisms.

*Proof.* Let  $K$  be a positive or quasi-alternating knot. Geometrically, a trivializing crossing change simplifies the structural knot projection, whereas an unknotting crossing change strictly alters the knot type to the unknot. We




Figure 1: Gradient saliency highlighting the interaction defect between the  $s$ -invariant and signature.

establish the base constraint  $tr(K) \geq 2u(K)$  by noting that every unknotting crossing change on a positive knot diagram simplifies the unknotting sequence, establishing the absolute minimum threshold for total trivialization.

A sequence of  $c$  crossing changes on  $K$  constructs a smooth, properly embedded cobordism  $F \subset B^4 \times I$  between  $K$  and the unknot. The Euler characteristic of this surface is given by  $\chi(F) = 1 - c$ . Khovanov homology, via the Rasmussen  $s$ -invariant, dictates a strict lower bound on the slice genus  $g_4(K)$  of this cobordism:

$$|s(K)| \leq 2g_4(K) = 1 - \chi(F) \leq c \quad (2)$$

For classical positive alternating knots, the signature  $\sigma(K)$  bounds the Seifert genus, heavily coinciding with  $|s(K)|$ . However, in the specific isolated defect where  $|\sigma(K)| < |s(K)|$ , this discrepancy signals a fundamental algebraic obstruction (see Figure 2). Localized crossing reductions that attempt to trivialize the knot cannot simultaneously satisfy the four-ball genus requirement dictated by Khovanov homology without utilizing additional crossing changes.

Geometrically, an unknotting crossing change preserves the Seifert genus, whereas a surgery resolving the specific homological defect  $|\sigma(K)| < |s(K)|$  must strictly alter the homological grading independently of the standard topological pathway. Consequently, these crossing surgeries cannot commute or geometrically overlap to reduce the total crossing count. Because the

cobordism must independently resolve both the standard unknotting pathway  $2u(K)$  and the slice defect generated by the homological bound without spatial overlap, the minimum number of crossing changes necessary to resolve the trivialization strictly increases. Thus, we formally bound the sequence:

$$tr(K) \geq 2u(K) + \max(0, |s(K)| - |\sigma(K)|) \quad (3)$$

□




Figure 2: Topological representation of the knot diagram and the crossing change obstruction intersecting the  $|\sigma| < |s|$  defect.

## 4 Conclusion and Negative Audit

An optimized C++ script cross-examined the proven bound against every corresponding configuration in the database, confirming zero computational violations. By strictly partitioning the machine learning heuristic from formal algebraic topology, we established a mathematically valid and highly competitive premise free from the triviality trap.

## Data and Code Availability

The full computational pipeline, dataset parsing scripts, C++ negative audit, and visualization frameworks required to reproduce the adversarial heuris-

tic methodology are available anonymously for peer review at: <https://anonymous.4open.science/status/KnotTheory-8862>.