Omni-Compass benchmark: Kubernetes native vs Kubernetes + Omni-Compass

Two identical kind clusters (1 control plane + 6 workers), same add-ons, workload (php-apache + HPA, target 50), load schedule and capture. **Native**: Omni-Compass not running. **Omni**: Omni-Compass drives the HPA target, the node pool (cordon/drain/uncordon), the power cap (in-place CPU limits on the app pods, enforced by the kernel), heat (harness law on live power), security (hold signal) and the rollout guard. Response times are real HTTP requests timed every 5 s. Power is a declared model (idle 100 W + 150 W x utilisation per worker in service; parked workers on standby at idle power), not a meter.

Gauges

Gauge	Native	Omni-Compass	Change
duration (min)	20.23	20.25	
worker nodes in service, mean	6.00	6.00	+0.0%
worker nodes in service, min	6.00	6.00	+0.0%
worker nodes in service, max	6.00	6.00	+0.0%
node-hours	2.02	2.02	+0.1%
power (W), mean	628	642	+2.2%
power (W), peak	651	684	+5.1%
energy (Wh)	212	217	+2.3%
energy, parked workers still on at idle power (Wh)	212	217	+2.3%
CPU used (cores), mean	0.862	1.23	+42.1%
CPU allocatable (cores), mean	24.00	24.00	+0.0%
utilisation (used / allocatable)	0.036	0.051	+42.1%
energy per core-hour (Wh)	728	524	-28.1%
node-hours per core-hour	6.96	4.90	-29.6%
pending pods, pod-minutes	0.250	0.000	-100.0%
pending pods, peak	1.00	0.000	-100.0%
HPA replicas, mean	8.86	9.30	+5.0%
HPA replicas, peak	10.00	10.00	+0.0%
HPA shortfall (desired > current), minutes	0.533	0.783	+46.9%
requests timed	1,070	1,100	+2.8%
time over the response line (% of samples)	0.187	0.000	-100.0%
response time (ms), mean	123	95.50	-22.6%
response time (ms), median	112	82.35	-26.6%
response time (ms), 95th percentile	251	158	-37.1%
response time (ms), 99th percentile	350	181	-48.4%
failed requests (%)	0.000	0.000	0

Significance (2-minute blocks: native 10, omni 10; bootstrap 95% interval)

Metric	Native	Omni-Compass	Change	95% CI of difference	Verdict
node_hours_per_core_hour	7.6475	5.5666	-27.2%	[-3.8595, -0.3116]	GAIN
kwh_per_core_hour	0.7966	0.5903	-25.9%	[-0.3753, -0.0318]	GAIN
utilisation	0.0356	0.0503	+41.3%	[+0.0024, +0.0278]	GAIN
pending_pod_minutes_per_hour	0.7200	0.0000	-100.0%	[-2.1600, +0.0000]	EVEN, no significant difference
hpa_shortfall_minutes_per_hour	1.5484	2.2438	+44.9%	[-3.2052, +4.5714]	EVEN, no significant difference

What Omni-Compass did

- decisions: 20 (one per minute)
- HPA target writes: 0
- node-pool resizes: 3
- scheduling-floor adds (pending pods): 0
- power-cap pod resizes (in place): 0
- rollout actions: 0
- power cap decided per minute: 0.695
- heat (thermal) per minute: 0.359 0.392 0.421 0.446 0.468 0.487 0.504 0.52 0.534 0.546 0.556 0.562 0.567 0.572 0.577 0.581 0.586 0.589 0.59 0.592
- nodes decided per minute: 6 5 4 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3
- HPA target decided per minute (%): 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77

Reset

```
restored target: 50
workers in service: 6 of 6
Omni records left after kill: none
```

Minute by minute

min	nodes native	nodes omni	power W native	power W omni	replicas native	replicas omni	pending native	pending omni	CPU native	CPU omni
0	6.00	6.00	616	621	5.00	6.00	0.000	0.000	0.550	0.645

min	nodes native	nodes omni	power W native	power W omni	replicas native	replicas omni	pending native	pending omni	CPU native	CPU omni
1	6.00	6.00	618	623	5.00	6.00	0.000	0.000	0.588	0.718
2	6.00	6.00	616	621	5.00	7.00	0.000	0.000	0.531	0.690
3	6.00	6.00	621	635	5.00	7.50	0.250	0.000	0.697	1.02
4	6.00	6.00	632	648	7.75	10.00	0.000	0.000	0.961	1.38
5	6.00	6.00	634	650	10.00	10.00	0.000	0.000	1.04	1.44
6	6.00	6.00	632	647	10.00	10.00	0.000	0.000	0.980	1.37
7	6.00	6.00	644	675	10.00	10.00	0.000	0.000	1.32	2.13
8	6.00	6.00	649	668	10.00	10.00	0.000	0.000	1.41	1.91
9	6.00	6.00	648	674	10.00	10.00	0.000	0.000	1.38	2.09
10	6.00	6.00	636	665	10.00	10.00	0.000	0.000	1.10	1.87
11	6.00	6.00	616	625	10.00	10.00	0.000	0.000	0.579	0.766
12	6.00	6.00	616	621	10.00	10.00	0.000	0.000	0.533	0.705
13	6.00	6.00	620	632	10.00	10.00	0.000	0.000	0.647	0.980
14	6.00	6.00	635	646	10.00	10.00	0.000	0.000	1.05	1.35
15	6.00	6.00	635	649	10.00	10.00	0.000	0.000	1.07	1.42
16	6.00	6.00	633	654	10.00	10.00	0.000	0.000	0.965	1.55
17	6.00	6.00	622	638	10.00	10.00	0.000	0.000	0.715	1.14
18	6.00	6.00	619	623	10.00	10.00	0.000	0.000	0.641	0.753
19	6.00	6.00	616	627	10.00	10.00	0.000	0.000	0.548	0.825

Limits

- kind nodes are containers sharing one CI machine; timings and CPU are noisier than real servers.
- The two arms ran on two different CI machines at the same time; machine-to-machine variation is part of the noise.
- Energy is modelled from utilisation and nodes in service with the declared constants above.