Omni-Compass benchmark: Kubernetes native vs Kubernetes + Omni-Compass

Two identical kind clusters (1 control plane + 6 workers), same add-ons, workload (php-apache + HPA, target 50), load schedule and capture. **Native**: Omni-Compass not running. **Omni**: Omni-Compass drives the HPA target, the node pool (cordon/drain/uncordon), the power cap (in-place CPU limits on the app pods, enforced by the kernel), heat (harness law on live power), security (hold signal) and the rollout guard. Response times are real HTTP requests timed every 5 s. Power is a declared model (idle 100 W + 150 W x utilisation per worker in service; parked workers on standby at idle power), not a meter.

Gauges

Gauge	Native	Omni-Compass	Change
duration (min)	20.17	20.08	
worker nodes in service, mean	6.00	6.00	+0.0%
worker nodes in service, min	6.00	6.00	+0.0%
worker nodes in service, max	6.00	6.00	+0.0%
node-hours	2.02	2.01	-0.4%
power (W), mean	626	641	+2.5%
power (W), peak	646	682	+5.6%
energy (Wh)	210	215	+2.1%
energy, parked workers still on at idle power (Wh)	210	215	+2.1%
CPU used (cores), mean	0.794	1.22	+53.8%
CPU allocatable (cores), mean	24.00	24.00	+0.0%
utilisation (used / allocatable)	0.033	0.051	+53.8%
energy per core-hour (Wh)	788	525	-33.4%
node-hours per core-hour	7.56	4.91	-35.0%
pending pods, pod-minutes	0.250	0.000	-100.0%
pending pods, peak	1.00	0.000	-100.0%
HPA replicas, mean	8.70	9.45	+8.7%
HPA replicas, peak	10.00	10.00	+0.0%
HPA shortfall (desired > current), minutes	0.517	0.517	+0.0%
requests timed	1,130	1,095	-3.1%
time over the response line (% of samples)	0.000	0.000	0
response time (ms), mean	64.36	95.98	+49.1%
response time (ms), median	44.00	81.50	+85.2%
response time (ms), 95th percentile	149	154	+2.9%
response time (ms), 99th percentile	221	179	-19.1%
failed requests (%)	0.000	0.000	0

Significance (2-minute blocks: native 10, omni 9; bootstrap 95% interval)

Metric	Native	Omni-Compass	Change	95% CI of difference	Verdict
node_hours_per_core_hour	8.4516	5.3717	-36.4%	[-5.1128, -1.0855]	GAIN
kwh_per_core_hour	0.8767	0.5705	-34.9%	[-0.5071, -0.1110]	GAIN
utilisation	0.0328	0.0518	+58.3%	[+0.0064, +0.0332]	GAIN
pending_pod_minutes_per_hour	0.7258	0.0000	-100.0%	[-2.1774, +0.0000]	EVEN, no significant difference
hpa_shortfall_minutes_per_hour	1.4942	1.6340	+9.4%	[-2.8078, +2.6746]	EVEN, no significant difference

What Omni-Compass did

• decisions: 20 (one per minute)

• HPA target writes: 0

• node-pool resizes: 3

• scheduling-floor adds (pending pods): 0

• power-cap pod resizes (in place): 0

• rollout actions: 0

• power cap decided per minute: 1.0 1.0 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695

• heat (thermal) per minute: 0.358 0.392 0.421 0.446 0.469 0.489 0.505 0.52 0.534 0.547 0.557 0.562 0.567 0.572 0.577 0.581 0.585 0.589 0.59 0.591

• nodes decided per minute: 6 6 5 4 4 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3

• HPA target decided per minute (%): 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77

Reset

```
restored target: 50
workers in service: 6 of 6
Omni records left after kill: none
```

Minute by minute

min	nodes native	nodes omni	power W native	power W omni	replicas native	replicas omni	pending native	pending omni	CPU native	CPU omni
0	6.00	6.00	612	618	6.00	6.00	0.000	0.000	0.442	0.629

min	nodes native	nodes omni	power W native	power W omni	replicas native	replicas omni	pending native	pending omni	CPU native	CPU omni
1	6.00	6.00	614	626	6.00	7.50	0.000	0.000	0.474	0.784
2	6.00	6.00	614	624	6.00	8.00	0.000	0.000	0.496	0.759
3	6.00	6.00	618	633	6.00	8.00	0.250	0.000	0.582	0.954
4	6.00	6.00	631	646	7.00	10.00	0.000	0.000	0.922	1.37
5	6.00	6.00	633	648	9.00	10.00	0.000	0.000	0.942	1.40
6	6.00	6.00	634	643	9.00	10.00	0.000	0.000	1.01	1.25
7	6.00	6.00	638	667	9.33	10.00	0.000	0.000	1.14	1.91
8	6.00	6.00	645	679	10.00	10.00	0.000	0.000	1.30	2.23
9	6.00	6.00	643	675	10.00	10.00	0.000	0.000	1.25	2.11
10	6.00	6.00	638	670	10.00	10.00	0.000	0.000	1.11	1.99
11	6.00	6.00	617	624	10.00	10.00	0.000	0.000	0.554	0.735
12	6.00	6.00	615	621	10.00	10.00	0.000	0.000	0.597	0.727
13	6.00	6.00	625	632	10.00	10.00	0.000	0.000	0.765	0.967
14	6.00	6.00	629	646	10.00	10.00	0.000	0.000	0.896	1.36
15	6.00	6.00	631	648	10.00	10.00	0.000	0.000	0.891	1.39
16	6.00	6.00	629	646	9.00	10.00	0.000	0.000	0.901	1.36
17	6.00	6.00	622	631	9.00	10.00	0.000	0.000	0.709	1.09
18	6.00	6.00	615	623	9.00	10.00	0.000	0.000	0.521	0.713
19	6.00	6.00	614	624	9.00	10.00	0.000	0.000	0.484	0.738

Limits

- kind nodes are containers sharing one CI machine; timings and CPU are noisier than real servers.
- The two arms ran on two different CI machines at the same time; machine-to-machine variation is part of the noise.
- Energy is modelled from utilisation and nodes in service with the declared constants above.