Omni-Compass benchmark: Kubernetes native vs Kubernetes + Omni-Compass

Two identical kind clusters (1 control plane + 6 workers), same add-ons, workload (php-apache + HPA, target 50), load schedule and capture. **Native**: Omni-Compass not running. **Omni**: Omni-Compass drives the HPA target, the node pool (cordon/drain/uncordon), the power cap (in-place CPU limits on the app pods, enforced by the kernel), heat (harness law on live power), security (hold signal) and the rollout guard. Response times are real HTTP requests timed every 5 s. Power is a declared model (idle 100 W + 150 W x utilisation per worker in service; parked workers on standby at idle power), not a meter.

Gauges

Gauge	Native	Omni-Compass	Change
duration (min)	20.23	20.08	
worker nodes in service, mean	6.00	6.00	-0.0%
worker nodes in service, min	6.00	6.00	+0.0%
worker nodes in service, max	6.00	6.00	+0.0%
node-hours	2.02	2.01	-0.7%
power (W), mean	630	638	+1.4%
power (W), peak	652	676	+3.7%
energy (Wh)	212	214	+0.6%
energy, parked workers still on at idle power (Wh)	212	214	+0.6%
CPU used (cores), mean	0.910	1.15	+26.1%
CPU allocatable (cores), mean	24.00	24.00	-0.0%
utilisation (used / allocatable)	0.038	0.048	+26.1%
energy per core-hour (Wh)	692	556	-19.6%
node-hours per core-hour	6.59	5.23	-20.7%
pending pods, pod-minutes	0.000	0.533	new
pending pods, peak	0.000	2.00	new
HPA replicas, mean	9.20	9.39	+2.1%
HPA replicas, peak	10.00	10.00	+0.0%
HPA shortfall (desired > current), minutes	0.783	0.533	-31.9%
requests timed	1,025	1,120	+9.3%
time over the response line (% of samples)	1.17	0.000	-100.0%
response time (ms), mean	175	75.79	-56.7%
response time (ms), median	141	68.55	-51.5%
response time (ms), 95th percentile	374	105	-71.9%
response time (ms), 99th percentile	522	123	-76.4%
failed requests (%)	0.000	0.000	0

Significance (2-minute blocks: native 10, omni 10; bootstrap 95% interval)

Metric	Native	Omni-Compass	Change	95% CI of difference	Verdict
node_hours_per_core_hour	7.1993	6.0026	-16.6%	[-2.9501, +0.5611]	EVEN, no significant difference
kwh_per_core_hour	0.7520	0.6329	-15.8%	[-0.2821, +0.0572]	EVEN, no significant difference
utilisation	0.0374	0.0469	+25.3%	[-0.0023, +0.0221]	EVEN, no significant difference
pending_pod_minutes_per_hour	0.0000	1.5360	n/a	[+0.0000, +4.6080]	EVEN, no significant difference
hpa_shortfall_minutes_per_hour	2.2797	1.5360	-32.6%	[-3.8035, +3.0902]	EVEN, no significant difference

What Omni-Compass did

• decisions: 20 (one per minute)

• HPA target writes: 0

• node-pool resizes: 3

• scheduling-floor adds (pending pods): 0

• power-cap pod resizes (in place): 0

• rollout actions: 0

• power cap decided per minute: 1.0 1.0 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695 0.695

• heat (thermal) per minute: 0.358 0.392 0.421 0.445 0.468 0.487 0.503 0.518 0.531 0.543 0.553 0.559 0.564 0.569 0.574 0.579 0.582 0.586 0.588 0.589

• nodes decided per minute: 6 5 4 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3

• HPA target decided per minute (%): 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77 77

Reset

```
restored target: 50
workers in service: 6 of 6
Omni records left after kill: none
```

Minute by minute

min	nodes native	nodes omni	power W native	power W omni	replicas native	replicas omni	pending native	pending omni	CPU native	CPU omni
0	6.00	6.00	618	618	5.00	7.00	0.000	0.000	0.587	0.582

min	nodes native	nodes omni	power W native	power W omni	replicas native	replicas omni	pending native	pending omni	CPU native	CPU omni
1	6.00	6.00	618	621	7.00	7.00	0.000	0.000	0.638	0.689
2	6.00	6.00	618	622	7.00	7.00	0.000	0.000	0.601	0.730
3	6.00	6.00	624	631	7.00	7.25	0.000	0.500	0.752	0.935
4	6.00	6.00	634	644	9.00	10.00	0.000	0.000	1.04	1.30
5	6.00	6.00	634	644	9.33	10.00	0.000	0.000	1.04	1.27
6	6.00	6.00	635	643	10.00	10.00	0.000	0.000	1.05	1.28
7	6.00	6.00	645	656	10.00	10.00	0.000	0.000	1.33	1.66
8	6.00	6.00	648	671	10.00	10.00	0.000	0.000	1.39	1.99
9	6.00	6.00	646	669	10.00	10.00	0.000	0.000	1.35	1.97
10	6.00	6.00	640	652	10.00	10.00	0.000	0.000	1.18	1.53
11	6.00	6.00	620	622	10.00	10.00	0.000	0.000	0.650	0.727
12	6.00	6.00	620	620	10.00	10.00	0.000	0.000	0.662	0.649
13	6.00	6.00	624	629	10.00	10.00	0.000	0.000	0.762	0.946
14	6.00	6.00	638	644	10.00	10.00	0.000	0.000	1.13	1.30
15	6.00	6.00	634	644	10.00	10.00	0.000	0.000	1.03	1.30
16	6.00	6.00	634	647	10.00	10.00	0.000	0.000	1.04	1.39
17	6.00	6.00	627	638	10.00	10.00	0.000	0.000	0.826	1.17
18	6.00	6.00	619	623	10.00	10.00	0.000	0.000	0.638	0.742
19	6.00	6.00	618	620	10.00	10.00	0.000	0.000	0.597	0.655

Limits

- kind nodes are containers sharing one CI machine; timings and CPU are noisier than real servers.
- The two arms ran on two different CI machines at the same time; machine-to-machine variation is part of the noise.
- Energy is modelled from utilisation and nodes in service with the declared constants above.