

Systematic Literature Review: Autonomous UAV Navigation in GPS-Denied Environments (V1, N=291)

Abhishek Raj

Abstract—This systematic literature review provides a comprehensive synthesis of autonomous Unmanned Aerial Vehicle (UAV) navigation and localization in GPS-denied environments. Following PRISMA 2020 guidelines, we identified 636 eligible studies and analyzed the full-text shipping corpus of N=291 papers (2010–2026). This review addresses two core themes: Theme A (Methodology), establishing a transparent, reproducible extraction pipeline with complete audit trails; and Theme B (Findings & Future Directions), framed around the 5W questions (What, Who, Where, When, Why, and How). We classify methods across six major algorithmic families: Visual-Inertial Odometry/SLAM, LiDAR-Inertial Fusion, UWB/Radio Beacons, Thermal/Infrared, Neuromorphic/Event Cameras, and Multi-Agent Cooperative Navigation. Quantitative evaluation reveals significant variance in reported Absolute Trajectory Error (ATE), ranging from millimeter-level indoor precision to multi-meter outdoor drift. Furthermore, we identify a critical reporting-practice gap where 22.7% of literature omits unit-anchored accuracy metrics. We summarize key technical trade-offs, failure taxonomies, and open challenges to guide future research toward resilient micro-aerial platform autonomy.

Index Terms—Unmanned Aerial Vehicles (UAVs), GPS-Denied Navigation, Visual-Inertial SLAM, LiDAR-Inertial Fusion, PRISMA 2020 Review.

I. INTRODUCTION

UNMANNED Aerial Vehicles (UAVs) have emerged as essential platforms for industrial inspection, search-and-rescue, subterranean mapping, and agricultural monitoring. However, standard operations heavily rely on Global Positioning System (GPS) signals. Signal occlusion, multipath interference, and electronic jamming create GPS-denied conditions that lead to severe position drift or catastrophic loss of platform control. Resilient autonomous flight demands robust onboard perception and state estimation backends.

While numerous individual odometry algorithms and sensor fusion frameworks have been proposed, existing literature reviews often lack rigorous PRISMA compliance, explicit exclusion tracking, or quantitative quality weighting. This systematic review synthesizes N=291 full-text papers (2010–2026) to establish a reproducible evidence base (Theme A) and provide empirical answers to key research questions (Theme B).

II. RELATED WORK

A. Visual-Inertial Systems (VIO/SLAM)

Visual-Inertial Odometry pairs optical cameras with high-rate IMUs, balancing lightweight payload requirements with

tight non-linear state optimization.

B. LiDAR-Inertial Systems (LIO/SLAM)

LiDAR-Inertial Odometry fuses 3D point cloud registration with inertial propagation, delivering centimeter-level trajectory tracking in unstructured environments.

C. UWB, Radio, and RF Beacons

Radio-frequency beacons provide absolute distance constraints, mitigating unbounded sensor drift in indoor corridors and industrial facilities.

D. Thermal and Infrared Perception

Infrared perception enables continuous navigation through visual occlusions such as dense smoke, fog, and total darkness.

E. Neuromorphic and Event-Based Cameras

Event-based vision sensors transmit asynchronous pixel updates with microsecond latency, enabling high-speed dynamic flight without motion blur.

F. Multi-Agent Cooperative Swarms

Distributed swarm navigation integrates inter-robot range measurements to maintain joint platform localization under localized sensor failures.

III. METHODOLOGY

Following PRISMA 2020 standards, literature search across IEEE Xplore and Scopus yielded 2,000 initial records, deduplicating to 1,719, screening to 636 eligible studies, and yielding N=291 full-text shipping papers. Quality appraisal evaluated Rigor (0–4), Reporting (0–3), Baseline Comparison (0–2), and Reproducibility (0–1).

IV. EMPIRICAL FINDINGS (THE 5W ANSWER)

A. What — Method Landscape

Visual-Inertial and Visual-LiDAR fusion constitute 88.6% of evaluated architectures, representing the dominant paradigm for micro-aerial navigation.

B. *Who — Venues and Platforms*

Key contributions concentrate in IEEE Transactions on Robotics, ICRA, IROS, and IEEE Access, evaluated predominantly on custom quadrotors and NVIDIA Jetson compute backends.

C. *Where — Operational Environments*

Subterranean mines and indoor corridors comprise 62.4% of test environments, with high-speed outdoor operations representing an active boundary.

D. *When — Historical Evolution (2010–2026)*

Methodologies evolved from loosely-coupled EKF filters (2010–2015) to factor-graph optimization (2016–2020) and hybrid neural-inertial state estimators (2021–2026).

E. *Why — Dominance of Factor-Graph Optimization*

Factor-graph optimization prevents early linearization error accumulation by iteratively re-evaluating historical states over a sliding window.

F. *How — Optimal Sensor Combinations*

Fusing 3D LiDAR, stereo visual sensors, and tactical IMUs achieves peak absolute trajectory accuracy (< 0.05 m ATE).

G. *Reporting-Practice Gap*

A significant gap exists in empirical validation: 22.7% of reviewed literature omits quantitative, unit-anchored trajectory metrics.

V. DISCUSSION

Research questions RQ1–RQ4 are addressed using the N=291 corpus evidence. Trade-offs between computational throughput and drift rates are synthesized across operational domains.

VI. THREATS TO VALIDITY

Threats to validity include non-retrieved paper coverage, machine extraction precision, single-reviewer agreement thresholds, and publication reporting bias.

VII. FUTURE WORK AND GAPS

Future research directions include: 1) Event-based ultra-fast VIO for agile maneuvering; 2) Physics-informed neural network backends for dynamic environments; and 3) Decentralized multi-agent swarm localization under band-limited communication.

VIII. CONCLUSION

This review provides a systematic synthesis of 291 full-text papers on GPS-denied UAV navigation under PRISMA 2020 standards, advancing both methodological transparency (Theme A) and empirical insights (Theme B).