Multi-Agent Programming Contest MASSim Server Manual (2015 Edition)

http://www.multiagentcontest.org/

Tobias Ahlbrecht Jürgen Dix Federico Schlesinger May 18, 2015

New in 2015: Since we implemented a brand new scenario for 2015, scenario specific configuration have changed. The general server configuration, however, remains the same.

Contents

1	Sta	rting the Programs	2
	1.1	MASSim Server	2
	1.2	MASSim Monitor	2
	1.3	MASSim Web Server	2
2	Cor	nfiguring MASSim	3
	2.1	General Configuration	3
	2.2	Simulation Configuration	4
		2.2.1 Roles	7
		2.2.2 Products	
		2.2.3 Facilities	8
		2.2.4 Jobs	10
		2.2.5 Agents	11
	2.3	9	

1 Starting the Programs

For Microsoft Windows we suggest that you install MSYS¹ or Cygwin² in order to run the MASSim-software taking advantage of the shell scripts.

1.1 MASSim Server

You can start the MASSim server by invoking this:

\$./startServer.sh

You will then be prompted to choose a simulation. We mention the files explicitly. The server generates XML files, statistics etc. Please have a look at the folders (output and backup that were generated during a run.

1.2 MASSim Monitor

In parallel you can also start the monitor which will allow you to observe the current simulation. The monitor can be invoked like this:

\$./startMapMonitor.sh

The monitor has currently two different options for the visualization. Please have a look at the scenario description for details. Also note, this monitor provides you with complete information. Your agents on the other hand do not have access to complete information.

The monitor also stores the match on hard disk. You can view these files by invoking:

\$./startMapFileViewer.sh /path/where/the/files/are

1.3 MASSim Web Server

For the tournament we always provide a web server that is running on an Apache using Apache Tomcat and RMI as well as XML and XSLT. This server is not needed for the development of your multi-agent system, however, for the sake of completeness we provide some information how to install it. A install script that explains the procedure is placed in scripts/tools/. If you have any questions please contact the organizers.

New in 2015:
Monitor name
has been updated

¹http://www.mingw.org/wiki/MSYS

²http://www.cygwin.com/

2 Configuring MASSim

When starting MASSim, you must provide a configuration file to the server. Configuration files are XML-based, and a set of configuration files is already available in the scripts/conf sub-folder of your MASSim installation. A detailed explanation of the configuration file is given next.

2.1 General Configuration

The general structure of the configuration file is depicted in Fig. 1. Note, however, that we use some additional XML features that allows us to use more than one file and reuse parts of the XML in different parts of the configuration. Therefore, you have to look into the main file as well as into the corresponding config.dtd file. You can set a starting time with time now. Also, a debug-level was introduced. Additionally, we describe some parameters in more detail.

```
<?xml version="1.0" encoding="UTF-8"?>
        backuppath="backup"
<conf
        launch-sync-type="key"
        reportpath="./backup/"
        time="14:05"
        time-to-launch="10000"
        tournamentmode="0"
        tournamentname="City2015"
        debug-level="normal" >
    <simulation-server>
        <network-agent backlog="10" port="12300"/>
    </simulation-server>
    <match>
        <simulation ...> ... </simulation>
        <simulation ...> ... </simulation>
    </match>
    . . .
    <match>
    </match>
    <accounts>
        . . .
    </accounts>
</conf>
```

Figure 1: General structure of the MASSim configuration-file.

Tag: conf. The attributes of the conf tag are the following:

- backuppath The path where important information of each simulation step is stored.
- launch-sync-type Determines whether the server is started by pressing ENTER or after a certain time defined in time-to-launch or at time point (defined by time). The value can be key, timer or time.
- reportpath The path where the overall tournament results are stored.
- time The time point for the option time.
- time-to-launch The time for the option timer.
- tournamentmode Defines the structure of the tournament. 0 sets it to a round robin tournament. 1 is used when only one team should play against all others. Finally, 2 allows one to set up all matches manually. You have to add some code similar to the one in Fig. 2 after </match> to make it work.

```
<manual-mode>
  <match team1="A" team2="B"/>
  <match team1="A" team2="C"/>
  <match team1="B" team2="D"/>
  </manual-mode>
```

Figure 2: Manual mode.

- tournamentname Sets the tournament name to this value.
- debug-level Changes the verbosity of the output on shell. Allowed values: debug, normal, critical, error.

Tag: simulation-server. The simulation-server tag has one child which has two attributes. backlog defines the time intervals (in milliseconds) for printing the debug messages to stdout or stderr respectively. The attribute port sets the port of the server.

Tag: match. A configuration can have one or more match tags, that will be instantiated depending on the tournamentmode attribute.

Tag: accounts. Finally, the accounts tag contains the details about the agents that are allowed to take part in the matches.

2.2 Simulation Configuration

The simulation tag is used to specify the scenario to be run, along with all the parameters that affect the simulation.

Tag: simulation. The attributes available for the simulation tag are the following:

- id An identifier for the simulation. To distinguish among different instances of the simulation executed during a tournament, this identifier will be appended to the names of the teams taking part in that instance.
- simulationclass The name of the main Java class implementing the scenario. For the 2015 Mars Scenario, the class that must be used here is massim.competition2015.MapSimulation.
- configuration class The name of the Java class that will hold the configuration data specified in the configuration child tag. For the 2015 Logistics Scenario, the class to use is massim.competition2015.configuration.MapSimulationConfiguration.
- rmixmlobsserverhost The host to which the scenario monitor should connect.
- rmixmlobsserverport The port to which the scenario monitor should connect.
- rmixmlobserver The name of the Java class that will translate the current scenario state into XML data, and send it via RMI to the scenario monitor when connected. For the 2015 Logistics Scenario, the class to use is massim.competition2015.MapSimulationRMIXMLDocumentObserver.
- xmlstatisticsobserver This is needed for the *Apache Tomcat* Connection Status and Results page.
- rmixmlobserverweb This is needed for the *Apache Tomcat* Current Simulation and Results page.
- visualisationobserver This defines the class for the visualization.
- visualisationobserver-outputpath This defines the output path for the visualization files.
- xmlobserver This allows one to store the results of a simulation as xml file.
- xmlobserverpath This is the path for the xmlobserver.

A skeleton XML for the simulation tag is shown in Fig. 3. It has two children: configuration and agents. The configuration part is scenario-specific, and must be in correspondence with the configuration class specified in the simulation attributes. For the 2015 Logistics scenario, the configuration attributes are the following:

• maxNumberOfSteps - The number of steps that the simulation must run until determining a winner.

```
<simulation ...>
    <configuration ...>
        <roles>
            <role ...>
                 <roads>
                     <road .../>
                     <road .../>
                 </roads>
                 <tools>
                     <tool .../>
                     <tool .../>
                 </tools>
            </role>
        </roles>
        <facilities>
           <facility ...>
                <location .../>
           </facility>
        </facilities>
        <jobs>
           <job ...>
                cproducts>
                   cproduct ...>
                   . . .
                </products>
           </job>
        </jobs>
        cproducts>
           cproduct ...>
                <requirements>
                   cproduct ...>
                   . . .
                </requirements>
           </product>
        </products>
    </configuration>
    <agents>
        <agent ...>
            <configuration .../>
        </agent>
        <agent ...>
            <configuration .../>
        </agent>
        . . .
    </agents>
                                  6
</simulation>
```

Figure 3: Simulation XML structure

- numberOfAgents The total number of agents that take part in the simulation run.
- numberOfTeams The number of teams that take part in the simulation run.
- minLon, minLat, maxLon, maxLat Max and min latitude and longitude of the map to use. Currently this only affects the visualization tool.
- proximity Determines the max lateral and vertical distance that two elements may be from each other, to be considered to be at the same location. It is determined as a fraction of degrees of Latitude/longitude³
- cellSize Determines the size of the unit of distance that is calculated when agent move (agent's speed determines how many times this distance is advanced in a single step). It is determined as a fraction of degrees of Latitude/longitude³.

2.2.1 Roles

The roles section defines the different roles that agents participating in the simulation will assume. A role encompasses all the internal characteristics of the agent. The following attributes should be specified for each role:

- name The name by which this role is referenced.
- speed The speed at which the agent moves in a single step (a positive integer). The units of distance are determined by the configuration's attribute cellSize.
- loadCapacity Determines the maximum volume that the agent is able to carry (a positive integer).
- batteryCapacity Determines the maximum possible battery charge (a positive integer).

The roads section determines the kind of paths that the agents of this role can take for moving from one location to another. Each one is defined by a road tag with a single name attribute (e.g. <roads><road name="road"/></roads>). Currently we only define two kinds of road: road, which allows the agent to use regular streets, and air, which allows an agent to move in straight line to its destination.

The tools section determines which items can be used as tools by agents of this roles, when assembling new items. Each one is defined by a tool tag with a single id attribute (e.g. <tools><tool id="tool1"/><tool id="tool2"/></tools>). The available items are defined in the products section described below.

³For simplification purposes, Latitude and Longitude are used in this regards as if its units were uniform and they formed a perfect grid.

2.2.2 Products

The products section defines the characteristics of all the different items to be used in the simulation. The following attributes should be specified for each item:

- id The id by which this item is referenced.
- volume A positive integer, indicates the volume of this item, which ultimately limits the total number of items that an agent may carry, that may be stored in a storage facility, etc.
- userAssembled Either true or false, determines whether agents may assemble this product from other products.

When the product may be assembled by agents, a list of requirements (products) follows. An example can be seen below. Each product in the list has three attributes:

- id The id of the item.
- amount The quantity of instances of this product needed to assemble one unit of the root product.
- consumed Either true or false, determines whether this items are lost during the assembly of the root product (i.e., this product is used as prime matter), or not (i.e., this product is used as a tool).

2.2.3 Facilities

The facilities section defines all the different facilities present in the simulation. Some attributes depend on the type of the facility, but common to all are the id of the facility, and type, which can be one either shop, workshop, storage, dump or charging. Additionally, all facilities define their position in the map in the sub-tag location which includes two attributes: lat and lon, as real numbers.

The additional attributes for each type of facility are described next:

- workshop:
 - cost An integer indicating the cost associated to using this facility on a single step.

• storage:

- cost An integer indicating the cost (per unit of volume) associated to storing items at this facility.
- capacity An integer indicating the max possible total sum of the volumes of the items stored at this facility.

• dump:

 cost - An integer indicating the cost associated to using this facility on a single step.

• charging:

- cost An integer indicating the cost per unit of battery charge at this charging station.
- rate An integer indicating the charging rate, i.e., the number of units of battery charge by which the charge of an agent is increased on a single step (when the agent is indeed charged and its max charge is not reached).
- concurrent An integer indicating the max number of agent that
 may be effectively charging their batteries at this station the same
 time (when these number is reached, following agents are temporarily
 placed into a queue).
- shop: Shops do not define extra attributes. Instead, they define a list of products (available for buying at that shop) as shown in the example below. The attributes for each product in this list are:
 - id The id of the item.
 - amount The quantity of instances of this product that the shop holds in stock at the beginning of the simulation.
 - cost An integer indicating the price of a single unit of this item in this shop.
 - restock The number of simulation steps after which a new unit of this item is added to the shop's stock (0 means never).

```
<facility type="shop" id="shop1">
    <location lat="52.3619" lon="9.7299"/>
    <products>
        <product id="item1" cost="5" amount="500" restock="2" />
            <product id="item2" cost="17" amount="50" restock="3"/>
        </products>
</facility>
```

2.2.4 Jobs

The jobs section defines the system-created jobs for the simulation. Some attributes depend on the type of job, but most of them are common. All are described below:

- id The id by which the job will be identified.
- type The type of job: either priced or auction.
- firstStepAuction⁴ The number of the simulation step at which this Job shall begin its auction period.
- firstStepActive The number of the simulation step at which this Job shall become active (for auction jobs this means the end of the auction period).
- lastStepActive The number of the simulation step at which this Job shall be finalized if it wasn't completed.
- reward⁵ The reward to give that completes this priced job (integer).
- maxReward⁴ The biggest bid amount for this job that shall be accepted if no better bid is placed (integer).
- fine⁴ The amou
- storageId the id of the storage facility where the items must be delivered in order to complete this job.

The target of the job is defined as a list of products (under the sub-tag cproducts>)) where each product (sub-tag cproduct>)) has just two attributes:
The id of the product and the amount required. Here is an example of an auction job:

⁴Only for auction jobs.

 $^{^5{}m Only}$ for priced jobs.

2.2.5 Agents

The agents part of the simulation configuration is where it is defined how server-side teams are to be composed during the simulation. Agents defined here will be matched with agents defined in the accounts section to be controlled externally by the participants. This matching of agents varies in function of the tournamentmode parameter explained in 2.1.

The attributes for the agent tag are:

- team The server-side name of the team.
- agentclass The name of main Java class implementing the agents. For the 2015 Mars scenario, the class to use is massim.competition2015.GraphSimulationAgent.
- agentcreationclass The name of the Java class that will hold the configuration parsed from the configuration child tag. For the 2015 Mars scenario, the class to use is massim.competition2015.GraphSimulationAgentParameter.

The configuration child tag for the 2015 Logistics scenario has three attribute: roleName, which refers to the name of one of the previously defined roles; and lat and lon that define the initial location of the agent.

2.3 Accounts Configuration

In the accounts section of the configuration file, one can configure the developers' team that will participate in the tournament, and with which credentials each developer-side agent will connect to *MASSim* to control its server-side counterpart.

The actionclassmap has one attribute name and defines all available action classes for the agent accounts. Each actionclass has a class attribute and an id. An account is structured as follows:

- actionclassmap Refers to the actionclassmap name that is used for this
 account.
- auxtimeout Additional timeout for messages. The purpose of this parameter is to give the agents some additional time to allow the server to process the message.
- defaultactionclass Sets the default action class.
- maxpacketlength Defines the maximal length of on message.
- password The password for the agent.
- team The team name for the agent.
- timeout The timout for messages.
- username The user name of the agent.