


Anatomy of an Intelligence Substrate

System Architecture and Emergent Telemetry of the "Six" Engine



CLASSIFIED
SPECIFICATION DOCUMENT

[THE PARTICLE]

The Programmable Value Token
(Data Architecture)

[THE MUSCLE]

Multi-Substrate Compute Matrix
(Hardware Execution)

[THE NERVOUS SYSTEM]


UniConn Transport Layer
(Network Protocol)

[THE BRAIN]

Adaptive Markov Trie & Kadabra
(Emergent Intelligence)

[THE CORE] Memory Map and Programmable Data Structure (Hardware Implementation)


[WORDS 0-7]
Tokens (512 bits): The raw cryptographic or sensory input data.



[WORDS 8-15]
Affinity (512 bits): LSH and Bloom filter overlaps defining structural identity.



[WORDS 16-23]
Program (512 bits): In-band execution opcodes. The data carries its own logic.




```
<344E;
0005, 0083;
0078, 30710, 4101;
5010, 0401:70023; 7, 008, 21;
0085, 21[31];
5001: 30
...
```

[WORDS 24-31]
Signals (512 bits): The projection output after truth-table execution.




X	X	A	T
0	0	1	0
0	0	1	0
1	1	0	1
1	1	0	1



[THE CHRONICLE] Temporal State Tracking and Deterministic Clocking (Logic Flow and LFSR)




AccumulateDelta: Compresses the change between two states as a differential sketch via direct XOR of the Token regions into the StateAccumulator word.



LFSRStep: Advances the StateSequence word through a maximal-length cycle (8191 states) to provide deterministic, distributed clocking without wall-time synchronization.

[THE EXECUTION SURFACE] Universal Bitwise Parallel Processing (Hardware Implementation)




Static "A" Region: The noometre proceeded in a rigidic holding brackst be locked in a rigid-static holding bracket.

16-Phase "B" Rotation: mounted 16-Phase mouniters for 8 bits each time, easrly shifts the rotation track dlayam.

[THE HARDWARE BACKEND MATRIX] Diagnostic Comparison (Platform Capabilities)



	x86 / ARM64	Nvidia CUDA	Apple Silicon
Architecture	CPU	GPU	SoC
SIMD Instruction	AVX2 & SSE2 / NEON	PTX Kernels	Metal Shading Language
Memory Model	In-band pointer access	Host-to-Device Copy	StorageModeShared (Unified Memory)
Primary Advantage	Ultra-low latency single frames	Massive parallel batch throughput	Zero-copy hardware sharing



[THE PRIORITY SPILL RING] High-Performance Bounded Queue System

prioritySpillRing

A 65,536-capacity multi-producer, multi-consumer (MPMC) bounded queue.

Lock-Free Coordination

Producers and consumers coordinate exclusively via atomic operations on sequence, head, and tail indices—zero mutexes.


Producer Input

SECONDARY OVERFLOW QUEUE

Overflow Handling

Saturated PRIORITY frames block until the unified queue drains, capping worst-case fan-in without unbounded memory allocation.

[THE NETWORK LAYER] UniConn Value Distribution Prism (Transport Delegation)



Unified
io.ReadWriteCloser
Interface



Loopback

Value

2

Broadcast

00:501
Lazy Readiness Evaluation

00:301
Active Transport Delegation

UniConn

3

Armored Tunnel

IPC (Same-Machine)

Unix Domain Sockets

- Highly reliable ☒
- Message-oriented ☒
- Used for local multi-process substrates. ☒

UDP (LAN Broadcast)

Native Multicast (224.0.0.x)

- Unreliable, unordered ☒
- One write = one datagram ☒
- Used for local area swarm discovery and gossip. ☒

QUIC (WAN Reliable)

Built on x/net/quic

- Reliable, ordered, encrypted ☒
- Bidirectional streams ☒
- Used for secure, long-distance peer-to-peer tunnels. ☒

[THE COMMUNICATION FABRIC] Circuit Breaker State Machine

Failure Threshold
Consecutive connection or protocol failures trigger the breaker to open, instantly failing subsequent calls to protect resources.

Cooldown Timer
After the cooldown duration, the circuit enters a testing state to probe network recovery.



Failure Threshold Exceeded

Cooldown Timer Expired


Failure

Success

Success

Drop Saturation
Non-blocking error queues monitor for internal backpressure, logging dropped events if the worker pool is overwhelmed.

Standard XOR Routing



Randomized structural distribution,
blind to content.

Kadabra Affinity



"Like attracts like."
Clusters self-organize based on shared
knowledge domains and structural overlap.

[THE INTELLIGENCE FABRIC] Compute Affinity Flow

512-bit Tokens Region

73 97 113 131 151 167 181 199

Majority Vote

ComputeAffinityLSH

Projects the token region into a 512-bit space using 8 independent SimHash projections via majority vote. Stable but sensitive to structural similarities.


3-byte
n-grams

64-bit filter

ComputeAffinityBloom

Generates a 64-bit filter from overlapping 3-byte n-grams. High AND-popcount mathematically guarantees shared substrings.

[THE INTELLIGENCE FABRIC] Dynamic Surprisal Regulation





Adaptive State
Tunes fixed constants via lightweight online statistics.

Volatility Response
High surprisal (unexpected input) automatically accelerates decay (forgetting stale data) and lowers temperature (exploiting known paths).

Confidence Scaling
High classification entropy expands the context window and widens the search beam.

[THE INTELLIGENCE FABRIC] Self-Reinforcing Mechanical Loop



Consensus Mechanism
Decentralized node communication to establish a shared digest of the environment.


Structured Permutation
Affine coupling layers align bit representations across scales for coherence.

Dominant Thought Isolation
Eigenmode analysis identifies the primary mode of collective intelligence.

[THE INTELLIGENCE FABRIC] Attention By Differential Survival

In-Phase (Dominant Mode)

Decay pressure is suppressed
(retention amplified).
Learning pressure is amplified
(absorbs related input faster).



Anti-Phase (Noise)

Decay pressure is amplified (stale
knowledge pruned aggressively).
Learning pressure is suppressed
(wastes no effort on noise).



Attention By Survival
The system selects dominant modes
by differential survival, not neural
weight matrices.

[THE INTELLIGENCE FABRIC] Unified Value Propagation Schematic

