

Authors' Guide

Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

© 2025 Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

Text licensed under CC-by-SA-4.0

Code licensed under AGPL-3.0

This is (still!) an incomplete draft.

Please send any corrections, comments etc. to feedback_host@mailthing.com

Last updated May 25, 2025.

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

To a job well done

Table of Contents

Table of Contents iii

Chapter Sketches 1

✓

Chapter 1: Function Definitions & Flow Control 2

🔧

Chapter 2: Haskell Setup 3

abc

Chapter 3: Basic Datatypes 4

📊

Chapter 4: Types as Sets 5

📄

Chapter 5: Lists 6

↔

Chapter 6: Polymorphism & Higher Order Functions 7

🔄

Chapter 7: Advanced List Operations 8

📁

Chapter 8: Precomp Data Structures 9

🔗

Chapter 9: Computation as Reduction 10

☢

Chapter 10: Complexity 11

📁

Chapter 11: Post Comp Data Types 12

🏠

Chapter 12: Typeclasses 13

▶▶

Chapter 13: Monads 14

📁

Directory Structure 15

Pedagogy 16

Personality of Narrator 17

How to know whether a Concept has been Learnt 18

λ

function to an either type 18

What does it Mean to Teach a Haskell Concept ? 19

How to Teach a Haskell Concept 20

Using Imported Functions 21

Code Block 22

Inline Code Block 22

Floating Code Block 22

Literate Haskell 22

Hiding a Code Block 22

Code Block Title 22

λ

helloWorld function 22

Referencing a Code Block 22

Definition 23

Definition Box 23

Emphasizing the Subject 23

Emphasizing the Definition 23

Definition Box Title 23

⊆

empty set 23

Referencing a Definition 23

Exercise 24

Exercise Box 24

Exercise Box Custom Title 24

Referencing an Exercise 24

Proof 25

Proof Environment 25

Theorem Environment 25

Tree 26

Conversion 26

Displaying a Tree 26

Padding 26

Width of a Tree 26

Depth of a Tree 26

Wiiide Trees 26

Deeeep Trees 26

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

Chapter Sketches

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

✓ **Chapter 1: Function Definitions & Flow Control**

- **Topics:** Function definition, pattern matching, recursion, induction, `let`, `where`, `if-then-else` as flow control.
- **Time:** 1 Class + 1 Tutorial
- **Author:** RSA
- **Notes:** No polymorphism; fully pen-and-paper before code.

—

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

Chapter 2: Haskell Setup

- **Topics:** Minimal setup (hopefully using HaskellKISS) for different OS.
- **Time:** 1 Parallel Tutorial
- **Authors:**
 - **Windows:** R
 - **Linux:** S
 - **macOS:** A

—

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

Chapter 3: Basic Datatypes

- **Topics:**
 - `Bool`, `Int` vs `Integer` in extremely brief terms, `Char` (`ord`, `chr`)
 - Use of `.` vs `"."`
- **Time:** 1 Class + 1 Tutorial
- **Author:** A
- **Notes:** No polymorphism yet.
- **Assignment:** Number Theory & Logic Ops

—

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal



Chapter 4: Types as Sets

- **Topics:**
 - Tuples as \times , **Either** as \cup , **(\rightarrow)** as A^B , **::** as \in
 - Currying (concept only), implicit parentheses
 - Basic set theory concepts
- **Time:** 1 Class + 1 Tutorial
- **Author:** R

—



Chapter 5: Lists

- **Topics:**

- List definition & comprehension
- Lists as syntax trees
- Operations: `head`, `tail`, `!!`, `elem`, `drop`, `take`, `splitAt`
- Merge sort, infinite lists
- Code Examples:

```
l = 0 : l
l n = n : l (n+1)
l a b = a : l b (a+b)
```

- **Time:** 2 Classes + 2 Tutorials
- **Author:** R

—

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal



Chapter 6: Polymorphism & Higher Order Functions

- **Topics:**

- Intro to polymorphism
- Higher-order functions
- Operators and functions:

```
( $\$$ ) :: (a  $\rightarrow$  b)  $\rightarrow$  a  $\rightarrow$  b  
a  $\rightarrow$  b  $\rightarrow$  (a, b)  
curry, uncurry
```

- **Time:** 1 Class + 2 Tutorials
- **Author:** S

—

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

Chapter 7: Advanced List Operations

- **Topics:**
 - `map`, `filter`, Cartesian product, first through list comprehension, then explicitly defined
 - Quick sort through list comprehension
 - `zip`, `zipWith`
 - Folds, scans (with syntax tree understanding)
 - Miller–Rabin primality test
- **Time:** 2 Classes + 3 Tutorials
- **Author:** A

—

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal



Chapter 8: Precomp Data Structures

- **Topics:**
 - Define recursion in recursive data types
 - Define whatever happened in the basic datatypes section.
 - Define Nat, List, Tree
- **Time:**
- **Author:** A

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal



Chapter 9: Computation as Reduction

- **Topics:**
 - Reduction-based computation (skip Big O)
 - Syntax trees, lazy evaluation
 - Examples:
 - Fibonacci via infinite list
 - Test if the following works:

```
(map recip [-5..]) !! n
```

- **Time:** 1 Class + 2 Tutorials
- **Author:** S

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

Chapter 10: Complexity

- **Topics:**
 - Some Notion of complexity that is pretty theoretical
- **Time:**
- **Author:** A

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal



Chapter 11: Post Comp Data Types

- **Topics:**
 - Queue
 - Segment Trees
 - BST
 - Set
 - Map
- **Time:**
- **Author:** A

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal



Chapter 12: Typeclasses

- **Topics:**
 - Recall Polymorphism
 - `deriving`
 - Under the hood of `deriving`
 - Custom Classes
- **Author:** R
- **Time:**

Chapter 13: Monads

- **Topics:**

- Functors
- Applicative Functors?
- Monads:
 - Theory
 - Do notation
 - Simple Writer - Cost as `(,) Integer`
 - Maybe Monad
 - Simple Reader - `(→) x`
 - Simple State - Light Switch
 - Monoid Monad
 - Simple Writer - IO

- **Author:** R

- **Time:** 5 Classes + 5 Tutorials


—



Directory Structure

In general, do not make new typst files in the chapter area, just edit the previously existent ones. If you use a figure, please save it as a separate .typ or .asy file in figures and import when required.

haskell-course/



Tutorials, assignments and solutions refer to tutorial handouts(if needed), class and tutorial assignments and their solution files. Keep them as .typ/.tex files for now, the required .hs/.lhs files will be generated later.

Also, if you need to cite something, cite it at the end of your chapter as a comment starting with cite.

```
// cite:
// citation 1
// citation 2
```

I will at some point make a script to compile citations. OR We can use <https://typst.app/docs/reference/model/cite/> and Hayagriva

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

Pedagogy

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

Personality of Narrator

We always use the “we” grammatical turn as far as possible, and a few steps further still.

How to know whether a Concept has been Learnt

By testing whether they can parse Haskell in natural language

We can test a student upon their knowledge of a Haskell function by asking the student to narrate in detail in a natural language such as English, the steps the function is taking in the execution of its definition.

For example,

Consider the following problem : We have to make a function that provides feedback on a quiz. We are given the marks obtained by a student in the quiz marked out of 10 total marks. If the marks obtained are less than 3, return 'F', otherwise return the marks as a percentage -

λ function to an either type

```
feedback :: Integer → Either Char Integer
-- Left ~ Char, Integer ~ Right
feedback n
  | n < 3      = Left 'F'
  | otherwise = Right ( 10 * n ) -- multiply by 10 to get percentage
```

You then ask the student to describe in detail how the function works.

They should ideally answer - “

Let `feedback` be a function that takes an `Integer` as input and returns `Either` a `Char` or an `Integer`.

As `Char` and `Integer` occurs on the left and right of each other in the expression `Either Char Integer`, thus `Char` and `Integer` will henceforth be referred to as `Left` and `Right` respectively.

Let the input to the function `feedback` be `n`.

If `n<3`, then we return `'F'`. To denote that `'F'` is a `Char`, we will tag `'F'` as `Left`. (remember that `Left` refers to `Char`!)

`otherwise`, we will multiply `n` by `10` to get the percentage out of 100 (as the actual quiz is marked out of 10). To denote that the output `10*n` is an `Integer`, we will tag it with the word `Right`. (remember that `Right` refers to `Integer`!)

“

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

What does it Mean to Teach a Haskell Concept ?

Teaching is a very abstract notion. We can make that notion more explicit by assuming that what we actually want to do is get the student to a position where they can pass the test described in the above section with flying colours, i.e.,

Teaching \approx Teaching to pass the test of the previous section

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

How to Teach a Haskell Concept

Assuming the suppositions of the previous sections hold any water, the method to teach a Haskell concept appears quite simple -

Show the students how to parse Haskell in natural language over and over again until they get it

Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

Using Imported Functions

21

Code Block

We can write any text that is meant to be code using the usual syntax of using backticks (`).

Inline Code Block

We can make a code block in the middle of a line.

Let us take the ``hello`` function as an example.

Let us take the `hello` function as an example.

Floating Code Block

We can make a code block that floats out-of-line on its own.

```
```\n\nhello :: any → String\nhello  _  = "world"\n```\n
```

```
hello :: any → String\nhello _ = "world"
```

Literate Haskell

We are using `markdown-unlit` as our literate haskell pre-processor. It only processes those *floating* code blocks at *zero indentation depth* which have been *marked as haskell* code blocks. So, if you want your code to be visible to lhs, you need to write “haskell” immediately after the 3 backticks, leaving no space in between.

```
```\nhaskell\nhello :: any → String\nhello  _  = "world"\n```\n
```

```
hello :: any → String\nhello  _  = "world"
```

Hiding a Code Block

We can hide a code block by putting it inside the Typst function `#metadata()`.

```
#metadata(\n\n  hello :: any → String\n  hello  _  = "world"\n\n)\n
```

This can be *useful* if paired with the syntax required for *Literate Haskell*, as then we can have code that doesn’t appear on the PDF, but still executable by Literate Haskell. And thus readers would stilll be able to access it in GHCi without it taking up valuable reading space on the PDF.

Code Block Title

We will often find it a good idea to title a code block, because then it will show up in the table of contents, in the glossary and can be referenced. If the first line of the code in a *floating* code block begins with `-- |`, then the rest of that line will be taken as the title.

```
```\n\n-- | helloWorld function\nhello :: any → String\nhello  _  = "world"\n```\n
```

```
λ helloWorld function\nhello :: any → String\nhello _ = "world"
```

Referencing a Code Block

A *titled* definition with a *unique title* can referenced by the usual syntax.

Recalling `@code_of_helloWorld_function`, we can proceed.

Recalling `λ helloWorld function`, we can proceed.

## Definition

To use this module, we need to `#import "../Modules/Definition.typ": def`

### Definition Box

We can call the function `#def()` upon some content put that content in a *floating* definition box. We can put any text that is meant to be definition in a definition box.

```
#def[
 The empty set is the set that
 contains no elements or equivalently,
 $\{\}$.
]
```

The empty set is the set that contains no elements or equivalently,  $\{\}$ .

### Emphasizing the Subject

To increase readability, we can emphasize the subject of the definition by wrapping it in **\*\***.

```
#def[
 The *empty set* is the set that
 contains no elements or equivalently,
 $\{\}$.
]
```

The **empty set** is the set that contains no elements or equivalently,  $\{\}$ .

### Emphasizing the Definition

To increase readability, we can emphasize *the part of the text that is the actual definition* by wrapping that part in `__`.

```
#def[
 The empty set is the _set that
 contains no elements_ or equivalently,
 _ $\{\}$ _.
]
```

The empty set is the *set that contains no elements* or equivalently,  $\{\}$ .

### Definition Box Title

We will often find it a good idea to title a definition, because then it will show up in the table of contents, in the glossary and can be referenced.

We can set the `subject` settable argument of the `#def()` function to a **string** if we want to add a title.

```
#def(subject: "empty set")[
 The empty set is the set that
 contains no elements or equivalently,
 $\{\}$.
]
```

÷ **empty set**

The empty set is the set that contains no elements or equivalently,  $\{\}$ .

### Referencing a Definition

A *titled* definition with a *unique title* can be referenced by the usual syntax.

Recalling `@definition_of_empty_set`, we can proceed.

Recalling ÷ **empty set**, we can proceed.

## Exercise

To use this module, we need to `#import "../Modules/Exercise.typ": exercise`

### Exercise Box

We can call the function `#exercise()` upon some content put that content in a *floating* exercise box.

We can put any text that is meant to be an exercise in an exercise box.

```
#exercise[
 If a type `T` has n elements, then
 how many elements does `Maybe T` have?
]
```

#### Exercise

If a type `T` has  $n$  elements, then how many elements does `Maybe T` have?

### Exercise Box Custom Title

We will often find it a good idea to title an exercise, because then it will show up in the collection of exercises when we use `#exercises`, in the glossary and can be referenced.

We can set the `subject` settable argument of the `#exercise()` function to a **string** if we want to add a title.

```
#exercise(subject : "maybe")[
 If a type `T` has n elements, then
 how many elements does `Maybe T` have?
]
```

#### maybe

If a type `T` has  $n$  elements, then how many elements does `Maybe T` have?

### Referencing an Exercise

A *titled* exercise with a *unique title* can referenced by the usual syntax.

Recalling `@exercise_of_maybe`, we can proceed.

Recalling  `maybe`, we can proceed.

## Authors' Guide – Ryan Hota, Shubh Sharma, Arjun Maneesh Agarwal

### Proof

To use this module, we need to `#import " ../Modules/Proof.typ": proof`

### Proof Environment

We can call the function `#proof()` upon some content to prepend that content with a “Proof” tag. We can treat any text that is meant to be an proof in this manner.

```
#proof[
 Here is a proof.
]
```

**Proof** Here is a proof.

### Theorem Environment

To add line with a “Theroem” tag above the proof, we can set the `thm` settable argument of the `#proof` function to that line.

```
#proof(thm: [This is a theorem
statement.])[
 Here is a proof.
]
```

**Theorem** This is a theorem statement.

**Proof** Here is a proof.

