On the Edge of Stability: Spiking Reservoir State-Space Encoding of Affective EEG

Andrew A. Lane*, Wendy Tang*, and Brady D. Nelson†
*Department of Electrical and Computer Engineering, Stony Brook University, Stony Brook, NY, USA
†Department of Psychology, Stony Brook University, Stony Brook, NY, USA

***Abstract*—Affective EEG event-related potentials (ERPs) are noisy, subject-dependent measurements of evoked neural dynamics, and robustness rankings can depend as much on the evaluation protocol as on the representation. We compare four affective-ERP representations under subject-grouped validation with subject-level uncertainty: spectral band-power, ERP-window amplitudes, a fixed leaky integrate-and-fire reservoir summarized by a six-bin spike-count (BSC_6) embedding and operated near its measured edge of stability ($\rho^* \approx 0.82$, the onset of recurrence-driven firing, below the $\rho = 1$ echo-state heuristic; removing the recurrence costs 0.049 balanced accuracy, BA, 95% CI $[-0.098, -0.002]$), and a trained EEGNet, with electrode removal, amplitude noise, and temporal jitter applied to the raw signal identically for every encoder. Two channel-dropout artifacts are quantified and proved. Raw retention has a chance floor that favors near-chance models: the reservoir keeps 100% at 30% dropout because its clean BA, 0.487, is close to the $1/3$ floor. Zero-fill of dropped channels is not invariant to an information-preserving re-centering of the features, so it penalizes non-centered encoders: across 10–50% dropout, in-distribution fills raise them by up to 0.13 BA while the reservoir's near-centered embedding is unchanged by the constant fills, and at 30% dropout zero-fill halves the measured lead of ERP-window features over the reservoir ($+0.05$ versus $+0.09$ to $+0.11$ BA). For EEGNet, channel-dropout augmentation more than halves the loss to electrode removal (BA at 30% removal 0.660 to 0.703; clean 0.731). On DEAP, the fill rule alone moves the measured robustness of band-power features by up to 0.11 BA. We recommend reporting absolute accuracy with subject-level uncertainty alongside retention, stating and varying the fill rule, and reporting trained models with and without augmentation.**

***Index Terms*—EEG, event-related potentials, spiking neural networks, reservoir computing, affective computing, neuromorphic computing, ARSPI-Net.**

I. Introduction

Electroencephalographic event-related potentials (ERPs) provide millisecond-scale measurements of evoked neural dynamics, but the recorded waveform is a noisy, low-dimensional, and subject-dependent projection of an unobserved neural process [14], [15]. A representation may separate affective conditions under one protocol while preserving little usable structure after amplitude noise, temporal misalignment, or channel loss.

Endpoint accuracy alone also says little about what a representation preserves, which matters for spiking encodings. Fixed recurrent reservoirs and spiking networks provide nonlinear temporal expansions [1], [4], but EEG/ERP studies often treat them primarily as classifiers [11], [17]. How such encodings change under perturbation remains underreported, even though preprocessing and electrode-loss choices materially change EEG results [18]–[20].

This paper evaluates whether channel-dropout robustness rankings for affective-ERP representations are stable under reasonable changes to the scoring protocol. We compare spectral band-power, ERP-window amplitudes, a fixed leaky integrate-and-fire (LIF) reservoir summarized by six spike-count bins (BSC_6) and compressed for a linear readout, and a trained EEGNet. The reservoir is not a proposed winner but a fixed, near-centered reference whose dynamics are not retrained under perturbation. The contributions are:

1) A subject-grouped robustness comparison of affective-ERP representations under electrode removal, amplitude noise, and temporal jitter applied identically to every encoder's input, with subject-level confidence intervals and a permutation null (Secs. V-A, V-C; Tables I, III).
2) Two protocol artifacts in channel-dropout evaluation, raw-retention inflation near the chance floor and zero-fill bias for non-centered features, each stated as a proposition (Sec. III-E) and the second also tested on DEAP (Secs. V-B, V-D).
3) Paired subject-level evidence that zero-imputation halves the measured lead of ERP-window features over the reservoir, while channel-dropout augmentation more than halves the trained EEGNet's loss to electrode removal (Fig. 3, Tables II, III).
4) A fixed-reservoir reference analysis: a spectral-radius sweep with a no-recurrence ablation, a measured damage-spreading curve whose half-maximum crossing $\rho^* \approx 0.82$ marks the onset of recurrence-driven firing, with a one-step branching bound on where damage can first spread (Fig. 1), and a single-bin ablation separating the state-space expansion from temporal bin granularity (Eq. (4)).

Clinical labels and affective categories define the task structure; the representations and their invariances under perturbation are the object of study.

II. Related Work

ERP/EEG analysis commonly uses window amplitudes, Hjorth [12] and wavelet/spectral descriptors [13], and linear models [15], which are interpretable through known components such as the P300 and late positive potential [14] but can miss nonlinear temporal interactions. Reservoir computing offers a complementary approach: a fixed high-dimensional

recurrent system maps the input to a state trajectory read out by a simple classifier [1]–[4], and spiking liquid-state machines add event-based timing and count structure [7], [8]. Reservoir computation is often reported to peak near the transition between ordered and chaotic dynamics, located by how far a small state perturbation spreads [5], [6]; for a thresholded reservoir that transition need not coincide with the $\rho = 1$ echo-state heuristic [2] (Sec. III). When the recurrent dynamics are fixed, the reservoir can be analyzed as a measurement operator rather than only as a classifier.

Spiking and deep networks are now widely applied to EEG [11], [16], [17]. Much of this literature emphasizes endpoint accuracy over preprocessing and acquisition choices [20], [21]. Neuromorphic reservoir features for affective EEG were introduced in prior ARSPI-Net work [9], [10]; here we establish their perturbation and invariance properties and identify two scoring artifacts that distort robustness comparisons.

Dynamic spatial filtering addresses missing or corrupted channels with a learned channel-attention front end [23], and channel-dropout or amplitude-noise augmentation are standard ways to harden trained models [24]. A recent EEG foundation-model benchmark finds that apparent channel-dropout fragility can depend on whether dropped channels are removed or zero-padded [22]. More broadly, missing-data handling in neuroimaging spans a spectrum from constant fills and spherical-spline interpolation of absent electrodes [25], through learned imputation and learned spatial filtering [23], to conditional generative synthesis of entire missing modalities with ViT-GAN and latent-diffusion models [26], [27]. The four fills we study sit at the simple end of that spectrum, with no learned imputer. We separate two scoring effects, raw-retention inflation and zero-fill bias, and use the training-free, near-centered reservoir as the reference.

III. Methods

A. ERP Observation Model

Let $X_s^{(c)} \in \mathbb{R}^{C\times T}$ denote the trial-averaged ERP observation for subject s and affective condition c, with C electrodes (channels) and T temporal samples. We treat $X_s^{(c)}$ as a noisy observation of an unobserved neural state trajectory:

$$\xi_{t+1} = f_\theta(\xi_t, u_t) + \eta_t, \qquad x_t = H\xi_t + \epsilon_t, \tag{1}$$

where ξ_t is the latent neural state, H the scalp measurement operator, and ϵ_t measurement and preprocessing noise; the signal-level perturbations below act on this model (Sec. V-C).

B. Spiking Reservoir Encoding

For each electrode trace, the signal is passed through a fixed LIF reservoir of 256 neurons with recurrent weights W scaled to spectral radius $\rho = 0.9$ (near the measured edge of stability; Fig. 1d), input weights W_{in}, leak parameter $\beta = 0.05$, and firing threshold $\vartheta = 0.5$:

$$v_t = \left[(1-\beta)\,(1-z_{t-1}) \odot v_{t-1} + W z_{t-1} + W_{\text{in}} x_t\right]_+, \tag{2}$$

$$z_t = \mathbf{1}[v_t \geq \vartheta], \tag{3}$$

where v_t is the membrane state, z_t is the binary spike vector, $[\cdot]_+$ is rectification at zero, and the factor $(1 - z_{t-1})$ resets every unit that spiked at the previous step. W_{in} and W are drawn once from a Xavier-uniform law (seed 42); the reservoir is fixed, and only the readout is trained. To test whether the recurrent dynamics matter, the same reservoir is rescaled to $\rho \in \{0, 0.3, 0.6, 0.9, 1.2, 1.5\}$ with every other parameter fixed ($\rho = 0$ removes the recurrence, leaving a feedforward LIF layer). A label-free order parameter measures damage spreading [5]: two copies receive the same electrode drive, one unit's spike is flipped at the start of the analysis window, and the normalized Hamming distance between the copies' spike vectors, averaged over the steps more than ten after the flip and over 400 sampled drives and flipped units, measures how far the flip spreads; ρ^* is the half-maximum crossing of this curve over $\rho \in [0, 2]$, interpolated on a grid of step 0.1. A one-step branching count bounds where damage can first spread: a flipped spike in unit j shifts the recurrent input of unit i by W_{ij} at the next step and flips its spike only if the pre-threshold membrane lies within $|W_{ij}|$ of ϑ, so with p_ϑ the density of pre-threshold membrane values at ϑ (per unit of membrane potential, averaged over units and steps) and $\bar\kappa$ the mean column sum $\sum_i |W_{ij}|$ at unit spectral radius (13.4 for the seed-42 weights), one flip produces $m(\rho) \approx \rho\, p_\vartheta \bar\kappa$ further flips, and damage can spread once $m > 1$, i.e. beyond $\rho_c \approx 1/(p_\vartheta \bar\kappa)$. This threshold is set by the mean column ℓ_1 norm of W and the fraction of units near threshold, not by the unit circle, and it need not coincide with ρ^* (Sec. V-A); the count ignores persisting sub-threshold differences, which add flips, rectification at zero, which erases some, and the flipped unit's own reset. The criterion is refutable: equating ρ_c with $\rho^* \approx 0.82$ would require $p_\vartheta \approx 0.09$ per unit of membrane potential, far below the $1/\vartheta = 2$ of a uniform density on $[0, \vartheta)$; the membrane histogram at the operating point, not reported here, decides whether ρ^* is the branching threshold or the onset of recurrence-driven firing.

Activity is summarized by six equal temporal bins over the window $t \in [10, 70)$ in sample units; with stimulus onset at sample 51 (Sec. IV-A), this spans about -160 to $+73$ ms around onset. For reservoir unit j and bin k, the binned spike-count code is $b_{j,k} = \sum_{t\in\mathcal{B}_k} z_j(t)$, $k = 1, \ldots, 6$. Each electrode's spike-bin vector is projected onto one 64-component PCA basis shared across electrodes, and the 34 projections are concatenated into a trial-level representation $E_s^{(c)} \in \mathbb{R}^{2176}$. The encoding is a fixed composition of a nonlinear temporal map, spike-count binning, and the unsupervised projection:

$$E = \phi_{\text{PCA}}\big([b_1, \ldots, b_6]\big) = \Phi(X), \tag{4}$$

so $E = \Phi(X)$ is a fixed, label-free representation. The PCA basis is fitted, unsupervised, on the training subjects of each fold only; fitting it once over all subjects (transductive with respect to subject inclusion) is reported as a sensitivity check in Sec. V-A. A single-bin control (BSC_1, total spike count in the window) uses the identical pipeline. The window lies mostly before onset and excludes the later components the ERP-window baseline sees; because every epoch is z-scored

over its full length, pre-stimulus samples also carry an offset set by the post-stimulus signal, so we do not attribute the reservoir's accuracy to a specific evoked component.

C. Baselines and Readout

Two classical baselines are evaluated under the same subject-grouped protocol. The band-power baseline (A0) uses Welch band power in five bands (1–4, 4–8, 8–13, 13–30, 30–45 Hz) per channel ($5 \times 34 = 170$ dimensions). The ERP-window baseline ($\mathrm{A0}_e$) uses mean amplitude in three fixed windows, about -120–0 ms (pre-stimulus baseline), 50–250 ms (early components), and 250–600 ms (P300 and late positive potential) relative to onset, per channel ($3 \times 34 = 102$ dimensions).

As a trained deep baseline we evaluate EEGNet-8,2 [16] on the raw 34×256 ERP signal under the identical subject-grouped folds, trained per fold (Adam, 80 epochs) with train-only per-channel standardization, with and without augmentation by random channel dropout and additive noise.

D. Perturbation Diagnostics

The feature-coordinate experiment (Sec. V-B) suppresses a dropped channel's feature block after extraction and refills it by one of four rules, isolating the fill convention; it applies to the fixed encoders. The signal-level experiment (Sec. V-C) corrupts the test subjects' raw signal before any feature extraction, identically for every encoder including EEGNet (same draws in each fold; training on the clean signal): removal of 10, 30, or 50% of the electrodes, white noise at 5 dB SNR per channel, and an alignment shift of up to ± 50 ms, with all features recomputed from the corrupted signal. In Eq. (1), noise augments ϵ_t, removal zeroes rows of H, and jitter shifts the sampling index of x_t. Performance is balanced accuracy (BA).

E. Scoring Conventions and Two Confounds

Let $c = 1/3$ be chance BA for three balanced classes. *Raw retention* is $R = \mathrm{BA}_{\mathrm{pert}}/\mathrm{BA}_{\mathrm{clean}}$ and *above-chance retention* is $A = (\mathrm{BA}_{\mathrm{pert}} - c)/(\mathrm{BA}_{\mathrm{clean}} - c)$. Channel dropout also requires a fill rule for a dropped channel's features: we compare zero-fill with train-mean fill, then add two in-distribution checks, train-fitted k-nearest-neighbor fill (k=10) and a within-sample spatial fill (mean of the retained channels).

A robustness score describes the representation alone only if it is invariant under the reparametrizations of the features that leave the clean readout unchanged; for a train-standardized readout these include every per-feature affine map. Two common scores fail this test.

Proposition 1 (fill rule and re-centering). *Let $z = D_\sigma^{-1}(x - \mu)$ be the standardized readout input, $D_\sigma = \mathrm{diag}(\sigma)$, with μ, σ fitted on the training subjects, and let S index the dropped coordinates. Zero-fill ($x_S = 0$) and mean fill ($x_S = \mu_S$) differ by the fixed shift*

$$z_S^{\mathrm{zero}} - z_S^{\mathrm{mean}} = -D_{\sigma,S}^{-1}\mu_S. \tag{5}$$

Under a constant re-centering $x \mapsto x - b$ the clean input and the mean-fill input are unchanged, whereas the zero-fill input shifts by $D_{\sigma,S}^{-1}b_S$; the two fills coincide if and only if $\mu_S = 0$.

Proof. Refitting on re-centered data gives $\mu - b$ and the same σ, so z is unchanged and the mean fill maps to the origin for every b, while a zero-filled coordinate maps to $-(\mu_i - b_i)/\sigma_i$, a shift of b_i/σ_i. □

For a linear readout with class weights w the two fills differ in the dropped block's contribution to each class logit by $\sum_{i \in S} w_i \mu_i / \sigma_i$ in magnitude, so they disagree only as far as the dropped features are non-centered (kNN fill, translation-equivariant, is likewise invariant to re-centering). Averaged over features and training folds, $|\mu_i|/\sigma_i$ is 0.06 for the reservoir's PCA code, against 0.75 for ERP-window and 1.20 for band-power, which is why the reservoir is the reference in Sec. V-B.

Proposition 2 (chance floor). *If $\mathrm{BA}_{\mathrm{pert}} \geq c$ in expectation, then $\mathbb{E}[R] \geq c/\mathrm{BA}_{\mathrm{clean}}$, a floor that rises toward 1 as the clean score approaches chance, whereas $A = 0$ at chance for every encoder. To first order in the sampling error s of $\mathrm{BA}_{\mathrm{pert}}$, the sampling error of A is $s/(\mathrm{BA}_{\mathrm{clean}} - c)$.*

Proof. Substitute $\mathrm{BA}_{\mathrm{pert}} = c$ in R; the error term is the delta method with $\mathrm{BA}_{\mathrm{clean}}$ held fixed. □

For the reservoir ($\mathrm{BA}_{\mathrm{clean}} = 0.487$) the floor is 0.69 and the error multiplier 6.5, against 0.53 and 3.4 for ERP-window (0.629).

IV. Experimental Protocol

A. Dataset and Task

The experiments use trial-averaged affective ERP data from the Stress, Health, and the Psychophysiology of Emotion (SHAPE) project [29], collected by the Laboratory for Clinical Affective Neuroscience at Stony Brook University, with 211 subjects after exclusion of one anomalous subject record. Each subject contributes three affective conditions (negative, neutral, pleasant), yielding 633 subject-condition observations. Each recorded epoch (34 scalp channels at 1024 Hz, 1.2 s, baseline-corrected over the 200 ms pre-stimulus interval) is analyzed as every fourth of its first 1024 samples: 256 samples at 256 Hz spanning -200 to $+800$ ms around stimulus onset (onset at sample 51), z-scored per channel within each epoch; the grand averages show the expected late-positive-potential enhancement for emotional over neutral stimuli (Fig. 2).

B. Validation

All results are computed under a single protocol: Stratified-GroupKFold (5 folds, seeds 42–46), train-only standardization, and a balanced L2 logistic readout; observations from the same subject never span train and test, and EEGNet is trained on the same folds. Uncertainty is estimated at the level of the subject, not the fold: for each representation we average the out-of-fold class probabilities of every observation across the five repeated partitions, then form 95% confidence intervals (CIs) from 4000 resamples of the 211 subjects with replacement, keeping a resampled subject's three observations together; macro one-vs-rest AUC uses the same pooled probabilities. Encoder, fill,




Fig. 1. The fixed LIF reservoir as a dynamical system, linked to accuracy. (a) Spike raster for one condition (shaded = the $t \in [10, 70)$ window, about -160 to $+73$ ms around onset at step 51). (b) Population state-space trajectory (first three principal components of the membrane state), from epoch start (dark) to end (light), for the three conditions; the trajectories largely overlap. (c) Subject-level BA (95% CI) versus spectral radius ρ, clean and with 30% of electrodes removed; $\rho = 0$ removes the recurrence, and the dash-dot line marks the pre-specified $\rho = 0.9$. (d) Damage-spreading order parameter versus ρ; shading and the panel's labels change at the half-maximum crossing $\rho^* \approx 0.82$, read in Sec. V-A as the onset of recurrence-driven firing; dash-dot = $\rho = 0.9$, dotted = the echo-state heuristic $\rho = 1$.




Fig. 2. Trial-averaged affective ERP data (SHAPE cohort; grand averages over 211 subjects). (a) Grand-average waveforms per condition at the most affect-discriminative channel; time 0 = stimulus onset (dashed), shaded = the late ERP-window feature (250–600 ms). (b) Spatiotemporal map of the emotional-minus-neutral difference across all 34 channels (dotted = the same window; −/+ mark the sign). (c) Global field power per condition.

and condition contrasts are paired differences under the same resampling. Pooling the partitions before resampling keeps the dependence among the 25 overlapping fold estimates out of the intervals; no test treats folds as independent.

V. Results

A. Clean Classification and Controls

Table I reports clean three-class performance. The trained EEGNet is the most accurate representation (BA 0.731, 95% CI $[0.701, 0.763]$); among the fixed encoders, ERP-window features lead ($A0_e$, 0.629), above band-power (A0, 0.494) and the reservoir embedding (A1, 0.487), whose subject-level intervals overlap. A within-subject label-permutation null (20 permutations) gives mean BA 0.33 to 0.34 (SD at most 0.024, maximum 0.39), so each fixed encoder carries genuine but modest signal.

Controls. The single-bin total-count code (BSC_1, BA 0.487 $[0.450, 0.523]$) matches BSC_6: the paired difference BSC_6 minus BSC_1 is $+0.001$ BA (95% CI $[-0.044, +0.047]$) clean and -0.001 ($[-0.046, +0.041]$) with 30% of electrodes removed, so the reservoir's accuracy comes from the fixed state-space expansion, not temporal bin granularity; we claim no temporal-coding benefit for BSC_6.

TABLE I
CLEAN THREE-CLASS PERFORMANCE WITH SUBJECT-LEVEL BOOTSTRAP 95% CIS, MACRO-F1, AND MACRO ONE-VS-REST ROC-AUC FROM THE POOLED OUT-OF-FOLD PROBABILITIES. CHANCE IS 1/3 (AUC 0.5); THE TRAINED MODEL IS COMPARED ON BA ONLY.

Cfg	Features	BA [95% CI]	F1	AUC
D0	EEGNet (raw, trained)	0.731 [0.701, 0.763]	–	–
$A0_e$	ERP-window (102)	0.629 [0.597, 0.660]	0.629	0.799
A0	Band-power (170)	0.494 [0.460, 0.528]	0.492	0.682
A1	Reservoir BSC_6 (2176)	0.487 [0.447, 0.523]	0.485	0.658

Spectral radius and recurrent dynamics. The recurrent dynamics contribute: relative to the pre-specified $\rho = 0.9$, the feedforward layer ($\rho = 0$) loses 0.049 BA (95% CI $[-0.098, -0.002]$), and the strongly recurrent $\rho = 1.5$ loses 0.057 ($[-0.106, -0.011]$; -0.058, $[-0.103, -0.016]$, with 30% of electrodes removed; Fig. 1c). Between $\rho = 0.3$ and 1.2 the differences from $\rho = 0.9$ are within noise, as is the $\rho = 0$ contrast under 30% removal (-0.030, $[-0.074, +0.016]$), so

the optimum is broad. After an initial step at small ρ, the order parameter rises with its largest increment between $\rho = 0.8$ and 0.9 and saturates above $\rho \approx 1.2$; its half-maximum crossing is $\rho^* \approx 0.82$, below the echo-state heuristic $\rho = 1$ (Fig. 1d), and the mean firing rate doubles across it (0.06 at $\rho = 0.6$, 0.12 at $\rho = 0.9$). The crossing is not where damage first spreads: relative to the $2r(1-r)$ at which unrelated spike trains at rate r differ, the damage is already 0.72 at $\rho = 0.3$ and stays within 0.72–0.84 up to 1.5, so the flip does not die out at any $\rho > 0$ on the grid and the rise across ρ^* is largely the rise of the firing rate. We therefore read ρ^*, the edge of stability of the title, as the onset of recurrence-driven firing; the pre-specified operating point lies just above it, inside the broad optimum.

Fitting the PCA basis on all subjects (transductive) gives BA 0.485 $[0.447, 0.521]$, against 0.487, and $\{16, 32, 64, 128\}$ components give 0.477–0.507, inside the 64-component interval: the pooled basis shows no evidence of optimistic inflation under this subject-grouped protocol, and the component count does not account for the results.

B. Two Confounds in Channel-Dropout Robustness

Channel dropout is where the reported conclusion depends on the scoring convention (Table II, Fig. 3).

Accuracy-floor effect. With zero-imputation, raw retention ranks the reservoir first at 30% dropout: its BA does not move (retention 100%, against 85% for ERP-window; 97% under signal-level removal, Table III). By Proposition 2 this ranking is nearly forced: the reservoir's raw retention cannot fall below 0.69 unless its perturbed score falls below chance, and under the fixed-denominator approximation its above-chance retention carries a 95% interval of roughly ± 0.25 (against ± 0.11 for ERP-window), so the retention columns of Table II are diagnostics only.

Zero-imputation effect. At 30% dropout, train-mean imputation (Sec. III-E) raises band-power from 0.417 to 0.472 and ERP-window features from 0.536 to 0.578, while the reservoir does not change (0.487 under both fills). ERP-window features lead the reservoir under every fill, but the fill sets the size of the lead: the paired difference ERP-window minus reservoir is $+0.049$ BA (95% CI $[+0.003, +0.095]$) under zero-fill and $+0.092$ to $+0.107$ under the three in-distribution fills, whose CIs all lie above $+0.04$. Zero-imputation thus halves the measured advantage of the strongest fixed encoder, because only the non-centered encoder's score moves with the constant.

Generality. The mean-minus-zero gaps at 30% dropout are $+0.042$ ($[+0.011, +0.074]$) for ERP-window, $+0.055$ ($[+0.024, +0.087]$) for band-power, and -0.000 ($[-0.022, +0.022]$) for the reservoir, ordered as the non-centeredness in Eq. (5). Across 10–50% dropout the reservoir's two constant-fill scores agree within 0.016 BA and no CI excludes zero, whereas the gap of the non-centered encoders varies with the rate and is significant for band-power at 20 and 30% and for ERP-window at 30% (Fig. 3a). kNN fill differs in kind (Fig. 3b): it adds content rather than moving the origin, and at 40 and 50% it significantly raises every encoder, ERP-window most ($+0.13$ BA at 50%, $[+0.09, +0.16]$).

TABLE II

CHANNEL DROPOUT AT 30%: NAIVE AND CORRECTED EVALUATION. "ZERO" AND "MEAN" DENOTE ZERO- AND TRAIN-MEAN FILL OF DROPPED CHANNELS; FOR EEGNET (RAW-SIGNAL MODEL) "ZERO" IS SIGNAL-LEVEL REMOVAL OF 30% OF THE ELECTRODES (TABLE III). RAW-RET. IS $\mathrm{BA}_{\mathrm{zero}}/\mathrm{BA}_{\mathrm{clean}}$; AC-RET. IS ABOVE-CHANCE RETENTION UNDER MEAN FILL (REMOVAL FOR EEGNET); "+AUG." DENOTES TRAIN-TIME AUGMENTATION. PER-CELL 95% CIS ARE ± 0.03 TO ± 0.04.

Representation	Clean	Zero	Mean	raw-ret.	AC-ret.
EEGNet	0.731	0.660	–	90%	82%
+ aug.	0.731	0.703	–	96%	93%
ERP-window	0.629	0.536	0.578	85%	83%
Band-power	0.494	0.417	0.472	84%	86%
Reservoir	0.487	0.487	0.487	100%	100%




Fig. 3. How much the fill rule alone moves channel-dropout accuracy: paired subject-level change in BA relative to zero-fill, with 95% CIs, versus the share of electrodes dropped. (a) Train-mean fill, which differs from zero-fill only by the shift of Eq. (5); the legend gives each encoder's mean $|\mu|/\sigma$. (b) kNN fill, which changes the block's content.

C. Signal-Level Perturbations

In the signal-level experiment (Table III), for band-power and ERP-window a removed electrode is exactly zero-fill (their removal rows equal the zero-fill scores of Sec. V-B); for the reservoir a silent electrode's zero spike-count block projects away from the PCA origin, so the shift of Eq. (5) reappears before the projection.

First, ERP-window features remain the most accurate fixed encoder under every condition; their paired lead over the reservoir is $+0.06$ to $+0.14$ BA, every CI excluding zero. Second, the reservoir holds its accuracy through 30% removal (loss 0.013, 95% CI $[-0.014, +0.041]$) but falls to 0.393 at 50%, close to chance (loss 0.093, $[+0.055, +0.131]$), so its fill invariance is a property of its feature space, not robustness to missing electrodes. Third, 5 dB noise costs band-power 0.059 BA ($[+0.019, +0.098]$) while ERP-window and the reservoir stay within noise of their clean scores, and ± 50 ms jitter moves no fixed encoder.

Training effect. EEGNet ingests the same corrupted signal and is the most accurate encoder in every condition (paired lead over ERP-window $+0.08$ to $+0.20$ across both training variants, every CI excluding zero); unaugmented, it

TABLE III
SIGNAL-LEVEL PERTURBATIONS: SUBJECT-LEVEL BA WITH EVERY REPRESENTATION RECOMPUTED FROM THE CORRUPTED TEST SIGNAL (SAME DRAWS FOR ALL ENCODERS; TRAINING ON CLEAN DATA, EEGNET ALSO WITH AUGMENTATION). PER-CELL 95% CIS ARE ± 0.03 TO ± 0.04.

Condition	Band-pow.	ERP-win.	Reserv.	EEGNet	+aug.
Clean	0.494	0.629	0.487	0.731	0.731
10% removed	0.476	0.602	0.469	0.719	0.722
30% removed	0.417	0.536	0.474	0.660	0.703
50% removed	0.450	0.474	0.393	0.588	0.670
Noise 5 dB	0.436	0.619	0.479	0.738	0.727
Jitter ± 50 ms	0.496	0.626	0.493	0.719	0.708




Fig. 4. (a) External check on DEAP [28] (32 subjects, within-subject binary valence, band-power; clean BA 0.639; CIs from resampling subjects). (b) EEGNet without and with channel-dropout and noise augmentation under the signal-level conditions of Table III (subject-level 95% CIs): augmentation leaves clean accuracy unchanged and cuts the loss to electrode removal by more than half.

loses 0.071 BA at 30% removal and 0.144 at 50%. Retraining with channel-dropout and amplitude-noise augmentation leaves clean accuracy unchanged (paired difference -0.000, $[-0.025, +0.022]$) and cuts these losses by more than half, to 0.028 and 0.062: the augmented network is ahead by $+0.043$ ($[+0.009, +0.077]$) at 30% and $+0.082$ ($[+0.049, +0.115]$) at 50%. For this architecture, dropout robustness is thus set largely by the training procedure (Fig. 4b).

D. External Replication on an Independent Affective Dataset

To test whether the imputation effect is specific to SHAPE, we evaluate band-power features on DEAP [28], an independent affective EEG dataset (32 subjects, 40 trials each), on a binary valence task under the standard within-subject protocol (per-subject stratified 5-fold; DEAP band-power is at chance cross-subject). The same pattern appears, larger than in SHAPE (Fig. 4a). At 30% dropout, band-power scores BA 0.540 under zero-imputation (95% CI $[0.528, 0.552]$) but 0.621 $[0.591, 0.648]$ under mean and 0.638 $[0.607, 0.668]$ under kNN imputation, with CIs from resampling the 32 subjects' mean BA. With clean BA 0.639, zero-imputation indicates a 0.10 BA loss and kNN imputation almost none: for band-power features (four log-power bands) on a second dataset, task, and montage, the imputation convention alone moves measured robustness by up to 0.11 BA.

VI. DISCUSSION

The main result is methodological: neither raw retention nor zero-fill scoring describes the representation alone (Propositions 1 and 2), and for trained models augmentation is a third, training-side factor. After accounting for these choices, the fixed reservoir should not be described as the most channel-robust encoder: ERP-window features lead it under every fill at 30% dropout and under every signal-level condition, zero-imputation halves that lead, and the augmented EEGNet is the most accurate and the strongest dropout baseline here. The reservoir remains useful as a near-centered reference that makes the artifact visible in the other encoders, but its invariance belongs to its feature space and does not survive signal-level removal of half the electrodes. Its dynamics still matter: removing the recurrence or driving it into the strongly recurrent regime lowers accuracy, and the operating point lies just above the onset of recurrence-driven firing; whether this matches the edge-of-chaos picture of other reservoirs [5], [6] turns on the membrane density at threshold, which the one-step branching bound makes the deciding quantity.

These results suggest a minimal reporting standard for EEG robustness studies: report absolute accuracy with subject-level uncertainty alongside raw and above-chance retention, state the channel-fill rule, test at least one in-distribution fill, and report trained-model results with and without perturbation augmentation.

Limitations. The primary cohort is a single trial-averaged affective-ERP dataset. The fill-rule effect follows from Proposition 1 and is observed across three fills, five dropout rates, and DEAP, but paradigm-matched multi-cohort ERP validation would strengthen it. EEGNet is trained with one fixed recipe, without a hyperparameter search, and the spectral-radius sweep uses a single draw of the reservoir weights and reports no membrane histogram. Adversarial attacks, montage shifts, graph topology, and structure–function coupling are outside its scope.

VII. CONCLUSION

Channel-dropout robustness rankings for affective-ERP representations depend on the scoring protocol: raw retention has a chance floor, zero-fill depends on the coordinate origin, and trained models need their augmentation state made explicit. Here zero-fill halves the measured lead of the strongest fixed encoder, the spiking reservoir near its measured edge of stability makes these effects visible without being the most accurate encoder, and the fill-rule effect replicates on DEAP.

Ethics. The SHAPE study was collected by the Stony Brook University Laboratory for Clinical Affective Neuroscience under its Institutional Review Board oversight; DEAP is public under its original protocol [28]. **Data Availability.** For SHAPE data, contact that laboratory [29].

REFERENCES

[1] W. Maass, T. Natschläger, and H. Markram, "Real-time computing without stable states: A new framework for neural computation based on perturbations," *Neural Computation*, vol. 14, no. 11, pp. 2531–2560, 2002.

[2] H. Jaeger, "The echo state approach to analysing and training recurrent neural networks," German National Research Center for Information Technology, GMD Report 148, 2001.

[3] H. Jaeger and H. Haas, "Harnessing nonlinearity: Predicting chaotic systems and saving energy in wireless communication," *Science*, vol. 304, no. 5667, pp. 78–80, 2004.

[4] M. Lukoševičius and H. Jaeger, "Reservoir computing approaches to recurrent neural network training," *Computer Science Review*, vol. 3, no. 3, pp. 127–149, 2009.

[5] N. Bertschinger and T. Natschläger, "Real-time computation at the edge of chaos in recurrent neural networks," *Neural Computation*, vol. 16, no. 7, pp. 1413–1436, 2004.

[6] R. Legenstein and W. Maass, "Edge of chaos and prediction of computational performance for neural circuit models," *Neural Networks*, vol. 20, no. 3, pp. 323–334, 2007.

[7] P. U. Diehl and M. Cook, "Unsupervised learning of digit recognition using spike-timing-dependent plasticity," *Frontiers in Computational Neuroscience*, vol. 9, p. 99, 2015.

[8] K. Roy, A. Jaiswal, and P. Panda, "Towards spike-based machine intelligence with neuromorphic computing," *Nature*, vol. 575, pp. 607–617, 2019.

[9] A. Lane, W. Tang, and B. Nelson, "Towards ARSPI-Net: Development of an efficient hybrid deep learning framework," in *Proc. IEEE Long Island Systems, Applications and Technology Conf. (LISAT)*, Old Westbury, NY, USA, 2023, pp. 1–8.

[10] A. Lane, W. Tang, and B. Nelson, "Towards ARSPI-Net: Advancing EEG feature extraction with neuromorphic algorithms," in *Proc. IEEE Long Island Systems, Applications and Technology Conf. (LISAT)*, Holtsville, NY, USA, 2024, pp. 1–8.

[11] P. Gong, P. Wang, Y. Zhou, and D. Zhang, "A spiking neural network with adaptive graph convolution and LSTM for EEG-based brain-computer interfaces," *IEEE Trans. Neural Syst. Rehabil. Eng.*, vol. 31, pp. 1440–1450, 2023.

[12] B. Hjorth, "EEG analysis based on time domain properties," *Electroencephalography and Clinical Neurophysiology*, vol. 29, no. 3, pp. 306–310, 1970.

[13] A. Subasi, "EEG signal classification using wavelet feature extraction and a mixture of expert model," *Expert Systems with Applications*, vol. 32, no. 4, pp. 1084–1093, 2007.

[14] S. Makeig, M. Westerfield, T.-P. Jung, S. Enghoff, J. Townsend, E. Courchesne, and T. J. Sejnowski, "Dynamic brain sources of visual evoked responses," *Science*, vol. 295, no. 5555, pp. 690–694, 2002.

[15] B. Blankertz, S. Lemm, M. Treder, S. Haufe, and K.-R. Müller, "Single-trial analysis and classification of ERP components: a tutorial," *NeuroImage*, vol. 56, no. 2, pp. 814–825, 2011.

[16] V. J. Lawhern, A. J. Solon, N. R. Waytowich, S. M. Gordon, C. P. Hung, and B. J. Lance, "EEGNet: A compact convolutional neural network for EEG-based brain-computer interfaces," *Journal of Neural Engineering*, vol. 15, no. 5, 056013, 2018.

[17] A. Craik, Y. He, and J. L. Contreras-Vidal, "Deep learning for electroencephalogram (EEG) classification tasks: A review," *Journal of Neural Engineering*, vol. 16, no. 3, 031001, 2019.

[18] H.-S. Chiang, M.-Y. Chen, and L.-S. Liao, "Cognitive depression detection cyber-medical system based on EEG analysis and deep learning approaches," *IEEE J. Biomed. Health Inform.*, vol. 27, no. 2, pp. 608–616, 2023.

[19] Y. Guo, K. Yang, and Y. Wu, "A multi-modality attention network for driver fatigue detection based on frontal EEG, EDA and PPG signals," *IEEE J. Biomed. Health Inform.*, vol. 29, no. 6, pp. 4009–4022, 2025.

[20] F. Del Pup, A. Zanola, L. F. Tshimanga, A. Bertoldo, and M. Atzori, "The more, the better? Evaluating the role of EEG preprocessing for deep learning applications," *IEEE Trans. Neural Syst. Rehabil. Eng.*, vol. 33, pp. 1061–1070, 2025.

[21] S. Kornblith, M. Norouzi, H. Lee, and G. Hinton, "Similarity of neural network representations revisited," in *Proc. Int. Conf. Machine Learning*, 2019, pp. 3519–3529.

[22] U. Širca, M. Alimardani, S. Zafeiriou, and K. Barmpas, "Beyond accuracy: Robustness, interpretability and expressiveness of EEG foundation models," *arXiv:2605.17562*, 2026.

[23] H. Banville, S. U. N. Wood, C. Aimone, D.-A. Engemann, and A. Gramfort, "Robust learning from corrupted EEG with dynamic spatial filtering," *NeuroImage*, vol. 251, 118994, 2022.

[24] C. Rommel, J. Paillard, T. Moreau, and A. Gramfort, "Data augmentation for learning predictive models on EEG: A systematic comparison," *Journal of Neural Engineering*, vol. 19, no. 6, 066020, 2022.

[25] F. Perrin, J. Pernier, O. Bertrand, and J. F. Echallier, "Spherical splines for scalp potential and current density mapping," *Electroencephalography and Clinical Neurophysiology*, vol. 72, no. 2, pp. 184–187, 1989.

[26] Y. Bi, A. Abrol, S. Jia, J. Sui, and V. D. Calhoun, "Gray matters: ViT-GAN framework for identifying schizophrenia biomarkers linking structural MRI and functional network connectivity," *NeuroImage*, vol. 297, 120674, 2024.

[27] X. Hu, J. Yang, S. Jia, Y. Bi, and V. D. Calhoun, "GM-LDM: Latent diffusion model for brain biomarker identification through functional data-driven gray matter synthesis," arXiv:2506.12719, 2025.

[28] S. Koelstra *et al.*, "DEAP: A database for emotion analysis using physiological signals," *IEEE Trans. Affective Computing*, vol. 3, no. 1, pp. 18–31, 2012.

[29] Laboratory for Clinical Affective Neuroscience, "The Stress, Health, and the Psychophysiology of Emotion (SHAPE) project," Stony Brook University, Stony Brook, NY, USA. [Online]. Available: https://lab-can.com