What a Linear Encoding Model Leaves at the Beat: A Pre-Registered Test of Residual Beat-Locking, a Spiking-Reservoir Readout, and the Identifiability Limits of Oscillator-versus-Evoked Comparisons in Single-Listen EEG

[Authors to be added]

***Abstract*—Whether beat-locked EEG reflects entrained oscillators or summed evoked responses is often argued from frequency-tagging magnitudes, which cannot separate the two. We asked a narrower, testable question: does fronto-central EEG keep beat-locked power after a cross-validated linear encoding model of the music, a temporal response function (TRF), is removed? In a pre-registered two-stage test on 34 participants listening to music at 13 tempi (Weineck et al. 2022 data), the residual kept beat-locked power ([CONFIRMATORY]; median standardized effect 0.228, 31/34 positive). A fixed spiking reservoir (ARSPI-Net, 256 leaky integrate-and-fire units) read out linearly was equivalent to the linear statistic, and a weight-shuffled copy matched it ([CONFIRMATORY], [EXPLORATORY]). Exploratory checks showed the residual is not explained by underfitting (linear-world residual 0.039) and splits into a spectral part (0.156) and a smaller phase-dependent part (0.045). Oscillator-bank encoding models did not beat the TRF at held-out tempi ([EXPLORATORY]). A simulation map of that comparison ([SIMULATED]) showed the committed rule has no false positives but reaches 80 % power only for an oscillator supplying a share of about 0.89 of the stimulus-locked amplitude, and that its Hopf-versus-linear-bank criterion has no regularization-stable answer. The comparison against the TRF alone bounds, under the real pipeline's procedure, oscillatory structure beyond the TRF at about 60 % of the amplitude ([EXPLORATORY]). The contribution is a calibrated statement of what single-listen encoding comparisons can and cannot decide about entrainment.**

***Index Terms*—EEG, neural entrainment, temporal response function, reservoir computing, spiking neural network, pre-registration, identifiability.**

I. Introduction

Rhythmic music drives EEG activity at the beat frequency, and whether this reflects endogenous oscillators entrained by the stimulus or a superposition of transient evoked responses is a long-running question [1], [2], [3]. Frequency-tagging magnitudes alone do not distinguish the two accounts [4], [5], [6], [7], [8], [9], [10], and encoding models (temporal response functions, TRFs) describe stimulus-locked responses without settling the mechanism [CITE?: mTRF/TRF method; no usable entry in the repository literature].

We replace the mechanism question with three that the data can answer: (i) after a cross-validated linear encoding model of four music features is subtracted, does beat-locked power remain (H2)? (ii) does a fixed spiking reservoir add detection power over a linear statistic (H1, H3)? (iii) at held-out tempi, does an oscillator encoding model predict the EEG better than the TRF, and how large an oscillator contribution could that comparison detect at single-listen signal-to-noise ratio? The first two were pre-registered ([CONFIRMATORY]); the third, and every check around the first two, is labelled [EXPLORATORY] or [SIMULATED]. The reservoir is the canonical ARSPI-Net leaky integrate-and-fire (LIF) reservoir [11], used here as a characterized instrument rather than a classifier [12], [13].

Contributions: (1) a pre-registered, calibrated residual beat-tagging test with its null validated and rejected nulls recorded; (2) an equivalence result for a fixed spiking reservoir against its linear readout; (3) an identifiability map of the oscillator-versus-evoked held-out-tempo comparison, showing where it can and cannot decide and how much of its answer depends on the regularization of the comparison models.

II. Methods

A. Data

We used the openly available EEG of Weineck, Wen and Henry [14]: 34 participants, 32 channels, music at 13 tempi from 1 to 4 Hz. Stimulus features (spectral flux, beat onsets, envelope and its derivative) were taken from the authors' source data and matched to trials by duration one-to-one; trials with ambiguous matches were dropped. EEG was band-passed 0.5–30 Hz, average-referenced and resampled to 64 Hz for the TRF and 256 Hz for the reservoir; the target was the mean of 8 fronto-central channels. Stage 2 used 3300 one-to-one trials; every participant met the pre-registered minimum of 40 trials.

B. Pre-registration and timeline

The pre-registration (two-stage design, hypotheses, statistic, null, equivalence bounds) was frozen at commit 935c80a before any group test; addendum A1 (commit 73626a0) recorded before the stage-1 group test that stage 1 had 8 participants. Stage 1 tested H2 at $\alpha = 0.01$; stage 2 (all 34 participants, downloaded unconditionally) at $\alpha = 0.04$. Stage-1 and stage-2 results were committed at 4e0d5fc and c8b1503. Every

Manuscript draft. Pre-registration frozen at commit 935c80a of the project repository.

exploratory analysis had its plan and decision rule committed before it ran: underfitting check 8f89920, oscillator decision rule d54f0ef, robustness grid 499972d, identifiability plan 8b4abe0, addenda A3 cf0a65e and A4 a0013f4 (extension ce2d574).

C. Residual beat-tagging

Per participant, a ridge TRF (lags 0–400 ms, four features, regularization chosen by nested leave-one-trial-out cross-validation) predicted each held-out trial; the residual is the EEG minus that prediction. Beat-locking was scored with one statistic for every signal: Welch power at the trial's own tempo and its octave, relative to a local baseline, compared with the same score at the other grid tempi. The per-trial standardized effect δ is the mean over trials of own-tempo minus mean other-tempo score, divided by its standard deviation across trials. The null shuffles stimulus labels across trials (500 shuffles); nulls that fail on a periodic grid (circular shift, phase randomization) or inflated false positives in calibration were rejected and are recorded in the pre-registration. H2: residual $\delta > 0$ (one-sided Wilcoxon signed-rank over participants). H1/H3: reservoir minus linear statistic on the drive and on the residual, equivalent within $\pm 0.10\,\delta$ by two one-sided tests [CITE?: TOST equivalence testing; not in the repository literature].

D. ARSPI-Net reservoir

The canonical reservoir has 256 LIF units, leak $\beta = 0.05$, spectral radius $\rho = 0.9$, seed 42; it is driven by the (residual or raw) fronto-central signal at 256 Hz and read out linearly as the first principal component across units (R). A copy with shuffled recurrent weights rescaled to the same spectral radius (Rs) tests whether the recurrent structure matters [12], [13], [11].

E. Exploratory checks of H2

(i) Underfitting: a pooled leave-one-participant-out TRF; the tagging of the TRF prediction itself; and a linear world (fitted kernels convolved with the real features plus noise matched to the observed held-out r) through the identical pipeline. (ii) IAAFT surrogates of the residual [15], [16], splitting δ into a part the surrogates keep (spectral) and a part they destroy (phase-dependent). (iii) A robustness grid of 11 rows (seeds, ρ, β, TRF variants, IAAFT). (iv) The 13-tempo curve rescored on a fixed number of beat cycles per tempo.

F. Oscillator encoding models (Theory 3)

Banks of driven Hopf (Stuart–Landau) oscillators, resonate-and-fire units and linear damped oscillators [17], [18], [19] were driven by the beat-related features; their lagged outputs, alone or added to the TRF, were fitted by ridge regression and evaluated at held-out tempi (leave-one-tempo-out, configuration and regularization chosen in an inner loop). The committed rule: the Hopf-augmented model beats the best TRF (median $\Delta r > 0$, one-sided Wilcoxon $p < 0.01$; criterion 1) and beats the linear-bank-augmented model ($p < 0.05$; criterion 2).

G. Identifiability simulation

Simulated participants used real fitted kernels (34 participants) and real stimulus features: the signal was $s = (1 - w)P_e/\mathrm{sd}_e + wP_o/\mathrm{sd}_o$, with P_e the evoked (TRF) prediction, P_o the Hopf-bank prediction and w the oscillator's amplitude share, plus noise with the pooled residual spectrum scaled to a target held-out r (calibrated: 0.040 at a target of 0.04). Each cell ran 20 datasets of 20 participants through the identical leave-one-tempo-out comparison and the committed rule, computed from per-trial sufficient statistics with the modal regularization of the real data. World A is the committed grid (held-out r, trials per tempo, training tempi, w). Addendum A3 added World B (signal variance held constant across w), World C (P_o replaced by its residual after projection onto the TRF design, i.e. only TRF-inexpressible oscillator structure) and a nested-regularization check; addendum A4 added nested-regularization cells for criterion 1 and a lambda-pair sensitivity analysis of criterion 2. Rates carry 95 % Clopper–Pearson intervals [CITE?: Clopper–Pearson interval; not in the repository literature]; W80 is the interpolated w at 80 % detection.

III. Results

A. H2: beat-locked power beyond the linear encoding model

Stage 1 (8 participants) did not reach its threshold ($p = 0.055$ against $\alpha = 0.01$; median δ 0.091). At stage 2 ([CONFIRMATORY]) the residual kept beat-locked power: median $\delta = 0.228$ [0.121, 0.277], 31/34 positive, $p = 8.0 \times 10^{-9}$ (Fig. 2a; drive 0.317 [0.228, 0.364]). This is a statement about this linear encoding model, not about oscillators. [EXPLORATORY] The linear world left 0.039 against the real 0.228 ($p = 7.3 \times 10^{-8}$), and a pooled TRF left 0.245, so underfitting does not account for it (Fig. 3a). IAAFT surrogates retained 0.156 [0.113, 0.231] (spectral) and removed 0.045 [0.022, 0.072] (phase-dependent; 26/34 positive, $p = 0.0003$; Fig. 3b): the residual beat-locking is nonlinear relative to the TRF and predominantly spectral, with a smaller reliable phase-coherent part. No robustness row flipped H2 (0 of 11; Fig. 7).

B. The reservoir is equivalent to its linear readout

[CONFIRMATORY] On the drive and on the residual, the reservoir statistic was equivalent to the linear statistic (90 % intervals -0.010 to +0.003 and -0.007 to +0.006, inside ± 0.10; Fig. 2b). It exceeded envelope and squared statistics (0.162 to 0.269) only because those were null on the residual. [EXPLORATORY] Shuffling the recurrent weights changed nothing (R$-$Rs -0.0045 [-0.011, +0.006]), nor did removing recurrence (R at $\rho = 0.9$ minus R at $\rho = 0$: -0.0035 [-0.016, +0.013]; per-participant correlation 0.984; Fig. 4). The H2 statistic itself never passes through the reservoir, so its robustness rows over seed, ρ and β are identical by construction.

C. Oscillator encoding models at held-out tempi

[EXPLORATORY] Under the rule fixed in advance, the oscillator account was not supported: Hopf-augmented minus

best TRF median Δr −0.010, 3/34 positive ($p = 1.00$), negative at 13 of 13 held-out tempi, with no preferred rate (Fig. 5a,b); pooled across participants −0.002 (8/34 positive). The apparent rise of tagging toward 4 Hz did not survive a fixed number of beat cycles per tempo (participant slopes +0.484 z/Hz, $p = 0.0001$, full duration; +0.015, $p = 0.37$, fixed cycles; Fig. 5c).

D. What the comparison can decide: identifiability

[SIMULATED] At the operating point of these data (held-out r 0.04, 40 trials per tempo, 12 training tempi) the committed rule had no false positives (maximum rate 0.00, upper 95 % bound 0.17 with 20 datasets) and reached 80 % detection only at an oscillator amplitude share of 0.89 (99 % of the variance), unchanged by a 8-fold change in held-out r or a 8-fold change in trial count, by power matching (World B, 0.92) and in refined cells (0.88, 0.89); World C, the TRF-inexpressible oscillator, was never detected (maximum rate 0.10) (Fig. 6). The two generating predictions overlap (median r 0.53), and the TRF design expresses a median 62 % of the oscillator prediction's variance (range 29–85 %; 82 % for a 0–1000 ms TRF).

[EXPLORATORY] (outside the committed rule) The limit sits in criterion 2. Criterion 1 alone reached 80 % at $w = 0.58$ (World A), 0.58 (B) and 0.47 (C) with fixed regularization, and at 0.59 (World A, bracket 0.5–0.6) and at or below 0.6 (World C) under the real pipeline's nested regularization. Criterion 2 has no regularization-stable answer: at $w = 1$ it passed in World A in 20/20 datasets with the committed pair, 0/20 with both models at $\lambda = 1$, 18/20 at $\lambda = 10$ and 10/10 under nested selection; in World C 1/20, 1/20, 20/20 and 0/10. With each model at its own inner-loop regularization, the rule detected World A at W80 0.96 and never detected World C.

[EXPLORATORY] Placement of the real data: criterion 1 itself failed (median Δr −0.010, 3/34 positive, $p = 1.00$), below the simulated evoked-only world (−0.0067). Taking the largest criterion-1 W80 among the worlds as the conservative bound, the real data exclude, at about 80 % power, oscillatory structure beyond the TRF supplying more than about 60 % of the stimulus-locked amplitude.

IV. Discussion

Residual beat-locked power beyond a four-feature linear encoding model is real in these data and is not an underfitting artifact; most of it is spectral, so a linear model with different features or a nonlinear stimulus-response map could absorb it [20], [21]. Neither the spiking reservoir nor its recurrence added detection power, which makes the reservoir a calibrated, scaled copy of its input in the beat band rather than a detector of structure the linear statistic misses; this is a measured, negative result about the instrument. The oscillator-versus-evoked comparison at held-out tempi did not favor oscillators, but the identifiability map limits what that null means: the committed rule cannot see an oscillator supplying half the amplitude, and its Hopf-versus-linear criterion changes verdict with the regularization of the comparison model. A methods lesson follows: encoding-model comparisons of mechanism need identifiability maps at the data's own SNR, and comparison-model regularization must be reported as part of the result. Designs that perturb rhythm (missing beats, tempo changes, offset persistence with ringing controls) are where the distinction can live [22], [3], [23].

V. Limitations

Single dataset with one listening paradigm; generalization to naturalistic single listens (NMED-T [CITE?: NMED-T dataset paper; entry incomplete in the source]) is pending. The TRF uses four features and 0–400 ms lags; other feature sets may absorb part of the residual. Stage 1 alone was inconclusive and H2 rests on stage 2. The identifiability simulation fixes the oscillator configuration, uses Gaussian noise with a smooth spectrum, 20 participants per dataset (the real group had 34) and 20 datasets per cell; nested-regularization cells had 10. Exploratory analyses are post hoc relative to the confirmatory tests, though each plan was committed before it ran.

Data and Code Availability

EEG: Weineck et al. [14], CC BY 4.0, not redistributed. Code, aggregate results, pre-registration and all plans: project repository [URL to be added]; every number in this manuscript is generated from the results files by `make_numbers.py`.

References

[1] Doelling and Assaneo, "Neural oscillations are a start toward understanding brain activity rather than the end," *PLoS Biol*, vol. 19, p. e3001234, 2021.

[2] Breska and Deouell, "Delta phase-locking reflects temporal predictability but not rhythmic entrainment," *PLoS Biol*, vol. 15, p. e2001665, 2017.

[3] van Bree, Sohoglu, Davis, and Zoefel, "Sustained neural rhythms reveal endogenous oscillations supporting speech perception," *PLoS Biol*, vol. 19, p. e3001142, 2021.

[4] Nozaradan, Peretz, Missal, and Mouraux, "Tagging the neuronal entrainment to beat and meter," *J Neurosci*, vol. 31, no. 28, pp. 10 234–10 240, 2011, pMID 21753000.

[5] Henry, Herrmann, and Grahn, "What can we learn about beat perception by comparing brain signals and stimulus envelopes?" *PLoS ONE*, vol. 12, p. e0172454, 2017, behavioural data only: Dryad doi:10.5061/dryad.37jg4.

[6] Zhou, Melloni, Poeppel, and Ding, "Interpretations of frequency domain analyses of neural entrainment: periodicity, fundamental frequency, and harmonics," *Front Hum Neurosci*, vol. 10, p. 274, 2016.

[7] Novembre and Iannetti, "Tagging the musical beat: neural entrainment or event-related potentials?" *PNAS*, vol. 115, pp. E11 002–E11 003, 2018.

[8] Rajendran and Schnupp, "Frequency tagging cannot measure neural tracking of beat or meter," *PNAS*, vol. 116, no. 8, pp. 2779–2780, 2019.

[9] Doelling, Assaneo, Bevilacqua, Pesaran, and Poeppel, "An oscillator model better predicts cortical entrainment to music," *PNAS*, vol. 116, no. 20, pp. 10 113–10 121, 2019.

[10] Damsma, de Roo, Doelling, Bazin, and Bouwer, "Tempo-dependent selective enhancement of neural responses at the beat frequency can be mimicked by both an oscillator and an evoked model," *Cerebral Cortex*, vol. 35, no. 9, p. bhaf258, 2025, data: OSF ghp94 (https://osf.io/ghp94/); raw EEG on UvA DARE, doi:10.21942/uva.26233139.

[11] Lane, Tang, and Nelson, "Towards ARSPI-NET: advancing EEG feature extraction with neuromorphic..." in *IEEE LISAT 2024*, 2024, title truncated in source; Stony Brook record.

[12] Verstraeten, Schrauwen, D'Haene, and Stroobandt, "An experimental unification of reservoir computing methods," *Neural Netw*, 2007.

[13] Soures and Kudithipudi, "Spiking reservoir networks: brain-inspired recurrent algorithms that use random, fixed synaptic strengths," *IEEE Signal Processing Magazine*, vol. 36, no. 6, 2019. [Online]. Available: https://consensus.app/papers/details/70534f0b9195541daeffebef85898a6f/




Fig. 1. Pipeline and example trial (see docs/FIGURES.md).




Fig. 2. Confirmatory stage 2: H2 and H1/H3 equivalence.

[14] Weineck, Wen, and Henry, "Neural synchronization is strongest to the spectral flux of slow music and depends on familiarity and beat salience," *eLife*, vol. 11, p. e75515, 2022, data: OSF y5xhs (https://osf.io/y5xhs/).
[15] Theiler, Eubank, Longtin, Galdrikian, and Farmer, "Testing for nonlinearity in time series: the method of surrogate data," *Physica D*, vol. 58, pp. 77–94, 1992.
[16] Schreiber and Schmitz, "Improved surrogate data for nonlinearity tests," *PRL*, vol. 77, p. 635, 1996.
[17] Large, Almonte, and Velasco, "A canonical model for gradient frequency neural networks," *Physica D*, vol. 239, pp. 905–911, 2010.
[18] Large, Herrera, and Velasco, "Neural networks for beat perception in musical rhythm," *Front Syst Neurosci*, vol. 9, p. 159, 2015.
[19] Izhikevich, "Resonate-and-fire neurons," *Neural Networks*, vol. 14, no. 6-7, pp. 883–894, 2001.
[20] De Clercq *et al.*, "Beyond linear neural envelope tracking: a mutual information approach," *J Neural Eng*, 2022. [Online]. Available: https://consensus.app/papers/details/45d086db6a565e45b1232dd4064454ce/
[21] Wilroth *et al.*, "Nonlinearity detection and compensation for EEG-based speech tracking," in *ICASSP 2024*, 2024. [Online]. Available: https://consensus.app/papers/details/8b700d6130ff517ba5cb4a021da6143b/
[22] Tal, Large, Rabinovitch, Wei, Schroeder, Poeppel, and Zion Golumbic, "Neural entrainment to the beat: the 'missing-pulse' phenomenon," *J Neurosci*, vol. 37, no. 26, pp. 6331–6341, 2017.
[23] Pesnot Lerousseau, Trébuchon, Morillon, and Schön, "Frequency selectivity of persistent cortical oscillatory responses to auditory rhythmic stimulation," *J Neurosci*, vol. 41, no. 38, pp. 7991–8006, 2021.




Fig. 3. Underfitting check and IAAFT decomposition (exploratory).




Fig. 4. Reservoir versus shuffled weights and versus no recurrence (exploratory).




Fig. 5. Oscillator encoding at held-out tempi and the cycle-count control (exploratory).




Fig. 6. Identifiability of an oscillator component (simulated).




Fig. 7. Robustness grid (exploratory).