

# Algebraic subtyping for algebraic effects and handlers

AXEL FAES, KU Leuven

AMR HANY SALEH, KU Leuven

TOM SCHRIJVERS, KU Leuven

Algebraic effects and handlers are a very active area of research. An important aspect is the development of an optimising compiler. EFF is an ML-style language with support for effects and forms the testbed for the optimising compiler. However, the type-&-effect system of EFF is unsatisfactory. This is due to the lack of some elegant properties. It is also awkward to implement and use in practice.

Additional Key Words and Phrases: algebraic effect handler, algebraic subtyping, effects, optimised compilation

## CONTENTS

Abstract	1
Contents	1
List of Figures	2
List of Tables	2
1 Introduction	3
1.1 Motivation	3
1.2 Goals	3
1.3 Results	4
2 Background	4
2.1 Programming language theory	4
2.2 Subtyping	5
2.3 Algebraic effects and handlers	5
3 Related Work (Algebraic Subtyping)	5
4 Related Work (EFF)	5
4.1 Types and terms	5
4.2 Type System	5
4.2.1 Subtyping	5
4.2.2 Typing rules	6
5 Core Language (EFFCORE)	7
5.1 Types and terms	8
5.2 Type system	8
5.3 Typing rules	8
5.4 Reformulated typing rules	10
6 Proofs	15
6.1 Instantiation	15
6.2 Weakening	15
6.3 Substitution	15
6.4 Soundness	15
7 Type Inference	15
7.1 Polar types	15
7.2 Unification	15

Authors' addresses: Axel Faes, Department of Computer Science, KU Leuven, axel.faes@student.kuleuven.be; Amr Hany Saleh, Department of Computer Science, KU Leuven, amrhanyshehata.saleh@kuleuven.be; Tom Schrijvers, Department of Computer Science, KU Leuven, tom.schrijvers@kuleuven.be.

7.3	Principal Type Inference	17
8	Implementation	23
9	Evaluation	23
10	Conclusion	23
	Acknowledgments	23
	References	23

## LIST OF FIGURES

1	Typing rules: judgements	4
2	Typing rules: manipulate context	4
3	Terms of $\text{EFF}$	5
4	Types of $\text{EFF}$	6
5	Subtyping for pure and dirty types of $\text{EFF}$	6
6	Typing of $\text{EFF}$	7
7	Terms of $\text{EFFCORE}$	8
8	Types of $\text{EFFCORE}$	9
9	Relationship between Equivalence and Subtyping	9
10	Equations of distributive lattices for types	10
11	Equations for function, handler and dirty types	10
12	Equations of distributive lattices for dirts	11
13	Subtyping for dirts of $\text{EFFCORE}$	11
14	Typing of $\text{EFFCORE}$	12
15	Definitions for typing schemes and reformulated typing rules	13
16	Reformulated typing rules of $\text{EFFCORE}$	14
17	Polar types of $\text{EFFCORE}$	15
18	Bisubstitutions	16
19	Parameterisation and typing	16
20	Polar recursive type	17
21	Constructed types	17
22	Constraint solving	18
23	Constraint decomposition	19
24	Biunification algorithm	20
25	Type inference algorithm for expressions	21
26	Type inference algorithm for computations	22

## LIST OF TABLES

## 1 INTRODUCTION

The specification for a type-&-effect system with algebraic subtyping for algebraic effects and handlers is given in this document. The formal properties of this system are studied in order to find which properties are satisfied compared to other type-&-effect systems. The proposed type-&-effect system builds on two very recent developments in the area of programming language theory.

*Algebraic subtyping.* In his December 2016 PhD thesis, Stephen Dolan (University of Cambridge, UK), has presented a novel type system that combines subtyping and parametric polymorphism in a particularly attractive and elegant fashion. A cornerstone of his design are the algebraic properties that the subtyping relation should respect.

*Algebraic effects and handlers.* These are a new formalism for formally modelling side-effects (e.g. mutable state or non-determinism) in programming languages, developed by Matija Pretnar (University of Ljubljana) and Gordon Plotkin (University of Edinburgh). This approach is gaining a lot of traction, not only as a formalism but also as a practical feature in actual programming languages (e.g. the Koka language developed by Microsoft Research). We are collaborating with Matija Pretnar on the efficient implementation of one such language, called Eff. Axel Faes has contributed to this collaboration during a project he did for the Honoursprogramme of the Faculty of Engineering Science.

### 1.1 Motivation

Algebraic effects and handlers benefit from a custom type-&-effect system, a type system that also tracks which effects can happen in a program. Several such type-&-effect systems have been proposed in the literature, but all are unsatisfactory. We attribute this to the lack of the elegant properties of Dolan's type system. Indeed the existing type-&-effect systems are not only theoretically unsatisfactory, but they are also awkward to implement and use in practice.

*Research questions.*

- How can Dolan's elegant type system be extended with effect information?
- Which properties are preserved and which aren't preserved?
- What advantages are there to a type-&-effect system based on Dolan's elegant type system?

### 1.2 Goals

The goal of this thesis is to derive a type-&-effect system that extends Dolan's elegant type system with effect information. This type-&-effect system should inherit Dolan's harmonious combination of subtyping (in our case induced by a lattice structure on the effect information) with parametric polymorphism and preserve all of its desirable properties (both low-level algebraic properties and high-level meta-theoretical properties like type soundness and the existence of principal types). Afterwards this type-&-effect system The following approach is taken:

- (1) Study of the relevant literature and theoretical background.
- (2) Design of a type-&-effect system derived from Dolan's, that integrates effects.
- (3) Proving the desirable properties of the proposed type-&-effect system: type soundness, principal typing, ...
- (4) Time permitting: Design of a type inference algorithm that derives the principal types of programs without type annotations and proving its correctness.
- (5) Time permitting: Implementation of the algorithm and comparing it to other algorithms (such as row polymorphism based type-&-effect systems).

### 1.3 Results

Describe what the resulting product is and how it is useful or provides an advantage over other solutions.

## 2 BACKGROUND

### 2.1 Programming language theory

The field of programming language theory is a branch of computer science that describes how to formally describe complete programming languages and programming language features, such as algebraic effect handlers.

The work described in this thesis uses several aspects from programming language theory. A first subdiscipline is type theory. Type theory is used to formally describe type systems. A type system is a set of rules that are used to describe the accepted structure of a programming language. Each rule uses or assigns types to the various terms of the programming language. The typing rules typically have one of the following forms:

$$\begin{array}{c}
 \text{FACT} \\
 \Gamma \vdash e : \tau
 \end{array}
 \qquad
 \begin{array}{c}
 \text{INFERENCE RULE} \\
 \frac{\Gamma \vdash e_1 : \tau_1 \rightarrow \tau_2 \quad \Gamma \vdash e_2 : \tau_1}{\Gamma \vdash e_1 e_2 : \tau_2}
 \end{array}$$

Fig. 1. Typing rules: judgements

A *Fact* states that, under the assumption of  $\Gamma$ ,  $e$  has type  $\tau$ . The context,  $\Gamma$ , is a mapping of the free variables of  $e$  to their types. It is called a fact since the rule always holds.

An *Inference rule* states that, if a derivation for  $\Gamma \vdash e_1 : \tau_1 \rightarrow \tau_2$  can be found and a derivation for  $\Gamma \vdash e_2 : \tau_1$  can be found, it follows that there is a derivation for  $\Gamma \vdash e_1 e_2 : \tau_2$ .

In this example,  $e_1$  is a function type. There is also a derivation for  $e_2$  which has the same type as the argument type of  $e_1$ . The inference rule then states that the application of  $e_2$  to  $e_1$  has type  $\tau_2$ . Thus, the semantics of the programming language constructs, such as function application, are defined by the typing rules.

An inference rule can be read in multiple ways. It can be read top-down or bottom-up. Reading it top-down gives the above described reasoning. Given some expressions and some constraints, another expression can be constructed with a specific type. The bottom-up approach states that, given an expression such as the function application, there is a specific way the different parts of the expression can be typed. In the given example, a function expression has type  $\tau_2$ . Therefore, both  $e_1$  and  $e_2$  must follow a specific set of constraints. It is known that a function needs to exist of type  $\tau_1 \rightarrow \tau_2$  and an expression that matches the argument of the function,  $\tau_1$  needs to exist.

Figure 2 also shows that the context,  $\Gamma$ , can be manipulated. In the typing rule, the context is used for the  $\lambda$ -abstraction. The condition states that  $e$  has type  $\tau_2$  given that context and that  $x$ , which can be a free variable in the expression  $e$ , has type  $\tau_1$ .

$$\begin{array}{c}
 \text{FUN} \\
 \frac{\Gamma, x : \tau_1 \vdash e : \tau_2}{\Gamma \vdash \lambda x. c : \tau_1 \rightarrow \tau_2}
 \end{array}$$

Fig. 2. Typing rules: manipulate context

## 2.2 Subtyping

## 2.3 Algebraic effects and handlers

### 3 RELATED WORK (ALGEBRAIC SUBTYPING)

Subtyping is a partial order which is a reflexive transitive binary relation satisfying antisymmetry (subtyping rules). The subtyping order also forms a distributive lattice (equivalence rules).

### 4 RELATED WORK (EFF)

The type-&-effect system that is used in EFF is based on subtyping and dirty types [1].

#### 4.1 Types and terms

*Terms.* Figure 3 shows the two types of terms in EFF. There are values  $v$  and computations  $c$ . Computations are terms that can contain effects. Effects are denoted as operations  $Op$  which can be called.

value $v ::=$	$x$	variable
	true	true
	false	false
	$\lambda x. c$	function
	{	handler
	return $x \mapsto c_r,$	return case
	$[Op\ y\ k \mapsto c_{Op}]_{Op \in O}$	operation cases
	}	
comp $c ::=$	$v_1\ v_2$	application
	do $x \leftarrow c_1 ; c_2$	sequencing
	if $e$ then $c_1$ else $c_2$	conditional
	let rec $f\ x = c_1$ in $c_2$	rec definition
	return $v$	returned val
	$Op\ v$	operation call
	handle $c$ with $v$	handling

Fig. 3. Terms of EFF

*Types.* Figure 4 shows the types of EFF. There are two main sorts of types. There are (pure) types  $A, B$  and dirty types  $\underline{C}, \underline{D}$ . A dirty type is a pure type  $A$  tagged with a finite set of operations  $\Delta$ , which we call dirt, that can be called. This finite set  $\Delta$  is an over-approximation of the operations that are actually called. The type  $\underline{C} \Rightarrow \underline{D}$  is used for handlers because a handler takes an input computation  $\underline{C}$ , handles the effects in this computation and outputs computation  $\underline{D}$  as the result.

#### 4.2 Type System

**4.2.1 Subtyping.** The dirty type  $A ! \Delta$  is assigned to a computation returning values of type  $A$  and potentially calling operations from the set  $\Delta$ . This set  $\Delta$  is always an over-approximation of the actually called operations, and may safely be increased, inducing a natural subtyping judgement  $A ! \Delta \leq A ! \Delta'$  on dirty types. As dirty types can occur inside pure types, we also get a derived subtyping judgement on pure types. Both judgements are defined in Figure 5. Observe that, as usual, subtyping is contravariant in the argument types of functions and handlers, and covariant in their return types.

(pure) type $A, B ::=$	$\text{bool}$	bool type
	$  A \rightarrow \underline{C}$	function type
	$  \underline{C} \Rightarrow \underline{D}$	handler type
dirty type $\underline{C}, \underline{D} ::=$	$A ! \Delta$	
dirt $\Delta ::=$	$\{Op_1, \dots, Op_n\}$	

Fig. 4. Types of EFF

### Subtyping

$\text{SUB-bool}$	$\text{SUB} \rightarrow$	$\text{SUB} \Rightarrow$	$\text{SUB} !$
$\frac{}{\text{bool} \leq \text{bool}}$	$\frac{A' \leq A \quad \underline{C} \leq \underline{C'}}{A \rightarrow \underline{C} \leq A' \rightarrow \underline{C'}}$	$\frac{\underline{C'} \leq \underline{C} \quad \underline{D} \leq \underline{D'}}{\underline{C} \Rightarrow \underline{D} \leq \underline{C'} \Rightarrow \underline{D'}}$	$\frac{A \leq A' \quad \Delta \subseteq \Delta'}{A ! \Delta \leq A' ! \Delta'}$

Fig. 5. Subtyping for pure and dirty types of EFF

**4.2.2 Typing rules.** Figure 6 defines the typing judgements for values and computations with respect to a standard typing context  $\Gamma$ .

*Values.* The rules for subtyping, variables, and functions are entirely standard. For constants we assume a signature  $\Sigma$  that assigns a type  $A$  to each constant  $k$ , which we write as  $(k : A) \in \Sigma$ .

A handler expression has type  $A ! \Delta \cup \mathcal{O} \Rightarrow B ! \Delta$  iff all branches (both the operation cases and the return case) have dirty type  $B ! \Delta$  and the operation cases cover the set of operations  $\mathcal{O}$ . Note that the intersection  $\Delta \cap \mathcal{O}$  is not necessarily empty. The handler deals with the operations  $\mathcal{O}$ , but in the process may re-issue some of them (i.e.,  $\Delta \cap \mathcal{O}$ ).

When typing operation cases, the given signature for the operation  $(Op : A_{Op} \rightarrow B_{Op}) \in \Sigma$  determines the type  $A_{Op}$  of the parameter  $x$  and the domain  $B_{Op}$  of the continuation  $k$ . As our handlers are deep, the codomain of  $k$  should be the same as the type  $B ! \Delta$  of the cases.

*Computations.* With the following exceptions, the typing judgement  $\Gamma \vdash c : \underline{C}$  has a straightforward definition. The `return` construct renders a value  $v$  as a pure computation, i.e., with empty dirt. An operation invocation  $Op\ v$  is typed according to the operation's signature, with the operation itself as its only operation. Finally, rule `WITH` shows that a handler with type  $\underline{C} \Rightarrow \underline{D}$  transforms a computation with type  $\underline{C}$  into a computation with type  $\underline{D}$ .

typing contexts  $\Gamma ::= \epsilon \mid \Gamma, x : A$

### Expressions

$$\frac{\text{SUBVAL} \quad \Gamma \vdash v : A \quad A \leq A'}{\Gamma \vdash v : A'}$$

$$\frac{\text{VAR} \quad (x : A) \in \Gamma}{\Gamma \vdash x : A}$$

$$\frac{\text{TRUE}}{\Gamma \vdash \text{true} : \text{bool}}$$

$$\frac{\text{FALSE}}{\Gamma \vdash \text{false} : \text{bool}}$$

$$\frac{\text{FUN} \quad \Gamma, x : A \vdash c : \underline{C}}{\Gamma \vdash \lambda x. c : A \rightarrow \underline{C}}$$

### HAND

$$\frac{\Gamma, x : A \vdash c_r : B ! \Delta \quad \left[ (Op : A_{Op} \rightarrow B_{Op}) \in \Sigma \quad \Gamma, y : A_{Op}, k : B_{Op} \rightarrow B ! \Delta \vdash c_{Op} : B ! \Delta \right]_{Op \in O}}{\Gamma \vdash \{\text{return } x \mapsto c_r, [Op \ y \ k \mapsto c_{Op}]_{Op \in O}\} : \quad A ! \Delta \cup O \Rightarrow B ! \Delta}$$

### Computations

$$\frac{\text{SUBCOMP} \quad \Gamma \vdash c : \underline{C} \quad \underline{C} \leq \underline{C'}}{\Gamma \vdash c : \underline{C'}}$$

$$\frac{\text{APP} \quad \Gamma \vdash v_1 : A \rightarrow \underline{C} \quad \Gamma \vdash v_2 : A}{\Gamma \vdash v_1 v_2 : \underline{C}}$$

$$\frac{\text{COND} \quad \Gamma \vdash v : \text{bool} \quad \Gamma \vdash c_1 : \underline{C} \quad \Gamma \vdash c_2 : \underline{C}}{\Gamma \vdash \text{if } v \text{ then } c_1 \text{ else } c_2 : \underline{C}}$$

$$\frac{\text{LETREC} \quad \Gamma, f : A \rightarrow \underline{C}, x : A \vdash c_1 : \underline{C} \quad \Gamma, f : A \rightarrow \underline{C} \vdash c_2 : \underline{D}}{\Gamma \vdash \text{let rec } f \ x = c_1 \text{ in } c_2 : \underline{D}}$$

$$\frac{\text{RET} \quad \Gamma \vdash v : A}{\Gamma \vdash \text{return } v : A ! \emptyset}$$

$$\frac{\text{OP} \quad (Op : A \rightarrow B) \in \Sigma \quad \Gamma \vdash v : A}{\Gamma \vdash Op \ v : B ! \{Op\}}$$

$$\frac{\text{DO} \quad \Gamma \vdash c_1 : A ! \Delta \quad \Gamma, x : A \vdash c_2 : B ! \Delta}{\Gamma \vdash \text{do } x \leftarrow c_1 ; c_2 : B ! \Delta}$$

$$\frac{\text{WITH} \quad \Gamma \vdash v : \underline{C} \Rightarrow \underline{D} \quad \Gamma \vdash c : \underline{C}}{\Gamma \vdash \text{handle } c \text{ with } v : \underline{D}}$$

Fig. 6. Typing of EFF

## 5 CORE LANGUAGE (EFFCORE)

EFFCORE is a language with row-based effects, intersection and union types and effects and is subtyping based.

Define your problem very clearly. Provide a formal definition if possible, using mathematical definitions.

## 5.1 Types and terms

*Terms.* Figure 7 shows the two types of terms in EFFCORE. There are values  $v$  and computations  $c$ . Computations are terms that can contain effects. Effects are denoted as operations  $Op$  which can be called. The function term is explicitly annotated with a type and type abstraction and type application has been added to the language. These terms only work on pure types.

value $v ::=$	$x$	$\lambda$ -variable
	$\hat{x}$	let-variable
	true	true
	false	false
	$\lambda x.c$	function
	{	<b>handler</b>
	return $x \mapsto c_r,$	<b>return case</b>
	$[Op\ y\ k \mapsto c_{op}]_{op \in O}$	<b>operation cases</b>
	}	
comp $c ::=$	$v_1\ v_2$	application
	do $\hat{x} = c_1 ; c_2$	sequencing
	let $\hat{x} = v$ in $c$	let
	if $e$ then $c_1$ else $c_2$	conditional
	return $v$	<b>returned val</b>
	$Op\ v$	<b>operation call</b>
	handle $c$ with $v$	<b>handling</b>

Fig. 7. Terms of EFFCORE

*Types.* Figure 8 shows the types of EFFCORE. There are two main sorts of types. There are (pure) types  $A, B$  and dirty types  $\underline{C}, \underline{D}$ . A dirty type is a pure type  $A$  tagged with a finite set of operations  $\Delta$ , which we call dirt, that can be called. It can also be an union or intersection of dirty types. In further sections, the relations between dirty intersections or unions and pure intersections or unions are explained. The finite set  $\Delta$  is an over-approximation of the operations that are actually called. Row variables are introduced as well as intersection and unions. The  $\cdot(\text{DOT})$  is used to close rows that do not end with a row variable. The type  $\underline{C} \Rightarrow \underline{D}$  is used for handlers because a handler takes an input computation  $\underline{C}$ , handles the effects in this computation and outputs computation  $\underline{D}$  as the result.

## 5.2 Type system

## 5.3 Typing rules

Figure 14 defines the typing judgements for values and computations with respect to a standard typing context  $\Gamma$ .

*Values.* The rules for subtyping, variables, type abstraction, type application and functions are entirely standard. For constants we assume a signature  $\Sigma$  that assigns a type  $A$  to each constant  $k$ , which we write as  $(k : A) \in \Sigma$ .

A handler expression has type  $A ! \Delta \cup O \Rightarrow B ! \Delta$  iff all branches (both the operation cases and the return case) have dirty type  $B ! \Delta$  and the operation cases cover the set of operations  $O$ . Note that the intersection  $\Delta \cap O$  is not necessarily empty (with  $\cap$  being the intersection of the



typing contexts $\Gamma ::= \epsilon \mid \Gamma, x : A \mid \Gamma, \hat{x} : \forall \bar{\alpha}. B$	
monomorphic typing contexts $\Xi ::= \epsilon \mid \Xi, x : A$	
polymorphic typing contexts $\Pi ::= \epsilon \mid \Pi, \hat{x} : [\Xi]A$	
(pure) type $A, B ::= \text{bool}$	bool type
$\mid A \rightarrow \underline{C}$	function type
$\mid \underline{C} \Rightarrow \underline{D}$	<b>handler type</b>
$\mid \alpha$	type variable
$\mid \mu \alpha. A$	recursive type
$\mid \top$	top
$\mid \perp$	bottom
$\mid A \sqcap B$	intersection
$\mid A \sqcup B$	union
dirty type $\underline{C}, \underline{D} ::= A ! \Delta$	
dirt $\Delta ::= \text{Op}$	operation
$\mid \delta$	dirt variable
$\mid \emptyset$	empty dirt
$\mid \Delta_1 \sqcap \Delta_2$	intersection
$\mid \Delta_1 \sqcup \Delta_2$	union
All operations $\Omega ::= \bigsqcup \text{Op}_i \mid \text{Op}_i \in \Sigma$	

Fig. 8. Types of EffCore

$A_1 \leq A_2 \leftrightarrow A_1 \sqcup A_2 \equiv A_2$
$A_1 \leq A_2 \leftrightarrow A_1 \equiv A_1 \sqcap A_2$
$\Delta_1 \leq \Delta_2 \leftrightarrow \Delta_1 \sqcup \Delta_2 \equiv \Delta_2$
$\Delta_1 \leq \Delta_2 \leftrightarrow \Delta_1 \equiv \Delta_1 \sqcap \Delta_2$
$\underline{C}_1 \leq \underline{C}_2 \leftrightarrow \underline{C}_1 \sqcup \underline{C}_2 \equiv \underline{C}_2$
$\underline{C}_1 \leq \underline{C}_2 \leftrightarrow \underline{C}_1 \equiv \underline{C}_1 \sqcap \underline{C}_2$

Fig. 9. Relationship between Equivalence and Subtyping

operations, not to be confused with the  $\sqcap$  type). The handler deals with the operations  $\mathcal{O}$ , but in the process may re-issue some of them (i.e.,  $\Delta \cap \mathcal{O}$ ).

When typing operation cases, the given signature for the operation ( $\text{Op} : A_{\text{Op}} \rightarrow B_{\text{Op}} \in \Sigma$ ) determines the type  $A_{\text{Op}}$  of the parameter  $x$  and the domain  $B_{\text{Op}}$  of the continuation  $k$ . As our handlers are deep, the codomain of  $k$  should be the same as the type  $B ! \Delta$  of the cases.

*Computations.* With the following exceptions, the typing judgement  $\Gamma \vdash c : \underline{C}$  has a straightforward definition. The return construct renders a value  $v$  as a pure computation, i.e., with empty dirt. In this case, this is defined as a set with the  $(\text{DOT})$  as the only element. An operation

$A \sqcup A \equiv A$	$A \sqcap A \equiv A$
$A_1 \sqcup A_2 \equiv A_2 \sqcup A_1$	$A_1 \sqcap A_2 \equiv A_2 \sqcap A_1$
$A_1 \sqcup (A_2 \sqcup A_3) \equiv (A_1 \sqcup A_2) \sqcup A_3$	$A_1 \sqcap (A_2 \sqcap A_3) \equiv (A_1 \sqcap A_2) \sqcap A_3$
$A_1 \sqcup (A_1 \sqcap A_2) \equiv A_1$	$A_1 \sqcap (A_1 \sqcup A_2) \equiv A_1$
$\perp \sqcup A \equiv A$	$\perp \sqcap A \equiv \perp$
$\top \sqcup A \equiv \top$	$\top \sqcap A \equiv A$
$A_1 \sqcup (A_2 \sqcap A_3) \equiv (A_1 \sqcup A_2) \sqcap (A_1 \sqcup A_3)$	
$A_1 \sqcap (A_2 \sqcup A_3) \equiv (A_1 \sqcap A_2) \sqcup (A_1 \sqcap A_3)$	

Fig. 10. Equations of distributive lattices for types

$(A_1 \rightarrow \underline{C}_1) \sqcup (A_2 \rightarrow \underline{C}_2) \equiv (A_1 \sqcap A_2) \rightarrow (\underline{C}_1 \sqcup \underline{C}_2)$
$(A_1 \rightarrow \underline{C}_1) \sqcap (A_2 \rightarrow \underline{C}_2) \equiv (A_1 \sqcup A_2) \rightarrow (\underline{C}_1 \sqcap \underline{C}_2)$
$(A_1 \Rightarrow \underline{C}_1) \sqcup (A_2 \Rightarrow \underline{C}_2) \equiv (A_1 \sqcap A_2) \Rightarrow (\underline{C}_1 \sqcup \underline{C}_2)$
$(A_1 \Rightarrow \underline{C}_1) \sqcap (A_2 \Rightarrow \underline{C}_2) \equiv (A_1 \sqcup A_2) \Rightarrow (\underline{C}_1 \sqcap \underline{C}_2)$
$(\underline{C}_1 \sqcup \underline{C}_2) \equiv (A_1 ! \Delta_1 \sqcup A_2 ! \Delta_2) \equiv (A_1 \sqcup A_2) ! (\Delta_1 \sqcup \Delta_2)$
$(\underline{C}_1 \sqcap \underline{C}_2) \equiv (A_1 ! \Delta_1 \sqcap A_2 ! \Delta_2) \equiv (A_1 \sqcap A_2) ! (\Delta_1 \sqcap \Delta_2)$

Fig. 11. Equations for function, handler and dirty types

invocation  $\text{Op } v$  is typed according to the operation's signature, with the operation itself as its only operation. Finally, rule **WITH** shows that a handler with type  $\underline{C} \Rightarrow \underline{D}$  transforms a computation with type  $\underline{C}$  into a computation with type  $\underline{D}$ .

#### 5.4 Reformulated typing rules

$\Delta \sqcup \Delta \equiv \Delta$	$\Delta \sqcap \Delta \equiv \Delta$
$\Delta_1 \sqcup \Delta_2 \equiv \Delta_2 \sqcup \Delta_1$	$\Delta_1 \sqcap \Delta_2 \equiv \Delta_2 \sqcap \Delta_1$
$\Delta_1 \sqcup (\Delta_2 \sqcup \Delta_3) \equiv (\Delta_1 \sqcup \Delta_2) \sqcup \Delta_3$	$\Delta_1 \sqcap (\Delta_2 \sqcap \Delta_3) \equiv (\Delta_1 \sqcap \Delta_2) \sqcap \Delta_3$
$\Delta_1 \sqcup (\Delta_1 \sqcap \Delta_2) \equiv \Delta_1$	$\Delta_1 \sqcap (\Delta_1 \sqcup \Delta_2) \equiv \Delta_1$
$\emptyset \sqcup \Delta \equiv \Delta$	$\emptyset \sqcap \Delta \equiv \emptyset$
$\Omega \sqcup \Delta \equiv \Omega$	$\Omega \sqcap \Delta \equiv \Delta$
$\Delta_1 \sqcup (\Delta_2 \sqcap \Delta_3) \equiv (\Delta_1 \sqcup \Delta_2) \sqcap (\Delta_1 \sqcup \Delta_3)$	
$\Delta_1 \sqcap (\Delta_2 \sqcup \Delta_3) \equiv (\Delta_1 \sqcap \Delta_2) \sqcup (\Delta_1 \sqcap \Delta_3)$	

Fig. 12. Equations of distributive lattices for dirt

### Subtyping of dirt

SUB-!-Row-Row

$$\frac{n \geq 0 \quad m \geq 0 \quad p \geq 0 \quad \{Op_1, \dots, Op_n, Op_{n+m+1}, \dots, Op_{n+m+p}, \delta_1\} \leq \{Op_1, \dots, Op_n, Op_{n+1}, \dots, Op_{n+m}, \delta_2\}}{\{\delta_1\} \leq \{Op_{n+1}, \dots, Op_{n+m}, \delta_3\} \quad \{\delta_3\} = \{Op_{n+m}, \dots, Op_{n+m+p}, \delta_2\}}$$

SUB-!-Dot-Row

$$\frac{n \geq 0 \quad m \geq 0 \quad p \geq 0 \quad \{Op_1, \dots, Op_n, Op_{n+m+1}, \dots, Op_{n+m+p}, \cdot\} \leq \{Op_1, \dots, Op_n, Op_{n+1}, \dots, Op_{n+m}, \delta_2\}}{\emptyset \leq \{Op_{n+1}, \dots, Op_{n+m}, \delta_3\} \quad \{\delta_3\} = \{Op_{n+m}, \dots, Op_{n+m+p}, \delta_2\}}$$

SUB-!-Row-Dot

$$\frac{n \geq 0 \quad m \geq 0 \quad \{Op_1, \dots, Op_n, \delta_1\} \leq \{Op_1, \dots, Op_n, Op_{n+1}, Op_{n+m}, \cdot\}}{\{\delta_1\} \leq \{Op_{n+1}, Op_{n+m}, \cdot\}}$$

SUB-!-Dot-Dot

$$\frac{n \geq 0 \quad m \geq 0 \quad \{Op_1, \dots, Op_n, \cdot\} \leq \{Op_1, \dots, Op_n, Op_{n+1}, \dots, Op_{n+m}, \cdot\}}{\emptyset \leq \{Op_{n+1}, Op_{n+m}, \cdot\}}$$

Fig. 13. Subtyping for dirt of EffCORE

typing contexts  $\Gamma ::= \epsilon \mid \Gamma, x : A \mid \Gamma, \mathbf{x} : \forall \bar{\alpha}. B$

### Expressions

$$\begin{array}{c} \text{SUBVAL} \\ \frac{\Gamma \vdash v : A \quad A \leq B}{\Gamma \vdash v : B} \end{array} \quad \begin{array}{c} \text{VAR-}\lambda \\ \frac{(x : A) \in \Gamma}{\Gamma \vdash x : A} \end{array} \quad \begin{array}{c} \text{VAR-}\forall \\ \frac{(\mathbf{x} : \forall \bar{\alpha}. A) \in \Gamma}{\Gamma \vdash \mathbf{x} : A[\bar{A}/\bar{\alpha}]} \end{array} \quad \begin{array}{c} \text{TRUE} \\ \frac{}{\Gamma \vdash \text{true} : \text{bool}} \end{array}$$

$$\begin{array}{c} \text{FALSE} \\ \frac{}{\Gamma \vdash \text{false} : \text{bool}} \end{array} \quad \begin{array}{c} \text{FUN} \\ \frac{\Gamma, x : A \vdash c : \underline{C}}{\Gamma \vdash \lambda x. c : A \rightarrow \underline{C}} \end{array}$$

### HAND

$$\frac{\Gamma, x : A \vdash c_r : B ! \Delta \quad \left[ (\text{Op} : A_{\text{Op}} \rightarrow B_{\text{Op}}) \in \Sigma \quad \Gamma, y : A_{\text{Op}}, k : B_{\text{Op}} \rightarrow B ! \Delta \vdash c_{\text{Op}} : B ! \Delta \right]_{\text{Op} \in \mathcal{O}}}{\Gamma \vdash \{\text{return } x \mapsto c_r, [\text{Op } y \mapsto c_{\text{Op}}]_{\text{Op} \in \mathcal{O}}\} : \quad A ! \Delta \sqcup \mathcal{O} \Rightarrow B ! \Delta}$$

### Computations

$$\begin{array}{c} \text{SUBCOMP} \\ \frac{\Gamma \vdash c : \underline{C} \quad \underline{C} \leq \underline{D}}{\Gamma \vdash c : \underline{D}} \end{array} \quad \begin{array}{c} \text{APP} \\ \frac{\Gamma \vdash v_1 : A \rightarrow \underline{C} \quad \Gamma \vdash v_2 : A}{\Gamma \vdash v_1 v_2 : \underline{C}} \end{array}$$

$$\begin{array}{c} \text{COND} \\ \frac{\Gamma \vdash v : \text{bool} \quad \Gamma \vdash c_1 : \underline{C} \quad \Gamma \vdash c_2 : \underline{C}}{\Gamma \vdash \text{if } v \text{ then } c_1 \text{ else } c_2 : \underline{C}} \end{array} \quad \begin{array}{c} \text{RET} \\ \frac{\Gamma \vdash v : A}{\Gamma \vdash \text{return } v : A ! \emptyset} \end{array}$$

$$\begin{array}{c} \text{OP} \\ \frac{(\text{Op} : A \rightarrow B) \in \Sigma \quad \Gamma \vdash v : A}{\Gamma \vdash \text{Op } v : B ! \text{Op}} \end{array} \quad \begin{array}{c} \text{LET} \\ \frac{\Gamma \vdash v : A \quad \Gamma, \mathbf{x} : \forall \bar{\alpha}. A \vdash c : B ! \Delta \quad \alpha \notin \text{FTV}(\Gamma)}{\Gamma \vdash \text{let } \mathbf{x} = v \text{ in } c : B ! \Delta} \end{array}$$

$$\begin{array}{c} \text{DO} \\ \frac{\Gamma \vdash c_1 : A ! \Delta \quad \Gamma, \mathbf{x} : \forall \bar{\alpha}. A \vdash c_2 : B ! \Delta \quad \alpha \notin \text{FTV}(\Gamma)}{\Gamma \vdash \text{do } \mathbf{x} = c_1 ; c_2 : B ! \Delta} \end{array} \quad \begin{array}{c} \text{WITH} \\ \frac{\Gamma \vdash v : \underline{C} \Rightarrow \underline{D} \quad \Gamma \vdash c : \underline{C}}{\Gamma \vdash \text{handle } c \text{ with } v : \underline{D}} \end{array}$$

Fig. 14. Typing of EffCORE

**ΞDEF**  
 Ξ contains free λ-bound variables

**SUBSCHEME**  
 $[\Xi_2]A_2 \leq [\Xi_1]A_1 \leftrightarrow A_2 \leq A_1, \Xi_1 \leq \Xi_2$

**SUBINST**  
 $[\Xi_2]A_2 \leq^\vee [\Xi_1]A_1 \leftrightarrow \rho([\Xi_2]A_2) \leq [\Xi_1]A_1$  for some substitution  $\rho$   
 (instantiate type + dirt vars)

**INTER**  

$$\frac{\begin{array}{l} \text{dom}(\Xi_1 \sqcap \Xi_2) = \text{dom}(\Xi_1) \cup \text{dom}(\Xi_2) \\ (\Xi_1 \sqcap \Xi_2)(x) = \Xi_1(x) \sqcap \Xi_2(x), \text{ interpreting } \Xi_i(x) = \top \text{ if } x \in \text{dom}(\Xi_i) \text{ (for } i \in \{1, 2\}) \end{array}}{\Xi_1 \text{ and } \Xi_2 \text{ have greatest lower bound: } \Xi_1 \sqcap \Xi_2}$$

**SUBSTEQ**  
 $\rho([\Xi]A) \equiv [\rho(\Xi)]\rho(A)$

**Eq**  
 $[\Xi_2]A_2 \equiv^\vee [\Xi_1]A_1 \leftrightarrow [\Xi_2]A_2 \leq^\vee [\Xi_1]A_1, [\Xi_1]A_1 \leq^\vee [\Xi_2]A_2$

**WEAKENINGMONO**  
 $\Xi_2 \leq^\vee \Xi_1 \leftrightarrow \text{dom}(\Xi_2) \supseteq \text{dom}(\Xi_1), \Xi_2(x) \leq^\vee \Xi_1(x) \mid x \in \text{dom}(\Xi_1)$

**WEAKENINGPOLY**  
 $\Pi_2 \leq^\vee \Pi_1 \leftrightarrow \text{dom}(\Pi_2) \supseteq \text{dom}(\Pi_1), \Pi_2(\hat{\mathbf{x}}) \leq^\vee \Pi_1(\hat{\mathbf{x}}) \mid \hat{\mathbf{x}} \in \text{dom}(\Pi_1)$

Fig. 15. Definitions for typing schemes and reformulated typing rules

monomorphic typing contexts  $\Xi ::= \epsilon \mid \Xi, x : A$   
 polymorphic typing contexts  $\Pi ::= \epsilon \mid \Pi, \hat{\mathbf{x}} : [\Xi]A$

### Expressions

$$\begin{array}{c}
 \text{SUBVAL} \\
 \frac{\Pi \Vdash v : [\Xi_1]A_1 \quad [\Xi_1]A_1 \leq^v [\Xi_2]A_2}{\Pi \Vdash v : [\Xi_2]A_2}
 \end{array}
 \quad
 \begin{array}{c}
 \text{VAR-}\Xi \\
 \frac{}{\Pi \Vdash x : [x : A]A}
 \end{array}
 \quad
 \begin{array}{c}
 \text{VAR-}\Pi \\
 \frac{(\hat{\mathbf{x}} : [\Xi]A) \in \Pi}{\Pi \Vdash \hat{\mathbf{x}} : [\Xi]A}
 \end{array}$$
  

$$\begin{array}{c}
 \text{TRUE} \\
 \frac{}{\Pi \Vdash \text{true} : []\text{bool}}
 \end{array}
 \quad
 \begin{array}{c}
 \text{FALSE} \\
 \frac{}{\Pi \Vdash \text{false} : []\text{bool}}
 \end{array}
 \quad
 \begin{array}{c}
 \text{FUN} \\
 \frac{\Pi \Vdash c : [\Xi, x : A]\underline{C}}{\Pi \Vdash \lambda x. c : [\Xi](A \rightarrow \underline{C})}
 \end{array}$$
  

$$\begin{array}{c}
 \text{HAND} \\
 \frac{\Pi \Vdash c_r : [\Xi, x : A](B ! \Delta) \quad \left[ (Op : A_{Op} \rightarrow B_{Op}) \in \Sigma \quad \Pi \Vdash c_{Op} : [\Xi, y : A_{Op}, k : B_{Op} \rightarrow B ! \Delta](B ! \Delta) \right]_{Op \in O}}{\Pi \Vdash \{\text{return } x \mapsto c_r, [Op \ y \ k \mapsto c_{Op}]_{Op \in O}\} : [\Xi](A ! \Delta \sqcup O \Rightarrow B ! \Delta)}
 \end{array}$$

### Computations

$$\begin{array}{c}
 \text{SUBCOMP} \\
 \frac{\Pi \Vdash c : [\Xi_1]\underline{C}_1 \quad [\Xi_1]\underline{C}_1 \leq^v [\Xi_2]\underline{C}_2}{\Pi \Vdash c : [\Xi_2]\underline{C}_2}
 \end{array}
 \quad
 \begin{array}{c}
 \text{APP} \\
 \frac{\Pi \Vdash v_1 : [\Xi](A \rightarrow \underline{C}) \quad \Pi \Vdash v_2 : [\Xi]A}{\Pi \Vdash v_1 v_2 : [\Xi]\underline{C}}
 \end{array}$$
  

$$\begin{array}{c}
 \text{COND} \\
 \frac{\Pi \Vdash v : [\Xi]\text{bool} \quad \Pi \Vdash c_1 : [\Xi]\underline{C} \quad \Pi \Vdash c_2 : [\Xi]\underline{C}}{\Pi \Vdash \text{if } v \text{ then } c_1 \text{ else } c_2 : [\Xi]\underline{C}}
 \end{array}
 \quad
 \begin{array}{c}
 \text{RET} \\
 \frac{\Pi \Vdash v : [\Xi]A}{\Pi \Vdash \text{return } v : [\Xi](A ! \emptyset)}
 \end{array}$$
  

$$\begin{array}{c}
 \text{OP} \\
 \frac{(Op : A \rightarrow B) \in \Sigma \quad \Pi \Vdash v : [\Xi]A}{\Pi \Vdash Op \ v : [\Xi](B ! Op)}
 \end{array}
 \quad
 \begin{array}{c}
 \text{LET} \\
 \frac{\Pi \Vdash v : [\Xi_1]A \quad \Pi, \hat{\mathbf{x}} : [\Xi_1]A \Vdash c : [\Xi_2](B ! \Delta)}{\Gamma \Vdash \text{let } \hat{\mathbf{x}} = v \text{ in } c : [\Xi_1 \sqcap \Xi_2](B ! \Delta)}
 \end{array}$$
  

$$\begin{array}{c}
 \text{DO} \\
 \frac{\Pi \Vdash c_1 : [\Xi_1](A ! \Delta) \quad \Pi, \hat{\mathbf{x}} : [\Xi_1]A \Vdash c_2 : [\Xi_2](B ! \Delta)}{\Gamma \Vdash \text{do } \hat{\mathbf{x}} = c_1 ; c_2 : [\Xi_1 \sqcap \Xi_2](B ! \Delta)}
 \end{array}$$
  

$$\begin{array}{c}
 \text{WITH} \\
 \frac{\Pi \Vdash v : [\Xi](\underline{C} \Rightarrow \underline{D}) \quad \Pi \Vdash c : [\Xi]\underline{C}}{\Pi \Vdash \text{handle } c \text{ with } v : [\Xi]\underline{D}}
 \end{array}$$

Fig. 16. Reformulated typing rules of EFFCORE

## 6 PROOFS

### 6.1 Instantiation

### 6.2 Weakening

### 6.3 Substitution

### 6.4 Soundness

## 7 TYPE INFERENCE

### 7.1 Polar types

polymorphic typing contexts $\Pi$	$::= \epsilon \mid \Pi, \mathbf{x} : [\Xi^-]A^+$	
(pure) type $A^+, B^+$	$::= \text{bool}$	bool type
	$\mid A^- \rightarrow \underline{C}^+$	function type
	$\mid \underline{C}^- \Rightarrow \underline{D}^+$	<b>handler type</b>
	$\mid \alpha$	type variable
	$\mid \mu\alpha.A^+$	recursive type
	$\mid \perp$	bottom
	$\mid A^+ \sqcup B^+$	union
dirty type $\underline{C}^+, \underline{D}^+$	$::= A^+ ! \Delta^+$	
(pure) type $A^-, B^-$	$::= \text{bool}$	bool type
	$\mid A^+ \rightarrow \underline{C}^-$	function type
	$\mid \underline{C}^+ \Rightarrow \underline{D}^-$	<b>handler type</b>
	$\mid \alpha$	type variable
	$\mid \mu\alpha.A^-$	recursive type
	$\mid \top$	top
	$\mid A^- \sqcap B^-$	intersection
dirty type $\underline{C}^-, \underline{D}^-$	$::= A^- ! \Delta^-$	
dirt $\Delta^+$	$::= \text{Op}$	operation
	$\mid \delta$	dirt variable
	$\mid \emptyset$	empty dirt
	$\mid \Delta_1^+ \sqcup \Delta_2^+$	union
dirt $\Delta^-$	$::= \text{Op}$	operation
	$\mid \delta$	dirt variable
	$\mid \Omega$	full dirt (all operations, top)
	$\mid \Delta_1^- \sqcup \Delta_2^-$	union
	$\mid \Delta_1^- \sqcap \Delta_2^-$	intersection

Fig. 17. Polar types of EFFCORE

### 7.2 Unification

To operate on polar type terms, we generalise from substitutions to bisubstitutions, which map type variables to a pair of a positive and a negative type term. The definitions for bisubstitutions are given in Figure 18.

The presence of explicit type application in F,  $F_\omega$  and CoC makes the exact parameterisation of a polymorphic type relevant. Conversely, in ML, the parameterisation is irrelevant and all that matters is the set of possible instances.

BISUBSTITUTION	
$\xi = [A^+/\alpha^+, A^-/\alpha^-, \Delta^+/\delta^+, \Delta^-/\delta^-]$	
$\xi'(\alpha^+) = \alpha$	$\xi'(\alpha^-) = \alpha$
$\xi'(\delta^+) = \delta$	$\xi'(\delta^-) = \delta$
$\xi'(\_) = \_$	
$\xi(\underline{C}^+) \equiv \xi(A^+ ! \Delta^+) \equiv \xi(A^+) ! \xi(\Delta^+)$	$\xi(\underline{C}^-) \equiv \xi(A^- ! \Delta^-) \equiv \xi(A^-) ! \xi(\Delta^-)$
$\xi(\Delta_1^+ \sqcup \Delta_2^+) \equiv \xi(\Delta_1^+) \sqcup \xi(\Delta_2^+)$	$\xi(\Delta_1^- \sqcap \Delta_2^-) \equiv \xi(\Delta_1^-) \sqcap \xi(\Delta_2^-)$
$\xi(0p) \equiv 0p$	$\xi(\Delta_1^- \sqcup \Delta_2^-) \equiv \xi(\Delta_1^-) \sqcup \xi(\Delta_2^-)$
$\xi(\emptyset) \equiv \emptyset$	$\xi(0p) \equiv 0p$
$\xi(A_1^+ \sqcup A_2^+) \equiv \xi(A_1^+) \sqcup \xi(A_2^+)$	$\xi(\Omega) \equiv \Omega$
$\xi(\perp) \equiv \perp$	$\xi(A_1^- \sqcap A_2^-) \equiv \xi(A_1^-) \sqcap \xi(A_2^-)$
$\xi(bool) \equiv bool$	$\xi(\top) \equiv \top$
$\xi(A^- \rightarrow A^+) \equiv \xi(A^-) \rightarrow \xi(A^+)$	$\xi(bool) \equiv bool$
$\xi(A^- \Rightarrow A^+) \equiv \xi(A^-) \Rightarrow \xi(A^+)$	$\xi(A^+ \rightarrow A^-) \equiv \xi(A^+) \rightarrow \xi(A^-)$
$\xi(\mu\alpha.A^+) \equiv \mu\alpha.\xi'(A^+)$	$\xi(A^+ \Rightarrow A^-) \equiv \xi(A^+) \Rightarrow \xi(A^-)$
	$\xi(\mu\alpha.A^-) \equiv \mu\alpha.\xi'(A^-)$

Fig. 18. Bisubstitutions

$\forall\alpha\forall\beta.\alpha \rightarrow \beta \rightarrow \alpha$	$\forall\beta\forall\alpha.\alpha \rightarrow \beta \rightarrow \alpha$
$\{\alpha \rightarrow \beta \rightarrow \alpha \mid \alpha, \beta \text{types}\}$	$\{\alpha \rightarrow \beta \rightarrow \alpha \mid \beta, \alpha \text{types}\}$

Fig. 19. Parameterisation and typing

Thus, when manipulating constraints, an ML type checker need only preserve equivalence of the set of instances, and not equivalence of the parameterisation. This freedom is not much used in plain ML, since unification happens to preserve equivalence of the parameterisation. However, this freedom is what allows MLsub to eliminate subtyping constraints.

For all positive type terms  $A^+$  and variables, there exist positive type terms  $A_\alpha^+$  and  $A_g^+$  such that  $A_\alpha^+ \in \perp, \alpha$ ,  $\alpha$  is guarded in  $A_g^+$ , and  $A^+$  is equivalent to  $A_\alpha^+ \sqcup A_g^+$ .

For all negative type terms  $A^-$  and variables, there exist negative type terms  $A_\alpha^-$  and  $A_g^-$  such that  $A_\alpha^- \in \top, \alpha$ ,  $\alpha$  is guarded in  $A_g^-$ , and  $A^-$  is equivalent to  $A_\alpha^- \sqcap A_g^-$ .



$$\mu^+ \alpha . A^+ = \mu \alpha . A_g^+ \quad \mu^- \alpha . A^- = \mu \alpha . A_g^-$$

Fig. 20. Polar recursive type

**Constructed (predicate):**  
**constructed( $A$ )**

*constructed*( $A \rightarrow \underline{C}$ )

*constructed*( $\underline{C} \Rightarrow \underline{D}$ )

*constructed*(*bool*)

Fig. 21. Constructed types

### 7.3 Principal Type Inference

We introduce a judgement form  $\Pi \triangleright e : [\Xi^-]A^+$ , stating that  $[\Xi^-]A^+$  is the principal typing scheme of  $e$  under the polar typing context  $\Pi$ .

**Atomic (partial function):**

**atomic**( $A^+ \leq A^-$ ) =  $\theta$ , **atomic**( $\Delta^+ \leq \Delta^-$ ) =  $\theta$

$$\frac{\text{constructed}(A^-) \quad \beta \text{ not free in } A^-}{\text{atomic}(\beta \leq A^-) = [\beta \sqcap A^- / \beta^-]}$$

$$\frac{\text{constructed}(A^-) \quad \beta \text{ free in } A^-}{\text{atomic}(\beta \leq A^-) = [\mu^- \alpha. (\beta \sqcap [\alpha / \beta^-](A^-)) / \beta^-]}$$

$$\frac{\text{constructed}(A^+) \quad \beta \text{ not free in } A^+}{\text{atomic}(A^+ \leq \beta) = [\beta \sqcup A^+ / \beta^+]}$$

$$\frac{\text{constructed}(A^+) \quad \beta \text{ free in } A^+}{\text{atomic}(A^+ \leq \beta) = [\mu^+ \alpha. (\beta \sqcup [\alpha / \beta^+](A^+)) / \beta^+]}$$

$$\text{atomic}(\beta \leq \gamma) = [\mu^- \alpha. (\beta \sqcap [\alpha / \beta^-](\gamma)) / \beta^-] \equiv [\beta \sqcap \gamma / \beta^-] \equiv [\beta \sqcup \gamma / \gamma^+]$$

$$\text{atomic}(\delta \leq \text{Op}^-) = [\delta \sqcap \text{Op} / \delta^-]$$

$$\text{atomic}(\text{Op}^+ \leq \delta) = [\delta \sqcup \text{Op} / \delta^+]$$

$$\text{atomic}(\delta \leq (\Delta_1 \sqcup \Delta_2)) = [\delta \sqcap (\Delta_1 \sqcup \Delta_2) / \delta^-]$$

$$\text{atomic}(\delta_1 \leq \delta_2) = [\delta_1 \sqcup \delta_2 / \delta_2^+] \equiv [\delta_1 \sqcap \delta_2 / \delta_1^-]$$

Fig. 22. Constraint solving

**Subi (partial function):**

$$\mathbf{subi}(A^+ \leq A^-) = C, \mathbf{subi}(\Delta^+ \leq \Delta^-) = C, \mathbf{subi}(\underline{C}^+ \leq \underline{C}^-) = C$$

$$\mathbf{subi}(A^+ ! \Delta^+ \leq A^- ! \Delta^-) = \{A^+ \leq A^-, \Delta^+ \leq \Delta^-\}$$

$$\mathbf{subi}(A_1^- \rightarrow \underline{C}_1^+ \leq A_2^+ \rightarrow \underline{C}_2^-) = \{A_2^+ \leq A_1^-, \underline{C}_1^+ \leq \underline{C}_2^-\}$$

$$\mathbf{subi}(\underline{C}_1^- \Rightarrow \underline{D}_1^+ \leq \underline{C}_2^+ \Rightarrow \underline{D}_2^-) = \{\underline{C}_2^+ \leq \underline{C}_1^-, \underline{D}_1^+ \leq \underline{D}_2^-\}$$

$$\mathbf{subi}(\text{bool} \leq \text{bool}) = \{\}$$

$$\mathbf{subi}(\mu\alpha.A^+ \leq A^-) = \{[\mu\alpha.A^+/\alpha](A^+) \leq A^-\}$$

$$\mathbf{subi}(A^+ \leq \mu\alpha.A^-) = \{A^+ \leq [\mu\alpha.A^-/\alpha]A^-\}$$

$$\mathbf{subi}(A_1^+ \sqcup A_2^+ \leq A^-) = \{A_1^+ \leq A^-, A_2^+ \leq A^-\}$$

$$\mathbf{subi}(A^+ \leq A_1^- \sqcap A_2^-) = \{A^+ \leq A_1^-, A^+ \leq A_2^-\}$$

$$\mathbf{subi}(\perp \leq A^-) = \{\}$$

$$\mathbf{subi}(A^+ \leq \top) = \{\}$$

$$\mathbf{subi}(0p \leq 0p) = \{\}$$

$$\mathbf{subi}(\Delta_1^+ \sqcup \Delta_2^+ \leq \Delta^-) = \{\Delta_1^+ \leq \Delta^-, \Delta_2^+ \leq \Delta^-\}$$

$$\mathbf{subi}(\Delta^+ \leq 0p \sqcup \Delta^-) = \{\Delta^+ \leq \Delta^-\}$$

$$\mathbf{subi}(\Delta^+ \leq \Delta^- \sqcup 0p) = \{\Delta^+ \leq \Delta^-\}$$

$$\mathbf{subi}(\Delta^+ \leq \Delta_1^- \sqcup \Delta_2^-) = \{\Delta^+ \leq \Delta_1^-, \Delta^+ \leq \Delta_2^-\}$$

$$\mathbf{subi}(\Delta^+ \leq \Delta_1^- \sqcap \Delta_2^-) = \{\Delta^+ \leq \Delta_1^-, \Delta^+ \leq \Delta_2^-\}$$

$$\mathbf{subi}(\emptyset \leq \Delta^-) = \{\}$$

$$\mathbf{subi}(\Delta^+ \leq \Omega) = \{\}$$

Fig. 23. Constraint decomposition

**Binunify(History, ConstraintSet) = substitution**

START

$$biunify(C) = biunify(\emptyset; C)$$

EMPTY

$$biunify(H; \epsilon) = 1$$

REDUNDANT

$$c \in H$$

$$\frac{}{biunify(H; c :: C) = biunify(H; C)}$$

ATOMIC

$$atomic(c) = \theta_c$$

$$\frac{}{biunify(H; c :: C) = biunify(\theta_c(H \cup \{c\}); \theta_c(C)) \cdot \theta_c}$$

DECOMPOSE

$$subi(c) = C'$$

$$\frac{}{biunify(H; c :: C) = biunify(H \cup \{c\}; C' \# C)}$$

Fig. 24. Biunification algorithm

monomorphic typing contexts  $\Xi^- ::= \epsilon \mid \Xi^-, x : A^-$   
 polymorphic typing contexts  $\Pi ::= \epsilon \mid \Pi, \hat{x} : [\Xi^-]A^+$

### Expressions

$$\begin{array}{c}
 \text{VAR-}\Xi \quad \frac{}{\Pi \triangleright x : [x : \alpha]\alpha} \quad \text{VAR-}\Pi \quad \frac{(\hat{x} : [\Xi^-]A^+) \in \Pi}{\Pi \triangleright \hat{x} : [\Xi^-]A^+} \quad \text{TRUE} \quad \frac{}{\Pi \triangleright \text{true} : []bool} \quad \text{FALSE} \quad \frac{}{\Pi \triangleright \text{false} : []bool} \\
 \\
 \text{FUN} \quad \frac{\Pi \triangleright c : [\Xi^-]\underline{C}^+}{\Pi \triangleright \lambda x.c : [\Xi^- \setminus x](\Xi^-(x) \rightarrow \underline{C}^+)} \\
 \\
 \text{HAND} \quad \frac{\Pi \Vdash c_r : [\Xi_r^-](B^+ ! \Delta^+) \quad \left[ (Op : A_{Op}^+ \rightarrow B_{Op}^-) \in \Sigma \quad \Pi \Vdash c_{Op} : [\Xi_{Op}^-](\underline{C}_{Op}^+) \right]_{Op \in O}}{\Pi \Vdash \{\text{return } x \mapsto c_r, [Op \ y \ k \mapsto c_{Op}]_{Op \in O}\} : [\Xi_r^- \sqcap (\bigcap [\Xi_{Op}^- | Op \in O])](\alpha_1 ! \delta_1 \sqcup O \Rightarrow \alpha_2 ! \delta_2)} \\
 \\
 \xi = biunify \left( \begin{array}{c} B^+ ! \Delta^+ \leq \alpha_2 ! \delta_2 \\ \alpha_1 \leq \Xi_r^-(x) \\ \delta_1 \leq \delta_2 \\ \left[ \begin{array}{c} A_{Op}^+ \leq \Xi_{Op}^-(y) \\ B_{Op}^- \rightarrow \underline{C}_{Op}^+ \leq \Xi_{Op}^-(k) \\ \underline{C}_{Op}^+ \leq \alpha_2 ! \delta_2 \end{array} \right]_{Op \in O} \end{array} \right)
 \end{array}$$

Fig. 25. Type inference algorithm for expressions

monomorphic typing contexts  $\Xi^- ::= \epsilon \mid \Xi^-, x : A^-$   
 polymorphic typing contexts  $\Pi ::= \epsilon \mid \Pi, \hat{\mathbf{x}} : [\Xi^-]A^+$

### Computations

$$\begin{array}{c}
 \text{APP} \\
 \frac{\Pi \triangleright v_1 : [\Xi_1^-]A_1^+ \quad \Pi \triangleright v_2 : [\Xi_2^-]A_2^+}{\Pi \triangleright v_1 v_2 : \xi([\Xi_1^- \sqcap \Xi_2^-](\alpha ! \delta))} \xi = \text{biunify}(A_1^+ \leq A_2^+ \rightarrow (\alpha ! \delta)) \\
 \\
 \text{COND} \\
 \frac{\Pi \triangleright v : [\Xi_1^-]A^+ \quad \Pi \triangleright c_1 : [\Xi_2^-]\underline{C}_1^+ \quad \Pi \triangleright c_2 : [\Xi_3^-]\underline{C}_2^+}{\Pi \triangleright \text{if } v \text{ then } c_1 \text{ else } c_2 : \xi([\Xi_1^- \sqcap \Xi_2^- \sqcap \Xi_3^-](\alpha ! \delta))} \xi = \text{biunify} \left( \begin{array}{l} A^+ \leq \text{bool} \\ \underline{C}_1^+ \leq (\alpha ! \delta) \\ \underline{C}_2^+ \leq (\alpha ! \delta) \end{array} \right) \\
 \\
 \text{RET} \qquad \frac{\Pi \triangleright v : [\Xi^-]A^+}{\Pi \triangleright \text{return } v : [\Xi^-](A^+ ! \emptyset)} \qquad \text{OP} \qquad \frac{(\text{Op} : A^+ \rightarrow B^-) \in \Sigma \quad \Pi \triangleright v : [\Xi^-]A^+}{\Pi \triangleright \text{Op } v : [\Xi^-](B^+ ! \text{Op})} \\
 \\
 \text{LET} \\
 \frac{\Pi \triangleright v : [\Xi_1^-]A^+ \quad \Pi, \hat{\mathbf{x}} : [\Xi_1^-]A^+ \triangleright c : [\Xi_2^-](B^+ ! \Delta^+)}{\Gamma \triangleright \text{let } \hat{\mathbf{x}} = v \text{ in } c : [\Xi_1^- \sqcap \Xi_2^-](B^+ ! \Delta^+)} \\
 \\
 \text{DO} \\
 \frac{\Pi \triangleright c_1 : [\Xi_1^-](A^+ ! \Delta_1^+) \quad \Pi, \hat{\mathbf{x}} : [\Xi_1^-]A^+ \triangleright c_2 : [\Xi_2^-](B^+ ! \Delta_2^+)}{\Gamma \triangleright \text{do } \hat{\mathbf{x}} = c_1 ; c_2 : [\Xi_1^- \sqcap \Xi_2^-](B^+ ! \Delta_2^+)} \\
 \\
 \text{WITH} \\
 \frac{\Pi \triangleright v : [\Xi_1^-]\underline{C}_1^+ \quad \Pi \triangleright c : [\Xi_2^-]\underline{C}_2^+}{\Pi \triangleright \text{handle } c \text{ with } v : \xi([\Xi_1^- \sqcap \Xi_2^-](\alpha ! \delta))} \xi = \text{biunify}(\underline{C}_1^+ \leq \underline{C}_2^+ \Rightarrow (\alpha ! \delta))
 \end{array}$$

Fig. 26. Type inference algorithm for computations

## 8 IMPLEMENTATION

Describe the approach itself, in such detail that a reader could also implement this approach if s/he wished to do that.

## 9 EVALUATION

Novel approaches to problems are often evaluated empirically. Describe the evaluation process in such detail that a reader could reproduce the results. Describe in detail the setup of an experiment. Argue why this experiment is useful, and what you could learn from it. Be precise about what you want to measure, or about the hypothesis that you are testing. Discuss and interpret the results in terms of your experimental questions. Summarize the conclusions of the experimental evaluation.

## 10 CONCLUSION

Briefly recall what the goal of the work was. Summarize what you have done, summarize the results, and present conclusions. Conclusions include a critical assessment: where the original goals reached? Discuss the limitations of your work. Describe how the work could possibly be extended in the future, mitigating limitations or solving remaining problems.

## ACKNOWLEDGMENTS

I would like to thank Amr Hany Saleh for his continuous guidance and help.

## REFERENCES

- [1] Andrej Bauer and Matija Pretnar. 2014. An Effect System for Algebraic Effects and Handlers. *Logical Methods in Computer Science* 10, 4 (2014). [https://doi.org/10.2168/LMCS-10\(4:9\)2014](https://doi.org/10.2168/LMCS-10(4:9)2014)
- [2] Andrej Bauer and Matija Pretnar. 2015. Programming with algebraic effects and handlers. *J. Log. Algebr. Meth. Program.* 84, 1 (2015), 108–123. <https://doi.org/10.1016/j.jlamp.2014.02.001>
- [3] Stephen Dolan and Alan Mycroft. 2017. Polymorphism, Subtyping, and Type Inference in MLsub. In *Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages (POPL 2017)*. ACM, New York, NY, USA, 60–72. <https://doi.org/10.1145/3009837.3009882>
- [4] Daniel Hillerström and Sam Lindley. 2016. Liberating Effects with Rows and Handlers. In *Proceedings of the 1st International Workshop on Type-Driven Development (TyDe 2016)*. ACM, New York, NY, USA, 15–27. <https://doi.org/10.1145/2976022.2976033>
- [5] Daan Leijen. 2014. Koka: Programming with row polymorphic effect types. *arXiv preprint arXiv:1406.2061* (2014).
- [6] Daan Leijen. 2017. Type Directed Compilation of Row-typed Algebraic Effects. In *Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages (POPL 2017)*. ACM, New York, NY, USA, 486–499. <https://doi.org/10.1145/3009837.3009872>
- [7] Sam Lindley, Conor McBride, and Craig McLaughlin. 2017. Do Be Do Be Do. In *Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages (POPL 2017)*. ACM, New York, NY, USA, 500–514. <https://doi.org/10.1145/3009837.3009897>
- [8] Gordon D. Plotkin and Matija Pretnar. 2013. Handling Algebraic Effects. *Logical Methods in Computer Science* 9, 4 (2013). [https://doi.org/10.2168/LMCS-9\(4:23\)2013](https://doi.org/10.2168/LMCS-9(4:23)2013)
- [9] Matija Pretnar. 2014. Inferring Algebraic Effects. *Logical Methods in Computer Science* 10, 3 (2014). [https://doi.org/10.2168/LMCS-10\(3:21\)2014](https://doi.org/10.2168/LMCS-10(3:21)2014)
- [10] Matija Pretnar. 2015. An introduction to algebraic effects and handlers. invited tutorial paper. *Electronic Notes in Theoretical Computer Science* 319 (2015), 19–35.
- [11] Didier Rémy. 1994. Theoretical Aspects of Object-oriented Programming. MIT Press, Cambridge, MA, USA, Chapter Type Inference for Records in Natural Extension of ML, 67–95. <http://dl.acm.org/citation.cfm?id=186677.186689>