

MODEL 463 as of model year 2013
/facelift 2012

G1 On-board electrical system battery



P54.10-2095-11

<div> <div></div> <div></div> </div>	Remove/install		
<div> <div>⚠</div> <div>Danger!</div> </div> <div> <div>🔧</div> </div>	<p>Risk of explosion caused by escaping oxyhydrogen gas. Risk of injury caused by caustic burns to eyes, skin and mucous membranes from battery electrolyte (contains diluted sulfuric acid) or metal spatter due to short circuit. Risk of burn injuries caused by short circuit. Risk of poisoning caused by swallowing battery electrolyte (contains diluted sulfuric acid) or absorption of lead over the skin or orifices</p> <p>Notes on battery</p>	<p>No fire, sparks, open flames or smoking. Wear acid-resistant gloves and clothing and safety glasses with side guards. Do not place any conductive objects on the battery and avoid any short circuit from battery positive to ground. Only pour liquid battery electrolyte (diluted sulfuric acid) into suitable and appropriately marked containers.</p>	<p>AS54.10-Z-0001-01A</p> <p>AH54.10-P-0001-01A</p>
1	Remove cupholder	Vehicles with code (FG2) Front and rear cup holder	
2	Remove cover of on-board electrical system battery (G1) in rear footwell		
3	Detach ground line from on-board electrical system battery (G1)		
4	Install in the reverse order		
5	Perform basic programming		AR00.19-P-0200GW