Problem 6

In [115…
```
%matplotlib inline
import matplotlib.pyplot as plt
import numpy as np
import torch
import torchvision
import torchvision.transforms as transforms
import torch.nn as nn
import torch.nn.functional as F
import torch.optim as optim
```

Prepare for Dataset

In [116…
```
transform = transforms.Compose(
    [transforms.ToTensor(),
     transforms.Normalize((0.5, 0.5, 0.5), (0.5, 0.5, 0.5))])

trainset = torchvision.datasets.CIFAR10(root='./data', train=True,
                                        download=True, transform=transform)
trainloader = torch.utils.data.DataLoader(trainset, batch_size=4,
                                          shuffle=True, num_workers=2)

testset = torchvision.datasets.CIFAR10(root='./data', train=False,
                                       download=True, transform=transform)
testloader = torch.utils.data.DataLoader(testset, batch_size=4,
                                         shuffle=False, num_workers=2)

classes = ('plane', 'car', 'bird', 'cat',
           'deer', 'dog', 'frog', 'horse', 'ship', 'truck')
```

Choose a Device

In [117…
```
# If there are GPUs, choose the first one for computing. Otherwise use CPU.
device = torch.device("cuda:0" if torch.cuda.is_available() else "cpu")
print(device)
# If 'cuda:0' is printed, it means GPU is available.
```

```
cuda:0
```

Network Definition

In [118…
```
class Net(nn.Module):
    def __init__(self):
        super(Net, self).__init__()
        ###### Fill the blank here ######
        self.conv1 = nn.Conv2d(3, 32, 3, stride=1, padding=1)
        self.bn1 = nn.BatchNorm2d(32)
        self.conv2 = nn.Conv2d(32, 64, 3, stride=1, padding=1)
        self.bn2 = nn.BatchNorm2d(64)
```

```
        self.conv3 = nn.Conv2d(64, 128, 3, stride=1, padding=1)
        self.bn3 = nn.BatchNorm2d(128)

        self.pool = nn.MaxPool2d(2, 2)
        self.dropout_conv = nn.Dropout2d(0.25)

        self.fc1 = nn.Linear(128 * 4 * 4, 256)
        self.dropout_fc = nn.Dropout(0.5)
        self.fc2 = nn.Linear(256, 10)

    def forward(self, x):
        ###### Fill the blank here ######
        x = self.pool(F.relu(self.bn1(self.conv1(x))))
        x = self.dropout_conv(x)
        x = self.pool(F.relu(self.bn2(self.conv2(x))))
        x = self.dropout_conv(x)
        x = self.pool(F.relu(self.bn3(self.conv3(x))))
        x = self.dropout_conv(x)

        x = x.view(x.size(0), -1)
        x = F.relu(self.fc1(x))
        x = self.dropout_fc(x)
        x = self.fc2(x)
        return x

net = Net()     # Create the network instance.
net.to(device)  # Move the network parameters to the specified device.
```

Out[118…

```
Net(
  (conv1): Conv2d(3, 32, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
  (bn1): BatchNorm2d(32, eps=1e-05, momentum=0.1, affine=True, track_running_stats
=True)
  (conv2): Conv2d(32, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
  (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats
=True)
  (conv3): Conv2d(64, 128, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
  (bn3): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stat
s=True)
  (pool): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=Fals
e)
  (dropout_conv): Dropout2d(p=0.25, inplace=False)
  (fc1): Linear(in_features=2048, out_features=256, bias=True)
  (dropout_fc): Dropout(p=0.5, inplace=False)
  (fc2): Linear(in_features=256, out_features=10, bias=True)
)
```

Optimizer and Loss Function

In [119…

```
loss_func = nn.CrossEntropyLoss()
opt = optim.Adam(net.parameters(), lr=1e-3)
scheduler = optim.lr_scheduler.StepLR(opt, step_size=7, gamma=0.5)
```

Training Procedure

In [120…

```
avg_losses = []   # Avg. losses.
epochs = 25       # Total epochs.
print_freq = 1000  # Print frequency.

for epoch in range(epochs):  # Loop over the dataset multiple times.
    running_loss = 0.0       # Initialize running loss.
    for i, data in enumerate(trainloader, 0):
        # Get the inputs.
        inputs, labels = data

        # Move the inputs to the specified device.
        inputs, labels = inputs.to(device), labels.to(device)

        # Zero the parameter gradients.
        opt.zero_grad()

        # Forward step.
        outputs = net(inputs)
        loss = loss_func(outputs, labels)

        # Backward step.
        loss.backward()

        # Optimization step (update the parameters).
        opt.step()

        # Print statistics.
        running_loss += loss.item()
        if i % print_freq == print_freq - 1: # Print every several mini-batches.
            avg_loss = running_loss / print_freq
            print('[epoch: {}, i: {:5d}] avg mini-batch loss: {:.3f}'.format(
                epoch, i, avg_loss))
            avg_losses.append(avg_loss)
            running_loss = 0.0
    scheduler.step()


print('Finished Training.')
```

```
[epoch: 23, i:  4999] avg mini-batch loss: 0.823
[epoch: 23, i:  5999] avg mini-batch loss: 0.876
[epoch: 23, i:  6999] avg mini-batch loss: 0.821
[epoch: 23, i:  7999] avg mini-batch loss: 0.814
[epoch: 23, i:  8999] avg mini-batch loss: 0.812
[epoch: 23, i:  9999] avg mini-batch loss: 0.838
[epoch: 23, i: 10999] avg mini-batch loss: 0.857
[epoch: 23, i: 11999] avg mini-batch loss: 0.798
[epoch: 24, i:   999] avg mini-batch loss: 0.835
[epoch: 24, i:  1999] avg mini-batch loss: 0.842
[epoch: 24, i:  2999] avg mini-batch loss: 0.852
[epoch: 24, i:  3999] avg mini-batch loss: 0.814
[epoch: 24, i:  4999] avg mini-batch loss: 0.822
[epoch: 24, i:  5999] avg mini-batch loss: 0.796
[epoch: 24, i:  6999] avg mini-batch loss: 0.838
[epoch: 24, i:  7999] avg mini-batch loss: 0.879
[epoch: 24, i:  8999] avg mini-batch loss: 0.815
[epoch: 24, i:  9999] avg mini-batch loss: 0.842
[epoch: 24, i: 10999] avg mini-batch loss: 0.830
[epoch: 24, i: 11999] avg mini-batch loss: 0.860
Finished Training.
```

Training Loss Curve

In [121…


```
plt.plot(avg_losses)
plt.xlabel('mini-batch index / {}'.format(print_freq))
plt.ylabel('avg. mini-batch loss')
plt.show()
```



Evaluate on Test Dataset

In [122…
```
# Check several images.
dataiter = iter(testloader)
images, labels = next(dataiter)
imshow(torchvision.utils.make_grid(images))
print('GroundTruth: ', ' '.join('%5s' % classes[labels[j]] for j in range(4)))
outputs = net(images.to(device))
_, predicted = torch.max(outputs, 1)

print('Predicted: ', ' '.join('%5s' % classes[predicted[j]]
                              for j in range(4)))
```




```
GroundTruth:    cat  ship  ship plane
Predicted:    dog  ship  ship plane
```

In [123…
```
# Get test accuracy.
correct = 0
total = 0
with torch.no_grad():
    for data in testloader:
        images, labels = data
        images, labels = images.to(device), labels.to(device)
        outputs = net(images)
        _, predicted = torch.max(outputs.data, 1)
        total += labels.size(0)
        correct += (predicted == labels).sum().item()

print('Accuracy of the network on the 10000 test images: %d %%' % (
    100 * correct / total))
```

```
Accuracy of the network on the 10000 test images: 67 %
```

In [124…
```
# Get test accuracy for each class.
class_correct = list(0. for i in range(10))
class_total = list(0. for i in range(10))
with torch.no_grad():
    for data in testloader:
        images, labels = data
        images, labels = images.to(device), labels.to(device)
        outputs = net(images)
        _, predicted = torch.max(outputs, 1)
        c = (predicted == labels).squeeze()
        for i in range(4):
            label = labels[i]
```

```
            class_correct[label] += c[i].item()
            class_total[label] += 1

for i in range(10):
    print('Accuracy of %5s : %2d %%' % (
        classes[i], 100 * class_correct[i] / class_total[i]))
```

```
Accuracy of plane : 68 %
Accuracy of   car : 78 %
Accuracy of  bird : 51 %
Accuracy of   cat : 49 %
Accuracy of  deer : 64 %
Accuracy of   dog : 54 %
Accuracy of  frog : 73 %
Accuracy of horse : 66 %
Accuracy of  ship : 78 %
Accuracy of truck : 75 %
```