Problem 5

In [1]:
```
%matplotlib inline
import matplotlib.pyplot as plt
import numpy as np
import torch
import torchvision
import torchvision.transforms as transforms
import torch.nn as nn
import torch.nn.functional as F
import torch.optim as optim
```

Prepare for Dataset

In [2]:
```
transform = transforms.Compose(
    [transforms.ToTensor(),
     transforms.Normalize((0.5, 0.5, 0.5), (0.5, 0.5, 0.5))])

trainset = torchvision.datasets.CIFAR10(root='./data', train=True,
                                        download=True, transform=transform)
trainloader = torch.utils.data.DataLoader(trainset, batch_size=4,
                                          shuffle=True, num_workers=2)


testset = torchvision.datasets.CIFAR10(root='./data', train=False,
                                       download=True, transform=transform)
testloader = torch.utils.data.DataLoader(testset, batch_size=4,
                                         shuffle=False, num_workers=2)

classes = ('plane', 'car', 'bird', 'cat',
           'deer', 'dog', 'frog', 'horse', 'ship', 'truck')
```

```
100%|██████████| 170M/170M [00:16<00:00, 10.5MB/s]
```

In [3]:
```
# The function to show an image.
def imshow(img):
    img = img / 2 + 0.5     # Unnormalize.
    npimg = img.numpy()
    plt.imshow(np.transpose(npimg, (1, 2, 0)))
    plt.show()

# Get some random training images.
dataiter = iter(trainloader)
images, labels = next(dataiter)
# Show images.
imshow(torchvision.utils.make_grid(images))
# Print labels.
print(' '.join('%5s' % classes[labels[j]] for j in range(4)))
```



```
dog   car   dog horse
```

Choose a Device

In [4]:
```python
# If there are GPUs, choose the first one for computing. Otherwise use CPU.
device = torch.device("cuda:0" if torch.cuda.is_available() else "cpu")
print(device)
# If 'cuda:0' is printed, it means GPU is available.
```

```
cuda:0
```

Network Definition

In [5]:
```python
class Net(nn.Module):
    def __init__(self):
        super(Net, self).__init__()
        ###### Fill the blank here ######
        self.conv1 = nn.Conv2d(3, 10, 3, stride=1, padding=1)
        self.conv2 = nn.Conv2d(10, 20, 3, stride=1, padding=1)
        self.fc1 = nn.Linear(1280, 100)
        self.fc2 = nn.Linear(100, 10)

    def forward(self, x):
        ###### Fill the blank here ######
        x = F.relu(self.conv1(x))
        x = F.avg_pool2d(x, 2)
        x = F.relu(self.conv2(x))
        x = F.avg_pool2d(x, 2)
        x = x.view(x.size(0), -1)
        x = F.relu(self.fc1(x))
        x = self.fc2(x)
        return x

net = Net()     # Create the network instance.
net.to(device)  # Move the network parameters to the specified device.
```

Out[5]:
```
Net(
  (conv1): Conv2d(3, 10, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
  (conv2): Conv2d(10, 20, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
  (fc1): Linear(in_features=1280, out_features=100, bias=True)
  (fc2): Linear(in_features=100, out_features=10, bias=True)
)
```

Optimizer and Loss Function

In [6]:
```
# We use cross-entropy as loss function.
loss_func = nn.CrossEntropyLoss()
# We use stochastic gradient descent (SGD) as optimizer.
opt = optim.SGD(net.parameters(), lr=0.001, momentum=0.9)
```

Training Procedure

In [7]:
```
avg_losses = []   # Avg. losses.
epochs = 10       # Total epochs.
print_freq = 100  # Print frequency.

for epoch in range(epochs):  # Loop over the dataset multiple times.
    running_loss = 0.0       # Initialize running loss.
    for i, data in enumerate(trainloader, 0):
        # Get the inputs.
        inputs, labels = data

        # Move the inputs to the specified device.
        inputs, labels = inputs.to(device), labels.to(device)

        # Zero the parameter gradients.
        opt.zero_grad()

        # Forward step.
        outputs = net(inputs)
        loss = loss_func(outputs, labels)

        # Backward step.
        loss.backward()

        # Optimization step (update the parameters).
        opt.step()


        # Print statistics.
        running_loss += loss.item()
        if i % print_freq == print_freq - 1: # Print every several mini-batches.
            avg_loss = running_loss / print_freq
            print('[epoch: {}, i: {:5d}] avg mini-batch loss: {:.3f}'.format(
                epoch, i, avg_loss))
            avg_losses.append(avg_loss)
            running_loss = 0.0

print('Finished Training.')
```

```
[epoch: 9, i: 10799] avg mini-batch loss: 0.571
[epoch: 9, i: 10899] avg mini-batch loss: 0.603
[epoch: 9, i: 10999] avg mini-batch loss: 0.584
[epoch: 9, i: 11099] avg mini-batch loss: 0.604
[epoch: 9, i: 11199] avg mini-batch loss: 0.590
[epoch: 9, i: 11299] avg mini-batch loss: 0.625
[epoch: 9, i: 11399] avg mini-batch loss: 0.718
[epoch: 9, i: 11499] avg mini-batch loss: 0.686
[epoch: 9, i: 11599] avg mini-batch loss: 0.681
[epoch: 9, i: 11699] avg mini-batch loss: 0.652
[epoch: 9, i: 11799] avg mini-batch loss: 0.676
[epoch: 9, i: 11899] avg mini-batch loss: 0.637
[epoch: 9, i: 11999] avg mini-batch loss: 0.638
[epoch: 9, i: 12099] avg mini-batch loss: 0.516
[epoch: 9, i: 12199] avg mini-batch loss: 0.622
[epoch: 9, i: 12299] avg mini-batch loss: 0.648
[epoch: 9, i: 12399] avg mini-batch loss: 0.696
[epoch: 9, i: 12499] avg mini-batch loss: 0.735
Finished Training.
```

Training Loss Curve


In [8]:
```
plt.plot(avg_losses)
plt.xlabel('mini-batch index / {}'.format(print_freq))
plt.ylabel('avg. mini-batch loss')
plt.show()
```



Evaluate on Test Dataset

In [11]:
```
# Check several images.
dataiter = iter(testloader)
images, labels = next(dataiter)
imshow(torchvision.utils.make_grid(images))
print('GroundTruth: ', ' '.join('%5s' % classes[labels[j]] for j in range(4)))
outputs = net(images.to(device))
_, predicted = torch.max(outputs, 1)

print('Predicted: ', ' '.join('%5s' % classes[predicted[j]]
                              for j in range(4)))
```




```
GroundTruth:    cat  ship  ship plane
Predicted:   ship   car  ship plane
```

In [12]:
```
# Get test accuracy.
correct = 0
total = 0
with torch.no_grad():
    for data in testloader:
        images, labels = data
        images, labels = images.to(device), labels.to(device)
        outputs = net(images)
        _, predicted = torch.max(outputs.data, 1)
        total += labels.size(0)
        correct += (predicted == labels).sum().item()

print('Accuracy of the network on the 10000 test images: %d %%' % (
    100 * correct / total))
```

```
Accuracy of the network on the 10000 test images: 65 %
```

In [13]:
```
# Get test accuracy for each class.
class_correct = list(0. for i in range(10))
class_total = list(0. for i in range(10))
with torch.no_grad():
    for data in testloader:
        images, labels = data
        images, labels = images.to(device), labels.to(device)
        outputs = net(images)
        _, predicted = torch.max(outputs, 1)
        c = (predicted == labels).squeeze()
        for i in range(4):
            label = labels[i]
            class_correct[label] += c[i].item()
            class_total[label] += 1
```

```
for i in range(10):
    print('Accuracy of %5s : %2d %%' % (
        classes[i], 100 * class_correct[i] / class_total[i]))
```

```
Exception ignored in: <function _MultiProcessingDataLoaderIter.__del__ at 0x7da492d9
3c40>
Traceback (most recent call last):
  File "/usr/local/lib/python3.12/dist-packages/torch/utils/data/dataloader.py", lin
e 1654, in __del__
    self._shutdown_workers()
  File "/usr/local/lib/python3.12/dist-packages/torch/utils/data/dataloader.py", lin
e 1637, in _shutdown_workers
    if w.is_alive():
       ^^^^^^^^^^^^
  File "/usr/lib/python3.12/multiprocessing/process.py", line 160, in is_alive
    assert self._parent_pid == os.getpid(), 'can only test a child process'
           ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
AssertionError: can only test a child process
Exception ignored in: <function _MultiProcessingDataLoaderIter.__del__ at 0x7da492d9
3c40>Traceback (most recent call last):

  File "/usr/local/lib/python3.12/dist-packages/torch/utils/data/dataloader.py", lin
e 1654, in __del__
    self._shutdown_workers()
  File "/usr/local/lib/python3.12/dist-packages/torch/utils/data/dataloader.py", lin
e 1637, in _shutdown_workers
    if w.is_alive():
       ^^^^^^^^^^^^
  File "/usr/lib/python3.12/multiprocessing/process.py", line 160, in is_alive
    assert self._parent_pid == os.getpid(), 'can only test a child process'
           ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
AssertionError: can only test a child process
Accuracy of plane : 75 %
Accuracy of   car : 73 %
Accuracy of  bird : 46 %
Accuracy of   cat : 44 %
Accuracy of  deer : 70 %
Accuracy of   dog : 44 %
Accuracy of  frog : 64 %
Accuracy of horse : 71 %
Accuracy of  ship : 81 %
Accuracy of truck : 79 %
```