```
{% extends "layout_content.html" %}
{% block content %}
    <h1 class="mb-3" style="display: inline-block;">My Classes ({{ classes.total }})</h1>
    <a class="btn btn-secondary btn-sm ml-4 mb-3" style="display: inline-block;" href="{{ url_for('new_class') }}">Add Class</a>
    {% for class in classes.items %}
        <article class="media content-section parent">

            <div class="ribbon"><a style="color:white;" href="{{ url_for('courses', course_id=class.course.id) }}">{{ class.course.name }}</a></div>

            <div class="media-body">
                <div class="article-metadata">
                    <small class="text-muted mr-2">Beginning: {{ class.class_starting_date.strftime('%d %b %Y') }}</small>
                </div>
                <h2><a class="article-title" href="{{ url_for('xclass', class_id=class.id) }}">{{ class.class_name }}</a></h2>
                <div class="mt-3 mb-0">
                    <a class="btn btn-primary btn-sm mt-1 mb-1 mr-1" href="{{ url_for('xclass', class_id=class.id) }}">Manage</a>
                    <a class="btn btn-secondary btn-sm mt-1 mb-1" href="{{ url_for('class_report', class_id=class.id) }}">Get Report</a>
                    <a class="btn btn-secondary btn-sm mt-1 mb-1" href="{{ url_for('update_class', class_id=class.id) }}">Update</a>
                    <button type="button" class="btn btn-danger btn-sm m-1" data-toggle="modal" data-target="#deleteModal{{ class.id }}">Delete</button>
                </div>
            </div>
        </article>
        <!-- Modal -->
        <div class="modal fade" id="deleteModal{{ class.id }}" tabindex="-1" role="dialog" aria-labelledby="deleteModalLabel" aria-hidden="true">
            <div class="modal-dialog" role="document">
                <div class="modal-content">

                    <div class="modal-header">
                        <h5 class="modal-title" id="deleteModalLabel">Delete Class?</h5>
                        <button type="button" class="close" data-dismiss="modal" aria-label="Close">
                            <span aria-hidden="true">&times;</span>
                        </button>
                    </div>
                    <p class="modal-body"><font color="red">Warning: All this Classes students will also be deleted if this class is the only class they are assigned to!</font></p>
                    <div class="modal-footer">
                        <button type="button" class="btn btn-secondary" data-dismiss="modal">Close</button>
                        <form action="{{ url_for('delete_class', class_id=class.id) }}" method="POST">
                            <input class="btn btn-danger" type="submit" value="Delete">
                        </form>
                    </div>
                </div>
            </div>
        </div>
    {% endfor %}
    {% for page_num in classes.iter_pages(left_edge=1, right_edge=1, left_current=1, right_current=2) %}
        {% if page_num %}
        {% if classes.page == page_num %}
            <a class="btn btn-info mb-4" href="{{ url_for('classes', page=page_num) }}">{{ page_num }}</a>
        {% else %}
            <a class="btn btn-outline-info mb-4" href="{{ url_for('classes', page=page_num) }}">{{ page_num }}</a>
        {% endif %}
        {% else %}
            ...
        {% endif %}
    {% endfor %}

{% endblock content %}
```