```html
{% extends "layout_content.html" %}
{% block content %}
  <article class="parent media content-section">

    <div class="ribbon"><a style="color:white;" href="{{ url_for('courses', course_id=homework.topic.course.id) }}">{{ homework.topic.course.name }}</a></div>

    <img class="rounded-circle article-img" src="{{ url_for('static', filename='profile_pics/def.png') }}">
    <div class="media-body">
      <h2><a class="article-title" href="{{ url_for('homework', homework_id=homework.id) }}">{{ homework.name }}</a></h2>


      <h4 class="m-0 p-0 mb-2">Classes Assigned To</h4>
  <p class="m-0 p-0 mb-3">
      {% for class in homework.topic.course.classes %}
      - {{ class.class_name }}<br>
      {% endfor %}

      </p>

      <h4 class="mt-2">Recorded Performance</h4>

      {% if class_perf.datasets %}

      <div id="graph-container">
        <canvas id="performanceGraph"></canvas>
      </div>


      {% else %}
      <p>No data to graph.</p>
      {% endif %}

      <div class="mt-3 mb-0">
        <a class="btn btn-secondary btn-sm mt-1 mb-1" href="{{ url_for('update_homework', homework_id=homework.id) }}">Update Details</a>
        <!-- <a class="btn btn-secondary btn-sm mt-1 mb-1 ml-1" href="">Add To Class</a> -->
        <!-- <a class="btn btn-secondary btn-sm mt-1 mb-1 ml-1" href="">Remove From Class</a> -->
        <button type="button" class="btn btn-danger btn-sm m-1" data-toggle="modal" data-target="#deleteModal">Delete</button>
      </div>
    </div>
  </article>
  <!-- Modal -->
  <div class="modal fade" id="deleteModal" tabindex="-1" role="dialog" aria-labelledby="deleteModalLabel" aria-hidden="true">
    <div class="modal-dialog" role="document">
      <div class="modal-content">
        <div class="modal-header">
          <h5 class="modal-title" id="deleteModalLabel">Delete Class?</h5>
          <button type="button" class="close" data-dismiss="modal" aria-label="Close">
            <span aria-hidden="true">&times;</span>
          </button>
        </div>
        <div class="modal-footer">
          <button type="button" class="btn btn-secondary" data-dismiss="modal">Close</button>
          <form action="{{ url_for('delete_homework', homework_id=homework.id) }}" method="POST">
            <input class="btn btn-danger" type="submit" value="Delete">
          </form>
        </div>
      </div>
    </div>
  </div>
```

```html
 <script src="https://code.jquery.com/jquery-3.4.1.js" integrity="sha256-
WpOohJOqMqqyKL9FccASB9O0KwACQJpFTUBLTYOVvVU=" crossorigin="anonymous"></script>
 <script src="https://cdn.jsdelivr.net/npm/chart.js@2.8.0"></script>
 <script type="text/javascript" src="{{ url_for('static', filename='js/dashboard_charts.js') }}"></script>
 <script type="text/javascript">

  // Setting graph to load onload.
  $(document).ready(function() {
   changeChart("performanceGraph", "bar",
        {{ class_perf.labels | safe }},
        {{ class_perf.datasets | safe }});
  });
  </script>
{% endblock content %}
```