```html
{% extends "layout_content.html" %}
{% block content %}
    <h1 class="mb-3" style="display: inline-block;">My Courses ({{ courses.total }})</h1>
    <a class="btn btn-secondary btn-sm ml-4 mb-3" style="display: inline-block;" href="{{ url_for('new_course') }}">Add
Course</a>
    {% for course in courses.items %}
        <article class="media content-section">
        <div class="media-body">

            <div style="display: inline-block">
                <h2><a class="article-title" href="{{ url_for('courses', course_id=course.id) }}">{{ course.name }}</a></h2>
            </div>

            <div style="display: inline-block; float:right;">
                <!-- <a class="btn btn-primary btn-sm mt-1 mb-1 mr-1" href="{{ url_for('courses', course_id=course.id) }}">Manage</a> -
->
                <a class="btn btn-secondary btn-sm mt-1 mb-1" href="{{ url_for('new_topic', course_id=course.id, next='courses')
}}">Add Topic</a>
                <a class="btn btn-secondary btn-sm mt-1 ml-1 mb-1" href="{{ url_for('new_exam', course_id=course.id, next='courses')
}}">Add Exam</a>
                <div style="display: inline-block;" class="dropdown show ml-1">
                    <a class="btn btn-secondary btn-sm mt-1 mb-1 mr-1 dropdown-toggle" href="#" role="button"
id="dropdownMenuLink" data-toggle="dropdown" aria-haspopup="true" aria-expanded="false">
                        <i class='fas fa-bars'></i>
                    </a>
                    <div class="dropdown-menu" aria-labelledby="dropdownMenuLink">
                        <a class="dropdown-item" href="{{ url_for('update_course', course_id=course.id) }}">Update Details</a>
                        <button type="button" class="dropdown-item btn-danger" style="color:red;" data-toggle="modal" data-
target="#deleteModal{{ course.id }}">Delete</button>
                    </div>
                </div>
                <!-- <a class="btn btn-secondary btn-sm mt-1 ml-1 mb-1" href="{{ url_for('update_course', course_id=course.id)
}}">Update Details</a>
                <button type="button" class="btn btn-danger btn-sm ml-1 mb-1 mt-1 mr-0" data-toggle="modal" data-
target="#deleteModal{{ course.id }}">Delete</button> -->
            </div>

            <div class="mb-3">
                <p class="m-0">Duration: {{ course.start_date.strftime('%b %Y') }}-{{
course.start_date.replace(year=course.start_date.year + course.year_num).strftime('%y') }} ({{ course.year_num }} Years)</p>
                <p class="m-0">Grading System: {{ course.grading_system[1:] }}</p>

                {% if course.classes|length > 0 %}
                <p>Classes Enrolled:
                {% for xclass in course.classes %}
                <br>- {{ xclass.class_name }}
                {% endfor %}
                </p>
                {% else %}
                <p>Classes Enrolled: None</p>
                {% endif %}

            </div>


            {% if course.topics %}
                <h5>Topics</h5>
                {% for topic in course.topics %}
                <article class="content-section" style="background:#eeeeee;">
                    <div style="display: inline-block;">
                    <a href="{{ url_for('topic', topic_id=topic.id) }}"><h6 class="mt-2">{{ topic.name }}</h6></a>
                    </div>
                    <div style="display: inline-block;" class="float-right">

                        <div style="display: inline-block;" class="dropdown show">
```

```html
                <a class="btn btn-secondary btn-sm mt-1 mb-1 mr-1 dropdown-toggle" href="#" role="button"
id="dropdownMenuLink" data-toggle="dropdown" aria-haspopup="true" aria-expanded="false">
                  <i class='fas fa-bars'></i>
                </a>
                <div class="dropdown-menu" aria-labelledby="dropdownMenuLink">
                  <a class="dropdown-item" href="{{ url_for('topic', topic_id=topic.id) }}">Manage</a>
                  <a class="dropdown-item" href="{{ url_for('update_topic', topic_id=topic.id) }}">Update Details</a>
                  <button type="button" class="dropdown-item btn-danger" style="color:red;" data-toggle="modal" data-
target="#deleteModalT{{ topic.id }}">Delete</button>
                </div>
              </div>
            </div>
          </article>
          <!-- Modal -->
          <div class="modal fade" id="deleteModalT{{ topic.id }}" tabindex="-1" role="dialog" aria-
labelledby="deleteModalLabel" aria-hidden="true">
            <div class="modal-dialog" role="document">
              <div class="modal-content">
                <div class="modal-header">
                  <h5 class="modal-title" id="deleteModalLabel">Delete Topic?</h5>
                  <button type="button" class="close" data-dismiss="modal" aria-label="Close">
                    <span aria-hidden="true">&times;</span>
                  </button>
                </div>
                <p class="modal-body"><font color="red">Warning: All this Topic's homeworks and tests will also be
deleted!</font></p>
                <div class="modal-footer">
                  <button type="button" class="btn btn-secondary" data-dismiss="modal">Close</button>
                  <form action="{{ url_for('delete_topic', topic_id=topic.id) }}" method="POST">
                    <input class="btn btn-danger" type="submit" value="Delete">
                  </form>
                </div>
              </div>
            </div>
          </div>
      {% endfor %}
    {% endif %}


      {% if course.exams %}
        <h5>Exams</h5>
      {% for exam in course.exams %}
        <article class="content-section" style="background:#eeeeee;">
          <div style="display: inline-block;">
          <a href="{{ url_for('courses', course_id=course.id) }}"><h6 class="mt-2">{{ exam.name }}</h6></a>
          </div>
          <div style="display: inline-block;" class="float-right">
          <!-- <a class="btn btn-primary btn-sm mt-1 mb-1 mr-1" href="{{ url_for('courses', course_id=course.id)
}}">Manage</a> -->
            <a class="btn btn-primary btn-sm mt-1 mb-1 mr-1" href="{{ url_for('mark_exam', exam_id=exam.id) }}">Mark
Exam</a>
            <div style="display: inline-block;" class="dropdown show">
              <a class="btn btn-secondary btn-sm mt-1 mb-1 mr-1 dropdown-toggle" href="#" role="button"
id="dropdownMenuLink" data-toggle="dropdown" aria-haspopup="true" aria-expanded="false">
                <i class='fas fa-bars'></i>
              </a>
              <div class="dropdown-menu" aria-labelledby="dropdownMenuLink">
                <a class="dropdown-item" href="{{ url_for('courses', course_id=course.id) }}">Manage</a>
                <a class="dropdown-item" href="{{ url_for('update_exam', exam_id=exam.id) }}">Update Details</a>
                <button type="button" class="dropdown-item btn-danger" style="color:red;" data-toggle="modal" data-
target="#deleteModalE{{ exam.id }}">Delete</button>
              </div>
            </div>
            <!-- <a class="btn btn-secondary btn-sm mt-1 mb-1" href="{{ url_for('update_exam', exam_id=exam.id) }}">Update
```

```html
Details</a>
                <button type="button" class="btn btn-danger btn-sm ml-1 mb-1 mt-1 mr-0" data-toggle="modal" data-target="#deleteModalE{{ exam.id }}">Delete</button> -->
            </div>
          </article>
          <!-- Modal -->
          <div class="modal fade" id="deleteModalE{{ exam.id }}" tabindex="-1" role="dialog" aria-labelledby="deleteModalLabel" aria-hidden="true">
            <div class="modal-dialog" role="document">
              <div class="modal-content">
                <div class="modal-header">
                  <h5 class="modal-title" id="deleteModalLabel">Delete Exam?</h5>
                  <button type="button" class="close" data-dismiss="modal" aria-label="Close">
                    <span aria-hidden="true">&times;</span>
                  </button>
                </div>
                <div class="modal-footer">
                  <button type="button" class="btn btn-secondary" data-dismiss="modal">Close</button>
                  <form action="{{ url_for('delete_exam', exam_id=exam.id) }}" method="POST">
                    <input class="btn btn-danger" type="submit" value="Delete">
                  </form>
                </div>
              </div>
            </div>
          </div>
        {% endfor %}
      {% endif %}


    </div>
  </article>
  <!-- Modal -->
  <div class="modal fade" id="deleteModal{{ course.id }}" tabindex="-1" role="dialog" aria-labelledby="deleteModalLabel" aria-hidden="true">
    <div class="modal-dialog" role="document">
      <div class="modal-content">
        <div class="modal-header">
          <h5 class="modal-title" id="deleteModalLabel">Delete Course?</h5>
          <button type="button" class="close" data-dismiss="modal" aria-label="Close">
            <span aria-hidden="true">&times;</span>
          </button>
        </div>
        <p class="modal-body"><font color="red">Warning: All this Course's topics, classes and students will also be deleted!</font></p>
        <div class="modal-footer">
          <button type="button" class="btn btn-secondary" data-dismiss="modal">Close</button>
          <form action="{{ url_for('delete_course', course_id=course.id) }}" method="POST">
            <input class="btn btn-danger" type="submit" value="Delete">
          </form>
        </div>
      </div>
    </div>
  </div>
{% endfor %}
{% for page_num in courses.iter_pages(left_edge=1, right_edge=1, left_current=1, right_current=2) %}
  {% if page_num %}
    {% if courses.page == page_num %}
      <a class="btn btn-info mb-4" href="{{ url_for('courses', page=page_num) }}">{{ page_num }}</a>
    {% else %}
      <a class="btn btn-outline-info mb-4" href="{{ url_for('courses', page=page_num) }}">{{ page_num }}</a>
    {% endif %}
  {% else %}
    ...
  {% endif %}
```

```
    {% endfor %}


{% endblock content %}
```