

CERBERUS 2080™ Bill of Materials, V1.1, June 2021

Provided as-is, expressly without warranties or representations of any kind. This list was prepared in good faith, but may contain inaccuracies.

	Part	Comments	Designator on PCB	Quantity	Price indication per unit*	Price indication, total*
ICs and IC sockets	Alliance Memory AS6C62256-55PCN , SRAM - Asynchronous Memory IC 256Kb (32K x 8) Parallel 55ns 28-PDIP	High and Low memories	LOW-MEM,HIGH-MEM	2	€ 2,94	€ 5,88
	AR 28 HZL-TT , 28 (2 x 14) Pos DIP, 0.6" (15.24mm) Row Spacing, Socket, Through Hole	Or an equivalent 28-pos 0.6" (15.24mm) Row Spacing DIP socket. I highly recommend PRECISION sockets.	LOW-MEM,HIGH-MEM	2	€ 1,27	€ 2,54
	Microchip ATF1504AS-10JU44 , IC CPLD 64MC 10NS 44PLCC	Cavia CPLD	CAVIA	1	€ 3,00	€ 3,00
	Microchip ATF1508AS-10JU84 , IC CPLD 128MC 10NS 84PLCC	SCUNK and SPACER CPLDs	SPACER,SCUNK	2	€ 9,15	€ 18,30
	Adam Tech PLCC-44-AT , 44 (4 x 11) Pos PLCC Socket, Through Hole	Or an equivalent PLCC44 through-hole IC socket	CAVIA	1	€ 1,08	€ 1,08
	Adam Tech PLCC-84-AT , 84 (4 x 21) Pos PLCC Socket, Through Hole	Or an equivalent PLCC84 through-hole IC socket	SPACER,SCUNK	2	€ 1,26	€ 2,52
	SN74HC244N , Buffer, Non-Inverting 2 Element 4 Bit per Element 3-State Output 20-PDIP	Alternatives from other manufacturers should be OK, but always use HC family	BUFFER2,BUFFER1	2	€ 0,50	€ 1,00
	AR 20 HZL-TT , IC socket, 20 (2 x 10) Pos DIP, 0.3" (7.62mm) Row Spacing, Through Hole, Pitch - Mating 0.100" (2.54mm)	Or an equivalent 20-pos DIP socket. I highly recommend PRECISION sockets.	BUFFER2,BUFFER1	2	€ 0,46	€ 0,92
	W65C02S6TPG-14 , IC, CPU, 14 MHz	W65C02S CPU	W65C02S	1	€ 6,99	€ 6,99
	Z84C0010PEG , IC, CPU, 10 MHz	Z80 CPU	Z80	1	€ 5,42	€ 5,42
	AR 40 HZL-TT , IC Socket, 40 (2 x 20) Pos DIP, 0.6" (15.24mm) Row Spacing, Through Hole, Pitch - Mating 0.100" (2.54mm)	Or an equivalent 40-pos DIP socket. I highly recommend PRECISION sockets.	Z80,W65C02S	2	€ 1,81	€ 3,62
	Microchip ATMEGA328P-PU , IC, microcontroller	CAT microcontroller	CAT	1	€ 2,15	€ 2,15
	AR 28-HZL/01/7-TT , IC socket, 28 (2 x 14) Pos DIP, 0.3" (7.62mm) Row Spacing Socket, Through Hole, Pitch - Mating 0.100" (2.54mm)	Or an equivalent 28-pos 0.3" (7.62mm) Row Spacing DIP socket. I highly recommend PRECISION sockets.	CAT	1	€ 2,19	€ 2,19
Oscillators & sockets	Renesas 7132LA55PDGI , SRAM - Dual Port, Asynchronous Memory IC 16Kb (2K x 8) Parallel 55ns 48-PDIP	The two dual-ported memories of 2 KB	VIDEO-DPRAM,CHAR-DPRAM	2	€ 10,33	€ 20,66
	AR 48 HZL-TT , IC Socket, 48 (2 x 24) Pos DIP, 0.6" (15.24mm) Row Spacing, Through Hole, Pitch - Mating 0.100" (2.54mm)	Or an equivalent 48-pos DIP socket. I highly recommend PRECISION sockets, particularly for 48 pins. Dual-wipe sockets will be hard to install, go for precision sockets.	VIDEO-DPRAM,CHAR-DPRAM	2	€ 2,17	€ 4,34
	OSZI 16,000000 MHz standard clock oscillator CMOS/TTL compatible	Or an equivalent 16 MHz 4-pin strong oscillator with 5V signal amplitude	MAIN-OSCILLATOR	1	€ 1,01	€ 1,01
Capacitors	ECS-100AX-25.175 25.175 MHz standard clock oscillator CMOS/TTL compatible	Or an equivalent 25.175 MHz 4-pin strong oscillator with 5V signal amplitude	VIDEO-OSCILLATOR	1	€ 1,25	€ 1,25
	Aries Electronics A462-ND , OSCILLATOR SOCKET FULL SIZE 4PIN	Sockets for the oscillators. Models of the same size from other brands should be OK.	MAIN-OSCILLATOR,VIDEO-OSCILLATOR	2	€ 0,65	€ 1,30
	10µF 16V Aluminum Electrolytic Capacitor, radial, through-hole, lead spacing between 0.098" (2.50mm) and 0.138" (3.50mm)	Higher voltage is OK, but observe lead spacing	C31,C35,C19,C2	4	€ 0,25	€ 1,00
Transistors	100µF 16V Aluminum Electrolytic Capacitor, radial, through-hole, lead spacing between 0.098" (2.50mm) and 0.138" (3.50mm)	Higher voltage is OK, but observe lead spacing	C32,C34,C36,C15,C14	5	€ 0,25	€ 1,25
	470µF 16V Aluminum Electrolytic Capacitor, radial, through-hole, lead spacing between 0.098" (2.50mm) and 0.138" (3.50mm)	Higher voltage is OK, but observe lead spacing	C1	1	€ 0,32	€ 0,32
	470pF Ceramic Capacitor C0G, NP0 Radial, through-hole, lead spacing 0.200" (5.08mm)	Anything at or above 10V will do, but observe lead spacing	C4,C5	2	€ 0,38	€ 0,76
	100nF , Ceramic Capacitor Y5V, radial, lead spacing 0.197" (5.00mm)	Anything at or above 10V will do, but observe lead spacing	C20,C21,C22,C23,C24,C25,C26,C27,C28,C29,C30,C38,C39,C40,C6,C17,C3,C16,C7,C9,C8,C12,C13,C11,C10,C18	26	€ 0,20	€ 5,20
	100pF , Ceramic Capacitor X7R radial, lead spacing 0.197" (5.00mm)	Anything at or above 10V will do, but observe lead spacing	C33,C37	2	€ 0,18	€ 0,36
	BC547B , Bipolar (BJT) Transistor NPN 45V 100mA 300MHz 500mW Through Hole TO-92-3	Or equivalent NPN transistor in the same package	Q3,Q2	2	€ 0,39	€ 0,78
Transistors	BC337-40 , Bipolar (BJT) Transistor NPN 45V 800mA 210MHz 625mW Through Hole TO-92	Or equivalent NPN transistor in the same package (But attention: this one should be a high-current transistor)	Q1	1	€ 0,34	€ 0,34

Resistors	10KΩ, Axial Metal Film Resistor, 1/4W, through-hole	The tolerance is not important. 5% will do just fine.	R11,R12,R49,R50,R63,R6,R5,R7,R8,R10,R9,R36,R35,R34,R33,R32,R31,R30,R29,R28,R27,R26,R25,R24,R23,R22,R21,R20,R19,R18,R17,R16,R15,R14,R13,R39,R40,R41,R42,R43,R44,R45,R46,R47,R48,R51,R52,R54,R55,R56,R57,R58,R59,R60,R61,R62	56	€ 0,02	€ 1,23
	2K2Ω, Axial Metal Film Resistor, 1/4W, through-hole, 1% tolerance		R53	1	€ 0,09	€ 0,09
	68Ω, Axial Metal Film Resistor, 1/4W, through-hole, 1% tolerance		R3,R2	2	€ 0,09	€ 0,18
	75Ω, Axial Metal Film Resistor, 1/4W, through-hole, 1% tolerance		R1	1	€ 0,09	€ 0,09
	220Ω, Axial Metal Film Resistor, 1/4W, through-hole, 1% tolerance		R4	1	€ 0,09	€ 0,09
	270Ω, Axial Metal Film Resistor, 1/4W, through-hole, 1% tolerance		R37,R38	2	€ 0,09	€ 0,18
Connectors	40-pin Pin Header strip, male, vertical, through hole, 2.54mm pin pitch	Cut the strip in the appropriate sizes to fit the respective PCB designations	ADDRESS-BUS-HEADER, DATA-BUS-HEADER, 5V-GND-1,5V-GND-2,5V-GND-3,5V-GND-4	1	€ 0,60	€ 0,60
	TE Connectivity 103308-1, Connector Header Through Hole 10 position 0.100" (2.54mm)	These are the headers for JTAG in-system programming of the CPLDs	JTAG-SPACER,JTAG-CAVIA,JTAG-SCUNK	3	€ 1,65	€ 4,95
	CADANIA 1AA300833_JHJC PS/2 keyboard connector	This is the PS/2 keyboard connector on the board	PS2-KEYBOARD-PORT	1	€ 0,53	€ 0,53
	Würth Elektronik 694106301002 DC Power Jack x6.4mm, Right Angle	Or equivalent barrel connector for 9V DC input	9V-DC	1	€ 1,20	€ 1,20
	MOLEX 90147-1106, 6 Position Receptacle Connector 0.100" (2.54mm) Through Hole	Or equivalent, with the same physical dimensions. You may not need one of these, if your uSD card adapter has 8 pins.	FTDI-ADAPTER-PORT, SD-CARD-ADAPTER-PORT1, SD-CARD-ADAPTER-PORT3	2	€ 1,67	€ 3,34
	MOLEX 90147-1108, 8 Position Receptacle Connector 0.100" (2.54mm) Through Hole	Or equivalent, with the same physical dimensions. You may not need this one, if your uSD card adapter has 6 pins.	SD-CARD-ADAPTER-PORT2, SD-CARD-ADAPTER-PORT4, SD-CARD-ADAPTER-PORT5	1	€ 2,20	€ 2,20
Various	Amphenol L77HDE15SD1CH4RHNVGA, D-Sub High Density Connectors Dsub, Stamped Signal 3A, High Density, Right Angle PCB Thru Hole, FP=8.89mm (.350"), 15 Socket, Bright Tin Shell, Flash Gold, 4-40 Rear Insert, Ground Tab with Boardlock, High Temp, Nickel Shell, VGA	This is the VGA connector on the board	VGA	1	€ 1,52	€ 1,52
	SB2H100-E3/54, Diode Schottky 100V 2A Through Hole DO-204AC (DO-15)	The one diode on the board	D1	1	€ 0,38	€ 0,38
	T7YA103MT20, Trimmer Potentiometer, through hole, 10Kohms, 20%	The trim potentiometer	TRIM-POT	1	€ 2,02	€ 2,02
	Traco Power TSR 2-2450, Linear Regulator Replacement DC DC Converter 1 Output 5V 2A 6.5V - 36V Input	The half-priced TSR 1-2450 (1A) should also do fine. This component is over-specified in CERBERUS.	REGULATOR	1	€ 8,95	€ 8,95
	Ekulit SUMMER CPM 121, RMP-14SP, Piezzo buzzer	Or equivalent buzzer with 7.6mm separation between the two leads	BUZZER	1	€ 1,16	€ 1,16
	Würth Elektronik 151051BS04000, LED BLUE DIFFUSED 5MM ROUND Through-Hole	Any standard, 5mm discrete LED will do	POWER	1	€ 0,21	€ 0,21
	E-Switch 500SSP1S2M7QEA, Slide Switch SPDT Through Hole, Right Angle, Vertical, 5A, 120V	This is the power on/off switch	SWITCH	1	€ 2,89	€ 2,89
	AZDelivery Micro SD TF Card Adapter, Memory Card Shield Module compatible with Arduino, using a 6-pin connector	A (micro)SD Card adapter is required by CERBERUS 2080. There are alternatives to this particular model, though, including some that use an 8-pin connector.	SD-CARD-ADAPTER-PORT1	1	€ 4,57	€ 4,57
	Nylon male stand-off, M2, 10+6mm, with matching nut and screw	These are to hold the (u)S card adapter in place	SD-CARD-ADAPTER-PORT1	4	€ 0,25	€ 1,00
PCB	Standard 12mm self-adhesive rubber feet	Standard rubber feet to avoid contact between solder joints and the surface where the computer sits	Try to place the rubber feet near to each of the four corners of the board, without touching solder joints	4	€ 0,20	€ 0,80
	CERBERUS 2080™ PCB	Minimum order is 5 pieces. Estimated price is 1/5 of that.	Not applicable	1	€ 10,72	€ 10,72
* Prices can vary widely depending on retailer, quantity purchased and time of purchase.					TOTAL*:	€ 143,08