MAINTAIN APPLICATION-BASED POLICIES



THE BEST WAY TO PROTECT THE FUTURE IS TO PREPARE FOR IT

- Migrate to an App-ID-based Security policy
- Maintain an App-ID Security policy
- Maintain App-ID





Learning Objectives

After you complete this module, you should be able to:

- Convert to an application-based Security policy
- Maintain an application-based Security policy
- Maintain an optimal App-ID configuration on your firewall





Migrate to an App-ID-based Security policy


Maintain an App-ID Security policy

Maintain App-ID






Moving to Application-Based Policies



Greenfield Example



Example Migration Method: Overview

Phase 1

Migrate legacy portbased policy to Palo Alto Networks firewall.



Phase 2

Add applicationbased rules above corresponding portbased rules.



Phase 3

Remove port-based rules.

Goals:

- Successful cutover.
- Minimize user issues.
- Capture application traffic.

Goals:

- Reduce the attack surface.
- Remove unknown applications as soon as possible.

Goals:

Complete policy migration.

Expedition (Migration Tool)

- Migrate policy from a pre-existing firewall.
- https://live.paloaltonetworks.com/t5/expedition-migration-tool/ct-p/migration_tool

Welcome to Expedition

ABOUT


Expedition is the fourth evolution of the Palo Alto Networks Migration Tool. The purpose of this tool is to help reduce the time and efforts of migrating a configuration from a supported vendor to Palo Alto Networks.

By using Expedition (Migration Tool), everyone can convert a configuration from Checkpoint, Cisco, or any other vendor to a PAN-OS and give you more time to improve the results. Expedition (Migration Tool) 3 added some functionalities to allow our customers to enforce security policies based on App-ID and User-ID as well. READ MORE

NOTE: Expedition is supported by the community as best effort. The Palo Alto Networks TAC does not provide support, so please post your questions in the community by clicking "Ask Questions" below.

Get the Expedition Installer

Phase 1: Migrate Port-Based Rules




paloalto®

^{*}Expedition tool provides some automation.

Phase 2: View Data of Port-Based Rules

Use **No App Specified** to discover port-based rules.




Phase 2: Discover Applications Matching a Port-Based Rule


Policies > Security > Policy Optimizer > No App Specified




- Click App Seen number or Compare to view any applications that matched the port-based rule.
- The firewall displays a list of applications seen and identified by a rule.
- Use applications listed to create applicationbased rule(s).




Phase 2: Clone a Port-Based Rule Using "Create Cloned Rule"




Result of "Create Cloned Rule"



Phase 2: Replace a Port-Based Rule Using "Add to This Rule"




Result of "Add to This Rule"




Phase 2: Replace a Port-Based Rule Using "Add to Existing Rule"

Option 3 of 4:




Result of "Add to Existing Rule"




Phase 2: Replace a Port-Based Rule Using "Match Usage"

Option 4 of 4:




- Use only when the rule matches a small number of legitimate applications.
- Copies all applications under Apps Seen to Apps on Rule.
- Firewall replaces portbased rule with application-based rule.

Result of "Match Usage"




Prioritize Port-Based Rules to Convert




Phase 3: Review Port-Based Rules

- After 60 days, review the Hit Count columns in the Security policy.
- Look for port-based rules with zero hits.



Phase 3: Disable Port-Based Rules



- Disable port-based rules that have not matched to any new traffic.
- Disabled rules are rendered in gray italic font.
- Tag rules that must be removed later (optional).

Phase 3: Remove Port-Based Rules

- After 90 days, delete port-based rules that have not matched to any new traffic.
- The goals:
 - At least 80% applicationbased rules
 - No inbound or outbound unknown applications (internal is acceptable)





Migrate to an App-ID-based Security policy



Maintain an App-ID Security policy

Maintain App-ID






Discover Security Policy Rules That Allow Unused Applications

- Applications in use change over time.
- Regularly identify and adjust allowed applications:
 - Maintains the smallest possible attack surface


Policies > Security > Policy Optimizer > Unused Apps



Rule allows five applications, but only three applications are currently in use.

View Unused Applications Allowed by a Security Policy Rule

Policies > Security > Policy Optimizer > Unused Apps



Migrate to an App-ID-based Security policy

Maintain an App-ID Security policy




Maintain App-ID







Applications and Threats Content Updates



Applications and Threats Package Contents



App-ID and Content-ID Depend on Content Updates



- To maintain optimal protection, schedule regular content updates.
- If App-ID cannot identify the traffic, then Content-ID cannot inspect the traffic.

29 | © 2017-2020 Palo Alto Networks, Inc.

Determine Your Content Update Workflow and Configuration

Application-Uptime

- 1. Allow new App-IDs in Security policy rule.
- 2. Schedule download and install.
- 3. Review content release notes.
- 4. View new and modified App-IDs.
- 5. Review and update policies.
- 6. Commit the configuration.

Priority for Firewall?

Security-First


- 1. Schedule download and install.
- 2. Review content release notes.
- 3. View new and modified App-IDs.
- 4. Review and update policies.
- 5. Commit the configuration.

- Priorities can be different for different firewalls:
 - Perimeter firewalls, internal firewalls, remote offices, test-dev environments, etc.

paloalto

Not Blocking New Applications


Application-Uptime Recommended



Schedule Download and Install

Application-Uptime and Security-First

Device > Dynamic Updates



Application-Uptime

Security-First




Review Content Update Release Notes

Application-Uptime and Security-First

Device > Dynamic Updates

VERSION	FILE NAME	FEATURES	ТҮРЕ	SIZE	SHA256	RELEASE DATE V	DOWNLO	CURRENTLY INSTALLED	ACTION	DOCUMENTA
Applications and Threats Last checked: 2020/07/22 01:02:06 UTC Schedule: Every Wednesday at 01:02 (Download only)										
8296-6207	panupv2-all-contents-8296-6207	Apps, Threats	Full	56 MB	a643b97f	2020/07/21 02:20:59 UTC	~		Install Review Policies Review Apps	Release Notes

https://support.paloaltonetworks.com




- Content Release Notes describe Security policy impacts.
- Get Content Release Notes from:
 - Firewall
 - Customer Support email

Review New and Updated Application Details

Application-Uptime and Security-First


Device > Dynamic Updates



Review Policies

Application-Uptime and Security-First


Device > Dynamic Updates



Update Policies


Application-Uptime and Security-First

Device > Dynamic Updates > Review Policies




Manual Download Example

Device > Dynamic Updates



Manual Install Example

Device > Dynamic Updates



- 2. Click Continue Installation.
- Disabling of new application signatures enables you to review and update policies even after a commit operation:
 - Possibly time-consuming to re-enable
- 3. Commit your configuration.



Module Summary

Now that you have completed this module, you should be able to:

- Convert to an application-based Security policy
- Maintain an application-based Security policy
- Maintain an optimal App-ID configuration on your firewall



Questions



Lab 11: Maintaining Application Based Policies

- Create and Test a Custom Service Object for HTTP
- Create and Test an FTP Application-Based Security Policy Rule
- Schedule App-ID Updates

paloalto®



Protecting our digital way of life.