



Downloadable Dynamometer Database (D³) - Test Summary Sheet



2015 Chevrolet SparkEV

Vehicle architecture	Battery Electric vehicle
Document date	9/1/2015
Revision Number	1
Notes:	

Vehicle Setup Information

Test cell location	ANL APRF Bldg 371
Vehicle dynamometer input	
Test weight [lb]	3157
Target A [lb]	23.36367
Target B [lb/mph]	0.3946
Target C [lb/mph ²]	0.01245
Test Fuel Information	
Fuel type	Electricity
Fuel density [g/ml]	-
Fuel Net HV [BTU/lbm]	-

Test ID [id]	Cycle	Cold start (CS) Hot start (HS)	Date	Test Cell Temp [C]	Test Cell RH [%]	Test Cell Baro [in-Hg]	Vehicle cooling fan speed: Speed Match [SM] or constant speed [CS]	Solar Lampz [W/m2]	Vehicle Climate Control settings	Hood Position [Up] or [Closed]	Window Position [Closed] or [Down]	Cycle Distance [mi]	Cycle Fuel economy [mpg] (Enlist Bag)	Cycle Fuel Consumed [gal] (Enlist Bag)	Cycle HV battery Integrated net current [DC A]	Cycle HV battery Average Zero crossing Voltage [V]	Cycle HV battery Net Energy [DC Wh]	Cycle HV battery Net Energy Consumption [DC Wh/mi]
Test information				Test cell information				Test cell setup		Vehicle setup		Electric energy consumption						
61508024	UDDS #1, Ph 1+2		08/13/15	-6	30	29	SM	NO	72F	Closed	Down	7.44	-	-	8.226	386.8	3181.21	427.41
61508024	Hwy #1, Ph 3		08/13/15	-5	25	29	SM	NO	72F	Closed	Down	10.25	-	-	7.588	374.1	2838.86	277.05
61508024	UDDS #2, Ph 4+5		08/13/15	-6	36	29	SM	NO	72F	Closed	Down	7.49	-	-	7.186	366.5	2632.78	351.39
61508024	US06 #1, Ph 6+7		08/13/15	-5	22	29	SM	NO	72F	Closed	Down	8.02	-	-	7.688	353.6	2711.44	337.99
61508025	US06 #2, Ph 1+2		08/13/15	-7	22	29	SM	NO	72F	Closed	Down	8.00	-	-	8.070	343.1	2761.99	345.06
61508025	UDDS #3, Ph 3+4		08/13/15	-6	42	29	SM	NO	72F	Closed	Down	7.50	-	-	7.305	333.6	2435.84	324.83
61508025	HWY#2, Ph 5		08/13/15	-5	30	29	SM	NO	72F	Closed	Down	4.13	-	-	3.040	292.0	887.74	215.20
Full charge test summary												Totals	52.83		49.1		17450	
Re-charging information				-5 Temperature during charge [C]														
Level: 2				Charge integrated power [AC Wh] 19868														
61508026	UDDS #1, Ph 1+2		08/20/15	-6	24	29	SM	NO	72F	Closed	Down	7.44	-	-	8.819	383.9	3387.51	455.16
61508026	Hwy #1, Ph 3		08/20/15	-4	20	29	SM	NO	72F	Closed	Down	10.23	-	-	7.661	370.7	2840.33	277.57
61508026	UDDS #2, Ph 4+5		08/20/15	-7	27	29	SM	NO	72F	Closed	Down	7.43	-	-	7.150	364.6	2605.57	350.47
61508026	US06 #1, Ph 6+7		08/20/15	-5	18	29	SM	NO	72F	Closed	Down	8.03	-	-	7.730	351.6	2709.65	337.52
61508027	US06 #2, Ph 1+2		08/20/15	-5	21	29	SM	NO	72F	Closed	Down	8.03	-	-	8.188	341.4	2787.11	347.08
61508027	UDDS #3, Ph 3+4		08/20/15	-6	27	29	SM	NO	72F	Closed	Down	7.49	-	-	6.933	329.5	2284.46	305.12
61508027	HWY#2, Ph 5		08/20/15	-5	20	29	SM	NO	72F	Closed	Down	3.27	-	-	2.519	267.1	672.96	205.53
61508013	UDDS #1, Ph 1+2		08/10/15	23	42	29	SM	NO	OFF	Closed	Down	7.46	-	-	3.402	391.6	1332.35	178.57
61508013	Hwy #1, Ph 3		08/10/15	25	37	29	SM	NO	OFF	Closed	Down	10.24	-	-	4.824	385.4	1859.05	181.61
61508013	UDDS #2, Ph 4+5		08/10/15	20	51	29	SM	NO	OFF	Closed	Down	7.47	-	-	3.325	382.1	1270.53	170.01
61508013	US06 #1, Ph 6+7		08/10/15	23	39	29	SM	NO	OFF	Closed	Down	8.02	-	-	5.371	373.4	2000.88	249.63
61508014	SSS 65 mph until middle deplete Ph1		08/10/15	26	37	29	SM	NO	OFF	Closed	Down	9.30	-	-	5.939	364.3	2163.49	232.69
61508014	US06 #2, Ph 3+4		08/10/15	22	40	29	SM	NO	OFF	Closed	Down	8.02	-	-	5.566	357.9	3506.50	437.07
61508015	UDDS #3, Ph 1+2		08/10/15	20	50	29	SM	NO	OFF	Closed	Down	7.49	-	-	3.594	353.6	1270.89	169.75
61508015	Hwy #2, Ph 3		08/10/15	25	37	29	SM	NO	OFF	Closed	Down	10.27	-	-	5.341	346.9	1852.59	180.38
61508015	UDDS #4, Ph 4+5		08/10/15	20	50	29	SM	NO	OFF	Closed	Down	7.49	-	-	3.708	340.9	1264.01	168.85
61508016	SSS 65 mph until deplete		08/10/15	26	35	29	SM	NO	OFF	Closed	Down	10.84	-	-	8.269	278.5	2302.99	212.54
Full charge test summary												Totals	86.59		49.3		18823	
Re-charging information				22 Temperature during charge [C]														
Level: 2				Charge integrated power [AC Wh] 20586														
61508004	SSS 0-80-0, 0% grade		08/07/15	24	37	29	SM	NO	OFF	Closed	Down	6.22	-	-	3.478	382.0	1328.75	213.62
61508006	SSS 0-80-0, 6% grade		08/07/15	23	39	29	SM	NO	OFF	Closed	Down	6.23	-	-	10.793	364.0	3924.75	630.35
61508007	WOTs#6		08/07/15	21	42	29	SM	NO	OFF	Closed	Down	5.25	-	-	6.047	328.6	1986.83	378.53
61508008	Passing maneuvers, 0% grade		08/07/15	24	37	29	SM	NO	OFF	Closed	Down	3.37	-	-	2.761	347.5	959.40	284.38
61508009	Passing maneuvers, 3% grade		08/07/15	25	35	29	SM	NO	OFF	Closed	Down	3.35	-	-	5.001	341.1	1705.84	509.28
61508010	Passing maneuvers, 6% grade		08/07/15	25	35	29	SM	NO	OFF	Closed	Down	3.34	-	-	6.754	344.0	2323.23	695.72
61508011	25% gradability		08/07/15	24	36	29	SM	NO	OFF	Closed	Down	0.63	-	-	4.287	329.3	1411.86	2239.31
61508017	UDDS #1, Ph 1+2		08/11/15	35	47	29	SM	850	72F	Closed	Down	7.45	-	-	4.341	391.3	1698.77	228.02
61508017	Hwy #1, Ph 3		08/11/15	38	31	29	SM	850	72F	Closed	Down	10.22	-	-	5.009	384.7	1927.16	188.52
61508017	UDDS #2, Ph 4+5		08/11/15	34	46	29	SM	850	72F	Closed	Down	7.48	-	-	4.015	380.6	1528.25	204.21
61508017	US06 #1, Ph 6+7		08/11/15	35	26	29	SM	850	72F	Closed	Down	8.02	-	-	5.517	371.5	2045.72	254.99
61508018	SSS 65MPH, Ph 1		08/11/15	38	29	29	SM	850	72F	Closed	Closed	2.81	-	-	1.947	366.2	712.92	253.85
61508018	US06 #2, Ph 3+4		08/11/15	35	27	29	SM	850	72F	Closed	Closed	8.03	-	-	5.687	361.3	3592.14	447.60
61508019	SC03, Ph 2		08/11/15	35	31	29	SM	850	72F	Closed	Closed	3.59	-	-	2.150	353.3	759.56	211.48
61508020	Hwy #2		08/11/15	38	25	29	SM	850	72F	Closed	Closed	10.25	-	-	5.489	348.5	1912.76	186.66
61508021	UDDS #3, Ph 1+2		08/11/15	34	37	29	SM	850	72F	Closed	Closed	7.48	-	-	4.343	342.1	1485.65	198.62
61508022	SSS 65 to deplete		08/11/15	39	21	29	SM	850	72F	Closed	Closed	12.01	-	-	9.197	294.2	2706.00	225.41
Full charge test summary												Totals	77.34		47.7		18369	
Re-charging information				32 Temperature during charge [C]														
Level: 2				Charge integrated power [AC Wh] 21305														

Summary notes

For the highway and US06, SC03, cycles only the second (hot) test results are presented in this summary.

Electric energy consumption:

HV battery Integrated net current --> Integrated current as reported by power analyzer

HV battery Average Zero crossing Voltage --> Calculated Average Zero crossing Voltage over the phase or cycle

HV Net Energy --> Integrated power as reported by power analyzer

Note that HV Net Energy is not equal to the product of HV battery Integrated net current times Average Zero crossing Voltage.

* Target Coefficients developed during AVTE coast down testing

Advanced Powertrain Research Facility Data referencing:

The purpose of this website is to provide publicly available data regarding advanced technology vehicles. Derived from independent laboratory testing, the data is intended to enhance the understanding of advanced vehicle technologies for researchers, students, and professionals engaged in energy efficient vehicle research, development and education. Data from this website can only be used with the following attribution: "This data is from the Downloadable Dynamometer Database (<http://www.transportation.anl.gov/D3/>) and was generated at the Advanced Powertrain Research Facility (APRF) at Argonne National Laboratory under the funding and guidance of the U.S. Department of Energy (DOE)" or using a standard bibliographic reference. Please contact d3info@anl.gov for questions, comments, or inquiries.