


System Design



Client Side Architecture

Types of Client

Logical manipulation has to be done on data before returning to client then, The logic may reside on server side or client side. On this basis Client are classified into two types

1. Thin Client
2. Thick Client

- Thin Client

When Logic that has to be performed on data reside on Server Side then it is classified as Thin Client. It depends on Cloud platform for its features.

Eg: Netflix

- Thick Client

When The logic that has to be performed on data resides on server side then it is known as Thick Client. It's function can also run offline. and runs at least some features locally on your device.


Eg: Google Docs (It perform calculations and computational related stuff using local resources but data is stored in database).

Database Architecture (Tier 1, Tier 2, Tier 3)

There are Mainly three types of Database architectures

Tier 1 Architecture

This is the most simplest of all the database, server and client all reside at a same machine.




Single Tier Architecture

These could be installed and run on a single machine without any external resources.

Eg: when we install an SQL database to practice SQL queries.

Tier 2 Architecture

In this architecture the presentation layer runs on client side while database resides at an external resource.




It has better security and scalability scope as compared to Tier 1. Here logic can reside either on client side or side depending on service.

Tier 3 Architecture


A three tier architecture is most scalable among the three. It has three layers

- Presentation Layer (PC, Tablet or any sort of UI Screen)
- Application layer (server)
- Database Server



Here Logic resides at server side and data is stored at database. This architecture can integrate data from different resources

In some cases even Tier 3 architecture isn't sufficient so load balance, caching layer, etc are introduced



How Internet Works ?

What Happens when you hit a web address into web Browser

- Firstly the web address is converted into an IP using DNS lookup then your browser look up in local browser cache if it didn't find a copy in browser's cache then it will look up at OS cache.
- If it didn't finds a cached version then it will look up at ISP. If its not present even there then it will give recursive calls to several other bigger ISPs and then lastly it will call TLD (Top Level Domain).
- Once the IP address if found then client sends a HTTP request to server to send a copy of website using TCP/IP.
- The Server then respond with a "200" response code. and send contents of website in packets to client.

Request Methods

<div><div>Aa</div>Method</div>	<div><div>≡</div>Description</div>
Untitled	
GET	Used to get contents from server Eg: playing a new unloaded YouTube Video
PUT	Replaces an existing target with a new value Eg: Changing password
DELETE	Removes an existing target Eg: Delete a tweet or a Instagram post
POST	Used to send data to server Eg: Submit button in google forms

HTTP Response Codes

<div><div>Aa</div>Response Code</div>	<div><div>≡</div>Description</div>
Untitled	
1XX	Request is still in progress
2XX	OK
3XX	Redirect, Request to some other server
4XX	Request Invalid (Client Side Issue)
5XX	Server Side Issue (Server Down etc)

HTTP Status Codes		
Level 200 (Success) 200 : OK 201 : Created 203 : Non-Authoritative Information 204 : No Content	Level 400 400 : Bad Request 401 : Unauthorized 403 : Forbidden 404 : Not Found 409 : Conflict	Level 500 500 : Internal Server Error 503 : Service Unavailable 501 : Not Implemented 504 : Gateway Timeout 599 : Network timeout 502 : Bad Gateway

Author: Uzair Ali