

Formal Languages and Computational Models

Programming Languages



CS 214



Turing Machines


In _____ (years before the first programmable computer),
_____ created a model for the process of computation
known today as the _____, consisting of:

- An *I/O tape* consisting of an arbitrary number of *cells*, each able to store an arbitrary symbol;
- A *tape head* able to read/write a cell; and
- A *finite-state control* that governs movement of the head over the cells.





Turing Machines (ii)

Each “execution cycle”, a TM _____ a *symbol* from the tape.



Depending on that *symbol* and its current state, it may then:

- _____;
- _____; and
- _____.



The finite state controller starts in state 0: the _____, and continues execution until it enters an _____, at which point it halts and its I/O tape contains the result of the computation.



Example: TM Addition

To add two numbers m and n :

- Precond: I/O tape contains m ones, a zero, and n ones.
- Postcond: I/O tape contains $m+n$ ones.


Our finite state controller uses these states and rules:

- State 0: If *symbol* is 1 or blank: move head right; goto State 0.
If *symbol* is 0: goto State 1
- State 1: Write 1; move head right; goto State 2.
- State 2: If *symbol* is 1: move head right; goto State 2.
If *symbol* is blank: move head left; goto State 3
- State 3: Write blank; goto State 4.
- State 4: Accept.




Example: $3 + 2$

To compute $3 + 2$, we start with:



Step	State _i	Read	Write	Move	State _i
------	--------------------	------	-------	------	--------------------

1	0	1	_____	_____	_____
2	0	1	_____	_____	_____
3	0	1	_____	_____	_____
4	0	0	_____	_____	_____
5	1	-	_____	_____	_____
6	2	1	_____	_____	_____
7	2	1	_____	_____	_____
8	2	blank	_____	_____	_____
9	3	-	_____	_____	_____
10	4	-	_____	_____	_____



TMs and Computability

In 1931, _____ proved that there exist easily-described functions that cannot be computed.

In 1936, _____ proved that a TM can be built for any computable function.

He later proved that a _____ can be built that can perform the task of any single-function TM, implying:

- Since it is independent of any particular hardware details, a proof about a UTM applies to every computer that will ever be built!
- If a function f can be computed, then a UTM can compute f .
- If a UTM cannot compute a function g ,
then _____.

Turing proved the _____ cannot be solved by a UTM.




The Chomsky Hierarchy

In 1956, _____ classified languages as follows:

<u>Level</u>	<u>Language</u>	<u>Recognizer</u>
_____	_____ (REs)	_____ (FSM)
_____	_____ (CFLs)	_____ (PDA)
_____	_____ (CSLs)	_____ (LBA)
_____	_____ (ULs)	_____ (TM)

Chomsky's categories form a *hierarchy*, organized by their power of expression (language) and power of recognition (automaton):



Chomsky and BNFs

The *Chomsky Hierarchy* specifies that:

- A _____ can recognize any language able to be recognized.
- A _____ can recognize CSLs, CFLs, & REs but not ULs.
- A _____ can recognize CFLs & REs but not CSLs or ULs.
- A _____ can recognize REs but not CFLs, CSLs or ULs.

The BNF is a tool for specifying _____ syntax.

- Programming language syntax is relatively “easy”, linguistically.

It can also be used to specify RE syntax

(but doing so is overkill -- simpler tools are available).

Different tools are needed to specify CFL and/or UL syntax.



PDAs and (BNF) Parsing

A PDA is a FSM with a _____ on which it can save things...

Recall our basic parsing algorithm (for BNFs):

0. Push S (the starting symbol) onto a stack.
 1. Get the first terminal symbol t from the input file.
 2. Repeat the following steps:
 - a. Pop the stack into *topSymbol*;
 - b. If *topSymbol* is a nonterminal:
 - 1) Choose a production p of *topSymbol* based on t
 - 2) If $p \neq \epsilon$:
Push p right-to-left onto the stack.
 - c. Else if *topSymbol* is a terminal && *topSymbol* == t :
Get the next terminal symbol t from the input file.
 - d. Else
Generate a 'parse error' message.
- while the stack is not empty.

A FSM cannot parse a CFL/ BNF because it has _____.



The Random Access Machine (RAM)

Proving things about TMs was a bit clumsy...

1963: *Shepherdson and Sturgis* devise the RAM as a model that is equivalent to a TM but more convenient to use:

The RAM has four components

- *A memory*: an integer array, indexed from zero.
- *A program*: a sequence of numbered instructions.
- *An input file*.
- *An output file*.

Shepherdson and Sturgis proved _____,
_____, and vice versa.



The RAM Instruction Set

- $M[i] = n$ → store n at index i
- $M[i] = M[j]$ → copy value at j to i
- $M[i] = M[j] + M[k]$ → add and store
- $M[i] = M[j] - M[k]$ → subtract and store
- $M[M[j]] = M[k]$ → indirection
- read $M[i]$ → input (destructive)
- write $M[i]$ → output
- goto s → unconditional branch
- if $M[i] \geq 0$ goto s → conditional branch
- halt → terminate execution

Later extensions added other operators (arithmetic, relational)


The result was quite similar to a _____.



Example 1

Here is a RAM for a computation...

What does it do (try some sample inputs)?



Example 2

Here is a different RAM. What does it compute?

program

```
1. M[0] = 64.  
2. M[1] = 91.  
3. M[2] = 32.  
4. read M[3].  
5. if M[3] >= 0 goto 7.  
6. goto 14.  
7. M[4] = M[0] - M[3].  
8. M[5] = M[3] - M[1].  
9. if M[4] >= 0 goto 12.  
10. if M[5] >= 0 goto 12.  
11. M[3] = M[3] + M[2].  
12. write M[3].  
13. goto 4.  
14. halt.
```

memory

[0]	
[1]	
[2]	
[3]	
[4]	
[5]	
...	

input

output



RAM Extensions

Like a TM, a RAM can compute anything that is computable.

With these simple extensions:

- _____ instead of memory locations
- _____ and _____ operators
- other _____ ($==$, $!=$, $<$, $>$, $>=$) operators
- _____ within arithmetic expressions

it becomes a convenient tool for studying HLL constructs, as a “portable assembly language” to study how a compiler can translate HLL constructs.



RAM Extension Examples

Example 1 program

```
1. read val.  
2. if val >= 0 goto 4.  
3. val = 0 - val.  
4. write val.  
5. halt.
```

Example 2 program

```
1. read ch.  
2. if ch < 0 goto 10.  
3. lo = ch - 65.  
4. hi = ch - 90  
5. if lo < 0 goto 8.  
6. if hi > 0 goto 8.  
7. ch = ch + 32.  
8. write ch.  
9. goto 1.  
10. halt.
```

Even with the improvements, such programs are hard to read because of their coding style (aka _____)...



Summary

The _____ names four “levels” of language, plus the weakest machine able to recognize at each level:

3 Regular Expressions	→ Finite State Machine
2 Context Free Languages	→ Pushdown Automata
1 Context Sensitive Languages	→ Linear Bounded Automata
0 Unrestricted Languages	→ Turing Machine

The _____ is the most powerful of the machines, able to

- recognize any language capable of being recognized.
- compute any function capable of being computed.

The _____ is a computational model that is

- as powerful as the TM
- more convenient than the TM for studying HLL constructs.

