

# Visualization of relativistic phenomena

Zoltán Simon

---

## Abstract

*Special relativity describes many phenomena, not observable in everyday life. This article presents an educational application, which helps to understand these effects. It models vision of objects travelling close to the speed of light. It visualizes length contraction, time dilatation, relativistic Doppler effect and more. It considers the path of light between the object and our eye, but it also presents an opportunity to visualize events happening simultaneously as well. It allows to switch between Lorentz and Galilean transformation, so we can compare Einstein's and Newton's model. It serves with a three-dimensional space-time diagram, on which we have a chance to further analyse the movement of objects.*

Categories and Subject Descriptors (according to ACM CCS): I.3.3 [Computer Graphics]: Visualization of relativistic phenomena

---

## 1. Introduction

Theory of relativity is a key part of modern physics. There are many use cases of this theory. Despite of it's importance there is very little chance for people to experience relativistic phenomena in their everyday life, thus differences between Isaac Newton's classical and Albert Einstein's modern model remain unexplored. The application described in this article offers a way to visualise the most well-known phenomena associated with special relativity. The goal of this article is to showcase the algorithmic challenges surrounding this program and introduce solutions for these problems.

## 2. Previous Work

This article is a direct follow up of the work <sup>1</sup>. It explains previously neglected details, e.g. implementation of Wigner-rotation.

## 3. Our proposal in detail

### 4. Implementation of physical models

The rules of simulation are based on Einstein's postulates <sup>2</sup>. These suggest that

- an observer can not differentiate between different inertial frames of reference by taking measurements in each frame of reference.
- the velocity of propagation of any physical effect can not exceed the speed of light in vacuum:  $c = 299792458 \frac{m}{s} \sim 3 \cdot 10^8 \frac{m}{s}$ .

These two constraints do not provide sufficient tools for the programmer on their own. However, all the required formulas can be derived from these two postulates.

### 4.1. Usage of the term „absolute frame”

To simplify representation of world lines every event and velocity is described in the same frame of reference. In code this frame of reference is called absolute frame. This helps circumvent confusion when transforming between different observer's proper frames. Each value is stored as it is measured in absolute frame. When visualising a given value, than it gets transformed to a particular observers proper frame.

### 4.2. Representation of physical bodies

To model the journey of physical objects through space-time, it is convenient to assign a world line to each object. To be more precise, this is going to be the world line of the object's origin. For practical purposes this origin point is selected to be the same as the origin point in model space. Such world line can be stored as a set of events. Between the events we assume geodetic world lines. At this point it is necessary to note, that we also assume flat space-time. This method allows us to represent world lines consisting of few geodetic sections easily. World lines of accelerating objects appear curved in space-time diagrams. We can approximate these lines by a set of short geodetic sections. This approximation is useful, because along the small sections we can use

the simple formulas of Lorentz transformation. The downside of this method is, that many calculations require iteration over the small sections. E. g. determining the age of an object without a priori information requires summing of ageing of the object along the geodetic sections. The other obvious downside of such approximation is, that the resulting world line is going to have low resolution. This is particularly noticeable, when we –as a viewer– place ourselves in the proper frame of such accelerating object. In this case the violent jumping nature of the movement of surroundings is much more noticeable.

## 5. View modes

The application supports multiple view modes. The two main modes are the real time three dimensional view and the diagram view. In the real time mode the scene is shown as regular three dimensional scene, changing over time. We can look around with the virtual camera to observe the moving objects. The objects appear

## 6. Digitising Errors

Like most cartographic algorithms, the Douglas–Peucker algorithm does not fully address the issue of digitising errors. When estimating truth values, it is usually assumed that the true line (in this case the analogue line) lies within the error band of the digitised line. This band is also known as the Perkal epsilon band. In his review on issues relating to the accuracy of spatial databases, Goodchild<sup>8</sup> indicated that researchers have proposed uniform, normal and even bimodal distributions of error across this band. This concept provides some basis for estimating the position of the true line at locations between digitised points. Here, we are merely concerned with the accuracy of digitised points. Whilst it is probable that operators digitise points along high curvatures more carefully than at intermediate positions, there is at present no sound basis for modelling the distribution of error along the line. As in the Circular Map Accuracy Standard, it is usual to assume a bivariate normal distribution of error when estimating the position of the true point. In the context of line simplification, absolute positional accuracy is less important than the relative position of points describing the shape of features along the line.

The DoE/SDD boundary data contain some gross digitising errors. For example, inlet X in Figure 2c does not feature on conventional Ordnance Survey 1:50 000 maps of the area. The data are also not very accurate where coastlines are convoluted. Even if we ignore these and other gross errors, such as spikes, there will always be an element of random error in digitised data. It is reasonable to assume that points digitised from 1:50 000 source material may only be accurate to within  $\pm 5$  metres. This algorithm does not lead to a substantial accumulation of rounding errors, hence the numerical errors discussed earlier tend to be very small compared with digitising errors.

For the purposes of our argument, it is unnecessary to undertake an exhaustive evaluation of the consequences Douglas and Peucker have treated overhangs and closed loops as different problems, and have used different methods to cope with each case.

## 6.1. Numerical Problems

The FORTRAN programs by Douglas, White, and Wade use single precision REALS when computing offsets (see results in Table 1). Whilst double precision accuracy may be attained through the use of compiler options, we are unsure whether previous research has been based on programs compiled in this manner. Wade's program was so compiled for use in our previous evaluations. Forrest stated that Ramshaw (1982) had to adopt carefully tuned double and single precision floating point arithmetic to compute the intersection of line segments whose end points were defined as integers. Forrest exclaimed "This is an object lesson to us all: constructing geometric objects defined on a grid of points, requiring ten bits for representation can lead to double precision floating point arithmetic!".

Most evaluative studies do not cite the co-ordinates in use. We do not know whether the published test lines were in original digitiser co-ordinates or whether they had been converted to geographic references. British National Grid co-ordinates for the administrative boundaries of England, Scotland and Wales (digitised by the Department of Environment (DoE) and Scottish Development Department (SDD)) are input to one metre accuracy and require seven decimal digits for representation if we include the northern islands of Scotland. At the South West Universities Regional Computer Centre these co-ordinates have been rounded to 10 metre resolution; even this requires six decimal digits. Seamless cartographic files at continental and global scales use much larger ranges of geographic co-ordinates.

A limited number of papers actually described improved for new algorithms or methods for visualization<sup>8, 9, 10</sup>. This may be caused by the complexity of the environment in which a method is used; issues of system architecture, user interface, data handling, etc. must be dealt with before a new presentation technique can show its full advantage. But even so, we think the field can use more contributions of this type.

There was also a discussion session on the merits of animation and special effects (such as sound) to support visualization. For example, in the area of flow visualization, it is quite common to use animation, and techniques for video registration have been developed.

## 7. Issues in Visualization

Scientific visualization is an interdisciplinary field, which can only flourish when computer graphics experts cooperate with specialists from application areas, and providers



3. Albert Einstein. *Relativity: The Special and General Theory*. Henry Holt and company, 1920.
4. Y. Le Lous, “Report on the First Eurographics Workshop on Visualization in Scientific Computing”, *Computer Graphics Forum* **9**(4), pp. 371–372 (December 1990).
5. J. Foley, A. van Dam, S. Feiner, J. Hugues, and R. Phillips. *Introduction to Computer Graphics*. Addison Wesley, 1993.
6. K.Ch. Posch and D.W. Fellner. The Circle-Brush Algorithm. *Transactions on Graphics*, **18**(1):1–24, 1989.
7. T.A. Foley, H. Hagen, and G.M. Nielson. Visualizing and modeling unstructured data. *The Visual Computer*, (9):439–449, 1993.
8. M. Levoy. Efficient ray tracing of volume data. *ACM Transactions on Graphics*, **9**(3):245–261, July 1990.
9. T. Porter and T. Duff. Compositing digital images. *ACM Computer Graphics (Proc. of SIGGRAPH '84)*, **18**:253–259, 1984.
10. R. Ronfard and J. Rossignac. Full-range approximation of triangulated polyhedra. *Computer Graphics Forum (Eurographics'96 Proc.)*, **15**(3):67–76, 1996.