PY0101EN-2-3-Sets

July 8, 2021

1 Sets in Python

Estimated time needed: **20** minutes

1.1 Objectives

After completing this lab you will be able to:

- Work with sets in Python, including operations and logic operations.

Table of Contents

```
<ul>
    <li>
        <a href="#set">Sets</a>
        <ul>
            <li><a href="content">Set Content</a></li>
            <li><a href="op">Set Operations</a></li>
            <li><a href="logic">Sets Logic Operations</a></li>
        </ul>
    </li>
    <li>
        <a href="#quiz">Quiz on Sets</a>
    </li>
</ul>
```

Sets

Set Content

A set is a unique collection of objects in Python. You can denote a set with a pair of curly brackets {}. Python will automatically remove duplicate items:

```
[ ]: # Create a set

set1 = {"pop", "rock", "soul", "hard rock", "rock", "R&B", "rock", "disco"}
set1
```

The process of mapping is illustrated in the figure:

You can also create a set from a list as follows:

```
[5]:  # Convert list to set

      album_list = [ "Michael Jackson", "Thriller", 1982, "00:42:19", \
                     "Pop, Rock, R&B", 46.0, 65, "30-Nov-82", None, 10.0]
      album_set = set(album_list)
      album_set
```

```
[5]:  {'00:42:19',
       10.0,
       1982,
       '30-Nov-82',
       46.0,
       65,
       'Michael Jackson',
       None,
       'Pop, Rock, R&B',
       'Thriller'}
```

Now let us create a set of genres:

```
[ ]:  # Convert list to set

      music_genres = set(["pop", "pop", "rock", "folk rock", "hard rock", "soul", \
                          "progressive rock", "soft rock", "R&B", "disco"])
      music_genres
```

Set Operations

Let us go over set operations, as these can be used to change the set. Consider the set A:

```
[6]:  # Sample set

      A = set(["Thriller", "Back in Black", "AC/DC"])
      A
```

```
[6]:  {'AC/DC', 'Back in Black', 'Thriller'}
```

We can add an element to a set using the add() method:

```
[9]:  # Add element to set

      A.add("NSYNC")
      A
```

```
[9]:  {'AC/DC', 'ASYNC', 'Back in Black', 'NSYNC', 'Thriller'}
```

If we add the same element twice, nothing will happen as there can be no duplicates in a set:

```
[ ]: # Try to add duplicate element to the set

     A.add("NSYNC")
     A
```

We can remove an item from a set using the remove method:

```
[ ]: # Remove the element from set

     A.remove("NSYNC")
     A
```

We can verify if an element is in the set using the in command:

```
[34]: # Verify if the element is in the set

      # "AC/DC" in A
      '1' in {'1', '2'}
```

```
[34]: True
```

Sets Logic Operations

Remember that with sets you can check the difference between sets, as well as the symmetric difference, intersection, and union:

Consider the following two sets:

```
[11]: # Sample Sets

      album_set1 = set(["Thriller", 'AC/DC', 'Back in Black'])
      album_set2 = set([ "AC/DC", "Back in Black", "The Dark Side of the Moon"])
```

```
[12]: # Print two sets

      album_set1, album_set2
```

```
[12]: ({'AC/DC', 'Back in Black', 'Thriller'},
       {'AC/DC', 'Back in Black', 'The Dark Side of the Moon'})
```

As both sets contain AC/DC and Back in Black we represent these common elements with the intersection of two circles.

You can find the intersect of two sets as follow using &:

```
[13]: # Find the intersections

      intersection = album_set1 & album_set2
      intersection
```

[13]: {'AC/DC', 'Back in Black'}

You can find all the elements that are only contained in album_set1 using the difference method:

```
[14]: # Find the difference in set1 but not set2

      album_set1.difference(album_set2)
```

[14]: {'Thriller'}

You only need to consider elements in album_set1; all the elements in album_set2, including the intersection, are not included.

The elements in album_set2 but not in album_set1 is given by:

```
[15]: album_set2.difference(album_set1)
```

[15]: {'The Dark Side of the Moon'}

You can also find the intersection of album_list1 and album_list2, using the intersection method:

```
[16]: # Use intersection method to find the intersection of album_list1 and␣
      ↪album_list2

      album_set1.intersection(album_set2)
```

[16]: {'AC/DC', 'Back in Black'}

This corresponds to the intersection of the two circles:

The union corresponds to all the elements in both sets, which is represented by coloring both circles:

The union is given by:

```
[17]: # Find the union of two sets

      album_set1.union(album_set2)
```

[17]: {'AC/DC', 'Back in Black', 'The Dark Side of the Moon', 'Thriller'}

And you can check if a set is a superset or subset of another set, respectively, like this:

```
[ ]: # Check if superset

     set(album_set1).issuperset(album_set2)
```

```
[ ]: # Check if subset

     set(album_set2).issubset(album_set1)
```

Here is an example where issubset() and issuperset() return true:

```
[ ]: # Check if subset

     set({"Back in Black", "AC/DC"}).issubset(album_set1)
```

```
[ ]: # Check if superset

     album_set1.issuperset({"Back in Black", "AC/DC"})
```

Quiz on Sets

Convert the list ['rap','house','electronic music', 'rap'] to a set:

```
[18]: # Write your code below and press Shift+Enter to execute
      a_list = ['rap','house','electronic music', 'rap']
      a_set  = set(a_list)
      a_set
```

```
[18]: {'electronic music', 'house', 'rap'}
```

Click here for the solution

```
set(['rap','house','electronic music','rap'])
```

Consider the list $A = [1, 2, 2, 1]$ and set $B = set([1, 2, 2, 1])$, does $sum(A) == sum(B)$?

```
[27]: # Write your code below and press Shift+Enter to execute
      A = [1, 2, 2, 1]
      B = set([1, 2, 2, 1])
      print("Sum of A is: ",sum(A))
      print("Sum of B is: ",sum(B))
```

```
Sum of A is:  6
Sum of B is:  3
```

Click here for the solution

```
A = [1, 2, 2, 1]
B = set([1, 2, 2, 1])
print("the sum of A is:", sum(A))
print("the sum of B is:", sum(B))
```

Create a new set album_set3 that is the union of album_set1 and album_set2:

```
[32]: # Write your code below and press Shift+Enter to execute

      album_set1 = set(["Thriller", 'AC/DC', 'Back in Black'])
      album_set2 = set([ "AC/DC", "Back in Black", "The Dark Side of the Moon"])
      album_set3 = album_set1.union(album_set2)
      print(album_set3)
```

```
{'Back in Black', 'Thriller', 'The Dark Side of the Moon', 'AC/DC'}
```

Click here for the solution

```
album_set3 = album_set1.union(album_set2)
album_set3
```

Find out if album_set1 is a subset of album_set3:

[31]:
```python
# Write your code below and press Shift+Enter to execute
set(album_set1).issubset(album_set3)
```

[31]: True

Click here for the solution

```
album_set1.issubset(album_set3)
```

The last exercise!

Congratulations, you have completed your first lesson and hands-on lab in Python. However, there is one more thing you need to do. The Data Science community encourages sharing work. The best way to share and showcase your work is to share it on GitHub. By sharing your notebook on GitHub you are not only building your reputation with fellow data scientists, but you can also show it off when applying for a job. Even though this was your first piece of work, it is never too early to start building good habits. So, please read and follow this article to learn how to share your work.

1.2 Author

Joseph Santarcangelo

1.3 Other contributors

Mavis Zhou

1.4 Change Log

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2020-08-26	2.0	Lavanya	Moved lab to course repo in GitLab

##