
HPX Documentation

2.0.0

The STE || AR Group

August 16, 2026

USER DOCUMENTATION

Welcome to the *HPX* documentation!

If you're new to *HPX* you can get started with the *Quick start* guide. Don't forget to read the *Terminology* section to learn about the most important concepts in *HPX*. The *Examples* give you a feel for how it is to write real *HPX* applications and the *Manual* contains detailed information about everything from building *HPX* to debugging it. There are links to blog posts and videos about *HPX* in *Additional material*.

You can find a comprehensive list of contact options on [Support for deploying and using HPX¹](#). Do not hesitate to contact us if you can't find what you are looking for in the documentation!

See *Citing HPX* for details on how to cite *HPX* in publications. See *HPX users* for a list of institutions and projects using *HPX*.

There are also available a [PDF](#) version of this documentation as well as a [Single HTML Page](#).

¹ <https://github.com/TheHPXProject/hpx/blob/master/.github/SUPPORT.md>

WHAT IS *HPX*?

HPX is a C++ Standard Library for Concurrency and Parallelism. It implements all of the corresponding facilities as defined by the C++ Standard. Additionally, in *HPX* we implement functionalities proposed as part of the ongoing C++ standardization process. We also extend the C++ Standard APIs to the distributed case. *HPX* is developed by the STE||AR group (see *People*).

The goal of *HPX* is to create a high quality, freely available, open source implementation of a new programming model for conventional systems, such as classic Linux based Beowulf clusters or multi-socket highly parallel SMP nodes. At the same time, we want to have a very modular and well designed runtime system architecture which would allow us to port our implementation onto new computer system architectures. We want to use real-world applications to drive the development of the runtime system, coining out required functionalities and converging onto a stable API which will provide a smooth migration path for developers.

The API exposed by *HPX* is not only modeled after the interfaces defined by the C++11/14/17/20 ISO standard. It also adheres to the programming guidelines used by the Boost collection of C++ libraries. We aim to improve the scalability of today's applications and to expose new levels of parallelism which are necessary to take advantage of the exascale systems of the future.

HPX is a member of the High-Performance Software Foundation ([HPSF](https://hpsf.io)²) network, which signals its commitment to the open-source, high-performance computing (HPC) community. By joining [HPSF](https://hpsf.io)³ - and, concurrently, the Linux Foundation - *HPX* gains access to a broader collaborative ecosystem that promotes shared standards, interoperable tools, and joint research initiatives, all of which accelerates the development of scalable parallel applications. This dual affiliation enhances *HPX*'s credibility, attracting contributors and industry partners who value the rigorous governance and transparent development practices upheld by both organizations. Consequently, *HPX* can more effectively influence the direction of future HPC frameworks while benefiting from the collective expertise, resources, and industry backing provided by [HPSF](https://hpsf.io)⁴ and the Linux Foundation.

² <https://hpsf.io/projects/hpx/>

³ <https://hpsf.io/projects/hpx/>

⁴ <https://hpsf.io/projects/hpx/>

WHAT'S SO SPECIAL ABOUT *HPX*?

- *HPX* exposes a uniform, standards-oriented API for ease of programming parallel and distributed applications.
- It enables programmers to write fully asynchronous code using hundreds of millions of threads.
- *HPX* provides unified syntax and semantics for local and remote operations.
- *HPX* makes concurrency manageable with dataflow and future based synchronization.
- It implements a rich set of runtime services supporting a broad range of use cases.
- *HPX* exposes a uniform, flexible, and extendable performance counter framework which can enable runtime adaptivity
- It is designed to solve problems conventionally considered to be scaling-impaired.
- *HPX* has been designed and developed for systems of any scale, from hand-held devices to very large scale systems.
- It is the first fully functional implementation of the ParalleX execution model.
- *HPX* is published under a liberal open-source license and has an open, active, and thriving developer community.

2.1 Quick start

The following steps will help you get started with *HPX*. Before getting started, make sure you have all the necessary prerequisites, which are listed in `_prerequisites`. After *Installing HPX*, you can check how to run a simple example *Hello, World!*. *Writing task-based applications* explains how you can get started with *HPX*. You can refer to our *Migration guide* if you use other APIs for parallelism (like OpenMP, MPI or Intel Threading Building Blocks (TBB)) and you would like to convert your code to *HPX* code.

2.1.1 Installing *HPX*

The easiest way to install *HPX* on your system is by choosing one of the steps below:

1. **vcpkg**

You can download and install *HPX* using the `vcpkg`⁵ dependency manager:

```
$ vcpkg install hpx
```

2. **Spack**

Another way to install *HPX* is using `Spack`⁶:

⁵ <https://github.com/Microsoft/vcpkg>

⁶ <https://spack.readthedocs.io/en/latest/>

```
$ spack install hpx
```

3. Conan

You can also use the [Conan](https://conan.io/)⁷ package manager to build and use *HPX* in your projects. First, export the *HPX* recipe from the *HPX* repository to your local Conan cache:

```
$ git clone https://github.com/TheHPXProject/hpx.git
$ cd hpx
$ conan create . --build=missing
```

This builds *HPX* and makes it available in your local Conan cache. You can then use it in your Conan-based projects by adding it to your `conanfile.txt`:

```
[requires]
hpx/2.0.0

[generators]
CMakeDeps
CMakeToolchain
```

Then use `find_package(HPX REQUIRED)` in your `CMakeLists.txt` as usual. Conan will automatically handle building *HPX* with your chosen configuration options and provide the necessary CMake integration files.

4. Fedora

Installation can be done with [Fedora](https://fedoraproject.org/wiki/DNF)⁸ as well:

```
$ dnf install hpx*
```

5. Arch Linux

HPX is available in the [Arch User Repository \(AUR\)](https://wiki.archlinux.org/title/Arch_User_Repository)⁹ as `hpx` too.

More information or alternatives regarding the installation can be found in the *Building HPX*, a detailed guide with thorough explanation of ways to build and use *HPX*.

2.1.2 Hello, World!

To get started with this minimal example you need to create a new project directory and a file `CMakeLists.txt` with the contents below in order to build an executable using [CMake](https://www.cmake.org/)¹⁰ and *HPX*:

```
cmake_minimum_required(VERSION 3.19)
project(my_hpx_project CXX)
find_package(HPX REQUIRED)
add_executable(my_hpx_program main.cpp)
target_link_libraries(my_hpx_program HPX::hpx HPX::wrap_main hpx::iostreams_component)
```

The next step is to create a `main.cpp` with the contents below:

⁷ <https://conan.io/>

⁸ <https://fedoraproject.org/wiki/DNF>

⁹ https://wiki.archlinux.org/title/Arch_User_Repository

¹⁰ <https://www.cmake.org>

```
// Including 'hpx/hpx_main.hpp' instead of the usual 'hpx/hpx_init.hpp' enables
// to use the plain C-main below as the direct main HPX entry point.
#include <hpx/hpx_main.hpp>
#include <hpx/iostream.hpp>

int main()
{
    // Say hello to the world!
    hpx::cout << "Hello World!\n" << std::flush;
    return 0;
}
```

Then, in your project directory run the following:

```
$ mkdir build && cd build
$ cmake -DHPX_DIR=</path/to/hpx/installation> ..
$ make all
$ ./my_hpx_program
```

```
$ ./my_hpx_program
Hello World!
```

The program looks almost like a regular C++ hello world with the exception of the two includes and `hpx::cout`.

- When you include `hpx_main.hpp` *HPX* makes sure that `main` actually gets launched on the *HPX* runtime. So while it looks almost the same you can now use futures, `async`, parallel algorithms and more which make use of the *HPX* runtime with lightweight threads.
- `hpx::cout` is a replacement for `std::cout` to make sure printing never blocks a lightweight thread. You can read more about `hpx::cout` in *The HPX I/O-streams component*.

Note:

- You will most likely have more than one `main.cpp` file in your project. See the section on *Using HPX with CMake-based projects* for more details on how to use `add_hpx_executable`.
- `HPX::wrap_main` is required if you are implicitly using `main()` as the runtime entry point. See *Re-use the main() function as the main HPX entry point* for more information.
- `hpx::iostreams_component` is optional for a minimal project but lets us use the *HPX* equivalent of `std::cout`, i.e., the *HPX The HPX I/O-streams component* functionality in our application.
- You do not have to let *HPX* take over your main function like in the example. See *Starting the HPX runtime* for more details on how to initialize and run the *HPX* runtime.

Caution: Ensure that *HPX* is installed with `HPX_WITH_DISTRIBUTED_RUNTIME=ON` to prevent encountering an error indicating that the `HPX::iostreams_component` target is not found.

When including `hpx_main.hpp` the user-defined `main` gets renamed and the real `main` function is defined by *HPX*. This means that the user-defined `main` must include a return statement, unlike the real `main`. If you do not include the return statement, you may end up with confusing compile time errors mentioning `user_main` or even runtime errors.

2.1.3 Writing task-based applications

So far we haven't done anything that can't be done using the C++ standard library. In this section we will give a short overview of what you can do with *HPX* on a single node. The essence is to avoid global synchronization and break up your application into small, composable tasks whose dependencies control the flow of your application. Remember, however, that *HPX* allows you to write distributed applications similarly to how you would write applications for a single node (see *Why HPX?* and *Writing distributed applications*).

If you are already familiar with `async` and `future` from the C++ standard library, the same functionality is available in *HPX*.

The following terminology is essential when talking about task-based C++ programs:

- **lightweight thread**: Essential for good performance with task-based programs. Lightweight refers to smaller stacks and faster context switching compared to OS threads. Smaller overheads allow the program to be broken up into smaller tasks, which in turns helps the runtime fully utilize all processing units.
- **async**: The most basic way of launching tasks asynchronously. Returns a `future<T>`.
- **future<T>**: Represents a value of type `T` that will be ready in the future. The value can be retrieved with `get` (blocking) and one can check if the value is ready with `is_ready` (non-blocking).
- **shared_future<T>**: Same as `future<T>` but can be copied (similar to `std::unique_ptr` vs `std::shared_ptr`).
- **continuation**: A function that is to be run after a previous task has run (represented by a future). `then` is a method of `future<T>` that takes a function to run next. Used to build up dataflow DAGs (directed acyclic graphs). `shared_futures` help you split up nodes in the DAG and functions like `when_all` help you join nodes in the DAG.

The following example is a collection of the most commonly used functionality in *HPX*:

```
#include <hpx/algorithm.hpp>
#include <hpx/future.hpp>
#include <hpx/init.hpp>

#include <iostream>
#include <random>
#include <vector>

void final_task(hpx::future<hpx::tuple<hpx::future<double>, hpx::future<void>>>>)
{
    std::cout << "in final_task" << std::endl;
}

int hpx_main()
{
    // A function can be launched asynchronously. The program will not block
    // here until the result is available.
    hpx::future<int> f = hpx::async([]() { return 42; });
    std::cout << "Just launched a task!" << std::endl;

    // Use get to retrieve the value from the future. This will block this task
    // until the future is ready, but the HPX runtime will schedule other tasks
    // if there are tasks available.
    std::cout << "f contains " << f.get() << std::endl;
}
```

(continues on next page)

(continued from previous page)

```

// Let's launch another task.
hpx::future<double> g = hpx::async([]() { return 3.14; });

// Tasks can be chained using the then method. The continuation takes the
// future as an argument.
hpx::future<double> result = g.then([](hpx::future<double>&& gg) {
    // This function will be called once g is ready. gg is g moved
    // into the continuation.
    return gg.get() * 42.0 * 42.0;
});

// You can check if a future is ready with the is_ready method.
std::cout << "Result is ready? " << result.is_ready() << std::endl;

// You can launch other work in the meantime. Let's sort a vector.
std::vector<int> v(1000000);

// We fill the vector synchronously and sequentially.
hpx::generate(hpx::execution::seq, std::begin(v), std::end(v), &std::rand);

// We can launch the sort in parallel and asynchronously.
hpx::future<void> done_sorting =
    hpx::sort(hpx::execution::par(           // In parallel.
              hpx::execution::task),        // Asynchronously.
              std::begin(v), std::end(v));

// We launch the final task when the vector has been sorted and result is
// ready using when_all.
auto all = hpx::when_all(result, done_sorting).then(&final_task);

// We can wait for all to be ready.
all.wait();

// all must be ready at this point because we waited for it to be ready.
std::cout << (all.is_ready() ? "all is ready!" : "all is not ready...")
          << std::endl;

return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}

```

Try copying the contents to your `main.cpp` file and look at the output. It can be a good idea to go through the program step by step with a debugger. You can also try changing the types or adding new arguments to functions to make sure you can get the types to match. The type of the `then` method can be especially tricky to get right (the continuation needs to take the future as an argument).

Note: HPX programs accept command line arguments. The most important one is `--hpx:threads=N` to set the number of OS threads used by HPX. HPX uses one thread per core by default. Play around with the example above

and see what difference the number of threads makes on the `sort` function. See *Launching and configuring HPX applications* for more details on how and what options you can pass to *HPX*.

Tip: The example above used the construction `hpx::when_all(...).then(...)`. For convenience and performance it is a good idea to replace uses of `hpx::when_all(...).then(...)` with `dataflow`. See *Dataflow* for more details on `dataflow`.

Tip: If possible, try to use the provided parallel algorithms instead of writing your own implementation. This can save you time and the resulting program is often faster.

2.1.4 Next steps

If you haven't done so already, reading the *Terminology* section will help you get familiar with the terms used in *HPX*.

The *Examples* section contains small, self-contained walkthroughs of example *HPX* programs. The *Local to remote* example is a thorough, realistic example starting from a single node implementation and going stepwise to a distributed implementation.

The *Manual* contains detailed information on writing, building and running *HPX* applications.

2.2 Tutorials

This section provides structured, video-based learning resources for *HPX*. The tutorials complement the reference documentation with guided, example-driven explanations of core concepts and advanced features.

Each tutorial introduces the relevant concepts and then applies them step by step through practical code examples. The focus is on demonstrating how to design, implement, and reason about parallel and distributed applications using *HPX*. While the main documentation emphasizes API descriptions and detailed reference material, the tutorial series adopts a practical, code-oriented approach.

The tutorials are intended for a broad audience: from beginners setting up *HPX* for the first time to advanced users exploring performance tuning, custom executors, and SIMD vectorization. Together, they form a structured learning path that lowers the entry barrier while progressively introducing more advanced features.

The complete video series is available on YouTube:

[HPX Tutorial Playlist](#)¹¹

The code is available on Github:

HPX Tutorial Code <https://github.com/STELLAR-GROUP/HPX_Tutorials_Code>

¹¹ <https://www.youtube.com/watch?v=OZWTmrIWUF0&list=PL7vEgTL3FalZkvNqssEP9-tXQ5rEwZy2l&index=1>

2.2.1 Available Modules

- **Introduction to |hpx|**

Foundational overview of *HPX*, including its architecture, design principles, and key capabilities in the context of high-performance computing.

- **Building |hpx| on Windows/Unix**

Step-by-step guidance on installing *HPX* and setting up the environment based on your operating system.

- **Running |hpx| applications**

Demonstration on how to build and run a simple Hello World example using *HPX*.

- **Algorithms in |hpx|**

Overview of the parallel algorithms provided by *HPX* and explanation on how execution policies unlock high-performance C++ computing.

- **Vectorization and SIMD in |hpx|**

Introduction to data-parallel programming, SIMD execution policies, and vectorization techniques relevant to modern C++ and HPC workloads.

- **Futures and Asynchronous Programming**

Explanation of the asynchronous programming model in *HPX*, including futures, *async*, and dataflow-based execution patterns.

- **Performance Analysis and Optimization**

Guidance on profiling *HPX* applications, analyzing performance counters, identifying bottlenecks, and applying optimization strategies.

- **Task Scheduling and Custom Executors**

Detailed discussion of the execution model in *HPX*, built-in executors, and mechanisms for defining custom execution strategies.

- **Migration Guides**

Best practices and recommendations for transitioning from other HPC frameworks to *HPX*.

- **HPX in Practice**

Examples of open-source libraries and applications using *HPX*, illustrating real-world usage patterns and ecosystem integration.

2.3 Examples

The following sections analyze some examples to help you get familiar with the *HPX* style of programming. We start off with simple examples that utilize basic *HPX* elements and then begin to expose the reader to the more complex and powerful *HPX* concepts. Section *Building tests and examples* shows how you can build the examples.

2.3.1 Asynchronous execution

The Fibonacci sequence is a sequence of numbers starting with 0 and 1 where every subsequent number is the sum of the previous two numbers. In this example, we will use *HPX* to calculate the value of the *n*-th element of the Fibonacci sequence. In order to compute this problem in parallel, we will use a facility known as a future.

As shown in the Fig. ?? below, a future encapsulates a delayed computation. It acts as a proxy for a result initially not known, most of the time because the computation of the result has not completed yet. The future synchronizes the access of this value by optionally suspending any *HPX*-threads requesting the result until the value is available. When a future is created, it spawns a new *HPX*-thread (either remotely with a *parcel* or locally by placing it into the thread

queue) which, when run, will execute the function associated with the future. The arguments of the function are bound when the future is created.




Fig. 2.1: Schematic of a future execution.

Once the function has finished executing, a write operation is performed on the future. The write operation marks the future as completed, and optionally stores data returned by the function. When the result of the delayed computation is needed, a read operation is performed on the future. If the future's function hasn't completed when a read operation is performed on it, the reader *HPX*-thread is suspended until the future is ready. The future facility allows *HPX* to schedule work early in a program so that when the function value is needed it will already be calculated and available. We use this property in our Fibonacci example below to enable its parallel execution.

Setup

The source code for this example can be found here: `fibonacci_local.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.fibonacci_local
```

To run the program type:

```
$ ./bin/fibonacci_local
```

This should print (time should be approximate):

```
fibonacci(10) == 55
elapsed time: 0.002430 [s]
```

This run used the default settings, which calculate the tenth element of the Fibonacci sequence. To declare which Fibonacci value you want to calculate, use the `--n-value` option. Additionally you can use the `--hpx:threads` option to declare how many OS-threads you wish to use when running the program. For instance, running:


```
$ ./bin/fibonacci --n-value 20 --hpx:threads 4
```

Will yield:

```
fibonacci(20) == 6765
elapsed time: 0.062854 [s]
```

Walkthrough

Now that you have compiled and run the code, let's look at how the code works. Since this code is written in C++, we will begin with the `main()` function. Here you can see that in *HPX*, `main()` is only used to initialize the runtime system. It is important to note that application-specific command line options are defined here. *HPX* uses [Boost.Program_options](https://www.boost.org/doc/html/program_options.html)¹² for command line processing. You can see that our programs `--n-value` option is set by calling the `add_options()` method on an instance of `hpx::program_options::options_description`. The default value of the variable is set to 10. This is why when we ran the program for the first time without using the `--n-value` option the program returned the 10th value of the Fibonacci sequence. The constructor argument of the description is the text that appears when a user uses the `--hpx:help` option to see what command line options are available. `HPX_APPLICATION_STRING` is a macro that expands to a string constant containing the name of the *HPX* application currently being compiled.

In *HPX* `main()` is used to initialize the runtime system and pass the command line arguments to the program. If you wish to add command line options to your program you would add them here using the instance of the Boost class `options_description`, and invoking the public member function `.add_options()` (see [Boost Documentation](https://www.boost.org/doc/)¹³ for more details). `hpx::init` calls `hpx_main()` after setting up *HPX*, which is where the logic of our program is encoded.

```
int main(int argc, char* argv[])
{
    // Configure application-specific options
    hpx::program_options::options_description desc_commandline(
        "Usage: " HPX_APPLICATION_STRING " [options]");

    // clang-format off
    desc_commandline.add_options()
        ("n-value",
         hpx::program_options::value<std::uint64_t>()->default_value(10),
         "n value for the Fibonacci function")
        ;
    // clang-format on

    // Initialize and run HPX
    hpx::local::init_params init_args;
    init_args.desc_cmdline = desc_commandline;

    return hpx::local::init(hpx_main, argc, argv, init_args);
}
```

The `hpx::init` function in `main()` starts the runtime system, and invokes `hpx_main()` as the first *HPX*-thread. Below we can see that the basic program is simple. The command line option `--n-value` is read in, a timer (`hpx::chrono::high_resolution_timer`) is set up to record the time it takes to do the computation, the `fibonacci` function is invoked synchronously, and the answer is printed out.

¹² https://www.boost.org/doc/html/program_options.html

¹³ <https://www.boost.org/doc/>

```

int hpx_main(hpx::program_options::variables_map& vm)
{
    hpx::threads::add_scheduler_mode(
        hpx::threads::policies::scheduler_mode::fast_idle_mode);

    // extract command line argument, i.e. fib(N)
    std::uint64_t n = vm["n-value"].as<std::uint64_t>();

    {
        // Keep track of the time required to execute.
        hpx::chrono::high_resolution_timer t;

        std::uint64_t r = fibonacci(n);

        char const* fmt = "fibonacci({1}) == {2}\\nelapsed time: {3} [s]\\n";
        hpx::util::format_to(std::cout, fmt, n, r, t.elapsed());
    }

    return hpx::local::finalize();    // Handles HPX shutdown
}

```

The `fibonacci` function itself is synchronous as the work done inside is asynchronous. To understand what is happening we have to look inside the `fibonacci` function:

```

std::uint64_t fibonacci(std::uint64_t n)
{
    if (n < 2)
        return n;

    hpx::future<std::uint64_t> n1 = hpx::async(fibonacci, n - 1);
    std::uint64_t n2 = fibonacci(n - 2);

    return n1.get() + n2;    // wait for the Future to return their values
}

```

This block of code looks similar to regular C++ code. First, if `(n < 2)`, meaning `n` is 0 or 1, then we return 0 or 1 (recall the first element of the Fibonacci sequence is 0 and the second is 1). If `n` is larger than 1 we spawn two new tasks whose results are contained in `n1` and `n2`. This is done using `hpx::async` which takes as arguments a function (function pointer, object or lambda) and the arguments to the function. Instead of returning a `std::uint64_t` like `fibonacci` does, `hpx::async` returns a future of a `std::uint64_t`, i.e. `hpx::future<std::uint64_t>`. Each of these futures represents an asynchronous, recursive call to `fibonacci`. After we've created the futures, we wait for both of them to finish computing, we add them together, and return that value as our result. We get the values from the futures using the `get` method. The recursive call tree will continue until `n` is equal to 0 or 1, at which point the value can be returned because it is implicitly known. When this termination condition is reached, the futures can then be added up, producing the `n`-th value of the Fibonacci sequence.

Note that calling `get` potentially blocks the calling `HPX`-thread, and lets other `HPX`-threads run in the meantime. There are, however, more efficient ways of doing this. `examples/quickstart/fibonacci_futures.cpp` contains many more variations of locally computing the Fibonacci numbers, where each method makes different tradeoffs in where asynchrony and parallelism is applied. To get started, however, the method above is sufficient and optimizations can be applied once you are more familiar with `HPX`. The example *Dataflow* presents dataflow, which is a way to more efficiently chain together multiple tasks.

2.3.2 Parallel algorithms

This program will perform a matrix multiplication in parallel. The output will look something like this:

```
Matrix A is :
4 9 6
1 9 8

Matrix B is :
4 9
6 1
9 8

Resultant Matrix is :
124 93
130 82
```

Setup

The source code for this example can be found here: `matrix_multiplication.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.matrix_multiplication
```

To run the program type:

```
$ ./bin/matrix_multiplication
```

or:

```
$ ./bin/matrix_multiplication --n 2 --m 3 --k 2 --s 100 --l 0 --u 10
```

where the first matrix is $n \times m$ and the second $m \times k$, s is the seed for creating the random values of the matrices and the range of these values is $[l, u]$

This should print:

```
Matrix A is :
4 9 6
1 9 8

Matrix B is :
4 9
6 1
9 8

Resultant Matrix is :
124 93
130 82
```

Notice that the numbers may be different because of the random initialization of the matrices.

Walkthrough

Now that you have compiled and run the code, let's look at how the code works.

First, `main()` is used to initialize the runtime system and pass the command line arguments to the program. `hpx::init` calls `hpx_main()` after setting up HPX, which is where our program is implemented.

```
int main(int argc, char* argv[])
{
    using namespace hpx::program_options;
    options_description cmdline("usage: " HPX_APPLICATION_STRING " [options]");
    // clang-format off
    cmdline.add_options()
        ("n",
         hpx::program_options::value<std::size_t>()->default_value(2),
         "Number of rows of first matrix")
        ("m",
         hpx::program_options::value<std::size_t>()->default_value(3),
         "Number of columns of first matrix (equal to the number of rows of "
         "second matrix)")
        ("k",
         hpx::program_options::value<std::size_t>()->default_value(2),
         "Number of columns of second matrix")
        ("seed,s",
         hpx::program_options::value<unsigned int>(),
         "The random number generator seed to use for this run")
        ("l",
         hpx::program_options::value<int>()->default_value(0),
         "Lower limit of range of values")
        ("u",
         hpx::program_options::value<int>()->default_value(10),
         "Upper limit of range of values");
    // clang-format on
    hpx::local::init_params init_args;
    init_args.desc_cmdline = cmdline;

    return hpx::local::init(hpx_main, argc, argv, init_args);
}
```

Proceeding to the `hpx_main()` function, we can see that matrix multiplication can be done very easily.

```
int hpx_main(hpx::program_options::variables_map& vm)
{
    using element_type = int;

    // Define matrix sizes
    std::size_t const rowsA = vm["n"].as<std::size_t>();
    std::size_t const colsA = vm["m"].as<std::size_t>();
    std::size_t const rowsB = colsA;
    std::size_t const colsB = vm["k"].as<std::size_t>();
    std::size_t const rowsR = rowsA;
    std::size_t const colsR = colsB;

    // Initialize matrices A and B
```

(continues on next page)

(continued from previous page)

```

std::vector<int> A(rowsA * colsA);
std::vector<int> B(rowsB * colsB);
std::vector<int> R(rowsR * colsR);

// Define seed
unsigned int seed = std::random_device{}();
if (vm.count("seed"))
    seed = vm["seed"].as<unsigned int>();

gen.seed(seed);
std::cout << "using seed: " << seed << std::endl;

// Define range of values
int const lower = vm["l"].as<int>();
int const upper = vm["u"].as<int>();

// Matrices have random values in the range [lower, upper]
std::uniform_int_distribution<element_type> dis(lower, upper);
auto generator = std::bind(dis, gen);
hpx::ranges::generate(A, generator);
hpx::ranges::generate(B, generator);

// Perform matrix multiplication
hpx::experimental::for_loop(hpx::execution::par, 0, rowsA, [&](auto i) {
    hpx::experimental::for_loop(0, colsB, [&](auto j) {
        R[i * colsR + j] = 0;
        hpx::experimental::for_loop(0, rowsB, [&](auto k) {
            R[i * colsR + j] += A[i * colsA + k] * B[k * colsB + j];
        });
    });
});

// Print all 3 matrices
print_matrix(A, rowsA, colsA, "A");
print_matrix(B, rowsB, colsB, "B");
print_matrix(R, rowsR, colsR, "R");

return hpx::local::finalize();
}

```

First, the dimensions of the matrices are defined. If they were not given as command-line arguments, their default values are 2 x 3 for the first matrix and 3 x 2 for the second. We use standard vectors to define the matrices to be multiplied as well as the resultant matrix.

To give some random initial values to our matrices, we use `std::uniform_int_distribution`¹⁴. Then, `std::bind()` is used along with `hpx::ranges::generate()` to yield two matrices A and B, which contain values in the range of [0, 10] or in the range defined by the user at the command-line arguments. The seed to generate the values can also be defined by the user.

The next step is to perform the matrix multiplication in parallel. This can be done by just using an `hpx::experimental::for_loop` combined with a parallel execution policy `hpx::execution::par` as the outer loop of the multiplication. Note that the execution of `hpx::experimental::for_loop` without specifying an execu-

¹⁴ https://en.cppreference.com/w/cpp/numeric/random/uniform_int_distribution

tion policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Finally, the matrices A, B that are multiplied as well as the resultant matrix R are printed using the following function.

```
void print_matrix(std::vector<int> const& M, std::size_t rows, std::size_t cols,
    char const* message)
{
    std::cout << "\nMatrix " << message << " is:" << std::endl;
    for (std::size_t i = 0; i < rows; i++)
    {
        for (std::size_t j = 0; j < cols; j++)
            std::cout << M[i * cols + j] << " ";
        std::cout << "\n";
    }
}
```

2.3.3 Asynchronous execution with actions

This example extends the *previous example* by introducing *actions*: functions that can be run remotely. In this example, however, we will still only run the action locally. The mechanism to execute *actions* stays the same: `hpx::async`. Later examples will demonstrate running actions on remote *localities* (e.g. *Remote execution with actions*).

Setup

The source code for this example can be found here: `fibonacci.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.fibonacci
```

To run the program type:

```
$ ./bin/fibonacci
```

This should print (time should be approximate):

```
fibonacci(10) == 55
elapsed time: 0.00186288 [s]
```

This run used the default settings, which calculate the tenth element of the Fibonacci sequence. To declare which Fibonacci value you want to calculate, use the `--n-value` option. Additionally you can use the `--hpx:threads` option to declare how many OS-threads you wish to use when running the program. For instance, running:

```
$ ./bin/fibonacci --n-value 20 --hpx:threads 4
```

Will yield:

```
fibonacci(20) == 6765
elapsed time: 0.233827 [s]
```

Walkthrough

The code needed to initialize the *HPX* runtime is the same as in the *previous example*:

```
int main(int argc, char* argv[])
{
    // Configure application-specific options
    hpx::program_options::options_description desc_commandline(
        "Usage: " HPX_APPLICATION_STRING " [options]");

    desc_commandline.add_options()("n-value",
        hpx::program_options::value<std::uint64_t>()->default_value(10),
        "n value for the Fibonacci function");

    // Initialize and run HPX
    hpx::init_params init_args;
    init_args.desc_cmdline = desc_commandline;

    return hpx::init(argc, argv, init_args);
}
```

The `hpx::init` function in `main()` starts the runtime system, and invokes `hpx_main()` as the first *HPX*-thread. The command line option `--n-value` is read in, a timer (`hpx::chrono::high_resolution_timer`) is set up to record the time it takes to do the computation, the *fibonacci action* is invoked synchronously, and the answer is printed out.

```
int hpx_main(hpx::program_options::variables_map& vm)
{
    // extract command line argument, i.e. fib(N)
    std::uint64_t n = vm["n-value"].as<std::uint64_t>();

    {
        // Keep track of the time required to execute.
        hpx::chrono::high_resolution_timer t;

        // Wait for fib() to return the value
        fibonacci_action fib;
        std::uint64_t r = fib(hpx::find_here(), n);

        char const* fmt = "fibonacci({1}) == {2}\\nelapsed time: {3} [s]\\n";
        hpx::util::format_to(std::cout, fmt, n, r, t.elapsed());
    }

    return hpx::finalize();    // Handles HPX shutdown
}
```

Upon a closer look we see that we've created a `std::uint64_t` to store the result of invoking our *fibonacci_action* `fib`. This *action* will launch synchronously (as the work done inside of the *action* will be asynchronous itself) and return the result of the Fibonacci sequence. But wait, what is an *action*? And what is this *fibonacci_action*? For starters, an *action* is a wrapper for a function. By wrapping functions, *HPX* can send packets of work to different processing units. These vehicles allow users to calculate work now, later, or on certain nodes. The first argument to our *action* is the location where the *action* should be run. In this case, we just want to run the *action* on the machine that we are currently on, so we use `hpx::find_here`. To further understand this we turn to the code to find where *fibonacci_action* was defined:

```
// forward declaration of the Fibonacci function
std::uint64_t fibonacci(std::uint64_t n);

// This is to generate the required boilerplate we need for the remote
// invocation to work.
HPX_PLAIN_ACTION(fibonacci, fibonacci_action)
```

A plain *action* is the most basic form of *action*. Plain *actions* wrap simple global functions which are not associated with any particular object (we will discuss other types of *actions* in *Components and actions*). In this block of code the function `fibonacci()` is declared. After the declaration, the function is wrapped in an *action* in the declaration `HPX_PLAIN_ACTION`. This function takes two arguments: the name of the function that is to be wrapped and the name of the *action* that you are creating.

This picture should now start making sense. The function `fibonacci()` is wrapped in an *action* `fibonacci_action`, which was run synchronously but created asynchronous work, then returns a `std::uint64_t` representing the result of the function `fibonacci()`. Now, let's look at the function `fibonacci()`:

```
std::uint64_t fibonacci(std::uint64_t n)
{
    if (n < 2)
        return n;

    // We restrict ourselves to execute the Fibonacci function locally.
    hpx::id_type const locality_id = hpx::find_here();

    // Invoking the Fibonacci algorithm twice is inefficient.
    // However, we intentionally demonstrate it this way to create some
    // heavy workload.

    fibonacci_action fib;
    hpx::future<std::uint64_t> n1 = hpx::async(fib, locality_id, n - 1);
    hpx::future<std::uint64_t> n2 = hpx::async(fib, locality_id, n - 2);

    return n1.get() +
        n2.get();    // wait for the Futures to return their values
}
```

This block of code is much more straightforward and should look familiar from the *previous example*. First, if `(n < 2)`, meaning `n` is 0 or 1, then we return 0 or 1 (recall the first element of the Fibonacci sequence is 0 and the second is 1). If `n` is larger than 1 we spawn two tasks using `hpx::async`. Each of these futures represents an asynchronous, recursive call to `fibonacci`. As previously we wait for both futures to finish computing, get the results, add them together, and return that value as our result. The recursive call tree will continue until `n` is equal to 0 or 1, at which point the value can be returned because it is implicitly known. When this termination condition is reached, the futures can then be added up, producing the `n`-th value of the Fibonacci sequence.

2.3.4 Remote execution with actions

This program will print out a hello world message on every OS-thread on every *locality*. The output will look something like this:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 1 on locality 1
hello world from OS-thread 0 on locality 0
hello world from OS-thread 0 on locality 1
```

Setup

The source code for this example can be found here: `hello_world_distributed.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.hello_world_distributed
```

To run the program type:

```
$ ./bin/hello_world_distributed
```

This should print:

```
hello world from OS-thread 0 on locality 0
```

To use more OS-threads use the command line option `--hpx:threads` and type the number of threads that you wish to use. For example, typing:

```
$ ./bin/hello_world_distributed --hpx:threads 2
```

will yield:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 0
```

Notice how the ordering of the two print statements will change with subsequent runs. To run this program on multiple localities please see the section *How to use HPX applications with PBS*.

Walkthrough

Now that you have compiled and run the code, let's look at how the code works, beginning with `main()`:

```
// Here is the main entry point. By using the include 'hpx/hpx_main.hpp' HPX
// will invoke the plain old C-main() as its first HPX thread.
int main()
{
    // Get a list of all available localities.
    std::vector<hpx::id_type> localities = hpx::find_all_localities();

    // Reserve storage space for futures, one for each locality.
    std::vector<hpx::future<void>> futures;
```

(continues on next page)

(continued from previous page)

```

futures.reserve(localities.size());

for (hpx::id_type const& node : localities)
{
    // Asynchronously start a new task. The task is encapsulated in a
    // future, which we can query to determine if the task has
    // completed.
    typedef hello_world_foreman_action action_type;
    futures.push_back(hpx::async<action_type>(node));
}

// The non-callback version of hpx::wait_all takes a single parameter,
// a vector of futures to wait on. hpx::wait_all only returns when
// all of the futures have finished.
hpx::wait_all(futures);
return 0;
}

```

In this excerpt of the code we again see the use of futures. This time the futures are stored in a vector so that they can easily be accessed. `hpx::wait_all` is a family of functions that wait on for an `std::vector<>` of futures to become ready. In this piece of code, we are using the synchronous version of `hpx::wait_all`, which takes one argument (the `std::vector<>` of futures to wait on). This function will not return until all the futures in the vector have been executed.

In *Asynchronous execution with actions* we used `hpx::find_here` to specify the target of our actions. Here, we instead use `hpx::find_all_localities`, which returns an `std::vector<>` containing the identifiers of all the machines in the system, including the one that we are on.

As in *Asynchronous execution with actions* our futures are set using `hpx::async<>`. The `hello_world_foreman_action` is declared here:

```

// Define the boilerplate code necessary for the function 'hello_world_foreman'
// to be invoked as an HPX action.
HPX_PLAIN_ACTION(hello_world_foreman, hello_world_foreman_action)

```

Another way of thinking about this wrapping technique is as follows: functions (the work to be done) are wrapped in actions, and actions can be executed locally or remotely (e.g. on another machine participating in the computation).

Now it is time to look at the `hello_world_foreman()` function which was wrapped in the action above:

```

void hello_world_foreman()
{
    // Get the number of worker OS-threads in use by this locality.
    std::size_t const os_threads = hpx::get_os_thread_count();

    // Populate a set with the OS-thread numbers of all OS-threads on this
    // locality. When the hello world message has been printed on a particular
    // OS-thread, we will remove it from the set.
    std::set<std::size_t> attendance;
    for (std::size_t os_thread = 0; os_thread < os_threads; ++os_thread)
        attendance.insert(os_thread);

    // As long as there are still elements in the set, we must keep scheduling
    // HPX-threads. Because HPX features work-stealing task schedulers, we have

```

(continues on next page)

(continued from previous page)

```

// no way of enforcing which worker OS-thread will actually execute
// each HPX-thread.
while (!attendance.empty())
{
    // Each iteration, we create a task for each element in the set of
    // OS-threads that have not said "Hello world". Each of these tasks
    // is encapsulated in a future.
    std::vector<hpx::future<std::size_t>> futures;
    futures.reserve(attendance.size());

    for (std::size_t worker : attendance)
    {
        // Asynchronously start a new task. The task is encapsulated in a
        // future that we can query to determine if the task has completed.
        //
        // We give the task a hint to run on a particular worker thread
        // (core) and suggest binding the scheduled thread to the given
        // core, but no guarantees are given by the scheduler that the task
        // will actually run on that worker thread. It will however try as
        // hard as possible to place the new task on the given worker
        // thread.
        hpx::execution::parallel_executor exec(
            hpx::threads::thread_priority::bound);

        hpx::threads::thread_schedule_hint hint(
            hpx::threads::thread_schedule_hint_mode::thread,
            static_cast<std::int16_t>(worker));

        // Annotate the created threads with the given thread name
        hpx::execution::experimental::annotating_executor annotating_exec(
            hpx::execution::experimental::with_hint(exec, hint),
            std::string("hello_world_worker#") + std::to_string(worker));

        futures.push_back(
            hpx::async(annotating_exec, hello_world_worker, worker));
    }

    // Wait for all of the futures to finish. The callback version of the
    // hpx::wait_each function takes two arguments: a vector of futures,
    // and a binary callback. The callback takes two arguments; the first
    // is the index of the future in the vector, and the second is the
    // return value of the future. hpx::wait_each doesn't return until
    // all the futures in the vector have returned.
    hpx::spinlock mtx;
    hpx::wait_each(hpx::unwrapping([&](std::size_t t) {
        if (std::size_t(-1) != t)
        {
            std::lock_guard<hpx::spinlock> lk(mtx);
            attendance.erase(t);
        }
    })),
        futures);

```

(continues on next page)

(continued from previous page)

```

    }
}

```

Now, before we discuss `hello_world_foreman()`, let's talk about the `hpx::wait_each` function. The version of `hpx::wait_each` invokes a callback function provided by the user, supplying the callback function with the result of the future.

In `hello_world_foreman()`, an `std::set<>` called `attendance` keeps track of which OS-threads have printed out the hello world message. When the OS-thread prints out the statement, the future is marked as ready, and `hpx::wait_each` in `hello_world_foreman()`. If it is not executing on the correct OS-thread, it returns a value of -1, which causes `hello_world_foreman()` to leave the OS-thread id in `attendance`.

```

std::size_t hello_world_worker(std::size_t desired)
{
    // Returns the OS-thread number of the worker that is running this
    // HPX-thread.
    std::size_t current = hpx::get_worker_thread_num();
    if (current == desired)
    {
        // The HPX-thread has been run on the desired OS-thread.
        char const* msg = "hello world from OS-thread {1} on locality {2}\n";

        hpx::util::format_to(hpx::cout, msg, desired, hpx::get_locality_id())
            << std::flush;

        return desired;
    }

    // This HPX-thread has been run by the wrong OS-thread, make the foreman
    // try again by rescheduling it.
    return std::size_t(-1);
}

```

Because *HPX* features work stealing task schedulers, there is no way to guarantee that an action will be scheduled on a particular OS-thread. This is why we must use a guess-and-check approach.

2.3.5 Components and actions

The accumulator examples demonstrate the use of components. Components are C++ classes that expose methods as a type of *HPX* action. These actions are called component actions. There are three examples: - accumulator - template accumulator - template function accumulator

Components are globally named, meaning that a component action can be called remotely (e.g., from another machine). There are two accumulator examples in *HPX*.

In the *Asynchronous execution with actions* and the *Remote execution with actions*, we introduced plain actions, which wrapped global functions. The target of a plain action is an identifier which refers to a particular machine involved in the computation. For plain actions, the target is the machine where the action will be executed.

Component actions, however, do not target machines. Instead, they target component instances. The instance may live on the machine that we've invoked the component action from, or it may live on another machine.

The components in these examples expose three different functions:

- `reset()` - Resets the accumulator value to 0.

- `add(arg)` - Adds `arg` to the accumulators value.
- `query()` - Queries the value of the accumulator.

These examples create an instance of the (template or template function) accumulator, and then allow the user to enter commands at a prompt, which subsequently invoke actions on the accumulator instance.

Accumulator

Setup

The source code for this example can be found here: `accumulator_client.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.accumulators.accumulator
```

To run the program type:

```
$ ./bin/accumulator_client
```

Once the program starts running, it will print the following prompt and then wait for input. An example session is given below:

```
commands: reset, add [amount], query, help, quit
> add 5
> add 10
> query
15
> add 2
> query
17
> reset
> add 1
> query
1
> quit
```

Walkthrough

Now, let's take a look at the source code of the accumulator example. This example consists of two parts: an *HPX* component library (a library that exposes an *HPX* component) and a client application which uses the library. This walkthrough will cover the *HPX* component library. The code for the client application can be found here: `accumulator_client.cpp`.

An *HPX* component is represented by two C++ classes:

- **A server class** - The implementation of the component's functionality.
- **A client class** - A high-level interface that acts as a proxy for an instance of the component.

Typically, these two classes both have the same name, but the server class usually lives in different sub-namespaces (server). For example, the full names of the two classes in accumulator are:

- `examples::server::accumulator` (server class)

- `examples::accumulator` (client class)

The server class

The following code is from `server/accumulator.hpp`¹⁵.

All *HPX* component server classes must inherit publicly from the *HPX* component base class: `hpx::components::component_base`

The accumulator component inherits from `hpx::components::locking_hook`. This allows the runtime system to ensure that all action invocations are serialized. That means that the system ensures that no two actions are invoked at the same time on a given component instance. This makes the component thread safe and no additional locking has to be implemented by the user. Moreover, an accumulator component is a component because it also inherits from `hpx::components::component_base` (the template argument passed to `locking_hook` is used as its base class). The following snippet shows the corresponding code:

```
class accumulator
: public hpx::components::locking_hook<
    hpx::components::component_base<accumulator>>
```

Our accumulator class will need a data member to store its value in, so let's declare a data member:

```
argument_type value_;
```

The constructor for this class simply initializes `value_` to 0:

```
accumulator()
: value_(0)
{
}
```

Next, let's look at the three methods of this component that we will be exposing as component actions:

Here are the action types. These types wrap the methods we're exposing. The wrapping technique is very similar to the one used in the *Asynchronous execution with actions* and the *Remote execution with actions*:

```
HPX_DEFINE_COMPONENT_ACTION(accumulator, reset)
HPX_DEFINE_COMPONENT_ACTION(accumulator, add)
HPX_DEFINE_COMPONENT_ACTION(accumulator, query)
```

The last piece of code in the server class header is the declaration of the action type registration code:

```
HPX_REGISTER_ACTION_DECLARATION(
    examples::server::accumulator::reset_action, accumulator_reset_action)

HPX_REGISTER_ACTION_DECLARATION(
    examples::server::accumulator::add_action, accumulator_add_action)

HPX_REGISTER_ACTION_DECLARATION(
    examples::server::accumulator::query_action, accumulator_query_action)
```

Note: The code above must be placed in the global namespace.

¹⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/examples/accumulators/server/accumulator.hpp>

The rest of the registration code is in `accumulator.cpp`¹⁶

```

////////////////////////////////////
// Add factory registration functionality.
HPX_REGISTER_COMPONENT_MODULE()

////////////////////////////////////
typedef hpx::components::component<examples::server::accumulator>
    accumulator_type;

HPX_REGISTER_COMPONENT(accumulator_type, accumulator)

////////////////////////////////////
// Serialization support for accumulator actions.
HPX_REGISTER_ACTION(
    accumulator_type::wrapped_type::reset_action, accumulator_reset_action)
HPX_REGISTER_ACTION(
    accumulator_type::wrapped_type::add_action, accumulator_add_action)
HPX_REGISTER_ACTION(
    accumulator_type::wrapped_type::query_action, accumulator_query_action)

```

Note: The code above must be placed in the global namespace.

The client class

The following code is from `accumulator.hpp`¹⁷

The client class is the primary interface to a component instance. Client classes are used to create components:

```

// Create a component on this locality.
examples::accumulator c = hpx::new<examples::accumulator>(hpx::find_here());

```

and to invoke component actions:

```
c.add(hpx::launch::apply, 4);
```

Clients, like servers, need to inherit from a base class, this time, `hpx::components::client_base`:

```

class accumulator
: public hpx::components::client_base<accumulator, server::accumulator>

```

For readability, we typedef the base class like so:

```

typedef hpx::components::client_base<accumulator, server::accumulator>
    base_type;

```

Here are examples of how to expose actions through a client class:

There are a few different ways of invoking actions:

¹⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/examples/accumulators/accumulator.cpp>

¹⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/examples/accumulators/accumulator.hpp>

- **Non-blocking:** For actions that don't have return types, or when we do not care about the result of an action, we can invoke the action using fire-and-forget semantics. This means that once we have asked *HPX* to compute the action, we forget about it completely and continue with our computation. We use `hpx::post` to invoke an action in a non-blocking fashion.

```
void reset(hpx::launch::apply_policy)
{
    HPX_ASSERT(this->get_id());

    typedef server::accumulator::reset_action action_type;
    hpx::post(action_type(), this->get_id());
}
```

- **Asynchronous:** Futures, as demonstrated in *Asynchronous execution*, *Asynchronous execution with actions*, and the *Remote execution with actions*, enable asynchronous action invocation. Here's an example from the accumulator client class:

```
hpx::future<argument_type> query(hpx::launch::async_policy)
{
    HPX_ASSERT(this->get_id());

    typedef server::accumulator::query_action action_type;
    return hpx::async(action_type(), this->get_id());
}
```

- **Synchronous:** To invoke an action in a fully synchronous manner, we can simply call `hpx::sync` which is semantically equivalent to `hpx::async().get()` (i.e., create a future and immediately wait on it to be ready). Here's an example from the accumulator client class:

```
void add(argument_type arg)
{
    HPX_ASSERT(this->get_id());

    typedef server::accumulator::add_action action_type;
    action_type()(this->get_id(), arg);
}
```

Note that `this->get_id()` references a data member of the `hpx::components::client_base` base class which identifies the server accumulator instance.

`hpx::id_type` is a type which represents a global identifier in *HPX*. This type specifies the target of an action. This is the type that is returned by `hpx::find_here` in which case it represents the *locality* the code is running on.

Template accumulator

Walkthrough

The server class

The following code is from `server/template_accumulator.hpp`¹⁸.

¹⁸ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/examples/accumulators/server/template_accumulator.hpp

Similarly to the accumulator example, the component server class inherits publicly from `hpx::components::component_base` and from `hpx::components::locking_hook` ensuring thread-safe method invocations.

```
template <typename T>
class template_accumulator
: public hpx::components::locking_hook<
    hpx::components::component_base<template_accumulator<T>>>
```

The body of the template accumulator class remains mainly the same as the accumulator with the difference that it uses templates in the data types.

```
typedef T argument_type;

template_accumulator()
: value_(0)
{
}

////////////////////////////////////
// Exposed functionality of this component.

/// Reset the components value to 0.
void reset()
{
    // set value_ to 0.
    value_ = 0;
}

/// Add the given number to the accumulator.
void add(argument_type arg)
{
    // add value_ to arg, and store the result in value_.
    value_ += arg;
}

/// Return the current value to the caller.
argument_type query() const
{
    // Get the value of value_.
    return value_;
}

////////////////////////////////////
// Each of the exposed functions needs to be encapsulated into an
// action type, generating all required boilerplate code for threads,
// serialization, etc.
HPX_DEFINE_COMPONENT_ACTION(template_accumulator, reset)
HPX_DEFINE_COMPONENT_ACTION(template_accumulator, add)
HPX_DEFINE_COMPONENT_ACTION(template_accumulator, query)
```

The last piece of code in the server class header is the declaration of the action type registration code. `REGISTER_TEMPLATE_ACCUMULATOR_DECLARATION(type)` declares actions for the specified type, while `REGISTER_TEMPLATE_ACCUMULATOR(type)` registers the actions and the component for the specified type, using macros

to handle boilerplate code.

```
#define REGISTER_TEMPLATE_ACCUMULATOR_DECLARATION(type) \
    HPX_REGISTER_ACTION_DECLARATION( \
        examples::server::template_accumulator<type>::reset_action, \
        HPX_PP_CAT(__template_accumulator_reset_action_, type)) \
 \
    HPX_REGISTER_ACTION_DECLARATION( \
        examples::server::template_accumulator<type>::add_action, \
        HPX_PP_CAT(__template_accumulator_add_action_, type)) \
 \
    HPX_REGISTER_ACTION_DECLARATION( \
        examples::server::template_accumulator<type>::query_action, \
        HPX_PP_CAT(__template_accumulator_query_action_, type)) \
    /**/

#define REGISTER_TEMPLATE_ACCUMULATOR(type) \
    HPX_REGISTER_ACTION( \
        examples::server::template_accumulator<type>::reset_action, \
        HPX_PP_CAT(__template_accumulator_reset_action_, type)) \
 \
    HPX_REGISTER_ACTION( \
        examples::server::template_accumulator<type>::add_action, \
        HPX_PP_CAT(__template_accumulator_add_action_, type)) \
 \
    HPX_REGISTER_ACTION( \
        examples::server::template_accumulator<type>::query_action, \
        HPX_PP_CAT(__template_accumulator_query_action_, type)) \
 \
    typedef ::hpx::components::component< \
        examples::server::template_accumulator<type>> \
        HPX_PP_CAT(__template_accumulator_, type); \
    HPX_REGISTER_COMPONENT(HPX_PP_CAT(__template_accumulator_, type)) \
    /**/
```

Note: The code above must be placed in the global namespace.

Finally, `HPX_REGISTER_COMPONENT_MODULE()` in file `server/template_accumulator.cpp`¹⁹ adds the factory registration functionality.

¹⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/examples/accumulators/server/template_accumulator.cpp

The client class

The client class of the template accumulator can be found in `template_accumulator.hpp`²⁰ and is very similar to the client class of the accumulator with the only difference that it uses templates and hence can work with different types.

Template function accumulator

Walkthrough

The server class

The following code is from `server/template_function_accumulator.hpp`²¹.

The component server class inherits publicly from `hpx::components::component_base`.

```
class template_function_accumulator
: public hpx::components::component_base<template_function_accumulator>
```

`typedef hpx::spinlock mutex_type` defines a `mutex_type` as `hpx::spinlock` for thread safety, while the code that follows exposes the functionality of this component.

```
////////////////////////////////////
// Exposed functionality of this component.

/// Reset the value to 0.
void reset()
{
    // Atomically set value_ to 0.
    std::lock_guard<mutex_type> l(mtx_);
    value_ = 0;
}

/// Add the given number to the accumulator.
template <typename T>
void add(T arg)
{
    // Atomically add value_ to arg, and store the result in value_.
    std::lock_guard<mutex_type> l(mtx_);
    value_ += static_cast<double>(arg);
}

/// Return the current value to the caller.
double query() const
{
    // Get the value of value_.
    std::lock_guard<mutex_type> l(mtx_);
    return value_;
}
```

²⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/examples/accumulators/template_accumulator.hpp

²¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/examples/accumulators/server/template_function_accumulator.hpp

- `reset()`: Resets the accumulator value to 0 in a thread-safe manner using `std::lock_guard`.
- `add()`: Adds a value to the accumulator, allowing any type `T` that can be cast to double.
- `query()`: Returns the current value of the accumulator in a thread-safe manner.

To define the actions for `reset()` and `query()` we can use the macro `HPX_DEFINE_COMPONENT_ACTION`. However, actions with template arguments require special type definitions. Therefore, we use `make_action()` to define `add()`.

```

////////////////////////////////////
// Each of the exposed functions needs to be encapsulated into an
// action type, generating all required boilerplate code for threads,
// serialization, etc.

HPX_DEFINE_COMPONENT_ACTION(template_function_accumulator, reset)
HPX_DEFINE_COMPONENT_ACTION(template_function_accumulator, query)

// Actions with template arguments (see add<>() above) require special
// type definitions. The simplest way to define such an action type is
// by deriving from the HPX facility make_action.
template <typename T>
struct add_action
    : hpx::actions::make_action<void> (template_function_accumulator::*)(
        T),
        &template_function_accumulator::template add<T>,
        add_action<T>::type
{
};

```

The last piece of code in the server class header is the action registration:

```

HPX_REGISTER_ACTION_DECLARATION(
    examples::server::template_function_accumulator::reset_action,
    managed_accumulator_reset_action)

HPX_REGISTER_ACTION_DECLARATION(
    examples::server::template_function_accumulator::query_action,
    managed_accumulator_query_action)

```

Note: The code above must be placed in the global namespace.

The rest of the registration code is in `accumulator.cpp`²²

```

////////////////////////////////////
// Add factory registration functionality.
HPX_REGISTER_COMPONENT_MODULE()

////////////////////////////////////
typedef hpx::components::component<
    examples::server::template_function_accumulator>
    accumulator_type;

```

(continues on next page)

²² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/examples/accumulators/accumulator.cpp>

(continued from previous page)

```

HPX_REGISTER_COMPONENT(accumulator_type, template_function_accumulator)

////////////////////////////////////
// Serialization support for managed_accumulator actions.
HPX_REGISTER_ACTION(accumulator_type::wrapped_type::reset_action,
    managed_accumulator_reset_action)
HPX_REGISTER_ACTION(accumulator_type::wrapped_type::query_action,
    managed_accumulator_query_action)

```

Note: The code above must be placed in the global namespace.

The client class

The client class of the template accumulator can be found in `template_function_accumulator.hpp`²³ and is very similar to the client class of the accumulator with the only difference that it uses templates and hence can work with different types.

2.3.6 Dataflow

HPX provides its users with several different tools to simply express parallel concepts. One of these tools is a *local control object (LCO)* called dataflow. An *LCO* is a type of component that can spawn a new thread when triggered. They are also distinguished from other components by a standard interface that allow users to understand and use them easily. A Dataflow, being an *LCO*, is triggered when the values it depends on become available. For instance, if you have a calculation X that depends on the results of three other calculations, you could set up a dataflow that would begin the calculation X as soon as the other three calculations have returned their values. Dataflows are set up to depend on other dataflows. It is this property that makes dataflow a powerful parallelization tool. If you understand the dependencies of your calculation, you can devise a simple algorithm that sets up a dependency tree to be executed. In this example, we calculate compound interest. To calculate compound interest, one must calculate the interest made in each compound period, and then add that interest back to the principal before calculating the interest made in the next period. A practical person would, of course, use the formula for compound interest:

$$F = P(1 + i)^n$$

where F is the future value, P is the principal value, i is the interest rate, and n is the number of compound periods.

However, for the sake of this example, we have chosen to manually calculate the future value by iterating:

$$I = Pi$$

and

$$P = P + I$$

²³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/examples/accumulators/template_function_accumulator.hpp

Setup

The source code for this example can be found here: `interest_calculator.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.interest_calculator
```

To run the program type:

```
$ ./bin/interest_calculator --principal 100 --rate 5 --cp 6 --time 36
Final amount: 134.01
Amount made: 34.0096
```

Walkthrough

Let us begin with `main`. Here we can see that we again are using `Boost.Program_options` to set our command line variables (see *Asynchronous execution with actions* for more details). These options set the principal, rate, compound period, and time. It is important to note that the units of time for `cp` and `time` must be the same.

```
int main(int argc, char** argv)
{
    options_description cmdline("Usage: " HPX_APPLICATION_STRING " [options]");

    cmdline.add_options()("principal", value<double>()->default_value(1000),
        "The principal [$]")("rate", value<double>()->default_value(7),
        "The interest rate [%]")("cp", value<int>()->default_value(12),
        "The compound period [months]")("time",
        value<int>()->default_value(12 * 30),
        "The time money is invested [months]");

    hpx::init_params init_args;
    init_args.desc_cmdline = cmdline;

    return hpx::init(argc, argv, init_args);
}
```

Next we look at `hpx_main`.

```
int hpx_main(variables_map& vm)
{
    {
        using hpx::dataflow;
        using hpx::make_ready_future;
        using hpx::shared_future;
        using hpx::unwrapping;
        hpx::id_type here = hpx::find_here();

        double init_principal =
            vm["principal"].as<double>();           //Initial principal
        double init_rate = vm["rate"].as<double>(); //Interest rate
        int cp = vm["cp"].as<int>();                 //Length of a compound period
```

(continues on next page)

(continued from previous page)

```

int t = vm["time"].as<int>();    //Length of time money is invested

init_rate /= 100;    //Rate is a % and must be converted
t /= cp;    //Determine how many times to iterate interest calculation:
//How many full compound periods can fit in the time invested

// In non-dataflow terms the implemented algorithm would look like:
//
// int t = 5;    // number of time periods to use
// double principal = init_principal;
// double rate = init_rate;
//
// for (int i = 0; i < t; ++i)
// {
//     double interest = calc(principal, rate);
//     principal = add(principal, interest);
// }
//
// Please note the similarity with the code below!

shared_future<double> principal = make_ready_future(init_principal);
shared_future<double> rate = make_ready_future(init_rate);

for (int i = 0; i < t; ++i)
{
    shared_future<double> interest =
        dataflow(unwrapping(calc), principal, rate);
    principal = dataflow(unwrapping(add), principal, interest);
}

// wait for the dataflow execution graph to be finished calculating our
// overall interest
double result = principal.get();

std::cout << "Final amount: " << result << std::endl;
std::cout << "Amount made: " << result - init_principal << std::endl;
}

return hpx::finalize();
}

```

Here we find our command line variables read in, the rate is converted from a percent to a decimal, the number of calculation iterations is determined, and then our shared_futures are set up. Notice that we first place our principal and rate into shares futures by passing the variables `init_principal` and `init_rate` using `hpx::make_ready_future`.

In this way `hpx::shared_future<double> principal` and `rate` will be initialized to `init_principal` and `init_rate` when `hpx::make_ready_future<double>` returns a future containing those initial values. These shared futures then enter the for loop and are passed to `interest`. Next `principal` and `interest` are passed to the reassignment of `principal` using a `hpx::dataflow`. A dataflow will first wait for its arguments to be ready before launching any callbacks, so `add` in this case will not begin until both `principal` and `interest` are ready. This loop continues for each compound period that must be calculated. To see how `interest` and `principal` are calculated in the loop, let us look at `calc_action` and `add_action`:

```
// Calculate interest for one period
double calc(double principal, double rate)
{
    return principal * rate;
}

////////////////////////////////////
// Add the amount made to the principal
double add(double principal, double interest)
{
    return principal + interest;
}
```

After the shared future dependencies have been defined in `hpx_main`, we see the following statement:

```
double result = principal.get();
```

This statement calls `hpx::future::get` on the shared future `principal` which had its value calculated by our for loop. The program will wait here until the entire dataflow tree has been calculated and the value assigned to `result`. The program then prints out the final value of the investment and the amount of interest made by subtracting the final value of the investment from the initial value of the investment.

2.3.7 Local to remote

When developers write code they typically begin with a simple serial code and build upon it until all of the required functionality is present. The following set of examples were developed to demonstrate this iterative process of evolving a simple serial program to an efficient, fully-distributed *HPX* application. For this demonstration, we implemented a 1D heat distribution problem. This calculation simulates the diffusion of heat across a ring from an initialized state to some user-defined point in the future. It does this by breaking each portion of the ring into discrete segments and using the current segment's temperature and the temperature of the surrounding segments to calculate the temperature of the current segment in the next timestep as shown by Fig. ?? below.




Fig. 2.2: Heat diffusion example program flow.

We parallelize this code over the following eight examples:

- Example 1
- Example 2
- Example 3
- Example 4
- Example 5

- Example 6
- Example 7
- Example 8

The first example is straight serial code. In this code we instantiate a vector `U` that contains two vectors of doubles as seen in the structure `stepper`.

```
struct stepper
{
    // Our partition type
    typedef double partition;

    // Our data for one time step
    typedef std::vector<partition> space;

    // Our operator
    static double heat(double left, double middle, double right)
    {
        return middle + (k * dt / (dx * dx)) * (left - 2 * middle + right);
    }

    // do all the work on 'nx' data points for 'nt' time steps
    space do_work(std::size_t nx, std::size_t nt)
    {
        // U[t][i] is the state of position i at time t.
        std::vector<space> U(2);
        for (space& s : U)
            s.resize(nx);

        // Initial conditions: f(0, i) = i
        for (std::size_t i = 0; i != nx; ++i)
            U[0][i] = double(i);

        // Actual time step loop
        for (std::size_t t = 0; t != nt; ++t)
        {
            space const& current = U[t % 2];
            space& next = U[(t + 1) % 2];

            next[0] = heat(current[nx - 1], current[0], current[1]);

            for (std::size_t i = 1; i != nx - 1; ++i)
                next[i] = heat(current[i - 1], current[i], current[i + 1]);

            next[nx - 1] = heat(current[nx - 2], current[nx - 1], current[0]);
        }

        // Return the solution at time-step 'nt'.
        return U[nt % 2];
    }
};
```

Each element in the vector of doubles represents a single grid point. To calculate the change in heat distribution, the temperature of each grid point, along with its neighbors, is passed to the function `heat`. In order to improve readability,

references named `current` and `next` are created which, depending on the time step, point to the first and second vector of doubles. The first vector of doubles is initialized with a simple heat ramp. After calling the heat function with the data in the `current` vector, the results are placed into the `next` vector.

In example 2 we employ a technique called futurization. Futurization is a method by which we can easily transform a code that is serially executed into a code that creates asynchronous threads. In the simplest case this involves replacing a variable with a future to a variable, a function with a future to a function, and adding a `.get()` at the point where a value is actually needed. The code below shows how this technique was applied to the `struct stepper`.

```
struct stepper
{
    // Our partition type
    typedef hpx::shared_future<double> partition;

    // Our data for one time step
    typedef std::vector<partition> space;

    // Our operator
    static double heat(double left, double middle, double right)
    {
        return middle + (k * dt / (dx * dx)) * (left - 2 * middle + right);
    }

    // do all the work on 'nx' data points for 'nt' time steps
    hpx::future<space> do_work(std::size_t nx, std::size_t nt)
    {
        using hpx::dataflow;
        using hpx::unwrapping;

        // U[t][i] is the state of position i at time t.
        std::vector<space> U(2);
        for (space& s : U)
            s.resize(nx);

        // Initial conditions: f(0, i) = i
        for (std::size_t i = 0; i != nx; ++i)
            U[0][i] = hpx::make_ready_future(double(i));

        auto Op = unwrapping(&stepper::heat);

        // Actual time step loop
        for (std::size_t t = 0; t != nt; ++t)
        {
            space const& current = U[t % 2];
            space& next = U[(t + 1) % 2];

            // WHEN U[t][i-1], U[t][i], and U[t][i+1] have been computed, THEN we
            // can compute U[t+1][i]
            for (std::size_t i = 0; i != nx; ++i)
            {
                next[i] =
                    dataflow(hpx::launch::async, Op, current[idx(i, -1, nx)],
                            current[i], current[idx(i, +1, nx)]);
            }
        }
    }
}
```

(continues on next page)

(continued from previous page)

```

    }

    // Now the asynchronous computation is running; the above for-loop does not
    // wait on anything. There is no implicit waiting at the end of each timestep;
    // the computation of each U[t][i] will begin as soon as its dependencies
    // are ready and hardware is available.

    // Return the solution at time-step 'nt'.
    return hpx::when_all(U[nt % 2]);
}
};

```

In example 2, we redefine our partition type as a `shared_future` and, in main, create the object `result`, which is a future to a vector of partitions. We use `result` to represent the last vector in a string of vectors created for each timestep. In order to move to the next timestep, the values of a partition and its neighbors must be passed to `heat` once the futures that contain them are ready. In *HPX*, we have an LCO (Local Control Object) named `Dataflow` that assists the programmer in expressing this dependency. `Dataflow` allows us to pass the results of a set of futures to a specified function when the futures are ready. `Dataflow` takes three types of arguments, one which instructs the dataflow on how to perform the function call (async or sync), the function to call (in this case `Op`), and futures to the arguments that will be passed to the function. When called, dataflow immediately returns a future to the result of the specified function. This allows users to string dataflows together and construct an execution tree.

After the values of the futures in dataflow are ready, the values must be pulled out of the future container to be passed to the function `heat`. In order to do this, we use the *HPX* facility `unwrapping`, which underneath calls `.get()` on each of the futures so that the function `heat` will be passed doubles and not futures to doubles.

By setting up the algorithm this way, the program will be able to execute as quickly as the dependencies of each future are met. Unfortunately, this example runs terribly slow. This increase in execution time is caused by the overheads needed to create a future for each data point. Because the work done within each call to `heat` is very small, the overhead of creating and scheduling each of the three futures is greater than that of the actual useful work! In order to amortize the overheads of our synchronization techniques, we need to be able to control the amount of work that will be done with each future. We call this amount of work per overhead grain size.

In example 3, we return to our serial code to figure out how to control the grain size of our program. The strategy that we employ is to create “partitions” of data points. The user can define how many partitions are created and how many data points are contained in each partition. This is accomplished by creating the struct `partition`, which contains a member object `data_`, a vector of doubles that holds the data points assigned to a particular instance of `partition`.

In example 4, we take advantage of the partition setup by redefining `space` to be a vector of `shared_futures` with each future representing a partition. In this manner, each future represents several data points. Because the user can define how many data points are in each partition, and, therefore, how many data points are represented by one future, a user can control the grainsize of the simulation. The rest of the code is then futurized in the same manner as example 2. It should be noted how strikingly similar example 4 is to example 2.

Example 4 finally shows good results. This code scales equivalently to the OpenMP version. While these results are promising, there are more opportunities to improve the application’s scalability. Currently, this code only runs on one *locality*, but to get the full benefit of *HPX*, we need to be able to distribute the work to other machines in a cluster. We begin to add this functionality in example 5.

In order to run on a distributed system, a large amount of boilerplate code must be added. Fortunately, *HPX* provides us with the concept of a *component*, which saves us from having to write quite as much code. A component is an object that can be remotely accessed using its global address. Components are made of two parts: a server and a client class. While the client class is not required, abstracting the server behind a client allows us to ensure type safety instead of having to pass around pointers to global objects. Example 5 renames example 4’s struct `partition` to `partition_data` and adds serialization support. Next, we add the server side representation of the data in the structure `partition_server`. `Partition_server` inherits from `hpx::components::component_base`, which contains a server-side component

boilerplate. The boilerplate code allows a component's public members to be accessible anywhere on the machine via its Global Identifier (GID). To encapsulate the component, we create a client side helper class. This object allows us to create new instances of our component and access its members without having to know its GID. In addition, we are using the client class to assist us with managing our asynchrony. For example, our client class `partition`'s member function `get_data()` returns a future to `partition_data` `get_data()`. This struct inherits its boilerplate code from `hpx::components::client_base`.

In the structure `stepper`, we have also had to make some changes to accommodate a distributed environment. In order to get the data from a particular neighboring partition, which could be remote, we must retrieve the data from all of the neighboring partitions. These retrievals are asynchronous and the function `heat_part_data`, which, amongst other things, calls `heat`, should not be called unless the data from the neighboring partitions have arrived. Therefore, it should come as no surprise that we synchronize this operation with another instance of `dataflow` (found in `heat_part`). This `dataflow` receives futures to the data in the current and surrounding partitions by calling `get_data()` on each respective partition. When these futures are ready, `dataflow` passes them to the `unwrapping` function, which extracts the `shared_array` of doubles and passes them to the `lambda`. The `lambda` calls `heat_part_data` on the `locality`, which the middle partition is on.

Although this example could run distributed, it only runs on one *locality*, as it always uses `hpx::find_here()` as the target for the functions to run on.

In example 6, we begin to distribute the partition data on different nodes. This is accomplished in `stepper::do_work()` by passing the GID of the *locality* where we wish to create the partition to the partition constructor.

```
for (std::size_t i = 0; i != np; ++i)
    U[0][i] = partition(localities[locidx(i, np, nl)], nx, double(i));
```

We distribute the partitions evenly based on the number of localities used, which is described in the function `locidx`. Because some of the data needed to update the partition in `heat_part` could now be on a new *locality*, we must devise a way of moving data to the *locality* of the middle partition. We accomplished this by adding a switch in the function `get_data()` that returns the end element of the buffer `data_` if it is from the left partition or the first element of the buffer if the data is from the right partition. In this way only the necessary elements, not the whole buffer, are exchanged between nodes. The reader should be reminded that this exchange of end elements occurs in the function `get_data()` and, therefore, is executed asynchronously.

Now that we have the code running in distributed, it is time to make some optimizations. The function `heat_part` spends most of its time on two tasks: retrieving remote data and working on the data in the middle partition. Because we know that the data for the middle partition is local, we can overlap the work on the middle partition with that of the possibly remote call of `get_data()`. This algorithmic change, which was implemented in example 7, can be seen below:

```
// The partitioned operator, it invokes the heat operator above on all elements
// of a partition.
static partition heat_part(
    partition const& left, partition const& middle, partition const& right)
{
    using hpx::dataflow;
    using hpx::unwrapping;

    hpx::shared_future<partition_data> middle_data =
        middle.get_data(partition_server::middle_partition);

    hpx::future<partition_data> next_middle = middle_data.then(
        unwrapping([middle](partition_data const& m) -> partition_data {
            HPX_UNUSED(middle);
```

(continues on next page)

(continued from previous page)

```

        // All local operations are performed once the middle data of
        // the previous time step becomes available.
        std::size_t size = m.size();
        partition_data next(size);
        for (std::size_t i = 1; i != size - 1; ++i)
            next[i] = heat(m[i - 1], m[i], m[i + 1]);
        return next;
    }));

    return dataflow(hpx::launch::async,
        unwrapping([left, middle, right](partition_data next,
            partition_data const& l, partition_data const& m,
            partition_data const& r) -> partition {
                HPX_UNUSED(left);
                HPX_UNUSED(right);

                // Calculate the missing boundary elements once the
                // corresponding data has become available.
                std::size_t size = m.size();
                next[0] = heat(l[size - 1], m[0], m[1]);
                next[size - 1] = heat(m[size - 2], m[size - 1], r[0]);

                // The new partition_data will be allocated on the same locality
                // as 'middle'.
                return partition(middle.get_id(), std::move(next));
            }),
        std::move(next_middle),
        left.get_data(partition_server::left_partition), middle_data,
        right.get_data(partition_server::right_partition));
}

```

Example 8 completes the futurization process and utilizes the full potential of *HPX* by distributing the program flow to multiple localities, usually defined as nodes in a cluster. It accomplishes this task by running an instance of *HPX* main on each *locality*. In order to coordinate the execution of the program, the `struct stepper` is wrapped into a component. In this way, each *locality* contains an instance of `stepper` that executes its own instance of the function `do_work()`. This scheme does create an interesting synchronization problem that must be solved. When the program flow was being coordinated on the head node, the GID of each component was known. However, when we distribute the program flow, each partition has no notion of the GID of its neighbor if the next partition is on another *locality*. In order to make the GIDs of neighboring partitions visible to each other, we created two buffers to store the GIDs of the remote neighboring partitions on the left and right respectively. These buffers are filled by sending the GID of newly created edge partitions to the right and left buffers of the neighboring localities.

In order to finish the simulation, the solution vectors named `result` are then gathered together on *locality* 0 and added into a vector of spaces `overall_result` using the *HPX* functions `gather_id` and `gather_here`.

Example 8 completes this example series, which takes the serial code of example 1 and incrementally morphs it into a fully distributed parallel code. This evolution was guided by the simple principles of futurization, the knowledge of grainsize, and utilization of components. Applying these techniques easily facilitates the scalable parallelization of most applications.

2.3.8 Serializing user-defined types

In order to facilitate the sending and receiving of complex datatypes HPX provides a serialization abstraction.

Just like boost, hpx allows users to serialize user-defined types by either providing the serializer as a member function or defining the serialization as a free function.

Unlike Boost HPX doesn't acknowledge second unsigned int parameter, it is solely there to preserve API compatibility with Boost Serialization

This tutorial was heavily inspired by [Boost's serialization concepts](#)²⁴.

Setup

The source code for this example can be found here: `custom_serialization.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.custom_serialization
```

To run the program type:

```
$ ./bin/custom_serialization
```

This should print:

```
Rectangle(Point(x=0,y=0),Point(x=0,y=5))  
gravity.g = 9.81%
```

Serialization Requirements

In order to serialize objects in HPX, at least one of the following criteria must be met:

In the case of default constructible objects:

- The object is an empty type.
- Has a serialization function as shown in this tutorial.
- All members are accessible publicly and they can be used in structured binding contexts.

Otherwise:

- They need to have special serialization support.

²⁴ https://www.boost.org/doc/libs/1_79_0/libs/serialization/doc/serialization.html

Member function serialization

```
struct point_member_serialization
{
    int x{0};
    int y{0};

    // Required when defining the serialization function as private
    // In this case it isn't
    // Provides serialization access to HPX
    friend class hpx::serialization::access;

    // Second argument exists solely for compatibility with boost serialize
    // it is NOT processed by HPX in any way.
    template <typename Archive>
    void serialize(Archive& ar, unsigned int const)
    {
        // clang-format off
        ar & x & y;
        // clang-format on
    }
};

// Allow bitwise serialization
HPX_IS_BITWISE_SERIALIZABLE(point_member_serialization)
```

Notice that `point_member_serialization` is defined as bitwise serializable (see *Bitwise serialization for bitwise copyable data* for more details). HPX is also able to recursively serialize composite classes and structs given that its members are serializable.

```
struct rectangle_member_serialization
{
    point_member_serialization top_left;
    point_member_serialization lower_right;

    template <typename Archive>
    void serialize(Archive& ar, unsigned int const)
    {
        // clang-format off
        ar & top_left & lower_right;
        // clang-format on
    }
};
```

Free function serialization

In order to decouple your models from HPX, HPX also allows for the definition of free function serializers.

```
struct rectangle_free
{
    point_member_serialization top_left;
    point_member_serialization lower_right;
};

template <typename Archive>
void serialize(Archive& ar, rectangle_free& pt, unsigned int const)
{
    // clang-format off
    ar & pt.lower_right & pt.top_left;
    // clang-format on
}
```

Even if you can't modify a class to befriend it, you can still be able to serialize your class provided that your class is default constructable and you are able to reconstruct it yourself.

```
class point_class
{
public:
    point_class(int x, int y)
        : x(x)
        , y(y)
    {
    }

    point_class() = default;

    [[nodiscard]] int get_x() const noexcept
    {
        return x;
    }

    [[nodiscard]] int get_y() const noexcept
    {
        return y;
    }

private:
    int x;
    int y;
};

template <typename Archive>
void load(Archive& ar, point_class& pt, unsigned int const)
{
    int x, y;
    ar >> x >> y;
    pt = point_class(x, y);
}
```

(continues on next page)

(continued from previous page)

```

}

template <typename Archive>
void save(Archive& ar, point_class const& pt, unsigned int const)
{
    ar << pt.get_x() << pt.get_y();
}

// This tells HPX that you have spilt your serialize function into
// load and save
HPX_SERIALIZATION_SPLIT_FREE(point_class)

```

Serializing non default constructable classes

Some classes don't provide any default constructor.

```

class planet_weight_calculator
{
public:
    explicit planet_weight_calculator(double g)
        : g(g)
    {
    }

    template <class Archive>
    friend void save_construct_data(
        Archive&, planet_weight_calculator const*, unsigned int);

    [[nodiscard]] double get_g() const
    {
        return g;
    }

private:
    // Provides serialization access to HPX
    friend class hpx::serialization::access;
    template <class Archive>
    void serialize(Archive&, unsigned int const)
    {
        // Serialization will be done in the save_construct_data
        // Still needs to be defined
    }

    double g;
};

```

In this case you have to define a `save_construct_data` and `load_construct_data` in which you do the serialization yourself.

```

template <class Archive>
inline void save_construct_data(Archive& ar,

```

(continues on next page)

(continued from previous page)

```

    planet_weight_calculator const* weight_calc, unsigned int const)
{
    ar << weight_calc->g;    // Do all of your serialization here
}

template <class Archive>
inline void load_construct_data(
    Archive& ar, planet_weight_calculator* weight_calc, unsigned int const)
{
    double g;
    ar >> g;

    // ::new(ptr) construct new object at given address
    hpx::construct_at(weight_calc, g);
}

```

Bitwise serialization for bitwise copyable data

When sending non arithmetic types not defined by `std::is_arithmetic`²⁵, HPX has to (de)serialize each object separately. However, if the class you are trying to send consists only of bitwise copyable datatypes, you may mark your class as such. Then HPX will serialize your object bitwise instead of element wise. This has enormous benefits, especially when sending a vector/array of your class. To define your class as such you need to call `HPX_IS_BITWISE_SERIALIZABLE(T)` with your desired custom class.

```

struct point_member_serialization
{
    int x{0};
    int y{0};

    // Required when defining the serialization function as private
    // In this case it isn't
    // Provides serialization access to HPX
    friend class hpx::serialization::access;

    // Second argument exists solely for compatibility with boost serialize
    // it is NOT processed by HPX in any way.
    template <typename Archive>
    void serialize(Archive& ar, unsigned int const)
    {
        // clang-format off
        ar & x & y;
        // clang-format on
    }
};

// Allow bitwise serialization
HPX_IS_BITWISE_SERIALIZABLE(point_member_serialization)

```

²⁵ https://en.cppreference.com/w/cpp/types/is_arithmetic

2.3.9 Termination detection

This example demonstrates how to use *HPX*'s termination detection API to ensure all asynchronous work has completed before shutting down the runtime. This is particularly useful when you need to guarantee that all posted tasks have finished execution before the application exits.

Overview

The termination detection API provides a way to wait for all local *HPX*-threads to complete their work. This is essential in scenarios where you spawn asynchronous tasks using *hpx::post* or *hpx::async* and need to ensure they all finish before the runtime shuts down.

The API supports several use cases:

- **Basic usage:** Wait indefinitely for all tasks to complete
- **Timeout:** Wait for a specified duration
- **Deadline:** Wait until a specific time point
- **Cancellation:** Support for cancellation tokens to interrupt the wait

Setup

The source code for this example can be found here: `termination_detection.cpp`.

To compile this program, go to your *HPX* build directory (see *Building HPX* for information on configuring and building *HPX*) and enter:

```
$ make examples.quickstart.termination_detection
```

To run the program type:

```
$ ./bin/termination_detection
```

This will execute all four examples demonstrating different usage patterns of the termination detection API.

Walkthrough

The example demonstrates four different usage patterns of the termination detection API. Let's examine each one:

Basic usage

The simplest form waits indefinitely for all local threads to complete:

This is useful when you want to ensure all work is done before shutting down, and you don't have time constraints.

Timeout usage

You can specify a maximum duration to wait:

The function returns `true` if all threads completed within the timeout, or `false` if the timeout elapsed. This is useful when you want to give tasks a reasonable amount of time to complete but don't want to wait indefinitely.

Deadline usage

Similar to timeout, but you specify an absolute time point:

This is useful when you have a specific deadline by which all work must be completed.

Cancellation support

The most flexible form supports cancellation tokens:

This allows external control over the wait operation. You can request cancellation from another thread, which is useful in scenarios like graceful shutdown with user interruption support.

API Reference

The termination detection API is available in the `hpx::local` namespace:

`void hpx::local::termination_detection()`

Wait indefinitely for all local *HPX*-threads to complete.

`bool hpx::local::termination_detection(hpx::chrono::steady_duration const &timeout)`

Wait for all local *HPX*-threads to complete, with a timeout.

Parameters

timeout – Maximum duration to wait

Returns

`true` if all threads completed, `false` if timeout elapsed

`bool hpx::local::termination_detection(hpx::chrono::steady_time_point const &deadline)`

Wait for all local *HPX*-threads to complete, until a deadline.

Parameters

deadline – Absolute time point to wait until

Returns

`true` if all threads completed, `false` if deadline passed

`bool hpx::local::termination_detection(hpx::stop_token stop_token, hpx::chrono::steady_duration const &timeout)`

Wait for all local *HPX*-threads to complete, with cancellation support.

Parameters

- **stop_token** – Token that can be used to request cancellation
- **timeout** – Maximum duration to wait (defaults to maximum duration)

Returns

`true` if all threads completed, `false` if timeout elapsed or stop was requested

Use cases

The termination detection API is particularly useful in the following scenarios:

- **Graceful shutdown:** Ensure all background tasks complete before exiting
- **Testing:** Verify that all spawned tasks have finished in unit tests
- **Batch processing:** Wait for all work items in a batch to complete
- **Resource cleanup:** Ensure all tasks using shared resources have finished before cleanup

See also

- `hpx::post` - Fire-and-forget asynchronous execution
- `hpx::async` - Asynchronous execution with a future
- `hpx::finalize` - Shut down the *HPX* runtime

2.4 Manual

The manual is your comprehensive guide to *HPX*. It contains detailed information on how to build and use *HPX* in different scenarios.

2.4.1 Prerequisites

Supported platforms

At this time, *HPX* supports the following platforms. Other platforms may work, but we do not test *HPX* with other platforms, so please be warned.

Table 2.1: Supported Platforms for *HPX*

Name	Minimum Version	Architectures
Linux	2.6	x86-32, x86-64, k1om
BlueGeneQ	V1R2M0	PowerPC A2
Windows	Any Windows system	x86-32, x86-64
Mac OSX	Any OSX system	x86-64
ARM	Any ARM system	Any architecture
RISC-V	Any RISC-V system	Any architecture

Supported compilers

The table below shows the supported compilers for *HPX*.

Table 2.2: Supported Compilers for *HPX*

Name	Minimum Version	Latest tested
GNU Compiler Collection (g++) ²⁶	12.0	15.0
clang: a C language family frontend for LLVM ²⁷	16.0	20.0
Visual C++ ²⁸ (x64)	2022	2022

Software and libraries

The table below presents all the necessary prerequisites for building *HPX*.

Table 2.3: Software prerequisites for *HPX*

	Name	Minimum Version	Latest tested
Build System	CMake ²⁹	3.20	4.1
Required Libraries	Boost ³⁰	1.71.0	1.88.0
	Portable Hardware Locality (HWLOC) ³¹	1.5	2.4

The most important dependencies are [Boost](#)³² and [Portable Hardware Locality \(HWLOC\)](#)³³. The installation of Boost is described in detail in Boost's [Getting Started](#)³⁴ document. A recent version of hwloc is required in order to support thread pinning and NUMA awareness and can be found in [Hwloc Downloads](#)³⁵.

HPX is written in 99.99% Standard C++ (the remaining 0.01% is platform specific assembly code). As such, *HPX* is compilable with almost any standards compliant C++ compiler. The code base takes advantage of C++ language and standard library features when available.

Note: When building Boost using gcc, please note that it is required to specify a `cxxflags=-std=c++20` command line argument to b2 (bjam).

Note: In most configurations, *HPX* depends only on header-only Boost. Boost.Filesystem is required if the standard library does not support filesystem. The following are not needed by default, but are required in certain configurations: Boost.Chrono, Boost.DateTime, Boost.Log, Boost.LogSetup, Boost.Regex, and Boost.Thread.

Depending on the options you chose while building and installing *HPX*, you will find that *HPX* may depend on several other libraries such as those listed below.

Note: In order to use a high speed parcellport, we currently recommend configuring *HPX* to use MPI so that MPI can be used for communication between different localities. Please set the CMake variable `MPI_CXX_COMPILER` to your MPI C++ compiler wrapper if not detected automatically.

Table 2.4: Optional software prerequisites for *HPX*

Name	Minimum version
google-perftools ³⁶	1.7.1
jemalloc ³⁷	2.1.0
mi-malloc ³⁸	1.0.0
Performance Application Programming Interface (PAPI)	

²⁶ <https://gcc.gnu.org>

²⁷ <https://clang.llvm.org/>

²⁸ <https://msdn.microsoft.com/en-us/visualc/default.aspx>

²⁹ <https://www.cmake.org>

³⁰ <https://www.boost.org/>

³¹ <https://www.open-mpi.org/projects/hwloc/>

³² <https://www.boost.org/>

³³ <https://www.open-mpi.org/projects/hwloc/>

³⁴ https://www.boost.org/more/getting_started/index.html

³⁵ <https://www.open-mpi.org/software/hwloc/v1.11>

2.4.2 Getting HPX

Download a tarball of the latest release from [HPX Downloads](#)³⁹ and unpack it or clone the repository directly using git:

```
$ git clone https://github.com/TheHPXProject/hpx.git
```

It is also recommended that you check out the latest stable tag:

```
$ cd hpx
```

```
$ git checkout v2.0.0
```

2.4.3 Building HPX

Basic information

The build system for *HPX* is based on [CMake](#)⁴⁰, a cross-platform build-generator tool which is not responsible for building the project but rather generates the files needed by your build tool (GNU make, Visual Studio, etc.) for building *HPX*. If CMake is not already installed in your system, you can download it and install it here: [CMake Downloads](#)⁴¹.

Once [CMake](#)⁴² has been run, the build process can be started. The build process consists of the following parts:

- The *HPX* core libraries (target `core`): This forms the basic set of *HPX* libraries.
- *HPX* Examples (target `examples`): This target is enabled by default and builds all *HPX* examples (disable by setting `HPX_WITH_EXAMPLES:BOOL=Off`). *HPX* examples are part of the `all` target and are included in the installation if enabled.
- *HPX* Tests (target `tests`): This target builds the *HPX* test suite and is enabled by default (disable by setting `HPX_WITH_TESTS:BOOL=Off`). They are not built by the `all` target and have to be built separately.
- *HPX* Documentation (target `docs`): This target builds the documentation, and is not enabled by default (enable by setting `HPX_WITH_DOCUMENTATION:BOOL=On`. For more information see *Documentation*.

The *HPX* build process is highly configurable through [CMake](#)⁴³, and various [CMake](#)⁴⁴ variables influence the build process. A list with the most important [CMake](#)⁴⁵ variables can be found in the section that follows, while the complete list of available [CMake](#)⁴⁶ variables is in *CMake options*. These variables can be used to refine the recipes that can be found at *Platform specific build recipes*, a section that shows some basic steps on how to build *HPX* for a specific platform.

In order to use *HPX*, only the core libraries are required. In order to use the optional libraries, you need to specify them as link dependencies in your build (See *Creating HPX projects*).

³⁶ <https://code.google.com/p/gperftools>

³⁷ <http://jemalloc.net>

³⁸ <http://microsoft.github.io/mimalloc/>

³⁹ <https://hpx.stellar-group.org/downloads/>

⁴⁰ <https://www.cmake.org>

⁴¹ <https://www.cmake.org/cmake/resources/software.html>

⁴² <https://www.cmake.org>

⁴³ <https://www.cmake.org>

⁴⁴ <https://www.cmake.org>

⁴⁵ <https://www.cmake.org>

⁴⁶ <https://www.cmake.org>

Most important CMake options

While building *HPX*, you are provided with multiple CMake options which correspond to different configurations. Below, there is a set of the most important and frequently used CMake options.

HPX_WITH_MALLOC

Use a custom allocator. Using a custom allocator tuned for multithreaded applications is very important for the performance of *HPX* applications. When debugging applications, it's useful to set this to `system`, as custom allocators can hide some memory-related bugs. Note that setting this to something other than `system` requires an external dependency.

HPX_WITH_CUDA

Enable support for CUDA. Use `CMAKE_CUDA_COMPILER` to set the CUDA compiler. This is a standard CMake⁴⁷ variable, like `CMAKE_CXX_COMPILER`.

HPX_WITH_PARCELPORTR_MPI

Enable the MPI parcellport. This enables the use of MPI for the networking operations in the *HPX* runtime. The default value is `OFF` because it's not available on all systems and/or requires another dependency. However, it is the recommended parcellport.

HPX_WITH_PARCELPORTR_TCP

Enable the TCP parcellport. Enables the use of TCP for networking in the runtime. The default value is `ON`. However, it's only recommended for debugging purposes, as it is slower than the MPI parcellport.

HPX_WITH_PARCELPORTR_LCI

Enable the LCI parcellport. This enables the use of LCI for the networking operations in the *HPX* runtime. The default value is `OFF` because it's not available on all systems and/or requires another dependency. However, this experimental parcellport may provide better performance than the MPI parcellport. Please refer to *Using the LCI parcellport* for more information about the LCI parcellport.

HPX_WITH_APEX

Enable APEX integration. [APEX](https://uo-oaciss.github.io/apex/quickstarthpx/)⁴⁸ can be used to profile *HPX* applications. In particular, it provides information about individual tasks in the *HPX* runtime.

HPX_WITH_GENERIC_CONTEXT_COROUTINES

Enable Boost. Context for task context switching. It must be enabled for non-x86 architectures such as ARM and Power.

HPX_WITH_MAX_CPU_COUNT

Set the maximum CPU count supported by *HPX*. The default value is 64, and should be set to a number at least as high as the number of cores on a system including virtual cores such as hyperthreads.

HPX_WITH_CXX_STANDARD

Set a specific C++ standard version e.g. `HPX_WITH_CXX_STANDARD=23`. The default and minimum value is 20. Possible values are 20, 23, or 26.

HPX_WITH_EXAMPLES

Build examples.

HPX_WITH_TESTS

Build tests.

⁴⁷ <https://www.cmake.org>

⁴⁸ <https://uo-oaciss.github.io/apex/quickstarthpx/>

HPX_WITH_DEBUG_POSTFIX

Set the postfix for debug libraries. The default is `d`. This variable is used to set `CMAKE_DEBUG_POSTFIX` and is only relevant for Debug builds or multi-configuration generators. The default rarely needs to be changed. It ensures that generated debug binaries have a different name than release binaries, which is important to avoid ABI problems when both debug and release binaries are installed on the same system.

For a complete list of available [CMake](#)⁴⁹ variables that influence the build of *HPX*, see *CMake options*.

Build types

[CMake](#)⁵⁰ can be configured to generate project files suitable for builds that have enabled debugging support or for an optimized build (without debugging support). The [CMake](#)⁵¹ variable used to set the build type is `CMAKE_BUILD_TYPE` (for more information see the [CMake Documentation](#)⁵²). Available build types are:

- **Debug:** Full debug symbols are available as well as additional assertions to help debugging. To enable the debug build type for the *HPX* API, the C++ Macro `HPX_DEBUG` is defined.
- **RelWithDebInfo:** Release build with debugging symbols. This is most useful for profiling applications
- **Release:** Release build. This disables assertions and enables default compiler optimizations.
- **RelMinSize:** Release build with optimizations for small binary sizes.

Important: We currently don't guarantee ABI compatibility between Debug and Release builds. Please make sure that applications built against *HPX* use the same build type as you used to build *HPX*. For CMake builds, this means that the `CMAKE_BUILD_TYPE` variables have to match and for projects not using [CMake](#)⁵³, the `HPX_DEBUG` macro has to be set in debug mode.

Using CMake Presets

HPX provides a `CMakePresets.json` file which includes a variety of pre-defined build configurations. These presets allow you to easily configure the build for common scenarios without needing to manually specify multiple CMake variables.

To use a preset, you can use the `--preset` option with CMake:

```
$ cmake --preset <preset-name>
$ cmake --build --preset <preset-name>
```

Some of the available presets include:

- **default:** Standard release build with tests and examples enabled.
- **minimal:** Minimal build with only core features (no tests, examples, or tools).
- **full:** Full build with all standard features enabled.
- **debug:** Debug build with symbols and debug-optimized settings.
- **performance:** Build optimized for performance analysis with APEX profiling.
- **cuda:** Build with CUDA support (requires CUDA toolkit).

⁴⁹ <https://www.cmake.org>

⁵⁰ <https://www.cmake.org>

⁵¹ <https://www.cmake.org>

⁵² https://cmake.org/cmake/help/latest/variable/CMAKE_BUILD_TYPE.html

⁵³ <https://www.cmake.org>

- `sycl`: Build with SYCL support (requires compatible compiler).
- `sanitizer-address`: Build with AddressSanitizer enabled.

For a full list of available presets, you can run:

```
$ cmake --list-presets
```

Platform specific build recipes

Unix variants

Once you have the source code and the dependencies and assuming all your dependencies are in paths known to `CMake`⁵⁴, the following gets you started:

1. First, set up a separate build directory to configure the project:

```
$ mkdir build && cd build
```

2. To configure the project you have the following options:

- To build the core *HPX* libraries and examples, and install them to your chosen location (recommended):

```
$ cmake -DCMAKE_INSTALL_PREFIX=/install/path ..
```

Tip: If you want to change `CMake`⁵⁵ variables for your build, it is usually a good idea to start with a clean build directory to avoid configuration problems. It is especially important that you use a clean build directory when changing between Release and Debug modes.

- To install *HPX* to the default system folders, simply leave out the `CMAKE_INSTALL_PREFIX` option:

```
$ cmake ..
```

- If your dependencies are in custom locations, you may need to tell `CMake`⁵⁶ where to find them by passing one or more options to `CMake`⁵⁷ as shown below:

```
$ cmake -DBoost_ROOT=/path/to/boost
      -DHWloc_ROOT=/path/to/hwloc
      -DTcmalloc_ROOT=/path/to/tcmalloc
      -DJemalloc_ROOT=/path/to/jemalloc
      [other CMake variable definitions]
      /path/to/source/tree
```

For instance:

```
$ cmake -DBoost_ROOT=/packages/boost -DHWloc_ROOT=/packages/hwloc -DCMAKE_
INSTALL_PREFIX=/packages/hpx ~/downloads/hpx_1.5.1
```

- If you want to try *HPX* without using a custom allocator pass `-DHPX_WITH_MALLOC=system` to `CMake`⁵⁸:

⁵⁴ <https://www.cmake.org>

⁵⁵ <https://www.cmake.org>

⁵⁶ <https://www.cmake.org>

⁵⁷ <https://www.cmake.org>

⁵⁸ <https://www.cmake.org>

```
$ cmake -DCMAKE_INSTALL_PREFIX=/install/path -DHPX_WITH_MALLOC=system ..
```

Note: Please pay special attention to the section about *HPX_WITH_MALLOC:STRING* as this is crucial for getting decent performance.

Important: If you are building *HPX* for a system with more than 64 processing units, you must change the *CMake*⁵⁹ variable *HPX_WITH_MAX_CPU_COUNT* (to a value at least as big as the number of (virtual) cores on your system). Note that the default value is 64.

Caution: Compiling and linking *HPX* needs a considerable amount of memory. It is advisable that at least 2 GB of memory per parallel process is available.

3. Once the configuration is complete, to build the project you run:

```
$ cmake --build . --target install
```

Windows

Note: The following build recipes are mostly user-contributed and may be outdated. We always welcome updated and new build recipes.

To build *HPX* under Windows 10 x64 with Visual Studio 2015:

- Download the CMake V3.19 installer (or latest version) from [here](#)⁶⁰
- Download the hwloc V1.11.0 (or the latest version) from [here](#)⁶¹ and unpack it.
- Download the latest Boost libraries from [here](#)⁶² and unpack them.
- Build the Boost DLLs and LIBs by using these commands from Command Line (or PowerShell). Open CMD/PowerShell inside the Boost dir and type in:

```
.\bootstrap.bat
```

This batch file will set up everything needed to create a successful build. Now execute:

```
.\b2.exe link=shared variant=release,debug architecture=x86 address-model=64  
↪threading=multi --build-type=complete install
```

This command will start a (very long) build of all available Boost libraries. Please, be patient.

- Open CMake-GUI.exe and set up your source directory (input field 'Where is the source code') to the *base directory* of the source code you downloaded from *HPX*'s GitHub pages. Here's an example of CMake path settings, which point to the Documents/GitHub/hpx folder:

⁵⁹ <https://www.cmake.org>

⁶⁰ <https://blog.kitware.com/cmake-3-19-0-available-for-download/>

⁶¹ <https://www.open-mpi.org/software/hwloc/v2.11/>

⁶² <https://www.boost.org/users/download/>




Fig. 2.3: Example CMake path settings.

Inside ‘Where is the source-code’ enter the base directory of your *HPX* source directory (do not enter the “src” sub-directory!). Inside ‘Where to build the binaries’ you should put in the path where all the building processes will happen. This is important because the building machinery will do an “out-of-tree” build. CMake will not touch or change the original source files in any way. Instead, it will generate Visual Studio Solution Files, which will build *HPX* packages out of the *HPX* source tree.

- Set new configuration variables (in CMake, not in Windows environment): Boost_ROOT, Hwloc_ROOT, Asio_ROOT, CMAKE_INSTALL_PREFIX. The meaning of these variables is as follows:
 - Boost_ROOT the *HPX* root directory of the unpacked Boost headers/cpp files.
 - Hwloc_ROOT the *HPX* root directory of the unpacked Portable Hardware Locality files.
 - Asio_ROOT the *HPX* root directory of the unpacked ASIO files. Alternatively use HPX_WITH_FETCH_ASIO with value True.
 - CMAKE_INSTALL_PREFIX the *HPX* root directory where the future builds of *HPX* should be installed.

Note: *HPX* is a very large software collection, so it is not recommended to use the default C:\Program Files\hpx. Many users may prefer to use simpler paths *without* whitespace, like C:\bin\hpx or D:\bin\hpx etc.

To insert new env-vars click on “Add Entry” and then insert the name inside “Name”, select PATH as Type and put the path-name in the “Path” text field. Repeat this for the first three variables.

This is how variable insertion will look:




Fig. 2.4: Example CMake adding entry.

Alternatively, users could provide `Boost_LIBRARYDIR` instead of `Boost_ROOT`; the difference is that `Boost_LIBRARYDIR` should point to the subdirectory inside Boost root where all the compiled DLLs/LIBs are. For example, `Boost_LIBRARYDIR` may point to the `bin.v2` subdirectory under the Boost rootdir. It is important to keep the meanings of these two variables separated from each other: `Boost_DIR` points to the ROOT folder of the Boost library. `Boost_LIBRARYDIR` points to the subdir inside the Boost root folder where the compiled binaries are.

- Click the ‘Configure’ button of CMake-GUI. You will be immediately presented with a small window where you can select the C++ compiler to be used within Visual Studio. This has been tested using the latest v14 (a.k.a C++ 2015) but older versions should be sufficient too. Make sure to select the 64Bit compiler.
- After the generate process has finished successfully, click the ‘Generate’ button. Now, CMake will put new VS Solution files into the BUILD folder you selected at the beginning.
- Open Visual Studio and load the `HPX.sln` from your build folder.
- Go to `CMakePredefinedTargets` and build the `INSTALL` project:





Fig. 2.5: Visual Studio `INSTALL` target.

It will take some time to compile everything, and in the end you should see an output similar to this one:

2.4.4 CMake options

In order to configure *HPX*, you can set a variety of options to allow CMake to generate your specific makefiles/project files. A list of the most important CMake options can be found in *Most important CMake options*, while this section includes the comprehensive list.



```
Output
Show output from: Build
116> -- Installing: C:/bin/HPX/bin/1d_stencil_2.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_3.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_4.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_4_parallel.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_5.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_6.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_7.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_8.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_1_omp.exe
116> -- Installing: C:/bin/HPX/bin/1d_stencil_3_omp.exe
116> -- Installing: C:/bin/HPX/bin/simple_central_tuplespace_client.exe
116> -- Installing: C:/bin/HPX/lib/hpx_simple_central_tuplespaced.lib
116> -- Installing: C:/bin/HPX/lib/hpx_simple_central_tuplespaced.dll
116> -- Installing: C:/bin/HPX/bin/transpose_serial.exe
116> -- Installing: C:/bin/HPX/bin/transpose_serial_block.exe
116> -- Installing: C:/bin/HPX/bin/transpose_smp.exe
116> -- Installing: C:/bin/HPX/bin/transpose_smp_block.exe
116> -- Installing: C:/bin/HPX/bin/transpose_block.exe
116> -- Installing: C:/bin/HPX/bin/transpose_serial_vector.exe
116> -- Installing: C:/bin/HPX/bin/hpx_runtime.exe
===== Build: 116 succeeded, 0 failed, 0 up-to-date, 0 skipped =====
```

Fig. 2.6: Visual Studio build output.

Variables that influence how *HPX* is built

The options are split into these categories:

- *Generic options*
- *Build Targets options*
- *Thread Manager options*
- *AGAS options*
- *Parcelport options*
- *Profiling options*
- *Debugging options*
- *Modules options*

Generic options

- `HPX_WITH_AUTOMATIC_SERIALIZATION_REGISTRATION:BOOL`
- `HPX_WITH_BUILD_BINARY_PACKAGE:BOOL`
- `HPX_WITH_CHECK_MODULE_DEPENDENCIES:BOOL`
- `HPX_WITH_COMPILER_WARNINGS:BOOL`
- `HPX_WITH_COMPILER_WARNINGS_AS_ERRORS:BOOL`
- `HPX_WITH_COMPRESSION_BZIP2:BOOL`
- `HPX_WITH_COMPRESSION_SNAPPY:BOOL`
- `HPX_WITH_COMPRESSION_ZLIB:BOOL`
- `HPX_WITH_CONTRACTS_MODE:STRING`
- `HPX_WITH_CUDA:BOOL`
- `HPX_WITH_CXX20_STD_EXECUTION_POLICES:INTERNAL`
- `HPX_WITH_CXX_MODULES:BOOL`
- `HPX_WITH_CXX_STANDARD:STRING`
- `HPX_WITH_DATAPAR_BACKEND:STRING`
- `HPX_WITH_DEPRECATION_WARNINGS:BOOL`
- `HPX_WITH_DISABLED_SIGNAL_EXCEPTION_HANDLERS:BOOL`
- `HPX_WITH_DYNAMIC_HPX_MAIN:BOOL`
- `HPX_WITH_FAULT_TOLERANCE:BOOL`
- `HPX_WITH_FULL_RPATH:BOOL`
- `HPX_WITH_GCC_VERSION_CHECK:BOOL`
- `HPX_WITH_GENERIC_CONTEXT_COROUTINES:BOOL`
- `HPX_WITH_GIT_HOOKS:BOOL`
- `HPX_WITH_HIDDEN_VISIBILITY:BOOL`
- `HPX_WITH_HIP:BOOL`
- `HPX_WITH_HIPSYCL:BOOL`
- `HPX_WITH_IGNORE_COMPILER_COMPATIBILITY:BOOL`
- `HPX_WITH_LOGGING:BOOL`
- `HPX_WITH_MALLOC:STRING`
- `HPX_WITH_MODULES_AS_STATIC_LIBRARIES:BOOL`
- `HPX_WITH_MODULE_COMPATIBILITY_HEADERS:BOOL`
- `HPX_WITH_NICE_THREADLEVEL:BOOL`
- `HPX_WITH_PARCEL_COALESCING:BOOL`
- `HPX_WITH_PKGCONFIG:BOOL`
- `HPX_WITH_PRECOMPILED_HEADERS:BOOL`
- `HPX_WITH_PSEUDO_DEPENDENCIES:BOOL`

- `HPX_WITH_RUN_MAIN_EVERYWHERE:BOOL`
- `HPX_WITH_STACKOVERFLOW_DETECTION:BOOL`
- `HPX_WITH_STATIC_LINKING:BOOL`
- `HPX_WITH_SUPPORT_NO_UNIQUE_ADDRESS_ATTRIBUTE:BOOL`
- `HPX_WITH_SYCL:BOOL`
- `HPX_WITH_SYCL_FLAGS:STRING`
- `HPX_WITH_UNITY_BUILD:BOOL`
- `HPX_WITH_VIM_YCM:BOOL`
- `HPX_WITH_ZERO_COPY_SERIALIZATION_THRESHOLD:STRING`

HPX_WITH_AUTOMATIC_SERIALIZATION_REGISTRATION:BOOL

Use automatic serialization registration for actions and functions. This affects compatibility between HPX applications compiled with different compilers (default ON)

HPX_WITH_BUILD_BINARY_PACKAGE:BOOL

Build HPX on the build infrastructure on any LINUX distribution (default: OFF).

HPX_WITH_CHECK_MODULE_DEPENDENCIES:BOOL

Verify that no modules are cross-referenced from a different module category (default: OFF)

HPX_WITH_COMPILER_WARNINGS:BOOL

Enable compiler warnings (default: ON)

HPX_WITH_COMPILER_WARNINGS_AS_ERRORS:BOOL

Turn compiler warnings into errors (default: OFF)

HPX_WITH_COMPRESSION_BZIP2:BOOL

Enable bzip2 compression for parcel data (default: OFF).

HPX_WITH_COMPRESSION_SNAPPY:BOOL

Enable snappy compression for parcel data (default: OFF).

HPX_WITH_COMPRESSION_ZLIB:BOOL

Enable zlib compression for parcel data (default: OFF).

HPX_WITH_CONTRACTS_MODE:STRING

Contract evaluation mode for pre-C++26 compilers, options are: ENFORCE, QUICK_ENFORCE, OBSERVE, IGNORE

HPX_WITH_CUDA:BOOL

Enable support for CUDA (default: OFF)

HPX_WITH_CXX20_STD_EXECUTION_POLICES:INTERNAL**HPX_WITH_CXX_MODULES:BOOL**

Enable exposing C++20 modules (default: OFF).

HPX_WITH_CXX_STANDARD:STRING

Set the C++ standard to use when compiling HPX itself. (default: 20)

HPX_WITH_DATAPAR_BACKEND:STRING

Define which vectorization library should be used. Options are: VC, EVE, STD_EXPERIMENTAL_SIMD, SVE, EMULATE, NONE

HPX_WITH_DEPRECATED_WARNINGS:BOOL

Enable warnings for deprecated facilities (default: ON).

HPX_WITH_DISABLED_SIGNAL_EXCEPTION_HANDLERS:BOOL

Disables the mechanism that produces debug output for caught signals and unhandled exceptions (default: OFF)

HPX_WITH_DYNAMIC_HPX_MAIN:BOOL

Enable dynamic overload of system main() (Linux and Apple only, default: ON)

HPX_WITH_FAULT_TOLERANCE:BOOL

Build HPX to tolerate failures of nodes, i.e. ignore errors in active communication channels (default: OFF)

HPX_WITH_FULL_RPATH:BOOL

Build and link HPX libraries and executables with full RPATHs (default: ON)

HPX_WITH_GCC_VERSION_CHECK:BOOL

Don't ignore version reported by gcc (default: ON)

HPX_WITH_GENERIC_CONTEXT_COROUTINES:BOOL

Use Boost.Context as the underlying coroutines context switch implementation.

HPX_WITH_GIT_HOOKS:BOOL

Enable git commit hooks for formatting checks on commit (default: OFF).

HPX_WITH_HIDDEN_VISIBILITY:BOOL

Use -fvisibility=hidden for builds on platforms which support it (default OFF)

HPX_WITH_HIP:BOOL

Enable compilation with HIPCC (default: OFF)

HPX_WITH_HIPSYCL:BOOL

Use hipsycl cmake integration (default: OFF)

HPX_WITH_IGNORE_COMPILER_COMPATIBILITY:BOOL

Ignore compiler incompatibility in dependent projects (default: ON).

HPX_WITH_LOGGING:BOOL

Build HPX with logging enabled (default: ON).

HPX_WITH_MALLOC:STRING

Define which allocator should be linked in. Options are: system, tcmalloc, jemalloc, mimalloc, tbbmalloc, and custom (default is: tcmalloc)

HPX_WITH_MODULES_AS_STATIC_LIBRARIES:BOOL

Compile HPX modules as STATIC (whole-archive) libraries instead of OBJECT libraries (Default: ON)

HPX_WITH_MODULE_COMPATIBILITY_HEADERS:BOOL

Generate backwards-compatibility headers for HPX Modules (default: OFF)

HPX_WITH_NICE_THREADLEVEL:BOOL

Set HPX worker threads to have high NICE level (may impact performance) (default: OFF)

HPX_WITH_PARCEL_COALESCING:BOOL

Enable the parcel coalescing plugin (default: ON).

HPX_WITH_PKGCONFIG:BOOL

Enable generation of pkgconfig files (default: ON on Linux without CUDA/HIP, otherwise OFF)

HPX_WITH_PRECOMPILED_HEADERS:BOOL

Enable precompiled headers for certain build targets (experimental) (default OFF)

HPX_WITH_PSEUDO_DEPENDENCIES:BOOL

Turn compiler warnings into errors (default: ON)

HPX_WITH_RUN_MAIN_EVERYWHERE:BOOL

Run hpx_main by default on all localities (default: OFF, deprecated, will be removed).

HPX_WITH_STACKOVERFLOW_DETECTION:BOOL

Enable stackoverflow detection for HPX threads/coroutines (default: OFF, debug: ON).

HPX_WITH_STATIC_LINKING:BOOL

Compile HPX statically linked libraries (Default: OFF)

HPX_WITH_SUPPORT_NO_UNIQUE_ADDRESS_ATTRIBUTE:BOOL

Enable the use of the `[[no_unique_address]]` attribute (default: ON)

HPX_WITH_SYCL:BOOL

Enable support for Sycl (default: OFF)

HPX_WITH_SYCL_FLAGS:STRING

Sycl compile flags for selecting specific targets (default: empty)

HPX_WITH_UNITY_BUILD:BOOL

Enable unity build for certain build targets (default OFF)

HPX_WITH_VIM_YCM:BOOL

Generate HPX completion file for VIM YouCompleteMe plugin

HPX_WITH_ZERO_COPY_SERIALIZATION_THRESHOLD:STRING

The threshold in bytes to when perform zero copy optimizations (default: 8192)

Build Targets options

- *HPX_WITH_ASIO_TAG:STRING*
- *HPX_WITH_COMPILE_ONLY_TESTS:BOOL*
- *HPX_WITH_DISTRIBUTED_RUNTIME:BOOL*
- *HPX_WITH_DOCUMENTATION:BOOL*
- *HPX_WITH_DOCUMENTATION_OUTPUT_FORMATS:STRING*
- *HPX_WITH_EXAMPLES:BOOL*
- *HPX_WITH_EXAMPLES_HDF5:BOOL*
- *HPX_WITH_EXAMPLES_OPENMP:BOOL*
- *HPX_WITH_EXAMPLES_QT4:BOOL*
- *HPX_WITH_EXAMPLES_QTHREADS:BOOL*
- *HPX_WITH_EXAMPLES_TASKBENCH:BOOL*
- *HPX_WITH_EXAMPLES_TBB:BOOL*
- *HPX_WITH_EXECUTABLE_PREFIX:STRING*
- *HPX_WITH_FAIL_COMPILE_TESTS:BOOL*

- *HPX_WITH_FETCH_APEX:BOOL*
- *HPX_WITH_FETCH_ASIO:BOOL*
- *HPX_WITH_FETCH_BOOST:BOOL*
- *HPX_WITH_FETCH_GASNET:BOOL*
- *HPX_WITH_FETCH_HWLOC:BOOL*
- *HPX_WITH_FETCH_LCI:BOOL*
- *HPX_WITH_FETCH_LCW:BOOL*
- *HPX_WITH_IO_COUNTERS:BOOL*
- *HPX_WITH_LCI_BOOTSTRAP_MPI:BOOL*
- *HPX_WITH_LCI_TAG:STRING*
- *HPX_WITH_LCW_TAG:STRING*
- *HPX_WITH_NANOBENCH:BOOL*
- *HPX_WITH_PARALLEL_LINK_JOBS:STRING*
- *HPX_WITH_TESTS:BOOL*
- *HPX_WITH_TESTS_BENCHMARKS:BOOL*
- *HPX_WITH_TESTS_EXAMPLES:BOOL*
- *HPX_WITH_TESTS_EXTERNAL_BUILD:BOOL*
- *HPX_WITH_TESTS_HEADERS:BOOL*
- *HPX_WITH_TESTS_REGRESSIONS:BOOL*
- *HPX_WITH_TESTS_UNIT:BOOL*
- *HPX_WITH_THRUST:BOOL*
- *HPX_WITH_TOOLS:BOOL*

HPX_WITH_ASIO_TAG:STRING

Asio repository tag or branch

HPX_WITH_COMPILE_ONLY_TESTS:BOOL

Create build system support for compile time only HPX tests (default ON)

HPX_WITH_DISTRIBUTED_RUNTIME:BOOL

Enable the distributed runtime (default: ON). Turning off the distributed runtime completely disallows the creation and use of components and actions. Turning this option off is experimental!

HPX_WITH_DOCUMENTATION:BOOL

Build the HPX documentation (default OFF).

HPX_WITH_DOCUMENTATION_OUTPUT_FORMATS:STRING

List of documentation output formats to generate. Valid options are `html;singlehtml;latexpdf;man`. Multiple values can be separated with semicolons. (default `html`).

HPX_WITH_EXAMPLES:BOOL

Build the HPX examples (default ON)

HPX_WITH_EXAMPLES_HDF5:BOOL

Enable examples requiring HDF5 support (default: OFF).

HPX_WITH_EXAMPLES_OPENMP:BOOL

Enable examples requiring OpenMP support (default: OFF).

HPX_WITH_EXAMPLES_QT4:BOOL

Enable examples requiring Qt4 support (default: OFF).

HPX_WITH_EXAMPLES_QTHREADS:BOOL

Enable examples requiring QThreads support (default: OFF).

HPX_WITH_EXAMPLES_TASKBENCH:BOOL

Enable the task-bench example (fetched from upstream StanfordLegion/task-bench, default: OFF).

HPX_WITH_EXAMPLES_TBB:BOOL

Enable examples requiring TBB support (default: OFF).

HPX_WITH_EXECUTABLE_PREFIX:STRING

Executable prefix (default none), **‘hpx_’** useful for system install.

HPX_WITH_FAIL_COMPILE_TESTS:BOOL

Create build system support for fail compile HPX tests (default ON)

HPX_WITH_FETCH_APEX:BOOL

Use FetchContent to fetch APEX. By default an installed APEX will be used. (default: OFF)

HPX_WITH_FETCH_ASIO:BOOL

Use FetchContent to fetch Asio. By default an installed Asio will be used. (default: OFF)

HPX_WITH_FETCH_BOOST:BOOL

Use FetchContent to fetch Boost. By default an installed Boost will be used. (default: OFF)

HPX_WITH_FETCH_GASNET:BOOL

Use FetchContent to fetch GASNET. By default an installed GASNET will be used. (default: OFF).

HPX_WITH_FETCH_HWLOC:BOOL

Use FetchContent to fetch Hwloc. By default an installed Hwloc will be used. (default: OFF)

HPX_WITH_FETCH_LCI:BOOL

Use FetchContent to fetch LCI. By default an installed LCI will be used. (default: OFF)

HPX_WITH_FETCH_LCW:BOOL

Use FetchContent to fetch LCW. By default an installed LCW will be used. (default: OFF)

HPX_WITH_IO_COUNTERS:BOOL

Enable IO counters (default: ON)

HPX_WITH_LCI_BOOTSTRAP_MPI:BOOL

Configure the autofetched LCI with mpi bootstrap support (default: OFF)

HPX_WITH_LCI_TAG:STRING

LCI repository tag or branch

HPX_WITH_LCW_TAG:STRING

LCW repository tag or branch

HPX_WITH_NANOBENCH:BOOL

Use Nanobench for performance tests. Nanobench will be fetched using FetchContent (default: OFF)

HPX_WITH_PARALLEL_LINK_JOBS:STRING

Number of Parallel link jobs while building hpx (only for Ninja as generator) (default 2)

HPX_WITH_TESTS:BOOL

Build the HPX tests (default ON)

HPX_WITH_TESTS_BENCHMARKS:BOOL

Build HPX benchmark tests (default: ON)

HPX_WITH_TESTS_EXAMPLES:BOOL

Add HPX examples as tests (default: ON)

HPX_WITH_TESTS_EXTERNAL_BUILD:BOOL

Build external cmake build tests (default: ON)

HPX_WITH_TESTS_HEADERS:BOOL

Build HPX header tests (default: OFF)

HPX_WITH_TESTS_REGRESSIONS:BOOL

Build HPX regression tests (default: ON)

HPX_WITH_TESTS_UNIT:BOOL

Build HPX unit tests (default: ON)

HPX_WITH_THRUST:BOOL

Enable support for NVIDIA Thrust integration (default: ON when CUDA is enabled, OFF otherwise)

HPX_WITH_TOOLS:BOOL

Build HPX tools (default: OFF)

Thread Manager options

- *HPX_COROUTINES_WITH_SWAP_CONTEXT_EMULATION:BOOL*
- *HPX_COROUTINES_WITH_THREAD_SCHEDULE_HINT_RUNS_AS_CHILD:BOOL*
- *HPX_WITH_COROUTINE_COUNTERS:BOOL*
- *HPX_WITH_IO_POOL:BOOL*
- *HPX_WITH_MAX_CPU_COUNT:STRING*
- *HPX_WITH_MAX_NUMA_DOMAIN_COUNT:STRING*
- *HPX_WITH_SCHEDULER_LOCAL_STORAGE:BOOL*
- *HPX_WITH_SPINLOCK_DEADLOCK_DETECTION:BOOL*
- *HPX_WITH_SPINLOCK_POOL_NUM:STRING*
- *HPX_WITH_STACKTRACES:BOOL*
- *HPX_WITH_STACKTRACES_DEMANGLE_SYMBOLS:BOOL*
- *HPX_WITH_STACKTRACES_STATIC_SYMBOLS:BOOL*
- *HPX_WITH_THREAD_BACKTRACE_DEPTH:STRING*
- *HPX_WITH_THREAD_BACKTRACE_ON_SUSPENSION:BOOL*
- *HPX_WITH_THREAD_CREATION_AND_CLEANUP_RATES:BOOL*
- *HPX_WITH_THREAD_CUMULATIVE_COUNTS:BOOL*

- `HPX_WITH_THREAD_IDLE_RATES:BOOL`
- `HPX_WITH_THREAD_LOCAL_STORAGE:BOOL`
- `HPX_WITH_THREAD_MANAGER_IDLE_BACKOFF:BOOL`
- `HPX_WITH_THREAD_QUEUE_WAITTIME:BOOL`
- `HPX_WITH_THREAD_STACK_MMAP:BOOL`
- `HPX_WITH_THREAD_STEALING_COUNTS:BOOL`
- `HPX_WITH_THREAD_TARGET_ADDRESS:BOOL`
- `HPX_WITH_TIMER_POOL:BOOL`
- `HPX_WITH_WORK_REQUESTING_SCHEDULERS:BOOL`

HPX_COROUTINES_WITH_SWAP_CONTEXT_EMULATION:BOOL

Emulate SwapContext API for coroutines (Windows only, default: OFF)

HPX_COROUTINES_WITH_THREAD_SCHEDULE_HINT_RUNS_AS_CHILD:BOOL

Futures attempt to run associated threads directly if those have not been started (default: OFF)

HPX_WITH_COROUTINE_COUNTERS:BOOL

Enable keeping track of coroutine creation and rebind counts (default: OFF)

HPX_WITH_IO_POOL:BOOL

Disable internal IO thread pool, do not change if not absolutely necessary (default: ON)

HPX_WITH_MAX_CPU_COUNT:STRING

HPX applications will not use more that this number of OS-Threads (empty string means dynamic) (default: "")

HPX_WITH_MAX_NUMA_DOMAIN_COUNT:STRING

HPX applications will not run on machines with more NUMA domains (default: 8)

HPX_WITH_SCHEDULER_LOCAL_STORAGE:BOOL

Enable scheduler local storage for all HPX schedulers (default: OFF)

HPX_WITH_SPINLOCK_DEADLOCK_DETECTION:BOOL

Enable spinlock deadlock detection (default: OFF)

HPX_WITH_SPINLOCK_POOL_NUM:STRING

Number of elements a spinlock pool manages (default: 128)

HPX_WITH_STACKTRACES:BOOL

Attach backtraces to HPX exceptions (default: ON)

HPX_WITH_STACKTRACES_DEMANGLE_SYMBOLS:BOOL

Thread stack back trace symbols will be demangled (default: ON)

HPX_WITH_STACKTRACES_STATIC_SYMBOLS:BOOL

Thread stack back trace will resolve static symbols (default: OFF)

HPX_WITH_THREAD_BACKTRACE_DEPTH:STRING

Thread stack back trace depth being captured (default: 20)

HPX_WITH_THREAD_BACKTRACE_ON_SUSPENSION:BOOL

Enable thread stack back trace being captured on suspension (default: OFF)

HPX_WITH_THREAD_CREATION_AND_CLEANUP_RATES:BOOL

Enable measuring thread creation and cleanup times (default: OFF)

HPX_WITH_THREAD_CUMULATIVE_COUNTS:BOOL

Enable keeping track of cumulative thread counts in the schedulers (default: ON)

HPX_WITH_THREAD_IDLE_RATES:BOOL

Enable measuring the percentage of overhead times spent in the scheduler (default: OFF)

HPX_WITH_THREAD_LOCAL_STORAGE:BOOL

Enable thread local storage for all HPX threads (default: OFF)

HPX_WITH_THREAD_MANAGER_IDLE_BACKOFF:BOOL

HPX scheduler threads do exponential backoff on idle queues (default: ON)

HPX_WITH_THREAD_QUEUE_WAITTIME:BOOL

Enable collecting queue wait times for threads (default: OFF)

HPX_WITH_THREAD_STACK_MMAP:BOOL

Use mmap for stack allocation on appropriate platforms

HPX_WITH_THREAD_STEALING_COUNTS:BOOL

Enable keeping track of counts of thread stealing incidents in the schedulers (default: OFF)

HPX_WITH_THREAD_TARGET_ADDRESS:BOOL

Enable storing target address in thread for NUMA awareness (default: OFF)

HPX_WITH_TIMER_POOL:BOOL

Disable internal timer thread pool, do not change if not absolutely necessary (default: ON)

HPX_WITH_WORK_REQUESTING_SCHEDULERS:BOOL

Enable work requesting scheduler (default: ON)

AGAS options

- *HPX_WITH_AGAS_DUMP_REFCNT_ENTRIES:BOOL*

HPX_WITH_AGAS_DUMP_REFCNT_ENTRIES:BOOL

Enable dumps of the AGAS refcnt tables to logs (default: OFF)

Parcelport options

- *HPX_WITH_NETWORKING:BOOL*
- *HPX_WITH_PARCELPART_ACTION_COUNTERS:BOOL*
- *HPX_WITH_PARCELPART_COUNTERS:BOOL*
- *HPX_WITH_PARCELPART_GASNET:BOOL*
- *HPX_WITH_PARCELPART_LCI:BOOL*
- *HPX_WITH_PARCELPART_LCI_LOG:STRING*
- *HPX_WITH_PARCELPART_LCI_PCOUNTER:STRING*
- *HPX_WITH_PARCELPART_LCW:BOOL*
- *HPX_WITH_PARCELPART_LCW_LOG:STRING*

- *HPX_WITH_PARCELPOR_T_LCW_P_COUNTER:STRING*
- *HPX_WITH_PARCELPOR_T_LIBFABRIC:BOOL*
- *HPX_WITH_PARCELPOR_T_MPI:BOOL*
- *HPX_WITH_PARCELPOR_T_TCP:BOOL*
- *HPX_WITH_PARCEL_PROFILING:BOOL*

HPX_WITH_NETWORKING:BOOL

Enable support for networking and multi-node runs (default: ON)

HPX_WITH_PARCELPOR_T_ACTION_COUNTERS:BOOL

Enable performance counters reporting parcellport statistics on a per-action basis.

HPX_WITH_PARCELPOR_T_COUNTERS:BOOL

Enable performance counters reporting parcellport statistics.

HPX_WITH_PARCELPOR_T_GASNET:BOOL

Enable the GASNET based parcellport.

HPX_WITH_PARCELPOR_T_LCI:BOOL

Enable the LCI based parcellport.

HPX_WITH_PARCELPOR_T_LCI_LOG:STRING

Enable the LCI-parcellport-specific logger

HPX_WITH_PARCELPOR_T_LCI_P_CCOUNTER:STRING

Enable the LCI-parcellport-specific performance counter

HPX_WITH_PARCELPOR_T_LCW:BOOL

Enable the LCW based parcellport.

HPX_WITH_PARCELPOR_T_LCW_LOG:STRING

Enable the LCW-parcellport-specific logger

HPX_WITH_PARCELPOR_T_LCW_P_CCOUNTER:STRING

Enable the LCW-parcellport-specific performance counter

HPX_WITH_PARCELPOR_T_LIBFABRIC:BOOL

Enable the libfabric based parcellport. This is currently an experimental feature

HPX_WITH_PARCELPOR_T_MPI:BOOL

Enable the MPI based parcellport.

HPX_WITH_PARCELPOR_T_TCP:BOOL

Enable the TCP based parcellport.

HPX_WITH_PARCEL_PROFILING:BOOL

Enable profiling data for parcels

Profiling options

- *HPX_LIKWID_WITH_LIKWID:BOOL*
- *HPX_WITH_APEX:BOOL*
- *HPX_WITH_ITTNOTIFY:BOOL*
- *HPX_WITH_PAPI:BOOL*
- *HPX_WITH_TRACY:BOOL*

HPX_LIKWID_WITH_LIKWID:BOOL

Enable Likwid instrumentation support.

HPX_WITH_APEX:BOOL

Enable APEX instrumentation support.

HPX_WITH_ITTNOTIFY:BOOL

Enable Amplifier (ITT) instrumentation support.

HPX_WITH_PAPI:BOOL

Enable the PAPI based performance counter.

HPX_WITH_TRACY:BOOL

Enable Tracy instrumentation support.

Debugging options

- *HPX_WITH_ASSERTS_AS_CONTRACT_ASSERTS:BOOL*
- *HPX_WITH_ATTACH_DEBUGGER_ON_TEST_FAILURE:BOOL*
- *HPX_WITH_CONTRACTS:BOOL*
- *HPX_WITH_PARALLEL_TESTS_BIND_NONE:BOOL*
- *HPX_WITH_SANITIZERS:BOOL*
- *HPX_WITH_TESTS_COMMAND_LINE:STRING*
- *HPX_WITH_TESTS_DEBUG_LOG:BOOL*
- *HPX_WITH_TESTS_DEBUG_LOG_DESTINATION:STRING*
- *HPX_WITH_TESTS_MAX_THREADS_PER_LOCALITY:STRING*
- *HPX_WITH_THREAD_DEBUG_INFO:BOOL*
- *HPX_WITH_THREAD_DESCRIPTION_FULL:BOOL*
- *HPX_WITH_THREAD_GUARD_PAGE:BOOL*
- *HPX_WITH_VALGRIND:BOOL*
- *HPX_WITH_VERIFY_LOCKS:BOOL*
- *HPX_WITH_VERIFY_LOCKS_BACKTRACE:BOOL*

HPX_WITH_ASSERTS_AS_CONTRACT_ASSERTS:BOOL

Swap `hpx_assert` with `hpx_contract_assert`

HPX_WITH_ATTACH_DEBUGGER_ON_TEST_FAILURE:BOOL

Break the debugger if a test has failed (default: OFF)

HPX_WITH_CONTRACTS:BOOL

Enable C++ contracts support in HPX

HPX_WITH_PARALLEL_TESTS_BIND_NONE:BOOL

Pass `-hpx:bind=none` to tests that may run in parallel (cmake `-j` flag) (default: OFF)

HPX_WITH_SANITIZERS:BOOL

Configure with sanitizer instrumentation support.

HPX_WITH_TESTS_COMMAND_LINE:STRING

Add given command line options to all tests run

HPX_WITH_TESTS_DEBUG_LOG:BOOL

Turn on debug logs (`-hpx:debug-hpx-log`) for tests (default: OFF)

HPX_WITH_TESTS_DEBUG_LOG_DESTINATION:STRING

Destination for test debug logs (default: `cout`)

HPX_WITH_TESTS_MAX_THREADS_PER_LOCALITY:STRING

Maximum number of threads to use for tests (default: 0, use the number of threads specified by the test)

HPX_WITH_THREAD_DEBUG_INFO:BOOL

Enable thread debugging information (default: OFF, implicitly enabled in debug builds)

HPX_WITH_THREAD_DESCRIPTION_FULL:BOOL

Use function address for thread description (default: OFF)

HPX_WITH_THREAD_GUARD_PAGE:BOOL

Enable thread guard page (default: ON)

HPX_WITH_VALGRIND:BOOL

Enable Valgrind instrumentation support.

HPX_WITH_VERIFY_LOCKS:BOOL

Enable lock verification code (default: OFF, enabled in debug builds)

HPX_WITH_VERIFY_LOCKS_BACKTRACE:BOOL

Enable thread stack back trace being captured on lock registration (to be used in combination with `HPX_WITH_VERIFY_LOCKS=ON`, default: OFF)

Modules options

- *HPX_ALLOCATOR_SUPPORT_WITH_CACHING:BOOL*
- *HPX_COMMAND_LINE_HANDLING_LOCAL_WITH_JSON_CONFIGURATION_FILES:BOOL*
- *HPX_DATASTRUCTURES_WITH_ADAPT_STD_TUPLE:BOOL*
- *HPX_DATASTRUCTURES_WITH_ADAPT_STD_VARIANT:BOOL*
- *HPX_FILESYSTEM_WITH_BOOST_FILESYSTEM_COMPATIBILITY:BOOL*
- *HPX_FUNCTIONAL_WITH_BOOST_PLACEHOLDERS:BOOL*
- *HPX_IOSTREAM_WITH_WIDE_STREAMS:BOOL*
- *HPX_ITERATOR_SUPPORT_WITH_BOOST_ITERATOR_TRAVERSAL_TAG_COMPATIBILITY:BOOL*

- *HPX_LOGGING_WITH_SEPARATE_DESTINATIONS:BOOL*
- *HPX_SERIALIZATION_WITH_ALLOW_CONST_TUPLE_MEMBERS:BOOL*
- *HPX_SERIALIZATION_WITH_ALLOW_RAW_POINTER_SERIALIZATION:BOOL*
- *HPX_SERIALIZATION_WITH_ALL_TYPES_ARE_BITWISE_SERIALIZABLE:BOOL*
- *HPX_SERIALIZATION_WITH_BOOST_TYPES:BOOL*
- *HPX_SERIALIZATION_WITH_SUPPORTS_ENDIANESS:BOOL*
- *HPX_TOPOLOGY_WITH_ADDITIONAL_HWLOC_TESTING:BOOL*
- *HPX_WITH_POWER_COUNTER:BOOL*
- *HPX_WITH_SUPERVISION:BOOL*

HPX_ALLOCATOR_SUPPORT_WITH_CACHING:BOOL

Enable caching allocator. (default: ON)

HPX_COMMAND_LINE_HANDLING_LOCAL_WITH_JSON_CONFIGURATION_FILES:BOOL

Enable reading JSON formatted configuration files on the command line.

(default: OFF)

HPX_DATASTRUCTURES_WITH_ADAPT_STD_TUPLE:BOOL

Enable compatibility of `hpx::get` with `std::tuple`. (default: ON)

HPX_DATASTRUCTURES_WITH_ADAPT_STD_VARIANT:BOOL

Enable compatibility of `hpx::get` with `std::variant`.

(default: OFF)

HPX_FILESYSTEM_WITH_BOOST_FILESYSTEM_COMPATIBILITY:BOOL

Enable `Boost.FileSystem` compatibility. (default: OFF)

HPX_FUNCTIONAL_WITH_BOOST_PLACEHOLDERS:BOOL

Enable support for Boost placeholder types. (default: OFF)

HPX_IOSTREAM_WITH_WIDE_STREAMS:BOOL

Enable wide IO streams. (default: OFF)

HPX_ITERATOR_SUPPORT_WITH_BOOST_ITERATOR_TRAVERSAL_TAG_COMPATIBILITY:BOOL

Enable `Boost.Iterator` traversal tag compatibility. (default: OFF)

HPX_LOGGING_WITH_SEPARATE_DESTINATIONS:BOOL

Enable separate logging channels for AGAS, timing, and parcel transport. (default: ON)

HPX_SERIALIZATION_WITH_ALLOW_CONST_TUPLE_MEMBERS:BOOL

Enable serializing `std::tuple` with `const` members. (default: OFF)

HPX_SERIALIZATION_WITH_ALLOW_RAW_POINTER_SERIALIZATION:BOOL

Enable serializing raw pointers. (default: OFF)

HPX_SERIALIZATION_WITH_ALL_TYPES_ARE_BITWISE_SERIALIZABLE:BOOL

Assume all types are bitwise serializable. (default: OFF)

HPX_SERIALIZATION_WITH_BOOST_TYPES:BOOL

Enable serialization of certain Boost types. (default: OFF)

HPX_SERIALIZATION_WITH_SUPPORTS_ENDIANESS:BOOL

Support endian conversion on inout and output archives. (default: OFF)

HPX_TOPOLOGY_WITH_ADDITIONAL_HWLOC_TESTING:BOOL

Enable HWLOC filtering that makes it report no cores, this is purely an option supporting better testing - do not enable under normal circumstances. (default: OFF)

HPX_WITH_POWER_COUNTER:BOOL

Enable use of performance counters based on pwr library (default: OFF)

HPX_WITH_SUPERVISION:BOOL

Enable supervision functionalities. (default: OFF)

Additional tools and libraries used by HPX

Here is a list of additional libraries and tools that are either optionally supported by the build system or are optionally required for certain examples or tests. These libraries and tools can be detected by the *HPX* build system.

Each of the tools or libraries listed here will be automatically detected if they are installed in some standard location. If a tool or library is installed in a different location, you can specify its base directory by appending `_ROOT` to the variable name as listed below. For instance, to configure a custom directory for Boost, specify `Boost_ROOT=/custom/boost/root`.

Boost_ROOT:PATH

Specifies where to look for the Boost installation to be used for compiling *HPX*. Set this if CMake is not able to locate a suitable version of Boost. The directory specified here can be either the root of an installed Boost distribution or the directory where you unpacked and built Boost without installing it (with staged libraries).

Hwloc_ROOT:PATH

Specifies where to look for the hwloc library. Set this if CMake is not able to locate a suitable version of hwloc. Hwloc provides platform- independent support for extracting information about the used hardware architecture (number of cores, number of NUMA domains, hyperthreading, etc.). *HPX* utilizes this information if available.

Papi_ROOT:PATH

Specifies where to look for the PAPI library. The PAPI library is needed to compile a special component exposing PAPI hardware events and counters as *HPX* performance counters. This is not available on the Windows platform.

Amplifier_ROOT:PATH

Specifies where to look for one of the tools of the Intel Parallel Studio product, either Intel Amplifier or Intel Inspector. This should be set if the CMake variable `HPX_USE_ITT_NOTIFY` is set to ON. Enabling ITT support in *HPX* will integrate any application with the mentioned Intel tools, which customizes the generated information for your application and improves the generated diagnostics.

In addition, some of the examples may need the following variables:

Hdf5_ROOT:PATH

Specifies where to look for the Hierarchical Data Format V5 (HDF5) include files and libraries.

2.4.5 Using *HPX* on Compiler Explorer

Compiler Explorer⁶³ (CE) is a browser-based tool that compiles C++ code in real time and shows assembly, program output, and optimization results side by side. It is widely used for quick experiments, conference demos, and sharing reproducible snippets. This page explains how to build *HPX* for CE, how to link against its static libraries from a raw compiler command, and how to use the *sandbox header* that *HPX* ships specifically for constrained environments.

Sandbox environment constraints

CE executes compiled programs inside a Linux container (nsjail) with no network access and limited resources. The constraints that matter most for *HPX* are:

- No network namespace — sockets cannot be opened. Any attempt to initialise the distributed runtime will fail with `EACCES` at startup.
- A small PID budget (typically 32 PIDs) — *HPX* starts cleanly within this limit when the worker thread count is kept low.
- A short execution timeout — CE's public instance allows roughly 10 seconds. An *HPX* fork or self-hosted instance can relax this to 30 seconds, which is enough for benchmarks on problem sizes of one million elements or more.
- Static linking is required — the sandbox does not augment `LD_LIBRARY_PATH`, so shared *HPX* libraries are not found at runtime.

Building *HPX* for Compiler Explorer

HPX ships a `godbolt-minimal` configure preset in `CMakePresets.json` that encodes all the flags needed for a CE-compatible build:

```
$ cmake --preset godbolt-minimal
$ cmake --build --preset godbolt-minimal
```

This preset enables:

- `HPX_WITH_STATIC_LINKING=ON` — bundles everything into the `.a` archives that CE links against.
- `HPX_WITH_NETWORKING=OFF` — disables the `parcels` so *HPX* never attempts to open a network socket.
- `HPX_WITH_FETCH_ASIO=ON` — downloads Asio via `FetchContent`, removing the need for a system-level Asio installation.
- `HPX_WITH_MALLOC=system` — uses the system allocator; avoids a `jemalloc` or `tcmalloc` dependency.
- `HPX_WITH_TESTS=OFF`, `HPX_WITH_EXAMPLES=OFF`, `HPX_WITH_DOCUMENTATION=OFF` — skips everything that CE does not need.

The preset produces four static libraries under `build/godbolt-minimal/lib/`:

```
libhpx_wrap.a
libhpx_init.a
libhpx.a
libhpx_core.a
```

⁶³ <https://godbolt.org>

These are the only artifacts that CE consumes.

Note: The `HPX_WITH_CXX_STANDARD` variable pins the C++ standard for the build (e.g. `-DHPX_WITH_CXX_STANDARD=20`). This is *HPX*'s own cache variable and is distinct from `CMAKE_CXX_STANDARD`, which *HPX* rejects unless `HPX_USE_CMAKE_CXX_STANDARD` is also set.

Linking without CMake

CE's backend compiles user code with a raw `g++` or `clang++` invocation. The complete set of flags needed is:

```
$ g++ -std=c++20 -O2 -o my_program my_program.cpp \
    -isystem /path/to/hpx/include \
    -isystem /path/to/boost/include \
    -L/path/to/hpx/lib \
    -DHPX_APPLICATION_EXPORTS \
    -Wl,-wrap=main \
    -lhpx_wrap -lhpx_init -lhpx -lhpx_core \
    -lpthread -ldl -lrt
```

Two details here are easy to get wrong:

Library link order. The order `hpx_wrap` → `hpx_init` → `hpx` → `hpx_core` must be preserved. Reversing it produces undefined-reference errors because `hpx_wrap` depends on symbols in `hpx_init`, which depends on the full runtime in `hpx`, which in turn depends on the core library.

The `-Wl,-wrap=main` flag. Including `hpx/hpx_main.hpp` (see *Re-use the `main()` function as the main HPX entry point*) works by re-routing control through *HPX*'s own entry point before the user's `main` is called. On Linux this is implemented via the linker's `--wrap` option; the flag must therefore appear on the *linker* command line, not merely in the compile flags. Without it, the *HPX* runtime is never initialised and all API calls crash at startup. See *Linux implementation* for a detailed explanation of the mechanism.

Important: `-DHPX_APPLICATION_EXPORTS` must be passed as a preprocessor definition when compiling application code against the static libraries. Omitting it causes link failures related to *HPX*'s symbol visibility macros.

Writing *HPX* code for Compiler Explorer

The simplest way to write an *HPX* program for CE is to include `hpx/hpx_main.hpp`. This header arranges for the *HPX* runtime to be initialised before `main` runs, so the body of `main` can call any *HPX* API function directly:

```
#include <hpx/hpx_main.hpp>
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>

#include <iostream>
#include <numeric>
#include <vector>

int main()
{
    std::vector<int> v(1'000'000);
```

(continues on next page)

(continued from previous page)

```

std::iota(v.begin(), v.end(), 0);

long long sum = hpx::transform_reduce(
    hpx::execution::par, v.begin(), v.end(), 0LL,
    std::plus<>{}, [](int x) { return static_cast<long long>(x); });

std::cout << "sum = " << sum << "\n";
}

```

Caution: Include `hpx/hpx_main.hpp` in exactly one translation unit — the file that contains `main`. Including it in more than one file causes a multiple definition error for the `include_libhpx_wrap` variable that controls runtime initialisation.

The `hpx/experimental/sandbox.hpp` header

HPX ships a header-only toolkit at `hpx/experimental/sandbox.hpp` designed specifically for code running in constrained environments. It provides:

- **Environment introspection** — `hpx::experimental::sandbox::detect_environment()` returns an `environment_info` struct describing the number of physical cores, processing units, NUMA domains, and active HPX worker threads. The `is_sandbox` flag is set when the `COMPILER_EXPLORER` or `HPX_SANDBOX` environment variable is present, letting code adapt its behaviour automatically.
- **Timing** — `hpx::experimental::sandbox::measure(fn, iterations)` runs a callable `fn` for `iterations` repetitions (with one warmup pass) and returns the mean execution time in milliseconds.
- **Comparative benchmarking** — `hpx::experimental::sandbox::benchmark(label, seq_fn, par_fn, iterations)` measures both a sequential and a parallel version of the same computation, computes speedup and parallel efficiency, and returns a `benchmark_report` struct. Calling `report.print(std::cout)` produces a fixed-width table that renders cleanly in CE's output pane.

A typical usage pattern looks like this:

```

#include <hpx/hpx_main.hpp>
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>
#include <hpx/experimental/sandbox.hpp>

#include <algorithm>
#include <iostream>
#include <numeric>
#include <vector>

int main()
{
    namespace sb = hpx::experimental::sandbox;

    sb::describe_environment(std::cout);

    std::vector<int> data(500'000);
    std::iota(data.begin(), data.end(), 0);
}

```

(continues on next page)

(continued from previous page)

```

auto report = sb::benchmark(
    "transform_reduce",
    [&]() {
        hpx::transform_reduce(
            hpx::execution::seq,
            data.begin(), data.end(), 0LL,
            std::plus<{}>, [](int x) { return (long long)x; });
    },
    [&]() {
        hpx::transform_reduce(
            hpx::execution::par,
            data.begin(), data.end(), 0LL,
            std::plus<{}>, [](int x) { return (long long)x; });
    });

report.print(std::cout);
}

```

The output includes sequential and parallel mean times, speedup, parallel efficiency, and a verdict (Excellent scaling, Good scaling, Moderate scaling, Limited scaling, or No speedup).

Note: All functions in `hpx/experimental/sandbox.hpp` must be called from within a running *HPX* runtime, i.e., from an *HPX* thread. Calling them before `hpx::init` or after `hpx::finalize` is undefined behaviour. When using `hpx/hpx_main.hpp`, the body of `main` satisfies this requirement automatically.

Known limitations in sandboxed environments

- **Single locality only.** The distributed runtime can be compiled in (`HPX_WITH_DISTRIBUTED_RUNTIME=ON`) and actions on locality 0 work normally, but there is no way to launch a second locality from within CE's sandbox. Code that calls `hpx::find_all_localities()` or `hpx::get_num_localities()` will always see exactly one locality.
- **Networking is disabled.** `HPX_WITH_NETWORKING=OFF` means all parcelport-dependent functionality (remote actions, distributed data structures) is unavailable regardless of what the code requests.
- **Thread count is limited by the sandbox's CPU allocation.** CE's public instance typically exposes two cores. Use `--hpx:threads=N` on the command line or `hpx::init_params::cfg` in code to set the worker count explicitly rather than relying on hardware detection. See *Launching and configuring HPX applications* for details.
- **macOS link flag differs.** The `-Wl,-wrap=main` flag is Linux-specific. On macOS the linker uses `-Wl,-e,_initialize_main` instead. CE runs Linux containers, so this only matters when building the CE integration locally on macOS for testing.

2.4.6 Migration guide

The Migration Guide serves as a valuable resource for developers seeking to transition their parallel computing applications from different APIs (i.e. OpenMP, Intel Threading Building Blocks (TBB), MPI) to *HPX*. *HPX*, an advanced C++ library, offers a versatile and high-performance platform for parallel and distributed computing, providing a wide range of features and capabilities. This guide aims to assist developers in understanding the key differences between different APIs and *HPX*, and it provides step-by-step instructions for converting code to *HPX* code effectively.

Some general steps that can be used to migrate code to *HPX* code are the following:

1. Install *HPX* using the *Quick start* guide.
2. Include the *HPX* header files:

Add the necessary header files for *HPX* at the beginning of your code, such as:

```
#include <hpx/init.hpp>
```

3. Replace your code with *HPX* code using the guide that follows.
4. Use *HPX*-specific features and APIs:

HPX provides additional features and APIs that can be used to take advantage of the library's capabilities. For example, you can use the *HPX* asynchronous execution to express fine-grained tasks and dependencies, or utilize *HPX*'s distributed computing features for distributed memory systems.

5. Compile and run the *HPX* code:

Compile the converted code with the *HPX* library and run it using the appropriate *HPX* runtime environment.

OpenMP

The OpenMP API supports multi-platform shared-memory parallel programming in C/C++. Typically it is used for loop-level parallelism, but it also supports function-level parallelism. Below are some examples on how to convert OpenMP to *HPX* code:

OpenMP parallel for loop

Parallel for loop

OpenMP code:

```
#pragma omp parallel for
for (int i = 0; i < n; ++i) {
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>

hpx::experimental::for_loop(hpx::execution::par, 0, n, [&](int i) {
    // loop body
});
```

In the above code, the OpenMP `#pragma omp parallel for` directive is replaced with `hpx::experimental::for_loop` from the *HPX* library. The loop body within the lambda function will be executed in parallel for each iteration.

Private variables

OpenMP code:

```
int x = 0;

#pragma omp parallel for private(x)
for (int i = 0; i < n; ++i) {
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>

hpx::experimental::for_loop(hpx::execution::par, 0, n, [&](int i) {
    int x = 0; // Declare 'x' as a local variable inside the loop body
    // loop body
});
```

The variable *x* is declared as a local variable inside the loop body, ensuring that it is private to each thread.

Shared variables

OpenMP code:

```
int x = 0;

#pragma omp parallel for shared(x)
for (int i = 0; i < n; ++i) {
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>

std::atomic<int> x = 0; // Declare 'x' as a shared variable outside the loop

hpx::experimental::for_loop(hpx::execution::par, 0, n, [&](int i) {
    // loop body
});
```

To ensure variable *x* is shared among all threads, you simply have to declare it as an atomic variable outside the *for_loop*.

Number of threads

OpenMP code:

```
#pragma omp parallel for num_threads(2)
for (int i = 0; i < n; ++i) {
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>

hpx::execution::experimental::num_cores nc(2);

hpx::experimental::for_loop(hpx::execution::par.with(nc), 0, n, [&](int i) {
    // loop body
});
```

To declare the number of threads to be used for the parallel region, you can use `hpx::execution::experimental::num_cores` and pass the number of cores (*nc*) to `hpx::experimental::for_loop` using `hpx::execution::par.with(nc)`. This example uses 2 threads for the parallel loop.

Reduction

OpenMP code:

```
int s = 0;

#pragma omp parallel for reduction(+: s)
for (int i = 0; i < n; ++i) {
    s += i;
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>

int s = 0;

hpx::experimental::for_loop(hpx::execution::par, 0, n, reduction(s, 0, plus<>()), [&
↪](int i, int& accum) {
    accum += i;
    // loop body
});
```

The reduction clause specifies that the variable *s* should be reduced across iterations using the *plus<>* operation. It initializes *s* to 0 at the beginning of the loop and accumulates the values of *s* from each iteration using the + operator. The lambda function representing the loop body takes two parameters: *i*, which represents the loop index, and *accum*, which is the reduction variable *s*. The lambda function is executed for each iteration of the loop. The reduction ensures that the *accum* value is correctly accumulated across different iterations and threads.

Schedule

OpenMP code:

```
int s = 0;

// static scheduling with chunk size 1000
#pragma omp parallel for schedule(static, 1000)
for (int i = 0; i < n; ++i) {
    // loop body
}
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>

hpx::execution::experimental::static_chunk_size cs(1000);

hpx::experimental::for_loop(hpx::execution::par.with(cs), 0, n, [&](int i) {
    // loop body
});
```

To define the scheduling type, you can use the corresponding execution policy from `hpx::execution::experimental`, define the chunk size (cs, here declared as 1000) and pass it to the `hpx::experimental::for_loop` using `hpx::execution::par.with(cs)`.

Accordingly, other types of scheduling are available and can be used in a similar manner:

```
#include <hpx/execution.hpp>
hpx::execution::experimental::dynamic_chunk_size cs(1000);
```

```
#include <hpx/execution.hpp>
hpx::execution::experimental::guided_chunk_size cs(1000);
```

```
#include <hpx/execution.hpp>
hpx::execution::experimental::auto_chunk_size cs(1000);
```

OpenMP single thread

OpenMP code:

```
{ // parallel code
    #pragma omp single
    {
        // single-threaded code
    }
    // more parallel code
}
```

HPX equivalent:

```
#include <hpx/mutex.hpp>

hpx::mutex mtx;

{ // parallel code
  { // single-threaded code
    std::scoped_lock l(mtx);
  }
  // more parallel code
}
```

To make sure that only one thread accesses a specific code within a parallel section you can use `hpx::mutex` and `std::scoped_lock` to take ownership of the given mutex `mtx`. For more information about mutexes please refer to *Mutex*.

OpenMP tasks

Simple tasks

OpenMP code:

```
// executed asynchronously by any available thread
#pragma omp task
{
  // task code
}
```

HPX equivalent:

```
#include <hpx/future.hpp>

auto future = hpx::async([](){
  // task code
});
```

or

```
#include <hpx/future.hpp>

hpx::post([](){
  // task code
}); // fire and forget
```

The tasks in *HPX* can be defined simply by using the `async` function and passing as argument the code you wish to run asynchronously. Another alternative is to use `post` which is a fire-and-forget method.

Tip: If you think you will like to synchronize your tasks later on, we suggest you use `hpx::async` which provides synchronization options, while `hpx::post` explicitly states that there is no return value or way to synchronize with the function execution. Synchronization options are listed below.

Task wait

OpenMP code:

```
#pragma omp task
{
    // task code
}

#pragma omp taskwait
// code after completion of task
```

HPX equivalent:

```
#include <hpx/future.hpp>

hpx::async([](){
    // task code
}).get(); // wait for the task to complete

// code after completion of task
```

The `get()` function can be used to ensure that the task created with `hpx::async` is completed before the code continues executing beyond that point.

Multiple tasks synchronization

OpenMP code:

```
#pragma omp task
{
    // task 1 code
}

#pragma omp task
{
    // task 2 code
}

#pragma omp taskwait
// code after completion of both tasks 1 and 2
```

HPX equivalent:

```
#include <hpx/future.hpp>

auto future1 = hpx::async([](){
    // task 1 code
});

auto future2 = hpx::async([](){
    // task 2 code
});
```

(continues on next page)

(continued from previous page)

```
auto future = hpx::when_all(future1, future2).then([](auto&&){
    // code after completion of both tasks 1 and 2
});
```

If you would like to synchronize multiple tasks, you can use the `hpx::when_all` function to define which futures have to be ready and the `then()` function to declare what should be executed once these futures are ready.

Dependencies

OpenMP code:

```
int a = 10;
int b = 20;
int c = 0;

#pragma omp task depend(in: a, b) depend(out: c)
{
    // task code
    c = 100;
}
```

HPX equivalent:

```
#include <hpx/future.hpp>

int a = 10;
int b = 20;
int c = 0;

// Create a future representing 'a'
auto future_a = hpx::make_ready_future(a);

// Create a future representing 'b'
auto future_b = hpx::make_ready_future(b);

// Create a task that depends on 'a' and 'b' and executes 'task_code'
auto future_c = hpx::dataflow(
    []() {
        // task code
        return 100;
    },
    future_a, future_b);

c = future_c.get();
```

If one of the arguments of `hpx::dataflow` is a future, then it will wait for the future to be ready to launch the thread. Hence, to define the dependencies of tasks you have to create futures representing the variables that create dependencies and pass them as arguments to `hpx::dataflow`. `get()` is used to save the result of the future to the desired variable.

Nested tasks

OpenMP code:

```
#pragma omp task
{
    // Outer task code
    #pragma omp task
    {
        // Inner task code
    }
}
```

HPX equivalent:

```
#include <hpx/future.hpp>

auto future_outer = hpx::async([](){
    // Outer task code

    hpx::async([](){
        // Inner task code
    });
});
```

or

```
#include <hpx/future.hpp>

auto future_outer = hpx::post([](){ // fire and forget
    // Outer task code

    hpx::post([](){ // fire and forget
        // Inner task code
    });
});
```

If you have nested tasks, you can simply use nested `hpx::async` or `hpx::post` calls. The implementation is similar if you want to take care of synchronization:

OpenMP code:

```
#pragma omp taskwait
{
    // Outer task code
    #pragma omp taskwait
    {
        // Inner task code
    }
}
```

HPX equivalent:

```
#include <hpx/future.hpp>

auto future_outer = hpx::async([]() {
    // Outer task code

    hpx::async([]() {
        // Inner task code
    }).get();    // Wait for the inner task to complete
});

future_outer.get();    // Wait for the outer task to complete
```

Task yield

OpenMP code:

```
#pragma omp task
{
    // code before yielding
    #pragma omp taskyield
    // code after yielding
}
```

HPX equivalent:

```
#include <hpx/future.hpp>
#include <hpx/thread.hpp>

auto future = hpx::async([](){
    // code before yielding
});

// yield execution to potentially allow other tasks to run
hpx::this_thread::yield();

// code after yielding
```

After creating a task using `hpx::async`, `hpx::this_thread::yield` can be used to reschedule the execution of threads, allowing other threads to run.

Task group

OpenMP code:

```
#pragma omp taskgroup
{
    #pragma omp task
    {
        // task 1 code
    }
}
```

(continues on next page)

(continued from previous page)

```

#pragma omp task
{
    // task 2 code
}

```

HPX equivalent:

```

#include <hpx/task_group.hpp>

// Declare a task group
hpx::experimental::task_group tg;

// Run the tasks
tg.run([](){
    // task 1 code
});
tg.run(
    // task 2 code
);

// Wait for the task group
tg.wait();

```

To create task groups, you can use `hpx::experimental::task_group`. The function `run()` can be used to run each task within the task group, while `wait()` can be used to achieve synchronization. If you do not care about waiting for the task group to complete its execution, you can simply remove the `wait()` function.

OpenMP sections

OpenMP code:

```

#pragma omp sections
{
    #pragma omp section
    // section 1 code
    #pragma omp section
    // section 2 code
} // implicit synchronization

```

HPX equivalent:

```

#include <hpx/future.hpp>

auto future_section1 = hpx::async([](){
    // section 1 code
});
auto future_section2 = hpx::async([](){
    // section 2 code
});

```

(continues on next page)

(continued from previous page)

```
// synchronization: wait for both sections to complete
hpx::wait_all(future_section1, future_section2);
```

Unlike tasks, there is an implicit synchronization barrier at the end of each *sections* directive in OpenMP. This synchronization is achieved using `hpx::wait_all` function.

Note: If the *nowait* clause is used in the *sections* directive, then you can just remove the `hpx::wait_all` function while keeping the rest of the code as it is.

Intel Threading Building Blocks (TBB)

Intel Threading Building Blocks (TBB) provides a high-level interface for parallelism and concurrent programming using standard ISO C++ code. Below are some examples on how to convert Intel Threading Building Blocks (TBB) to HPX code:

parallel_for

Intel Threading Building Blocks (TBB) code:

```
auto values = std::vector<double>(10000);

tbb::parallel_for( tbb::blocked_range<int>(0, values.size()),
                  [&](tbb::blocked_range<int> r)
{
    for (int i=r.begin(); i<r.end(); ++i)
    {
        // loop body
    }
});
```

HPX equivalent:

```
#include <hpx/algorithm.hpp>

auto values = std::vector<double>(10000);

hpx::experimental::for_loop(hpx::execution::par, 0, values.size(), [&](int i) {
    // loop body
});
```

In the above code, `tbb::parallel_for` is replaced with `hpx::experimental::for_loop` from the HPX library. The loop body within the lambda function will be executed in parallel for each iteration.

parallel_for_each

Intel Threading Building Blocks (TBB) code:

```

auto values = std::vector<double>(10000);

tbb::parallel_for_each(values.begin(), values.end(), [&]() {
    // loop body
});

```

HPX equivalent:

```

#include <hpx/algorithm.hpp>

auto values = std::vector<double>(10000);

hpx::for_each(hpx::execution::par, values.begin(), values.end(), [&]() {
    // loop body
});

```

By utilizing `hpx::for_each` and specifying a parallel execution policy with `hpx::execution::par`, it is possible to transform `tbb::parallel_for_each` into its equivalent counterpart in HPX.

parallel_invoke

Intel Threading Building Blocks (TBB) code:

```

tbb::parallel_invoke(task1, task2, task3);

```

HPX equivalent:

```

#include <hpx/future.hpp>

hpx::wait_all(hpx::async(task1), hpx::async(task2), hpx::async(task3));

```

To convert `tbb::parallel_invoke` to HPX, we use `hpx::async` to asynchronously execute each task, which returns a future representing the result of each task. We then pass these futures to `hpx::when_all`, which waits for all the futures to complete before returning.

parallel_pipeline

Intel Threading Building Blocks (TBB) code:

```

tbb::parallel_pipeline(4,
    tbb::make_filter<void, int>(tbb::filter::serial_in_order,
        [](tbb::flow_control& fc) -> int {
            // Generate numbers from 1 to 10
            static int i = 1;
            if (i <= 10) {
                return i++;
            }
            else {

```

(continues on next page)

(continued from previous page)

```

        fc.stop();
        return 0;
    }
}) &
tbb::make_filter<int, int>(tbb::filter::parallel,
    [](int num) -> int {
        // Multiply each number by 2
        return num * 2;
    }) &
tbb::make_filter<int, void>(tbb::filter::serial_in_order,
    [](int num) {
        // Print the results
        std::cout << num << " ";
    })
);

```

HPX equivalent:

```

#include <iostream>
#include <vector>
#include <ranges>
#include <hpx/algorithm.hpp>

// generate the values
auto range = std::views::iota(1) | std::views::take(10);

// materialize the output vector
std::vector<int> results(10);

// in parallel execution of pipeline and transformation
hpx::ranges::transform(
    hpx::execution::par, range, result.begin(), [](int i) { return 2 * i; });

// print the modified vector
for (int i : result)
{
    std::cout << i << " ";
}
std::cout << std::endl;

```

The line `auto range = std::views::iota(1) | std::views::take(10);` generates a range of values using the `std::views::iota` function. It starts from the value 1 and generates an infinite sequence of incrementing values. The `std::views::take(10)` function is then applied to limit the sequence to the first 10 values. The result is stored in the `range` variable.

Hint: A view is a lightweight object that represents a particular view of a sequence or range. It acts as a read-only interface to the original data, providing a way to query and traverse the elements without making any copies or modifications.

Views can be composed and chained together to form complex pipelines of operations. These operations are evaluated lazily, meaning that the actual computation is performed only when the result is needed or consumed.

Since views perform lazy evaluation, we use `std::vector<int> results(10);` to materialize the vector that will store the

transformed values. The `hpx::ranges::transform` function is then used to perform a parallel transformation on the range. The transformed values will be written to the `results` vector.

Hint: Ranges enable loop fusion by combining multiple operations into a single parallel loop, eliminating waiting time and reducing overhead. Using ranges, you can express these operations as a pipeline of transformations on a sequence of elements. This pipeline is evaluated in a single pass, performing all the desired operations in parallel without the need to wait between them.

In addition, *HPX* enhances the benefits of range fusion by offering parallel execution policies, which can be used to optimize the execution of the fused loop across multiple threads.

parallel_reduce

Reduction

Intel Threading Building Blocks (TBB) code:

```
auto values = std::vector<double>{1,2,3,4,5,6,7,8,9};

auto total = tbb::parallel_reduce(
    tbb::blocked_range<int>(0, values.size()),
    0.0,
    [&](tbb::blocked_range<int> r, double running_total)
    {
        for (int i=r.begin(); i<r.end(); ++i)
        {
            running_total += values[i];
        }

        return running_total;
    },
    std::plus<double>());
```

HPX equivalent:

```
#include <hpx/numeric.hpp>

auto values = std::vector<double>{1,2,3,4,5,6,7,8,9};

auto total = hpx::reduce(
    hpx::execution::par, values.begin(), values.end(), 0, std::plus{});
```

By utilizing `hpx::reduce` and specifying a parallel execution policy with `hpx::execution::par`, it is possible to transform `tbb::parallel_reduce` into its equivalent counterpart in *HPX*. As demonstrated in the previous example, the management of intermediate results is seamlessly handled internally by *HPX*, eliminating the need for explicit consideration.

Transformation & Reduction

Intel Threading Building Blocks (TBB) code:

```
auto values = std::vector<double>{1,2,3,4,5,6,7,8,9};

auto transform_function(double current_value){
    // transformation code
}

auto total = tbb::parallel_reduce(
    tbb::blocked_range<int>(0, values.size()),
    0.0,
    [&](tbb::blocked_range<int> r, double transformed_val)
    {
        for (int i=r.begin(); i<r.end(); ++i)
        {
            transformed_val += transform_function(values[i]);
        }
        return transformed_val;
    },
    std::plus<double>());
```

HPX equivalent:

```
#include <hpx/numeric.hpp>

auto values = std::vector<double>{1,2,3,4,5,6,7,8,9};

auto transform_function(double current_value)
{
    // transformation code
}

auto total = hpx::transform_reduce(hpx::execution::par, values.begin(),
    values.end(), 0, std::plus{}),
    [&](double current_value) { return transform_function(current_value); });
```

In situations where certain values require transformation before the reduction process, *HPX* provides a straightforward solution through `hpx::transform_reduce`. The `transform_function()` allows for the application of the desired transformation to each value.

parallel_scan

Intel Threading Building Blocks (TBB) code:

```
tbb::parallel_scan(tbb::blocked_range<size_t>(0, input.size()),
    0,
    [&input, &output](const tbb::blocked_range<size_t>& range, int& partial_sum, bool is_
    ↪final_scan) {
        for (size_t i = range.begin(); i != range.end(); ++i) {
            partial_sum += input[i];
        }
    },
    output);
```

(continues on next page)

(continued from previous page)

```

        if (is_final_scan) {
            output[i] = partial_sum;
        }
    }
    return partial_sum;
},
[](int left_sum, int right_sum) {
    return left_sum + right_sum;
}
);

```

HPX equivalent:

```

#include <hpx/numeric.hpp>

hpx::inclusive_scan(hpx::execution::par, input.begin(), input.end(),
    output.begin(),
    [](const int& left, const int& right) { return left + right; });

```

`hpx::inclusive_scan` with `hpx::execution::par` as execution policy can be used to perform a prefix scan in parallel. The management of intermediate results is seamlessly handled internally by HPX, eliminating the need for explicit consideration. `input.begin()` and `input.end()` refer to the beginning and end of the sequence of elements the algorithm will be applied to respectively. `output.begin()` refers to the beginning of the destination, while the last argument specifies the function which will be invoked for each of the values of the input sequence.

Apart from `hpx::inclusive_scan`, HPX provides its users with `hpx::exclusive_scan`. The key difference between inclusive scan and exclusive scan lies in the treatment of the current element during the scan operation. In an inclusive scan, each element in the output sequence includes the contribution of the corresponding element in the input sequence, while in an exclusive scan, the current element in the input sequence does not contribute to the corresponding element in the output sequence.

parallel_sort

Intel Threading Building Blocks (TBB) code:

```

std::vector<int> numbers = {9, 2, 7, 1, 5, 3};

tbb::parallel_sort(numbers.begin(), numbers.end());

```

HPX equivalent:

```

#include <hpx/algorithm.hpp>

std::vector<int> numbers = {9, 2, 7, 1, 5, 3};

hpx::sort(hpx::execution::par, numbers.begin(), numbers.end());

```

`hpx::sort` provides an equivalent functionality to `tbb::parallel_sort`. When given a parallel execution policy with `hpx::execution::par`, the algorithm employs parallel execution, allowing for efficient sorting across available threads.

task_group

Intel Threading Building Blocks (TBB) code:

```
// Declare a task group
tbb::task_group tg;

// Run the tasks
tg.run(task1);
tg.run(task2);

// Wait for the task group
tg.wait();
```

HPX equivalent:

```
#include <hpx/task_group.hpp>

// Declare a task group
hpx::experimental::task_group tg;

// Run the tasks
tg.run(task1);
tg.run(task2);

// Wait for the task group
tg.wait();
```

HPX drew inspiration from Intel Threading Building Blocks (TBB) to introduce the `hpx::experimental::task_group` feature. Therefore, utilizing `hpx::experimental::task_group` provides an equivalent functionality to `tbb::task_group`.

MPI

MPI is a standardized communication protocol and library that allows multiple processes or nodes in a parallel computing system to exchange data and coordinate their execution.

List of MPI-HPX functions

MPI function	HPX equivalent
<i>MPI_Allgather</i>	<i>hpx::collectives::all_gather</i>
<i>MPI_Allreduce</i>	<i>hpx::collectives::all_reduce</i>
<i>MPI_Alltoall</i>	<i>hpx::collectives::all_to_all</i>
<i>MPI_Barrier</i>	<i>hpx::distributed::barrier</i>
<i>MPI_Bcast</i>	<i>hpx::collectives::broadcast_to()</i> and <i>hpx::collectives::broadcast_from()</i> used with <i>get()</i>
<i>MPI_Comm_size</i>	<i>hpx::get_num_localities</i>
<i>MPI_Comm_rank</i>	<i>hpx::get_locality_id()</i>
<i>MPI_Exscan</i>	<i>hpx::collectives::exclusive_scan()</i> used with <i>get()</i>
<i>MPI_Gather</i>	<i>hpx::collectives::gather_here()</i> and <i>hpx::collectives::gather_there()</i> used with <i>get()</i>
<i>MPI_Irecv</i>	<i>hpx::collectives::get()</i>
<i>MPI_Isend</i>	<i>hpx::collectives::set()</i>
<i>MPI_Reduce</i>	<i>hpx::collectives::reduce_here</i> and <i>hpx::collectives::reduce_there</i> used with <i>get()</i>
<i>MPI_Scan</i>	<i>hpx::collectives::inclusive_scan()</i> used with <i>get()</i>
<i>MPI_Scatter</i>	<i>hpx::collectives::scatter_to()</i> and <i>hpx::collectives::scatter_from()</i>
<i>MPI_Wait</i>	<i>hpx::collectives::get()</i> used with a future i.e. <i>setf.get()</i>

MPI_Send & MPI_Recv

Let's assume we have the following simple message passing code where each process sends a message to the next process in a circular manner. The exchanged message is modified and printed to the console.

MPI code:

```
#include <cstdint>
#include <cstdint>
#include <iostream>
#include <mpi.h>
#include <vector>

constexpr int times = 2;

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);

    int this_locality;
    MPI_Comm_rank(MPI_COMM_WORLD, &this_locality);

    int next_locality = (this_locality + 1) % num_localities;
    std::vector<int> msg_vec = {0, 1};

    int cnt = 0;
    int msg = msg_vec[this_locality];
```

(continues on next page)

(continued from previous page)

```

int recv_msg;
MPI_Request request_send, request_recv;
MPI_Status status;

while (cnt < times) {
    cnt += 1;

    MPI_Isend(&msg, 1, MPI_INT, next_locality, cnt, MPI_COMM_WORLD,
              &request_send);
    MPI_Irecv(&recv_msg, 1, MPI_INT, next_locality, cnt, MPI_COMM_WORLD,
              &request_recv);

    MPI_Wait(&request_send, &status);
    MPI_Wait(&request_recv, &status);

    std::cout << "Time: " << cnt << ", Locality " << this_locality
              << " received msg: " << recv_msg << "\n";

    recv_msg += 10;
    msg = recv_msg;
}

MPI_Finalize();
return 0;
}

```

HPX equivalent:

```

#include <hpx/config.hpp>

#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/algorithm.hpp>
#include <hpx/hpx_init.hpp>
#include <hpx/modules/collectives.hpp>

#include <cstdint>
#include <cstdint>
#include <iostream>
#include <utility>
#include <vector>

using namespace hpx::collectives;

constexpr char const* channel_communicator_name =
    "/example/channel_communicator/";

// the number of times
constexpr int times = 2;

int hpx_main()
{

```

(continues on next page)

(continued from previous page)

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t this_locality = hpx::get_locality_id();

// allocate channel communicator
// NOTE: The communicator object must be kept alive until all
// participating sites have successfully connected. Destroying it
// prematurely may cause other sites to hang. Consider using a barrier
// after creation if the communicator would otherwise go out of scope.
auto comm = create_channel_communicator(hpx::launch::sync,
    channel_communicator_name, num_sites_arg(num_localities),
    this_site_arg(this_locality));

std::uint32_t next_locality = (this_locality + 1) % num_localities;
std::vector<int> msg_vec = {0, 1};

int cnt = 0;
int msg = msg_vec[this_locality];

// send values to another locality
auto setf = set(comm, that_site_arg(next_locality), msg, tag_arg(cnt));
auto got_msg = get<int>(comm, that_site_arg(next_locality), tag_arg(cnt));

setf.get();

while (cnt < times)
{
    cnt += 1;

    auto done_msg = got_msg.then([&](auto&& f) {
        int rec_msg = f.get();
        std::cout << "Time: " << cnt << ", Locality " << this_locality
            << " received msg: " << rec_msg << "\n";

        // change msg by adding 10
        rec_msg += 10;

        // start next round
        setf =
            set(comm, that_site_arg(next_locality), rec_msg, tag_arg(cnt));
        got_msg =
            get<int>(comm, that_site_arg(next_locality), tag_arg(cnt));
        setf.get();
    });

    done_msg.get();
}

return hpx::finalize();
}
#endif

int main(int argc, char* argv[])

```

(continues on next page)

(continued from previous page)

```

{
  #if !defined(HPX_COMPUTE_DEVICE_CODE)
    hpx::init_params params;
    params.cfg = {"--hpx:run-hpx-main"};
    return hpx::init(argc, argv, params);
  #else
    (void) argc;
    (void) argv;
    return 0;
  #endif
}

```

To perform message passing between different processes in *HPX* we can use a channel communicator. To understand this example, let's focus on the *hpx_main()* function:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- *create_channel_communicator* function is used to create a channel to serve the communication. This function takes several arguments, including the launch policy (*hpx::launch::sync*), the name of the communicator (*channel_communicator_name*), the number of localities, and the ID of the current locality.
- The communication follows a ring pattern, where each process (or locality) sends a message to its neighbor in a circular manner. This means that the messages circulate around the localities, ensuring that the communication wraps around when reaching the end of the locality sequence. To achieve this, the *next_locality* variable is calculated as the ID of the next locality in the ring.
- The initial values for the communication are set (*msg_vec*, *cnt*, *msg*).
- The *set()* function is called to send the message to the next locality in the ring. The message is sent asynchronously and is associated with a tag (*cnt*).
- The *get()* function is called to receive a message from the next locality. It is also associated with the same tag as the *set()* operation.
- The *setf.get()* call blocks until the message sending operation is complete.
- A continuation is set up using the function *then()* to handle the received message. Inside the continuation:
 - The received message value (*rec_msg*) is retrieved using *f.get()*.
 - The received message is printed to the console and then modified by adding 10.
 - The *set()* and *get()* operations are repeated to send and receive the modified message to the next locality.
 - The *setf.get()* call blocks until the new message sending operation is complete.
- The *done_msg.get()* call blocks until the continuation is complete for the current loop iteration.

Having said that, we conclude to the following table:

MPI_Gather

The following code gathers data from all processes to the root process and verifies the gathered data in the root process.

MPI code:

```
#include <iostream>
#include <mpi.h>
#include <numeric>
#include <vector>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities, this_locality;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);
    MPI_Comm_rank(MPI_COMM_WORLD, &this_locality);

    std::vector<int> local_data; // Data to be gathered

    if (this_locality == 0) {
        local_data.resize(num_localities); // Resize the vector on the root process
    }

    // Each process calculates its local data value
    int my_data = 42 + this_locality;

    for (std::uint32_t i = 0; i != 10; ++i) {

        // Gather data from all processes to the root process (process 0)
        MPI_Gather(&my_data, 1, MPI_INT, local_data.data(), 1, MPI_INT, 0,
                  MPI_COMM_WORLD);

        // Only the root process (process 0) will print the gathered data
        if (this_locality == 0) {
            std::cout << "Gathered data on the root: ";
            for (int i = 0; i < num_localities; ++i) {
                std::cout << local_data[i] << " ";
            }
            std::cout << std::endl;
        }
    }
    std::cout << std::endl;

    MPI_Finalize();
    return 0;
}
```

HPX equivalent:

```
std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t this_locality = hpx::get_locality_id();

// test functionality based on immediate local result value
```

(continues on next page)

(continued from previous page)

```

auto gather_direct_client = create_communicator(gather_direct_basename,
    num_sites_arg(num_localities), this_site_arg(this_locality));

for (std::uint32_t i = 0; i != 10; ++i)
{
    if (this_locality == 0)
    {
        hpx::future<std::vector<std::uint32_t>> overall_result =
            gather_here(gather_direct_client, std::uint32_t(42));

        std::vector<std::uint32_t> sol = overall_result.get();
        std::cout << "Gathered data on the root:";

        for (std::size_t j = 0; j != sol.size(); ++j)
        {
            HPX_TEST(j + 42 == sol[j]);
            std::cout << " " << sol[j];
        }
        std::cout << std::endl;
    }
    else
    {
        hpx::future<void> overall_result =
            gather_there(gather_direct_client, this_locality + 42);
        overall_result.get();
    }
}

```

This code will print 10 times the following message:

```
Gathered data on the root: 42 43
```

HPX uses two functions to implement the functionality of *MPI_Gather*: *gather_here* and *gather_there*. *gather_here* is gathering data from all localities to the locality with ID 0 (root locality). *gather_there* allows non-root localities to participate in the gather operation by sending data to the root locality. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *create_communicator()* is used to create a communicator called *gather_direct_client*.
- If the current locality is the root (its ID is equal to 0):
 - The *gather_here* function is used to perform the gather operation. It collects data from all other localities into the *overall_result* future object. The function arguments provide the necessary information, such as the base name for the gather operation (*gather_direct_basename*), the value to be gathered (*value*), the number of localities (*num_localities*), the current locality ID (*this_locality*), and the generation number (related to the gather operation).
 - The *get()* member function of the *overall_result* future is used to retrieve the gathered data.
 - The next *for* loop is used to verify the correctness of the gathered data (*sol*). *HPX_TEST* is a macro provided by the HPX testing utilities to perform similar testing with the Standard C++ macro *assert*.
- If the current locality is not the root:

- The *gather_there* function is used to participate in the gather operation initiated by the root locality. It sends the data (in this case, the value *this_locality* + 42) to the root locality, indicating that it should be included in the gathering.
- The *get()* member function of the *overall_result* future is used to wait for the gather operation to complete for this locality.

MPI_Scatter

The following code gathers data from all processes to the root process and verifies the gathered data in the root process.

MPI code:

```
#include <iostream>
#include <mpi.h>
#include <vector>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities, this_locality;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);
    MPI_Comm_rank(MPI_COMM_WORLD, &this_locality);

    int num_localities = num_localities;
    std::vector<int> data(num_localities);

    if (this_locality == 0) {
        // Fill the data vector on the root locality (locality 0)
        for (int i = 0; i < num_localities; ++i) {
            data[i] = 42 + i;
        }
    }

    int local_data; // Variable to store the received data

    // Scatter data from the root locality to all other localities
    MPI_Scatter(&data[0], 1, MPI_INT, &local_data, 1, MPI_INT, 0, MPI_COMM_WORLD);

    // Now, each locality has its own local_data

    // Print the local_data on each locality
    std::cout << "Locality " << this_locality << " received " << local_data
              << std::endl;

    MPI_Finalize();
    return 0;
}
```

HPX equivalent:

```
std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
HPX_TEST_LTE(std::uint32_t(2), num_localities);
```

(continues on next page)

(continued from previous page)

```

std::uint32_t this_locality = hpx::get_locality_id();

auto scatter_direct_client =
    hpx::collectives::create_communicator(scatter_direct_basename,
        num_sites_arg(num_localities), this_site_arg(this_locality));

// test functionality based on immediate local result value
for (std::uint32_t i = 0; i != 10; ++i)
{
    if (this_locality == 0)
    {
        std::vector<std::uint32_t> data(num_localities);
        std::iota(data.begin(), data.end(), 42 + i);

        hpx::future<std::uint32_t> result =
            scatter_to(scatter_direct_client, std::move(data));

        HPX_TEST_EQ(i + 42 + this_locality, result.get());
    }
    else
    {
        hpx::future<std::uint32_t> result =
            scatter_from<std::uint32_t>(scatter_direct_client);

        HPX_TEST_EQ(i + 42 + this_locality, result.get());

        std::cout << "Locality " << this_locality << " received "
            << i + 42 + this_locality << std::endl;
    }
}

```

For `num_localities = 2` and since we run for 10 iterations this code will print the following message:

```

Locality 1 received 43
Locality 1 received 44
Locality 1 received 45
Locality 1 received 46
Locality 1 received 47
Locality 1 received 48
Locality 1 received 49
Locality 1 received 50
Locality 1 received 51
Locality 1 received 52

```

HPX uses two functions to implement the functionality of *MPI_Scatter*: `hpx::scatter_to` and `hpx::scatter_from`. `hpx::scatter_to` is distributing the data from the locality with ID 0 (root locality) to all other localities. `hpx::scatter_from` allows non-root localities to receive the data from the root locality. In more detail:

- `hpx::get_num_localities(hpx::launch::sync)` retrieves the number of localities, while `hpx::get_locality_id()` returns the ID of the current locality.
- The function `hpx::collectives::create_communicator()` is used to create a communicator called `scatter_direct_client`.

- If the current locality is the root (its ID is equal to 0):
 - The data vector is filled with values ranging from $42 + i$ to $42 + i + \text{num_localities} - 1$.
 - The `hpx::scatter_to` function is used to perform the scatter operation using the communicator `scatter_direct_client`. This scatters the data vector to other localities and returns a future representing the result.
 - `HPX_TEST_EQ` is a macro provided by the *HPX* testing utilities to test the distributed values.
- If the current locality is not the root:
 - The `hpx::scatter_from` function is used to collect the data by the root locality.
 - `HPX_TEST_EQ` is a macro provided by the *HPX* testing utilities to test the collected values.

MPI_Allgather

The following code gathers data from all processes and sends the data to all processes.

MPI code:

```
#include <cstdint>
#include <iostream>
#include <mpi.h>
#include <vector>

int main(int argc, char **argv) {
    MPI_Init(&argc, &argv);

    int rank, size;
    MPI_Comm_rank(MPI_COMM_WORLD, &rank);
    MPI_Comm_size(MPI_COMM_WORLD, &size);

    // Get the number of MPI processes
    int num_localities = size;

    // Get the MPI process rank
    int here = rank;

    std::uint32_t value = here;

    std::vector<std::uint32_t> r(num_localities);

    // Perform an all-gather operation to gather values from all processes.
    MPI_Allgather(&value, 1, MPI_UINT32_T, r.data(), 1, MPI_UINT32_T,
                 MPI_COMM_WORLD);

    // Print the result.
    std::cout << "Locality " << here << " has values:";
    for (size_t j = 0; j < r.size(); ++j) {
        std::cout << " " << r[j];
    }
    std::cout << std::endl;

    MPI_Finalize();
}
```

(continues on next page)

(continued from previous page)

```

    return 0;
}

```

HPX equivalent:

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t here = hpx::get_locality_id();

// test functionality based on immediate local result value
auto all_gather_direct_client =
    create_communicator(all_gather_direct_basename,
        num_sites_arg(num_localities), this_site_arg(here));

std::uint32_t value = here;

hpx::future<std::vector<std::uint32_t>> overall_result =
    all_gather(all_gather_direct_client, value);

std::vector<std::uint32_t> r = overall_result.get();

std::cout << "Locality " << here << " has values:";
for (std::size_t j = 0; j != r.size(); ++j)
{
    std::cout << " " << j;
}
std::cout << std::endl;

```

For num_localities = 2 this code will print the following message:

```

Locality 0 has values: 0 1
Locality 1 has values: 0 1

```

HPX uses the function *all_gather* to implement the functionality of *MPI_Allgather*. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *hpx::collectives::create_communicator()* is used to create a communicator called *all_gather_direct_client*.
- The values that the localities exchange with each other are equal to each locality's ID.
- The gather operation is performed using *all_gather*. The result is stored in an *hpx::future* object called *overall_result*, which represents a future result that can be retrieved later when needed.
- The *get()* function waits until the result is available and then stores it in the vector called *r*.

MPI_Allreduce

The following code combines values from all processes and distributes the result back to all processes.

MPI code:

```
#include <stdint>
#include <iostream>
#include <mpi.h>

int main(int argc, char **argv) {
    MPI_Init(&argc, &argv);

    int rank, size;
    MPI_Comm_rank(MPI_COMM_WORLD, &rank);
    MPI_Comm_size(MPI_COMM_WORLD, &size);

    // Get the number of MPI processes
    int num_localities = size;

    // Get the MPI process rank
    int here = rank;

    // Create a communicator for the all reduce operation.
    MPI_Comm all_reduce_direct_client;
    MPI_Comm_split(MPI_COMM_WORLD, 0, rank, &all_reduce_direct_client);

    // Perform the all reduce operation to calculate the sum of 'here' values.
    std::uint32_t value = here;
    std::uint32_t res = 0;
    MPI_Allreduce(&value, &res, 1, MPI_UINT32_T, MPI_SUM,
                 all_reduce_direct_client);

    std::cout << "Locality " << rank << " has value: " << res << std::endl;

    MPI_Finalize();
    return 0;
}
```

HPX equivalent:

```
std::uint32_t const num_localities =
    hpx::get_num_localities(hpx::launch::sync);
std::uint32_t const here = hpx::get_locality_id();

auto const all_reduce_direct_client =
    create_communicator(all_reduce_direct_basename,
                        num_sites_arg(num_localities), this_site_arg(here));

std::uint32_t value = here;

hpx::future<std::uint32_t> overall_result =
    all_reduce(all_reduce_direct_client, value, std::plus<std::uint32_t>{});
```

(continues on next page)

(continued from previous page)

```
std::uint32_t res = overall_result.get();
std::cout << "Locality " << here << " has value: " << res << std::endl;
```

For `num_localities = 2` this code will print the following message:

```
Locality 0 has value: 1
Locality 1 has value: 1
```

HPX uses the function *all_reduce* to implement the functionality of *MPI_Allreduce*. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *hpx::collectives::create_communicator()* is used to create a communicator called *all_reduce_direct_client*.
- The value of each locality is equal to its ID.
- The reduce operation is performed using *all_reduce*. The result is stored in an *hpx::future* object called *overall_result*, which represents a future result that can be retrieved later when needed.
- The *get()* function waits until the result is available and then stores it in the variable *res*.

MPI_Alltoall

The following code gathers data from and scatters data to all processes.

MPI code:

```
#include <algorithm>
#include <stdint>
#include <iostream>
#include <mpi.h>
#include <vector>

int main(int argc, char **argv) {
    MPI_Init(&argc, &argv);

    int rank, size;
    MPI_Comm_rank(MPI_COMM_WORLD, &rank);
    MPI_Comm_size(MPI_COMM_WORLD, &size);

    // Get the number of MPI processes
    int num_localities = size;

    // Get the MPI process rank
    int this_locality = rank;

    // Create a communicator for all-to-all operation.
    MPI_Comm all_to_all_direct_client;
    MPI_Comm_split(MPI_COMM_WORLD, 0, rank, &all_to_all_direct_client);

    std::vector<std::uint32_t> values(num_localities);
    std::fill(values.begin(), values.end(), this_locality);
```

(continues on next page)

(continued from previous page)

```

// Create vectors to store received values.
std::vector<std::uint32_t> r(num_localities);

// Perform an all-to-all operation to exchange values with other localities.
MPI_Alltoall(values.data(), 1, MPI_UINT32_T, r.data(), 1, MPI_UINT32_T,
             all_to_all_direct_client);

// Print the results.
std::cout << "Locality " << this_locality << " has values:";
for (std::size_t j = 0; j != r.size(); ++j) {
    std::cout << " " << r[j];
}
std::cout << std::endl;

MPI_Finalize();
return 0;
}

```

HPX equivalent:

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t this_locality = hpx::get_locality_id();

auto all_to_all_direct_client =
    create_communicator(all_to_all_direct_basename,
                       num_sites_arg(num_localities), this_site_arg(this_locality));

std::vector<std::uint32_t> values(num_localities);
std::fill(values.begin(), values.end(), this_locality);

hpx::future<std::vector<std::uint32_t>> overall_result =
    all_to_all(all_to_all_direct_client, std::move(values));

std::vector<std::uint32_t> r = overall_result.get();
std::cout << "Locality " << this_locality << " has values:";

for (std::size_t j = 0; j != r.size(); ++j)
{
    std::cout << " " << r[j];
}
std::cout << std::endl;

```

For num_localities = 2 this code will print the following message:

```

Locality 0 has values: 0 1
Locality 1 has values: 0 1

```

HPX uses the function *all_to_all* to implement the functionality of *MPI_Alltoall*. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *hpx::collectives::create_communicator()* is used to create a communicator called

all_to_all_direct_client.

- The value each locality sends is equal to its ID.
- The all-to-all operation is performed using *all_to_all*. The result is stored in an *hpx::future* object called *overall_result*, which represents a future result that can be retrieved later when needed.
- The *get()* function waits until the result is available and then stores it in the variable *r*.

MPI_Barrier

The following code shows how barrier is used to synchronize multiple processes.

MPI code:

```
#include <cstdlib>
#include <iostream>
#include <mpi.h>

int main(int argc, char **argv) {
    MPI_Init(&argc, &argv);

    std::size_t iterations = 5;

    int rank, size;
    MPI_Comm_rank(MPI_COMM_WORLD, &rank);
    MPI_Comm_size(MPI_COMM_WORLD, &size);

    for (std::size_t i = 0; i != iterations; ++i) {
        MPI_Barrier(MPI_COMM_WORLD);
        if (rank == 0) {
            std::cout << "Iteration " << i << " completed." << std::endl;
        }
    }

    MPI_Finalize();
    return 0;
}
```

HPX equivalent:

```
std::size_t iterations = 5;
std::uint32_t this_locality = hpx::get_locality_id();

char const* const barrier_test_name = "/test/barrier/multiple";

hpx::distributed::barrier b(barrier_test_name);
for (std::size_t i = 0; i != iterations; ++i)
{
    b.wait();
    if (this_locality == 0)
    {
        std::cout << "Iteration " << i << " completed." << std::endl;
    }
}
```


This code will print the following message:

```
Iteration 0 completed.
Iteration 1 completed.
Iteration 2 completed.
Iteration 3 completed.
Iteration 4 completed.
```

HPX uses the function *barrier* to implement the functionality of *MPI_Barrier*. In more detail:

- After defining the number of iterations, we use *hpx::get_locality_id()* to get the ID of the current locality.
- *char const* const barrier_test_name = "/test/barrier/multiple"*: This line defines a constant character array as the name of the barrier. This name is used to identify the barrier across different localities. All participating threads that use this name will synchronize at this barrier.
- Using *hpx::distributed::barrier b(barrier_test_name)*, we create an instance of the distributed barrier with the previously defined name. This barrier will be used to synchronize the execution of threads across different localities.
- Running for all the desired iterations, we use *b.wait()* to synchronize the threads. Each thread waits until all other threads also reach this point before any of them can proceed further.

MPI_Bcast

The following code broadcasts data from one process to all other processes.

MPI code:

```
#include <iostream>
#include <mpi.h>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);

    int here;
    MPI_Comm_rank(MPI_COMM_WORLD, &here);

    int value;

    for (int i = 0; i < 5; ++i) {
        if (here == 0) {
            value = i + 42;
        }

        // Broadcast the value from process 0 to all other processes
        MPI_Bcast(&value, 1, MPI_INT, 0, MPI_COMM_WORLD);

        if (here != 0) {
            std::cout << "Locality " << here << " received " << value << std::endl;
        }
    }
}
```

(continues on next page)

(continued from previous page)

```

    }

    MPI_Finalize();
    return 0;
}

```

HPX equivalent:

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);

std::uint32_t here = hpx::get_locality_id();

auto broadcast_direct_client =
    create_communicator(broadcast_direct_basename,
        num_sites_arg(num_localities), this_site_arg(here));

// test functionality based on immediate local result value
for (std::uint32_t i = 0; i != 5; ++i)
{
    if (here == 0)
    {
        hpx::future<std::uint32_t> result =
            broadcast_to(broadcast_direct_client, i + 42);

        result.get();
    }
    else
    {
        hpx::future<std::uint32_t> result =
            hpx::collectives::broadcast_from<std::uint32_t>(
                broadcast_direct_client);

        uint32_t r = result.get();

        std::cout << "Locality " << here << " received " << r << std::endl;
    }
}

```

For num_localities = 2 this code will print the following message:

```

Locality 1 received 42
Locality 1 received 43
Locality 1 received 44
Locality 1 received 45
Locality 1 received 46

```

HPX uses two functions to implement the functionality of *MPI_Bcast*: *broadcast_to* and *broadcast_from*. *broadcast_to* is broadcasting the data from the root locality to all other localities. *broadcast_from* allows non-root localities to collect the data sent by the root locality. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *create_communicator()* is used to create a communicator called *broadcast_direct_client*.

- If the current locality is the root (its ID is equal to 0):
 - The *broadcast_to* function is used to perform the broadcast operation using the communicator *broadcast_direct_client*. This sends the data to other localities and returns a future representing the result.
 - The *get()* member function of the *result* future is used to wait for and retrieve the result.
- If the current locality is not the root:
 - The *broadcast_from* function is used to collect the data by the root locality.
 - The *get()* member function of the *result* future is used to wait for the result.

MPI_Exscan

The following code computes the exclusive scan (partial reductions) of data on a collection of processes.

MPI code:

```
#include <iostream>
#include <mpi.h>
#include <numeric>
#include <vector>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);

    int here;
    MPI_Comm_rank(MPI_COMM_WORLD, &here);

    // Calculate the value for this locality (here)
    int value = here;

    // Perform an exclusive scan
    std::vector<int> result(num_localities);
    MPI_Exscan(&value, &result[0], 1, MPI_INT, MPI_SUM, MPI_COMM_WORLD);

    if (here != 0) {
        int r = result[here - 1]; // Result is in the previous rank's slot

        std::cout << "Locality " << here << " has value " << r << std::endl;
    }

    MPI_Finalize();
    return 0;
}
```

HPX equivalent:

```
std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t here = hpx::get_locality_id();

auto exclusive_scan_client = create_communicator(exclusive_scan_basename,
```

(continues on next page)

(continued from previous page)

```

    num_sites_arg(num_localities), this_site_arg(here));

// test functionality based on immediate local result value
std::uint32_t value = here;

hpx::future<std::uint32_t> overall_result = exclusive_scan(
    exclusive_scan_client, value, std::plus<std::uint32_t>{});

uint32_t r = overall_result.get();

if (here != 0)
{
    std::cout << "Locality " << here << " has value " << r << std::endl;
}

```

For num_localities = 2 this code will print the following message:

```
Locality 1 has value 0
```

HPX uses the function *exclusive_scan* to implement *MPI_Exscan*. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *create_communicator()* is used to create a communicator called *exclusive_scan_client*.
- The *exclusive_scan* function is used to perform the exclusive scan operation using the communicator *exclusive_scan_client*. *std::plus<std::uint32_t>{}* specifies the binary associative operator to use for the scan. In this case, it's addition for summing values.
- The *get()* member function of the *overall_result* future is used to wait for the result.

MPI_Scan

The following code Computes the inclusive scan (partial reductions) of data on a collection of processes.

MPI code:

```

#include <iostream>
#include <mpi.h>
#include <numeric>
#include <vector>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_localities;
    MPI_Comm_size(MPI_COMM_WORLD, &num_localities);

    int here;
    MPI_Comm_rank(MPI_COMM_WORLD, &here);

    // Calculate the value for this locality (here)
    int value = here;

```

(continues on next page)

(continued from previous page)

```

std::vector<int> result(num_localities);

MPI_Scan(&value, &result[0], 1, MPI_INT, MPI_SUM, MPI_COMM_WORLD);

std::cout << "Locality " << here << " has value " << result[0] << std::endl;

MPI_Finalize();
return 0;
}

```

HPX equivalent:

```

std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t here = hpx::get_locality_id();

auto inclusive_scan_client = create_communicator(inclusive_scan_basename,
    num_sites_arg(num_localities), this_site_arg(here));

std::uint32_t value = here;

hpx::future<std::uint32_t> overall_result = inclusive_scan(
    inclusive_scan_client, value, std::plus<std::uint32_t>{});

uint32_t r = overall_result.get();

std::cout << "Locality " << here << " has value " << r << std::endl;

```

For num_localities = 2 this code will print the following message:

```

Locality 0 has value 0
Locality 1 has value 1

```

HPX uses the function *inclusive_scan* to implement *MPI_Scan*. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *create_communicator()* is used to create a communicator called *inclusive_scan_client*.
- The *inclusive_scan* function is used to perform the exclusive scan operation using the communicator *inclusive_scan_client*. *std::plus<std::uint32_t>{}* specifies the binary associative operator to use for the scan. In this case, it's addition for summing values.
- The *get()* member function of the *overall_result* future is used to wait for the result.

MPI_Reduce

The following code performs a global reduce operation across all processes.

MPI code:

```
#include <iostream>
#include <mpi.h>

int main(int argc, char *argv[]) {
    MPI_Init(&argc, &argv);

    int num_processes;
    MPI_Comm_size(MPI_COMM_WORLD, &num_processes);

    int this_rank;
    MPI_Comm_rank(MPI_COMM_WORLD, &this_rank);

    int value = this_rank;

    int result = 0;

    // Perform the reduction operation
    MPI_Reduce(&value, &result, 1, MPI_INT, MPI_SUM, 0, MPI_COMM_WORLD);

    // Print the result for the root process (process 0)
    if (this_rank == 0) {
        std::cout << "Locality " << this_rank << " has value " << result
                  << std::endl;
    }

    MPI_Finalize();
    return 0;
}
```

HPX equivalent:

```
std::uint32_t num_localities = hpx::get_num_localities(hpx::launch::sync);
std::uint32_t this_locality = hpx::get_locality_id();

auto reduce_direct_client = create_communicator(reduce_direct_basename,
        num_sites_arg(num_localities), this_site_arg(this_locality));

std::uint32_t value = hpx::get_locality_id();

if (this_locality == 0)
{
    hpx::future<std::uint32_t> overall_result = reduce_here(
        reduce_direct_client, value, std::plus<std::uint32_t>{});

    uint32_t r = overall_result.get();

    std::cout << "Locality " << this_locality << " has value " << r
              << std::endl;
}
```

(continues on next page)

(continued from previous page)

```

}
else
{
    hpx::future<void> overall_result =
        reduce_there(reduce_direct_client, std::move(value));
    overall_result.get();
}

```

This code will print the following message:

```
Locality 0 has value 1
```

HPX uses two functions to implement the functionality of *MPI_Reduce*: *reduce_here* and *reduce_there*. *reduce_here* is gathering data from all localities to the locality with ID 0 (root locality) and then performs the defined reduction operation. *reduce_there* allows non-root localities to participate in the reduction operation by sending data to the root locality. In more detail:

- *hpx::get_num_localities(hpx::launch::sync)* retrieves the number of localities, while *hpx::get_locality_id()* returns the ID of the current locality.
- The function *create_communicator()* is used to create a communicator called *reduce_direct_client*.
- If the current locality is the root (its ID is equal to 0):
 - The *reduce_here* function initiates a reduction operation with addition (*std::plus*) as the reduction operator. The result is stored in *overall_result*.
 - The *get()* member function of the *overall_result* future is used to wait for the result.
- If the current locality is not the root:
 - The *reduce_there* initiates a remote reduction operation.
 - The *get()* member function of the *overall_result* future is used to wait for the remote reduction operation to complete. This is done to ensure synchronization among localities.

Migrating to C++26 reflection-based actions

Starting with HPX 2.0, C++26 static reflection (P2996) can be used to define distributed actions without the verbose macro boilerplate previously required. This section describes how to migrate existing action definitions to the new reflection-based API when building with `HPX_WITH_CXX26_REFLECTION=ON`.

Build requirements

Reflection-based actions require a C++26-capable compiler with reflection support enabled:

- GCC 16.0.1 trunk or later (`stellargroup/gcc_trunk_build_env:1`) with `-freflection -std=c++26`
- Clang 22 with P2996 support (`stellargroup/clang_p2996_build_env:1`) with `-freflection-latest -stdlib=libc++`

Reflection support is auto-detected by HPX's CMake build system via `hpx_check_for_cxx26_reflection()` in `cmake/HPX_PerformCxxFeatureTests.cmake`. No manual flag is required when using a supported compiler — `HPX_HAVE_CXX26_REFLECTION` is set automatically.

Existing code requires no changes

The most important point: **existing code using** `HPX_PLAIN_ACTION`, `HPX_DEFINE_COMPONENT_ACTION`, and related macros requires zero source changes. When `HPX_WITH_CXX26_REFLECTION=ON`, these macros automatically use the reflection-based implementation internally. No `HPX_REGISTER_ACTION` calls are needed — registration is automatic.

```
// This works unchanged with or without reflection enabled.
// When HPX_WITH_CXX26_REFLECTION=ON, it automatically uses
// reflect_action<^^some_function> internally.
HPX_PLAIN_ACTION(some_function, some_action)
```

Explicit migration: plain actions

For new code or explicit migration, use `HPX_ACTION` or `reflect_action` directly:

```
// Before: three-step macro sequence
HPX_PLAIN_ACTION(app::compute, compute_action)
HPX_REGISTER_ACTION_DECLARATION(compute_action)
HPX_REGISTER_ACTION(compute_action)

// After: single line, no registration required
HPX_ACTION(app::compute, compute_action)

// Or equivalently, using the template directly:
using compute_action = hpx::actions::reflect_action<^^app::compute>;
```

Explicit migration: component actions

```
// Before: three-step macro sequence
HPX_DEFINE_COMPONENT_ACTION(server, compute, compute_action)
HPX_REGISTER_ACTION_DECLARATION(compute_action)
HPX_REGISTER_ACTION(compute_action)

// After: single line
HPX_COMPONENT_ACTION(server, compute, compute_action)

// Or equivalently:
using compute_action =
    hpx::actions::reflect_component_action<^^server::compute>;
```

Explicit migration: direct plain actions

```
// Before: three-step macro sequence
HPX_PLAIN_DIRECT_ACTION(app::compute, compute_action)
HPX_REGISTER_ACTION_DECLARATION(compute_action)
HPX_REGISTER_ACTION(compute_action)

// After: single line
```

(continues on next page)

(continued from previous page)

```
HPX_DIRECT_ACTION(app::compute, compute_action)

// Or equivalently, using the template directly:
using compute_action =
    hpx::actions::reflect_direct_action<^^app::compute>;
```

Explicit migration: direct component actions

Direct actions execute without spawning a new HPX thread — locally they run inline on the calling thread, and remotely on the target locality's existing HPX thread. The reflection-based API preserves this behavior:

```
// Before: three-step macro sequence
HPX_DEFINE_COMPONENT_DIRECT_ACTION(server, compute, compute_action)
HPX_REGISTER_ACTION_DECLARATION(compute_action)
HPX_REGISTER_ACTION(compute_action)

// After: single line
HPX_COMPONENT_DIRECT_ACTION(server, compute, compute_action)

// Or equivalently, using the template directly:
using compute_action =
    hpx::actions::reflect_component_direct_action<^^server::compute>;
```

Overloaded functions

Reflection cannot disambiguate overloaded functions. If your action function is overloaded, keep the existing HPX_PLAIN_ACTION macro:

```
// Not supported with reflection (ambiguous):
// using my_action = hpx::actions::reflect_action<^^overloaded_func>;

// Use the existing macro instead:
HPX_PLAIN_ACTION(static_cast<int*>)(int)>(overloaded_func), my_action)
```

Properties available at compile time

Reflection-based action types expose additional compile-time properties:

```
using my_action = hpx::actions::reflect_action<^^app::compute>;

// Number of parameters
static_assert(my_action::arity == 2);

// Function pointer type and value
using fptr = my_action::func_ptr_type;
constexpr auto fp = my_action::func_ptr;
```

2.4.7 Building tests and examples

Tests

To build the tests:

```
$ cmake --build . --target tests
```

To control which tests to run use `ctest`:

- To run single tests, for example a test for `for_loop`:

```
$ ctest --output-on-failure -R tests.unit.modules.algorithms.algorithms.for_loop
```

- To run a whole group of tests:

```
$ ctest --output-on-failure -R tests.unit
```

Examples

- To build (and install) all examples invoke:

```
$ cmake -DHPX_WITH_EXAMPLES=On .  
$ make examples  
$ make install
```

- To build the `hello_world_1` example run:

```
$ make hello_world_1
```

HPX executables end up in the `bin` directory in your build directory. You can now run `hello_world_1` and should see the following output:

```
$ ./bin/hello_world_1  
Hello World!
```

You've just run an example which prints `Hello World!` from the *HPX* runtime. The source for the example is in `examples/quickstart/hello_world_1.cpp`. The `hello_world_distributed` example (also available in the `examples/quickstart` directory) is a distributed hello world program, which is described in *Remote execution with actions*. It provides a gentle introduction to the distributed aspects of *HPX*.

Tip: Most build targets in *HPX* have two names: a simple name and a hierarchical name corresponding to what type of example or test the target is. If you are developing *HPX* it is often helpful to run `make help` to get a list of available targets. For example, `make help | grep hello_world` outputs the following:

```
... examples.quickstart.hello_world_2  
... hello_world_2  
... examples.quickstart.hello_world_1  
... hello_world_1  
... examples.quickstart.hello_world_distributed  
... hello_world_distributed
```

It is also possible to build, for instance, all quickstart examples using `make examples.quickstart`.

2.4.8 Creating HPX projects

Using HPX with pkg-config

How to build HPX applications with pkg-config

After you are done installing *HPX*, you should be able to build the following program. It prints Hello World! on the *locality* you run it on.

```
// Including 'hpx/hpx_main.hpp' instead of the usual 'hpx/hpx_init.hpp' enables
// to use the plain C-main below as the direct main HPX entry point.
#include <hpx/hpx_main.hpp>
#include <hpx/iostream.hpp>

int main()
{
    // Say hello to the world!
    hpx::cout << "Hello World!\n" << std::flush;
    return 0;
}
```

Copy the text of this program into a file called `hello_world.cpp`.

Now, in the directory where you put `hello_world.cpp`, issue the following commands (where `$HPX_LOCATION` is the build directory or `CMAKE_INSTALL_PREFIX` you used while building *HPX*):

```
$ export PKG_CONFIG_PATH=$PKG_CONFIG_PATH:$HPX_LOCATION/lib/pkgconfig
$ c++ -o hello_world hello_world.cpp \
    `pkg-config --cflags --libs hpx_application` \
    -lhpx_iostreams -DHPX_APPLICATION_NAME=hello_world
```

Important: When using `pkg-config` with *HPX*, the `pkg-config` flags must go after the `-o` flag.

Note: *HPX* libraries have different names in debug and release mode. If you want to link against a debug *HPX* library, you need to use the `_debug` suffix for the `pkg-config` name. That means instead of `hpx_application` or `hpx_component`, you will have to use `hpx_application_debug` or `hpx_component_debug`. Moreover, all referenced *HPX* components need to have an appended `d` suffix. For example, instead of `-lhpx_iostreams` you will need to specify `-lhpx_iostreamsd`.

Important: If the *HPX* libraries are in a path that is not found by the dynamic linker, you will need to add the path `$HPX_LOCATION/lib` to your linker search path (for example `LD_LIBRARY_PATH` on Linux).

To test the program, type:

```
$ ./hello_world
```

which should print Hello World! and exit.

How to build *HPX* components with pkg-config

Let's try a more complex example involving an *HPX* component. An *HPX* component is a class that exposes *HPX* actions. *HPX* components are compiled into dynamically loaded modules called component libraries. Here's the source code:

hello_world_component.cpp

```
#include <hpx/config.hpp>
#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/iostream.hpp>
#include "hello_world_component.hpp"

#include <iostream>

namespace examples { namespace server {
    void hello_world::invoke()
    {
        hpx::cout << "Hello HPX World!" << std::endl;
    }
}} // namespace examples::server

HPX_REGISTER_COMPONENT_MODULE()

typedef hpx::components::component<examples::server::hello_world>
    hello_world_type;

HPX_REGISTER_COMPONENT(hello_world_type, hello_world)

HPX_REGISTER_ACTION(
    examples::server::hello_world::invoke_action, hello_world_invoke_action)
#endif
```

hello_world_component.hpp

```
#pragma once

#include <hpx/config.hpp>
#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/hpx.hpp>
#include <hpx/include/actions.hpp>
#include <hpx/include/components.hpp>
#include <hpx/include/lcos.hpp>
#include <hpx/serialization.hpp>

#include <utility>

namespace examples { namespace server {
    struct HPX_COMPONENT_EXPORT hello_world
        : hpx::components::component_base<hello_world>
    {
        void invoke();
        HPX_DEFINE_COMPONENT_ACTION(hello_world, invoke)
    };
}
```

(continues on next page)

(continued from previous page)

```

}} // namespace examples::server

HPX_REGISTER_ACTION_DECLARATION(
    examples::server::hello_world::invoke_action, hello_world_invoke_action)

namespace examples {
    struct hello_world
    : hpx::components::client_base<hello_world, server::hello_world>
    {
        typedef hpx::components::client_base<hello_world, server::hello_world>
            base_type;

        hello_world(hpx::future<hpx::id_type>&& f)
            : base_type(std::move(f))
        {
        }

        hello_world(hpx::id_type&& f)
            : base_type(std::move(f))
        {
        }

        void invoke()
        {
            hpx::async<server::hello_world::invoke_action>(this->get_id())
                .get();
        }
    };
} // namespace examples

#endif

```

hello_world_client.cpp

```

#include <hpx/config.hpp>
#if defined(HPX_COMPUTE_HOST_CODE)
#include <hpx/wrap_main.hpp>

#include "hello_world_component.hpp"

int main()
{
    {
        // Create a single instance of the component on this locality.
        examples::hello_world client =
            hpx::new_<examples::hello_world>(hpx::find_here());

        // Invoke the component's action, which will print "Hello World!".
        client.invoke();
    }

    return 0;
}

```

(continues on next page)

(continued from previous page)

```
}  
#endif
```

Copy the three source files above into three files (called `hello_world_component.cpp`, `hello_world_component.hpp` and `hello_world_client.cpp`, respectively).

Now, in the directory where you put the files, run the following command to build the component library. (where `$HPX_LOCATION` is the build directory or `CMAKE_INSTALL_PREFIX` you used while building *HPX*):

```
$ export PKG_CONFIG_PATH=$PKG_CONFIG_PATH:$HPX_LOCATION/lib/pkgconfig  
$ c++ -o libhpx_hello_world.so hello_world_component.cpp \  
  `pkg-config --cflags --libs hpx_component` \  
  -lhpx_iostreams -DHPX_COMPONENT_NAME=hpx_hello_world
```

Now pick a directory in which to install your *HPX* component libraries. For this example, we'll choose a directory named `my_hpx_libs`:

```
$ mkdir ~/my_hpx_libs  
$ mv libhpx_hello_world.so ~/my_hpx_libs
```

Note: *HPX* libraries have different names in debug and release mode. If you want to link against a debug *HPX* library, you need to use the `_debug` suffix for the pkg-config name. That means instead of `hpx_application` or `hpx_component` you will have to use `hpx_application_debug` or `hpx_component_debug`. Moreover, all referenced *HPX* components need to have a appended `d` suffix, e.g. instead of `-lhpx_iostreams` you will need to specify `-lhpx_iostreamsd`.

Important: If the *HPX* libraries are in a path that is not found by the dynamic linker. You need to add the path `$HPX_LOCATION/lib` to your linker search path (for example `LD_LIBRARY_PATH` on Linux).

Now, to build the application that uses this component (`hello_world_client.cpp`), we do:

```
$ export PKG_CONFIG_PATH=$PKG_CONFIG_PATH:$HPX_LOCATION/lib/pkgconfig  
$ c++ -o hello_world_client hello_world_client.cpp \  
  `pkg-config --cflags --libs hpx_application` \  
  -L${HOME}/my_hpx_libs -lhpx_hello_world -lhpx_iostreams
```

Important: When using `pkg-config` with *HPX*, the `pkg-config` flags must go after the `-o` flag.

Finally, you'll need to set your `LD_LIBRARY_PATH` before you can run the program. To run the program, type:

```
$ export LD_LIBRARY_PATH="$LD_LIBRARY_PATH:$HOME/my_hpx_libs"  
$ ./hello_world_client
```

which should print `Hello HPX World!` and exit.

Using HPX with CMake-based projects

In addition to the pkg-config support discussed on the previous pages, *HPX* comes with full CMake support. In order to integrate *HPX* into existing or new CMakeLists.txt, you can leverage the `find_package`⁶⁴ command integrated into CMake. Following, is a Hello World component example using CMake.

Let's revisit what we have. We have three files that compose our example application:

- `hello_world_component.hpp`
- `hello_world_component.cpp`
- `hello_world_client.hpp`

The basic structure to include *HPX* into your CMakeLists.txt is shown here:

```
# Require a recent version of cmake
cmake_minimum_required(VERSION 3.18 FATAL_ERROR)

# This project is C++ based.
project(your_app CXX)

# Instruct cmake to find the HPX settings
find_package(HPX)
```

In order to have CMake find *HPX*, it needs to be told where to look for the `HPXConfig.cmake` file that is generated when *HPX* is built or installed. It is used by `find_package(HPX)` to set up all the necessary macros needed to use *HPX* in your project. The ways to achieve this are:

- Set the `HPX_DIR` CMake variable to point to the directory containing the `HPXConfig.cmake` script on the command line when you invoke CMake:

```
$ cmake -DHPX_DIR=$HPX_LOCATION/lib/cmake/HPX ...
```

where `$HPX_LOCATION` is the build directory or `CMAKE_INSTALL_PREFIX` you used when building/configuring *HPX*.

- Set the `CMAKE_PREFIX_PATH` variable to the root directory of your *HPX* build or install location on the command line when you invoke CMake:

```
$ cmake -DCMAKE_PREFIX_PATH=$HPX_LOCATION ...
```

The difference between `CMAKE_PREFIX_PATH` and `HPX_DIR` is that CMake will add common postfixes, such as `lib/cmake/<project`, to the `CMAKE_PREFIX_PATH` and search in these locations too. Note that if your project uses *HPX* as well as other CMake-managed projects, the paths to the locations of these multiple projects may be concatenated in the `CMAKE_PREFIX_PATH`.

- The variables above may be set in the CMake GUI or curses `ccmake` interface instead of the command line.

Additionally, if you wish to require *HPX* for your project, replace the `find_package(HPX)` line with `find_package(HPX REQUIRED)`.

You can check if *HPX* was successfully found with the `HPX_FOUND` CMake variable.

⁶⁴ https://www.cmake.org/cmake/help/latest/command/find_package.html

Using CMake targets

The recommended way of setting up your targets to use *HPX* is to link to the `HPX::hpx` CMake⁶⁵ target:

```
target_link_libraries(hello_world_component PUBLIC HPX::hpx)
```

This requires that you have already created the target like this:

```
add_library(hello_world_component SHARED hello_world_component.cpp)
target_include_directories(hello_world_component PUBLIC ${CMAKE_CURRENT_SOURCE_DIR})
```

When you link your library to the `HPX::hpx` CMake⁶⁶ target, you will be able use *HPX* functionality in your library. To use `main()` as the implicit entry point in your application you must additionally link your application to the CMake target `HPX::wrap_main`. This target is automatically linked to executables if you are using the macros described below (*Using macros to create new targets*). See *Re-use the `main()` function as the main *HPX* entry point* for more information on implicitly using `main()` as the entry point. If you want the same wrapping behavior without including `hpx/hpx_main.hpp`⁶⁷, link to the `HPX::auto_wrap_main` target instead. This enables the runtime initialization around `main()` unconditionally and is useful for codebases where adding the header to `main.cpp` is impractical

Note: The use of `HPX::auto_wrap_main` is not supported when using the native Windows MSVC toolchain.

If you want to use the facilities exposed by `hpx::runtime_manager` in binaries that were not linked as executables (e.g., in shared libraries), you will need make your cmake target explicitly depend on the `HPX::init` target:

```
add_library(hello_world_component SHARED hello_world_component.cpp)
target_link_libraries(hello_world_component PRIVATE HPX::init)
```

Otherwise you may see compilation errors complaining about the header file `hpx/runtime_manager.hpp` not being found.

Creating a component requires setting two additional compile definitions:

```
target_compile_options(hello_world_component
    HPX_COMPONENT_NAME=hello_world
    HPX_COMPONENT_EXPORTS)
```

Instead of setting these definitions manually you may link to the `HPX::component` target, which sets `HPX_COMPONENT_NAME` to `hpx_<target_name>`, where `<target_name>` is the target name of your library. Note that these definitions should be `PRIVATE` to make sure these definitions are not propagated transitively to dependent targets.

In addition to making your library a component you can make it a plugin. To do so link to the `HPX::plugin` target. Similarly to `HPX::component` this will set `HPX_PLUGIN_NAME` to `hpx_<target_name>`. This definition should also be `PRIVATE`. Unlike regular shared libraries, plugins are loaded at runtime from certain directories and will not be found without additional configuration. Plugins should be installed into a directory containing only plugins. For example, the plugins created by *HPX* itself are installed into the `hpx` subdirectory in the library install directory (typically `lib` or `lib64`). When using the `HPX::plugin` target you need to install your plugins into an appropriate directory. You may also want to set the location of your plugin in the build directory with the `*_OUTPUT_DIRECTORY*` CMake target properties to be able to load the plugins in the build directory. Once you've set the install or output directory of your plugin you need to tell your executable where to find it at runtime. You can do this either by setting the environment variable `HPX_COMPONENT_PATHS` or the ini setting `hpx.component_paths` (see `--hpx:ini`) to the directory containing your plugin.

⁶⁵ <https://www.cmake.org>

⁶⁶ <https://www.cmake.org>

⁶⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/wrap/include/hpx/hpx_main.hpp

Using macros to create new targets

In addition to the targets described above, *HPX* provides convenience macros to hide optional boilerplate code that may be useful for your project. The link to the targets described above. We recommend that you use the targets directly whenever possible as they tend to compose better with other targets.

The macro for adding an *HPX* component is `add_hpx_component`. It can be used in your `CMakeLists.txt` file like this:

```
# build your application using HPX
add_hpx_component(hello_world
  SOURCES hello_world_component.cpp
  HEADERS hello_world_component.hpp
  COMPONENT_DEPENDENCIES iostreams)
```

Note: `add_hpx_component` adds a `_component` suffix to the target name. In the example above, a `hello_world_component` target will be created.

The available options to `add_hpx_component` are:

- `SOURCES`: The source files for that component
- `HEADERS`: The header files for that component
- `DEPENDENCIES`: Other libraries or targets this component depends on
- `COMPONENT_DEPENDENCIES`: The components this component depends on
- `PLUGIN`: Treats this component as a plugin-able library
- `COMPILE_FLAGS`: Additional compiler flags
- `LINK_FLAGS`: Additional linker flags
- `FOLDER`: Adds the headers and source files to this Source Group folder
- `EXCLUDE_FROM_ALL`: Do not build this component as part of the `all` target

After adding the component, the way you add the executable is as follows:

```
# build your application using HPX
add_hpx_executable(hello_world
  SOURCES hello_world_client.cpp
  COMPONENT_DEPENDENCIES hello_world)
```

Note: `add_hpx_executable` automatically adds a `_component` suffix to dependencies specified in `COMPONENT_DEPENDENCIES`, meaning you can directly use the name given when adding a component using `add_hpx_component`.

When you configure your application, all you need to do is set the `HPX_DIR` variable to point to the installation of *HPX*.

Note: All library targets built with *HPX* are exported and readily available to be used as arguments to `target_link_libraries`⁶⁸ in your targets. The *HPX* include directories are available with the `HPX_INCLUDE_DIRS` CMake variable.

⁶⁸ https://www.cmake.org/cmake/help/latest/command/target_link_libraries.html

Using the *HPX* compiler wrapper `hpxcxx`

The `hpxcxx` compiler wrapper helps to compile a *HPX* component, application, or object file, based on the arguments passed to it.

```
$ hpxcxx [--exe=<APPLICATION_NAME> | --comp=<COMPONENT_NAME> | -c] FLAGS FILES
```

The `hpxcxx` command **requires** that either an application or a component is built or `-c` flag is specified. If the build is against a debug build, the `-g` is to be specified while building.

Optional FLAGS

- `-l <LIBRARY> | -l<LIBRARY>`: Links `<LIBRARY>` to the build
- `-g`: Specifies that the application or component build is against a debug build
- `-rd`: Sets `release-with-debug-info` option
- `-mr`: Sets `minsize-release` option

All other flags (like `-o OUTPUT_FILE`) are directly passed to the underlying C++ compiler.

Using macros to set up existing targets to use *HPX*

In addition to the `add_hpx_component` and `add_hpx_executable`, you can use the `hpx_setup_target` macro to have an already existing target to be used with the *HPX* libraries:

```
hpx_setup_target(target)
```

Optional parameters are:

- `EXPORT`: Adds it to the CMake export list `HPXTargets`
- `INSTALL`: Generates an install rule for the target
- `PLUGIN`: Treats this component as a plugin-able library
- `TYPE`: The type can be: `EXECUTABLE`, `LIBRARY` or `COMPONENT`
- `DEPENDENCIES`: Other libraries or targets this component depends on
- `COMPONENT_DEPENDENCIES`: The components this component depends on
- `COMPILE_FLAGS`: Additional compiler flags
- `LINK_FLAGS`: Additional linker flags

If you do not use CMake, you can still build against *HPX*, but you should refer to the section on *How to build HPX components with pkg-config*.

Note: Since *HPX* relies on dynamic libraries, the dynamic linker needs to know where to look for them. If *HPX* isn't installed into a path that is configured as a linker search path, external projects need to either set `RPATH` or adapt `LD_LIBRARY_PATH` to point to where the *HPX* libraries reside. In order to set `RPATHs`, you can include `HPX_SetFullRPATH` in your project after all libraries you want to link against have been added. Please also consult the CMake documentation [here](https://gitlab.kitware.com/cmake/community/wikis/doc/cmake/RPATH-handling)⁶⁹.

⁶⁹ <https://gitlab.kitware.com/cmake/community/wikis/doc/cmake/RPATH-handling>

Using HPX with Makefile

A basic project building with *HPX* is through creating makefiles. The process of creating one can get complex depending upon the use of cmake parameter `HPX_WITH_HPX_MAIN` (which defaults to ON).

How to build *HPX* applications with makefile

If *HPX* is installed correctly, you should be able to build and run a simple Hello World program. It prints Hello World! on the *locality* you run it on.

```
// Including 'hpx/hpx_main.hpp' instead of the usual 'hpx/hpx_init.hpp' enables
// to use the plain C-main below as the direct main HPX entry point.
#include <hpx/hpx_main.hpp>
#include <hpx/iostream.hpp>

int main()
{
    // Say hello to the world!
    hpx::cout << "Hello World!\n" << std::flush;
    return 0;
}
```

Copy the content of this program into a file called `hello_world.cpp`.

Now, in the directory where you put `hello_world.cpp`, create a Makefile. Add the following code:

```
CXX=(CXX) # Add your favourite compiler here or let makefile choose default.

CXXFLAGS=-O3 -std=c++17

Boost_ROOT=/path/to/boost
Hwloc_ROOT=/path/to/hwloc
Tcmalloc_ROOT=/path/to/tcmalloc
HPX_ROOT=/path/to/hpx

INCLUDE_DIRECTIVES=$(HPX_ROOT)/include $(Boost_ROOT)/include $(Hwloc_ROOT)/include

LIBRARY_DIRECTIVES=-L$(HPX_ROOT)/lib $(HPX_ROOT)/lib/libhpx_init.a $(HPX_ROOT)/lib/
↳ libhpx.so $(Boost_ROOT)/lib/libboost_atomic-mt.so $(Boost_ROOT)/lib/libboost_
↳ filesystem-mt.so $(Boost_ROOT)/lib/libboost_program_options-mt.so $(Boost_ROOT)/lib/
↳ libboost_regex-mt.so $(Boost_ROOT)/lib/libboost_system-mt.so -lpthread $(Tcmalloc_
↳ ROOT)/libtcmalloc_minimal.so $(Hwloc_ROOT)/libhwloc.so -ldl -lrt

LINK_FLAGS=$(HPX_ROOT)/lib/libhpx_wrap.a -Wl,-wrap=main # should be left empty for HPX_
↳ WITH_HPX_MAIN=OFF

hello_world: hello_world.o
    $(CXX) $(CXXFLAGS) -o hello_world hello_world.o $(LIBRARY_DIRECTIVES) $(LINK_FLAGS)

hello_world.o:
    $(CXX) $(CXXFLAGS) -c -o hello_world.o hello_world.cpp $(INCLUDE_DIRECTIVES)
```

Important: `LINK_FLAGS` should be left empty if `HPX_WITH_HPX_MAIN` is set to OFF. Boost in the above example

is build with `--layout=tagged`. Actual Boost flags may vary on your build of Boost.

To build the program, type:

```
$ make
```

A successful build should result in `hello_world` binary. To test, type:

```
$ ./hello_world
```

How to build *HPX* components with makefile

Let's try a more complex example involving an *HPX* component. An *HPX* component is a class that exposes *HPX* actions. *HPX* components are compiled into dynamically-loaded modules called component libraries. Here's the source code:

hello_world_component.cpp

```
#include <hpx/config.hpp>
#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/iostream.hpp>
#include "hello_world_component.hpp"

#include <iostream>

namespace examples { namespace server {
    void hello_world::invoke()
    {
        hpx::cout << "Hello HPX World!" << std::endl;
    }
}} // namespace examples::server

HPX_REGISTER_COMPONENT_MODULE()

typedef hpx::components::component<examples::server::hello_world>
    hello_world_type;

HPX_REGISTER_COMPONENT(hello_world_type, hello_world)

HPX_REGISTER_ACTION(
    examples::server::hello_world::invoke_action, hello_world_invoke_action)
#endif
```

hello_world_component.hpp

```
#pragma once

#include <hpx/config.hpp>
#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/hpx.hpp>
#include <hpx/include/actions.hpp>
#include <hpx/include/components.hpp>
```

(continues on next page)

(continued from previous page)

```

#include <hpx/include/lcos.hpp>
#include <hpx/serialization.hpp>

#include <utility>

namespace examples { namespace server {
    struct HPX_COMPONENT_EXPORT hello_world
        : hpx::components::component_base<hello_world>
    {
        void invoke();
        HPX_DEFINE_COMPONENT_ACTION(hello_world, invoke)
    };
}} // namespace examples::server

HPX_REGISTER_ACTION_DECLARATION(
    examples::server::hello_world::invoke_action, hello_world_invoke_action)

namespace examples {
    struct hello_world
        : hpx::components::client_base<hello_world, server::hello_world>
    {
        typedef hpx::components::client_base<hello_world, server::hello_world>
            base_type;

        hello_world(hpx::future<hpx::id_type>&& f)
            : base_type(std::move(f))
        {
        }

        hello_world(hpx::id_type&& f)
            : base_type(std::move(f))
        {
        }

        void invoke()
        {
            hpx::async<server::hello_world::invoke_action>(this->get_id())
                .get();
        }
    };
} // namespace examples

#endif

```

hello_world_client.cpp

```

#include <hpx/config.hpp>
#if defined(HPX_COMPUTE_HOST_CODE)
#include <hpx/wrap_main.hpp>

#include "hello_world_component.hpp"

```

(continues on next page)

(continued from previous page)

```

int main()
{
    {
        // Create a single instance of the component on this locality.
        examples::hello_world client =
            hpx::new_<examples::hello_world>(hpx::find_here());

        // Invoke the component's action, which will print "Hello World!".
        client.invoke();
    }

    return 0;
}
#endif

```

Now, in the directory, create a Makefile. Add the following code:

```

CXX=(CXX) # Add your favourite compiler here or let makefile choose default.

CXXFLAGS=-O3 -std=c++17

Boost_ROOT=/path/to/boost
Hwloc_ROOT=/path/to/hwloc
Tcmalloc_ROOT=/path/to/tcmalloc
HPX_ROOT=/path/to/hpx

INCLUDE_DIRECTIVES=$(HPX_ROOT)/include $(Boost_ROOT)/include $(Hwloc_ROOT)/include

LIBRARY_DIRECTIVES=-L$(HPX_ROOT)/lib $(HPX_ROOT)/lib/libhpx_init.a $(HPX_ROOT)/lib/
↳ libhpx.so $(Boost_ROOT)/lib/libboost_atomic-mt.so $(Boost_ROOT)/lib/libboost_
↳ filesystem-mt.so $(Boost_ROOT)/lib/libboost_program_options-mt.so $(Boost_ROOT)/lib/
↳ libboost_regex-mt.so $(Boost_ROOT)/lib/libboost_system-mt.so -lpthread $(Tcmalloc_
↳ ROOT)/libtcmalloc_minimal.so $(Hwloc_ROOT)/libhwloc.so -ldl -lrt

LINK_FLAGS=$(HPX_ROOT)/lib/libhpx_wrap.a -Wl,-wrap=main # should be left empty for HPX_
↳ WITH_HPX_MAIN=OFF

hello_world_client: libhpx_hello_world hello_world_client.o
    $(CXX) $(CXXFLAGS) -o hello_world_client $(LIBRARY_DIRECTIVES) libhpx_hello_world
↳ $(LINK_FLAGS)

hello_world_client.o: hello_world_client.cpp
    $(CXX) $(CXXFLAGS) -o hello_world_client.o hello_world_client.cpp $(INCLUDE_DIRECTIVES)

libhpx_hello_world: hello_world_component.o
    $(CXX) $(CXXFLAGS) -o libhpx_hello_world hello_world_component.o $(LIBRARY_DIRECTIVES)

hello_world_component.o: hello_world_component.cpp
    $(CXX) $(CXXFLAGS) -c -o hello_world_component.o hello_world_component.cpp $(INCLUDE_
↳ DIRECTIVES)

```

To build the program, type:

```
$ make
```

A successful build should result in `hello_world` binary. To test, type:

```
$ ./hello_world
```

Note: Due to high variations in CMake flags and library dependencies, it is recommended to build *HPX* applications and components with `pkg-config` or `CMakeLists.txt`. Writing `Makefile` may result in broken builds if due care is not taken. `pkg-config` files and CMake systems are configured with CMake build of *HPX*. Hence, they are stable when used together and provide better support overall.

2.4.9 Starting the *HPX* runtime

In order to write an application that uses services from the *HPX* runtime system, you need to initialize the *HPX* library by inserting certain calls into the code of your application. Depending on your use case, this can be done in 3 different ways:

- *Minimally invasive:* Re-use the `main()` function as the main *HPX* entry point.
- *Balanced use case:* Supply your own main *HPX* entry point while blocking the main thread.
- *Most flexibility:* Supply your own main *HPX* entry point while avoiding blocking the main thread.
- *Suspend and resume:* As above but suspend and resume the *HPX* runtime to allow for other runtimes to be used.

Re-use the `main()` function as the main *HPX* entry point

This method is the least intrusive to your code. However, it provides you with the smallest flexibility in terms of initializing the *HPX* runtime system. The following code snippet shows what a minimal *HPX* application using this technique looks like:

```
#include <hpx/hpx_main.hpp>

int main(int argc, char* argv[])
{
    return 0;
}
```

The only change to your code you have to make is to include the file `hpx/hpx_main.hpp`. In this case the function `main()` will be invoked as the first *HPX* thread of the application. The runtime system will be initialized behind the scenes before the function `main()` is executed and will automatically stop after `main()` has returned. For this method to work you must link your application to the CMake⁷⁰ target `HPX::wrap_main`. This is done automatically if you are using the provided macros (*Using macros to create new targets*) to set up your application, but must be done explicitly if you are using targets directly (*Using CMake targets*). All *HPX* API functions can be used from within the `main()` function now. If you cannot or do not want to include `hpx/hpx_main.hpp` in `main.cpp`, you can instead link against `HPX::auto_wrap_main`. That target enables the same runtime startup path without needing the header-triggered option.

Note: The use of `HPX::auto_wrap_main` is not supported when using the native Windows MSVC toolchain.

⁷⁰ <https://www.cmake.org>

Note: The function `main()` does not need to expect receiving `argc` and `argv` as shown above, but could expose the signature `int main()`. This is consistent with the usually allowed prototypes for the function `main()` in C++ applications.

All command line arguments specific to *HPX* will still be processed by the *HPX* runtime system as usual. However, those command line options will be removed from the list of values passed to `argc/argv` of the function `main()`. The list of values passed to `main()` will hold only the commandline options that are not recognized by the *HPX* runtime system (see the section *HPX Command Line Options* for more details on what options are recognized by *HPX*).

Note: In this mode all one-letter shortcuts that are normally available on the *HPX* command line are disabled (such as `-t` or `-l` see *HPX Command Line Options*). This is done to minimize any possible interaction between the command line options recognized by the *HPX* runtime system and any command line options defined by the application.

The value returned from the function `main()` as shown above will be returned to the operating system as usual.

Important: To achieve this seamless integration, the header file `hpx/hpx_main.hpp` defines a macro:

```
#define main hpx_startup::user_main
```

which could result in unexpected behavior.

Important: To achieve this seamless integration, we use different implementations for different operating systems. In case of Linux or macOS, the code present in `hpx_wrap.cpp` is put into action. We hook into the system function in case of Linux and provide alternate entry point in case of macOS. For other operating systems we rely on a macro:

```
#define main hpx_startup::user_main
```

provided in the header file `hpx/hpx_main.hpp`. This implementation can result in unexpected behavior.

Caution: We make use of an *override* variable `include_libhpx_wrap` in the header file `hpx/hpx_main.hpp` to swiftly choose the function call stack at runtime. Therefore, the header file should *only* be included in the main executable. Including it in the components will result in multiple definition of the variable.

Supply your own main *HPX* entry point while blocking the main thread

With this method you need to provide an explicit main-thread function named `hpx_main` at global scope. This function will be invoked as the main entry point of your *HPX* application on the console *locality* only (this function will be invoked as the first *HPX* thread of your application). All *HPX* API functions can be used from within this function.

The thread executing the function `hpx::init` will block waiting for the runtime system to exit. The value returned from `hpx_main` will be returned from `hpx::init` after the runtime system has stopped.

The function `hpx::finalize` has to be called on one of the *HPX* localities in order to signal that all work has been scheduled and the runtime system should be stopped after the scheduled work has been executed.

This method of invoking *HPX* has the advantage of the user being able to decide which version of `hpx::init` to call. This allows to pass additional configuration parameters while initializing the *HPX* runtime system.


```
#include <hpx/hpx_init.hpp>

int hpx_main(int argc, char* argv[])
{
    // Any HPX application logic goes here...
    return hpx::finalize();
}

int main(int argc, char* argv[])
{
    // Initialize HPX, run hpx_main as the first HPX thread, and
    // wait for hpx::finalize being called.
    return hpx::init(argc, argv);
}
```

Note: The function `hpx_main` does not need to expect receiving `argc/argv` as shown above, but could expose one of the following signatures:

```
int hpx_main();
int hpx_main(int argc, char* argv[]);
int hpx_main(hpx::program_options::variables_map& vm);
```

This is consistent with (and extends) the usually allowed prototypes for the function `main()` in C++ applications.

The header file to include for this method of using *HPX* is `hpx/hpx_init.hpp`.

There are many additional overloads of `hpx::init` available, such as the ability to provide your own entry-point function instead of `hpx_main`. Please refer to the function documentation for more details (see: `hpx/hpx_init.hpp`).

Supply your own main *HPX* entry point while avoiding blocking the main thread

With this method you need to provide an explicit main thread function named `hpx_main` at global scope. This function will be invoked as the main entry point of your *HPX* application on the console *locality* only (this function will be invoked as the first *HPX* thread of your application). All *HPX* API functions can be used from within this function.

The thread executing the function `hpx::start` will *not* block waiting for the runtime system to exit, but will return immediately. The function `hpx::finalize` has to be called on one of the *HPX* localities in order to signal that all work has been scheduled and the runtime system should be stopped after the scheduled work has been executed.

This method of invoking *HPX* is useful for applications where the main thread is used for special operations, such as GUIs. The function `hpx::stop` can be used to wait for the *HPX* runtime system to exit and should at least be used as the last function called in `main()`. The value returned from `hpx_main` will be returned from `hpx::stop` after the runtime system has stopped.

```
#include <hpx/hpx_start.hpp>

int hpx_main(int argc, char* argv[])
{
    // Any HPX application logic goes here...
    return hpx::finalize();
}
```

(continues on next page)

(continued from previous page)

```
int main(int argc, char* argv[])
{
    // Initialize HPX, run hpx_main.
    hpx::start(argc, argv);

    // ...Execute other code here...

    // Wait for hpx::finalize being called.
    return hpx::stop();
}
```

Note: The function `hpx_main` does not need to expect receiving `argc/argv` as shown above, but could expose one of the following signatures:

```
int hpx_main();
int hpx_main(int argc, char* argv[]);
int hpx_main(hpx::program_options::variables_map& vm);
```

This is consistent with (and extends) the usually allowed prototypes for the function `main()` in C++ applications.

The header file to include for this method of using *HPX* is `hpx/hpx_start.hpp`.

There are many additional overloads of `hpx::start` available, such as the option for users to provide their own entry point function instead of `hpx_main`. Please refer to the function documentation for more details (see: `hpx/hpx_start.hpp`).

Supply your own explicit startup function as the main *HPX* entry point

There is also a way to specify any function (besides `hpx_main`) to be used as the main entry point for your *HPX* application:

```
#include <hpx/hpx_init.hpp>

int application_entry_point(int argc, char* argv[])
{
    // Any HPX application logic goes here...
    return hpx::finalize();
}

int main(int argc, char* argv[])
{
    // Initialize HPX, run application_entry_point as the first HPX thread,
    // and wait for hpx::finalize being called.
    return hpx::init(&application_entry_point, argc, argv);
}
```

Note: The function supplied to `hpx::init` must have one of the following prototypes:

```
int application_entry_point(int argc, char* argv[]);
int application_entry_point(hpx::program_options::variables_map&
    vm);
```

Note: If `nullptr` is used as the function argument, *HPX* will not run any startup function on this locality.

Suspending and resuming the *HPX* runtime

In some applications it is required to combine *HPX* with other runtimes. To support this use case, *HPX* provides two functions: `hpx::suspend` and `hpx::resume`. `hpx::suspend` is a blocking call which will wait for all scheduled tasks to finish executing and then put the thread pool OS threads to sleep. `hpx::resume` simply wakes up the sleeping threads so that they are ready to accept new work. `hpx::suspend` and `hpx::resume` can be found in the header `hpx/hpx_suspend.hpp`.

```
#include <hpx/hpx_start.hpp>
#include <hpx/hpx_suspend.hpp>

int main(int argc, char* argv[])
{
    // Initialize HPX, don't run hpx_main
    hpx::start(nullptr, argc, argv);

    // Schedule a function on the HPX runtime
    hpx::post(&my_function, ...);

    // Wait for all tasks to finish, and suspend the HPX runtime
    hpx::suspend();

    // Execute non-HPX code here

    // Resume the HPX runtime
    hpx::resume();

    // Schedule more work on the HPX runtime

    // hpx::finalize has to be called from the HPX runtime before hpx::stop
    hpx::post([]() { hpx::finalize(); });
    return hpx::stop();
}
```

Note: `hpx::suspend` does not wait for `hpx::finalize` to be called. Only call `hpx::finalize` when you wish to fully stop the *HPX* runtime.

Warning:

`hpx::suspend` only waits for local tasks, i.e. tasks on the current locality, to finish executing. When using `hpx::suspend` in a multi-locality scenario the user is responsible for ensuring that any work required from other localities has also finished.

HPX also supports suspending individual thread pools and threads. For details on how to do that, see the documentation

for `hpx::threads::thread_pool_base`.

Automatically suspending worker threads

The previous method guarantees that the worker threads are suspended when you ask for it and that they stay suspended. An alternative way to achieve the same effect is to tweak how quickly *HPX* suspends its worker threads when they run out of work. The following configuration values make sure that *HPX* idles very quickly:

```
hpx.max_idle_backoff_time = 1000
hpx.max_idle_loop_count = 0
```

They can be set on the command line using `--hpx:ini=hpx.max_idle_backoff_time=1000` and `--hpx:ini=hpx.max_idle_loop_count=0`. See *Launching and configuring HPX applications* for more details on how to set configuration parameters.

After setting idling parameters the previous example could now be written like this instead:

```
#include <hpx/hpx_start.hpp>

int main(int argc, char* argv[])
{
    // Initialize HPX, don't run hpx_main
    hpx::start(nullptr, argc, argv);

    // Schedule some functions on the HPX runtime
    // NOTE: run_as_hpx_thread blocks until completion.
    hpx::run_as_hpx_thread(&my_function, ...);
    hpx::run_as_hpx_thread(&my_other_function, ...);

    // hpx::finalize has to be called from the HPX runtime before hpx::stop
    hpx::post([]() { hpx::finalize(); });
    return hpx::stop();
}
```

In this example each call to `hpx::run_as_hpx_thread` acts as a “parallel region”.

Working of `hpx_main.hpp`

In order to initialize *HPX* from `main()`, we make use of linker tricks.

It is implemented differently for different operating systems. The method of implementation is as follows:

- *Linux*: Using linker `--wrap` option.
- *Mac OSX*: Using the linker `-e` option.
- *Windows*: Using `#define main hpx_startup::user_main`

Linux implementation

We make use of the Linux linker `ld`'s `--wrap` option to wrap the `main()` function. This way any calls to `main()` are redirected to our own implementation of `main`. It is here that we check for the existence of `hpx_main.hpp` by making use of a shadow variable `include_libhpx_wrap`. The value of this variable determines the function stack at runtime.

The implementation can be found in `libhpx_wrap.a`.

Important: It is necessary that `hpx_main.hpp` be not included more than once. Multiple inclusions can result in multiple definition of `include_libhpx_wrap`.

Mac OSX implementation

Here we make use of yet another linker option `-e` to change the entry point to our custom entry function `initialize_main`. We initialize the *HPX* runtime system from this function and call `main` from the initialized system. We determine the function stack at runtime by making use of the shadow variable `include_libhpx_wrap`.

The implementation can be found in `libhpx_wrap.a`.

Important: It is necessary that `hpx_main.hpp` be not included more than once. Multiple inclusions can result in multiple definition of `include_libhpx_wrap`.

Windows implementation

We make use of a macro `#define main hpx_startup::user_main` to take care of the initializations.

This implementation could result in unexpected behaviors.

2.4.10 Launching and configuring *HPX* applications

Configuring *HPX* applications

All *HPX* applications can be configured using special command line options and/or using special configuration files. This section describes the available options, the configuration file format, and the algorithm used to locate possible predefined configuration files. Additionally, this section describes the defaults assumed if no external configuration information is supplied.

During startup any *HPX* application applies a predefined search pattern to locate one or more configuration files. All found files will be read and merged in the sequence they are found into one single internal database holding all configuration properties. This database is used during the execution of the application to configure different aspects of the runtime system.

In addition to the ini files, any application can supply its own configuration files, which will be merged with the configuration database as well. Moreover, the user can specify additional configuration parameters on the command line when executing an application. The *HPX* runtime system will merge all command line configuration options (see the description of the `--hpx:ini`, `--hpx:config`, and `--hpx:app-config` command line options).

The *HPX* ini file format

All *HPX* applications can be configured using a special file format that is similar to the well-known [Windows INI file format](#)⁷¹. This is a structured text format that allows users to group key/value pairs (properties) into sections. The basic element contained in an ini file is the property. Every property has a name and a value, delimited by an equal sign '='. The name appears to the left of the equal sign:

```
name=value
```

The value may contain equal signs as only the first '=' character is interpreted as the delimiter between name and value. Whitespace before the name, after the value and immediately before and after the delimiting equal sign is ignored. Whitespace inside the value is retained.

Properties may be grouped into arbitrarily named sections. The section name appears on a line by itself, in square brackets. All properties after the section declaration are associated with that section. There is no explicit “end of section” delimiter; sections end at the next section declaration or the end of the file:

```
[section]
```

In *HPX* sections can be nested. A nested section has a name composed of all section names it is embedded in. The section names are concatenated using a dot '.':

```
[outer_section.inner_section]
```

Here, `inner_section` is logically nested within `outer_section`.

It is possible to use the full section name concatenated with the property name to refer to a particular property. For example, in:

```
[a.b.c]  
d = e
```

the property value of `d` can be referred to as `a.b.c.d=e`.

In *HPX* ini files can contain comments. Hash signs '#' at the beginning of a line indicate a comment. All characters starting with '#' until the end of the line are ignored.

If a property with the same name is reused inside a section, the second occurrence of this property name will override the first occurrence (discard the first value). Duplicate sections simply merge their properties together, as if they occurred contiguously.

In *HPX* ini files a property value `${F00:default}` will use the environmental variable `F00` to extract the actual value if it is set and `default` otherwise. No default has to be specified. Therefore, `${F00}` refers to the environmental variable `F00`. If `F00` is not set or empty, the overall expression will evaluate to an empty string. A property value `[$section.key:default]` refers to the value held by the property `section.key` if it exists and `default` otherwise. No default has to be specified. Therefore `[$section.key]` refers to the property `section.key`. If the property `section.key` is not set or empty, the overall expression will evaluate to an empty string.

Note: Any property `[$section.key:default]` is evaluated whenever it is queried and not when the configuration data is initialized. This allows for lazy evaluation and relaxes initialization order of different sections. The only exception are recursive property values, e.g., values referring to the very key they are associated with. Those property values are evaluated at initialization time to avoid infinite recursion.

⁷¹ https://en.wikipedia.org/wiki/INI_file

Built-in default configuration settings

During startup any *HPX* application applies a predefined search pattern to locate one or more configuration files. All found files will be read and merged in the sequence they are found into one single internal data structure holding all configuration properties.

As a first step the internal configuration database is filled with a set of default configuration properties. Those settings are described on a section by section basis below.

Note: You can print the default configuration settings used for an executable by specifying the command line option `--hpx:dump-config`.

The system configuration section

```
[system]
pid = <process-id>
prefix = <current prefix path of core HPX library>
executable = <current prefix path of executable>
```

Property	Description
<code>system.pid</code>	This is initialized to store the current OS-process id of the application instance.
<code>system.prefix</code>	This is initialized to the base directory <i>HPX</i> has been loaded from.
<code>system.executable_prefix</code>	This is initialized to the base directory the current executable has been loaded from.

The *HPX* configuration section

```
[hpx]
location = ${HPX_LOCATION:${system.prefix}}
component_path = ${hpx.location}/lib/hpx:${system.executable_prefix}/lib/hpx:${system.
↪executable_prefix}/../lib/hpx
master_ini_path = ${hpx.location}/share/hpx-<version>:${system.executable_prefix}/share/
↪hpx-<version>:${system.executable_prefix}/../share/hpx-<version>
ini_path = ${hpx.master_ini_path}/ini
os_threads = 1
cores = all
localities = 1
program_name =
cmd_line =
lock_detection = ${HPX_LOCK_DETECTION:0}
throw_on_held_lock = ${HPX_THROW_ON_HELD_LOCK:1}
minimal_deadlock_detection = <debug>
spinlock_deadlock_detection = <debug>
spinlock_deadlock_detection_limit = ${HPX_SPINLOCK_DEADLOCK_DETECTION_LIMIT:1000000}
max_background_threads = ${HPX_MAX_BACKGROUND_THREADS:${hpx.os_threads}}
max_idle_loop_count = ${HPX_MAX_IDLE_LOOP_COUNT:<hpx_idle_loop_count_max>}
max_busy_loop_count = ${HPX_MAX_BUSY_LOOP_COUNT:<hpx_busy_loop_count_max>}
max_idle_backoff_time = ${HPX_MAX_IDLE_BACKOFF_TIME:<hpx_idle_backoff_time_max>}
```

(continues on next page)

(continued from previous page)

```
exception_verbosity = ${HPX_EXCEPTION_VERBOSITY:2}
trace_depth = ${HPX_TRACE_DEPTH:20}
handle_signals = ${HPX_HANDLE_SIGNALS:1}
handle_failed_new = ${HPX_HANDLE_FAILED_NEW:1}



### [hpx.stacks]


small_size = ${HPX_SMALL_STACK_SIZE:<hpx_small_stack_size>}
medium_size = ${HPX_MEDIUM_STACK_SIZE:<hpx_medium_stack_size>}
large_size = ${HPX_LARGE_STACK_SIZE:<hpx_large_stack_size>}
huge_size = ${HPX_HUGE_STACK_SIZE:<hpx_huge_stack_size>}
use_guard_pages = ${HPX_THREAD_GUARD_PAGE:1}
```


Property	Description
<code>hpx.location</code>	This is initialized to the id of the <i>locality</i> this application instance is running on.
<code>hpx.component_path</code>	Duplicates are discarded. This property can refer to a list of directories separated by ':' (Linux, Android, and MacOS) or by ';' (Windows).
<code>hpx.master_ini_path</code>	This is initialized to the list of default paths of the main <code>hpx.ini</code> configuration files. This property can refer to a list of directories separated by ':' (Linux, Android, and MacOS) or using ';' (Windows).
<code>hpx.ini_path</code>	This is initialized to the default path where <i>HPX</i> will look for more ini configuration files. This property can refer to a list of directories separated by ':' (Linux, Android, and MacOS) or using ';' (Windows).
<code>hpx.os_threads</code>	This setting reflects the number of OS threads used for running <i>HPX</i> threads. Defaults to number of detected cores (not hyperthreads/PUs).
<code>hpx.cores</code>	This setting reflects the number of cores used for running <i>HPX</i> threads. Defaults to number of detected cores (not hyperthreads/PUs).
<code>hpx.localities</code>	This setting reflects the number of localities the application is running on. Defaults to 1.
<code>hpx.program_name</code>	This setting reflects the program name of the application instance. Initialized from the command line <code>argv[0]</code> .
<code>hpx.cmd_line</code>	This setting reflects the actual command line used to launch this application instance.
<code>hpx.lock_detection</code>	This setting verifies that no locks are being held while a <i>HPX</i> thread is suspended. This setting is applicable only if <code>HPX_WITH_VERIFY_LOCKS</code> is set during configuration in CMake.
<code>hpx.throw_on_hold</code>	This setting causes an exception if during lock detection at least one lock is being held while a <i>HPX</i> thread is suspended. This setting is applicable only if <code>HPX_WITH_VERIFY_LOCKS</code> is set during configuration in CMake. This setting has no effect if <code>hpx.lock_detection=0</code> .
<code>hpx.minimal_deadlock_detection</code>	This setting enables support for minimal deadlock detection for <i>HPX</i> threads. By default this is set to 1 (for Debug builds) or to 0 (for Release, RelWithDebInfo, RelMinSize builds). This setting is effective only if <code>HPX_WITH_THREAD_DEADLOCK_DETECTION</code> is set during configuration in CMake.
<code>hpx.spinlock_deadlock_detection</code>	This setting verifies that spinlocks don't spin longer than specified using the <code>spinlock_deadlock_detection_limit</code> . This setting is applicable only if <code>HPX_WITH_SPINLOCK_DEADLOCK_DETECTION</code> is set during configuration in CMake. By default this is set to 1 (for Debug builds) or to 0 (for Release, RelWithDebInfo, RelMinSize builds).
<code>hpx.spinlock_deadlock_detection_limit</code>	This setting specifies the upper limit of the allowed number of spins that spinlocks are allowed to perform. This setting is applicable only if <code>HPX_WITH_SPINLOCK_DEADLOCK_DETECTION</code> is set during configuration in CMake. By default this is set to 1000000.
<code>hpx.max_background_threads</code>	This setting defines the number of threads in the scheduler, which are used to execute background work. By default this is the same as the number of cores used for the scheduler.
<code>hpx.max_idle_loop_count</code>	By default this is defined by the preprocessor constant <code>HPX_IDLE_LOOP_COUNT_MAX</code> . This is an internal setting that you should change only if you know exactly what you are doing.
<code>hpx.max_busy_loop_count</code>	This setting defines the maximum value of the busy-loop counter in the scheduler. By default this is defined by the preprocessor constant <code>HPX_BUSY_LOOP_COUNT_MAX</code> . This is an internal setting that you should change only if you know exactly what you are doing.
<code>hpx.max_idle_backoff_time</code>	This setting defines the maximum time (in milliseconds) for the scheduler to sleep after <code>hpx.max_idle_loop_count</code> iterations. This setting is applicable only if <code>HPX_WITH_THREAD_MANAGER_IDLE_BACKOFF</code> is set during configuration in CMake ⁷² . By default this is defined by the preprocessor constant <code>HPX_IDLE_BACKOFF_TIME_MAX</code> . This is an internal setting that you should change only if you know exactly what you are doing.
<code>hpx.exception_verbosity</code>	This setting defines the verbosity of exceptions. Valid values are integers. A setting of 2 or higher prints all available information. A setting of 1 leaves out the build configuration and environment variables. A setting of 0 or lower prints only the description of the thrown exception and the file name, function, and line number where the exception was thrown. The default value is 2 or the value of the environment variable <code>HPX_EXCEPTION_VERBOSITY</code> .
<code>hpx.trace_depth</code>	This setting defines the number of stack-levels printed in generated stack backtraces. This defaults to 20, but can be changed using the cmake <code>HPX_WITH_THREAD_BACKTRACE_DEPTH</code> configuration setting.
<code>hpx.handle_signals</code>	This setting defines whether <i>HPX</i> will register signal handlers that will print the configuration information (stack backtrace, system information, etc.) whenever a signal is raised. The default is 1. Setting this value to 0 can be useful in cases when generating a core-dump on segmentation faults or similar signals is desired.

The `hpx.threadpools` configuration section

```
[hpx.threadpools]
io_pool_size = ${HPX_NUM_IO_POOL_SIZE:2}
parcel_pool_size = ${HPX_NUM_PARCEL_POOL_SIZE:2}
timer_pool_size = ${HPX_NUM_TIMER_POOL_SIZE:2}
```

Property	Description
<code>hpx.threadpools.io_pool_size</code>	The value of this property defines the number of OS threads created for the internal I/O thread pool.
<code>hpx.threadpools.parcel_pool_size</code>	The value of this property defines the number of OS threads created for the internal parcel thread pool.
<code>hpx.threadpools.timer_pool_size</code>	The value of this property defines the number of OS threads created for the internal timer thread pool.

The `hpx.thread_queue` configuration section

Important: These are the setting control internal values used by the thread scheduling queues in the *HPX* scheduler. You should not modify these settings unless you know exactly what you are doing.

```
[hpx.thread_queue]
min_tasks_to_steal_pending = ${HPX_THREAD_QUEUE_MIN_TASKS_TO_STEAL_PENDING:0}
min_tasks_to_steal_staged = ${HPX_THREAD_QUEUE_MIN_TASKS_TO_STEAL_STAGED:0}
min_add_new_count = ${HPX_THREAD_QUEUE_MIN_ADD_NEW_COUNT:10}
max_add_new_count = ${HPX_THREAD_QUEUE_MAX_ADD_NEW_COUNT:10}
max_delete_count = ${HPX_THREAD_QUEUE_MAX_DELETE_COUNT:1000}
```

Property	Description
<code>hpx.thread_queue.min_tasks_to_steal_pending</code>	The value of this property defines the number of pending <i>HPX</i> threads that have to be available before neighboring cores are allowed to steal work. The default is to allow stealing always.
<code>hpx.thread_queue.min_tasks_to_steal_staged</code>	The value of this property defines the number of staged <i>HPX</i> tasks that need to be available before neighboring cores are allowed to steal work. The default is to allow stealing always.
<code>hpx.thread_queue.min_add_new_count</code>	The value of this property defines the minimal number of tasks to be converted into <i>HPX</i> threads whenever the thread queues for a core have run empty.
<code>hpx.thread_queue.max_add_new_count</code>	The value of this property defines the maximal number of tasks to be converted into <i>HPX</i> threads whenever the thread queues for a core have run empty.
<code>hpx.thread_queue.max_delete_count</code>	The value of this property defines the number of terminated <i>HPX</i> threads to discard during each invocation of the corresponding function.

⁷² <https://www.cmake.org>

The `hpx.components` configuration section

```
[hpx.components]
load_external = ${HPX_LOAD_EXTERNAL_COMPONENTS:1}
```

Property	Description
<code>hpx.components.load_external</code>	This entry defines whether external components will be loaded on this <i>locality</i> . This entry is normally set to 1, and usually there is no need to directly change this value. It is automatically set to 0 for a dedicated AGAS server <i>locality</i> .

Additionally, the section `hpx.components` will be populated with the information gathered from all found components. The information loaded for each of the components will contain at least the following properties:

```
[hpx.components.<component_instance_name>]
name = <component_name>
path = <full_path_of_the_component_module>
enabled = ${hpx.components.load_external}
```

Property	Description
<code>hpx.components.<component_instance_name>.name</code>	This is the name of a component, usually the same as the second argument to the macro used while registering the component with <code>HPX_REGISTER_COMPONENT</code> . Set by the component factory.
<code>hpx.components.<component_instance_name>.path</code>	This is either the full path file name of the component module or the directory the component module is located in. In this case, the component module name will be derived from the property <code>hpx.components.<component_instance_name>.name</code> . Set by the component factory.
<code>hpx.components.<component_instance_name>.enabled</code>	This setting explicitly enables or disables the component. This is an optional property. <code>HPX</code> assumes that the component is enabled if it is not defined.

The value for `<component_instance_name>` is usually the same as for the corresponding `name` property. However, generally it can be defined to any arbitrary instance name. It is used to distinguish between different ini sections, one for each component.

The `hpx.parcel` configuration section

```
[hpx.parcel]
address = ${HPX_PARCEL_SERVER_ADDRESS:<hpx_initial_ip_address>}
port = ${HPX_PARCEL_SERVER_PORT:<hpx_initial_ip_port>}
bootstrap = ${HPX_PARCEL_BOOTSTRAP:<hpx_parcel_bootstrap>}
max_connections = ${HPX_PARCEL_MAX_CONNECTIONS:<hpx_parcel_max_connections>}
max_connections_per_locality = ${HPX_PARCEL_MAX_CONNECTIONS_PER_LOCALITY:<hpx_parcel_max_
↳connections_per_locality>}
max_message_size = ${HPX_PARCEL_MAX_MESSAGE_SIZE:<hpx_parcel_max_message_size>}
max_outbound_message_size = ${HPX_PARCEL_MAX_OUTBOUND_MESSAGE_SIZE:<hpx_parcel_max_
↳outbound_message_size>}
array_optimization = ${HPX_PARCEL_ARRAY_OPTIMIZATION:1}
zero_copy_optimization = ${HPX_PARCEL_ZERO_COPY_OPTIMIZATION:${hpx.parcel.array_
↳optimization}}
```

(continues on next page)

(continued from previous page)

```

zero_copy_receive_optimization = ${HPX_PARCEL_ZERO_COPY_RECEIVE_OPTIMIZATION:${hpx.
↪parcel.array_optimization}}
async_serialization = ${HPX_PARCEL_ASYNC_SERIALIZATION:1}
message_handlers = ${HPX_PARCEL_MESSAGE_HANDLERS:0}

```

Property	Description
<code>hpx.parcel.address</code>	This property defines the default IP address to be used for the <i>parcel</i> layer to listen to. This IP address will be used as long as no other values are specified (for instance, using the <code>--hpx:hpx</code> command line option). The expected format is any valid IP address or domain name format that can be resolved into an IP address. The default depends on the compile time preprocessor constant <code>HPX_INITIAL_IP_ADDRESS</code> ("127.0.0.1").
<code>hpx.parcel.port</code>	This property defines the default IP port to be used for the <i>parcel</i> layer to listen to. This IP port will be used as long as no other values are specified (for instance using the <code>--hpx:hpx</code> command line option). The default depends on the compile time preprocessor constant <code>HPX_INITIAL_IP_PORT</code> (7910).
<code>hpx.parcel.bootstrap</code>	This property defines which <i>parcelpport</i> type should be used during application bootstrap. The default depends on the compile time preprocessor constant <code>HPX_PARCEL_BOOTSTRAP</code> ("tcp").
<code>hpx.parcel.max_connections</code>	This property defines how many network connections between different localities are overall kept alive by each <i>locality</i> . The default depends on the compile time preprocessor constant <code>HPX_PARCEL_MAX_CONNECTIONS</code> (512).
<code>hpx.parcel.max_connections_per_locality</code>	This property defines the maximum number of network connections that one <i>locality</i> will open to another <i>locality</i> . The default depends on the compile time preprocessor constant <code>HPX_PARCEL_MAX_CONNECTIONS_PER_LOCALITY</code> (4).
<code>hpx.parcel.max_message_size</code>	This property defines the maximum allowed message size that will be transferrable through the <i>parcel</i> layer. The default depends on the compile time preprocessor constant <code>HPX_PARCEL_MAX_MESSAGE_SIZE</code> (1000000000 bytes).
<code>hpx.parcel.max_outbound_message_size</code>	This property defines the maximum allowed outbound coalesced message size that will be transferrable through the <i>parcel</i> layer. The default depends on the compile time preprocessor constant <code>HPX_PARCEL_MAX_OUTBOUND_MESSAGE_SIZE</code> (1000000 bytes).
<code>hpx.parcel.array_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize array optimizations during serialization of <i>parcel</i> data. The default is 1.
<code>hpx.parcel.zero_copy_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations during serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.array_optimization</code> .
<code>hpx.parcel.zero_copy_receive_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations on the receiving end during de-serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.array_optimization</code> .
<code>hpx.parcel.zero_copy_serialization_threshold</code>	This property defines the threshold value (in bytes) starting at which the serialization layer will apply zero-copy optimizations for serialized entities. The default value is defined by the preprocessor constant <code>HPX_ZERO_COPY_SERIALIZATION_THRESHOLD</code> .
<code>hpx.parcel.async_serialization</code>	This property defines whether this <i>locality</i> is allowed to spawn a new thread for serialization (this is both for encoding and decoding parcels). The default is 1.
<code>hpx.parcel.message_handlers</code>	This property defines whether message handlers are loaded. The default is 0.
<code>hpx.parcel.max_background_threads</code>	This property defines how many cores should be used to perform background operations. The default is -1 (all cores).

The following settings relate to the TCP/IP parcelport.

```
[hpx.parcel.tcp]
enable = ${HPX_HAVE_PARCELPORT_TCP:${hpx.parcel.enabled}}
array_optimization = ${HPX_PARCEL_TCP_ARRAY_OPTIMIZATION:${hpx.parcel.array_
↳optimization}}
zero_copy_optimization = ${HPX_PARCEL_TCP_ZERO_COPY_OPTIMIZATION:${hpx.parcel.zero_copy_
↳optimization}}
zero_copy_receive_optimization = ${HPX_PARCEL_TCP_ZERO_COPY_RECEIVE_OPTIMIZATION:${hpx.
↳parcel.zero_copy_receive_optimization}}
zero_copy_serialization_threshold = ${HPX_PARCEL_TCP_ZERO_COPY_SERIALIZATION_THRESHOLD:
↳${hpx.parcel.zero_copy_serialization_threshold}}
async_serialization = ${HPX_PARCEL_TCP_ASYNC_SERIALIZATION:${hpx.parcel.async_
↳serialization}}
parcel_pool_size = ${HPX_PARCEL_TCP_PARCEL_POOL_SIZE:${hpx.threadpools.parcel_pool_size}}
max_connections = ${HPX_PARCEL_TCP_MAX_CONNECTIONS:${hpx.parcel.max_connections}}
max_connections_per_locality = ${HPX_PARCEL_TCP_MAX_CONNECTIONS_PER_LOCALITY:${hpx.
↳parcel.max_connections_per_locality}}
max_message_size = ${HPX_PARCEL_TCP_MAX_MESSAGE_SIZE:${hpx.parcel.max_message_size}}
max_outbound_message_size = ${HPX_PARCEL_TCP_MAX_OUTBOUND_MESSAGE_SIZE:${hpx.parcel.max_
↳outbound_message_size}}
max_background_threads = ${HPX_PARCEL_TCP_MAX_BACKGROUND_THREADS:${hpx.parcel.max_
↳background_threads}}
```

Property	Description
<code>hpx.parcel.tcp.enable</code>	Enables the use of the default TCP parcelport. Note that the initial bootstrap of the overall HPX application will be performed using the default TCP connections. This parcelport is enabled by default. This will be disabled only if MPI is enabled (see below).
<code>hpx.parcel.tcp.array_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize array optimizations in the TCP/IP parcelport during serialization of parcel data. The default is the same value as set for <code>hpx.parcel.array_optimization</code> .
<code>hpx.parcel.tcp.zero_copy_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations during serialization of parcel data. The default is the same value as set for <code>hpx.parcel.zero_copy_optimization</code> .
<code>hpx.parcel.tcp.zero_copy_receive_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations on the receiving end in the TCP/IP parcelport during de-serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.zero_copy_optimization</code> .
<code>hpx.parcel.tcp.zero_copy_serialization_threshold</code>	This property defines the threshold value (in bytes) starting at which the serialization layer will apply zero copy optimizations for serialized entities. The default is the same value as set for <code>hpx.parcel.zero_copy_serialization_threshold</code> .
<code>hpx.parcel.tcp.async_serialization</code>	This property defines whether this <i>locality</i> is allowed to spawn a new thread for serialization in the TCP/IP parcelport (this is both for encoding and decoding parcels). The default is the same value as set for <code>hpx.parcel.async_serialization</code> .
<code>hpx.parcel.tcp.parcel_pool_size</code>	The value of this property defines the number of OS threads created for the internal parcel thread pool of the TCP <i>parcel</i> port. The default is taken from <code>hpx.threadpools.parcel_pool_size</code> .
<code>hpx.parcel.tcp.max_connections</code>	This property defines how many network connections between different localities are overall kept alive by each <i>locality</i> . The default is taken from <code>hpx.parcel.max_connections</code> .
<code>hpx.parcel.tcp.max_connections_per_locality</code>	This property defines the maximum number of network connections that one <i>locality</i> will open to another <i>locality</i> . The default is taken from <code>hpx.parcel.max_connections_per_locality</code> .
<code>hpx.parcel.tcp.max_message_size</code>	This property defines the maximum allowed message size that will be transferrable through the <i>parcel</i> layer. The default is taken from <code>hpx.parcel.max_message_size</code> .
<code>hpx.parcel.tcp.max_outbound_message_size</code>	This property defines the maximum allowed outbound coalesced message size that will be transferrable through the <i>parcel</i> layer. The default is taken from <code>hpx.parcel.max_outbound_message_size</code> .
<code>hpx.parcel.tcp.max_background_threads</code>	This property defines how many cores should be used to perform background operations. The default is taken from <code>hpx.parcel.max_background_threads</code> .

The following settings relate to the MPI parcelport. These settings take effect only if the compile time constant `HPX_HAVE_PARCELPOR_T_MPI` is set (the equivalent CMake variable is `HPX_WITH_PARCELPOR_T_MPI` and has to be set to ON).

```
[hpx.parcel.mpi]
enable = ${HPX_HAVE_PARCELPOR_T_MPI:[hpx.parcel.enabled]}
env = ${HPX_HAVE_PARCELPOR_T_MPI_ENV:MV2_COMM_WORLD_RANK,PMI_RANK,OMPI_COMM_WORLD_SIZE,
↪ALPS_APP_PE,PALS_NODEID}
multithreaded = ${HPX_HAVE_PARCELPOR_T_MPI_MULTITHREADED:1}
rank = <MPI_rank>
processor_name = <MPI_processor_name>
array_optimization = ${HPX_HAVE_PARCEL_MPI_ARRAY_OPTIMIZATION:[hpx.parcel.array_
↪optimization]}
zero_copy_optimization = ${HPX_HAVE_PARCEL_MPI_ZERO_COPY_OPTIMIZATION:[hpx.parcel.zero_
↪copy_optimization]}
zero_copy_receive_optimization = ${HPX_HAVE_PARCEL_MPI_ZERO_COPY_RECEIVE_OPTIMIZATION:
↪[hpx.parcel.zero_copy_receive_optimization]}
```

(continues on next page)

(continued from previous page)

```
zero_copy_serialization_threshold = ${HPX_PARCEL_MPI_ZERO_COPY_SERIALIZATION_THRESHOLD:
↪$[hpx.parcels.zero_copy_serialization_threshold]}
use_io_pool = ${HPX_HAVE_PARCEL_MPI_USE_IO_POOL:$1}
async_serialization = ${HPX_HAVE_PARCEL_MPI_ASYNC_SERIALIZATION:$[hpx.parcels.async_
↪serialization]}
parcel_pool_size = ${HPX_HAVE_PARCEL_MPI_PARCEL_POOL_SIZE:$[hpx.threadpools.parcel_pool_
↪size]}
max_connections = ${HPX_HAVE_PARCEL_MPI_MAX_CONNECTIONS:$[hpx.parcels.max_connections]}
max_connections_per_locality = ${HPX_HAVE_PARCEL_MPI_MAX_CONNECTIONS_PER_LOCALITY:$[hpx.
↪parcels.max_connections_per_locality]}
max_message_size = ${HPX_HAVE_PARCEL_MPI_MAX_MESSAGE_SIZE:$[hpx.parcels.max_message_
↪size]}
max_outbound_message_size = ${HPX_HAVE_PARCEL_MPI_MAX_OUTBOUND_MESSAGE_SIZE:$[hpx.
↪parcels.max_outbound_message_size]}
max_background_threads = ${HPX_PARCEL_MPI_MAX_BACKGROUND_THREADS:$[hpx.parcels.max_
↪background_threads]}
```


Property	Description
<code>hpx.parcel.mpi.enable</code>	Enables the use of the MPI parcelport. <i>HPX</i> tries to detect if the application was started within a parallel MPI environment. If the detection was successful, the MPI parcelport is enabled by default. To explicitly disable the MPI parcelport, set to 0. Note that the initial bootstrap of the overall <i>HPX</i> application will be performed using MPI as well.
<code>hpx.parcel.mpi.env</code>	This property influences which environment variables (separated by commas) will be analyzed to find out whether the application was invoked by MPI.
<code>hpx.parcel.mpi.multithreaded</code>	This property is used to determine what threading mode to use when initializing MPI. If this setting is 0, <i>HPX</i> will initialize MPI with <code>MPI_THREAD_SINGLE</code> . If the value is not equal to 0, <i>HPX</i> will initialize MPI with <code>MPI_THREAD_MULTII</code> .
<code>hpx.parcel.mpi.rank</code>	This property will be initialized to the MPI rank of the <i>locality</i> .
<code>hpx.parcel.mpi.processor_name</code>	This property will be initialized to the MPI processor name of the <i>locality</i> .
<code>hpx.parcel.mpi.array_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize array optimizations in the MPI parcelport during serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.array_optimization</code> .
<code>hpx.parcel.mpi.zero_copy_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations in the MPI parcelport during serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.zero_copy_optimization</code> .
<code>hpx.parcel.mpi.zero_copy_receive_optimization</code>	This property defines whether this <i>locality</i> is allowed to utilize zero copy optimizations on the receiving end in the MPI parcelport during de-serialization of <i>parcel</i> data. The default is the same value as set for <code>hpx.parcel.zero_copy_optimization</code> .
<code>hpx.parcel.mpi.zero_copy_serialization_threshold</code>	This property defines the threshold value (in bytes) starting at which the serialization layer will apply zero-copy optimizations for serialized entities. The default is the same value as set for <code>hpx.parcel.zero_copy_serialization_threshold</code> .
<code>hpx.parcel.mpi.use_io_pool</code>	This property can be set to run the progress thread inside of <i>HPX</i> threads instead of a separate thread pool. The default is 1.
<code>hpx.parcel.mpi.async_serialization</code>	This property defines whether this <i>locality</i> is allowed to spawn a new thread for serialization in the MPI parcelport (this is both for encoding and decoding parcels). The default is the same value as set for <code>hpx.parcel.async_serialization</code> .
<code>hpx.parcel.mpi.parcel_pool_size</code>	The value of this property defines the number of OS threads created for the internal parcel thread pool of the MPI <i>parcel</i> port. The default is taken from <code>hpx.threadpools.parcel_pool_size</code> .
<code>hpx.parcel.mpi.max_connections</code>	This property defines how many network connections between different localities are overall kept alive by each <i>locality</i> . The default is taken from <code>hpx.parcel.max_connections</code> .
<code>hpx.parcel.mpi.max_connections_per_locality</code>	This property defines the maximum number of network connections that one <i>locality</i> will open to another <i>locality</i> . The default is taken from <code>hpx.parcel.max_connections_per_locality</code> .
<code>hpx.parcel.mpi.max_message_size</code>	This property defines the maximum allowed message size that will be transferrable through the <i>parcel</i> layer. The default is taken from <code>hpx.parcel.max_message_size</code> .
<code>hpx.parcel.mpi.max_outbound_message_size</code>	This property defines the maximum allowed outbound coalesced message size that will be transferrable through the <i>parcel</i> layer. The default is taken from <code>hpx.parcel.max_outbound_message_size</code> .
<code>hpx.parcel.mpi.max_background_threads</code>	This property defines how many cores should be used to perform background operations. The default is taken from <code>hpx.parcel.max_background_threads</code> .

The `hpx.agas` configuration section

```
[hpx.agas]
address = ${HPX_AGAS_SERVER_ADDRESS:<hpx_initial_ip_address>}
port = ${HPX_AGAS_SERVER_PORT:<hpx_initial_ip_port>}
service_mode = hosted
dedicated_server = 0
max_pending_refcnt_requests = ${HPX_AGAS_MAX_PENDING_REFCNT_REQUESTS:<hpx_initial_agas_
↪max_pending_refcnt_requests>}
use_caching = ${HPX_AGAS_USE_CACHING:1}
use_range_caching = ${HPX_AGAS_USE_RANGE_CACHING:1}
local_cache_size = ${HPX_AGAS_LOCAL_CACHE_SIZE:<hpx_agas_local_cache_size>}
```

Property	Description
<code>hpx.agas.address</code>	This property defines the default IP address to be used for the AGAS root server. This IP address will be used as long as no other values are specified (for instance, using the <code>--hpx:agas</code> command line option). The expected format is any valid IP address or domain name format that can be resolved into an IP address. The default depends on the compile time preprocessor constant <code>HPX_INITIAL_IP_ADDRESS</code> ("127.0.0.1").
<code>hpx.agas.port</code>	This property defines the default IP port to be used for the AGAS root server. This IP port will be used as long as no other values are specified (for instance, using the <code>--hpx:agas</code> command line option). The default depends on the compile time preprocessor constant <code>HPX_INITIAL_IP_PORT</code> (7009).
<code>hpx.agas.service_mode</code>	This property specifies what type of AGAS service is running on this <i>locality</i> . Currently, two modes exist. The <i>locality</i> that acts as the AGAS server runs in <code>bootstrap</code> mode. All other localities are in <code>hosted</code> mode.
<code>hpx.agas.dedicated_server</code>	This property specifies whether the AGAS server is exclusively running AGAS services and not hosting any application components. It is a boolean value. Set to 1 if <code>--hpx:run-agas-server-only</code> is present.
<code>hpx.agas.max_pending_refcnt_requests</code>	This property defines the number of reference counting requests (increments or decrements) to buffer. The default depends on the compile time preprocessor constant <code>HPX_AGAS_MAX_PENDING_REFCNT_REQUESTS</code> (4096).
<code>hpx.agas.use_caching</code>	This property specifies whether a software address translation cache is used. It is a boolean value. Defaults to 1.
<code>hpx.agas.use_range_caching</code>	This property specifies whether range-based caching is used by the software address translation cache. This property is ignored if <code>hpx.agas.use_caching</code> is false. It is a boolean value. Defaults to 1.
<code>hpx.agas.local_cache_size</code>	This property defines the size of the software address translation cache for AGAS services. This property is ignored if <code>hpx.agas.use_caching</code> is false. Note that if <code>hpx.agas.use_range_caching</code> is true, this size will refer to the maximum number of ranges stored in the cache, not the number of entries spanned by the cache. The default depends on the compile time preprocessor constant <code>HPX_AGAS_LOCAL_CACHE_SIZE</code> (4096).

The `hpx.commandline` configuration section

The following table lists the definition of all pre-defined command line option shortcuts. For more information about commandline options, see the section *HPX Command Line Options*.

```
[hpx.commandline]
aliasing = ${HPX_COMMANDLINE_ALIASING:1}
allow_unknown = ${HPX_COMMANDLINE_ALLOW_UNKNOWN:0}

[hpx.commandline.aliases]
-a = --hpx:agas
-c = --hpx:console
-h = --hpx:help
-I = --hpx:ini
-l = --hpx:localities
-p = --hpx:app-config
-q = --hpx:queuing
-r = --hpx:run-agas-server
-t = --hpx:threads
-v = --hpx:version
-w = --hpx:worker
-x = --hpx:hpx
-0 = --hpx:node=0
-1 = --hpx:node=1
-2 = --hpx:node=2
-3 = --hpx:node=3
-4 = --hpx:node=4
-5 = --hpx:node=5
-6 = --hpx:node=6
-7 = --hpx:node=7
-8 = --hpx:node=8
-9 = --hpx:node=9
```

Note: The short options listed above are disabled by default if the application is built using `#include <hpx/hpx_main.hpp>`. See *Re-use the `main()` function as the main HPX entry point* for more information. The rationale behind this is that in this case the user's application may handle its own command line options, since *HPX* passes all unknown options to `main()`. Short options like `-t` are prone to create ambiguities regarding what the application will support. Hence, the user should instead rely on the corresponding long options like `--hpx:threads` in such a case.

Property	Description
<code>hpx.commandline.aliases</code>	Enable command line aliases as defined in the section <code>hpx.commandline.aliases</code> (see below). Defaults to 1.
<code>hpx.commandline.allow_unknown</code>	Allow for unknown command line options to be passed through to <code>hpx_main()</code> Defaults to 0.
<code>hpx.commandline.aliases.-a</code>	On the commandline <code>-a</code> expands to: <code>--hpx:agas</code> .
<code>hpx.commandline.aliases.-c</code>	On the commandline <code>-c</code> expands to: <code>--hpx:console</code> .
<code>hpx.commandline.aliases.-h</code>	On the commandline <code>-h</code> expands to: <code>--hpx:help</code> .
<code>hpx.commandline.aliases.--help</code>	On the commandline <code>--help</code> expands to: <code>--hpx:help</code> .
<code>hpx.commandline.aliases.-I</code>	On the commandline <code>-I</code> expands to: <code>--hpx:ini</code> .
<code>hpx.commandline.aliases.-l</code>	On the commandline <code>-l</code> expands to: <code>--hpx:localities</code> .
<code>hpx.commandline.aliases.-p</code>	On the commandline <code>-p</code> expands to: <code>--hpx:app-config</code> .
<code>hpx.commandline.aliases.-q</code>	On the commandline <code>-q</code> expands to: <code>--hpx:queuing</code> .
<code>hpx.commandline.aliases.-r</code>	On the commandline <code>-r</code> expands to: <code>--hpx:run-agas-server</code> .
<code>hpx.commandline.aliases.-t</code>	On the commandline <code>-t</code> expands to: <code>--hpx:threads</code> .
<code>hpx.commandline.aliases.-v</code>	On the commandline <code>-v</code> expands to: <code>--hpx:version</code> .
<code>hpx.commandline.aliases.--version</code>	On the commandline <code>--version</code> expands to: <code>--hpx:version</code> .
<code>hpx.commandline.aliases.-w</code>	On the commandline <code>-w</code> expands to: <code>--hpx:worker</code> .
<code>hpx.commandline.aliases.-x</code>	On the commandline <code>-x</code> expands to: <code>--hpx:hpx</code> .
<code>hpx.commandline.aliases.-0</code>	On the commandline <code>-0</code> expands to: <code>--hpx:node=0</code> .
<code>hpx.commandline.aliases.-1</code>	On the commandline <code>-1</code> expands to: <code>--hpx:node=1</code> .
<code>hpx.commandline.aliases.-2</code>	On the commandline <code>-2</code> expands to: <code>--hpx:node=2</code> .
<code>hpx.commandline.aliases.-3</code>	On the commandline <code>-3</code> expands to: <code>--hpx:node=3</code> .
<code>hpx.commandline.aliases.-4</code>	On the commandline <code>-4</code> expands to: <code>--hpx:node=4</code> .
<code>hpx.commandline.aliases.-5</code>	On the commandline <code>-5</code> expands to: <code>--hpx:node=5</code> .
<code>hpx.commandline.aliases.-6</code>	On the commandline <code>-6</code> expands to: <code>--hpx:node=6</code> .
<code>hpx.commandline.aliases.-7</code>	On the commandline <code>-7</code> expands to: <code>--hpx:node=7</code> .
<code>hpx.commandline.aliases.-8</code>	On the commandline <code>-8</code> expands to: <code>--hpx:node=8</code> .
<code>hpx.commandline.aliases.-9</code>	On the commandline <code>-9</code> expands to: <code>--hpx:node=9</code> .

Loading INI files

During startup and after the internal database has been initialized as described in the section *Built-in default configuration settings*, HPX will try to locate and load additional ini files to be used as a source for configuration properties. This allows for a wide spectrum of additional customization possibilities by the user and system administrators. The sequence of locations where HPX will try loading the ini files is well defined and documented in this section. All ini files found are merged into the internal configuration database. The merge operation itself conforms to the rules as described in the section *The HPX ini file format*.

1. Load all component shared libraries found in the directories specified by the property `hpx.component_path` and retrieve their default configuration information (see section *Loading components* for more details). This property can refer to a list of directories separated by ':' (Linux, Android, and MacOS) or by ';' (Windows).
2. Load all files named `hpx.ini` in the directories referenced by the property `hpx.master_ini_path`. This property can refer to a list of directories separated by ':' (Linux, Android, and MacOS) or by ';' (Windows).
3. Load a file named `.hpx.ini` in the current working directory, e.g., the directory the application was invoked from.
4. Load a file referenced by the environment variable `HPX_INI`. This variable is expected to provide the full path name of the ini configuration file (if any).
5. Load a file named `/etc/hpx.ini`. This lookup is done on non-Windows systems only.
6. Load a file named `.hpx.ini` in the home directory of the current user, e.g., the directory referenced by the environment variable `HOME`.
7. Load a file named `.hpx.ini` in the directory referenced by the environment variable `PWD`.
8. Load the file specified on the command line using the option `--hpx:config`.
9. Load all properties specified on the command line using the option `--hpx:ini`. The properties will be added to the database in the same sequence as they are specified on the command line. The format for those options is, for instance, `--hpx:ini=hpx.default_stack_size=0x4000`. In addition to the explicit command line options, this will set the following properties as implied from other settings:
 - `hpx.parcel.address` and `hpx.parcel.port` as set by `--hpx:hpx`
 - `hpx.agas.address`, `hpx.agas.port` and `hpx.agas.service_mode` as set by `--hpx:agas`
 - `hpx.program_name` and `hpx.cmd_line` will be derived from the actual command line
 - **`hpx.os_threads` and `hpx.localities` as set by**
 `--hpx:threads` and `--hpx:localities`
 - `hpx.runtime_mode` will be derived from any explicit `--hpx:console`, `--hpx:worker`, or `--hpx:connect`, or it will be derived from other settings, such as `--hpx:node=0`, which implies `--hpx:console`.
10. Load files based on the pattern `*.ini` in all directories listed by the property `hpx.ini_path`. All files found during this search will be merged. The property `hpx.ini_path` can hold a list of directories separated by ':' (on Linux or Mac) or ';' (on Windows).
11. Load the file specified on the command line using the option `--hpx:app-config`. Note that this file will be merged as the content for a top level section `[application]`.

Note: Any changes made to the configuration database caused by one of the steps will influence the loading process for all subsequent steps. For instance, if one of the ini files loaded changes the property `hpx.ini_path`, this will influence the directories searched in step 9 as described above.

Important: The *HPX* core library will verify that all configuration settings specified on the command line (using the `--hpx:ini` option) will be checked for validity. That means that the library will accept only *known* configuration settings. This is to protect the user from unintentional typos while specifying those settings. This behavior can be overwritten by appending a '!' to the configuration key, thus forcing the setting to be entered into the configuration database. For instance: `--hpx:ini=hpx.foo! = 1`

If any of the environment variables or files listed above are not found, the corresponding loading step will be silently skipped.

Loading components

HPX relies on loading application specific components during the runtime of an application. Moreover, *HPX* comes with a set of preinstalled components supporting basic functionalities useful for almost every application. Any component in *HPX* is loaded from a shared library, where any of the shared libraries can contain more than one component type. During startup, *HPX* tries to locate all available components (e.g., their corresponding shared libraries) and creates an internal component registry for later use. This section describes the algorithm used by *HPX* to locate all relevant shared libraries on a system. As described, this algorithm is customizable by the configuration properties loaded from the ini files (see section *Loading INI files*).

Loading components is a two-stage process. First *HPX* tries to locate all component shared libraries, loads those, and generates a default configuration section in the internal configuration database for each component found. For each found component the following information is generated:

```
[hpx.components.<component_instance_name>]
name = <name_of_shared_library>
path = ${component_path}
enabled = ${hpx.components.load_external}
default = 1
```

The values in this section correspond to the expected configuration information for a component as described in the section *Built-in default configuration settings*.

In order to locate component shared libraries, *HPX* will try loading all shared libraries (files with the platform specific extension of a shared library, Linux: *.so, Windows: *.dll, MacOS: *.dylib found in the directory referenced by the ini property `hpx.component_path`).

This first step corresponds to step 1) during the process of filling the internal configuration database with default information as described in section *Loading INI files*.

After all of the configuration information has been loaded, *HPX* performs the second step in terms of loading components. During this step, *HPX* scans all existing configuration sections `[hpx.component.<some_component_instance_name>]` and instantiates a special factory object for each of the successfully located and loaded components. During the application's life time, these factory objects are responsible for creating new and discarding old instances of the component they are associated with. This step is performed after step 1) of the process of filling the internal configuration database with default information as described in section *Loading INI files*.

Application specific component example

This section assumes there is a simple application component that exposes one member function as a component action. The header file `app_server.hpp` declares the C++ type to be exposed as a component. This type has a member function `print_greeting()`, which is exposed as an action `print_greeting_action`. We assume the source files for this example are located in a directory referenced by `$APP_ROOT`:

```
// file: $APP_ROOT/app_server.hpp
#include <hpx/hpx.hpp>
#include <hpx/include/iostreams.hpp>

namespace app
{
    // Define a simple component exposing one action 'print_greeting'
    class HPX_COMPONENT_EXPORT server
    : public hpx::components::component_base<server>
    {
        void print_greeting ()
        {
            hpx::cout << "Hey, how are you?\n" << std::flush;
        }

        // Component actions need to be declared, this also defines the
        // type 'print_greeting_action' representing the action.
        HPX_DEFINE_COMPONENT_ACTION(server, print_greeting, print_greeting_action);
    };
}

// Declare boilerplate code required for each of the component actions.
HPX_REGISTER_ACTION_DECLARATION(app::server::print_greeting_action);
```

The corresponding source file contains mainly macro invocations that define the boilerplate code needed for *HPX* to function properly:

```
// file: $APP_ROOT/app_server.cpp
#include "app_server.hpp"

// Define boilerplate required once per component module.
HPX_REGISTER_COMPONENT_MODULE();

// Define factory object associated with our component of type 'app::server'.
HPX_REGISTER_COMPONENT(app::server, app_server);

// Define boilerplate code required for each of the component actions. Use the
// same argument as used for HPX_REGISTER_ACTION_DECLARATION above.
HPX_REGISTER_ACTION(app::server::print_greeting_action);
```

The following gives an example of how the component can be used. Here, one instance of the `app::server` component is created on the current *locality* and the exposed action `print_greeting_action` is invoked using the global id of the newly created instance. Note that no special code is required to delete the component instance after it is not needed anymore. It will be deleted automatically when its last reference goes out of scope (shown in the example below at the closing brace of the block surrounding the code):


```
// file: $APP_ROOT/use_app_server_example.cpp
#include <hpx/hpx_init.hpp>
#include "app_server.hpp"

int hpx_main()
{
    {
        // Create an instance of the app_server component on the current locality.
        hpx::naming::id_type app_server_instance =
            hpx::create_component<app::server>(hpx::find_here());

        // Create an instance of the action 'print_greeting_action'.
        app::server::print_greeting_action print_greeting;

        // Invoke the action 'print_greeting' on the newly created component.
        print_greeting(app_server_instance);
    }
    return hpx::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::init(argc, argv);
}
```

In order to make sure that the application will be able to use the component `app::server`, special configuration information must be passed to *HPX*. The simplest way to allow *HPX* to ‘find’ the component is to provide special ini configuration files that add the necessary information to the internal configuration database. The component should have a special ini file containing the information specific to the component `app_server`.

```
# file: $APP_ROOT/app_server.ini
[hpx.components.app_server]
name = app_server
path = $APP_LOCATION/
```

Here, `$APP_LOCATION` is the directory where the (binary) component shared library is located. *HPX* will attempt to load the shared library from there. The section name `hpx.components.app_server` reflects the instance name of the component (`app_server` is an arbitrary, but unique name). The property value for `hpx.components.app_server.name` should be the same as used for the second argument to the macro `HPX_REGISTER_COMPONENT` above.

Additionally, a file `.hpx.ini`, which could be located in the current working directory (see step 3 as described in the section *Loading INI files*), can be used to add to the ini search path for components:

```
# file: $PWD/.hpx.ini
[hpx]
ini_path = ${hpx.ini_path}:$APP_ROOT/
```

This assumes that the above ini file specific to the component is located in the directory `$APP_ROOT`.

Note: It is possible to reference the defined property from inside its value. *HPX* will gracefully use the previous value of `hpx.ini_path` for the reference on the right hand side and assign the overall (now expanded) value to the property.

Logging

HPX uses a sophisticated logging framework, allowing users to follow in detail what operations have been performed inside the *HPX* library in what sequence. This information proves to be very useful for diagnosing problems or just for improving the understanding of what is happening in *HPX* as a consequence of invoking *HPX* API functionality.

Default logging

Enabling default logging is a simple process. The detailed description in the remainder of this section explains different ways to customize the defaults. Default logging can be enabled by using one of the following:

- A command line switch `--hpx:debug-hpx-log`, which will enable logging to the console terminal.
- The command line switch `--hpx:debug-hpx-log=<filename>`, which enables logging to a given file `<filename>`.
- Setting an environment variable `HPX_LOGLEVEL=<loglevel>` while running the *HPX* application. In this case `<loglevel>` should be a number between (or equal to) 1 and 5 where 1 means minimal logging and 5 causes all available messages to be logged. When setting the environment variable, the logs will be written to a file named `hpx.<PID>.lo` in the current working directory, where `<PID>` is the process id of the console instance of the application.

Customizing logging

Generally, logging can be customized either using environment variable settings or using by an ini configuration file. Logging is generated in several categories, each of which can be customized independently. All customizable configuration parameters have reasonable defaults, allowing for the use of logging without any additional configuration effort. The following table lists the available categories.

Table 2.5: Logging categories

Category	Category shortcut	Information to be generated	Environment variable
General	None	Logging information generated by different subsystems of <i>HPX</i> , such as thread-manager, parcel layer, LCOs, etc.	<code>HPX_LOGLEVEL</code>
<i>AGAS</i>	<code>AGAS</code>	Logging output generated by the <i>AGAS</i> subsystem	<code>HPX_AGAS_LOGLEVEL</code>
Application	<code>APP</code>	Logging generated by applications.	<code>HPX_APP_LOGLEVEL</code>

By default, all logging output is redirected to the console instance of an application, where it is collected and written to a file, one file for each logging category.

Each logging category can be customized at two levels. The parameters for each are stored in the ini configuration sections `hpx.logging.CATEGORY` and `hpx.logging.console.CATEGORY` (where `CATEGORY` is the category shortcut as listed in the table above). The former influences logging at the source *locality* and the latter modifies the logging behaviour for each of the categories at the console instance of an application.

Levels

All *HPX* logging output has seven different logging levels. These levels can be set explicitly or through environment variables in the main *HPX* ini file as shown below. The logging levels and their associated integral values are shown in the table below, ordered from most verbose to least verbose. By default, all *HPX* logs are set to 0, e.g., all logging output is disabled by default.

Table 2.6: Logging levels

Logging level	Integral value
<debug>	5
<info>	4
<warning>	3
<error>	2
<fatal>	1
No logging	0

Tip: The easiest way to enable logging output is to set the environment variable corresponding to the logging category to an integral value as described in the table above. For instance, setting `HPX_LOGLEVEL=5` will enable full logging output for the general category. Please note that the syntax and means of setting environment variables varies between operating systems.

Configuration

Logs will be saved to destinations as configured by the user. By default, logging output is saved on the console instance of an application to `hpx.<CATEGORY>.<PID>.lo` (where `CATEGORY` and `PID` are placeholders for the category shortcut and the OS process id). The output for the general logging category is saved to `hpx.<PID>.log`. The default settings for the general logging category are shown here (the syntax is described in the section *The HPX ini file format*):

```
[hpx.logging]
level = ${HPX_LOGLEVEL:0}
destination = ${HPX_LOGDESTINATION:console}
format = ${HPX_LOGFORMAT:(T%locality%/%hpxthread%.%hpxphase%/%hpxcomponent%) P%parentloc
↳ %/%hpxparent%.%hpxparentphase% %time%($hh:$mm.$ss.$mili) [%idx%]|\\n}
```

The logging level is taken from the environment variable `HPX_LOGLEVEL` and defaults to zero, e.g., no logging. The default logging destination is read from the environment variable `HPX_LOGDESTINATION`. On any of the localities it defaults to `console`, which redirects all generated logging output to the console instance of an application. The following table lists the possible destinations for any logging output. It is possible to specify more than one destination separated by whitespace.

Table 2.7: Logging destinations

Logging destination	Description
<code>file(<filename>)</code>	Directs all output to a file with the given <code><filename></code> .
<code>cout</code>	Directs all output to the local standard output of the application instance on this <i>locality</i> .
<code>cerr</code>	Directs all output to the local standard error output of the application instance on this <i>locality</i> .
<code>console</code>	Directs all output to the console instance of the application. The console instance has its logging destinations configured separately.
<code>android_log</code>	Directs all output to the (Android) system log (available on Android systems only).

The logging format is read from the environment variable `HPX_LOGFORMAT`, and it defaults to a complex format description. This format consists of several placeholder fields (for instance `%locality%`), which will be replaced by concrete values when the logging output is generated. All other information is transferred verbatim to the output. The table below describes the available field placeholders. The separator character `|` separates the logging message prefix formatted as shown and the actual log message which will replace the separator.

Table 2.8: Available field placeholders

Name	Description
<i>locality</i>	The id of the <i>locality</i> on which the logging message was generated.
<i>hpxthread</i>	The id of the <i>HPX</i> thread generating this logging output.
<i>hpxphase</i>	The phase ⁷⁴ of the <i>HPX</i> thread generating this logging output.
<i>hpxcomponent</i>	The local virtual address of the component which the current <i>HPX</i> thread is accessing.
<i>parentloc</i>	The id of the <i>locality</i> where the <i>HPX</i> thread was running that initiated the current <i>HPX</i> thread. The current <i>HPX</i> thread is generating this logging output.
<i>hpxparent</i>	The id of the <i>HPX</i> thread that initiated the current <i>HPX</i> thread. The current <i>HPX</i> thread is generating this logging output.
<i>hpxparentphase</i>	The phase of the <i>HPX</i> thread when it initiated the current <i>HPX</i> thread. The current <i>HPX</i> thread is generating this logging output.
<i>time</i>	The time stamp for this logging outputline as generated by the source <i>locality</i> .
<i>idx</i>	The sequence number of the logging output line as generated on the source <i>locality</i> .
<i>osthread</i>	The sequence number of the OS thread that executes the current <i>HPX</i> thread.

Note: Not all of the field placeholder may be expanded for all generated logging output. If no value is available for a particular field, it is replaced with a sequence of `'-'` characters.

Here is an example line from a logging output generated by one of the *HPX* examples (please note that this is generated on a single line, without a line break):

```
(T000000000/0000000002d46f90.01/00000000009ebc10) P-----/0000000002d46f80.02 17:49.37.
↪320 [0000000000000004d]
    <info> [RT] successfully created component {0000000100ff0001, 0000000000030002} of
↪type: component_barrier[7(3)]
```

The default settings for the general logging category on the console is shown here:

```
[hpx.logging.console]
level = ${HPX_LOGLEVEL:[hpx.logging.level]}
destination = ${HPX_CONSOLE_LOGDESTINATION:file(hpx.${system.pid}.log)}
format = ${HPX_CONSOLE_LOGFORMAT:|}
```

These settings define how the logging is customized once the logging output is received by the console instance of an application. The logging level is read from the environment variable `HPX_LOGLEVEL` (as set for the console instance of the application). The level defaults to the same values as the corresponding settings in the general logging configuration shown before. The destination on the console instance is set to be a file that's name is generated based on its OS process id. Setting the environment variable `HPX_CONSOLE_LOGDESTINATION` allows customization of the naming scheme for the output file. The logging format is set to leave the original logging output unchanged, as received from one of the localities the application runs on.

⁷⁴ The phase of a *HPX*-thread counts how often this thread has been activated.

HPX Command Line Options

The predefined command line options for any application using `hpx::init` are described in the following subsections.

HPX options (allowed on command line only)

--hpx:help

Print out program usage (default: this message). Possible values: `full` (additionally prints options from components).

--hpx:version

Print out *HPX* version and copyright information.

--hpx:info

Print out *HPX* configuration information.

--hpx:options-file arg

Specify a file containing command line options (alternatively: `@filepath`).

HPX options (additionally allowed in an options file)

--hpx:worker

Run this instance in worker mode.

--hpx:console

Run this instance in console mode.

--hpx:connect

Run this instance in worker mode, but connecting late.

--hpx:run-agas-server

Run *AGAS* server as part of this runtime instance.

--hpx:run-hpx-main

Run the `hpx_main` function, regardless of *locality* mode.

--hpx:hpx arg

The IP address the *HPX* parcellport is listening on, expected format: `address:port` (default: `127.0.0.1:7910`).

--hpx:agas arg

The IP address the *AGAS* root server is running on, expected format: `address:port` (default: `127.0.0.1:7910`).

--hpx:run-agas-server-only

Run only the *AGAS* server.

--hpx:nodefile arg

The file name of a node file to use (list of nodes, one node name per line and core).

--hpx:nodes arg

The (space separated) list of the nodes to use (usually this is extracted from a node file).

--hpx:endnodes

This can be used to end the list of nodes specified using the option `--hpx:nodes`.

--hpx:ifsuffix arg

Suffix to append to host names in order to resolve them to the proper network interconnect.

--hpx:ifprefix arg

Prefix to prepend to host names in order to resolve them to the proper network interconnect.

--hpx:iftransform arg

Sed-style search and replace (s/search/replace/) used to transform host names to the proper network interconnect.

--hpx:force_ipv4

Network hostnames will be resolved to ipv4 addresses instead of using the first resolved endpoint. This is especially useful on Windows where the local hostname will resolve to an ipv6 address while remote network hostnames are commonly resolved to ipv4 addresses.

--hpx:localities arg

The number of localities to wait for at application startup (default: 1).

--hpx:node arg

Number of the node this *locality* is run on (must be unique).

--hpx:ignore-batch-env

Ignore batch environment variables.

--hpx:expect-connecting-localities

This *locality* expects other localities to dynamically connect (this is implied if the number of initial localities is larger than 1).

--hpx:pu-offset

The first processing unit this instance of *HPX* should be run on (default: 0).

--hpx:pu-step

The step between used processing unit numbers for this instance of *HPX* (default: 1).

--hpx:threads arg

The number of operating system threads to spawn for this *HPX locality*. Possible values are: numeric values 1, 2, 3 and so on, *all* (which spawns one thread per processing unit, includes hyperthreads), or *cores* (which spawns one thread per core) (default: *cores*).

--hpx:cores arg

The number of cores to utilize for this *HPX locality* (default: *all*, i.e., the number of cores is based on the number of threads *--hpx:threads* assuming *--hpx:bind=compact*).

--hpx:affinity arg

The affinity domain the OS threads will be confined to, possible values: *pu*, *core*, *numa*, *machine* (default: *pu*).

--hpx:bind arg

he detailed affinity description for the OS threads, see *More details about HPX command line options* for a detailed description of possible values. Do not use with *--hpx:pu-step*, *--hpx:pu-offset* or *--hpx:affinity* options. Implies *--hpx:numa-sensitive* (*--hpx:bind=none*) disables defining thread affinities).

--hpx:use-process-mask

Use the process mask to restrict available hardware resources (implies *--hpx:ignore-batch-env*).

--hpx:print-bind

Print to the console the bit masks calculated from the arguments specified to all *--hpx:bind* options.

--hpx:queuing arg

The queue scheduling policy to use. Options are local, local-priority-fifo, local-priority-lifo, static, static-priority, abp-priority-fifo, local-workrequesting-fifo, local-workrequesting-lifo, local-workrequesting-mc, and abp-priority-lifo (default: local-priority-fifo).

--hpx:high-priority-threads arg

The number of operating system threads maintaining a high priority queue (default: number of OS threads), valid for `--hpx:queuing=abp-priority`, `--hpx:queuingstatic-priority` and `--hpx:queuinglocal-priority` only.

--hpx:numa-sensitive

Makes the scheduler NUMA sensitive.

HPX configuration options**--hpx:app-config arg**

Load the specified application configuration (ini) file.

--hpx:config arg

Load the specified *HPX* configuration (ini) file.

--hpx:ini arg

Add a configuration definition to the default runtime configuration.

--hpx:exit

Exit after configuring the runtime.

HPX debugging options**--hpx:list-symbolic-names**

List all registered symbolic names after startup.

--hpx:list-component-types

List all dynamic component types after startup.

--hpx:dump-config-initial

Print the initial runtime configuration.

--hpx:dump-config

Print the final runtime configuration.

--hpx:debug-hpx-log [arg]

Enable all messages on the *HPX* log channel and send all *HPX* logs to the target destination (default: cout).

--hpx:debug-agas-log [arg]

Enable all messages on the *AGAS* log channel and send all *AGAS* logs to the target destination (default: cout).

--hpx:debug-parcel-log [arg]

Enable all messages on the parcel transport log channel and send all parcel transport logs to the target destination (default: cout).

--hpx:debug-timing-log [arg]

Enable all messages on the timing log channel and send all timing logs to the target destination (default: cout).

--hpx:debug-app-log [arg]

Enable all messages on the application log channel and send all application logs to the target destination (default: cout).

--hpx:debug-clp

Debug command line processing.

--hpx:attach-debugger arg

Wait for a debugger to be attached, possible arg values: `startup` or `exception` (default: `startup`)

HPX options related to performance counters**--hpx:print-counter**

Print the specified performance counter either repeatedly and/or at the times specified by `--hpx:print-counter-at` (see also option `--hpx:print-counter-interval`).

--hpx:print-counter-reset

Print the specified performance counter either repeatedly and/or at the times specified by `--hpx:print-counter-at`. Reset the counter after the value is queried (see also option `--hpx:print-counter-interval`).

--hpx:print-counter-interval

Print the performance counter(s) specified with `--hpx:print-counter` repeatedly after the time interval (specified in milliseconds), (default: 0, which means print once at shutdown).

--hpx:print-counter-destination

Print the performance counter(s) specified with `--hpx:print-counter` to the given file (default: console).

--hpx:list-counters

List the names of all registered performance counters, possible values: `minimal` (prints counter name skeletons), `full` (prints all available counter names).

--hpx:list-counter-infos

List the description of all registered performance counters, possible values: `minimal` (prints info for counter name skeletons), `full` (prints all available counter infos).

--hpx:print-counter-format

Print the performance counter(s) specified with `--hpx:print-counter`. Possible formats in CSV include a format with a header or without any header (see option `--hpx:no-csv-header`). Possible values: `csv` (prints counter values in CSV format with full names as header), `csv-short` (prints counter values in CSV format with short names provided with `--hpx:print-counter` as `--hpx:print-counter shortname`, `full-countername`

--hpx:no-csv-header

Print the performance counter(s) specified with `--hpx:print-counter` and `csv` or `csv-short` format specified with `--hpx:print-counter-format` without header.

--hpx:print-counter-at arg

Print the performance counter(s) specified with `--hpx:print-counter` (or `--hpx:print-counter-reset`) at the given point in time, possible argument values: `startup`, `shutdown` (default), `noshutdown`.

--hpx:reset-counters

Reset all performance counter(s) specified with `--hpx:print-counter` after they have been evaluated.

--hpx:print-counters-locally

Each *locality* prints only its own local counters. If this is used with `--hpx:print-counter-destination=<file>`, the code will append a `".<locality_id>"` to the file name in order to avoid clashes between localities.

Command line argument shortcuts

Additionally, the following shortcuts are available from every *HPX* application.

Table 2.9: Predefined command line option shortcuts

Shortcut option	Equivalent long option
-a	--hpx:agas
-c	--hpx:console
-h	--hpx:help
-I	--hpx:ini
-l	--hpx:localities
-p	--hpx:app-config
-q	--hpx:queuing
-r	--hpx:run-agas-server
-t	--hpx:threads
-v	--hpx:version
-w	--hpx:worker
-x	--hpx:hpx
-0	--hpx:node=0
-1	--hpx:node=1
-2	--hpx:node=2
-3	--hpx:node=3
-4	--hpx:node=4
-5	--hpx:node=5
-6	--hpx:node=6
-7	--hpx:node=7
-8	--hpx:node=8
-9	--hpx:node=9

Note: The short options listed above are disabled by default if the application is built using `#include <hpx/hpx_main.hpp>`. See *Re-use the main() function as the main HPX entry point* for more information. The rationale behind this is that in this case the user's application may handle its own command line options, since *HPX* passes all unknown options to `main()`. Short options like `-t` are prone to create ambiguities regarding what the application will support. Hence, the user should instead rely on the corresponding long options like `--hpx:threads` in such a case.

It is possible to define your own shortcut options. In fact, all of the shortcuts listed above are pre-defined using the technique described here. Also, it is possible to redefine any of the pre-defined shortcuts to expand differently as well.

Shortcut options are obtained from the internal configuration database. They are stored as key-value properties in a special properties section named `hpx.commandline`. You can define your own shortcuts by adding the corresponding definitions to one of the ini configuration files as described in the section *Configuring HPX applications*. For instance, in order to define a command line shortcut `--p`, which should expand to `-hpx:print-counter`, the following configuration information needs to be added to one of the ini configuration files:

```
[hpx.commandline.aliases]
--pc = --hpx:print-counter
```

Note: Any arguments for shortcut options passed on the command line are retained and passed as arguments to the corresponding expanded option. For instance, given the definition above, the command line option:

```
--pc=/threads{locality#0/total}/count/cumulative
```

would be expanded to:

```
--hpx:print-counter=/threads{locality#0/total}/count/cumulative
```

Important: Any shortcut option should either start with a single '-' or with two '--' characters. Shortcuts starting with a single '-' are interpreted as short options (i.e., everything after the first character following the '-' is treated as the argument). Shortcuts starting with '--' are interpreted as long options. No other shortcut formats are supported.

Specifying options for single localities only

For runs involving more than one *locality*, it is sometimes desirable to supply specific command line options to single localities only. When the *HPX* application is launched using a scheduler (like PBS; for more details see section *How to use HPX applications with PBS*), specifying dedicated command line options for single localities may be desirable. For this reason all of the command line options that have the general format `--hpx:<some_key>` can be used in a more general form: `--hpx:<N>:<some_key>`, where `<N>` is the number of the *locality* this command line option will be applied to; all other localities will simply ignore the option. For instance, the following PBS script passes the option `--hpx:pu-offset=4` to the *locality* '1' only.

```
#!/bin/bash
#
#PBS -l nodes=2:ppn=4

APP_PATH=~/.packages/hpx/bin/hello_world_distributed
APP_OPTIONS=

pbsdsh -u $APP_PATH $APP_OPTIONS --hpx:1:pu-offset=4 --hpx:nodes=`cat $PBS_NODEFILE`
```

Caution: If the first application specific argument (inside `$APP_OPTIONS`) is a non-option (i.e., does not start with a - or a --), then it must be placed before the option `--hpx:nodes`, which, in this case, should be the last option on the command line.

Alternatively, use the option `--hpx:endnodes` to explicitly mark the end of the list of node names:

```
$ pbsdsh -u $APP_PATH --hpx:1:pu-offset=4 --hpx:nodes=`cat $PBS_NODEFILE` --
↪hpx:endnodes $APP_OPTIONS
```

More details about HPX command line options

This section documents the following list of the command line options in more detail:

- The command line option `--hpx:bind`

The command line option `--hpx:bind`

This command line option allows one to specify the required affinity of the HPX worker threads to the underlying processing units. As a result the worker threads will run only on the processing units identified by the corresponding bind specification. The affinity settings are to be specified using `--hpx:bind=<BINDINGS>`, where <BINDINGS> have to be formatted as described below.

In addition to the syntax described below, one can use `--hpx:bind=none` to disable all binding of any threads to a particular core. This is mostly supported for debugging purposes.

The specified affinities refer to specific regions within a machine hardware topology. In order to understand the hardware topology of a particular machine, it may be useful to run the `lstopo` tool, which is part of Portable Hardware Locality (HWLOC), to see the reported topology tree. Seeing and understanding a topology tree will definitely help in understanding the concepts that are discussed below.

Affinities can be specified using hwloc tuples. Tuples of hwloc *objects* and associated *indexes* can be specified in the form `object:index`, `object:index-index` or `object:index,...,index`. Hwloc objects represent types of mapped items in a topology tree. Possible values for objects are `socket`, `numanode`, `core` and `pu` (processing unit). Indexes are non-negative integers that specify a unique physical object in a topology tree using its logical sequence number.

Chaining multiple tuples together in the more general form `object1:index1[.object2:index2[...]]` is permissible. While the first tuple's object may appear anywhere in the topology, the Nth tuple's object must have a shallower topology depth than the (N+1)th tuple's object. Put simply: as you move right in a tuple chain, objects must go deeper in the topology tree. Indexes specified in chained tuples are relative to the scope of the parent object. For example, `socket:0.core:1` refers to the second core in the first socket (all indices are zero based).

Multiple affinities can be specified using several `--hpx:bind` command line options or by appending several affinities separated by a `' ; '`. By default, if multiple affinities are specified, they are added.

"all" is a special affinity consisting in the entire current topology.

Note: All "names" in an affinity specification, such as `thread`, `socket`, `numanode`, `pu` or `all`, can be abbreviated. Thus, the affinity specification `threads:0-3=socket:0.core:1.pu:1` is fully equivalent to its shortened form `t:0-3=s:0.c:1.p:1`.

Here is a full grammar describing the possible format of mappings:

```

mappings      ::=  distribution | mapping (";" mapping)*
distribution  ::=  "compact" | "scatter" | "balanced" | "numa-balanced"
mapping       ::=  thread_spec "=" pu_specs
thread_spec   ::=  "thread:" range_specs
pu_specs      ::=  pu_spec ( "." pu_spec )*
pu_spec       ::=  type ":" range_specs | "~" pu_spec
range_specs   ::=  range_spec ( "," range_spec )*
range_spec    ::=  int | int "-" int | "all"
type          ::=  "socket" | "numanode" | "core" | "pu"

```

The following example assumes a system with at least 4 cores, where each core has more than 1 processing unit (hardware threads). Running `hello_world_distributed` with 4 OS threads (on 4 processing units), where each of those threads is bound to the first processing unit of each of the cores, can be achieved by invoking:

```
$ hello_world_distributed -t4 --hpx:bind=thread:0-3=core:0-3.pu:0
```

Here, `thread:0-3` specifies the OS threads used to define affinity bindings, and `core:0-3.pu:0` defines that for each of the cores (`core:0-3`) only their first processing unit `pu:0` should be used.

Note: The command line option `--hpx:print-bind` can be used to print the bitmasks generated from the affinity mappings as specified with `--hpx:bind`. For instance, on a system with hyperthreading enabled (i.e. 2 processing units per core), the command line:

```
$ hello_world_distributed -t4 --hpx:bind=thread:0-3=core:0-3.pu:0 --hpx:print-bind
```

will cause this output to be printed:

```
0: PU L#0(P#0), Core L#0, Socket L#0, Node L#0(P#0)
1: PU L#2(P#2), Core L#1, Socket L#0, Node L#0(P#0)
2: PU L#4(P#4), Core L#2, Socket L#0, Node L#0(P#0)
3: PU L#6(P#6), Core L#3, Socket L#0, Node L#0(P#0)
```

where each bit in the bitmasks corresponds to a processing unit the listed worker thread will be bound to run on.

The difference between the four possible predefined distribution schemes (`compact`, `scatter`, `balanced` and `numa-balanced`) is best explained with an example. Imagine that we have a system with 4 cores and 4 hardware threads per core on 2 sockets. If we place 8 threads the assignments produced by the `compact`, `scatter`, `balanced` and `numa-balanced` types are shown in the figure below. Notice that `compact` does not fully utilize all the cores in the system. For this reason it is recommended that applications are run using the `scatter` or `balanced/numa-balanced` options in most cases.

In addition to the predefined distributions it is possible to restrict the resources used by *HPX* to the process CPU mask. The CPU mask is typically set by e.g. `MPI`⁷³ and batch environments. Using the command line option `--hpx:use-process-mask` makes *HPX* act as if only the processing units in the CPU mask are available for use by *HPX*. The number of threads is automatically determined from the CPU mask. The number of threads can still be changed manually using this option, but only to a number less than or equal to the number of processing units in the CPU mask. The option `--hpx:print-bind` is useful in conjunction with `--hpx:use-process-mask` to make sure threads are placed as expected.

2.4.11 Writing single-node applications

Being a C++ Standard Library for Concurrency and Parallelism, *HPX* implements all of the corresponding facilities as defined by the C++ Standard but also those which are proposed as part of the ongoing C++ standardization process. This section focuses on the features available in *HPX* for parallel and concurrent computation on a single node, although many of the features presented here are also implemented to work in the distributed case.

⁷³ https://en.wikipedia.org/wiki/Message_Passing_Interface




Fig. 2.7: Schematic of thread affinity type distributions.

Synchronization objects

The following objects are providing synchronization for *HPX* applications:

1. *Barrier*
2. *Condition variable*
3. *Latch*
4. *Mutex*
5. *Shared mutex*
6. *Semaphore*
7. *Composable guards*

Barrier

Barriers are used for synchronizing multiple threads. They provide a synchronization point, where all threads must wait until they have all reached the barrier, before they can continue execution. This allows multiple threads to work together to solve a common task, and ensures that no thread starts working on the next task until all threads have completed the current task. This ensures that all threads are in the same state before performing any further operations, leading to a more consistent and accurate computation.

Unlike latches, barriers are reusable: once the participating threads are released from a barrier's synchronization point, they can re-use the same barrier. It is thus useful for managing repeated tasks, or phases of a larger task, that are handled by multiple threads. The code below shows how barriers can be used to synchronize two threads:

```
#include <hpx/barrier.hpp>
#include <hpx/future.hpp>
#include <hpx/init.hpp>

#include <iostream>

int hpx_main()
{
    hpx::barrier b(2);

    hpx::future<void> f1 = hpx::async([&b]() {
        std::cout << "Thread 1 started." << std::endl;
        // Do some computation
        b.arrive_and_wait();
        // Continue with next task
        std::cout << "Thread 1 finished." << std::endl;
    });

    hpx::future<void> f2 = hpx::async([&b]() {
        std::cout << "Thread 2 started." << std::endl;
        // Do some computation
        b.arrive_and_wait();
        // Continue with next task
        std::cout << "Thread 2 finished." << std::endl;
    });
}
```

(continues on next page)

(continued from previous page)

```

    f1.get();
    f2.get();

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}

```

In this example, two `hpx::future` objects are created, each representing a separate thread of execution. The `wait` function of the `hpx::barrier` object is called by each thread. The threads will wait at the barrier until both have reached it. Once both threads have reached the barrier, they can continue with their next task.

Condition variable

A *condition variable* is a synchronization primitive in *HPX* that allows a thread to wait for a specific condition to be satisfied before continuing execution. It is typically used in conjunction with a mutex or a lock to protect shared data that is being modified by multiple threads. Hence, it blocks one or more threads until another thread both modifies a shared variable (the condition) and notifies the `condition_variable`. The code below shows how two threads modifying the shared variable data can be synchronized using the `condition_variable`:

```

#include <hpx/condition_variable.hpp>
#include <hpx/init.hpp>
#include <hpx/mutex.hpp>
#include <hpx/thread.hpp>

#include <iostream>
#include <string>

hpx::condition_variable cv;
hpx::mutex m;
std::string data;
bool ready = false;
bool processed = false;

void worker_thread()
{
    // Wait until the main thread signals that data is ready
    std::unique_lock<hpx::mutex> lk(m);
    cv.wait(lk, [] { return ready; });

    // Access the shared resource
    std::cout << "Worker thread: Processing data...\n";
    data = "Test data after";

    // Send data back to the main thread
    processed = true;
    std::cout << "Worker thread: data processing is complete\n";
}

```

(continues on next page)

(continued from previous page)

```

    // Manual unlocking is done before notifying, to avoid waking up
    // the waiting thread only to block again
    lk.unlock();
    cv.notify_one();
}

int hpx_main()
{
    hpx::thread worker(worker_thread);

    // Do some work
    std::cout << "Main thread: Preparing data...\n";
    data = "Test data before";
    hpx::this_thread::sleep_for(std::chrono::seconds(1));
    std::cout << "Main thread: Data before processing = " << data << '\n';

    // Signal that data is ready and send data to worker thread
    {
        std::lock_guard<hpx::mutex> lk(m);
        ready = true;
        std::cout << "Main thread: Data is ready...\n";
    }
    cv.notify_one();

    // Wait for the worker thread to finish
    {
        std::unique_lock<hpx::mutex> lk(m);
        cv.wait(lk, [] { return processed; });
    }
    std::cout << "Main thread: Data after processing = " << data << '\n';
    worker.join();

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}

```

The main thread of the code above starts by creating a worker thread and preparing the shared variable data. Once the data is ready, the main thread acquires a lock on the mutex `m` using `std::lock_guard<hpx::mutex> lk(m)` and sets the ready flag to true, then signals the worker thread to start processing by calling `cv.notify_one()`. The `cv.wait()` call in the main thread then blocks until the worker thread signals that processing is complete by setting the processed flag.

The worker thread starts by acquiring a lock on the mutex `m` to ensure exclusive access to the shared data. The `cv.wait()` call blocks the thread until the ready flag is set by the main thread. Once this is true, the worker thread accesses the shared data resource, processes it, and sets the processed flag to indicate completion. The mutex is then unlocked using `lk.unlock()` and the `cv.notify_one()` call signals the main thread to resume execution. Finally, the new data is printed by the main thread to the console.

Latch

A *latch* is a downward counter which can be used to synchronize threads. The value of the counter is initialized on creation. Threads may block on the latch until the counter is decremented to zero. There is no possibility to increase or reset the counter, which makes the latch a single-use barrier.

In *HPX*, a latch is implemented as a counting semaphore, which can be initialized with a specific count value and decremented each time a thread reaches the latch. When the count value reaches zero, all waiting threads are unblocked and allowed to continue execution. The code below shows how latch can be used to synchronize 16 threads:

```
std::ptrdiff_t num_threads = 16;

/////////////////////////////////////////////////////////////////
void wait_for_latch(hpx::latch& l)
{
    l.arrive_and_wait();
}

/////////////////////////////////////////////////////////////////
int hpx_main(hpx::program_options::variables_map& vm)
{
    num_threads = vm["num-threads"].as<std::ptrdiff_t>();

    hpx::latch l(num_threads + 1);

    std::vector<hpx::future<void>> results;
    for (std::ptrdiff_t i = 0; i != num_threads; ++i)
        results.push_back(hpx::async(&wait_for_latch, std::ref(l)));

    // Wait for all threads to reach this point.
    l.arrive_and_wait();

    hpx::wait_all(results);

    return hpx::local::finalize();
}
```

In the above code, the `hpx_main` function creates a latch object `l` with a count of `num_threads + 1` and `num_threads` number of threads using `hpx::async`. These threads call the `wait_for_latch` function and pass the reference to the latch object. In the `wait_for_latch` function, the thread calls the `arrive_and_wait` method on the latch, which decrements the count of the latch and causes the thread to wait until the count reaches zero. Finally, the main thread waits for all the threads to arrive at the latch by calling the `arrive_and_wait` method and then waits for all the threads to finish by calling the `hpx::wait_all` method.

Mutex

A *mutex* (short for “mutual exclusion”) is a synchronization primitive in *HPX* used to control access to a shared resource, ensuring that only one thread can access it at a time. A mutex is used to protect data structures from race conditions and other synchronization-related issues. When a thread acquires a mutex, other threads that try to access the same resource will be blocked until the mutex is released. The code below shows the basic use of mutexes:

```
#include <hpx/future.hpp>
#include <hpx/init.hpp>
#include <hpx/mutex.hpp>

#include <iostream>

int hpx_main()
{
    hpx::mutex m;

    hpx::future<void> f1 = hpx::async([&m]() {
        std::scoped_lock sl(m);
        std::cout << "Thread 1 acquired the mutex" << std::endl;
    });

    hpx::future<void> f2 = hpx::async([&m]() {
        std::scoped_lock sl(m);
        std::cout << "Thread 2 acquired the mutex" << std::endl;
    });

    hpx::wait_all(f1, f2);

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}
```

In this example, two *HPX* threads created using `hpx::async` are acquiring a `hpx::mutex m`. `std::scoped_lock sl(m)` is used to take ownership of the given mutex `m`. When control leaves the scope in which the `scoped_lock` object was created, the `scoped_lock` is destructed and the mutex is released.

Attention: A common way to acquire and release mutexes is by using the function `m.lock()` before accessing the shared resource, and `m.unlock()` called after the access is complete. However, these functions may lead to deadlocks in case of exception(s). That is, if an exception happens when the mutex is locked then the code that unlocks the mutex will never be executed, the lock will remain held by the thread that acquired it, and other threads will be unable to access the shared resource. This can cause a deadlock if the other threads are also waiting to acquire the same lock. For this reason, we suggest you use `std::scoped_lock`, which prevents this issue by releasing the lock when control leaves the scope in which the `scoped_lock` object was created.

Shared mutex

A *shared mutex* is a synchronization primitive that can be used to protect shared data from being simultaneously accessed by multiple threads. In contrast to other mutex types which facilitate exclusive access, a `shared_mutex` has two levels of access:

- *Exclusive access* prevents any other thread from acquiring the mutex, just as with the normal mutex. It does not matter if the other thread tries to acquire shared or exclusive access.
- *Shared access* allows multiple threads to acquire the mutex, but all of them only in shared mode. Exclusive access is not granted until all of the previous shared holders have returned the mutex (typically, as long as an exclusive request is waiting, new shared ones are queued to be granted after the exclusive access).

Shared mutexes are especially useful when shared data can be safely read by any number of threads simultaneously, but a thread may only write the same data when no other thread is reading or writing at the same time. A typical scenario is a database: The data can be read simultaneously by different threads with no problem. However, modification of the database is critical: if some threads read data while another one is writing, the threads reading may receive inconsistent data. Hence, while a thread is writing, reading should not be allowed. After writing is complete, reads can occur simultaneously again. The code below shows how `shared_mutex` can be used to synchronize reads and writes:

```
int const writers = 3;
int const readers = 3;
int const cycles = 10;

using std::chrono::milliseconds;

int hpx_main()
{
    std::vector<hpx::thread> threads;
    std::atomic<bool> ready(false);
    hpx::shared_mutex stm;

    for (int i = 0; i < writers; ++i)
    {
        threads.emplace_back([&ready, &stm, i] {
            std::mt19937 urng(static_cast<std::uint32_t>(std::time(nullptr)));
            std::uniform_int_distribution<int> dist(1, 1000);

            while (!ready)
            { /** wait... ***/
            }

            for (int j = 0; j < cycles; ++j)
            {
                // scope of unique_lock
                {
                    std::unique_lock<hpx::shared_mutex> ul(stm);

                    std::cout << "^^^ Writer " << i << " starting..."
                                << std::endl;
                    hpx::this_thread::sleep_for(milliseconds(dist(urng)));
                    std::cout << "vvv Writer " << i << " finished."
                                << std::endl;
                }
            }
        });
    }
}
```

(continues on next page)

(continued from previous page)

```

        hpx::this_thread::sleep_for(milliseconds(dist(urng)));
    }
    });
}

for (int i = 0; i < readers; ++i)
{
    int k = writers + i;
    threads.emplace_back([&ready, &stm, k, i] {
        HPX_UNUSED(k);
        std::mt19937 urng(static_cast<std::uint32_t>(std::time(nullptr)));
        std::uniform_int_distribution<int> dist(1, 1000);

        while (!ready)
        { /*** wait... ***/
        }

        for (int j = 0; j < cycles; ++j)
        {
            // scope of shared_lock
            {
                std::shared_lock<hpx::shared_mutex> sl(stm);

                std::cout << "Reader " << i << " starting..." << std::endl;
                hpx::this_thread::sleep_for(milliseconds(dist(urng)));
                std::cout << "Reader " << i << " finished." << std::endl;
            }
            hpx::this_thread::sleep_for(milliseconds(dist(urng)));
        }
    });
}

ready = true;
for (auto& t : threads)
    t.join();

return hpx::local::finalize();
}

```

The above code creates writers and readers threads, each of which will perform cycles of operations. Both the writer and reader threads use the `hpx::shared_mutex` object `stm` to synchronize access to a shared resource.

- For the writer threads, a `unique_lock` on the shared mutex is acquired before each write operation and is released after control leaves the scope in which the `unique_lock` object was created.
- For the reader threads, a `shared_lock` on the shared mutex is acquired before each read operation and is released after control leaves the scope in which the `shared_lock` object was created.

Before each operation, both the reader and writer threads sleep for a random time period, which is generated using a random number generator. The random time period simulates the processing time of the operation.

Semaphore

Semaphores are a synchronization mechanism used to control concurrent access to a shared resource. The two types of semaphores are:

- counting semaphore: it has a counter that is bigger than zero. The counter is initialized in the constructor. Acquiring the semaphore decreases the counter and releasing the semaphore increases the counter. If a thread tries to acquire the semaphore when the counter is zero, the thread will block until another thread increments the counter by releasing the semaphore. Unlike `hpx::mutex`, an `hpx::counting_semaphore` is not bound to a thread, which means that the acquire and release call of a semaphore can happen on different threads.
- binary semaphore: it is an alias for a `hpx::counting_semaphore<1>`. In this case, the least maximal value is 1. `hpx::binary_semaphore` can be used to implement locks.

```
#include <hpx/init.hpp>
#include <hpx/semaphore.hpp>
#include <hpx/thread.hpp>

#include <iostream>

// initialize the semaphore with a count of 3
hpx::counting_semaphore<> semaphore(3);

void worker()
{
    semaphore.acquire();    // decrement the semaphore's count
    std::cout << "Entering critical section" << std::endl;
    hpx::this_thread::sleep_for(std::chrono::seconds(1));
    semaphore.release();    // increment the semaphore's count
    std::cout << "Exiting critical section" << std::endl;
}

int hpx_main()
{
    hpx::thread t1(worker);
    hpx::thread t2(worker);
    hpx::thread t3(worker);
    hpx::thread t4(worker);
    hpx::thread t5(worker);

    t1.join();
    t2.join();
    t3.join();
    t4.join();
    t5.join();

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}
```

In this example, the counting semaphore is initialized to the value of 3. This means that up to 3 threads can access the

critical section (the section of code inside the `worker()` function) at the same time. When a thread enters the critical section, it acquires the semaphore, which decrements the count, while when it exits the critical section, it releases the semaphore, incrementing thus the count. The `worker()` function simulates a critical section by acquiring the semaphore, sleeping for 1 second and then releasing the semaphore.

In the main function, 5 worker threads are created and started, each trying to enter the critical section. If the count of the semaphore is already 0, a worker will wait until another worker releases the semaphore (increasing its value).

Composable guards

Composable guards operate in a manner similar to locks, but are applied only to asynchronous functions. The guard (or guards) is automatically locked at the beginning of a specified task and automatically unlocked at the end. Because guards are never added to an existing task's execution context, the calling of guards is freely composable and can never deadlock.

To call an application with a single guard, simply declare the guard and call `run_guarded()` with a function (`task`):

```
hpx::lcos::local::guard gu;  
run_guarded(gu, task);
```

If a single method needs to run with multiple guards, use a guard set:

```
std::shared_ptr<hpx::lcos::local::guard> gu1(new hpx::lcos::local::guard());  
std::shared_ptr<hpx::lcos::local::guard> gu2(new hpx::lcos::local::guard());  
gs.add(*gu1);  
gs.add(*gu2);  
run_guarded(gs, task);
```

Guards use two atomic operations (which are not called repeatedly) to manage what they do, so overhead should be extremely low.

Execution control

The following objects are providing control of the execution in *HPX* applications:

1. *Futures*
2. *Channels*
3. *Task blocks*
4. *Task groups*
5. *Threads*

Futures

Futures are a mechanism to represent the result of a potentially asynchronous operation. A future is a type that represents a value that will become available at some point in the future, and it can be used to write asynchronous and parallel code. Futures can be returned from functions that perform time-consuming operations, allowing the calling code to continue executing while the function performs its work. The value of the future is set when the operation completes and can be accessed later. Futures are used in *HPX* to write asynchronous and parallel code. Below is an example demonstrating different features of futures:

```

#include <hpx/assert.hpp>
#include <hpx/future.hpp>
#include <hpx/hpx_main.hpp>
#include <hpx/tuple.hpp>

#include <iostream>
#include <utility>

int main()
{
    // Asynchronous execution with futures
    hpx::future<void> f1 = hpx::async(hpx::launch::async, []() {});
    hpx::shared_future<int> f2 =
        hpx::async(hpx::launch::async, []() { return 42; });
    hpx::future<int> f3 =
        f2.then([](hpx::shared_future<int>&& f) { return f.get() * 3; });

    hpx::promise<double> p;
    auto f4 = p.get_future();
    HPX_ASSERT(!f4.is_ready());
    p.set_value(123.45);
    HPX_ASSERT(f4.is_ready());

    hpx::packaged_task<int()> t([]() { return 43; });
    hpx::future<int> f5 = t.get_future();
    HPX_ASSERT(!f5.is_ready());
    t();
    HPX_ASSERT(f5.is_ready());

    // Fire-and-forget
    hpx::post([]() {
        std::cout << "This will be printed later\n" << std::flush;
    });

    // Synchronous execution
    hpx::sync([]() {
        std::cout << "This will be printed immediately\n" << std::flush;
    });

    // Combinators
    hpx::future<double> f6 = hpx::async([]() { return 3.14; });
    hpx::future<double> f7 = hpx::async([]() { return 42.0; });
    std::cout
        << hpx::when_all(f6, f7)
            .then([](hpx::future<
                hpx::tuple<hpx::future<double>, hpx::future<double>>>
                f) {
                hpx::tuple<hpx::future<double>, hpx::future<double>> t =
                    f.get();
                double pi = hpx::get<0>(t).get();
                double r = hpx::get<1>(t).get();
                return pi * r * r;
            })

```

(continues on next page)

(continued from previous page)

```

        .get()
    << std::endl;

    // Easier continuations with dataflow; it waits for all future or
    // shared_future arguments before executing the continuation, and also
    // accepts non-future arguments
    hpx::future<double> f8 = hpx::async([]() { return 3.14; });
    hpx::future<double> f9 = hpx::make_ready_future(42.0);
    hpx::shared_future<double> f10 = hpx::async([]() { return 123.45; });
    hpx::future<hpx::tuple<double, double>> f11 = hpx::dataflow(
        [](hpx::future<double> a, hpx::future<double> b,
            hpx::shared_future<double> c, double d) {
            return hpx::make_tuple<>(a.get() + b.get(), c.get() / d);
        },
        f8, f9, f10, -3.9);

    // split_future gives a tuple of futures from a future of tuple
    hpx::tuple<hpx::future<double>, hpx::future<double>> f12 =
        hpx::split_future(std::move(f11));
    std::cout << hpx::get<1>(f12).get() << std::endl;

    return 0;
}

```

The first section of the main function demonstrates how to use futures for asynchronous execution. The first two lines create two futures, one for void and another for an integer, using the `hpx::async()` function. These futures are executed *asynchronously* in separate threads using the `hpx::launch::async` launch policy. The third future is created by *chaining* the second future using the `then()` member function. This future multiplies the result of the second future by 3.

The next part of the code demonstrates how to use *promises* and *packaged tasks*, which are constructs used for communicating data between threads. The `promise` class is used to store a value that can be retrieved *later* using a future. The `packaged_task` class represents a task that can be executed *asynchronously*, and its result can be obtained using a future. The last three lines create a packaged task that returns an integer, obtain its future, execute the task, and check whether the future is ready or not.

The code then demonstrates how to use the `hpx::post()` and `hpx::sync()` functions for *fire-and-forget* and *synchronous* execution, respectively. The `hpx::post()` function executes a given function *asynchronously* and *returns immediately* without waiting for the result. The `hpx::sync()` function executes a given function *synchronously* and *waits* for the result before returning.

Next the code demonstrates the use of *combinators*, which are higher-order functions that combine two or more futures into a single future. The `hpx::when_all()` function is used to combine two futures, which return double values, into a tuple of futures. The `then()` member function is then used to compute the area of a circle using the values of the two futures. The `get()` member function is used to retrieve the result of the computation.

The last section demonstrates the use of `hpx::dataflow()`, which is a higher-order function that waits for all the future or `shared_future` arguments to be ready before executing the continuation. The `hpx::make_ready_future()` function is used to create a future with a given value. The `hpx::split_future()` function is used to split a future of a tuple into a tuple of futures. The last line retrieves the value of the second future in the tuple using `hpx::get()` and prints it to the console.

Extended facilities for futures

Concurrency is about both decomposing and composing the program from the parts that work well individually and together. It is in the composition of connected and multicore components where today's C++ libraries are still lacking.

The functionality of `std::future`⁷⁵ offers a partial solution. It allows for the separation of the initiation of an operation and the act of waiting for its result; however, the act of waiting is synchronous. In communication-intensive code this act of waiting can be unpredictable, inefficient and simply frustrating. The example below illustrates a possible synchronous wait using futures:

```
#include <future>
using namespace std;
int main()
{
    future<int> f = async([]() { return 123; });
    int result = f.get(); // might block
}
```

For this reason, *HPX* implements a set of extensions to `std::future`⁷⁶ (as proposed by N4313⁷⁷). This proposal introduces the following key asynchronous operations to `hpx::future`, `hpx::shared_future` and `hpx::async`, which enhance and enrich these facilities.

Table 2.11: Facilities extending `std::future`

Facility	Description
<code>hpx::future::then</code>	In asynchronous programming, it is very common for one asynchronous operation, on completion, to invoke a second operation and pass data to it. The current C++ standard does not allow one to register a continuation to a future. With <code>then</code> , instead of waiting for the result, a continuation is “attached” to the asynchronous operation, which is invoked when the result is ready. Continuations registered using <code>then</code> function will help to avoid blocking waits or wasting threads on polling, greatly improving the responsiveness and scalability of an application.
unwrapping constructor for <code>hpx::future</code>	In some scenarios, you might want to create a future that returns another future, resulting in nested futures. Although it is possible to write code to unwrap the outer future and retrieve the nested future and its result, such code is not easy to write because users must handle exceptions and it may cause a blocking call. Unwrapping can allow users to mitigate this problem by doing an asynchronous call to unwrap the outermost future.
<code>hpx::future::is_ready</code>	There are often situations where a <code>get()</code> call on a future may not be a blocking call, or is only a blocking call under certain circumstances. This function gives the ability to test for early completion and allows us to avoid associating a continuation, which needs to be scheduled with some non-trivial overhead and near-certain loss of cache efficiency.
<code>hpx::make_ready_future</code>	Some functions may know the value at the point of construction. In these cases the value is immediately available, but needs to be returned as a future. By using <code>hpx::make_ready_future</code> a future can be created that holds a pre-computed result in its shared state. In the current standard it is non-trivial to create a future directly from a value. First a promise must be created, then the promise is set, and lastly the future is retrieved from the promise. This can now be done with one operation.

The standard also omits the ability to compose multiple futures. This is a common pattern that is ubiquitous in other asynchronous frameworks and is absolutely necessary in order to make C++ a powerful asynchronous programming language. Not including these functions is synonymous to Boolean algebra without AND/OR.

⁷⁵ <http://en.cppreference.com/w/cpp/thread/future>

⁷⁶ <http://en.cppreference.com/w/cpp/thread/future>

⁷⁷ <http://wg21.link/n4313>

In addition to the extensions proposed by N4313⁷⁸, HPX adds functions allowing users to compose several futures in a more flexible way.

Table 2.12: Facilities for composing `hpx::futures`

Facility	Description
<code>hpx::when_any</code> , <code>hpx::when_any_n</code>	Asynchronously wait for at least one of multiple future or shared_future objects to finish.
<code>hpx::wait_any</code> , <code>hpx::wait_any_n</code>	Synchronously wait for at least one of multiple future or shared_future objects to finish.
<code>hpx::when_all</code> , <code>hpx::when_all_n</code>	Asynchronously wait for all future and shared_future objects to finish.
<code>hpx::wait_all</code> , <code>hpx::wait_all_n</code>	Synchronously wait for all future and shared_future objects to finish.
<code>hpx::when_some</code> , <code>hpx::when_some_n</code>	Asynchronously wait for multiple future and shared_future objects to finish.
<code>hpx::wait_some</code> , <code>hpx::wait_some_n</code>	Synchronously wait for multiple future and shared_future objects to finish.
<code>hpx::when_each</code>	Asynchronously wait for multiple future and shared_future objects to finish and call a function for each of the future objects as soon as it becomes ready.
<code>hpx::wait_each</code> , <code>hpx::wait_each_n</code>	Synchronously wait for multiple future and shared_future objects to finish and call a function for each of the future objects as soon as it becomes ready.

Channels

Channels combine communication (the exchange of a value) with synchronization (guaranteeing that two calculations (tasks) are in a known state). A channel can transport any number of values of a given type from a sender to a receiver:

```
hpx::lcos::local::channel<int> c;
hpx::future<int> f = c.get();
HPX_ASSERT(!f.is_ready());
c.set(42);
HPX_ASSERT(f.is_ready());
std::cout << f.get() << std::endl;
```

Channels can be handed to another thread (or in case of channel components, to other localities), thus establishing a communication channel between two independent places in the program:

```
void do_something(hpx::lcos::local::receive_channel<int> c,
hpx::lcos::local::send_channel<> done)
{
    // prints 43
    std::cout << c.get(hpx::launch::sync) << std::endl;
    // signal back
    done.set();
}

void send_receive_channel()
{
    hpx::lcos::local::channel<int> c;
    hpx::lcos::local::channel<> done;
```

(continues on next page)

⁷⁸ <http://wg21.link/n4313>

(continued from previous page)

```

hpx::post(&do_something, c, done);

// send some value
c.set(43);
// wait for thread to be done
done.get().wait();
}

```

Note how `hpx::lcos::local::channel::get` without any arguments returns a future which is ready when a value has been set on the channel. The launch policy `hpx::launch::sync` can be used to make `hpx::lcos::local::channel::get` block until a value is set and return the value directly.

A channel component is created on one *locality* and can be sent to another *locality* using an action. This example also demonstrates how a channel can be used as a range of values:

```

// channel components need to be registered for each used type (not needed
// for hpx::lcos::local::channel)
HPX_REGISTER_CHANNEL(double)

void channel_sender(hpx::lcos::channel<double> c)
{
    for (double d : c)
        hpx::cout << d << std::endl;
}
HPX_PLAIN_ACTION(channel_sender)

void channel()
{
    // create the channel on this locality
    hpx::lcos::channel<double> c(hpx::find_here());

    // pass the channel to a (possibly remote invoked) action
    hpx::post(channel_sender_action(), hpx::find_here(), c);

    // send some values to the receiver
    std::vector<double> v = {1.2, 3.4, 5.0};
    for (double d : v)
        c.set(d);

    // explicitly close the communication channel (implicit at destruction)
    c.close();
}

```

Task blocks

Task blocks in *HPX* provide a way to structure and organize the execution of tasks in a parallel program, making it easier to manage dependencies between tasks. A task block actually is a group of tasks that can be executed in parallel. Tasks in a task block can depend on other tasks in the same task block. The task block allows the runtime to optimize the execution of tasks, by scheduling them in an optimal order based on the dependencies between them.

The `define_task_block`, `run` and the `wait` functions implemented based on N4755⁷⁹ are based on the `task_block` concept that is a part of the common subset of the [Microsoft Parallel Patterns Library \(PPL\)](https://msdn.microsoft.com/en-us/library/dd492418.aspx)⁸⁰ and the [Intel Threading Building Blocks \(TBB\)](https://www.threadingbuildingblocks.org/)⁸¹ libraries.

These implementations adopt a simpler syntax than exposed by those libraries— one that is influenced by language-based concepts, such as `spawn` and `sync` from [Cilk++](https://ericniebler.com/2014/05/19/cilk-plus/)⁸² and `async` and `finish` from [X10](https://ericniebler.com/2014/05/19/cilk-plus/)⁸³. They improve on existing practice in the following ways:

- The exception handling model is simplified and more consistent with normal C++ exceptions.
- Most violations of strict fork-join parallelism can be enforced at compile time (with compiler assistance, in some cases).
- The syntax allows scheduling approaches other than child stealing.

Consider an example of a parallel traversal of a tree, where a user-provided function `compute` is applied to each node of the tree, returning the sum of the results:

```
template <typename Func>
int traverse(node& n, Func && compute)
{
    int left = 0, right = 0;
    define_task_block(
        [&](task_block<>& tr) {
            if (n.left)
                tr.run([&] { left = traverse(*n.left, compute); });
            if (n.right)
                tr.run([&] { right = traverse(*n.right, compute); });
        });

    return compute(n) + left + right;
}
```

The example above demonstrates the use of two of the functions, `hpx::experimental::define_task_block` and the `hpx::experimental::task_block::run` member function of a `hpx::experimental::task_block`.

The `task_block` function delineates a region in a program code potentially containing invocations of threads spawned by the `run` member function of the `task_block` class. The `run` function spawns an *HPX* thread, a unit of work that is allowed to execute in parallel with respect to the caller. Any parallel tasks spawned by `run` within the task block are joined back to a single thread of execution at the end of the `define_task_block`. `run` takes a user-provided function object `f` and starts it asynchronously—i.e., it may return before the execution of `f` completes. The *HPX* scheduler may choose to run `f` immediately or delay running `f` until compute resources become available.

A `task_block` can be constructed only by `define_task_block` because it has no public constructors. Thus, `run` can be invoked directly or indirectly only from a user-provided function passed to `define_task_block`:

⁷⁹ <http://wg21.link/n4755>

⁸⁰ <https://msdn.microsoft.com/en-us/library/dd492418.aspx>

⁸¹ <https://www.threadingbuildingblocks.org/>

⁸² <https://software.intel.com/en-us/articles/intel-cilk-plus/>

⁸³ <https://x10-lang.org/>

```

void g();

void f(task_block<>& tr)
{
    tr.run(g);           // OK, invoked from within task_block in h
}

void h()
{
    define_task_block(f);
}

int main()
{
    task_block<> tr;      // Error: no public constructor
    tr.run(g);           // No way to call run outside of a define_task_block
    return 0;
}

```

Extensions for task blocks

Using execution policies with task blocks

HPX implements some extensions for `task_block` beyond the actual standards proposal N4755⁸⁴. The main addition is that a `task_block` can be invoked with an execution policy as its first argument, very similar to the parallel algorithms.

An execution policy is an object that expresses the requirements on the ordering of functions invoked as a consequence of the invocation of a task block. Enabling passing an execution policy to `define_task_block` gives the user control over the amount of parallelism employed by the created `task_block`. In the following example the use of an explicit `par` execution policy makes the user's intent explicit:

```

template <typename Func>
int traverse(node *n, Func&& compute)
{
    int left = 0, right = 0;

    define_task_block(
        execution::par,           // execution::parallel_policy
        [&](task_block<>& tb) {
            if (n->left)
                tb.run([&] { left = traverse(n->left, compute); });
            if (n->right)
                tb.run([&] { right = traverse(n->right, compute); });
        });

    return compute(n) + left + right;
}

```

This also causes the `hpx::experimental::task_block` object to be a template in our implementation. The template argument is the type of the execution policy used to create the task block. The template argument defaults to `hpx::execution::parallel_policy`.

⁸⁴ <http://wg21.link/n4755>

HPX still supports calling `hpx::experimental::define_task_block` without an explicit execution policy. In this case the task block will run using the `hpx::execution::parallel_policy`.

HPX also adds the ability to access the execution policy that was used to create a given `task_block`.

Using executors to run tasks

Often, users want to be able to not only define an execution policy to use by default for all spawned tasks inside the task block, but also to customize the execution context for one of the tasks executed by `task_block::run`. Adding an optionally passed executor instance to that function enables this use case:

```
template <typename Func>
int traverse(node *n, Func&& compute)
{
    int left = 0, right = 0;

    define_task_block(
        execution::par,                // execution::parallel_policy
        [&](auto& tb) {
            if (n->left)
            {
                // use explicitly specified executor to run this task
                tb.run(my_executor(), [&] { left = traverse(n->left, compute); });
            }
            if (n->right)
            {
                // use the executor associated with the par execution policy
                tb.run([&] { right = traverse(n->right, compute); });
            }
        });

    return compute(n) + left + right;
}
```

HPX still supports calling `hpx::experimental::task_block::run` without an explicit executor object. In this case the task will be run using the executor associated with the execution policy that was used to call `hpx::experimental::define_task_block`.

Task groups

A *task group* in HPX is a synchronization primitive that allows you to execute a group of tasks concurrently and wait for their completion before continuing. The tasks in an `hpx::experimental::task_group` can be added dynamically. This is the HPX implementation of `tbb::task_group` of the Intel Threading Building Blocks (TBB)⁸⁵ library.

The example below shows that to use a task group, you simply create an `hpx::task_group` object and add tasks to it using the `run()` method. Once all the tasks have been added, you can call the `wait()` method to synchronize the tasks and wait for them to complete.

```
#include <hpx/experimental/task_group.hpp>
#include <hpx/init.hpp>
```

(continues on next page)

⁸⁵ <https://www.threadingbuildingblocks.org/>

(continued from previous page)

```
#include <iostream>

void task1()
{
    std::cout << "Task 1 executed." << std::endl;
}

void task2()
{
    std::cout << "Task 2 executed." << std::endl;
}

int hpx_main()
{
    hpx::experimental::task_group tg;

    tg.run(task1);
    tg.run(task2);

    tg.wait();

    std::cout << "All tasks finished!" << std::endl;

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}
```

Note: *task groups* and *task blocks* are both ways to group and synchronize parallel tasks, but *task groups* are used to group multiple tasks together as a single unit, while *task blocks* are used to execute a loop in parallel, with each iteration of the loop executing in a separate task. If the difference is not clear yet, continue reading.

A *task group* is a construct that allows multiple parallel tasks to be grouped together as a single unit. The task group provides a way to synchronize all the tasks in the group before continuing with the rest of the program.

A *task block*, on the other hand, is a parallel loop construct that allows you to execute a loop in parallel, with each iteration of the loop executing in a separate task. The loop iterations are executed in a block, meaning that the loop body is executed as a single task.

Threads

A thread in *HPX* refers to a sequence of instructions that can be executed concurrently with other such sequences in multithreading environments, while sharing a same address space. These threads can communicate with each other through various means, such as futures or shared data structures.

The example below demonstrates how to launch multiple threads and synchronize them using a `hpx::latch` object. It also shows how to query the state of threads and wait for futures to complete.

```
#include <hpx/future.hpp>
#include <hpx/init.hpp>
#include <hpx/thread.hpp>

#include <functional>
#include <iostream>
#include <vector>

int const num_threads = 10;

/////////////////////////////////////////////////////////////////
void wait_for_latch(hpx::latch& l)
{
    l.arrive_and_wait();
}

int hpx_main()
{
    // Spawn a couple of threads
    hpx::latch l(num_threads + 1);

    std::vector<hpx::future<void>> results;
    results.reserve(num_threads);

    for (int i = 0; i != num_threads; ++i)
        results.push_back(hpx::async(&wait_for_latch, std::ref(l)));

    // Allow spawned threads to reach latch
    hpx::this_thread::yield();

    // Enumerate all suspended threads
    hpx::threads::enumerate_threads(
        [](hpx::threads::thread_id_type id) -> bool {
            std::cout << "thread " << hpx::thread::id(id) << " is "
                << hpx::threads::get_thread_state_name(
                    hpx::threads::get_thread_state(id))
                << std::endl;
            return true;    // always continue enumeration
        },
        hpx::threads::thread_schedule_state::suspended);

    // Wait for all threads to reach this point.
    l.arrive_and_wait();
}
```

(continues on next page)

(continued from previous page)

```

    hpx::wait_all(results);

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}

```

In more detail, the `wait_for_latch()` function is a simple helper function that waits for a `hpx::latch` object to be released. At this point we remind that `hpx::latch` is a synchronization primitive that allows multiple threads to wait for a common event to occur.

In the `hpx_main()` function, an `hpx::latch` object is created with a count of `num_threads + 1`, indicating that `num_threads` threads need to arrive at the latch before the latch is released. The loop that follows launches `num_threads` asynchronous operations, each of which calls the `wait_for_latch` function. The resulting futures are added to the vector.

After the threads have been launched, `hpx::this_thread::yield()` is called to give them a chance to reach the latch before the program proceeds. Then, the `hpx::threads::enumerate_threads` function prints the state of each suspended thread, while the next call of `l.arrive_and_wait()` waits for all the threads to reach the latch. Finally, `hpx::wait_all` is called to wait for all the futures to complete.

Hint: An advantage of using `hpx::thread` over other threading libraries is that it is optimized for high-performance parallelism, with support for lightweight threads and task scheduling to minimize thread overhead and maximize parallelism. Additionally, `hpx::thread` integrates seamlessly with other features of *HPX* such as futures, promises, and task groups, making it a powerful tool for parallel programming.

Checkout the examples of *Shared mutex*, *Condition variable*, *Semaphore* to see how *HPX* threads are used in combination with other features.

High level parallel facilities

In preparation for the upcoming C++ Standards, there are currently several proposals targeting different facilities supporting parallel programming. *HPX* implements (and extends) some of those proposals. This is well aligned with our strategy to align the APIs exposed from *HPX* with current and future C++ Standards.

At this point, *HPX* implements several of the C++ Standardization working papers, most notably [N4409](http://wg21.link/n4409)⁸⁶ (Working Draft, Technical Specification for C++ Extensions for Parallelism), [N4755](http://wg21.link/n4755)⁸⁷ (Task Blocks), and [N4406](http://wg21.link/n4406)⁸⁸ (Parallel Algorithms Need Executors).

⁸⁶ <http://wg21.link/n4409>

⁸⁷ <http://wg21.link/n4755>

⁸⁸ <http://wg21.link/n4406>

Using parallel algorithms

A parallel algorithm is a function template declared in the namespace `hpx::parallel`.

All parallel algorithms are very similar in semantics to their sequential counterparts (as defined in the namespace `std`) with an additional formal template parameter named `ExecutionPolicy`. The execution policy is generally passed as the first argument to any of the parallel algorithms and describes the manner in which the execution of these algorithms may be parallelized and the manner in which they apply user-provided function objects.

The applications of function objects in parallel algorithms invoked with an execution policy object of type `hpx::execution::sequenced_policy` or `hpx::execution::sequenced_task_policy` execute in sequential order. For `hpx::execution::sequenced_policy` the execution happens in the calling thread.

The applications of function objects in parallel algorithms invoked with an execution policy object of type `hpx::execution::parallel_policy` or `hpx::execution::parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and are indeterminately sequenced within each thread.

Important: It is the caller's responsibility to ensure correctness, such as making sure that the invocation does not introduce data races or deadlocks.

The example below demonstrates how to perform a sequential and parallel `hpx::for_each` loop on a vector of integers.

```
#include <hpx/algorithm.hpp>
#include <hpx/execution.hpp>
#include <hpx/init.hpp>

#include <iostream>
#include <vector>

int hpx_main()
{
    std::vector<int> v{1, 2, 3, 4, 5};

    auto print = [](int const& n) { std::cout << n << ' '; };

    std::cout << "Print sequential: ";
    hpx::for_each(v.begin(), v.end(), print);
    std::cout << '\n';

    std::cout << "Print parallel: ";
    hpx::for_each(hpx::execution::par, v.begin(), v.end(), print);
    std::cout << '\n';

    return hpx::local::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::local::init(hpx_main, argc, argv);
}
```

The above code uses `hpx::for_each` to print the elements of the vector `v{1, 2, 3, 4, 5}`. At first, `hpx::for_each()` is called without an execution policy, which means that it applies the lambda function `print` to each element in the vector sequentially. Hence, the elements are printed in order.

Next, `hpx::for_each()` is called with the `hpx::execution::par` execution policy, which applies the lambda function `print` to each element in the vector in parallel. Therefore, the output order of the elements in the vector is not deterministic and may vary from run to run.

Parallel exceptions

During the execution of a standard parallel algorithm, if temporary memory resources are required by any of the algorithms and no memory is available, the algorithm throws a `std::bad_alloc` exception.

During the execution of any of the parallel algorithms, if the application of a function object terminates with an uncaught exception, the behavior of the program is determined by the type of execution policy used to invoke the algorithm:

- If the execution policy object is of type `hpx::execution::parallel_unsequenced_policy`, `hpx::terminate` shall be called.
- If the execution policy object is of type `hpx::execution::sequenced_policy`, `hpx::execution::sequenced_task_policy`, `hpx::execution::parallel_policy`, or `hpx::execution::parallel_task_policy`, the execution of the algorithm terminates with an `hpx::exception_list` exception. All uncaught exceptions thrown during the application of user-provided function objects shall be contained in the `hpx::exception_list`.

For example, the number of invocations of the user-provided function object in `for_each` is unspecified. When `hpx::for_each` is executed sequentially, only one exception will be contained in the `hpx::exception_list` object.

These guarantees imply that, unless the algorithm has failed to allocate memory and terminated with `std::bad_alloc`, all exceptions thrown during the execution of the algorithm are communicated to the caller. It is unspecified whether an algorithm implementation will “forge ahead” after encountering and capturing a user exception.

The algorithm may terminate with the `std::bad_alloc` exception even if one or more user-provided function objects have terminated with an exception. For example, this can happen when an algorithm fails to allocate memory while creating or adding elements to the `hpx::exception_list` object.

Parallel algorithms

HPX provides implementations of the following parallel algorithms:

Table 2.13: Non-modifying parallel algorithms of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::adjacent_find</code>	Computes the differences between adjacent elements in a range.	<code>adjacent_find</code> ⁸⁹
<code>hpx::all_of</code>	Checks if a predicate is <code>true</code> for all of the elements in a range.	<code>all_any_none_of</code> ⁹⁰
<code>hpx::any_of</code>	Checks if a predicate is <code>true</code> for any of the elements in a range.	<code>all_any_none_of</code> ⁹¹
<code>hpx::count</code>	Returns the number of elements equal to a given value.	<code>count</code> ⁹²
<code>hpx::count_if</code>	Returns the number of elements satisfying a specific criteria.	<code>count_if</code> ⁹³
<code>hpx::equal</code>	Determines if two sets of elements are the same.	<code>equal</code> ⁹⁴
<code>hpx::find</code>	Finds the first element equal to a given value.	<code>find</code> ⁹⁵
<code>hpx::find_end</code>	Finds the last sequence of elements in a certain range.	<code>find_end</code> ⁹⁶
<code>hpx::find_first_of</code>	Searches for any one of a set of elements.	<code>find_first_of</code> ⁹⁷
<code>hpx::find_if</code>	Finds the first element satisfying a specific criteria.	<code>find_if</code> ⁹⁸
<code>hpx::find_if_not</code>	Finds the first element not satisfying a specific criteria.	<code>find_if_not</code> ⁹⁹
<code>hpx::for_each</code>	Applies a function to a range of elements.	<code>for_each</code> ¹⁰⁰
<code>hpx::for_each_n</code>	Applies a function to a number of elements.	<code>for_each_n</code> ¹⁰¹
<code>hpx::lexicographical_compare</code>	Checks if a range of values is lexicographically less than another range of values.	<code>lexicographical_compare</code> ¹⁰²
<code>hpx::mismatch</code>	Finds the first position where two ranges differ.	<code>mismatch</code> ¹⁰³
<code>hpx::none_of</code>	Checks if a predicate is <code>true</code> for none of the elements in a range.	<code>all_any_none_of</code> ¹⁰⁴
<code>hpx::search</code>	Searches for a range of elements.	<code>search</code> ¹⁰⁵
<code>hpx::search_n</code>	Searches for a number consecutive copies of an element in a range.	<code>search_n</code> ¹⁰⁶

⁸⁹ http://en.cppreference.com/w/cpp/algorithm/adjacent_find⁹⁰ http://en.cppreference.com/w/cpp/algorithm/all_any_none_of⁹¹ http://en.cppreference.com/w/cpp/algorithm/all_any_none_of⁹² <http://en.cppreference.com/w/cpp/algorithm/count>⁹³ http://en.cppreference.com/w/cpp/algorithm/count_if⁹⁴ <http://en.cppreference.com/w/cpp/algorithm/equal>⁹⁵ <http://en.cppreference.com/w/cpp/algorithm/find>⁹⁶ http://en.cppreference.com/w/cpp/algorithm/find_end⁹⁷ http://en.cppreference.com/w/cpp/algorithm/find_first_of⁹⁸ http://en.cppreference.com/w/cpp/algorithm/find_if⁹⁹ http://en.cppreference.com/w/cpp/algorithm/find_if_not¹⁰⁰ http://en.cppreference.com/w/cpp/algorithm/for_each¹⁰¹ http://en.cppreference.com/w/cpp/algorithm/for_each_n¹⁰² http://en.cppreference.com/w/cpp/algorithm/lexicographical_compare¹⁰³ <http://en.cppreference.com/w/cpp/algorithm/mismatch>¹⁰⁴ http://en.cppreference.com/w/cpp/algorithm/all_any_none_of¹⁰⁵ <http://en.cppreference.com/w/cpp/algorithm/search>¹⁰⁶ http://en.cppreference.com/w/cpp/algorithm/search_n

Table 2.14: Modifying parallel algorithms of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::copy</code>	Copies a range of elements to a new location.	<code>exclusive_scan</code> ¹⁰⁷
<code>hpx::copy_n</code>	Copies a number of elements to a new location.	<code>copy_n</code> ¹⁰⁸
<code>hpx::copy_if</code>	Copies the elements from a range to a new location for which the given predicate is <code>true</code>	<code>copy</code> ¹⁰⁹
<code>hpx::move</code>	Moves a range of elements to a new location.	<code>move</code> ¹¹⁰
<code>hpx::fill</code>	Assigns a range of elements a certain value.	<code>fill</code> ¹¹¹
<code>hpx::fill_n</code>	Assigns a value to a number of elements.	<code>fill_n</code> ¹¹²
<code>hpx::generate</code>	Saves the result of a function in a range.	<code>generate</code> ¹¹³
<code>hpx::generate_n</code>	Saves the result of N applications of a function.	<code>generate_n</code> ¹¹⁴
<code>hpx::experimental::reduce_by_key</code>	Performs an inclusive scan on consecutive elements with matching keys, with a reduction to output only the final sum for each key. The key sequence <code>{1,1,1,2,3,3,3,3,1}</code> and value sequence <code>{2,3,4,5,6,7,8,9,10}</code> would be reduced to <code>keys={1,2,3,1}</code> , <code>values={9,5,30,10}</code> .	
<code>hpx::remove</code>	Removes the elements from a range that are equal to the given value.	<code>remove</code> ¹¹⁵
<code>hpx::remove_if</code>	Removes the elements from a range that are equal to the given predicate is <code>false</code>	<code>remove</code> ¹¹⁶
<code>hpx::remove_copy</code>	Copies the elements from a range to a new location that are not equal to the given value.	<code>remove_copy</code> ¹¹⁷
<code>hpx::remove_copy_if</code>	Copies the elements from a range to a new location for which the given predicate is <code>false</code>	<code>remove_copy</code> ¹¹⁸
<code>hpx::replace</code>	Replaces all values satisfying specific criteria with another value.	<code>replace</code> ¹¹⁹
<code>hpx::replace_if</code>	Replaces all values satisfying specific criteria with another value.	<code>replace</code> ¹²⁰
<code>hpx::replace_copy</code>	Copies a range, replacing elements satisfying specific criteria with another value.	<code>replace_copy</code> ¹²¹
<code>hpx::replace_copy_if</code>	Copies a range, replacing elements satisfying specific criteria with another value.	<code>replace_copy</code> ¹²²
<code>hpx::reverse</code>	Reverses the order elements in a range.	<code>reverse</code> ¹²³
<code>hpx::reverse_copy</code>	Creates a copy of a range that is reversed.	<code>reverse_copy</code> ¹²⁴
<code>hpx::rotate</code>	Rotates the order of elements in a range.	<code>rotate</code> ¹²⁵
<code>hpx::rotate_copy</code>	Copies and rotates a range of elements.	<code>rotate_copy</code> ¹²⁶
<code>hpx::shift_left</code>	Shifts the elements in the range left by n positions.	<code>shift_left</code> ¹²⁷
<code>hpx::shift_right</code>	Shifts the elements in the range right by n positions.	<code>shift_right</code> ¹²⁸
<code>hpx::swap_ranges</code>	Swaps two ranges of elements.	<code>swap_ranges</code> ¹²⁹
<code>hpx::transform</code>	Applies a function to a range of elements.	<code>transform</code> ¹³⁰
<code>hpx::unique</code>	Eliminates all but the first element from every consecutive group of equivalent elements from a range.	<code>unique</code> ¹³¹
<code>hpx::unique_copy</code>	Copies the elements from one range to another in such a way that there are no consecutive equal elements.	<code>unique_copy</code> ¹³²

Table 2.15: Set operations on sorted sequences of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::merge</code>	Merges two sorted ranges.	<code>merge</code> ¹³³
<code>hpx::inplace_merge</code>	Merges two ordered ranges in-place.	<code>inplace_merge</code> ¹³⁴
<code>hpx::includes</code>	Returns true if one set is a subset of another.	<code>includes</code> ¹³⁵
<code>hpx::set_difference</code>	Computes the difference between two sets.	<code>set_difference</code> ¹³⁶
<code>hpx::set_intersection</code>	Computes the intersection of two sets.	<code>set_intersection</code> ¹³⁷
<code>hpx::set_symmetric_difference</code>	Computes the symmetric difference between two sets.	<code>set_symmetric_difference</code> ¹³⁸
<code>hpx::set_union</code>	Computes the union of two sets.	<code>set_union</code> ¹³⁹

Table 2.16: Heap operations of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::is_heap</code>	Returns true if the range is max heap.	<code>is_heap</code> ¹⁴⁰
<code>hpx::is_heap_until</code>	Returns the first element that breaks a max heap.	<code>is_heap_until</code> ¹⁴¹
<code>hpx::make_heap</code>	Constructs a max heap in the range [first, last).	<code>make_heap</code> ¹⁴²

¹⁰⁷ http://en.cppreference.com/w/cpp/algorithm/exclusive_scan¹⁰⁸ http://en.cppreference.com/w/cpp/algorithm/copy_n¹⁰⁹ <http://en.cppreference.com/w/cpp/algorithm/copy>¹¹⁰ <http://en.cppreference.com/w/cpp/algorithm/move>¹¹¹ <http://en.cppreference.com/w/cpp/algorithm/fill>¹¹² http://en.cppreference.com/w/cpp/algorithm/fill_n¹¹³ <http://en.cppreference.com/w/cpp/algorithm/generate>¹¹⁴ http://en.cppreference.com/w/cpp/algorithm/generate_n¹¹⁵ <http://en.cppreference.com/w/cpp/algorithm/remove>¹¹⁶ <http://en.cppreference.com/w/cpp/algorithm/remove>¹¹⁷ http://en.cppreference.com/w/cpp/algorithm/remove_copy¹¹⁸ http://en.cppreference.com/w/cpp/algorithm/remove_copy¹¹⁹ <http://en.cppreference.com/w/cpp/algorithm/replace>¹²⁰ <http://en.cppreference.com/w/cpp/algorithm/replace>¹²¹ http://en.cppreference.com/w/cpp/algorithm/replace_copy¹²² http://en.cppreference.com/w/cpp/algorithm/replace_copy¹²³ <http://en.cppreference.com/w/cpp/algorithm/reverse>¹²⁴ http://en.cppreference.com/w/cpp/algorithm/reverse_copy¹²⁵ <http://en.cppreference.com/w/cpp/algorithm/rotate>¹²⁶ http://en.cppreference.com/w/cpp/algorithm/rotate_copy¹²⁷ http://en.cppreference.com/w/cpp/algorithm/shift_left¹²⁸ http://en.cppreference.com/w/cpp/algorithm/shift_right¹²⁹ http://en.cppreference.com/w/cpp/algorithm/swap_ranges¹³⁰ <http://en.cppreference.com/w/cpp/algorithm/transform>¹³¹ <http://en.cppreference.com/w/cpp/algorithm/unique>¹³² http://en.cppreference.com/w/cpp/algorithm/unique_copy¹³³ <http://en.cppreference.com/w/cpp/algorithm/merge>¹³⁴ http://en.cppreference.com/w/cpp/algorithm/inplace_merge¹³⁵ <http://en.cppreference.com/w/cpp/algorithm/includes>¹³⁶ http://en.cppreference.com/w/cpp/algorithm/set_difference¹³⁷ http://en.cppreference.com/w/cpp/algorithm/set_intersection¹³⁸ http://en.cppreference.com/w/cpp/algorithm/set_symmetric_difference¹³⁹ http://en.cppreference.com/w/cpp/algorithm/set_union

Table 2.17: Minimum/maximum operations of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::max_element</code>	Returns the largest element in a range.	<code>max_element</code> ¹⁴³
<code>hpx::min_element</code>	Returns the smallest element in a range.	<code>min_element</code> ¹⁴⁴
<code>hpx::minmax_element</code>	Returns the smallest and the largest element in a range.	<code>minmax_element</code> ¹⁴⁵

Table 2.18: Partitioning Operations of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::nth_element</code>	Partially sorts the given range making sure that it is partitioned by the given element	<code>nth_element</code> ¹⁴⁶
<code>hpx::is_partitioned</code>	Returns <code>true</code> if each true element for a predicate precedes the false elements in a range.	<code>is_partitioned</code> ¹⁴⁷
<code>hpx::partition</code>	Divides elements into two groups without preserving their relative order.	<code>partition</code> ¹⁴⁸
<code>hpx::partition_copy</code>	Copies a range dividing the elements into two groups.	<code>partition_copy</code> ¹⁴⁹
<code>hpx::stable_partition</code>	Divides elements into two groups while preserving their relative order.	<code>stable_partition</code> ¹⁵⁰

Table 2.19: Sorting Operations of header `hpx/algorithm.hpp`

Name	Description	C++ standard
<code>hpx::is_sorted</code>	Returns <code>true</code> if each element in a range is sorted.	<code>is_sorted</code> ¹⁵¹
<code>hpx::is_sorted_until</code>	Returns the first unsorted element.	<code>is_sorted_until</code> ¹⁵²
<code>hpx::sort</code>	Sorts the elements in a range.	<code>sort</code> ¹⁵³
<code>hpx::stable_sort</code>	Sorts the elements in a range, maintain sequence of equal elements.	<code>stable_sort</code> ¹⁵⁴
<code>hpx::partial_sort</code>	Sorts the first elements in a range.	<code>partial_sort</code> ¹⁵⁵
<code>hpx::partial_sort_copy</code>	Sorts the first elements in a range, storing the result in another range.	<code>partial_sort_copy</code> ¹⁵⁶
<code>hpx::experimental::sort_by_key</code>	Sorts a range of data using keys supplied in another range.	

¹⁴⁰ http://en.cppreference.com/w/cpp/algorithm/is_heap¹⁴¹ http://en.cppreference.com/w/cpp/algorithm/is_heap_until¹⁴² http://en.cppreference.com/w/cpp/algorithm/make_heap¹⁴³ http://en.cppreference.com/w/cpp/algorithm/max_element¹⁴⁴ http://en.cppreference.com/w/cpp/algorithm/min_element¹⁴⁵ http://en.cppreference.com/w/cpp/algorithm/minmax_element¹⁴⁶ http://en.cppreference.com/w/cpp/algorithm/nth_element¹⁴⁷ http://en.cppreference.com/w/cpp/algorithm/is_partitioned¹⁴⁸ <http://en.cppreference.com/w/cpp/algorithm/partition>¹⁴⁹ http://en.cppreference.com/w/cpp/algorithm/partition_copy¹⁵⁰ http://en.cppreference.com/w/cpp/algorithm/stable_partition

Table 2.20: Numeric Parallel Algorithms of header `hpx/numeric.hpp`

Name	Description	C++ standard
<code>hpx::adjacent_difference</code>	Calculates the difference between each element in an input range and the preceding element.	<code>adjacent_difference</code> ¹⁵⁷
<code>hpx::exclusive_scan</code>	Does an exclusive parallel scan over a range of elements.	<code>exclusive_scan</code> ¹⁵⁸
<code>hpx::inclusive_scan</code>	Does an inclusive parallel scan over a range of elements.	<code>inclusive_scan</code> ¹⁵⁹
<code>hpx::reduce</code>	Sums up a range of elements.	<code>reduce</code> ¹⁶⁰
<code>hpx::transform_exclusive_scan</code>	Does an exclusive parallel scan over a range of elements after applying a function.	<code>transform_exclusive_scan</code> ¹⁶¹
<code>hpx::transform_inclusive_scan</code>	Does an inclusive parallel scan over a range of elements after applying a function.	<code>transform_inclusive_scan</code> ¹⁶²
<code>hpx::transform_reduce</code>	Sums up a range of elements after applying a function. Also, accumulates the inner products of two input ranges.	<code>transform_reduce</code> ¹⁶³

¹⁵¹ http://en.cppreference.com/w/cpp/algorithm/is_sorted¹⁵² http://en.cppreference.com/w/cpp/algorithm/is_sorted_until¹⁵³ <http://en.cppreference.com/w/cpp/algorithm/sort>¹⁵⁴ http://en.cppreference.com/w/cpp/algorithm/stable_sort¹⁵⁵ http://en.cppreference.com/w/cpp/algorithm/partial_sort¹⁵⁶ http://en.cppreference.com/w/cpp/algorithm/partial_sort_copy¹⁵⁷ http://en.cppreference.com/w/cpp/algorithm/adjacent_difference¹⁵⁸ http://en.cppreference.com/w/cpp/algorithm/exclusive_scan¹⁵⁹ http://en.cppreference.com/w/cpp/algorithm/inclusive_scan¹⁶⁰ <http://en.cppreference.com/w/cpp/algorithm/reduce>¹⁶¹ http://en.cppreference.com/w/cpp/algorithm/transform_exclusive_scan¹⁶² http://en.cppreference.com/w/cpp/algorithm/transform_inclusive_scan¹⁶³ http://en.cppreference.com/w/cpp/algorithm/transform_reduce

Table 2.21: Dynamic Memory Management of header `hpx/memory.hpp`

Name	Description	C++ standard
<code>hpx::destroy</code>	Destroys a range of objects.	<code>destroy</code> ¹⁶⁴
<code>hpx::destroy_n</code>	Destroys a range of objects.	<code>destroy_n</code> ¹⁶⁵
<code>hpx::uninitialized_copy</code>	Copies a range of objects to an uninitialized area of memory.	<code>uninitialized_copy</code> ¹⁶⁶
<code>hpx::uninitialized_copy_n</code>	Copies a number of objects to an uninitialized area of memory.	<code>uninitialized_copy_n</code> ¹⁶⁷
<code>hpx::uninitialized_default_construct</code>	Constructs a range of objects to an uninitialized area of memory.	<code>uninitialized_default_construct</code> ¹⁶⁸
<code>hpx::uninitialized_default_construct_n</code>	Constructs a number of objects to an uninitialized area of memory.	<code>uninitialized_default_construct_n</code> ¹⁶⁹
<code>hpx::uninitialized_fill</code>	Copies an object to an uninitialized area of memory.	<code>uninitialized_fill</code> ¹⁷⁰
<code>hpx::uninitialized_fill_n</code>	Copies an object to an uninitialized area of memory.	<code>uninitialized_fill_n</code> ¹⁷¹
<code>hpx::uninitialized_move</code>	Moves a range of objects to an uninitialized area of memory.	<code>uninitialized_move</code> ¹⁷²
<code>hpx::uninitialized_move_n</code>	Moves a number of objects to an uninitialized area of memory.	<code>uninitialized_move_n</code> ¹⁷³
<code>hpx::uninitialized_value_construct</code>	Constructs objects in an uninitialized area of memory.	<code>uninitialized_value_construct</code> ¹⁷⁴
<code>hpx::uninitialized_value_construct_n</code>	Constructs objects in an uninitialized area of memory.	<code>uninitialized_value_construct_n</code> ¹⁷⁵

Table 2.22: Index-based for-loops of header `hpx/algorithm.hpp`

Name	Description
<code>hpx::experimental::for_loop</code>	Implements loop functionality over a range specified by integral or iterator bounds.
<code>hpx::experimental::for_loop_strided</code>	Implements loop functionality over a range specified by integral or iterator bounds.
<code>hpx::experimental::for_loop_n</code>	Implements loop functionality over a range specified by integral or iterator bounds.
<code>hpx::experimental::for_loop_n_strided</code>	Implements loop functionality over a range specified by integral or iterator bounds.

¹⁶⁴ <http://en.cppreference.com/w/cpp/memory/destroy>¹⁶⁵ http://en.cppreference.com/w/cpp/memory/destroy_n¹⁶⁶ http://en.cppreference.com/w/cpp/memory/uninitialized_copy¹⁶⁷ http://en.cppreference.com/w/cpp/memory/uninitialized_copy_n¹⁶⁸ http://en.cppreference.com/w/cpp/memory/uninitialized_default_construct¹⁶⁹ http://en.cppreference.com/w/cpp/memory/uninitialized_default_construct_n¹⁷⁰ http://en.cppreference.com/w/cpp/memory/uninitialized_fill¹⁷¹ http://en.cppreference.com/w/cpp/memory/uninitialized_fill_n¹⁷² http://en.cppreference.com/w/cpp/memory/uninitialized_move¹⁷³ http://en.cppreference.com/w/cpp/memory/uninitialized_move_n¹⁷⁴ http://en.cppreference.com/w/cpp/memory/uninitialized_value_construct¹⁷⁵ http://en.cppreference.com/w/cpp/memory/uninitialized_value_construct_n

Executor parameters and executor parameter traits

HPX introduces the notion of execution parameters and execution parameter traits. At this point, the only parameter that can be customized is the size of the chunks of work executed on a single *HPX* thread (such as the number of loop iterations combined to run as a single task).

An executor parameter object is responsible for exposing the calculation of the size of the chunks scheduled. It abstracts the (potentially platform-specific) algorithms of determining those chunk sizes.

The way executor parameters are implemented is aligned with the way executors are implemented. All functionalities of concrete executor parameter types are exposed and accessible through a corresponding customization point, e.g. `get_chunk_size()`.

With `executor_parameter_traits`, clients access all types of executor parameters uniformly, e.g.:

```
std::size_t chunk_size =  
    hpx::execution::experimental::get_chunk_size(my_parameter, my_executor,  
        num_cores, num_tasks);
```

This call synchronously retrieves the size of a single chunk of loop iterations (or similar) to combine for execution on a single *HPX* thread if the overall number of cores `num_cores` and tasks to schedule is given by `num_tasks`. The lambda function exposes a means of test-probing the execution of a single iteration for performance measurement purposes. The execution parameter type might dynamically determine the execution time of one or more tasks in order to calculate the chunk size; see `hpx::execution::experimental::auto_chunk_size` for an example of this executor parameter type.

Other functions in the interface exist to discover whether an executor parameter type should be invoked once (i.e., it returns a static chunk size; see `hpx::execution::experimental::static_chunk_size`) or whether it should be invoked for each scheduled chunk of work (i.e., it returns a variable chunk size; for an example, see `hpx::execution::experimental::guided_chunk_size`).

Although this interface appears to require executor parameter type authors to implement all different basic operations, none are required. In practice, all operations have sensible defaults. However, some executor parameter types will naturally specialize all operations for maximum efficiency.

HPX implements the following executor parameter types:

- `hpx::execution::experimental::auto_chunk_size`: Loop iterations are divided into pieces and then assigned to threads. The number of loop iterations combined is determined based on measurements of how long the execution of 1% of the overall number of iterations takes. This executor parameter type makes sure that as many loop iterations are combined as necessary to run for the amount of time specified.
- `hpx::execution::experimental::static_chunk_size`: Loop iterations are divided into pieces of a given size and then assigned to threads. If the size is not specified, the iterations are, if possible, evenly divided contiguously among the threads. This executor parameters type is equivalent to OpenMP's STATIC scheduling directive.
- `hpx::execution::experimental::dynamic_chunk_size`: Loop iterations are divided into pieces of a given size and then dynamically scheduled among the cores; when a core finishes one chunk, it is dynamically assigned another. If the size is not specified, the default chunk size is 1. This executor parameter type is equivalent to OpenMP's DYNAMIC scheduling directive.
- `hpx::execution::experimental::guided_chunk_size`: Iterations are dynamically assigned to cores in blocks as cores request them until no blocks remain to be assigned. This is similar to `dynamic_chunk_size` except that the block size decreases each time a number of loop iterations is given to a thread. The size of the initial block is proportional to `number_of_iterations / number_of_cores`. Subsequent blocks are proportional to `number_of_iterations_remaining / number_of_cores`. The optional chunk size parameter defines the minimum block size. The default minimal chunk size is 1. This executor parameter type is equivalent to OpenMP's GUIDED scheduling directive.

2.4.12 Writing distributed applications

This section focuses on the features of *HPX* needed to write distributed applications, namely the *Active Global Address Space* (AGAS), remotely executable functions (i.e., *actions*), and distributed objects (i.e., *components*).

Global names

HPX implements an *Active Global Address Space* (AGAS) which exposes a single uniform address space spanning all localities an application runs on. AGAS is a fundamental component of the ParalleX execution model. Conceptually, there is no rigid demarcation of local or global memory in AGAS; all available memory is a part of the same address space. AGAS enables named objects to be moved (migrated) across localities without having to change the object's name; i.e., no references to migrated objects have to be ever updated. This feature has significance for dynamic load balancing and in applications where the workflow is highly dynamic, allowing work to be migrated from heavily loaded nodes to less loaded nodes. In addition, immutability of names ensures that AGAS does not have to keep extra indirections ("bread crumbs") when objects move, hence, minimizing complexity of code management for system developers as well as minimizing overheads in maintaining and managing aliases.

The AGAS implementation in *HPX* does not automatically expose every local address to the global address space. It is the responsibility of the programmer to explicitly define which of the objects have to be globally visible and which of the objects are purely local.

In *HPX* global addresses (global names) are represented using the `hpx::id_type` data type. This data type is conceptually very similar to `void*` pointers as it does not expose any type information of the object it is referring to.

The only predefined global addresses are assigned to all localities. The following *HPX* API functions allow one to retrieve the global addresses of localities:

- `hpx::find_here`: retrieves the global address of the *locality* this function is called on.
- `hpx::find_all_localities`: retrieves the global addresses of all localities available to this application (including the *locality* the function is being called on).
- `hpx::find_remote_localities`: retrieves the global addresses of all remote localities available to this application (not including the *locality* the function is being called on).
- `hpx::get_num_localities`: retrieves the number of localities available to this application.
- `hpx::find_locality`: retrieves the global address of any *locality* supporting the given component type.
- `hpx::get_colocation_id`: retrieves the global address of the *locality* currently hosting the object with the given global address.

Additionally, the global addresses of localities can be used to create new instances of components using the following *HPX* API function:

- `hpx::components::new_`: Creates a new instance of the given *Component* type on the specified *locality*.

Note: *HPX* does not expose any functionality to delete component instances. All global addresses (as represented using `hpx::id_type`) are automatically garbage collected. When the last (global) reference to a particular component instance goes out of scope, the corresponding component instance is automatically deleted.

Posting actions

Action type definition

Actions are special types used to describe possibly remote operations. For every global function and every member function which has to be invoked distantly, a special type must be defined. For any global function the special macro `HPX_PLAIN_ACTION` can be used to define the action type. Here is an example demonstrating this:

```
namespace app
{
    void some_global_function(double d)
    {
        cout << d;
    }
}

// This will define the action type 'some_global_action' which represents
// the function 'app::some_global_function'.
HPX_PLAIN_ACTION(app::some_global_function, some_global_action);
```

Important: The macro `HPX_PLAIN_ACTION` has to be placed in global namespace, even if the wrapped function is located in some other namespace. The newly defined action type is placed in the global namespace as well.

If the action type should be defined somewhere not in global namespace, the action type definition has to be split into two macro invocations (`HPX_DEFINE_PLAIN_ACTION` and `HPX_REGISTER_ACTION`) as shown in the next example:

```
namespace app
{
    void some_global_function(double d)
    {
        cout << d;
    }

    // On conforming compilers the following macro expands to:
    //
    //     typedef hpx::actions::make_action<
    //         decltype(&some_global_function), &some_global_function
    //     >::type some_global_action;
    //
    // This will define the action type 'some_global_action' which represents
    // the function 'some_global_function'.
    HPX_DEFINE_PLAIN_ACTION(some_global_function, some_global_action);
}

// The following macro expands to a series of definitions of global objects
// which are needed for proper serialization and initialization support
// enabling the remote invocation of the function`some_global_function`
HPX_REGISTER_ACTION(app::some_global_action, app_some_global_action);
```

The shown code defines an action type `some_global_action` inside the namespace `app`.

Important: If the action type definition is split between two macros as shown above, the name of the action type to

create has to be the same for both macro invocations (here `some_global_action`).

Important: The second argument passed to `HPX_REGISTER_ACTION` (`app_some_global_action`) has to comprise a globally unique C++ identifier representing the action. This is used for serialization purposes.

For member functions of objects which have been registered with AGAS (e.g., ‘components’), a different registration macro `HPX_DEFINE_COMPONENT_ACTION` has to be utilized. Any component needs to be declared in a header file and have some special support macros defined in a source file. Here is an example demonstrating this. The first snippet has to go into the header file:

```
namespace app
{
    struct some_component
    : hpx::components::component_base<some_component>
    {
        int some_member_function(std::string s)
        {
            return std::stoi(s);
        }

        // This will define the action type 'some_member_action' which
        // represents the member function 'some_member_function' of the
        // object type 'some_component'.
        HPX_DEFINE_COMPONENT_ACTION(some_component, some_member_function,
            some_member_action);
    };
};

// Note: The second argument to the macro below has to be systemwide-unique
// C++ identifiers
HPX_REGISTER_ACTION_DECLARATION(app::some_component::some_member_action, some_component_
↪some_action);
```

The next snippet belongs in a source file (e.g., the main application source file) in the simplest case:

```
typedef hpx::components::component<app::some_component> component_type;
typedef app::some_component some_component;

HPX_REGISTER_COMPONENT(component_type, some_component);

// The parameters for this macro have to be the same as used in the corresponding
// HPX_REGISTER_ACTION_DECLARATION() macro invocation above
typedef some_component::some_member_action some_component_some_action;
HPX_REGISTER_ACTION(some_component_some_action);
```

While these macro invocations are a bit more complex than those for simple global functions, they should still be manageable.

The most important macro invocation is the `HPX_DEFINE_COMPONENT_ACTION` in the header file as this defines the action type we need to invoke the member function. For a complete example of a simple component action see `component_in_executable.cpp`.

Reflection-based component actions (experimental)

Note: This feature requires a compiler with C++26 reflection support (`HPX_HAVE_CXX26_REFLECTION`) and is currently experimental.

When reflection support is available, component actions can be defined with a single macro instead of the three-step process described above:

```
namespace app
{
    struct some_component
    : hpx::components::component_base<some_component>
    {
        int some_member_function(std::string s)
        {
            return std::stoi(s);
        }
        // This single line replaces HPX_DEFINE_COMPONENT_ACTION,
        // HPX_REGISTER_ACTION_DECLARATION, and HPX_REGISTER_ACTION.
        HPX_COMPONENT_ACTION(some_component, some_member_function,
            some_member_action);
    };
}
```

The resulting `some_member_action` type can be used exactly like an action type created with `HPX_DEFINE_COMPONENT_ACTION`, with `hpx::post`, `hpx::async`, and `hpx::sync`, or by invoking it directly. No separate registration step is required in the source file.

Action invocation

The process of invoking a global function (or a member function of an object) with the help of the associated action is called ‘posting the action’. Actions can have arguments, which will be supplied while the action is applied. At the minimum, one parameter is required to post any action - the id of the *locality* the associated function should be invoked on (for global functions), or the id of the component instance (for member functions). Generally, *HPX* provides several ways to post an action, all of which are described in the following sections.

Generally, *HPX* actions are very similar to ‘normal’ C++ functions except that actions can be invoked remotely. Fig. ?? below shows an overview of the main API exposed by *HPX*. This shows the function invocation syntax as defined by the C++ language (dark gray), the additional invocation syntax as provided through C++ Standard Library features (medium gray), and the extensions added by *HPX* (light gray) where:

- `f` function to invoke,
- `p...`: (optional) arguments,
- `R`: return type of `f`,
- `action`: action type defined by, `HPX_DEFINE_PLAIN_ACTION` or `HPX_DEFINE_COMPONENT_ACTION` encapsulating `f`,
- `a`: an instance of the type `action`,
- `id`: the global address the action is applied to.

R f(p...)	Synchronous (return R)	Asynchronous (return future<R>)	Fire & Forget (return void)
Functions (direct)	f(p...) C++	async(f, p...)	post(f, p...)
Functions (lazy)	bind(f, p...)(...)	async(bind(f, p...), ...) C++ Library	post(bind(f, p...), ...)
Actions (direct)	HPX_ACTION(f, a) a(id, p...)	HPX_ACTION(f, a) async(a, id, p...)	HPX_ACTION(f, a) post(a, id, p...)
Actions (lazy)	HPX_ACTION(f, a) bind(a, id, p...)(...)	HPX_ACTION(f, a) async(bind(a, id, p...), ...)	HPX_ACTION(f, a) post(bind(a, id, p...), ...) HPX

Fig. 2.8: Overview of the main API exposed by *HPX*.

This figure shows that *HPX* allows the user to **post** actions with a syntax similar to the C++ standard. In fact, all action types have an overloaded function operator allowing to synchronously **post** the action. Further, *HPX* implements `hpx::async` which semantically works similar to the way `std::async` works for plain C++ function.

Note: The similarity of posting an action to conventional function invocations extends even further. *HPX* implements `hpx::bind` and `hpx::function` two facilities which are semantically equivalent to the `std::bind` and `std::function` types as defined by the C++11 Standard. While `hpx::async` extends beyond the conventional semantics by supporting actions and conventional C++ functions, the *HPX* facilities `hpx::bind` and `hpx::function` extend beyond the conventional standard facilities too. The *HPX* facilities not only support conventional functions, but can be used for actions as well.

Additionally, *HPX* exposes `hpx::post` and `hpx::async_continue` both of which refine and extend the standard C++ facilities.

The different ways to invoke a function in *HPX* will be explained in more detail in the following sections.

Posting an action asynchronously without any synchronization

This method ('fire and forget') will make sure the function associated with the action is scheduled to run on the target *locality*. Posting the action does not wait for the function to start running, instead it is a fully asynchronous operation. The following example shows how to **post** the action as defined in the previous section on the local *locality* (the *locality* this code runs on):

```
some_global_action act;    // define an instance of some_global_action
hpx::post(act, hpx::find_here(), 2.0);
```

(the function `hpx::find_here()` returns the id of the local *locality*, i.e. the *locality* this code executes on).

Any component member function can be invoked using the same syntactic construct. Given that `id` is the global address for a component instance created earlier, this invocation looks like:

```
some_component_action act;    // define an instance of some_component_action
hpx::post(act, id, "42");
```

In this case any value returned from this action (e.g. in this case the integer 42 is ignored. Please look at *Action type definition* for the code defining the component action `some_component_action` used.

Posting an action asynchronously with synchronization

This method will make sure the action is scheduled to run on the target *locality*. Posting the action itself does not wait for the function to start running or to complete, instead this is a fully asynchronous operation similar to using `hpx::post` as described above. The difference is that this method will return an instance of a `hpx::future<>` encapsulating the result of the (possibly remote) execution. The future can be used to synchronize with the asynchronous operation. The following example shows how to post the action from above on the local *locality*:

```
some_global_action act;    // define an instance of some_global_action
hpx::future<void> f = hpx::async(act, hpx::find_here(), 2.0);
//
// ... other code can be executed here
//
f.get();    // this will possibly wait for the asynchronous operation to 'return'
```

(as before, the function `hpx::find_here()` returns the id of the local *locality* (the *locality* this code is executed on).

Note: The use of a `hpx::future<void>` allows the current thread to synchronize with any remote operation not returning any value.

Note: Any `std::future<>` returned from `std::async()` is required to block in its destructor if the value has not been set for this future yet. This is not true for `hpx::future<>` which will never block in its destructor, even if the value has not been returned to the future yet. We believe that consistency in the behavior of futures is more important than standards conformance in this case.

Any component member function can be invoked using the same syntactic construct. Given that `id` is the global address for a component instance created earlier, this invocation looks like:

```
some_component_action act;    // define an instance of some_component_action
hpx::future<int> f = hpx::async(act, id, "42");
//
// ... other code can be executed here
//
cout << f.get();    // this will possibly wait for the asynchronous operation to 'return'
↪ 42
```

Note: The invocation of `f.get()` will return the result immediately (without suspending the calling thread) if the result from the asynchronous operation has already been returned. Otherwise, the invocation of `f.get()` will suspend the execution of the calling thread until the asynchronous operation returns its result.

Posting an action synchronously

This method will schedule the function wrapped in the specified action on the target *locality*. While the invocation appears to be synchronous (as we will see), the calling thread will be suspended while waiting for the function to return. Invoking a plain action (e.g. a global function) synchronously is straightforward:

```
some_global_action act;    // define an instance of some_global_action
act(hpx::find_here(), 2.0);
```

While this call looks just like a normal synchronous function invocation, the function wrapped by the action will be scheduled to run on a new thread and the calling thread will be suspended. After the new thread has executed the wrapped global function, the waiting thread will resume and return from the synchronous call.

Equivalently, any action wrapping a component member function can be invoked synchronously as follows:

```
some_component_action act;    // define an instance of some_component_action
int result = act(id, "42");
```

The action invocation will either schedule a new thread locally to execute the wrapped member function (as before, `id` is the global address of the component instance the member function should be invoked on), or it will send a parcel to the remote *locality* of the component causing a new thread to be scheduled there. The calling thread will be suspended until the function returns its result. This result will be returned from the synchronous action invocation.

It is very important to understand that this ‘synchronous’ invocation syntax in fact conceals an asynchronous function call. This is beneficial as the calling thread is suspended while waiting for the outcome of a potentially remote operation. The *HPX* thread scheduler will schedule other work in the meantime, allowing the application to make further progress while the remote result is computed. This helps overlapping computation with communication and hiding communication latencies.

Note: The syntax of posting an action is always the same, regardless whether the target *locality* is remote to the invocation *locality* or not. This is a very important feature of *HPX* as it frees the user from the task of keeping track what actions have to be applied locally and which actions are remote. If the target for posting an action is local, a new thread is automatically created and scheduled. Once this thread is scheduled and run, it will execute the function encapsulated by that action. If the target is remote, *HPX* will send a parcel to the remote *locality* which encapsulates the action and its parameters. Once the parcel is received on the remote *locality* *HPX* will create and schedule a new thread there. Once this thread runs on the remote *locality*, it will execute the function encapsulated by the action.

Posting an action with a continuation but without any synchronization

This method is very similar to the method described in section *Posting an action asynchronously without any synchronization*. The difference is that it allows the user to chain a sequence of asynchronous operations, while handing the (intermediate) results from one step to the next step in the chain. Where `hpx::post` invokes a single function using ‘fire and forget’ semantics, `hpx::post_continue` asynchronously triggers a chain of functions without the need for the execution flow ‘to come back’ to the invocation site. Each of the asynchronous functions can be executed on a different *locality*.

Posting an action with a continuation and with synchronization

This method is very similar to the method described in section *Posting an action asynchronously with synchronization*. In addition to what `hpx::async` can do, the functions `hpx::async_continue` takes an additional function argument. This function will be called as the continuation of the executed action. It is expected to perform additional operations and to make sure that a result is returned to the original invocation site. This method chains operations asynchronously by providing a continuation operation which is automatically executed once the first action has finished executing.

As an example we chain two actions, where the result of the first action is forwarded to the second action and the result of the second action is sent back to the original invocation site:

```
// first action
std::int32_t action1(std::int32_t i)
{
    return i+1;
}
HPX_PLAIN_ACTION(action1);    // defines action1_type

// second action
std::int32_t action2(std::int32_t i)
{
    return i*2;
}
HPX_PLAIN_ACTION(action2);    // defines action2_type

// this code invokes 'action1' above and passes along a continuation
// function which will forward the result returned from 'action1' to
// 'action2'.
action1_type act1;           // define an instance of 'action1_type'
action2_type act2;           // define an instance of 'action2_type'
hpx::future<int> f =
    hpx::async_continue(act1, hpx::make_continuation(act2),
        hpx::find_here(), 42);
hpx::cout << f.get() << "\n";    // will print: 86 ((42 + 1) * 2)
```

By default, the continuation is executed on the same *locality* as `hpx::async_continue` is invoked from. If you want to specify the *locality* where the continuation should be executed, the code above has to be written as:

```
// this code invokes 'action1' above and passes along a continuation
// function which will forward the result returned from 'action1' to
// 'action2'.
action1_type act1;           // define an instance of 'action1_type'
action2_type act2;           // define an instance of 'action2_type'
hpx::future<int> f =
    hpx::async_continue(act1, hpx::make_continuation(act2, hpx::find_here()),
        hpx::find_here(), 42);
hpx::cout << f.get() << "\n";    // will print: 86 ((42 + 1) * 2)
```

Similarly, it is possible to chain more than 2 operations:

```
action1_type act1;           // define an instance of 'action1_type'
action2_type act2;           // define an instance of 'action2_type'
hpx::future<int> f =
    hpx::async_continue(act1,
```

(continues on next page)

(continued from previous page)

```

    hpx::make_continuation(act2, hpx::make_continuation(act1)),
    hpx::find_here(), 42);
hpx::cout << f.get() << "\n";    // will print: 87 ((42 + 1) * 2 + 1)

```

The function `hpx::make_continuation` creates a special function object which exposes the following prototype:

```

struct continuation
{
    template <typename Result>
    void operator()(hpx::id_type id, Result&& result) const
    {
        ...
    }
};

```

where the parameters passed to the overloaded function operator `operator()()` are:

- the `id` is the global id where the final result of the asynchronous chain of operations should be sent to (in most cases this is the id of the `hpx::future` returned from the initial call to `hpx::async_continue`. Any custom continuation function should make sure this `id` is forwarded to the last operation in the chain.
- the `result` is the result value of the current operation in the asynchronous execution chain. This value needs to be forwarded to the next operation.

Note: All of those operations are implemented by the predefined continuation function object which is returned from `hpx::make_continuation`. Any (custom) function object used as a continuation should conform to the same interface.

Action error handling

Like in any other asynchronous invocation scheme it is important to be able to handle error conditions occurring while the asynchronous (and possibly remote) operation is executed. In *HPX* all error handling is based on standard C++ exception handling. Any exception thrown during the execution of an asynchronous operation will be transferred back to the original invocation *locality*, where it is rethrown during synchronization with the calling thread.

Important: Exceptions thrown during asynchronous execution can be transferred back to the invoking thread only for the synchronous and the asynchronous case with synchronization. Like with any other unhandled exception, any exception thrown during the execution of an asynchronous action *without* synchronization will result in calling `hpx::terminate` causing the running application to exit immediately.

Note: Even if error handling internally relies on exceptions, most of the API functions exposed by *HPX* can be used without throwing an exception. Please see *Working with exceptions* for more information.

As an example, we will assume that the following remote function will be executed:

```

namespace app
{
    void some_function_with_error(int arg)

```

(continues on next page)

(continued from previous page)

```

{
    if (arg < 0) {
        HPX_THROW_EXCEPTION(hpx::error::bad_parameter,
            "some_function_with_error",
            "some really bad error happened");
    }
    // do something else...
}
}

// This will define the action type 'some_error_action' which represents
// the function 'app::some_function_with_error'.
HPX_PLAIN_ACTION(app::some_function_with_error, some_error_action);

```

The use of `HPX_THROW_EXCEPTION` to report the error encapsulates the creation of a `hpx::exception` which is initialized with the error code `hpx::error::bad_parameter`. Additionally it carries the passed strings, the information about the file name, line number, and call stack of the point the exception was thrown from.

We invoke this action using the synchronous syntax as described before:

```

// note: wrapped function will throw hpx::exception
some_error_action act;           // define an instance of some_error_action
try {
    act(hpx::find_here(), -3);    // exception will be rethrown from here
}
catch (hpx::exception const& e) {
    // prints: 'some really bad error happened: HPX(bad parameter)'
    cout << e.what();
}

```

If this action is invoked asynchronously with synchronization, the exception is propagated to the waiting thread as well and is re-thrown from the future's function `get()`:

```

// note: wrapped function will throw hpx::exception
some_error_action act;           // define an instance of some_error_action
hpx::future<void> f = hpx::async(act, hpx::find_here(), -3);
try {
    f.get();                     // exception will be rethrown from here
}
catch (hpx::exception const& e) {
    // prints: 'some really bad error happened: HPX(bad parameter)'
    cout << e.what();
}

```

For more information about error handling please refer to the section *Working with exceptions*. There we also explain how to handle error conditions without having to rely on exception.

Writing components

A component in *HPX* is a C++ class which can be created remotely and for which its member functions can be invoked remotely as well. The following sections highlight how components can be defined, created, and used.

Defining components

In order for a C++ class type to be managed remotely in *HPX*, the type must be derived from the `hpx::components::component_base` template type. We call such C++ class types 'components'.

Note that the component type itself is passed as a template argument to the base class:

```
// header file some_component.hpp

#include <hpx/include/components.hpp>

namespace app
{
    // Define a new component type 'some_component'
    struct some_component
        : hpx::components::component_base<some_component>
    {
        // This member function is has to be invoked remotely
        int some_member_function(std::string const& s)
        {
            return std::stoi(s);
        }

        // This will define the action type 'some_member_action' which
        // represents the member function 'some_member_function' of the
        // object type 'some_component'.
        HPX_DEFINE_COMPONENT_ACTION(some_component, some_member_function, some_member_
        ↪action);
    };
}

// This will generate the necessary boiler-plate code for the action allowing
// it to be invoked remotely. This declaration macro has to be placed in the
// header file defining the component itself.
//
// Note: The second argument to the macro below has to be systemwide-unique
//       C++ identifiers
//
HPX_REGISTER_ACTION_DECLARATION(app::some_component::some_member_action, some_component_
↪some_action);
```

There is more boiler plate code which has to be placed into a source file in order for the component to be usable. Every component type is required to have macros placed into its source file, one for each component type and one macro for each of the actions defined by the component type.

For instance:

```
// source file some_component.cpp
```

(continues on next page)

(continued from previous page)

```
#include "some_component.hpp"

// The following code generates all necessary boiler plate to enable the
// remote creation of 'app::some_component' instances with 'hpx::new_<>()'
//
using some_component = app::some_component;
using some_component_type = hpx::components::component<some_component>;

// Please note that the second argument to this macro must be a
// (system-wide) unique C++-style identifier (without any namespaces)
//
HPX_REGISTER_COMPONENT(some_component_type, some_component);
```

Note: When C++26 reflection is enabled (HPX_WITH_CXX26_REFLECTION=ON), the second argument to `HPX_REGISTER_COMPONENT` can be omitted. The component name is then derived automatically from the server type via `std::meta::identifier_of`:

```
// With C++26 reflection -- single argument, name derived automatically
HPX_REGISTER_COMPONENT(some_component_type)
```

The derived name is fully qualified (includes enclosing namespaces) and is equivalent to the explicit two-argument form. Explicit names always take precedence over reflection-derived ones.

```
// The parameters for this macro have to be the same as used in the corresponding //
HPX_REGISTER_ACTION_DECLARATION() macro invocation in the corresponding // header file. //
// Please note that the second argument to this macro must be a // (system-wide) unique C++-style identifier
// (without any namespaces) // HPX_REGISTER_ACTION(app::some_component::some_member_action,
some_component_some_action);
```

Defining client side representation classes

Often it is very convenient to define a separate type for a component which can be used on the client side (from where the component is instantiated and used). This step might seem as unnecessary duplicating code, however it significantly increases the type safety of the code.

A possible implementation of such a client side representation for the component described in the previous section could look like:

```
#include <hpx/include/components.hpp>

namespace app
{
    // Define a client side representation type for the component type
    // 'some_component' defined in the previous section.
    //
    struct some_component_client
    : hpx::components::client_base<some_component_client, some_component>
    {
        using base_type = hpx::components::client_base<
            some_component_client, some_component>;
    };
}
```

(continues on next page)

(continued from previous page)

```

    some_component_client(hpx::future<hpx::id_type> && id)
        : base_type(std::move(id))
    {}

    hpx::future<int> some_member_function(std::string const& s)
    {
        some_component::some_member_action act;
        return hpx::async(act, get_id(), s);
    }
};
}

```

A client side object stores the global id of the component instance it represents. This global id is accessible by calling the function `client_base<>::get_id()`. The special constructor which is provided in the example allows to create this client side object directly using the API function `hpx::new_`.

Creating component instances

Instances of defined component types can be created in two different ways. If the component to create has a defined client side representation type, then this can be used, otherwise use the server type.

The following examples assume that `some_component_type` is the type of the server side implementation of the component to create. All additional arguments (see , ... notation below) are passed through to the corresponding constructor calls of those objects:

```

// create one instance on the given locality
hpx::id_type here = hpx::find_here();
hpx::future<hpx::id_type> f =
    hpx::new_<some_component_type>(here, ...);

// create one instance using the given distribution
// policy (here: hpx::colocating_distribution_policy)
hpx::id_type here = hpx::find_here();
hpx::future<hpx::id_type> f =
    hpx::new_<some_component_type>(hpx::colocated(here), ...);

// create multiple instances on the given locality
hpx::id_type here = find_here();
hpx::future<std::vector<hpx::id_type>> f =
    hpx::new_<some_component_type[]>(here, num, ...);

// create multiple instances using the given distribution
// policy (here: hpx::binpacking_distribution_policy)
hpx::future<std::vector<hpx::id_type>> f = hpx::new_<some_component_type[]>(
    hpx::binpacking(hpx::find_all_localities()), num, ...);

```

The examples below demonstrate the use of the same API functions for creating client side representation objects (instead of just plain ids). These examples assume that `client_type` is the type of the client side representation of the component type to create. As above, all additional arguments (see , ... notation below) are passed through to the corresponding constructor calls of the server side implementation objects corresponding to the `client_type`:

```
// create one instance on the given locality
hpx::id_type here = hpx::find_here();
client_type c = hpx::new_<client_type>(here, ...);

// create one instance using the given distribution
// policy (here: hpx::colocating_distribution_policy)
hpx::id_type here = hpx::find_here();
client_type c = hpx::new_<client_type>(hpx::colocated(here), ...);

// create multiple instances on the given locality
hpx::id_type here = hpx::find_here();
hpx::future<std::vector<client_type>> f =
    hpx::new_<client_type[]>(here, num, ...);

// create multiple instances using the given distribution
// policy (here: hpx::binpacking_distribution_policy)
hpx::future<std::vector<client_type>> f = hpx::new_<client_type[]>(
    hpx::binpacking(hpx::find_all_localities()), num, ...);
```

Using component instances

After having created the component instances as described above, we can simply use them as indicated below:

```
#include <hpx/include/components.hpp>
#include <iostream>
#include <vector>

// Define a simple component
struct some_component : hpx::components::component_base<some_component>
{
    void print() const
    {
        std::cout << "Hello from component instance!" << std::endl;
    }
    HPX_DEFINE_COMPONENT_ACTION(some_component, print, print_action);
};

typedef some_component::print_action print_action;

// Create one instance on the given locality
hpx::id_type here = hpx::find_here();
hpx::future<hpx::id_type> f1 =
    hpx::new_<some_component>(here);

// Get the future value
hpx::id_type instance_id = f1.get();

// Invoke action on the instance
hpx::async<print_action>(instance_id).get();

// Create multiple instances on the given locality
```

(continues on next page)

(continued from previous page)

```

int num = 3;
hpx::future<std::vector<hpx::id_type>> f2 =
    hpx::new_<some_component[]>(here, num);

// Get the future value
std::vector<hpx::id_type> instance_ids = f2.get();

// Invoke action on each instance
for (const auto& id : instance_ids)
{
    hpx::async<print_action>(id).get();
}

```

We can use the component instances with distribution policies the same way.

Segmented containers

In parallel programming, there is now a plethora of solutions aimed at implementing “partially contiguous” or segmented data structures, whether on shared memory systems or distributed memory systems. *HPX* implements such structures by drawing inspiration from Standard C++ containers.

Using segmented containers

A segmented container is a template class that is described in the namespace `hpx`. All segmented containers are very similar semantically to their sequential counterpart (defined in namespace `std` but with an additional template parameter named `DistPolicy`). The distribution policy is an optional parameter that is passed last to the segmented container constructor (after the container size when no default value is given, after the default value if not). The distribution policy describes the manner in which a container is segmented and the placement of each segment among the available runtime localities.

However, only a part of the `std` container member functions were reimplemented:

- (constructor), (destructor), `operator=`
- `operator[]`
- `begin`, `cbegin`, `end`, `cend`
- `size`

An example of how to use the `partitioned_vector` container would be:

```

#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

// By default, the number of segments is equal to the current number of
// localities
//
hpx::partitioned_vector<double> va(50);
hpx::partitioned_vector<double> vb(50, 0.0);

```

An example of how to use the `partitioned_vector` container with distribution policies would be:

```
#include <hpx/include/partitioned_vector.hpp>
#include <hpx/modules/runtime_distributed.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

std::size_t num_segments = 10;
std::vector<hpx::id_type> locs = hpx::find_all_localities();

auto layout =
    hpx::container_layout( num_segments, locs );

// The number of segments is 10 and those segments are spread across the
// localities collected in the variable locs in a Round-Robin manner
//
hpx::partitioned_vector<double> va(50, layout);
hpx::partitioned_vector<double> vb(50, 0.0, layout);
```

By definition, a segmented container must be accessible from any thread although its construction is synchronous only for the thread who has called its constructor. To overcome this problem, it is possible to assign a symbolic name to the segmented container:

```
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

hpx::future<void> fserver = hpx::async(
    [](){
        hpx::partitioned_vector<double> v(50);

        // Register the 'partitioned_vector' with the name "some_name"
        //
        v.register_as("some_name");

        /* Do some code */
    });

hpx::future<void> fclient =
    hpx::async(
        [](){
            // Naked 'partitioned_vector'
            //
            hpx::partitioned_vector<double> v;

            // Now the variable v points to the same 'partitioned_vector' that has
            // been registered with the name "some_name"
            //
```

(continues on next page)

(continued from previous page)

```
v.connect_to("some_name");

/* Do some code */
});
```

Segmented containers

HPX provides the following segmented containers:

Table 2.23: Sequence containers

Name	Description	In header	C++ standard
<code>hpx::partitioned_vector</code>	Dynamic segmented contiguous array.	<code><hpx/include/partitioned_vector.hpp></code>	<code>vector</code> ¹⁷⁶

Table 2.24: Unordered associative containers

Name	Description	In header	C++ standard
<code>hpx::unordered_map</code>	Segmented collection of key-value pairs, hashed by keys, keys are unique.	<code><hpx/include/unordered_map.hpp></code>	<code>unordered_map</code> ¹⁷⁷

Segmented iterators and segmented iterator traits

The basic iterator used in the STL library is only suitable for one-dimensional structures. The iterators we use in HPX must adapt to the segmented format of our containers. Our iterators are then able to know when incrementing themselves if the next element of type T is in the same data segment or in another segment. In this second case, the iterator will automatically point to the beginning of the next segment.

Note: Note that the dereference operation `operator *` does not directly return a reference of type T& but an intermediate object wrapping this reference. When this object is used as an l-value, a remote write operation is performed; When this object is used as an r-value, implicit conversion to T type will take care of performing remote read operation.

It is sometimes useful not only to iterate element by element, but also segment by segment, or simply get a local iterator in order to avoid additional construction costs at each dereferencing operations. To mitigate this need, the `hpx::traits::segmented_iterator_traits` are used.

With `segmented_iterator_traits` users can uniformly get the iterators which specifically iterates over segments (by providing a segmented iterator as a parameter), or get the local begin/end iterators of the nearest local segment (by providing a per-segment iterator as a parameter):

```
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
```

(continues on next page)

¹⁷⁶ <http://en.cppreference.com/w/cpp/container/vector>

¹⁷⁷ http://en.cppreference.com/w/cpp/container/unordered_map

(continued from previous page)

```

//
HPX_REGISTER_PARTITIONED_VECTOR(double);

using iterator = hpx::partitioned_vector<T>::iterator;
using traits    = hpx::traits::segmented_iterator_traits<iterator>;

hpx::partitioned_vector<T> v;
std::size_t count = 0;

auto seg_begin = traits::segment(v.begin());
auto seg_end   = traits::segment(v.end());

// Iterate over segments
for (auto seg_it = seg_begin; seg_it != seg_end; ++seg_it)
{
    auto loc_begin = traits::begin(seg_it);
    auto loc_end   = traits::end(seg_it);

    // Iterate over elements inside segments
    for (auto lit = loc_begin; lit != loc_end; ++lit, ++count)
    {
        *lit = count;
    }
}

```

Which is equivalent to:

```

hpx::partitioned_vector<T> v;
std::size_t count = 0;

auto begin = v.begin();
auto end   = v.end();

for (auto it = begin; it != end; ++it, ++count)
{
    *it = count;
}

```

Using views

The use of multidimensional arrays is quite common in the numerical field whether to perform dense matrix operations or to process images. It exist many libraries which implement such object classes overloading their basic operators (e.g. +, -, *, (), etc.). However, such operation becomes more delicate when the underlying data layout is segmented or when it is mandatory to use optimized linear algebra subroutines (i.e. BLAS subroutines).

Our solution is thus to relax the level of abstraction by allowing the user to work not directly on n-dimensionnal data, but on “n-dimensionnal collections of 1-D arrays”. The use of well-accepted techniques on contiguous data is thus preserved at the segment level, and the composability of the segments is made possible thanks to multidimensional array-inspired access mode.

Preface: Why SPMD?

Although *HPX* refutes by design this programming model, the *locality* plays a dominant role when it comes to implement vectorized code. To maximize local computations and avoid unneeded data transfers, a parallel section (or Single Programming Multiple Data section) is required. Because the use of global variables is prohibited, this parallel section is created via the RAII idiom.

To define a parallel section, simply write an action taking a `spmd_block` variable as a first parameter:

```
#include <hpx/modules/collectives.hpp>

void bulk_function(hpx::lcos::spmd_block block /* , arg0, arg1, ... */)
{
    // Parallel section

    /* Do some code */
}
HPX_PLAIN_ACTION(bulk_function, bulk_action);
```

Note: In the following paragraphs, we will use the term “image” several times. An image is defined as a lightweight process whose entry point is a function provided by the user. It’s an “image of the function”.

The `spmd_block` class contains the following methods:

- Team information: `get_num_images`, `this_image`, `images_per_locality`
- Control statements: `sync_all`, `sync_images`

Here is a sample code summarizing the features offered by the `spmd_block` class:

```
#include <hpx/modules/collectives.hpp>

void bulk_function(hpx::lcos::spmd_block block /* , arg0, arg1, ... */)
{
    std::size_t num_images = block.get_num_images();
    std::size_t this_image = block.this_image();
    std::size_t images_per_locality = block.images_per_locality();

    /* Do some code */

    // Synchronize all images in the team
    block.sync_all();

    /* Do some code */

    // Synchronize image 0 and image 1
    block.sync_images(0,1);

    /* Do some code */

    std::vector<std::size_t> vec_images = {2,3,4};

    // Synchronize images 2, 3 and 4
    block.sync_images(vec_images);
}
```

(continues on next page)

(continued from previous page)

```

// Alternative call to synchronize images 2, 3 and 4
block.sync_images(vec_images.begin(), vec_images.end());

/* Do some code */

// Non-blocking version of sync_all()
hpx::future<void> event =
    block.sync_all(hpx::launch::async);

// Callback waiting for 'event' to be ready before being scheduled
hpx::future<void> cb =
    event.then(
        [](hpx::future<void>)
        {

            /* Do some code */

        });

// Finally wait for the execution tree to be finished
cb.get();
}
HPX_PLAIN_ACTION(bulk_test_function, bulk_test_action);

```

Then, in order to invoke the parallel section, call the function `define_spmd_block` specifying an arbitrary symbolic name and indicating the number of images per *locality* to create:

```

void bulk_function(hpx::lcos::spmd_block block, /* , arg0, arg1, ... */)
{
}
HPX_PLAIN_ACTION(bulk_test_function, bulk_test_action);

int main()
{
    /* std::size_t arg0, arg1, ...; */

    bulk_action act;
    std::size_t images_per_locality = 4;

    // Instantiate the parallel section
    hpx::lcos::define_spmd_block(
        "some_name", images_per_locality, std::move(act) /*, arg0, arg1, ... */);

    return 0;
}

```

Note: In principle, the user should never call the `spmd_block` constructor. The `define_spmd_block` function is responsible of instantiating `spmd_block` objects and broadcasting them to each created image.

SPMD multidimensional views

Some classes are defined as “container views” when the purpose is to observe and/or modify the values of a container using another perspective than the one that characterizes the container. For example, the values of an `std::vector` object can be accessed via the expression `[i]`. Container views can be used, for example, when it is desired for those values to be “viewed” as a 2D matrix that would have been flattened in a `std::vector`. The values would be possibly accessible via the expression `vv(i, j)` which would call internally the expression `v[k]`.

By default, the `partitioned_vector` class integrates 1-D views of its segments:

```
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

using iterator = hpx::partitioned_vector<double>::iterator;
using traits    = hpx::traits::segmented_iterator_traits<iterator>;

hpx::partitioned_vector<double> v;

// Create a 1-D view of the vector of segments
auto vv = traits::segment(v.begin());

// Access segment i
std::vector<double> v = vv[i];
```

Our views are called “multidimensional” in the sense that they generalize to N dimensions the purpose of `segmented_iterator_traits::segment()` in the 1-D case. Note that in a parallel section, the 2-D expression `a(i, j) = b(i, j)` is quite confusing because without convention, each of the images invoked will race to execute the statement. For this reason, our views are not only multidimensional but also “spmd-aware”.

Note: SPMD-awareness: The convention is simple. If an assignment statement contains a view subscript as an l-value, it is only and only the image holding the r-value who is evaluating the statement. (In MPI sense, it is called a Put operation).

Subscript-based operations

Here are some examples of using subscripts in the 2-D view case:

```
#include <hpx/components/containers/partitioned_vector/partitioned_vector_view.hpp>
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(double);

using Vec = hpx::partitioned_vector<double>;
using View_2D = hpx::partitioned_vector_view<double, 2>;
```

(continues on next page)

(continued from previous page)

```

/* Do some code */

Vec v;

// Parallel section (suppose 'block' an spmd_block instance)
{
    std::size_t height, width;

    // Instantiate the view
    View_2D vv(block, v.begin(), v.end(), {height,width});

    // The l-value is a view subscript, the image that owns vv(1,0)
    // evaluates the assignment.
    vv(0,1) = vv(1,0);

    // The l-value is a view subscript, the image that owns the r-value
    // (result of expression 'std::vector<double>(4,1.0)') evaluates the
    // assignment : oops! race between all participating images.
    vv(2,3) = std::vector<double>(4,1.0);
}

```

Iterator-based operations

Here are some examples of using iterators in the 3-D view case:

```

#include <hpx/components/containers/partitioned_vector/partitioned_vector_view.hpp>
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(int);

using Vec = hpx::partitioned_vector<int>;
using View_3D = hpx::partitioned_vector_view<int,3>;

/* Do some code */

Vec v1, v2;

// Parallel section (suppose 'block' an spmd_block instance)
{
    std::size_t size_x, size_y, size_z;

    // Instantiate the views
    View_3D vv1(block, v1.begin(), v1.end(), {size_x,size_y,size_z});
    View_3D vv2(block, v2.begin(), v2.end(), {size_x,size_y,size_z});

    // Save previous segments covered by vv1 into segments covered by vv2
    auto vv2_it = vv2.begin();

```

(continues on next page)

(continued from previous page)

```

auto vv1_it = vv1.cbegin();

for(; vv2_it != vv2.end(); vv2_it++, vv1_it++)
{
    // It's a Put operation
    *vv2_it = *vv1_it;
}

// Ensure that all images have performed their Put operations
block.sync_all();

// Ensure that only one image is putting updated data into the different
// segments covered by vv1
if(block.this_image() == 0)
{
    int idx = 0;

    // Update all the segments covered by vv1
    for(auto i = vv1.begin(); i != vv1.end(); i++)
    {
        // It's a Put operation
        *i = std::vector<float>(elt_size,idx++);
    }
}
}

```

Here is an example that shows how to iterate only over segments owned by the current image:

```

#include <hpx/components/containers/partitioned_vector/partitioned_vector_view.hpp>
#include <hpx/components/containers/partitioned_vector/partitioned_vector_local_view.hpp>
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(float);

using Vec = hpx::partitioned_vector<float>;
using View_1D = hpx::partitioned_vector_view<float,1>;

/* Do some code */

Vec v;

// Parallel section (suppose 'block' an spmd_block instance)
{
    std::size_t num_segments;

    // Instantiate the view
    View_1D vv(block, v.begin(), v.end(), {num_segments});

    // Instantiate the local view from the view

```

(continues on next page)

(continued from previous page)

```

    auto local_vv = hpx::local_view(vv);

    for ( auto i = local_vv.begin(); i != local_vv.end(); i++ )
    {
        std::vector<float> & segment = *i;

        /* Do some code */
    }
}

```

Instantiating sub-views

It is possible to construct views from other views: we call it sub-views. The constraint nevertheless for the subviews is to retain the dimension and the value type of the input view. Here is an example showing how to create a sub-view:

```

#include <hpx/components/containers/partitioned_vector/partitioned_vector_view.hpp>
#include <hpx/include/partitioned_vector.hpp>

// The following code generates all necessary boiler plate to enable the
// remote creation of 'partitioned_vector' segments
//
HPX_REGISTER_PARTITIONED_VECTOR(float);

using Vec = hpx::partitioned_vector<float>;
using View_2D = hpx::partitioned_vector_view<float,2>;

/* Do some code */

Vec v;

// Parallel section (suppose 'block' an spmd_block instance)
{
    std::size_t N = 20;
    std::size_t tileSize = 5;

    // Instantiate the view
    View_2D vv(block, v.begin(), v.end(), {N,N});

    // Instantiate the subview
    View_2D svv(
        block,&vv(tileSize,0),&vv(2*tileSize-1,tileSize-1),{tileSize,tileSize},{N,N});

    if(block.this_image() == 0)
    {
        // Equivalent to 'vv(tileSize,0) = 2.0f'
        svv(0,0) = 2.0f;

        // Equivalent to 'vv(2*tileSize-1,tileSize-1) = 3.0f'
        svv(tileSize-1,tileSize-1) = 3.0f;
    }
}

```

(continues on next page)

(continued from previous page)

}

Note: The last parameter of the subview constructor is the size of the original view. If one would like to create a subview of the subview and so on, this parameter should stay unchanged. {N,N} for the above example).

C++ co-arrays

Fortran has extended its scalar element indexing approach to reference each segment of a distributed array. In this extension, a segment is attributed a ?co-index? and lives in a specific *locality*. A co-index provides the application with enough information to retrieve the corresponding data reference. In C++, containers present themselves as a ?smarter? alternative of Fortran arrays but there are still no corresponding standardized features similar to the Fortran co-indexing approach. We present here an implementation of such features in *HPX*.

Preface: co-array, a segmented container tied to a SPMD multidimensional views

As mentioned before, a co-array is a distributed array whose segments are accessible through an array-inspired access mode. We have previously seen that it is possible to reproduce such access mode using the concept of views. Nevertheless, the user must pre-create a segmented container to instantiate this view. We illustrate below how a single constructor call can perform those two operations:

```
#include <hpx/components/containers/coarray/coarray.hpp>
#include <hpx/modules/collectives.hpp>

// The following code generates all necessary boiler plate to enable the
// co-creation of 'coarray'
//
HPX_REGISTER_COARRAY(double);

// Parallel section (suppose 'block' an spmd_block instance)
{
    using hpx::container::placeholders::_;

    std::size_t height=32, width=4, segment_size=10;

    hpx::coarray<double,3> a(block, "a", {height,width,_}, segment_size);

    /* Do some code */
}
```

Unlike segmented containers, a co-array object can only be instantiated within a parallel section. Here is the description of the parameters to provide to the coarray constructor:

Table 2.25: Parameters of coarray constructor

Parameter	Description
<code>block</code>	Reference to a <code>spmd_block</code> object
<code>"a"</code>	Symbolic name of type <code>std::string</code>
<code>{height,width, _}</code>	Dimensions of the coarray object
<code>segment_size</code>	Size of a co-indexed element (i.e. size of the object referenced by the expression <code>a(i,j,k)</code>)

Note that the “last dimension size” cannot be set by the user. It only accepts the constexpr variable `hpx::container::placeholders::_`. This size, which is considered private, is equal to the number of current images (value returned by `block.get_num_images()`).

Note: An important constraint to remember about coarray objects is that all segments sharing the same “last dimension index” are located in the same image.

Using co-arrays

The member functions owned by the coarray objects are exactly the same as those of `spmd` multidimensional views. These are:

- * Subscript-based operations
- * Iterator-based operations

However, one additional functionality is provided. Knowing that the element `a(i,j,k)` is in the memory of the `k`th image, the use of local subscripts is possible.

Note: For `spmd` multidimensional views, subscripts are only global as it still involves potential remote data transfers.

Here is an example of using local subscripts:

```
#include <hpx/components/containers/coarray/coarray.hpp>
#include <hpx/modules/collectives.hpp>

// The following code generates all necessary boiler plate to enable the
// co-creation of 'coarray'
//
HPX_REGISTER_COARRAY(double);

// Parallel section (suppose 'block' an spmd_block instance)
{
    using hpx::container::placeholders::_;

    std::size_t height=32, width=4, segment_size=10;

    hpx::coarray<double,3> a(block, "a", {height,width,_}, segment_size);

    double idx = block.this_image()*height*width;

    for (std::size_t j = 0; j<width; j++)
```

(continues on next page)

(continued from previous page)

```

for (std::size_t i = 0; i<height; i++)
{
    // Local write operation performed via the use of local subscript
    a(i,j,_) = std::vector<double>(elt_size,idx);
    idx++;
}

block.sync_all();
}

```

Note: When the “last dimension index” of a subscript is equal to `hpx::container::placeholders::_`, local subscript (and not global subscript) is used. It is equivalent to a global subscript used with a “last dimension index” equal to the value returned by `block.this_image()`.

2.4.13 Running on batch systems

This section walks you through launching *HPX* applications on various batch systems.

How to use *HPX* applications with PBS

Most *HPX* applications are executed on parallel computers. These platforms typically provide integrated job management services that facilitate the allocation of computing resources for each parallel program. *HPX* includes support for one of the most common job management systems, the Portable Batch System (PBS).

All PBS jobs require a script to specify the resource requirements and other parameters associated with a parallel job. The PBS script is basically a shell script with PBS directives placed within commented sections at the beginning of the file. The remaining (not commented-out) portions of the file executes just like any other regular shell script. While the description of all available PBS options is outside the scope of this tutorial (the interested reader may refer to in-depth [documentation](#)¹⁷⁸ for more information), below is a minimal example to illustrate the approach. The following test application will use the multithreaded `hello_world_distributed` program, explained in the section *Remote execution with actions*.

```

#!/bin/bash
#
#PBS -l nodes=2:ppn=4

APP_PATH=~/.packages/hpx/bin/hello_world_distributed
APP_OPTIONS=

pbsdsh -u $APP_PATH $APP_OPTIONS --hpx:nodes=`cat $PBS_NODEFILE`

```

Caution: If the first application specific argument (inside `$APP_OPTIONS`) is a non-option (i.e., does not start with a `-` or a `--`), then the argument has to be placed before the option `--hpx:nodes`, which, in this case, should be the last option on the command line.

Alternatively, use the option `--hpx:endnodes` to explicitly mark the end of the list of node names:

```
$ pbsdsh -u $APP_PATH --hpx:nodes`cat $PBS_NODEFILE` --hpx:endnodes $APP_OPTIONS
```

¹⁷⁸ <http://www.clusterresources.com/torquedocs21/>

The `#PBS -l nodes=2:ppn=4` directive will cause two compute nodes to be allocated for the application, as specified in the option `nodes`. Each of the nodes will dedicate four cores to the program, as per the option `ppn`, short for “processors per node” (PBS does not distinguish between processors and cores). Note that requesting more cores per node than physically available is pointless and may prevent PBS from accepting the script.

On newer PBS versions the PBS command syntax might be different. For instance, the PBS script above would look like:

```
#!/bin/bash
#
#PBS -l select=2:ncpus=4

APP_PATH=~/packages/hpx/bin/hello_world_distributed
APP_OPTIONS=

pbsdsh -u $APP_PATH $APP_OPTIONS --hpx:nodes=`cat $PBS_NODEFILE`
```

`APP_PATH` and `APP_OPTIONS` are shell variables that respectively specify the correct path to the executable (`hello_world_distributed` in this case) and the command line options. Since the `hello_world_distributed` application doesn’t need any command line options, `APP_OPTIONS` has been left empty. Unlike in other execution environments, there is no need to use the `--hpx:threads` option to indicate the required number of OS threads per node; the *HPX* library will derive this parameter automatically from PBS.

Finally, `pbsdsh` is a PBS command that starts tasks to the resources allocated to the current job. It is recommended to leave this line as shown and modify only the PBS options and shell variables as needed for a specific application.

Important: A script invoked by `pbsdsh` starts in a very basic environment: the user’s `$HOME` directory is defined and is the current directory, the `LANG` variable is set to `C` and the `PATH` is set to the basic `/usr/local/bin:/usr/bin:/bin` as defined in a system-wide file `pbs_environment`. Nothing that would normally be set up by a system shell profile or user shell profile is defined, unlike the environment for the main job script.

Another choice is for the `pbsdsh` command in your main job script to invoke your program via a shell, like `sh` or `bash`, so that it gives an initialized environment for each instance. Users can create a small script `runme.sh`, which is used to invoke the program:

```
#!/bin/bash
# Small script which invokes the program based on what was passed on its
# command line.
#
# This script is executed by the bash shell which will initialize all
# environment variables as usual.
$@
```

Now, the script is invoked using the `pbsdsh` tool:

```
#!/bin/bash
#
#PBS -l nodes=2:ppn=4

APP_PATH=~/packages/hpx/bin/hello_world_distributed
APP_OPTIONS=
```

(continues on next page)

(continued from previous page)

```
pbsdsh -u runme.sh $APP_PATH $APP_OPTIONS --hpx:nodes=`cat $PBS_NODEFILE`
```

All that remains now is submitting the job to the queuing system. Assuming that the contents of the PBS script were saved in the file `pbs_hello_world.sh` in the current directory, this is accomplished by typing:

```
$ qsub ./pbs_hello_world_pbs.sh
```

If the job is accepted, `qsub` will print out the assigned job ID, which may look like:

```
$ 42.supercomputer.some.university.edu
```

To check the status of your job, issue the following command:

```
$ qstat 42.supercomputer.some.university.edu
```

and look for a single-letter job status symbol. The common cases include:

- *Q* - signifies that the job is queued and awaiting its turn to be executed.
- *R* - indicates that the job is currently running.
- *C* - means that the job has completed.

The example `qstat` output below shows a job waiting for execution resources to become available:

Job id	Name	User	Time Use	S	Queue
-----	-----	-----	-----	-----	-----
42.supercomputer	...ello_world.sh	joe_user		0 Q	batch

After the job completes, PBS will place two files, `pbs_hello_world.sh.o42` and `pbs_hello_world.sh.e42`, in the directory where the job was submitted. The first contains the standard output and the second contains the standard error from all the nodes on which the application executed. In our example, the error output file should be empty and the standard output file should contain something similar to:

```
hello world from OS-thread 3 on locality 0
hello world from OS-thread 2 on locality 0
hello world from OS-thread 1 on locality 1
hello world from OS-thread 0 on locality 0
hello world from OS-thread 3 on locality 1
hello world from OS-thread 2 on locality 1
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 1
```

Congratulations! You have just run your first distributed *HPX* application!

How to use *HPX* applications with SLURM

Just like PBS (described in section *How to use HPX applications with PBS*), SLURM is a job management system which is widely used on large supercomputing systems. Any *HPX* application can easily be run using SLURM. This section describes how this can be done.

The easiest way to run an *HPX* application using SLURM is to utilize the command line tool `srun`, which interacts with the SLURM batch scheduling system:

```
$ srun -p <partition> -N <number-of-nodes> hpx-application <application-arguments>
```

Here, `<partition>` is one of the node partitions existing on the target machine (consult the machine's documentation to get a list of existing partitions) and `<number-of-nodes>` is the number of compute nodes that should be used. By default, the *HPX* application is started with one *locality* per node and uses all available cores on a node. You can change the number of localities started per node (for example, to account for NUMA effects) by specifying the `-n` option of `srun`. The number of cores per *locality* can be set by `-c`. The `<application-arguments>` are any application specific arguments that need to be passed on to the application.

Note: There is no need to use any of the *HPX* command line options related to the number of localities, number of threads, or related to networking ports. All of this information is automatically extracted from the SLURM environment by the *HPX* startup code.

Important: The `srun` documentation explicitly states: “If `-c` is specified without `-n`, as many tasks will be allocated per node as possible while satisfying the `-c` restriction. For instance on a cluster with 8 CPUs per node, a job request for 4 nodes and 3 CPUs per task may be allocated 3 or 6 CPUs per node (1 or 2 tasks per node) depending upon resource consumption by other jobs.” For this reason, it's recommended to always specify `-n <number-of-instances>`, even if `<number-of-instances>` is equal to one (1).

Interactive shells

To get an interactive development shell on one of the nodes, users can issue the following command:

```
$ srun -p <node-type> -N <number-of-nodes> --pty /bin/bash -l
```

After the shell has been opened, users can run their *HPX* application. By default, it uses all available cores. Note that if you requested one node, you don't need to do `srun` again. However, if you requested more than one node, and want to run your distributed application, you can use `srun` again to start up the distributed *HPX* application. It will use the resources that have been requested for the interactive shell.

Scheduling batch jobs

The above mentioned method of running *HPX* applications is fine for development purposes. The disadvantage that comes with `srun` is that it only returns once the application is finished. This might not be appropriate for longer-running applications (for example, benchmarks or larger scale simulations). In order to cope with that limitation, users can use the `sbatch` command.

The `sbatch` command expects a script that it can run once the requested resources are available. In order to request resources, users need to add `#SBATCH` comments in their script or provide the necessary parameters to `sbatch` directly. The parameters are the same as with `run`. The commands you need to execute are the same you would need to start your application as if you were in an interactive shell.

2.4.14 Debugging HPX applications

Using a debugger with HPX applications

Using a debugger such as `gdb` with *HPX* applications is no problem. However, there are some things to keep in mind to make the experience somewhat more productive.

Call stacks in *HPX* can often be quite unwieldy as the library is heavily templated and the call stacks can be very deep. For this reason it is sometimes a good idea compile *HPX* in `RelWithDebInfo` mode, which applies some optimizations but keeps debugging symbols. This can often compress call stacks significantly. On the other hand, stepping through the code can also be more difficult because of statements being reordered and variables being optimized away. Also, note that because *HPX* implements user-space threads and context switching, call stacks may not always be complete in a debugger.

HPX launches not only worker threads but also a few helper threads. The first thread is the main thread, which typically does no work in an *HPX* application, except at startup and shutdown. If using the default settings, *HPX* will spawn six additional threads (used for service thread pools). The first worker thread is usually the eighth thread, and most user codes will be run on these worker threads. The last thread is a helper thread used for *HPX* shutdown.

Finally, since *HPX* is a multi-threaded runtime, the following `gdb` options can be helpful:

```
set pagination off
set non-stop on
```

Non-stop mode allows users to have a single thread stop on a breakpoint without stopping all other threads as well.

Using sanitizers with HPX applications

Warning: Not all parts of *HPX* are sanitizer clean. This means that users may end up with false positives from *HPX* itself when using sanitizers for their applications.

To use sanitizers with *HPX*, turn on `HPX_WITH_SANITIZERS` and turn off `HPX_WITH_STACKOVERFLOW_DETECTION` during `CMake`¹⁷⁹ configuration. It's recommended to also build Boost with the same sanitizers that will be used for *HPX*. The appropriate sanitizers can then be enabled using `CMake` by appending `-fsanitize=address` `-fno-omit-frame-pointer` to `CMAKE_CXX_FLAGS` and `-fsanitize=address` to `CMAKE_EXE_LINKER_FLAGS`. Replace `address` with the sanitizer that you want to use.

Debugging applications using core files

For *HPX* to generate useful core files, *HPX* has to be compiled without signal and exception handlers `HPX_WITH_DISABLED_SIGNAL_EXCEPTION_HANDLERS:BOOL`. If this option is not specified, the signal handlers change the application state. For example, after a segmentation fault the stack trace will show the signal handler. Similarly, unhandled exceptions are also caught by these handlers and the stack trace will not point to the location where the unhandled exception was thrown.

In general, core files are a helpful tool to inspect the state of the application at the moment of the crash (post-mortem debugging), without the need of attaching a debugger beforehand. This approach to debugging is especially useful if the error cannot be reliably reproduced, as only a single crashed application run is required to gain potentially helpful information like a stacktrace.

To debug with core files, the operating system first has to be told to actually write them. On most Unix systems this can be done by calling:

¹⁷⁹ <https://www.cmake.org>

```
$ ulimit -c unlimited
```

in the shell. Now the debugger can be started up with:

```
$ gdb <application> <core file name>
```

The debugger should now display the last state of the application. The default file name for core files is `core`.

2.4.15 Optimizing *HPX* applications

Performance counters

Performance counters in *HPX* are used to provide information as to how well the runtime system or an application is performing. The counter data can help determine system bottlenecks, and fine-tune system and application performance. The *HPX* runtime system, its networking, and other layers provide counter data that an application can consume to provide users with information about how well the application is performing.

Applications can also use counter data to determine how much system resources to consume. For example, an application that transfers data over the network could consume counter data from a network switch to determine how much data to transfer without competing for network bandwidth with other network traffic. The application could use the counter data to adjust its transfer rate as the bandwidth usage from other network traffic increases or decreases.

Performance counters are *HPX* parallel processes that expose a predefined interface. *HPX* exposes special API functions that allow one to create, manage, and read the counter data, and release instances of performance counters. Performance Counter instances are accessed by name, and these names have a predefined structure which is described in the section *Performance counter names*. The advantage of this is that any Performance Counter can be accessed remotely (from a different *locality*) or locally (from the same *locality*). Moreover, since all counters expose their data using the same API, any code consuming counter data can be utilized to access arbitrary system information with minimal effort.

Counter data may be accessed in real time. More information about how to consume counter data can be found in the section *Consuming performance counter data*.

All *HPX* applications provide command line options related to performance counters, such as the ability to list available counter types, or periodically query specific counters to be printed to the screen or save them in a file. For more information, please refer to the section *HPX Command Line Options*.

Performance counter names

All Performance Counter instances have a name uniquely identifying each instance. This name can be used to access the counter, retrieve all related meta data, and to query the counter data (as described in the section *Consuming performance counter data*). Counter names are strings with a predefined structure. The general form of a countername is:

```
/objectname{full_instancename}/countername@parameters
```

where `full_instancename` could be either another (full) counter name or a string formatted as:

```
parentinstancename#parentindex/instancename#instanceindex
```

Each separate part of a countername (e.g., `objectname`, `countername` `parentinstancename`, `instancename`, and `parameters`) should start with a letter ('a'... 'z', 'A'... 'Z') or an underscore character ('_'), optionally followed by letters, digits ('0'... '9'), hyphen ('-'), or underscore characters. Whitespace is not allowed inside a counter name. The characters '/', '{', '}', '#', and '@' have a special meaning and are used to delimit the different parts of the counter name.

The parts `parentinstanceindex` and `instanceindex` are integers. If an index is not specified, *HPX* will assume a default of `-1`.

Two counter name examples

This section gives examples of both simple counter names and aggregate counter names. For more information on simple and aggregate counter names, please see *Performance counter instances*.

An example of a well-formed (and meaningful) simple counter name would be:

```
/threads{locality#0/total}/count/cumulative
```

This counter returns the current cumulative number of executed (retired) *HPX* threads for the *locality* `0`. The counter type of this counter is `/threads/count/cumulative` and the full instance name is `locality#0/total`. This counter type does not require an `instanceindex` or `parameters` to be specified.

In this case, the `parentindex` (the `'0'`) designates the *locality* for which the counter instance is created. The counter will return the number of *HPX* threads retired on that particular *locality*.

Another example for a well formed (aggregate) counter name is:

```
/statistics{/threads{locality#0/total}/count/cumulative}/average@500
```

This counter takes the simple counter from the first example, samples its values every `500` milliseconds, and returns the average of the value samples whenever it is queried. The counter type of this counter is `/statistics/average` and the instance name is the full name of the counter for which the values have to be averaged. In this case, the `parameters` (the `'500'`) specify the sampling interval for the averaging to take place (in milliseconds).

Performance counter types

Every performance counter belongs to a specific performance counter type which classifies the counters into groups of common semantics. The type of a counter is identified by the `objectname` and the `countername` parts of the name.

```
/objectname/countername
```

When an application starts *HPX* will register all available counter types on each of the localities. These counter types are held in a special performance counter registration database, which can be used to retrieve the meta data related to a counter type and to create counter instances based on a given counter instance name.

Performance counter instances

The `full_instancename` distinguishes different counter instances of the same counter type. The formatting of the `full_instancename` depends on the counter type. There are two types of counters: simple counters, which usually generate the counter values based on direct measurements, and aggregate counters, which take another counter and transform its values before generating their own counter values. An example for a simple counter is given *above*: counting retired *HPX* threads. An aggregate counter is shown as an example *above* as well: calculating the average of the underlying counter values sampled at constant time intervals.

While simple counters use instance names formatted as `parentinstancename#parentindex/instancename#instanceindex`, most aggregate counters have the full counter name of the embedded counter as their instance name.

Not all simple counter types require specifying all four elements of a full counter instance name; some of the parts (`parentinstancename`, `parentindex`, `instancename`, and `instanceindex`) are optional for specific counters.

Please refer to the documentation of a particular counter for more information about the formatting requirements for the name of this counter (see *Existing HPX performance counters*).

The `parameters` are used to pass additional information to a counter at creation time. They are optional, and they fully depend on the concrete counter. Even if a specific counter type allows additional parameters to be given, those usually are not required as sensible defaults will be chosen. Please refer to the documentation of a particular counter for more information about what parameters are supported, how to specify them, and what default values are assumed (see also *Existing HPX performance counters*).

Every *locality* of an application exposes its own set of performance counter types and performance counter instances. The set of exposed counters is determined dynamically at application start based on the execution environment of the application. For instance, this set is influenced by the current hardware environment for the *locality* (such as whether the *locality* has access to accelerators), and the software environment of the application (such as the number of OS threads used to execute *HPX* threads).

Using wildcards in performance counter names

It is possible to use wildcard characters when specifying performance counter names. Performance counter names can contain two types of wildcard characters:

- Wildcard characters in the performance counter type
- Wildcard characters in the performance counter instance name

A wildcard character has a meaning which is very close to usual file name wildcard matching rules implemented by common shells (like `bash`).

Table 2.26: Wildcard characters in the performance counter type

Wild-card	Description
*	This wildcard character matches any number (zero or more) of arbitrary characters.
?	This wildcard character matches any single arbitrary character.
[...]	This wildcard character matches any single character from the list of specified within the square brackets.

Table 2.27: Wildcard characters in the performance counter instance name

Wild-card	Description
*	This wildcard character matches any <i>locality</i> or any thread, depending on whether it is used for <code>locality#*</code> or <code>worker-thread#*</code> . No other wildcards are allowed in counter instance names.

Consuming performance counter data

You can consume performance data using either the command line interface, the *HPX* application or the *HPX* API. The command line interface is easier to use, but it is less flexible and does not allow one to adjust the behaviour of your application at runtime. The command line interface provides a convenience abstraction but simplified abstraction for querying and logging performance counter data for a set of performance counters.

Consuming performance counter data from the command line

HPX provides a set of predefined command line options for every application that uses `hpx::init` for its initialization. While there are many more command line options available (see *HPX Command Line Options*), the set of options related to performance counters allows one to list existing counters, and query existing counters once at application termination or repeatedly after a constant time interval.

The following table summarizes the available command line options:

Table 2.28: HPX Command Line Options Related to Performance Counters

Command line option	Description
<code>--hpx:print-counter</code>	Prints the specified performance counter either repeatedly and/or at the times specified by <code>--hpx:print-counter-at</code> (see also option <code>--hpx:print-counter-interval</code>).
<code>--hpx:print-counter-reset</code>	Prints the specified performance counter either repeatedly and/or at the times specified by <code>--hpx:print-counter-at</code> . Reset the counter after the value is queried (see also option <code>--hpx:print-counter-interval</code>).
<code>--hpx:print-counter-interval</code>	Prints the performance counter(s) specified with <code>--hpx:print-counter</code> repeatedly after the time interval (specified in milliseconds) (default:0 which means print once at shutdown).
<code>--hpx:print-counter-destination</code>	Prints the performance counter(s) specified with <code>--hpx:print-counter</code> to the given file (default: console).
<code>--hpx:list-counters</code>	List names of all registered performance counters.
<code>--hpx:list-counter-infos</code>	List detailed description of all registered performance counters.
<code>--hpx:print-counter-format</code>	Prints the performance counter(s) specified with <code>--hpx:print-counter</code> . Possible formats in CVS format with header or without any header (see option <code>--hpx:no-csv-header</code>), possible values: <code>csv</code> (prints counter values in CSV format with full names as header) <code>csv-short</code> (prints counter values in CSV format with shortnames provided with <code>--hpx:print-counter</code> as <code>--hpx:print-counter-shortname,full-countername</code>).
<code>--hpx:no-csv-header</code>	Prints the performance counter(s) specified with <code>--hpx:print-counter</code> and <code>csv</code> or <code>csv-short</code> format specified with <code>--hpx:print-counter-format</code> without header.
<code>--hpx:print-counter-at arg</code>	Prints the performance counter(s) specified with <code>--hpx:print-counter</code> (or <code>--hpx:print-counter-reset</code>) at the given point in time. Possible argument values: <code>startup</code> , <code>shutdown</code> (default), <code>noshutdown</code> .
<code>--hpx:reset-counters</code>	Reset the performance counter(s) specified with <code>--hpx:print-counter</code> after they have been evaluated.
<code>--hpx:print-counter-types</code>	Append counter type description to generated output.
<code>--hpx:print-local-only</code>	Prints only its own local counters.

While the options `--hpx:list-counters` and `--hpx:list-counter-infos` give a short list of all available counters, the full documentation for those can be found in the section *Existing HPX performance counters*.

HPX-Top

HPX-Top is a real-time, terminal-based dashboard designed for monitoring the health and performance of distributed *HPX* applications. Inspired by tools like *htop* and *bt*, it provides a high-level overview of system utilization, network flow, and internal runtime metrics.



Fig. 2.9: HPX-Top Real-time Performance Dashboard

Features

- **Locality-Aware Monitoring:** Automatically detects and displays metrics for all localities in a running distributed application.
- **Thread Pool Utilization:** Visualizes real-time usage of worker threads with instantaneous counts and historical sparkline graphs.
- **Parcel Throughput:** Tracks incoming and outgoing parcels, helping to identify network-bound bottlenecks or communication hotspots.
- **AGAS Health Monitor:** Displays cache hit and miss rates for the Application Global Address Space (AGAS), crucial for diagnosing naming service bottlenecks.

Usage

HPX-Top is implemented as a Python script that acts as a wrapper around your *HPX* application. It automatically configures the necessary performance counters and output formats.

The tool requires the rich Python library for rendering the terminal UI:

```
$ pip install rich
```

To monitor an *HPX* application, launch it through `hpx-top.py`:

```
$ python3 tools/hpx-top.py ./your_application --hpx:threads=4 [other HPX flags]
```

You can also run HPX-Top in mock mode to explore the interface without a running *HPX* application:

```
$ python3 tools/hpx-top.py --mock
```

Technical Details

The tool leverages *HPX*'s built-in performance counter framework. It launches the target application with specific flags (`--hpx:print-counter-interval` and `--hpx:print-counter-format=csv-short`) and parses the standard output in a non-blocking background thread to update the TUI.

HPX Smart Telemetry (`hpx_stat_viewer`)

HPX Smart Telemetry (`hpx_stat_viewer.py`) is an intelligent, lightweight performance dashboard designed to identify performance anomalies in real-time. While `hpx-top` provides a broad system overview, `hpx_stat_viewer` focuses on deep-dive analysis of specific metrics with built-in heuristic alerting.



Fig. 2.10: HPX Smart Telemetry Dashboard with Anomaly Detection

Features

- **Heuristic Anomaly Detection:** Uses an Exponential Moving Average (EMA) to monitor counter trends. It automatically flags sudden spikes (+150%) or drops (-60%) with prominent visual alerts like [SPIKE] and [DROP].
- **Live History Sparklines:** Displays 10-tick historical trend graphs next to every metric, helping developers distinguish between momentary noise and persistent bottlenecks.
- **Smart Filtering and Grouping:** Supports regex-based counter filtering and automatically groups metrics by locality for large-scale distributed runs.
- **Zero-Dependency Core:** Requires no external TUI libraries, making it highly portable for various terminal environments.

Usage

`hpx_stat_viewer.py` reads HPX counter data from standard input in `csv-short` transient format. This allows it to be used for both live monitoring and post-mortem analysis of log files.

To monitor a live application with smart filtering:

```
$ ./your_hpx_app --hpx:print-counter-interval=500 --hpx:print-counter-format=csv-short ..
↩ | \
python3 tools/hpx_stat_viewer.py --filter "threads|utilization"
```

To replay an offline performance log for analysis:


```
$ python3 tools/hpx_stat_viewer.py --replay your_hpx_counters.csv --speed 0.5
```

Technical Details

The dashboard implements a thread-safe parser that handles HPX's CSV-short format. The anomaly detection engine uses a smoothing factor of 0.4 for its EMA calculations, balancing responsiveness with stability. It is officially integrated into the HPX installation rules under the `tools` component.

A simple example

All of the commandline options mentioned above can be tested using the `hello_world_distributed` example.

Listing all available counters `hello_world_distributed --hpx:list-counters` yields:

```
List of available counter instances (replace * below with the appropriate
sequence number)
```

```
-----
/agas/count/allocate /agas/count/bind /agas/count/bind_gid
/agas/count/bind_name ... /threads{locality#*/allocator#*/count/objects
/threads{locality#*/total}/count/stack-recycles
/threads{locality#*/total}/idle-rate
/threads{locality#*/worker-thread#*/idle-rate
```

Providing more information about all available counters, `hello_world_distributed --hpx:list-counter-infos` yields:

```
Information about available counter instances (replace * below with the
appropriate sequence number)
```

```
-----
fullname: /agas/count/allocate helptext: returns the number of invocations of
the AGAS service 'allocate' type: counter_type::raw version: 1.0.0
-----
```

```
-----
fullname: /agas/count/bind helptext: returns the number of invocations of the
AGAS service 'bind' type: counter_type::raw version: 1.0.0
-----
```

```
-----
fullname: /agas/count/bind_gid helptext: returns the number of invocations of
the AGAS service 'bind_gid' type: counter_type::raw version: 1.0.0
-----
```

```
...
```

This command will not only list the counter names but also a short description of the data exposed by this counter.

Note: The list of available counters may differ depending on the concrete execution environment (hardware or software) of your application.

Requesting the counter data for one or more performance counters can be achieved by invoking `hello_world_distributed` with a list of counter names:

```
$ hello_world_distributed \  
  --hpx:print-counter=/threads{locality#0/total}/count/cumulative \  
  --hpx:print-counter=/agas{locality#0/total}/count/bind
```

which yields for instance:

```
hello world from OS-thread 0 on locality 0  
/threads{locality#0/total}/count/cumulative,1,0.212527,[s],33  
/agas{locality#0/total}/count/bind,1,0.212790,[s],11
```

The first line is the normal output generated by `hello_world_distributed` and has no relation to the counter data listed. The last two lines contain the counter data as gathered at application shutdown. These lines have six fields, the counter name, the sequence number of the counter invocation, the time stamp at which this information has been sampled, the unit of measure for the time stamp, the actual counter value and an optional unit of measure for the counter value.

Note: The command line option `--hpx:print-counter-types` will append a seventh field to the generated output. This field will hold an abbreviated counter type.

The actual counter value can be represented by a single number (for counters returning singular values) or a list of numbers separated by `' '` (for counters returning an array of values, like for instance a histogram).

Note: The name of the performance counter will be enclosed in double quotes `''` if it contains one or more commas `','`.

Requesting to query the counter data once after a constant time interval with this command line:

```
$ hello_world_distributed \  
  --hpx:print-counter=/threads{locality#0/total}/count/cumulative \  
  --hpx:print-counter=/agas{locality#0/total}/count/bind \  
  --hpx:print-counter-interval=20
```

yields for instance (leaving off the actual console output of the `hello_world_distributed` example for brevity):

```
threads{locality#0/total}/count/cumulative,1,0.002409,[s],22  
agas{locality#0/total}/count/bind,1,0.002542,[s],9  
threads{locality#0/total}/count/cumulative,2,0.023002,[s],41  
agas{locality#0/total}/count/bind,2,0.023557,[s],10  
threads{locality#0/total}/count/cumulative,3,0.037514,[s],46  
agas{locality#0/total}/count/bind,3,0.038679,[s],10
```

The command `--hpx:print-counter-destination=<file>` will redirect all counter data gathered to the specified file name, which avoids cluttering the console output of your application.

The command line option `--hpx:print-counter` supports using a limited set of wildcards for a (very limited) set of use cases. In particular, all occurrences of `#*` as in `locality#*` and in `worker-thread#*` will be automatically expanded to the proper set of performance counter names representing the actual environment for the executed program. For instance, if your program is utilizing four worker threads for the execution of *HPX* threads (see command line option `--hpx:threads`) the following command line

```
$ hello_world_distributed \
  --hpx:threads=4 \
  --hpx:print-counter=/threads{locality#0/worker-thread#*}/count/cumulative
```

will print the value of the performance counters monitoring each of the worker threads:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 0
hello world from OS-thread 3 on locality 0
hello world from OS-thread 2 on locality 0
/threads{locality#0/worker-thread#0}/count/cumulative,1,0.0025214,[s],27
/threads{locality#0/worker-thread#1}/count/cumulative,1,0.0025453,[s],33
/threads{locality#0/worker-thread#2}/count/cumulative,1,0.0025683,[s],29
/threads{locality#0/worker-thread#3}/count/cumulative,1,0.0025904,[s],33
```

The command `--hpx:print-counter-format` takes values `csv` and `csv-short` to generate CSV formatted counter values with a header.

With format as `csv`:

```
$ hello_world_distributed \
  --hpx:threads=2 \
  --hpx:print-counter-format csv \
  --hpx:print-counter /threads{locality#*/total}/count/cumulative \
  --hpx:print-counter /threads{locality#*/total}/count/cumulative-phases
```

will print the values of performance counters in CSV format with the full countername as a header:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 0
/threads{locality#*/total}/count/cumulative,/threads{locality#*/total}/count/cumulative-
↪phases
39,93
```

With format `csv-short`:

```
$ hello_world_distributed \
  --hpx:threads 2 \
  --hpx:print-counter-format csv-short \
  --hpx:print-counter cumulative,/threads{locality#*/total}/count/cumulative \
  --hpx:print-counter phases,/threads{locality#*/total}/count/cumulative-phases
```

will print the values of performance counters in CSV format with the short countername as a header:

```
hello world from OS-thread 1 on locality 0
hello world from OS-thread 0 on locality 0
cumulative,phases
39,93
```

With format `csv` and `csv-short` when used with `--hpx:print-counter-interval`:

```
$ hello_world_distributed \
  --hpx:threads 2 \
  --hpx:print-counter-format csv-short \
```

(continues on next page)

(continued from previous page)

```
--hpx:print-counter cumulative,/threads{locality#*/total}/count/cumulative \  
--hpx:print-counter phases,/threads{locality#*/total}/count/cumulative-phases \  
--hpx:print-counter-interval 5
```

will print the header only once repeating the performance counter value(s) repeatedly:

```
cum,phases  
25,42  
hello world from OS-thread 1 on locality 0  
hello world from OS-thread 0 on locality 0  
44,95
```

The command `--hpx:no-csv-header` can be used with `--hpx:print-counter-format` to print performance counter values in CSV format without any header:

```
$ hello_world_distributed \  
--hpx:threads 2 \  
--hpx:print-counter-format csv-short \  
--hpx:print-counter cumulative,/threads{locality#*/total}/count/cumulative \  
--hpx:print-counter phases,/threads{locality#*/total}/count/cumulative-phases \  
--hpx:no-csv-header
```

will print:

```
hello world from OS-thread 1 on locality 0  
hello world from OS-thread 0 on locality 0  
37,91
```

Consuming performance counter data using the *HPX* API

HPX provides an API that allows users to discover performance counters and to retrieve the current value of any existing performance counter from any application.

Discover existing performance counters

Retrieve the current value of any performance counter

Performance counters are specialized *HPX* components. In order to retrieve a counter value, the performance counter needs to be instantiated. *HPX* exposes a client component object for this purpose:

```
hpx::performance_counters::performance_counter counter(std::string const& name);
```

Instantiating an instance of this type will create the performance counter identified by the given name. Only the first invocation for any given counter name will create a new instance of that counter. All following invocations for a given counter name will reference the initially created instance. This ensures that at any point in time there is never more than one active instance of any of the existing performance counters.

In order to access the counter value (or to invoke any of the other functionality related to a performance counter, like `start`, `stop` or `reset`) member functions of the created client component instance should be called:

```
// print the current number of threads created on locality 0
hpx::performance_counters::performance_counter count(
    "/threads{locality#0/total}/count/cumulative");
hpx::cout << count.get_value<int>().get() << std::endl;
```

For more information about the client component type, see `hpx::performance_counters::performance_counter`

Note: In the above example `count.get_value()` returns a future. In order to print the result we must append `.get()` to retrieve the value. You could write the above example like this for more clarity:

```
// print the current number of threads created on locality 0
hpx::performance_counters::performance_counter count(
    "/threads{locality#0/total}/count/cumulative");
hpx::future<int> result = count.get_value<int>();
hpx::cout << result.get() << std::endl;
```

Providing performance counter data

HPX offers several ways by which you may provide your own data as a performance counter. This has the benefit of exposing additional, possibly application-specific information using the existing Performance Counter framework, unifying the process of gathering data about your application.

An application that wants to provide counter data can implement a performance counter to provide the data. When a consumer queries performance data, the HPX runtime system calls the provider to collect the data. The runtime system uses an internal registry to determine which provider to call.

Generally, there are two ways of exposing your own performance counter data: a simple, function-based way and a more complex, but more powerful way of implementing a full performance counter. Both alternatives are described in the following sections.

Exposing performance counter data using a simple function

The simplest way to expose arbitrary numeric data is to write a function which will then be called whenever a consumer queries this counter. Currently, this type of performance counter can only be used to expose integer values. The expected signature of this function is:

```
std::int64_t some_performance_data(bool reset);
```

The argument `bool reset` (which is supplied by the runtime system when the function is invoked) specifies whether the counter value should be reset after evaluating the current value (if applicable).

For instance, here is such a function returning how often it was invoked:

```
// The atomic variable 'counter' ensures the thread safety of the counter.
boost::atomic<std::int64_t> counter(0);

std::int64_t some_performance_data(bool reset)
{
    std::int64_t result = ++counter;
    if (reset)
        counter = 0;
```

(continues on next page)

(continued from previous page)

```

    return result;
}

```

This example function exposes a linearly-increasing value as our performance data. The value is incremented on each invocation, i.e., each time a consumer requests the counter data of this performance counter.

The next step in exposing this counter to the runtime system is to register the function as a new raw counter type using the *HPX* API function `hpx::performance_counters::install_counter_type`. A counter type represents certain common characteristics of counters, like their counter type name and any associated description information. The following snippet shows an example of how to register the function `some_performance_data`, which is shown above, for a counter type named `"/test/data"`. This registration has to be executed before any consumer instantiates, and queries an instance of this counter type:

```

#include <hpx/include/performance_counters.hpp>

void register_counter_type()
{
    // Call the HPX API function to register the counter type.
    hpx::performance_counters::install_counter_type(
        "/test/data",                // counter type name
        &some_performance_data,      // function providing counter_
↪data
        "returns a linearly increasing counter value" // description text (optional)
        ""                          // unit of measure (optional)
    );
}

```

Now it is possible to instantiate a new counter instance based on the naming scheme `"/test{locality#*/total}/data"` where `*` is a zero-based integer index identifying the *locality* for which the counter instance should be accessed. The function `hpx::performance_counters::install_counter_type` enables users to instantiate exactly one counter instance for each *locality*. Repeated requests to instantiate such a counter will return the same instance, i.e., the instance created for the first request.

If this counter needs to be accessed using the standard *HPX* command line options, the registration has to be performed during application startup, before `hpx_main` is executed. The best way to achieve this is to register an *HPX* startup function using the API function `hpx::register_startup_function` before calling `hpx::init` to initialize the runtime system:

```

int main(int argc, char* argv[])
{
    // By registering the counter type we make it available to any consumer
    // who creates and queries an instance of the type "/test/data".
    //
    // This registration should be performed during startup. The
    // function 'register_counter_type' should be executed as an HPX thread right
    // before hpx_main is executed.
    hpx::register_startup_function(&register_counter_type);

    // Initialize and run HPX.
    return hpx::init(argc, argv);
}

```

Please see the code in `simplest_performance_counter.cpp` for a full example demonstrating this functionality.

Implementing a full performance counter

Sometimes, the simple way of exposing a single value as a performance counter is not sufficient. For that reason, *HPX* provides a means of implementing full performance counters which support:

- Retrieving the descriptive information about the performance counter
- Retrieving the current counter value
- Resetting the performance counter (value)
- Starting the performance counter
- Stopping the performance counter
- Setting the (initial) value of the performance counter

Every full performance counter will implement a predefined interface:

```
// Copyright (c) 2007-2026 Hartmut Kaiser
//
// SPDX-License-Identifier: BSL-1.0
// Distributed under the Boost Software License, Version 1.0. (See accompanying
// file LICENSE_1_0.txt or copy at http://www.boost.org/LICENSE_1_0.txt)

#pragma once

#include <hpx/config.hpp>
#include <hpx/modules/async_base.hpp>
#include <hpx/modules/components.hpp>
#include <hpx/modules/execution.hpp>
#include <hpx/modules/functional.hpp>
#include <hpx/modules/futures.hpp>

#include <hpx/performance_counters/counters_fwd.hpp>
#include <hpx/performance_counters/server/base_performance_counter.hpp>

#include <string>
#include <utility>
#include <vector>

#include <hpx/config/warnings_prefix.hpp>

////////////////////////////////////
namespace hpx::performance_counters {
    //////////////////////////////////////
    HPX_CXX_EXPORT struct HPX_EXPORT performance_counter
        : components::client_base<performance_counter,
            server::base_performance_counter>
    {
        using base_type = components::client_base<performance_counter,
            server::base_performance_counter>;

        performance_counter() = default;
    };
}
```

(continues on next page)

(continued from previous page)

```

explicit performance_counter(std::string const& name);

performance_counter(
    std::string const& name, hpx::id_type const& locality);

performance_counter(id_type const& id)
    : base_type(id)
{
}

performance_counter(future<id_type>&& id)
    : base_type(HPX_MOVE(id))
{
}

performance_counter(hpx::future<performance_counter>&& c)
    : base_type(HPX_MOVE(c))
{
}

////////////////////////////////////
future<counter_info> get_info() const;
counter_info get_info(
    launch::sync_policy, error_code& ec = throws) const;

future<counter_value> get_counter_value(bool reset) const;
counter_value get_counter_value(
    launch::sync_policy, bool reset, error_code& ec = throws) const;

future<counter_value> get_counter_value() const;
counter_value get_counter_value(
    launch::sync_policy, error_code& ec = throws) const;

future<counter_values_array> get_counter_values_array(bool reset) const;
counter_values_array get_counter_values_array(
    launch::sync_policy, bool reset, error_code& ec = throws) const;

future<counter_values_array> get_counter_values_array() const;
counter_values_array get_counter_values_array(
    launch::sync_policy, error_code& ec = throws) const;

////////////////////////////////////
future<bool> start() const;
bool start(launch::sync_policy, error_code& ec = throws) const;

future<bool> stop() const;
bool stop(launch::sync_policy, error_code& ec = throws) const;

future<void> reset() const;
void reset(launch::sync_policy, error_code& ec = throws) const;

future<void> reinit(bool reset = true) const;

```

(continues on next page)

(continued from previous page)

```

void reinit(launch::sync_policy, bool reset = true,
            error_code& ec = throws) const;

////////////////////////////////////
future<std::string> get_name() const;
std::string get_name(
    launch::sync_policy, error_code& ec = throws) const;

private:
    template <typename T>
    static T extract_value(future<counter_value>&& value)
    {
        return value.get().get_value<T>();
    }

public:
    template <typename T>
    future<T> get_value(bool reset = false)
    {
        return get_counter_value(reset).then(hpx::launch::sync,
            hpx::bind_front(&performance_counter::extract_value<T>));
    }
    template <typename T>
    T get_value(
        launch::sync_policy, bool reset = false, error_code& ec = throws)
    {
        return get_counter_value(launch::sync, reset).get_value<T>(ec);
    }

    template <typename T>
    future<T> get_value() const
    {
        return get_counter_value(false).then(hpx::launch::sync,
            hpx::bind_front(&performance_counter::extract_value<T>));
    }
    template <typename T>
    T get_value(launch::sync_policy, error_code& ec = throws) const
    {
        return get_counter_value(launch::sync, false).get_value<T>(ec);
    }
};

// Return all counters matching the given name (with optional wild cards).
HPX_CXX_EXPORT HPX_EXPORT std::vector<performance_counter>
discover_counters(std::string const& name, error_code& ec = throws);
} // namespace hpx::performance_counters

#include <hpx/config/warnings_suffix.hpp>

```

In order to implement a full performance counter, you have to create an *HPX* component exposing this interface. To simplify this task, *HPX* provides a ready-made base class which handles all the boiler plate of creating a component for you. The remainder of this section will explain the process of creating a full performance counter based on the Sine example, which you can find in the directory `examples/performance_counters/sine/`.

The base class is defined in the header file `base_performance_counter.cpp` as:

```
// Copyright (c) 2007-2026 Hartmut Kaiser
//
// SPDX-License-Identifier: BSL-1.0
// Distributed under the Boost Software License, Version 1.0. (See accompanying
// file LICENSE_1_0.txt or copy at http://www.boost.org/LICENSE_1_0.txt)

#pragma once

#include <hpx/config.hpp>
#include <hpx/modules/actions_base.hpp>
#include <hpx/modules/components_base.hpp>
#include <hpx/modules/runtime_local.hpp>

#include <hpx/performance_counters/counters.hpp>
#include <hpx/performance_counters/server/base_performance_counter.hpp>

#ifdef DOXYGEN
//[performance_counter_base_class
namespace hpx::performance_counters {

    template <typename Derived>
    class base_performance_counter;
} // namespace hpx::performance_counters
//]
#endif

////////////////////////////////////
namespace hpx::performance_counters {

    HPX_CXX_EXPORT template <typename Derived>
    class base_performance_counter
        : public hpx::performance_counters::server::base_performance_counter
        , public hpx::components::component_base<Derived>
    {
    private:
        using base_type = hpx::components::component_base<Derived>;

    public:
        using type_holder = Derived;
        using base_type_holder =
            hpx::performance_counters::server::base_performance_counter;

        // NOLINTBEGIN(bugprone-crt-p-constructor-accessibility)
        base_performance_counter() = default;

        explicit base_performance_counter(
            hpx::performance_counters::counter_info const& info)
            : base_type_holder(info)
        {
        }
    }
}
```

(continues on next page)

(continued from previous page)

```

// NOLINTEND(bugprone-crtip-constructor-accessibility)

// Disambiguate finalize() which is implemented in both base classes
void finalize()
{
    base_type_holder::finalize();
    base_type::finalize();
}

hpx::naming::address get_current_address() const
{
    return hpx::naming::address(
        hpx::naming::get_gid_from_locality_id(hpx::get_locality_id()),
        hpx::components::get_component_type<Derived>(),
        const_cast<Derived*>(static_cast<Derived const*>(this)));
}
};
} // namespace hpx::performance_counters

```

The single template parameter is expected to receive the type of the derived class implementing the performance counter. In the Sine example this looks like:

```

// Copyright (c) 2007-2012 Hartmut Kaiser
//
// SPDX-License-Identifier: BSL-1.0
// Distributed under the Boost Software License, Version 1.0. (See accompanying
// file LICENSE_1_0.txt or copy at http://www.boost.org/LICENSE_1_0.txt)

#pragma once

#include <hpx/config.hpp>
#if !defined(HPX_COMPUTE_DEVICE_CODE)
#include <hpx/hpx.hpp>
#include <hpx/include/lcos_local.hpp>
#include <hpx/include/performance_counters.hpp>
#include <hpx/include/util.hpp>

#include <cstdint>

namespace performance_counters { namespace sine { namespace server {
    //////////////////////////////////////
    //[sine_counter_definition
    class sine_counter
    : public hpx::performance_counters::base_performance_counter<sine_counter>
    {
    public:
        sine_counter()
            : current_value_(0)
            , evaluated_at_(0)
        {
        }
    }
}
}
}

```

(continues on next page)

(continued from previous page)

```

explicit sine_counter(
    hpx::performance_counters::counter_info const& info);

    /// This function will be called in order to query the current value of
    /// this performance counter
    hpx::performance_counters::counter_value get_counter_value(bool reset);

    /// The functions below will be called to start and stop collecting
    /// counter values from this counter.
    bool start();
    bool stop();

    /// finalize() will be called just before the instance gets destructed
    void finalize();

protected:
    bool evaluate();

private:
    typedef hpx::spinlock mutex_type;

    mutable mutex_type mtx_;
    double current_value_;
    std::uint64_t evaluated_at_;

    hpx::util::interval_timer timer_;
};
}}} /// namespace performance_counters::sine::server
#endif

```

i.e., the type `sine_counter` is derived from the base class passing the type as a template argument (please see `simplest_performance_counter.cpp` for the full source code of the counter definition). For more information about this technique (called Curiously Recurring Template Pattern - CRTP), please see for instance the corresponding [Wikipedia article](http://en.wikipedia.org/wiki/Curiously_recurring_template_pattern)¹⁸⁰. This base class itself is derived from the `performance_counter` interface described above.

Additionally, a full performance counter implementation not only exposes the actual value but also provides information about:

- The point in time a particular value was retrieved.
- A (sequential) invocation count.
- The actual counter value.
- An optional scaling coefficient.
- Information about the counter status.

¹⁸⁰ http://en.wikipedia.org/wiki/Curiously_recurring_template_pattern

Existing HPX performance counters

The HPX runtime system exposes a wide variety of predefined performance counters. These counters expose critical information about different modules of the runtime system. They can help determine system bottlenecks and fine-tune system and application performance.

Table 2.29: AGAS performance counter /agas/count/<agas_service>

Counter type	/agas/count/<agas_service> where <agas_service> is one of the following: <i>primary namespace services:</i> route, bind_gid, resolve_gid, unbind_gid, increment_credit, decrement_credit, allocate, begin_migration, end_migration <i>component namespace services:</i> bind_prefix, bind_name, resolve_id, unbind_name, iterate_types, get_component_typename, num_localities_type <i>locality namespace services:</i> free, localities, num_localities, num_threads, resolve_locality, resolved_localities <i>symbol namespace services:</i> bind, resolve, unbind, iterate_names, on_symbol_namespace_event
Counter instance formatting	<agas_instance>/total where <agas_instance> is the name of the AGAS service to query. Currently, this value will be locality#0 where 0 is the root <i>locality</i> (the id of the locality hosting the AGAS service). The value for * can be any <i>locality</i> id for the following <agas_service>: route, bind_gid, resolve_gid, unbind_gid, increment_credit, decrement_credit, bin, resolve, unbind, and iterate_names (only the primary and symbol AGAS service components live on all localities, whereas all other AGAS services are available on locality#0 only).
Description	Returns the total number of invocations of the specified AGAS service since its creation.

Table 2.30: AGAS performance counter /agas/<agas_service_category>/count

Counter type	/agas/<agas_service_category>/count where <agas_service_category> is one of the following: primary, locality, component or symbol
Counter instance formatting	<agas_instance>/total where <agas_instance> is the name of the AGAS service to query. Currently, this value will be locality#0 where 0 is the root <i>locality</i> (the id of the <i>locality</i> hosting the AGAS service). Except for <agas_service_category>, primary or symbol for which the value for * can be any <i>locality</i> id (only the primary and symbol AGAS service components live on all localities, whereas all other AGAS services are available on locality#0 only).
Description	Returns the overall total number of invocations of all AGAS services provided by the given AGAS service category since its creation.

Table 2.31: AGAS performance counter /agas/<agas_service_category>/count

Counter type	/agas/<agas_service_category>/count where <agas_service_category> is one of the following: <code>primary</code> , <code>locality</code> , <code>component</code> or <code>symbol</code>
Counter instance formatting	<agas_instance>/total where <agas_instance> is the name of the AGAS service to query. Currently, this value will be <code>locality#0</code> where <code>0</code> is the root <i>locality</i> (the id of the <i>locality</i> hosting the AGAS service). Except for <agas_service_category>, <code>primary</code> or <code>symbol</code> for which the value for <code>*</code> can be any <i>locality</i> id (only the primary and symbol AGAS service components live on all localities, whereas all other AGAS services are available on <code>locality#0</code> only).
Description	Returns the overall total number of invocations of all AGAS services provided by the given AGAS service category since its creation.

Table 2.32: AGAS performance counter agas/time/<agas_service>

Counter type	agas/time/<agas_service> where <agas_service> is one of the following: <i>primary namespace services:</i> <code>route</code> , <code>bind_gid</code> , <code>resolve_gid</code> , <code>unbind_gid</code> , <code>increment_credit</code> , <code>decrement_credit</code> , <code>allocate</code> , <code>begin_migration</code> , <code>end_migration</code> <i>component namespace services:</i> <code>bind_prefix</code> , <code>bind_name</code> , <code>resolve_id</code> , <code>unbind_name</code> , <code>iterate_types</code> , <code>get_component_typename</code> , <code>num_localities_type</code> <i>locality namespace services:</i> <code>free</code> , <code>localities</code> , <code>num_localities</code> , <code>num_threads</code> , <code>resolve_locality</code> , <code>resolved_localities</code> <i>symbol namespace services:</i> <code>bind</code> , <code>resolve</code> , <code>unbind</code> , <code>iterate_names</code> , <code>on_symbol_namespace_event</code>
Counter instance formatting	<agas_instance>/total where <agas_instance> is the name of the AGAS service to query. Currently, this value will be <code>locality#0</code> where <code>0</code> is the root <i>locality</i> (the id of the <i>locality</i> hosting the AGAS service). The value for <code>*</code> can be any <i>locality</i> id for the following <agas_service>: <code>route</code> , <code>bind_gid</code> , <code>resolve_gid</code> , <code>unbind_gid</code> , <code>increment_credit</code> , <code>decrement_credit</code> , <code>bin</code> , <code>resolve</code> , <code>unbind</code> , and <code>iterate_names</code> (only the primary and symbol AGAS service components live on all localities, whereas all other AGAS services are available on <code>locality#0</code> only).
Description	Returns the overall execution time of the specified AGAS service since its creation (in nanoseconds).

Table 2.33: AGAS performance counter /agas/<agas_service_category>/time`

Counter type	/agas/<agas_service_category>/time where <agas_service_category> is one of the following: <code>primary</code> , <code>locality</code> , <code>component</code> or <code>symbol</code>
Counter instance formatting	<agas_instance>/total where <agas_instance> is the name of the AGAS service to query. Currently, this value will be <code>locality#0</code> where <code>0</code> is the root <i>locality</i> (the id of the <i>locality</i> hosting the AGAS service). Except for <agas_service_category> <code>primary</code> or <code>symbol</code> for which the value for <code>*</code> can be any <i>locality</i> id (only the primary and symbol AGAS service components live on all localities, whereas all other AGAS services are available on <code>locality#0</code> only).
Description	Returns the overall execution time of all AGAS services provided by the given AGAS service category since its creation (in nanoseconds).

Table 2.34: AGAS performance counter /agas/count/entries

Counter type	/agas/count/entries
Counter instance formatting	locality#*/total where * is the <i>locality</i> id of the <i>locality</i> the AGAS cache should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of cache entries resident in the AGAS cache of the specified <i>locality</i> (see <cache_statistics>).

Table 2.35: AGAS performance counter /agas/count/<cache_statistics>

Counter type	/agas/count/<cache_statistics> where <cache_statistics> is one of the following: cache/evictions, cache/hits, cache/insertions, cache/misses
Counter instance formatting	locality#*/total where * is the <i>locality</i> id of the <i>locality</i> the AGAS cache should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i>
Description	Returns the number of cache events (evictions, hits, inserts, and misses) in the AGAS cache of the specified <i>locality</i> (see <cache_statistics>).

Table 2.36: AGAS performance counter /agas/count/<full_cache_statistics>

Counter type	/agas/count/<full_cache_statistics> where <full_cache_statistics> is one of the following: cache/get_entry, cache/insert_entry, cache/update_entry, cache/erase_entry
Counter instance formatting	locality#*/total where * is the <i>locality</i> id of the <i>locality</i> the AGAS cache should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of invocations of the specified cache API function of the AGAS cache.

Table 2.37: AGAS performance counter /agas/time/<full_cache_statistics>

Counter type	/agas/time/<full_cache_statistics> where <full_cache_statistics> is one of the following: cache/get_entry, cache/insert_entry, cache/update_entry, cache/erase_entry
Counter instance formatting	locality#*/total where * is the <i>locality</i> id of the <i>locality</i> the AGAS cache should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall time spent executing of the specified API function of the AGAS cache.

Table 2.38: Parcel layer performance counter `/data/count/<connection_type>/<operation>`

Counter type	<code>/data/count/<connection_type>/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of raw (uncompressed) bytes sent or received (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>) for the specified <code><connection_type></code> . The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.39: Parcel layer performance counter `/data/time/<connection_type>/<operation>`

Counter type	<code>/data/time/<connection_type>/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the total transmission time should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the total time (in nanoseconds) between the start of each asynchronous transmission operation and the end of the corresponding operation for the specified <code><connection_type></code> the given <i>locality</i> (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>). The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.40: Parcel layer performance counter `/serialize/count/<connection_type>/<operation>`

Counter type	<code>/serialize/count/<connection_type>/<operation></code> where: <operation> is one of the following: <code>sent</code> , <code>received</code> <connection_type> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where * is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of bytes transferred (see <operation>, e.g. <code>sent</code> or <code>received</code> possibly compressed) for the specified <connection_type> by the given <i>locality</i> . The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.
Description	If the configure-time option <code>-DHPX_WITH_PARCELPORNT_ACTION_COUNTERS=On</code> was specified, this counter allows one to specify an optional action name as its parameter. In this case the counter will report the number of bytes transmitted for the given action only.

Table 2.41: Parcel layer performance counter `/serialize/time/<connection_type>/<operation>`

Counter type	<code>/serialize/time/<connection_type>/<operation></code> where: <operation> is one of the following: <code>sent</code> , <code>received</code> <connection_type> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where * is the <i>locality</i> id of the <i>locality</i> the serialization time should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall time spent performing outgoing data serialization for the specified <connection_type> on the given <i>locality</i> (see <operation>, e.g. <code>sent</code> or <code>received</code>). The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.
Parameters	If the configure-time option <code>-DHPX_WITH_PARCELPORNT_ACTION_COUNTERS=On</code> was specified, this counter allows one to specify an optional action name as its parameter. In this case the counter will report the serialization time for the given action only.

Table 2.42: Parcel layer performance counter `/parcels/count/routed`

Counter type	<code>/parcels/count/routed</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of routed parcels should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of routed (outbound) parcels transferred by the given <i>locality</i> . Routed parcels are those which cannot directly be delivered to its destination as the local AGAS is not able to resolve the destination address. In this case a parcel is sent to the AGAS service component which is responsible for creating the destination GID (and is responsible for resolving the destination address). This AGAS service component will deliver the parcel to its final target.
Parameters	If the configure-time option <code>-DHPX_WITH_PARCELPOR_ACTION_COUNTERS=On</code> was specified, this counter allows one to specify an optional action name as its parameter. In this case the counter will report the number of parcels for the given action only.

Table 2.43: Parcel layer performance counter `/parcels/count/<connection_type>/<operation>`

Counter type	<code>/parcels/count/<connection_type>/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of parcels should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of parcels transferred using the specified <code><connection_type></code> by the given <i>locality</i> (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>). The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPOR_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPOR_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPOR_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPOR_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.44: Parcel layer performance counter `/messages/count/`
`<connection_type>/<operation>`

Counter type	<code>/messages/count/<connection_type>/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of messages should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of messages ¹⁸¹ transferred using the specified <code><connection_type></code> by the given <i>locality</i> (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>) The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.45: Parcel layer performance counter `/parcelport/count/`
`<connection_type>/zero_copy_chunks/<operation>`

Counter type	<code>/parcelport/count/<connection_type>/zero_copy_chunks/<operation></code> where: <code><operation></code> is one of the following: <code>sent</code> , <code>received</code> <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of zero-copy chunks sent or received (see <code><operation></code> , e.g. <code>sent</code> or <code>received</code>) for the specified <code><connection_type></code> . The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

¹⁸¹ A message can potentially consist of more than one *parcel*.

Table 2.46: Parcel layer performance counter `/parcelport/count-max/<connection_type>/zero_copy_chunks/<operation>`

Counter type	<code>/parcelport/count-max/<connection_type>/zero_copy_chunks/<operation></code> where: <operation> is one of the following: <code>sent</code> , <code>received</code> <connection_type> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where * is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the maximum number of zero-copy chunks sent or received per message (see <operation>, e.g. <code>sent</code> or <code>received</code>) for the specified <connection_type>. The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.47: Parcel layer performance counter `/parcelport/size/<connection_type>/zero_copy_chunks/<operation>`

Counter type	<code>/parcelport/size/<connection_type>/zero_copy_chunks/<operation></code> where: <operation> is one of the following: <code>sent</code> , <code>received</code> <connection_type> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where * is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall size of zero-copy chunks sent or received (see <operation>, e.g. <code>sent</code> or <code>received</code>) for the specified <connection_type>. The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.48: Parcel layer performance counter `/parcelport/size-max/<connection_type>/zero_copy_chunks/<operation>`

Counter type	<code>/parcelport/size-max/<connection_type>/zero_copy_chunks/<operation></code> where: <operation> is one of the following: <code>sent</code> , <code>received</code> <connection_type> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where * is the <i>locality</i> id of the <i>locality</i> the overall number of transmitted bytes should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the maximum size of zero-copy chunks sent or received (see <operation>, e.g. <code>sent</code> or <code>received</code>) for the specified <connection_type>. The performance counters are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_COUNTERS</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_COUNTERS</code> . The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.49: Parcel layer performance counter `/parcelport/count/<connection_type>/<cache_statistics>`

Counter type	<code>/parcelport/count/<connection_type>/<cache_statistics></code> where: <cache_statistics> is one of the following: <code>cache/insertions</code> , <code>cache/evictions</code> , <code>cache/hits</code> , <code>cache/misses</code> , <code>cache/reclaims</code> <connection_type> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where * is the <i>locality</i> id of the <i>locality</i> the number of messages should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number cache events (evictions, hits, inserts, misses, and reclaims) for the connection cache of the given connection type on the given <i>locality</i> (see <cache_statistics>, e.g. <code>ache/insertions</code> , <code>cache/evictions</code> , <code>cache/hits</code> , <code>cache/misses</code> or `` <code>cache/reclaims</code> ``). The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPORNT_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPORNT_MPI</code> . Please see <i>CMake options</i> for more details.

Table 2.50: Parcel layer performance counter `/parcelport/count/<connection_type>/cache-reservation-failures`

Counter type	<code>/parcelport/count/<connection_type>/cache-reservation-failures</code> where <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the counter should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the cumulative number of times <code>get_or_reserve()</code> returned <code>false</code> because every connection slot in the connection cache was already checked out (pool saturation). This is distinct from ordinary cache misses, which occur whenever a new connection to a <i>locality</i> is first created and do not cause parcel deferral. A non-zero and growing value of this counter means that outgoing parcels are being silently queued until a connection is reclaimed; raising <code>hpx.max_connections</code> or <code>hpx.max_connections_per_locality</code> in the ini configuration will relieve the saturation. When pool exhaustion is detected, <i>HPX</i> also emits a warning-level log message (throttled to at most once every five seconds) of the form: <code>parcelport connection cache exhausted: N/M connections in use, K deferred reservation(s) since last reset</code>. The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPOR_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPOR_MPI</code>. Please see <i>CMake options</i> for more details.

Table 2.51: Parcel layer performance counters `/parcelport/count/<connection_type>/cache-connections` and `/parcelport/count/<connection_type>/cache-max-connections`

Counter type	<code>/parcelport/count/<connection_type>/cache-connections</code> <code>/parcelport/count/<connection_type>/cache-max-connections</code> where <code><connection_type></code> is one of the following: <code>tcp</code> , <code>mpi</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the counter should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	<code>cache-connections</code> returns the current number of connections tracked by the connection cache for the given connection type on the given <i>locality</i>. This includes both connections that are currently checked out and connections that are idle and available for reuse. <code>cache-max-connections</code> returns the configured upper limit on the total number of connections the cache is allowed to hold. This value is fixed at startup and corresponds to the <code>hpx.max_connections</code> ini key. Together these two counters give the pool utilisation ratio. If <code>cache-connections</code> is consistently equal to <code>cache-max-connections</code> and <code>cache-reservation-failures</code> is increasing, the connection pool is saturated and the limit should be raised. The performance counters for the connection type <code>mpi</code> are available only if the compile time constant <code>HPX_HAVE_PARCELPOR_MPI</code> was defined while compiling the <i>HPX</i> core library (which is not defined by default). The corresponding cmake configuration constant is <code>HPX_WITH_PARCELPOR_MPI</code>. Please see <i>CMake options</i> for more details.

Table 2.52: Parcel layer performance counter `/parcelqueue/length/<operation>`

Counter type	<code>/parcelqueue/length/<operation></code> where <code><operation></code> is one of the following: <code>sent</code> , <code>receive</code>
Counter instance formatting	<code>locality#*/total</code> where <code>*</code> is the <i>locality</i> id of the <i>locality</i> the <i>parcel</i> queue should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the current number of parcels stored in the <i>parcel</i> queue (see <code><operation></code> for which queue to query, e.g. <code>sent</code> or <code>received</code>).

Table 2.53: Thread manager performance counter `/threads/count/cumulative`

Counter type	<code>/threads/count/cumulative</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the overall number of retired <i>HPX</i> -threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . pool#* is defining the pool for which the current value of the idle-loop counter should be queried for. worker-thread#* is defining the worker thread for which the overall number of retired <i>HPX</i> -threads should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the overall number of executed (retired) <i>HPX</i> -threads on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the accumulated number of retired <i>HPX</i> -threads for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the overall number of retired <i>HPX</i> -threads for all worker threads separately. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> is set to <code>ON</code> (default: <code>ON</code>).

Table 2.54: Thread manager performance counter `/threads/time/average`

Counter type	<code>/threads/time/average</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average time spent executing one <i>HPX</i> -thread should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the average time spent executing one <i>HPX</i> -thread should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the average time spent executing one <i>HPX</i> -thread on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the average time spent executing one <i>HPX</i> -thread for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the average time spent executing one <i>HPX</i> -thread for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.55: Thread manager performance counter `/threads/time/average-overhead`

Counter type	<code>/threads/time/average-overhead</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average overhead spent executing one <i>HPX</i> -thread should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the average overhead spent executing one <i>HPX</i> -thread should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the average time spent on overhead while executing one <i>HPX</i> -thread on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the average time spent on overhead while executing one <i>HPX</i> -thread for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the average time spent on overhead executing one <i>HPX</i> -thread for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.56: Thread manager performance counter `/threads/count/cumulative-phases`

Counter type	<code>/threads/count/cumulative-phases</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the overall number of executed <i>HPX</i> -thread phases (invocations) should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the overall number of executed <i>HPX</i> -thread phases (invocations) should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the overall number of executed <i>HPX</i> -thread phases (invocations) on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the accumulated number of executed <i>HPX</i> -thread phases (invocations) for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the overall number of executed <i>HPX</i> -thread phases for all worker threads separately. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> is set to ON (default: ON). The unit of measure for this counter is nanosecond [ns].

Table 2.57: Thread manager performance counter `/threads/time/average-phase`

Counter type	<code>/threads/time/average-phase</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average time spent executing one <i>HPX</i> -thread phase (invocation) should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the average time executing one <i>HPX</i> -thread phase (invocation) should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the average time spent executing one <i>HPX</i> -thread phase (invocation) on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the average time spent executing one <i>HPX</i> -thread phase (invocation) for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the average time spent executing one <i>HPX</i> -thread phase for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.58: Thread manager performance counter `/threads/time/average-phase-overhead`

Counter type	<code>/threads/time/average-phase-overhead</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average time overhead executing one <i>HPX</i> -thread phase (invocation) should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the average overhead executing one <i>HPX</i> -thread phase (invocation) should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the average time spent on overhead executing one <i>HPX</i> -thread phase (invocation) on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the average time spent on overhead while executing one <i>HPX</i> -thread phase (invocation) for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the average time spent on overhead executing one <i>HPX</i> -thread phase for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.59: Thread manager performance counter `/threads/time/overall`

Counter type	<code>/threads/time/overall</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the overall time spent running the scheduler should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the overall time spent running the scheduler should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the overall time spent running the scheduler on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the overall time spent running the scheduler for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the overall time spent running the scheduler for all worker threads separately. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_IDLE_RATES</code> is set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.60: Thread manager performance counter `/threads/time/cumulative`

Counter type	<code>/threads/time/cumulative</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the overall time spent executing all <i>HPX</i> -threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the overall time spent executing all <i>HPX</i> -threads should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the overall time spent executing all <i>HPX</i> -threads on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the overall time spent executing all <i>HPX</i> -threads for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the overall time spent executing all <i>HPX</i> -threads for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_THREAD_MAINTAIN_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_THREAD_MAINTAIN_IDLE_RATES</code> are set to ON (default: OFF).

Table 2.61: Thread manager performance counter `/threads/time/cumulative-overheads`

Counter type	<code>/threads/time/cumulative-overheads</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the overall overhead time incurred by executing all <i>HPX</i> -threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the the overall overhead time incurred by executing all <i>HPX</i> -threads should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the overall overhead time incurred executing all <i>HPX</i> -threads on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the overall overhead time incurred executing all <i>HPX</i> -threads for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the overall overhead time incurred executing all <i>HPX</i> -threads for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_THREAD_MAINTAIN_CUMULATIVE_COUNTS</code> (default: ON) and <code>HPX_THREAD_MAINTAIN_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.62: Thread manager performance counter `threads/count/instantaneous/<thread-state>`

Counter type	<code>threads/count/instantaneous/<thread-state></code> where: <code><thread-state></code> is one of the following: <code>all</code> , <code>active</code> , <code>pending</code> , <code>suspended</code> , <code>terminated</code> , <code>staged</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current number of threads with the given state should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the current number of threads with the given state should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool. The <code>staged</code> thread state refers to registered tasks before they are converted to thread objects.
Description	Returns the current number of <i>HPX</i> -threads having the given thread state on the given <i>locality</i> . If the instance name is <code>total</code> the counter returns the current number of <i>HPX</i> -threads of the given state for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the current number of <i>HPX</i> -threads in the given state for all worker threads separately.

Table 2.63: Thread manager performance counter threads/
wait-time/<thread-state>

Counter type	threads/wait-time/<thread-state> where: <thread-state> is one of the following: pending staged
Counter instance formatting	locality#*/total or locality#*/worker-thread#* or locality#*/pool#*/worker-thread#* where: locality#* is defining the <i>locality</i> for which the average wait time of <i>HPX</i> -threads (pending) or thread descriptions (staged) with the given state should be queried for. The <i>locality</i> id (given by *) is a (zero based) number identifying the <i>locality</i> . pool#* is defining the pool for which the current value of the idle-loop counter should be queried for. worker-thread#* is defining the worker thread for which the average wait time for the given state should be queried for. The worker thread number (given by the *) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool. The staged thread state refers to the wait time of registered tasks before they are converted into thread objects, while the pending thread state refers to the wait time of threads in any of the scheduling queues.
Description	Returns the average wait time of <i>HPX</i> -threads (if the thread state is pending or of task descriptions (if the thread state is staged on the given <i>locality</i> since application start. If the instance name is <code>total</code> the counter returns the wait time of <i>HPX</i> -threads of the given state for all worker threads (cores) on that <i>locality</i> . If the instance name is <code>worker-thread#*</code> the counter will return the wait time of <i>HPX</i> -threads in the given state for all worker threads separately. These counters are available only if the compile time constant <code>HPX_WITH_THREAD_QUEUE_WAITTIME</code> was defined while compiling the <i>HPX</i> core library (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.64: Thread manager performance counter `/threads/idle-rate`

Counter type	<code>/threads/idle-rate</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average idle rate of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the averaged idle rate should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the average idle rate for the given worker thread(s) on the given <i>locality</i> . The idle rate is defined as the ratio of the time spent on scheduling and management tasks and the overall time spent executing work since the application started. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_IDLE_RATES</code> is set to ON (default: OFF).

Table 2.65: Thread manager performance counter `/threads/creation-idle-rate`

Counter type	<code>/threads/creation-idle-rate</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average creation idle rate of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the averaged idle rate should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the average idle rate for the given worker thread(s) on the given <i>locality</i> which is caused by creating new threads. The creation idle rate is defined as the ratio of the time spent on creating new threads and the overall time spent executing work since the application started. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_IDLE_RATES</code> (default: OFF) and <code>HPX_WITH_THREAD_CREATION_AND_CLEANUP_RATES</code> are set to ON.

Table 2.66: Thread manager performance counter `/threads/cleanup-idle-rate`

Counter type	<code>/threads/cleanup-idle-rate</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the average cleanup idle rate of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the averaged cleanup idle rate should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the average idle rate for the given worker thread(s) on the given <i>locality</i> which is caused by cleaning up terminated threads. The cleanup idle rate is defined as the ratio of the time spent on cleaning up terminated thread objects and the overall time spent executing work since the application started. This counter is available only if the configuration time constants <code>HPX_WITH_THREAD_IDLE_RATES</code> (default: <code>OFF</code>) and <code>HPX_WITH_THREAD_CREATION_AND_CLEANUP_RATES</code> are set to <code>ON</code> .

Table 2.67: Thread manager performance counter `/threadqueue/length`

Counter type	<code>/threadqueue/length</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current length of all thread queues in the scheduler for all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the current length of all thread queues in the scheduler should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the overall length of all queues for the given worker thread(s) on the given <i>locality</i> .

Table 2.68: Thread manager performance counter `/threads/count/stack-unbinds`

Counter type	<code>/threads/count/stack-unbinds</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the unbind (madvise) operations should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the total number of <i>HPX</i> -thread unbind (madvise) operations performed for the referenced <i>locality</i> . Note that this counter is not available on Windows based platforms.

Table 2.69: Thread manager performance counter `/threads/count/stack-recycles`

Counter type	<code>/threads/count/stack-recycles</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the recycling operations should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the total number of <i>HPX</i> -thread recycling operations performed.

Table 2.70: Thread manager performance counter `/threads/count/stolen-from-pending`

Counter type	<code>/threads/count/stolen-from-pending</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of ‘stole’ threads should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the total number of <i>HPX</i> -threads ‘stolen’ from the pending thread queue by a neighboring thread worker thread (these threads are executed by a different worker thread than they were initially scheduled on). This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to <code>ON</code> (default: <code>ON</code>).

Table 2.71: Thread manager performance counter `/threads/count/pending-misses`

Counter type	<code>/threads/count/pending-misses</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the number of pending queue misses of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the number of pending queue misses should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the total number of times that the referenced worker-thread on the referenced <i>locality</i> failed to find pending <i>HPX</i> -threads in its associated queue. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to ON (default: ON).

Table 2.72: Thread manager performance counter `/threads/count/pending-accesses`

Counter type	<code>/threads/count/pending-accesses</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the number of pending queue accesses of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the number of pending queue accesses should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the total number of times that the referenced worker-thread on the referenced <i>locality</i> looked for pending <i>HPX</i> -threads in its associated queue. This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to ON (default: ON).

Table 2.73: Thread manager performance counter `/threads/count/stolen-from-staged`

Counter type	<code>/threads/count/stolen-from-staged</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the number of <i>HPX</i> -threads stolen from the staged queue of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the number of <i>HPX</i> -threads stolen from the staged queue should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the total number of <i>HPX</i> -threads ‘stolen’ from the staged thread queue by a neighboring worker thread (these threads are executed by a different worker thread than they were initially scheduled on). This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to ON (default: ON).

Table 2.74: Thread manager performance counter `/threads/count/stolen-to-pending`

Counter type	<code>/threads/count/stolen-to-pending</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the number of <i>HPX</i> -threads stolen to the pending queue of all (or one) worker threads should be queried for. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the number of <i>HPX</i> -threads stolen to the pending queue should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the total number of <i>HPX</i> -threads ‘stolen’ to the pending thread queue of the worker thread (these threads are executed by a different worker thread than they were initially scheduled on). This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to ON (default: ON).

Table 2.75: Thread manager performance counter `/threads/count/stolen-to-staged`

Counter type	<code>/threads/count/stolen-to-staged</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the number of <i>HPX</i> -threads stolen to the staged queue of all (or one) worker threads should be queried for. The <i>locality</i> id (given by <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the number of <i>HPX</i> -threads stolen to the staged queue should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the ‘default’ pool.
Description	Returns the total number of <i>HPX</i> -threads ‘stolen’ to the staged thread queue of a neighboring worker thread (these threads are executed by a different worker thread than they were initially scheduled on). This counter is available only if the configuration time constant <code>HPX_WITH_THREAD_STEALING_COUNTS</code> is set to ON (default: ON).

Table 2.76: Thread manager performance counter `/threads/count/objects`

Counter type	<code>/threads/count/objects</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/allocator#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current (cumulative) number of all created <i>HPX</i> -thread objects should be queried for. The <i>locality</i> id (given by <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>allocator#*</code> is defining the number of the allocator instance using which the threads have been created. <i>HPX</i> uses a varying number of allocators to create (and recycle) <i>HPX</i> -thread objects, most likely these counters are of use for debugging purposes only. The allocator id (given by <code>*</code>) is a (zero based) number identifying the allocator to query.
Description	Returns the total number of <i>HPX</i> -thread objects created. Note that thread objects are reused to improve system performance, thus this number does not reflect the number of actually executed (retired) <i>HPX</i> -threads.

Table 2.77: Thread manager performance counter `/scheduler/`
`utilization/instantaneous`

Counter type	<code>/scheduler/utilization/instantaneous</code>
Counter instance formatting	<code>locality#*/total</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current (instantaneous) scheduler utilization queried for. The <i>locality</i> id (given by <code>*</code>) is a (zero based) number identifying the <i>locality</i> .
Description	Returns the total (instantaneous) scheduler utilization. This is the current percentage of scheduler threads executing <i>HPX</i> threads.
Parameters	Percent

Table 2.78: Thread manager performance counter `/threads/`
`idle-loop-count/instantaneous`

Counter type	<code>/threads/idle-loop-count/instantaneous</code>
Counter instance formatting	<code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current current accumulated value of all idle-loop counters of all worker threads should be queried. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the current value of the idle-loop counter should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the current (instantaneous) idle-loop count for the given <i>HPX</i> - worker thread or the accumulated value for all worker threads.

Table 2.79: Thread manager performance counter `/threads/
busy-loop-count/instantaneous`

Counter type	<code>/threads/busy-loop-count/instantaneous</code>
Counter instance formatting	<code>locality#*/worker-thread#*</code> or <code>locality#*/pool#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current current accumulated value of all busy-loop counters of all worker threads should be queried. The <i>locality</i> id (given by the <code>*</code>) is a (zero based) number identifying the <i>locality</i> . <code>pool#*</code> is defining the pool for which the current value of the idle-loop counter should be queried for. <code>worker-thread#*</code> is defining the worker thread for which the current value of the busy-loop counter should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> . If no pool-name is specified the counter refers to the 'default' pool.
Description	Returns the current (instantaneous) busy-loop count for the given <i>HPX</i> - worker thread or the accumulated value for all worker threads.

Table 2.80: Thread manager performance counter `/threads/time/
background-work-duration`

Counter type	<code>/threads/time/background-work-duration</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the overall time spent performing background work should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the overall time spent performing background work should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the overall time spent performing background work on the given locality since application start. If the instance name is <code>total</code> the counter returns the overall time spent performing background work for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return the overall time spent performing background work for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: OFF) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns].

Table 2.81: Thread manager performance counter `/threads/background-overhead`

Counter type	<code>/threads/background-overhead</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the background overhead should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the background overhead should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the background overhead on the given locality since application start. If the instance name is <code>total</code> the counter returns the background overhead for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return background overhead for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: OFF) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure displayed for this counter is 0.1%.

Table 2.82: Thread manager performance counter `/threads/time/background-send-duration`

Counter type	<code>/threads/time/background-send-duration</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the overall time spent performing background work related to sending parcels should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the overall time spent performing background work related to sending parcels should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the overall time spent performing background work related to sending parcels on the given locality since application start. If the instance name is <code>total</code> the counter returns the overall time spent performing background work for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return the overall time spent performing background work for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: OFF) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns]. This counter will currently return meaningful values for the MPI parcellport only.

Table 2.83: Thread manager performance counter `/threads/background-send-overhead`

Counter type	<code>/threads/background-send-overhead</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the background overhead related to sending parcels should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the background overhead related to sending parcels should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the background overhead related to sending parcels on the given locality since application start. If the instance name is <code>total</code> the counter returns the background overhead for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return background overhead for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: OFF) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure displayed for this counter is 0.1%. This counter will currently return meaningful values for the MPI parcellport only.

Table 2.84: Thread manager performance counter `/threads/time/background-receive-duration`

Counter type	<code>/threads/time/background-receive-duration</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the overall time spent performing background work related to receiving parcels should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the overall time spent performing background work related to receiving parcels should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the overall time spent performing background work related to receiving parcels on the given locality since application start. If the instance name is <code>total</code> the counter returns the overall time spent performing background work for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return the overall time spent performing background work for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: OFF) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to ON (default: OFF). The unit of measure for this counter is nanosecond [ns]. This counter will currently return meaningful values for the MPI parcellport only.

Table 2.85: Thread manager performance counter `/threads/background-receive-overhead`

Counter type	<code>/threads/background-receive-overhead</code>
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the locality for which the background overhead related to receiving should be queried for. The locality id (given by <code>*</code>) is a (zero based) number identifying the locality. <code>worker-thread#*</code> is defining the worker thread for which the background overhead related to receiving parcels should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code> .
Description	Returns the background overhead related to receiving parcels on the given locality since application start. If the instance name is <code>total</code> the counter returns the background overhead for all worker threads (cores) on that locality. If the instance name is <code>worker-thread#*</code> the counter will return background overhead for all worker threads separately. This counter is available only if the configuration time constants <code>HPX_WITH_BACKGROUND_THREAD_COUNTERS</code> (default: <code>OFF</code>) and <code>HPX_WITH_THREAD_IDLE_RATES</code> are set to <code>ON</code> (default: <code>OFF</code>). The unit of measure displayed for this counter is 0.1%. This counter will currently return meaningful values for the MPI parcelport only.

Table 2.86: General performance counter `/runtime/count/component`

Counter type	<code>/runtime/count/component</code>
Counter instance formatting	<code>locality#*/total</code> where: <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of components should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall number of currently active components of the specified type on the given <i>locality</i> .
Parameters	The type of the component. This is the string which has been used while registering the component with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <code>HPX_REGISTER_COMPONENT</code> .

Table 2.87: General performance counter `/runtime/count/action-invocation`

Counter type	<code>/runtime/count/action-invocation</code>
Counter instance formatting	<code>locality#*/total</code> where: <code>*</code> is the <i>locality</i> id of the <i>locality</i> the number of action invocations should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall (local) invocation count of the specified action type on the given <i>locality</i> .
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <code>HPX_REGISTER_ACTION</code> or <code>HPX_REGISTER_ACTION_ID</code> .

Table 2.88: General performance counter `/runtime/count/remote-action-invocation`

Counter type	<code>/runtime/count/remote-action-invocation</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of action invocations should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall (remote) invocation count of the specified action type on the given <i>locality</i> .
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> .

Table 2.89: General performance counter `/runtime/uptime`

Counter type	<code>/runtime/uptime</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the system uptime should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the overall time since application start on the given <i>locality</i> in nanoseconds.

Table 2.90: General performance counter `/runtime/memory/virtual`

Counter type	<code>/runtime/memory/virtual</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the allocated virtual memory should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the amount of virtual memory currently allocated by the referenced <i>locality</i> (in bytes).

Table 2.91: General performance counter `/runtime/memory/resident`

Counter type	<code>/runtime/memory/resident</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the allocated resident memory should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the amount of resident memory currently allocated by the referenced <i>locality</i> (in bytes).

Table 2.92: General performance counter `/runtime/memory/total`

Counter type	<code>/runtime/memory/total</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the total available memory should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> . Note: only supported in Linux.
Description	Returns the total available memory for use by the referenced <i>locality</i> (in bytes). This counter is available on Linux and Windows systems only.

Table 2.93: General performance counter `/runtime/io/read_bytes_issued`

Counter type	<code>/runtime/io/read_bytes_issued</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of bytes read should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of bytes read by the process (aggregate of count arguments passed to <code>read()</code> call or its analogues). This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.94: General performance counter `/runtime/io/write_bytes_issued`

Counter type	<code>/runtime/io/write_bytes_issued</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of bytes written should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of bytes written by the process (aggregate of count arguments passed to <code>write()</code> call or its analogues). This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.95: General performance counter `/runtime/io/read_syscalls`

Counter type	<code>/runtime/io/read_syscalls</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of system calls should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of system calls that perform I/O reads. This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.96: General performance counter `/runtime/io/write_syscalls`

Counter type	<code>/runtime/io/write_syscalls</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of system calls should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of system calls that perform I/O writes. This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.97: General performance counter `/runtime/io/read_bytes_transferred`

Counter type	<code>/runtime/io/read_bytes_transferred</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of bytes transferred should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of bytes retrieved from storage by I/O operations. This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.98: General performance counter `/runtime/io/write_bytes_transferred`

Counter type	<code>/runtime/io/write_bytes_transferred</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of bytes transferred should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of bytes retrieved from storage by I/O operations. This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.99: General performance counter `/runtime/io/write_bytes_cancelled`

Counter type	<code>/runtime/io/write_bytes_cancelled</code>
Counter instance formatting	<code>locality#*/total</code> where: * is the <i>locality</i> id of the <i>locality</i> the number of bytes not being transferred should be queried. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of bytes accounted by <code>write_bytes_transferred</code> that has not been ultimately stored due to truncation or deletion. This performance counter is available only on systems which expose the related data through the <code>/proc</code> file system.

Table 2.100: Performance counter `/papi/<papi_event>`

Counter type	<code>/papi/<papi_event></code> where: <papi_event> is the name of the PAPI event to expose as a performance counter (such as <code>PAPI_SR_INS</code>). Note that the list of available PAPI events changes depending on the used architecture. For a full list of available PAPI events and their (short) description use the <code>--hpx:list-counters</code> and <code>--hpx:papi-event-info=all</code> command line options.
Counter instance formatting	<code>locality#*/total</code> or <code>locality#*/worker-thread#*</code> where: <code>locality#*</code> is defining the <i>locality</i> for which the current current accumulated value of all busy-loop counters of all worker threads should be queried. The <i>locality</i> id (given by <code>*</code>) is a (zero based) number identifying the <i>locality</i>. <code>worker-thread#*</code> is defining the worker thread for which the current value of the busy-loop counter should be queried for. The worker thread number (given by the <code>*</code>) is a (zero based) worker thread number (given by the <code>*</code>) is a (zero based) number identifying the worker thread. The number of available worker threads is usually specified on the command line for the application using the option <code>--hpx:threads</code>.
Description	Returns the current count of occurrences of the specified PAPI event. This counter is available only if the configuration time constant <code>HPX_WITH_PAPI</code> is set to <code>ON</code> (default: <code>OFF</code>).

Table 2.101: Performance counter `/statistics/average`

Counter type	<code>/statistics/average</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current average (mean) value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to two comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume <code>1000</code> [ms] as the default. The second value can be either <code>0</code> or <code>1</code> and specifies whether the underlying counter should be reset during evaluation <code>1</code> or not <code>0</code> . The default value is <code>0</code> .

Table 2.102: Performance counter `/statistics/rolling_average`

Counter type	<code>/statistics/rolling_average</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current rolling average (mean) value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to three comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume <code>1000</code> [ms] as the default. The second value will be interpreted as the size of the rolling window (the number of latest values to use to calculate the rolling average). The default value for this is <code>10</code> . The third value can be either <code>0</code> or <code>1</code> and specifies whether the underlying counter should be reset during evaluation <code>1</code> or not <code>0</code> . The default value is <code>0</code> .

Table 2.103: Performance counter `/statistics/stddev`

Counter type	<code>/statistics/stddev</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current standard deviation (stddev) value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to two comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.104: Performance counter `/statistics/rolling_stddev`

Counter type	<code>/statistics/rolling_stddev</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current rolling variance (stddev) value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to three comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value will be interpreted as the size of the rolling window (the number of latest values to use to calculate the rolling average). The default value for this is 10. The third value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.105: Performance counter `/statistics/median`

Counter type	<code>/statistics/median</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current (statistically estimated) median value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to two comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.106: Performance counter `/statistics/max`

Counter type	<code>/statistics/max</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current maximum value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to two comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume 1000 [ms] as the default. The second value can be either 0 or 1 and specifies whether the underlying counter should be reset during evaluation 1 or not 0. The default value is 0.

Table 2.107: Performance counter `/statistics/rolling_max`

Counter type	<code>/statistics/rolling_max</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current rolling maximum value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to three comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume <code>1000</code> [ms] as the default. The second value will be interpreted as the size of the rolling window (the number of latest values to use to calculate the rolling average). The default value for this is <code>10</code> . The third value can be either <code>0</code> or <code>1</code> and specifies whether the underlying counter should be reset during evaluation <code>1</code> or not <code>0</code> . The default value is <code>0</code> .

Table 2.108: Performance counter `/statistics/min`

Counter type	<code>/statistics/min</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current minimum value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to two comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume <code>1000</code> [ms] as the default. The second value can be either <code>0</code> or <code>1</code> and specifies whether the underlying counter should be reset during evaluation <code>1</code> or not <code>0</code> . The default value is <code>0</code> .

Table 2.109: Performance counter `/statistics/rolling_min`

Counter type	<code>/statistics/rolling_min</code>
Counter instance formatting	Any full performance counter name. The referenced performance counter is queried at fixed time intervals as specified by the first parameter.
Description	Returns the current rolling minimum value calculated based on the values queried from the underlying counter (the one specified as the instance name).
Parameters	Any parameter will be interpreted as a list of up to three comma separated (integer) values, where the first is the time interval (in milliseconds) at which the underlying counter should be queried. If no value is specified, the counter will assume <code>1000</code> [ms] as the default. The second value will be interpreted as the size of the rolling window (the number of latest values to use to calculate the rolling average). The default value for this is <code>10</code> . The third value can be either <code>0</code> or <code>1</code> and specifies whether the underlying counter should be reset during evaluation <code>1</code> or not <code>0</code> . The default value is <code>0</code> .

Table 2.110: Performance counter `/arithmetics/add`

Counter type	<code>/arithmetics/add</code>
Description	Returns the sum calculated based on the values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.111: Performance counter `/arithmetics/subtract`

Counter type	<code>/arithmetics/subtract</code>
Description	Returns the difference calculated based on the values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.112: Performance counter `/arithmetics/multiply`

Counter type	<code>/arithmetics/multiply</code>
Description	Returns the product calculated based on the values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.113: Performance counter `/arithmetics/divide`

Counter type	<code>/arithmetics/divide</code>
Description	Returns the result of division of the values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.114: Performance counter `/arithmetics/mean`

Counter type	<code>/arithmetics/mean</code>
Description	Returns the average value of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.115: Performance counter `/arithmetics/variance`

Counter type	<code>/arithmetics/variance</code>
Description	Returns the standard deviation of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.116: Performance counter `/arithmetics/median`

Counter type	<code>/arithmetics/median</code>
Description	Returns the median value of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.117: Performance counter `/arithmetics/min`

Counter type	<code>/arithmetics/min</code>
Description	Returns the minimum value of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.118: Performance counter `/arithmetics/max`

Counter type	<code>/arithmetics/max</code>
Description	Returns the maximum value of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Table 2.119: Performance counter `/arithmetics/count`

Counter type	<code>/arithmetics/count</code>
Description	Returns the count value of all values queried from the underlying counters (the ones specified as the parameters).
Parameters	The parameter will be interpreted as a comma separated list of full performance counter names which are queried whenever this counter is accessed. Any wildcards in the counter names will be expanded.

Note: The `/arithmetics` counters can consume an arbitrary number of other counters. For this reason those have to be specified as parameters (a comma separated list of counters appended after a '@'). For instance:

```
$ ./bin/hello_world_distributed -t2 \
  --hpx:print-counter=/threads{locality#0/worker-thread#*}/count/cumulative \
  --hpx:print-counter=/arithmetics/add@/threads{locality#0/worker-thread#*}/count/
↪cumulative
hello world from OS-thread 0 on locality 0
hello world from OS-thread 1 on locality 0
/threads{locality#0/worker-thread#0}/count/cumulative,1,0.515640,[s],25
/threads{locality#0/worker-thread#1}/count/cumulative,1,0.515520,[s],36
/arithmetics/add@/threads{locality#0/worker-thread#*}/count/cumulative,1,0.516445,[s],64
```

Since all wildcards in the parameters are expanded, this example is fully equivalent to specifying both counters separately to `/arithmetics/add`:

```
$ ./bin/hello_world_distributed -t2 \
  --hpx:print-counter=/threads{locality#0/worker-thread#*}/count/cumulative \
  --hpx:print-counter=/arithmetics/add@
  /threads{locality#0/worker-thread#0}/count/cumulative,\
  /threads{locality#0/worker-thread#1}/count/cumulative
```


Table 2.120: Performance counter /coalescing/count/parcels

Counter type	/coalescing/count/parcels
Counter instance formatting	locality#*/total where: * is the <i>locality</i> id of the <i>locality</i> the number of parcels for the given action should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of parcels handled by the message handler associated with the action which is given by the counter parameter.
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> .

Table 2.121: Performance counter /coalescing/count/messages

Counter type	/coalescing/count/messages
Counter instance formatting	locality#*/total where: * is the <i>locality</i> id of the <i>locality</i> the number of messages for the given action should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the number of messages generated by the message handler associated with the action which is given by the counter parameter.
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> .

Table 2.122: Performance counter /coalescing/count/average-parcels-per-message

Counter type	/coalescing/count/average-parcels-per-message
Counter instance formatting	locality#*/total where: * is the <i>locality</i> id of the <i>locality</i> the number of messages for the given action should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the average number of parcels sent in a message generated by the message handler associated with the action which is given by the counter parameter.
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> .

Table 2.123: Performance counter /coalescing/time/average-parcel-arrival

Counter type	/coalescing/time/average-parcel-arrival
Counter instance formatting	locality#*/total where: * is the <i>locality</i> id of the <i>locality</i> the average time between parcels for the given action should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns the average time between arriving parcels for the action which is given by the counter parameter.
Parameters	The action type. This is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> .

Table 2.124: Performance counter /coalescing/time/parcel-arrival-histogram

Counter type	/coalescing/time/parcel-arrival-histogram
Counter instance formatting	locality#*/total where: * is the <i>locality</i> id of the <i>locality</i> the average time between parcels for the given action should be queried for. The <i>locality</i> id is a (zero based) number identifying the <i>locality</i> .
Description	Returns a histogram representing the times between arriving parcels for the action which is given by the counter parameter. This counter returns an array of values, where the first three values represent the three parameters used for the histogram followed by one value for each of the histogram buckets. The first unit of measure displayed for this counter [ns] refers to the lower and upper boundary values in the returned histogram data only. The second unit of measure displayed [0.1%] refers to the actual histogram data. For each bucket the counter shows a value between 0 and 1000 which corresponds to a percentage value between 0% and 100%.
Parameters	The action type and optional histogram parameters. The action type is the string which has been used while registering the action with <i>HPX</i> , e.g. which has been passed as the second parameter to the macro <i>HPX_REGISTER_ACTION</i> or <i>HPX_REGISTER_ACTION_ID</i> . The action type may be followed by a comma separated list of up-to three numbers: the lower and upper boundaries for the collected histogram, and the number of buckets for the histogram to generate. By default these three numbers will be assumed to be 0 ([ns], lower bound), 1000000 ([ns], upper bound), and 20 (number of buckets to generate).

Note: The performance counters related to *parcel* coalescing are available only if the configuration time constant *HPX_WITH_PARCEL_COALESCING* is set to ON (default: ON). However, even in this case it will be available only for actions that are enabled for parcel coalescing (see the macros *HPX_ACTION_USES_MESSAGE_COALESCING* and *HPX_ACTION_USES_MESSAGE_COALESCING_NOTHROW*).

APEX integration

HPX provides integration with *APEX*¹⁸², which is a framework for application profiling using task timers and various performance counters Huck *et al.*¹⁹⁰. It can be added as a git submodule by turning on the option *HPX_WITH_APEX:BOOL* during *CMake*¹⁸³ configuration. *TAU*¹⁸⁴ is an optional dependency when using *APEX*.

To build *HPX* with *APEX*¹⁸⁵, add *HPX_WITH_APEX=ON*, and, optionally, *Tau_ROOT=\$PATH_TO_TAU* to your *CMake*¹⁸⁶ configuration. In addition, you can override the tag used for *APEX*¹⁸⁷ with the *HPX_WITH_APEX_TAG* option. Please see the *APEX HPX documentation*¹⁸⁸ for detailed instructions on using *APEX*¹⁸⁹ with *HPX*.

¹⁸² <http://uo-oaciss.github.io/apex>

¹⁹⁰ K. A. Huck, A. Porterfield, N Chaimov, H. Kaiser, A. D. Malony, T. Sterling, and R. Fowler. *An autonomic performance environment for exascale*. Supercomputing Frontiers and Innovations, 2015.

¹⁸³ <https://www.cmake.org>

¹⁸⁴ <https://www.cs.uoregon.edu/research/tau/home.php>

¹⁸⁵ <http://uo-oaciss.github.io/apex>

¹⁸⁶ <https://www.cmake.org>

¹⁸⁷ <http://uo-oaciss.github.io/apex>

¹⁸⁸ <https://uo-oaciss.github.io/apex/usage/#hpx-louisiana-state-university>

¹⁸⁹ <http://uo-oaciss.github.io/apex>

References

2.4.16 Using the LCI parcelport

Basic information

The [Lightweight Communication Interface](#)¹⁹¹ (LCI) is an ongoing research project aiming to provide efficient support for applications with irregular and asynchronous communication patterns such as graph analysis, sparse linear algebra, and task-based runtime on modern parallel architectures. Its features include (a) support for more communication primitives such as two-sided send/recv and one-sided (dynamic or direct) remote put/get (b) better multi-threaded performance (c) explicit user control of communication resource (d) flexible signaling mechanisms such as synchronizer, completion queue, and active message handler. It is designed to be a low-level communication library used by high-level libraries and frameworks.

The LCI parcelport is an experimental parcelport. It aims to provide the best possible communication performance on high-performance computation platforms. Compared to the MPI parcelport, it uses much fewer messages and memory copies to transfer an *HPX* parcel over the network. Its message transmission path involves minimum synchronization points and is almost lock-free. It is expected to be much faster than the MPI parcelport.

Build *HPX* with the LCI parcelport

While building *HPX*, you can specify a set of [CMake](#)¹⁹² variables to enable and configure the LCI parcelport. Below, there is a set of the most important and frequently used CMake variables.

HPX_WITH_PARCELPORT_LCI

Enable the LCI parcelport. This enables the use of LCI for networking operations in the *HPX* runtime. The default value is OFF because it's not available on all systems and/or requires another dependency. However, this experimental parcelport may provide better performance than the MPI parcelport. You must set this variable to ON in order to use the LCI parcelport. All the following variables only make sense when this variable is set to ON.

HPX_WITH_FETCH_LCI

Use FetchContent to fetch LCI. The default value is OFF. If this option is set to OFF. You need to install your own LCI library and *HPX* will try to find it using [CMake](#)¹⁹³ `find_package`. You can specify the location of the LCI installation by the environmental variable `LCI_ROOT`. Refer to the [LCI README](#)¹⁹⁴ for how to install LCI. If this option is set to ON, *HPX* will fetch and build LCI for you. You can use the following [CMake](#)¹⁹⁵ variables to configure this behavior for your platform.

HPX_WITH_LCI_TAG

This variable only takes effect when `HPX_WITH_FETCH_LCI` is set to ON and `FETCHCONTENT_SOURCE_DIR_LCI` is not set. *HPX* will fetch LCI from its github repository. This variable controls the branch/tag LCI will be fetched.

FETCHCONTENT_SOURCE_DIR_LCI

This variable only takes effect when `HPX_WITH_FETCH_LCI` is set to ON. When it is defined, `HPX_WITH_LCI_TAG` will be ignored. It accepts a path to a local version of LCI source code and *HPX* will fetch and build LCI from there. The default value is set conservatively for the stability of *HPX*, but users are welcome to set this variable to `master` for potentially better performance.

¹⁹¹ <https://github.com/uiuc-hpc/lci>

¹⁹² <https://www.cmake.org>

¹⁹³ <https://www.cmake.org>

¹⁹⁴ <https://github.com/uiuc-hpc/lci#readme>

¹⁹⁵ <https://www.cmake.org>

Run HPX with the LCI parcelport

We use the same mechanisms as MPI to launch LCI, so you can use the same way you run MPI parcelport to run LCI parcelport. Typically, it would be `hpxrun.py`, `mpirun`, or `srun`.

`hpxrun.py` serves as a wrapper for `mpirun` and `srun`. If you are using `hpxrun.py`, pass `-p lci` to the scripts. You also need to pass either `-r mpi` or `-r srun` to select the correct run wrapper according to the platform.

If you are using `mpirun` or `srun`, you can just pass `--hpx:ini=hpx.parcel.lci.priority=1000`, `--hpx:ini=hpx.parcel.lci.enable=1`, and `--hpx:ini=hpx.parcel.bootstrap=lci` to the HPX applications.

The `hpxrun.py` argument `-r none` (the default option for the run wrapper) and its corresponding HPX arguments `--hpx:hpx` and `--hpx:agas` do not work for the MPI or the LCI parcelport.

Performance tuning of the LCI parcelport

We encourage users to set the following environmental variables when using the LCI parcelport to get better performance.

```
$ export LCI_SERVER_MAX_SENDS=1024
$ export LCI_SERVER_MAX_RECVS=4096
$ export LCI_SERVER_NUM_PKTS=65536
$ export LCI_SERVER_MAX_CQES=65536
$ export LCI_PACKET_SIZE=12288
```

This setting needs roughly 800MB memory per process. The memory consumption mainly comes from the packets, which can be calculated using $LCI_SERVER_NUM_PKTS \times LCI_PACKET_SIZE$.

In addition, users can tune the following command-line options when using the LCI parcelport to get better performance.

--hpx:ini=hpx.parcel.lci.ndevices=<int>

The number of LCI devices to use. The default value is 2. An LCI device represents a collection of network resources. More devices lead to lower thread contention, but too many devices may lead to load imbalance or hardware overhead.

--hpx:ini=hpx.parcel.lci.progress_type=<worker|rp>

The way to progress the LCI device. The default value is `worker`. The `worker` option uses all worker threads to progress the LCI devices. The `rp` option uses dedicated pinned threads to progress the LCI devices. Normally, the `worker` option gives better performance, but the `rp` option has been observed with better performance on some clusters with prior generation of InfiniBand hardware.

Reference

Yan, Jiakun, Hartmut Kaiser, and Marc Snir. *Understanding the Communication Needs of Asynchronous Many-Task Systems—A Case Study of HPX+ LCI*. arXiv preprint, 2025.

Yan, Jiakun, and Marc Snir. *LCI: a Lightweight Communication Interface for Efficient Asynchronous Multithreaded Communication*. The International Conference for High Performance Computing, Networking, Storage, and Analysis (SC), 2025.

2.4.17 Using the LCW parcelport

Basic information

The LCW parcelport is an advanced MPI parcelport that can utilize the MPICH VCI and Continuation extensions. The exact MPI implementation is wrapped in a thin wrapper layer (the Lightweight Communication Wrapper, or LCW). This wrapper provides an active message, send/recv, completion queue, and device abstraction on top of MPI (with/without extensions), GASNet-EX, and LCI. The GASNet-EX backend of LCW cannot be used in *HPX* for now, as it lacks send/recv support.

Build *HPX* with the LCW parcelport

While building *HPX*, you can specify a set of [CMake](https://www.cmake.org)¹⁹⁶ variables to enable and configure the LCW parcelport. Below, there is a set of the most important and frequently used CMake variables.

HPX_WITH_PARCELPORT_LCW

Enable the LCW parcelport. This enables the use of LCW for networking operations in the *HPX* runtime. The default value is OFF because it's not available on all systems and/or requires another dependency. You must set this variable to ON in order to use the LCW parcelport. All the following variables only make sense when this variable is set to ON.

HPX_WITH_FETCH_LCW

Use FetchContent to fetch LCW. The default value is OFF. If this option is set to OFF. You need to install your own LCW library and *HPX* will try to find it using [CMake](https://www.cmake.org)¹⁹⁷ `find_package`. You can specify the location of the LCW installation by the environmental variable `LCW_ROOT`. Refer to the [LCW README](https://github.com/JiakunYan/lcw#readme)¹⁹⁸ for how to install LCW. If this option is set to ON. *HPX* will fetch and build LCW for you. You can use the following [CMake](https://www.cmake.org)¹⁹⁹ variables to configure this behavior for your platform.

HPX_WITH_LCW_TAG

This variable only takes effect when `HPX_WITH_FETCH_LCW` is set to ON and `FETCHCONTENT_SOURCE_DIR_LCW` is not set. *HPX* will fetch LCW from its github repository. This variable controls the branch/tag LCW will be fetched.

FETCHCONTENT_SOURCE_DIR_LCW

This variable only takes effect when `HPX_WITH_FETCH_LCW` is set to ON. When it is defined, `HPX_WITH_LCW_TAG` will be ignored. It accepts a path to a local version of LCW source code and *HPX* will fetch and build LCW from there.

Run *HPX* with the LCW parcelport

You can configure runtime behavior with the following options.

--hpx:ini=hpx.parcel.lcw.ndevices=<n>

The number of LCW devices to use (default: 2). Each LCW device maps to an MPI communicator or an LCI device. When the MPICH VCI extension is enabled, each MPI communicator will be mapped to a dedicated collection of network resources. More devices lead to lower thread contention, but too many devices may lead to load imbalance or hardware overhead.

¹⁹⁶ <https://www.cmake.org>

¹⁹⁷ <https://www.cmake.org>

¹⁹⁸ <https://github.com/JiakunYan/lcw#readme>

¹⁹⁹ <https://www.cmake.org>

Reference

Yan, Jiakun, Marc Snir, and Yanfei Guo. *Examining MPI and its Extensions for Asynchronous Multithreaded Communication*. In *European MPI Users' Group Meeting*, pp. 122-142. Cham: Springer Nature Switzerland, 2025.

2.4.18 HPX runtime and resources

HPX thread scheduling policies

The HPX runtime has six thread scheduling policies: local-priority, static-priority, local, static, local-workrequesting-fifo, and abp-priority. These policies can be specified from the command line using the command line option `--hpx:queuing`. In order to use a particular scheduling policy, the runtime system must be built with the appropriate scheduler flag turned on (e.g. `cmake -DHPX_THREAD_SCHEDULERS=local`, see *CMake options* for more information).

Priority local scheduling policy (default policy)

The priority local scheduling policy maintains one queue per operating system (OS) thread. The OS thread pulls its work from this queue. By default the number of high priority queues is equal to the number of OS threads; the number of high priority queues can be specified on the command line using `--hpx:high-priority-threads`. High priority threads are executed by any of the OS threads before any other work is executed. When a queue is empty, work will be taken from high priority queues first. There is one low priority queue from which threads will be scheduled only when there is no other work.

For this scheduling policy there is an option to turn on NUMA sensitivity using the command line option `--hpx:numa-sensitive`. When NUMA sensitivity is turned on, work stealing is done from queues associated with the same NUMA domain first, only after that work is stolen from other NUMA domains.

This scheduler is enabled at build time by default using the FIFO (first-in-first-out) queueing policy. This policy can be invoked using `--hpx:queuinglocal-priority-fifo`. The scheduler can also be enabled using the LIFO (last-in-first-out) policy. This is not the default policy and must be invoked using the command line option `--hpx:queuinglocal-priority-lifo`.

Static priority scheduling policy

- invoke using: `--hpx:queuingstatic-priority` (or `-qs`)

The static scheduling policy maintains one queue per OS thread from which each OS thread pulls its tasks (user threads). Threads are distributed in a round robin fashion. There is no thread stealing in this policy.

Local scheduling policy

- invoke using: `--hpx:queuinglocal` (or `-ql`)
- flag to turn on for build: `HPX_THREAD_SCHEDULERS=all` or `HPX_THREAD_SCHEDULERS=local`

The local scheduling policy maintains one queue per OS thread from which each OS thread pulls its tasks (user threads).

Static scheduling policy

- invoke using: `--hpx:queuingstatic`
- flag to turn on for build: `HPX_THREAD_SCHEDULERS=all` or `HPX_THREAD_SCHEDULERS=static`

The static scheduling policy maintains one queue per OS thread from which each OS thread pulls its tasks (user threads). Threads are distributed in a round robin fashion. There is no thread stealing in this policy.

Priority ABP scheduling policy

- invoke using: `--hpx:queuingabp-priority-fifo`
- flag to turn on for build: `HPX_THREAD_SCHEDULERS=all` or `HPX_THREAD_SCHEDULERS=abp-priority`

Priority ABP policy maintains a double ended lock free queue for each OS thread. By default the number of high priority queues is equal to the number of OS threads; the number of high priority queues can be specified on the command line using `--hpx:high-priority-threads`. High priority threads are executed by the first OS threads before any other work is executed. When a queue is empty work will be taken from high priority queues first. There is one low priority queue from which threads will be scheduled only when there is no other work. For this scheduling policy there is an option to turn on NUMA sensitivity using the command line option `--hpx:numa-sensitive`. When NUMA sensitivity is turned on work stealing is done from queues associated with the same NUMA domain first, only after that work is stolen from other NUMA domains.

This scheduler can be used with two underlying queuing policies (FIFO: first-in-first-out, and LIFO: last-in-first-out). In order to use the LIFO policy use the command line option `--hpx:queuingabp-priority-lifo`.

Work requesting scheduling policies

- invoke using: `--hpx:queuinglocal-workrequesting-fifo`, using `--hpx:queuinglocal-workrequesting-lifo`, or using `--hpx:queuinglocal-workrequesting-mc`

The work-requesting policies rely on a different mechanism of balancing work between cores (compared to the other policies listed above). Instead of actively trying to steal work from other cores, requesting work relies on a less disruptive mechanism. If a core runs out of work, instead of actively looking at the queues of neighboring cores, in this case a request is posted to another core. This core now (whenever it is not busy with other work) either responds to the original core by sending back work or passes the request on to the next possible core in the system. In general, this scheme avoids contention on the work queues as those are always accessed by their own cores only.

The HPX resource partitioner

The HPX resource partitioner lets you take the execution resources available on a system—processing units, cores, and numa domains—and assign them to thread pools. By default HPX creates a single thread pool name `default`. While this is good for most use cases, the resource partitioner lets you create multiple thread pools with custom resources and options.

Creating custom thread pools is useful for cases where you have tasks which absolutely need to run without interference from other tasks. An example of this is when using MPI²⁰⁰ for distribution instead of the built-in mechanisms in HPX (useful in legacy applications). In this case one can create a thread pool containing a single thread for MPI communication. MPI tasks will then always run on the same thread, instead of potentially being stuck in a queue behind other threads.

²⁰⁰ https://en.wikipedia.org/wiki/Message_Passing_Interface

Note that *HPX* thread pools are completely independent from each other in the sense that task stealing will never happen between different thread pools. However, tasks running on a particular thread pool can schedule tasks on another thread pool.

Note: It is simpler in some situations to schedule important tasks with high priority instead of using a separate thread pool.

Using the resource partitioner

The `hpx::resource::partitioner` is now created during *HPX* runtime initialization without explicit action needed from the user. To specify some of the initialization parameters you can use the `hpx::init_params`.

The resource partitioner callback is the interface to add thread pools to the *HPX* runtime and to assign resources to the thread pools. In order to create custom thread pools you can specify the resource partitioner callback `hpx::init_params::rp_callback` which will be called once the resource partitioner will be created, see the example below. You can also specify other parameters, see `hpx::init_params`.

To add a thread pool use the `hpx::resource::partitioner::create_thread_pool` method. If you simply want to use the default scheduler and scheduler options, it is enough to call `rp.create_thread_pool("my-thread-pool")`.

Then, to add resources to the thread pool you can use the `hpx::resource::partitioner::add_resource` method. The resource partitioner exposes the hardware topology retrieved using [Portable Hardware Locality \(HWLOC\)](#)²⁰¹ and lets you iterate through the topology to add the wanted processing units to the thread pool. Below is an example of adding all processing units from the first NUMA domain to a custom thread pool, unless there is only one NUMA domain in which case we leave the first processing unit for the default thread pool:

Note: Whatever processing units are not assigned to a thread pool by the time `hpx::init` is called will be added to the default thread pool. It is also possible to explicitly add processing units to the default thread pool, and to create the default thread pool manually (in order to e.g. set the scheduler type).

Tip: The command line option `--hpx:print-bind` is useful for checking that the thread pools have been set up the way you expect.

Difference between the old and new version

In the old version, you had to create an instance of the `resource_partitioner` with `argc` and `argv`.

```
int main(int argc, char** argv)
{
    hpx::resource::partitioner rp(argc, argv);
    hpx::init();
}
```

From *HPX* 1.5.0 onwards, you just pass `argc` and `argv` to `hpx::init()` or `hpx::start()` for the binding options to be parsed by the resource partitioner.

²⁰¹ <https://www.open-mpi.org/projects/hwloc/>


```
int main(int argc, char** argv)
{
    hpx::init_params init_args;
    hpx::init(argc, argv, init_args);
}
```

In the old version, when creating a custom thread pool, you just called the utilities on the resource partitioner instantiated previously.

```
int main(int argc, char** argv)
{
    hpx::resource::partitioner rp(argc, argv);

    rp.create_thread_pool("my-thread-pool");

    bool one_numa_domain = rp.numa_domains().size() == 1;
    bool skipped_first_pu = false;

    hpx::resource::numa_domain const& d = rp.numa_domains()[0];

    for (const hpx::resource::core& c : d.cores())
    {
        for (const hpx::resource::pu& p : c.pus())
        {
            if (one_numa_domain && !skipped_first_pu)
            {
                skipped_first_pu = true;
                continue;
            }

            rp.add_resource(p, "my-thread-pool");
        }
    }

    hpx::init();
}
```

You now specify the resource partitioner callback which will tie the resources to the resource partitioner created during runtime initialization.

```
void init_resource_partitioner_handler(hpx::resource::partitioner& rp)
{
    rp.create_thread_pool("my-thread-pool");

    bool one_numa_domain = rp.numa_domains().size() == 1;
    bool skipped_first_pu = false;

    hpx::resource::numa_domain const& d = rp.numa_domains()[0];

    for (const hpx::resource::core& c : d.cores())
    {
        for (const hpx::resource::pu& p : c.pus())
        {
```

(continues on next page)

(continued from previous page)

```
        if (one_numa_domain && !skipped_first_pu)
        {
            skipped_first_pu = true;
            continue;
        }

        rp.add_resource(p, "my-thread-pool");
    }
}

int main(int argc, char* argv[])
{
    hpx::init_params init_args;
    init_args.rp_callback = &init_resource_partitioner_handler;

    hpx::init(argc, argv, init_args);
}
```

Advanced usage

It is possible to customize the built in schedulers by passing scheduler options to `hpx::resource::partitioner::create_thread_pool`. It is also possible to create and use custom schedulers.

Note: It is not recommended to create your own scheduler. The *HPX* developers use this to experiment with new scheduler designs before making them available to users via the standard mechanisms of choosing a scheduler (command line options). If you would like to experiment with a custom scheduler the resource partitioner example `shared_priority_queue_scheduler.cpp` contains a fully implemented scheduler with logging, etc. to make exploration easier.

To choose a scheduler and custom mode for a thread pool, pass additional options when creating the thread pool like this:

```
rp.create_thread_pool("my-thread-pool",
    hpx::resource::policies::local_priority_lifo,
    hpx::policies::scheduler_mode(
        hpx::policies::scheduler_mode::default |
        hpx::policies::scheduler_mode::enable_elasticity));
```

The available schedulers are documented here: `hpx::resource::scheduling_policy`, and the available scheduler modes here: `hpx::threads::policies::scheduler_mode`. Also see the examples folder for examples of advanced resource partitioner usage: `simple_resource_partitioner.cpp` and `oversubscribing_resource_partitioner.cpp`.

2.4.19 Executors

Executors in *HPX* provide a flexible way to control **how, when, and where** tasks are executed. Instead of manually creating threads or managing thread pools, you can hand your tasks to an executor, and it takes care of the details of running them.

This page introduces the concept of executors, the main types available in *HPX*, and how to create custom executors.

What is an executor?

An **executor** is an abstraction that separates the *what* from the *how* of task execution:

- **What:** the work to be performed (e.g. a function or task).
- **How:** whether the task runs synchronously, asynchronously, or in parallel across multiple cores.

By using executors, you can switch between execution strategies without rewriting your algorithms. *HPX* provides a rich set of executors with a unified API.

Main Executors in *HPX*

HPX provides multiple executors. Below are three of the most commonly used:

Parallel Executor

- Default in *HPX*.
- Creates a new HPX thread for every scheduled task.
- Works well for large tasks, but frequent small tasks incur overhead due to thread creation/destruction.

```
#include <hpx/execution.hpp>
#include <hpx/algorithm.hpp>
#include <vector>

std::vector<int> data(100, 1);

hpx::for_each(
    hpx::execution::par,
    data.begin(), data.end(),
    [](int &x) {
        x += 1;
    }
);
```

Fork-Join Executor

- Spawns one thread per CPU core when created.
- Threads are reused across tasks, avoiding repeated creation costs.
- Efficient for workloads with many sequential parallel regions.
- May waste resources if parallel work is limited.

```
#include <hpx/execution.hpp>
#include <hpx/algorithm.hpp>
#include <vector>

std::vector<int> data(100, 1);

hpx::execution::experimental::fork_join_executor exec;

hpx::for_each(
    hpx::execution::par.on(exec),
    data.begin(), data.end(),
    [](int &x) {
        x += 1;
    }
);
```

Sequential Executor

- Executes all tasks synchronously on the calling thread.
- Useful for debugging (deterministic execution) or when parallelism brings no benefit.
- Maintains the same executor-based API while running tasks sequentially.

```
#include <hpx/execution.hpp>
#include <hpx/algorithm.hpp>
#include <vector>

std::vector<int> data(100, 1);

hpx::execution::sequenced_executor seq_exec;

hpx::for_each(
    hpx::execution::seq.on(seq_exec),
    data.begin(), data.end(),
    [](int &x) { x += 1; }
);
```

Executors in real-world applications

A practical example is the **LULESH** mini-application (a hydrodynamics benchmark).




Fig. 2.11: Parallel executor: creates and destroys threads for each loop.

- With the **parallel executor**, each parallel loop creates and destroys new threads, introducing overhead.
- With the **fork-join executor**, threads are created once and reused across loops, reducing overhead and improving performance.

In studies, the fork-join executor achieved significant speedups, in some cases more than twice as fast as traditional OpenMP implementations.




Fig. 2.13: Performance comparison between executors in the LULESH benchmark.

Custom executors

While *HPX* provides a variety of built-in executors, you may sometimes need to adapt task execution to your own requirements. This is where **custom executors** come in. By writing a small wrapper around an existing executor, you can extend its behavior—for example, to add logging, profiling information, or special scheduling rules—while still taking advantage of the *HPX* executor API.

Custom annotating executor

The following example shows how to implement a simple executor that annotates tasks with a string label for easier debugging and profiling.

Note: Annotations do not affect how tasks run or what results they produce. Their main purpose is to give human-readable names to tasks so that they can be identified in profilers, and debuggers.

Full example code

```
#include <hpx/hpx_main.hpp>
#include <hpx/include/parallel_executors.hpp>
#include <hpx/include/async.hpp>
#include <hpx/execution.hpp>
#include <hpx/modules/async_base.hpp>
#include <hpx/modules/threading_base.hpp>

#include <iostream>
#include <string>
#include <utility>

template <typename BaseExecutor>
struct simple_annotating_executor
{
    BaseExecutor base_;
    const char* annotation_;

    simple_annotating_executor(BaseExecutor exec, const char* ann)
        : base_(std::move(exec)), annotation_(ann)
    {}

    // Non-blocking one-way executor
    template <typename F, typename... Ts>
    friend void tag_invoke(hpx::parallel::execution::post_t,
                          simple_annotating_executor const& exec,
                          F&& f, Ts&&... ts)
    {
        hpx::post(
```

(continues on next page)

(continued from previous page)

```

        hpx::annotated_function(std::forward<F>(f), exec.annotation_),
        std::forward<Ts>(ts)...);
    }

    // Synchronous execution
    template <typename F, typename... Ts>
    friend auto tag_invoke(hpx::parallel::execution::sync_execute_t,
        simple_annotating_executor const& exec,
        F&& f, Ts&&... ts)
    {
        return hpx::parallel::execution::sync_execute(
            exec.base_,
            hpx::annotated_function(std::forward<F>(f), exec.annotation_),
            std::forward<Ts>(ts)...);
    }
};

// Example functions
int compute_square(int x)
{
    std::cout << "[sync_execute] Running task with annotation\n";
    return x * x;
}

void say_hello()
{
    std::cout << "[post] Running task with annotation\n";
}

int main()
{
    simple_annotating_executor exec(hpx::execution::parallel_executor{}, "my_custom_task
↪");

    // Synchronous execution
    int result = hpx::parallel::execution::sync_execute(exec, &compute_square, 7);
    std::cout << "Result from sync_execute: " << result << "\n";

    // Post a task
    hpx::parallel::execution::post(exec, &say_hello);

    return 0;
}

```

Explanation

The first lines pull in the necessary HPX headers for executors, asynchronous execution, and annotated functions. The key one here is `hpx/threading_base/annotated_function.hpp`, which provides the facility to tag tasks with a string label. We then define a `simple_annotating_executor` that wraps another executor and associates an annotation string with every task:

```
template <typename BaseExecutor>
struct simple_annotating_executor
{
    BaseExecutor base_;
    const char* annotation_;

    simple_annotating_executor(BaseExecutor exec, const char* ann)
        : base_(std::move(exec)), annotation_(ann)
    {}
};
```

The `post` customization schedules a task to run asynchronously. We wrap the task in `hpx::annotated_function` so that it carries the annotation. Executors in HPX customize these operations through `tag_invoke` overloads, which are selected by special tag objects like `post_t` and `sync_execute_t`. This is why the executor interface may look different from a normal member function API.

```
template <typename F, typename... Ts>
friend void tag_invoke(hpx::parallel::execution::post_t,
                      simple_annotating_executor const& exec,
                      F&& f, Ts&&... ts)
{
    hpx::post(
        hpx::annotated_function(std::forward<F>(f), exec.annotation_),
        std::forward<Ts>(ts)...);
}
```

The `sync_execute` customization runs a task immediately and returns the result. Again, we wrap the function with an annotation before executing. The key difference is that `post` schedules a task in a fire-and-forget style (no result is returned), while `sync_execute` blocks until the task finishes and gives you the result back.

```
template <typename F, typename... Ts>
friend auto tag_invoke(hpx::parallel::execution::sync_execute_t,
                      simple_annotating_executor const& exec,
                      F&& f, Ts&&... ts)
{
    return hpx::parallel::execution::sync_execute(
        exec.base_,
        hpx::annotated_function(std::forward<F>(f), exec.annotation_),
        std::forward<Ts>(ts)...);
}
```

Note how we delegate the actual execution to `exec.base_`, the underlying executor. This makes the custom executor lightweight: it only adds annotations, while leaving the scheduling strategy to the base executor (here, a *parallel_executor*).

We define two simple functions to demonstrate both synchronous and asynchronous execution: These functions also print to `std::cout`, but this output is not the actual annotation. Annotations are stored internally by HPX and become visible when you use debugging or profiling tools.


```

int compute_square(int x)
{
    std::cout << "[sync_execute] Running task with annotation\n";
    return x * x;
}

void say_hello()
{
    std::cout << "[post] Running task with annotation\n";
}

```

Finally, in main we create the executor with a base executor and annotation string. We then run one task with `sync_execute` (blocking, returns result) and one with `post` (asynchronous, fire-and-forget). You can also create multiple annotating executors with different strings, so each task gets its own label. This is especially useful in larger applications with many different kinds of tasks, where annotations make it much easier to trace what is happening.

```

int main()
{
    simple_annotating_executor exec(hpx::execution::parallel_executor{}, "my_custom_task
↪");

    // Synchronous execution
    int result = hpx::parallel::execution::sync_execute(exec, &compute_square, 7);
    std::cout << "Result from sync_execute: " << result << "\n";

    // Post a task
    hpx::parallel::execution::post(exec, &say_hello);

    return 0;
}

```

Custom annotating executor with parallel algorithms

The following example demonstrates how to use a custom annotating executor with *HPX* parallel algorithms, such as `for_each`. This allows you to attach annotations to tasks while executing them in parallel.

Full example code

```

#include <hpx/execution.hpp>
#include <hpx/hpx_main.hpp>
#include <hpx/include/parallel_algorithm.hpp>
#include <hpx/include/parallel_executors.hpp>
#include <hpx/modules/threading_base.hpp>

#include <iostream>
#include <utility>
#include <vector>

template <typename BaseExecutor>
struct simple_annotating_executor

```

(continues on next page)

(continued from previous page)

```

{
    BaseExecutor base_;
    char const* annotation_;

    using execution_category =
        hpx::traits::executor_execution_category_t<BaseExecutor>;

    simple_annotating_executor(BaseExecutor exec, char const* ann)
    : base_(std::move(exec))
    , annotation_(ann)
    {
    }

    // Bulk async_execute (used by parallel algorithms)
    template <typename F, typename Shape, typename... Ts>
    friend auto tag_invoke(hpx::parallel::execution::bulk_async_execute_t,
        simple_annotating_executor const& exec, F&& f, Shape const& shape,
        Ts&&... ts)
    {
        return hpx::parallel::execution::bulk_async_execute(
            exec.base_,
            hpx::annotated_function(std::forward<F>(f), exec.annotation_),
            shape, std::forward<Ts>(ts)...);
    }
};

namespace hpx::execution::experimental {

    // The annotating executor exposes the same executor categories as its
    // underlying (wrapped) executor.

    template <typename BaseExecutor>
    struct is_two_way_executor<simple_annotating_executor<BaseExecutor>>
    : is_two_way_executor<BaseExecutor>
    {
    };
} // namespace hpx::execution::experimental

int main()
{
    using base_executor = hpx::execution::parallel_executor;
    simple_annotating_executor exec(base_executor{}, "for_each_task");

    std::vector<int> data = {1, 2, 3, 4, 5};

    // Use the custom executor with a parallel algorithm
    hpx::for_each(hpx::execution::par.on(exec), // attach executor
        data.begin(), data.end(), [](int& x) {
            std::cout << "Processing " << x << " on thread "
                << hpx::get_worker_thread_num() << "\n";
            x *= x;
        });
}

```

(continues on next page)

(continued from previous page)

```

std::cout << "Squared values: ";
for (int v : data)
    std::cout << v << " ";
std::cout << "\n";

return 0;
}

```

Explanation

Similar as before, the first lines pull in the necessary HPX headers for executors, asynchronous execution, and annotated functions. The key one here is *hpx/threading_base/annotated_function.hpp*, which provides the facility to tag tasks with a string label. We then define a *simple_annotating_executor* that wraps another executor and associates an annotation string with every task:

```

template <typename BaseExecutor>
struct simple_annotating_executor
{
    BaseExecutor base_;
    const char* annotation_;

    using execution_category =
        hpx::traits::executor_execution_category_t<BaseExecutor>;

    simple_annotating_executor(BaseExecutor exec, const char* ann)
        : base_(std::move(exec)), annotation_(ann)
    {}
};

```

Note that we expose the execution category of the custom executor with *using execution_category = hpx::traits::executor_execution_category_t<BaseExecutor>*. We inherit the execution category from the underlying executor (*BaseExecutor*), which ensures that our *simple_annotating_executor* behaves like the base executor in terms of parallelism and task execution capabilities.

The *bulk_async_execute* customization schedules a set of tasks to run asynchronously. We wrap each task in *hpx::annotated_function* so that it carries the annotation. Executors in *HPX* customize these operations through *tag_invoke* overloads, which are selected by special tag objects like *bulk_async_execute_t*. This is why the executor interface may look different from a normal member function API - it uses tag dispatch to integrate seamlessly with the *HPX* parallel algorithms infrastructure.

```

template <typename F, typename Shape, typename... Ts>
friend auto tag_invoke(hpx::parallel::execution::bulk_async_execute_t,
    simple_annotating_executor const& exec, F&& f, Shape const& shape,
    Ts&&... ts)
{
    return hpx::parallel::execution::bulk_async_execute(
        exec.base_,
        hpx::annotated_function(std::forward<F>(f), exec.annotation_),
        shape, std::forward<Ts>(ts)...);
}

```

Note how we delegate the actual execution to *exec.base_*, the underlying executor. This makes the custom executor lightweight: it only adds annotations, while leaving the scheduling strategy to the base executor (here, a *parallel_executor*).

The *hpx::execution::experimental* namespace contains traits that describe executor capabilities, such as whether an executor can run tasks one-way, two-way, or never-blocking. These traits are used internally by *HPX* to verify that an executor is compatible with a given parallel algorithm or execution policy.

```
namespace hpx::execution::experimental {

    // The annotating executor exposes the same executor categories as its
    // underlying (wrapped) executor.

    template <typename BaseExecutor>
    struct is_never_blocking_one_way_executor<
        simple_annotating_executor<BaseExecutor>>
    : is_never_blocking_one_way_executor<BaseExecutor>
    {
    };

    template <typename BaseExecutor>
    struct is_one_way_executor<simple_annotating_executor<BaseExecutor>>
    : is_one_way_executor<BaseExecutor>
    {
    };

    template <typename BaseExecutor>
    struct is_two_way_executor<simple_annotating_executor<BaseExecutor>>
    : is_two_way_executor<BaseExecutor>
    {
    };

}
```

- *is_never_blocking_one_way_executor* indicates whether the executor can schedule tasks in a fire-and-forget style without blocking.
- *is_one_way_executor* indicates support for one-way execution (tasks can be scheduled but no result is returned).
- *is_two_way_executor* indicates support for two-way execution (tasks return a result or a future).

In all cases, the custom executor inherits the capabilities of the base executor, so it integrates seamlessly with *HPX* algorithms.

This design ensures that *simple_annotating_executor* can be used anywhere its underlying executor could be used, while still adding the annotation functionality. It keeps the custom executor lightweight and fully compatible with the parallel algorithms infrastructure.

In main, we create the executor with a base executor and an annotation string, and then use it with a parallel algorithm:

```
int main()
{
    using base_executor = hpx::execution::parallel_executor;
    simple_annotating_executor exec(base_executor{}, "for_each_task");

    std::vector<int> data = {1, 2, 3, 4, 5};

    // Use the custom executor with a parallel algorithm
```

(continues on next page)

(continued from previous page)

```

hpx::for_each(hpx::execution::par.on(exec),    // attach executor
    data.begin(), data.end(), [](int& x) {
        std::cout << "Processing " << x << " on thread "
            << hpx::get_worker_thread_num() << "\n";
        x *= x;
    });

std::cout << "Squared values: ";
for (int v : data)
    std::cout << v << " ";
std::cout << "\n";

return 0;
}

```

First, we create a base executor (*parallel_executor*) and wrap it in our *simple_annotating_executor*, providing an annotation string “for_each_task”. This custom executor will attach the annotation to every task it schedules, while delegating actual execution to the base executor.

We then use `hpx::for_each` with a parallel execution policy and attach our custom executor using `par.on(exec)`: `hpx::execution::par.on(exec)` attaches our custom executor to the algorithm. `for_each` internally partitions the work across threads and schedules each task using *bulk_async_execute*. Each task is annotated with “for_each_task”, visible in debuggers and profilers. The results of the parallel computation are stored in the data vector, demonstrating that the algorithm

executed successfully in parallel.

This pattern is especially useful in larger applications with many tasks, as annotations make it much easier to trace and debug the execution of parallel algorithms.

2.4.20 Error handling

Like in any other asynchronous invocation scheme, it is important to be able to handle error conditions occurring while the asynchronous (and possibly remote) operation is executed. In *HPX* all error handling is based on standard C++ exception handling. Any exception thrown during the execution of an asynchronous operation will be transferred back to the original invocation *locality*, where it will be rethrown during synchronization with the calling thread.

The source code for this example can be found here: `error_handling.cpp`.

Working with exceptions

For the following description assume that the function `raise_exception()` is executed by invoking the plain action `raise_exception_type`.

```

void raise_exception()
{
    HPX_THROW_EXCEPTION(
        hpx::error::no_success, "raise_exception", "simulated error");
}
HPX_PLAIN_ACTION(raise_exception, raise_exception_action)

```

The exception is thrown using the macro `HPX_THROW_EXCEPTION`. The type of the thrown exception is `hpx::exception`. This associates additional diagnostic information with the exception, such as file name and line

number, *locality* id and thread id, and stack backtrace from the point where the exception was thrown.

Any exception thrown during the execution of an action is transferred back to the (asynchronous) invocation site. It will be rethrown in this context when the calling thread tries to wait for the result of the action by invoking either `future<>::get()` or the synchronous action invocation wrapper as shown here:

Note: The exception is transferred back to the invocation site even if it is executed on a different *locality*.

Additionally, this example demonstrates how an exception thrown by an (possibly remote) action can be handled. It shows the use of `hpx::diagnostic_information`, which retrieves all available diagnostic information from the exception as a formatted string. This includes, for instance, the name of the source file and line number, the sequence number of the OS thread and the *HPX* thread id, the *locality* id and the stack backtrace of the point where the original exception was thrown.

Under certain circumstances it is desirable to output only some of the diagnostics, or to output those using different formatting. For this case, *HPX* exposes a set of lower-level functions as demonstrated in the following code snippet:

Working with error codes

Most of the API functions exposed by *HPX* can be invoked in two different modes. By default those will throw an exception on error as described above. However, sometimes it is desirable not to throw an exception in case of an error condition. In this case an object instance of the `hpx::error_code` type can be passed as the last argument to the API function. In case of an error, the error condition will be returned in that `hpx::error_code` instance. The following example demonstrates extracting the full diagnostic information without exception handling:

```
hpx::cout << "Error reporting using error code\n";

// Create a new error_code instance.
hpx::error_code ec;

// If an instance of an error_code is passed as the last argument while
// invoking the action, the function will not throw in case of an error
// but store the error information in this error_code instance instead.
raise_exception_action do_it;
do_it(hpx::find_here(), ec);

if (ec)
{
    // Print just the essential error information.
    hpx::cout << "returned error: " << ec.get_message() << "\n";

    // Print all of the available diagnostic information as stored with
    // the exception.
    hpx::cout << "diagnostic information:"
               << hpx::diagnostic_information(ec) << "\n";
}

hpx::cout << std::flush;
```

Note: The error information is transferred back to the invocation site even if it is executed on a different *locality*.

This example shows how an error can be handled without having to resolve to exceptions and that the returned `hpx::error_code` instance can be used in a very similar way as the `hpx::exception` type above. Simply pass it to the `hpx::diagnostic_information`, which retrieves all available diagnostic information from the error code instance as a formatted string.

As for handling exceptions, when working with error codes, under certain circumstances it is desirable to output only some of the diagnostics, or to output those using different formatting. For this case, *HPX* exposes a set of lower-level functions usable with error codes as demonstrated in the following code snippet:

```
hpx::cout << "Detailed error reporting using error code\n";

// Create a new error_code instance.
hpx::error_code ec;

// If an instance of an error_code is passed as the last argument while
// invoking the action, the function will not throw in case of an error
// but store the error information in this error_code instance instead.
raise_exception_action do_it;
do_it(hpx::find_here(), ec);

if (ec)
{
    // Print the elements of the diagnostic information separately.
    hpx::cout << "{what}: " << hpx::get_error_what(ec) << "\n";
    hpx::cout << "{locality-id}: " << hpx::get_error_locality_id(ec)
        << "\n";
    hpx::cout << "{hostname}: " << hpx::get_error_host_name(ec)
        << "\n";
    hpx::cout << "{pid}: " << hpx::get_error_process_id(ec) << "\n";
    hpx::cout << "{function}: " << hpx::get_error_function_name(ec)
        << "\n";
    hpx::cout << "{file}: " << hpx::get_error_file_name(ec) << "\n";
    hpx::cout << "{line}: " << hpx::get_error_line_number(ec)
        << "\n";
    hpx::cout << "{os-thread}: " << hpx::get_error_os_thread(ec)
        << "\n";
    hpx::cout << "{thread-id}: " << std::hex
        << hpx::get_error_thread_id(ec) << "\n";
    hpx::cout << "{thread-description}: "
        << hpx::get_error_thread_description(ec) << "\n\n";
    hpx::cout << "{state}: " << std::hex << hpx::get_error_state(ec)
        << "\n";
    hpx::cout << "{stack-trace}: " << hpx::get_error_backtrace(ec)
        << "\n";
    hpx::cout << "{env}: " << hpx::get_error_env(ec) << "\n";
}

hpx::cout << std::flush;
```

For more information please refer to the documentation of `hpx::get_error_what`, `hpx::get_error_locality_id`, `hpx::get_error_host_name`, `hpx::get_error_process_id`, `hpx::get_error_function_name`, `hpx::get_error_file_name`, `hpx::get_error_line_number`, `hpx::get_error_os_thread`, `hpx::get_error_thread_id`, `hpx::get_error_thread_description`, `hpx::get_error_backtrace`, `hpx::get_error_env`, and `hpx::get_error_state`.

Lightweight error codes

Sometimes it is not desirable to collect all the ambient information about the error at the point where it happened as this might impose too much overhead for simple scenarios. In this case, *HPX* provides a lightweight error code facility that will hold the error code only. The following snippet demonstrates its use:

```
hpx::cout << "Error reporting using an lightweight error code\n";

// Create a new error_code instance.
hpx::error_code ec(hpx::throwmode::lightweight);

// If an instance of an error_code is passed as the last argument while
// invoking the action, the function will not throw in case of an error
// but store the error information in this error_code instance instead.
raise_exception_action do_it;
do_it(hpx::find_here(), ec);

if (ec)
{
    // Print just the essential error information.
    hpx::cout << "returned error: " << ec.get_message() << "\n";

    // Print all of the available diagnostic information as stored with
    // the exception.
    hpx::cout << "error code:" << ec.value() << "\n";
}

hpx::cout << std::flush;
```

All functions that retrieve other diagnostic elements from the `hpx::error_code` will fail if called with a lightweight `error_code` instance.

2.4.21 The *HPX* I/O-streams component

The *HPX* I/O-streams subsystem extends the standard C++ output streams `std::cout` and `std::cerr` to work in the distributed setting of an *HPX* application. All of the output streamed to `hpx::cout` will be dispatched to `std::cout` on the console *locality*. Likewise, all output generated from `hpx::cerr` will be dispatched to `std::cerr` on the console *locality*.

Note: All existing standard manipulators can be used in conjunction with `hpx::cout` and `hpx::cerr`.

In order to use either `hpx::cout` or `hpx::cerr`, application codes need to `#include <hpx/include/iostreams.hpp>`. For an example, please see the following ‘Hello world’ program:

```
// Including 'hpx/hpx_main.hpp' instead of the usual 'hpx/hpx_init.hpp' enables
// to use the plain C-main below as the direct main HPX entry point.
#include <hpx/hpx_main.hpp>
#include <hpx/iostream.hpp>

int main()
{
    // Say hello to the world!
```

(continues on next page)

(continued from previous page)

```

    hpx::cout << "Hello World!\n" << std::flush;
    return 0;
}

```

Additionally, those applications need to link with the `iostreams` component. When using CMake this can be achieved by using the `COMPONENT_DEPENDENCIES` parameter; for instance:

```

include(HPX_AddExecutable)

add_hpx_executable(
    hello_world
    SOURCES hello_world.cpp
    COMPONENT_DEPENDENCIES iostreams
)

```

Note: The `hpx::cout` and `hpx::cerr` streams buffer all output locally until a `std::endl` or `std::flush` is encountered. That means that no output will appear on the console as long as either of these is explicitly used.

2.4.22 Supervision dispatch

The supervision dispatch component (`hpx::supervision`, built on top of the *Supervision module* module) lets a locality discover its peers, detect when one of them has gone silent, and safely stop dispatching work to a peer that has latched a terminal lifecycle event - all without every caller needing to make an authoritative, synchronous round-trip for every dispatch.

This page describes the initialization and shutdown ordering applications must follow, the one-shot nature of peer discovery, the distinction between the locally cached peer state and the registry's authoritative state, and how that distinction shows up in the two-tier admission check used by fenced dispatch. For the detailed semantics of individual lifecycle events, `check_admission`, and `dispatch_outcome` values, see *Supervision module*; this page does not repeat that reference material. For the API reference of the dispatch-specific types and functions this component introduces - `registry`, `sentinel`, `discovery::discover_and_join`, and `dispatch_work` - see *Supervision dispatch module*.

Initialization and shutdown ordering

Supervision dispatch is brought up with a single call to `hpx::supervision::init` and torn down with a single call to `hpx::supervision::finalize`:

```

#include <hpx/supervision_dispatch.hpp>

// Blocking, one-shot startup for this locality.
hpx::supervision::init(hpx::launch::sync);

// ... application runs, dispatching fenced work to peers ...

// Cooperative, one-shot shutdown for this locality.
hpx::supervision::finalize();

```

`init()` performs, in order:

1. Creation of a local `sentinel` and `registry` component for this locality.

2. Publication of `event::started` on the sentinel - *before* either component's symbol name is registered with AGAS, so that no peer can discover and join a not-yet-started sentinel.
3. Registration of both symbol names.
4. A single `hpx::supervision::discover_and_join` pass that joins every peer registry reachable within `discovery_timeout`. Its result is a list of `joined_discovery_result` (peer paired with the shadow id its `join()` call was assigned); peers that time out mid-pass are omitted from that list entirely rather than leaving a gap in it.

`init()` is idempotent: calling it while already active is a no-op, and concurrent callers attach to a single in-flight initialization rather than racing to create duplicate sentinels/registries. `finalize()` mirrors this ordering in reverse - it publishes `event::completed` for the local sentinel, unregisters both symbol names, and releases the components - and is always safe to call speculatively (e.g. during shutdown) even if `init()` was never called, since it is a no-op unless the runtime is currently active.

Applications should treat `init()/finalize()` as a matched pair around the portion of the program that performs supervised, fenced dispatch, and should not assume any lifecycle event is visible to peers before `init()`'s future (or synchronous call) has completed.

Calling `init()` again after it has already succeeded is a documented no-op: it returns an already-ready future without repeating any of the four steps above, and in particular does **not** re-run `discover_and_join()`. Peers that started, or otherwise became discoverable, after the first `init()` call completed are *not* retroactively added to the registry by a second call - the one-shot discovery behavior described below applies equally to repeated `init()` calls, not just the first one. To pick up such a peer, join it explicitly via `registry::join()`. Calling `init()` while a previous call is still in progress attaches to that same in-flight initialization rather than starting a second one; calling it while `finalize()` is concurrently in progress fails immediately with `hpx::error::invalid_status` rather than queuing behind it.

What is a target, and how is it introduced

A “target” is nothing more than an `hpx::id_type` - the id of any locality or component whose lifecycle should be tracked. It is not a distinct kind of object, and there is no separate handle or wrapper type: the same id you'd use to invoke an action on a component is what you pass as `target` to `publish_event()`, `check_admission()`, `dispatch_work()`, and the rest of the supervision API.

Because `dispatch_work()` resolves `target` via `hpx::colocated()` to find the locality to dispatch to, a target must also be independently resolvable by AGAS to some locality - this is a separate requirement from having recorded supervision state, and it is not something supervision dispatch itself grants. Any id obtained the ordinary way (creating a component, `hpx::find_here()`, a symbolic-name lookup, a peer's joined sentinel/registry id) already satisfies this. If a target id can no longer be resolved to a locality - for instance, because the underlying component was already destroyed and unregistered - `dispatch_work()` fails when `hpx::colocated()` cannot resolve it, *before* either admission check runs; this is a distinct failure mode from `hpx::error::target_fenced` and is not something publishing `event::started` can paper over.

In practice, two kinds of ids show up as targets in this component:

- The sentinel/registry ids of peer localities, once joined via `hpx::supervision::registry::join` - these are the targets whose shadow state feeds `registry::snapshot_peers()` and local admission filtering.
- The ids of individual localities/components that fenced work is dispatched against via `hpx::supervision::dispatch_work` (`dispatch_work(target, epoch, ...)`) - these need not be peers' localities at all; any component id that has had lifecycle events published for it can be fenced.

Unlike joining a peer registry, there is no explicit “register this target” call for the underlying supervision manager. A target is introduced implicitly, purely as a side effect of publishing its first event: the supervision manager tracks targets in a map keyed by id, and a lookup miss is treated as “this target has never been seen,” with an implicit current epoch of `0` and a default event of `unknown`. The lifecycle-transition validation then requires that the *first* event ever published for

a target open with `started` - publishing anything else for a target with no prior recorded state is rejected as an invalid transition. Put simply:

```
// Introduces `some_actor` as a tracked target under epoch 0. This is the
// only step required - no prior registration call exists.
hpx::supervision::publish_event(some_actor, hpx::supervision::event::started, 0);

// From this point on, `some_actor` has recorded state: query_state(),
// check_admission(), and dispatch_work() against it now reflect that
// state rather than "unknown."
```

Before a target's first `started` publication, it has no recorded state at all: `query_state()` reports it as `unknown` rather than as any specific lifecycle stage, and `check_admission()` for an epoch-0, never-published target behaves as admitting (there is nothing latched to fence against yet). Once introduced, a target's tracked state persists on the supervision manager that owns it until either it reaches a terminal event that is superseded by a higher epoch (see "Epochs and when to change them" below), or it is explicitly forgotten via `remove_target()` - typically done by callers that know a given id will never be queried or observed again locally, e.g. after a failed registration attempt or once a peer has been evicted from the registry, to avoid accumulating unbounded per-target state.

Removing a target

`hpx::supervision::remove_target` is the counterpart to introducing a target: it unconditionally erases whatever supervision state is locally recorded for a target id, on a single locality.

```
// Synchronous version, target on a possibly remote locality:
hpx::supervision::remove_target(hpx::launch::sync, locality, target);
```

See *Supervision module* for the full semantics of `remove_target`, and *Supervision dispatch module* for this component's own API reference.

A few points worth calling out:

- **It is a forget operation, not a lifecycle event.** It erases the target's tracked state (epoch, current event, sequence number) and any observers still registered for it, without publishing an event of any kind. This is different from a target reaching a terminal event - removal discards history rather than recording an outcome.
- **It is local only.** Removal only clears state held on the given locality (or the calling locality, for the local-only overload). It does not touch target's state on any other locality, and it does not affect AGAS registration or symbolic names for that id.
- **It is safe to call on a target with no recorded state.** This is a documented no-op rather than an error, so callers do not need to first check whether a target was ever introduced before removing it.
- **Republishing afterward reintroduces the target from scratch.** After removal, publishing `event::started` for the same id behaves exactly as if the id had never been seen before - epoch resets to whatever the new `started` publication specifies.
- **Safe to call from within the target's own observer callback.** Calling `remove_target()` on target from inside one of target's own observer callbacks is supported and does not deadlock.

Removing a target is the natural cleanup step once it is known to be permanently done with - for example, once a peer has been evicted from the registry, or once a fenced target has reached a terminal event and will not be reincarnated under a new epoch - so that per-target state does not accumulate indefinitely over the lifetime of a long-running application.

Application-visible state machines

Applications observe two distinct, overlapping state machines.

Per-locality dispatcher lifecycle

Tracked once per locality (`dispatch_api.cpp`), driven by `init()/finalize()`:

```
uninitialized -> initializing -> active -> finalizing -> uninitialized
```

- **uninitialized:** no local registry exist.
- **initializing:** registry creation, `event::started` publication, symbol registration, and the one-shot `discover_and_join()` pass are in progress. Concurrent callers attach to the same in-flight initialization rather than racing.
- **active:** heartbeat and failure-detection background tasks are running.
- **finalizing:** background tasks are being stopped, `event::completed` is published, and both symbol names are being unregistered before component release.

`init()/finalize()` are idempotent no-ops when already in the target state. A failure during `initializing` unregisters any names already registered and returns to `uninitialized` rather than leaving the locality stuck mid-transition.

Per-target lifecycle event

Reported by an actor about itself (`hpx::supervision::event`), tracked per epoch and mirrored into peer shadows:

```
unknown -> started -> running -> suspending -> completed
                \-> failed
                \-> losing_locality
```

`completed` and `failed` are terminal: once published for a target/epoch, later terminal publications for that same target/epoch are rejected as already-terminal, and publications carrying a lower epoch are rejected as stale. `losing_locality` is a non-terminal warning that the hosting locality may become unavailable.

How they interact

The dispatcher-lifecycle state machine governs whether *this locality* can participate at all. The per-target event state machine governs whether *a specific peer* remains eligible for fenced dispatch. Failure detection moves a peer's locally cached shadow toward `failed` only when a timeout on `await_terminal` coincides with an unchanged event sequence number - a timeout alone is not sufficient, since the peer may simply still be `running`. This local `failed` marking never touches the peer's own authoritative state; it only affects what this locality's client-side filtering sees, per the shadow/authoritative distinction above.

Heartbeats: distinguishing idle from dead

While a locality is `active` (see “Application-visible state machines” above), a background heartbeat task runs alongside the failure-detection loop. Its job is narrow but essential: periodically republish `event::running` against the locality, purely to keep that locality’s event sequence number and timestamp advancing even when the application itself has nothing new to report.

Why this is needed

Failure detection works by calling `await_terminal()` with a timeout against each joined peer’s shadow. On its own, a bare timeout on that call is ambiguous: it fires identically whether the peer has crashed, or the peer is simply alive and quietly idle – `running` is a stable state that can legitimately persist for a long time with no events published at all. Without some independent signal of liveness, failure detection would have no way to tell these two situations apart, and would either fence peers that are perfectly healthy but quiet, or fail to fence peers that have genuinely died.

The heartbeat resolves this by giving every alive peer a steady, low-cost source of forward progress – its event sequence number – independent of whatever the application is actually doing. This lets `peer_is_alive_but_silent()` compare a peer’s sequence number immediately before and after an `await_terminal()` timeout:

- If the sequence number **advanced** during the timeout window, the peer’s heartbeat kept running, so the peer is alive but simply not reporting a terminal event - no action is taken.
- If the sequence number **did not change**, the peer’s own heartbeat task has itself gone silent, which is treated as genuine evidence of a stall, and the failure-detection loop fences the peer locally by publishing `event::failed` against its shadow (never against the peer’s own, remote, authoritative state - see “Shadow state versus the authoritative registry” above).

Operational properties

- **Best-effort.** A failed heartbeat publication attempt does not stop or crash the loop; it is simply retried on the next interval.
- **Fixed interval, tied to detection timing.** The heartbeat republishes at roughly a third of the failure-detection poll timeout, so that under normal conditions several heartbeats land within any single detection window – making a missed heartbeat a meaningful signal rather than noise from timing jitter.
- **Started and stopped in lockstep with failure detection.** Both background tasks are started together, immediately after the one-shot `discover_and_join()` pass inside `init()`, and both are signaled to stop and joined together during `finalize()`, before `event::completed` is published and either symbol name is unregistered.
- **Entirely internal.** Applications do not start, stop, or configure the heartbeat directly, and do not need to publish any events themselves to keep it running – it is a side effect of calling `init()`, and requires no ongoing application action beyond staying inside the `init()/finalize()` bracket.

In short, the heartbeat is what makes failure detection’s timeout-based stall check meaningful at all: without it, a timeout by itself would not be able to distinguish “no news” from “no pulse.”

This is also why fenced dispatch depends on the heartbeat working correctly, not just on failure detection running. `check_admission()` - whether called as the caller’s local, non-authoritative early-out or as the target’s own authoritative re-check inside `invoke_fenced_action()` - ultimately answers “is this target still available” by consulting whatever lifecycle state has been latched for it, which for peers is only ever updated to `failed` once failure detection has genuine evidence of a stall. Without the heartbeat, that evidence would not exist: a silent-but-alive peer and a genuinely dead one would look identical to `await_terminal()`, and admission would have no reliable basis for deciding whether it is safe to keep dispatching work to that locality. In short, the heartbeat is not just an internal detail of failure detection - it is what makes the fencing decisions applications rely on throughout this page trustworthy in the first place.

One-shot discovery and staleness

The `discover_and_join()` pass performed by `init()` runs exactly once. It finds whichever peer registries are reachable *at that moment* and joins them; it does not re-run periodically, and peers that join the system later are not automatically discovered by localities that have already initialized. This has two practical implications:

- A locality's set of known peers is fixed at `init()` time (plus any peers joined explicitly afterwards via `registry::join()`). It does not grow on its own as new peers appear.
- Because failure detection (see below) only tracks peers that have actually been joined, a peer that starts too late to be discovered is invisible to both admission filtering and fencing until it is joined explicitly.

Applications that need a stable, complete peer set at some later point should join peers explicitly (`registry::join()`) rather than relying on rediscovery after `init()`.

Shadow state versus the authoritative registry

Once a peer is joined, its lifecycle state is mirrored locally into a *shadow* target owned by the joining registry - a lightweight, locally readable copy of that peer's most recently observed state, updated as lifecycle and heartbeat events arrive. This shadow state is what `registry::snapshot_peers()` and the local admission check consult.

It is important to keep two things distinct:

- **Shadow state** (local): a locally cached view of a peer's lifecycle, updated asynchronously as events are received. It can lag reality by however long it takes an event to propagate, and can go stale entirely if the peer's heartbeat has stopped but failure detection has not yet timed out.
- **Registry state** (remote, authoritative): the actual lifecycle/fencing state tracked by the peer's own supervision manager, on the peer's own locality. This is the only state that is authoritative for admission decisions.

Failure detection narrows - but does not eliminate - the gap between the two: a background loop periodically checks each joined peer's shadow for silence and marks it accordingly, but there is always a window between a peer actually going silent and that silence being locally observed.

How registries stay synchronized

The shadow-mirroring described above is not maintained by polling. It is driven entirely by event-based observer callbacks, registered once at `registry::join()` time and then firing automatically for the lifetime of the joined peer.

Registration, at join time

When `registry::join(peer_locality)` is called, the local registry does two things before returning a shadow id to the caller. A peer's identity *is* its locality since exactly one registry exists per locality.

1. **Seeds the shadow with the peer's current state.** It performs a single, synchronous `query_state()` call against `peer_locality` to read whatever epoch the peer is currently in, then publishes `event::started` for that epoch onto a freshly minted shadow id. This seed step exists so the shadow reflects the peer's state as of joining, rather than starting from `unknown` and waiting for the first subsequent event to arrive.
2. **Registers a lifecycle-event observer** on `peer_locality` (via `hpx::supervision::register_observer()`), along with an activity-transition observer (via `register_activity_observer()`, currently a no-op placeholder reserved for future use). These registrations live on the peer's own locality and are what make the subsequent synchronization automatic: no further polling or explicit refresh call from the local registry is needed.

Both registrations are made atomically with respect to concurrent `join()` calls for the same peer (a reservation is taken in `peers_` before either remote call is issued), and either observer failing to register cleanly rolls back the other, so a peer is never left half-joined.

Ongoing synchronization

From then on, every event the peer publishes for itself - including the heartbeat's periodic `event::running` republication (see "Heartbeats: distinguishing idle from dead" above) - invokes the registered lifecycle observer callback on the *peer's* locality, which in turn calls back into the joining registry to mirror that event onto the local shadow, at the same epoch it actually occurred in. No round trip is initiated by the joining side to "check in" on a peer; synchronization is entirely push-driven by whichever locality actually observes the peer's own state changing.

If the mirrored event is terminal (`completed` or `failed`), the callback additionally schedules - via `hpx::post()`, deferred rather than inline, since the callback itself does not hold the registry's lock - the peer's eviction from `peers_`. Once evicted, the peer no longer appears in `registry::snapshot_peers()`, and its observer registrations are unregistered on the peer's locality so nothing is left listening for further events from a peer that has already reached a terminal state.

What this does and does not cover

This automatic synchronization keeps the shadow up to date with whatever the peer *chooses to publish* - it is not a substitute for failure detection. A peer that stops publishing anything at all (e.g. because it crashed) generates no event, so no observer callback fires, and the shadow simply stops advancing. Detecting that silence, and deciding whether it means the peer is dead rather than merely idle, is exactly the job of the heartbeat/failure-detection pairing described earlier in this page - the observer-based synchronization described here and the polling-with-timeout failure detection described earlier are complementary, not overlapping, mechanisms.

Because `observers_` is keyed per target and holds a list rather than a single callback, this fan-out is genuinely one-to-many: if several localities have each independently joined the same peer, a single event published by that peer notifies every one of their registries in the same pass, each mirroring the event onto its own local shadow. This reach is scoped to the publishing target, however - only localities that have actually called `join()` against that specific peer are registered as observers and receive its events. A locality that has not joined a given peer is not notified when that peer publishes, regardless of whether it participates in supervision dispatch generally.

Client-side filtering versus fenced-dispatch admission

This shadow/authoritative distinction is exactly why fenced dispatch performs *two* admission checks rather than one:

- **Client-side filtering** (`check_admission()` called directly by the caller, or peer filtering based on `registry::snapshot_peers()`) consults only the locally cached shadow state. It is fast and involves no remote round-trip, but its answer can be stale: it may say a peer is admitted when the peer has, in fact, already latched a terminal event that just hasn't propagated back yet. This check is an optimization - a cheap way to avoid dispatching work that is *already known locally* to be pointless - and must never be treated as authoritative.
- **Fenced-dispatch admission** (the re-check performed inside `invoke_fenced_action()`, once the dispatched action has actually reached the target's own locality via `hpx::colocated`) runs on the same locality/thread that owns the target's authoritative supervision state, with no suspension point between the check and the action invocation that follows it. This is the check that actually decides whether the wrapped action runs, and it is what closes the race between a stale client-side "admitted" result and a peer that has since gone terminal.

In short: use client-side filtering to avoid *obviously* wasted dispatches; rely only on the fenced-dispatch outcome to know whether work actually ran.

Epochs and when to change them

Every lifecycle event and every fenced dispatch is scoped to an epoch (`std::uint64_t`, defaulting to 0). The epoch is what lets a target be “un-fenced” and reused after it has latched a terminal event, instead of being permanently unusable once it completes or fails once.

A target’s epoch only ever increases, and publications are compared against whatever epoch is currently in effect for that target:

- A publication for the **same** epoch as the target’s current one is normal progression (`started` -> `running` -> ... -> a terminal event), subject to the terminal/already-terminal rule described above.
- A publication for a **lower** epoch than the target’s current one is rejected as stale (`publish_result::stale_epoch`) and has no effect - this guards against a delayed or reordered event from an earlier generation of the target clobbering newer state.
- A publication for a **higher** epoch than the target’s current one resets the target: it becomes the new current epoch, the event sequence number resets, and any previously latched terminal event (`completed/ failed`) under the old epoch no longer fences new dispatches. This is the only way to make a target eligible for fenced dispatch again after it has gone terminal.

The same epoch value is consulted end-to-end: `check_admission(target, epoch)` compares the *epoch you pass in* against the target’s current epoch, not just whether the target is terminal in some absolute sense. This is why both `dispatch_work()`’s local check and `invoke_fenced_action()`’s remote re-check take an explicit epoch argument rather than operating on “the” state of the target.

When to keep the epoch the same

Use the same epoch value across all fenced dispatches that belong to the same logical run/incarnation of the target - e.g. repeated or retried calls against a target that is still expected to be `started/running` under the epoch it was initialized with. Fencing is only meaningful when related dispatches share an epoch: if a target has already latched `failed` for epoch N, every further dispatch under epoch N is correctly rejected, which is the intended behavior - it stops work from continuing to target something that has already terminated in this generation.

When to bump the epoch

Bump to a new, higher epoch when you are intentionally starting a new generation of the target and want prior terminal state to stop fencing new work - typically when a target is restarted/reincarnated after failing or completing, and you want dispatch to resume against the restarted instance rather than remain permanently fenced by the old generation’s terminal event. Concretely: publish the target’s own `event::started` under the new epoch as part of bringing the restarted instance up, then use that same, higher epoch value for subsequent dispatches and admission checks against it.

Do not reuse an old epoch value after bumping, and do not bump the epoch merely to “clear” a fence for the *same* running instance - if the target has not actually restarted, admission is correctly rejecting dispatch because the target is genuinely terminal, and forcing an epoch bump only defeats that protection rather than fixing the underlying condition.


How fenced work is invoked

`hpx::supervision::dispatch_work<action_type>(target, epoch, action, args...)` is the entry point callers use. It performs two distinct steps, on two different localities:

1. **Local, non-authoritative early-out (caller's locality).** `dispatch_work()` first calls `check_admission(target, epoch)` against the caller's own locally cached shadow state. If this reports `dispatch_outcome::rejected_fenced`, `dispatch_work()` returns an already-exceptional future carrying `hpx::error::target_fenced` immediately - no parcel is ever sent, and the wrapped action is never invoked. This is purely an optimization to avoid a wasted round trip; it is not authoritative, since the shadow state it consults can be stale (see the sections above).
2. **Colocated dispatch and authoritative re-check (target's locality).** If the local check does not reject, `dispatch_work()` wraps the caller's action in a generated `fenced_action` and dispatches it via `hpx::async` to `hpx::colocated(target)` - i.e. it runs on the same locality that hosts `target` and owns its authoritative supervision state. The action body that actually runs there is `invoke_fenced_action()`, which performs a *second* `check_admission(target, epoch)` call. Because this call executes on the same locality/thread that owns the target's supervision state, with no suspension point before the wrapped action runs immediately afterward (via `hpx::sync`, invoked directly/locally with no further parcel hop), this second check is authoritative. If it also reports `rejected_fenced` - meaning the target latched a terminal event for this epoch sometime between the caller's stale check and this point - `invoke_fenced_action()` throws `hpx::error::target_fenced` instead of invoking the action.

Note that “dispatched to the target's locality” does not imply a network round-trip: `hpx::colocated(target)` resolves to whichever locality actually hosts `target`, including the invoking locality itself when `target` happens to be local. In that case no parcel is sent, but `invoke_fenced_action()` - and, if admitted, the wrapped action inside it - still each run on a newly spawned HPX thread rather than inline on the calling thread, exactly as an unfenced `hpx::async<Action>(target, args...)` call behaves when `target` is local: it schedules a new thread rather than invoking the action synchronously in place. The one exception, on both sides, is an action explicitly declared as a `direct_action`, which HPX is permitted to invoke inline when the target is local; `fenced_action` itself is an ordinary action, and the wrapped user `Action` follows whatever declaration the caller gave it. Either way, fenced dispatch adds only the two-tier admission check described above - it does not change whether or where the action is scheduled to run relative to unfenced dispatch.

Both the local early-out and the remote re-check surface failure as the same exception type/message shape (`hpx::error::target_fenced`), so callers handle a single error regardless of which side detected the fence:



Only `target` (not `epoch`) is forwarded into the wrapped action's own argument list; the `epoch` is fencing metadata consumed entirely by the dispatch machinery. A convenience overload of `dispatch_work()` accepts an action instance directly rather than only an action type, but follows the identical two-check flow described above.

Relationship to unfenced dispatch

From the caller's point of view, converting an unfenced dispatch into a fenced one requires exactly two changes to the call site:

```
// Unfenced:
hpx::future<result_type> f = hpx::async<Action>(target, args...);

// Fenced:
hpx::future<result_type> f =
    hpx::supervision::dispatch_work<Action>(target, epoch, args...);
```

1. Replace the call to `hpx::async<Action>` with `hpx::supervision::dispatch_work<Action>`.
2. Insert the fencing `epoch` as the second argument, ahead of the action's own arguments (`args...` is otherwise unchanged and is forwarded to `Action` verbatim).

Both a template-argument form and an instance-argument form are available for `dispatch_work()`, mirroring the two ways `hpx::async` can be called:

```
// Action specified as an explicit template argument (as above):
hpx::future<result_type> f =
    hpx::supervision::dispatch_work<Action>(target, epoch, args...);

// Convenience overload: action passed as an instance, deduced instead of
// spelled out explicitly. Note the action instance comes *first*, ahead
// of `target` and `epoch`.
hpx::future<result_type> f =
    hpx::supervision::dispatch_work(Action(), target, epoch, args...);
```

The instance-argument overload is a thin wrapper that simply forwards to the template-argument overload above; the two are otherwise identical in behavior (same two-check admission flow, same exception on fencing, same argument forwarding to `Action`). It exists purely so that call sites already holding an action instance - rather than naming the action type directly - don't need an extra step to obtain one, the same convenience `hpx::async` itself offers by accepting either an action type or an action instance.

Everything else - `target`, the returned `hpx::future<result_type>`, and how the caller consumes it (`.get()`, continuations, etc.) - stays the same. The only additional caller-side responsibility is handling `hpx::error::target_fenced` on that future (see below), since a fenced dispatch never invokes `Action` at all, whereas an unfenced `hpx::async<Action>` call has no equivalent rejection path.

Observing whether an action was fenced

From the caller's point of view, `dispatch_work()` always returns an `hpx::future`. Whether the fence was detected locally (early-out, no dispatch sent) or remotely (authoritative re-check on the target's own locality), the future becomes exceptional in exactly the same way, so callers do not need to special-case which side caught it:

```
hpx::future<result_type> f =
    hpx::supervision::dispatch_work(action, target, epoch, args...);

try
{
    result_type result = f.get();
    // Admitted on both checks; action ran and produced `result`.
```

(continues on next page)

(continued from previous page)

```

}
catch (hpx::exception const& e)
{
    if (e.get_error() == hpx::error::target_fenced)
    {
        // Fenced - either the caller's local admission check rejected
        // it before any dispatch was sent, or the target's own
        // authoritative re-check rejected it just before invocation.
        // The wrapped action was NOT invoked in either case.
    }
    else
    {
        throw;    // some other failure (e.g. transport, target action
                  // itself threw)
    }
}
}

```

Two points worth calling out explicitly:

- `e.get_error() == hpx::error::target_fenced` is the single, reliable signal that an action was fenced. Matching on the exception's `what()` text is unnecessary and discouraged, since the message wording is not part of the stable contract; only the error code is.
- A fenced result and a “the action itself threw” result are both surfaced through the same future/exception mechanism, so callers must check `get_error()` to distinguish “not invoked because fenced” from “invoked, but failed.” There is no separate return value, flag, or callback that reports fencing independently of the future's exceptional state.

Because `f.get()` throws synchronously the moment either check rejects, a caller waiting with a timeout (see below) sees ready-with-exception rather than ready-with-result if either side fenced the dispatch before the timeout elapsed.

Worked examples

Fencing a silent peer

```

#include <hpx/supervision_dispatch.hpp>

hpx::supervision::registry local_registry(hpx::find_here());

hpx::supervision::joined_peer const peer = local_registry.join(
    hpx::launch::sync, hpx::find_here());

// ... time passes; the peer's heartbeat stops ...

// Client-side filtering: cheap, but only as fresh as the last observed
// heartbeat/lifecycle event mirrored onto `shadow`.
for (auto const& peer : local_registry.snapshot_peers(hpx::launch::sync))
{
    if (peer.state == hpx::supervision::lifecycle_state::failed)
    {
        // Skip obviously-dead peers before even attempting dispatch.
        continue;
    }
}

```

(continues on next page)

(continued from previous page)

```

}
// Attempt fenced dispatch anyway; the target-side re-check inside
// invoke_fenced_action() is authoritative and will reject the action
// with hpx::error::target_fenced if the peer has latched a terminal
// event we haven't observed locally yet.
}

```

Waiting on a dispatch outcome with a timeout

```

#include <hpx/async_combinators/wait_all_for.hpp>
#include <hpx/supervision_dispatch.hpp>

hpx::future<result_type> f =
    hpx::supervision::dispatch_work(target, epoch, action, args...);

if (hpx::wait_all_for(std::chrono::seconds(5), f) ==
    hpx::future_status::ready)
{
    try
    {
        result_type result = f.get();
    }
    catch (hpx::exception const& e)
    {
        if (e.get_error() == hpx::error::target_fenced)
        {
            // Authoritative rejection: the target latched a terminal
            // event for this epoch before the action could run.
        }
    }
}
else
{
    // Dispatch did not complete within the timeout; the target may be
    // slow, unreachable, or the shadow state used for client-side
    // filtering may be stale.
}

```

Querying state and publishing events through a handle

The handle returned by `init()` also doubles as the argument to a small family of convenience overloads of `query_state()/publish_event()` that resolve locality and target automatically, instead of requiring the caller to extract `handle.get_id()` and `hpx::find_here()` manually:

```

#include <hpx/supervision_dispatch.hpp>

hpx::supervision::registry const handle =
    hpx::supervision::init(hpx::launch::sync);

```

(continues on next page)

(continued from previous page)

```
// Recover the epoch init() started this handle's locality at, for use
// with dispatch_work()/publish_event() later on.
std::uint64_t const epoch =
    hpx::supervision::query_state(hpx::launch::sync, handle).epoch;

// ... later, e.g. once this locality's own supervised work completes ...
hpx::supervision::publish_event(
    hpx::launch::sync, handle, hpx::supervision::event::completed, epoch);
```

Querying a peer's state after joining it follows the same pattern, using a `discovered_peer` in place of an explicit locality/target pair:

```
for (auto const& peer :
    hpx::supervision::discover_and_join(handle))
{
    hpx::supervision::lifecycle_state const peer_state =
        hpx::supervision::query_state(hpx::launch::sync, handle, peer);
    // `handle` is only needed here for overload resolution; `peer`
    // alone carries the locality/target this call actually queries.
}
```

There is no peer-publishing overload: a locality only ever publishes lifecycle events it self, never on behalf of a peer's.

A worked example combining this with a supervised worker loop - covering when to publish started/running/a terminal event for a worker's own locality, and how a supervisor queries peer worker state through the handle above - is available in `components/supervision_dispatch/examples/plain_worker.cpp`.

See *Supervision module* for the full semantics of `check_admission`, `dispatch_outcome`, and the individual lifecycle events referenced above, and *Supervision dispatch module* for the API reference of this component's own types and functions (`registry`, `sentinel`, `discovery`, and `dispatch_work`).

2.4.23 Troubleshooting

Common issues

This section contains commonly encountered problems when compiling or using HPX.

See also the closed issues on [GitHub](https://github.com/TheHPXProject/hpx/issues?q=is%3Aissue+is%3Aclosed)²⁰² to find out how other people resolved a similar problem. If nothing of that works, you can also open a new issue on [GitHub](https://github.com/TheHPXProject/hpx/issues)²⁰³ or contact us using one the options found in [Support for deploying and using HPX](#)²⁰⁴.

²⁰² <https://github.com/TheHPXProject/hpx/issues?q=is%3Aissue+is%3Aclosed>

²⁰³ <https://github.com/TheHPXProject/hpx/issues>

²⁰⁴ <https://github.com/TheHPXProject/hpx/blob/master/.github/SUPPORT.md>

`hpx::iostreams_component` target not found

You may see a [CMake](#)²⁰⁵ error message that looks a bit like this:

```
error: `hpx::iostreams_component` target not found
```

Simply ensure that *HPX* is installed with `HPX_WITH_DISTRIBUTED_RUNTIME=ON` to prevent encountering such error(s). This is required if you want to use `hpx::cout`.

Undefined reference to `hpx::cout`

You may see a linker error message that looks a bit like this:

```
hello_world.cpp:(.text+0x5aa): undefined reference to `hpx::cout'
```

This usually happens if you are trying to use *HPX* iostreams functionality such as `hpx::cout` but are not linking against it. The iostreams functionality is not part of the core *HPX* library, and must be linked to explicitly. Typically this can be solved by adding `COMPONENT_DEPENDENCIES iostreams` to a call to `add_hpx_library/add_hpx_executable/hpx_setup_target` if using [CMake](#)²⁰⁶. See *Creating HPX projects* for more details.

Build fails with ASIO error

You may see an error message that looks a bit like this:

```
Cannot open include file asio/io_context.hpp
```

This can be resolved by using `-DHPX_WITH_FETCH_ASIO=ON` to the `cmake` command line.

See also the corresponding closed [Issue #5404](#)²⁰⁷ for more information.

Build fails with TCMalloc error

You may see an error message that looks a bit like this:

```
Could NOT find TCMalloc (missing: Tcmalloc_LIBRARY Tcmalloc_INCLUDE_DIR)
ERROR: HPX_WITH_MALLOC was set to tcmalloc, but tcmalloc could not be
found. Valid options for HPX_WITH_MALLOC are: system, tcmalloc, jemalloc,
mimalloc, tbbmalloc, and custom
```

This can be resolved either by defining `HPX_WITH_MALLOC=system` or by installing TCMalloc. This error occurs when users don't specify an option for `HPX_WITH_MALLOC`; in that case, *HPX* will be looking `tcmalloc`, which is the default value.

²⁰⁵ <https://www.cmake.org>

²⁰⁶ <https://www.cmake.org>

²⁰⁷ <https://github.com/TheHPXProject/hpx/issues/5404>

Useful suggestions

Reducing compilation time

If you want to significantly reduce compilation time, you can just use the local part of *HPX* for parallelism by disabling the distributed functionality. Moreover, you can avoid compiling examples. These can be done with the following flags:

```
-DHPX_WITH_NETWORKING=OFF
-DHPX_WITH_DISTRIBUTED_RUNTIME=OFF
-DHPX_WITH_EXAMPLES=OFF
-DHPX_WITH_TESTS=OFF
```

Linking *HPX* to your application

If you want to avoid installing and linking *HPX*, you can just build *HPX* and then use the following flag on your *HPX* application CMake configuration:

```
-DHPX_DIR=<build_dir>/lib/cmake/HPX
```

Note: For this to work you need not to specify `-DCMAKE_INSTALL_PREFIX` when building *HPX*.

HPX-application build type conformance

Your application's build type should align with the *HPX* build type. For example, if you specified `-DCMAKE_BUILD_TYPE=Debug` during the *HPX* compilation, then your application needs to be compiled with the same flag. We recommend keeping a separate build folder for different build types and just point accordingly to the type you want by using `-DHPX_DIR=<build_dir>/lib/cmake/HPX`.

2.5 Terminology

This section gives definitions for some of the terms used throughout the *HPX* documentation and source code.

Locality

A locality in *HPX* describes a synchronous domain of execution, or the domain of bounded upper response time. This normally is just a single node in a cluster or a NUMA domain in a SMP machine.

Active Global Address Space

AGAS

HPX incorporates a global address space. Any executing thread can access any object within the domain of the parallel application with the caveat that it must have appropriate access privileges. The model does not assume that global addresses are cache coherent; all loads and stores will deal directly with the site of the target object. All global addresses within a Synchronous Domain are assumed to be cache coherent for those processor cores that incorporate transparent caches. The Active Global Address Space used by *HPX* differs from research PGAS²⁰⁸ models. Partitioned Global Address Space is passive in their means of address translation. Copy semantics, distributed compound operations, and affinity relationships are some of the global functionality supported by AGAS.

²⁰⁸ <https://www.pgas.org/>

Process

The concept of the “process” in *HPX* is extended beyond that of either sequential execution or communicating sequential processes. While the notion of process suggests action (as do “function” or “subroutine”) it has a further responsibility of context, that is, the logical container of program state. It is this aspect of operation that process is employed in *HPX*. Furthermore, referring to “parallel processes” in *HPX* designates the presence of parallelism within the context of a given process, as well as the coarse grained parallelism achieved through concurrency of multiple processes of an executing user job. *HPX* processes provide a hierarchical name space within the framework of the active global address space and support multiple means of internal state access from external sources.

Parcel

The Parcel is a component in *HPX* that communicates data, invokes an action at a distance, and distributes flow-control through the migration of continuations. Parcels bridge the gap of asynchrony between synchronous domains while maintaining symmetry of semantics between local and global execution. Parcels enable message-driven computation and may be seen as a form of “active messages”. Other important forms of message-driven computation predating active messages include [dataflow tokens](#)²⁰⁹, the *J-machine*’s²¹⁰ support for remote method instantiation, and at the coarse grained variations of Unix remote procedure calls, among others. This enables work to be moved to the data as well as performing the more common action of bringing data to the work. A parcel can cause actions to occur remotely and asynchronously, among which are the creation of threads at different system nodes or synchronous domains.

Local Control Object

Lightweight Control Object

LCO

A local control object (sometimes called a lightweight control object) is a general term for the synchronization mechanisms used in *HPX*. Any object implementing a certain concept can be seen as an LCO. This concept encapsulates the ability to be triggered by one or more events which when taking the object into a predefined state will cause a thread to be executed. This could either create a new thread or resume an existing thread.

The LCO is a family of synchronization functions potentially representing many classes of synchronization constructs, each with many possible variations and multiple instances. The LCO is sufficiently general that it can subsume the functionality of conventional synchronization primitives such as spinlocks, mutexes, semaphores, and global barriers. However due to the rich concept an LCO can represent powerful synchronization and control functionality not widely employed, such as dataflow and futures (among others), which open up enormous opportunities for rich diversity of distributed control and operation.

See *lcops* for more details on how to use LCOs in *HPX*.

Action

An action is a function that can be invoked remotely. In *HPX* a plain function can be made into an action using a macro. See *applying_actions* for details on how to use actions in *HPX*.

Component

A component is a C++ object which can be accessed remotely. A component can also contain member functions which can be invoked remotely. These are referred to as component actions. See *Writing components* for details on how to use components in *HPX*.

²⁰⁹ http://en.wikipedia.org/wiki/Dataflow_architecture

²¹⁰ <http://en.wikipedia.org/wiki/J%E2%80%93Machine>

2.6 Why HPX?

Current advances in high performance computing (HPC) continue to suffer from the issues plaguing parallel computation. These issues include, but are not limited to, ease of programming, inability to handle dynamically changing workloads, scalability, and efficient utilization of system resources. Emerging technological trends such as multi-core processors further highlight limitations of existing parallel computation models. To mitigate the aforementioned problems, it is necessary to rethink the approach to parallelization models. ParalleX contains mechanisms such as multi-threading, *parcels*, *global name space* support, percolation and *local control objects (LCO)*. By design, ParalleX overcomes limitations of current models of parallelism by alleviating contention, latency, overhead and starvation. With ParalleX, it is further possible to increase performance by at least an order of magnitude on challenging parallel algorithms, e.g., dynamic directed graph algorithms and adaptive mesh refinement methods for astrophysics. An additional benefit of ParalleX is fine-grained control of power usage, enabling reductions in power consumption.

2.6.1 ParalleX—a new execution model for future architectures

ParalleX is a new parallel execution model that offers an alternative to the conventional computation models, such as message passing. ParalleX distinguishes itself by:

- Split-phase transaction model
- Message-driven
- Distributed shared memory (not cache coherent)
- Multi-threaded
- Futures synchronization
- *Local Control Objects (LCOs)*
- Synchronization for anonymous producer-consumer scenarios
- Percolation (pre-staging of task data)

The ParalleX model is intrinsically latency hiding, delivering an abundance of variable-grained parallelism within a hierarchical namespace environment. The goal of this innovative strategy is to enable future systems delivering very high efficiency, increased scalability and ease of programming. ParalleX can contribute to significant improvements in the design of all levels of computing systems and their usage from application algorithms and their programming languages to system architecture and hardware design together with their supporting compilers and operating system software.

2.6.2 What is HPX?

High Performance ParalleX (*HPX*) is the first runtime system implementation of the ParalleX execution model. The *HPX* runtime software package is a modular, feature-complete, and performance-oriented representation of the ParalleX execution model targeted at conventional parallel computing architectures, such as SMP nodes and commodity clusters. It is academically developed and freely available under an open source license. We provide *HPX* to the community for experimentation and application to achieve high efficiency and scalability for dynamic adaptive and irregular computational problems. *HPX* is a C++ library that supports a set of critical mechanisms for dynamic adaptive resource management and lightweight task scheduling within the context of a global address space. It is solidly based on many years of experience in writing highly parallel applications for HPC systems.

The two-decade success of the communicating sequential processes (CSP) execution model and its message passing interface (MPI) programming model have been seriously eroded by challenges of power, processor core complexity, multi-core sockets, and heterogeneous structures of GPUs. Both efficiency and scalability for some current (strong scaled) applications and future Exascale applications demand new techniques to expose new sources of algorithm parallelism and exploit unused resources through adaptive use of runtime information.

The ParalleX execution model replaces CSP to provide a new computing paradigm embodying the governing principles for organizing and conducting highly efficient scalable computations greatly exceeding the capabilities of today's problems. *HPX* is the first practical, reliable, and performance-oriented runtime system incorporating the principal concepts of the ParalleX model publicly provided in open source release form.

HPX is designed by the STE||AR²¹¹ Group (Systems Technology, Emergent Parallelism, and Algorithm Research) at Louisiana State University (LSU)²¹²'s Center for Computation and Technology (CCT)²¹³ to enable developers to exploit the full processing power of many-core systems with an unprecedented degree of parallelism. STE||AR²¹⁴ is a research group focusing on system software solutions and scientific application development for hybrid and many-core hardware architectures.

For more information about the STE||AR²¹⁵ Group, see *People*.

2.6.3 What makes our systems slow?

Estimates say that we currently run our computers at well below 100% efficiency. The theoretical peak performance (usually measured in FLOPS²¹⁶—floating point operations per second) is much higher than any practical peak performance reached by any application. This is particularly true for highly parallel hardware. The more hardware parallelism we provide to an application, the better the application must scale in order to efficiently use all the resources of the machine. Roughly speaking, we distinguish two forms of scalability: strong scaling (see Amdahl's Law²¹⁷) and weak scaling (see Gustafson's Law²¹⁸). Strong scaling is defined as how the solution time varies with the number of processors for a fixed **total** problem size. It gives an estimate of how much faster we can solve a particular problem by throwing more resources at it. Weak scaling is defined as how the solution time varies with the number of processors for a fixed problem size **per processor**. In other words, it defines how much more data can we process by using more hardware resources.

In order to utilize as much hardware parallelism as possible an application must exhibit excellent strong and weak scaling characteristics, which requires a high percentage of work executed in parallel, i.e., using multiple threads of execution. Optimally, if you execute an application on a hardware resource with *N* processors it either runs *N* times faster or it can handle *N* times more data. Both cases imply 100% of the work is executed on all available processors in parallel. However, this is just a theoretical limit. Unfortunately, there are more things that limit scalability, mostly inherent to the hardware architectures and the programming models we use. We break these limitations into four fundamental factors that make our systems *SLOW*:

- **Starvation** occurs when there is insufficient concurrent work available to maintain high utilization of all resources.
- **Latencies** are imposed by the time-distance delay intrinsic to accessing remote resources and services.
- **Overhead** is work required for the management of parallel actions and resources on the critical execution path, which is not necessary in a sequential variant.
- **Waiting** for contention resolution is the delay due to the lack of availability of oversubscribed shared resources.

Each of those four factors manifests itself in multiple and different ways; each of the hardware architectures and programming models expose specific forms. However, the interesting part is that all of them are limiting the scalability of applications no matter what part of the hardware jungle we look at. Hand-helds, PCs, supercomputers, or the cloud, all suffer from the reign of the 4 horsemen: **Starvation**, **Latency**, **Overhead**, and **Contention**. This realization is very important as it allows us to derive the criteria for solutions to the scalability problem from first principles, and it allows us to focus our analysis on very concrete patterns and measurable metrics. Moreover, any derived results will be applicable to a wide variety of targets.

²¹¹ <https://stellar-group.org>

²¹² <https://www.lsu.edu>

²¹³ <https://www.cct.lsu.edu>

²¹⁴ <https://stellar-group.org>

²¹⁵ <https://stellar-group.org>

²¹⁶ <http://en.wikipedia.org/wiki/FLOPS>

²¹⁷ http://en.wikipedia.org/wiki/Amdahl%27s_law

²¹⁸ http://en.wikipedia.org/wiki/Gustafson%27s_law

2.6.4 Technology demands new response

Today's computer systems are designed based on the initial ideas of [John von Neumann](#)²¹⁹, as published back in 1945, and later extended by the [Harvard architecture](#)²²⁰. These ideas form the foundation, the execution model, of computer systems we use currently. However, a new response is required in the light of the demands created by today's technology.

So, what are the overarching objectives for designing systems allowing for applications to scale as they should? In our opinion, the main objectives are:

- Performance: as previously mentioned, scalability and efficiency are the main criteria people are interested in.
- Fault tolerance: the low expected mean time between failures ([MTBF](#)²²¹) of future systems requires embracing faults, not trying to avoid them.
- Power: minimizing energy consumption is a must as it is one of the major cost factors today, and will continue to rise in the future.
- Generality: any system should be usable for a broad set of use cases.
- Programmability: for programmer this is a very important objective, ensuring long term platform stability and portability.

What needs to be done to meet those objectives, to make applications scale better on tomorrow's architectures? Well, the answer is almost obvious: we need to devise a new execution model—a set of governing principles for the holistic design of future systems—targeted at minimizing the effect of the outlined **SLOW** factors. Everything we create for future systems, every design decision we make, every criteria we apply, have to be validated against this single, uniform metric. This includes changes in the hardware architecture we prevalently use today, and it certainly involves new ways of writing software, starting from the operating system, runtime system, compilers, and at the application level. However, the key point is that all those layers have to be co-designed; they are interdependent and cannot be seen as separate facets. The systems we have today have been evolving for over 50 years now. All layers function in a certain way, relying on the other layers to do so. But we do not have the time to wait another 50 years for a new coherent system to evolve. The new paradigms are needed now—therefore, co-design is the key.

2.6.5 Governing principles applied while developing HPX

As it turns out, we do not have to start from scratch. Not everything has to be invented and designed anew. Many of the ideas needed to combat the 4 horsemen already exist, many for more than 30 years. All it takes is to gather them into a coherent approach. We'll highlight some of the derived principles we think to be crucial for defeating **SLOW**. Some of those are focused on high-performance computing, others are more general.

Focus on latency hiding instead of latency avoidance

It is impossible to design a system exposing zero latencies. In an effort to come as close as possible to this goal many optimizations are mainly targeted towards minimizing latencies. Examples for this can be seen everywhere, such as low latency network technologies like [InfiniBand](#)²²², caching memory hierarchies in all modern processors, the constant optimization of existing [MPI](#)²²³ implementations to reduce related latencies, or the data transfer latencies intrinsic to the way we use [GPGPU](#)s²²⁴ today. It is important to note that existing latencies are often tightly related to some resource having to wait for the operation to be completed. At the same time it would be perfectly fine to do some other, unrelated work in the meantime, allowing the system to hide the latencies by filling the idle-time with useful work. Modern systems already employ similar techniques (pipelined instruction execution in the processor cores,

²¹⁹ <http://qss.stanford.edu/~godfrey/vonNeumann/vnedvac.pdf>

²²⁰ http://en.wikipedia.org/wiki/Harvard_architecture

²²¹ http://en.wikipedia.org/wiki/Mean_time_between_failures

²²² <http://en.wikipedia.org/wiki/InfiniBand>

²²³ https://en.wikipedia.org/wiki/Message_Passing_Interface

²²⁴ <http://en.wikipedia.org/wiki/GPGPU>

asynchronous input/output operations, and many more). What we propose is to go beyond anything we know today and to make latency hiding an intrinsic concept of the operation of the whole system stack.

Embrace fine-grained parallelism instead of heavyweight threads

If we plan to hide latencies even for very short operations, such as fetching the contents of a memory cell from main memory (if it is not already cached), we need to have very lightweight threads with extremely short context switching times, optimally executable within one cycle. Granted, for mainstream architectures, this is not possible today (even if we already have special machines supporting this mode of operation, such as the [Cray XMT](http://en.wikipedia.org/wiki/Cray_XMT)²²⁵). For conventional systems, however, the smaller the overhead of a context switch and the finer the granularity of the threading system, the better will be the overall system utilization and its efficiency. For today's architectures we already see a flurry of libraries providing exactly this type of functionality: non-pre-emptive, task-queue based parallelization solutions, such as [Intel Threading Building Blocks \(TBB\)](https://www.threadingbuildingblocks.org/)²²⁶, [Microsoft Parallel Patterns Library \(PPL\)](https://msdn.microsoft.com/en-us/library/dd492418.aspx)²²⁷, [Cilk++](https://software.intel.com/en-us/articles/intel-cilk-plus/)²²⁸, and many others. The possibility to suspend a current task if some preconditions for its execution are not met (such as waiting for I/O or the result of a different task), seamlessly switching to any other task which can continue, and to reschedule the initial task after the required result has been calculated, which makes the implementation of latency hiding almost trivial.

Rediscover constraint-based synchronization to replace global barriers

The code we write today is riddled with implicit (and explicit) global barriers. By “global barriers,” we mean the synchronization of the control flow between several (very often all) threads (when using [OpenMP](https://openmp.org/wp/)²²⁹) or processes ([MPI](https://en.wikipedia.org/wiki/Message_Passing_Interface)²³⁰). For instance, an implicit global barrier is inserted after each loop parallelized using [OpenMP](https://openmp.org/wp/)²³¹ as the system synchronizes the threads used to execute the different iterations in parallel. In [MPI](https://en.wikipedia.org/wiki/Message_Passing_Interface)²³² each of the communication steps imposes an explicit barrier onto the execution flow as (often all) nodes have to be synchronized. Each of those barriers is like the eye of a needle the overall execution is forced to be squeezed through. Even minimal fluctuations in the execution times of the parallel threads (jobs) causes them to wait. Additionally, it is often only one of the executing threads that performs the actual reduce operation, which further impedes parallelism. A closer analysis of a couple of key algorithms used in science applications reveals that these global barriers are not always necessary. In many cases it is sufficient to synchronize a small subset of the threads. Any operation should proceed whenever the preconditions for its execution are met, and only those. Usually there is no need to wait for iterations of a loop to finish before you can continue calculating other things; all you need is to complete the iterations that produce the required results for the next operation. Good bye global barriers, hello constraint based synchronization! People have been trying to build this type of computing (and even computers) since the 1970s. The theory behind what they did is based on ideas around static and dynamic dataflow. There are certain attempts today to get back to those ideas and to incorporate them with modern architectures. For instance, a lot of work is being done in the area of constructing dataflow-oriented execution trees. Our results show that employing dataflow techniques in combination with the other ideas, as outlined herein, considerably improves scalability for many problems.

²²⁵ http://en.wikipedia.org/wiki/Cray_XMT

²²⁶ <https://www.threadingbuildingblocks.org/>

²²⁷ <https://msdn.microsoft.com/en-us/library/dd492418.aspx>

²²⁸ <https://software.intel.com/en-us/articles/intel-cilk-plus/>

²²⁹ <https://openmp.org/wp/>

²³⁰ https://en.wikipedia.org/wiki/Message_Passing_Interface

²³¹ <https://openmp.org/wp/>

²³² https://en.wikipedia.org/wiki/Message_Passing_Interface

Adaptive locality control instead of static data distribution

While this principle seems to be a given for single desktop or laptop computers (the operating system is your friend), it is everything but ubiquitous on modern supercomputers, which are usually built from a large number of separate nodes (i.e., Beowulf clusters), tightly interconnected by a high-bandwidth, low-latency network. Today's prevalent programming model for those is MPI, which does not directly help with proper data distribution, leaving it to the programmer to decompose the data to all of the nodes the application is running on. There are a couple of specialized languages and programming environments based on PGAS²³³ (Partitioned Global Address Space) designed to overcome this limitation, such as Chapel²³⁴, X10²³⁵, UPC²³⁶, or Fortress²³⁷. However, all systems based on PGAS rely on static data distribution. This works fine as long as this static data distribution does not result in heterogeneous workload distributions or other resource utilization imbalances. In a distributed system these imbalances can be mitigated by migrating part of the application data to different localities (nodes). The only framework supporting (limited) migration today is Charm++²³⁸. The first attempts towards solving related problem go back decades as well, a good example is the Linda coordination language²³⁹. Nevertheless, none of the other mentioned systems support data migration today, which forces the users to either rely on static data distribution and live with the related performance hits or to implement everything themselves, which is very tedious and difficult. We believe that the only viable way to flexibly support dynamic and adaptive *locality* control is to provide a global, uniform address space to the applications, even on distributed systems.

Prefer moving work to the data over moving data to the work

For the best performance it seems obvious to minimize the amount of bytes transferred from one part of the system to another. This is true on all levels. At the lowest level we try to take advantage of processor memory caches, thus, minimizing memory latencies. Similarly, we try to amortize the data transfer time to and from GPGPUs²⁴⁰ as much as possible. At high levels we try to minimize data transfer between different nodes of a cluster or between different virtual machines on the cloud. Our experience (well, it's almost common wisdom) shows that the amount of bytes necessary to encode a certain operation is very often much smaller than the amount of bytes encoding the data the operation is performed upon. Nevertheless, we still often transfer the data to a particular place where we execute the operation just to bring the data back to where it came from afterwards. As an example let's look at the way we usually write our applications for clusters using MPI. This programming model is all about data transfer between nodes. MPI is the prevalent programming model for clusters, and it is fairly straightforward to understand and to use. Therefore, we often write applications in a way that accommodates this model, centered around data transfer. These applications usually work well for smaller problem sizes and for regular data structures. The larger the amount of data we have to churn and the more irregular the problem domain becomes, the worse the overall machine utilization and the (strong) scaling characteristics become. While it is not impossible to implement more dynamic, data driven, and asynchronous applications using MPI, it is somewhat difficult to do so. At the same time, if we look at applications that prefer to execute the code close to the *locality* where the data was placed, i.e., utilizing active messages (for instance based on Charm++²⁴¹), we see better asynchrony, simpler application codes, and improved scaling.

²³³ <https://www.pgas.org/>

²³⁴ <https://chapel.cray.com/>

²³⁵ <https://x10-lang.org/>

²³⁶ <https://upc.lbl.gov/>

²³⁷ <https://labs.oracle.com/projects/plrg/Publications/index.html>

²³⁸ <https://charm.cs.uiuc.edu/>

²³⁹ [http://en.wikipedia.org/wiki/Linda_\(coordination_language\)](http://en.wikipedia.org/wiki/Linda_(coordination_language))

²⁴⁰ <http://en.wikipedia.org/wiki/GPGPU>

²⁴¹ <https://charm.cs.uiuc.edu/>

Favor message driven computation over message passing

Today's prevalently used programming model on parallel (multi-node) systems is MPI. It is based on message passing, as the name implies, which means that the receiver has to be aware of a message about to come in. Both codes, the sender and the receiver, have to synchronize in order to perform the communication step. Even the newer, asynchronous interfaces require explicitly coding the algorithms around the required communication scheme. As a result, everything but the most trivial MPI applications spends a considerable amount of time waiting for incoming messages, thus, causing starvation and latencies to impede full resource utilization. The more complex and more dynamic the data structures and algorithms become, the larger the adverse effects. The community discovered message-driven and data-driven methods of implementing algorithms a long time ago, and systems such as Charm++²⁴² have already integrated active messages demonstrating the validity of the concept. Message-driven computation allows for sending messages without requiring the receiver to actively wait for them. Any incoming message is handled asynchronously and triggers the encoded action by passing along arguments and—possibly—continuations. HPX combines this scheme with work-queue based scheduling as described above, which allows the system to almost completely overlap any communication with useful work, thereby minimizing latencies.

2.7 Additional material

- 2-day workshop held at CSCS in 2016
 - Recorded lectures²⁴³
 - Slides²⁴⁴
- Tutorials repository²⁴⁵
- C++ Lectures <https://www.youtube.com/playlist?list=PL7vEgTL3FalY2eBxudIwsfz8OKvE9sd_z>
- Parallel C++ for Scientific Applications Lectures <<https://www.youtube.com/watch?v=RdmXiilArM&list=PL7vEgTL3Falab59uJ>>
- STE||AR Group blog posts²⁴⁶
- Basic HPX recipes
 - Exporting a free function from a shared library which lives in a namespace, to use as Action²⁴⁷
 - Turning a struct or class into a component and use it's methods²⁴⁸
 - Creating and referencing components in hpx²⁴⁹

²⁴² <https://charm.cs.uiuc.edu/>

²⁴³ <https://www.youtube.com/playlist?list=PL1tk5lGm7zvSXfS-sqOOmIJ0lFNjKze18>

²⁴⁴ <https://github.com/STELLAR-GROUP/tutorials/tree/master/cscs2016>

²⁴⁵ <https://github.com/STELLAR-GROUP/tutorials>

²⁴⁶ <http://stellar-group.org/blog/>

²⁴⁷ <https://gitlab.com/-/snippets/1821389>

²⁴⁸ <https://gitlab.com/-/snippets/1822983>

²⁴⁹ <https://gitlab.com/-/snippets/1828131>

2.8 Overview

HPX is organized into different sub-libraries and those in turn into modules. The libraries and modules are independent, with clear dependencies and no cycles. As an end-user, the use of these libraries is completely transparent. If you use e.g. `add_hpx_executable` to create a target in your project you will automatically get all modules as dependencies. See below for a list of the available libraries and modules. Currently these are nothing more than an internal grouping and do not affect usage. They cannot be consumed individually at the moment.

Note: There is a dependency report that displays useful information about the structure of the code. It is available for each commit at [HPX Dependency report](#).

2.8.1 Core modules

affinity

The affinity module contains helper functionality for mapping worker threads to hardware resources.

See the *API reference* of the module for more details.

algorithms

The algorithms module exposes the full set of algorithms defined by the C++ standard. There is also partial support for C++ ranges.

See the *API reference* of the module for more details.

allocator_support

This module provides utilities for allocators. It contains `hpx::util::internal_allocator` which directly forwards allocation calls to `jemalloc`. This utility is mainly useful on Windows.

See the *API reference* of the module for more details.

asio

The asio module is a thin wrapper around the [Boost.Asio](#)²⁵⁰ library, providing a few additional helper functions.

See the *API reference* of the module for more details.

²⁵⁰ https://www.boost.org/doc/libs/release/doc/html/boost_asio.html

assertion

The assertion library implements the macros `HPX_ASSERT` and `HPX_ASSERT_MSG`. Those two macros can be used to implement assertions which are turned off during a release build.

By default, the location and function where the assert has been called from are displayed when the assertion fires. This behavior can be modified by using `hpx::assertion::set_assertion_handler`. When HPX initializes, it uses this function to specify a more elaborate assertion handler. If your application needs to customize this, it needs to do so before calling `hpx::init`, `hpx_main` or using the C-main wrappers.

See the *API reference* of the module for more details.

async_base

The `async_base` module defines the basic functionality for spawning tasks on thread pools. This module does not implement any functionality on its own, but is extended by `async_local` and `async_distributed` with implementations for the local and distributed cases.

See the *API reference* of this module for more details.

async_combinators

This module contains combinators for futures. The `when_*` functions allow you to turn multiple futures into a single future which is ready when all, any, some, or each of the given futures are ready. The `wait_*` combinators are equivalent to the `when_*` functions except that they do not return a future. Those wait for all futures to become ready before returning to the user. Note that the `wait_*` functions will rethrow one of the exceptions from exceptional futures. The `wait_*_nothrow` combinators are equivalent to the `wait_*` functions exception that they do not throw if one of the futures has become exceptional.

The `split_future` combinator takes a single future of a container (e.g. `tuple`) and turns it into a container of futures.

See `lcos_local`, `synchronization`, and `async_distributed` for other synchronization facilities.

See the *API reference* of this module for more details.

async_cuda

This library adds a simple API that enables the user to retrieve a future from a [CUDA](https://www.nvidia.com/object/cuda_home_new.html)²⁵¹ stream. Typically, a user may launch one or more kernels and then get a future from the stream that will become ready when those kernels have completed. It is important to note that multiple kernels may be launched without fetching a future, and multiple futures may be obtained from the helper. Please refer to the unit tests and examples for further examples.

See the *API reference* of this module for more details.

²⁵¹ https://www.nvidia.com/object/cuda_home_new.html

async_local

This module extends *async_base* to provide local implementations of `hpx::async`, `hpx::post`, `hpx::sync`, and `hpx::dataflow`. The *async_distributed* module extends the functionality in this module to work with *actions*.

See the API reference of this module for more details.

async_mpi

The MPI library is intended to simplify the process of integrating [MPI²⁵²](https://en.wikipedia.org/wiki/Message_Passing_Interface) based codes with the *HPX* runtime. Any MPI function that is asynchronous and uses an `MPI_Request` may be converted into an `hpx::future`. The syntax is designed to allow a simple replacement of the MPI call with a futurized async version that accepts an executor instead of a communicator, and returns a future instead of assigning a request. Typically, an MPI call of the form

```
int MPI_Isend(buf, count, datatype, rank, tag, comm, request);
```

becomes

```
hpx::future<int> f = hpx::async(executor, MPI_Isend, buf, count, datatype, rank, tag);
```

When the MPI operation is complete, the future will become ready. This allows communication to be integrated cleanly with the rest of *HPX*, in particular the continuation style of programming may be used to build up more complex code. Consider the following example, that chains user processing, sends and receives using continuations...

```
// create an executor for MPI dispatch
hpx::mpi::experimental::executor exec(MPI_COMM_WORLD);

// post an asynchronous receive using MPI_Irecv
hpx::future<int> f_recv = hpx::async(
    exec, MPI_Irecv, &data, rank, MPI_INT, rank_from, i);

// attach a continuation to run when the recv completes,
f_recv.then([=, &tokens, &counter](auto&&)
{
    // call an application specific function
    msg_recv(rank, size, rank_to, rank_from, tokens[i], i);

    // send a new message
    hpx::future<int> f_send = hpx::async(
        exec, MPI_Isend, &tokens[i], 1, MPI_INT, rank_to, i);

    // when that send completes
    f_send.then([=, &tokens, &counter](auto&&)
    {
        // call an application specific function
        msg_send(rank, size, rank_to, rank_from, tokens[i], i);
    });
});
```

The example above makes use of `MPI_Isend` and `MPI_Irecv`, but *any* MPI function that uses requests may be futurized in this manner. The following is a (non exhaustive) list of MPI functions that *should* be supported, though not all have been tested at the time of writing (please report any problems to the issue tracker).

²⁵² https://en.wikipedia.org/wiki/Message_Passing_Interface

```
int MPI_Isend(...);
int MPI_Ibsend(...);
int MPI_Issend(...);
int MPI_Irsend(...);
int MPI_Irecv(...);
int MPI_Imrecv(...);
int MPI_Ibarrier(...);
int MPI_Ibcast(...);
int MPI_Igather(...);
int MPI_Igatherv(...);
int MPI_Iscatter(...);
int MPI_Iscatterv(...);
int MPI_Iallgather(...);
int MPI_Iallgatherv(...);
int MPI_Ialltoall(...);
int MPI_Ialltoallv(...);
int MPI_Ialltoallw(...);
int MPI_Ireduce(...);
int MPI_Iallreduce(...);
int MPI_Ireduce_scatter(...);
int MPI_Ireduce_scatter_block(...);
int MPI_Iscan(...);
int MPI_Iexscan(...);
int MPI_Ineighbor_allgather(...);
int MPI_Ineighbor_allgatherv(...);
int MPI_Ineighbor_alltoall(...);
int MPI_Ineighbor_alltoallv(...);
int MPI_Ineighbor_alltoallw(...);
```

Note that the *HPX* mpi futurization wrapper should work with *any* asynchronous MPI call, as long as the function signature has the last two arguments `MPI_xxx(..., MPI_Comm comm, MPI_Request *request)` - internally these two parameters will be substituted by the executor and future data parameters that are supplied by template instantiations inside the `hpx::mpi` code.

See the API reference of this module for more details.

async_sycl

This module allows creating HPX futures using [SYCL](https://en.wikipedia.org/wiki/SYCL)²⁵³ events, effectively integrating asynchronous SYCL kernels and memory transfers with HPX. Building on this integration, this module also contains a SYCL executor. This executor encapsulates a SYCL queue. When SYCL queue member functions are launched with this executor, the user can automatically obtain the HPX futures associated with them.

The creation of the HPX futures using SYCL events is based on the same event polling mechanism that the CUDA HPX integration uses. Each registered event gets an associated callback and gets inserted into a callback vector to be polled by the scheduler in between tasks. Once the polling reveals the event is complete, the callback will be called, which in turn sets the future to ready (see `sycl_event_callback.cpp`). There are multiple adaptations for HipSYCL for this: To keep the runtime alive (avoiding the repeated on-the-fly creation of the runtime during the polling), we keep a default queue. Furthermore, we flush the internal SYCL DAG to ensure that the launched SYCL function is actually being executed.

The SYCL executor offers the usual `post` and `async_execute` functions. Additionally, it contains two `get_future` functions. One expects a pre-existing SYCL event to return a future, the other one does not but will launch an empty SYCL kernel instead, to obtain an event (causing higher overhead for the sake of being more convenient). The `post` and

²⁵³ <https://en.wikipedia.org/wiki/SYCL>

async_execute implementations here are actually different for HipSYCL and OneAPI, since the sycl::queue in OneAPI uses a different interface (using a code_location parameter) which requires some adaptations here.

To make this module compile, we use the -fno-sycl and -fsycl compiler parameters for the OneAPI use-case (requiring HPX to be compiled with dpcpp). For HipSYCL we use its cmake integration instead (requiring HPX to be compiled with clang++ and including HipSYCL as a library).

To build with OneAPI, use the CMake Variable HPX_WITH_SYCL=ON. To build with HipSYCL, use HPX_WITH_SYCL=ON and HPX_WITH_HIPSYCL=ON (and make sure find_package will find HipSYCL).

Lastly, the module contains three tests/examples. All three implement a simple vector add example. The first one obtains a future using the free method get_future, the second one uses a single SYCL executor and the last one is using multiple executors called from multiple host threads.

To build the tests, use "make tests.unit.modules.async_sycl" To run the tests, use "ctest -R sycl".

NOTE: Theoretically, this module could work with other SYCL implementations, but was only tested using OneAPI and HipSYCL so far.

See the *API reference* of this module for more details.

batch_environments

This module allows for the detection of execution as batch jobs, a series of programs executed without user intervention. All data is preselected and will be executed according to preset parameters, such as date or completion of another task. Batch environments are especially useful for executing repetitive tasks.

HPX supports the creation of batch jobs through the Portable Batch System (PBS) and SLURM.

For more information on batch environments, see *Running on batch systems* and the API reference for the module.

cache

This module provides two cache data structures:

- `hpx::util::cache::local_cache`
- `hpx::util::cache::lru_cache`

See the *API reference* of the module for more details.

checkpoint_base

The checkpoint_base module contains lower level facilities that wrap simple check-pointing capabilities. This module does not implement special handling for futures or components, but simply serializes all arguments to or from a given container.

This module exposes the `hpx::util::save_checkpoint_data`, `hpx::util::restore_checkpoint_data`, and `hpx::util::prepare_checkpoint_data` APIs. These functions encapsulate the basic serialization functionalities necessary to save/restore a variadic list of arguments to/from a given data container.

See the *API reference* of this module for more details.

command_line_handling_local

TODO: High-level description of the module.

See the API reference of this module for more details.

compute_local

TODO: High-level description of the module.

See the *API reference* of this module for more details.

concepts

This module provides helpers for emulating concepts. It provides the following macros:

- `HPX_CONCEPT_REQUIRES`
- `HPX_HAS_MEMBER_XXX_TRAIT_DEF`
- `HPX_HAS_XXX_TRAIT_DEF`

See the API reference of the module for more details.

concurrency

This module provides concurrency primitives useful for multi-threaded programming such as:

- `hpx::barrier`
- `hpx::util::cache_line_data` and `hpx::util::cache_aligned_data`: wrappers for aligning and padding data to cache lines.
- various lockfree queue data structures

See the API reference of the module for more details.

config

The config module contains various configuration options, typically hidden behind macros that choose the correct implementation based on the compiler and other available options. It also contains platform independent macros to control inlining, export sets and more.

See the *API reference* of the module for more details.

config_registry

The config_registry module is a low level module providing helper functionality for registering configuration entries to a global registry from other modules. The `hpx::config_registry::add_module_config` function is used to add configuration options, and `hpx::config_registry::get_module_configs` can be used to retrieve configuration entries registered so far. `add_module_config_helper` can be used to register configuration entries through static global options.

See the API reference of this module for more details.

contracts

The contracts module provides C++ contracts support for HPX with intelligent fallback to assertions when native contracts are not available. This module implements a forward-compatible API that works across different C++ standards and compiler capabilities.

The module provides three primary macros: `HPX_PRE`, `HPX_POST`, and `HPX_CONTRACT_ASSERT`. These macros automatically adapt their behavior based on compiler capabilities:

- When C++26 native contracts are available (`__cpp_contracts` defined), they map to standard contract syntax
- When `HPX_WITH_CXX26_CONTRACTS=OFF`, preconditions and postconditions become no-ops while contract assertions remain available as enhanced assertions

Configuration

Enable contracts in CMake:

```
cmake -DHPX_WITH_CXX26_CONTRACTS=ON -DCMAKE_CXX_STANDARD=26
```

Enable contract-enhanced assertions (optional):

```
cmake -DHPX_WITH_CXX26_CONTRACTS=ON -DHPX_CONTRACTS_WITH_ASSERTS_AS_CONTRACT_ASSERTS=ON
```

Contract assertions work even when contracts are disabled:

```
cmake -DHPX_WITH_CXX26_CONTRACTS=OFF # HPX_CONTRACT_ASSERT still maps to HPX_ASSERT
```

Advanced Features

Contract-Enhanced Assertions

When `HPX_CONTRACTS_WITH_ASSERTS_AS_CONTRACT_ASSERTS=ON` is enabled, regular `HPX_ASSERT` calls are automatically upgraded to use contract assertions in C++26 mode:

```
void example_function(int value)
{
    HPX_ASSERT(value > 0); // Becomes contract_assert(value > 0) in C++26 mode
    // ... rest of function
}
```

Warning: Enhanced assertions only provide benefits when native C++26 contracts are supported by the compiler. Without native contract support, `HPX_ASSERT` -> `HPX_CONTRACT_ASSERT` -> `HPX_ASSERT` (no enhancement). CMake will issue a warning if you enable this option without native contract support.

This provides enhanced contract semantics throughout your existing codebase without requiring changes to assertion code. The transformation occurs in the contracts module (`contracts.hpp`) where the `HPX_ASSERT` macro is overridden to use `HPX_CONTRACT_ASSERT` when `HPX_WITH_ASSERTS_AS_CONTRACT_ASSERTS=ON`:

- `HPX_WITH_CXX26_CONTRACTS=ON` - Contracts module is enabled
- `HPX_CONTRACTS_WITH_ASSERTS_AS_CONTRACT_ASSERTS=ON` - Assertion enhancement is enabled

The implementation works by redefining `HPX_ASSERT` in `contracts.hpp` to use `HPX_CONTRACT_ASSERT`, which automatically adapts to the current contract mode (native C++26 contracts or assertion fallback). This ensures all existing `HPX_ASSERT` calls throughout the HPX codebase automatically gain contract semantics when available.

Usage Examples

Preconditions and postconditions using declaration syntax (C++26):

```
int divide(int a, int b) HPX_PRE(b != 0)
{
    return a / b;
}

int factorial(int n) HPX_PRE(n >= 0) HPX_POST(r; r > 0)
{
    return n <= 1 ? 1 : n * factorial(n - 1);
}
```

Contract assertions (available in all modes):

```
void process_array(std::vector<int>& arr, size_t index)
{
    HPX_CONTRACT_ASSERT(index < arr.size());
    arr[index] *= 2;
}
```

Design Philosophy

HPX_CONTRACT_ASSERT: Enhanced assertion mechanism

Available even when `HPX_WITH_CONTRACTS=OFF` because it provides value as an enhanced assertion. Maps to `HPX_ASSERT` in all configurations.

HPX_PRE/HPX_POST: True contract syntax

Represent language-level contract semantics. When contracts are enabled but native C++26 contracts are not available, these become no-ops to maintain forward compatibility. When `HPX_WITH_CONTRACTS=OFF`, they are also no-ops. This prepares for C++26 migration where they will be attached to function declarations rather than used in function bodies.

Migration Strategy

The module is designed for smooth migration to C++26 native contracts:

Current (transition mode):

```
int func(int x)
{
    HPX_PRE(x > 0);    // No-op in fallback mode, active in native mode
    return x;
}
```

Target (C++26 native):

```
int func(int x) HPX_PRE(x > 0)
{
    return x;
}
```

Note: In fallback mode, HPX_PRE and HPX_POST become no-ops to maintain forward compatibility and avoid performance overhead. Use HPX_CONTRACT_ASSERT when you need runtime validation in all modes.

Testing

The module includes comprehensive testing with automatic compiler capability detection. Tests are organized into three categories:

- **Declaration tests:** Test C++26 native contract syntax when `__cpp_contracts` is available
- **Fallback tests:** Test assertion fallback behavior when contracts are not natively supported
- **Disabled tests:** Test no-op behavior when contracts are disabled

The test suite automatically detects compiler capabilities at configure time and builds only the appropriate tests for the current configuration.

See the *API reference* of the module for more details.

coroutines

The coroutines module provides coroutine (user-space thread) implementations for different platforms.

See the *API reference* of the module for more details.

datastructures

The datastructures module provides basic data structures (typically provided for compatibility with older C++ standards):

- `hpx::detail::small_vector`
- `hpx::util::basic_any`
- `hpx::util::member_pack`
- `hpx::optional`
- `hpx::tuple`
- `hpx::variant`

See the *API reference* of the module for more details.

debugging

This module provides helpers for demangling symbol names.

See the *API reference* of the module for more details.

errors

This module provides support for exceptions and error codes:

- `hpx::exception`
- `hpx::error_code`
- `hpx::error`

See the *API reference* of the module for more details.

execution

This library implements executors and execution policies for use with parallel algorithms and other facilities related to managing the execution of tasks.

See the *API reference* of the module for more details.

execution_base

The basic execution module is the main entry point to implement parallel and concurrent operations. It is modeled after P0443²⁵⁴ with some additions and implementations for the described concepts. Most notably, it provides an abstraction for execution resources, execution contexts and execution agents in such a way, that it provides customization points that those aforementioned concepts can be replaced and combined with ease.

For that purpose, three virtual base classes are provided to be able to provide implementations with different properties:

- **resource_base:** This is the abstraction for execution resources, that is for example CPU cores or an accelerator.
- **context_base:** An execution context uses execution resources and is able to spawn new execution agents, as new threads of executions on the available resources.
- **agent_base:** The execution agent represents the thread of execution, and can be used to yield, suspend, resume or abort a thread of execution.

executors

The executors module exposes executors and execution policies. Most importantly, it exposes the following classes and constants:

- `hpx::execution::sequenced_executor`
- `hpx::execution::parallel_executor`
- `hpx::execution::sequenced_policy`
- `hpx::execution::parallel_policy`
- `hpx::execution::parallel_unsequenced_policy`

²⁵⁴ <http://wg21.link/p0443>

- `hpx::execution::sequenced_task_policy`
- `hpx::execution::parallel_task_policy`
- `hpx::execution::seq`
- `hpx::execution::par`
- `hpx::execution::par_unseq`
- `hpx::execution::task`

See the *API reference* of this module for more details.

filesystem

This module provides a compatibility layer for the C++17 filesystem library. If the filesystem library is available this module will simply forward its contents into the `hpx::filesystem` namespace. If the library is not available it will fall back to Boost.Filesystem instead.

See the *API reference* of the module for more details.

format

The format module exposes the `format` and `format_to` functions for formatting strings.

See the *API reference* of the module for more details.

functional

This module provides function wrappers and helpers for managing functions and their arguments.

- `hpx::function`
- `hpx::function_ref`
- `hpx::move_only_function`
- `hpx::bind`
- `hpx::bind_back`
- `hpx::bind_front`
- `hpx::util::deferred_call`
- `hpx::invoke`
- `hpx::invoke_r`
- `hpx::invoke_fused`
- `hpx::invoke_fused_r`
- `hpx::mem_fn`
- `hpx::util::one_shot`
- `hpx::util::protect`
- `hpx::util::result_of`
- `hpx::placeholders::_1`

- `hpx::placeholders::_2`
- ...
- `hpx::placeholders::_9`

See the *API reference* of the module for more details.

futures

This module defines the `hpx::future` and `hpx::shared_future` classes corresponding to the C++ standard library classes `std::future`²⁵⁵ and `std::shared_future`²⁵⁶. Note that the specializations of `hpx::future::then` for executors and execution policies are defined in the *execution* module.

See the *API reference* of this module for more details.

hardware

The hardware module abstracts away hardware specific details of timestamps and CPU features.

See the *API reference* of the module for more details.

hashing

The hashing module provides two hashing implementations:

- `hpx::util::fibhash`
- `hpx::util::jenkins_hash`

See the *API reference* of the module for more details.

include_local

This module provides no functionality in itself. Instead it provides headers that group together other headers that often appear together. This module provides local-only headers.

See the *API reference* of this module for more details.

ini

TODO: High-level description of the module.

See the *API reference* of this module for more details.

²⁵⁵ <http://en.cppreference.com/w/cpp/thread/future>

²⁵⁶ http://en.cppreference.com/w/cpp/thread/shared_future

init_runtime_local

TODO: High-level description of the module.

See the API reference of this module for more details.

io_service

This module provides an abstraction over Boost.ASIO, combining multiple `asio::io_contexts` into a single pool. `hpx::util::io_service_pool` provides a simple pool of `asio::io_contexts` with an API similar to `asio::io_context`. `hpx::threads::detail::io_service_thread_pool` wraps `hpx::util::io_service_pool` into an interface derived from `hpx::threads::detail::thread_pool_base`.

See the *API reference* of this module for more details.

iterator_support

This module provides helpers for iterators. It provides `hpx::util::iterator_facade` and `hpx::util::iterator_adaptor` for creating new iterators, and the trait `hpx::util::is_iterator` along with more specific iterator traits.

See the API reference of the module for more details.

itt_notify

This module provides support for profiling with Intel VTune²⁵⁷.

See the API reference of this module for more details.

lci_base

This module provides helper functionality for detecting LCI environments.

See the API reference of this module for more details.

lcos_local

This module provides the following local *LCOs*:

- `hpx::lcos::local::and_gate`
- `hpx::lcos::local::channel`
- `hpx::lcos::local::one_element_channel`
- `hpx::lcos::local::receive_channel`
- `hpx::lcos::local::send_channel`
- `hpx::lcos::local::guard`
- `hpx::lcos::local::guard_set`
- `hpx::lcos::local::run_guarded`
- `hpx::lcos::local::conditional_trigger`

²⁵⁷ <https://software.intel.com/content/www/us/en/develop/tools/vtune-profiler.html>

- `hpx::packaged_task`
- `hpx::promise`
- `hpx::lcos::local::receive_buffer`
- `hpx::lcos::local::trigger`

See *lcos_distributed* for distributed LCOs. Basic synchronization primitives for use in *HPX* threads can be found in *synchronization*. *async_combinators* contains useful utility functions for combining futures.

See the *API reference* of this module for more details.

likwid

TODO: High-level description of the module.

See the *API reference* of this module for more details.

lock_registration

This module contains functionality for registering locks to detect when they are locked and unlocked on different threads.

See the *API reference* of this module for more details.

logging

This module provides useful macros for logging information.

See the *API reference* of the module for more details.

memory

Part of this module is a forked version of `boost::intrusive_ptr` from `Boost.SmartPtr`²⁵⁸.

See the *API reference* of the module for more details.

mpi_base

This module provides helper functionality for detecting `MPI`²⁵⁹ environments.

See the *API reference* of this module for more details.

²⁵⁸ https://www.boost.org/doc/libs/release/libs/smart_ptr/doc/html/smart_ptr.html

²⁵⁹ https://en.wikipedia.org/wiki/Message_Passing_Interface

pack_traversal

This module exposes the basic functionality for traversing various packs, both synchronously and asynchronously: `hpx::util::traverse_pack` and `hpx::util::traverse_pack_async`. It also exposes the higher level functionality of unwrapping nested futures: `hpx::util::unwrap` and its function object form `hpx::util::functional::unwrap`.

See the *API reference* of this module for more details.

plugin

This module provides base utilities for creating plugins.

See the *API reference* of the module for more details.

prefix

This module provides utilities for handling the prefix of an *HPX* application, i.e. the paths used for searching components and plugins.

See the *API reference* of this module for more details.

preprocessor

This library contains useful preprocessor macros:

- `HPX_PP_CAT`: Concatenate two tokens
- `HPX_PP_EXPAND`: Expands a preprocessor token
- `HPX_PP_NARGS`: Determines the number of arguments passed to a variadic macro
- `HPX_PP_STRINGIZE`: Turns a token into a string
- `HPX_PP_STRIP_PARENS`: Strips parenthesis from a token

See the *API reference* of the module for more details.

program_options

The module `program_options` is a direct fork of the `Boost.Program_options`²⁶⁰ library (Boost V1.70.0²⁶¹). In order to be included as an *HPX* module, the `Boost.Program_options` library has been moved to the namespace `hpx::program_options`. We have also replaced all Boost facilities the library depends on with either the equivalent facilities from the standard library or from *HPX*. As a result, the *HPX* `program_options` module is fully interface compatible with `Boost.Program_options` (sans the `hpx` namespace and the `#include <hpx/modules/program_options.hpp>` changes that need to be applied to all code relying on this library).

All credit goes to Vladimir Prus, the author of the excellent `Boost.Program_options` library. All bugs have been introduced by us.

See the *API reference* of the module for more details.

²⁶⁰ https://www.boost.org/doc/html/program_options.html

²⁶¹ https://www.boost.org/doc/libs/1_70_0/doc/html/program_options.html

properties

This module implements the `prefer` customization point for properties in terms of [P2220](https://wg21.link/p2220)²⁶². This differs from [P1393](http://wg21.link/p1393)²⁶³ in that it relies fully on `tag_invoke` overloads and fewer base customization points. Actual properties are defined in modules. All functionality is experimental and can be accessed through the `hpx::experimental` namespace.

See the API reference of this module for more details.

resiliency

In *HPX*, a program failure is a manifestation of a failing task. This module exposes several APIs that allow users to manage failing tasks in a convenient way by either replaying a failed task or by replicating a specific task.

Task replay is analogous to the Checkpoint/Restart mechanism found in conventional execution models. The key difference being localized fault detection. When the runtime detects an error, it replays the failing task as opposed to completely rolling back the entire program to the previous checkpoint.

Task replication is designed to provide reliability enhancements by replicating a set of tasks and evaluating their results to determine a consensus among them. This technique is most effective in situations where there are few tasks in the critical path of the DAG which leaves the system underutilized or where hardware or software failures may result in an incorrect result instead of an error. However, the drawback of this method is the additional computational cost incurred by repeating a task multiple times.

The following API functions are exposed:

- `hpx::resiliency::experimental::async_replay`: This version of task replay will catch user-defined exceptions and automatically reschedule the task *N* times before throwing an `hpx::resiliency::experimental::abort_replay_exception` if no task is able to complete execution without an exception.
- `hpx::resiliency::experimental::async_replay_validate`: This version of replay adds an argument to `async_replay` which receives a user-provided validation function to test the result of the task against. If the task's output is validated, the result is returned. If the output fails the check or an exception is thrown, the task is replayed until no errors are encountered or the number of specified retries has been exceeded.
- `hpx::resiliency::experimental::async_replicate`: This is the most basic implementation of the task replication. The API returns the first result that runs without detecting any errors.
- `hpx::resiliency::experimental::async_replicate_validate`: This API additionally takes a validation function which evaluates the return values produced by the threads. The first task to compute a valid result is returned.
- `hpx::resiliency::experimental::async_replicate_vote`: This API adds a vote function to the basic replicate function. Many hardware or software failures are silent errors which do not interrupt program flow. In order to detect errors of this kind, it is necessary to run the task several times and compare the values returned by every version of the task. In order to determine which return value is “correct”, the API allows the user to provide a custom consensus function to properly form a consensus. This voting function then returns the “correct” answer.
- `hpx::resiliency::experimental::async_replicate_vote_validate`: This combines the features of the previously discussed replicate set. Replicate vote validate allows a user to provide a validation function to filter results. Additionally, as described in replicate vote, the user can provide a “voting function” which returns the consensus formed by the voting logic.

²⁶² <https://wg21.link/p2220>

²⁶³ <http://wg21.link/p1393>

- `hpx::resiliency::experimental::dataflow_replay`: This version of dataflow replay will catch user-defined exceptions and automatically reschedules the task N times before throwing an `hpx::resiliency::experimental::abort_replay_exception` if no task is able to complete execution without an exception. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.
- `hpx::resiliency::experimental::dataflow_replay_validate`: This version of replay adds an argument to dataflow replay which receives a user-provided validation function to test the result of the task against. If the task's output is validated, the result is returned. If the output fails the check or an exception is thrown, the task is replayed until no errors are encountered or the number of specified retries have been exceeded. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.
- `hpx::resiliency::experimental::dataflow_replicate`: This is the most basic implementation of the task replication. The API returns the first result that runs without detecting any errors. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.
- `hpx::resiliency::experimental::dataflow_replicate_validate`: This API additionally takes a validation function which evaluates the return values produced by the threads. The first task to compute a valid result is returned. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.
- `hpx::resiliency::experimental::dataflow_replicate_vote`: This API adds a vote function to the basic replicate function. Many hardware or software failures are silent errors which do not interrupt program flow. In order to detect errors of this kind, it is necessary to run the task several times and compare the values returned by every version of the task. In order to determine which return value is "correct", the API allows the user to provide a custom consensus function to properly form a consensus. This voting function then returns the "correct" answer. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.
- `hpx::resiliency::experimental::dataflow_replicate_vote_validate`: This combines the features of the previously discussed replicate set. Replicate vote validate allows a user to provide a validation function to filter results. Additionally, as described in replicate vote, the user can provide a "voting function" which returns the consensus formed by the voting logic. Any arguments for the executed task that are futures will cause the task invocation to be delayed until all of those futures have become ready.

See the *API reference* of the module for more details.

resource_partitioner

The `resource_partitioner` module defines `hpx::resource::partitioner`, the class used by the runtime and users to partition available hardware resources into thread pools. See *Using the resource partitioner* for more details on using the resource partitioner in applications.

See the API reference of this module for more details.

runtime_configuration

This module handles the configuration options required by the runtime.

See the *API reference* of this module for more details.

runtime_local

TODO: High-level description of the library.

See the *API reference* of this module for more details.

schedulers

This module provides schedulers used by thread pools in the *thread_pools* module. There are currently three main schedulers:

- `hpx::threads::policies::local_priority_queue_scheduler`
- `hpx::threads::policies::static_priority_queue_scheduler`
- `hpx::threads::policies::shared_priority_queue_scheduler`

Other schedulers are specializations or variations of the above schedulers. See the examples of the *resource_partitioner* module for examples of specifying a custom scheduler for a thread pool.

See the *API reference* of this module for more details.

serialization

This module provides serialization primitives and support for all built-in types as well as all C++ Standard Library collection and utility types. This list is extended by *HPX* vocabulary types with proper support for global reference counting. *HPX*'s mode of serialization is derived from Boost's [serialization model](https://www.boost.org/doc/libs/1_72_0/libs/serialization/doc/index.html)²⁶⁴ and, as such, is mostly interface compatible with its Boost counterpart.

The purest form of serializing data is to copy the content of the payload bit by bit; however, this method is impractical for generic C++ types, which might be composed of more than just regular built-in types. Instead, *HPX*'s approach to serialization is derived from the Boost Serialization library, and is geared towards allowing the programmer of a given class explicit control and syntax of what to serialize. It is based on operator overloading of two special archive types that hold a buffer or stream to store the serialized data and is responsible for dispatching the serialization mechanism to the intrusive or non-intrusive version. The serialization process is recursive. Each member that needs to be serialized must be specified explicitly. The advantage of this approach is that the serialization code is written in C++ and leverages all necessary programming techniques. The generic, user-facing interface allows for effective application of the serialization process without obstructing the algorithms that need special code for packing and unpacking. It also allows for optimizations in the implementation of the archives.

See the *API reference* of the module for more details.

²⁶⁴ https://www.boost.org/doc/libs/1_72_0/libs/serialization/doc/index.html

static_reinit

This module provides a simple wrapper around static variables that can be reinitialized.

See the *API reference* of this module for more details.

string_util

This module contains string utilities inspired by the Boost String Algorithms Library.

See the *API reference* of this module for more details.

synchronization

This module provides synchronization primitives that should be used rather than the C++ standard ones in *HPX* threads:

- `hpx::barrier`
- `hpx::binary_semaphore`
- `hpx::call_once`
- `hpx::condition_variable`
- `hpx::condition_variable_any`
- `hpx::counting_semaphore`
- `hpx::lcos::local::event`
- `hpx::latch`
- `hpx::mutex`
- `hpx::no_mutex`
- `hpx::once_flag`
- `hpx::recursive_mutex`
- `hpx::shared_mutex`
- `hpx::sliding_semaphore`
- `hpx::spinlock` (*std::mutex* compatible spinlock)
- `hpx::spinlock_no_backoff` (*boost::mutex* compatible spinlock)
- `hpx::spinlock_pool`
- `hpx::stop_callback`
- `hpx::stop_source`
- `hpx::stop_token`
- `hpx::in_place_stop_token`
- `hpx::timed_mutex`
- `hpx::upgrade_to_unique_lock`
- `hpx::upgrade_lock`

See *lcos_local*, *async_combinators*, and *async_distributed* for higher level synchronization facilities.

See the *API reference* of this module for more details.

tag_invoke

TODO: High-level description of the module.

See the *API reference* of this module for more details.

testing

The testing module contains useful macros for testing. The results of tests can be printed with `hpx::util::report_errors`. The following macros are provided:

- `HPX_TEST`
- `HPX_TEST_MSG`
- `HPX_TEST_EQ`
- `HPX_TEST_NEQ`
- `HPX_TEST_LT`
- `HPX_TEST_LTE`
- `HPX_TEST_RANGE`
- `HPX_TEST_EQ_MSG`
- `HPX_TEST_NEQ_MSG`
- `HPX_SANITY`
- `HPX_SANITY_MSG`
- `HPX_SANITY_EQ`
- `HPX_SANITY_NEQ`
- `HPX_SANITY_LT`
- `HPX_SANITY_LTE`
- `HPX_SANITY_RANGE`
- `HPX_SANITY_EQ_MSG`

See the API reference of the module for more details.

thread_pool_util

This module contains helper functions for asynchronously suspending and resuming thread pools and their worker threads.

See the *API reference* of this module for more details.

thread_pools

This module defines the thread pools and utilities used by the *HPX* runtime. The only thread pool implementation provided by this module is `hpx::threads::detail::scheduled_thread_pool`, which is derived from `hpx::threads::detail::thread_pool_base` defined in the *threading_base* module.

See the API reference of this module for more details.

thread_support

This module provides miscellaneous utilities for threading and concurrency.

See the *API reference* of the module for more details.

threading

This module provides the equivalents of `std::thread` and `std::jthread` for lightweight *HPX* threads:

- `hpx::thread`
- `hpx::jthread`

See the *API reference* of this module for more details.

threading_base

This module contains the base class definition required for threads. The base class `hpx::threads::thread_data` is inherited by two specializations for stackful and stackless threads: `hpx::threads::thread_data_stackful` and `hpx::threads::thread_data_stackless`. In addition, the module defines the base classes for schedulers and thread pools: `hpx::threads::policies::scheduler_base` and `hpx::threads::thread_pool_base`.

See the API reference of this module for more details.

thread_manager

This module defines the `hpx::threads::threadmanager` class. This is used by the runtime to manage the creation and destruction of thread pools. The *resource_partitioner* module handles the partitioning of resources into thread pools, but not the creation of thread pools.

See the API reference of this module for more details.

thrust

The thrust module integrates *HPX* parallel algorithms with NVIDIA Thrust, enabling GPU acceleration using familiar *HPX* algorithm syntax.

Execution Policies

- hpx::thrust::thrust_host_policy**
CPU execution using optimized parallel implementations
- hpx::thrust::thrust_device_policy**
Synchronous GPU execution
- hpx::thrust::thrust_task_policy**
Asynchronous GPU execution returning *HPX* futures

Policy Mappings

The *HPX* thrust policies map directly to Thrust execution policies:

```
// Policy mappings
hpx::thrust::thrust_host_policy    -> thrust::host
hpx::thrust::thrust_device_policy -> thrust::device
hpx::thrust::thrust_task_policy   -> thrust::par_nosync
```

Usage

Synchronous Device Execution

```
#include <hpx/modules/thrust.hpp>
#include <thrust/device_vector.h>

hpx::thrust::thrust_device_policy device{};
thrust::device_vector<int> d_vec(1000, 0);

hpx::fill(device, d_vec.begin(), d_vec.end(), 42);
int sum = hpx::reduce(device, d_vec.begin(), d_vec.end(), 0);
```

Asynchronous Execution with Futures

```
#include <hpx/modules/async_cuda.hpp>
#include <hpx/modules/thrust.hpp>

int hpx_main() {
    // Required for async operations
    hpx::cuda::experimental::enable_user_polling polling_guard("default");

    hpx::thrust::thrust_task_policy task{};
    thrust::device_vector<int> d_vec(1000, 1);

    auto fill_future = hpx::fill(task, d_vec.begin(), d_vec.end(), 42);
    fill_future.get(); // Standard HPX future operations
}
```

Build Requirements

- CUDA Toolkit 12.4.0+
- *HPX* with `HPX_WITH_CUDA=ON`
- Enable with: `cmake -DHPX_WITH_CUDA=ON ...`

See Also

- *async_cuda* - CUDA integration
- *execution* - *HPX* execution policies

timed_execution

This module provides extensions to the executor interfaces defined in the *execution* module that allow timed submission of tasks on thread pools (at or after a specified time).

See the *API reference* of this module for more details.

timing

This module provides the timing utilities (clocks and timers).

See the *API reference* of the module for more details.

topology

This module provides the class `hpx::threads::topology` which represents the hardware resources available on a node. The class is a light wrapper around the [Portable Hardware Locality \(HWLOC\)](https://www.open-mpi.org/projects/hwloc/)²⁶⁵ library. The `hpx::threads::cpu_mask` is a small companion class that represents a set of resources on a node.

See the *API reference* of the module for more details.

tracy

This modules enables the integration of *HPX* applications with the [|tracy|](https://github.com/jacobperron/tracy) profiler.

type_support

This module provides helper facilities related to types.

See the *API reference* of the module for more details.

²⁶⁵ <https://www.open-mpi.org/projects/hwloc/>

util

The util module provides miscellaneous standalone utilities.

See the *API reference* of the module for more details.

version

This module macros and functions for accessing version information about *HPX* and its dependencies.

See the *API reference* of this module for more details.

2.8.2 Main HPX modules

actions

TODO: High-level description of the library.

See the *API reference* of this module for more details.

actions_base

TODO: High-level description of the library.

See the *API reference* of this module for more details.

agas

TODO: High-level description of the module.

See the *API reference* of this module for more details.

agas_base

This module holds the implementation of the four AGAS services: primary namespace, locality namespace, component namespace, and symbol namespace.

See the *API reference* of this module for more details.

async_colocated

TODO: High-level description of the module.

See the *API reference* of this module for more details.

async_distributed

This module contains functionality for asynchronously launching work on remote localities: `hpx::async`, `hpx::post`. This module extends the local-only functions in `libs_async_local`.

See the API reference of this module for more details.

checkpoint

A common need of users is to periodically backup an application. This practice provides resiliency and potential restart points in code. HPX utilizes the concept of a **checkpoint** to support this use case.

Found in `hpx/util/checkpoint.hpp`, checkpoints are defined as objects that hold a serialized version of an object or set of objects at a particular moment in time. This representation can be stored in memory for later use or it can be written to disk for storage and/or recovery at a later point. In order to create and fill this object with data, users must use a function called `save_checkpoint`. In code the function looks like this:

```
hpx::future<hpx::util::checkpoint> hpx::util::save_checkpoint(a, b, c, ...);
```

`save_checkpoint` takes arbitrary data containers, such as `int`, `double`, `float`, `vector`, and `future`, and serializes them into a newly created checkpoint object. This function returns a `future` to a `checkpoint` containing the data. Here's an example of a simple use case:

```
using hpx::util::checkpoint;
using hpx::util::save_checkpoint;

std::vector<int> vec{1,2,3,4,5};
hpx::future<checkpoint> save_checkpoint(vec);
```

Once the future is ready, the checkpoint object will contain the `vector` `vec` and its five elements.

`prepare_checkpoint` takes arbitrary data containers (same as for `save_checkpoint`), , such as `int`, `double`, `float`, `vector`, and `future`, and calculates the necessary buffer space for the checkpoint that would be created if `save_checkpoint` was called with the same arguments. This function returns a `future` to a `checkpoint` that is appropriately initialized. Here's an example of a simple use case:

```
using hpx::util::checkpoint;
using hpx::util::prepare_checkpoint;

std::vector<int> vec{1,2,3,4,5};
hpx::future<checkpoint> prepare_checkpoint(vec);
```

Once the future is ready, the checkpoint object will be initialized with an appropriately sized internal buffer.

It is also possible to modify the launch policy used by `save_checkpoint`. This is accomplished by passing a launch policy as the first argument. It is important to note that passing `hpx::launch::sync` will cause `save_checkpoint` to return a `checkpoint` instead of a `future` to a `checkpoint`. All other policies passed to `save_checkpoint` will return a `future` to a `checkpoint`.

Sometimes `checkpoint` s must be declared before they are used. `save_checkpoint` allows users to move pre-created `checkpoint` s into the function as long as they are the first container passing into the function (In the case where a launch policy is used, the `checkpoint` will immediately follow the launch policy). An example of these features can be found below:

```
char character = 'd';
int integer = 10;
float flt = 10.01f;
bool boolean = true;
std::string str = "I am a string of characters";
std::vector<char> vec(str.begin(), str.end());
checkpoint archive;

// Test 1
// test basic functionality
hpx::shared_future<checkpoint> f_archive = save_checkpoint(
    std::move(archive), character, integer, flt, boolean, str, vec);
```

Once users can create checkpoints they must now be able to restore the objects they contain into memory. This is accomplished by the function `restore_checkpoint`. This function takes a `checkpoint` and fills its data into the containers it is provided. It is important to remember that the containers must be ordered in the same way they were placed into the checkpoint. For clarity see the example below:

```
char character2;
int integer2;
float flt2;
bool boolean2;
std::string str2;
std::vector<char> vec2;

restore_checkpoint(data, character2, integer2, flt2, boolean2, str2, vec2);
```

The core utility of `checkpoint` is in its ability to make certain data persistent. Often, this means that the data needs to be stored in an object, such as a file, for later use. *HPX* has two solutions for these issues: stream operator overloads and access iterators.

HPX contains two stream overloads, `operator<<` and `operator>>`, to stream data out of and into `checkpoint`. Here is an example of the overloads in use below:

```
double a9 = 1.0, b9 = 1.1, c9 = 1.2;
std::ofstream test_file_9("test_file_9.txt");
hpx::future<checkpoint> f_9 = save_checkpoint(a9, b9, c9);
test_file_9 << f_9.get();
test_file_9.close();

double a9_1, b9_1, c9_1;
std::ifstream test_file_9_1("test_file_9.txt");
checkpoint archive9;
test_file_9_1 >> archive9;
restore_checkpoint(archive9, a9_1, b9_1, c9_1);
```

This is the primary way to move data into and out of a `checkpoint`. It is important to note, however, that users should be cautious when using a stream operator to load data and another function to remove it (or vice versa). Both `operator<<` and `operator>>` rely on a `.write()` and a `.read()` function respectively. In order to know how much data to read from the `std::istream`, the `operator<<` will write the size of the checkpoint before writing the checkpoint data. Correspondingly, the `operator>>` will read the size of the stored data before reading the data into a new instance of `checkpoint`. As long as the user employs the `operator<<` and `operator>>` to stream the data, this detail can be ignored.

Important: Be careful when mixing `operator<<` and `operator>>` with other facilities to read and write to a checkpoint. `operator<<` writes an extra variable, and `operator>>` reads this variable back separately. Used together the user will not encounter any issues and can safely ignore this detail.

Users may also move the data into and out of a checkpoint using the exposed `.begin()` and `.end()` iterators. An example of this use case is illustrated below.

```
std::ofstream test_file_7("checkpoint_test_file.txt");
std::vector<float> vec7{1.02f, 1.03f, 1.04f, 1.05f};
hpx::future<checkpoint> fut_7 = save_checkpoint(vec7);
checkpoint archive7 = fut_7.get();
std::copy(archive7.begin(),      // Write data to ofstream
          archive7.end(),        // ie. the file
          std::ostream_iterator<char>(test_file_7));
test_file_7.close();

std::vector<float> vec7_1;
std::vector<char> char_vec;
std::ifstream test_file_7_1("checkpoint_test_file.txt");
if (test_file_7_1)
{
    test_file_7_1.seekg(0, test_file_7_1.end);
    auto length = test_file_7_1.tellg();
    test_file_7_1.seekg(0, test_file_7_1.beg);
    char_vec.resize(length);
    test_file_7_1.read(char_vec.data(), length);
}
checkpoint archive7_1(std::move(char_vec));    // Write data to checkpoint
restore_checkpoint(archive7_1, vec7_1);
```

Checkpointing components

`save_checkpoint` and `restore_checkpoint` are also able to store components inside checkpoints. This can be done in one of two ways. First a client of the component can be passed to `save_checkpoint`. When the user wishes to resurrect the component she can pass a client instance to `restore_checkpoint`.

This technique is demonstrated below:

```
// Try to checkpoint and restore a component with a client
std::vector<int> vec3{10, 10, 10, 10, 10};

// Create a component instance through client constructor
data_client D(hpx::find_here(), std::move(vec3));
hpx::future<checkpoint> f3 = save_checkpoint(D);

// Create a new client
data_client E;

// Restore server inside client instance
restore_checkpoint(f3.get(), E);
```

The second way a user can save a component is by passing a `shared_ptr` to the component to `save_checkpoint`.

This component can be resurrected by creating a new instance of the component type and passing a `shared_ptr` to the new instance to `restore_checkpoint`.

This technique is demonstrated below:

```
// test checkpoint a component using a shared_ptr
std::vector<int> vec{1, 2, 3, 4, 5};
data_client A(hpx::find_here(), std::move(vec));

// Checkpoint Server
hpx::id_type old_id = A.get_id();

hpx::future<std::shared_ptr<data_server>> f_a_ptr =
    hpx::get_ptr<data_server>(A.get_id());
std::shared_ptr<data_server> a_ptr = f_a_ptr.get();
hpx::future<checkpoint> f = save_checkpoint(a_ptr);
auto&& data = f.get();

// test prepare_checkpoint API
checkpoint c = prepare_checkpoint(hpx::launch::sync, a_ptr);
HPX_TEST(c.size() == data.size());

// Restore Server
// Create a new server instance
std::shared_ptr<data_server> b_server;
restore_checkpoint(data, b_server);
```

collectives

The `collectives` module exposes a set of distributed collective operations. Those can be used to exchange data between participating sites in a coordinated way. At this point the module exposes the following collective primitives:

- `hpx::collectives::all_gather`: receives a set of values from all participating sites.
- `hpx::collectives::all_reduce`: performs a reduction on data from each participating site to each participating site.
- `hpx::collectives::all_to_all`: each participating site provides its element of the data to collect while all participating sites receive the data from every other site.
- `hpx::collectives::broadcast_to` and `hpx::collectives::broadcast_from`: performs a broadcast operation from a root site to all participating sites.
- `hpx::collectives::exclusive_scan`: performs an exclusive scan operation on a set of values received from all call sites operating on the given base name.
- `hpx::collectives::gather_here` and `hpx::collectives::gather_there`: gathers values from all participating sites.
- `hpx::collectives::inclusive_scan`: performs an inclusive scan operation on a set of values received from all call sites operating on the given base name.
- `hpx::collectives::reduce_here` and `hpx::collectives::reduce_there`: performs a reduction on data from each participating site to a root site.
- `hpx::collectives::scatter_to` and `hpx::collectives::scatter_from`: receives an element of a set of values operating on the given base name.

- `hpx::lcos::broadcast`: performs a given action on all given global identifiers.
- `hpx::distributed::barrier`: distributed barrier.
- `hpx::lcos::fold`: performs a fold with a given action on all given global identifiers.
- `hpx::distributed::latch`: distributed latch.
- `hpx::lcos::reduce`: performs a reduction on data from each given global identifiers.
- `hpx::lcos::smd_block`: performs the same operation on a local image while providing handles to the other images.

See the *API reference* of the module for more details.

Hierarchical collectives

Hierarchical communicators split a collective into sub-communicators arranged as a tree. This reduces the number of participants in each individual operation, but it also means that one user-visible hierarchical call can touch several internal communicators.

Generation model

Hierarchical collectives use two internal generations for each user generation. For a user generation k , the first internal phase uses $2k - 1$ and the second uses $2k$. Single-pass hierarchical operations and the inter-group exchange of `hpx::collectives::all_to_all` advance the communicator by two generations in one step so that shared hierarchical communicators stay aligned with two-phase collectives.

When a hierarchical communicator instance is shared between collective operations, callers must pass explicit, strictly consecutive positive generation numbers. Two-phase hierarchical collectives, including `hpx::collectives::all_gather`, `hpx::collectives::all_reduce`, `hpx::collectives::all_to_all`, `hpx::collectives::inclusive_scan`, `hpx::collectives::exclusive_scan`, and `hpx::distributed::barrier`, reject the default generation because their phase generations are derived from the explicit user generation.

command_line_handling

The `command_line_handling` module defines and handles the command-line options required by the *HPX* runtime, combining them with configuration options defined by the *runtime_configuration* module. The actual parsing of command line options is handled by the *program_options* module.

See the *API reference* of the module for more details.

components

TODO: High-level description of the module.

See the *API reference* of this module for more details.

components_base

TODO: High-level description of the library.

See the *API reference* of this module for more details.

compute

The compute module provides utilities for handling task and memory affinity on host systems.

See the *API reference* of the module for more details.

distribution_policies

TODO: High-level description of the module.

See the *API reference* of this module for more details.

execution_distributed

Provides distributed sender and receiver facilities for HPX execution.

See the *API reference* of this module for more details.

executors_distributed

This module provides the executor `hpx::parallel::execution::distribution_policy_executor`. It allows one to create work that is implicitly distributed over multiple localities.

See the *API reference* of this module for more details.

include

This module provides no functionality in itself. Instead it provides headers that group together other headers that often appear together.

See the *API reference* of this module for more details.

init_runtime

TODO: High-level description of the library.

See the *API reference* of this module for more details.

lcos_distributed

This module contains distributed *LCOs*. Currently the only LCO provided is `:cpp:class::hpx::lcos::channel`, a construct for sending values from one *locality* to another. See `libs_lcos_local` for local LCOs.

See the API reference of this module for more details.

naming

TODO: High-level description of the module.

See the API reference of this module for more details.

naming_base

This module provides a forward declaration of *address_type*, *component_type* and *invalid_locality_id*.

See the *API reference* of this module for more details.

parcelport_lci

TODO: High-level description of the module.

See the API reference of this module for more details.

parcelport_mpi

TODO: High-level description of the module.

See the API reference of this module for more details.

parcelport_tcp

TODO: High-level description of the module.

See the API reference of this module for more details.

parcelset

TODO: High-level description of the module.

See the *API reference* of this module for more details.

parcelset_base

TODO: High-level description of the module.

See the *API reference* of this module for more details.

performance_counters

This module provides the basic functionality required for defining performance counters. See *Performance counters* for more information about performance counters.

See the API reference of this module for more details.

plugin_factories

TODO: High-level description of the module.

See the *API reference* of this module for more details.

resiliency_distributed

Software resiliency features of *HPX* were introduced in the *resiliency module*. This module extends the APIs to run on distributed-memory systems allowing the user to invoke the failing task on other localities at runtime. This is useful in cases where a node is identified to fail more often (e.g., for certain ALU computes) as the task can now be replayed or replicated among different localities. The API exposed allows for an easy integration with the local only resiliency APIs as well.

Distributed software resilience APIs have a similar function signature and lives under the same namespace of *hpx::resiliency::experimental*. The difference arises in the formal parameters where distributed APIs takes the localities as the first argument, and an action as opposed to a function or a function object. The localities signify the order in which the API will either schedule (in case of Task Replay) tasks in a round robin fashion or replicate the tasks onto the list of localities.

The list of APIs exposed by distributed resiliency modules is the same as those defined in *local resiliency module*.

See the *API reference* of this module for more details.

runtime_components

TODO: High-level description of the module.

See the *API reference* of this module for more details.

runtime_distributed

TODO: High-level description of the module.

See the *API reference* of this module for more details.

segmented_algorithms

Segmented algorithms extend the usual parallel *algorithms* by providing overloads that work with distributed containers, such as partitioned vectors.

See the *API reference* of the module for more details.

statistics

This module provide some statistics utilities like rolling min/max and histogram.

See the API reference of the module for more details.

Supervision module

The supervision module provides lifecycle event publication, state querying, and observer registration for actors/components running on local or remote localities.

Overview

Several core operations are exposed, each with a local (synchronous) call and a remote (locality-qualified, future-returning or `launch::sync_policy`) call:

Functions

Table 2.125: *hpx::supervision* functions

Function	Description
<i>hpx::supervision::publish_event</i>	<i>Publish a lifecycle event for a target.</i>
<i>hpx::supervision::query_state</i>	<i>Query the most recently observed lifecycle state.</i>
<i>hpx::supervision::register_observer</i>	<i>Register an observer for a target's lifecycle events.</i>
<i>hpx::supervision::unregister_observer</i>	<i>Unregister a previously registered lifecycle observer.</i>
<i>hpx::supervision::remove_target</i>	<i>Clear all locally tracked state for a target.</i>
<i>hpx::supervision::await_terminal</i>	<i>Wait for a target to reach a terminal lifecycle event.</i>
<i>hpx::supervision::check_admission</i>	<i>Check whether a target currently admits new dispatch.</i>
<i>hpx::supervision::register_activity_observer</i>	<i>Register an observer for activity-state transitions of all targets.</i>
<i>hpx::supervision::unregister_activity_observer</i>	<i>Unregister a previously registered activity observer.</i>

Publishing events

```
hpx::future<hpx::supervision::publish_result> hpx::supervision::publish_event(hpx::id_type const
                                                                              &locality, hpx::id_type
                                                                              const &target,
                                                                              hpx::supervision::event ev,
                                                                              std::uint64_t epoch = 0)
```

```
hpx::supervision::publish_result hpx::supervision::publish_event(hpx::launch::sync_policy, hpx::id_type
                                                                              const &locality, hpx::id_type const
                                                                              &target, hpx::supervision::event ev,
                                                                              std::uint64_t epoch = 0, hpx::error_code
                                                                              &ec = hpx::throws)
```

```
hpx::supervision::publish_result hpx::supervision::publish_event(hpx::id_type const &target,  
                                                                hpx::supervision::event ev, std::uint64_t  
                                                                epoch = 0, hpx::error_code &ec =  
                                                                hpx::throws)
```

Publish a lifecycle event for `target`. Events are visible immediately to local observers; remote observers are notified within roughly one to two parcel round-trips. Publishing non-terminal events is not idempotent - each call creates a distinct, timestamped record. `event::completed` and `event::failed` are latched: the first terminal publication for a target returns `publish_result::applied`; every later terminal publication for that target is a no-op that returns `publish_result::already_terminal`.

Querying lifecycle state

```
hpx::future<hpx::supervision::lifecycle_state> hpx::supervision::query_state(hpx::id_type const &locality,  
                                                                hpx::id_type const &target)
```

```
hpx::supervision::lifecycle_state hpx::supervision::query_state(hpx::launch::sync_policy, hpx::id_type const  
                                                                &locality, hpx::id_type const &target,  
                                                                hpx::error_code &ec = hpx::throws)
```

```
hpx::supervision::lifecycle_state hpx::supervision::query_state(hpx::id_type const &target, hpx::error_code  
                                                                &ec = hpx::throws)
```

Query the most recently observed lifecycle state for `target`. Includes a sequence number for gap detection and a staleness error code for remote queries whose result may lag the latest event.

Registering observers

```
hpx::future<hpx::id_type> hpx::supervision::register_observer(hpx::id_type const &locality, hpx::id_type  
                                                                const &target,  
                                                                hpx::supervision::lifecycle_callback const  
                                                                &callback, std::optional<std::uint64_t>  
                                                                epoch_filter = std::nullopt)
```

```
hpx::id_type hpx::supervision::register_observer(hpx::launch::sync_policy, hpx::id_type const &locality,  
                                                                hpx::id_type const &target,  
                                                                hpx::supervision::lifecycle_callback const &callback,  
                                                                std::optional<std::uint64_t> epoch_filter = std::nullopt,  
                                                                hpx::error_code &ec = hpx::throws)
```

```
hpx::id_type hpx::supervision::register_observer(hpx::id_type const &target,  
                                                                hpx::supervision::lifecycle_callback const &callback,  
                                                                std::optional<std::uint64_t> epoch_filter = std::nullopt,  
                                                                hpx::error_code &ec = hpx::throws)
```

Register `callback` to be invoked on lifecycle events of `target`, returning an observer handle usable with `unregister_observer`. Local callbacks fire synchronously within the publish call; remote callbacks fire via a retried parcel. If `epoch_filter` is set, the observer only receives notifications (including the initial state snapshot delivered at registration time) whose epoch matches; by default the observer receives notifications for every epoch.

Unregistering observers

```
hpx::future<void> hpx::supervision::unregister_observer(hpx::id_type const &locality, hpx::id_type const &observer_handle)
```

```
void hpx::supervision::unregister_observer(hpx::launch::sync_policy, hpx::id_type const &locality,
                                           hpx::id_type const &observer_handle, hpx::error_code &ec =
                                           hpx::throws)
```

```
void hpx::supervision::unregister_observer(hpx::id_type const &observer_handle, hpx::error_code &ec =
                                           hpx::throws)
```

Unregister a previously registered observer. `observer_handle` must have been obtained from `register_observer`; a handle obtained from `register_activity_observer`, or any handle never returned by either registration function, is rejected.

Removing target state

```
hpx::future<void> hpx::supervision::remove_target(hpx::id_type const &locality, hpx::id_type const &target)
```

```
void hpx::supervision::remove_target(hpx::launch::sync_policy, hpx::id_type const &locality, hpx::id_type
                                     const &target, hpx::error_code &ec = hpx::throws)
```

```
void hpx::supervision::remove_target(hpx::id_type const &target, hpx::error_code &ec = hpx::throws)
```

Clear all locally tracked state for `target`. Unlike `unregister_observer`, which removes a single previously registered observer handle, `remove_target` unconditionally forgets every piece of local state held for `target` - its recorded lifecycle state and current epoch, and any observers still registered for it - regardless of any specific observer handle. Intended for callers that know `target` will never be queried or observed again locally (e.g. after a failed registration that seeded some state for it, or once a peer has been evicted), so that local state does not accumulate indefinitely.

Waiting for terminal events

```
hpx::future<hpx::supervision::lifecycle_state> hpx::supervision::await_terminal(hpx::id_type const
                                                                               &locality, hpx::id_type
                                                                               const &target,
                                                                               std::uint64_t epoch = 0,
                                                                               std::chrono::steady_clock::duration
                                                                               timeout =
                                                                               std::chrono::steady_clock::duration::max())
```

```
hpx::supervision::lifecycle_state hpx::supervision::await_terminal(hpx::launch::sync_policy, hpx::id_type
                                                                     const &locality, hpx::id_type const
                                                                     &target, std::uint64_t epoch = 0,
                                                                     std::chrono::steady_clock::duration
                                                                     timeout =
                                                                     std::chrono::steady_clock::duration::max(),
                                                                     hpx::error_code &ec = hpx::throws)
```

```
hpx::future<hpx::supervision::lifecycle_state> hpx::supervision::await_terminal(hpx::id_type const &target,
                                                                              std::uint64_t epoch = 0,
                                                                              std::chrono::steady_clock::duration
                                                                              timeout =
                                                                              std::chrono::steady_clock::duration::max())
```

Asynchronously wait, one-shot and without blocking a worker thread, and the `launch::sync_policy` overload waits synchronously until `target` reaches a terminal event (`event::completed` or `event::failed`) within `epoch`. If a terminal event has already been recorded for `target` in `epoch`, the returned future is immediately satisfied with that state. Waits are scoped to a single epoch: if `target`'s epoch advances past `epoch` before a terminal event occurs, any outstanding waiter for the stale epoch is invalidated. A waiter that reaches neither of these outcomes is bounded by `timeout` (or a built-in default if `timeout` is left at its sentinel value `std::chrono::steady_clock::duration::max()`), after which it is swept and invalidated. Dispatch is routed locally when `target`'s supervision manager lives on the calling locality, and remotely (via a registered distributed action) otherwise.

Checking dispatch admission

```
hpx::supervision::dispatch_outcome hpx::supervision::check_admission(hpx::id_type const &target,
                                                                      std::uint64_t epoch = 0)
```

Check whether `target` currently admits new dispatch under `epoch`, i.e. whether it is safe to schedule or route work to it right now. This is a pure, `noexcept` local read of the same terminal latch state consulted by `await_terminal`: it returns `dispatch_outcome::rejected_fenced` if `target` has already latched a terminal event (`event::completed` or `event::failed`) under `epoch`, and `dispatch_outcome::admitted` otherwise. Unlike `publish_result`, which reports how a publication was resolved, `dispatch_outcome` answers the separate, consumer-side question of whether dispatch should proceed; it must only be called on the locality `target` lives on.

This admission fence is scoped to a single locality's latch state: it reflects only terminal events published to the supervision manager hosting `target`, and it fails open (returns `admitted`) when `target` is unknown locally, including when its terminal event was only ever published elsewhere. There is no built-in mechanism that propagates terminal latch state across localities - observer registration delivers notifications, not admission state. Any additional locality that needs to fence its own dispatch decisions on `target` must independently mirror or route to the owning locality's state; this module does not provide that for you.

Registering activity observers

```
hpx::future<hpx::id_type> hpx::supervision::register_activity_observer(hpx::id_type const &locality,
                                                                      hpx::supervision::activity_callback
                                                                      const &callback,
                                                                      std::optional<std::uint64_t>
                                                                      epoch_filter = std::nullopt)
```

```
hpx::id_type hpx::supervision::register_activity_observer(hpx::launch::sync_policy, hpx::id_type const
&locality,
hpx::supervision::activity_callback const
&callback, std::optional<std::uint64_t>
epoch_filter = std::nullopt, hpx::error_code
&ec = hpx::throws)
```

```
hpx::id_type hpx::supervision::register_activity_observer(hpx::supervision::activity_callback const
&callback, std::optional<std::uint64_t>
epoch_filter = std::nullopt, hpx::error_code
&ec = hpx::throws)
```

Register callback to observe activity-state transitions (between `hpx::supervision::activity_state::inactive` and `active`) of *all* targets tracked by a locality's supervision manager. Unlike `register_observer`, none of these overloads take a `target` parameter: the feature reports on every target the addressed manager tracks rather than on a single one.

Registering an activity observer for an already-active target triggers a replay of its current state. The snapshot of tracked state and the insertion of the observer are performed atomically under the manager's internal lock, which guarantees exactly-once delivery: the observer receives either the replay or a live transition that raced with registration, but never both and never neither.

Note that the notification itself (replay or live) is delivered after the lock is released. Its delivery order relative to any other concurrent live notification for the same target is *not* guaranteed, only the exactly-once property is guaranteed, not relative ordering.

Activity notifications are a pure discovery/notification signal: unlike `publish_event`, registering or unregistering an activity observer never feeds the terminal latch consulted by `check_admission`.

If `epoch_filter` is set, `callback` only receives notifications - including the registration-time replay - whose epoch matches; by default it receives notifications regardless of epoch.

Unregistering activity observers

```
hpx::future<void> hpx::supervision::unregister_activity_observer(hpx::id_type const &locality,
                                                             hpx::id_type const
                                                             &observer_handle)
```

```
void hpx::supervision::unregister_activity_observer(hpx::launch::sync_policy, hpx::id_type const
                                                  &locality, hpx::id_type const &observer_handle,
                                                  hpx::error_code &ec = hpx::throws)
```

```
void hpx::supervision::unregister_activity_observer(hpx::id_type const &observer_handle,
                                                  hpx::error_code &ec = hpx::throws)
```

Unregister a previously registered activity observer. `observer_handle` must have been obtained from `register_activity_observer`; a handle obtained from `register_observer`, or any handle never returned by either registration function, is rejected.

See the *API reference* of this module for more details.

2.9 API reference

HPX follows a versioning scheme with three numbers: `major.minor.patch`. We guarantee no breaking changes in the API for patch releases. Minor releases may remove or break existing APIs, but only after a deprecation period of at least two minor releases. In rare cases do we outright remove old and unused functionality without a deprecation period.

We do not provide any ABI compatibility guarantees between any versions, debug and release builds, and builds with different C++ standards.

The public API of HPX is presented below. Clicking on a name brings you to the full documentation for the class or function. Including the header specified in a heading brings in the features listed under that heading.

Note: Names listed here are guaranteed stable with respect to semantic versioning. However, at the moment the list is incomplete and certain unlisted features are intended to be in the public API. While we work on completing the list,

if you're unsure about whether a particular unlisted name is part of the public API you can get into contact with us or open an issue and we'll clarify the situation.

2.9.1 Public API

Our API is semantically conforming; hence, the reader is highly encouraged to refer to the corresponding facility in the [C++ Standard](#)²⁶⁶ if needed. All names below are also available in the top-level `hpx` namespace unless otherwise noted. The names in `hpx` should be preferred. The names in sub-namespaces will eventually be removed.

`hpx/algorithm.hpp`

The header `hpx/algorithm.hpp`²⁶⁷ corresponds to the C++ standard library header `algorithm`²⁶⁸. See *Using parallel algorithms* for more information about the parallel algorithms.

Classes

Table 2.126: Classes of header `hpx/algorithm.hpp`

Class	C++ standard
<code>hpx::experimental::reduction</code>	N4808 ²⁶⁹
<code>hpx::experimental::induction</code>	N4808 ²⁷⁰

Functions

Table 2.127: *hpx* functions of header `hpx/algorithm.hpp`

<i>hpx</i> function	C++ standard
<code>hpx::adjacent_find</code>	std::adjacent_find ²⁷¹
<code>hpx::all_of</code>	std::all_of ²⁷²
<code>hpx::any_of</code>	std::any_of ²⁷³
<code>hpx::copy</code>	std::copy ²⁷⁴
<code>hpx::copy_if</code>	std::copy_if ²⁷⁵
<code>hpx::copy_n</code>	std::copy_n ²⁷⁶
<code>hpx::count</code>	std::count ²⁷⁷
<code>hpx::count_if</code>	std::count_if ²⁷⁸
<code>hpx::ends_with</code>	std::ends_with ²⁷⁹
<code>hpx::equal</code>	std::equal ²⁸⁰
<code>hpx::fill</code>	std::fill ²⁸¹
<code>hpx::fill_n</code>	std::fill_n ²⁸²
<code>hpx::find</code>	std::find ²⁸³
<code>hpx::find_end</code>	std::find_end ²⁸⁴
<code>hpx::find_first_of</code>	std::find_first_of ²⁸⁵

continues on next page

²⁶⁶ <https://en.cppreference.com/w/cpp/header>

²⁶⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

²⁶⁸ <http://en.cppreference.com/w/cpp/header/algorithm>

²⁶⁹ <http://wg21.link/n4808>

²⁷⁰ <http://wg21.link/n4808>

Table 2.127 – continued from previous page

<i>hpx</i> function	C++ standard
<i>hpx::find_if</i>	<code>std::find_if</code> ²⁸⁶
<i>hpx::find_if_not</i>	<code>std::find_if_not</code> ²⁸⁷
<i>hpx::for_each</i>	<code>std::for_each</code> ²⁸⁸
<i>hpx::for_each_n</i>	<code>std::for_each_n</code> ²⁸⁹
<i>hpx::generate</i>	<code>std::generate</code> ²⁹⁰
<i>hpx::generate_n</i>	<code>std::generate_n</code> ²⁹¹
<i>hpx::includes</i>	<code>std::includes</code> ²⁹²
<i>hpx::inplace_merge</i>	<code>std::inplace_merge</code> ²⁹³
<i>hpx::is_heap</i>	<code>std::is_heap</code> ²⁹⁴
<i>hpx::is_heap_until</i>	<code>std::is_heap_until</code> ²⁹⁵
<i>hpx::is_partitioned</i>	<code>std::is_partitioned</code> ²⁹⁶
<i>hpx::is_sorted</i>	<code>std::is_sorted</code> ²⁹⁷
<i>hpx::is_sorted_until</i>	<code>std::is_sorted_until</code> ²⁹⁸
<i>hpx::lexicographical_compare</i>	<code>std::lexicographical_compare</code> ²⁹⁹
<i>hpx::make_heap</i>	<code>std::make_heap</code> ³⁰⁰
<i>hpx::max_element</i>	<code>std::max_element</code> ³⁰¹
<i>hpx::merge</i>	<code>std::merge</code> ³⁰²
<i>hpx::min_element</i>	<code>std::min_element</code> ³⁰³
<i>hpx::minmax_element</i>	<code>std::minmax_element</code> ³⁰⁴
<i>hpx::mismatch</i>	<code>std::mismatch</code> ³⁰⁵
<i>hpx::move</i>	<code>std::move</code> ³⁰⁶
<i>hpx::none_of</i>	<code>std::none_of</code> ³⁰⁷
<i>hpx::nth_element</i>	<code>std::nth_element</code> ³⁰⁸
<i>hpx::partial_sort</i>	<code>std::partial_sort</code> ³⁰⁹
<i>hpx::partial_sort_copy</i>	<code>std::partial_sort_copy</code> ³¹⁰
<i>hpx::partition</i>	<code>std::partition</code> ³¹¹
<i>hpx::partition_copy</i>	<code>std::partition_copy</code> ³¹²
<i>hpx::experimental::reduce_by_key</i>	<code>reduce_by_key</code> ³¹³
<i>hpx::remove</i>	<code>std::remove</code> ³¹⁴
<i>hpx::remove_copy</i>	<code>std::remove_copy</code> ³¹⁵
<i>hpx::remove_copy_if</i>	<code>std::remove_copy_if</code> ³¹⁶
<i>hpx::remove_if</i>	<code>std::remove_if</code> ³¹⁷
<i>hpx::replace</i>	<code>std::replace</code> ³¹⁸
<i>hpx::replace_copy</i>	<code>std::replace_copy</code> ³¹⁹
<i>hpx::replace_copy_if</i>	<code>std::replace_copy_if</code> ³²⁰
<i>hpx::replace_if</i>	<code>std::replace_if</code> ³²¹
<i>hpx::reverse</i>	<code>std::reverse</code> ³²²
<i>hpx::reverse_copy</i>	<code>std::reverse_copy</code> ³²³
<i>hpx::rotate</i>	<code>std::rotate</code> ³²⁴
<i>hpx::rotate_copy</i>	<code>std::rotate_copy</code> ³²⁵
<i>hpx::search</i>	<code>std::search</code> ³²⁶
<i>hpx::search_n</i>	<code>std::search_n</code> ³²⁷
<i>hpx::set_difference</i>	<code>std::set_difference</code> ³²⁸
<i>hpx::set_intersection</i>	<code>std::set_intersection</code> ³²⁹
<i>hpx::set_symmetric_difference</i>	<code>std::set_symmetric_difference</code> ³³⁰
<i>hpx::set_union</i>	<code>std::set_union</code> ³³¹
<i>hpx::shift_left</i>	<code>std::shift_left</code> ³³²
<i>hpx::shift_right</i>	<code>std::shift_right</code> ³³³
<i>hpx::sort</i>	<code>std::sort</code> ³³⁴

continues on next page

Table 2.127 – continued from previous page

<i>hpx</i> function	C++ standard
<i>hpx::experimental::sort_by_key</i>	sort_by_key ³³⁵
<i>hpx::stable_partition</i>	std::stable_partition ³³⁶
<i>hpx::stable_sort</i>	std::stable_sort ³³⁷
<i>hpx::starts_with</i>	std::starts_with ³³⁸
<i>hpx::swap_ranges</i>	std::swap_ranges ³³⁹
<i>hpx::transform</i>	std::transform ³⁴⁰
<i>hpx::unique</i>	std::unique ³⁴¹
<i>hpx::unique_copy</i>	std::unique_copy ³⁴²
<i>hpx::experimental::for_loop</i>	N4808 ³⁴³
<i>hpx::experimental::for_loop_strided</i>	N4808 ³⁴⁴
<i>hpx::experimental::for_loop_n</i>	N4808 ³⁴⁵
<i>hpx::experimental::for_loop_n_strided</i>	N4808 ³⁴⁶

http://en.cppreference.com/w/cpp/algorithm/adjacent_find
http://en.cppreference.com/w/cpp/algorithm/all_any_none_of
http://en.cppreference.com/w/cpp/algorithm/all_any_none_of
<http://en.cppreference.com/w/cpp/algorithm/copy>
<http://en.cppreference.com/w/cpp/algorithm/copy>
http://en.cppreference.com/w/cpp/algorithm/copy_n
<http://en.cppreference.com/w/cpp/algorithm/count>
<http://en.cppreference.com/w/cpp/algorithm/count>
http://en.cppreference.com/w/cpp/algorithm/ranges/ends_with
<http://en.cppreference.com/w/cpp/algorithm/equal>
<http://en.cppreference.com/w/cpp/algorithm/fill>
http://en.cppreference.com/w/cpp/algorithm/fill_n
<http://en.cppreference.com/w/cpp/algorithm/find>
http://en.cppreference.com/w/cpp/algorithm/find_end
http://en.cppreference.com/w/cpp/algorithm/find_first_of
<http://en.cppreference.com/w/cpp/algorithm/find>
<http://en.cppreference.com/w/cpp/algorithm/find>
http://en.cppreference.com/w/cpp/algorithm/for_each
http://en.cppreference.com/w/cpp/algorithm/for_each_n
<http://en.cppreference.com/w/cpp/algorithm/generate>
http://en.cppreference.com/w/cpp/algorithm/generate_n
<http://en.cppreference.com/w/cpp/algorithm/includes>
http://en.cppreference.com/w/cpp/algorithm/inplace_merge
http://en.cppreference.com/w/cpp/algorithm/is_heap
http://en.cppreference.com/w/cpp/algorithm/is_heap_until
http://en.cppreference.com/w/cpp/algorithm/is_partitioned
http://en.cppreference.com/w/cpp/algorithm/is_sorted
http://en.cppreference.com/w/cpp/algorithm/is_sorted_until
http://en.cppreference.com/w/cpp/algorithm/lexicographical_compare
http://en.cppreference.com/w/cpp/algorithm/make_heap
http://en.cppreference.com/w/cpp/algorithm/max_element
<http://en.cppreference.com/w/cpp/algorithm/merge>
http://en.cppreference.com/w/cpp/algorithm/min_element
http://en.cppreference.com/w/cpp/algorithm/minmax_element
<http://en.cppreference.com/w/cpp/algorithm/mismatch>
<http://en.cppreference.com/w/cpp/algorithm/move>
http://en.cppreference.com/w/cpp/algorithm/all_any_none_of
http://en.cppreference.com/w/cpp/algorithm/nth_element
http://en.cppreference.com/w/cpp/algorithm/partial_sort
http://en.cppreference.com/w/cpp/algorithm/partial_sort_copy
<http://en.cppreference.com/w/cpp/algorithm/partition>
http://en.cppreference.com/w/cpp/algorithm/partition_copy
https://thrust.github.io/doc/group__reductions_gad5623f203f9b3fdcab72481c3913f0e0.html
<http://en.cppreference.com/w/cpp/algorithm/remove>
http://en.cppreference.com/w/cpp/algorithm/remove_copy
http://en.cppreference.com/w/cpp/algorithm/remove_copy
<http://en.cppreference.com/w/cpp/algorithm/remove>
<http://en.cppreference.com/w/cpp/algorithm/replace>
http://en.cppreference.com/w/cpp/algorithm/replace_copy
http://en.cppreference.com/w/cpp/algorithm/replace_copy
<http://en.cppreference.com/w/cpp/algorithm/replace>
<http://en.cppreference.com/w/cpp/algorithm/reverse>
http://en.cppreference.com/w/cpp/algorithm/reverse_copy
<http://en.cppreference.com/w/cpp/algorithm/rotate>
http://en.cppreference.com/w/cpp/algorithm/rotate_copy
<http://en.cppreference.com/w/cpp/algorithm/search>
http://en.cppreference.com/w/cpp/algorithm/search_n
http://en.cppreference.com/w/cpp/algorithm/set_difference
http://en.cppreference.com/w/cpp/algorithm/set_intersection
http://en.cppreference.com/w/cpp/algorithm/set_symmetric_difference
http://en.cppreference.com/w/cpp/algorithm/set_union
<http://en.cppreference.com/w/cpp/algorithm/shift>
<http://en.cppreference.com/w/cpp/algorithm/shift>
<http://en.cppreference.com/w/cpp/algorithm/sort>
https://thrust.github.io/doc/group__sorting_gabe038d6107f7c824cf74120500ef45ea.html
http://en.cppreference.com/w/cpp/algorithm/stable_partition
http://en.cppreference.com/w/cpp/algorithm/stable_sort
http://en.cppreference.com/w/cpp/algorithm/ranges/starts_with

2.9. API reference

http://en.cppreference.com/w/cpp/algorithm/swap_ranges
<http://en.cppreference.com/w/cpp/algorithm/transform>

<http://en.cppreference.com/w/cpp/algorithm/unique>
http://en.cppreference.com/w/cpp/algorithm/unique_copy

<http://wg21.link/n4808>
<http://wg21.link/n4808>

Table 2.128: *hpx::ranges* functions of header *hpx/algorithm.hpp*

<i>hpx::ranges</i> function	C++ standard
<i>hpx::ranges::adjacent_find</i>	<code>std::adjacent_find</code> ³⁴⁷
<i>hpx::ranges::all_of</i>	<code>std::all_of</code> ³⁴⁸
<i>hpx::ranges::any_of</i>	<code>std::any_of</code> ³⁴⁹
<i>hpx::ranges::copy</i>	<code>std::copy</code> ³⁵⁰
<i>hpx::ranges::copy_if</i>	<code>std::copy_if</code> ³⁵¹
<i>hpx::ranges::copy_n</i>	<code>std::copy_n</code> ³⁵²
<i>hpx::ranges::count</i>	<code>std::count</code> ³⁵³
<i>hpx::ranges::count_if</i>	<code>std::count_if</code> ³⁵⁴
<i>hpx::ranges::ends_with</i>	<code>std::ends_with</code> ³⁵⁵
<i>hpx::ranges::equal</i>	<code>std::equal</code> ³⁵⁶
<i>hpx::ranges::fill</i>	<code>std::fill</code> ³⁵⁷
<i>hpx::ranges::fill_n</i>	<code>std::fill_n</code> ³⁵⁸
<i>hpx::ranges::find</i>	<code>std::find</code> ³⁵⁹
<i>hpx::ranges::find_end</i>	<code>std::find_end</code> ³⁶⁰
<i>hpx::ranges::find_first_of</i>	<code>std::find_first_of</code> ³⁶¹
<i>hpx::ranges::find_if</i>	<code>std::find_if</code> ³⁶²
<i>hpx::ranges::find_if_not</i>	<code>std::find_if_not</code> ³⁶³
<i>hpx::ranges::for_each</i>	<code>std::for_each</code> ³⁶⁴
<i>hpx::ranges::for_each_n</i>	<code>std::for_each_n</code> ³⁶⁵
<i>hpx::ranges::generate</i>	<code>std::generate</code> ³⁶⁶
<i>hpx::ranges::generate_n</i>	<code>std::generate_n</code> ³⁶⁷
<i>hpx::ranges::includes</i>	<code>std::includes</code> ³⁶⁸
<i>hpx::ranges::inplace_merge</i>	<code>std::inplace_merge</code> ³⁶⁹
<i>hpx::ranges::is_heap</i>	<code>std::is_heap</code> ³⁷⁰
<i>hpx::ranges::is_heap_until</i>	<code>std::is_heap_until</code> ³⁷¹
<i>hpx::ranges::is_partitioned</i>	<code>std::is_partitioned</code> ³⁷²
<i>hpx::ranges::is_sorted</i>	<code>std::is_sorted</code> ³⁷³
<i>hpx::ranges::is_sorted_until</i>	<code>std::is_sorted_until</code> ³⁷⁴
<i>hpx::ranges::make_heap</i>	<code>std::make_heap</code> ³⁷⁵
<i>hpx::ranges::max_element</i>	<code>std::max_element</code> ³⁷⁶
<i>hpx::ranges::merge</i>	<code>std::merge</code> ³⁷⁷
<i>hpx::ranges::min_element</i>	<code>std::min_element</code> ³⁷⁸
<i>hpx::ranges::minmax_element</i>	<code>std::minmax_element</code> ³⁷⁹
<i>hpx::ranges::mismatch</i>	<code>std::mismatch</code> ³⁸⁰
<i>hpx::ranges::move</i>	<code>std::move</code> ³⁸¹
<i>hpx::ranges::none_of</i>	<code>std::none_of</code> ³⁸²
<i>hpx::ranges::nth_element</i>	<code>std::nth_element</code> ³⁸³
<i>hpx::ranges::partial_sort</i>	<code>std::partial_sort</code> ³⁸⁴
<i>hpx::ranges::partial_sort_copy</i>	<code>std::partial_sort_copy</code> ³⁸⁵
<i>hpx::ranges::partition</i>	<code>std::partition</code> ³⁸⁶
<i>hpx::ranges::partition_copy</i>	<code>std::partition_copy</code> ³⁸⁷
<i>hpx::ranges::set_difference</i>	<code>std::set_difference</code> ³⁸⁸
<i>hpx::ranges::set_intersection</i>	<code>std::set_intersection</code> ³⁸⁹
<i>hpx::ranges::set_symmetric_difference</i>	<code>std::set_symmetric_difference</code> ³⁹⁰
<i>hpx::ranges::set_union</i>	<code>std::set_union</code> ³⁹¹
<i>hpx::ranges::shift_left</i>	P2440 ³⁹²
<i>hpx::ranges::shift_right</i>	P2440 ³⁹³
<i>hpx::ranges::sort</i>	<code>std::sort</code> ³⁹⁴

continues on next page

Table 2.128 – continued from previous page

<i>hpx::ranges</i> function	C++ standard
<i>hpx::ranges::stable_partition</i>	std::stable_partition ³⁹⁵
<i>hpx::ranges::stable_sort</i>	std::stable_sort ³⁹⁶
<i>hpx::ranges::starts_with</i>	std::starts_with ³⁹⁷
<i>hpx::ranges::swap_ranges</i>	std::swap_ranges ³⁹⁸
<i>hpx::ranges::transform</i>	std::transform ³⁹⁹
<i>hpx::ranges::unique</i>	std::unique ⁴⁰⁰
<i>hpx::ranges::unique_copy</i>	std::unique_copy ⁴⁰¹
<i>hpx::ranges::experimental::for_loop</i>	N4808 ⁴⁰²
<i>hpx::ranges::experimental::for_loop_strided</i>	N4808 ⁴⁰³

hpx/any.hpp

The header `hpx/any.hpp`⁴⁰⁴ corresponds to the C++ standard library header `any`⁴⁰⁵.

`hpx::any` is compatible with `std::any`.

```
347 http://en.cppreference.com/w/cpp/algorithm/ranges/adjacent\_find
348 http://en.cppreference.com/w/cpp/algorithm/ranges/all\_any\_none\_of
349 http://en.cppreference.com/w/cpp/algorithm/ranges/all\_any\_none\_of
350 http://en.cppreference.com/w/cpp/algorithm/ranges/copy
351 http://en.cppreference.com/w/cpp/algorithm/ranges/copy
352 http://en.cppreference.com/w/cpp/algorithm/ranges/copy\_n
353 http://en.cppreference.com/w/cpp/algorithm/ranges/count
354 http://en.cppreference.com/w/cpp/algorithm/ranges/count
355 http://en.cppreference.com/w/cpp/algorithm/ranges/ends\_with
356 http://en.cppreference.com/w/cpp/algorithm/ranges/equal
357 http://en.cppreference.com/w/cpp/algorithm/ranges/fill
358 http://en.cppreference.com/w/cpp/algorithm/ranges/fill\_n
359 http://en.cppreference.com/w/cpp/algorithm/ranges/find
360 http://en.cppreference.com/w/cpp/algorithm/ranges/find\_end
361 http://en.cppreference.com/w/cpp/algorithm/ranges/find\_first\_of
362 http://en.cppreference.com/w/cpp/algorithm/ranges/find
363 http://en.cppreference.com/w/cpp/algorithm/ranges/find
364 http://en.cppreference.com/w/cpp/algorithm/ranges/for\_each
365 http://en.cppreference.com/w/cpp/algorithm/ranges/for\_each\_n
366 http://en.cppreference.com/w/cpp/algorithm/ranges/generate
367 http://en.cppreference.com/w/cpp/algorithm/ranges/generate\_n
368 http://en.cppreference.com/w/cpp/algorithm/ranges/includes
369 http://en.cppreference.com/w/cpp/algorithm/ranges/inplace\_merge
370 http://en.cppreference.com/w/cpp/algorithm/ranges/is\_heap
371 http://en.cppreference.com/w/cpp/algorithm/ranges/is\_heap\_until
372 http://en.cppreference.com/w/cpp/algorithm/ranges/is\_partitioned
373 http://en.cppreference.com/w/cpp/algorithm/ranges/is\_sorted
374 http://en.cppreference.com/w/cpp/algorithm/ranges/is\_sorted\_until
375 http://en.cppreference.com/w/cpp/algorithm/ranges/make\_heap
376 http://en.cppreference.com/w/cpp/algorithm/ranges/max\_element
377 http://en.cppreference.com/w/cpp/algorithm/ranges/merge
378 http://en.cppreference.com/w/cpp/algorithm/ranges/min\_element
379 http://en.cppreference.com/w/cpp/algorithm/ranges/minmax\_element
380 http://en.cppreference.com/w/cpp/algorithm/ranges/mismatch
381 http://en.cppreference.com/w/cpp/algorithm/ranges/move
382 http://en.cppreference.com/w/cpp/algorithm/ranges/all\_any\_none\_of
383 http://en.cppreference.com/w/cpp/algorithm/ranges/nth\_element
384 http://en.cppreference.com/w/cpp/algorithm/ranges/partial\_sort
385 http://en.cppreference.com/w/cpp/algorithm/ranges/partial\_sort\_copy
386 http://en.cppreference.com/w/cpp/algorithm/ranges/partition
387 http://en.cppreference.com/w/cpp/algorithm/ranges/partition\_copy
388 http://en.cppreference.com/w/cpp/algorithm/ranges/set\_difference
389 http://en.cppreference.com/w/cpp/algorithm/ranges/set\_intersection
390 http://en.cppreference.com/w/cpp/algorithm/ranges/set\_symmetric\_difference
391 http://en.cppreference.com/w/cpp/algorithm/ranges/set\_union
392 https://wg21.link/p2440
393 https://wg21.link/p2440
394 http://en.cppreference.com/w/cpp/algorithm/ranges/sort
395 http://en.cppreference.com/w/cpp/algorithm/ranges/stable\_partition
396 http://en.cppreference.com/w/cpp/algorithm/ranges/stable\_sort
397 http://en.cppreference.com/w/cpp/algorithm/ranges/starts\_with
398 http://en.cppreference.com/w/cpp/algorithm/ranges/swap\_ranges
399 http://en.cppreference.com/w/cpp/algorithm/ranges/transform
400 http://en.cppreference.com/w/cpp/algorithm/ranges/unique
401 http://en.cppreference.com/w/cpp/algorithm/ranges/unique\_copy
402 http://wg21.link/n4808
403 http://wg21.link/n4808
404 http://github.com/TheHPXProject/hpx/blob/5425060950dc6db4f0999faf6e63fc2337be393/libs/core/include\_local/include/hpx/any.hpp
405 http://en.cppreference.com/w/cpp/header/any
```

Classes

Table 2.129: Classes of header `hpx/any.hpp`

Class	C++ standard
<code>hpx::any</code>	std::any ⁴⁰⁶
<code>hpx::any_noser</code>	
<code>hpx::bad_any_cast</code>	std::bad_any_cast ⁴⁰⁷
<code>hpx::unique_any_noser</code>	

Functions

Table 2.130: Functions of header `hpx/any.hpp`

Function	C++ standard
<code>hpx::any_cast</code>	std::any_cast ⁴⁰⁸
<code>hpx::make_any</code>	std::make_any ⁴⁰⁹
<code>hpx::make_any_noser</code>	
<code>hpx::make_unique_any_noser</code>	

`hpx/assert.hpp`

The header `hpx/assert.hpp`⁴¹⁰ corresponds to the C++ standard library header `cassert`⁴¹¹.

`HPX_ASSERT` is the *HPX* equivalent to `assert` in `cassert`. `HPX_ASSERT` can also be used in CUDA device code.

Macros

Table 2.131: Macros of header `hpx/assert.hpp`

Macro
<code>HPX_ASSERT</code>
<code>HPX_ASSERT_MSG</code>

⁴⁰⁶ <http://en.cppreference.com/w/cpp/utility/any>

⁴⁰⁷ http://en.cppreference.com/w/cpp/utility/any/bad_any_cast

⁴⁰⁸ http://en.cppreference.com/w/cpp/utility/any/any_cast

⁴⁰⁹ http://en.cppreference.com/w/cpp/utility/any/make_any

⁴¹⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/assertion/include/hpx/assert.hpp>

⁴¹¹ <http://en.cppreference.com/w/cpp/header/cassert>

hpx/barrier.hpp

The header `hpx/barrier.hpp`⁴¹² corresponds to the C++ standard library header `barrier`⁴¹³ and contains a distributed barrier implementation. This functionality is also exposed through the `hpx::distributed` namespace. The name in `hpx::distributed` should be preferred.

Classes

Table 2.132: Classes of header `hpx/barrier.hpp`

Class	C++ standard
<code>hpx::barrier</code>	<code>std::barrier</code> ⁴¹⁴

Table 2.133: Distributed implementation of classes of header `hpx/barrier.hpp`

Class
<code>hpx::distributed::barrier</code>

hpx/channel.hpp

The header `hpx/channel.hpp`⁴¹⁵ contains a local and a distributed channel implementation. This functionality is also exposed through the `hpx::distributed` namespace. The name in `hpx::distributed` should be preferred.

Classes

Table 2.134: Classes of header `hpx/channel.hpp`

Class
<code>hpx::channel</code>

Table 2.135: Distributed implementation of classes of header `hpx/channel.hpp`

Class
<code>hpx::distributed::channel</code>

⁴¹² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/barrier.hpp>

⁴¹³ <http://en.cppreference.com/w/cpp/header/barrier>

⁴¹⁴ <http://en.cppreference.com/w/cpp/thread/barrier>

⁴¹⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/channel.hpp>

hpx/chrono.hpp

The header `hpx/chrono.hpp`⁴¹⁶ corresponds to the C++ standard library header `chrono`⁴¹⁷. The following replacements and extensions are provided compared to `chrono`⁴¹⁸.

Classes

Table 2.136: Classes of header `hpx/chrono.hpp`

Class	C++ standard
<code>hpx::chrono::high_resolution_clock</code>	<code>std::high_resolution_clock</code> ⁴¹⁹
<code>hpx::chrono::high_resolution_timer</code>	
<code>hpx::chrono::steady_time_point</code>	<code>std::time_point</code> ⁴²⁰

hpx/condition_variable.hpp

The header `hpx/condition_variable.hpp`⁴²¹ corresponds to the C++ standard library header `condition_variable`⁴²².

Classes

Table 2.137: Classes of header `hpx/condition_variable.hpp`

Class	C++ standard
<code>hpx::condition_variable</code>	<code>std::condition_variable</code> ⁴²³
<code>hpx::condition_variable_any</code>	<code>std::condition_variable_any</code> ⁴²⁴
<code>hpx::cv_status</code>	<code>std::cv_status</code> ⁴²⁵

hpx/exception.hpp

The header `hpx/exception.hpp`⁴²⁶ corresponds to the C++ standard library header `exception`⁴²⁷. `hpx::exception` extends `std::exception` and is the base class for all exceptions thrown in *HPX*. `HPX_THROW_EXCEPTION` can be used to throw *HPX* exceptions with file and line information attached to the exception.

⁴¹⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/chrono.hpp

⁴¹⁷ <http://en.cppreference.com/w/cpp/header/chrono>

⁴¹⁸ <http://en.cppreference.com/w/cpp/header/chrono>

⁴¹⁹ http://en.cppreference.com/w/cpp/chrono/high_resolution_clock

⁴²⁰ http://en.cppreference.com/w/cpp/chrono/time_point

⁴²¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/condition_variable.hpp

⁴²² http://en.cppreference.com/w/cpp/header/condition_variable

⁴²³ http://en.cppreference.com/w/cpp/thread/condition_variable

⁴²⁴ http://en.cppreference.com/w/cpp/thread/condition_variable_any

⁴²⁵ http://en.cppreference.com/w/cpp/thread/cv_status

⁴²⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/exception.hpp

⁴²⁷ <http://en.cppreference.com/w/cpp/header/exception>

Macros

- `HPX_THROW_EXCEPTION`

Classes

Table 2.138: Classes of header `hpx/exception.hpp`

Class	C++ standard
<code>hpx::exception</code>	<code>std::exception</code> ⁴²⁸

`hpx/execution.hpp`

The header `hpx/execution.hpp`⁴²⁹ corresponds to the C++ standard library header `execution`⁴³⁰. See *High level parallel facilities*, *Using parallel algorithms* and *Executor parameters and executor parameter traits* for more information about execution policies and executor parameters.

Note: These names are only available in the `hpx::execution` namespace, not in the top-level `hpx` namespace.

Constants

Table 2.139: Constants of header `hpx/execution.hpp`

Constant	C++ standard
<code>hpx::execution::seq</code>	<code>std::execution_policy_tag</code> ⁴³¹
<code>hpx::execution::par</code>	<code>std::execution_policy_tag</code> ⁴³²
<code>hpx::execution::par_unseq</code>	<code>std::execution_policy_tag</code> ⁴³³
<code>hpx::execution::task</code>	

⁴²⁸ <http://en.cppreference.com/w/cpp/error/exception>

⁴²⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

⁴³⁰ <http://en.cppreference.com/w/cpp/header/execution>

⁴³¹ http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag

⁴³² http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag

⁴³³ http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag

Classes

Table 2.140: Classes of header `hpx/execution.hpp`

Class	C++ standard
<code>hpx::execution::sequenced_policy</code>	<code>std::execution_policy_tag_t</code> ⁴³⁴
<code>hpx::execution::parallel_policy</code>	<code>std::execution_policy_tag_t</code> ⁴³⁵
<code>hpx::execution::parallel_unsequenced_policy</code>	<code>std::execution_policy_tag_t</code> ⁴³⁶
<code>hpx::execution::sequenced_task_policy</code>	
<code>hpx::execution::parallel_task_policy</code>	
<code>hpx::execution::experimental::auto_chunk_size</code>	
<code>hpx::execution::experimental::dynamic_chunk_size</code>	
<code>hpx::execution::experimental::guided_chunk_size</code>	
<code>hpx::execution::experimental::persistent_auto_chunk_size</code>	
<code>hpx::execution::experimental::static_chunk_size</code>	
<code>hpx::execution::experimental::num_cores</code>	

`hpx/functional.hpp`

The header `hpx/functional.hpp`⁴³⁷ corresponds to the C++ standard library header `functional`⁴³⁸. `hpx::function` is a more efficient and serializable replacement for `std::function`.

Constants

The following constants correspond to the C++ standard `std::placeholders`⁴³⁹

Table 2.141: Constants of header `hpx/functional.hpp`

Constant
<code>hpx::placeholders::_1</code>
<code>hpx::placeholders::_2</code>
...
<code>hpx::placeholders::_9</code>

⁴³⁴ http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag_t

⁴³⁵ http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag_t

⁴³⁶ http://en.cppreference.com/w/cpp/algorithm/execution_policy_tag_t

⁴³⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

⁴³⁸ <http://en.cppreference.com/w/cpp/header/functional>

⁴³⁹ <http://en.cppreference.com/w/cpp/utility/functional/placeholders>

Classes

Table 2.142: Classes of header `hpx/functional.hpp`

Class	C++ standard
<code>hpx::function</code>	<code>std::function</code> ⁴⁴⁰
<code>hpx::function_ref</code>	P0792 ⁴⁴¹
<code>hpx::move_only_function</code>	<code>std::move_only_function</code> ⁴⁴²
<code>hpx::is_bind_expression</code>	<code>std::is_bind_expression</code> ⁴⁴³
<code>hpx::is_placeholder</code>	<code>std::is_placeholder</code> ⁴⁴⁴
<code>hpx::scoped_annotation</code>	

Functions

Table 2.143: Functions of header `hpx/functional.hpp`

Function	C++ standard
<code>hpx::annotated_function</code>	
<code>hpx::bind</code>	<code>std::bind</code> ⁴⁴⁵
<code>hpx::bind_back</code>	<code>std::bind_front</code> ⁴⁴⁶
<code>hpx::bind_front</code>	<code>std::bind_front</code> ⁴⁴⁷
<code>hpx::invoke</code>	<code>std::invoke</code> ⁴⁴⁸
<code>hpx::invoke_fused</code>	<code>std::apply</code> ⁴⁴⁹
<code>hpx::invoke_fused_r</code>	
<code>hpx::mem_fn</code>	<code>std::mem_fn</code> ⁴⁵⁰

`hpx/future.hpp`

The header `hpx/future.hpp`⁴⁵¹ corresponds to the C++ standard library header `future`⁴⁵². See *Extended facilities for futures* for more information about extensions to futures compared to the C++ standard library.

This header file also contains overloads of `hpx::async`, `hpx::post`, `hpx::sync`, and `hpx::dataflow` that can be used with actions. See *Action invocation* for more information about invoking actions.

⁴⁴⁰ <http://en.cppreference.com/w/cpp/utility/functional/function>

⁴⁴¹ <http://wg21.link/p0792>

⁴⁴² http://en.cppreference.com/w/cpp/utility/functional/move_only_function

⁴⁴³ http://en.cppreference.com/w/cpp/utility/functional/is_bind_expression

⁴⁴⁴ http://en.cppreference.com/w/cpp/utility/functional/is_placeholder

⁴⁴⁵ <http://en.cppreference.com/w/cpp/utility/functional/bind>

⁴⁴⁶ http://en.cppreference.com/w/cpp/utility/functional/bind_front

⁴⁴⁷ http://en.cppreference.com/w/cpp/utility/functional/bind_front

⁴⁴⁸ <http://en.cppreference.com/w/cpp/utility/functional/invoke>

⁴⁴⁹ <http://en.cppreference.com/w/cpp/utility/apply>

⁴⁵⁰ http://en.cppreference.com/w/cpp/utility/functional/mem_fn

⁴⁵¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁴⁵² <http://en.cppreference.com/w/cpp/header/future>

Classes

Table 2.144: Classes of header `hpx/future.hpp`

Class	C++ standard
<code>hpx::future</code>	<code>std::future</code> ⁴⁵³
<code>hpx::shared_future</code>	<code>std::shared_future</code> ⁴⁵⁴
<code>hpx::promise</code>	<code>std::promise</code> ⁴⁵⁵
<code>hpx::launch</code>	<code>std::launch</code> ⁴⁵⁶
<code>hpx::packaged_task</code>	<code>std::packaged_task</code> ⁴⁵⁷

Note: All names except `hpx::promise` are also available in the top-level `hpx` namespace. `hpx::promise` refers to `hpx::distributed::promise`, a distributed variant of `hpx::promise`, but will eventually refer to `hpx::promise` after a deprecation period.

Table 2.145: Distributed implementation of classes of header `hpx/future.hpp`

Class
<code>hpx::distributed::promise</code>

Functions

Table 2.146: Functions of header `hpx/future.hpp`

Function	C++ standard
<code>hpx::async</code>	<code>std::async</code> ⁴⁵⁸
<code>hpx::post</code>	
<code>hpx::sync</code>	
<code>hpx::dataflow</code>	
<code>hpx::make_future</code>	
<code>hpx::make_shared_future</code>	
<code>hpx::make_ready_future</code>	P0159 ⁴⁵⁹
<code>hpx::make_ready_future_alloc</code>	
<code>hpx::make_ready_future_at</code>	
<code>hpx::make_ready_future_after</code>	
<code>hpx::make_exceptional_future</code>	P0159 ⁴⁶⁰
<code>hpx::when_all</code>	P0159 ⁴⁶¹
<code>hpx::when_any</code>	P0159 ⁴⁶²
<code>hpx::when_some</code>	
<code>hpx::when_each</code>	
<code>hpx::wait_all</code>	
<code>hpx::wait_any</code>	
<code>hpx::wait_some</code>	
<code>hpx::wait_each</code>	

⁴⁵³ <http://en.cppreference.com/w/cpp/thread/future>

⁴⁵⁴ http://en.cppreference.com/w/cpp/thread/shared_future

⁴⁵⁵ <http://en.cppreference.com/w/cpp/thread/promise>

⁴⁵⁶ <http://en.cppreference.com/w/cpp/thread/launch>

⁴⁵⁷ http://en.cppreference.com/w/cpp/thread/packaged_task

hpx/init.hpp

The header `hpx/init.hpp`⁴⁶³ contains functionality for starting, stopping, suspending, and resuming the *HPX* runtime. This is the main way to explicitly start the *HPX* runtime. See *Starting the HPX runtime* for more details on starting the *HPX* runtime.

Classes

Table 2.147: Classes of header `hpx/init.hpp`

Class
<code>hpx::init_params</code>
<code>hpx::runtime_mode</code>

Functions

Table 2.148: Functions of header `hpx/init.hpp`

Function
<code>hpx::init</code>
<code>hpx::start</code>
<code>hpx::finalize</code>
<code>hpx::disconnect</code>
<code>hpx::suspend</code>
<code>hpx::resume</code>

hpx/latch.hpp

The header `hpx/latch.hpp`⁴⁶⁴ corresponds to the C++ standard library header `latch`⁴⁶⁵. It contains a local and a distributed latch implementation. This functionality is also exposed through the `hpx::distributed` namespace. The name in `hpx::distributed` should be preferred.

Classes

Table 2.149: Classes of header `hpx/latch.hpp`

Class	C++ standard
<code>hpx::latch</code>	<code>std::latch</code> ⁴⁶⁶

⁴⁵⁸ <http://en.cppreference.com/w/cpp/thread/async>

⁴⁵⁹ <http://wg21.link/p0159>

⁴⁶⁰ <http://wg21.link/p0159>

⁴⁶¹ <http://wg21.link/p0159>

⁴⁶² <http://wg21.link/p0159>

⁴⁶³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/init_runtime/include/hpx/init.hpp

⁴⁶⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/latch.hpp>

⁴⁶⁵ <http://en.cppreference.com/w/cpp/header/latch>

⁴⁶⁶ <http://en.cppreference.com/w/cpp/thread/latch>

Table 2.150: Distributed implementation of classes of header `hpx/latch.hpp`

Class
<code>hpx::distributed::latch</code>

`hpx/mutex.hpp`

The header `hpx/mutex.hpp`⁴⁶⁷ corresponds to the C++ standard library header `mutex`⁴⁶⁸.

Classes

Table 2.151: Classes of header `hpx/mutex.hpp`

Class	C++ standard
<code>hpx::mutex</code>	<code>std::mutex</code> ⁴⁶⁹
<code>hpx::no_mutex</code>	
<code>hpx::once_flag</code>	<code>std::once_flag</code> ⁴⁷⁰
<code>hpx::recursive_mutex</code>	<code>std::recursive_mutex</code> ⁴⁷¹
<code>hpx::spinlock</code>	
<code>hpx::timed_mutex</code>	<code>std::timed_mutex</code> ⁴⁷²
<code>hpx::unlock_guard</code>	

Functions

Table 2.152: Functions of header `hpx/mutex.hpp`

Class	C++ standard
<code>hpx::call_once</code>	<code>std::call_once</code> ⁴⁷³

`hpx/memory.hpp`

The header `hpx/memory.hpp`⁴⁷⁴ corresponds to the C++ standard library header `memory`⁴⁷⁵. It contains parallel versions of the copy, fill, move, and construct helper functions in `memory`⁴⁷⁶. See *Using parallel algorithms* for more information about the parallel algorithms.

⁴⁶⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/mutex.hpp

⁴⁶⁸ <http://en.cppreference.com/w/cpp/header/mutex>

⁴⁶⁹ <http://en.cppreference.com/w/cpp/thread/mutex>

⁴⁷⁰ http://en.cppreference.com/w/cpp/thread/once_flag

⁴⁷¹ http://en.cppreference.com/w/cpp/thread/recursive_mutex

⁴⁷² http://en.cppreference.com/w/cpp/thread/timed_mutex

⁴⁷³ http://en.cppreference.com/w/cpp/thread/call_once

⁴⁷⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/memory.hpp

⁴⁷⁵ <http://en.cppreference.com/w/cpp/header/memory>

⁴⁷⁶ <http://en.cppreference.com/w/cpp/header/memory>

Functions

Table 2.153: *hpx* functions of header *hpx/memory.hpp*

<i>hpx</i> function	C++ standard
<i>hpx::uninitialized_copy</i>	<code>std::uninitialized_copy</code> ⁴⁷⁷
<i>hpx::uninitialized_copy_n</i>	<code>std::uninitialized_copy_n</code> ⁴⁷⁸
<i>hpx::uninitialized_default_construct</i>	<code>std::uninitialized_default_construct</code> ⁴⁷⁹
<i>hpx::uninitialized_default_construct_n</i>	<code>std::uninitialized_default_construct_n</code> ⁴⁸⁰
<i>hpx::uninitialized_fill</i>	<code>std::uninitialized_fill</code> ⁴⁸¹
<i>hpx::uninitialized_fill_n</i>	<code>std::uninitialized_fill_n</code> ⁴⁸²
<i>hpx::uninitialized_move</i>	<code>std::uninitialized_move</code> ⁴⁸³
<i>hpx::uninitialized_move_n</i>	<code>std::uninitialized_move_n</code> ⁴⁸⁴
<i>hpx::uninitialized_value_construct</i>	<code>std::uninitialized_value_construct</code> ⁴⁸⁵
<i>hpx::uninitialized_value_construct_n</i>	<code>std::uninitialized_value_construct_n</code> ⁴⁸⁶

Table 2.154: *hpx::ranges* functions of header *hpx/memory.hpp*

<i>hpx::ranges</i> function	C++ standard
<i>hpx::ranges::uninitialized_copy</i>	<code>std::uninitialized_copy</code> ⁴⁸⁷
<i>hpx::ranges::uninitialized_copy_n</i>	<code>std::uninitialized_copy_n</code> ⁴⁸⁸
<i>hpx::ranges::uninitialized_default_construct</i>	<code>std::uninitialized_default_construct</code> ⁴⁸⁹
<i>hpx::ranges::uninitialized_default_construct_n</i>	<code>std::uninitialized_default_construct_n</code> ⁴⁹⁰
<i>hpx::ranges::uninitialized_fill</i>	<code>std::uninitialized_fill</code> ⁴⁹¹
<i>hpx::ranges::uninitialized_fill_n</i>	<code>std::uninitialized_fill_n</code> ⁴⁹²
<i>hpx::ranges::uninitialized_move</i>	<code>std::uninitialized_move</code> ⁴⁹³
<i>hpx::ranges::uninitialized_move_n</i>	<code>std::uninitialized_move_n</code> ⁴⁹⁴
<i>hpx::ranges::uninitialized_value_construct</i>	<code>std::uninitialized_value_construct</code> ⁴⁹⁵
<i>hpx::ranges::uninitialized_value_construct_n</i>	<code>std::uninitialized_value_construct_n</code> ⁴⁹⁶

⁴⁷⁷ http://en.cppreference.com/w/cpp/memory/uninitialized_copy⁴⁷⁸ http://en.cppreference.com/w/cpp/memory/uninitialized_copy_n⁴⁷⁹ http://en.cppreference.com/w/cpp/memory/uninitialized_default_construct⁴⁸⁰ http://en.cppreference.com/w/cpp/memory/uninitialized_default_construct_n⁴⁸¹ http://en.cppreference.com/w/cpp/memory/uninitialized_fill⁴⁸² http://en.cppreference.com/w/cpp/memory/uninitialized_fill_n⁴⁸³ http://en.cppreference.com/w/cpp/memory/uninitialized_move⁴⁸⁴ http://en.cppreference.com/w/cpp/memory/uninitialized_move_n⁴⁸⁵ http://en.cppreference.com/w/cpp/memory/uninitialized_value_construct⁴⁸⁶ http://en.cppreference.com/w/cpp/memory/uninitialized_value_construct_n⁴⁸⁷ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_copy⁴⁸⁸ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_copy_n⁴⁸⁹ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_default_construct⁴⁹⁰ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_default_construct_n⁴⁹¹ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_fill⁴⁹² http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_fill_n⁴⁹³ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_move⁴⁹⁴ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_move_n⁴⁹⁵ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_value_construct⁴⁹⁶ http://en.cppreference.com/w/cpp/memory/ranges/uninitialized_value_construct_n

hpx/numeric.hpp

The header `hpx/numeric.hpp`⁴⁹⁷ corresponds to the C++ standard library header `numeric`⁴⁹⁸. See *Using parallel algorithms* for more information about the parallel algorithms.

Functions

Table 2.155: *hpx* functions of header `hpx/numeric.hpp`

<i>hpx</i> function	C++ standard
<code>hpx::adjacent_difference</code>	<code>std::adjacent_difference</code> ⁴⁹⁹
<code>hpx::exclusive_scan</code>	<code>std::exclusive_scan</code> ⁵⁰⁰
<code>hpx::inclusive_scan</code>	<code>std::inclusive_scan</code> ⁵⁰¹
<code>hpx::reduce</code>	<code>std::reduce</code> ⁵⁰²
<code>hpx::transform_exclusive_scan</code>	<code>std::transform_exclusive_scan</code> ⁵⁰³
<code>hpx::transform_inclusive_scan</code>	<code>std::transform_inclusive_scan</code> ⁵⁰⁴
<code>hpx::transform_reduce</code>	<code>std::transform_reduce</code> ⁵⁰⁵

Table 2.156: *hpx::ranges* functions of header `hpx/numeric.hpp`

<i>hpx::ranges</i> function
<code>hpx::ranges::adjacent_difference</code>
<code>hpx::ranges::exclusive_scan</code>
<code>hpx::ranges::inclusive_scan</code>
<code>hpx::ranges::reduce</code>
<code>hpx::ranges::transform_exclusive_scan</code>
<code>hpx::ranges::transform_inclusive_scan</code>
<code>hpx::ranges::transform_reduce</code>

hpx/optional.hpp

The header `hpx/optional.hpp`⁵⁰⁶ corresponds to the C++ standard library header `optional`⁵⁰⁷. `hpx::optional` is compatible with `std::optional`.

⁴⁹⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/numeric.hpp

⁴⁹⁸ <http://en.cppreference.com/w/cpp/header/numeric>

⁴⁹⁹ http://en.cppreference.com/w/cpp/algorithm/adjacent_difference

⁵⁰⁰ http://en.cppreference.com/w/cpp/algorithm/exclusive_scan

⁵⁰¹ http://en.cppreference.com/w/cpp/algorithm/inclusive_scan

⁵⁰² <http://en.cppreference.com/w/cpp/algorithm/reduce>

⁵⁰³ http://en.cppreference.com/w/cpp/algorithm/transform_exclusive_scan

⁵⁰⁴ http://en.cppreference.com/w/cpp/algorithm/transform_inclusive_scan

⁵⁰⁵ http://en.cppreference.com/w/cpp/algorithm/transform_reduce

⁵⁰⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/optional.hpp

⁵⁰⁷ <http://en.cppreference.com/w/cpp/header/optional>

Constants

- `hpx::nullopt`

Classes

Table 2.157: Classes of header `hpx/optional.hpp`

Class	C++ standard
<code>hpx::optional</code>	<code>std::optional</code> ⁵⁰⁸
<code>hpx::nullopt_t</code>	<code>std::nullopt_t</code> ⁵⁰⁹
<code>hpx::bad_optional_access</code>	<code>std::bad_optional_access</code> ⁵¹⁰

`hpx/runtime.hpp`

The header `hpx/runtime.hpp`⁵¹¹ contains functions for accessing local and distributed runtime information.

Typedefs

Table 2.158: Typedefs of header `hpx/runtime.hpp`

Typedef
<code>hpx::startup_function_type</code>
<code>hpx::shutdown_function_type</code>

Functions

Table 2.159: Functions of header `hpx/runtime.hpp`

Function
<code>hpx::find_root_locality</code>
<code>hpx::find_all_localities</code>
<code>hpx::find_remote_localities</code>
<code>hpx::find_locality</code>
<code>hpx::get_colocation_id</code>
<code>hpx::get_locality_id</code>
<code>hpx::get_num_worker_threads</code>
<code>hpx::get_worker_thread_num</code>
<code>hpx::get_thread_name</code>
<code>hpx::register_pre_startup_function</code>
<code>hpx::register_startup_function</code>
<code>hpx::register_pre_shutdown_function</code>
<code>hpx::register_shutdown_function</code>
<code>hpx::get_num_localities</code>
<code>hpx::get_locality_name</code>

⁵⁰⁸ <http://en.cppreference.com/w/cpp/utility/optional>

⁵⁰⁹ http://en.cppreference.com/w/cpp/utility/nullopt_t

⁵¹⁰ http://en.cppreference.com/w/cpp/utility/optional/bad_optional_access

⁵¹¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

hpx/experimental/scope.hpp

The header `hpx/experimental/scope.hpp`⁵¹² corresponds to the C++ standard library header `experimental/scope`⁵¹³.

Classes

Table 2.160: Classes of header `hpx/scope.hpp`

Class	C++ standard
<code>hpx::experimental::scope_exit</code>	<code>std::scope_exit</code> ⁵¹⁴
<code>hpx::experimental::scope_fail</code>	<code>std::scope_fail</code> ⁵¹⁵
<code>hpx::experimental::scope_success</code>	<code>std::scope_success</code> ⁵¹⁶

hpx/semaphore.hpp

The header `hpx/semaphore.hpp`⁵¹⁷ corresponds to the C++ standard library header `semaphore`⁵¹⁸.

Classes

Table 2.161: Classes of header `hpx/semaphore.hpp`

Class	C++ standard
<code>hpx::binary_semaphore</code>	<code>std::counting_semaphore</code> ⁵¹⁹
<code>hpx::counting_semaphore</code>	<code>std::counting_semaphore</code> ⁵²⁰

hpx/shared_mutex.hpp

The header `hpx/shared_mutex.hpp`⁵²¹ corresponds to the C++ standard library header `shared_mutex`⁵²².

⁵¹² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/experimental/scope.hpp

⁵¹³ <http://en.cppreference.com/w/cpp/header/experimental/scope>

⁵¹⁴ http://en.cppreference.com/w/cpp/experimental/scope_exit

⁵¹⁵ http://en.cppreference.com/w/cpp/experimental/scope_fail

⁵¹⁶ http://en.cppreference.com/w/cpp/experimental/scope_success

⁵¹⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/semaphore.hpp

⁵¹⁸ <http://en.cppreference.com/w/cpp/header/semaphore>

⁵¹⁹ http://en.cppreference.com/w/cpp/thread/counting_semaphore

⁵²⁰ http://en.cppreference.com/w/cpp/thread/counting_semaphore

⁵²¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/shared_mutex.hpp

⁵²² http://en.cppreference.com/w/cpp/header/shared_mutex

Classes

Table 2.162: Classes of header `hpx/shared_mutex.hpp`

Class	C++ standard
<code>hpx::shared_mutex</code>	<code>std::shared_mutex</code> ⁵²³

`hpx/source_location.hpp`

The header `hpx/source_location.hpp`⁵²⁴ corresponds to the C++ standard library header `source_location`⁵²⁵.

Classes

Table 2.163: Classes of header `hpx/system_error.hpp`

Class	C++ standard
<code>hpx::source_location</code>	<code>std::source_location</code> ⁵²⁶

`hpx/stop_token.hpp`

The header `hpx/stop_token.hpp`⁵²⁷ corresponds to the C++ standard library header `stop_token`⁵²⁸.

Constants

Table 2.164: Constants of header `hpx/stop_token.hpp`

Constant	C++ standard
<code>hpx::nostopstate</code>	<code>std::nostopstate</code> ⁵²⁹

Classes

Table 2.165: Classes of header `hpx/stop_token.hpp`

Class	C++ standard
<code>hpx::stop_callback</code>	<code>std::stop_callback</code> ⁵³⁰
<code>hpx::stop_source</code>	<code>std::stop_source</code> ⁵³¹
<code>hpx::stop_token</code>	<code>std::stop_token</code> ⁵³²
<code>hpx::nostopstate_t</code>	<code>std::nostopstate_t</code> ⁵³³

⁵²³ http://en.cppreference.com/w/cpp/thread/shared_mutex

⁵²⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/source_location.hpp

⁵²⁵ http://en.cppreference.com/w/cpp/header/source_location

⁵²⁶ http://en.cppreference.com/w/cpp/utility/source_location

⁵²⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/stop_token.hpp

⁵²⁸ http://en.cppreference.com/w/cpp/header/stop_token

⁵²⁹ http://en.cppreference.com/w/cpp/thread/stop_source/nostopstate

hpx/system_error.hpp

The header `hpx/system_error.hpp`⁵³⁴ corresponds to the C++ standard library header `system_error`⁵³⁵.

Classes

Table 2.166: Classes of header `hpx/system_error.hpp`

Class	C++ standard
<i>hpx::error_code</i>	<i>std::error_code</i> ⁵³⁶

hpx/task_block.hpp

The header `hpx/task_block.hpp`⁵³⁷ corresponds to the `task_block` feature in N4755⁵³⁸. See `using_task_block` for more details on using task blocks.

Classes

Table 2.167: Classes of header `hpx/task_block.hpp`

Class
<i>hpx::experimental::task_canceled_exception</i>
<i>hpx::experimental::task_block</i>

Functions

Table 2.168: Functions of header `hpx/task_block.hpp`

Function
<i>hpx::experimental::define_task_block</i>
<i>hpx::experimental::define_task_block_restore_thread</i>

⁵³⁰ http://en.cppreference.com/w/cpp/thread/stop_callback

⁵³¹ http://en.cppreference.com/w/cpp/thread/stop_source

⁵³² http://en.cppreference.com/w/cpp/thread/stop_token

⁵³³ http://en.cppreference.com/w/cpp/thread/stop_source/nostopstate_t

⁵³⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/system_error.hpp

⁵³⁵ http://en.cppreference.com/w/cpp/header/system_error

⁵³⁶ http://en.cppreference.com/w/cpp/error/error_code

⁵³⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/task_block.hpp

⁵³⁸ <http://wg21.link/n4755>

hpx/experimental/task_group.hpp

The header `hpx/experimental/task_group.hpp`⁵³⁹ corresponds to the `task_group` feature in oneAPI Threading Building Blocks (oneTBB)⁵⁴⁰.

Classes

Table 2.169: Classes of header `hpx/experimental/task_group.hpp`

Class
<code>hpx::experimental::task_group</code>

hpx/thread.hpp

The header `hpx/thread.hpp`⁵⁴¹ corresponds to the C++ standard library header `thread`⁵⁴². The functionality in this header is equivalent to the standard library thread functionality, with the exception that the *HPX* equivalents are implemented on top of lightweight threads and the *HPX* runtime.

Classes

Table 2.170: Classes of header `hpx/thread.hpp`

Class	C++ standard
<code>hpx::thread</code>	<code>std::thread</code> ⁵⁴³
<code>hpx::jthread</code>	<code>std::jthread</code> ⁵⁴⁴

Functions

Table 2.171: Functions of header `hpx/thread.hpp`

Function	C++ standard
<code>hpx::this_thread::yield</code>	<code>std::yield</code> ⁵⁴⁵
<code>hpx::this_thread::get_id</code>	<code>std::get_id</code> ⁵⁴⁶
<code>hpx::this_thread::sleep_for</code>	<code>std::sleep_for</code> ⁵⁴⁷
<code>hpx::this_thread::sleep_until</code>	<code>std::sleep_until</code> ⁵⁴⁸

⁵³⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/experimental/task_group.hpp

⁵⁴⁰ https://spec.oneapi.io/versions/1.0-rev-3/elements/oneTBB/source/task_scheduler/task_group/task_group_cls.html

⁵⁴¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/thread.hpp

⁵⁴² <http://en.cppreference.com/w/cpp/header/thread>

⁵⁴³ <http://en.cppreference.com/w/cpp/thread/thread>

⁵⁴⁴ <http://en.cppreference.com/w/cpp/thread/jthread>

⁵⁴⁵ <http://en.cppreference.com/w/cpp/thread/yield>

⁵⁴⁶ http://en.cppreference.com/w/cpp/thread/get_id

⁵⁴⁷ http://en.cppreference.com/w/cpp/thread/sleep_for

⁵⁴⁸ http://en.cppreference.com/w/cpp/thread/sleep_until

hpx/tuple.hpp

The header `hpx/tuple.hpp`⁵⁴⁹ corresponds to the C++ standard library header `tuple`⁵⁵⁰. `hpx::tuple` can be used in CUDA device code, unlike `std::tuple`.

Constants

Table 2.172: Constants of header `hpx/tuple.hpp`

Constant	C++ standard
<code>hpx::ignore</code>	<code>std::ignore</code> ⁵⁵¹

Classes

Table 2.173: Classes of header `hpx/tuple.hpp`

Class	C++ standard
<code>hpx::tuple</code>	<code>std::tuple</code> ⁵⁵²
<code>hpx::tuple_size</code>	<code>std::tuple_size</code> ⁵⁵³
<code>hpx::tuple_element</code>	<code>std::tuple_element</code> ⁵⁵⁴

Functions

Table 2.174: Functions of header `hpx/tuple.hpp`

Function	C++ standard
<code>hpx::make_tuple</code>	<code>std::tuple_element</code> ⁵⁵⁵
<code>hpx::tie</code>	<code>std::tie</code> ⁵⁵⁶
<code>hpx::forward_as_tuple</code>	<code>std::forward_as_tuple</code> ⁵⁵⁷
<code>hpx::tuple_cat</code>	<code>std::tuple_cat</code> ⁵⁵⁸
<code>hpx::get</code>	<code>std::get</code> ⁵⁵⁹

⁵⁴⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/tuple.hpp

⁵⁵⁰ <http://en.cppreference.com/w/cpp/header/tuple>

⁵⁵¹ <http://en.cppreference.com/w/cpp/utility/tuple/ignore>

⁵⁵² <http://en.cppreference.com/w/cpp/utility/tuple>

⁵⁵³ http://en.cppreference.com/w/cpp/utility/tuple_size

⁵⁵⁴ http://en.cppreference.com/w/cpp/utility/tuple_element

⁵⁵⁵ http://en.cppreference.com/w/cpp/utility/tuple/tuple_element

⁵⁵⁶ <http://en.cppreference.com/w/cpp/utility/tuple/tie>

⁵⁵⁷ http://en.cppreference.com/w/cpp/utility/tuple/forward_as_tuple

⁵⁵⁸ http://en.cppreference.com/w/cpp/utility/tuple/tuple_cat

⁵⁵⁹ <http://en.cppreference.com/w/cpp/utility/tuple/get>

hpx/type_traits.hpp

The header `hpx/type_traits.hpp`⁵⁶⁰ corresponds to the C++ standard library header `type_traits`⁵⁶¹.

Classes

Table 2.175: Classes of header `hpx/type_traits.hpp`

Class	C++ standard
<code>hpx::is_invocable</code>	<code>std::is_invocable</code> ⁵⁶²
<code>hpx::is_invocable_r</code>	<code>std::is_invocable</code> ⁵⁶³

hpx/unwrap.hpp

The header `hpx/unwrap.hpp`⁵⁶⁴ contains utilities for unwrapping futures.

Classes

Table 2.176: Classes of header `hpx/unwrap.hpp`

Class
<code>hpx::functional::unwrap</code>
<code>hpx::functional::unwrap_n</code>
<code>hpx::functional::unwrap_all</code>

Functions

Table 2.177: Functions of header `hpx/unwrap.hpp`

Function
<code>hpx::unwrap</code>
<code>hpx::unwrap_n</code>
<code>hpx::unwrap_all</code>
<code>hpx::unwrapping</code>
<code>hpx::unwrapping_n</code>
<code>hpx::unwrapping_all</code>

⁵⁶⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/type_traits.hpp

⁵⁶¹ http://en.cppreference.com/w/cpp/header/type_traits

⁵⁶² http://en.cppreference.com/w/cpp/types/is_invocable

⁵⁶³ http://en.cppreference.com/w/cpp/types/is_invocable

⁵⁶⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/unwrap.hpp

hpx/version.hpp

The header `hpx/version.hpp`⁵⁶⁵ provides version information about *HPX*.

Macros

Table 2.178: Macros of header `hpx/version.hpp`

Macro
<code>HPX_VERSION_MAJOR</code>
<code>HPX_VERSION_MINOR</code>
<code>HPX_VERSION_SUBMINOR</code>
<code>HPX_VERSION_FULL</code>
<code>HPX_VERSION_DATE</code>
<code>HPX_VERSION_TAG</code>
<code>HPX_AGAS_VERSION</code>

Functions

Table 2.179: Functions of header `hpx/version.hpp`

Function
<code>hpx::major_version</code>
<code>hpx::minor_version</code>
<code>hpx::subminor_version</code>
<code>hpx::full_version</code>
<code>hpx::full_version_as_string</code>
<code>hpx::tag</code>
<code>hpx::agas_version</code>
<code>hpx::build_type</code>
<code>hpx::build_date_time</code>

hpx/wrap_main.hpp

The header `hpx/wrap_main.hpp`⁵⁶⁶ does not provide any direct functionality but is used for implicitly using `main` as the runtime entry point. See *Re-use the `main()` function as the main HPX entry point* for more details on implicitly starting the *HPX* runtime.

⁵⁶⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/version/include/hpx/version.hpp>

⁵⁶⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/wrap/include/hpx/wrap_main.hpp

2.9.2 Public distributed API

Our Public Distributed API offers a rich set of tools and functions that enable developers to harness the full potential of distributed computing. Here, you'll find a comprehensive list of header files, classes and functions for various distributed computing features provided by *HPX*.

`hpx/barrier.hpp`

The header `hpx/barrier.hpp`⁵⁶⁷ includes a distributed barrier implementation. For information regarding the C++ standard library header `barrier`⁵⁶⁸, see *Public API*.

Classes

Table 2.180: Distributed implementation of classes of header `hpx/barrier.hpp`

Class
<code>hpx::distributed::barrier</code>

Functions

Table 2.181: *hpx* functions of header `hpx/barrier.hpp`

Function
<code>hpx::distributed::wait</code>
<code>hpx::distributed::synchronize</code>

`hpx/collectives.hpp`

The header `hpx/collectives.hpp`⁵⁶⁹ contains definitions and implementations related to the collectives operations.

Classes

Table 2.182: *hpx* classes of header `hpx/collectives.hpp`

Class
<code>hpx::collectives::num_sites_arg</code>
<code>hpx::collectives::this_site_arg</code>
<code>hpx::collectives::that_site_arg</code>
<code>hpx::collectives::generation_arg</code>
<code>hpx::collectives::root_site_arg</code>
<code>hpx::collectives::tag_arg</code>
<code>hpx::collectives::arity_arg</code>
<code>hpx::collectives::communicator</code>
<code>hpx::collectives::channel_communicator</code>

⁵⁶⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/barrier.hpp>

⁵⁶⁸ <http://en.cppreference.com/w/cpp/header/barrier>

⁵⁶⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/collectives.hpp>

Functions

Table 2.183: *hpx* functions of header `hpx/collectives.hpp`

Function
<code>hpx::collectives::all_gather</code>
<code>hpx::collectives::all_reduce</code>
<code>hpx::collectives::all_to_all</code>
<code>hpx::collectives::broadcast_to</code>
<code>hpx::collectives::broadcast_from</code>
<code>hpx::collectives::create_channel_communicator</code>
<code>hpx::collectives::set</code>
<code>hpx::collectives::get</code>
<code>hpx::collectives::create_communicator</code>
<code>hpx::collectives::create_hierarchical_communicator</code>
<code>hpx::collectives::create_local_communicator</code>
<code>hpx::collectives::communicator::set_info</code>
<code>hpx::collectives::communicator::get_info</code>
<code>hpx::collectives::communicator::is_root</code>
<code>hpx::collectives::exclusive_scan</code>
<code>hpx::collectives::gather_here</code>
<code>hpx::collectives::gather_there</code>
<code>hpx::collectives::inclusive_scan</code>
<code>hpx::collectives::reduce_here</code>
<code>hpx::collectives::reduce_there</code>
<code>hpx::collectives::scatter_from</code>
<code>hpx::collectives::scatter_to</code>

`hpx/latch.hpp`

The header `hpx/latch.hpp`⁵⁷⁰ includes a distributed latch implementation. For information regarding the C++ standard library header `latch`⁵⁷¹, see *Public API*.

⁵⁷⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/latch.hpp>

⁵⁷¹ <http://en.cppreference.com/w/cpp/header/latch>

Classes

Table 2.184: Distributed implementation of classes of header `hpx/latch.hpp`

Class
<code>hpx::distributed::latch</code>

Member functions

Table 2.185: *hpx* functions of class `hpx::distributed::latch` from header `hpx/latch.hpp`

Function
<code>hpx::distributed::latch::count_down_and_wait</code>
<code>hpx::distributed::latch::arrive_and_wait</code>
<code>hpx::distributed::latch::count_down</code>
<code>hpx::distributed::latch::is_ready</code>
<code>hpx::distributed::latch::try_wait</code>
<code>hpx::distributed::latch::wait</code>

`hpx/async.hpp`

The header `hpx/async.hpp`⁵⁷² includes distributed implementations of `hpx::async`, `hpx::post`, `hpx::sync`, and `hpx::dataflow`. For information regarding the C++ standard library header, see *Public API*.

Functions

Table 2.186: Distributed implementation of functions of header `hpx/async.hpp`

Functions
<code>modules_hpx/async_distributed/async.hpp_api</code>
<code>modules_hpx/async_distributed/sync.hpp_api</code>
<code>modules_hpx/async_distributed/post.hpp_api</code>
<code>modules_hpx/async_distributed/dataflow.hpp_api</code>

⁵⁷² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/async_distributed/include/hpx/async.hpp

hpx/components.hpp

The header `hpx/include/components.hpp`⁵⁷³ includes the components implementation. A component in *hpx* is a C++ class which can be created remotely and for which its member functions can be invoked remotely as well. More information about how components can be defined, created, and used can be found in *Writing components*. *Components and actions* includes examples on the accumulator, template accumulator and template function accumulator.

Macros

Table 2.187: *hpx* macros of header `hpx/components.hpp`

Macro
<code>HPX_DEFINE_COMPONENT_ACTION</code>
<code>HPX_REGISTER_ACTION_DECLARATION</code>
<code>HPX_REGISTER_ACTION</code>
<code>HPX_REGISTER_COMMANDLINE_MODULE</code>
<code>HPX_REGISTER_COMPONENT</code>
<code>HPX_REGISTER_COMPONENT_MODULE</code>
<code>HPX_REGISTER_STARTUP_MODULE</code>

Classes

Table 2.188: *hpx* classes of header `hpx/components.hpp`

Class
<code>hpx::components::client</code>
<code>hpx::components::client_base</code>
<code>hpx::components::component</code>
<code>hpx::components::component_base</code>
<code>hpx::components::component_commandline_base</code>

Functions

Table 2.189: *hpx* functions of header `hpx/components.hpp`

Function
<code>hpx::new_</code>

⁵⁷³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/include/components.hpp>

hpx/supervision_dispatch.hpp

The header `hpx/supervision_dispatch.hpp`⁵⁷⁴ provides peer discovery, cooperative lifecycle management, failure detection, and fenced action dispatch across localities. See *Supervision dispatch module* for the full API reference and *Supervision dispatch* for the narrative documentation.

Classes

Table 2.190: *hpx* classes of header `hpx/supervision_dispatch.hpp`

Class
<code>hpx::supervision::registry</code>

Functions

Table 2.191: *hpx* functions of header `hpx/supervision_dispatch.hpp`

Function
<code>hpx::supervision::discover_and_join</code>
<code>hpx::supervision::dispatch_work</code>

2.9.3 Supervision dispatch module

The supervision dispatch module provides peer discovery, cooperative lifecycle management, failure detection, and fenced action dispatch across localities, built on top of the *supervision* module’s lifecycle events and admission checks. See that module’s reference for the semantics of `hpx::supervision::check_admission` and `hpx::supervision::dispatch_outcome`; this page documents only the dispatch-specific surface layered on top of them. For the narrative on initialization ordering, one-shot discovery, shadow-state semantics, and client-side filtering versus fenced-dispatch admission, see *Supervision dispatch*.

Overview

Functions

Table 2.192: *hpx::supervision* dispatch functions

Function	Description
<code>hpx::supervision::init</code>	<i>One-shot, idempotent runtime initialization.</i>
<code>hpx::supervision::finalize</code>	<i>One-shot, idempotent runtime teardown.</i>
<code>hpx::supervision::is_initialized</code>	<i>Whether the runtime is currently active.</i>
<code>hpx::supervision::discover_peers</code>	<i>One-time discovery pull across localities.</i>
<code>hpx::supervision::fan_out_join</code>	<i>Fan out join() calls to discovered peers.</i>
<code>hpx::supervision::discover_and_join</code>	<i>Composed discovery-and-join pass.</i>
<code>hpx::supervision::dispatch_work</code>	<i>Dispatch an action under supervision fencing.</i>

⁵⁷⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/components/supervision_dispatch/include/hpx/supervision_dispatch.hpp

Types

Table 2.193: *hpx::supervision* dispatch types

Type	Description
<i>hpx::supervision::registry</i>	<i>Client handle mirroring a peer's lifecycle state.</i>
<i>hpx::supervision::server::peer_snapshot</i>	<i>Point-in-time view of a joined peer.</i>
<i>hpx::supervision::discovered_peer</i>	<i>A discovered peer with locality and join epoch.</i>

Lifecycle initialization and shutdown

```
hpx::shared_future<hpx::supervision::registry> hpx::supervision::init(hpx::chrono::steady_duration const
                                                                    &discovery_timeout =
                                                                    hpx::supervision::default_discovery_timeout)
```

```
hpx::supervision::registry hpx::supervision::init(hpx::launch::sync_policy, hpx::chrono::steady_duration
                                                    const &discovery_timeout =
                                                    hpx::supervision::default_discovery_timeout)
```

Performs one-shot, idempotent initialization of the supervision-dispatch runtime for this locality: creates a local registry, publishes `event::started` before its symbol name is registered, registers that name, and performs a single `discover_and_join()` pass. Calling `init()` while already active is a no-op; concurrent callers during initializing attach to the in-flight operation instead of racing it.

```
void hpx::supervision::finalize()
```

Performs one-shot, idempotent teardown of the runtime previously started by `init()`: publishes `event::completed` at the current/unchanged epoch, unregisters the registry's symbol name, and releases the registry. A no-op unless the runtime is currently active.

```
bool hpx::supervision::is_initialized() noexcept
```

Returns whether the runtime is currently active. Never blocks; safe to call from any thread, including while `init()/finalize()` is in flight.

Peer discovery

```
struct hpx::supervision::discovered_peer
```

A peer whose registry symbol name resolved during a `discover_peers()` call. Holds locality, registry_client, and join_epoch. `discover_peers()` leaves `join_epoch` at `hpx::supervision::unjoined_epoch` (never 0, which is a legitimate join epoch); `fan_out_join()` fills it in with the epoch recorded by `registry::join()`. `locality` is cached for convenience but is never independently resolved or validated: it is always derived from `registry_client` itself (see `registry::get_locality()`), since exactly one registry exists per locality.

```
std::vector<hpx::supervision::discovered_peer> hpx::supervision::discover_peers(hpx::chrono::steady_duration
                                                                                const &timeout =
                                                                                hpx::supervision::default_discovery_timeout)
```

Performs a one-time discovery pull: concurrently resolves the pinned registry name of every remote locality, bounded by a single wait for `timeout`. Localities that have not yet called `init()` are silently excluded rather than causing a hang or failure.

std::vector<hpx::supervision::discovered_peer> *hpx::supervision::fan_out_join(...)*

Fans out `join()` calls from `local_registry` to every entry in `peers`. Reuses `registry::join()`'s reservation/idempotency machinery, so repeated or overlapping calls never create more than one shadow per peer locality.

Returns a `discovered_peer` for each peer whose `join()` call settled successfully within `timeout`, in the same relative order as `peers`. Peers whose `join()` call did not settle in time are omitted from the result (rather than left as gaps or defaulted entries), so the returned vector is a same-order *subset* of `peers`, not index-aligned with it.

std::vector<hpx::supervision::discovered_peer> *hpx::supervision::discover_and_join(hpx::supervision::registry*
const
&local_registry,
hpx::chrono::steady_duration
const &timeout =
hpx::supervision::default_discovery_time)

Composes a single reactive discovery-and-join pass: one `discover_peers()` pull followed by one `fan_out_join()` call. Introduces no polling, timer, or repeated broadcast of its own.

Returns the same `discovered_peer` vector produced by `fan_out_join()` for the peers it discovered.

State query and event publication

hpx::future<hpx::supervision::lifecycle_state> *hpx::supervision::query_state(hpx::supervision::registry*
const &handle)

hpx::supervision::lifecycle_state *hpx::supervision::query_state(hpx::launch::sync_policy,*
hpx::supervision::registry const &handle,
hpx::error_code &ec = *hpx::throws*)

hpx::future<hpx::supervision::lifecycle_state> *hpx::supervision::query_state(hpx::supervision::registry*
const &handle,
hpx::supervision::discovered_peer
const &peer)

hpx::supervision::lifecycle_state *hpx::supervision::query_state(hpx::launch::sync_policy,*
hpx::supervision::registry const &handle,
hpx::supervision::discovered_peer const
&peer, *hpx::error_code* &ec = *hpx::throws*)

The self variants resolve both locality and target to `hpx::find_here()` and query it on the local locality; the peer variants resolve both locality and target from `peer.locality` instead - `handle` is accepted only for overload resolution and symmetry with the self variants, and is otherwise unused in that case. Each overload is a thin forwarder over the corresponding raw-id `query_state()` overload in *Supervision module*; see that module's reference for the fields of the returned `lifecycle_state`, including the epoch value useful for recovering the epoch a handle's locality was started at.

hpx::future<hpx::supervision::publish_result> *hpx::supervision::publish_event(hpx::supervision::registry*
const &handle,
hpx::supervision::event ev,
std::uint64_t epoch = 0)

hpx::supervision::publish_result *hpx::supervision::publish_event(hpx::launch::sync_policy,*
hpx::supervision::registry const &handle,
hpx::supervision::event ev, *std::uint64_t*
epoch = 0, *hpx::error_code* &ec =
hpx::throws)

Handle-based convenience overloads of `hpx::supervision::publish_event` that resolve both locality and target to `hpx::find_here()` instead of requiring the caller to name them explicitly. Thin forwarders over the raw-id `publish_event()` overloads in *Supervision module*. There is no peer variant: a locality publishes lifecycle events only for itself, never on behalf of a peer. The default epoch value of 0 is only correct for a locality's very first publication after `init()`; once the target's real epoch has advanced, 0 is stale. Callers publishing events after the initial one should first obtain the current epoch - e.g. via `query_state(hpx::launch::sync, handle).epoch` - and pass it explicitly."

Registry client

class `hpx::supervision::registry`

A lightweight, self-supervising client handle for pairing with peer localities; mirrors a peer's lifecycle state locally via `join()` and can itself be discovered by name in AGAS.

`hpx::future<hpx::supervision::joined_peer> join(hpx::id_type const &peer_locality) const`

`hpx::supervision::joined_peer join(hpx::launch::sync_policy, hpx::id_type const &peer_locality, hpx::error_code &ec = hpx::throws) const`

Joins a peer locality: creates (or reuses) local supervision state mirroring the peer's lifecycle. The returned `joined_peer::target` is `peer_locality` itself (not a generated local id) and is what `dispatch_work()` colocates against.

`hpx::future<std::vector<hpx::supervision::server::peer_snapshot>> snapshot_peers() const`

`std::vector<hpx::supervision::server::peer_snapshot> snapshot_peers(hpx::launch::sync_policy, hpx::error_code &ec = hpx::throws) const`

Returns a point-in-time snapshot of all fully joined, non-evicting peers.

`hpx::future<bool> register_name()`

`bool register_name(hpx::launch::sync_policy, hpx::error_code &ec = hpx::throws)`

`hpx::future<hpx::id_type> unregister_name() const`

`hpx::id_type unregister_name(hpx::launch::sync_policy, hpx::error_code &ec = hpx::throws) const`

struct `hpx::supervision::server::peer_snapshot`

Plain-data view of a single joined peer: `peer_locality` and `join_epoch`.

Fenced dispatch

template<typename **Action**, typename ...**Ts**>

decltype(auto) `hpx::supervision::dispatch_work(hpx::id_type const &target, std::uint64_t epoch, Ts&&... ts)`

Dispatches **Action** to **target** under supervision fencing. Performs a cheap, non-authoritative admission check on the caller's locality to short-circuit an already-known-fenced target, then dispatches to the target's own locality (via `hpx::colocated`) where an authoritative re-check against the same latch consulted by `hpx::supervision::check_admission` runs immediately before the wrapped action executes, on the same thread, closing the admission/invoke race. See *Supervision dispatch* for the full client-side-filtering versus fenced-admission narrative and worked examples.

Throws

`hpx::exception` with `hpx::error::target_fenced` if the target has latched a terminal event for epoch since the client-side check; the wrapped action is not invoked in that case.

Testing support

The following are declared in `hpx/supervision_dispatch/testing.hpp` and are **not** part of the stable public dispatch API; they exist solely to make unit tests for this module deterministic:

```
std::vector<hpx::supervision::server::peer_snapshot> hpx::supervision::testing::local_snapshot_peers()

void hpx::supervision::testing::set_failure_detection_poll_timeout_for_testing(hpx::chrono::steady_duration
                                                                              const
                                                                              &timeout)

hpx::id_type hpx::supervision::testing::last_join_locality()

void hpx::supervision::testing::suspend_heartbeat_for_testing()

bool hpx::supervision::testing::failure_detection_sweep_in_flight_for_testing()
```

See the *API reference* of this module for more details, and *Supervision module* for the underlying lifecycle event, admission, and dispatch-outcome semantics this module builds on.

2.9.4 Full API

The full API of *HPX* is presented below. The listings for the public API above refer to the full documentation below.

Note: Most names listed in the full API reference are implementation details or considered unstable. They are listed mostly for completeness. If there is a particular feature you think deserves being in the public API we may consider promoting it. In general we prioritize making sure features corresponding to C++ standard library features are stable and complete.

actions

See *Public API* for a list of names and headers that are part of the public *HPX* API.

`hpx/actions/action_support.hpp`

Defined in header `hpx/actions/action_support.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

`hpx/actions/transfer_base_action.hpp`

Defined in header `hpx/actions/transfer_base_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions/actions_fwd.hpp

Defined in header `hpx/actions/actions_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions/transfer_action.hpp

Defined in header `hpx/actions/transfer_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions/base_action.hpp

Defined in header `hpx/actions/base_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

actions_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions_base/basic_action_fwd.hpp

Defined in header `hpx/actions_base/basic_action_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **actions**

```
template<typename Component, typename Signature, typename Derived>
```

```
struct basic_action
```

```
    #include <basic_action_fwd.hpp>
```

Template Parameters

- **Component** – component type
- **Signature** – return type and arguments
- **Derived** – derived action class

hpx/actions_base/reflect_action.hpp

Defined in header `hpx/actions_base/reflect_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Reflection-based action definition for HPX remote operations.

HPX_REGISTER_ACTION_DECLARATION

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `HPX_REGISTER_ACTION`

Warning: doxygenfunction: Cannot find function “HPX_REGISTER_ACTION_DECLARATION” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

HPX_REGISTER_ACTION

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `HPX_REGISTER_ACTION_DECLARATION`

Warning: doxygenfunction: Cannot find function “HPX_REGISTER_ACTION” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

`hpx/actions_base/preassigned_action_id.hpp`

Defined in header `hpx/actions_base/preassigned_action_id.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **actions**

HPX_DEFINE_COMPONENT_ACTION

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Warning: doxygenfunction: Unable to resolve function “HPX_DEFINE_COMPONENT_ACTION” with arguments “None”. Candidate function could not be parsed. Parsing error is Error when parsing function declaration. If the function has no return type: Invalid C++ declaration: Expected end of definition or ;. [error at 87] `HPX_DEFINE_COMPONENT_ACTION (action_move_semantics, test_movable, test_movable_action) HPX_DEFINE_COMPONENT_ACTION(action_move_semantics` _____^ If the function has a return type:

Error in declarator If declarator-id with parameters-and-qualifiers: Invalid C++ declaration: Expected identifier in nested name. [error at 28] HPX_DEFINE_COMPONENT_ACTION (action_move_semantics, test_movable, test_movable_action) HPX_DEFINE_COMPONENT_ACTION(action_move_semantics _____^ If parenthesis in noptr-declarator: Error in declarator or parameters-and-qualifiers

If pointer to member declarator: Invalid C++ declaration: Expected ‘::’ in pointer to member (function). [error at 50] HPX_DEFINE_COMPONENT_ACTION (action_move_semantics, test_movable, test_movable_action) HPX_DEFINE_COMPONENT_ACTION(action_move_semantics _____^

If declarator-id: Invalid C++ declaration: Expecting “(” in parameters-and-qualifiers. [error at 50] HPX_DEFINE_COMPONENT_ACTION (action_move_semantics, test_movable, test_movable_action) HPX_DEFINE_COMPONENT_ACTION(action_move_semantics _____^

hpx/actions_base/actions_base_fwd.hpp

Defined in header `hpx/actions_base/actions_base_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace actions
```

hpx/actions_base/plain_action.hpp

Defined in header `hpx/actions_base/plain_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace actions
```

```
        namespace traits
```

hpx/actions_base/lambda_to_action.hpp

Defined in header `hpx/actions_base/lambda_to_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/actions_base/actions_base_support.hpp

Defined in header `hpx/actions_base/actions_base_support.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace actions
```

hpx/actions_base/macros.hpp

Defined in header `hpx/actions_base/macros.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_REGISTER_ACTION_INVOCATION_COUNT(Action)

HPX_REGISTER_PER_ACTION_DATA_COUNTER_TYPES(Action)

HPX_MAKE_ACTION(func)

HPX_MAKE_DIRECT_ACTION(func)

HPX_DECLARE_ACTION(...)

Declares an action type.

HPX_REGISTER_ACTION_DECLARATION(...)

Declare the necessary component action boilerplate code.

The macro *HPX_REGISTER_ACTION_DECLARATION* can be used to declare all the boilerplate code which is required for proper functioning of component actions in the context of HPX.

The parameter *action* is the type of the action to declare the boilerplate for.

This macro can be invoked with an optional second parameter. This parameter specifies a unique name of the action to be used for serialization purposes. The second parameter has to be specified if the first parameter is not usable as a plain (nonqualified) C++ identifier, i.e. the first parameter contains special characters which cannot be part of a C++ identifier, such as '<', '>', or ':'.

```
namespace app
{
    // Define a simple component exposing one action 'print_greeting'
    class HPX_COMPONENT_EXPORT server
    : public hpx::components::component_base<server>
    {
        void print_greeting ()
        {
            hpx::cout << "Hey, how are you?\n" << std::flush;
        }
    }
}
```

(continues on next page)

(continued from previous page)

```

    // Component actions need to be declared, this also defines the
    // type 'print_greeting_action' representing the action.
    HPX_DEFINE_COMPONENT_ACTION(server,
        print_greeting, print_greeting_action);
};
}

// Declare boilerplate code required for each of the component actions.
HPX_REGISTER_ACTION_DECLARATION(app::server::print_greeting_action)

```

Example:

Note: This macro has to be used once for each of the component actions defined using one of the *HPX_DEFINE_COMPONENT_ACTION* macros. It has to be visible in all translation units using the action, thus it is recommended to place it into the header file defining the component.

HPX_REGISTER_ACTION_DECLARATION(...)**HPX_REGISTER_ACTION_DECLARATION_1(action)****HPX_REGISTER_ACTION(...)**

Define the necessary component action boilerplate code.

The macro *HPX_REGISTER_ACTION* can be used to define all the boilerplate code which is required for proper functioning of component actions in the context of HPX.

The parameter *action* is the type of the action to define the boilerplate for.

This macro can be invoked with an optional second parameter. This parameter specifies a unique name of the action to be used for serialization purposes. The second parameter has to be specified if the first parameter is not usable as a plain (nonqualified) C++ identifier, i.e. the first parameter contains special characters which cannot be part of a C++ identifier, such as '<', '>', or ':'.

Note: This macro has to be used once for each of the component actions defined using one of the *HPX_DEFINE_COMPONENT_ACTION* or *HPX_DEFINE_PLAIN_ACTION* macros. It has to occur exactly once for each of the actions, thus it is recommended to place it into the source file defining the component.

Note: Only one of the forms of this macro *HPX_REGISTER_ACTION* or *HPX_REGISTER_ACTION_ID* should be used for a particular action, never both.

HPX_REGISTER_ACTION_ID(action, actionname, actionid)

Define the necessary component action boilerplate code and assign a predefined unique id to the action.

The macro *HPX_REGISTER_ACTION* can be used to define all the boilerplate code which is required for proper functioning of component actions in the context of HPX.

The parameter *action* is the type of the action to define the boilerplate for.

The parameter *actionname* specifies a unique name of the action to be used for serialization purposes. The second parameter has to be usable as a plain (nonqualified) C++ identifier, it should not contain special characters which cannot be part of a C++ identifier, such as '<', '>', or ':'.

The parameter *actionid* specifies a unique integer value which will be used to represent the action during serialization.

Note: This macro has to be used once for each of the component actions defined using one of the *HPX_DEFINE_COMPONENT_ACTION* or global actions *HPX_DEFINE_PLAIN_ACTION* macros. It has to occur exactly once for each of the actions, thus it is recommended to place it into the source file defining the component.

Note: Only one of the forms of this macro *HPX_REGISTER_ACTION* or *HPX_REGISTER_ACTION_ID* should be used for a particular action, never both.

HPX_DEFINE_COMPONENT_ACTION(...)

Registers a member function of a component as an action type with HPX.

The macro *HPX_DEFINE_COMPONENT_ACTION* can be used to register a member function of a component as an action type named *action_type*.

The parameter *component* is the type of the component exposing the member function *func* which should be associated with the newly defined action type. The parameter *action_type* is the name of the action type to register with HPX.

```
namespace app
{
    // Define a simple component exposing one action 'print_greeting'
    class HPX_COMPONENT_EXPORT server
    : public hpx::components::component_base<server>
    {
    public:
        void print_greeting() const
        {
            hpx::cout << "Hey, how are you?\n" << std::flush;
        }

        // Component actions need to be declared, this also defines the
        // type 'print_greeting_action' representing the action.
        HPX_DEFINE_COMPONENT_ACTION(server, print_greeting,
            print_greeting_action);
    };
}
```

Example:

The first argument must provide the type name of the component the action is defined for.

The second argument must provide the member function name the action should wrap.

The default value for the third argument (the typename of the defined action) is derived from the name of the function (as passed as the second argument) by appending ‘_action’. The third argument can be omitted only if the second argument with an appended suffix ‘_action’ resolves to a valid, unqualified C++ type name.

Note: The macro *HPX_DEFINE_COMPONENT_ACTION* can be used with 2 or 3 arguments. The third argument is optional.

HPX_DEFINE_PLAIN_ACTION(...)

Defines a plain action type.

```
namespace app
{
    void some_global_function(double d)
    {
        cout << d;
    }

    // This will define the action type 'app::some_global_action' which
    // represents the function 'app::some_global_function'.
    HPX_DEFINE_PLAIN_ACTION(some_global_function, some_global_action);
}
```

Example:

Note: Usually this macro will not be used in user code unless the intent is to avoid defining the action_type in global namespace. Normally, the use of the macro *HPX_PLAIN_ACTION* is recommended.

Note: The macro *HPX_DEFINE_PLAIN_ACTION* can be used with 1 or 2 arguments. The second argument is optional. The default value for the second argument (the typename of the defined action) is derived from the name of the function (as passed as the first argument) by appending ‘_action’. The second argument can be omitted only if the first argument with an appended suffix ‘_action’ resolves to a valid, unqualified C++ type name.

HPX_DECLARE_PLAIN_ACTION(...)

Declares a plain action type.

HPX_PLAIN_ACTION(...)

Defines a plain action type based on the given function *func* and registers it with HPX.

The macro *HPX_PLAIN_ACTION* can be used to define a plain action (e.g. an action encapsulating a global or free function) based on the given function *func*. It defines the action type *name* representing the given function. This macro additionally registers the newly define action type with HPX.

The parameter *func* is a global or free (non-member) function which should be encapsulated into a plain action. The parameter *name* is the name of the action type defined by this macro.

```

namespace app {
    void some_global_function(double d) {
        cout << d;
    }
}

// This will define the action type 'some_global_action' which
// represents the function 'app::some_global_function'.
HPX_PLAIN_ACTION(app::some_global_function, some_global_action)

```

Example:

Note: The macro *HPX_PLAIN_ACTION* has to be used at global namespace even if the wrapped function is located in some other namespace. The newly defined action type is placed into the global namespace as well.

Note: The macro *HPX_PLAIN_ACTION_ID* can be used with 1, 2, or 3 arguments. The second and third arguments are optional. The default value for the second argument (the typename of the defined action) is derived from the name of the function (as passed as the first argument) by appending ‘_action’. The second argument can be omitted only if the first argument with an appended suffix ‘_action’ resolves to a valid, unqualified C++ type name. The default value for the third argument is *hpx::components::factory_state::check*.

Note: Only one of the forms of this macro *HPX_PLAIN_ACTION* or *HPX_PLAIN_ACTION_ID* should be used for a particular action, never both.

HPX_PLAIN_ACTION_ID(func, name, id)

Defines a plain action type based on the given function *func* and registers it with HPX.

The macro *HPX_PLAIN_ACTION_ID* can be used to define a plain action (e.g. an action encapsulating a global or free function) based on the given function *func*. It defines the action type *actionname* representing the given function.

The parameter *actionid* specifies a unique integer value which will be used to represent the action during serialization.

The parameter *func* is a global or free (non-member) function which should be encapsulated into a plain action. The parameter *name* is the name of the action type defined by this macro.

The second parameter has to be usable as a plain (nonqualified) C++ identifier, it should not contain special characters which cannot be part of a C++ identifier, such as ‘<’, ‘>’, or ‘.’.

```

namespace app {
    void some_global_function(double d) {
        cout << d;
    }
}

// This will define the action type 'some_global_action' which
// represents the function 'app::some_global_function'.

```

(continues on next page)

(continued from previous page)

```
HPX_PLAIN_ACTION_ID(app::some_global_function, some_global_action,
    some_unique_id);
```

Example:

Note: The macro *HPX_PLAIN_ACTION_ID* has to be used at global namespace even if the wrapped function is located in some other namespace. The newly defined action type is placed into the global namespace as well.

Note: Only one of the forms of this macro *HPX_PLAIN_ACTION* or *HPX_PLAIN_ACTION_ID* should be used for a particular action, never both.

HPX_REGISTER_ACTION_FACTORY_ID(Name, Id)

hpx/actions_base/traits/action_remote_result.hpp

Defined in header `hpx/actions_base/traits/action_remote_result.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **traits**

Typedefs

```
template<typename Result>
using action_remote_result_t = typename action_remote_result<Result>::type

template<typename Result>
struct action_remote_result : public detail::action_remote_result_customization_point<Result>
```

agas

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/agas/addressing_service.hpp

Defined in header `hpx/agas/addressing_service.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace agas
```

```
        struct addressing_service
```

Public Types

```
        using component_id_type = components::component_type
```

```
        using iterate_names_return_type = std::map<std::string, hpx::id_type>
```

```
        using iterate_types_function_type = hpx::function<void(std::string const&,
        components::component_type), true>
```

```
        using mutex_type = hpx::spinlock
```

```
        using gva_cache_type = hpx::util::cache::lru_cache<gva_cache_key, gva,
        hpx::util::cache::statistics::local_full_statistics>
```

```
        using migrated_objects_table_type = std::set<naming::gid_type>
```

```
        using refcnt_requests_type = std::map<naming::gid_type, std::int64_t>
```

```
        using resolved_localities_type = std::map<naming::gid_type, parcelset::endpoints_type>
```

Public Functions

```
        HPX_NON_COPYABLE(addressing_service)
```

```
        explicit addressing_service(util::runtime_configuration const &ini_)
```

```
        ~addressing_service() = default
```

```
        void bootstrap(parcelset::endpoints_type const &endpoints, util::runtime_configuration &rtcfg)
```

```
        void initialize(std::uint64_t rts_lva)
```

```
        void adjust_local_cache_size(std::size_t) const
```

Adjust the size of the local AGAS Address resolution cache.


```

inline state get_status() const

inline void set_status(state new_state)

inline naming::gid_type const &get_local_locality(error_code& = throws) const

void set_local_locality(naming::gid_type const &g)

void register_console(parcelset::endpoints_type const &eps)

inline bool is_bootstrap() const

inline bool is_console() const
    Returns whether this addressing_service represents the console locality.

inline bool is_connecting() const
    Returns whether this addressing_service is connecting to a running application.

bool resolve_locally_known_addresses(naming::gid_type const &id, naming::address &addr)
    const

void register_server_instances()

void unregister_server_instances(hpx::error_code &ec = hpx::throws)

void garbage_collect_non_blocking(error_code &ec = throws)

void garbage_collect(error_code &ec = throws)

inline server::primary_namespace &get_local_primary_namespace_service()

inline naming::address::address_type get_primary_ns_lva() const

inline naming::address::address_type get_symbol_ns_lva() const

inline server::component_namespace *get_local_component_namespace_service() const

inline server::locality_namespace *get_local_locality_namespace_service() const

inline server::symbol_namespace &get_local_symbol_namespace_service() const

inline naming::address::address_type get_runtime_support_lva() const

std::uint64_t get_cache_entries(bool) const

std::uint64_t get_cache_hits(bool) const

std::uint64_t get_cache_misses(bool) const

std::uint64_t get_cache_evictions(bool) const

std::uint64_t get_cache_insertions(bool) const

std::uint64_t get_cache_get_entry_count(bool reset) const

std::uint64_t get_cache_insertion_entry_count(bool reset) const

std::uint64_t get_cache_update_entry_count(bool reset) const

std::uint64_t get_cache_erase_entry_count(bool reset) const

```

`std::uint64_t get_cache_get_entry_time(bool reset) const`

`std::uint64_t get_cache_insertion_entry_time(bool reset) const`

`std::uint64_t get_cache_update_entry_time(bool reset) const`

`std::uint64_t get_cache_erase_entry_time(bool reset) const`

`bool register_locality(parcelset::endpoints_type const &endpoints, naming::gid_type &prefix,
std::uint32_t num_threads, error_code &ec = throws)`

Add a locality to the runtime.

`parcelset::endpoints_type const &resolve_locality(naming::gid_type const &gid, error_code
&ec = throws)`

Resolve a locality to its prefix.

Returns

Returns an empty vector if the locality is not registered.

`bool has_resolved_locality(naming::gid_type const &gid)`

`bool unregister_locality(naming::gid_type const &gid, error_code &ec = throws)`

Remove a locality from the runtime.

`void remove_resolved_locality(naming::gid_type const &gid)`

remove given locality from locality cache

`bool get_console_locality(naming::gid_type &locality, error_code &ec = throws)`

Get locality locality_id of the console locality.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **locality** – [out] The locality_id value uniquely identifying the console locality. This is valid only, if the return value of this function is true.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if a console locality_id exists and returns *false* otherwise.

`bool get_localities(std::vector<naming::gid_type> &locality_ids,
components::component_type type, error_code &ec = throws) const`

Query for the locality_ids of all known localities.

This function returns the locality_ids of all localities known to the AGAS server or all localities having a registered factory for a given component type.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **locality_ids** – [out] The vector will contain the prefixes of all localities registered with the AGAS server. The returned vector holds the prefixes representing the run-time_support components of these localities.

- **type** – [in] The component type will be used to determine the set of prefixes having a registered factory for this component. The default value for this parameter is *components::component_enum_type::invalid*, which will return prefixes of all localities.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
inline bool get_localities(std::vector<naming::gid_type> &locality_ids, error_code &ec =
    throws) const
```

```
hpx::future<std::uint32_t> get_num_localities_async(components::component_type type =
    to_int(hpx::components::component_enum_type::invalid))
    const
```

Query for the number of all known localities.

This function returns the number of localities known to the AGAS server or the number of localities having a registered factory for a given component type.

Parameters

type – [in] The component type will be used to determine the set of prefixes having a registered factory for this component. The default value for this parameter is *components::component_type::invalid*, which will return prefixes of all localities.

Returns

A future that becomes ready with the number of matching localities.

```
std::uint32_t get_num_localities(components::component_type type, error_code &ec = throws)
    const
```

Query for the number of all known localities.

This function returns the number of localities known to the AGAS server or the number of localities having a registered factory for a given component type.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **type** – [in] The component type will be used to determine the set of prefixes having a registered factory for this component. The default value for this parameter is *components::component_type::invalid*, which will return prefixes of all localities.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
inline std::uint32_t get_num_localities(error_code &ec = throws) const
```

Query for the number of all known localities.

This function returns the number of localities known to the AGAS server or the number of localities having a registered factory for a given component type.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
hpx::future<std::uint32_t> get_num_overall_threads_async() const
```

```
std::uint32_t get_num_overall_threads(error_code &ec = throws) const  
  
hpx::future<std::vector<std::uint32_t>> get_num_threads_async() const  
  
std::vector<std::uint32_t> get_num_threads(error_code &ec = throws) const  
  
components::component_type get_component_id(std::string const &name, error_code &ec =  
                                              throws) const
```

Return a unique id usable as a component type.

This function returns the component type id associated with the given component name. If this is the first request for this component name a new unique id will be created.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **name** – [in] The component name (string) to get the component type for.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns the currently associated component type. Any error results in an exception thrown from this function.

```
void iterate_types(iterate_types_function_type const &f, error_code &ec = throws) const  
  
std::string get_component_type_name(components::component_type id, error_code &ec =  
                                     throws) const  
  
inline components::component_type register_factory(naming::gid_type const &locality_id,  
                                                    std::string const &name, error_code &ec  
                                                    = throws) const
```

Register a factory for a specific component type.

This function allows to register a component factory for a given locality and component type.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **locality_id** – [in] The locality value uniquely identifying the given locality the factory needs to be registered for.
- **name** – [in] The component name (string) to register a factory for the given component type for.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns the currently associated component type. Any error results in an exception thrown from this function. The returned component type is the same as if the function *get_component_id* was called using the same component name.

```
components::component_type register_factory(std::uint32_t locality_id, std::string const  
                                             &name, error_code &ec = throws) const
```

```
bool get_id_range(std::uint64_t count, naming::gid_type &lower_bound, naming::gid_type
                  &upper_bound, error_code &ec = throws)
```

Get unique range of freely assignable global ids.

Every locality needs to be able to assign global ids to different components without having to consult the AGAS server for every id to generate. This function can be called to preallocate a range of ids usable for this purpose.

Note: This function assigns a range of global ids usable by the given locality for newly created components. Any of the returned global ids still has to be bound to a local address, either by calling *bind* or *bind_range*.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **count** – [in] The number of global ids to be generated.
- **lower_bound** – [out] The lower bound of the assigned id range. The returned value can be used as the first id to assign. This is valid only, if the return value of this function is true.
- **upper_bound** – [out] The upper bound of the assigned id range. The returned value can be used as the last id to assign. This is valid only, if the return value of this function is true.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if a new range has been generated (it has been called for the first time for the given locality) and returns *false* if this locality already got a range assigned in an earlier call. Any error results in an exception thrown from this function.

```
inline bool bind_local(naming::gid_type const &id, naming::address const &addr, error_code
                       &ec = throws)
```

Bind a global address to a local address.

Every element in the HPX namespace has a unique global address (global id). This global address has to be associated with a concrete local address to be able to address an instance of a component using its global address.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: Binding a gid to a local address sets its global reference count to one.

Parameters

- **id** – [in] The global address which has to be bound to the local address.
- **addr** – [in] The local address to be bound to the global address.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true*, if this global id got associated with an local address. It returns

false otherwise.

```
inline hpx::future<bool> bind_async(naming::gid_type const &id, naming::address const &addr,  
                                   std::uint32_t locality_id)
```

```
inline hpx::future<bool> bind_async(naming::gid_type const &id, naming::address const &addr,  
                                   naming::gid_type const &locality)
```

```
bool bind_range_local(naming::gid_type const &lower_id, std::uint64_t count, naming::address  
                     const &baseaddr, std::uint64_t offset, error_code &ec = throws)
```

Bind unique range of global ids to given base address.

Every locality needs to be able to bind global ids to different components without having to consult the AGAS server for every id to bind. This function can be called to bind a range of consecutive global ids to a range of consecutive local addresses (separated by a given *offset*).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: Binding a gid to a local address sets its global reference count to one.

Parameters

- **lower_id** – [in] The lower bound of the assigned id range. The value can be used as the first id to assign.
- **count** – [in] The number of consecutive global ids to bind starting at *lower_id*.
- **baseaddr** – [in] The local address to bind to the global id given by *lower_id*. This is the base address for all additional local addresses to bind to the remaining global ids.
- **offset** – [in] The offset to use to calculate the local addresses to be bound to the range of global ids.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true*, if the given range was successfully bound. It returns *false* otherwise.

```
hpx::future<bool> bind_range_async(naming::gid_type const &lower_id, std::uint64_t count,  
                                   naming::address const &baseaddr, std::uint64_t offset,  
                                   naming::gid_type const &locality)
```

```
inline hpx::future<bool> bind_range_async(naming::gid_type const &lower_id, std::uint64_t  
                                         count, naming::address const &baseaddr,  
                                         std::uint64_t offset, std::uint32_t locality_id)
```

```
inline bool unbind_local(naming::gid_type const &id, error_code &ec = throws)
```

Unbind a global address.

Remove the association of the given global address with any local address, which was bound to this global address. Additionally it returns the local address which was bound at the time of this call.

Note: You can unbind only global ids bound using the function *bind*. Do not use this function to unbind any of the global ids bound using *bind_range*.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will raise an error if the global reference count of the given gid is not zero!

Parameters

- **id** – [in] The global address (id) for which the association has to be removed.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns *true* if the association has been removed, and it returns *false* if no association existed. Any error results in an exception thrown from this function.

```
inline bool unbind_local(naming::gid_type const &id, naming::address &addr, error_code &ec =
    throws)
```

Unbind a global address.

Remove the association of the given global address with any local address, which was bound to this global address. Additionally it returns the local address which was bound at the time of this call.

Note: You can unbind only global ids bound using the function *bind*. Do not use this function to unbind any of the global ids bound using *bind_range*.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will raise an error if the global reference count of the given gid is not zero!

Parameters

- **id** – [in] The global address (id) for which the association has to be removed.
- **addr** – [out] The local address which was associated with the given global address (id). This is valid only if the return value of this function is true.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns *true* if the association has been removed, and it returns *false* if no association existed. Any error results in an exception thrown from this function.

```
inline bool unbind_range_local(naming::gid_type const &lower_id, std::uint64_t count,
    error_code &ec = throws)
```

Unbind the given range of global ids.

Note: You can unbind only global ids bound using the function *bind_range*. Do not use this function to unbind any of the global ids bound using *bind*.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will raise an error if the global reference count of the given gid is not zero!

Parameters

- **lower_id** – [in] The lower bound of the assigned id range. The value must be the first id of the range as specified to the corresponding call to *bind_range*.
- **count** – [in] The number of consecutive global ids to unbind starting at *lower_id*. This number must be identical to the number of global ids bound by the corresponding call to *bind_range*.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if a new range has been generated (it has been called for the first time for the given locality) and returns *false* if this locality already got a range assigned in an earlier call. Any error results in an exception thrown from this function.

```
bool unbind_range_local(naming::gid_type const &lower_id, std::uint64_t count,  
                        naming::address &addr, error_code &ec = throws)
```

Unbind the given range of global ids.

Note: You can unbind only global ids bound using the function *bind_range*. Do not use this function to unbind any of the global ids bound using *bind*.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will raise an error if the global reference count of the given gid is not zero!

Parameters

- **lower_id** – [in] The lower bound of the assigned id range. The value must be the first id of the range as specified to the corresponding call to *bind_range*.
- **count** – [in] The number of consecutive global ids to unbind starting at *lower_id*. This number must be identical to the number of global ids bound by the corresponding call to *bind_range*.
- **addr** – [out] The local address which was associated with the given global address (id). This is valid only if the return value of this function is true.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if a new range has been generated (it has been called for the first time for the given locality) and returns *false* if this locality already got a range assigned in an earlier call.

```
hpx::future<naming::address> unbind_range_async(naming::gid_type const &lower_id,  
                                              std::uint64_t count = 1)
```



```
inline bool is_local_address_cached(naming::gid_type const &id, error_code &ec = throws)
```

Test whether the given address refers to a local object.

This function will test whether the given address refers to an object living on the locality of the caller.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The address to test.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if the passed address refers to an object which lives on the locality of the caller.

```
bool is_local_address_cached(naming::gid_type const &id, naming::address &addr,  
                             error_code &ec = throws)
```

```
bool is_local_address_cached(naming::gid_type const &id, naming::address &addr,  
                             std::pair<bool, components::pinned_ptr> &r,  
                             hpx::move_only_function<std::pair<bool,  
                             components::pinned_ptr>(naming::address const&)> &&f,  
                             error_code &ec = throws)
```

```
bool is_local_lva_encoded_address(std::uint64_t msb) const
```

```
inline bool resolve_local(naming::gid_type const &id, naming::address &addr, error_code &ec  
                           = throws)
```

Resolve a given global address (*id*) to its associated local address.

This function returns the local address which is currently associated with the given global address (*id*).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The global address (*id*) for which the associated local address should be returned.
- **addr** – [out] The local address which currently is associated with the given global address (*id*), this is valid only if the return value of this function is true.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if the global address has been resolved successfully (there exists an association to a local address) and the associated local address has been returned. The function returns *false* if no association exists for the given global address. Any error results in an exception thrown from this function.

```
inline bool resolve_local(hpx::id_type const &id, naming::address &addr, error_code &ec =  
                           throws)
```

```
inline naming::address resolve_local(naming::gid_type const &id, error_code &ec = throws)

inline naming::address resolve_local(hpx::id_type const &id, error_code &ec = throws)

hpx::future_or_value<naming::address> resolve_async(naming::gid_type const &id)

inline hpx::future_or_value<naming::address> resolve_async(hpx::id_type const &id)

hpx::future_or_value<id_type> get_colocation_id_async(hpx::id_type const &id)

bool resolve_full_local(naming::gid_type const &id, naming::address &addr, error_code &ec
                        = throws)

inline bool resolve_full_local(hpx::id_type const &id, naming::address &addr, error_code &ec
                               = throws)

inline naming::address resolve_full_local(naming::gid_type const &id, error_code &ec =
                                           throws)

inline naming::address resolve_full_local(hpx::id_type const &id, error_code &ec = throws)

hpx::future_or_value<naming::address> resolve_full_async(naming::gid_type const &id)

inline hpx::future_or_value<naming::address> resolve_full_async(hpx::id_type const &id)

bool resolve_cached(naming::gid_type const &id, naming::address &addr, error_code &ec =
                    throws)

inline bool resolve_cached(hpx::id_type const &id, naming::address &addr, error_code &ec =
                           throws)

inline bool resolve_local(naming::gid_type const *gids, naming::address *addrs, std::size_t size,
                           hpx::detail::dynamic_bitset<> &locals, error_code &ec = throws)

bool resolve_full_local(naming::gid_type const *gids, naming::address *addrs, std::size_t size,
                        hpx::detail::dynamic_bitset<> &locals, error_code &ec = throws)

bool resolve_cached(naming::gid_type const *gids, naming::address *addrs, std::size_t size,
                    hpx::detail::dynamic_bitset<> &locals, error_code &ec = throws)

hpx::future_or_value<std::int64_t> incref_async(naming::gid_type const &gid, std::int64_t
                                              credits = 1, hpx::id_type const &keep_alive =
                                              hpx::invalid_id)
```

Increment the global reference count for the given id.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **gid** – [in] The global address (id) for which the global reference count has to be incremented.
- **credits** – [in] The number of reference counts to add for the given id.
- **keep_alive** – [in] Id to keep alive (if valid)

Returns

Whether the operation was successful.

```
inline std::int64_t incref(naming::gid_type const &gid, std::int64_t credits = 1, error_code &ec =
    throws)
```

```
void decref(naming::gid_type const &id, std::int64_t credits = 1, error_code &ec = throws)
```

Decrement the global reference count for the given id.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The global address (id) for which the global reference count has to be decremented.
- **credits** – [in] The number of reference counts to add for the given id.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global reference count after the decrement.

```
hpx::future<iterate_names_return_type> iterate_ids(std::string const &pattern) const
```

Invoke the supplied *hpx::function* for every registered global name.

This function iterates over all registered global ids and returns every found entry matching the given name pattern. Any error results in an exception thrown (or reported) from this function.

Parameters

pattern – [in] pattern (possibly using wildcards) to match all existing entries against

```
bool register_name(std::string const &name, naming::gid_type const &id, error_code &ec =
    throws) const
```

Register a global name with a global address (id)

This function registers an association between a global name (string) and a global address (id) usable with one of the functions above (bind, unbind, and resolve).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **name** – [in] The global name (string) to be associated with the global address.
- **id** – [in] The global address (id) to be associated with the global address.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The function returns *true* if the global name was registered. It returns false if the global name is not registered.

```
hpx::future<bool> register_name_async(std::string const &name, hpx::id_type const &id) const
```

```
bool register_name(std::string const &name, hpx::id_type const &id, error_code &ec = throws)
    const
```

```
hpx::future<hpx::id_type> unregister_name_async(std::string const &name) const
```

Unregister a global name (release any existing association).

This function releases any existing association of the given global name with a global address (id).

Parameters

name – [in] The global name (string) for which any association with a global address (id) has to be released.

Returns

A future that becomes ready with the global id that was associated with the given name.

`hpx::id_type unregister_name(std::string const &name, error_code &ec = throws) const`

Unregister a global name (release any existing association)

This function releases any existing association of the given global name with a global address (id).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **name** – [in] The global name (string) for which any association with a global address (id) has to be released.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global id that was associated with the given name. Any error results in an exception thrown from this function.

`hpx::future<hpx::id_type> resolve_name_async(std::string const &name) const`

Query for the global address associated with a given global name.

This function returns the global address associated with the given global name.

Parameters

name – [in] The global name (string) for which the currently associated global address has to be retrieved.

Returns

A future holding the global id currently associated with the given global name.

`hpx::id_type resolve_name(std::string const &name, error_code &ec = throws) const`

Query for the global address associated with a given global name.

This function returns the global address associated with the given global name.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **name** – [in] The global name (string) for which the currently associated global address has to be retrieved.
- **ec** – [in,out] This represents the error status on exit. If this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global id currently associated with the given global name.

`future<hpx::id_type> on_symbol_namespace_event(std::string const &name, bool
call_for_past_events = false) const`

Install a listener for a given symbol namespace event.

This function installs a listener for a given symbol namespace event. It returns a future which becomes ready as a result of the listener being triggered.

Note: The only event type which is currently supported is *symbol_ns_bind*, i.e. the listener is triggered whenever a global id is registered with the given name.

Parameters

- **name** – [in] The global name (string) for which the given event should be triggered.
- **call_for_past_events** – [in, optional] Trigger the listener even if the given event has already happened in the past. The default for this parameter is *false*.

Returns

A future instance encapsulating the global id which is causing the registered listener to be triggered.

```
void update_cache_entry(naming::gid_type const &gid, gva const &gva, error_code &ec =
                        throws)
```

Warning: This function is for internal use only. It is dangerous and may break your code if you use it.

```
inline void update_cache_entry(naming::gid_type const &gid, naming::address const &addr,
                                std::uint64_t count = 0, std::uint64_t offset = 0, error_code &ec
                                = throws)
```

Warning: This function is for internal use only. It is dangerous and may break your code if you use it.

```
bool get_cache_entry(naming::gid_type const &gid, gva &gva, naming::gid_type &idbase,
                     error_code &ec = throws) const
```

Warning: This function is for internal use only. It is dangerous and may break your code if you use it.

```
void remove_cache_entry(naming::gid_type const &id, error_code &ec = throws) const
```

Warning: This function is for internal use only. It is dangerous and may break your code if you use it.

```
void clear_cache(error_code &ec = throws) const
```

Warning: This function is for internal use only. It is dangerous and may break your code if you use it.

```
void start_shutdown(error_code &ec = throws)
```

```
hpx::future<std::pair<hpx::id_type, naming::address>> begin_migration(hpx::id_type const &id)
start/stop migration of an object
```

Returns

Current locality and address of the object to migrate

bool **end_migration**(*hpx::id_type* const &id)

std::pair<bool, *components::pinned_ptr*> **was_object_migrated**(*naming::gid_type* const &gid,
hpx::move_only_function<*components::pinned_ptr*
&&f>)

Maintain list of migrated objects.

hpx::future<void> **mark_as_migrated**(*naming::gid_type* const &gid,
hpx::move_only_function<*std::pair*<bool,
hpx::future<void>>()> &&f, bool
expect_to_be_marked_as_migrating)

Mark the given object as being migrated (if the object is unpinned). Delay migration until the object is unpinned otherwise.

void **unmark_as_migrated**(*naming::gid_type* const &gid, *hpx::move_only_function*<void()>
&&f)

Remove the given object from the table of migrated objects.

void **pre_cache_endpoints**(*std::vector*<*parcelset::endpoints_type*> const&)

Public Members

mutable *hpx::shared_mutex* **gva_cache_mtx_**

std::shared_ptr<*gva_cache_type*> **gva_cache_**

mutable *mutex_type* **migrated_objects_mtx_** =
mutex_type("addressing_service::migrated_objects_mtx")

migrated_objects_table_type **migrated_objects_table_**

mutable *mutex_type* **console_cache_mtx_** =
mutex_type("addressing_service::console_cache_mtx")

std::uint32_t **console_cache_**

const *std::size_t* **max_refcnt_requests_**

mutex_type **refcnt_requests_mtx_** = *mutex_type*("addressing_service::refcnt_requests_mtx")

std::size_t **refcnt_requests_count_**

bool **enable_refcnt_caching_**

std::shared_ptr<*refcnt_requests_type*> **refcnt_requests_**

```

const service_mode service_type

const runtime_mode runtime_type

const bool caching_

const bool range_caching_

const threads::thread_priority action_priority_

std::uint64_t rts_lva_

std::unique_ptr<component_namespace> component_ns_

std::unique_ptr<locality_namespace> locality_ns_

symbol_namespace symbol_ns_

primary_namespace primary_ns_

std::atomic<hpx::state> state_

naming::gid_type locality_

mutable hpx::shared_mutex resolved_localities_mtx_

resolved_localities_type resolved_localities_

```

Public Static Functions

```

static std::int64_t synchronize_with_async_incref(std::int64_t old_credit, hpx::id_type const
&id, std::int64_t compensated_credit)

```

Protected Functions

```

void launch_bootstrap(parcelset::endpoints_type const &endpoints, util::runtime_configuration
&rtcfg)

naming::address resolve_full_postproc(naming::gid_type const &id,
primary_namespace::resolved_type const&)

bool bind_postproc(naming::gid_type const &id, gva const &g, future<bool> f)

bool was_object_migrated_locked(naming::gid_type const &id)
    Maintain list of migrated objects.

```

Private Functions

void **send_refcnt_requests**(std::unique_lock<mutex_type> &l, error_code &ec = throws)

Assumes that *refcnt_requests_mtx_* is locked.

void **send_refcnt_requests_non_blocking**(std::unique_lock<mutex_type> &l, error_code &ec)

Assumes that *refcnt_requests_mtx_* is locked.

std::vector<hpx::future<std::vector<std::int64_t>>> **send_refcnt_requests_async**(std::unique_lock<mutex_type> &l)

Assumes that *refcnt_requests_mtx_* is locked.

void **send_refcnt_requests_sync**(std::unique_lock<mutex_type> &l, error_code &ec)

Assumes that *refcnt_requests_mtx_* is locked.

agas_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/agas_base/server/primary_namespace.hpp

Defined in header `hpx/agas_base/server/primary_namespace.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Variables

HPX_ACTION_USES_MEDIUM_STACK(hpx::agas::server::primary_namespace::allocate_action) **HPX_REGISTER_ACTION**
hpx::naming::address > std_pair_address_id_type

namespace **hpx**

namespace **agas**

Functions

naming::gid_type **bootstrap_primary_namespace_gid**()

hpx::id_type **bootstrap_primary_namespace_id**()

namespace **server**

AGAS's primary namespace maps 128-bit global identifiers (GIDs) to resolved addresses.

The following is the canonical description of the partitioning of AGAS's primary namespace.

-----MSB----- -----LSB-----	
BBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBB	
prefix RC ----identifier----	
MSB	- Most significant bits (bit 64 to bit 127)
LSB	- Least significant bits (bit 0 to bit 63)
prefix	- Highest 32 bits (bit 96 to bit 127) of the MSB. Each locality is assigned a prefix. This creates a 96-bit address space for each locality.
RC	- Bit 88 to bit 92 of the MSB. This is the log2 of the number of reference counting credits on the GID. Bit 93 is used by the locking scheme for gid_types. Bit 94 is a flag which is set if the credit value is valid. Bit 95 is a flag that is set if a GID's credit count is ever split (e.g. if the GID is ever passed to another locality).
identifier	- Bit 64 to bit 86 of the MSB, and the entire LSB. The content of these bits depends on the component type of the underlying object. For all user-defined components, these bits contain a unique 88-bit number which is assigned sequentially for each locality. For <code>\a hpx#components#component_enum_type#runtime_support</code> the high 24 bits are zeroed and the low 64 bits hold the LVA of the component.

The following address ranges are reserved. Some are either explicitly or implicitly protected by AGAS. The letter x represents a single-byte wild card.

```

00000000xxxxxxxxxxxxxxxxxxxxxxxxxxxx
    Historically unused address space reserved for future use.
xxxxxxxxxxxx0000xxxxxxxxxxxxxxxxxxxx
    Address space for LVA-encoded GIDs.
00000001xxxxxxxxxxxxxxxxxxxxxxxxxxxx
    Prefix of the bootstrap AGAS locality.
000000010000000010000000000000001
    Address of the primary_namespace component on the bootstrap AGAS
    locality.
000000010000000010000000000000002
    Address of the component_namespace component on the bootstrap AGAS
    locality.
000000010000000010000000000000003
    Address of the symbol_namespace component on the bootstrap AGAS
    locality.
000000010000000010000000000000004
    Address of the locality_namespace component on the bootstrap AGAS
    locality.

```

Note: The layout of the address space is implementation defined, and subject to change. Never write application code that relies on the internal layout of GIDs. AGAS only guarantees that all assigned

GIDs will be unique.

Variables

```
constexpr char const *const primary_namespace_service_name = "primary/"
```

```
struct primary_namespace : public components::fixed_component_base<primary_namespace>
```

Public Types

```
using mutex_type = hpx::spinlock
```

```
using base_type = components::fixed_component_base<primary_namespace>
```

```
using component_type = std::int32_t
```

```
using gva_table_data_type = std::pair<gva, naming::gid_type>
```

```
using gva_table_type = std::map<naming::gid_type, gva_table_data_type>
```

```
using refcnt_table_type = std::map<naming::gid_type, std::int64_t>
```

```
using resolved_type = hpx::tuple<naming::gid_type, gva, naming::gid_type>
```

Public Functions

```
inline mutex_type &mutex()
```

```
void wait_for_migration_locked(std::unique_lock<mutex_type> &l, naming::gid_type  
                             const &id, error_code &ec)
```

```
inline primary_namespace()
```

```
void finalize() const
```

```
inline void set_local_locality(naming::gid_type const &g)
```

```
void register_server_instance(char const *servicename, std::uint32_t locality_id =  
                             naming::invalid_locality_id, error_code &ec = throws)
```

```
void unregister_server_instance(error_code &ec = throws) const
```

```
bool bind_gid(gva const &g, naming::gid_type id, naming::gid_type const &locality)
```

```
std::pair<hpx::id_type, naming::address> begin_migration(naming::gid_type id)
```

```

bool end_migration(naming::gid_type const &id)

resolved_type resolve_gid(naming::gid_type const &id)

hpx::id_type colocate(naming::gid_type const &id)

naming::address unbind_gid(std::uint64_t count, naming::gid_type id)

std::int64_t increment_credit(std::int64_t credits, naming::gid_type lower,
                               naming::gid_type upper)

std::vector<std::int64_t> decrement_credit(std::vector<hpx::tuple<std::int64_t,
                                           naming::gid_type, naming::gid_type>> const
                                           &requests)

std::pair<naming::gid_type, naming::gid_type> allocate(std::uint64_t count)

resolved_type resolve_gid_locked(std::unique_lock<mutex_type> &l, naming::gid_type
                                   const &gid, error_code &ec)

```

Public Members

```
counter_data counter_data_
```

Private Types

```
using migration_table_type = std::map<naming::gid_type, hpx::tuple<bool, std::size_t,
lcos::local::detail::condition_variable>>
```

```
using free_entry_allocator_type = util::internal_allocator<free_entry>
```

```
using free_entry_list_type = std::list<free_entry, free_entry_allocator_type>
```

Private Functions

```
resolved_type resolve_gid_locked_non_local(std::unique_lock<mutex_type> &l,
                                           naming::gid_type const &gid, error_code
                                           &ec)
```

```
void increment(naming::gid_type const &lower, naming::gid_type const &upper, std::int64_t
               const &credits, error_code &ec)
```

```
void resolve_free_list(std::unique_lock<mutex_type> &l,
                      std::list<refcnt_table_type::iterator> const &free_list,
                      free_entry_list_type &free_entry_list, naming::gid_type const
                      &lower, naming::gid_type const &upper, error_code &ec)
```

```
void decrement_sweep(free_entry_list_type &free_list, naming::gid_type const &lower,
                     naming::gid_type const &upper, std::int64_t credits, error_code &ec)
```

```
void free_components_sync(free_entry_list_type const &free_list, naming::gid_type const  
                          &lower, naming::gid_type const &upper, error_code &ec)  
                          const
```

Private Members

```
mutex_type mutex_ = mutex_type("primary_namespace")
```

```
gva_table_type gvas_
```

```
refcnt_table_type refcnts_
```

```
std::string instance_name_
```

```
naming::gid_type next_id_
```

```
naming::gid_type locality_
```

```
migration_table_type migrating_objects_
```

```
struct counter_data
```

Public Functions

```
counter_data(counter_data const&) = delete
```

```
counter_data(counter_data&&) = delete
```

```
counter_data &operator=(counter_data const&) = delete
```

```
counter_data &operator=(counter_data&&) = delete
```

```
counter_data() = default
```

```
std::int64_t get_bind_gid_count(bool)
```

```
std::int64_t get_resolve_gid_count(bool)
```

```
std::int64_t get_unbind_gid_count(bool)
```

```
std::int64_t get_increment_credit_count(bool)
```

```
std::int64_t get_decrement_credit_count(bool)
```

```
std::int64_t get_allocate_count(bool)
```

```
std::int64_t get_begin_migration_count(bool)
```

```
std::int64_t get_end_migration_count(bool)
```

```

std::int64_t get_overall_count(bool)
std::int64_t get_bind_gid_time(bool)
std::int64_t get_resolve_gid_time(bool)
std::int64_t get_unbind_gid_time(bool)
std::int64_t get_increment_credit_time(bool)
std::int64_t get_decrement_credit_time(bool)
std::int64_t get_allocate_time(bool)
std::int64_t get_begin_migration_time(bool)
std::int64_t get_end_migration_time(bool)
std::int64_t get_overall_time(bool)
void increment_bind_gid_count()
void increment_resolve_gid_count()
void increment_unbind_gid_count()
void increment_increment_credit_count()
void increment_decrement_credit_count()
void increment_allocate_count()
void increment_begin_migration_count()
void increment_end_migration_count()
void enable_all()

```

Public Members

```

api_counter_data bind_gid_

api_counter_data resolve_gid_

api_counter_data unbind_gid_

api_counter_data increment_credit_

api_counter_data decrement_credit_

api_counter_data allocate_

api_counter_data begin_migration_

```

```
api_counter_data end_migration_
```

```
struct api_counter_data
```

Public Members

```
std::atomic<std::int64_t> count_ = 0
```

```
std::atomic<std::int64_t> time_ = 0
```

```
bool enabled_ = false
```

```
struct free_entry
```

Public Functions

```
inline free_entry (agas::gva const &gva, naming::gid_type const &gid, naming::gid_type  
                  const &loc)
```

Public Members

```
agas::gva gva_
```

```
naming::gid_type gid_
```

```
naming::gid_type locality_
```

async_colocated

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::get_colocation_id

Defined in header `hpx/runtime.hpp`⁵⁷⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

⁵⁷⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

hpx::id_type **hpx::get_colocation_id**(*launch::sync_policy*, *hpx::id_type* const &id, *error_code* &ec = *throws*)

Return the id of the locality where the object referenced by the given id is currently located on.

The function *hpx::get_colocation_id()* returns the id of the locality where the given object is currently located.

See also:

hpx::get_colocation_id()

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The id of the object to locate.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx::future<hpx::id_type> **hpx::get_colocation_id**(*hpx::id_type* const &id)

Asynchronously return the id of the locality where the object referenced by the given id is currently located on.

See also:

hpx::get_colocation_id(launch::sync_policy)

Parameters

- **id** – [in] The id of the object to locate.

async_distributed

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/async_distributed/packaged_action.hpp

Defined in header *hpx/async_distributed/packaged_action.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **lcos**

template<typename **Action**, typename **Result**, bool **DirectExecute**>

class **packaged_action**

#include <packaged_action.hpp> A *packaged_action* can be used by a single *thread* to invoke a (re-mote) action and wait for the result. The result is expected to be sent back to the *packaged_action* using the LCO's *set_event* action

A *packaged_action* is one of the simplest synchronization primitives provided by HPX. It allows to synchronize on an eager evaluated remote operation returning a result of the type *Result*.

Note: The action executed using the *packaged_action* as a continuation must return a value of a type convertible to the type as specified by the template parameter *Result*.

Template Parameters

- **Action** – The template parameter *Action* defines the action to be executed by this *packaged_action* instance. The arguments *arg0*,... *argN* are used as parameters for this action.
- **Result** – The template parameter *Result* defines the type this *packaged_action* is expected to return from its associated future *packaged_action::get_future*.
- **DirectExecute** – The template parameter *DirectExecute* is an optimization aid allowing to execute the action directly if the target is local (without spawning a new thread for this). This template does not have to be supplied explicitly as it is derived from the template parameter *Action*.

```
template<typename Action, typename Result>
```

```
class packaged_action<Action, Result, false> : public hpx::distributed::promise<Result,  
hpx::traits::extract_action<Action>::remote_result_type>
```

```
    Subclassed by hpx::lcos::packaged_action< Action, Result, true >
```

Public Functions

```
inline packaged_action()
```

```
template<typename Allocator>
```

```
inline packaged_action(std::allocator_arg_t, Allocator const &alloc)
```

```
template<typename ...Ts>
```

```
inline void post(hpx::id_type const &id, Ts&&... vs)
```

```
template<typename ...Ts>
```

```
inline void post(naming::address &&addr, hpx::id_type const &id, Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>
```

```
inline void post_cb(hpx::id_type const &id, Callback &&cb, Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>
```

```
inline void post_cb(naming::address &&addr, hpx::id_type const &id, Callback &&cb, Ts&&...  
vs)
```

```
template<typename ...Ts>
```

```
inline void post_p(hpx::id_type const &id, hpx::launch policy, Ts&&... vs)
```

```
template<typename ...Ts>
```

```
inline void post_p(naming::address &&addr, hpx::id_type const &id, hpx::launch policy, Ts&&...  
vs)
```

```
template<typename Callback, typename ...Ts>
```

```
inline void post_p_cb(hpx::id_type const &id, hpx::launch policy, Callback &&cb, Ts&&... vs)
```

```
template<typename Callback, typename ...Ts>
```



```

inline void post_p_cb(naming::address &&addr, hpx::id_type const &id, hpx::launch policy,
                     Callback &&cb, Ts&&... vs)

template<typename ...Ts>
inline void post_deferred(naming::address &&addr, hpx::id_type const &id, hpx::launch policy,
                         Ts&&... vs)

template<typename Callback, typename ...Ts>
inline void post_deferred_cb(naming::address &&addr, hpx::id_type const &id, hpx::launch
                             policy, Callback &&cb, Ts&&... vs)

```

Protected Types

```

using action_type = hpx::traits::extract_action<Action>::type

using remote_result_type = action_type::remote_result_type

using base_type = hpx::distributed::promise<Result, remote_result_type>

```

Protected Functions

```

template<typename ...Ts>
inline void do_post(naming::address &&addr, hpx::id_type const &id, hpx::launch policy, Ts&&...
                  vs)

template<typename ...Ts>
inline void do_post(hpx::id_type const &id, hpx::launch policy, Ts&&... vs)

template<typename Callback, typename ...Ts>
inline void do_post_cb(naming::address &&addr, hpx::id_type const &id, hpx::launch policy,
                      Callback &&cb, Ts&&... vs)

template<typename Callback, typename ...Ts>
inline void do_post_cb(hpx::id_type const &id, hpx::launch policy, Callback &&cb, Ts&&... vs)

template<typename Action, typename Result>

class packaged_action<Action, Result, true> : public hpx::lcos::packaged_action<Action, Result,
false>

```

Public Functions

```

inline packaged_action()
    Construct a (non-functional) instance of a packaged_action. To use this instance its member function post needs to be directly called.

template<typename Allocator>
inline packaged_action(std::allocator_arg_t, Allocator const &alloc)

template<typename ...Ts>

```

```
inline void post(hpx::id_type const &id, Ts&&... vs)

template<typename ...Ts>
inline void post(naming::address &&addr, hpx::id_type const &id, Ts&&... vs)

template<typename Callback, typename ...Ts>
inline void post_cb(hpx::id_type const &id, Callback &&cb, Ts&&... vs)

template<typename Callback, typename ...Ts>
inline void post_cb(naming::address &&addr, hpx::id_type const &id, Callback &&cb, Ts&&...
vs)
```

Private Types

```
using action_type = packaged_action<Action, Result, false>::action_type
```

hpx::post (distributed)

Defined in header `hpx/async.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

hpx::post

```
template<typename F, typename ...Ts>
bool hpx::post(F &&f, Ts&&... ts)
```

Runs the function `f` asynchronously (potentially in a separate thread which might be a part of a thread pool). This is done in a fire-and-forget manner, meaning there is no return value or way to synchronize with the function execution (it does not return an *hpx::future* that would hold the result of that function call).

hpx::post is particularly useful when synchronization mechanisms as heavyweight as futures are not desired, and instead, more lightweight mechanisms like latches or atomic variables are preferred. Essentially, the *post* function enables the launch of a new thread without the overhead of creating a future.

Note: *hpx::post* is similar to *hpx::async* but does not return a future. This is why there is no way of finding out the result/failure of the execution of this function.

```
template<typename Action, typename ...Ts>
bool hpx::post(hpx::id_type const &id, Ts&&... vs)

template<typename Action, typename Client, typename Stub, typename Data, typename ...Ts>
bool hpx::post(components::client_base<Client, Stub, Data> const &c, Ts&&... vs)

template<typename Action, typename DistPolicy, typename ...Ts>
bool hpx::post(DistPolicy const &policy, Ts&&... vs)

template<typename Action, typename Continuation, typename ...Ts>
bool hpx::post(Continuation &&c, hpx::id_type const &gid, Ts&&... vs)

template<typename Action, typename Continuation, typename Client, typename Stub, typename Data,
typename ...Ts>
```

```
bool hpx::post(Continuation &&cont, components::client_base<Client, Stub, Data> const &c, Ts&&... vs)
```

```
template<typename Action, typename Continuation, typename DistPolicy, typename ...Ts>
```

```
bool hpx::post(Continuation &&c, DistPolicy const &policy, Ts&&... vs)
```

```
template<typename Action, typename Target, typename ...Ts>
```

```
bool hpx::post(Action &&action, Target &&target, Ts&&... ts)
```

The distributed implementation of `hpx::post` can be used by giving an action instance as argument instead of a function, and also by providing another argument with the locality ID or the target ID.

Template Parameters

- **Action** – The type of action instance
- **Target** – The type of target where the action should be executed
- **Ts** – The type of any additional arguments

Parameters

- **action** – The action instance to be executed
- **target** – The target where the action should be executed
- **ts** – Additional arguments

Returns

true if the action was successfully posted, false otherwise.

hpx/async_distributed/trigger_lco_fwd.hpp

Defined in header `hpx/async_distributed/trigger_lco_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

Functions

```
void trigger_lco_event(hpx::id_type id, naming::address &&addr, bool move_credits = true)
```

Trigger the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should be triggered.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
inline void trigger_lco_event(hpx::id_type const &id, bool move_credits = true)
```

Trigger the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should be triggered.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
void trigger_lco_event(hpx::id_type id, naming::address &&addr, hpx::id_type const &cont, bool  
    move_credits = true)
```

Trigger the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should be triggered.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
inline void trigger_lco_event(hpx::id_type const &id, hpx::id_type const &cont, bool move_credits =  
    true)
```

Trigger the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should be triggered.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
template<typename Result>
```

```
void set_lco_value(hpx::id_type id, naming::address &&addr, Result &&t, bool move_credits = true)
```

Set the result value for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **t** – [in] This is the value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
template<typename Result>
```

```
void set_lco_value(hpx::id_type const &id, Result &&t, bool move_credits = true)
```

Set the result value for the (managed) LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **t** – [in] This is the value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
template<typename Result>
```

```
void set_lco_value_unmanaged(hpx::id_type const &id, Result &&t, bool move_credits = true)
```

Set the result value for the (unmanaged) LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **t** – [in] This is the value which should be sent to the LCO.

- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

template<typename **Result**>

void **set_lco_value**(*hpx::id_type* id, *naming::address &&addr*, *Result &&t*, *hpx::id_type* const &cont, bool move_credits = true)

Set the result value for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **t** – [in] This is the value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

template<typename **Result**>

void **set_lco_value**(*hpx::id_type* const &id, *Result &&t*, *hpx::id_type* const &cont, bool move_credits = true)

Set the result value for the (managed) LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **t** – [in] This is the value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

template<typename **Result**>

void **set_lco_value_unmanaged**(*hpx::id_type* const &id, *Result &&t*, *hpx::id_type* const &cont, bool move_credits = true)

Set the result value for the (unmanaged) LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the given value.
- **t** – [in] This is the value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

void **set_lco_error**(*hpx::id_type* id, *naming::address &&addr*, *std::exception_ptr* const &e, bool move_credits = true)

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **e** – [in] This is the error value which should be sent to the LCO.

- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

void **set_lco_error**(*hpx::id_type* id, *naming::address* &&addr, *std::exception_ptr* &&e, bool move_credits = true)

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **e** – [in] This is the error value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

inline void **set_lco_error**(*hpx::id_type* const &id, *std::exception_ptr* const &e, bool move_credits = true)

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **e** – [in] This is the error value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

inline void **set_lco_error**(*hpx::id_type* const &id, *std::exception_ptr* &&e, bool move_credits = true)

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **e** – [in] This is the error value which should be sent to the LCO.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

void **set_lco_error**(*hpx::id_type* id, *naming::address* &&addr, *std::exception_ptr* const &e, *hpx::id_type* const &cont, bool move_credits = true)

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **e** – [in] This is the error value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

void **set_lco_error**(*hpx::id_type* id, *naming::address* &&addr, *std::exception_ptr* &&e, *hpx::id_type* const &cont, bool move_credits = true)

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.

- **addr** – [in] This represents the addr of the LCO which should be triggered.
- **e** – [in] This is the error value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
inline void set_lco_error(hpx::id_type const &id, std::exception_ptr const &e, hpx::id_type const &cont,
                        bool move_credits = true)
```

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **e** – [in] This is the error value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

```
inline void set_lco_error(hpx::id_type const &id, std::exception_ptr &&e, hpx::id_type const &cont, bool
                        move_credits = true)
```

Set the error state for the LCO referenced by the given id.

Parameters

- **id** – [in] This represents the id of the LCO which should receive the error value.
- **e** – [in] This is the error value which should be sent to the LCO.
- **cont** – [in] This represents the LCO to trigger after completion.
- **move_credits** – [in] If this is set to *true* then it is ok to send all credits in *id* along with the generated message. The default value is *true*.

hpx::distributed::promise

Defined in header `hpx/future.hpp`⁵⁷⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename Result, typename RemoteResult>
```

```
class promise
```

A promise can be used by a single *thread* to invoke a (remote) action and wait for the result. The result is expected to be sent back to the promise using the LCO's `set_event` action

A promise is one of the simplest synchronization primitives provided by HPX. It allows to synchronize on a eager evaluated remote operation returning a result of the type *Result*. The *promise* allows to synchronize exactly one *thread* (the one passed during construction time).

```
// Create the promise (the expected result is a id_type)
hpx::distributed::promise<hpx::id_type> p;

// Get the associated future
```

(continues on next page)

⁵⁷⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

(continued from previous page)

```
future<hpx::id_type> f = p.get_future();

// initiate the action supplying the promise as a
// continuation
apply<some_action>(new continuation(p.get_id()), ...);

// Wait for the result to be returned, yielding control
// in the meantime.
hpx::id_type result = f.get();
// ...
```

Note: The action executed by the promise must return a value of a type convertible to the type as specified by the template parameter *RemoteResult*

Template Parameters

- **Result** – The template parameter *Result* defines the type this promise is expected to return from *promise::get*.
- **RemoteResult** – The template parameter *RemoteResult* defines the type this promise is expected to receive from the remote action.

hpx/async_distributed/promise.hpp

Defined in header `hpx/async_distributed/promise.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<>

```
class promise<void, hpx::util::unused_type> : public lcos::detail::promise_base<void, hpx::util::unused_type,
lcos::detail::promise_data<void>>
```

Public Functions

promise() = default

constructs a promise object and a shared state.

template<typename **Allocator**>

inline **promise**(std::allocator_arg_t, *Allocator* const &a)

constructs a promise object and a shared state. The constructor uses the allocator *to* allocate the memory for the shared state.

promise(*promise* &&other) noexcept = default

constructs a new promise object and transfers ownership of the shared state of other (if any) to the newly-constructed object.

Post

other has no shared state.

~promise() = default

Abandons any shared state.

promise &**operator**=(*promise* &&*other*) noexcept = default

Abandons any shared state (30.6.4) and then as if `promise(HPX_MOVE(other)).swap(*this)`.

Returns

*this.

inline void **swap**(*promise* &*other*) noexcept

Exchanges the shared state of *this and other.

Post

*this has the shared state (if any) that other had prior to the call to swap. other has the shared state (if any) that *this had prior to the call to swap.

inline void **set_value**()

atomically stores the value r in the shared state and makes that state ready (30.6.4).

Throws

future_error – if its shared state already has a stored value. if shared state has no stored value exception is raised. **promise_already_satisfied** if its shared state already has a stored value or exception. **no_state** if *this has no shared state.

Private Types

```
using base_type = lcos::detail::promise_base<void, hpx::util::unused_type,
lcos::detail::promise_data<void>>
```

```
template<typename R, typename Allocator>
```

```
struct uses_allocator<hpx::distributed::promise<R>, Allocator> : public true_type
```

```
#include <promise.hpp> Requires: Allocator shall be an allocator (17.6.3.5)
```

```
namespace hpx
```

```
namespace distributed
```

Functions

```
template<typename Result, typename RemoteResult>
```

```
void swap(promise<Result, RemoteResult> &x, promise<Result, RemoteResult> &y) noexcept
```

```
template<typename Result, typename RemoteResult>
```

```
class promise
```

```
#include <promise.hpp>
```

```
template<> unused_type > : public lcos::detail::promise_base< void,
hpx::util::unused_type, lcos::detail::promise_data< void > >
```

Public Functions

promise() = default

constructs a promise object and a shared state.

template<typename **Allocator**>

inline **promise**(*std::allocator_arg_t*, *Allocator* const &a)

constructs a promise object and a shared state. The constructor uses the allocator *to* allocate the memory for the shared state.

promise(*promise* &&other) noexcept = default

constructs a new promise object and transfers ownership of the shared state of other (if any) to the newly- constructed object.

Post

other has no shared state.

~promise() = default

Abandons any shared state.

promise &**operator**=(*promise* &&other) noexcept = default

Abandons any shared state (30.6.4) and then as if `promise(HPX_MOVE(other)).swap(*this)`.

Returns

*this.

inline void **swap**(*promise* &other) noexcept

Exchanges the shared state of *this and other.

Post

*this has the shared state (if any) that other had prior to the call to swap. other has the shared state (if any) that *this had prior to the call to swap.

inline void **set_value**()

atomically stores the value *r* in the shared state and makes that state ready (30.6.4).

Throws

future_error – if its shared state already has a stored value. if shared state has no stored value exception is raised. **promise_already_satisfied** if its shared state already has a stored value or exception. **no_state** if *this has no shared state.

Private Types

using **base_type** = *lcos::detail::promise_base*<void, *hpx::util::unused_type*,
lcos::detail::promise_data<void>>

namespace **std**

template<typename R, typename **Allocator**> **promise**< R >,

Allocator > : public **true_type**

#include <promise.hpp> Requires: Allocator shall be an allocator (17.6.3.5)

hpx/async_distributed/transfer_continuation_action.hpp

Defined in header `hpx/async_distributed/transfer_continuation_action.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/async_distributed/continuation.hpp

Defined in header `hpx/async_distributed/continuation.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<>

struct **typed_continuation**<void, util::unused_type> : public *hpx::actions::continuation*

Public Types

using **result_type** = void

Public Functions

typed_continuation() = default

explicit **typed_continuation**(*hpx::id_type* const &id)

explicit **typed_continuation**(*hpx::id_type* &&id) noexcept

template<typename **F**>
inline **typed_continuation**(*hpx::id_type* const &id, *F* &&f)

template<typename **F**>
inline **typed_continuation**(*hpx::id_type* &&id, *F* &&f)

typed_continuation(*hpx::id_type* const &id, *naming::address* &&addr)

typed_continuation(*hpx::id_type* &&id, *naming::address* &&addr) noexcept

template<typename **F**>
inline **typed_continuation**(*hpx::id_type* const &id, *naming::address* &&addr, *F* &&f)

template<typename **F**>
inline **typed_continuation**(*hpx::id_type* &&id, *naming::address* &&addr, *F* &&f)

template<typename **F**>
inline explicit **typed_continuation**(*F* &&f)

typed_continuation(*typed_continuation*&&) noexcept

typed_continuation &**operator**=(*typed_continuation*&&) noexcept

void **trigger**() const

void **trigger_value**(*util::unused_type*&&) const

void **trigger_value**(*util::unused_type* const&) const

Private Types

```
using function_type = hpx::distributed::move_only_function<void(hpx::id_type)>
```

Private Functions

```
void serialize(hpx::serialization::input_archive &ar, unsigned)
```

```
void serialize(hpx::serialization::output_archive &ar, unsigned)
```

Private Members

```
function_type f_
```

Friends

```
friend class hpx::serialization::access
```

```
namespace hpx
```

```
namespace actions
```

```
class continuation
```

```
Subclassed by hpx::actions::typed_continuation<Result, Result>, hpx::actions::typed_continuation<  
void, util::unused_type>
```

Public Types

```
using continuation_tag = void
```

Public Functions

```
continuation()
```

```
explicit continuation(hpx::id_type const &id)
```

```
explicit continuation(hpx::id_type &&id)
```

```
continuation(hpx::id_type const &id, naming::address &&addr)
```

```
continuation(hpx::id_type &&id, naming::address &&addr) noexcept
```

```
continuation(continuation &&o) noexcept
```

```
continuation &operator=(continuation &&o) noexcept
```

```

void trigger_error(std::exception_ptr const &e) const
    Deliver an exception to this continuation's destination instead of a value.
    Parameters
        e – The exception to forward to the destination.

void trigger_error(std::exception_ptr &&e) const
    Deliver an exception to this continuation's destination instead of a value.
    Parameters
        e – The exception to forward to the destination.

void serialize(hpx::serialization::input_archive &ar, unsigned)

void serialize(hpx::serialization::output_archive &ar, unsigned)

inline constexpr hpx::id_type const &get_id() const noexcept

inline constexpr naming::address get_addr() const noexcept

```

Protected Attributes

```
hpx::id_type id_
```

```
naming::address addr_
```

```
template<typename Result, typename RemoteResult>
```

```
struct typed_continuation
```

Public Functions

```

typed_continuation() = default

inline explicit typed_continuation(hpx::id_type const &id)

inline explicit typed_continuation(hpx::id_type &&id) noexcept

template<typename F>
inline typed_continuation(hpx::id_type const &id, F &&f)

template<typename F>
inline typed_continuation(hpx::id_type &&id, F &&f)

inline typed_continuation(hpx::id_type const &id, naming::address &&addr)

inline typed_continuation(hpx::id_type &&id, naming::address &&addr) noexcept

template<typename F>
inline typed_continuation(hpx::id_type const &id, naming::address &&addr, F &&f)

template<typename F>
inline typed_continuation(hpx::id_type &&id, naming::address &&addr, F &&f)

template<typename F>
inline explicit typed_continuation(F &&f)

```

```
typed_continuation(typed_continuation&&) noexcept = default  
typed_continuation &operator=(typed_continuation&&) noexcept = default  
inline void trigger_value(RemoteResult &&result)
```

Private Types

```
using base_type = typed_continuation<RemoteResult>  
  
using function_type = hpx::distributed::move_only_function<void(hpx::id_type, RemoteResult)>
```

Private Functions

```
template<typename Archive>  
inline void serialize(Archive &ar, unsigned)
```

Friends

```
friend class hpx::serialization::access  
  
template<typename Result>  
struct typed_continuation<Result, Result> : public hpx::actions::continuation
```

Public Types

```
using result_type = Result
```

Public Functions

```
typed_continuation() = default  
  
inline explicit typed_continuation(hpx::id_type const &id)  
  
inline explicit typed_continuation(hpx::id_type &&id) noexcept  
  
template<typename F>  
inline typed_continuation(hpx::id_type const &id, F &&f)  
  
template<typename F>  
inline typed_continuation(hpx::id_type &&id, F &&f)  
  
inline typed_continuation(hpx::id_type const &id, naming::address &&addr)  
  
inline typed_continuation(hpx::id_type &&id, naming::address &&addr) noexcept  
  
template<typename F>
```

```

inline typed_continuation(hpx::id_type const &id, naming::address &&addr, F &&f)

template<typename F>
inline typed_continuation(hpx::id_type &&id, naming::address &&addr, F &&f)

template<typename F>
inline explicit typed_continuation(F &&f)

typed_continuation(typed_continuation&&) noexcept = default
typed_continuation &operator=(typed_continuation&&) noexcept = default

inline void trigger_value(Result &&result)

```

Protected Attributes

function_type **f_**

Private Types

```
using function_type = hpx::distributed::move_only_function<void(hpx::id_type, Result)>
```

Private Functions

```

template<typename Archive>
inline void serialize(Archive &ar, unsigned)

```

Friends

```
friend class hpx::serialization::access
```

```
template<> unused_type > : public hpx::actions::continuation
```

Public Types

```
using result_type = void
```

Public Functions

```

typed_continuation() = default

explicit typed_continuation(hpx::id_type const &id)

explicit typed_continuation(hpx::id_type &&id) noexcept

template<typename F>

```

```
inline typed_continuation(hpx::id_type const &id, F &&f)

template<typename F>
inline typed_continuation(hpx::id_type &&id, F &&f)

typed_continuation(hpx::id_type const &id, naming::address &&addr)

typed_continuation(hpx::id_type &&id, naming::address &&addr) noexcept

template<typename F>
inline typed_continuation(hpx::id_type const &id, naming::address &&addr, F &&f)

template<typename F>
inline typed_continuation(hpx::id_type &&id, naming::address &&addr, F &&f)

template<typename F>
inline explicit typed_continuation(F &&f)

typed_continuation(typed_continuation&&) noexcept

typed_continuation &operator=(typed_continuation&&) noexcept

void trigger() const

void trigger_value(util::unused_type&&) const

void trigger_value(util::unused_type const&) const
```

Private Types

```
using function_type = hpx::distributed::move_only_function<void(hpx::id_type)>
```

Private Functions

```
void serialize(hpx::serialization::input_archive &ar, unsigned)

void serialize(hpx::serialization::output_archive &ar, unsigned)
```

Private Members

```
function_type f_
```

Friends

```
friend class hpx::serialization::access
```


hpx/async_distributed/trigger_lco.hpp

Defined in header `hpx/async_distributed/trigger_lco.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

hpx/async_distributed/trigger.hpp

Defined in header `hpx/async_distributed/trigger.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace actions
```

Functions

```
template<typename Result, typename RemoteResult, typename F, typename ...Ts>
void trigger(typed_continuation<Result, RemoteResult> &&cont, F &&f, Ts&&... vs) noexcept
```

Invoke *f* with the given arguments and forward its result to *cont*.

On success, the result of invoking *f* is passed to *cont.trigger_value()*. If invoking *f* throws, the exception is forwarded to the destination instead by calling *cont.trigger_error()* so that `hpx::exceptions` are propagated back to the client.

Parameters

- **cont** – The continuation that either the result or an exception is delivered to.
- **f** – The callable to invoke.
- **vs** – The arguments to invoke *f* with.

```
template<typename Result, typename F, typename ...Ts>
void trigger(typed_continuation<Result, util::unused_type> &&cont, F &&f, Ts&&... vs) noexcept
```

Invoke *f* with the given arguments and notify *cont* of completion. Overload for when the return type is “void” aka `util::unused_type`.

On success, *cont.trigger()* is called to signal completion. If invoking *f* throws, the exception is forwarded to the destination instead by calling *cont.trigger_error()* so that `hpx::exceptions` are propagated back to the client.

Parameters

- **cont** – The continuation that completion or an exception is delivered to.
- **f** – The callable to invoke.
- **vs** – The arguments to invoke *f* with.

hpx::dataflow (distributed)

Defined in header `hpx/async.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

hpx::dataflow

Warning: doxygenfunction: Unable to resolve function “hpx::dataflow” with arguments (F&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename Target, typename ...Ts> decltype(auto) ↵
↵dataflow(Action &&action, Target &&target, Ts&&... ts)
- template<typename F, typename ...Ts> decltype(auto) dataflow(F &&f, Ts&&... ts)
```

Warning: doxygenfunction: Unable to resolve function “hpx::dataflow” with arguments (Action&&, Target&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename Target, typename ...Ts> decltype(auto) ↵
↵dataflow(Action &&action, Target &&target, Ts&&... ts)
- template<typename F, typename ...Ts> decltype(auto) dataflow(F &&f, Ts&&... ts)
```

hpx::sync (distributed)

Defined in header `hpx/async.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

hpx::sync

```
template<typename Action, typename F, typename ...Ts>
auto hpx::sync(F &&f, Ts&&... ts) -> decltype(detail::sync_action_dispatch<Action,
std::decay_t<F>>::call(HPX_FORWARD(F, f), HPX_FORWARD(Ts, ts)...))
```

The function template *sync* runs the function *f* synchronously and returns a `hpx::future` that will eventually hold the result of that function call.

```
template<typename Action, typename F, typename ...Ts>
auto hpx::sync(F &&f, Ts&&... ts) -> decltype(detail::sync_action_dispatch<Action,
std::decay_t<F>>::call(HPX_FORWARD(F, f), HPX_FORWARD(Ts, ts)...))
```

The function template *sync* runs the function *f* synchronously and returns a `hpx::future` that will eventually hold the result of that function call.

Warning: doxygenfunction: Unable to resolve function “hpx::sync” with arguments (Action&&, Target&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename F, typename ...Ts> auto sync(F &&f, Ts&&... ts) -
↵> decltype(detail::sync_action_dispatch<Action, std::decay_t<F>>::call(HPX_
↵FORWARD(F, f), HPX_FORWARD(Ts, ts)...))
```

```

- template<typename Action, typename Target, typename ...Ts> decltype(auto)
  ↳ sync(Action &&action, Target &&target, Ts&&... ts)
- template<typename F, typename ...Ts> decltype(auto) sync(F &&f, Ts&&... ts)

```

hpx::async (distributed)

Defined in header `hpx/async.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

`hpx::async`

```

template<typename Action, typename F, typename ...Ts>
auto hpx::async(F &&f, Ts&&... ts) -> decltype(detail::async_action_dispatch<Action,
    std::decay_t<F>>::call(HPX_FORWARD(F, f), HPX_FORWARD(Ts, ts)...))

```

The function template `async` runs the function `f` asynchronously (potentially in a separate thread which might be a part of a thread pool) and returns a `hpx::future` that will eventually hold the result of that function call. If no policy is defined, `async` behaves as if it is called with policy being `hpx::launch::async` | `hpx::launch::deferred`. Otherwise, it calls a function `f` with arguments `ts` according to a specific launch policy.

- If the `async` flag is set (i.e. `(policy & hpx::launch::async) != 0`), then `async` executes the callable object `f` on a new thread of execution (with all thread-locals initialized) as if spawned by `hpx::thread(std::forward<F>(f), std::forward<Ts>(ts)...)`, except that if the function `f` returns a value or throws an exception, it is stored in the shared state accessible through the `hpx::future` that `async` returns to the caller.
- If the `deferred` flag is set (i.e. `(policy & hpx::launch::deferred) != 0`), then `async` converts `f` and `ts...` the same way as by `hpx::thread` constructor, but does not spawn a new thread of execution. Instead, lazy evaluation is performed: the first call to a non-timed wait function on the `hpx::future` that `async` returned to the caller will cause the copy of `f` to be invoked (as a rvalue) with the copies of `ts...` (also passed as rvalues) in the current thread (which does not have to be the thread that originally called `hpx::async`). The result or exception is placed in the shared state associated with the future and only then it is made ready. All further accesses to the same `hpx::future` will return the result immediately.
- If neither `hpx::launch::async` nor `hpx::launch::deferred`, nor any implementation-defined policy flag is set in policy, the behavior is undefined.

If more than one flag is set, it is implementation-defined which policy is selected. For the default (both the `hpx::launch::async` and `hpx::launch::deferred` flags are set in policy), standard recommends (but doesn't require) utilizing available concurrency, and deferring any additional tasks.

In any case, the call to `hpx::async` synchronizes-with (as defined in `std::memory_order`) the call to `f`, and the completion of `f` is sequenced-before making the shared state ready. If the `async` policy is chosen, the associated thread completion synchronizes-with the successful return from the first function that is waiting on the shared state, or with the return of the last function that releases the shared state, whichever comes first. If `std::decay<Function>::type` or each type in `std::decay<Ts>::type` is not constructible from its corresponding argument, the program is ill-formed.

Parameters

- **f** – Callable object to call
- **ts** – parameters to pass to `f`

Returns

`hpx::future` referring to the shared state created by this call to `hpx::async`.

```
template<typename Action, typename F, typename ...Ts>
auto hpx::async(F &&f, Ts&&... ts) -> decltype(detail::async_action_dispatch<Action,
    std::decay_t<F>>::call(HPX_FORWARD(F, f), HPX_FORWARD(Ts, ts)...))
```

The function template *async* runs the function *f* asynchronously (potentially in a separate thread which might be a part of a thread pool) and returns a *hpx::future* that will eventually hold the result of that function call. If no policy is defined, *async* behaves as if it is called with policy being *hpx::launch::async* | *hpx::launch::deferred*. Otherwise, it calls a function *f* with arguments *ts* according to a specific launch policy.

- If the async flag is set (i.e. (policy & *hpx::launch::async*) != 0), then *async* executes the callable object *f* on a new thread of execution (with all thread-locals initialized) as if spawned by *hpx::thread*(std::forward<**F**>(f), std::forward<**Ts**>(ts)...), except that if the function *f* returns a value or throws an exception, it is stored in the shared state accessible through the *hpx::future* that *async* returns to the caller.
- If the deferred flag is set (i.e. (policy & *hpx::launch::deferred*) != 0), then *async* converts *f* and *ts...* the same way as by *hpx::thread* constructor, but does not spawn a new thread of execution. Instead, lazy evaluation is performed: the first call to a non-timed wait function on the *hpx::future* that *async* returned to the caller will cause the copy of *f* to be invoked (as a rvalue) with the copies of *ts...* (also passed as rvalues) in the current thread (which does not have to be the thread that originally called *hpx::async*). The result or exception is placed in the shared state associated with the future and only then it is made ready. All further accesses to the same *hpx::future* will return the result immediately.
- If neither *hpx::launch::async* nor *hpx::launch::deferred*, nor any implementation-defined policy flag is set in policy, the behavior is undefined.

If more than one flag is set, it is implementation-defined which policy is selected. For the default (both the *hpx::launch::async* and *hpx::launch::deferred* flags are set in policy), standard recommends (but doesn't require) utilizing available concurrency, and deferring any additional tasks.

In any case, the call to *hpx::async* synchronizes-with (as defined in std::memory_order) the call to *f*, and the completion of *f* is sequenced-before making the shared state ready. If the *async* policy is chosen, the associated thread completion synchronizes-with the successful return from the first function that is waiting on the shared state, or with the return of the last function that releases the shared state, whichever comes first. If std::decay<Function>::type or each type in std::decay<**Ts**>::type is not constructible from its corresponding argument, the program is ill-formed.

Parameters

- **f** – Callable object to call
- **ts** – parameters to pass to *f*

Returns

hpx::future referring to the shared state created by this call to *hpx::async*.

Warning: doxygenfunction: Unable to resolve function “hpx::async” with arguments (Executor&&, hpx::sycl::experimental::sycl_executor::queue_function_ptr_t<**Ts**...>&&, **Ts**&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename F, typename ...Ts> auto async(F &&f, Ts&&... ts)
-> decltype(detail::async_action_dispatch<Action, std::decay_t<F>>::call(HPX_
->FORWARD(F, f), HPX_FORWARD(Ts, ts)...))
- template<typename Action, typename Target, typename ...Ts> auto async(Action &&
->action, Target &&target, Ts&&... ts)
- template<typename Executor, typename ...Ts> decltype(auto) async(Executor &&exec,
->hpx::sycl::experimental::sycl_executor::queue_function_ptr_t<Ts...> &&f, Ts&&... ts)
- template<typename F, typename ...Ts> decltype(auto) async(F &&f, Ts&&... ts)
```

```
template<typename Action, typename Target, typename ...Ts>
auto hpx::async(Action &&action, Target &&target, Ts&&... ts)
```

The distributed implementation of **hpx::async** can be used by giving an action instance as argument instead of a function, and also by providing another argument with the locality ID or the target ID. The action executes asynchronously.

Template Parameters

- **Action** – The type of action instance
- **Target** – The type of target where the action should be executed
- **Ts** – The type of any additional arguments

Parameters

- **action** – The action instance to be executed
- **target** – The target where the action should be executed
- **ts** – Additional arguments

Returns

hpx::future referring to the shared state created by this call to **hpx::async**

hpx/async_distributed/base_lco_with_value.hpp

Defined in header **hpx/async_distributed/base_lco_with_value.hpp**.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace components
```

```
namespace lcos
```

```
template<typename Result, typename RemoteResult, typename ComponentTag>
```

```
class base_lco_with_value
```

```
    #include <base_lco_with_value.hpp>
```

```
template<typename ComponentTag>
```

```
class base_lco_with_value<void, void, ComponentTag> : public hpx::lcos::base_lco, public ComponentTag
```

#include <base_lco_with_value.hpp> The **base_lco<void>** specialization is used whenever the **set_event** action for a particular LCO doesn't carry any argument.

Template Parameters

void – This specialization expects no result value and is almost completely equivalent to the plain **base_lco**.

Public Types

```
using wrapping_type = detail::base_lco_wrapping_type<ComponentTag,  
base_lco_with_value>::type
```

```
using base_type_holder = base_lco_with_value
```

```
using set_value_action = base_lco::set_event_action
```

Public Functions

```
inline void get_value()
```

Protected Functions

```
~base_lco_with_value() override = default
```

Destructor, needs to be virtual to allow for clean destruction of derived objects

```
namespace traits
```

hpx/async_distributed/base_lco.hpp

Defined in header hpx/async_distributed/base_lco.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<>
```

```
struct get_lva<hpx::lcos::base_lco>
```

Public Static Functions

```
static inline constexpr hpx::lcos::base_lco *call(hpx::naming::address_type lva) noexcept
```

```
template<>
```

```
struct get_lva<hpx::lcos::base_lco const>
```

Public Static Functions

```
static inline constexpr hpx::lcos::base_lco const *call(hpx::naming::address_type lva) noexcept
```

```
namespace hpx
```

```
template<> base_lco >
```

Public Static Functions

static inline constexpr *hpx::lcos::base_lco* ***call**(*hpx::naming::address_type* lva) noexcept

template<> *base_lco* const >

Public Static Functions

static inline constexpr *hpx::lcos::base_lco* const ***call**(*hpx::naming::address_type* lva) noexcept

namespace **lcos**

class **base_lco**

#include <base_lco.hpp> The *base_lco* class is the common base class for all LCO's implementing a simple *set_event* action

Subclassed by *hpx::lcos::base_lco_with_value< void, void, ComponentTag >*

Public Types

typedef *components::managed_component<base_lco>* **wrapping_type**

typedef *base_lco* **base_type_holder**

Public Functions

virtual void **set_event**() = 0

virtual void **set_exception**(*std::exception_ptr* const &e)

virtual void **connect**(*hpx::id_type* const&)

virtual void **disconnect**(*hpx::id_type* const&)

virtual ~**base_lco**()

Destructor, needs to be virtual to allow for clean destruction of derived objects

void **set_event_nonvirt**()

The *function* *set_event_nonvirt* is called whenever a *set_event_action* is applied on a instance of a LCO. This function just forwards to the virtual function *set_event*, which is overloaded by the derived concrete LCO.

void **set_exception_nonvirt**(*std::exception_ptr* const &e)

The *function* *set_exception* is called whenever a *set_exception_action* is applied on a instance of a LCO. This function just forwards to the virtual function *set_exception*, which is overloaded by the derived concrete LCO.

Parameters

e – [in] The exception encapsulating the error to report to this LCO instance.

void **connect_nonvirt**(hpx::id_type const &id)

The *function* `connect_nonvirt` is called whenever a *connect_action* is applied on a instance of a LCO. This function just forwards to the virtual function *connect*, which is overloaded by the derived concrete LCO.

Parameters

id – [in] target id

void **disconnect_nonvirt**(hpx::id_type const &id)

The *function* `disconnect_nonvirt` is called whenever a *disconnect_action* is applied on a instance of a LCO. This function just forwards to the virtual function *disconnect*, which is overloaded by the derived concrete LCO.

Parameters

id – [in] target id

HPX_DEFINE_COMPONENT_DIRECT_ACTION (base_lco, set_event_nonvirt, set_event_action) HPX_DEFINE_COMPONENT_DIRECT_ACTION(base_lco

Each of the exposed functions needs to be encapsulated into an action type, allowing to generate all required boilerplate code for threads, serialization, etc.

The *set_event_action* may be used to unconditionally trigger any LCO instances, it carries no additional parameters. The *set_exception_action* may be used to transfer arbitrary error information from the remote site to the LCO instance specified as a continuation. This action carries 2 parameters:

Parameters

std::exception_ptr – [in] The exception encapsulating the error to report to this LCO instance.

set_exception_action HPX_DEFINE_COMPONENT_DIRECT_ACTION (base_lco, connect_nonvirt, connect_action) HPX_DEFINE_COMPONENT_DIRECT_ACTION(base_lco

The *connect_action* may be used to.

The *set_exception_action* may be used to

Public Members

set_exception_nonvirt

set_exception_action **disconnect_nonvirt**

Public Static Functions

static components::component_type **get_component_type**() noexcept

static void **set_component_type**(components::component_type type)

checkpoint

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/checkpoint/checkpoint.hpp

Defined in header `hpx/checkpoint/checkpoint.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

This header defines the `save_checkpoint` and `restore_checkpoint` functions. These functions are designed to help HPX application developer's checkpoint their applications. `Save_checkpoint` serializes one or more objects and saves them as a byte stream. `Restore_checkpoint` converts the byte stream back into instances of the objects.

namespace **hpx**

namespace **util**

Functions

`std::ostream &operator<<(std::ostream &ost, checkpoint const &ckp)`

Operator<< Overload

This overload is the main way to write data from a checkpoint to an object such as a file. Inside the function, the size of the checkpoint will be written to the stream before the checkpoint's data. The `operator>>` overload uses this to read the correct number of bytes. Be mindful of this additional write and read when you use different facilities to write out or read in data to a checkpoint!

Parameters

- **ost** – Output stream to write to.
- **ckp** – Checkpoint to copy from.

Returns

Operator<< returns the ostream object.

`std::istream &operator>>(std::istream &ist, checkpoint &ckp)`

Operator>> Overload

This overload is the main way to read in data from an object such as a file to a checkpoint. It is important to note that inside the function, the first variable to be read is the size of the checkpoint. This size variable is written to the stream before the checkpoint's data in the `operator<<` overload. Be mindful of this additional read and write when you use different facilities to read in or write out data from a checkpoint!

Parameters

- **ist** – Input stream to write from.
- **ckp** – Checkpoint to write to.

Returns

Operator>> returns the ostream object.

template<typename **T**, typename ...**Ts**>

```
hpx::future<checkpoint> save_checkpoint(T &&t, Ts&&... ts)
```

Save_checkpoint

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a shared_ptr to the component or by passing a component's client instance to save_checkpoint. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used save_checkpoint will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to save_checkpoint to be serialized and placed into a checkpoint object.
- **Ts** – More containers passed to save_checkpoint to be serialized and placed into a checkpoint object.
- **U** – This parameter is used to make sure that T is not a launch policy or a checkpoint. This forces the compiler to choose the correct overload.

Parameters

- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Save_checkpoint returns a future to a checkpoint with one exception: if you pass hpx::launch::sync as the first argument. In this case save_checkpoint will simply return a checkpoint.

```
template<typename T, typename ...Ts>
```

```
hpx::future<checkpoint> save_checkpoint(checkpoint &&c, T &&t, Ts&&... ts)
```

Save_checkpoint - Take a pre-initialized checkpoint

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a shared_ptr to the component or by passing a component's client instance to save_checkpoint. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used save_checkpoint will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to save_checkpoint to be serialized and placed into a checkpoint object.
- **Ts** – More containers passed to save_checkpoint to be serialized and placed into a checkpoint object.

Parameters

- **c** – Takes a pre-initialized checkpoint to copy data into.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Save_checkpoint returns a future to a checkpoint with one exception: if you pass hpx::launch::sync as the first argument. In this case save_checkpoint will simply return a checkpoint.

```
template<typename T, typename ...Ts>
```

```
hpx::future<checkpoint> save_checkpoint(hpx::launch p, T &&t, Ts&&... ts)
```

Save_checkpoint - Policy overload

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a shared_ptr to the component or by passing a component's client instance to save_checkpoint. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used save_checkpoint will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to save_checkpoint to be serialized and placed into a checkpoint object.
- **Ts** – More containers passed to save_checkpoint to be serialized and placed into a checkpoint object.

Parameters

- **p** – Takes an HPX launch policy. Allows the user to change the way the function is launched i.e. async, sync, etc.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Save_checkpoint returns a future to a checkpoint with one exception: if you pass hpx::launch::sync as the first argument. In this case save_checkpoint will simply return a checkpoint.

```
template<typename T, typename ...Ts>
hpx::future<checkpoint> save_checkpoint(hpx::launch p, checkpoint &&c, T &&t, Ts&&... ts)
    Save_checkpoint - Policy overload & pre-initialized checkpoint
```

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a shared_ptr to the component or by passing a component's client instance to save_checkpoint. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used save_checkpoint will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to save_checkpoint to be serialized and placed into a checkpoint object.
- **Ts** – More containers passed to save_checkpoint to be serialized and placed into a checkpoint object.

Parameters

- **p** – Takes an HPX launch policy. Allows the user to change the way the function is launched i.e. async, sync, etc.
- **c** – Takes a pre-initialized checkpoint to copy data into.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Save_checkpoint returns a future to a checkpoint with one exception: if you pass hpx::launch::sync as the first argument. In this case save_checkpoint will simply return a checkpoint.

```
template<typename T, typename ...Ts>
checkpoint save_checkpoint(hpx::launch::sync_policy sync_p, T &&t, Ts&&... ts)
    Save_checkpoint - Sync_policy overload
```

Save_checkpoint takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a shared_ptr to the

component or by passing a component's client instance to `save_checkpoint`. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used `save_checkpoint` will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.
- **Ts** – More containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.
- **U** – This parameter is used to make sure that **T** is not a checkpoint. This forces the compiler to choose the correct overload.

Parameters

- **sync_p** – `hpx::launch::sync_policy`
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

`Save_checkpoint` which is passed `hpx::launch::sync_policy` will return a checkpoint which contains the serialized values checkpoint.

```
template<typename T, typename ...Ts>
checkpoint save_checkpoint(hpx::launch::sync_policy sync_p, checkpoint &&c, T &&t, Ts&&... ts)
Save_checkpoint - Sync_policy overload & pre-init. checkpoint
```

`Save_checkpoint` takes any number of objects which a user may wish to store and returns a future to a checkpoint object. This function can also store a component either by passing a `shared_ptr` to the component or by passing a component's client instance to `save_checkpoint`. Additionally, the function can take a policy as a first object which changes its behavior depending on the policy passed to it. Most notably, if a sync policy is used `save_checkpoint` will simply return a checkpoint object.

Template Parameters

- **T** – Containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.
- **Ts** – More containers passed to `save_checkpoint` to be serialized and placed into a checkpoint object.

Parameters

- **sync_p** – `hpx::launch::sync_policy`
- **c** – Takes a pre-initialized checkpoint to copy data into.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

`Save_checkpoint` which is passed `hpx::launch::sync_policy` will return a checkpoint which contains the serialized values checkpoint.

```
template<typename T, typename ...Ts>
hpx::future<checkpoint> prepare_checkpoint(T const &t, Ts const&... ts)
prepare_checkpoint
```

`prepare_checkpoint` takes the containers which have to be filled from the byte stream by a subsequent `restore_checkpoint` invocation. `prepare_checkpoint` will calculate the necessary buffer size and will return an appropriately sized checkpoint object.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

prepare_checkpoint returns a properly resized checkpoint object that can be used for a subsequent restore_checkpoint operation.

```
template<typename T, typename ...Ts>
```

```
hpx::future<checkpoint> prepare_checkpoint(checkpoint &&c, T const &t, Ts const&... ts)
```

```
prepare_checkpoint
```

prepare_checkpoint takes the containers which have to be filled from the byte stream by a subsequent restore_checkpoint invocation. prepare_checkpoint will calculate the necessary buffer size and will return an appropriately sized checkpoint object.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **c** – Takes a pre-initialized checkpoint to prepare
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

prepare_checkpoint returns a properly resized checkpoint object that can be used for a subsequent restore_checkpoint operation.

```
template<typename T, typename ...Ts>
```

```
hpx::future<checkpoint> prepare_checkpoint(hpx::launch p, T const &t, Ts const&... ts)
```

```
prepare_checkpoint
```

prepare_checkpoint takes the containers which have to be filled from the byte stream by a subsequent restore_checkpoint invocation. prepare_checkpoint will calculate the necessary buffer size and will return an appropriately sized checkpoint object.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **p** – Takes an HPX launch policy. Allows the user to change the way the function is launched i.e. async, sync, etc.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

prepare_checkpoint returns a properly resized checkpoint object that can be used for a subsequent restore_checkpoint operation.

```
template<typename T, typename ...Ts>
```

```
hpx::future<checkpoint> prepare_checkpoint(hpx::launch p, checkpoint &&c, T const &t, Ts  
const&... ts)
```

```
prepare_checkpoint
```

prepare_checkpoint takes the containers which have to be filled from the byte stream by a subsequent restore_checkpoint invocation. prepare_checkpoint will calculate the necessary buffer size and will

return an appropriately sized checkpoint object.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **p** – Takes an HPX launch policy. Allows the user to change the way the function is launched i.e. async, sync, etc.
- **c** – Takes a pre-initialized checkpoint to prepare
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

prepare_checkpoint returns a properly resized checkpoint object that can be used for a subsequent restore_checkpoint operation.

```
template<typename T, typename ...Ts>
```

```
void restore_checkpoint(checkpoint const &c, T &t, Ts&... ts)
```

Restore_checkpoint

Restore_checkpoint takes a checkpoint object as a first argument and the containers which will be filled from the byte stream (in the same order as they were placed in save_checkpoint). Restore_checkpoint can resurrect a stored component in two ways: by passing in an instance of a component's shared_ptr or by passing in an instance of the component's client.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **c** – The checkpoint to restore.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Restore_checkpoint returns void.

```
class checkpoint
```

```
#include <checkpoint.hpp> Checkpoint Object
```

Checkpoint is the container object which is produced by save_checkpoint and is consumed by a restore_checkpoint. A checkpoint may be moved into the save_checkpoint object to write the byte stream to the pre-created checkpoint object.

Checkpoints are able to store all containers which are serializable including components.

Public Types

using **const_iterator** = *std::vector<char>::const_iterator*

Public Functions

checkpoint() = default

~checkpoint() = default

checkpoint(*checkpoint* const &c) = default

checkpoint(*checkpoint* &&c) noexcept = default

inline explicit **checkpoint**(*std::vector<char>* const &vec)

inline explicit **checkpoint**(*std::vector<char>* &&vec) noexcept

checkpoint &**operator**=(*checkpoint* const &c) = default

checkpoint &**operator**=(*checkpoint* &&c) noexcept = default

inline *const_iterator* **begin**() const noexcept

inline *const_iterator* **end**() const noexcept

inline *std::size_t* **size**() const noexcept

inline char ***data**() noexcept

inline char const ***data**() const noexcept

Private Functions

template<typename **Archive**>

inline void **serialize**(*Archive* &arch, unsigned int const)

Private Members

std::vector<char> **data_**

Friends

friend class *hpx::serialization::access*

friend *std::ostream* &**operator**<<(*std::ostream* &ost, *checkpoint* const &ckp)

Operator<< Overload

This overload is the main way to write data from a checkpoint to an object such as a file. Inside the function, the size of the checkpoint will be written to the stream before the checkpoint's data. The operator>> overload uses this to read the correct number of bytes. Be mindful of this additional write and read when you use different facilities to write out or read in data to a checkpoint!

Parameters

- **ost** – Output stream to write to.
- **ckp** – Checkpoint to copy from.

Returns

Operator<< returns the ostream object.

```
friend std::istream &operator>>(std::istream &ist, checkpoint &ckp)
```

Operator>> Overload

This overload is the main way to read in data from an object such as a file to a checkpoint. It is important to note that inside the function, the first variable to be read is the size of the checkpoint. This size variable is written to the stream before the checkpoint's data in the operator<< overload. Be mindful of this additional read and write when you use different facilities to read in or write out data from a checkpoint!

Parameters

- **ist** – Input stream to write from.
- **ckp** – Checkpoint to write to.

Returns

Operator>> returns the ostream object.

```
template<typename T, typename ...Ts>
```

```
friend void restore_checkpoint(checkpoint const &c, T &t, Ts&... ts)
```

Restore_checkpoint

Restore_checkpoint takes a checkpoint object as a first argument and the containers which will be filled from the byte stream (in the same order as they were placed in save_checkpoint). Restore_checkpoint can resurrect a stored component in two ways: by passing in an instance of a component's shared_ptr or by passing in an instance of the component's client.

Template Parameters

- **T** – A container to restore.
- **Ts** – Other containers to restore. Containers must be in the same order that they were inserted into the checkpoint.

Parameters

- **c** – The checkpoint to restore.
- **t** – A container to restore.
- **ts** – Other containers to restore Containers must be in the same order that they were inserted into the checkpoint.

Returns

Restore_checkpoint returns void.

```
inline friend bool operator==( checkpoint const &lhs, checkpoint const &rhs) noexcept
```

```
inline friend bool operator!=( checkpoint const &lhs, checkpoint const &rhs) noexcept
```


collectives

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::lcos::fold

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::lcos::fold_with_index`
- `hpx::lcos::inverse_fold`
- `hpx::lcos::inverse_fold_with_index`

Warning: doxygenfunction: Unable to resolve function “hpx::lcos::fold” with arguments “None”. Candidate function could not be parsed. Parsing error is Error in template parameter list. If parameter: Error when parsing template parameter. If unconstrained type parameter or template type parameter: Invalid C++ declaration: Expected ‘typename’ or ‘class’ in the beginning of template type parameter. [error at 73] `template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,...))> fold (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...)` _____^ If constrained type parameter or non-type parameter: Invalid C++ declaration: Expected identifier in nested name. [error at 73] `template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,...))> fold (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...)` _____^ If no parameter: Invalid C++ declaration: Expected “,” or “>”. [error at 73] `template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,...))> fold (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...)` _____^

hpx::lcos::fold_with_index

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::lcos::fold`
- `hpx::lcos::inverse_fold`
- `hpx::lcos::inverse_fold_with_index`

Warning: doxygenfunction: Unable to resolve function “hpx::lcos::fold_with_index” with arguments “None”. Candidate function could not be parsed. Parsing error is Error in template parameter list. If parameter: Error when parsing template parameter. If unconstrained type parameter or template type parameter: Invalid C++ declaration: Expected ‘typename’ or ‘class’ in the beginning of template type parameter. [error at 73] `template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,..., std::size_t))> fold_with_index (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...)` _____^

If constrained type parameter or non-type parameter: Invalid C++ declaration: Expected identifier in nested name. [error at 73] template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,..., std::size_t))> fold_with_index (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...) _____
 ^ If no parameter: Invalid C++ declaration: Expected “,” or “>”. [error at 73] template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,..., std::size_t))> fold_with_index (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...) _____^

hpx::lcos::inverse_fold

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::lcos::fold`
- `hpx::lcos::fold_with_index`
- `hpx::lcos::inverse_fold_with_index`

Warning: doxygenfunction: Unable to resolve function “hpx::lcos::inverse_fold” with arguments “None”. Candidate function could not be parsed. Parsing error is Error in template parameter list. If parameter: Error when parsing template parameter. If unconstrained type parameter or template type parameter: Invalid C++ declaration: Expected ‘typename’ or ‘class’ in the beginning of template type parameter. [error at 73] template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,...))> inverse_fold (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...) _____^ If constrained type parameter or non-type parameter: Invalid C++ declaration: Expected identifier in nested name. [error at 73] template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,...))> inverse_fold (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...) _____^ If no parameter: Invalid C++ declaration: Expected “,” or “>”. [error at 73] template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,...))> inverse_fold (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...) _____^

hpx::lcos::inverse_fold_with_index

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::lcos::fold`
- `hpx::lcos::fold_with_index`
- `hpx::lcos::inverse_fold`

Warning: doxygenfunction: Unable to resolve function “hpx::lcos::inverse_fold_with_index” with arguments “None”. Candidate function could not be parsed. Parsing error is Error in template parameter list. If parameter: Error when parsing template parameter. If unconstrained type parameter or template type parameter: Invalid C++ declaration: Expected ‘typename’ or ‘class’ in the beginning of template type parameter. [error at 73] template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN..., std::size_t))> inverse_fold_with_index (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...) _____^ If constrained type parameter or non-type parameter: Invalid C++ declaration: Expected identifier in nested name. [error at 73] template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN..., std::size_t))> inverse_fold_with_index (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...) _____^ If no parameter: Invalid C++ declaration: Expected “,” or “>”. [error at 73] template<typename Action, typename FoldOp, typename Init, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN..., std::size_t))> inverse_fold_with_index (std::vector< hpx::id_type > const &ids, FoldOp &&fold_op, Init &&init, ArgN argN,...) _____^

hpx::collectives::all_gather

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename T>
hpx::future<std::vector<std::decay_t<T>>> hpx::collectives::all_gather(char const *basename, T
                                                    &&result, num_sites_arg
                                                    num_sites = num_sites_arg(),
                                                    this_site_arg this_site =
                                                    this_site_arg(), generation_arg
                                                    generation = generation_arg(),
                                                    root_site_arg root_site =
                                                    root_site_arg())
```

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the `all_gather` operation
- **result** – The value to transmit to all participating sites from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_gather` operation performed on the given base name. This is optional and needs to be supplied only if the `all_gather` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `all_gather` support object. This value is optional and defaults to ‘0’ (zero).

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_gather` operation has been completed.

```
template<typename T>
hpx::future<std::vector<std::decay_t<T>>> hpx::collectives::all_gather(communicator comm, T
                                                                    &&result, this_site_arg this_site =
                                                                    this_site_arg(), generation_arg
                                                                    generation = generation_arg())
```

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the `all_gather` operation performed on the given base name. This is optional and needs to be supplied only if the `all_gather` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the `all_gather` operation performed on the given base name. This is optional and needs to be supplied only if the `all_gather` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_gather` operation has been completed.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_gather` operation has been completed.

```
template<typename T>
std::vector<std::decay_t<T>> hpx::collectives::all_gather(hpx::launch::sync_policy, char const
                                                         *basename, T &&result, num_sites_arg
                                                         num_sites = num_sites_arg(), this_site_arg
                                                         this_site = this_site_arg(), generation_arg
                                                         generation = generation_arg(), root_site_arg
                                                         root_site = root_site_arg())
```

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the `all_gather` operation
- **result** – The value to transmit to all participating sites from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_gather` operation performed on the given base name. This is optional and needs to be supplied only if the `all_gather` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `all_gather` support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
std::vector<std::decay_t<T>> hpx::collectives::all_gather(hpx::launch::sync_policy, communicator comm,
                                                         T &&result, this_site_arg this_site =
                                                         this_site_arg(), generation_arg generation =
                                                         generation_arg())
```

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllGather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_gather` operation performed on the given base name. This is optional and needs to be supplied only if the `all_gather` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the `all_gather` operation performed on the given base name. This is optional and needs to be supplied only if the `all_gather` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

hpx::collectives::channel_communicator

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::create_channel_communicator`
- `hpx::collectives::get`
- `hpx::collectives::set`

class **channel_communicator**

A handle identifying the communication channel to use for get/set operations

hpx::collectives::create_channel_communicator

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::channel_communicator`
- `hpx::collectives::get`
- `hpx::collectives::set`

```
hpx::future<channel_communicator> hpx::collectives::create_channel_communicator(char const
                                                                    *basename,
                                                                    num_sites_arg
                                                                    num_sites =
                                                                    num_sites_arg(),
                                                                    this_site_arg
                                                                    this_site =
                                                                    this_site_arg())
```

Create a new communicator object usable with peer-to-peer channel-based operations

This functions creates a new communicator object that can be called in order to pre-allocate a communicator object usable with multiple invocations of channel-based peer-to-peer operations.

Note: The caller must ensure that the communicator object returned by this function is kept alive (i.e., does not go out of scope) until all participating sites have successfully connected. Destroying the communicator before all sites have reached the creation point may cause the remaining sites to hang indefinitely. Consider using a

barrier or similar synchronization mechanism after creating the communicator to ensure all sites are connected before allowing it to be destroyed.

Parameters

- **basename** – The base name identifying the collective operation
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future to a new communicator object usable with the collective operation.

```
channel_communicator hpx::collectives::create_channel_communicator(hpx::launch::sync_policy, char
                                                                    const *basename,
                                                                    num_sites_arg num_sites =
                                                                    num_sites_arg(), this_site_arg
                                                                    this_site = this_site_arg())
```

Create a new communicator object usable with peer-to-peer channel-based operations

This functions creates a new communicator object that can be called in order to pre-allocate a communicator object usable with multiple invocations of channel-based peer-to-peer operations.

Note: The caller must ensure that the communicator object returned by this function is kept alive (i.e., does not go out of scope) until all participating sites have successfully connected. Destroying the communicator before all sites have reached the creation point may cause the remaining sites to hang indefinitely. Consider using a barrier or similar synchronization mechanism after creating the communicator to ensure all sites are connected before allowing it to be destroyed.

Parameters

- **basename** – The base name identifying the collective operation
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a new communicator object usable with the collective operation.

hpx::collectives::get

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::channel_communicator`
- `hpx::collectives::create_channel_communicator`
- `hpx::collectives::set`

template<typename T>

```
hpx::future<T> hpx::collectives::get(channel_communicator comm, that_site_arg site, tag_arg tag = tag_arg())
```

Send a value to the given site

This function receives a value from the given site based on the given communicator.

Parameters

- **comm** – The channel communicator object to use for the data transfer
- **site** – The source site

Returns

This function returns a `future<T>` that becomes ready once the data transfer operation has finished. The future will hold the received value.

hpx::collectives::set

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::channel_communicator`
- `hpx::collectives::create_channel_communicator`
- `hpx::collectives::get`

```
template<typename T>
```

```
hpx::future<void> hpx::collectives::set(channel_communicator comm, that_site_arg site, T &&value, tag_arg tag = tag_arg())
```

Send a value to the given site

This function sends a value to the given site based on the given communicator.

Parameters

- **comm** – The channel communicator object to use for the data transfer
- **site** – The destination site
- **value** – The value to send
- **tag** – The (optional) tag identifying the concrete operation

Returns

This function returns a `future<void>` that becomes ready once the data transfer operation has finished.

hpx::collectives::exclusive_scan

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename T, typename F>
```

```

hpx::future<std::decay_t<T>>> hpx::collectives::exclusive_scan(char const *basename, T &&result, F
                                                                    &&op, num_sites_arg num_sites =
                                                                    num_sites_arg(), this_site_arg this_site =
                                                                    this_site_arg(), generation_arg generation
                                                                    = generation_arg(), root_site_arg root_site
                                                                    = root_site_arg())

```

Exclusive scan a set of values from different call sites

This function performs an exclusive scan operation on a set of values received from all call sites operating on the given base name.

Note: This no-init overload has MPI_Exscan-like semantics, with a deterministic HPX first result: participating site 0 returns a value-initialized result (`std::decay_t<T>{}`, or `false` for `bool`). Use the overload taking an explicit `init` argument for C++ exclusive-scan semantics where site 0 returns `init`.

Parameters

- **basename** – The base name identifying the `exclusive_scan` operation
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `exclusive_scan` operation performed on the given base name. This is optional and needs to be supplied only if the `exclusive_scan` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `exclusive_scan` support object. This value is optional and defaults to '0' (zero).

Returns

For the participating site *i* this function returns the reduction (calculated according to the function *op*) of the values passed in by the participating sites 0, ..., *i*-1. Participating site 0 returns a value-initialized result. The returned future will become ready once the `exclusive_scan` operation has been completed.

```

template<typename T, typename F>
hpx::future<std::decay_t<T>>> hpx::collectives::exclusive_scan(communicator comm, T &&result, F
                                                                    &&op, this_site_arg this_site =
                                                                    this_site_arg(), generation_arg generation
                                                                    = generation_arg())

```

Exclusive scan a set of values from different call sites

This function performs an exclusive scan operation on a set of values received from all call sites operating on the given base name.

Exclusive scan a set of values from different call sites

This function performs an exclusive scan operation on a set of values received from all call sites operating on the given base name.

Note: This no-init overload has MPI_Exscan-like semantics, with a deterministic HPX first result: participating site 0 returns a value-initialized result (`std::decay_t<T>{}`, or `false` for `bool`). Use the overload taking an explicit `init` argument for C++ exclusive-scan semantics where site 0 returns `init`.

Note: This no-init overload has MPI_Exscan-like semantics, with a deterministic HPX first result: participating site 0 returns a value-initialized result (`std::decay_t<T>{}`, or `false` for `bool`). Use the overload taking an explicit `init` argument for C++ exclusive-scan semantics where site 0 returns `init`.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the exclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the exclusive_scan operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the exclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the exclusive_scan operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

For the participating site *i* this function returns the reduction (calculated according to the function *op*) of the values passed in by the participating sites 0, ..., *i*-1. Participating site 0 returns a value-initialized result. The returned future will become ready once the exclusive_scan operation has been completed.

Returns

For the participating site *i* this function returns a future the reduction (calculated according to the function *op*) of the values passed in by the participating sites 0, ..., *i*-1. Participating site 0 returns a value-initialized result. The returned future will become ready once the exclusive_scan operation has been completed.

Warning: doxygenfunction: Unable to resolve function “hpx::collectives::exclusive_scan” with arguments (hpx::launch::sync_policy, char const*, T&&, F&&, num_sites_arg, this_site_arg, generation_arg, root_site_arg) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename T, typename F> decltype(auto) exclusive_scan(hpx::launch::sync_
→policy, char const *basename, T &&result, F &&op, num_sites_arg num_sites = num_
→sites_arg(), this_site_arg this_site = this_site_arg(), generation_arg generation =
→generation_arg(), root_site_arg root_site = root_site_arg())
- template<typename T, typename F> decltype(auto) exclusive_scan(hpx::launch::sync_
→policy, communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
→arg(), generation_arg generation = generation_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> exclusive_scan(char_
→const *basename, T &&result, F &&op, num_sites_arg num_sites = num_sites_arg(),
→this_site_arg this_site = this_site_arg(), generation_arg generation = generation_
→arg(), root_site_arg root_site = root_site_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> exclusive_
→scan(communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
→arg(), generation_arg generation = generation_arg())
```

Warning: doxygenfunction: Unable to resolve function “hpx::collectives::exclusive_scan” with arguments (hpx::launch::sync_policy, communicator, T&&, F&&, this_site_arg, generation_arg) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename T, typename F> decltype(auto) exclusive_scan(hpx::launch::sync_
→policy, char const *basename, T &&result, F &&op, num_sites_arg num_sites = num_
→sites_arg(), this_site_arg this_site = this_site_arg(), generation_arg generation =
→generation_arg(), root_site_arg root_site = root_site_arg())
- template<typename T, typename F> decltype(auto) exclusive_scan(hpx::launch::sync_
→policy, communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
→arg(), generation_arg generation = generation_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> exclusive_scan(char_
→const *basename, T &&result, F &&op, num_sites_arg num_sites = num_sites_arg(),
→this_site_arg this_site = this_site_arg(), generation_arg generation = generation_
→arg(), root_site_arg root_site = root_site_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> exclusive_
→scan(communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
→arg(), generation_arg generation = generation_arg())
```

hpx::lcos::reduce

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::lcos::reduce_with_index`

Warning: doxygenfunction: Unable to resolve function “hpx::lcos::reduce” with arguments “None”. Candidate function could not be parsed. Parsing error is Error in template parameter list. If parame-

ter: Error when parsing template parameter. If unconstrained type parameter or template type parameter: Invalid C++ declaration: Expected ‘typename’ or ‘class’ in the beginning of template type parameter. [error at 60] template<typename Action, typename ReduceOp, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,...))> reduce (std::vector< hpx::id_type > const &ids, ReduceOp &&reduce_op, ArgN argN,...) _____^ If constrained type parameter or non-type parameter: Invalid C++ declaration: Expected identifier in nested name. [error at 60] template<typename Action, typename ReduceOp, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,...))> reduce (std::vector< hpx::id_type > const &ids, ReduceOp &&reduce_op, ArgN argN,...) _____^ If no parameter: Invalid C++ declaration: Expected “,” or “>”. [error at 60] template<typename Action, typename ReduceOp, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,...))> reduce (std::vector< hpx::id_type > const &ids, ReduceOp &&reduce_op, ArgN argN,...) _____^

hpx::lcos::reduce_with_index

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::lcos::reduce`

Warning: doxygenfunction: Unable to resolve function “hpx::lcos::reduce_with_index” with arguments “None”. Candidate function could not be parsed. Parsing error is Error in template parameter list. If parameter: Error when parsing template parameter. If unconstrained type parameter or template type parameter: Invalid C++ declaration: Expected ‘typename’ or ‘class’ in the beginning of template type parameter. [error at 60] template<typename Action, typename ReduceOp, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,..., std::size_t))> reduce_with_index (std::vector< hpx::id_type > const &ids, ReduceOp &&reduce_op, ArgN argN,...) _____^ If constrained type parameter or non-type parameter: Invalid C++ declaration: Expected identifier in nested name. [error at 60] template<typename Action, typename ReduceOp, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,..., std::size_t))> reduce_with_index (std::vector< hpx::id_type > const &ids, ReduceOp &&reduce_op, ArgN argN,...) _____^ If no parameter: Invalid C++ declaration: Expected “,” or “>”. [error at 60] template<typename Action, typename ReduceOp, typename ArgN, ...> hpx::future< decltype(Action(hpx::id_type, ArgN,..., std::size_t))> reduce_with_index (std::vector< hpx::id_type > const &ids, ReduceOp &&reduce_op, ArgN argN,...) _____^

hpx::distributed::latch

Defined in header `hpx/latch.hpp`⁵⁷⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

class **latch** : public `hpx::components::client_base<latch, hpx::lcos::server::latch>`

Latch is an implementation of a synchronization primitive that allows multiple threads to wait for a shared event to occur before proceeding. This latch can be invoked in a distributed application.

For a local only latch

⁵⁷⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/latch.hpp>

See also:

hpx::latch.

hpx::collectives::communicator

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::collectives::create_communicator*
- *hpx::collectives::create_local_communicator*
- *hpx::collectives::create_hierarchical_communicator*
- *hpx::collectives::communicator::set_info*
- *hpx::collectives::communicator::get_info*
- *hpx::collectives::communicator::is_root*

struct **communicator**

A communicator instance represents the list of sites that participate in a particular collective operation.

hpx::collectives::create_communicator

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::collectives::communicator*
- *hpx::collectives::create_local_communicator*
- *hpx::collectives::create_hierarchical_communicator*
- *hpx::collectives::communicator::set_info*
- *hpx::collectives::communicator::get_info*
- *hpx::collectives::communicator::is_root*

```
communicator hpx::collectives::create_communicator(char const *basename, num_sites_arg num_sites =
    num_sites_arg(), this_site_arg this_site =
    this_site_arg(), generation_arg generation =
    generation_arg(), root_site_arg root_site =
    root_site_arg())
```

Create a new communicator object usable with any collective operation

This functions creates a new communicator object that can be called in order to pre-allocate a communicator object usable with multiple invocations of the collective operations (such as *all_gather*, *all_reduce*, *all_to_all*, *broadcast*, etc.).

Parameters

- **basename** – The base name identifying the collective operation

- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the collective operation performed on the given base name. This is optional and needs to be supplied only if the collective operation on the given base name has to be performed more than once.
- **root_site** – The site that is responsible for creating the collective support object. This value is optional and defaults to '0' (zero).

Throws

`hpx::exception` – with `hpx::error::bad_parameter` if *basename* is null or empty, if the (resolved) *num_sites* is zero, if the (resolved) *this_site* is not smaller than *num_sites*, or if the (resolved) *root_site* does not designate a participating site.

Returns

This function returns a new communicator object usable with the collective operation.

communicator `hpx::collectives::create_communicator`(`hpx::launch::sync_policy` policy, char const **basename*, *num_sites_arg* num_sites, *this_site_arg* this_site, *generation_arg* generation, *root_site_arg* root_site)

hpx::collectives::create_local_communicator

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::communicator`
- `hpx::collectives::create_communicator`
- `hpx::collectives::create_hierarchical_communicator`
- `hpx::collectives::communicator::set_info`
- `hpx::collectives::communicator::get_info`
- `hpx::collectives::communicator::is_root`

communicator `hpx::collectives::create_local_communicator`(char const **basename*, *num_sites_arg* num_sites, *this_site_arg* this_site, *generation_arg* generation = *generation_arg*(), *root_site_arg* root_site = *root_site_arg*())

Create a new communicator object usable with any local collective operation

This functions creates a new communicator object that can be called in order to pre-allocate a communicator object usable with multiple invocations of the collective operations (such as *all_gather*, *all_reduce*, *all_to_all*, *broadcast*, etc.).

Parameters

- **basename** – The base name identifying the collective operation
- **num_sites** – The number of participating sites

- **this_site** – The sequence number of this invocation (usually the sequence number of the object participating in the collective operation). This value must be in the range [0, num_sites).
- **generation** – The generational counter identifying the sequence number of the collective operation performed on the given base name. This is optional and needs to be supplied only if the collective operation on the given base name has to be performed more than once.
- **root_site** – The site that is responsible for creating the collective support object. This value is optional and defaults to '0' (zero).

Throws

hpx::exception – with *hpx::error::bad_parameter* if *basename* is null or empty, if *num_sites* is unspecified or zero, if *this_site* is unspecified or not smaller than *num_sites*, or if the (resolved) *root_site* does not designate a participating site.

Returns

This function returns a new communicator object usable for all local collective operations.

communicator **hpx::collectives::create_local_communicator**(*hpx::launch::sync_policy* policy, char const *basename, *num_sites_arg* num_sites, *this_site_arg* this_site, *generation_arg* generation, *root_site_arg* root_site)

hpx::collectives::create_hierarchical_communicator

Defined in header *hpx/collectives.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::collectives::communicator*
- *hpx::collectives::create_communicator*
- *hpx::collectives::create_local_communicator*
- *hpx::collectives::communicator::set_info*
- *hpx::collectives::communicator::get_info*
- *hpx::collectives::communicator::is_root*

```
hierarchical_communicator hpx::collectives::create_hierarchical_communicator(char const
                                                                    *basename,
                                                                    num_sites_arg
                                                                    num_sites =
                                                                    num_sites_arg(),
                                                                    this_site_arg this_site
                                                                    = this_site_arg(),
                                                                    arity_arg arity =
                                                                    arity_arg(),
                                                                    generation_arg
                                                                    generation =
                                                                    generation_arg(),
                                                                    root_site_arg
                                                                    root_site =
                                                                    root_site_arg(),
                                                                    flat_fallback_threshold_arg
                                                                    threshold =
                                                                    flat_fallback_threshold_arg())
```

Create a new hierarchical communicator object usable with collective operations

This functions creates a new `hierarchical_communicator` object that can be called in order to pre-allocate a communicator object usable with multiple invocations of a collective operation (such as *all_gather*, *all_reduce*, *all_to_all*, *broadcast*, etc.).

Note: The sub-communicators of a `hierarchical_communicator` share one generation sequence per registered name. Every hierarchical collective advances each sub-communicator it touches by exactly two internal generations per call (a single-pass collective such as *broadcast*, *gather*, *scatter* or *reduce*, and the inter-group exchange of *all_to_all*, skip the second generation in one step rather than performing a second round-trip). A single hierarchical communicator instance may therefore be shared freely across collective operations, provided every call uses an explicit, strictly consecutive generation number so the shared sequence stays gap-free. Because the two-phase hierarchical collectives (*all_gather*, *all_reduce*, *all_to_all*, *inclusive_scan*, *exclusive_scan* and the hierarchical *barrier*) derive their phase generations from that explicit number, they require it and reject an auto (default) generation. The non-hierarchical (flat) collectives keep supporting the default generation, falling back to the internal per-communicator counter maintained in the *and_gate*. Once any operation on a communicator has used that default, later operations on the same instance may no longer pass an explicit generation number: the counter's position is no longer reliably known to the caller. The reverse transition, from explicit numbering back to the default, remains valid. All participants of a single operation must use the same generation mode.

Note: Hierarchical collective overloads that return *hpx::future* may still perform internal waits while walking the communicator tree. They should not be treated as fully non-blocking: validation failures are reported through the returned exceptional future, but internal phase hand-offs can throw or block before that future is delivered.

Parameters

- **basename** – The base name identifying the collective operation
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **arity** – The arity of the hierarchical tree of communicators to create for the given endpoint. The default arity is 2 and the value must be at least 2.

- **generation** – The generational counter identifying the sequence number of the collective operation performed on the given base name. This is optional and needs to be supplied only if the collective operation on the given base name has to be performed more than once.
- **root_site** – The site that is responsible for creating the collective support object. Hierarchical communicators currently support only site 0 as the root, which is also the default.
- **threshold** – The site-count threshold below which the communicator collapses to a single flat communicator spanning all sites (strict comparison: `num_sites < threshold`). The default is 16; pass 0 to disable the fallback and always build a tree.

Throws

`hpx::exception` – with `hpx::error::bad_parameter` if *basename* is null or empty, if the (resolved) *num_sites* is zero, if the (resolved) *this_site* is not smaller than *num_sites*, if the (resolved) *root_site* is not zero, or if *arity* is smaller than 2.

Returns

This function returns a new communicator object usable with the collective operation.

`hpx::collectives::communicator::set_info`

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::collectives::communicator`
- `hpx::collectives::create_communicator`
- `hpx::collectives::create_local_communicator`
- `hpx::collectives::create_hierarchical_communicator`
- `hpx::collectives::communicator::get_info`
- `hpx::collectives::communicator::is_root`

void `hpx::collectives::communicator::set_info`(*num_sites_arg* num_sites, *this_site_arg* this_site)
noexcept

Store the number of used sites and the index of the current site for this communicator instance.

Parameters

- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this site (usually the locality id).

`hpx::collectives::communicator::get_info`

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::collectives::communicator`
- `hpx::collectives::create_communicator`
- `hpx::collectives::create_local_communicator`

- `hpx::collectives::create_hierarchical_communicator`
- `hpx::collectives::communicator::set_info`
- `hpx::collectives::communicator::is_root`

`std::pair<num_sites_arg, this_site_arg> hpx::collectives::communicator::get_info() const noexcept`
Retrieve the number of used sites and the index of the current site for this communicator instance.

`hpx::collectives::communicator::is_root`

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::communicator`
- `hpx::collectives::create_communicator`
- `hpx::collectives::create_local_communicator`
- `hpx::collectives::create_hierarchical_communicator`
- `hpx::collectives::communicator::set_info`
- `hpx::collectives::communicator::get_info`

`bool hpx::collectives::communicator::is_root() const`

Return whether this communicator instance represents the root site of the communication operation.

`hpx::collectives::gather_here`

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::gather_there`

`template<typename T>`

```
hpx::future<std::vector<decay_t<T>>> hpx::collectives::gather_here(char const *basename, T &&result,
                                                                    num_sites_arg num_sites =
                                                                    num_sites_arg(), this_site_arg
                                                                    this_site = this_site_arg(),
                                                                    generation_arg generation =
                                                                    generation_arg())
```

Gather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the gather operation
- **result** – The value to transmit to the central gather point from this call site.
- **num_sites** – The number of participating sites (default: all localities).

- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

```
template<typename T>
hpx::future<std::vector<decay_t<T>>> hpx::collectives::gather_here(communicator comm, T &&result,
                                                                    this_site_arg this_site =
                                                                    this_site_arg(), generation_arg
                                                                    generation = generation_arg())
```

Gather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Gather a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

Warning: doxygenfunction: Unable to resolve function “hpx::collectives::gather_here” with arguments (hpx::launch::sync_policy, char const*, T&&, num_sites_arg, this_site_arg, generation_arg) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename T> decltype(auto) gather_here(hpx::launch::sync_policy, char_
↳const *basename, T &&result, num_sites_arg num_sites = num_sites_arg(), this_site_
↳arg this_site = this_site_arg(), generation_arg generation = generation_arg())
- template<typename T> decltype(auto) gather_here(hpx::launch::sync_policy,
↳communicator comm, T &&result, this_site_arg this_site = this_site_arg(),
↳generation_arg generation = generation_arg())
- template<typename T> hpx::future<std::vector<decay_t<T>>> gather_here(char const_
↳*basename, T &&result, num_sites_arg num_sites = num_sites_arg(), this_site_arg_
↳this_site = this_site_arg(), generation_arg generation = generation_arg())
- template<typename T> hpx::future<std::vector<decay_t<T>>> gather_here(communicator_
↳comm, T &&result, this_site_arg this_site = this_site_arg(), generation_arg_
↳generation = generation_arg())
```

Warning: doxygenfunction: Unable to resolve function “hpx::collectives::gather_here” with arguments (hpx::launch::sync_policy, communicator, T&&, this_site_arg, generation_arg) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename T> decltype(auto) gather_here(hpx::launch::sync_policy, char_
↳const *basename, T &&result, num_sites_arg num_sites = num_sites_arg(), this_site_
↳arg this_site = this_site_arg(), generation_arg generation = generation_arg())
- template<typename T> decltype(auto) gather_here(hpx::launch::sync_policy,
↳communicator comm, T &&result, this_site_arg this_site = this_site_arg(),
↳generation_arg generation = generation_arg())
- template<typename T> hpx::future<std::vector<decay_t<T>>> gather_here(char const_
↳*basename, T &&result, num_sites_arg num_sites = num_sites_arg(), this_site_arg_
↳this_site = this_site_arg(), generation_arg generation = generation_arg())
- template<typename T> hpx::future<std::vector<decay_t<T>>> gather_here(communicator_
↳comm, T &&result, this_site_arg this_site = this_site_arg(), generation_arg_
↳generation = generation_arg())
```

hpx::collectives::gather_there

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::collectives::gather_here`

template<typename T>

```
hpx::future<void> hpx::collectives::gather_there(char const *basename, T &&result, this_site_arg this_site
= this_site_arg(), generation_arg generation =
generation_arg(), root_site_arg root_site =
root_site_arg())
```

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Parameters

- **basename** – The base name identifying the gather operation
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The sequence number of the central gather point (usually the locality id). This value is optional and defaults to 0.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

template<typename T>

```
hpx::future<void> hpx::collectives::gather_there(communicator comm, T &&result, this_site_arg this_site
= this_site_arg(), generation_arg generation =
generation_arg())
```

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

Returns

This function returns a future holding a vector with all gathered values. It will become ready once the gather operation has been completed.

```
template<typename T>
void hpx::collectives::gather_there(hpx::launch::sync_policy, char const *basename, T &&result,
                                   this_site_arg this_site = this_site_arg(), generation_arg generation =
                                   generation_arg(), root_site_arg root_site = root_site_arg())
```

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Parameters

- **basename** – The base name identifying the gather operation
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

- **root_site** – The sequence number of the central gather point (usually the locality id). This value is optional and defaults to 0.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
void hpx::collectives::gather_there(hpx::launch::sync_policy, communicator comm, T &&result,
                                   this_site_arg this_site = this_site_arg(), generation_arg generation =
                                   generation_arg())
```

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Gather a given value at the given call site

This function transmits the value given by *result* to a central gather site (where the corresponding *gather_here* is executed)

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Note: The generation values from corresponding *gather_here* and *gather_there* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central gather point from this call site.
- **generation** – The generational counter identifying the sequence number of the gather operation performed on the given base name. This is optional and needs to be supplied only if the gather operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

hpx::collectives::all_reduce

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **T**, typename **F**>

```
hpx::future<std::decay_t<T>> hpx::collectives::all_reduce(char const *basename, T &&result, F &&op,
                                                         num_sites_arg num_sites = num_sites_arg(),
                                                         this_site_arg this_site = this_site_arg(),
                                                         generation_arg generation = generation_arg(),
                                                         root_site_arg root_site = root_site_arg())
```

AllReduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the all_reduce operation
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **generation** – The generational counter identifying the sequence number of the all_reduce operation performed on the given base name. This is optional and needs to be supplied only if the all_reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **root_site** – The site that is responsible for creating the all_reduce support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the all_reduce operation has been completed.

template<typename **T**, typename **F**>

```
hpx::future<std::decay_t<T>> hpx::collectives::all_reduce(communicator comm, T &&result, F &&op,
                                                         this_site_arg this_site = this_site_arg(),
                                                         generation_arg generation = generation_arg())
```

AllReduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllReduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **comm** – A communicator object returned from `create_communicator`

- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_reduce` operation performed on the given base name. This is optional and needs to be supplied only if the `all_reduce` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from `create_communicator`
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the `all_reduce` operation performed on the given base name. This is optional and needs to be supplied only if the `all_reduce` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_reduce` operation has been completed.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_reduce` operation has been completed.

Warning: doxygenfunction: Unable to resolve function “`hpx::collectives::all_reduce`” with arguments (`hpx::launch::sync_policy`, `char const*`, `T&&`, `F&&`, `num_sites_arg`, `this_site_arg`, `generation_arg`, `root_site_arg`) in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`. Potential matches:

```
- template<typename T, typename F> decltype(auto) all_reduce(hpx::launch::sync_policy_
↳policy, char const *basename, T &&result, F &&op, num_sites_arg num_sites = num_
↳sites_arg(), this_site_arg this_site = this_site_arg(), generation_arg generation =
↳generation_arg(), root_site_arg root_site = root_site_arg())
- template<typename T, typename F> decltype(auto) all_reduce(hpx::launch::sync_policy_
↳policy, communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
↳arg(), generation_arg generation = generation_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> all_reduce(char const_
↳*basename, T &&result, F &&op, num_sites_arg num_sites = num_sites_arg(), this_site_
↳arg this_site = this_site_arg(), generation_arg generation = generation_arg(), root_
↳site_arg root_site = root_site_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> all_
↳reduce(communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
↳arg(), generation_arg generation = generation_arg())
```

Warning: doxygenfunction: Unable to resolve function “`hpx::collectives::all_reduce`” with arguments (`hpx::launch::sync_policy`, `communicator`, `T&&`, `F&&`, `this_site_arg`, `generation_arg`) in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`. Potential matches:

```

- template<typename T, typename F> decltype(auto) all_reduce(hpx::launch::sync_policy_
↳ policy, char const *basename, T &&result, F &&op, num_sites_arg num_sites = num_
↳ sites_arg(), this_site_arg this_site = this_site_arg(), generation_arg generation = _
↳ generation_arg(), root_site_arg root_site = root_site_arg())
- template<typename T, typename F> decltype(auto) all_reduce(hpx::launch::sync_policy_
↳ policy, communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
↳ arg(), generation_arg generation = generation_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> all_reduce(char const_
↳ *basename, T &&result, F &&op, num_sites_arg num_sites = num_sites_arg(), this_site_
↳ arg this_site = this_site_arg(), generation_arg generation = generation_arg(), root_
↳ site_arg root_site = root_site_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> all_
↳ reduce(communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
↳ arg(), generation_arg generation = generation_arg())

```

hpx::collectives::scatter_from

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::scatter_to`

```

template<typename T>
hpx::future<T> hpx::collectives::scatter_from(char const *basename, this_site_arg this_site =
this_site_arg(), generation_arg generation =
generation_arg(), root_site_arg root_site = root_site_arg())

```

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Parameters

- **basename** – The base name identifying the scatter operation
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The sequence number of the central scatter point (usually the locality id). This value is optional and defaults to 0.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

```

template<typename T>
hpx::future<T> hpx::collectives::scatter_from(communicator comm, this_site_arg this_site =
this_site_arg(), generation_arg generation =
generation_arg())

```

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

```
template<typename T>
T hpx::collectives::scatter_from(hpx::launch::sync_policy, char const *basename, this_site_arg this_site =
    this_site_arg(), generation_arg generation = generation_arg(),
    root_site_arg root_site = root_site_arg())
```

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Parameters

- **basename** – The base name identifying the scatter operation
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The sequence number of the central scatter point (usually the locality id). This value is optional and defaults to 0.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

template<typename T>

```
T hpx::collectives::scatter_from(hpx::launch::sync_policy, communicator comm, this_site_arg this_site =  
                                this_site_arg(), generation_arg generation = generation_arg())
```

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Scatter (receive) a set of values to different call sites

This function receives an element of a set of values operating on the given base name.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

hpx::collectives::scatter_to

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::scatter_from`

```
template<typename T>
hpx::future<T> hpx::collectives::scatter_to(char const *basename, std::vector<T> &&result,
                                           num_sites_arg num_sites = num_sites_arg(), this_site_arg
                                           this_site = this_site_arg(), generation_arg generation =
                                           generation_arg())
```

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Parameters

- **basename** – The base name identifying the scatter operation
- **result** – The value to transmit to the central scatter point from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

```
template<typename T>
hpx::future<T> hpx::collectives::scatter_to(communicator comm, std::vector<T> &&result, this_site_arg
                                           this_site = this_site_arg(), generation_arg generation =
                                           generation_arg())
```

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central scatter point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central scatter point from this call site.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

Returns

This function returns a future holding the scattered value. It will become ready once the scatter operation has been completed.

```
template<typename T>
```

```
T hpx::collectives::scatter_to(hpx::launch::sync_policy, char const *basename, std::vector<T> &&result,  
                               num_sites_arg num_sites = num_sites_arg(), this_site_arg this_site =  
                               this_site_arg(), generation_arg generation = generation_arg())
```

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Parameters

- **basename** – The base name identifying the scatter operation
- **result** – The value to transmit to the central scatter point from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

```
template<typename T>
```

```
T hpx::collectives::scatter_to(hpx::launch::sync_policy, communicator comm, std::vector<T> &&result,
                               this_site_arg this_site = this_site_arg(), generation_arg generation =
                               generation_arg())
```

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Scatter (send) a part of the value set at the given call site

This function transmits the value given by *result* to a central scatter site (where the corresponding *scatter_from* is executed)

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Note: The generation values from corresponding *scatter_to* and *scatter_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central scatter point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to the central scatter point from this call site.
- **generation** – The generational counter identifying the sequence number of the scatter operation performed on the given base name. This is optional and needs to be supplied only if the scatter operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

Returns

This function returns the scattered value. It executes synchronously and directly returns the result.

hpx::lcos::spmd_block

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::lcos::define_spmd_block`

struct `spmd_block`

The class `spmd_block` defines an interface for launching multiple images while giving handles to each image to interact with the remaining images. The `define_spmd_block` function templates create multiple images of a user-defined action and launches them in a possibly separate thread. A temporary `spmd_block` object is created and diffused to each image. The constraint for the action given to the `define_spmd_block` function is to accept a `spmd_block` as first parameter.

hpx::lcos::define_spmd_block

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::lcos::spmd_block`

template<typename **F**, typename ...**Args**>

`hpx::future<void> hpx::lcos::define_spmd_block(std::string &&name, std::size_t images_per_locality, F &&, Args&&... args)`

hpx::collectives::all_to_all

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **T**>

`hpx::future<std::vector<T>> hpx::collectives::all_to_all(char const *basename, std::vector<T> &&local_result, num_sites_arg num_sites = num_sites_arg(), this_site_arg this_site = this_site_arg(), generation_arg generation = generation_arg(), root_site_arg root_site = root_site_arg(), pairwise_threshold_arg threshold = pairwise_threshold_arg())`

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the `all_to_all` operation
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **num_sites** – The number of participating sites (default: all localities).

- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the all_to_all operation performed on the given base name. This is optional and needs to be supplied only if the all_to_all operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the all_to_all support object. This value is optional and defaults to '0' (zero).
- **threshold** – The fixed row-size threshold, in bytes, at or above which rows are exchanged directly between sites instead of being routed through one communicator site. Automatic selection uses `sizeof(T)` only for a trivially copyable T; other row types stay routed unless every site passes zero. See *pairwise_threshold_arg* for the default and the remaining direct-exchange requirements. Successive generations using one basename may select different paths. Which path runs affects performance only, never the result.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the all_to_all operation has been completed.

```
template<typename T>
hpx::future<std::vector<T>> hpx::collectives::all_to_all(communicator fid, std::vector<T>
&&local_result, this_site_arg this_site =
this_site_arg(), generation_arg generation =
generation_arg())
```

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **fid** – A communicator object returned from *create_communicator*
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the all_to_all operation performed on the given base name. This is optional and needs to be supplied only if the all_to_all operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **fid** – A communicator object returned from *create_communicator*
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the all_to_all operation performed on the given base name. This is optional and needs to be supplied only if the all_to_all operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_to_all` operation has been completed.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `all_to_all` operation has been completed.

```
template<typename T>
std::vector<T> hpx::collectives::all_to_all(hpx::launch::sync_policy policy, char const *basename,
                                           std::vector<T> &&local_result, num_sites_arg num_sites =
                                           num_sites_arg(), this_site_arg this_site = this_site_arg(),
                                           generation_arg generation = generation_arg(), root_site_arg
                                           root_site = root_site_arg(), pairwise_threshold_arg threshold =
                                           pairwise_threshold_arg())
```

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the `all_to_all` operation
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `all_to_all` operation performed on the given base name. This is optional and needs to be supplied only if the `all_to_all` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `all_to_all` support object. This value is optional and defaults to ‘0’ (zero).
- **threshold** – The fixed row-size threshold, in bytes, at or above which rows are exchanged directly between sites instead of being routed through one communicator site. Automatic selection uses `sizeof(T)` only for a trivially copyable `T`; other row types stay routed unless every site passes zero. See `pairwise_threshold_arg` for the default and the remaining direct-exchange requirements. Successive generations using one `basename` may select different paths. Which path runs affects performance only, never the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

```
template<typename T>
std::vector<T> hpx::collectives::all_to_all(hpx::launch::sync_policy policy, communicator fid,
                                           std::vector<T> &&local_result, this_site_arg this_site =
                                           this_site_arg(), generation_arg generation = generation_arg())
```

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

AllToAll a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **fid** – A communicator object returned from *create_communicator*
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the all_to_all operation performed on the given base name. This is optional and needs to be supplied only if the all_to_all operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **fid** – A communicator object returned from *create_communicator*
- **local_result** – A vector of values to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the all_to_all operation performed on the given base name. This is optional and needs to be supplied only if the all_to_all operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

hpx::distributed::barrier

Defined in header [hpx/barrier.hpp](#)⁵⁷⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

explicit **hpx::distributed::barrier**(std::string const &base_name)

Creates a barrier, rank is locality id, size is number of localities

A barrier *base_name* is created. It expects that *hpx::get_num_localities()* participate and the local rank is *hpx::get_locality_id()*.

Parameters

base_name – The name of the barrier

hpx::distributed::barrier(std::string const &base_name, std::size_t num)

Creates a barrier with a given size, rank is locality id

A barrier *base_name* is created. It expects that *num* participate and the local rank is *hpx::get_locality_id()*.

Parameters

⁵⁷⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/barrier.hpp>

- **base_name** – The name of the barrier
- **num** – The number of participating threads

`hpx::distributed::barrier(std::string const &base_name, std::size_t num, std::size_t rank)`

Creates a barrier with a given size and rank

A barrier *base_name* is created. It expects that *num* participate and the local rank is *rank*.

Parameters

- **base_name** – The name of the barrier
- **num** – The number of participating threads
- **rank** – The rank of the calling site for this invocation

`hpx::distributed::barrier(std::string const &base_name, std::vector<std::size_t> const &ranks, std::size_t rank)`

Creates a barrier with a vector of ranks

A barrier *base_name* is created. It expects that `ranks.size()` and the local rank is *rank* (must be contained in *ranks*).

Parameters

- **base_name** – The name of the barrier
- **ranks** – Gives a list of participating ranks (this could be derived from a list of locality ids)
- **rank** – The rank of the calling site for this invocation

hpx::collectives::num_sites_arg

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::this_site_arg`
- `hpx::collectives::that_site_arg`
- `hpx::collectives::generation_arg`
- `hpx::collectives::root_site_arg`
- `hpx::collectives::tag_arg`
- `hpx::collectives::arity_arg`
- `hpx::collectives::flat_fallback_threshold_arg`

using `hpx::collectives::num_sites_arg = detail::argument_type<detail::num_sites_tag>`

The number of participating sites (default: all localities)

hpx::collectives::this_site_arg

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::num_sites_arg`
- `hpx::collectives::that_site_arg`
- `hpx::collectives::generation_arg`
- `hpx::collectives::root_site_arg`
- `hpx::collectives::tag_arg`
- `hpx::collectives::arity_arg`
- `hpx::collectives::flat_fallback_threshold_arg`

using `hpx::collectives::this_site_arg` = `detail::argument_type<detail::this_site_tag>`

The local end of the communication channel.

hpx::collectives::that_site_arg

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::num_sites_arg`
- `hpx::collectives::this_site_arg`
- `hpx::collectives::generation_arg`
- `hpx::collectives::root_site_arg`
- `hpx::collectives::tag_arg`
- `hpx::collectives::arity_arg`
- `hpx::collectives::flat_fallback_threshold_arg`

using `hpx::collectives::that_site_arg` = `detail::argument_type<detail::that_site_tag>`

The opposite end of the communication channel.

hpx::collectives::generation_arg

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::num_sites_arg`
- `hpx::collectives::this_site_arg`

- `hpx::collectives::that_site_arg`
- `hpx::collectives::root_site_arg`
- `hpx::collectives::tag_arg`
- `hpx::collectives::arity_arg`
- `hpx::collectives::flat_fallback_threshold_arg`

using `hpx::collectives::generation_arg` = detail::argument_type<detail::generation_tag>

The generational counter identifying the sequence number of the operation performed on the given base name. It needs to be supplied only if the operation on the given base name has to be performed more than once. It must be a positive number greater than zero. On any given communicator instance, operations that pass an explicit generation may not follow operations that used the default: the internal counter's position is no longer reliably known to the caller. The reverse transition, from explicit numbering back to the default, remains valid.

`hpx::collectives::root_site_arg`

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::num_sites_arg`
- `hpx::collectives::this_site_arg`
- `hpx::collectives::that_site_arg`
- `hpx::collectives::generation_arg`
- `hpx::collectives::tag_arg`
- `hpx::collectives::arity_arg`
- `hpx::collectives::flat_fallback_threshold_arg`

using `hpx::collectives::root_site_arg` = detail::argument_type<detail::root_site_tag, 0>

The site that is responsible for creating the support object of the operation. It defaults to '0' (zero).

`hpx::collectives::tag_arg`

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::num_sites_arg`
- `hpx::collectives::this_site_arg`
- `hpx::collectives::that_site_arg`
- `hpx::collectives::generation_arg`
- `hpx::collectives::root_site_arg`
- `hpx::collectives::arity_arg`

- `hpx::collectives::flat_fallback_threshold_arg`

using `hpx::collectives::tag_arg` = detail::argument_type<detail::tag_tag, 0>

The tag identifying the concrete operation.

`hpx::collectives::arity_arg`

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::num_sites_arg`
- `hpx::collectives::this_site_arg`
- `hpx::collectives::that_site_arg`
- `hpx::collectives::generation_arg`
- `hpx::collectives::root_site_arg`
- `hpx::collectives::tag_arg`
- `hpx::collectives::flat_fallback_threshold_arg`

using `hpx::collectives::arity_arg` = detail::argument_type<detail::arity_tag, 2>

The number of children each of the communication nodes is connected to (default: 2).

`hpx::collectives::flat_fallback_threshold_arg`

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::num_sites_arg`
- `hpx::collectives::this_site_arg`
- `hpx::collectives::that_site_arg`
- `hpx::collectives::generation_arg`
- `hpx::collectives::root_site_arg`
- `hpx::collectives::tag_arg`
- `hpx::collectives::arity_arg`

using `hpx::collectives::flat_fallback_threshold_arg` =
detail::argument_type<detail::flat_fallback_threshold_tag, 16>

The site-count threshold below which a hierarchical_communicator collapses to a single flat communicator spanning all sites. At small site counts, flat collectives outperform hierarchical composition because tree-walking overhead exceeds the synchronization-depth benefit. Pass 0 to disable the fallback and always build a tree.

hpx::lcos::broadcast

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::lcos::broadcast_post`
- `hpx::lcos::broadcast_with_index`
- `hpx::lcos::broadcast_post_with_index`

Warning: doxygenfunction: Unable to resolve function “hpx::lcos::broadcast” with arguments “None”. Candidate function could not be parsed. Parsing error is Error in template parameter list. If parameter: Error when parsing template parameter. If unconstrained type parameter or template type parameter: Invalid C++ declaration: Expected ‘typename’ or ‘class’ in the beginning of template type parameter. [error at 41] template<typename Action, typename ArgN, ...> hpx::future< std::vector< decltype(Action(hpx::id_type, ArgN,...))> > broadcast (std::vector< hpx::id_type > const &ids, ArgN argN,...) _____^ If constrained type parameter or non-type parameter: Invalid C++ declaration: Expected identifier in nested name. [error at 41] template<typename Action, typename ArgN, ...> hpx::future< std::vector< decltype(Action(hpx::id_type, ArgN,...))> > broadcast (std::vector< hpx::id_type > const &ids, ArgN argN,...) _____^ If no parameter: Invalid C++ declaration: Expected “,” or “>”. [error at 41] template<typename Action, typename ArgN, ...> hpx::future< std::vector< decltype(Action(hpx::id_type, ArgN,...))> > broadcast (std::vector< hpx::id_type > const &ids, ArgN argN,...) _____^

hpx::lcos::broadcast_post

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::lcos::broadcast`
- `hpx::lcos::broadcast_with_index`
- `hpx::lcos::broadcast_post_with_index`

Warning: doxygenfunction: Unable to resolve function “hpx::lcos::broadcast_post” with arguments “None”. Candidate function could not be parsed. Parsing error is Error in template parameter list. If parameter: Error when parsing template parameter. If unconstrained type parameter or template type parameter: Invalid C++ declaration: Expected ‘typename’ or ‘class’ in the beginning of template type parameter. [error at 41] template<typename Action, typename ArgN, ...> void broadcast_post (std::vector< hpx::id_type > const &ids, ArgN argN,...) _____^ If constrained type parameter or non-type parameter: Invalid C++ declaration: Expected identifier in nested name. [error at 41] template<typename Action, typename ArgN, ...> void broadcast_post (std::vector< hpx::id_type > const &ids, ArgN argN,...) _____^ If no parameter: Invalid C++ declaration: Expected “,” or “>”. [error at 41] template<typename Action, typename ArgN, ...> void broadcast_post (std::vector< hpx::id_type > const &ids, ArgN argN,...) _____^

hpx::lcos::broadcast_with_index

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::lcos::broadcast`
- `hpx::lcos::broadcast_post`
- `hpx::lcos::broadcast_post_with_index`

Warning: doxygenfunction: Unable to resolve function “`hpx::lcos::broadcast_with_index`” with arguments “None”. Candidate function could not be parsed. Parsing error is Error in template parameter list. If parameter: Error when parsing template parameter. If unconstrained type parameter or template type parameter: Invalid C++ declaration: Expected ‘typename’ or ‘class’ in the beginning of template type parameter. [error at 41] `template<typename Action, typename ArgN, ...> hpx::future< std::vector< decltype(Action(hpx::id_type, ArgN,..., std::size_t))> > broadcast_with_index (std::vector< hpx::id_type > const &ids, ArgN argN,...)` _____^ If constrained type parameter or non-type parameter: Invalid C++ declaration: Expected identifier in nested name. [error at 41] `template<typename Action, typename ArgN, ...> hpx::future< std::vector< decltype(Action(hpx::id_type, ArgN,..., std::size_t))> > broadcast_with_index (std::vector< hpx::id_type > const &ids, ArgN argN,...)` _____^ If no parameter: Invalid C++ declaration: Expected “,” or “>”. [error at 41] `template<typename Action, typename ArgN, ...> hpx::future< std::vector< decltype(Action(hpx::id_type, ArgN,..., std::size_t))> > broadcast_with_index (std::vector< hpx::id_type > const &ids, ArgN argN,...)` _____^

hpx::lcos::broadcast_post_with_index

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::lcos::broadcast`
- `hpx::lcos::broadcast_post`
- `hpx::lcos::broadcast_with_index`

Warning: doxygenfunction: Unable to resolve function “`hpx::lcos::broadcast_post_with_index`” with arguments “None”. Candidate function could not be parsed. Parsing error is Error in template parameter list. If parameter: Error when parsing template parameter. If unconstrained type parameter or template type parameter: Invalid C++ declaration: Expected ‘typename’ or ‘class’ in the beginning of template type parameter. [error at 41] `template<typename Action, typename ArgN, ...> void broadcast_post_with_index (std::vector< hpx::id_type > const &ids, ArgN argN,...)` _____^ If constrained type parameter or non-type parameter: Invalid C++ declaration: Expected identifier in nested name. [error at 41] `template<typename Action, typename ArgN, ...> void broadcast_post_with_index (std::vector< hpx::id_type > const &ids, ArgN argN,...)` _____^ If no parameter: Invalid C++ declaration: Expected “,” or “>”. [error at 41] `template<typename Action, typename ArgN, ...> void broadcast_post_with_index (std::vector< hpx::id_type > const &ids, ArgN argN,...)` _____^

hpx::collectives::broadcast_to

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::broadcast_from`

template<typename T>

```
hpx::future<T> hpx::collectives::broadcast_to(char const *basename, T &&local_result, num_sites_arg
num_sites = num_sites_arg(), this_site_arg this_site =
this_site_arg(), generation_arg generation =
generation_arg())
```

Broadcast a value to different call sites

This function sends a set of values to all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the broadcast operation
- **local_result** – A value to transmit to all participating sites from this call site.
- **num_sites** – The number of participating sites (default: all localities).
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

template<typename T>

```
hpx::future<T> hpx::collectives::broadcast_to(communicator comm, T &&local_result, this_site_arg
this_site = this_site_arg(), generation_arg generation =
generation_arg())
```

Broadcast a value to different call sites

This function sends a set of values to all call sites operating on the given base name.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **local_result** – A value to transmit to all participating sites from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only

if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

```
template<typename T>
hpx::future<T> hpx::collectives::broadcast_to(communicator comm, generation_arg generation, T
&&local_result, this_site_arg this_site = this_site_arg())
```

Broadcast a value to different call sites

This function sends a set of values to all call sites operating on the given base name.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **local_result** – A value to transmit to all participating sites from this call site.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

Warning: doxygenfunction: Unable to resolve function “hpx::collectives::broadcast_to” with arguments (hpx::launch::sync_policy, char const*, T&&, num_sites_arg, this_site_arg, generation_arg) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename T> decltype(auto) broadcast_to(hpx::launch::sync_policy policy,
↳ char const *basename, T &&local_result, num_sites_arg num_sites = num_sites_arg(),
↳ this_site_arg this_site = this_site_arg(), generation_arg generation = generation_
↳ arg())
- template<typename T> decltype(auto) broadcast_to(hpx::launch::sync_policy policy,
↳ communicator comm, T &&local_result, this_site_arg this_site = this_site_arg(),
↳ generation_arg generation = generation_arg())
- template<typename T> hpx::future<T> broadcast_to(char const *basename, T &&local_
↳ result, num_sites_arg num_sites = num_sites_arg(), this_site_arg this_site = this_
↳ site_arg(), generation_arg generation = generation_arg())
- template<typename T> hpx::future<T> broadcast_to(communicator comm, T &&local_
↳ result, this_site_arg this_site = this_site_arg(), generation_arg generation =
↳ generation_arg())
- template<typename T> hpx::future<T> broadcast_to(communicator comm, generation_arg_
↳ generation, T &&local_result, this_site_arg this_site = this_site_arg())
```

Warning: doxygenfunction: Unable to resolve function “hpx::collectives::broadcast_to” with arguments (hpx::launch::sync_policy, communicator, T&&, this_site_arg, generation_arg) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename T> decltype(auto) broadcast_to(hpx::launch::sync_policy policy,
↳ char const *basename, T &&local_result, num_sites_arg num_sites = num_sites_arg(),
↳ this_site_arg this_site = this_site_arg(), generation_arg generation = generation_
↳ arg())
- template<typename T> decltype(auto) broadcast_to(hpx::launch::sync_policy policy,
↳ communicator comm, T &&local_result, this_site_arg this_site = this_site_arg(),
↳ generation_arg generation = generation_arg())
- template<typename T> hpx::future<T> broadcast_to(char const *basename, T &&local_
↳ result, num_sites_arg num_sites = num_sites_arg(), this_site_arg this_site = this_
↳ site_arg(), generation_arg generation = generation_arg())
- template<typename T> hpx::future<T> broadcast_to(communicator comm, T &&local_
↳ result, this_site_arg this_site = this_site_arg(), generation_arg generation =
↳ generation_arg())
- template<typename T> hpx::future<T> broadcast_to(communicator comm, generation_arg
↳ generation, T &&local_result, this_site_arg this_site = this_site_arg())
```

hpx::collectives::broadcast_from

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::broadcast_to`

```
template<typename T>
hpx::future<T> hpx::collectives::broadcast_from(char const *basename, this_site_arg this_site =
this_site_arg(), generation_arg generation =
generation_arg(), root_site_arg root_site =
root_site_arg())
```

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the broadcast operation
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **root_site** – The site responsible for broadcasting the value. This is optional and defaults to site 0 (zero).

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

```
template<typename T>
hpx::future<T> hpx::collectives::broadcast_from(communicator comm, this_site_arg this_site =
                                                this_site_arg(), generation_arg generation =
                                                generation_arg())
```

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

Returns

This function returns a future holding the value that was sent to all participating sites. It will become ready once the broadcast operation has been completed.

```
template<typename T>
T hpx::collectives::broadcast_from(hpx::launch::sync_policy policy, char const *basename, this_site_arg
                                   this_site = this_site_arg(), generation_arg generation =
                                   generation_arg(), root_site_arg root_site = root_site_arg())
```

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **basename** – The base name identifying the broadcast operation
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site responsible for broadcasting the value. This is optional and defaults to site 0 (zero).

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

template<typename T>

```
T hpx::collectives::broadcast_from(hpx::launch::sync_policy policy, communicator comm, this_site_arg  
    this_site = this_site_arg(), generation_arg generation =  
    generation_arg())
```

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Receive a value that was broadcast to different call sites

This function sends a set of values to all call sites operating on the given base name.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Note: The generation values from corresponding *broadcast_to* and *broadcast_from* have to match.

Parameters

- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **policy** – The execution policy specifying synchronous execution.
- **comm** – A communicator object returned from *create_communicator*
- **generation** – The generational counter identifying the sequence number of the broadcast operation performed on the given base name. This is optional and needs to be supplied only if the broadcast operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

Returns

This function returns a vector with all values send by all participating sites. This function executes synchronously and directly returns the result.

hpx/collectives/macros.hpp

Defined in header `hpx/collectives/macros.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

`HPX_REGISTER_BROADCAST_POST_ACTION_DECLARATION(...)`

`HPX_REGISTER_BROADCAST_POST_ACTION_DECLARATION_(...)`

`HPX_REGISTER_BROADCAST_POST_ACTION_DECLARATION_1(Action)`

`HPX_REGISTER_BROADCAST_POST_ACTION_DECLARATION_2(Action, Name)`

`HPX_REGISTER_BROADCAST_POST_ACTION(...)`

`HPX_REGISTER_BROADCAST_POST_ACTION_(...)`

`HPX_REGISTER_BROADCAST_POST_ACTION_1(Action)`

`HPX_REGISTER_BROADCAST_POST_ACTION_2(Action, Name)`

`HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_DECLARATION(...)`

`HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_DECLARATION_(...)`

`HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_DECLARATION_1(Action)`

`HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_DECLARATION_2(Action, Name)`

`HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION(...)`

`HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_(...)`

`HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_1(Action)`

`HPX_REGISTER_BROADCAST_POST_WITH_INDEX_ACTION_2(Action, Name)`

`HPX_REGISTER_BROADCAST_ACTION_DECLARATION(...)`

`HPX_REGISTER_BROADCAST_ACTION_DECLARATION_(...)`

`HPX_REGISTER_BROADCAST_ACTION_DECLARATION_1(Action)`

`HPX_REGISTER_BROADCAST_ACTION_DECLARATION_2(Action, Name)`

HPX_REGISTER_BROADCAST_ACTION(...)
HPX_REGISTER_BROADCAST_ACTION_(...)
HPX_REGISTER_BROADCAST_ACTION_1(Action)
HPX_REGISTER_BROADCAST_ACTION_2(Action, Name)
HPX_REGISTER_BROADCAST_ACTION_ID(Action, Name, Id)
HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_DECLARATION(...)
HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_DECLARATION_(...)
HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_DECLARATION_1(Action)
HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_DECLARATION_2(Action, Name)
HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION(...)
HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_(...)
HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_1(Action)
HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_2(Action, Name)
HPX_REGISTER_BROADCAST_WITH_INDEX_ACTION_ID(Action, Name, Id)
HPX_REGISTER_FOLD_ACTION_DECLARATION(...)
HPX_REGISTER_FOLD_ACTION_DECLARATION_(...)
HPX_REGISTER_FOLD_ACTION_DECLARATION_2(Action, FoldOp)
HPX_REGISTER_FOLD_ACTION_DECLARATION_3(Action, FoldOp, Name)
HPX_REGISTER_FOLD_ACTION(...)
HPX_REGISTER_FOLD_ACTION_(...)
HPX_REGISTER_FOLD_ACTION_2(Action, FoldOp)
HPX_REGISTER_FOLD_ACTION_3(Action, FoldOp, Name)
HPX_REGISTER_FOLD_WITH_INDEX_ACTION_DECLARATION(...)
HPX_REGISTER_FOLD_WITH_INDEX_ACTION_DECLARATION_(...)
HPX_REGISTER_FOLD_WITH_INDEX_ACTION_DECLARATION_2(Action, FoldOp)
HPX_REGISTER_FOLD_WITH_INDEX_ACTION_DECLARATION_3(Action, FoldOp, Name)
HPX_REGISTER_FOLD_WITH_INDEX_ACTION(...)
HPX_REGISTER_FOLD_WITH_INDEX_ACTION_(...)
HPX_REGISTER_FOLD_WITH_INDEX_ACTION_2(Action, FoldOp)
HPX_REGISTER_FOLD_WITH_INDEX_ACTION_3(Action, FoldOp, Name)
HPX_REGISTER_REDUCE_ACTION_DECLARATION(...)


```

HPX_REGISTER_REDUCE_ACTION_DECLARATION_(...)
HPX_REGISTER_REDUCE_ACTION_DECLARATION_2(Action, ReduceOp)
HPX_REGISTER_REDUCE_ACTION_DECLARATION_3(Action, ReduceOp, Name)
HPX_REGISTER_REDUCE_ACTION(...)
HPX_REGISTER_REDUCE_ACTION_(...)
HPX_REGISTER_REDUCE_ACTION_2(Action, ReduceOp)
HPX_REGISTER_REDUCE_ACTION_3(Action, ReduceOp, Name)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_DECLARATION(...)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_DECLARATION_(...)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_DECLARATION_2(Action, ReduceOp)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_DECLARATION_3(Action, ReduceOp, Name)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION(...)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_(...)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_2(Action, ReduceOp)
HPX_REGISTER_REDUCE_WITH_INDEX_ACTION_3(Action, ReduceOp, Name)

```

hpx::collectives::reduce_here

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::reduce_there`

```

template<typename T, typename F>
hpx::future<std::decay_t<T>> hpx::collectives::reduce_here(char const *basename, T &&result, F &&op,
                                                         num_sites_arg num_sites = num_sites_arg(),
                                                         this_site_arg this_site = this_site_arg(),
                                                         generation_arg generation =
                                                         generation_arg())

```

Reduce a set of values from different call sites

This function receives a set of values from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the reduce operation
- **result** – A value to reduce on the central reduction point from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.

- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the reduce operation has been completed.

```
template<typename T, typename F>
hpx::future<decay_t<T>> hpx::collectives::reduce_here(comm, T &&result, F &&op,
                                                    this_site_arg this_site = this_site_arg(),
                                                    generation_arg generation = generation_arg())
```

Reduce a set of values from different call sites

This function receives a set of values that are the result of applying a given operator on values supplied from all call sites operating on the given base name.

Reduce a set of values from different call sites

This function receives a set of values that are the result of applying a given operator on values supplied from all call sites operating on the given base name.

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the root_site from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the root_site from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a future holding a value calculated based on the values send by all participating sites. It will become ready once the reduce operation has been completed.

Returns

This function returns a future holding a value calculated based on the values send by all participating sites. It will become ready once the reduce operation has been completed.

Warning: doxygenfunction: Unable to resolve function “hpx::collectives::reduce_here” with arguments (hpx::launch::sync_policy, char const*, T&&, F&&, num_sites_arg, this_site_arg, generation_arg) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename T, typename F> decltype(auto) reduce_here(hpx::launch::sync_
    ↪policy, char const *basename, T &&result, F &&op, num_sites_arg num_sites = num_
    ↪sites_arg(), this_site_arg this_site = this_site_arg(), generation_arg generation =
    ↪generation_arg())
- template<typename T, typename F> decltype(auto) reduce_here(hpx::launch::sync_
    ↪policy, communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
    ↪arg(), generation_arg generation = generation_arg())
- template<typename T, typename F> hpx::future<decay_t<T>> reduce_here(communicator_
    ↪comm, T &&result, F &&op, this_site_arg this_site = this_site_arg(), generation_arg_
    ↪generation = generation_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> reduce_here(char_
    ↪const *basename, T &&result, F &&op, num_sites_arg num_sites = num_sites_arg(),
    ↪this_site_arg this_site = this_site_arg(), generation_arg generation = generation_
    ↪arg())
```

Warning: doxygenfunction: Unable to resolve function “hpx::collectives::reduce_here” with arguments (hpx::launch::sync_policy, communicator, T&&, F&&, this_site_arg, generation_arg) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename T, typename F> decltype(auto) reduce_here(hpx::launch::sync_
    ↪policy, char const *basename, T &&result, F &&op, num_sites_arg num_sites = num_
    ↪sites_arg(), this_site_arg this_site = this_site_arg(), generation_arg generation =
    ↪generation_arg())
- template<typename T, typename F> decltype(auto) reduce_here(hpx::launch::sync_
    ↪policy, communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
    ↪arg(), generation_arg generation = generation_arg())
- template<typename T, typename F> hpx::future<decay_t<T>> reduce_here(communicator_
    ↪comm, T &&result, F &&op, this_site_arg this_site = this_site_arg(), generation_arg_
    ↪generation = generation_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> reduce_here(char_
    ↪const *basename, T &&result, F &&op, num_sites_arg num_sites = num_sites_arg(),
    ↪this_site_arg this_site = this_site_arg(), generation_arg generation = generation_
    ↪arg())
```

hpx::collectives::reduce_there

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::collectives::reduce_here`

template<typename **T**, typename **F**>

```
hpx::future<void> hpx::collectives::reduce_there(char const *basename, T &&result, this_site_arg this_site
                                                    = this_site_arg(), generation_arg generation =
                                                    generation_arg(), root_site_arg root_site =
                                                    root_site_arg())
```

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Parameters

- **basename** – The base name identifying the reduction operation
- **result** – A future referring to the value to transmit to the central reduction point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The sequence number of the central reduction point (usually the locality id). This value is optional and defaults to 0.

Returns

This function returns a *future<void>*. It will become ready once the reduction operation has been completed.

template<typename **T**>

```
hpx::future<void> hpx::collectives::reduce_there(communicator comm, T &&result, this_site_arg this_site
                                                    = this_site_arg(), generation_arg generation =
                                                    generation_arg())
```

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the central reduction point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the central reduction point from this call site.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a future holding a value calculated based on the values send by all participating sites. It will become ready once the reduce operation has been completed.

Returns

This function returns a future holding a value calculated based on the values send by all participating sites. It will become ready once the reduce operation has been completed.

```
template<typename T>
void hpx::collectives::reduce_there(hpx::launch::sync_policy, char const *basename, T &&result,
                                   this_site_arg this_site = this_site_arg(), generation_arg generation =
                                   generation_arg(), root_site_arg root_site = root_site_arg())
```

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Parameters

- **basename** – The base name identifying the reduction operation
- **result** – A future referring to the value to transmit to the central reduction point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.

- **root_site** – The sequence number of the central reduction point (usually the locality id). This value is optional and defaults to 0.

```
template<typename T>
void hpx::collectives::reduce_there(hpx::launch::sync_policy, communicator comm, T &&result,
                                   this_site_arg this_site = this_site_arg(), generation_arg generation =
                                   generation_arg())
```

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Reduce a given value at the given call site

This function transmits the value given by *result* to a central reduce site (where the corresponding *reduce_here* is executed)

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Note: The generation values from corresponding *reduce_here* and *reduce_there* have to match.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the central reduction point from this call site.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – A value to reduce on the central reduction point from this call site.
- **generation** – The generational counter identifying the sequence number of the reduce operation performed on the given base name. This is optional and needs to be supplied only if the reduce operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

hpx::collectives::inclusive_scan

Defined in header `hpx/collectives.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **T**, typename **F**>

```
hpx::future<std::decay_t<T>> hpx::collectives::inclusive_scan(char const *basename, T &&result, F
                                                                    &&op, num_sites_arg num_sites =
                                                                    num_sites_arg(), this_site_arg this_site =
                                                                    this_site_arg(), generation_arg generation
                                                                    = generation_arg(), root_site_arg root_site
                                                                    = root_site_arg())
```

Inclusive `inclusive_scan` a set of values from different call sites

This function performs an inclusive scan operation on a set of values received from all call sites operating on the given base name.

Parameters

- **basename** – The base name identifying the `inclusive_scan` operation
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **num_sites** – The number of participating sites (default: all localities).
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever `hpx::get_locality_id()` returns.
- **generation** – The generational counter identifying the sequence number of the `inclusive_scan` operation performed on the given base name. This is optional and needs to be supplied only if the `inclusive_scan` operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **root_site** – The site that is responsible for creating the `inclusive_scan` support object. This value is optional and defaults to '0' (zero).

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the `inclusive_scan` operation has been completed.

template<typename **T**, typename **F**>

```
hpx::future<std::decay_t<T>> hpx::collectives::inclusive_scan(communicator comm, T &&result, F
                                                                    &&op, this_site_arg this_site =
                                                                    this_site_arg(), generation_arg generation
                                                                    = generation_arg())
```

Inclusive `inclusive_scan` a set of values from different call sites

This function performs an inclusive scan operation on a set of values received from all call sites operating on the given base name.

Inclusive `inclusive_scan` a set of values from different call sites

This function performs an inclusive scan operation on a set of values received from all call sites operating on the given base name.

Parameters

- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.
- **generation** – The generational counter identifying the sequence number of the inclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the inclusive_scan operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **comm** – A communicator object returned from *create_communicator*
- **result** – The value to transmit to all participating sites from this call site.
- **op** – Reduction operation to apply to all values supplied from all participating sites
- **generation** – The generational counter identifying the sequence number of the inclusive_scan operation performed on the given base name. This is optional and needs to be supplied only if the inclusive_scan operation on the given base name has to be performed more than once. The generation number (if given) must be a positive number greater than zero.
- **this_site** – The sequence number of this invocation (usually the locality id). This value is optional and defaults to whatever *hpx::get_locality_id()* returns.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the inclusive_scan operation has been completed.

Returns

This function returns a future holding a vector with all values send by all participating sites. It will become ready once the inclusive_scan operation has been completed.

Warning: doxygenfunction: Unable to resolve function “hpx::collectives::inclusive_scan” with arguments (hpx::launch::sync_policy, char const*, T&&, F&&, num_sites_arg, this_site_arg, generation_arg, root_site_arg) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename T, typename F> decltype(auto) inclusive_scan(hpx::launch::sync_
  ↳policy, char const *basename, T &&result, F &&op, num_sites_arg num_sites = num_
  ↳sites_arg(), this_site_arg this_site = this_site_arg(), generation_arg generation =
  ↳generation_arg(), root_site_arg root_site = root_site_arg())
- template<typename T, typename F> decltype(auto) inclusive_scan(hpx::launch::sync_
  ↳policy, communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
  ↳arg(), generation_arg generation = generation_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> inclusive_scan(char_
  ↳const *basename, T &&result, F &&op, num_sites_arg num_sites = num_sites_arg(),
  ↳this_site_arg this_site = this_site_arg(), generation_arg generation = generation_
  ↳arg(), root_site_arg root_site = root_site_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> inclusive_
  ↳scan(communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
  ↳arg(), generation_arg generation = generation_arg())
```


Warning: doxygenfunction: Unable to resolve function “hpx::collectives::inclusive_scan” with arguments (hpx::launch::sync_policy, communicator, T&&, F&&, this_site_arg, generation_arg) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename T, typename F> decltype(auto) inclusive_scan(hpx::launch::sync_
→policy, char const *basename, T &&result, F &&op, num_sites_arg num_sites = num_
→sites_arg(), this_site_arg this_site = this_site_arg(), generation_arg generation =
→generation_arg(), root_site_arg root_site = root_site_arg())
- template<typename T, typename F> decltype(auto) inclusive_scan(hpx::launch::sync_
→policy, communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
→arg(), generation_arg generation = generation_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> inclusive_scan(char_
→const *basename, T &&result, F &&op, num_sites_arg num_sites = num_sites_arg(),
→this_site_arg this_site = this_site_arg(), generation_arg generation = generation_
→arg(), root_site_arg root_site = root_site_arg())
- template<typename T, typename F> hpx::future<std::decay_t<T>> inclusive_
→scan(communicator comm, T &&result, F &&op, this_site_arg this_site = this_site_
→arg(), generation_arg generation = generation_arg())
```

components

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx::components::client

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

template<typename **Component**, typename **Data** = void>

class **client** : public `hpx::components::client_base<client<Component, void>, Component, void>`

The client class is a wrapper that manages a distributed component. It extends `client_base` with specific `Component` and `Data` types.

Template Parameters

- **Component** – The type of the component.
- **Data** – The type of the data associated with the client (default is void).

hpx/components/get_ptr.hpp

Defined in header `hpx/components/get_ptr.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

```
template<typename Component>  
hpx::future<std::shared_ptr<Component>> get_ptr(hpx::id_type const &id)
```

Returns a future referring to the pointer to the underlying memory of a component.

The function `hpx::get_ptr` can be used to extract a future referring to the pointer to the underlying memory of a given component.

Note: This function will successfully return the requested result only if the given component is currently located on the calling locality. Otherwise, the function will raise an error.

Note: The component instance the returned pointer refers to can not be migrated as long as there is at least one copy of the returned `shared_ptr` alive.

Parameters

id – [in] The global id of the component for which the pointer to the underlying memory should be retrieved.

Template Parameters

Component – The type of the server side component.

Returns

This function returns a future representing the pointer to the underlying memory for the component instance with the given *id*.

```
template<typename Derived, typename Stub, typename Data>  
hpx::future<std::shared_ptr<typename components::client_base<Derived, Stub, Data>::server_component_type>> get_ptr(com
```

Stub
Data
com
&c

Returns a future referring to the pointer to the underlying memory of a component.

The function `hpx::get_ptr` can be used to extract a future referring to the pointer to the underlying memory of a given component.

Note: This function will successfully return the requested result only if the given component is currently located on the calling locality. Otherwise, the function will raise an error.

Note: The component instance the returned pointer refers to can not be migrated as long as there is at least one copy of the returned `shared_ptr` alive.

Parameters

c – [in] A client side representation of the component for which the pointer to the underlying memory should be retrieved.

Returns

This function returns a future representing the pointer to the underlying memory for the component instance with the given *id*.

```
template<typename Component>
std::shared_ptr<Component> get_ptr(launch::sync_policy p, hpx::id_type const &id, error_code &ec =
    throws)
```

Returns the pointer to the underlying memory of a component.

The function `hpx::get_ptr_sync` can be used to extract the pointer to the underlying memory of a given component.

Note: This function will successfully return the requested result only if the given component is currently located on the requesting locality. Otherwise, the function will raise an error.

Note: The component instance the returned pointer refers to can not be migrated as long as there is at least one copy of the returned `shared_ptr` alive.

Note: As long as `ec` is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter `ec`. Otherwise, it throws an instance of `hpx::exception`.

Parameters

- **p** – [in] The parameter `p` represents a placeholder type to turn make the call synchronous.
- **id** – [in] The global id of the component for which the pointer to the underlying memory should be retrieved.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Template Parameters

Component – The only template parameter has to be the type of the server side component.

Returns

This function returns the pointer to the underlying memory for the component instance with the given `id`.

```
template<typename Derived, typename Stub, typename Data>
std::shared_ptr<typename components::client_base<Derived, Stub, Data>::server_component_type> get_ptr(launch::sync_policy p,
    com-
    po-
    nents::client_base<Stub,
    Data>
    const
    &c,
    er-
    ror_code
    &ec
    =
    throws)
```

Returns the pointer to the underlying memory of a component.

The function `hpx::get_ptr_sync` can be used to extract the pointer to the underlying memory of a given component.

Note: This function will successfully return the requested result only if the given component is currently located on the requesting locality. Otherwise, the function will raise an error.

Note: The component instance the returned pointer refers to can not be migrated as long as there is at least one copy of the returned `shared_ptr` alive.

Note: As long as `ec` is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter `ec`. Otherwise, it throws an instance of `hpx::exception`.

Parameters

- **p** – [in] The parameter *p* represents a placeholder type to turn make the call synchronous.
- **c** – [in] A client side representation of the component for which the pointer to the underlying memory should be retrieved.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Returns

This function returns the pointer to the underlying memory for the component instance with the given *id*.

`hpx::components::client_base`

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename Derived, typename Stub, typename Data>
```

```
class client_base : public hpx::components::stub_base<ServerComponent>
```

This class template serves as a base class for client components, providing common functionality such as managing shared state, ID retrieval, and asynchronous operations.

Template Parameters

- **Derived** – The derived client component type.
- **Stub** – The stub type used for communication.
- **Data** – The extra data type used for additional information.

hpx/components/basename_registration_fwd.hpp

Defined in header `hpx/components/basename_registration_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

`hpx::future<bool> register_with_basename(std::string base_name, hpx::id_type const &id, std::size_t sequence_nr = ~static_cast<std::size_t>(0))`

Register the given id using the given base name.

The function registers the given ids using the provided base name.

Note: The operation will fail if the given sequence number is not unique.

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **id** – [in] The id to register using the given base name.
- **sequence_nr** – [in, optional] The sequential number to use for the registration of the id. This number has to be unique system-wide for each registration using the same base name. The default is the current locality identifier. Also, the sequence numbers have to be consecutive starting from zero.

Returns

A future representing the result of the registration operation itself.

`bool register_with_basename(hpx::launch::sync_policy, std::string base_name, hpx::id_type const &id, std::size_t sequence_nr = ~static_cast<std::size_t>(0), error_code &ec = throws)`

`hpx::future<bool> register_with_basename(std::string base_name, hpx::future<hpx::id_type> f, std::size_t sequence_nr = ~static_cast<std::size_t>(0))`

Register the id wrapped in the given future using the given base name.

The function registers the object the given future refers to using the provided base name.

Note: The operation will fail if the given sequence number is not unique.

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **f** – [in] The future which should be registered using the given base name.
- **sequence_nr** – [in, optional] The sequential number to use for the registration of the id. This number has to be unique system-wide for each registration using the same base name. The default is the current locality identifier. Also, the sequence numbers have to be consecutive starting from zero.

Returns

A future representing the result of the registration operation itself.

hpx/components/basename_registration.hpp

Defined in header `hpx/components/basename_registration.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
std::vector<hpx::future<hpx::id_type>> find_all_from_basename(std::string base_name, std::size_t  
                                                                num_ids)
```

Return all registered ids from all localities from the given base name.

This function locates all ids which were registered with the given base name. It returns a list of futures representing those ids.

Return all registered clients from all localities from the given base name.

This function locates all ids which were registered with the given base name. It returns a list of futures representing those ids.

Note: The futures will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Note: The futures embedded in the returned client objects will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **num_ids** – [in] The number of registered ids to expect.
- **base_name** – [in] The base name for which to retrieve the registered ids.
- **num_ids** – [in] The number of registered ids to expect.

Returns

A list of futures representing the ids which were registered using the given base name.

Template Parameters

Client – The client type to return

Returns

A list of futures representing the ids which were registered using the given base name.

```
std::vector<hpx::future<hpx::id_type>> find_all_from_basename(hpx::launch::sync_policy, std::string
                                                                base_name, std::size_t num_ids)
```

```
std::vector<hpx::future<hpx::id_type>> find_from_basename(std::string base_name,
                                                         std::vector<std::size_t> const &ids)
```

Return registered ids from the given base name and sequence numbers.

This function locates the ids which were registered with the given base name and the given sequence numbers. It returns a list of futures representing those ids.

Return registered clients from the given base name and sequence numbers.

This function locates the ids which were registered with the given base name and the given sequence numbers. It returns a list of futures representing those ids.

Note: The futures will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Note: The futures embedded in the returned client objects will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **ids** – [in] The sequence numbers of the registered ids.
- **base_name** – [in] The base name for which to retrieve the registered ids.
- **ids** – [in] The sequence numbers of the registered ids.

Returns

A list of futures representing the ids which were registered using the given base name and sequence numbers.

Template Parameters

Client – The client type to return

Returns

A list of futures representing the ids which were registered using the given base name and sequence numbers.

```
std::vector<hpx::future<hpx::id_type>> find_from_basename(hpx::launch::sync_policy, std::string
                                                                base_name, std::vector<std::size_t> const
                                                                &ids)
```

```
hpx::future<hpx::id_type> find_from_basename(std::string base_name, std::size_t sequence_nr =
                                                                ~static_cast<std::size_t>(0))
```

Return registered id from the given base name and sequence number.

This function locates the id which was registered with the given base name and the given sequence number. It returns a future representing those id.

This function locates the id which was registered with the given base name and the given sequence number. It returns a future representing those id.

Note: The future will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Note: The future embedded in the returned client object will become ready even if the event (for instance, binding the name to an id) has already happened in the past. This is important in order to reliably retrieve ids from a name, even if the name was already registered.

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **sequence_nr** – [in] The sequence number of the registered id.
- **base_name** – [in] The base name for which to retrieve the registered ids.
- **sequence_nr** – [in] The sequence number of the registered id.

Returns

A representing the id which was registered using the given base name and sequence numbers.

Template Parameters

Client – The client type to return

Returns

A representing the id which was registered using the given base name and sequence numbers.

```
hpx::id_type find_from_basename(hpx::launch::sync_policy, std::string base_name, std::size_t sequence_nr  
                                = ~static_cast<std::size_t>(0))
```

```
hpx::future<hpx::id_type> unregister_with_basename(std::string base_name, std::size_t sequence_nr =  
                                                    ~static_cast<std::size_t>(0))
```

Unregister the given id using the given base name.

The function unregisters the given ids using the provided base name.

Unregister the given base name.

The function unregisters the given ids using the provided base name.

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **sequence_nr** – [in, optional] The sequential number to use for the un-registration. This number has to be the same as has been used with *register_with_basename* before.
- **base_name** – [in] The base name for which to retrieve the registered ids.
- **sequence_nr** – [in, optional] The sequential number to use for the un-registration. This number has to be the same as has been used with *register_with_basename* before.

Returns

A future representing the result of the un-registration operation itself.

Template Parameters

Client – The client type to return

Returns

A future representing the result of the un-registration operation itself.

```
template<typename Client, typename Stub, typename Data>
hpx::future<bool> register_with_basename(std::string base_name, components::client_base<Client, Stub,
                                         Data> &client, std::size_t sequence_nr =
                                         ~static_cast<std::size_t>(0))
```

Register the id wrapped in the given client using the given base name.

The function registers the object the given client refers to using the provided base name.

Note: The operation will fail if the given sequence number is not unique.

Template Parameters

Client – The client type to register

Parameters

- **base_name** – [in] The base name for which to retrieve the registered ids.
- **client** – [in] The client which should be registered using the given base name.
- **sequence_nr** – [in, optional] The sequential number to use for the registration of the id. This number has to be unique system-wide for each registration using the same base name. The default is the current locality identifier. Also, the sequence numbers have to be consecutive starting from zero.

Returns

A future representing the result of the registration operation itself.

components_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/components_base/agas_interface.hpp

Defined in header `hpx/components_base/agas_interface.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **agas**

Functions

bool **is_console**()

bool **register_name**(*launch::sync_policy*, *std::string* const &name, *naming::gid_type* const &gid, *error_code* &ec = *throws*)

bool **register_name**(*launch::sync_policy*, *std::string* const &name, *hpx::id_type* const &id, *error_code* &ec = *throws*)

hpx::future<bool> **register_name**(*std::string* const &name, *hpx::id_type* const &id)

hpx::id_type **unregister_name**(*launch::sync_policy*, *std::string* const &name, *error_code* &ec = *throws*)

hpx::future<*hpx::id_type*> **unregister_name**(*std::string* const &name)

hpx::id_type **resolve_name**(*launch::sync_policy*, *std::string* const &name, *error_code* &ec = *throws*)

hpx::future<*hpx::id_type*> **resolve_name**(*std::string* const &name)

hpx::future<*std::uint32_t*> **get_num_localities**(*naming::component_type* type = *naming::component_invalid*)

std::uint32_t **get_num_localities**(*launch::sync_policy*, *naming::component_type* type, *error_code* &ec = *throws*)

inline *std::uint32_t* **get_num_localities**(*launch::sync_policy*, *error_code* &ec = *throws*)

std::string **get_component_type_name**(*naming::component_type* type, *error_code* &ec = *throws*)

hpx::future<*std::vector*<*std::uint32_t*>> **get_num_threads**()

std::vector<*std::uint32_t*> **get_num_threads**(*launch::sync_policy*, *error_code* &ec = *throws*)

hpx::future<*std::uint32_t*> **get_num_overall_threads**()

std::uint32_t **get_num_overall_threads**(*launch::sync_policy*, *error_code* &ec = *throws*)

std::uint32_t **get_locality_id**(*error_code* &ec = *throws*)

inline *hpx::naming::gid_type* **get_locality**()

std::vector<*std::uint32_t*> **get_all_locality_ids**(*naming::component_type* type, *error_code* &ec = *throws*)

inline *std::vector*<*std::uint32_t*> **get_all_locality_ids**(*error_code* &ec = *throws*)

bool **is_local_address_cached**(*naming::gid_type* const &gid, *error_code* &ec = *throws*)

bool **is_local_address_cached**(*naming::gid_type* const &gid, *naming::address* &addr, *error_code* &ec = *throws*)

bool **is_local_address_cached**(*naming::gid_type* const &gid, *naming::address* &addr, *std::pair*<bool, *components::pinned_ptr*> &r, *hpx::move_only_function*<*std::pair*<bool, *components::pinned_ptr*>(*naming::address* const&)> &&f, *error_code* &ec = *throws*)

```

inline bool is_local_address_cached(hpx::id_type const &id, error_code &ec = throws)

inline bool is_local_address_cached(hpx::id_type const &id, naming::address &addr, error_code
                                     &ec = throws)

inline bool is_local_address_cached(hpx::id_type const &id, naming::address &addr,
                                     std::pair<bool, components::pinned_ptr> &r,
                                     hpx::move_only_function<std::pair<bool,
                                     components::pinned_ptr>(naming::address const&)> &&f,
                                     error_code &ec = throws)

void update_cache_entry(naming::gid_type const &gid, naming::address const &addr, std::uint64_t
                        count = 0, std::uint64_t offset = 0, error_code &ec = throws)

bool is_local_lva_encoded_address(naming::gid_type const &gid)

inline bool is_local_lva_encoded_address(hpx::id_type const &id)

hpx::future_or_value<naming::address> resolve_async(hpx::id_type const &id)

hpx::future<naming::address> resolve(hpx::id_type const &id)

naming::address resolve(launch::sync_policy, hpx::id_type const &id, error_code &ec = throws)

bool resolve_local(naming::gid_type const &gid, naming::address &addr, error_code &ec = throws)

bool resolve_cached(naming::gid_type const &gid, naming::address &addr)

hpx::future<bool> bind(naming::gid_type const &gid, naming::address const &addr, std::uint32_t
                      locality_id)

bool bind(launch::sync_policy, naming::gid_type const &gid, naming::address const &addr,
          std::uint32_t locality_id, error_code &ec = throws)

hpx::future<bool> bind(naming::gid_type const &gid, naming::address const &addr, naming::gid_type
                      const &locality_)

bool bind(launch::sync_policy, naming::gid_type const &gid, naming::address const &addr,
          naming::gid_type const &locality_, error_code &ec = throws)

hpx::future<naming::address> unbind(naming::gid_type const &gid, std::uint64_t count = 1)

naming::address unbind(launch::sync_policy, naming::gid_type const &gid, std::uint64_t count = 1,
                        error_code &ec = throws)

bool bind_gid_local(naming::gid_type const &gid, naming::address const &addr, error_code &ec =
                    throws)

void unbind_gid_local(naming::gid_type const &gid, error_code &ec = throws)

bool bind_range_local(naming::gid_type const &gid, std::size_t count, naming::address const &addr,
                      std::size_t offset, error_code &ec = throws)

void unbind_range_local(naming::gid_type const &gid, std::size_t count, error_code &ec = throws)

void garbage_collect_non_blocking(error_code &ec = throws)

void garbage_collect(error_code &ec = throws)

```

void **garbage_collect_non_blocking**(*hpx::id_type* const &id, *error_code* &ec = *throws*)
 Invoke an asynchronous garbage collection step on the given target locality.

void **garbage_collect**(*hpx::id_type* const &id, *error_code* &ec = *throws*)
 Invoke a synchronous garbage collection step on the given target locality.

hpx::id_type **get_console_locality**(*error_code* &ec = *throws*)
 Return an *id_type* referring to the console locality.

naming::gid_type **get_next_id**(*std::size_t* count, *error_code* &ec = *throws*)

void **decref**(*naming::gid_type* const &id, *std::int64_t* credits, *error_code* &ec = *throws*)

hpx::future_or_value<std::int64_t> **incref**(*naming::gid_type* const &gid, *std::int64_t* credits,
 hpx::id_type const &keep_alive = *hpx::invalid_id*)

std::int64_t **incref**(*launch::sync_policy*, *naming::gid_type* const &gid, *std::int64_t* credits = 1,
 hpx::id_type const &keep_alive = *hpx::invalid_id*, *error_code* &ec = *throws*)

std::int64_t **replenish_credits**(*naming::gid_type* &gid)

hpx::future_or_value<id_type> **get_colocation_id**(*hpx::id_type* const &id)

hpx::id_type **get_colocation_id**(*launch::sync_policy*, *hpx::id_type* const &id, *error_code* &ec =
 throws)

hpx::future<hpx::id_type> **on_symbol_namespace_event**(*std::string* const &name, bool
 call_for_past_events)

hpx::future<std::pair<hpx::id_type, naming::address>> **begin_migration**(*hpx::id_type* const &id)

bool **end_migration**(*hpx::id_type* const &id)

hpx::future<void> **mark_as_migrated**(*naming::gid_type* const &gid,
 hpx::move_only_function<std::pair<bool,
 hpx::future<void>>()> &&f, bool
 expect_to_be_marked_as_migrating)

std::pair<bool, components::pinned_ptr> **was_object_migrated**(*naming::gid_type* const &gid,
 hpx::move_only_function<components::pinned_ptr()>
 &&f)

void **unmark_as_migrated**(*naming::gid_type* const &gid, *hpx::move_only_function<void()> &&f*)

hpx::future<std::map<std::string, hpx::id_type>> **find_symbols**(*std::string* const &pattern = *"*"*)

std::map<std::string, hpx::id_type> **find_symbols**(*hpx::launch::sync_policy*, *std::string* const &pattern
 = *"*"*)

naming::component_type **register_factory**(*std::uint32_t* prefix, *std::string* const &name, *error_code*
 &ec = *throws*)

naming::component_type **get_component_id**(*std::string* const &name, *error_code* &ec = *throws*)

void **destroy_component**(*naming::gid_type* const &gid, *naming::address* const &addr)

naming::address_type **get_primary_ns_lva**()

```

naming::address_type get_symbol_ns_lva()

naming::address_type get_runtime_support_lva()

struct agas_interface_functions &agas_init()

```

HPX_REGISTER_STARTUP_MODULE

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Warning: doxygenfunction: Cannot find function “HPX_REGISTER_STARTUP_MODULE” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx/components_base/component_type.hpp

Defined in header `hpx/components_base/component_type.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_COMPONENT_ENUM_TYPE_ENUM_DEPRECATION_MSG

HPX_FACTORY_STATE_ENUM_DEPRECATION_MSG

namespace **hpx**

namespace **components**

Typedefs

```

using component_deleter_type = void (*)(hpx::naming::gid_type const&, hpx::naming::address
const&)

```

Enums

```

enum class component_enum_type : naming::component_type

```

Values:

enumerator **invalid**

enumerator **runtime_support**

enumerator **plain_function**

enumerator **base_lco**

enumerator **base_lco_with_value_unmanaged**

enumerator **base_lco_with_value**

enumerator **latch**

enumerator **barrier**

enumerator **promise**

enumerator **agas_locality_namespace**

enumerator **agas_primary_namespace**

enumerator **agas_component_namespace**

enumerator **agas_symbol_namespace**

enumerator **supervision_manager**

enumerator **last**

enumerator **first_dynamic**

enum class **factory_state** : *std::uint8_t*

Values:

enumerator **enabled**

enumerator **disabled**

enumerator **check**

Functions

constexpr *naming::component_type* **to_int**(*component_enum_type* t) noexcept

constexpr int **to_int**(*factory_state* t) noexcept

bool &**enabled**(*component_type* type)

util::atomic_count &**instance_count**(*component_type* type)

component_deleter_type &**deleter**(*component_type* type)

bool **enumerate_instance_counts**(*hpx::move_only_function*<bool(*component_type*)> const &f)

std::string **get_component_type_name**(*component_type* type)

Return the string representation for a given component type id.

constexpr *component_type* **get_base_type**(*component_type* t) noexcept

The lower short word of the component type is the type of the component exposing the actions.

constexpr *component_type* **get_derived_type**(*component_type* t) noexcept

The upper short word of the component is the actual component type.

constexpr *component_type* **derived_component_type**(*component_type* derived, *component_type* base) noexcept

A component derived from a base component exposing the actions needs to have a specially formatted component type.

constexpr bool **types_are_compatible**(*component_type* lhs, *component_type* rhs) noexcept

Verify the two given component types are matching (compatible)

template<typename **Component**, typename **Enable** = void>

char const ***get_component_name**() noexcept

template<typename **Component**, typename **Enable** = void>

char const ***get_component_base_name**() noexcept

template<typename **Component**>

component_type **get_component_type**() noexcept

template<typename **Component**>

void **set_component_type**(*component_type* type)

Variables

constexpr *component_enum_type* **component_invalid** = *component_enum_type::invalid*

constexpr *component_enum_type* **component_runtime_support** =
component_enum_type::runtime_support

constexpr *component_enum_type* **component_plain_function** =
component_enum_type::plain_function

constexpr *component_enum_type* **component_base_lco** = *component_enum_type::base_lco*

```
constexpr component_enum_type component_base_lco_with_value_unmanaged =  
    component_enum_type::base_lco_with_value_unmanaged  
  
constexpr component_enum_type component_base_lco_with_value =  
    component_enum_type::base_lco_with_value  
  
constexpr component_enum_type component_latch = component_enum_type::latch  
  
constexpr component_enum_type component_barrier = component_enum_type::barrier  
  
constexpr component_enum_type component_promise = component_enum_type::promise  
  
constexpr component_enum_type component_agas_locality_namespace =  
    component_enum_type::agas_locality_namespace  
  
constexpr component_enum_type component_agas_primary_namespace =  
    component_enum_type::agas_primary_namespace  
  
constexpr component_enum_type component_agas_component_namespace =  
    component_enum_type::agas_component_namespace  
  
constexpr component_enum_type component_agas_symbol_namespace =  
    component_enum_type::agas_symbol_namespace  
  
constexpr component_enum_type component_last = component_enum_type::last  
  
constexpr component_enum_type component_first_dynamic = component_enum_type::first_dynamic  
  
constexpr factory_state factory_enabled = factory_state::enabled  
  
constexpr factory_state factory_disabled = factory_state::disabled  
  
constexpr factory_state factory_check = factory_state::check  
  
constexpr int component_type_mask = 0x3FF  
  
constexpr int component_type_shift = 10
```


hpx/components_base/get_lva.hpp

Defined in header `hpx/components_base/get_lva.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

```
template<typename Component, typename Enable = void>
```

```
struct get_lva
```

#include <get_lva.hpp> The `get_lva` template is a helper structure allowing to convert a local virtual address as stored in a local address (returned from the function `agas::addressing_service::resolve`) to the address of the component implementing the action.

The default implementation uses the template argument *Component* to deduce the type wrapping the component implementing the action. This is used to get the needed address.

Template Parameters

Component – This is the type of the component implementing the action to execute.

Public Static Functions

```
static inline constexpr Component *call(naming::address_type lva) noexcept
```

HPX_REGISTER_COMMANDLINE_MODULE

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Warning: doxygenfunction: Cannot find function “`HPX_REGISTER_COMMANDLINE_MODULE`” in doxygen xml output for project “`hpx`” from directory: `../hpx_autodoc`

hpx::components::component

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::components::component_base`

```
template<typename Component>
```

```
class component
```

The *component* class wraps around a given component type, adding additional type aliases and constructors. It inherits from the specified component type.

hpx::components::component_base

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::components::component`

template<typename **Component**>

class **component_base**

`component_base` serves as a base class for components. It provides common functionality needed by components, such as address and ID retrieval. The template parameter *Component* specifies the derived component type.

Subclassed by `Component`

hpx/components_base/server/fixed_component_base.hpp

Defined in header `hpx/components_base/server/fixed_component_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

template<typename **Component**>

class **fixed_component**

template<typename **Component**>

class **fixed_component_base**

hpx/components_base/server/managed_component_base.hpp

Defined in header `hpx/components_base/server/managed_component_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<>

struct **init**<*traits::construct_with_back_ptr*>

Public Static Functions

```
template<typename Component, typename Managed>
static inline constexpr void call(Component*, Managed*) noexcept

template<typename Component, typename Managed, typename ...Ts>
static inline void call_new(Component * &component, Managed *this_, Ts&&... vs)

template<>

struct init<traits::construct_without_back_ptr>
```

Public Static Functions

```
template<typename Component, typename Managed>
static inline void call(Component *component, Managed *this_)

template<typename Component, typename Managed, typename ...Ts>
static inline void call_new(Component * &component, Managed *this_, Ts&&... vs)

template<>

struct destroy_backptr<traits::managed_object_is_lifetime_controlled>
```

Public Static Functions

```
template<typename BackPtr>
static inline void call(BackPtr *back_ptr)

template<>

struct destroy_backptr<traits::managed_object_controls_lifetime>
```

Public Static Functions

```
template<typename BackPtr>
static inline constexpr void call(BackPtr*) noexcept

template<>

struct manage_lifetime<traits::managed_object_is_lifetime_controlled>
```

Public Static Functions

```
template<typename Component>
static inline constexpr void call(Component*) noexcept

template<typename Component>
static inline void addref(Component *component) noexcept

template<typename Component>
```

```
static inline void release(Component *component) noexcept  
  
template<>  
  
struct manage_lifetime<traits::managed_object_controls_lifetime>
```

Public Static Functions

```
template<typename Component>  
static inline void call(Component *component) noexcept(noexcept(component->finalize()))  
  
template<typename Component>  
static inline constexpr void addref(Component*) noexcept  
  
template<typename Component>  
static inline constexpr void release(Component*) noexcept
```

```
namespace hpx
```

```
namespace components
```

Functions

```
template<typename Component, typename Derived>  
void intrusive_ptr_add_ref(managed_component<Component, Derived> *p) noexcept  
  
template<typename Component, typename Derived>  
void intrusive_ptr_release(managed_component<Component, Derived> *p) noexcept  
  
template<typename Component, typename Derived>  
  
class managed_component  
    #include <managed_component_base.hpp>  
  
template<typename Component, typename Wrapper, typename CtorPolicy, typename DtorPolicy>  
  
class managed_component_base  
  
namespace detail_adl_barrier  
  
    template<typename DtorTag>  
  
    struct destroy_backptr  
  
    template<> managed_object_controls_lifetime >
```

Public Static Functions

```
template<typename BackPtr>
static inline constexpr void call(BackPtr*) noexcept
```

```
template<> managed_object_is_lifetime_controlled >
```

Public Static Functions

```
template<typename BackPtr>
static inline void call(BackPtr *back_ptr)
```

```
template<typename BackPtrTag>
```

```
struct init
```

```
template<> construct_with_back_ptr >
```

Public Static Functions

```
template<typename Component, typename Managed>
static inline constexpr void call(Component*, Managed*) noexcept
```

```
template<typename Component, typename Managed, typename ...Ts>
static inline void call_new(Component *&component, Managed *this_, Ts&&... vs)
```

```
template<> construct_without_back_ptr >
```

Public Static Functions

```
template<typename Component, typename Managed>
static inline void call(Component *component, Managed *this_)
```

```
template<typename Component, typename Managed, typename ...Ts>
static inline void call_new(Component *&component, Managed *this_, Ts&&... vs)
```

```
template<typename DtorTag>
```

```
struct manage_lifetime
```

```
template<> managed_object_controls_lifetime >
```

Public Static Functions

```
template<typename Component>
static inline void call(Component *component) noexcept(noexcept(component->finalize()))
```

```
template<typename Component>
static inline constexpr void addref(Component*) noexcept
```

```
template<typename Component>
static inline constexpr void release(Component*) noexcept
```

```
template<> managed_object_is_lifetime_controlled >
```

Public Static Functions

```
template<typename Component>
static inline constexpr void call(Component*) noexcept
```

```
template<typename Component>
static inline void addref(Component *component) noexcept
```

```
template<typename Component>
static inline void release(Component *component) noexcept
```

hpx/components_base/server/migration_support.hpp

Defined in header `hpx/components_base/server/migration_support.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

```
template<typename BaseComponent, typename Mutex = hpx::spinlock>
```

```
struct migration_support : public BaseComponent
```

```
    #include <migration_support.hpp> This hook has to be inserted into the derivation chain of any component for it to support migration.
```

Public Types

```
using decorates_action = void
```

Public Functions

```

inline migration_support()

template<typename T, typename ...Ts, typename =
    std::enable_if_t<!std::is_same_v<std::decay_t<T>, migration_support>>>
inline explicit migration_support(T &&t, Ts&&... ts)

migration_support(migration_support const&) = default
migration_support(migration_support&&) = default
migration_support &operator=(migration_support const&) = default
migration_support &operator=(migration_support&&) = default
~migration_support() = default

inline naming::gid_type get_base_gid(naming::gid_type const &assign_gid =
    naming::invalid_gid) const

inline bool pin() noexcept
inline bool unpin()

inline std::uint32_t pin_count() const noexcept

inline void mark_as_migrated()

inline hpx::future<void> mark_as_migrated(hpx::id_type const &to_migrate)

inline void unmark_as_migrated(hpx::id_type const &to_migrate)

```

Public Static Functions

```

static inline constexpr bool supports_migration() noexcept

static inline constexpr void on_migrated() noexcept

template<typename F>
static inline threads::thread_function_type decorate_action(naming::address_type lva, F &&f)

static inline std::pair<bool, components::pinned_ptr> was_object_migrated(hpx::naming::gid_type
    const &id, nam-
    ing::address_type
    lva)

```

Protected Functions

```

inline threads::thread_result_type thread_function(threads::thread_function_type &&f,
    components::pinned_ptr,
    threads::thread_restart_state state)

```

Private Types

```
using base_type = BaseComponent
```

```
using this_component_type = typename base_type::this_component_type
```

Private Members

```
hpx::intrusive_ptr<detail::migration_support_data<Mutex>> data_
```

```
hpx::promise<void> trigger_migration_
```

```
bool started_migration_ = false
```

```
bool was_marked_for_migration_ = false
```

compute

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/compute/host/target_distribution_policy.hpp

Defined in header `hpx/compute/host/target_distribution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

distribution_policies

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/distribution_policies/binpacking_distribution_policy.hpp

Defined in header `hpx/distribution_policies/binpacking_distribution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace components
```


Variables

```
constexpr char const *const default_binpacking_counter_name =
"/runtime{locality/total}/count/component@"
```

```
const binpacking_distribution_policy binpacked
```

A predefined instance of the binpacking *distribution_policy*. It will represent the local locality and will place all items to create here.

```
struct binpacking_distribution_policy
```

#include <binpacking_distribution_policy.hpp> This class specifies the parameters for a binpacking distribution policy to use for creating a given number of items on a given set of localities. The binpacking policy will distribute the new objects in a way such that each of the localities will equalize the number of overall objects of this type based on a given criteria (by default this criteria is the overall number of objects of this type).

Public Functions

```
inline binpacking_distribution_policy()
```

Default-construct a new instance of a *binpacking_distribution_policy*. This policy will represent one locality (the local locality).

```
inline binpacking_distribution_policy operator() (std::vector<id_type> const &locs, char const
*perf_counter_name =
default_binpacking_counter_name) const
```

Create a new *default_distribution* policy representing the given set of localities.

Parameters

- **locs** – [in] The list of localities the new instance should represent
- **perf_counter_name** – [in] The name of the performance counter which should be used as the distribution criteria (by default the overall number of existing instances of the given component type will be used).

```
inline binpacking_distribution_policy operator() (std::vector<id_type> &&locs, char const
*perf_counter_name =
default_binpacking_counter_name) const
```

Create a new *default_distribution* policy representing the given set of localities.

Parameters

- **locs** – [in] The list of localities the new instance should represent
- **perf_counter_name** – [in] The name of the performance counter which should be used as the distribution criteria (by default the overall number of existing instances of the given component type will be used).

```
inline binpacking_distribution_policy operator() (id_type const &loc, char const
*perf_counter_name =
default_binpacking_counter_name) const
```

Create a new *default_distribution* policy representing the given locality

Parameters

- **loc** – [in] The locality the new instance should represent
- **perf_counter_name** – [in] The name of the performance counter that should be used as the distribution criteria (by default the overall number of existing instances of the given component type will be used).

```
template<typename Component, typename ...Ts>
inline hpx::future<hpx::id_type> create(Ts&&... vs) const
```

Create one object on one of the localities associated by this policy instance

Parameters

vs – [in] The arguments which will be forwarded to the constructor of the new object.

Returns

A future holding the global address which represents the newly created object

```
template<bool WithCount, typename Component, typename ...Ts>
inline hpx::future<std::vector<bulk_locality_result>> bulk_create(std::size_t count, Ts&&... vs)
                                                    const
```

Create multiple objects on the localities associated by this policy instance

Parameters

- **count** – [in] The number of objects to create
- **vs** – [in] The arguments which will be forwarded to the constructors of the new objects.

Returns

A future holding the list of global addresses which represent the newly created objects

```
inline std::string const &get_counter_name() const
```

Returns the name of the performance counter associated with this policy instance.

```
inline std::size_t get_num_localities() const
```

Returns the number of associated localities for this distribution policy

Note: This function is part of the creation policy implemented by this class

hpx/distribution_policies/colocating_distribution_policy.hpp

Defined in header `hpx/distribution_policies/colocating_distribution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

Variables

const *colocating_distribution_policy* **colocated**

A predefined instance of the co-locating *distribution_policy*. It will represent the local locality and will place all items to create here.

struct **colocating_distribution_policy**

#include <*colocating_distribution_policy.hpp*> This class specifies the parameters for a distribution policy to use for creating a given number of items on the locality where a given object is currently placed.

Public Functions

constexpr **colocating_distribution_policy**() = default

Default-construct a new instance of a `colocating_distribution_policy`. This policy will represent the local locality.

inline *colocating_distribution_policy* **operator**() (id_type const &id) const

Create a new `colocating_distribution_policy` representing the locality where the given object is current located

Parameters

id – [in] The global address of the object with which the new instances should be colocated on

template<typename **Client**, typename **Stub**, typename **Data**>

inline *colocating_distribution_policy* **operator**() (*client_base*<*Client*, *Stub*, *Data*> const &client) const

Create a new `colocating_distribution_policy` representing the locality where the given object is current located

Parameters

client – [in] The client side representation of the object with which the new instances should be colocated on

template<typename **Component**, typename ...**Ts**>

inline *hpx::future*<*hpx::id_type*> **create**(*Ts*&&... vs) const

Create one object on the locality of the object this distribution policy instance is associated with

Note: This function is part of the placement policy implemented by this class

Parameters

vs – [in] The arguments which will be forwarded to the constructor of the new object.

Returns

A future holding the global address which represents the newly created object

template<bool **WithCount**, typename **Component**, typename ...**Ts**>

inline *hpx::future*<*std::vector*<*bulk_locality_result*>> **bulk_create**(*std::size_t* count, *Ts*&&... vs) const

Create multiple objects colocated with the object represented by this policy instance

Note: This function is part of the placement policy implemented by this class

Parameters

- **count** – [in] The number of objects to create
- **vs** – [in] The arguments which will be forwarded to the constructors of the new objects.

Returns

A future holding the list of global addresses which represent the newly created objects

template<typename **Action**, typename ...**Ts**>

inline *async_result*<*Action*>::type **async**(*launch* policy, *Ts*&&... vs) const

template<typename **Action**, typename **Callback**, typename ...**Ts**>

inline *async_result*<*Action*>::type **async_cb**(*launch* policy, *Callback* &&cb, *Ts*&&... vs) const

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Continuation, typename ...Ts>
inline bool apply(Continuation &&c, launch policy, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename ...Ts>
inline bool apply(launch policy, Ts&&... vs) const

template<typename Action, typename Continuation, typename Callback, typename ...Ts>
inline bool apply_cb(Continuation &&c, launch policy, Callback &&cb, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Callback, typename ...Ts>
inline bool apply_cb(launch policy, Callback &&cb, Ts&&... vs) const

inline hpx::id_type get_next_target() const
    Returns the locality which is anticipated to be used for the next async operation
```

Public Static Functions

```
static inline std::size_t get_num_localities()
    Returns the number of associated localities for this distribution policy
```

Note: This function is part of the creation policy implemented by this class

Private Functions

```
inline hpx::id_type resolve_direct_target() const

template<typename Action>
struct async_result
    #include <colocating_distribution_policy.hpp>
```

Note: This function is part of the invocation policy implemented by this class

Public Types

```
using type = hpx::future<typename traits::promise_local_result<typename  
hpx::traits::extract_action<Action>::remote_result_type>::type>
```

`hpx/distribution_policies/unwrapping_result_policy.hpp`

Defined in header `hpx/distribution_policies/unwrapping_result_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

struct **unwrapping_result_policy**

#include <unwrapping_result_policy.hpp> This class is a distribution policy that can be used with actions that return futures. For those actions it is possible to apply certain optimizations if the action is invoked synchronously.

Public Functions

inline explicit **unwrapping_result_policy**(id_type const &id)

template<typename **Client**, typename **Stub**, typename **Data**>
inline explicit **unwrapping_result_policy**(*client_base*<*Client*, *Stub*, *Data*> const &client)

template<typename **Action**, typename ...**Ts**>
inline *async_result*<*Action*>::type **async**(*launch* policy, *Ts*&&... vs) const

template<typename **Action**, typename ...**Ts**>
inline *async_result*<*Action*>::type **async**(*launch::sync_policy*, *Ts*&&... vs) const

template<typename **Action**, typename **Callback**, typename ...**Ts**>
inline *async_result*<*Action*>::type **async_cb**(*launch* policy, *Callback* &&cb, *Ts*&&... vs) const

template<typename **Action**, typename **Continuation**, typename ...**Ts**>
inline bool **apply**(*Continuation* &&c, *launch* policy, *Ts*&&... vs) const

Note: This function is part of the invocation policy implemented by this class

template<typename **Action**, typename ...**Ts**>
inline bool **apply**(*launch* policy, *Ts*&&... vs) const

template<typename **Action**, typename **Continuation**, typename **Callback**, typename ...**Ts**>
inline bool **apply_cb**(*Continuation* &&c, *launch* policy, *Callback* &&cb, *Ts*&&... vs) const

Note: This function is part of the invocation policy implemented by this class

template<typename **Action**, typename **Callback**, typename ...**Ts**>

```
inline bool apply_cb(launch policy, Callback &&cb, Ts&&... vs) const

inline hpx::id_type const &get_next_target() const

template<typename Action>

struct async_result
```

Public Types

```
using type = typename traits::promise_local_result<typename
hpx::traits::extract_action<Action>::remote_result_type>::type
```

hpx/distribution_policies/target_distribution_policy.hpp

Defined in header `hpx/distribution_policies/target_distribution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace components
```

Variables

```
const target_distribution_policy target
```

A predefined instance of the `target_distribution_policy`. It will represent the local locality and will place all items to create here.

```
struct target_distribution_policy
```

#include <target_distribution_policy.hpp> This class specifies the parameters for a simple distribution policy to use for creating (and evenly distributing) a given number of items on a given set of localities.

Public Functions

```
target_distribution_policy() = default
```

Default-construct a new instance of a `target_distribution_policy`. This policy will represent one locality (the local locality).

```
inline target_distribution_policy operator() (id_type const &id) const
```

Create a new `target_distribution_policy` representing the given locality

Parameters

loc – [in] The locality the new instance should represent

```
template<typename Component, typename ...Ts>
```

```
inline hpx::future<hpx::id_type> create(Ts&&... vs) const
```

Create one object on one of the localities associated by this policy instance

Note: This function is part of the placement policy implemented by this class

Parameters

vs – [in] The arguments which will be forwarded to the constructor of the new object.

Returns

A future holding the global address which represents the newly created object

```
template<bool WithCount, typename Component, typename ...Ts>
```

```
inline hpx::future<std::vector<bulk_locality_result>> bulk_create(std::size_t count, Ts&&... vs)
                                                    const
```

Create multiple objects on the localities associated by this policy instance

Note: This function is part of the placement policy implemented by this class

Parameters

- **count** – [in] The number of objects to create

- **vs** – [in] The arguments which will be forwarded to the constructors of the new objects.

Returns

A future holding the list of global addresses which represent the newly created objects

```
template<typename Action, typename ...Ts>
```

```
inline async_result<Action>::type async(launch policy, Ts&&... vs) const
```

```
template<typename Action, typename Callback, typename ...Ts>
```

```
inline async_result<Action>::type async_cb(launch policy, Callback &&cb, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Continuation, typename ...Ts>
```

```
inline bool apply(Continuation &&c, launch policy, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename ...Ts>
```

```
inline bool apply(launch policy, Ts&&... vs) const
```

```
template<typename Action, typename Continuation, typename Callback, typename ...Ts>
```

```
inline bool apply_cb(Continuation &&c, launch policy, Callback &&cb, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Callback, typename ...Ts>
```

```
inline bool apply_cb(launch policy, Callback &&cb, Ts&&... vs) const
```

```
inline std::size_t get_num_localities() const
```

Returns the number of associated localities for this distribution policy

Note: This function is part of the creation policy implemented by this class

```
inline hpx::id_type get_next_target() const
```

Returns the locality which is anticipated to be used for the next async operation

```
template<typename Action>
```

```
struct async_result
```

```
    #include <target_distribution_policy.hpp>
```

Note: This function is part of the invocation policy implemented by this class

Public Types

```
using type = hpx::future<typename traits::promise_local_result<typename  
hpx::traits::extract_action<Action>::remote_result_type>::type>
```

hpx/distribution_policies/default_distribution_policy.hpp

Defined in header `hpx/distribution_policies/default_distribution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace components
```

Variables

```
const default_distribution_policy default_layout
```

A predefined instance of the default *distribution_policy*. It will represent the local locality and will place all items to create here.

```
struct default_distribution_policy
```

#include <default_distribution_policy.hpp> This class specifies the parameters for a simple distribution policy to use for creating (and evenly distributing) a given number of items on a given set of localities.

Public Functions

constexpr **default_distribution_policy**() = default

Default-construct a new instance of a `default_distribution_policy`. This policy will represent one locality (the local locality).

inline *default_distribution_policy* **operator**() (std::vector<id_type> locs) const

Create a new *default_distribution* policy representing the given set of localities.

Parameters

locs – [in] The list of localities the new instance should represent

inline *default_distribution_policy* **operator**() (id_type loc) const

Create a new *default_distribution* policy representing the given locality

Parameters

loc – [in] The locality the new instance should represent

template<typename **Component**, typename ...**Ts**>

inline *hpx::future*<*hpx::id_type*> **create**(Ts&&... vs) const

Create one object on one of the localities associated by this policy instance

Note: This function is part of the placement policy implemented by this class

Parameters

vs – [in] The arguments which will be forwarded to the constructor of the new object.

Returns

A future holding the global address which represents the newly created object

template<bool **WithCount**, typename **Component**, typename ...**Ts**>

inline *hpx::future*<std::vector<bulk_locality_result>> **bulk_create**(std::size_t count, Ts&&... vs) const

Create multiple objects on the localities associated by this policy instance

Note: This function is part of the placement policy implemented by this class

Parameters

- **count** – [in] The number of objects to create
- **vs** – [in] The arguments which will be forwarded to the constructors of the new objects.

Returns

A future holding the list of global addresses that represent the newly created objects

template<typename **Action**, typename ...**Ts**>

inline *async_result*<*Action*>::type **async**(*launch* policy, Ts&&... vs) const

template<typename **Action**, typename **Callback**, typename ...**Ts**>

inline *async_result*<*Action*>::type **async_cb**(*launch* policy, *Callback* &&cb, Ts&&... vs) const

Note: This function is part of the invocation policy implemented by this class

template<typename **Action**, typename **Continuation**, typename ...**Ts**>

```
inline bool apply(Continuation &&c, launch policy, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename ...Ts>
inline bool apply(threads::thread_priority priority, Ts&&... vs) const

template<typename Action, typename Continuation, typename Callback, typename ...Ts>
inline bool apply_cb(Continuation &&c, launch policy, Callback &&cb, Ts&&... vs) const
```

Note: This function is part of the invocation policy implemented by this class

```
template<typename Action, typename Callback, typename ...Ts>
inline bool apply_cb(launch policy, Callback &&cb, Ts&&... vs) const

inline std::size_t get_num_localities() const
    Returns the number of associated localities for this distribution policy
```

Note: This function is part of the creation policy implemented by this class

```
inline hpx::id_type get_next_target() const
    Returns the locality which is anticipated to be used for the next async operation

template<typename Action>

struct async_result
    #include <default_distribution_policy.hpp>
```

Note: This function is part of the invocation policy implemented by this class

Public Types

```
using type = hpx::future<typename traits::promise_local_result<typename
hpx::traits::extract_action<Action>::remote_result_type>::type>
```

execution_distributed

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/execution_distributed/distributed_scheduler.hpp

Defined in header `hpx/execution_distributed/distributed_scheduler.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

P2300-compliant scheduler for cross-locality execution.

Provides a scheduler that dispatches work to a remote HPX locality via the parcelport, bridging the `hpx::future` completion back into the P2300 `set_value` / `set_error` receiver protocol.

Usage:

```

hpx::id_type remote = hpx::find_all_localities()[1];
auto sched = hpx::distributed::distributed_scheduler{remote};
auto result = ex::just(42)
    | ex::continues_on(sched)
    | ex::then([](int x){ return x * 2; })
    | tt::sync_wait();

```

hpx/execution_distributed/distributed_then_sender.hpp

Defined in header `hpx/execution_distributed/distributed_then_sender.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Placeholder for the distributed then sender adaptor.

A proper component-based receiver marshalling system (nvexec-style) will be implemented here in a future phase.

hpx/execution_distributed/distributed_continues_on_sender.hpp

Defined in header `hpx/execution_distributed/distributed_continues_on_sender.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Placeholder for the distributed `continues_on` sender adaptor.

A proper component-based receiver marshalling system (nvexec-style) will be implemented here in a future phase.

executors_distributed

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors_distributed/distribution_policy_executor.hpp

Defined in header `hpx/executors_distributed/distribution_policy_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

namespace **experimental**

Functions

```
template<typename DistPolicy>
distribution_policy_executor(DistPolicy&&) ->
    distribution_policy_executor<std::decay_t<DistPolicy>>
```

```
template<typename DistPolicy> HPX_DEPRECATED_V(1, 9,
    "hpx::parallel::execution::make_distribution_policy_executor is " "deprecated,
    use " "hpx::parallel::execution::distribution_policy_executor instead") distribution_policy_executor
```

Create a new *distribution_policy_executor* from the given *distribution_policy*.

Parameters

policy – The *distribution_policy* to create an executor from

```
template<typename DistPolicy>
```

```
class distribution_policy_executor
```

#include <distribution_policy_executor.hpp> A *distribution_policy_executor* creates groups of parallel execution agents that execute in threads implicitly created by the executor and placed on any of the associated localities.

Template Parameters

DistPolicy – The distribution policy type for which an executor should be created. The expression *hpx::traits::is_distribution_policy_v<DistPolicy>* must evaluate to true.

include

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/experimental/sandbox.hpp

Defined in header *hpx/experimental/sandbox.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **experimental**

namespace **sandbox**

Functions

environment_info **detect_environment**()

Detect and return information about the current environment.

inline void **describe_environment**(*std::ostream* &os)

Print a formatted environment report.

template<typename **F**>

double **measure**(*F* &&fn, *std::size_t* iterations = 5)

Measure the mean execution time of a callable.

template<typename **SeqFn**, typename **ParFn**>

benchmark_report **benchmark**(*std::string* label, *SeqFn* &&seq_fn, *ParFn* &&par_fn, *std::size_t* iterations = 5)

Compare sequential and parallel execution of the same work.

struct **benchmark_report**

#include <sandbox.hpp> Holds the results of a comparative benchmark.

Public Functions

void **print**(*std::ostream* &os) const

Print a formatted benchmark report.

Parameters

os – Output stream.

Public Members

std::string **label**

User-provided description.

std::size_t **iterations** = 0

Measurement iterations.

double **seq_mean_ms** = 0.0

Sequential mean time (ms)

double **par_mean_ms** = 0.0

Parallel mean time (ms)

double **speedup** = 0.0

seq_time / par_time

double **efficiency_pct** = 0.0

(speedup / workers) * 100

`std::size_t num_workers = 0`

HPX workers during measurement.

struct **environment_info**

#include <sandbox.hpp> Describes the hardware and runtime environment.

Public Functions

void **print**(`std::ostream &os`) const

Print a formatted environment report.

Parameters

os – Output stream.

Public Members

`std::size_t cores = 0`

Physical CPU cores.

`std::size_t pus = 0`

Processing units (hardware threads)

`std::size_t numa_nodes = 0`

NUMA domains.

`std::size_t hpx_workers = 0`

Active HPX worker threads.

bool **is_sandbox** = false

Likely constrained environment.

init_runtime

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/hpx_init.hpp

Defined in header `hpx/hpx_init.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

hpx/hpx_start.hpp

Defined in header `hpx/hpx_start.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

hpx::init_params

Defined in header `hpx/init.hpp`⁵⁷⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

struct **init_params**

Parameters used to initialize the HPX runtime through `hpx::init` and `hpx::start`.

hpx::start

Defined in header `hpx/init.hpp`⁵⁸⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
inline bool hpx::start(std::function<int(hpx::program_options::variables_map&)> f, int argc, char **argv,
                       init_params const &params = init_params())
```

Main non-blocking entry point for launching the HPX runtime system.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution. This overload will not call `hpx_main`.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as an HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the `parametermode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.
- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).

⁵⁷⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/init_runtime/include/hpx/init.hpp

⁵⁸⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/init_runtime/include/hpx/init.hpp

- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::start` function (See documentation of `hpx::init_params`)

Returns

The function returns *true* if command line processing succeeded and the runtime system was started successfully. It will return *false* otherwise.

```
inline bool hpx::start(std::function<int(int, char**)> f, int argc, char **argv, init_params const &params =  
    init_params())
```

Main non-blocking entry point for launching the HPX runtime system.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution. This overload will not call `hpx_main`.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as an HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.
- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::start` function (See documentation of `hpx::init_params`)

Returns

The function returns *true* if command line processing succeeded and the runtime system was started successfully. It will return *false* otherwise.

```
inline bool hpx::start(int argc, char **argv, init_params const &params = init_params())
```

Main non-blocking entry point for launching the HPX runtime system.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution. This overload will not call `hpx_main`.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as an HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the `parametermode`.

Parameters

- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::start` function (See documentation of `hpx::init_params`)

Returns

The function returns *true* if command line processing succeeded and the runtime system was started successfully. It will return *false* otherwise.

```
inline bool hpx::start(std::nullptr_t f, int argc, char **argv, init_params const &params = init_params())
```

Main non-blocking entry point for launching the HPX runtime system.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution. This overload will not call `hpx_main`.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as an HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the `parametermode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.
- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).

- **params** – [in] The parameters to the `hpx::start` function (See documentation of `hpx::init_params`)

Returns

The function returns *true* if command line processing succeeded and the runtime system was started successfully. It will return *false* otherwise.

```
inline bool hpx::start(init_params const &params = init_params())
```

Main non-blocking entry point for launching the HPX runtime system.

This is a simplified main, non-blocking entry point, which can be used to set up the runtime for an HPX application (the runtime system will be set up in console mode or worker mode depending on the command line settings). It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

This is the main, non-blocking entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as an HPX thread. It will return immediately after that. Use `hpx::wait` and `hpx::stop` to synchronize with the runtime system's execution.

Note: The created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. If not command line arguments are passed, console mode is assumed.

Note: If no command line arguments are passed the HPX runtime system will not support any of the default command line options as described in the section 'HPX Command Line Options'.

Parameters

params – [in] The parameters to the `hpx::start` function (See documentation of `hpx::init_params`)

Returns

The function returns *true* if command line processing succeeded and the runtime system was started successfully. It will return *false* otherwise.

hpx::suspend

Defined in header `hpx/init.hpp`⁵⁸¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::resume`

```
int hpx::suspend(error_code &ec = throws)
```

Suspend the runtime system.

The function `hpx::suspend` is used to suspend the HPX runtime system. It can only be used when running HPX on a single locality. It will block waiting for all thread pools to be empty. This function only be called when the runtime is running, or already suspended in which case this function will do nothing.

⁵⁸¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/init_runtime/include/hpx/init.hpp

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will always return zero.

hpx::resume

Defined in header [hpx/init.hpp](#)⁵⁸².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::suspend*

int **hpx::resume**(*error_code* &ec = *throws*)

Resume the HPX runtime system.

The function *hpx::resume* is used to resume the HPX runtime system. It can only be used when running HPX on a single locality. It will block waiting for all thread pools to be resumed. This function only be called when the runtime suspended, or already running in which case this function will do nothing.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will always return zero.

hpx::finalize

Defined in header [hpx/init.hpp](#)⁵⁸³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::disconnect*

int **hpx::finalize**(double shutdown_timeout, double localwait = -1.0, *hpx::error_code* &ec = *throws*)

Main function to gracefully terminate the HPX runtime system.

The function *hpx::finalize* is the main way to (gracefully) exit any HPX application. It must be called at least once, but can be called multiple times as well. However, only the first invocation will have effect. It will notify

⁵⁸² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/init_runtime/include/hpx/init.hpp

⁵⁸³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/init_runtime/include/hpx/init.hpp

all connected localities to finish execution. Only after all other localities have exited this function will return, allowing to exit the console locality as well.

During the execution of this function the runtime system will invoke all registered shutdown functions (see `hpx::init`) on all localities.

The default value (`-1.0`) will try to find a globally set timeout value (can be set as the configuration parameter `hpx.shutdown_timeout`), and if that is not set or `-1.0` as well, it will disable any timeout, each connected locality will wait for all existing HPX-threads to terminate.

The default value (`-1.0`) will try to find a globally set wait time value (can be set as the configuration parameter “`hpx.finalize_wait_time`”), and if this is not set or `-1.0` as well, it will disable any addition local wait time before proceeding.

This function will block and wait for all connected localities to exit before returning to the caller. It should be the last HPX-function called by any application.

Using this function is an alternative to `hpx::disconnect`, these functions do not need to be called both.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **shutdown_timeout** – This parameter allows to specify a timeout (in microseconds), specifying how long any of the connected localities should wait for pending tasks to be executed. After this timeout, all suspended HPX-threads will be aborted. Note, that this function will not abort any running HPX-threads. In any case the shutdown will not proceed as long as there is at least one pending/running HPX-thread.
- **localwait** – This parameter allows to specify a local wait time (in microseconds) before the connected localities will be notified and the overall shutdown process starts.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will always return zero.

```
inline int hpx::finalize(hpx::error_code &ec = throws)
```

Main function to gracefully terminate the HPX runtime system.

The function `hpx::finalize` is the main way to (gracefully) exit any HPX application. It must be called at least once, but can be called multiple times as well. However, only the first invocation will have effect. It will notify all connected localities to finish execution. Only after all other localities have exited this function will return, allowing to exit the console locality as well.

During the execution of this function the runtime system will invoke all registered shutdown functions (see `hpx::init`) on all localities.

This function will block and wait for all connected localities to exit before returning to the caller. It should be the last HPX-function called by any application.

Using this function is an alternative to `hpx::disconnect`, these functions do not need to be called both.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will always return zero.

`hpx::disconnect`

Defined in header `hpx/init.hpp`⁵⁸⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::finalize*

int **hpx::disconnect**(double shutdown_timeout, double localwait = -1.0, *hpx::error_code* &ec = *throws*)

Disconnect this locality from the application.

The function `hpx::disconnect` can be used to disconnect a locality from a running HPX application.

During the execution of this function the runtime system will invoke all registered shutdown functions (see `hpx::init`) on this locality.

The default value (-1.0) will try to find a globally set timeout value (can be set as the configuration parameter “`hpx.shutdown_timeout`”), and if that is not set or -1.0 as well, it will disable any timeout, each connected locality will wait for all existing HPX-threads to terminate.

The default value (-1.0) will try to find a globally set wait time value (can be set as the configuration parameter `hpx.finalize_wait_time`), and if this is not set or -1.0 as well, it will disable any addition local wait time before proceeding.

This function will block and wait for this locality to finish executing before returning to the caller. It should be the last HPX-function called by any locality being disconnected.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **shutdown_timeout** – This parameter allows to specify a timeout (in microseconds), specifying how long this locality should wait for pending tasks to be executed. After this timeout, all suspended HPX-threads will be aborted. Note, that this function will not abort any running HPX-threads. In any case the shutdown will not proceed as long as there is at least one pending/running HPX-thread.

⁵⁸⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/init_runtime/include/hpx/init.hpp

- **localwait** – This parameter allows to specify a local wait time (in microseconds) before the connected localities will be notified and the overall shutdown process starts.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will always return zero.

```
inline int hpx::disconnect(hpx::error_code &ec = throws)
```

Disconnect this locality from the application.

The function `hpx::disconnect` can be used to disconnect a locality from a running HPX application.

During the execution of this function the runtime system will invoke all registered shutdown functions (see `hpx::init`) on this locality.

This function will block and wait for this locality to finish executing before returning to the caller. It should be the last HPX-function called by any locality being disconnected.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will always return zero if successful, -1 otherwise.

```
int hpx::disconnect([[maybe_unused]] double shutdown_timeout, [[maybe_unused]] double localwait,  
[[maybe_unused]] error_code &ec)
```

hpx::init

Defined in header `hpx/init.hpp`⁵⁸⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
inline int hpx::init(std::function<int(hpx::program_options::variables_map&)> f, int argc, char **argv,  
init_params const &params = init_params())
```

Main entry point for launching the HPX runtime system.

This is the main entry point for any HPX application. This function (or one of its overloads) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by *f* as a HPX thread. This overload will not call `hpx_main`.

This is the main entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by *f* as a HPX thread.

⁵⁸⁵ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/init_runtime/include/hpx/init.hpp

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.
- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::init` function (See documentation of `hpx::init_params`)

Returns

The function returns the value, which has been returned from the user supplied `f`.

```
inline int hpx::init(std::function<int(int, char**)> f, int argc, char **argv, init_params const &params =
    init_params())
```

Main entry point for launching the HPX runtime system.

This is the main entry point for any HPX application. This function (or one of its overloads) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. This overload will not call `hpx_main`.

This is the main entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.
- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::init` function (See documentation of `hpx::init_params`)

Returns

The function returns the value, which has been returned from the user supplied `f`.

```
inline int hpx::init(int argc, char **argv, init_params const &params = init_params())
```

Main entry point for launching the HPX runtime system.

This is the main entry point for any HPX application. This function (or one of its overloads) should be called from the users `main()` function. This overload expects a user-defined function named `hpx_main` at global scope, which will be used as the entry point for the HPX application.

This is the main entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::init` function (See documentation of `hpx::init_params`)

Returns

The function returns the value, which has been returned from `hpx_main` (or 0 when executed in worker mode).

```
inline int hpx::init(std::nullptr_t f, int argc, char **argv, init_params const &params = init_params())
```

Main entry point for launching the HPX runtime system.

This is the main entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread. This overload will not call `hpx_main`.

This is the main entry point for any HPX application. This function (or one of its overloads below) should be called from the users `main()` function. It will set up the HPX runtime environment and schedule the function given by `f` as a HPX thread.

Note: If the parameter `mode` is not given (defaulted), the created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. Otherwise, it will be executed as specified by the parameter `mode`.

Parameters

- **f** – [in] The function to be scheduled as an HPX thread. Usually this function represents the main entry point of any HPX application. If `f` is `nullptr` the HPX runtime environment will be started without invoking `f`.

- **argc** – [in] The number of command line arguments passed in `argv`. This is usually the unchanged value as passed by the operating system (to `main()`).
- **argv** – [in] The command line arguments for this application, usually that is the value as passed by the operating system (to `main()`).
- **params** – [in] The parameters to the `hpx::init` function (See documentation of `hpx::init_params`)

Returns

The function returns the value, which has been returned from the user supplied `f`.

```
inline int hpx::init(init_params const &params = init_params())
```

Main entry point for launching the HPX runtime system.

This is a simplified main entry point, which can be used to set up the runtime for an HPX application (the runtime system will be set up in console mode or worker mode depending on the command line settings). This overload expects a user-defined function named `hpx_main` at global scope, which will be used as the entry point for the HPX application.

This is a simplified main entry point, which can be used to set up the runtime for an HPX application (the runtime system will be set up in console mode or worker mode depending on the command line settings).

Note: The created runtime system instance will be executed in console or worker mode depending on the command line arguments passed in `argc/argv`. If not command line arguments are passed, console mode is assumed.

Note: If no command line arguments are passed the HPX runtime system will not support any of the default command line options as described in the section ‘HPX Command Line Options’.

Parameters

params – [in] The parameters to the `hpx::init` function (See documentation of `hpx::init_params`)

Returns

The function returns the value, which has been returned from `hpx_main` (or 0 when executed in worker mode).

naming_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/naming_base/unmanaged.hpp

Defined in header `hpx/naming_base/unmanaged.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

`hpx::id_type unmanaged(hpx::id_type const &id)`

The helper function `hpx::unmanaged` can be used to generate a global identifier which does not participate in the automatic garbage collection.

Note: This function allows to apply certain optimizations to the process of memory management in HPX. It however requires the user to take full responsibility for keeping the referenced objects alive long enough.

Parameters

id – [in] The id to generated the unmanaged global id from This parameter can be itself a managed or a unmanaged global id.

Returns

This function returns a new global id referencing the same object as the parameter *id*. The only difference is that the returned global identifier does not participate in the automatic garbage collection.

namespace **naming**

parcelset

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/parcelset/parcelhandler.hpp

Defined in header `hpx/parcelset/parcelhandler.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/parcelset/parcelset_fwd.hpp

Defined in header `hpx/parcelset/parcelset_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/parcelset/connection_cache.hpp

Defined in header `hpx/parcelset/connection_cache.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/parcelset/message_handler_fwd.hpp

Defined in header `hpx/parcelset/message_handler_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

parcelset_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/parcelset_base/parcelport.hpp

Defined in header `hpx/parcelset_base/parcelport.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/parcelset_base/set_parcel_write_handler.hpp

Defined in header `hpx/parcelset_base/set_parcel_write_handler.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/parcelset_base/parcelset_base_fwd.hpp

Defined in header `hpx/parcelset_base/parcelset_base_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PARCELPORTR_BACKGROUND_MODE_ENUM_DEPRECATION_MSG

namespace **hpx**

namespace **parcelset**

Typedefs

```
using parcel_write_handler_type = hpx::function<bool(std::error_code const&, parcelset::parcel const&)>
```

The type of the function that can be registered as a parcel write handler using the function *hpx::set_parcel_write_handler*.

Note: A parcel write handler is a function which is called by the parcel layer whenever a parcel has been sent by the underlying networking library and if no explicit parcel handler function was specified for the parcel.

```
using write_handler_type = hpx::function<void(std::error_code const&, parcelset::parcel const&)>
```

Enums

```
enum class parcelport_background_mode : std::uint8_t
```

Type of background work to perform.

Values:

enumerator **flush_buffers**

perform buffer flush operations

enumerator **send**

perform send operations (includes buffer flush)

enumerator **receive**

perform receive operations

enumerator **all**

perform all operations

Functions

```
inline bool operator&(parcelport_background_mode lhs, parcelport_background_mode rhs)
```

```
char const *get_parcelport_background_mode_name(parcelport_background_mode mode)
```

Variables

parcel **empty_parcel**

constexpr *parcelport_background_mode* **parcelport_background_mode_flush_buffers** =
parcelport_background_mode::flush_buffers

constexpr *parcelport_background_mode* **parcelport_background_mode_send** =
parcelport_background_mode::send

constexpr *parcelport_background_mode* **parcelport_background_mode_receive** =
parcelport_background_mode::receive

constexpr *parcelport_background_mode* **parcelport_background_mode_all** =
parcelport_background_mode::all

plugin_factories

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/plugin_factories/message_handler_factory.hpp

Defined in header `hpx/plugin_factories/message_handler_factory.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/plugin_factories/plugin_registry.hpp

Defined in header `hpx/plugin_factories/plugin_registry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **plugins**

template<typename **Plugin**, char const *const **Name**, char const *const **Section**, char const *const **Suffix**>

struct **plugin_registry** : public *plugin_registry_base*

#include <plugin_registry.hpp> The *plugin_registry* provides a minimal implementation of a plugin's registry. If no additional functionality is required this type can be used to implement the full set of minimally required functions to be exposed by a plugin's registry instance.

Template Parameters

Plugin – The plugin type this registry should be responsible for.

Public Functions

inline bool **get_plugin_info**(*std::vector<std::string>* &fillini) override

Return the ini-information for all contained components.

Parameters

fillini – [in] The module is expected to fill this vector with the ini-information (one line per vector element) for all components implemented in this module.

Returns

Returns *true* if the parameter *fillini* has been successfully initialized with the registry data of all implemented in this module.

hpx/plugin_factories/binary_filter_factory.hpp

Defined in header `hpx/plugin_factories/binary_filter_factory.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **plugins**

template<typename **BinaryFilter**>

struct **binary_filter_factory** : public binary_filter_factory_base

#include <binary_filter_factory.hpp> The *message_handler_factory* provides a minimal implementation of a message handler's factory. If no additional functionality is required this type can be used to implement the full set of minimally required functions to be exposed by a message handler's factory instance.

Template Parameters

BinaryFilter – The message handler type this factory should be responsible for.

Public Functions

inline **binary_filter_factory**(*util::section* const *global, *util::section* const *local, bool isenabled)

Construct a new factory instance.

Note: The contents of both sections has to be cloned in order to save the configuration setting for later use.

Parameters

- **global** – [in] The pointer to a *hpx::util::section* instance referencing the settings read from the [settings] section of the global configuration file (`hpx.ini`) This pointer may be nullptr if no such section has been found.
- **local** – [in] The pointer to a *hpx::util::section* instance referencing the settings read from the section describing this component type: `[hpx.components.<name>]`, where `<name>` is the instance name of the component as given in the configuration files.
- **isenabled** –

~binary_filter_factory() override = default

```
inline serialization::binary_filter *create(bool compress, serialization::binary_filter *next_filter =
                                         nullptr) override
```

Create a new instance of a message handler

return Returns the newly created instance of the message handler supported by this factory

Protected Attributes

```
util::section global_settings_
```

```
util::section local_settings_
```

```
bool isEnabled_
```

hpx/plugin_factories/parcelport_factory.hpp

Defined in header `hpx/plugin_factories/parcelport_factory.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

resiliency_distributed

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/resiliency_distributed/async_replicate_distributed.hpp

Defined in header `hpx/resiliency_distributed/async_replicate_distributed.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace resiliency
```

```
        namespace experimental
```

Functions

```
template<typename Vote, typename Pred, typename Action, typename ...Ts>
decltype(auto) hpx_invoke(async_replicate_vote_validate_t, std::vector<hpx::id_type> const &ids,
                          Vote &&vote, Pred &&pred, Action &&action, Ts&&... ts)
```

ADL hook for distributed `async_replicate_vote_validate` CPO.

Asynchronously launches *action* on each locality in *ids*, validates results with *pred*, then runs valid results through *vote*.

Parameters

- **tag** – CPO tag (`async_replicate_vote_validate_t`).
- **ids** – Target localities (one invocation per locality).

- **vote** – Voting function selecting among valid results.
- **pred** – Predicate validating each invocation result.
- **action** – Action to invoke on each locality.
- **ts** – Arguments forwarded to *action*.

Returns

future with the voted-upon result.

```
template<typename Vote, typename Action, typename ...Ts>
decltype(auto) hpx_invoke(async_replicate_vote_t, std::vector<hpx::id_type> const &ids, Vote
&&vote, Action &&action, Ts&&... ts)
```

ADL hook for distributed *async_replicate_vote* CPO.

Asynchronously launches *action* on each locality in *ids*, runs valid results through *vote*. Validation uses the default exception check.

Parameters

- **tag** – CPO tag (*async_replicate_vote_t*).
- **ids** – Target localities (one invocation per locality).
- **vote** – Voting function selecting among valid results.
- **action** – Action to invoke on each locality.
- **ts** – Arguments forwarded to *action*.

Returns

future with the voted-upon result.

```
template<typename Pred, typename Action, typename ...Ts>
decltype(auto) hpx_invoke(async_replicate_validate_t, std::vector<hpx::id_type> const &ids, Pred
&&pred, Action &&action, Ts&&... ts)
```

ADL hook for distributed *async_replicate_validate* CPO.

Asynchronously launches *action* on each locality in *ids*, validates results with *pred*. Returns the first valid result.

Parameters

- **tag** – CPO tag (*async_replicate_validate_t*).
- **ids** – Target localities (one invocation per locality).
- **pred** – Predicate validating each invocation result.
- **action** – Action to invoke on each locality.
- **ts** – Arguments forwarded to *action*.

Returns

future with the first valid result.

```
template<typename Action, typename ...Ts>
decltype(auto) hpx_invoke(async_replicate_t, std::vector<hpx::id_type> const &ids, Action
&&action, Ts&&... ts)
```

ADL hook for distributed *async_replicate* CPO.

Asynchronously launches *action* on each locality in *ids*. Validates by checking for exceptions. Returns the first valid result.

Parameters

- **tag** – CPO tag (*async_replicate_t*).
- **ids** – Target localities (one invocation per locality).
- **action** – Action to invoke on each locality.
- **ts** – Arguments forwarded to *action*.

Returns

future with the first non-throwing result.

hpx/resiliency_distributed/async_replay_distributed.hpp

Defined in header `hpx/resiliency_distributed/async_replay_distributed.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **resiliency**

namespace **experimental**

Functions

```
template<typename Action, typename ...Ts>
hpx::future<hpx::util::detail::invoke_deferred_result_t<Action, hpx::id_type, Ts...>> hpx_invoke(async_replay_t,
                                                                                               std::vector<hpx::id_
                                                                                               const
                                                                                               &ids,
                                                                                               Ac-
                                                                                               tion
                                                                                               &&ac-
                                                                                               tion,
                                                                                               Ts&&...
                                                                                               ts)
```

ADL hook for distributed `async_replay` CPO.

Asynchronously launches *action* on localities in *ids*, replaying on the next locality on error (aborts on `abort_replay_exception`).

Parameters

- **tag** – CPO tag (`async_replay_t`).
- **ids** – Target localities to try in order.
- **action** – Action to invoke on each locality.
- **ts** – Arguments forwarded to *action*.

Returns

future with the first successful result.

```
template<typename Pred, typename Action, typename ...Ts>
hpx::future<hpx::util::detail::invoke_deferred_result_t<Action, hpx::id_type, Ts...>> hpx_invoke(async_replay_validate
                                                                                               std::vector<hpx::id_
                                                                                               const
                                                                                               &ids,
                                                                                               Pred
                                                                                               &&pred,
                                                                                               Ac-
                                                                                               tion
                                                                                               &&ac-
                                                                                               tion,
                                                                                               Ts&&...
                                                                                               ts)
```

ADL hook for distributed `async_replay_validate` CPO.

Asynchronously launches *action* on localities in *ids*, validating results with *pred*. Replays on the next locality on error (aborts on `abort_replay_exception`).

Parameters

- **tag** – CPO tag (`async_replay_validate_t`).
- **ids** – Target localities to try in order.
- **pred** – Predicate validating each invocation result.
- **action** – Action to invoke on each locality.
- **ts** – Arguments forwarded to *action*.

Returns

future with the first valid result.

runtime_components

See *Public API* for a list of names and headers that are part of the public *HPX* API.

HPX_REGISTER_COMPONENT

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Warning: doxygenfunction: Cannot find function “HPX_REGISTER_COMPONENT” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

hpx/runtime_components/component_registry.hpp

Defined in header `hpx/runtime_components/component_registry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

template<typename **Component**, *factory_state* **state**>

struct **component_registry** : public *component_registry_base*

#include <component_registry.hpp> The `component_registry` provides a minimal implementation of a component’s registry. If no additional functionality is required this type can be used to implement the full set of minimally required functions to be exposed by a component’s registry instance.

Template Parameters

Component – The component type this registry should be responsible for.

Public Functions

inline bool **get_component_info**(*std::vector<std::string> &fillini*, *std::string const &filepath*, bool *is_static = false*) override

Return the ini-information for all contained components.

Parameters

- **fillini** – [in] The module is expected to fill this vector with the ini-information (one line per vector element) for all components implemented in this module.
- **filepath** –
- **is_static** –

Returns

Returns *true* if the parameter *fillini* has been successfully initialized with the registry data of all implemented in this module.

inline void **register_component_type**() override

Enables this type of registry and sets its destroy mechanism.

hpx/runtime_components/reflect_client_macros.hpp

Defined in header `hpx/runtime_components/reflect_client_macros.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/runtime_components/reflect_client.hpp

Defined in header `hpx/runtime_components/reflect_client.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/runtime_components/components_fwd.hpp

Defined in header `hpx/runtime_components/components_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

components::server::runtime_support ***get_runtime_support_ptr**()

namespace **components**

template<typename **Component**>

struct **component_factory**

namespace **server**

namespace **stubs**

namespace **components**

hpx::new_

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename Component, typename ...Ts>  
auto hpx::new_(id_type const &locality, Ts&&... vs)
```

Create one or more new instances of the given *Component* type on the specified locality.

This function creates one or more new instances of the given *Component* type on the specified locality and returns a future object for the global address which can be used to reference the new component instance.

Note: This function requires to specify an explicit template argument which will define what type of component(s) to create, for instance:

```
hpx::future<hpx::id_type> f =  
    hpx::new_<some_component>(hpx::find_here(), ...);  
hpx::id_type id = f.get();
```

Parameters

- **locality** – [in] The global address of the locality where the new instance should be created on.
- **vs** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the constructor of the created component instance.

Returns

The function returns different types depending on its use:

- If the explicit template argument *Component* represents a component type (`traits::is_component<Component>::value` evaluates to true), the function will return an `hpx::future` object instance which can be used to retrieve the global address of the newly created component.
- If the explicit template argument *Component* represents a client side object (`traits::is_client<Component>::value` evaluates to true), the function will return a new instance of that type which can be used to refer to the newly created component instance.

```
template<typename Component, typename ...Ts>  
auto hpx::new_(id_type const &locality, std::size_t count, Ts&&... vs)
```

Create multiple new instances of the given *Component* type on the specified locality.

This function creates multiple new instances of the given *Component* type on the specified locality and returns a future object for the global address which can be used to reference the new component instance.

Note: This function requires to specify an explicit template argument which will define what type of component(s) to create, for instance:

```
hpx::future<std::vector<hpx::id_type> > f =
    hpx::new_<some_component[]>(hpx::find_here(), 10, ...);
hpx::id_type id = f.get();
```

Parameters

- **locality** – [in] The global address of the locality where the new instance should be created on.
- **count** – [in] The number of component instances to create
- **vs** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the constructor of the created component instance.

Returns

The function returns different types depending on its use:

- If the explicit template argument *Component* represents an array of a component type (i.e. *Component*[], where `traits::is_component<Component>::value` evaluates to true), the function will return an `hpx::future` object instance which holds a `std::vector<hpx::id_type>`, where each of the items in this vector is a global address of one of the newly created components.
- If the explicit template argument *Component* represents an array of a client side object type (i.e. *Component*[], where `traits::is_client<Component>::value` evaluates to true), the function will return an `hpx::future` object instance which holds a `std::vector<hpx::id_type>`, where each of the items in this vector is a client side instance of the given type, each representing one of the newly created components.

```
template<typename Component, typename DistPolicy, typename ...Ts>
auto hpx::new_(DistPolicy const &policy, Ts&&... vs)
```

Create one or more new instances of the given *Component* type based on the given distribution policy.

This function creates one or more new instances of the given *Component* type on the localities defined by the given distribution policy and returns a future object for global address which can be used to reference the new component instance(s).

Note: This function requires to specify an explicit template argument which will define what type of component(s) to create, for instance:

```
hpx::future<hpx::id_type> f =
    hpx::new_<some_component>(hpx::default_layout, ...);
hpx::id_type id = f.get();
```

Parameters

- **policy** – [in] The distribution policy used to decide where to place the newly created.
- **vs** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the constructor of the created component instance.

Returns

The function returns different types depending on its use:

- If the explicit template argument *Component* represents a component type (`traits::is_component<Component>::value` evaluates to true), the function will return an `hpx::future` object instance which can be used to retrieve the global address of the newly created component.
- If the explicit template argument *Component* represents a client side object (`traits::is_client<Component>::value` evaluates to true), the function will return a new instance of that type which can be used to refer to the newly created component instance.

```
template<typename Component, typename DistPolicy, typename ...Ts>  
auto hpx::new_(DistPolicy const &policy, std::size_t count, Ts&&... vs)
```

Create multiple new instances of the given *Component* type on the localities as defined by the given distribution policy.

This function creates multiple new instances of the given *Component* type on the localities defined by the given distribution policy and returns a future object for the global address which can be used to reference the new component instance.

Note: This function requires to specify an explicit template argument which will define what type of component(s) to create, for instance:

```
hpx::future<std::vector<hpx::id_type> > f =  
    hpx::new_<some_component[]>(hpx::default_layout, 10, ...);  
hpx::id_type id = f.get();
```

Parameters

- **policy** – [in] The distribution policy used to decide where to place the newly created.
- **count** – [in] The number of component instances to create
- **vs** – [in] Any number of arbitrary arguments (passed by value, by const reference or by rvalue reference) which will be forwarded to the constructor of the created component instance.

Returns

The function returns different types depending on its use:

- If the explicit template argument *Component* represents an array of a component type (i.e. *Component*[], where `traits::is_component<Component>::value` evaluates to true), the function will return an `hpx::future` object instance which holds a `std::vector<hpx::id_type>`, where each of the items in this vector is a global address of one of the newly created components.
- If the explicit template argument *Component* represents an array of a client side object type (i.e. *Component*[], where `traits::is_client<Component>::value` evaluates to true), the function will return an `hpx::future` object instance which holds a `std::vector<hpx::id_type>`, where each of the items in this vector is a client side instance of the given type, each representing one of the newly created components.

hpx/runtime_components/macros.hpp

Defined in header `hpx/runtime_components/macros.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY(...)

HPX_REGISTER_COMPONENT(...)

HPX_REGISTER_ENABLED_COMPONENT_FACTORY(ComponentType, componentname)

HPX_REGISTER_DISABLED_COMPONENT_FACTORY(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_1(...)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_1(ComponentType)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_2(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_3(ComponentType, componentname, state)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_DYNAMIC(...)

HPX_REGISTER_COMPONENT_DYNAMIC(...)

This macro is used create and to register a minimal component factory for a component type which allows it to be remotely created using the `hpx::new_<>` function. This macro can be invoked with one, two or three arguments

HPX_REGISTER_ENABLED_COMPONENT_FACTORY_DYNAMIC(ComponentType, componentname)

HPX_REGISTER_DISABLED_COMPONENT_FACTORY_DYNAMIC(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_DYNAMIC_1(...)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_DYNAMIC_1(ComponentType)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_DYNAMIC_2(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_FACTORY_DYNAMIC_3(ComponentType, componentname, state)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY(...)

This macro is used create and to register a minimal component registry with `Hpx.Plugin`.

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_1(...)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_2(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_3(ComponentType, componentname, state)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_DYNAMIC(...)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_DYNAMIC_1(...)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_DYNAMIC_2(ComponentType, componentname)

HPX_REGISTER_MINIMAL_COMPONENT_REGISTRY_DYNAMIC_3(ComponentType, componentname, state)

HPX_REGISTER_DERIVED_COMPONENT_FACTORY(...)

This macro is used create and to register a minimal component factory with `Hpx.Plugin`. This macro may be used if the registered component factory is the only factory to be exposed from a particular module. If more than one factory needs to be exposed the `HPX_REGISTER_COMPONENT_FACTORY` and `HPX_REGISTER_COMPONENT_MODULE` macros should be used instead.

HPX_REGISTER_DERIVED_COMPONENT_FACTORY_(...)**HPX_REGISTER_DERIVED_COMPONENT_FACTORY_3**(ComponentType, componentname, basecomponentname)**HPX_REGISTER_DERIVED_COMPONENT_FACTORY_4**(ComponentType, componentname, basecomponentname, state)**HPX_REGISTER_DERIVED_COMPONENT_FACTORY_DYNAMIC(...)****HPX_REGISTER_DERIVED_COMPONENT_FACTORY_DYNAMIC_(...)****HPX_REGISTER_DERIVED_COMPONENT_FACTORY_DYNAMIC_3**(ComponentType, componentname,
basecomponentname)**HPX_REGISTER_DERIVED_COMPONENT_FACTORY_DYNAMIC_4**(ComponentType, componentname,
basecomponentname, state)**HPX_DISTRIBUTED_METADATA_DECLARATION(...)****HPX_DISTRIBUTED_METADATA_DECLARATION_(...)****HPX_DISTRIBUTED_METADATA_DECLARATION_1**(config)**HPX_DISTRIBUTED_METADATA_DECLARATION_2**(config, name)**HPX_DISTRIBUTED_METADATA(...)****HPX_DISTRIBUTED_METADATA_(...)****HPX_DISTRIBUTED_METADATA_1**(config)**HPX_DISTRIBUTED_METADATA_2**(config, name)**runtime_distributed**

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/runtime_distributed.hpp

Defined in header `hpx/runtime_distributed.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

class **runtime_distributed**: public *runtime*

#include <runtime_distributed.hpp> The *runtime* class encapsulates the HPX runtime system in a simple to use way. It makes sure all required parts of the HPX runtime system are properly initialized.

Public Functions

explicit **runtime_distributed**(util::runtime_configuration &rtcfg, int (*pre_main)(runtime_mode) = nullptr, void (*post_main)() = nullptr)

Construct a new HPX runtime instance

Parameters

- **rtcfg** – Runtime configuration for this instance
- **pre_main** – Function to be called before running the main action of this instance
- **post_main** – Function to be called after running the main action of this instance

~runtime_distributed()

The destructor makes sure all HPX runtime services are properly shut down before exiting.

int **start**(hpx::function<hpx_main_function_type> const &func, bool blocking = false) override

Start the runtime system.

Parameters

- **func** – [in] This is the main function of an HPX application. It will be scheduled for execution by the thread manager as soon as the runtime has been initialized. This function is expected to expose an interface as defined by the typedef *hpx_main_function_type*.
- **blocking** – [in] This allows to control whether this call blocks until the runtime system has been stopped. If this parameter is *true* the function *runtime::start* will call *runtime::wait* internally.

Returns

If a blocking is a true, this function will return the value as returned as the result of the invocation of the function object given by the parameter *func*. Otherwise it will return zero.

int **start**(bool blocking = false) override

Start the runtime system.

Parameters

blocking – [in] This allows to control whether this call blocks until the runtime system has been stopped. If this parameter is *true* the function *runtime::start* will call *runtime::wait* internally .

Returns

If a blocking is a true, this function will return the value as returned as the result of the invocation of the function object given by the parameter *func*. Otherwise it will return zero.

int **wait**() override

Wait for the shutdown action to be executed.

Returns

This function will return the value as returned as the result of the invocation of the function object given by the parameter *func*.

void **stop**(bool blocking = true) override

Initiate termination of the runtime system.

Parameters

blocking – [in] This allows to control whether this call blocks until the runtime system has been fully stopped. If this parameter is *false* then this call will initiate the stop action but will return immediately. Use a second call to stop with this parameter set to *true* to wait for all internal work to be completed.

int **finalize**(double shutdown_timeout) override

void **stop_helper**(bool blocking, std::condition_variable &cond, std::mutex &mtx)

Stop the runtime system, wait for termination.

Parameters

- **blocking** – [in] This allows to control whether this call blocks until the runtime system has been fully stopped. If this parameter is *false* then this call will initiate the stop action but will return immediately. Use a second call to stop with this parameter set to *true* to wait for all internal work to be completed.
- **cond** – Condition used to update all thread when done
- **mtx** – Mutex used by this function to sync all threads

int **suspend**() override

Suspend the runtime system.

int **resume**() override

Resume the runtime system.

bool **report_error**(std::size_t num_thread, std::exception_ptr const &e, bool terminate_all = true) override

Report a non-recoverable error to the runtime system.

Parameters

- **num_thread** – [in] The number of the operating system thread the error has been detected in.
- **e** – [in] This is an instance encapsulating an exception which lead to this function call.
- **terminate_all** – [in] Kill all localities attached to the currently running application (default: true)

bool **report_error**(std::exception_ptr const &e, bool terminate_all = true) override

Report a non-recoverable error to the runtime system.

Note: This function will retrieve the number of the current shepherd thread and forward to the `report_error` function above.

Parameters

- **e** – [in] This is an instance encapsulating an exception which lead to this function call.
- **terminate_all** – [in] Kill all localities attached to the currently running application (default: true)

int **run**(hpx::function<hpx_main_function_type> const &func) override

Run the HPX runtime system, use the given function for the main *thread* and block waiting for all threads to finish.

Note: The parameter *func* is optional. If no function is supplied, the runtime system will simply wait for the shutdown action without explicitly executing any main thread.

Parameters

func – [in] This is the main function of an HPX application. It will be scheduled for execution by the thread manager as soon as the runtime has been initialized. This function is expected to expose an interface as defined by the typedef *hpx_main_function_type*. This parameter is optional and defaults to none main thread function, in which case all threads have to be scheduled explicitly.

Returns

This function will return the value as returned as the result of the invocation of the function object given by the parameter *func*.

int **run()** override

Run the HPX runtime system, initially use the given number of (OS) threads in the thread-manager and block waiting for all threads to finish.

Returns

This function will always return 0 (zero).

bool **is_networking_enabled()** override

template<typename **F**>

inline *components::server::console_error_dispatcher::sink_type* **set_error_sink**(*F* &&sink)

performance_counters::registry &**get_counter_registry**()

Allow access to the registry counter registry instance used by the HPX runtime.

performance_counters::registry const &**get_counter_registry**() const

Allow access to the registry counter registry instance used by the HPX runtime.

void **register_query_counters**(*std::shared_ptr<util::query_counters>* const &active_counters)

void **start_active_counters**(*error_code* &ec = *throws*) const

void **stop_active_counters**(*error_code* &ec = *throws*) const

void **reset_active_counters**(*error_code* &ec = *throws*) const

void **reinit_active_counters**(bool reset = true, *error_code* &ec = *throws*) const

void **evaluate_active_counters**(bool reset = false, char const *description = nullptr, *error_code* &ec = *throws*) const

void **stop_evaluating_counters**(bool terminate = false) const

agas::addressing_service &**get_agas_client**()

Allow access to the AGAS client instance used by the HPX runtime.

hpx::threads::threadmanager &**get_thread_manager**() override

Allow access to the thread manager instance used by the HPX runtime.

applier::applier &**get_applier**()

Allow access to the applier instance used by the HPX runtime.

std::string **here**() const override

Returns a string of the locality endpoints (usable in debug output)

naming::address_type **get_runtime_support_lva**() const

naming::gid_type **get_next_id**(*std::size_t* count = 1)

void **init_id_pool_range**()

util::unique_id_ranges &**get_id_pool**()

void **initialize_agas**()

Initialize AGAS operation.

void **add_pre_startup_function**(*startup_function_type* f) override

Add a function to be executed inside a HPX thread before `hpx_main` but guaranteed to be executed before any startup function registered with `add_startup_function`.

Note: The difference to a startup function is that all pre-startup functions will be (system-wide) executed before any startup function.

Parameters

f – The function ‘f’ will be called from inside a HPX thread before `hpx_main` is executed. This is very useful to setup the runtime environment of the application (install performance counters, etc.)

void **add_startup_function**(*startup_function_type* f) override

Add a function to be executed inside a HPX thread before `hpx_main`

Parameters

f – The function ‘f’ will be called from inside a HPX thread before `hpx_main` is executed. This is very useful to setup the runtime environment of the application (install performance counters, etc.)

void **add_pre_shutdown_function**(*shutdown_function_type* f) override

Add a function to be executed inside a HPX thread during `hpx::finalize`, but guaranteed before any of the shutdown functions is executed.

Note: The difference to a shutdown function is that all pre-shutdown functions will be (system-wide) executed before any shutdown function.

Parameters

f – The function ‘f’ will be called from inside a HPX thread while `hpx::finalize` is executed. This is very useful to tear down the runtime environment of the application (uninstall performance counters, etc.)

void **add_shutdown_function**(*shutdown_function_type* f) override

Add a function to be executed inside a HPX thread during `hpx::finalize`

Parameters

f – The function ‘f’ will be called from inside a HPX thread while `hpx::finalize` is executed. This is very useful to tear down the runtime environment of the application (uninstall performance counters, etc.)

hpx::util::io_service_pool ***get_thread_pool**(char const *name) override

Access one of the internal thread pools (`io_service` instances) HPX is using to perform specific tasks. The three possible values for the argument `name` are “`main_pool`”, “`io_pool`”, “`parcel_pool`”, and “`timer_pool`”. For any other argument value the function will return zero.

bool **register_thread**(char const *name, *std::size_t* num = 0, bool service_thread = true, *error_code* &ec = *throws*) override

Register an external OS-thread with HPX.

notification_policy_type **get_notification_policy**(char const *prefix, *runtime_local::os_thread_type* type) override

Generate a new notification policy instance for the given thread name `prefix`

std::uint32_t **get_locality_id**(*error_code* &ec) const override

```

std::size_t get_num_worker_threads() const override
std::uint32_t get_num_localities(hpx::launch::sync_policy, error_code &ec) const override
std::uint32_t get_initial_num_localities() const override
hpx::future<std::uint32_t> get_num_localities() const override
std::string get_locality_name() const override
std::uint32_t get_num_localities(hpx::launch::sync_policy, components::component_type type,
                                error_code &ec) const
hpx::future<std::uint32_t> get_num_localities(components::component_type type) const
std::uint32_t assign_cores(std::string const &locality_basename, std::uint32_t num_threads) override
std::uint32_t assign_cores() override

```

Public Static Functions

```

static void register_counter_types()
    Install all performance counters related to this runtime instance.

```

Private Types

```

using used_cores_map_type = std::map<std::string, std::uint32_t>

```

Private Functions

```

threads::thread_result_type run_helper(hpx::function<runtime::hpx_main_function_type> const
                                         &func, int &result)
void init_global_data()
void deinit_global_data()
void wait_helper(std::mutex &mtx, std::condition_variable &cond, bool &running)
void init_tss_helper(char const *context, runtime_local::os_thread_type type, std::size_t
                    local_thread_num, std::size_t global_thread_num, char const *pool_name, char
                    const *postfix, bool service_thread)
void deinit_tss_helper(char const *context, std::size_t num) const
void init_tss_ex(std::string const &locality, char const *context, runtime_local::os_thread_type type,
                 std::size_t local_thread_num, std::size_t global_thread_num, char const
                 *pool_name, char const *postfix, bool service_thread, error_code &ec) const

```

Private Members

runtime_mode **mode_**

util::unique_id_ranges **id_pool_**

agas::addressing_service **agas_client_**

applier::applier **applier_**

used_cores_map_type **used_cores_map_**

std::unique_ptr<components::server::runtime_support> **runtime_support_**

std::shared_ptr<util::query_counters> **active_counters_**

int (***pre_main_**)(*runtime_mode*)

void (***post_main_**())

Private Static Functions

static void **default_errorsink**(*std::string const&*)

hpx/runtime_distributed/applier.hpp

Defined in header `hpx/runtime_distributed/applier.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **applier**

class **applier**

#include <applier.hpp> The *applier* class is used to decide whether a particular action has to be issued on a local or a remote resource. If the target component is local a new *thread* will be created, if the target is remote a parcel will be sent.

Public Functions

applier(*applier* const&) = delete

applier(*applier*&&) = delete

applier &**operator**=(*applier* const&) = delete

applier &**operator**=(*applier*&&) = delete

applier()

void **init**(*threads::threadmanager* &tm)

~applier() = default

void **initialize**(*std::uint64_t* rts)

threads::threadmanager &**get_thread_manager**()

Access the *thread-manager* instance associated with this *applier*.

This function returns a reference to the thread manager this *applier* instance has been created with.

naming::gid_type const &**get_raw_locality**(*error_code* &ec = *throws*) const

Allow access to the locality of the locality this *applier* instance is associated with.

This function returns a reference to the locality this *applier* instance is associated with.

std::uint32_t **get_locality_id**(*error_code* &ec = *throws*) const

Allow access to the id of the locality this *applier* instance is associated with.

This function returns a reference to the id of the locality this *applier* instance is associated with.

bool **get_raw_remote_localities**(*std::vector<naming::gid_type>* &locality_ids,
components::component_type type =
to_int(hpx::components::component_enum_type::invalid),
error_code &ec = *throws*) const

Return list of localities of all remote localities registered with the AGAS service for a specific component type.

This function returns a list of all remote localities (all localities known to AGAS except the local one) supporting the given component type.

Parameters

- **locality_ids** – [out] The reference to a vector of *id_types* filled by the function.
- **type** – [in] The type of the component which needs to exist on the returned localities.

Returns

The function returns *true* if there is at least one remote locality known to the AGAS service (!*prefixes.empty()*).

bool **get_remote_localities**(*std::vector<hpx::id_type>* &locality_ids,
components::component_type type =
to_int(hpx::components::component_enum_type::invalid),
error_code &ec = *throws*) const

bool **get_raw_localities**(*std::vector<naming::gid_type>* &locality_ids,
components::component_type type =
to_int(hpx::components::component_enum_type::invalid)) const

Return list of `locality_ids` of all localities registered with the AGAS service for a specific component type.

This function returns a list of all localities (all localities known to AGAS except the local one) supporting the given component type.

Parameters

- **locality_ids** – [out] The reference to a vector of `id_types` filled by the function.
- **type** – [in] The type of the component which needs to exist on the returned localities.

Returns

The function returns *true* if there is at least one remote locality known to the AGAS service (!`prefixes.empty()`).

```
bool get_localities(std::vector<hpx::id_type> &locality_ids, error_code &ec = throws) const
```

```
bool get_localities(std::vector<hpx::id_type> &locality_ids, components::component_type  
                    type, error_code &ec = throws) const
```

```
inline naming::gid_type const &get_runtime_support_raw_gid() const
```

By convention the `runtime_support` has a `gid` identical to the prefix of the locality the `runtime_support` is responsible for

```
inline hpx::id_type const &get_runtime_support_gid() const
```

By convention the `runtime_support` has a `gid` identical to the prefix of the locality the `runtime_support` is responsible for

Private Members

```
threads::threadmanager *thread_manager_
```

```
hpx::id_type runtime_support_id_
```

hpx/runtime_distributed/migrate_component.hpp

Defined in header `hpx/runtime_distributed/migrate_component.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace components
```


Functions

```
template<typename Component, typename DistPolicy>
future<hpx::id_type> migrate(hpx::id_type const &to_migrate, [[maybe_unused]] DistPolicy const
&policy)
```

Migrate the given component to the specified target locality

The function *migrate*<*Component*> will migrate the component referenced by *to_migrate* to the locality specified with *target_locality*. It returns a future referring to the migrated component instance.

Parameters

- **to_migrate** – [in] The client side representation of the component to migrate.
- **policy** – [in] A distribution policy which will be used to determine the locality to migrate this object to.

Template Parameters

- **Component** – Specifies the component type of the component to migrate.
- **DistPolicy** – Specifies the distribution policy to use to determine the destination locality.

Returns

A future representing the global id of the migrated component instance. This should be the same as *migrate_to*.

```
template<typename Derived, typename Stub, typename Data, typename DistPolicy>
Derived migrate(client_base<Derived, Stub, Data> const &to_migrate, DistPolicy const &policy)
```

Migrate the given component to the specified target locality

The function *migrate*<*Component*> will migrate the component referenced by *to_migrate* to the locality specified with *target_locality*. It returns a future referring to the migrated component instance.

Parameters

- **to_migrate** – [in] The client side representation of the component to migrate.
- **policy** – [in] A distribution policy which will be used to determine the locality to migrate this object to.

Template Parameters

- **Derived** – Specifies the component type of the component to migrate.
- **DistPolicy** – Specifies the distribution policy to use to determine the destination locality.

Returns

A future representing the global id of the migrated component instance. This should be the same as *migrate_to*.

```
template<typename Component>
future<hpx::id_type> migrate(hpx::id_type const &to_migrate, hpx::id_type const &target_locality)
```

Migrate the component with the given id to the specified target locality

The function *migrate*<*Component*> will migrate the component referenced by *to_migrate* to the locality specified with *target_locality*. It returns a future referring to the migrated component instance.

Parameters

- **to_migrate** – [in] The global id of the component to migrate.
- **target_locality** – [in] The locality where the component should be migrated to.

Template Parameters

Component – Specifies the component type of the component to migrate.

Returns

A future representing the global id of the migrated component instance. This should be the same as *migrate_to*.

```
template<typename Derived, typename Stub, typename Data>
Derived migrate(client_base<Derived, Stub, Data> const &to_migrate, hpx::id_type const
&target_locality)
```

Migrate the given component to the specified target locality

The function *migrate*<*Component*> will migrate the component referenced by *to_migrate* to the locality specified with *target_locality*. It returns a future referring to the migrated component instance.

Parameters

- **to_migrate** – [in] The client side representation of the component to migrate.
- **target_locality** – [in] The id of the locality to migrate this object to.

Template Parameters

Derived – Specifies the component type of the component to migrate.

Returns

A client side representation of representing of the migrated component instance. This should be the same as *migrate_to*.

hpx/runtime_distributed/get_locality_name.hpp

Defined in header `hpx/runtime_distributed/get_locality_name.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

future<*std::string*> **get_locality_name**(*hpx::id_type* const &id)

Return the name of the referenced locality.

This function returns a future referring to the name for the locality of the given id.

See also:

std::string *get_locality_name*()

Parameters

id – [in] The global id of the locality for which the name should be retrieved

Returns

This function returns the name for the locality of the given id. The name is retrieved from the underlying networking layer and may be different for different parcel ports.

hpx/runtime_distributed/find_here.hpp

Defined in header `hpx/runtime_distributed/find_here.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

`hpx::id_type` **find_here**(*error_code* &*ec* = *throws*)

Return the global id representing this locality.

The function `find_here()` can be used to retrieve the global id usable to refer to the current locality.

See also:

`hpx::find_all_localities()`, `hpx::find_locality()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of `hpx::exception`.

Note: This function will return meaningful results only if called from an HPX-thread. It will return `hpx::invalid_id` otherwise.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Returns

The global id representing the locality this function has been called on.

`hpx/runtime_distributed/runtime_support.hpp`

Defined in header `hpx/runtime_distributed/runtime_support.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **agas**

Functions

struct `runtime_components_init_interface_functions` &**runtime_components_init**()

namespace **components**

Functions

struct counter_interface_functions &**counter_init**()

class **runtime_support** : public *hpx::components::stubs::runtime_support*
#include <runtime_support.hpp> The *runtime_support* class is the client side representation of a *server::runtime_support* component

Public Functions

inline **runtime_support**(*hpx::id_type* const &gid = *hpx::invalid_id*)

Create a client side representation for the existing *server::runtime_support* instance with the given global id *gid*.

template<typename **Component**, typename ...**Ts**>
inline *hpx::id_type* **create_component**(*Ts*&&... vs)

Create a new component type using the *runtime_support*.

template<typename **Component**, typename ...**Ts**>
inline *hpx::future*<*hpx::id_type*> **create_component_async**(*Ts*&&... vs)

Asynchronously create a new component using the *runtime_support*.

template<bool **WithCount**, typename **Component**, typename ...**Ts**>
inline *std::vector*<*hpx::id_type*> **bulk_create_component**(*std::size_t* count, *Ts*&&... vs)

Asynchronously create N new default constructed components using the *runtime_support*

template<bool **WithCount**, typename **Component**, typename ...**Ts**>
inline *hpx::future*<*std::vector*<*hpx::id_type*>> **bulk_create_components_async**(*std::size_t* count, *Ts*&&... vs)

Asynchronously create a new component using the *runtime_support*.

inline *hpx::future*<int> **load_components_async**() const

inline int **load_components**() const

inline *hpx::future*<void> **call_startup_functions_async**(bool pre_startup) const

inline void **call_startup_functions**(bool pre_startup) const

inline *hpx::future*<void> **shutdown_async**(double timeout = -1) const
Shutdown the given runtime system.

inline void **shutdown**(double timeout = -1) const

inline void **shutdown_all**(double timeout = -1) const
Shutdown the runtime systems of all localities.

inline *hpx::future*<void> **terminate_async**() const
Terminate the given runtime system.

inline void **terminate**() const

inline void **terminate_all**() const
Terminate the runtime systems of all localities.

```
inline void get_config(util::section &ini) const
    Retrieve configuration information.

inline hpx::id_type const &get_id() const

inline naming::gid_type const &get_raw_gid() const
```

Private Types

```
using base_type = stubs::runtime_support
```

Private Members

```
hpx::id_type gid_
```

hpx/runtime_distributed/copy_component.hpp

Defined in header `hpx/runtime_distributed/copy_component.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace components
```

Functions

```
template<typename Component>
future<hpx::id_type> copy(hpx::id_type const &to_copy)
```

Copy given component to the specified target locality.

The function `copy<Component>` will create a copy of the component referenced by `to_copy` on the locality specified with `target_locality`. It returns a future referring to the newly created component instance.

Note: The new component instance is created on the locality of the component instance which is to be copied.

Parameters

to_copy – [in] The global id of the component to copy

Template Parameters

The – only template argument specifies the component type to create.

Returns

A future representing the global id of the newly (copied) component instance.

```
template<typename Component>
```

future<hpx::id_type> **copy**(hpx::id_type const &to_copy, hpx::id_type const &target_locality)

Copy given component to the specified target locality.

The function *copy*<*Component*> will create a copy of the component referenced by *to_copy* on the locality specified with *target_locality*. It returns a future referring to the newly created component instance.

Parameters

- **to_copy** – [in] The global id of the component to copy
- **target_locality** – [in] The locality where the copy should be created.

Template Parameters

The – only template argument specifies the component type to create.

Returns

A future representing the global id of the newly (copied) component instance.

template<typename **Derived**, typename **Stub**, typename **Data**>
Derived **copy**(*client_base*<*Derived*, *Stub*, *Data*> const &to_copy, hpx::id_type const &target_locality =
hpx::invalid_id)

Copy given component to the specified target locality.

The function *copy* will create a copy of the component referenced by the client side object *to_copy* on the locality specified with *target_locality*. It returns a new client side object future referring to the newly created component instance.

Note: If the second argument is omitted (or is *invalid_id*) the new component instance is created on the locality of the component instance which is to be copied.

Parameters

- **to_copy** – [in] The client side object representing the component to copy
- **target_locality** – [in, optional] The locality where the copy should be created (default is same locality as source).

Template Parameters

The – only template argument specifies the component type to create.

Returns

A future representing the global id of the newly (copied) component instance.

hpx::find_root_locality

Defined in header [hpx/runtime.hpp](#)⁵⁸⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::find_all_localities*
- *hpx::find_remote_localities*

hpx::id_type **hpx::find_root_locality**(*error_code* &ec = *throws*)

Return the global id representing the root locality.

The function *find_root_locality*() can be used to retrieve the global id usable to refer to the root locality. The root locality is the locality where the main AGAS service is hosted.

⁵⁸⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

See also:

`hpx::find_all_localities()`, `hpx::find_locality()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will return meaningful results only if called from an HPX-thread. It will return *hpx::invalid_id* otherwise.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global id representing the root locality for this application.

`hpx::find_all_localities`

Defined in header [hpx/runtime.hpp](#)⁵⁸⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::find_root_locality`
- `hpx::find_remote_localities`

`std::vector<hpx::id_type> hpx::find_all_localities(error_code &ec = throws)`

Return the list of global ids representing all localities available to this application.

The function `find_all_localities()` can be used to retrieve the global ids of all localities currently available to this application.

See also:

`hpx::find_here()`, `hpx::find_locality()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

⁵⁸⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

Note: This function will return meaningful results only if called from an HPX-thread. It will return an empty vector otherwise.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global ids representing the localities currently available to this application.

`std::vector<hpx::id_type> hpx::find_all_localities(components::component_type type, error_code &ec = throws)`

Return the list of global ids representing all localities available to this application which support the given component type.

The function `find_all_localities()` can be used to retrieve the global ids of all localities currently available to this application which support the creation of instances of the given component type.

See also:

`hpx::find_here()`, `hpx::find_locality()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will return meaningful results only if called from an HPX-thread. It will return an empty vector otherwise.

Parameters

- **type** – [in] The type of the components for which the function should return the available localities.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global ids representing the localities currently available to this application which support the creation of instances of the given component type. If no localities supporting the given component type are currently available, this function will return an empty vector.

hpx::find_remote_localities

Defined in header [hpx/runtime.hpp](#)⁵⁸⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::find_root_locality`
- `hpx::find_all_localities`

`std::vector<hpx::id_type> hpx::find_remote_localities(error_code &ec = throws)`

Return the list of locality ids of remote localities supporting the given component type. By default this function will return the list of all remote localities (all but the current locality).

The function `find_remote_localities()` can be used to retrieve the global ids of all remote localities currently available to this application (i.e. all localities except the current one).

See also:

`hpx::find_here()`, `hpx::find_locality()`

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: This function will return meaningful results only if called from an HPX-thread. It will return an empty vector otherwise.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Returns

The global ids representing the remote localities currently available to this application.

`std::vector<hpx::id_type> hpx::find_remote_localities(components::component_type type, error_code &ec = throws)`

Return the list of locality ids of remote localities supporting the given component type. By default this function will return the list of all remote localities (all but the current locality).

The function `find_remote_localities()` can be used to retrieve the global ids of all remote localities currently available to this application (i.e. all localities except the current one) which support the creation of instances of the given component type.

⁵⁸⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

See also:

hpx::find_here(), *hpx::find_locality()*

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will return meaningful results only if called from an HPX-thread. It will return an empty vector otherwise.

Parameters

- **type** – [in] The type of the components for which the function should return the available remote localities.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global ids representing the remote localities currently available to this application.

hpx/runtime_distributed/runtime_fwd.hpp

Defined in header *hpx/runtime_distributed/runtime_fwd.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

runtime_distributed &**get_runtime_distributed**()

runtime_distributed ***get_runtime_distributed_ptr**()

naming::gid_type const &**get_locality**()

The function *get_locality* returns a reference to the locality prefix.

void **start_active_counters**(*error_code* &*ec* = *throws*)

Start all active performance counters, optionally naming the section of code.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: The active counters are those which have been specified on the command line while executing the application (see command line option `-hpx:print-counter`)

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

void **reset_active_counters**(*error_code* &ec = *throws*)

Resets all active performance counters.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: The active counters are those which have been specified on the command line while executing the application (see command line option `-hpx:print-counter`)

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

void **reinit_active_counters**(bool reset = true, *error_code* &ec = *throws*)

Re-initialize all active performance counters.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: The active counters are those which have been specified on the command line while executing the application (see command line option `-hpx:print-counter`)

Parameters

- **reset** – [in] Reset the current values before re-initializing counters (default: true)
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

void **stop_active_counters**(*error_code* &ec = *throws*)

Stop all active performance counters.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: The active counters are those which have been specified on the command line while executing the application (see command line option `-hpx:print-counter`)

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

void **evaluate_active_counters**(bool reset = false, char const *description = nullptr, *error_code* &ec = *throws*)

Evaluate and output all active performance counters, optionally naming the point in code marked by this function.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Note: The output generated by this function is redirected to the destination specified by the corresponding command line options (see `-hpx:print-counter-destination`).

Note: The active counters are those which have been specified on the command line while executing the application (see command line option `-hpx:print-counter`)

Parameters

- **reset** – [in] this is an optional flag allowing to reset the counter value after it has been evaluated.
- **description** – [in] this is an optional value naming the point in the code marked by the call to this function.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

serialization::binary_filter ***create_binary_filter**(char const *binary_filter_type, bool compress, *serialization::binary_filter* *next_filter = nullptr, *error_code* &ec = *throws*)

Create an instance of a binary filter plugin.

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of `hpx::exception`.

Parameters

- **binary_filter_type** – [in] The type of the binary filter to create
- **compress** – [in] The created filter should support compression
- **next_filter** – [in] Use this as the filter to dispatch the invocation into.

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx::find_locality

Defined in header [hpx/runtime.hpp](#)⁵⁸⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx::id_type **hpx::find_locality**(*components::component_type* type, *error_code* &ec = *throws*)

Return the global id representing an arbitrary locality which supports the given component type.

The function `find_locality()` can be used to retrieve the global id of an arbitrary locality currently available to this application which supports the creation of instances of the given component type.

See also:

hpx::find_here(), *hpx::find_all_localities()*

Note: Generally, the id of a locality can be used for instance to create new instances of components and to invoke plain actions (global functions).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Note: This function will return meaningful results only if called from an HPX-thread. It will return *hpx::invalid_id* otherwise.

Parameters

- **type** – [in] The type of the components for which the function should return any available locality.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

The global id representing an arbitrary locality currently available to this application which supports the creation of instances of the given component type. If no locality supporting the given component type is currently available, this function will return *hpx::invalid_id*.

⁵⁸⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

hpx/runtime_distributed/get_num_localities.hpp

Defined in header `hpx/runtime_distributed/get_num_localities.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

hpx::future<std::uint32_t> **get_num_localities**(*components::component_type* t)

Asynchronously return the number of localities which are currently registered for the running application.

The function *get_num_localities* asynchronously returns the number of localities currently connected to the console which support the creation of the given component type. The returned future represents the actual result.

See also:

hpx::find_all_localities, *hpx::get_num_localities*

Note: This function will return meaningful results only if called from an HPX-thread. It will return 0 otherwise.

Parameters

t – The component type for which the number of connected localities should be retrieved.

std::uint32_t **get_num_localities**(*launch::sync_policy*, *components::component_type* t, *error_code* &ec = *throws*)

Synchronously return the number of localities which are currently registered for the running application.

The function *get_num_localities* returns the number of localities currently connected to the console which support the creation of the given component type. The returned future represents the actual result.

See also:

hpx::find_all_localities, *hpx::get_num_localities*

Note: This function will return meaningful results only if called from an HPX-thread. It will return 0 otherwise.

Parameters

- **t** – The component type for which the number of connected localities should be retrieved.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx/runtime_distributed/applier_fwd.hpp

Defined in header `hpx/runtime_distributed/applier_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **applier**

Functions

applier &**get_applier**()

The function *get_applier* returns a reference to the (thread specific) *applier* instance.

applier ***get_applier_ptr**()

The function *get_applier* returns a pointer to the (thread specific) *applier* instance. The returned pointer is NULL if the current thread is not known to HPX or if the runtime system is not active.

namespace **applier**

The namespace *applier* contains all definitions needed for the class `hpx::applier::applier` and its related functionality. This namespace is part of the HPX core module.

hpx/runtime_distributed/stubs/runtime_support.hpp

Defined in header `hpx/runtime_distributed/stubs/runtime_support.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

namespace **stubs**

struct **runtime_support**

Subclassed by *hpx::components::runtime_support*

Public Static Functions

template<typename **Component**, typename ...**Ts**>

static inline *hpx::future*<*hpx::id_type*> **create_component_async**(*hpx::id_type* const &gid,
Ts&&... vs)

Create a new component *type* using the *runtime_support* with the given *targetgid*. This is a non-blocking call. The caller needs to call *future::get* on the result of this function to obtain the global id of the newly created object.

template<typename **Component**, typename ...**Ts**>

```
static inline hpx::id_type create_component(hpx::id_type const &gid, Ts&&... vs)
```

Create a new component *type* using the *runtime_support* with the given *targetgid*. Block for the creation to finish.

```
template<bool WithCount, typename Component, typename ...Ts>
```

```
static inline hpx::future<std::vector<hpx::id_type>> bulk_create_component_colocated_async(hpx::id_type const &gid, std::size_t count, Ts&&... vs)
```

Create multiple new components *type* using the *runtime_support* colocated with the given *targetgid*. This is a non-blocking call.

```
template<bool WithCount, typename Component, typename ...Ts>
```

```
static inline std::vector<hpx::id_type> bulk_create_component_colocated(hpx::id_type const &gid, std::size_t count, Ts&&... vs)
```

Create multiple new components *type* using the *runtime_support* colocated with the given *targetgid*. Block for the creation to finish.

```
template<bool WithCount, typename Component, typename ...Ts>
```

```
static inline hpx::future<std::vector<hpx::id_type>> bulk_create_component_async(hpx::id_type const &gid, std::size_t count, Ts&&... vs)
```

Create multiple new components *type* using the *runtime_support* on the given locality. This is a non-blocking call.

```
template<bool WithCount, typename Component, typename ...Ts>
```

```
static inline std::vector<hpx::id_type> bulk_create_component(hpx::id_type const &gid, std::size_t count, Ts&&... vs)
```

Create multiple new components *type* using the *runtime_support* on the given locality. Block for the creation to finish.

```
template<typename Component, typename ...Ts>
```

```
static inline hpx::future<hpx::id_type> create_component_colocated_async(hpx::id_type const &gid, Ts&&... vs)
```

Create a new component *type* using the *runtime_support* with the given *targetgid*. This is a non-blocking call. The caller needs to call *future::get* on the result of this function to obtain the global id of the newly created object.

```
template<typename Component, typename ...Ts>
```

```
static inline hpx::id_type create_component_colocated(hpx::id_type const &gid, Ts&&... vs)
```

Create a new component *type* using the *runtime_support* with the given *targetgid*. Block for the creation to finish.


```

template<typename Component>
static inline hpx::future<hpx::id_type> copy_create_component_async(hpx::id_type const
                                                                &gid,
                                                                std::shared_ptr<Component>
                                                                const &p, bool
                                                                local_op)

template<typename Component>
static inline hpx::id_type copy_create_component(hpx::id_type const &gid,
                                                  std::shared_ptr<Component> const &p,
                                                  bool local_op)

template<typename Component>
static inline hpx::future<hpx::id_type> migrate_component_async(hpx::id_type const
                                                                &target_locality,
                                                                std::shared_ptr<Component>
                                                                const &p, hpx::id_type
                                                                const &to_migrate)

template<typename Component, typename DistPolicy>
static inline hpx::future<hpx::id_type> migrate_component_async(DistPolicy const &policy,
                                                                std::shared_ptr<Component>
                                                                const &p, hpx::id_type
                                                                const &to_migrate)

template<typename Component, typename Target>
static inline hpx::id_type migrate_component(Target const &target, hpx::id_type const
                                                                &to_migrate, std::shared_ptr<Component>
                                                                const &p)

static hpx::future<int> load_components_async(hpx::id_type const &gid)

static int load_components(hpx::id_type const &gid)

static hpx::future<void> call_startup_functions_async(hpx::id_type const &gid, bool
                                                                pre_startup)

static void call_startup_functions(hpx::id_type const &gid, bool pre_startup)

static hpx::future<void> shutdown_async(hpx::id_type const &targetgid, double timeout = -1)
    Shutdown the given runtime system.

static void shutdown(hpx::id_type const &targetgid, double timeout = -1)

static void shutdown_all(hpx::id_type const &targetgid, double timeout = -1)
    Shutdown the runtime systems of all localities.

static void shutdown_all(double timeout = -1)

static hpx::future<void> terminate_async(hpx::id_type const &targetgid)
    Retrieve configuration information.
    Terminate the given runtime system

static void terminate(hpx::id_type const &targetgid)

```

```
static void terminate_all(hpx::id_type const &targetgid)
    Terminate the runtime systems of all localities.

static void terminate_all()

static void garbage_collect_non_blocking(hpx::id_type const &targetgid)

static hpx::future<void> garbage_collect_async(hpx::id_type const &targetgid)

static void garbage_collect(hpx::id_type const &targetgid)

static hpx::future<hpx::id_type> create_performance_counter_async(hpx::id_type const
                                                                    &targetgid, perfor-
                                                                    mance_counters::counter_info
                                                                    const &info)

static hpx::id_type create_performance_counter(hpx::id_type const &targetgid,
                                                performance_counters::counter_info
                                                const &info, error_code &ec = throws)

static hpx::future<util::section> get_config_async(hpx::id_type const &targetgid)
    Retrieve configuration information.

static void get_config(hpx::id_type const &targetgid, util::section &ini)

static void remove_from_connection_cache_async(hpx::id_type const &target,
                                                naming::gid_type const &gid,
                                                parcelset::endpoints_type const
                                                &endpoints)
```

hpx/runtime_distributed/server/runtime_support.hpp

Defined in header `hpx/runtime_distributed/server/runtime_support.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

namespace **server**

class **runtime_support**

Public Types

using **type_holder** = *runtime_support*

Public Functions

explicit **runtime_support**(*hpx::util::runtime_configuration* &cfg)

inline ~**runtime_support**()

void **delete_function_lists**()

void **tidy**()

template<typename **Component**>
naming::gid_type **create_component**()

Actions to create new objects.

template<typename **Component**, typename **T**, typename ...**Ts**>
naming::gid_type **create_component**(*T* v, *Ts...* vs)

template<typename **Component**, typename ...**Ts**>
std::vector<naming::gid_type> **bulk_create_component**(*std::size_t* count, *Ts...* vs)

template<typename **Component**, typename ...**Ts**>
std::vector<naming::gid_type> **bulk_create_component_with_count**(*std::size_t* count, *Ts...*
vs)

template<typename **Component**>
naming::gid_type **copy_create_component**(*std::shared_ptr<Component>* const &p, bool)

template<typename **Component**>
naming::gid_type **migrate_component_to_here**(*std::shared_ptr<Component>* const &p,
hpx::id_type)

void **shutdown**(double timeout, *hpx::id_type* const &respond_to)

Gracefully shutdown this runtime system instance.

void **shutdown_all**(double timeout)

Gracefully shutdown runtime system instances on all localities.

void **terminate**(*hpx::id_type* const &respond_to)

Shutdown this runtime system instance.

inline void **terminate_act**(*hpx::id_type* const &id)

void **terminate_all**()

Shutdown runtime system instances on all localities.

inline void **terminate_all_act**()

util::section **get_config**()

Retrieve configuration information.

int **load_components**()

Load all components on this locality.

void **call_startup_functions**(bool pre_startup)

void **call_shutdown_functions**(bool pre_shutdown)

void **garbage_collect**()

Force a garbage collection operation in the AGAS layer.

naming::gid_type **create_performance_counter**(performance_counters::counter_info const &info)

Create the given performance counter instance.

void **remove_from_connection_cache**(*naming::gid_type* const &gid,
parcelset::endpoints_type const &eps)

Remove the given locality from our connection cache.

HPX_DEFINE_COMPONENT_ACTION (runtime_support, terminate_act,
terminate_action) **HPX_DEFINE_COMPONENT_ACTION**(runtime_support
termination detection

terminate_all_action **HPX_DEFINE_COMPONENT_ACTION** (runtime_support,
remove_from_connection_cache) void **run**()

Start the *runtime_support* component.

void **wait**()

Wait for the *runtime_support* component to notify the calling thread.

This function will be called from the main thread, causing it to block while the HPX functionality is executed. The main thread will block until the shutdown_action is executed, which in turn notifies all waiting threads.

void **stop**(double timeout, *hpx::id_type* const &respond_to, bool remove_from_remote_caches)

Notify all waiting (blocking) threads allowing the system to be properly stopped.

Note: This function can be called from any thread.

void **remove_locality**(*hpx::id_type* const &locality, *error_code* &ec = *hpx::throws*)
called locally only

void **stopped**()

void **notify_waiting_main**()

inline bool **was_stopped**() const

void **add_pre_startup_function**(*startup_function_type* f)

void **add_startup_function**(*startup_function_type* f)

void **add_pre_shutdown_function**(*shutdown_function_type* f)

void **add_shutdown_function**(*shutdown_function_type* f)

Public Members

terminate_all_act

Public Static Functions

static inline component_type **get_component_type**()

static inline void **set_component_type**(component_type t)

static inline constexpr void **finalize**()

finalize() will be called just before the instance gets destructed

static inline bool **is_target_valid**(hpx::id_type const &id)

static void **remove_locality_from_connection_cache**(hpx::naming::gid_type const
&locality, bool skip_current =
false)

static void **remove_locality_from_console_connection_cache**(hpx::naming::gid_type
const &locality)

Protected Functions

int **load_components**(util::section &ini, naming::gid_type const &prefix,
agas::addressing_service &agas_client,
hpx::program_options::options_description &options,
std::set<std::string> &startup_handled)

bool **load_component**(hpx::util::plugin::dll &d, util::section &ini, std::string const &instance,
std::string const &component, filesystem::path const &lib,
naming::gid_type const &prefix, agas::addressing_service
&agas_client, bool isdefault, bool isenabled,
hpx::program_options::options_description &options,
std::set<std::string> &startup_handled)

bool **load_component_dynamic**(util::section &ini, std::string const &instance, std::string
const &component, filesystem::path lib, naming::gid_type
const &prefix, agas::addressing_service &agas_client, bool
isdefault, bool isenabled,
hpx::program_options::options_description &options,
std::set<std::string> &startup_handled)

bool **load_startup_shutdown_functions**(hpx::util::plugin::dll &d, error_code &ec)

bool **load_commandline_options**(hpx::util::plugin::dll &d,
hpx::program_options::options_description &options,
error_code &ec)

bool **load_component_static**(util::section &ini, std::string const &instance, std::string const
&component, filesystem::path const &lib, naming::gid_type
const &prefix, agas::addressing_service &agas_client, bool
isdefault, bool isenabled,
hpx::program_options::options_description &options,
std::set<std::string> &startup_handled)

```
bool load_startup_shutdown_functions_static(std::string const &mod, error_code
                                           &ec)

bool load_commandline_options_static(std::string const &mod,
                                     hpx::program_options::options_description
                                     &options, error_code &ec)

bool load_plugins(util::section &ini, hpx::program_options::options_description &options,
                 std::set<std::string> &startup_handled)

bool load_plugin(hpx::util::plugin::dll &d, util::section &ini, std::string const &instance,
                 std::string const &component, filesystem::path const &lib, bool isenabled,
                 hpx::program_options::options_description &options, std::set<std::string>
                 &startup_handled)

bool load_plugin_dynamic(util::section &ini, std::string const &instance, std::string const
                        &component, filesystem::path lib, bool isenabled,
                        hpx::program_options::options_description &options,
                        std::set<std::string> &startup_handled)

bool load_plugin_static(util::section &ini, std::string const &instance, std::string const
                        &plugin, bool isenabled,
                        hpx::program_options::options_description &options,
                        std::set<std::string> &startup_handled)

std::size_t dijkstra_termination_detection(std::vector<hpx::id_type> const
                                           &locality_ids)
```

Private Types

```
using plugin_map_mutex_type = hpx::spinlock

using plugin_factory_type = plugin_factory

using plugin_map_type = std::map<std::string, plugin_factory_type>

using modules_map_type = std::map<std::string, hpx::util::plugin::dll>

using static_modules_type = std::vector<static_factory_load_data_type>
```

Private Members

std::mutex **mtx_**

std::condition_variable **wait_condition_**

std::condition_variable **stop_condition_**

bool **stop_called_**

bool **stop_done_**

bool **terminated_**

std::thread::id **main_thread_id_**

std::atomic<bool> **shutdown_all_invoked_**

plugin_map_mutex_type **p_mtx_**

plugin_map_type **plugins_**

modules_map_type &**modules_**

static_modules_type **static_modules_**

hpx::spinlock **globals_mtx_**

std::list<startup_function_type> **pre_startup_functions_**

std::list<startup_function_type> **startup_functions_**

std::list<shutdown_function_type> **pre_shutdown_functions_**

std::list<shutdown_function_type> **shutdown_functions_**

struct **plugin_factory**

Public Functions

```
inline plugin_factory(std::shared_ptr<plugins::plugin_factory_base> const &f, bool  
enabled)
```

Public Members

```
std::shared_ptr<plugins::plugin_factory_base> first
```

```
bool isenabled
```

hpx/runtime_distributed/server/copy_component.hpp

Defined in header `hpx/runtime_distributed/server/copy_component.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace components
```

```
namespace server
```

Functions

```
template<typename Component>  
hpx::id_type copy_component_here(hpx::id_type const &to_copy)
```

```
template<typename Component>  
future<hpx::id_type> copy_component(hpx::id_type const &to_copy, hpx::id_type const  
&target_locality)
```

```
template<typename Component>  
struct copy_component_action : public hpx::actions::action<future<hpx::id_type>  
(*)(hpx::id_type const&, hpx::id_type const&), &copy_component<Component>,  
copy_component_action<Component>>
```

```
template<typename Component>  
struct copy_component_action_here : public hpx::actions::action<hpx::id_type (*)(hpx::id_type  
const&), &copy_component_here<Component>, copy_component_action_here<Component>>
```


segmented_algorithms

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/parallel/segmented_algorithms/fill.hpp

Defined in header `hpx/parallel/segmented_algorithms/fill.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename T>
SegIter hpx_invoke(hpx::fill_t, SegIter first, SegIter last, T const &value)
```

```
template<typename SegIter, typename Size, typename T>
SegIter hpx_invoke(hpx::fill_n_t, SegIter first, Size count, T const &value)
```

```
template<typename ExPolicy, typename SegIter, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> hpx_invoke(hpx::fill_t, ExPolicy
&&policy, SegIter first,
SegIter last, T const
&value)
```

```
template<typename ExPolicy, typename SegIter, typename Size, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> hpx_invoke(hpx::fill_n_t, ExPolicy
&&policy, SegIter first,
Size count, T const
&value)
```

hpx/parallel/segmented_algorithms/exclusive_scan.hpp

Defined in header `hpx/parallel/segmented_algorithms/exclusive_scan.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename OutIter, typename T, typename Op = std::plus<T>>
OutIter hpx_invoke(hpx::exclusive_scan_t, InIter first, InIter last, OutIter dest, T init, Op &&op =
    Op())
```

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T, typename Op =
    std::plus<T>>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx_invoke(hpx::exclusive_scan_t,
    ExPolicy &&policy,
    FwdIter1 first, FwdIter1
    last, FwdIter2 dest, T init,
    Op &&op = Op())
```

hpx/parallel/segmented_algorithms/equal.hpp

Defined in header `hpx/parallel/segmented_algorithms/equal.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter1, typename SegIter2, typename Pred = hpx::parallel::detail::equal_to>
bool hpx_invoke(hpx::equal_t, SegIter1 first1, SegIter1 last1, SegIter2 first2, Pred &&pred = Pred())
```

```
template<typename ExPolicy, typename SegIter1, typename SegIter2, typename Pred =
    hpx::parallel::detail::equal_to>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx_invoke(hpx::equal_t, ExPolicy
    &&policy, SegIter1 first1,
    SegIter1 last1, SegIter2
    first2, Pred &&pred =
    Pred())
```

hpx/parallel/segmented_algorithms/is_partitioned.hpp

Defined in header `hpx/parallel/segmented_algorithms/is_partitioned.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename Pred>
bool hpx_invoke(hpx::is_partitioned_t, InIter first, InIter last, Pred &&pred)

template<typename ExPolicy, typename SegIter, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx_invoke(hpx::is_partitioned_t,
                                                                           ExPolicy &&policy, SegIter
                                                                           first, SegIter last, Pred
                                                                           &&pred)
```

hpx/parallel/segmented_algorithms/replace_copy.hpp

Defined in header `hpx/parallel/segmented_algorithms/replace_copy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename OutIter, typename T>
OutIter hpx_invoke(hpx::replace_copy_t, SegIter first, SegIter last, OutIter dest, T const &old_value, T
                    const &new_value)

template<typename ExPolicy, typename SegIter, typename OutIter, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, OutIter> hpx_invoke(hpx::replace_copy_t,
                                                                           ExPolicy &&policy,
                                                                           SegIter first, SegIter last,
                                                                           OutIter dest, T const
                                                                           &old_value, T const
                                                                           &new_value)

template<typename SegIter, typename OutIter, typename Pred, typename T>
OutIter hpx_invoke(hpx::replace_copy_if_t, SegIter first, SegIter last, OutIter dest, Pred &&pred, T
                    const &new_value)

template<typename ExPolicy, typename SegIter, typename OutIter, typename Pred, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, OutIter> hpx_invoke(hpx::replace_copy_if_t,
                                                                           ExPolicy &&policy,
                                                                           SegIter first, SegIter last,
                                                                           OutIter dest, Pred
                                                                           &&pred, T const
                                                                           &new_value)
```

hpx/parallel/segmented_algorithms/minmax.hpp

Defined in header `hpx/parallel/segmented_algorithms/minmax.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

Typedefs

template<typename **T**>

using **minmax_element_result** = *hpx::parallel::util::min_max_result*<*T*>

namespace **segmented**

Typedefs

template<typename **T**>

using **minmax_element_result** = *hpx::parallel::util::min_max_result*<*T*>

Functions

template<typename **SegIter**, typename **F**>

SegIter **hpx_invoke**(*hpx::min_element_t*, *SegIter* first, *SegIter* last, *F* &&*f*)

template<typename **ExPolicy**, typename **SegIter**, typename **F**>

hpx::parallel::util::detail::algorithm_result_t<*ExPolicy*, *SegIter*> **hpx_invoke**(*hpx::min_element_t*,
ExPolicy &&*policy*,
SegIter first, *SegIter* last,
F &&*f*)

template<typename **SegIter**, typename **F**>

SegIter **hpx_invoke**(*hpx::max_element_t*, *SegIter* first, *SegIter* last, *F* &&*f*)

template<typename **ExPolicy**, typename **SegIter**, typename **F**>

hpx::parallel::util::detail::algorithm_result_t<*ExPolicy*, *SegIter*> **hpx_invoke**(*hpx::max_element_t*,
ExPolicy &&*policy*,
SegIter first, *SegIter* last,
F &&*f*)

template<typename **SegIter**, typename **F**>

minmax_element_result<*SegIter*> **hpx_invoke**(*hpx::minmax_element_t*, *SegIter* first, *SegIter* last, *F* &&*f*)

template<typename **ExPolicy**, typename **SegIter**, typename **F**>

```

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, minmax_element_result_t<SegIter>> hpx_invoke(hpx::minmax_element_result_t<SegIter>
    Ex-
    Pol-
    icy
    &&pol-
    icy,
    Se-
    gIter
    first,
    Se-
    gIter
    last,
    F
    &&f)

```

hpx/parallel/segmented_algorithms/adjacent_difference.hpp

Defined in header `hpx/parallel/segmented_algorithms/adjacent_difference.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```

template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx_invoke(hpx::adjacent_difference_t,
    ExPolicy &&policy,
    FwdIter1 first,
    FwdIter1 last, FwdIter2
    dest, Op &&op)

```

```

template<typename InIter1, typename InIter2, typename Op>
InIter2 hpx_invoke(hpx::adjacent_difference_t, InIter1 first, InIter1 last, InIter2 dest, Op &&op)

```

hpx/parallel/segmented_algorithms/adjacent_find.hpp

Defined in header `hpx/parallel/segmented_algorithms/adjacent_find.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename Pred>
InIter hpx_invoke(hpx::adjacent_find_t, InIter first, InIter last, Pred &&pred = Pred())

template<typename ExPolicy, typename SegIter, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> hpx_invoke(hpx::adjacent_find_t,
                                                                 ExPolicy &&policy,
                                                                 SegIter first, SegIter last,
                                                                 Pred &&pred)
```

hpx/parallel/segmented_algorithms/generate.hpp

Defined in header `hpx/parallel/segmented_algorithms/generate.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename F>
SegIter hpx_invoke(hpx::generate_t, SegIter first, SegIter last, F &&f)

template<typename SegIter, typename Size, typename F>
SegIter hpx_invoke(hpx::generate_n_t, SegIter first, Size count, F &&f)

template<typename ExPolicy, typename SegIter, typename F>
parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> hpx_invoke(hpx::generate_t, ExPolicy
                                                                 &&policy, SegIter first,
                                                                 SegIter last, F &&f)

template<typename ExPolicy, typename SegIter, typename Size, typename F>
parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> hpx_invoke(hpx::generate_n_t, ExPolicy
                                                                 &&policy, SegIter first, Size
                                                                 count, F &&f)
```

hpx/parallel/segmented_algorithms/copy.hpp

Defined in header `hpx/parallel/segmented_algorithms/copy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename OutIter>
OutIter hpx_invoke(hpx::copy_t, SegIter first, SegIter last, OutIter dest)
```

```
template<typename ExPolicy, typename SegIter, typename OutIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, OutIter> hpx_invoke(hpx::copy_t, ExPolicy
&&policy, SegIter first,
SegIter last, OutIter
dest)
```

hpx/parallel/segmented_algorithms/transform_exclusive_scan.hpp

Defined in header hpx/parallel/segmented_algorithms/transform_exclusive_scan.hpp.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **segmented**

Functions

```
template<typename InIter, typename OutIter, typename T, typename Op, typename Conv>
OutIter hpx_invoke(hpx::transform_exclusive_scan_t, InIter first, InIter last, OutIter dest, T init, Op
&&op, Conv &&conv)
```

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T, typename Op,
typename Conv>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx_invoke(hpx::transform_exclusive_scan_t,
ExPolicy &&policy,
FwdIter1 first, FwdIter1
last, FwdIter2 dest, T init,
Op &&op, Conv &&conv)
```

hpx/parallel/segmented_algorithms/transform_reduce.hpp

Defined in header hpx/parallel/segmented_algorithms/transform_reduce.hpp.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename T, typename Reduce, typename Convert>  
std::decay_t<T> hpx_invoke(hpx::transform_reduce_t, SegIter first, SegIter last, T &&init, Reduce  
&&red_op, Convert &&conv_op)
```

```
template<typename ExPolicy, typename SegIter, typename T, typename Reduce, typename  
Convert>  
parallel::util::detail::algorithm_result_t<ExPolicy, std::decay_t<T>> hpx_invoke(hpx::transform_reduce_t,  
ExPolicy &&policy,  
SegIter first, SegIter  
last, T &&init,  
Reduce &&red_op,  
Convert  
&&conv_op)
```

```
template<typename FwdIter1, typename FwdIter2, typename T, typename Reduce, typename  
Convert>  
T hpx_invoke(hpx::transform_reduce_t, FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, T init, Reduce  
&&red_op, Convert &&conv_op)
```

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T, typename  
Reduce, typename Convert>  
parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx_invoke(hpx::transform_reduce_t, ExPolicy  
&&policy, FwdIter1 first1,  
FwdIter1 last1, FwdIter2 first2, T  
init, Reduce &&red_op, Convert  
&&conv_op)
```

hpx/parallel/segmented_algorithms/transform.hpp

Defined in header `hpx/parallel/segmented_algorithms/transform.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename OutIter, typename F>
hpx::parallel::util::in_out_result<SegIter, OutIter> hpx_invoke(hpx::transform_t, SegIter first, SegIter
last, OutIter dest, F &&f)
```

```
template<typename ExPolicy, typename SegIter, typename OutIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, hpx::parallel::util::in_out_result<SegIter, OutIter>> hpx_invoke(
```

```
template<typename InIter1, typename InIter2, typename OutIter, typename F>
hpx::parallel::util::in_in_out_result<InIter1, InIter2, OutIter> hpx_invoke(hpx::transform_t, InIter1
first1, InIter1 last1, InIter2
first2, OutIter dest, F &&f)
```

```
template<typename ExPolicy, typename InIter1, typename InIter2, typename OutIter, typename
F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, hpx::parallel::util::in_in_out_result<InIter1, InIter2, OutIter>> hpx_invoke(
```

```
template<typename InIter1, typename InIter2, typename OutIter, typename F>
hpx::parallel::util::in_in_out_result<InIter1, InIter2, OutIter> hpx_invoke(hpx::transform_t, InIter1
first1, InIter1 last1, InIter2
first2, InIter2 last2, OutIter
dest, F &&f)
```

```
template<typename ExPolicy, typename InIter1, typename InIter2, typename OutIter, typename  
F>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, hpx::parallel::util::in_in_out_result<InIter1, InIter2, OutIter>> hpx
```

hpx/parallel/segmented_algorithms/count.hpp

Defined in header `hpx/parallel/segmented_algorithms/count.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename T>  
std::iterator_traits<InIter>::difference_type hpx_invoke(hpx::count_t, InIter first, InIter last, T const  
                                                         &value)
```

```
template<typename ExPolicy, typename SegIter, typename T>
```

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, typename std::iterator_traits<SegIter>::difference_type> **hpx_invo**

```
template<typename InIter, typename F>
std::iterator_traits<InIter>::difference_type hpx_invoke(hpx::count_if_t, InIter first, InIter last, F
&&f)
```

```
template<typename ExPolicy, typename SegIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, typename std::iterator_traits<SegIter>::difference_type> hpx_invo
```

hpx/parallel/segmented_algorithms/transform_inclusive_scan.hpp

Defined in header `hpx/parallel/segmented_algorithms/transform_inclusive_scan.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **segmented**

Functions

```
template<typename InIter, typename OutIter, typename Op, typename Conv>  
OutIter hpx_invoke(hpx::transform_inclusive_scan_t, InIter first, InIter last, OutIter dest, Op &&op,  
                    Conv &&conv)
```

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op, typename  
Conv>  
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx_invoke(hpx::transform_inclusive_scan_t,  
                                ExPolicy &&policy,  
                                FwdIter1 first, FwdIter1  
                                last, FwdIter2 dest, Op  
                                &&op, Conv &&conv)
```

```
template<typename InIter, typename OutIter, typename T, typename Op, typename Conv>  
OutIter hpx_invoke(hpx::transform_inclusive_scan_t, InIter first, InIter last, OutIter dest, Op &&op,  
                    Conv &&conv, T init)
```

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T, typename Op,  
typename Conv>  
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx_invoke(hpx::transform_inclusive_scan_t,  
                                ExPolicy &&policy,  
                                FwdIter1 first, FwdIter1 last,  
                                FwdIter2 dest, Op &&op,  
                                Conv &&conv, T init)
```

hpx/parallel/segmented_algorithms/is_sorted.hpp

Defined in header `hpx/parallel/segmented_algorithms/is_sorted.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename Pred = hpx::parallel::detail::less>  
InIter hpx_invoke(hpx::is_sorted_until_t, InIter first, InIter last, Pred &&pred = Pred())
```

```
template<typename ExPolicy, typename SegIter, typename Pred = hpx::parallel::detail::less>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> hpx_invoke(hpx::is_sorted_until_t,  
                                ExPolicy &&policy,  
                                SegIter first, SegIter last,  
                                Pred &&pred = Pred())
```

```
template<typename InIter, typename Pred = hpx::parallel::detail::less>
```

```

bool hpx_invoke(hpx::is_sorted_t, InIter first, InIter last, Pred &&pred = Pred())

template<typename ExPolicy, typename SegIter, typename Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx_invoke(hpx::is_sorted_t, ExPolicy
&&policy, SegIter first,
SegIter last, Pred &&pred =
Pred())

```

hpx/parallel/segmented_algorithms/mismatch.hpp

Defined in header `hpx/parallel/segmented_algorithms/mismatch.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```

template<typename SegIter1, typename SegIter2, typename Pred = hpx::parallel::detail::equal_to>
std::pair<SegIter1, SegIter2> hpx_invoke(hpx::mismatch_t, SegIter1 first1, SegIter1 last1, SegIter2
first2, Pred &&pred = Pred())

template<typename ExPolicy, typename SegIter1, typename SegIter2, typename Pred =
hpx::parallel::detail::equal_to>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<SegIter1, SegIter2>> hpx_invoke(hpx::mismatch_t,
Ex-
Pol-
icy
&&pol-
icy,
Se-
gIter1
first1,
Se-
gIter1
last1,
Se-
gIter2
first2,
Pred
&&pred
=
Pred())

template<typename SegIter1, typename SegIter2, typename Pred = hpx::parallel::detail::equal_to>

```

```
std::pair<SegIter1, SegIter2> hpx_invoke(hpx::mismatch_t, SegIter1 first1, SegIter1 last1, SegIter2
                                         first2, SegIter2 last2, Pred &&pred = Pred())

template<typename ExPolicy, typename SegIter1, typename SegIter2, typename Pred =
hpx::parallel::detail::equal_to>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<SegIter1, SegIter2>> hpx_invoke(hpx::mismatch_t,
                                                                                                     Ex-
                                                                                                     Pol-
                                                                                                     icy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     Se-
                                                                                                     gIter1
                                                                                                     first1,
                                                                                                     Se-
                                                                                                     gIter1
                                                                                                     last1,
                                                                                                     Se-
                                                                                                     gIter2
                                                                                                     first2,
                                                                                                     Se-
                                                                                                     gIter2
                                                                                                     last2,
                                                                                                     Pred
                                                                                                     &&pred
                                                                                                     =
                                                                                                     Pred())
```

hpx/parallel/segmented_algorithms/replace.hpp

Defined in header `hpx/parallel/segmented_algorithms/replace.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename SegIter, typename T>
SegIter hpx_invoke(hpx::replace_t, SegIter first, SegIter last, T const &old_value, T const
                  &new_value)

template<typename ExPolicy, typename SegIter, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> hpx_invoke(hpx::replace_t, ExPolicy
                                                                              &&policy, SegIter first,
                                                                              SegIter last, T const
                                                                              &old_value, T const
                                                                              &new_value)
```

```

template<typename SegIter, typename Pred, typename T>
SegIter hpx_invoke(hpx::replace_if_t, SegIter first, SegIter last, Pred &&pred, T const &new_value)

template<typename ExPolicy, typename SegIter, typename Pred, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> hpx_invoke(hpx::replace_if_t,
                                                                    ExPolicy &&policy,
                                                                    SegIter first, SegIter last,
                                                                    Pred &&pred, T const
                                                                    &new_value)

```

hpx/parallel/segmented_algorithms/reduce.hpp

Defined in header `hpx/parallel/segmented_algorithms/reduce.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

```
namespace hpx
```

```
    namespace segmented
```

Functions

```

template<typename InIterB, typename InIterE, typename T, typename F>
T hpx_invoke(hpx::reduce_t, InIterB first, InIterE last, T init, F &&f)

template<typename ExPolicy, typename InIterB, typename InIterE, typename T, typename F>
parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx_invoke(hpx::reduce_t, ExPolicy &&policy,
                                                                    InIterB first, InIterE last, T init, F
                                                                    &&f)

```

hpx/parallel/segmented_algorithms/all_any_none.hpp

Defined in header `hpx/parallel/segmented_algorithms/all_any_none.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

```
    namespace segmented
```

Functions

```
template<typename InIter, typename F>
bool hpx_invoke(hpx::none_of_t, InIter first, InIter last, F &&f)

template<typename ExPolicy, typename SegIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx_invoke(hpx::none_of_t, ExPolicy
&&policy, SegIter first,
SegIter last, F &&f)

template<typename InIter, typename F>
bool hpx_invoke(hpx::any_of_t, InIter first, InIter last, F &&f)

template<typename ExPolicy, typename SegIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx_invoke(hpx::any_of_t, ExPolicy
&&policy, SegIter first,
SegIter last, F &&f)

template<typename InIter, typename F>
bool hpx_invoke(hpx::all_of_t, InIter first, InIter last, F &&f)

template<typename ExPolicy, typename SegIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx_invoke(hpx::all_of_t, ExPolicy
&&policy, SegIter first,
SegIter last, F &&f)
```

hpx/parallel/segmented_algorithms/inclusive_scan.hpp

Defined in header `hpx/parallel/segmented_algorithms/inclusive_scan.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```
template<typename InIter, typename OutIter, typename Op = std::plus<>>
OutIter hpx_invoke(hpx::inclusive_scan_t, InIter first, InIter last, OutIter dest, Op &&op = Op())

template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op = std::plus<>>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx_invoke(hpx::inclusive_scan_t,
ExPolicy &&policy,
FwdIter1 first, FwdIter1
last, FwdIter2 dest, Op
&&op = Op())

template<typename InIter, typename OutIter, typename Op, typename T>
```



```

OutIter hpx_invoke(hpx::inclusive_scan_t, InIter first, InIter last, OutIter dest, Op &&op, T &&init)

template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op, typename T>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx_invoke(hpx::inclusive_scan_t,
                                                                    ExPolicy &&policy,
                                                                    FwdIter1 first, FwdIter1
                                                                    last, FwdIter2 dest, Op
                                                                    &&op, T &&init)

```

hpx/parallel/segmented_algorithms/for_each.hpp

Defined in header `hpx/parallel/segmented_algorithms/for_each.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **segmented**

Functions

```

template<typename InIter, typename F>
InIter hpx_invoke(hpx::for_each_t, InIter first, InIter last, F &&f)

template<typename ExPolicy, typename SegIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> hpx_invoke(hpx::for_each_t, ExPolicy
                                                                    &&policy, SegIter first,
                                                                    SegIter last, F &&f)

template<typename InIter, typename Size, typename F>
InIter hpx_invoke(hpx::for_each_n_t, InIter first, Size count, F &&f)

template<typename ExPolicy, typename SegIter, typename Size, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, SegIter> hpx_invoke(hpx::for_each_n_t,
                                                                    ExPolicy &&policy,
                                                                    SegIter first, Size count,
                                                                    F &&f)

```

supervision

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::supervision::supervision_manager

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

class **supervision_manager**

hpx::supervision::testing::set_register_observer_snapshot_hook

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

void **hpx::supervision::testing::set_register_observer_snapshot_hook**(*std::function*<void()> hook)
Set the hook invoked after an observer snapshot is captured.

Note: Used for testing purposes only.

Parameters

hook – Hook to invoke. An empty function clears the hook.

hpx::supervision::publish_event

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::supervision::query_state*
- *hpx::supervision::register_observer*
- *hpx::supervision::unregister_observer*
- *hpx::supervision::remove_target*
- *hpx::supervision::register_activity_observer*
- *hpx::supervision::unregister_activity_observer*
- *hpx::supervision::check_admission*
- *hpx::supervision::await_terminal*
- *hpx::supervision::is_valid_transition*

hpx::future<publish_result> **hpx::supervision::publish_event**(*hpx::id_type* const &locality, *hpx::id_type* const &target, *hpx::supervision::event* ev, *std::uint64_t* epoch = 0)

Publish a lifecycle event for a target actor on a possibly remote locality.

The function `publish_event()` asynchronously notifies the supervision manager running on *locality* that *target* has reached the lifecycle state *ev*. Registered observers of *target* are notified as a result.

Note: Publishing is not idempotent: publishing the same event twice creates two distinct records with different timestamps.

Note: Events are immediately visible to observers on the same locality as *target*; remote observers become aware of the event within about 1-2 parcel round-trips to the AGAS authority managing the actor's registration.

Parameters

- **locality** – [in] The locality on which the supervision manager responsible for *target* is running.
- **target** – [in] The actor (or component) for which the event is published.
- **ev** – [in] The lifecycle event to publish for *target*.
- **epoch** – [in] The epoch this publication belongs to. Publications are compared against the target's current epoch: publications for a lower epoch are rejected as stale no-ops, publications for a higher epoch reset the target's sequence number and become the new current epoch, and publications for the current epoch are applied normally (subject to terminal-state latching).

Throws

hpx::exception – if *locality* does not represent a locality, or if *target* does not represent a valid target. The returned future becomes exceptional if the operation fails.

Returns

A future that becomes ready once the event has been recorded by the supervision manager on *locality*, holding `publish_result::applied`, `publish_result::already_terminal` if *target* had already reached a terminal event (`completed` or `failed`) within *epoch*, or `publish_result::stale_epoch` if *epoch* is lower than the target's current epoch.

```
publish_result hpx::supervision::publish_event(hpx::launch::sync_policy, hpx::id_type const &locality,
                                              hpx::id_type const &target, hpx::supervision::event ev,
                                              std::uint64_t epoch = 0, hpx::error_code &ec =
                                              hpx::throws)
```

Publish a lifecycle event for a target actor on a possibly remote locality, blocking until the operation has completed.

This is the synchronous equivalent of `publish_event(hpx::id_type const&, hpx::id_type const&, event)`.

Note: Publishing non-terminal events is not idempotent: publishing the same event twice creates two distinct records with different timestamps. `event::completed` and `event::failed` are latched: the first terminal publication for a target wins, and every later terminal publication for that target is a no-op that returns `publish_result::already_terminal`.

Parameters

- **locality** – [in] The locality on which the supervision manager responsible for *target* is running.
- **target** – [in] The actor (or component) for which the event is published.
- **ev** – [in] The lifecycle event to publish for *target*.

- **epoch** – [in] The epoch this publication belongs to. See the asynchronous remote overload for the epoch-scoped semantics.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *locality* does not represent a locality, or if *target* does not represent a valid target, unless *ec* was not pre-initialized to *hpx::throws*. As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*.

Returns

publish_result::applied, *publish_result::already_terminal* if *target* had already reached a terminal event (completed or failed) within *epoch*, or *publish_result::stale_epoch* if *epoch* is lower than the target's current epoch.

```
publish_result hpx::supervision::publish_event(hpx::id_type const &target, hpx::supervision::event ev,
                                              std::uint64_t epoch = 0, hpx::error_code &ec = throws)
```

Publish a lifecycle event for a target actor on the local locality.

This overload publishes *ev* directly through the local supervision manager without going through AGAS or a remote parcel. It is intended to be called from within an actor or action running on the same locality as *target*.

Note: Publishing non-terminal events is not idempotent: publishing the same event twice creates two distinct records with different timestamps. *event::completed* and *event::failed* are latched: the first terminal publication for a target wins, and every later terminal publication for that target is a no-op that returns *publish_result::already_terminal*.

Note: Local observers of *target* are notified synchronously as part of this call.

Parameters

- **target** – [in] The actor (or component) for which the event is published. Must be local to the calling locality.
- **ev** – [in] The lifecycle event to publish for *target*.
- **epoch** – [in] The epoch this publication belongs to. See the asynchronous remote overload for the epoch-scoped semantics.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *target* does not represent a valid target, unless *ec* was not pre-initialized to *hpx::throws*.

Returns

publish_result::applied, *publish_result::already_terminal* if *target* had already reached a terminal event (completed or failed) within *epoch*, or *publish_result::stale_epoch* if *epoch* is lower than the target's current epoch.

```
hpx::future<publish_result> hpx::supervision::publish_event(registry const &handle, event ev, std::uint64_t
                                                         epoch = 0)
```

Publish a lifecycle event for the local locality tracked by *handle*.

Convenience overload of `hpx::supervision::publish_event(hpx::id_type const&, hpx::id_type const&, event, std::uint64_t)` that resolves both locality and target to `hpx::find_here()` instead of requiring the caller to name them explicitly. Forwards to `hpx::supervision::publish_event(hpx::find_here(), hpx::find_here(), ev, epoch)`.

Parameters

- **handle** – [in] The registry (typically returned by `init()`) whose locality the event is published for.
- **ev** – [in] The lifecycle event to publish.
- **epoch** – [in] The epoch this publication belongs to. Typically obtained from a prior `query_state(hpx::launch::sync, handle).epoch` call. See the raw-id overload for the epoch-scoped semantics.

Returns

A future that becomes ready once the event has been recorded, holding the same *publish_result* values as the raw-id overload.

`publish_result hpx::supervision::publish_event(hpx::launch::sync_policy policy, registry const &handle, event ev, std::uint64_t epoch = 0, hpx::error_code &ec = hpx::throws)`

Publish a lifecycle event for the local locality tracked by *handle*, blocking until the operation has completed.

This is the synchronous equivalent of `publish_event(registry const&, event, std::uint64_t)`.

Parameters

- **policy** – [in] Tag selecting the blocking overload of `publish_event()`.
- **handle** – [in] The registry whose locality the event is published for.
- **ev** – [in] The lifecycle event to publish.
- **epoch** – [in] The epoch this publication belongs to. See the asynchronous overload.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Throws

`hpx::exception` – if *handle* does not hold a valid registry client, unless *ec* was pre-initialized to something other than `hpx::throws`.

Returns

The same *publish_result* values as the raw-id overload.

`hpx::supervision::query_state`

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::supervision::publish_event`
- `hpx::supervision::register_observer`
- `hpx::supervision::unregister_observer`
- `hpx::supervision::remove_target`
- `hpx::supervision::register_activity_observer`

- `hpx::supervision::unregister_activity_observer`
- `hpx::supervision::check_admission`
- `hpx::supervision::await_terminal`
- `hpx::supervision::is_valid_transition`

`hpx::future<lifecycle_state> hpx::supervision::query_state(hpx::id_type const &locality, hpx::id_type const &target)`

Query the last known lifecycle state of a target actor on a possibly remote locality.

The function `query_state()` asynchronously retrieves the most recently published lifecycle event for *target*, as observed by the supervision manager running on *locality*.

Note: If *target* is not local to *locality*, the query is forwarded to the actor's home locality, adding about one parcel round-trip of latency.

Note: The returned `lifecycle_state::ec` may carry a staleness error code, indicating that the returned state may be stale if a preceding observer parcel has not yet been delivered.

Note: The `lifecycle_state::event_sequence_number` allows clients to detect gaps, e.g. if an observer callback was skipped due to a network failure.

Parameters

- **locality** – [in] The locality on which the supervision manager responsible for *target* is running.
- **target** – [in] The actor (or component) whose state is queried.

Throws

`hpx::exception` – if *locality* does not represent a locality, or if *target* does not represent a valid target. The returned future becomes exceptional if the operation fails.

Returns

A future holding the last event recorded for *target* (i.e., the most recent value in the runtime's event log), together with its timestamp and sequence number.

`lifecycle_state hpx::supervision::query_state(hpx::launch::sync_policy, hpx::id_type const &locality, hpx::id_type const &target, hpx::error_code &ec = hpx::throws)`

Query the last known lifecycle state of a target actor on a possibly remote locality, blocking until the result is available.

This is the synchronous equivalent of `query_state(hpx::id_type const&, hpx::id_type const&)`.

Note: The returned `lifecycle_state::ec` may carry a staleness error code, indicating that the returned state may be stale if a preceding observer parcel has not yet been delivered.

Parameters

- **locality** – [in] The locality on which the supervision manager responsible for *target* is running.
- **target** – [in] The actor (or component) whose state is queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *locality* does not represent a locality, or if *target* does not represent a valid target, unless *ec* was not pre-initialized to *hpx::throws*.

Returns

The last event recorded for *target*, together with its timestamp and sequence number.

```
lifecycle_state hpx::supervision::query_state(hpx::id_type const &target, hpx::error_code &ec =
                                             hpx::throws)
```

Query the last known lifecycle state of a target actor on the local locality.

Parameters

- **target** – [in] The actor (or component) whose state is queried. Must be local to the calling locality.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *target* does not represent a valid target, unless *ec* was not pre-initialized to *hpx::throws*.

Returns

The last event recorded locally for *target*, together with its timestamp and sequence number.

```
hpx::future<lifecycle_state> hpx::supervision::query_state(registry const &handle)
```

Query the last known lifecycle state of the local locality, as tracked by *handle*.

Convenience overload of `hpx::supervision::query_state(hpx::id_type const&, hpx::id_type const&)` that resolves both the locality and the target to *hpx::find_here()* instead of requiring the caller to name them explicitly. Forwards to `hpx::supervision::query_state(hpx::find_here(), hpx::find_here())`.

Parameters

handle – [in] The registry (typically returned by *init()*) whose locality's state is queried.

Returns

A future holding the last event recorded for the local locality, together with its timestamp, sequence number, and epoch (see *lifecycle_state::epoch* — in particular, useful for recovering the epoch *init()* started this locality's lifecycle tracking at, for use with *publish_event()*).

```
lifecycle_state hpx::supervision::query_state(hpx::launch::sync_policy policy, registry const &handle,
                                             hpx::error_code &ec = hpx::throws)
```

Query the last known lifecycle state of the local locality, as tracked by *handle*, blocking until the result is available.

This is the synchronous equivalent of `query_state(registry const&)`.

Parameters

- **policy** – Tag selecting the blocking overload of *query_state()*.
- **handle** – [in] The registry whose locality's state is queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *handle* does not hold a valid registry client, unless *ec* was pre-initialized to something other than *hpx::throws*.

Returns

The last event recorded for the local locality.

hpx::future<lifecycle_state> *hpx::supervision::query_state*(*registry* const &*handle*, *discovered_peer* const &*peer*)

Query the last known lifecycle state of a discovered peer's locality.

Convenience overload of *hpx::supervision::query_state*(*hpx::id_type* const&, *hpx::id_type* const&) that resolves both the locality and the target to *peer.locality* instead of requiring the caller to name them explicitly; mirroring the self-query overload above, but issued against *peer.locality*'s own supervision manager instead of the local one. Forwards to *hpx::supervision::query_state*(*peer.locality*, *peer.locality*).

Parameters

- **handle** – [in] Unused beyond overload resolution and symmetry with the self-query overload above; *peer* alone carries everything this call needs.
- **peer** – [in] The peer (typically returned by *discover_peers()*/ *discover_and_join()*) whose state is queried.

Returns

A future holding the last event recorded for *peer.locality*, as observed by the supervision manager running on *peer.locality*.

lifecycle_state *hpx::supervision::query_state*(*hpx::launch::sync_policy* *policy*, *registry* const &*handle*, *discovered_peer* const &*peer*, *hpx::error_code* &*ec* = *hpx::throws*)

Query the last known lifecycle state of a discovered peer's locality, blocking until the result is available.

This is the synchronous equivalent of *query_state*(*registry* const&, *discovered_peer* const&).

Parameters

- **policy** – Tag selecting the blocking overload of *query_state*().
- **handle** – [in] Unused beyond overload resolution; see the asynchronous overload.
- **peer** – [in] The peer whose state is queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *peer.locality* does not hold a valid registry client, unless *ec* was pre-initialized to something other than *hpx::throws*.

Returns

The last event recorded for *peer.locality*.

hpx::supervision::register_observer

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::supervision::publish_event`
- `hpx::supervision::query_state`
- `hpx::supervision::unregister_observer`
- `hpx::supervision::remove_target`
- `hpx::supervision::register_activity_observer`
- `hpx::supervision::unregister_activity_observer`
- `hpx::supervision::check_admission`
- `hpx::supervision::await_terminal`
- `hpx::supervision::is_valid_transition`

```
hpx::future<hpx::id_type> hpx::supervision::register_observer(hpx::id_type const &locality, hpx::id_type
                                                             const &target, lifecycle_callback const
                                                             &callback, std::optional<std::uint64_t>
                                                             epoch_filter = std::nullopt)
```

Register a callback to observe lifecycle events published by a target actor running on a possibly remote locality.

Note: If *locality* is the locality *target* is running on, the callback is invoked synchronously from within the publish call (best effort; the callback must not block indefinitely).

Note: If *locality* differs from the locality *target* is running on, the callback is invoked asynchronously via a dedicated parcel, with retry semantics (e.g., 3 attempts over 500 ms before logging failure).

Note: The callback must not throw; exceptions thrown from it are logged and do not affect the observer registration.

Parameters

- **locality** – [in] The locality on which the callback should be registered.
- **target** – [in] The actor (or component) to observe.
- **callback** – [in] The callback invoked whenever *target* publishes a lifecycle event.
- **epoch_filter** – [in] If set, restricts notifications to events published under this epoch; events published under any other epoch are silently skipped for this observer. If `std::nullopt` (the default), the observer is notified regardless of epoch.

Throws

`hpx::exception` – if *locality* does not represent a locality, or if *target* does not represent a valid target. The returned future becomes exceptional if the operation fails.

Returns

A future holding the global id of the observer handle. This handle must be passed to `unregister_observer()` in order to stop receiving notifications.

```
hpx::id_type hpx::supervision::register_observer(hpx::launch::sync_policy, hpx::id_type const &locality,
                                                hpx::id_type const &target, lifecycle_callback const
                                                &callback, std::optional<std::uint64_t> epoch_filter =
                                                std::nullopt, hpx::error_code &ec = hpx::throws)
```

Register a callback to observe lifecycle events published by a target actor running on a possibly remote locality, blocking until the registration has completed.

This is the synchronous equivalent of `register_observer(hpx::id_type const&, hpx::id_type const&, lifecycle_callback const&)`.

Parameters

- **locality** – [in] The locality on which the callback should be registered.
- **target** – [in] The actor (or component) to observe.
- **callback** – [in] The callback invoked whenever *target* publishes a lifecycle event.
- **epoch_filter** – [in] If set, restricts notifications to events published under this epoch; see the asynchronous overload for details.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Throws

`hpx::exception` – if *locality* does not represent a locality, or if *target* does not represent a valid target, unless *ec* was not pre-initialized to `hpx::throws`.

Returns

The global id of the observer handle. This handle must be passed to `unregister_observer()` in order to stop receiving notifications.

```
hpx::id_type hpx::supervision::register_observer(hpx::id_type const &target, lifecycle_callback const
                                                &callback, std::optional<std::uint64_t> epoch_filter =
                                                std::nullopt, hpx::error_code &ec = hpx::throws)
```

Register a callback to observe lifecycle events published by a target actor on the local locality.

Note: The callback is invoked synchronously from within the publish call (best effort; the callback must not block indefinitely) and must not throw; exceptions thrown from it are logged and do not affect the observer registration.

Parameters

- **target** – [in] The actor (or component) to observe. Must be local to the calling locality.
- **callback** – [in] The callback invoked whenever *target* publishes a lifecycle event.
- **epoch_filter** – [in] If set, restricts notifications to events published under this epoch; events published under any other epoch are silently skipped for this observer. If `std::nullopt` (the default), the observer is notified regardless of epoch.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Throws

hpx::exception – if *target* does not represent a valid target, unless *ec* was initialized to *hpx::throws*.

Returns

The global id of the observer handle. This handle must be passed to `unregister_observer()` in order to stop receiving notifications.

hpx::supervision::unregister_observer

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::supervision::publish_event*
- *hpx::supervision::query_state*
- *hpx::supervision::register_observer*
- *hpx::supervision::remove_target*
- *hpx::supervision::register_activity_observer*
- *hpx::supervision::unregister_activity_observer*
- *hpx::supervision::check_admission*
- *hpx::supervision::await_terminal*
- *hpx::supervision::is_valid_transition*

hpx::future<void> **hpx::supervision::unregister_observer**(*hpx::id_type* const &locality, *hpx::id_type* const &observer_handle)

Unregister a previously registered observer on a possibly remote locality.

Note: Once the returned future has become ready, no orphaned callbacks fire after unregistration completes.

Parameters

- **locality** – [in] The locality on which the observer was registered.
- **observer_handle** – [in] The handle returned by a prior call to `register_observer()`. Only handles returned from that function are accepted; passing a handle obtained from `register_activity_observer()` (or any foreign handle) is rejected.

Throws

hpx::exception – if *locality* does not represent a locality, or if *observer_handle* does not represent a valid observer handle. The returned future becomes exceptional if the operation fails.

Returns

A future that becomes ready once the observer has been unregistered.

```
void hpx::supervision::unregister_observer(hpx::launch::sync_policy, hpx::id_type const &locality,
                                          hpx::id_type const &observer_handle, hpx::error_code &ec =
                                          hpx::throws)
```

Unregister a previously registered observer on a possibly remote locality, blocking until the operation has completed.

This is the synchronous equivalent of `unregister_observer(hpx::id_type const&, hpx::id_type const&)`.

Note: No orphaned callbacks fire after unregistration completes.

Parameters

- **locality** – [in] The locality on which the observer was registered.
- **observer_handle** – [in] The handle returned by a prior call to `register_observer()`. See the asynchronous overload regarding foreign handles.
- **ec** – [in,out] this represents the error status on exit, if this pre-initialized to `hpx::throws` the function will throw on error instead.

Throws

`hpx::exception` – if *locality* does not represent a locality, or if *observer_handle* does not represent a valid observer handle, unless *ec* was initialized not to `hpx::throws`.

```
void hpx::supervision::unregister_observer(hpx::id_type const &observer_handle, hpx::error_code &ec =  
                                          hpx::throws)
```

Unregister a previously registered observer on the local locality.

Note: No orphaned callbacks fire after unregistration completes.

Parameters

- **observer_handle** – [in] The handle returned by a prior call to `register_observer()`. Must be local to the calling locality. See the remote overload regarding foreign handles.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Throws

`hpx::exception` – if *observer_handle* does not represent a valid observer handle, unless *ec* was not pre-initialized to `hpx::throws`.

`hpx::supervision::remove_target`

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::supervision::publish_event`
- `hpx::supervision::query_state`
- `hpx::supervision::register_observer`
- `hpx::supervision::unregister_observer`
- `hpx::supervision::register_activity_observer`

- *hpx::supervision::unregister_activity_observer*
- *hpx::supervision::check_admission*
- *hpx::supervision::await_terminal*
- *hpx::supervision::is_valid_transition*

hpx::future<void> hpx::supervision::remove_target(hpx::id_type const &locality, hpx::id_type const &target)

Clear all locally tracked state for a target on a possibly remote locality.

Unlike *unregister_observer()*, which removes a single previously registered observer handle, *remove_target()* unconditionally forgets every piece of local state held for *target* - its recorded lifecycle state (see *publish_event()* / *query_state()*) and any observers still registered for it (see *register_observer()*) - regardless of any specific observer handle.

Note: This is intended for callers that know *target* will never be queried or observed again locally (e.g. after a failed registration that seeded some state for it, or once a peer has been evicted), so that local state does not accumulate indefinitely. It is not itself a lifecycle event and does not affect *target's* state on any other locality.

Parameters

- **locality** – [in] The locality on which *target's* state is tracked.
- **target** – [in] The actor (or component) whose locally tracked state should be removed.

Throws

hpx::exception – if *locality* does not represent a locality, or if *target* does not represent a valid target. The returned future becomes exceptional if the operation fails.

Returns

A future that becomes ready once *target's* state has been removed.

void hpx::supervision::remove_target(hpx::launch::sync_policy, hpx::id_type const &locality, hpx::id_type const &target, hpx::error_code &ec = hpx::throws)

Clear all locally tracked state for a target on a possibly remote locality, blocking until the operation has completed.

This is the synchronous equivalent of *remove_target(hpx::id_type const&, hpx::id_type const&)*.

Parameters

- **locality** – [in] The locality on which *target's* state is tracked.
- **target** – [in] The actor (or component) whose locally tracked state should be removed.
- **ec** – [in,out] this represents the error status on exit, if this pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *locality* does not represent a locality, or if *target* does not represent a valid target, unless *ec* was initialized not to *hpx::throws*.

void hpx::supervision::remove_target(hpx::id_type const &target, hpx::error_code &ec = hpx::throws)

Clear all locally tracked state for a target on the local locality.

Parameters

- **target** – [in] The actor (or component) whose locally tracked state should be removed. Must be local to the calling locality.

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *target* does not represent a valid target, unless *ec* was not pre-initialized to *hpx::throws*.

hpx::supervision::register_activity_observer

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::supervision::publish_event*
- *hpx::supervision::query_state*
- *hpx::supervision::register_observer*
- *hpx::supervision::unregister_observer*
- *hpx::supervision::remove_target*
- *hpx::supervision::unregister_activity_observer*
- *hpx::supervision::check_admission*
- *hpx::supervision::await_terminal*
- *hpx::supervision::is_valid_transition*

```
hpx::future<hpx::id_type> hpx::supervision::register_activity_observer(hpx::id_type const &locality,  
                                                                    activity_callback const  
                                                                    &callback,  
                                                                    std::optional<std::uint64_t>  
                                                                    epoch_filter = std::nullopt)
```

Register a callback to observe activity-state transitions of all targets tracked on a possibly remote locality.

Note: For every target tracked on *locality* that is already `activity_state::active` at registration time, the new observer synchronously receives one replay notification (carrying `activity_transition::already_active`) as part of registration, taken under the same lock that serializes activity-state transitions. This guarantees the observer sees exactly one notification for each such target's current activity state: either the replay, or a live transition that raced with registration, but never both and never neither.

Note: If *locality* is the local locality, callbacks (including the registration-time replay) are invoked synchronously from within the call that triggered the transition (best effort; the callback must not block indefinitely).

Note: If *locality* is remote, callbacks are invoked asynchronously via a dedicated parcel, with retry semantics (e.g., 3 attempts over 500 ms before logging failure).

Note: The callback must not throw; exceptions thrown from it are logged and do not affect the observer registration.

Parameters

- **locality** – [in] The locality on which the callback should be registered.
- **callback** – [in] The callback invoked whenever any target tracked on *locality* transitions between *activity_state::inactive* and *activity_state::active*.
- **epoch_filter** – [in] If set, restricts notifications to transitions recorded under this epoch; transitions recorded under any other epoch are silently skipped for this observer. This also applies to the registration-time replay described below. If `std::nullopt` (the default), the observer is notified regardless of epoch.

Throws

hpx::exception – if *locality* does not represent a locality. The returned future becomes exceptional if the operation fails.

Returns

A future holding the global id of the observer handle. This handle must be passed to `unregister_activity_observer()` in order to stop receiving notifications.

```
hpx::id_type hpx::supervision::register_activity_observer(hpx::launch::sync_policy, hpx::id_type const
&locality, activity_callback const &callback,
std::optional<std::uint64_t> epoch_filter =
std::nullopt, hpx::error_code &ec =
hpx::throws)
```

Register a callback to observe activity-state transitions of all targets tracked on a possibly remote locality, blocking until the registration has completed.

This is the synchronous equivalent of `register_activity_observer(hpx::id_type const&, activity_callback const&, std::optional<std::uint64_t>)`.

Parameters

- **locality** – [in] The locality on which the callback should be registered.
- **callback** – [in] The callback invoked whenever any target tracked on *locality* transitions between *activity_state::inactive* and *activity_state::active*.
- **epoch_filter** – [in] If set, restricts notifications to transitions recorded under this epoch; see the asynchronous overload for details, including how this applies to the registration-time replay.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *locality* does not represent a locality, unless *ec* was not pre-initialized to *hpx::throws*.

Returns

The global id of the observer handle. This handle must be passed to `unregister_activity_observer()` in order to stop receiving notifications.

```
hpx::id_type hpx::supervision::register_activity_observer(activity_callback const &callback,
                                                         std::optional<std::uint64_t> epoch_filter =
                                                         std::nullopt, hpx::error_code &ec =
                                                         hpx::throws)
```

Register a callback to observe activity-state transitions of all targets tracked on the local locality.

Note: As for the remote overloads, for every target on the local locality that is already `activity_state::active` at registration time, one `activity_transition::already_active` replay notification is delivered synchronously as part of this call, taken under the same lock that serializes activity-state transitions, so the observer can neither miss nor double-receive any active target's current activity state.

Parameters

- **callback** – [in] The callback invoked whenever any target tracked on the local locality transitions between `activity_state::inactive` and `activity_state::active`.
- **epoch_filter** – [in] If set, restricts notifications to transitions recorded under this epoch, including the registration-time replay; see the remote overload for details. If `std::nullopt` (the default), the observer is notified regardless of epoch.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Throws

`hpx::exception` – if the operation fails, unless `ec` was initialized to `hpx::throws`.

Returns

The global id of the observer handle. This handle must be passed to `unregister_activity_observer()` in order to stop receiving notifications.

`hpx::supervision::unregister_activity_observer`

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::supervision::publish_event`
- `hpx::supervision::query_state`
- `hpx::supervision::register_observer`
- `hpx::supervision::unregister_observer`
- `hpx::supervision::remove_target`
- `hpx::supervision::register_activity_observer`
- `hpx::supervision::check_admission`
- `hpx::supervision::await_terminal`
- `hpx::supervision::is_valid_transition`

```
hpx::future<void> hpx::supervision::unregister_activity_observer(hpx::id_type const &locality,
                                                                hpx::id_type const
                                                                &observer_handle)
```


Unregister a previously registered activity observer on a possibly remote locality.

Note: Once the returned future has become ready, no orphaned callbacks fire after unregistration completes.

Parameters

- **locality** – [in] The locality on which the observer was registered.
- **observer_handle** – [in] The handle returned by a prior call to `register_activity_observer()`. Only handles returned from that function are accepted; passing a handle obtained from `register_observer()` (or any foreign handle) is rejected.

Throws

hpx::exception – if *locality* does not represent a locality, or if *observer_handle* does not represent a valid activity-observer handle. The returned future becomes exceptional if the operation fails.

Returns

A future that becomes ready once the observer has been unregistered.

```
void hpx::supervision::unregister_activity_observer(hpx::launch::sync_policy, hpx::id_type const
&locality, hpx::id_type const &observer_handle,
hpx::error_code &ec = hpx::throws)
```

Unregister a previously registered activity observer on a possibly remote locality, blocking until the operation has completed.

This is the synchronous equivalent of `unregister_activity_observer(hpx::id_type const&, hpx::id_type const&)`.

Note: No orphaned callbacks fire after unregistration completes.

Parameters

- **locality** – [in] The locality on which the observer was registered.
- **observer_handle** – [in] The handle returned by a prior call to `register_activity_observer()`. See the asynchronous overload regarding foreign handles.
- **ec** – [in,out] this represents the error status on exit, if this pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *locality* does not represent a locality, or if *observer_handle* does not represent a valid activity-observer handle, unless *ec* was initialized not to *hpx::throws*.

```
void hpx::supervision::unregister_activity_observer(hpx::id_type const &observer_handle,
hpx::error_code &ec = hpx::throws)
```

Unregister a previously registered activity observer on the local locality.

Note: No orphaned callbacks fire after unregistration completes.

Parameters

- **observer_handle** – [in] The handle returned by a prior call to `register_activity_observer()`. Must be local to the calling locality. See the remote overload regarding foreign handles.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

Throws

`hpx::exception` – if `observer_handle` does not represent a valid activity-observer handle, unless `ec` was not pre-initialized to `hpx::throws`.

hpx::supervision::check_admission

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::supervision::publish_event`
- `hpx::supervision::query_state`
- `hpx::supervision::register_observer`
- `hpx::supervision::unregister_observer`
- `hpx::supervision::remove_target`
- `hpx::supervision::register_activity_observer`
- `hpx::supervision::unregister_activity_observer`
- `hpx::supervision::await_terminal`
- `hpx::supervision::is_valid_transition`

dispatch_outcome `hpx::supervision::check_admission(hpx::id_type const &target, std::uint64_t epoch = 0)`

Check whether *target* currently admits new dispatch under *epoch*.

Queries the local supervision manager's terminal-latch state for *target* within *epoch*, i.e. the same state maintained by `publish_event()` and consulted by `await_terminal()`. Does not publish, mutate state, or notify observers.

Note: This is a pure local read of already-resident latch state, not a query that can fail the way a remote `publish_event()` call can; it never throws and carries no `hpx::error_code` out-parameter.

Note: The terminal latch consulted here is populated only by `publish_event()` calls delivered to *this* locality's supervision manager for *target*. It is not synchronized across localities: a terminal event published to a different locality's manager for the same logical target/epoch is invisible here and does not affect this call's outcome. `register_observer` / `unregister_observer` notifications do not feed this state either. Any locality other than the one hosting *target*'s supervision manager that needs to gate its own dispatch decisions on *target*'s terminal state must build that cross-locality propagation itself (e.g. registering an observer with the owning locality and re-publishing locally, or routing the admission decision to the owning locality); this API provides no such mechanism.

Parameters

- **target** – [in] The actor (or component) to check. Must be local to the calling locality.

- **epoch** – [in] The epoch dispatch would occur under.

Returns

`dispatch_outcome::rejected_fenced` if *target* has already latched a terminal event (completed or failed) under *epoch*, `dispatch_outcome::admitted` otherwise (including when *target* is unknown locally or invalid).

hpx::supervision::await_terminal

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::supervision::publish_event`
- `hpx::supervision::query_state`
- `hpx::supervision::register_observer`
- `hpx::supervision::unregister_observer`
- `hpx::supervision::remove_target`
- `hpx::supervision::register_activity_observer`
- `hpx::supervision::unregister_activity_observer`
- `hpx::supervision::check_admission`
- `hpx::supervision::is_valid_transition`

`hpx::future<lifecycle_state> hpx::supervision::await_terminal(hpx::id_type const &locality, hpx::id_type const &target, std::uint64_t epoch = 0, std::optional<std::chrono::steady_clock::duration> timeout = std::nullopt)`

Asynchronously wait for a target actor on a possibly remote locality to reach a terminal lifecycle event (completed or failed) within a given epoch.

The function `await_terminal()` is a one-shot, blocking-free counterpart to `register_observer()` for the specific case of waiting on the terminal transition: unlike an observer, it does not need to be explicitly unregistered, but it also only ever resolves once, for the exact (*target*, *epoch*) pair passed in.

Note: below for this call only. If `std::nullopt` (the default), *locality*'s current default timeout is used instead.

Note: below).

Note: *locality* bounds the lifetime of every waiter it registers on behalf of an outstanding call, so dropping the returned future without *target* ever reaching a terminal event under *epoch* does not leak the corresponding waiter entry indefinitely: it is swept and invalidated at or after *timeout* elapses, enforced by a background timer on *locality* independently of any further activity for *target*, so an idle target's waiter is not left to accumulate until some later, unrelated call happens to sweep it. Callers that need a tighter bound than *timeout* should still race the returned future against an external timeout.

Parameters

- **locality** – [in] The locality on which the supervision manager responsible for *target* is running.
- **target** – [in] The actor (or component) to wait on.
- **epoch** – [in] The epoch *target* must reach a terminal event under for the returned future to resolve. If *target*'s epoch is later superseded by a higher epoch (see the epoch semantics of *publish_event*) before it reaches a terminal event under *epoch*, the returned future becomes exceptional (see
- **timeout** – [in] Overrides the server-enforced timeout described in

Throws

- below) – instead of ever resolving with a value.
- *hpx::exception* – if *locality* does not represent a locality, or if *target* does not represent a valid target. The returned future becomes exceptional with a *hpx::error::stale_state* exception, naming *target*, *epoch*, and the epoch that superseded it, if *target*'s epoch advances past *epoch* before reaching a terminal event under it. It also becomes exceptional with a *hpx::error::future_cancelled* exception if neither of the above happens before *timeout* elapses (see

Returns

A future that becomes ready, holding the *lifecycle_state* recorded for *target*, as soon as *target* reaches a terminal event under *epoch*. If *target* has already reached a terminal event under *epoch* at the time of the call, the returned future is ready immediately.

```
lifecycle_state hpx::supervision::await_terminal(hpx::launch::sync_policy, hpx::id_type const &locality,  
                                                hpx::id_type const &target, std::uint64_t epoch = 0,  
                                                std::optional<std::chrono::steady_clock::duration>  
                                                timeout = std::nullopt, hpx::error_code &ec =  
                                                hpx::throws)
```

Wait for a target actor on a possibly remote locality to reach a terminal lifecycle event, blocking until it does.

This is the synchronous equivalent of *await_terminal*(*hpx::id_type* const&, *hpx::id_type* const&, *std::uint64_t*).

Note: This call blocks until *target* reaches a terminal event, its epoch is superseded, or *timeout* elapses.

Parameters

- **locality** – [in] The locality on which the supervision manager responsible for *target* is running.
- **target** – [in] The actor (or component) to wait on.
- **epoch** – [in] The epoch *target* must reach a terminal event under. See the asynchronous overload for details.
- **timeout** – [in] Overrides the server-enforced timeout described in the asynchronous overload for this call only. If *std::nullopt* (the default), *locality*'s current default timeout is used instead.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if *locality* does not represent a locality, or if *target* does not represent a valid target, unless *ec* was not pre-initialized to *hpx::throws*. Also throws (or sets *ec* to) a *hpx::error::stale_state* exception, naming *target*, *epoch*, and the epoch that superseded it, if *target*'s epoch advances past *epoch* before reaching a terminal event under it. Also throws (or sets *ec* to) a *hpx::error::future_cancelled* exception if neither of the above happens before *timeout* elapses.

Returns

The *lifecycle_state* recorded for *target* once it reaches a terminal event under *epoch*.

```
hpx::future<lifecycle_state> hpx::supervision::await_terminal(hpx::id_type const &target, std::uint64_t
    epoch = 0,
    std::optional<std::chrono::steady_clock::duration>
    timeout = std::nullopt)
```

Asynchronously wait for a target actor on the local locality to reach a terminal lifecycle event within a given epoch.

Note: As for the remote overloads, the returned future becomes exceptional with *hpx::error::stale_state* if *epoch* is superseded, or with *hpx::error::future_cancelled* if *timeout* elapses first.

Parameters

- **target** – [in] The actor (or component) to wait on. Must be local to the calling locality.
- **epoch** – [in] The epoch *target* must reach a terminal event under. See the remote overload for details.
- **timeout** – [in] Overrides the server-enforced timeout described in the asynchronous overload for this call only. If *std::nullopt* (the default), the local locality's default timeout is used instead.

Returns

A future that becomes ready, holding the *lifecycle_state* recorded for *target*, as soon as *target* reaches a terminal event under *epoch*. See the remote overload for how the returned future behaves if *target*'s epoch is superseded before reaching a terminal event under *epoch*.

```
lifecycle_state hpx::supervision::await_terminal(hpx::launch::sync_policy, hpx::id_type const &target,
    std::uint64_t epoch = 0,
    std::optional<std::chrono::steady_clock::duration>
    timeout = std::nullopt, hpx::error_code &ec =
    hpx::throws)
```

Synchronously wait for a local supervised target to reach a terminal lifecycle state (completed or failed).

This overload is restricted to targets that are guaranteed to be local to the calling locality. Because no dispatch/AGAS round-trip is required, it is cheaper than the remote *hpx::launch::sync_policy* overload and simply blocks the calling thread on the underlying local future.

Parameters

- **target** – The id of the supervised entity to wait on. Must refer to a component that is local to this locality.
- **epoch** – The join/generation epoch the caller expects *target* to still be part of. Passing an epoch that no longer matches the target's current epoch may cause the wait to resolve immediately with a mismatch-related error.

- **timeout** – Optional upper bound on how long to wait before giving up. If not supplied, uses the local supervision manager’s default timeout.
- **ec** – Used to report errors instead of throwing an exception. When `target` does not represent a valid id, `hpx::error::bad_parameter` is reported. If the wait is cancelled due to timeout elapsing without a terminal state being reached, `hpx::error::future_cancelled` is reported.

Throws

`hpx::exception` – if `ec` is `hpx::throws` (the default) and an error is encountered; otherwise sets `ec` to reflect the error and returns.

Returns

The terminal `lifecycle_state` observed for `target`, or a default-constructed `lifecycle_state` if an error occurred and `ec` was used to report it.

`hpx::supervision::is_valid_transition`

Defined in header `hpx/supervision.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::supervision::publish_event`
- `hpx::supervision::query_state`
- `hpx::supervision::register_observer`
- `hpx::supervision::unregister_observer`
- `hpx::supervision::remove_target`
- `hpx::supervision::register_activity_observer`
- `hpx::supervision::unregister_activity_observer`
- `hpx::supervision::check_admission`
- `hpx::supervision::await_terminal`

bool `hpx::supervision::is_valid_transition`(event from, event to) noexcept

Determine whether transitioning from lifecycle event *from* to lifecycle event *to* is permitted by the supervision lifecycle state machine.

`event::completed` and `event::failed` are terminal states and have no outgoing transitions. `event::losing_locality` is only reachable from `event::started`, `event::running`, or `event::suspending`, and may only transition to `failed`. A missing prior event is represented as `event::unknown`, from which the only valid transition is to `event::started`.

`hpx/supervision/server/supervision_manager.hpp`

Defined in header `hpx/supervision/server/supervision_manager.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

```
namespace supervision
```

```
namespace server
```

Variables

```
constexpr char const *const supervision_manager_name = "supervision_manager/"
```

```
struct observer_entry
```

Public Members

```
hpx::id_type agent
```

```
std::uint64_t epoch_filter
```

```
struct supervision_manager : public  
hpx::components::fixed_component_base<supervision_manager>
```

Public Types

```
using base_type = components::fixed_component_base<supervision_manager>
```

Public Functions

```
supervision_manager()
```

```
~supervision_manager()
```

```
void register_server_instance(char const *service_name, std::uint32_t locality_id,  
                             error_code &ec = throws)
```

```
void unregister_server_instance(error_code &ec = throws) const
```

```
publish_result publish_event(hpx::id_type const &target, event ev, std::uint64_t epoch)
```

Applies epoch/terminal-latch state-mutation rules, resolves any `await_terminal()` waiters affected by the transition, and invokes registered per-target lifecycle observers and activity observers for this call.

Parameters

- **target** – Target whose supervision state is updated. Must live on this locality.
- **ev** – Lifecycle event to apply.
- **epoch** – Epoch associated with ev.

Returns

The result of applying ev to target's state.

lifecycle_state **query_state**(hpx::id_type const &target)

hpx::id_type **register_observer**(hpx::id_type const &target, hpx::id_type const &agent,
std::uint64_t epoch_filter = static_cast<std::uint64_t>(-1))

void **unregister_observer**(hpx::id_type const &observer_handle)

void **remove_target**(hpx::id_type const &target)

Clears all locally tracked state for **target**.

Unlike `unregister_observer()`, which removes a single previously registered observer handle (and leaves any recorded lifecycle state for its target(s) intact), `remove_target()` unconditionally forgets every piece of local bookkeeping this supervision manager holds for **target** - its recorded lifecycle state and current epoch (see `publish_event()`), and any per-target observers still registered for it (see `register_observer()`) - regardless of any specific observer handle. Intended for callers that know **target** will never be queried or observed again locally (e.g. after a failed registration that seeded some state for it, or once a peer has been evicted) and want to reclaim that local state instead of letting it accumulate indefinitely.

void **tidy**()

Unconditionally clears all locally tracked state.

Snapshots every target currently present in `states_` or `observers_` under `mtx_`, releases the lock, then calls `remove_target()` for each one in turn, reusing its existing per-target teardown (waiter invalidation, activity-observer notifications, agent/state cleanup) instead of duplicating that logic here. Targets added concurrently with (or after) the snapshot are left untouched. If `states_` and `observers_` are empty at snapshot time, this is a no-op: `tidy()` never reports an error and never fires any notification of its own for the “nothing to do” case. Local-only: unlike `remove_target()`, this is not exposed as a remote action.

hpx::id_type **register_activity_observer**(hpx::id_type const &agent, std::uint64_t
epoch_filter = static_cast<std::uint64_t>(-1))

Registers a locality-scoped activity observer.

Replays targets that are already active when registration takes its snapshot.

The snapshot of the target’s tracked state and the insertion of the observer into the tracked set happen atomically under `mtx_`, which guarantees the observer receives exactly one notification for the target’s current state: either the replay (if already active at registration time) or a live transition that raced with registration, but never both and never neither.

Delivery of that notification (replay or live) happens after `mtx_` is released and is therefore not ordered relative to any other concurrent live notification for the same target; callers must not assume replay is delivered before or after a racing live event.

void **unregister_activity_observer**(hpx::id_type const &observer_handle)

Unregisters an activity observer.

The handle must have been returned by `register_activity_observer()`. As with `unregister_observer()`, no orphaned callbacks fire after this call completes. `observer_handle` must have been returned by `register_activity_observer()`; a handle returned by `register_observer()` instead (i.e. found in `agents_` rather than `activity_observers_`) is rejected.

hpx::future<lifecycle_state> **await_terminal**(hpx::id_type const &target, std::uint64_t epoch
= 0, std::chrono::steady_clock::duration timeout
= (std::chrono::steady_clock::duration::max)())

dispatch_outcome **check_admission**(hpx::id_type const &target, std::uint64_t epoch = 0)
const noexcept

Protected Types

```
using waiters_t = std::vector<waiter_entry>
```

```
using stale_waiters_t = std::vector<std::pair<std::uint64_t, waiters_t>>
```

```
using expired_waiters_t = std::vector<expired_waiter>
```

Protected Functions

```
hpx::future<void> fire_events(hpx::id_type const &target, lifecycle_event_notification const  
                             &notification)
```

```
hpx::future<void> fire_event(hpx::id_type const &target, hpx::id_type const &agent,  
                             lifecycle_event_notification notification)
```

```
hpx::future<void> deliver_activity_notification(activity_notification const  
                                                &notification,  
                                                std::vector<observer_entry> const  
                                                &observers)
```

```
hpx::future<void> fire_activity_event(hpx::id_type const &agent, activity_notification  
                                       notification)
```

```
void record_error(hpx::id_type const &target, std::uint64_t expected_sequence_number,  
                  hpx::error_code const &ec)
```

```
bool unregister_observer_target(hpx::id_type const &target, hpx::id_type const  
                                &observer_handle)
```

```
std::uint64_t current_epoch_for(hpx::id_type const &target) const
```

```
apply_event_outcome apply_event_and_resolve(hpx::id_type const &target, event ev,  
                                              std::uint64_t epoch)
```

```
waiters_t drain_terminal_waiters_locked(std::unique_lock<hpx::spinlock> &l,  
                                         hpx::id_type const &target, std::uint64_t  
                                         epoch, event last_event)
```

```
stale_waiters_t drain_stale_waiters_locked(std::unique_lock<hpx::spinlock> &l,  
                                             hpx::id_type const &target, std::uint64_t  
                                             epoch)
```

```
apply_result apply_new_epoch_locked(std::unique_lock<hpx::spinlock> &l, hpx::id_type  
                                     const &target, supervision::event ev, std::uint64_t  
                                     epoch)
```

```
std::optional<apply_result> apply_current_epoch_locked(std::unique_lock<hpx::spinlock>  
                                                         &l, hpx::id_type const &target,  
                                                         supervision::event ev,  
                                                         std::uint64_t epoch)
```

```
expired_waiters_t drain_expired_waiters_locked(std::unique_lock<hpx::spinlock> &l,  
                                                std::chrono::steady_clock::time_point  
                                                now)  
  
stale_waiters_t drain_all_waiters_for_target_locked(std::unique_lock<hpx::spinlock>  
                                                    &l, hpx::id_type const &target)  
  
void sweep_expired_waiters()  
  
void arm_sweep_timer_locked(std::unique_lock<hpx::spinlock> &&l)  
  
bool sweep_timer_callback()  
  
void recompute_earliest_deadline_locked(std::unique_lock<hpx::spinlock> &l)  
  
void remove_target_from_agents_locked(std::unique_lock<hpx::spinlock> &l,  
                                       hpx::id_type const &agent, hpx::id_type const  
                                       &target)
```

Protected Static Functions

```
static void invalidate_stale_waiters(hpx::id_type const &target, std::uint64_t epoch,  
                                     stale_waiters_t &stale)  
  
static void resolve_terminal_waiters(lifecycle_event_notification const &notification,  
                                       waiters_t &to_resolve)  
  
static void invalidate_expired_waiters(expired_waiters_t &expired)
```

Private Members

```
mutable hpx::spinlock mtx_  
  
hpx::spinlock sweep_timer_mtx_  
  
mutable std::string instance_name_  
  
std::map<hpx::id_type, lifecycle_state> states_  
  
std::map<hpx::id_type, std::vector<observer_entry>> observers_  
  
std::map<hpx::id_type, std::vector<hpx::id_type>> agents_  
  
std::vector<observer_entry> activity_observers_  
  
std::map<hpx::id_type, std::chrono::steady_clock::time_point> activated_at_  
  
std::map<waiter_key, waiters_t> waiters_
```

```
std::chrono::steady_clock::time_point earliest_deadline_ =  
(std::chrono::steady_clock::time_point::max())
```

```
hpx::util::pool_timer sweep_timer_
```

```
std::chrono::steady_clock::time_point armed_deadline_ =  
(std::chrono::steady_clock::time_point::max())
```

```
bool shutting_down_ = false
```

```
std::size_t callbacks_in_flight_ = 0
```

```
hpx::lcos::local::detail::condition_variable shutdown_cv_
```

```
struct apply_event_outcome
```

Public Members

```
publish_result result
```

```
lifecycle_event_notification notification
```

```
bool had_state_before = false
```

```
std::vector<observer_entry> activity_observers_snapshot
```

```
struct apply_result
```

Public Members

```
lifecycle_event_notification notification
```

```
waiters_t to_resolve
```

```
struct expired_waiter
```

Public Members

hpx::id_type **target**

std::uint64_t **epoch**

hpx::promise<lifecycle_state> **promise**

struct **waiter_entry**

Public Members

hpx::promise<lifecycle_state> **promise**

std::chrono::steady_clock::time_point **deadline**

struct **waiter_key**

Public Members

hpx::id_type **target**

std::uint64_t **epoch**

Friends

inline friend bool **operator<**(*waiter_key* const &lhs, *waiter_key* const &rhs)

inline friend bool **operator==**(*waiter_key* const &lhs, *waiter_key* const &rhs)

algorithms

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::experimental::task_canceled_exception

Defined in header `hpx/task_block.hpp`⁵⁹⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::experimental::task_block*

⁵⁹⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/task_block.hpp

- `hpx::experimental::define_task_block`
- `hpx::experimental::define_task_block_restore_thread`

class **task_canceled_exception** : public `hpx::exception`

The class `task_canceled_exception` defines the type of objects thrown by `task_block::run` or `task_block::wait` if they detect that an exception is pending within the current parallel region.

`hpx::experimental::task_block`

Defined in header `hpx/task_block.hpp`⁵⁹¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::experimental::task_canceled_exception`
- `hpx::experimental::define_task_block`
- `hpx::experimental::define_task_block_restore_thread`

template<typename **ExPolicy** = `hpx::execution::parallel_policy`>

class **task_block**

The class `task_block` defines an interface for forking and joining parallel tasks. The `define_task_block` and `define_task_block_restore_thread` function templates create an object of type `task_block` and pass a reference to that object to a user-provided callable object.

An object of class `task_block` cannot be constructed, destroyed, copied, or moved except by the implementation of the task region library. Taking the address of a `task_block` object via operator`&` or `addressof` is ill formed. The result of obtaining its address by any other means is unspecified.

A `task_block` is active if it was created by the nearest enclosing task block, where “task block” refers to an invocation of `define_task_block` or `define_task_block_restore_thread` and “nearest

enclosing” means the most recent invocation that has not yet completed. Code designated for execution in another thread by means other than the facilities in this section (e.g., using `thread` or `async`) are not enclosed in the task region and a `task_block` passed to (or captured by) such code is not active within that code. Performing any operation on a `task_block` that is not active results in undefined behavior.

The `task_block` that is active before a specific call to the `run` member function is not active within the asynchronous function that invoked `run`. (The invoked function should not, therefore, capture the `task_block` from the surrounding block.)

Example:

```
define_task_block([&](auto& tr) {
    tr.run([&] {
        tr.run([] { f(); });           // Error: tr is not active
        define_task_block([&](auto& tr) { // Nested task block
            tr.run(f);                 // OK: inner tr is active
            /// ...
        });
    }); /// ...
});
```

⁵⁹¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/task_block.hpp

Template Parameters

ExPolicy – The execution policy an instance of a task_block was created with. This defaults to *parallel_policy*.

hpx::experimental::define_task_block

Defined in header `hpx/task_block.hpp`⁵⁹².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::experimental::task_canceled_exception`
- `hpx::experimental::task_block`
- `hpx::experimental::define_task_block_restore_thread`

Warning: doxygenfunction: Unable to resolve function “hpx::experimental::define_task_block” with arguments (ExPolicy&&, F&&) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename ExPolicy, typename F> decltype(auto) define_task_block(ExPolicy &&  
  ↳ policy, F &&f)  
- template<typename F> void define_task_block(F &&f)
```

template<typename F>

void `hpx::experimental::define_task_block(F &&f)`

Constructs a task_block, *tr*, and invokes the expression *f(tr)* on the user-provided object, *f*. This version uses *parallel_policy* for task scheduling.

Postcondition: All tasks spawned from *f* have finished execution. A call to `define_task_block` may return on a different thread than that on which it was called.

Note: It is expected (but not mandated) that *f* will (directly or indirectly) call `tr.run(callable_object)`.

Template Parameters

F – The type of the user defined function to invoke inside the `define_task_block` (deduced). *F* shall be MoveConstructible.

Parameters

f – The user defined function to invoke inside the task block. Given a lvalue *tr* of type `task_block`, the expression, `(void)f(tr)`, shall be well-formed.

Throws

exception_list – specified in Exception Handling.

⁵⁹² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/task_block.hpp

hpx::experimental::define_task_block_restore_thread

Defined in header `hpx/task_block.hpp`⁵⁹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::experimental::task_canceled_exception`
- `hpx::experimental::task_block`
- `hpx::experimental::define_task_block`

```
template<typename ExPolicy, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::experimental::define_task_block_restore_thread(ExPolicy
&&policy,
F
&&f)
```

Constructs a `task_block`, `tr`, and invokes the expression $f(tr)$ on the user-provided object, f .

Postcondition: All tasks spawned from f have finished execution. A call to `define_task_block_restore_thread` always returns on the same thread as that on which it was called.

Note: It is expected (but not mandated) that f will (directly or indirectly) call `tr.run(callable_object)`.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the task block may be parallelized.
- **F** – The type of the user defined function to invoke inside the `define_task_block` (deduced). F shall be `MoveConstructible`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **f** – The user defined function to invoke inside the `define_task_block`. Given an lvalue tr of type `task_block`, the expression, `(void)f(tr)`, shall be well-formed.

Throws

`exception_list` – specified in Exception Handling.

```
template<typename F>
void hpx::experimental::define_task_block_restore_thread(F &&f)
```

Constructs a `task_block`, `tr`, and invokes the expression $f(tr)$ on the user-provided object, f . This version uses `parallel_policy` for task scheduling.

Postcondition: All tasks spawned from f have finished execution. A call to `define_task_block_restore_thread` always returns on the same thread as that on which it was called.

⁵⁹³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/task_block.hpp

Note: It is expected (but not mandated) that `f` will (directly or indirectly) call `tr.run(callable_object)`.

Template Parameters

F – The type of the user defined function to invoke inside the `define_task_block` (deduced). *F* shall be `MoveConstructible`.

Parameters

f – The user defined function to invoke inside the `define_task_block`. Given an lvalue *tr* of type `task_block`, the expression, `(void)f(tr)`, shall be well-formed.

Throws

exception_list – specified in Exception Handling.

hpx::experimental::run_on_all

Defined in header `hpx/task_block.hpp`⁵⁹⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Warning: doxygenfunction: Unable to resolve function “hpx::experimental::run_on_all” with arguments (ExPolicy&&, T&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename ExPolicy, typename T, typename ...Ts> decltype(auto) run_on_
  ↳ all(ExPolicy &&policy, T &&t, Ts&&... ts)
- template<typename T, typename ...Ts> decltype(auto) run_on_all(T &&t, Ts&&... ts)
```

Warning: doxygenfunction: Unable to resolve function “hpx::experimental::run_on_all” with arguments (T&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename ExPolicy, typename T, typename ...Ts> decltype(auto) run_on_
  ↳ all(ExPolicy &&policy, T &&t, Ts&&... ts)
- template<typename T, typename ...Ts> decltype(auto) run_on_all(T &&t, Ts&&... ts)
```

hpx::experimental::task_group

Defined in header `hpx/experimental/task_group.hpp`⁵⁹⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

class task_group

A *task_group* represents concurrent execution of a group of tasks. Tasks can be dynamically added to the group while it is executing.

⁵⁹⁴ [http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/task_block.](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/task_block.hpp)

hpp

⁵⁹⁵ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/experimental/task_group.hpp

hpx::ranges::fold_left

Defined in header `hpx/algorithm.hpp`⁵⁹⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::fold_left_first`
- `hpx::ranges::fold_right`
- `hpx::ranges::fold_right_last`
- `hpx::ranges::fold_left_with_iter`
- `hpx::ranges::fold_left_first_with_iter`

```
template<typename InIter, typename Sent, typename T, typename F>
auto hpx::ranges::fold_left(InIter first, Sent last, T init, F f)
```

Left-folds a range of elements using a binary operator.

Note: Complexity: Exactly N applications of the binary operator, where N = `std::distance(first, last)`.

Template Parameters

- **InIter** – The type of the source begin iterator (deduced). This iterator must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

The result of left-folding the range.

```
template<typename Rng, typename T, typename F>
auto hpx::ranges::fold_left(Rng &&rng, T init, F f)
```

Left-folds a range of elements using a binary operator.

Note: Complexity: Exactly N applications of the binary operator, where N = `std::distance(begin(rng), end(rng))`.

Template Parameters

⁵⁹⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Rng** – The type of the source range (deduced).
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

The result of left-folding the range.

hpx::ranges::fold_left_first

Defined in header [hpx/algorithm.hpp](#)⁵⁹⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- [hpx::ranges::fold_left](#)
- [hpx::ranges::fold_right](#)
- [hpx::ranges::fold_right_last](#)
- [hpx::ranges::fold_left_with_iter](#)
- [hpx::ranges::fold_left_first_with_iter](#)

```
template<typename InIter, typename Sent, typename F>  
auto hpx::ranges::fold_left_first(InIter first, Sent last, F f)
```

Left-folds a range using the first element as the initial value.

Note: Complexity: Exactly N-1 applications of the binary operator, where N = std::distance(first, last).

Template Parameters

- **InIter** – The type of the source begin iterator (deduced).
- **Sent** – The type of the source sentinel (deduced).
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence.
- **last** – Refers to the end of the sequence.
- **f** – Binary function object that will be applied.

Returns

An optional containing the fold result, or std::nullopt if the range is empty.

```
template<typename Rng, typename F>
```

⁵⁹⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

auto `hpx::ranges::fold_left_first`(*Rng* &&rng, *F* f)

Left-folds a range using the first element as the initial value.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements.
- **f** – Binary function object that will be applied.

Returns

An optional containing the fold result, or `std::nullopt` if the range is empty.

`hpx::ranges::fold_right`

Defined in header `hpx/algorithm.hpp`⁵⁹⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::fold_left`
- `hpx::ranges::fold_left_first`
- `hpx::ranges::fold_right_last`
- `hpx::ranges::fold_left_with_iter`
- `hpx::ranges::fold_left_first_with_iter`

template<typename **BidIter**, typename **Sent**, typename **T**, typename **F**>

auto `hpx::ranges::fold_right`(*BidIter* first, *Sent* last, *T* init, *F* f)

Right-folds a range of elements using a binary operator.

Note: Complexity: Exactly N applications of the binary operator.

Template Parameters

- **BidIter** – The type of the source begin iterator (deduced). This iterator must meet the requirements of a bidirectional iterator.
- **Sent** – The type of the source sentinel (deduced).
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence.
- **last** – Refers to the end of the sequence.
- **init** – The initial value for the fold operation.

⁵⁹⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **f** – Binary function object that will be applied.

Returns

The result of right-folding the range.

```
template<typename Rng, typename T, typename F>  
auto hpx::ranges::fold_right(Rng &&rng, T init, F f)
```

Right-folds a range of elements using a binary operator.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

The result of right-folding the range.

`hpx::ranges::fold_right_last`

Defined in header `hpx/algorithm.hpp`⁵⁹⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::fold_left`
- `hpx::ranges::fold_left_first`
- `hpx::ranges::fold_right`
- `hpx::ranges::fold_left_with_iter`
- `hpx::ranges::fold_left_first_with_iter`

```
template<typename BidIter, typename Sent, typename F>  
auto hpx::ranges::fold_right_last(BidIter first, Sent last, F f)
```

Right-folds a range using the last element as the initial value.

Template Parameters

- **BidIter** – The type of the source begin iterator (deduced).
- **Sent** – The type of the source sentinel (deduced).
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence.
- **last** – Refers to the end of the sequence.

⁵⁹⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **f** – Binary function object that will be applied.

Returns

An optional containing the fold result, or `std::nullopt` if the range is empty.

```
template<typename Rng, typename F>
auto hpx::ranges::fold_right_last(Rng &&rng, F f)
```

Right-folds a range using the last element as the initial value.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements.
- **f** – Binary function object that will be applied.

Returns

An optional containing the fold result, or `std::nullopt` if the range is empty.

hpx::ranges::fold_left_with_iter

Defined in header `hpx/algorithm.hpp`⁶⁰⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::fold_left`
- `hpx::ranges::fold_left_first`
- `hpx::ranges::fold_right`
- `hpx::ranges::fold_right_last`
- `hpx::ranges::fold_left_first_with_iter`

```
template<typename InIter, typename Sent, typename T, typename F>
auto hpx::ranges::fold_left_with_iter(InIter first, Sent last, T init, F f) ->
    fold_left_with_iter_result<InIter,
    std::decay_t<hpx::util::invoke_result_t<F&, T,
    hpx::traits::iter_reference_t<InIter>>>>
```

Left-folds a range and returns both the result and the end iterator.

Template Parameters

- **InIter** – The type of the source begin iterator (deduced).
- **Sent** – The type of the source sentinel (deduced).
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence.

⁶⁰⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **last** – Refers to the end of the sequence.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

A `fold_left_with_iter_result` containing the end iterator and the fold result.

```
template<typename Rng, typename T, typename F>
auto hpx::ranges::fold_left_with_iter(Rng &&rng, T init, F f) ->
    fold_left_with_iter_result<std::ranges::iterator_t<Rng>,
    std::decay_t<hpx::util::invoke_result_t<F&, T,
    hpx::traits::range_reference_t<Rng>>>>
```

Left-folds a range and returns both the result and the end iterator.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **T** – The type of the initial value.
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements.
- **init** – The initial value for the fold operation.
- **f** – Binary function object that will be applied.

Returns

A `fold_left_with_iter_result` containing the end iterator and the fold result.

`hpx::ranges::fold_left_first_with_iter`

Defined in header `hpx/algorithm.hpp`⁶⁰¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::fold_left`
- `hpx::ranges::fold_left_first`
- `hpx::ranges::fold_right`
- `hpx::ranges::fold_right_last`
- `hpx::ranges::fold_left_with_iter`

```
template<typename InIter, typename Sent, typename F>
auto hpx::ranges::fold_left_first_with_iter(InIter first, Sent last, F f) ->
    fold_left_first_with_iter_result<InIter,
    hpx::optional<std::decay_t<hpx::util::invoke_result_t<F&,
    hpx::traits::iter_reference_t<InIter>,
    hpx::traits::iter_reference_t<InIter>>>>>
```

Left-folds a range using the first element and returns both an optional result and the end iterator.

Template Parameters

⁶⁰¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **InIter** – The type of the source begin iterator (deduced).
- **Sent** – The type of the source sentinel (deduced).
- **F** – The type of the binary function object.

Parameters

- **first** – Refers to the beginning of the sequence.
- **last** – Refers to the end of the sequence.
- **f** – Binary function object that will be applied.

Returns

A `fold_left_first_with_iter_result` containing the end iterator and an optional with the fold result.

```
template<typename Rng, typename F>
auto hpx::ranges::fold_left_first_with_iter(Rng &&rng, F f) ->
    fold_left_first_with_iter_result<std::ranges::iterator_t<Rng>,
    hpx::optional<std::decay_t<hpx::util::invoke_result_t<F&,
    hpx::traits::range_reference_t<Rng>,
    hpx::traits::range_reference_t<Rng>>>>>
```

Left-folds a range using the first element and returns both an optional result and the end iterator.

Template Parameters

- **Rng** – The type of the source range (deduced).
- **F** – The type of the binary function object.

Parameters

- **rng** – Refers to the sequence of elements.
- **f** – Binary function object that will be applied.

Returns

A `fold_left_first_with_iter_result` containing the end iterator and an optional with the fold result.

hpx::ranges::fill

Defined in header `hpx/algorithm.hpp`⁶⁰².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::fill_n`

```
template<typename ExPolicy, typename Rng, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename hpx::traits::range_traits<Rng>::iterator_type>::type hpx::ranges::f
```

⁶⁰² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Assigns the given value to the elements in the range [first, last).

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename ExPolicy, typename Iter, typename Sent, typename T = typename  
std::iterator_traits<Iter>::value_type>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, Iter>::type hpx::ranges::fill(ExPolicy &&policy, Iter  
first, Sent last, T const  
&value)
```

Assigns the given value to the elements in the range [first, last).

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename Rng, typename T = typename std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
std::ranges::iterator_t<Rng> hpx::ranges::fill(Rng &&rng, T const &value)
```

Assigns the given value to the elements in the range [first, last).

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns *void*.

```
template<typename Iter, typename Sent, typename T = typename std::iterator_traits<Iter>::value_type>
Iter hpx::ranges::fill(Iter first, Sent last, T const &value)
```

Assigns the given value to the elements in the range [first, last).

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns *void*.

`hpx::ranges::fill_n`

Defined in header `hpx/algorithm.hpp`⁶⁰³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::fill`

```
template<typename ExPolicy, typename Rng, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::fill_n(ExPolicy
&&pol-
icy,
Rng
&&rng,
T
const
&value)
```

Assigns the given value value to the first count elements in the range beginning at first if count > 0. Does nothing otherwise.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

⁶⁰³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename ExPolicy, typename FwdIter, typename Size, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type hpx::ranges::fill_n(ExPolicy &&policy,
                                                                                      FwdIter first, Size
                                                                                      count, T const
                                                                                      &value)
```

Assigns the given value value to the first count elements in the range beginning at first if count > 0. Does nothing otherwise.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, for count > 0.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename Rng, typename T = typename std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
hpx::traits::range_traits<Rng>::iterator_type hpx::ranges::fill_n(Rng &&rng, T const &value)
```

Assigns the given value *value* to the first *count* elements in the range beginning at *first* if *count* > 0. Does nothing otherwise.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns an output iterator that compares equal to last.

```
template<typename FwdIter, typename Size, typename T = typename std::iterator_traits<FwdIter>::value_type>
FwdIter hpx::ranges::fill_n(Iterator first, Size count, T const &value)
```

Assigns the given value *value* to the first *count* elements in the range beginning at *first* if *count* > 0. Does nothing otherwise.

Note: Complexity: Performs exactly *count* assignments, for *count* > 0.

Template Parameters

- **Iterator** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns an output iterator that compares equal to last.

hpx::ranges::find

Defined in header [hpx/algorithm.hpp](#)⁶⁰⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::find_if`
- `hpx::ranges::find_if_not`
- `hpx::ranges::find_end`
- `hpx::ranges::find_first_of`
- `hpx::ranges::find_last`
- `hpx::ranges::find_last_if`
- `hpx::ranges::find_last_if_not`

Warning: doxygenfunction: Cannot find function “hpx::ranges::find” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::ranges::find_if

Defined in header [hpx/algorithm.hpp](#)⁶⁰⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::find`
- `hpx::ranges::find_if_not`
- `hpx::ranges::find_end`
- `hpx::ranges::find_first_of`
- `hpx::ranges::find_last`
- `hpx::ranges::find_last_if`
- `hpx::ranges::find_last_if_not`

Warning: doxygenfunction: Cannot find function “hpx::ranges::find_if” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

⁶⁰⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

⁶⁰⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

hpx::ranges::find_if_not

Defined in header [hpx/algorithm.hpp](#)⁶⁰⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::find`
- `hpx::ranges::find_if`
- `hpx::ranges::find_end`
- `hpx::ranges::find_first_of`
- `hpx::ranges::find_last`
- `hpx::ranges::find_last_if`
- `hpx::ranges::find_last_if_not`

Warning: doxygenfunction: Cannot find function “hpx::ranges::find_if_not” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::ranges::find_end

Defined in header [hpx/algorithm.hpp](#)⁶⁰⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::find`
- `hpx::ranges::find_if`
- `hpx::ranges::find_if_not`
- `hpx::ranges::find_first_of`
- `hpx::ranges::find_last`
- `hpx::ranges::find_last_if`
- `hpx::ranges::find_last_if_not`

Warning: doxygenfunction: Cannot find function “hpx::ranges::find_end” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

⁶⁰⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

⁶⁰⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

hpx::ranges::find_first_of

Defined in header [hpx/algorithm.hpp](#)⁶⁰⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::find`
- `hpx::ranges::find_if`
- `hpx::ranges::find_if_not`
- `hpx::ranges::find_end`
- `hpx::ranges::find_last`
- `hpx::ranges::find_last_if`
- `hpx::ranges::find_last_if_not`

Warning: doxygenfunction: Cannot find function “hpx::ranges::find_first_of” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::ranges::find_last

Defined in header [hpx/algorithm.hpp](#)⁶⁰⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::find`
- `hpx::ranges::find_if`
- `hpx::ranges::find_if_not`
- `hpx::ranges::find_end`
- `hpx::ranges::find_first_of`
- `hpx::ranges::find_last_if`
- `hpx::ranges::find_last_if_not`

Warning: doxygenfunction: Cannot find function “hpx::ranges::find_last” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

⁶⁰⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

⁶⁰⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

hpx::ranges::find_last_if

Defined in header [hpx/algorithm.hpp](#)⁶¹⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::find`
- `hpx::ranges::find_if`
- `hpx::ranges::find_if_not`
- `hpx::ranges::find_end`
- `hpx::ranges::find_first_of`
- `hpx::ranges::find_last`
- `hpx::ranges::find_last_if_not`

Warning: doxygenfunction: Cannot find function “hpx::ranges::find_last_if” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::ranges::find_last_if_not

Defined in header [hpx/algorithm.hpp](#)⁶¹¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::find`
- `hpx::ranges::find_if`
- `hpx::ranges::find_if_not`
- `hpx::ranges::find_end`
- `hpx::ranges::find_first_of`
- `hpx::ranges::find_last`
- `hpx::ranges::find_last_if`

Warning: doxygenfunction: Cannot find function “hpx::ranges::find_last_if_not” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

⁶¹⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

⁶¹¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

hpx::ranges::exclusive_scan

Defined in header [hpx/algorithm.hpp](#)⁶¹².

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter, typename Sent, typename OutIter, typename T = typename
std::iterator_traits<InIter>::value_type, typename Op = std::plus<T>>
exclusive_scan_result<InIter, OutIter> hpx::ranges::exclusive_scan(InIter first, Sent last, OutIter dest, T init,
                                                                Op &&op = Op())
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, *first, ..., *(first + (i - result) - 1)).

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aN*) is defined as:

- *a1* when *N* is 1
 - *op*(GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aK*), GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *aM*, ..., *aN*)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for **FwdIter1**.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

⁶¹² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename T = typename  
std::iterator_traits<FwdIter1>::value_type, typename Op = std::plus<T>>  
parallel::util::detail::algorithm_result<ExPolicy, exclusive_scan_result<FwdIter1, FwdIter2>>::type hpx::ranges::exclusive_sca
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, *first, ..., *(first + (i - result) - 1))`.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- *a1* when *N* is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter1.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns a `hpx::future<util::in_out_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `util::in_out_result<FwdIter1, FwdIter2>` otherwise. The *exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type, typename Op = std::plus<T>>
exclusive_scan_result<std::ranges::iterator_t<Rng>, O> hpx::ranges::exclusive_scan(Rng &&rng, O dest, T
init, Op &&op = Op())
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(+, init, *first, ..., *(first + (i - result) - 1))`

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate `std::plus<T>`.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)`
 - `GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN)` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename T = typename  
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type, typename Op = std::plus<T>>
```

`parallel::util::detail::algorithm_result<ExPolicy, exclusive_scan_result<std::ranges::iterator_t<Rng>, O>> hpx::ranges::exclusive`

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(+, init, *first, ..., *(first + (i - result) - 1))`

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the i th input element in the i th sum.

Note: Complexity: $O(last - first)$ applications of the predicate `std::plus<T>`.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)`
 - `GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN)` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns a `hpx::future<util::in_out_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *util::in_out_result<std::ranges::iterator_t<Rng>, O>* otherwise. The *exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::equal

Defined in header `hpx/algorithm.hpp`⁶¹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename  
Pred = equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::equal(ExPolicy &&policy, Iter1  
first1, Sent1 last1, Iter2 first2,  
Sent2 last2, Pred &&op =  
Pred(), Proj1 &&proj1 =  
Proj1(), Proj2 &&proj2 =  
Proj2())
```

Returns true if the range [first1, last1) is equal to the range [first2, last2), and false otherwise.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate *f*.

⁶¹³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: The two ranges are considered equal if, for every iterator i in the range $[first1, last1)$, $*i$ equals $*(first2 + (i - first1))$. This overload of `equal` uses `operator==` to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source iterators used for the end of the second range (deduced).
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *equal* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range `[first1, last1)` does not equal the length of the range `[first2, last2)`, it returns false.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = equal_to, typename Proj1 =  
hpx::identity, typename Proj2 = hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::equal(ExPolicy &&policy, Rng1  
                                         &&rng1, Rng2 &&rng2,  
                                         Pred &&op = Pred(), Proj1  
                                         &&proj1 = Proj1(), Proj2  
                                         &&proj2 = Proj2())
```

Returns true if the range `[first1, last1)` is equal to the range starting at `first2`, and false otherwise.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last1 - first1* applications of the predicate *f*.

Note: The two ranges are considered equal if, for every iterator *i* in the range `[first1, last1)`, **i* equals **(first2 + (i - first1))*. This overload of *equal* uses operator`==` to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.

- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *equal* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Pred = equal_to,
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
bool hpx::ranges::equal(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2, Pred &&op = Pred(), Proj1 &&proj1
                        = Proj1(), Proj2 &&proj2 = Proj2())
```

Returns true if the range [first1, last1) is equal to the range [first2, last2), and false otherwise.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate *f*.

Note: The two ranges are considered equal if, for every iterator *i* in the range [first1,last1), **i* equals **(first2 + (i - first1))*. This overload of *equal* uses `operator==` to determine if two elements are equal.

Template Parameters

- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source iterators used for the end of the second range (deduced).
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to *hpx::identity*

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range [first1, last1) does not equal the length of the range [first2, last2), it returns false.

```
template<typename Rng1, typename Rng2, typename Pred = equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
bool hpx::ranges::equal(Rng1 &&rng1, Rng2 &&rng2, Pred &&op = Pred(), Proj1 &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Returns true if the range [first1, last1) is equal to the range starting at first2, and false otherwise.

Note: Complexity: At most *last1 - first1* applications of the predicate *f*.

Note: The two ranges are considered equal if, for every iterator *i* in the range [first1,last1), **i* equals **(first2 + (i - first1))*. This overload of *equal* uses operator== to determine if two elements are equal.

Template Parameters

- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false.

`hpx::ranges::is_partitioned`

Defined in header `hpx/algorithm.hpp`⁶¹⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter, typename Sent, typename Pred, typename Proj = hpx::identity>
bool hpx::ranges::is_partitioned(FwdIter first, Sent last, Pred &&pred, Proj &&proj = Proj())
```

Determines if the range [first, last) is partitioned.

Note: Complexity: at most (N) predicate evaluations where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.
- **Pred** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`.

Parameters

⁶¹⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

`bool pred(const Type &a);`

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_partitioned* algorithm returns *bool*. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range *[first, last)* contains less than two elements, the function is always true.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred, typename Proj =  
hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::is_partitioned(ExPolicy  
                                                                 &&policy,  
                                                                 FwdIter first,  
                                                                 Sent last, Pred  
                                                                 &&pred, Proj  
                                                                 &&proj =  
                                                                 Proj())
```

Determines if the range *[first, last)* is partitioned.

The predicate operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (*N*) predicate evaluations where *N* = *distance*(*first*, *last*).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.

- **Pred** – The type of the function/function object to use (deduced). *Pred* must be *CopyConstructible* when using a parallel policy.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_partitioned* algorithm returns a *hpx::future<bool>* if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range [*first*, *last*) contains less than two elements, the function is always true.

```
template<typename Rng, typename Pred, typename Proj = hpx::identity>
bool hpx::ranges::is_partitioned(Rng &&rng, Pred &&pred, Proj &&proj = Proj())
```

Determines if the range *rng* is partitioned.

Note: Complexity: at most (*N*) predicate evaluations where *N* = `std::size(rng)`.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_partitioned* algorithm returns *bool*. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range *rng* contains less than two elements, the function is always true.

```
template<typename ExPolicy, typename Rng, typename Pred, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::is_partitioned(ExPolicy
                                                                 &&policy, Rng
                                                                 &&rng, Pred
                                                                 &&pred, Proj
                                                                 &&proj =
                                                                 Proj())
```

Determines if the range [first, last) is partitioned.

The predicate operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (*N*) predicate evaluations where *N* = `std::size(rng)`.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). *Pred* must be *CopyConstructible* when using a parallel policy.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_partitioned* algorithm returns a *hpx::future<bool>* if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range *rng* contains less than two elements, the function is always true.

hpx::ranges::set_intersection

Defined in header [hpx/algorithm.hpp](#)⁶¹⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Iter3, typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 =
hpx::identity>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, set_intersection_result<Iter1, Iter2, Iter3>>::type hpx::ranges::set_interse
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges [*first1*, *last1*) and [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

⁶¹⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

If some element is found m times in $[first1, last1)$ and n times in $[first2, last2)$, the first $\text{std::min}(m, n)$ elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.

- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *Iter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_intersection* algorithm returns a `hpx::future<ranges::set_intersection_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_intersection_result<Iter1, Iter2, Iter3>` otherwise. The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Iter3, typename Pred =
hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, set_intersection_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, std::ranges::iterator_t<Rng3>>>
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges [*first1*, *last1*) and [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found m times in $[first1, last1)$ and n times in $[first2, last2)$, the first $\text{std::min}(m, n)$ elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_intersection* algorithm returns a `hpx::future<ranges::set_intersection_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_intersection_result<Iter1, Iter2, Iter3>` otherwise. where *Iter1* is `range_iterator_t<Rng1>` and *Iter2* is `range_iterator_t<Rng2>` The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3, typename Pred
= hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
set_intersection_result<Iter1, Iter2, Iter3> hpx::ranges::set_intersection(Iter1 first1, Sent1 last1, Iter2 first2,
                                                                    Sent2 last2, Iter3 dest, Pred &&op
                                                                    = Pred(), Proj1 &&proj1 =
                                                                    Proj1(), Proj2 &&proj2 = Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges [*first1*, *last1*) and [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), the first `std::min(m, n)` elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter1*.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for *Iter2*.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *Iter1* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_intersection* algorithm returns `ranges::set_intersection_result<Iter1, Iter2, Iter3>`. The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2, typename Iter3, typename Pred = hpx::parallel::detail::less, typename  
Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```

set_intersection_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, Iter3> hpx::ranges::set_intersection(Rng1, Rng2, Iter3, dest, Pred, Proj1, Proj2)
    &&
    Rng1
    &&
    Iter3
    dest
    Pred
    &&
    =
    Pred
    Proj1
    &&
    =
    Proj1
    Proj2
    &&
    =
    Proj2

```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges *[first1, last1)* and *[first2, last2)*. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, the first `std::min(m, n)` elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *Iter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_intersection* algorithm returns *ranges::set_intersection_result<Iter1, Iter2, Iter3>*, where *Iter1* is *range_iterator_t<Rng1>* and *Iter2* is *range_iterator_t<Rng2>*. The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::ends_with

Defined in header `hpx/algorithm.hpp`⁶¹⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Pred =  
ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>  
bool hpx::ranges::ends_with(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2, Pred &&pred = Pred(), Proj1  
    &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Checks whether the second range defined by [first1, last1) matches the suffix of the first range defined by [first2, last2)

The assignments in the parallel *ends_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **Iter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the end source iterators used(deduced). This iterator type must meet the requirements of an sentinel for *Iter1*.
- **Iter2** – The type of the begin destination iterators used deduced). This iterator type must meet the requirements of a input iterator.

⁶¹⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Sent2** – The type of the end destination iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate *is* invoked.

Returns

The *ends_with* algorithm returns *bool*. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2,
typename Pred = ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, bool>::type hpx::ranges::ends_with(ExPolicy &&policy,
                                                                                      FwdIter1 first1, Sent1
                                                                                      last1, FwdIter2 first2,
                                                                                      Sent2 last2, Pred
                                                                                      &&pred = Pred(), Proj1
                                                                                      &&proj1 = Proj1(),
                                                                                      Proj2 &&proj2 =
                                                                                      Proj2())
```

Checks whether the second range defined by [first1, last1) matches the suffix of the first range defined by [first2, last2)

The assignments in the parallel *ends_with* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *ends_with* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used(deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **FwdIter2** – The type of the begin destination iterators used deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the end destination iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate *is* invoked.

Returns

The *ends_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

```
template<typename Rng1, typename Rng2, typename Pred = ranges::equal_to, typename Proj1 = hpx::identity,
typename Proj2 = hpx::identity>
bool hpx::ranges::ends_with(Rng1 &&rng1, Rng2 &&rng2, Pred &&pred = Pred(), Proj1 &&proj1 = Proj1(),
                           Proj2 &&proj2 = Proj2())
```

Checks whether the second range *rng2* matches the suffix of the first range *rng1*.

The assignments in the parallel *ends_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most $\min(N1, N2)$ applications of the predicate and both projections.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate *is* invoked.

Returns

The *ends_with* algorithm returns *bool*. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = ranges::equal_to, typename
Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, bool>::type hpx::ranges::ends_with(ExPolicy &&policy,
                                                                                          Rng1 &&rng1,
                                                                                          Rng2 &&rng2, Pred
                                                                                          &&pred = Pred(),
                                                                                          Proj1 &&proj1 =
                                                                                          Proj1(), Proj2
                                                                                          &&proj2 = Proj2())
```

Checks whether the second range *rng2* matches the suffix of the first range *rng1*.

The assignments in the parallel *ends_with* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *ends_with* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear: at most $\min(N1, N2)$ applications of the predicate and both projections.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate *is* invoked.

Returns

The *ends_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

hpx::ranges::min_element

Defined in header [hpx/algorithm.hpp](#)⁶¹⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ranges::max_element*
- *hpx::ranges::minmax_element*

⁶¹⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
template<typename FwdIter, typename Sent, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
FwdIter hpx::ranges::min_element(FwdIter first, Sent last, F &&f = F(), Proj &&proj = Proj())
```

Finds the smallest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *min_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const* &, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *min_element* algorithm returns *FwdIter*. The *min_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename Rng, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
std::ranges::iterator_t<Rng> hpx::ranges::min_element(Rng &&rng, F &&f = F(), Proj &&proj = Proj())
```

Finds the smallest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *min_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `min_element` algorithm returns a `hpx::traits::range_iterator<Rng>::type` otherwise. The `min_element` algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename F = hpx::parallel::detail::less,
typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::min_element(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter first,
                                                                                               Sent last, F &&f
                                                                                               = F(), Proj
                                                                                               &&proj = Proj())
```

Finds the smallest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel `min_element` algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel `min_element` algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.

- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for `FwdIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of `min_element` requires `F` to meet the requirements of `CopyConstructible`.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type `Type1` must be such that objects of type `FwdIter` can be dereferenced and then implicitly converted to `Type1`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `min_element` algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `FwdIter` otherwise. The `min_element` algorithm returns the iterator to the smallest element in the range `[first, last)`. If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename ExPolicy, typename Rng, typename F = hpx::parallel::detail::less, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::min_element(ExPolicy
&&pol-
icy,
Rng
&&rng,
F
&&f
=
F(),
Proj
&&proj
=
Proj())
```

Finds the smallest element in the range `[first, last)` using the given comparison function `f`.

The comparisons in the parallel `min_element` algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The comparisons in the parallel *min_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *min_element* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *min_element* algorithm returns a `hpx::future<hpx::traits::range_iterator<Rng>::type>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *min_element* algorithm returns the iterator to the smallest element in the range `[first, last)`. If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

hpx::ranges::max_element

Defined in header `hpx/algorithm.hpp`⁶¹⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::min_element`
- `hpx::ranges::minmax_element`

⁶¹⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
template<typename FwdIter, typename Sent, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
FwdIter hpx::ranges::max_element(FwdIter first, Sent last, F &&f = F(), Proj &&proj = Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *max_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the This argument is optional and defaults to *std::less*. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const &*, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *max_element* algorithm returns a *FwdIter*. The *max_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename Rng, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> hpx::ranges::max_element(Rng &&rng, F &&f = F(), Proj &&proj = Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *max_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the This argument is optional and defaults to *std::less*. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const &*, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *max_element* algorithm returns a *hpx::traits::range_iterator<Rng>::type* otherwise. The *max_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename F = hpx::parallel::detail::less,
typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::max_element(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter first,
                                                                                               Sent last, F &&f
                                                                                               = F(), Proj
                                                                                               &&proj = Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *max(N-1, 0)* comparisons, where *N* = *std::distance*(first, last).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *max_element* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the This argument is optional and defaults to `std::less`. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *max_element* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *max_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename ExPolicy, typename Rng, typename F = hpx::parallel::detail::less, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::max_element(ExPolicy
&&pol-
icy,
Rng
&&rng,
F
&&f
=
F(),
Proj
&&proj
=
Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *max_element* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the This argument is optional and defaults to *std::less*. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const &*, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *max_element* algorithm returns a `hpx::future<hpx::traits::range_iterator<Rng>::type>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *max_element* algorithm returns the iterator to the smallest element in the range `[first, last)`. If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

hpx::ranges::minmax_element

Defined in header [hpx/algorithm.hpp](#)⁶¹⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::min_element`
- `hpx::ranges::max_element`

```
template<typename FwdIter, typename Sent, typename F = hpx::parallel::detail::less, typename Proj =
hpx::identity>
minmax_element_result<FwdIter> hpx::ranges::minmax_element(FwdIter first, Sent last, F &&f = F(), Proj
&&proj = Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The assignments in the parallel *minmax_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: At most $\max(\text{floor}(3/2 * (N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for **FwdIter**.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. This argument is optional and defaults to `std::less`. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

⁶¹⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *minmax_element* algorithm returns a *minmax_element_result*<*FwdIter*, *FwdIter*>. The *min_max_element* algorithm returns a *min_max_result* consisting of an iterator to the smallest element as the min element and an iterator to the greatest element as the max element. Returns *minmax_element_result*{first, first} if the range is empty. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

```
template<typename Rng, typename F = hpx::parallel::detail::less, typename Proj = hpx::identity>
minmax_element_result<std::ranges::iterator_t<Rng>> hpx::ranges::minmax_element(Rng &&rng, F &&f =
                                                    F(), Proj &&proj =
                                                    Proj())
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The assignments in the parallel *minmax_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: At most $\max(\text{floor}(3/2*(N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. This argument is optional and defaults to *std::less*. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const &*, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *minmax_element* algorithm returns a *minmax_element_result*<*hpx::traits::range_iterator*<*Rng*>::type, *hpx::traits::range_iterator*<*Rng*>::type>. The *minmax_element* algorithm returns a *min_max_result* consisting of an range iterator to the smallest element as the min element and an range iterator to the greatest element as the max element. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename F = hpx::parallel::detail::less,
typename Proj = hpx::identity>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, minmax_element_result<FwdIter>> hpx::ranges::minmax_element(ExPo
&&p
icy,
FwdI
first,
Sent
last,
F
&&f
=
F(),
Proj
&&p
=
Proj(
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\max(\text{floor}(3/2 * (N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *minmax_element* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. This argument is optional and defaults to *std::less*. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *minmax_element* algorithm returns a *minmax_element_result*<*FwdIter*, *FwdIter*>. The *min-max_element* algorithm returns a *min_max_result* consisting of an iterator to the smallest element as the min element and an iterator to the greatest element as the max element. Returns *minmax_element_result*{first, first} if the range is empty. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

```
template<typename ExPolicy, typename Rng, typename F = hpx::parallel::detail::less, typename Proj =  
hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, minmax_element_result<std::ranges::iterator_t<Rng>>> hpx::ranges::minm
```

Finds the greatest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\max(\text{floor}(3/2 * (N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *minmax_element* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the the left argument is less than the right element. This argument is optional and defaults to `std::less`. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *minmax_element* algorithm returns a *minmax_element_result*<*hpx::traits::range_iterator*<*Rng*>::type, *hpx::traits::range_iterator*<*Rng*>::type>. The *minmax_element* algorithm returns a *min_max_result* consisting of an range iterator to the smallest element as the min element and an range iterator to the greatest element as the max element. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

hpx::ranges::set_difference

Defined in header [hpx/algorithm.hpp](#)⁶²⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3, typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

⁶²⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

hpx::parallel::util::detail::algorithm_result<ExPolicy, set_difference_result<Iter1, Iter3>>::type *hpx::ranges::set_difference*(*Ex*

Constructs a sorted range beginning at *dest* consisting of all elements present in the range [*first1*, *last1*) and not present in the range [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

Equivalent elements are treated individually, that is, if some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), it will be copied to *dest* exactly `std::max(m-n, 0)` times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N_1 + N_2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_difference* algorithm returns a `hpx::future<ranges::set_difference_result<Iter1, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns

ranges::set_difference_result<Iter1, Iter3> otherwise. The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Iter3, typename Pred =  
hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, set_difference_result<std::ranges::iterator_t<Rng1>, Iter3>> hpx::ranges::se
```

Constructs a sorted range beginning at *dest* consisting of all elements present in the range *[first1, last1)* and not present in the range *[first2, last2)*. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

Equivalent elements are treated individually, that is, if some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, it will be copied to *dest* exactly *std::max(m-n, 0)* times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_difference* algorithm returns a `hpx::future<ranges::set_difference_result<Iter1, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_difference_result<Iter1, Iter3>` otherwise. where *Iter1* is `range_iterator_t<Rng1>` and *Iter2* is `range_iterator_t<Rng2>` The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3, typename Pred
= hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
set_difference_result<Iter1, Iter3> hpx::ranges::set_difference(Iter1 first1, Sent1 last1, Iter2 first2, Sent2
                                                             last2, Iter3 dest, Pred &&op = Pred(), Proj1
                                                             &&proj1 = Proj1(), Proj2 &&proj2 =
                                                             Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in the range `[first1, last1)` and not

present in the range `[first2, last2)`. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

Equivalent elements are treated individually, that is, if some element is found *m* times in `[first1, last1)` and *n* times in `[first2, last2)`, it will be copied to *dest* exactly `std::max(m-n, 0)` times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_difference* algorithm returns *ranges::set_difference_result<Iter1, Iter3>*. The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2, typename Iter3, typename Pred = hpx::parallel::detail::less, typename
Proj1 = hpx::identity, typename Proj2 = hpx::identity>
set_difference_result<std::ranges::iterator_t<Rng1>, Iter3> hpx::ranges::set_difference(Rng1 &&rng1,
                                                                                      Rng2 &&rng2, Iter3
                                                                                      dest, Pred &&op =
                                                                                      Pred(), Proj1
                                                                                      &&proj1 = Proj1(),
                                                                                      Proj2 &&proj2 =
                                                                                      Proj2())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in the range [*first1*, *last1*) and not present in the range [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

Equivalent elements are treated individually, that is, if some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), it will be copied to *dest* exactly `std::max(m-n, 0)` times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *Iter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_difference* algorithm returns `ranges::set_difference_result<Iter1, Iter3>`. where *Iter1* is `range_iterator_t<Rng1>` and *Iter2* is `range_iterator_t<Rng2>` The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

`hpx::ranges::uninitialized_value_construct`

Defined in header `hpx/algorithm.hpp`⁶²¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::uninitialized_value_construct_n`

```
template<typename FwdIter, typename Sent>
```

```
FwdIter hpx::ranges::uninitialized_value_construct(FwdIter first, Sent last)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects.

⁶²¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *uninitialized_value_construct* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

Returns

The *uninitialized_value_construct* algorithm returns a returns *FwdIter*. The *uninitialized_value_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

```
template<typename ExPolicy, typename FwdIter, typename Sent>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::uninitialized_value_construct(ExPolicy
&&pol-
icy,
FwdIter
first,
Sent
last)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

Returns

The *uninitialized_value_construct* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_value_construct* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename Rng>
```

```
hpx::traits::range_traits<Rng>::iterator_type hpx::ranges::uninitialized_value_construct(Rng &&rng)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

rng – Refers to the range to which will be value constructed.

Returns

The *uninitialized_value_construct* algorithm returns a *hpx::traits::range_traits<Rng>::iterator_type*. The *uninitialized_value_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

```
template<typename ExPolicy, typename Rng>
```

```
parallel::util::detail::algorithm_result<ExPolicy, typename hpx::traits::range_traits<Rng>::iterator_type>::type hpx::ranges::unini
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range to which the value will be value constructed

Returns

The *uninitialized_value_construct* algorithm returns a `hpx::future<typename hpx::traits::range_traits<Rng>::iterator_type>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *typename hpx::traits::range_traits<Rng>::iterator_type* otherwise. The *uninitialized_value_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

hpx::ranges::uninitialized_value_construct_n

Defined in header `hpx/algorithm.hpp`⁶²².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::uninitialized_value_construct`

```
template<typename FwdIter, typename Size>
```

```
FwdIter hpx::ranges::uninitialized_value_construct_n(FwdIter first, Size count)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range `[first, first + count)` by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct_n* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

⁶²² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_value_construct_n* algorithm returns a *FwdIter*. The *uninitialized_value_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename ExPolicy, typename FwdIter, typename Size>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::uninitialized_value_construct_n(ExPolicy
&&pol-
icy,
FwdIter
first,
Size
count)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range `[first, first + count)` by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_value_construct_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_value_construct_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_value_construct_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_value_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::ranges::shift_left

Defined in header [hpx/algorithm.hpp](#)⁶²³.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter, typename Sent, typename Size>
FwdIter hpx::ranges::shift_left(FwdIter first, Sent last, Size n)
```

Shifts the elements in the range [first, last) by *n* positions towards the beginning of the range. For every integer *i* in [0, last - first

- *n*), moves the element originally at position first + *n* + *i* to position first + *i*.

The assignment operations in the parallel *shift_left* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most (last - first) - *n* assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **n** – Refers to the number of positions to shift.

⁶²³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *shift_left* algorithm returns *FwdIter*. The *shift_left* algorithm returns an iterator to the end of the resulting range.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Size>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::shift_left(ExPolicy
                                                                                               &&policy, FwdIter
                                                                                               first, Sent last, Size
                                                                                               n)
```

Shifts the elements in the range [first, last) by *n* positions towards the beginning of the range. For every integer *i* in [0, last - first

- *n*), moves the element originally at position first + *n* + *i* to position first + *i*.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most (last - first) - *n* assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *shift_left* algorithm returns an iterator to the end of the resulting range.

```
template<typename Rng, typename Size>
std::ranges::iterator_t<Rng> hpx::ranges::shift_left(Rng &&rng, Size n)
```

Shifts the elements in the range [first, last) by *n* positions towards the beginning of the range. For every integer *i* in [0, last - first

- *n*), moves the element originally at position first + *n* + *i* to position first + *i*.

The assignment operations in the parallel *shift_left* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most (last - first) - *n* assignments.

Note: The type of dereferenced *std::ranges::iterator_t<Rng>* must meet the requirements of *MoveAssignable*.

Template Parameters

- **Rng** – The type of the range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **rng** – Refers to the range in which the elements will be shifted.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns *std::ranges::iterator_t<Rng>*. The *shift_left* algorithm returns an iterator to the end of the resulting range.

```
template<typename ExPolicy, typename Rng, typename Size>
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::shift_left(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     Rng
                                                                                                     &&rng,
                                                                                                     Size
                                                                                                     n)
```

Shifts the elements in the range [first, last) by *n* positions towards the beginning of the range. For every integer *i* in [0, last - first

- *n*), moves the element originally at position first + *n* + *i* to position first + *i*.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced `std::ranges::iterator_t<Rng>` must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range in which the elements will be shifted.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::ranges::iterator_t<Rng>` otherwise. The *shift_left* algorithm returns an iterator to the end of the resulting range.

hpx::ranges::adjacent_difference

Defined in header [hpx/algorithm.hpp](#)⁶²⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter1, typename FwdIter2, typename Sent>
FwdIter2 hpx::ranges::adjacent_difference(FwdIter1 first, Sent last, FwdIter2 dest)
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **FwdIter1** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.

⁶²⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename Rng, typename FwdIter2>
FwdIter2 hpx::ranges::adjacent_difference(Rng &&rng, FwdIter2 dest)
```

Searches the *rng* for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::ranges::adjacent_difference(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     FwdIter1
                                                                                                     first,
                                                                                                     Sent
                                                                                                     last,
                                                                                                     FwdIter2
                                                                                                     dest)
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename ExPolicy, typename Rng, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::ranges::adjacent_difference(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     Rng
                                                                                                     &&rng,
                                                                                                     FwdIter2
                                                                                                     dest)
```

Searches the *rng* for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements.

```
template<typename FwdIter1, typename Sent, typename FwdIter2, typename Op>
FwdIter2 hpx::ranges::adjacent_difference(FwdIter1 first, Sent last, FwdIter2 dest, Op &&op)
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **FwdIter1** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Binary operation function object that will be applied. The signature of the function should be equivalent to the following:

Ret fun(const Type1 &a, const Type2 &b);
--

The signature does not need to have const &. The types *Type1* and *Type2* must be such that an object of type *iterator_traits<InputIt>::value_type* can be implicitly converted to both of them. The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename Rng, typename FwdIter2, typename Op>
FwdIter2 hpx::ranges::adjacent_difference(Rng &&rng, FwdIter2 dest, Op &&op)
```

Searches the *rng* for two consecutive identical elements.

Template Parameters

- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *Copy-Constructible*.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Binary operation function object that will be applied. The signature of the function should be equivalent to the following:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`. The types *Type1* and *Type2* must be such that an object of type *iterator_traits<InputIt>::value_type* can be implicitly converted to both of them. The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename Op>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::ranges::adjacent_difference(ExPolicy
                                                                                               &&pol-
                                                                                               icy,
                                                                                               FwdIter1
                                                                                               first,
                                                                                               Sent
                                                                                               last,
                                                                                               FwdIter2
                                                                                               dest,
                                                                                               Op
                                                                                               &&op)
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.

- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Binary operation function object that will be applied. The signature of the function should be equivalent to the following:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`. The types *Type1* and *Type2* must be such that an object of type *iterator_traits<InputIt>::value_type* can be implicitly converted to both of them. The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename ExPolicy, typename Rng, typename FwdIter2, typename Op>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::ranges::adjacent_difference(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     Rng
                                                                                                     &&rng,
                                                                                                     FwdIter2
                                                                                                     dest,
                                                                                                     Op
                                                                                                     &&op)
```

Searches the *rng* for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter2** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *Copy-Constructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Binary operation function object that will be applied. The signature of the function should be equivalent to the following:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`. The types *Type1* and *Type2* must be such that an object of type *iterator_traits<InputIt>::value_type* can be implicitly converted to both of them. The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *adjacent_difference* algorithm returns an iterator to the first of the identical elements.

hpx::ranges::adjacent_find

Defined in header `hpx/algorithm.hpp`⁶²⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter, typename Sent, typename Proj = hpx::identity, typename Pred = detail::equal_to>
FwdIter hpx::ranges::adjacent_find(FwdIter first, Sent last, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **FwdIter** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*
- **Pred** – The type of an optional function/function object to use.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.

⁶²⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *adjacent_find* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Proj = hpx::identity, typename Pred
= detail::equal_to>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type hpx::ranges::adjacent_find(ExPolicy
&&policy,
FwdIter first,
Sent last, Pred
&&pred =
Pred(), Proj
&&proj =
Proj())
```

Searches the range [first, last) for two consecutive identical elements. This version uses the given binary predicate *pred*.

The comparison operations in the parallel *adjacent_find* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *adjacent_find* invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

This overload of *adjacent_find* is available if the user decides to provide their algorithm their own binary predicate *pred*.

Note: Complexity: Exactly the smaller of (result - first) + 1 and (last - first) - 1 application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.

- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *adjacent_find* algorithm returns a *hpx::future<InIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *InIter* otherwise. The *adjacent_find* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename Rng, typename Proj = hpx::identity, typename Pred = detail::equal_to>
hpx::traits::range_traits<Rng>::iterator_type hpx::ranges::adjacent_find(Rng &&rng, Pred &&pred =
                                                                    Pred(), Proj &&proj = Proj())
```

Searches the range *rng* for two consecutive identical elements.

Note: Complexity: Exactly the smaller of $(\text{result} - \text{std::begin}(\text{rng})) + 1$ and $(\text{std::begin}(\text{rng}) - \text{std::end}(\text{rng})) - 1$ applications of the predicate where *result* is the value returned

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*
- **Pred** – The type of an optional function/function object to use.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *adjacent_find* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename ExPolicy, typename Rng, typename Proj = hpx::identity, typename Pred = detail::equal_to>
parallel::util::detail::algorithm_result<ExPolicy, typename hpx::traits::range_traits<Rng>::iterator_type>::type hpx::ranges::adjac
```

Searches the range *rng* for two consecutive identical elements.

The comparison operations in the parallel *adjacent_find* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *adjacent_find* invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

This overload of *adjacent_find* is available if the user decides to provide their algorithm their own binary predicate *pred*.

Note: Complexity: Exactly the smaller of $(\text{result} - \text{std::begin}(\text{rng})) + 1$ and $(\text{std::begin}(\text{rng}) - \text{std::end}(\text{rng})) - 1$ applications of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *adjacent_find* algorithm returns a *hpx::future<InIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *InIter* otherwise. The *adjacent_find* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

hpx::ranges::set_symmetric_difference

Defined in header `hpx/algorithm.hpp`⁶²⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename  
Iter3, typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 =  
hpx::identity>
```

⁶²⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

hpx::parallel::util::detail::algorithm_result<ExPolicy, set_symmetric_difference_result<Iter1, Iter2, Iter3>>::type hpx::ranges::set

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges *[first1, last1)* and *[first2, last2)*, but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, it will be copied to *dest* exactly $\text{std::abs}(m-n)$ times. If $m > n$, then the last $m-n$ of those elements are copied from *[first1, last1)*, otherwise the last $n-m$ elements are copied from *[first2, last2)*. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_symmetric_difference* algorithm returns a `hpx::future<ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy*

and returns `ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>` otherwise. The `set_symmetric_difference` algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Iter3, typename Pred =
hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, set_symmetric_difference_result<std::ranges::iterator_t<Rng1>, std::ranges::itera
```

Constructs a sorted range beginning at `dest` consisting of all elements present in either of the sorted ranges `[first1, last1)` and `[first2, last2)`, but not in both of them are copied to the range beginning at `dest`. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate `f`.

If some element is found m times in `[first1, last1)` and n times in `[first2, last2)`, it will be copied to `dest` exactly $\text{std::abs}(m-n)$ times. If $m > n$, then the last $m-n$ of those elements are copied from `[first1, last1)`, otherwise the last $n-m$ elements are copied from `[first2, last2)`. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_symmetric_difference* algorithm returns a `hpx::future<ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>` otherwise. where *Iter1* is `range_iterator_t<Rng1>` and *Iter2* is `range_iterator_t<Rng2>` The *set_symmetric_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3, typename Pred  
= hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```

set_symmetric_difference_result<Iter1, Iter2, Iter3> hpx::ranges::set_symmetric_difference(Iter1 first1,
                                                                                          Sent1 last1,
                                                                                          Iter2 first2,
                                                                                          Sent2 last2,
                                                                                          Iter3 dest,
                                                                                          Pred &&op =
                                                                                          Pred(), Proj1
                                                                                          &&proj1 =
                                                                                          Proj1(), Proj2
                                                                                          &&proj2 =
                                                                                          Proj2())

```

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges *[first1, last1)* and *[first2, last2)*, but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in *[first1, last1)* and *n* times in *[first2, last2)*, it will be copied to *dest* exactly $\text{std::abs}(m-n)$ times. If $m > n$, then the last $m-n$ of those elements are copied from *[first1, last1)*, otherwise the last $n-m$ elements are copied from *[first2, last2)*. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.

- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *Iter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_symmetric_difference* algorithm returns *ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>*. The *set_symmetric_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2, typename Iter3, typename Pred = hpx::parallel::detail::less, typename  
Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```
set_symmetric_difference_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, Iter3> hpx::ranges::set_symmetri
```

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges [*first1*, *last1*) and [*first2*, *last2*), but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found m times in $[first1, last1)$ and n times in $[first2, last2)$, it will be copied to *dest* exactly $\text{std::abs}(m-n)$ times. If $m > n$, then the last $m-n$ of those elements are copied from $[first1, last1)$, otherwise the last $n-m$ elements are copied from $[first2, last2)$. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_symmetric_difference* algorithm returns `ranges::set_symmetric_difference_result<Iter1, Iter2, Iter3>`, where *Iter1* is `range_iterator_t<Rng1>` and *Iter2* is `range_iterator_t<Rng2>`. The *set_symmetric_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::generate

Defined in header [hpx/algorithm.hpp](#)⁶²⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::generate_n`

```
template<typename ExPolicy, typename Rng, typename F>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::generate(ExPolicy  
                                                                                                     &&pol-  
                                                                                                     icy,  
                                                                                                     Rng  
                                                                                                     &&rng,  
                                                                                                     F  
                                                                                                     &&f)
```

Assign each element in range `[first, last)` a value generated by the given function object `f`

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

```
Ret fun();
```

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

⁶²⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *replace_if* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Iter, typename Sent, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> hpx::ranges::generate(ExPolicy &&policy, Iter
                                                                    first, Sent last, F &&f)
```

Assign each element in range [first, last) a value generated by the given function object *f*

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source end iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

Ret fun ();

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

```
template<typename Rng, typename F>
```

`std::ranges::iterator_t<Rng> hpx::ranges::generate(Rng &&rng, F &&f)`

Assign each element in range [first, last) a value generated by the given function object *f*

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

`Ret fun();`

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns *last*.

`template<typename Iter, typename Sent, typename F>
Iter hpx::ranges::generate(Iter first, Sent last, F &&f)`

Assign each element in range [first, last) a value generated by the given function object *f*

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **Iter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source end iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

`Ret fun();`

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns *last*.

hpx::ranges::generate_n

Defined in header [hpx/algorithm.hpp](#)⁶²⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::generate*

```
template<typename ExPolicy, typename FwdIter, typename Size, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::generate_n(ExPolicy
                                                    &&policy, FwdIter
                                                    first, Size count, F
                                                    &&f)
```

Assigns each element in range [first, first+count) a value generated by the given function object *g*.

The assignments in the parallel *generate_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *generate_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *count* invocations of *f* and assignments, for count > 0.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements in the sequence the algorithm will be applied to.

⁶²⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **f** – Refers to the generator function object that will be called. The signature of the function should be equivalent to

`Ret fun();`

The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

```
template<typename FwdIter, typename Size, typename F>
FwdIter hpx::ranges::generate_n(FwdIter first, Size count, F &&f)
```

Assigns each element in range [first, first+count) a value generated by the given function object g.

Note: Complexity: Exactly *count* invocations of *f* and assignments, for count > 0.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements in the sequence the algorithm will be applied to.
- **f** – Refers to the generator function object that will be called. The signature of the function should be equivalent to

`Ret fun();`

The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *replace_if* algorithm returns *last*.

hpx::ranges::reverse

Defined in header `hpx/algorithm.hpp`⁶²⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ranges::reverse_copy*

```
template<typename Iter, typename Sent>
```

⁶²⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Iter `hpx::ranges::reverse`(*Iter* first, *Sent* sent)

Reverses the order of the elements in the range [first, last). Behaves as if applying `std::iter_swap` to every pair of iterators `first+i`, `(last-i) - 1` for each non-negative `i < (last-first)/2`.

The assignments in the parallel *reverse* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns a *Iter*. It returns *last*.

```
template<typename Rng>
std::ranges::iterator_t<Rng> hpx::ranges::reverse(Rng &&rng)
```

Uses *rng* as the source range, as if using `util::begin(rng)` as *first* and `ranges::end(rng)` as *last*. Reverses the order of the elements in the range [first, last). Behaves as if applying `std::iter_swap` to every pair of iterators `first+i`, `(last-i) - 1` for each non-negative `i < (last-first)/2`.

The assignments in the parallel *reverse* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a bidirectional iterator.

Parameters

rng – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns a `hpx::traits::range_iterator<Rng>::type`. It returns *last*.

```
template<typename ExPolicy, typename Iter, typename Sent>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> hpx::ranges::reverse(ExPolicy &&policy, Iter
                                                                    first, Sent sent)
```

Reverses the order of the elements in the range [first, last). Behaves as if applying `std::iter_swap` to every pair of iterators `first+i`, `(last-i) - 1` for each non-negative `i < (last-first)/2`.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Rng>
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::reverse(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy, Rng
                                                                                                     &&rng)
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Reverses the order of the elements in the range $[first, last)$. Behaves as if applying *std::iter_swap* to every pair of iterators $first+i$, $(last-i) - 1$ for each non-negative $i < (last-first)/2$.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a bidirectional iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `hpx::future<std::ranges::iterator_t<Rng>>` otherwise. It returns *last*.

hpx::ranges::reverse_copy

Defined in header `hpx/algorithm.hpp`⁶³⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::reverse`

template<typename **Iter**, typename **Sent**, typename **OutIter**>

`reverse_copy_result<Iter, OutIter> hpx::ranges::reverse_copy(Iter first, Sent last, OutIter result)`

Copies the elements from the range [first, last) to another range beginning at result in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment $*(result + (last - first) - 1 - i) = *(first + i)$ once for each non-negative $i < (last - first)$. If the source and destination ranges (that is, [first, last) and [result, result+(last-first)) respectively) overlap, the behavior is undefined.

The assignments in the parallel *reverse_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for Iter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

⁶³⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **result** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns a *reverse_copy_result<Iter, OutIter>*. The *reverse_copy* algorithm returns the pair of the input iterator forwarded to the first element after the last in the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename OutIter>  
reverse_copy_result<std::ranges::iterator_t<Rng>, OutIter> hpx::ranges::reverse_copy(Rng &&rng, OutIter  
result)
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Copies the elements from the range [first, last) to another range beginning at *result* in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment $*(result + (last - first) - 1 - i) = *(first + i)$ once for each non-negative $i < (last - first)$. If the source and destination ranges (that is, [first, last) and [result, result+(last-first)) respectively) overlap, the behavior is undefined.

The assignments in the parallel *reverse_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a bidirectional iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **result** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns a *ranges::reverse_copy_result<std::ranges::iterator_t<Rng>, OutIter>*. The *reverse_copy* algorithm returns an object equal to {last, result + N} where $N = last - first$

```
template<typename ExPolicy, typename Iter, typename Sent, typename FwdIter>  
parallel::util::detail::algorithm_result<ExPolicy, reverse_copy_result<Iter, FwdIter>>::type hpx::ranges::reverse_copy(ExPolicy &&pol-  
icy,  
Iter  
first,  
Sent  
last,  
FwdIter  
re-  
sult)
```

Copies the elements from the range [first, last) to another range beginning at *result* in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment $*(result + (last - first) - 1 - i) =$

*(first + i) once for each non-negative $i < (\text{last} - \text{first})$. If the source and destination ranges (that is, $[\text{first}, \text{last})$ and $[\text{result}, \text{result} + (\text{last} - \text{first}))$ respectively) overlap, the behavior is undefined.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **result** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns a `hpx::future<reverse_copy_result<Iter, FwdIter> >` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *reverse_copy_result<Iter, FwdIter>* otherwise. The *reverse_copy* algorithm returns the pair of the input iterator forwarded to the first element after the last in the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename OutIter>
parallel::util::detail::algorithm_result<ExPolicy, reverse_copy_result<std::ranges::iterator_t<Rng>, OutIter>>::type hpx::ranges::r
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Copies the elements from the range $[\text{first}, \text{last})$ to another range beginning at *result* in such a way that the elements in the new range are

in reverse order. Behaves as if by executing the assignment $*(result + (last - first) - 1 - i) = *(first + i)$ once for each non-negative $i < (last - first)$. If the source and destination ranges (that is, $[first, last)$ and $[result, result + (last - first))$ respectively) overlap, the behavior is undefined.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a bidirectional iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **result** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns a `hpx::future<ranges::reverse_copy_result<std::ranges::iterator_t<Rng>, OutIter>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::reverse_copy_result<std::ranges::iterator_t<Rng>, OutIter>` otherwise. The *reverse_copy* algorithm returns an object equal to $\{last, result + N\}$ where $N = last - first$.

hpx::ranges::search

Defined in header `hpx/algorithm.hpp`⁶³¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::search_n`

```
template<typename FwdIter, typename Sent, typename FwdIter2, typename Sent2, typename Pred =  
hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

⁶³¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
FwdIter hpx::ranges::search(FwdIter first, Sent last, FwdIter2 s_first, Sent2 s_last, Pred &&op = Pred(), Proj1
&&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most ($S \cdot N$) comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used for the first range (deduced). This iterator type must meet the requirements of an sentinel.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source sentinel used for the second range (deduced). This iterator type must meet the requirements of an sentinel.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of type dereferenced *FwdIter*.
- **Proj2** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of type dereferenced *FwdIter2*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence [s_first, s_last) in range [first, last). If the length of the subsequence [s_first, s_last) is greater than the length of the range [first, last), *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename FwdIter2, typename Sent2,
typename Pred = hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type hpx::ranges::search(ExPolicy &&policy,
                                                                                   FwdIter first, Sent last,
                                                                                   FwdIter2 s_first, Sent2
                                                                                   s_last, Pred &&op =
                                                                                   Pred(), Proj1 &&proj1 =
                                                                                   Proj1(), Proj2 &&proj2 =
                                                                                   Proj2())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most ($S \cdot N$) comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used for the first range (deduced). This iterator type must meet the requirements of an sentinel.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source sentinel used for the second range (deduced). This iterator type must meet the requirements of an sentinel.

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of type dereferenced *FwdIter*.
- **Proj2** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of type dereferenced *FwdIter2*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence `[s_first, s_last)` in range `[first, last)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, last)`, *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename Rng1, typename Rng2, typename Pred = hpx::ranges::equal_to, typename Proj1 = hpx::identity,
typename Proj2 = hpx::identity>
std::ranges::iterator_t<Rng1> hpx::ranges::search(Rng1 &&rng1, Rng2 &&rng2, Pred &&op = Pred(), Proj1
&&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Searches the range `[first, last)` for any elements in the range `[s_first, s_last)`. Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most $(S*N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **Rng1** – The type of the examine range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the search range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of *Rng1*.
- **Proj2** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of *Rng2*.

Parameters

- **rng1** – Refers to the sequence of elements the algorithm will be examining.
- **rng2** – Refers to the sequence of elements the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of *rng1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of *rng2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence $[s_first, s_last)$ in range $[first, last)$. If the length of the subsequence $[s_first, s_last)$ is greater than the length of the range $[first, last)$, *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```

hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng1>> hpx::ranges::search(ExPolicy
                                                                &&pol-
                                                                icy,
                                                                Rng1
                                                                &&rng1,
                                                                Rng2
                                                                &&rng2,
                                                                Pred
                                                                &&op
                                                                =
                                                                Pred(),
                                                                Proj1
                                                                &&proj1
                                                                =
                                                                Proj1(),
                                                                Proj2
                                                                &&proj2
                                                                =
                                                                Proj2())

```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most ($S \cdot N$) comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the examine range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the search range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of *Rng1*.
- **Proj2** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of *Rng2*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **rng1** – Refers to the sequence of elements the algorithm will be examining.
- **rng2** – Refers to the sequence of elements the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of *rng1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of *rng2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence `[s_first, s_last)` in range `[first, last)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, last)`, *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

hpx::ranges::search_n

Defined in header `hpx/algorithm.hpp`⁶³².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::search*

```
template<typename FwdIter, typename FwdIter2, typename Sent2, typename Pred = hpx::ranges::equal_to,
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
FwdIter hpx::ranges::search_n(FwdIter first, std::size_t count, FwdIter2 s_first, Sent2 s_last, Pred &&op =
Pred(), Proj1 &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Searches the range `[first, last)` for any elements in the range `[s_first, s_last)`. Uses a provided predicate to compare elements.

The comparison operations in the parallel *search_n* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most $(S*N)$ comparisons where S = distance(`s_first`, `s_last`) and N = count.

Template Parameters

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.

⁶³² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source sentinel used for the second range (deduced). This iterator type must meet the requirements of an sentinel.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of type dereferenced *FwdIter*.
- **Proj2** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of type dereferenced *FwdIter2*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **count** – Refers to the range of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search_n* algorithm returns *FwdIter*. The *search_n* algorithm returns an iterator to the beginning of the last subsequence `[s_first, s_last)` in range `[first, first+count)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, first+count)`, *first* is returned. Additionally, if the size of the subsequence is empty or no subsequence is found, *first* is also returned.

```
template<typename ExPolicy, typename FwdIter, typename FwdIter2, typename Sent2, typename Pred =
hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type hpx::ranges::search_n(ExPolicy
                                                                    &&policy,
                                                                    FwdIter first,
                                                                    std::size_t count,
                                                                    FwdIter2 s_first,
                                                                    Sent2 s_last, Pred
                                                                    &&op = Pred(),
                                                                    Proj1 &&proj1 =
                                                                    Proj1(), Proj2
                                                                    &&proj2 =
                                                                    Proj2())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most ($S \cdot N$) comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{count}$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source sentinel used for the second range (deduced). This iterator type must meet the requirements of an sentinel.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of type dereferenced *FwdIter*.
- **Proj2** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of type dereferenced *FwdIter2*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **count** – Refers to the range of elements of the first range the algorithm will be applied to.

- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter1* as a projection operation before the actual predicate is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of type dereferenced *FwdIter2* as a projection operation before the actual predicate is invoked.

Returns

The *search_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search_n* algorithm returns an iterator to the beginning of the last subsequence [*s_first*, *s_last*) in range [*first*, *first*+*count*). If the length of the subsequence [*s_first*, *s_last*) is greater than the length of the range [*first*, *first*+*count*), *first* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *first* is also returned.

```
template<typename Rng1, typename Rng2, typename Pred = hpx::ranges::equal_to, typename Proj1 = hpx::identity,
typename Proj2 = hpx::identity>
std::ranges::iterator_t<Rng1> hpx::ranges::search_n(Rng1 &&rng1, std::size_t count, Rng2 &&rng2, Pred
&&op = Pred(), Proj1 &&proj1 = Proj1(), Proj2
&&proj2 = Proj2())
```

Searches the range [*first*, *last*) for any elements in the range [*s_first*, *s_last*). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most (*S***N*) comparisons where *S* = distance(*s_first*, *s_last*) and *N* = distance(*first*, *last*).

Template Parameters

- **Rng1** – The type of the examine range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the search range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

- **Proj1** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of *Rng1*.
- **Proj2** – The type of an optional projection function. This defaults to *hpx::identity* and is applied to the elements of *Rng2*.

Parameters

- **rng1** – Refers to the sequence of elements the algorithm will be examining.
- **count** – The number of elements to apply the algorithm on.
- **rng2** – Refers to the sequence of elements the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of *rng1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of *rng2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence [s_first, s_last) in range [first, last). If the length of the subsequence [s_first, s_last) is greater than the length of the range [first, last), *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = hpx::ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```

hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng1>> hpx::ranges::search_n(ExPolicy
                                                                    &&pol-
                                                                    icy,
                                                                    Rng1
                                                                    &&rng1,
                                                                    std::size_t
                                                                    count,
                                                                    Rng2
                                                                    &&rng2,
                                                                    Pred
                                                                    &&op
                                                                    =
                                                                    Pred(),
                                                                    Proj1
                                                                    &&proj1
                                                                    =
                                                                    Proj1(),
                                                                    Proj2
                                                                    &&proj2
                                                                    =
                                                                    Proj2())

```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most ($S \cdot N$) comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the examine range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the search range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of *Rng1*.
- **Proj2** – The type of an optional projection function. This defaults to `hpx::identity` and is applied to the elements of *Rng2*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the sequence of elements the algorithm will be examining.
- **count** – The number of elements to apply the algorithm on.
- **rng2** – Refers to the sequence of elements the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of *rng1* as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of *rng2* as a projection operation before the actual predicate *is* invoked.

Returns

The *search* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence [*s_first*, *s_last*) in range [*first*, *last*). If the length of the subsequence [*s_first*, *s_last*) is greater than the length of the range [*first*, *last*), *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

hpx::ranges::uninitialized_fill

Defined in header [hpx/algorithm.hpp](#)⁶³³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ranges::uninitialized_fill_n*

template<typename **FwdIter**, typename **Sent**, typename **T**>

FwdIter **hpx::ranges::uninitialized_fill**(*FwdIter* first, *Sent* last, *T* const &value)

Copies the given *value* to an uninitialized memory area, defined by the range [*first*, *last*). If an exception is thrown during the initialization, the function has no effects.

The assignments in the ranges *uninitialized_fill* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

⁶³³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns a *FwdIter*. The *uninitialized_fill* algorithm returns the output iterator to the element in the range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::uninitialized_fill(ExPolicy
                                                                                               &&pol-
                                                                                               icy,
                                                                                               FwdIter
                                                                                               first,
                                                                                               Sent
                                                                                               last, T
                                                                                               const
                                                                                               &value)
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns a returns *FwdIter*. The *uninitialized_fill* algorithm returns the output iterator to the element in the range, one past the last element copied.

```
template<typename Rng, typename T>  
hpx::traits::range_traits<Rng>::iterator_type hpx::ranges::uninitialized_fill(Rng &&rng, T const &value)
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_fill* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **rng** – Refers to the range to which the value will be filled
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns a returns *hpx::traits::range_traits<Rng>::iterator_type*. The *uninitialized_fill* algorithm returns the output iterator to the element in the range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename T>  
parallel::util::detail::algorithm_result<ExPolicy, typename hpx::traits::range_traits<Rng1>::iterator_type>::type hpx::ranges::unin
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range to which the value will be filled
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns a `hpx::future<typename hpx::traits::range_traits<Rng>::iterator_type>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *typename hpx::traits::range_traits<Rng>::iterator_type* otherwise. The *uninitialized_fill* algorithm returns the iterator to one past the last element filled in the range.

hpx::ranges::uninitialized_fill_n

Defined in header `hpx/algorithm.hpp`⁶³⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::uninitialized_fill*

template<typename **FwdIter**, typename **Size**, typename **T**>

FwdIter **hpx::ranges::uninitialized_fill_n**(*FwdIter* first, *Size* count, *T* const &value)

Copies the given *value* value to the first count elements in an uninitialized memory area beginning at first. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

⁶³⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill_n* algorithm returns a *FwdIter*. The *uninitialized_fill_n* algorithm returns the output iterator to the element in the range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename T>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::uninitialized_fill_n(ExPolicy  
                                                                                               &&pol-  
                                                                                               icy,  
                                                                                               FwdIter  
                                                                                               first,  
                                                                                               Size  
                                                                                               count,  
                                                                                               T  
                                                                                               const  
                                                                                               &value)
```

Copies the given *value* value to the first *count* elements in an uninitialized memory area beginning at *first*. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_fill_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill_n* algorithm returns a `hpx::future<FwdIter>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `FwdIter` otherwise. The *uninitialized_fill_n* algorithm returns the output iterator to the element in the range, one past the last element copied.

hpx::ranges::copy

Defined in header `hpx/algorithm.hpp`⁶³⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::copy_n`
- `hpx::ranges::copy_if`

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter>
parallel::util::detail::algorithm_result<ExPolicy, ranges::copy_result<FwdIter1, FwdIter>>::type hpx::ranges::copy(ExPolicy
&&policy,
FwdIter1
iter,
Sent1
sent,
FwdIter
dest)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

⁶³⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **iter** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns a `hpx::future<ranges::copy_result<FwdIter1, FwdIter> >` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::copy_result<FwdIter1, FwdIter>` otherwise. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename FwdIter>  
parallel::util::detail::algorithm_result<ExPolicy, ranges::copy_result<typename hpx::traits::range_traits<Rng>::iterator_type, FwdIter>
```

Copies the elements in the range *rng* to another range beginning at *dest*.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns a `hpx::future<ranges::copy_result<iterator_t<Rng>, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::copy_result<iterator_t<Rng>, FwdIter2>` otherwise. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename Sent1, typename FwdIter>
ranges::copy_result<FwdIter1, FwdIter> hpx::ranges::copy(FwdIter1 iter, Sent1 sent, FwdIter dest)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **iter** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename FwdIter>
ranges::copy_result<typename hpx::traits::range_traits<Rng>::iterator_type, FwdIter> hpx::ranges::copy(Rng
&&rng,
FwdIter
dest)
```

Copies the elements in the range *rng* to another range beginning at *dest*.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::copy_n

Defined in header [hpx/algorithm.hpp](#)⁶³⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::ranges::copy](#)
- [hpx::ranges::copy_if](#)

template<typename **ExPolicy**, typename **FwdIter1**, typename **Size**, typename **FwdIter2**>

[hpx::parallel::util::detail::algorithm_result<ExPolicy, ranges::copy_n_result<FwdIter1, FwdIter2>>::type](#) **hpx::ranges::copy_n**(*ExPolicy* &*policy*, *FwdIter1* *first*, *Size* *count*, *FwdIter2* *dest*)

Copies the elements in the range [*first*, *first* + *count*), starting from *first* and proceeding to *first* + *count* - 1., to another range beginning at *dest*.

The assignments in the parallel *copy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.

⁶³⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy_n* algorithm returns a `hpx::future<ranges::copy_n_result<FwdIter1, FwdIter2> >` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::copy_n_result<FwdIter1, FwdIter2>` otherwise. The *copy* algorithm returns the pair of the input iterator forwarded to the first element after the last in the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename Size, typename FwdIter2>
ranges::copy_n_result<FwdIter1, FwdIter2> hpx::ranges::copy_n(FwdIter1 first, Size count, FwdIter2 dest)
```

Copies the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns the pair of the input iterator forwarded to the first element after the last in the input sequence and the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::copy_if

Defined in header [hpx/algorithm.hpp](#)⁶³⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::copy`
- `hpx::ranges::copy_n`

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter, typename Pred,  
typename Proj = hpx::identity>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, ranges::copy_if_result<FwdIter1, FwdIter>>::type hpx::ranges::copy_if(E
```

Copies the elements in the range, defined by [first, last) to another range beginning at *dest*. The order of the elements that are not removed is preserved.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for FwdIter1.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

⁶³⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **iter** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *copy_if* algorithm returns a `hpx::future<ranges::copy_if_result<iterator_t<Rng>, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::copy_if_result<iterator_t<Rng>, FwdIter2>` otherwise. The *copy_if* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename FwdIter, typename Pred, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, ranges::copy_if_result<typename hpx::traits::range_traits<Rng>::iterator_type, FwdIter>>
```

Copies the elements in the range, defined by *rng* to another range beginning at *dest*. The order of the elements that are not removed is preserved.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – The binary predicate which returns `true` if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types `Type1` must be such that objects of type `FwdIter` can be dereferenced and then implicitly converted to `Type1`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `copy_if` algorithm returns a `hpx::future<ranges::copy_if_result<iterator_t<Rng>, FwdIter2>>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `ranges::copy_if_result<iterator_t<Rng>, FwdIter2>` otherwise. The `copy_if` algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename Sent1, typename FwdIter, typename Pred, typename Proj =  
hpx::identity>  
ranges::copy_if_result<FwdIter1, FwdIter> hpx::ranges::copy_if(FwdIter1 iter, Sent1 sent, FwdIter dest, Pred  
                        &&pred, Proj &&proj = Proj())
```

Copies the elements in the range, defined by [first, last) to another range beginning at *dest*. The order of the elements that are not removed is preserved.

Template Parameters

- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for `FwdIter1`.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **iter** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *copy_if* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename FwdIter, typename Pred, typename Proj = hpx::identity>
ranges::copy_if_result<typename hpx::traits::range_traits<Rng>::iterator_type, FwdIter> hpx::ranges::copy_if(Rng
&&rng,
FwdIter
dest,
Pred
&&pred,
Proj
&&proj
=
Proj())
```

Copies the elements in the range, defined by *rng* to another range beginning at *dest*. The order of the elements that are not removed is preserved.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *copy_if* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::is_heap

Defined in header `hpx/algorithm.hpp`⁶³⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::is_heap_until`

```
template<typename ExPolicy, typename Rng, typename Comp = hpx::parallel::detail::less, typename Proj =  
hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::is_heap(ExPolicy &&policy, Rng  
                                         &&rng, Comp &&comp =  
                                         Comp(), Proj &&proj =  
                                         Proj())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using `operator<()`).

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of

⁶³⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

the call is less than the second, and false otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_heap* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Comp = hpx::parallel::detail::less,
        typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::is_heap(ExPolicy &&policy, Iter
                                                                    first, Sent last, Comp
                                                                    &&comp = Comp(), Proj
                                                                    &&proj = Proj())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using `operator<()`).

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of

the call is less than the second, and false otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_heap* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

```
template<typename Rng, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>  
bool hpx::ranges::is_heap(Rng &&rng, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using `operator<()`).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most $2 * N$ applications of the projection *proj*, where $N = \text{last} - \text{first}$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to *bool*, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_heap* algorithm returns *bool*. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

```
template<typename Iter, typename Sent, typename Comp = hpx::parallel::detail::less, typename Proj =  
hpx::identity>
```

```
bool hpx::ranges::is_heap(Iter first, Sent last, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using `operator<()`).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most $2 * N$ applications of the projection *proj*, where $N = \text{last} - \text{first}$.

Template Parameters

- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `is_heap` algorithm returns *bool*. The `is_heap` algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

hpx::ranges::is_heap_until

Defined in header `hpx/algorithm.hpp`⁶³⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::is_heap`

```
template<typename ExPolicy, typename Rng, typename Comp = hpx::parallel::detail::less, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::is_heap_until(ExPolicy
&&pol-
icy,
Rng
&&rng,
Comp
&&comp
=
Comp(),
Proj
&&proj
=
Proj())
```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it*

⁶³⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

for which range [first, it) is a max heap. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_heap_until* algorithm returns a *hpx::future<RandIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandIter* otherwise. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at first which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Comp = hpx::parallel::detail::less,
        typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> hpx::ranges::is_heap_until(ExPolicy
                                                                 &&policy, Iter
                                                                 first, Sent last,
                                                                 Comp &&comp =
                                                                 Comp(), Proj
                                                                 &&proj = Proj())
```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most 2 * N applications of the projection *proj*, where N = last - first.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for Iter1.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_heap_until* algorithm returns a *hpx::future<RandIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandIter* otherwise. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at first which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap.

```
template<typename Rng, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> hpx::ranges::is_heap_until(Rng &&rng, Comp &&comp = Comp(), Proj
&&proj = Proj())
```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most $2 * N$ applications of the projection *proj*, where $N = \text{last} - \text{first}$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* is invoked.

Returns

The *is_heap_until* algorithm returns *RandIter*. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range $[\text{first}, \text{it})$ is a max heap.

```
template<typename Iter, typename Sent, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
Iter hpx::ranges::is_heap_until(Iter first, Sent last, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range $[\text{first}, \text{it})$ is a max heap. The function uses the given comparison function object *comp* (defaults to using `operator<()`).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Performs at most N applications of the comparison *comp*, at most $2 * N$ applications of the projection *proj*, where $N = \text{last} - \text{first}$.

Template Parameters

- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for *Iter*1.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_heap_until* algorithm returns *RandIter*. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at first which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap.

hpx::ranges::merge

Defined in header [hpx/algorithm.hpp](#)⁶⁴⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::inplace_merge*

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Iter3, typename Comp =
hpx::ranges::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, hpx::ranges::merge_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<
```

Merges two sorted ranges [first1, last1) and [first2, last2) into one sorted range beginning at *dest*. The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges.

⁶⁴⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`.
- **Proj1** – The type of an optional projection function to be used for elements of the first range. This defaults to `hpx::identity`.
- **Proj2** – The type of an optional projection function to be used for elements of the second range. This defaults to `hpx::identity`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first range of elements the algorithm will be applied to.
- **rng2** – Refers to the second range of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter1* and *Iter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*.

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual comparison *comp* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual comparison *comp* is invoked.

Returns

The *merge* algorithm returns a `hpx::future<merge_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *merge_result<Iter1, Iter2, Iter3>* otherwise. The *merge* algorithm returns the tuple of the source iterator *last1*, the source iterator *last2*, the destination iterator to the end of the *dest* range.

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Iter3, typename Comp = hpx::ranges::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, hpx::ranges::merge_result<Iter1, Iter2, Iter3>>::type hpx::ranges::merge(Ex
```

Merges two sorted ranges `[first1, last1)` and `[first2, last2)` into one sorted range beginning at *dest*. The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes

the assignments.

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a random access iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of a random access iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of a sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function to be used for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function to be used for elements of the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter1* and *Iter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual comparison *comp* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual comparison *comp* is invoked.

Returns

The *merge* algorithm returns a `hpx::future<merge_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *merge_result<Iter1, Iter2, Iter3>* otherwise. The *merge* algorithm returns the tuple of the source iterator *last1*, the source iterator *last2*, the destination iterator to the end of the *dest* range.

```
template<typename Rng1, typename Rng2, typename Iter3, typename Comp = hpx::ranges::less, typename Proj1 =
hpx::identity, typename Proj2 = hpx::identity>
hpx::ranges::merge_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, Iter3> hpx::ranges::merge(Rng1
&&rng1,
Rng2
&&rng2,
Iter3
dest,
Comp
&&comp
=
Comp(),
Proj1
&&proj1
=
Proj1(),
Proj2
&&proj2
=
Proj2())
```

Merges two sorted ranges `[first1, last1)` and `[first2, last2)` into one sorted range beginning at *dest*. The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function to be used for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function to be used for elements of the second range. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first range of elements the algorithm will be applied to.
- **rng2** – Refers to the second range of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter1* and *Iter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual comparison *comp* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual comparison *comp* is invoked.

Returns

The *merge* algorithm returns *merge_result*<*Iter1*, *Iter2*, *Iter3*>. The *merge* algorithm returns the tuple of the source iterator *last1*, the source iterator *last2*, the destination iterator to the end of the *dest* range.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3, typename Comp
= hpx::ranges::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::ranges::merge_result<Iter1, Iter2, Iter3> hpx::ranges::merge(Iter1 first1, Sent1 last1, Iter2 first2, Sent2
                                                                    last2, Iter3 dest, Comp &&comp = Comp(),
                                                                    Proj1 &&proj1 = Proj1(), Proj2 &&proj2 =
                                                                    Proj2())
```

Merges two sorted ranges [first1, last1) and [first2, last2) into one sorted range beginning at *dest*. The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an random access iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter1*.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an random access iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for *Iter2*.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an random access iterator.

- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function to be used for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function to be used for elements of the second range. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter1* and *Iter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual comparison *comp* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual comparison *comp* is invoked.

Returns

The *merge* algorithm returns *merge_result<Iter1, Iter2, Iter3>*. The *merge* algorithm returns the tuple of the source iterator *last1*, the source iterator *last2*, the destination iterator to the end of the *dest* range.

hpx::ranges::inplace_merge

Defined in header `hpx/algorithm.hpp`⁶⁴¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::merge`

```
template<typename ExPolicy, typename Rng, typename Iter, typename Comp = hpx::ranges::less, typename Proj = hpx::identity>
```

⁶⁴¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> hpx::ranges::inplace_merge(ExPolicy
                                                                    &&policy, Rng
                                                                    &&rng, Iter
                                                                    middle, Comp
                                                                    &&comp =
                                                                    Comp(), Proj
                                                                    &&proj = Proj())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range of elements the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *inplace_merge* algorithm returns a `hpx::future<Iter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. The *inplace_merge* algorithm returns the source iterator *last*

```
template<typename ExPolicy, typename Iter, typename Sent, typename Comp = hpx::ranges::less, typename
Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> hpx::ranges::inplace_merge(ExPolicy
&&policy, Iter
first, Iter middle,
Sent last, Comp
&&comp =
Comp(), Proj
&&proj = Proj())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for *Iter*1.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.

- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *inplace_merge* algorithm returns a `hpx::future<Iter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. The *inplace_merge* algorithm returns the source iterator *last*

```
template<typename Rng, typename Iter, typename Comp = hpx::ranges::less, typename Proj = hpx::identity>  
Iter hpx::ranges::inplace_merge(Rng &&rng, Iter middle, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the range of elements the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *inplace_merge* algorithm returns *Iter*. The *inplace_merge* algorithm returns the source iterator *last*

```
template<typename Iter, typename Sent, typename Comp = hpx::ranges::less, typename Proj = hpx::identity>
Iter hpx::ranges::inplace_merge(Iter first, Iter middle, Sent last, Comp &&comp = Comp(), Proj &&proj =
    Proj())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in the each of original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and the each projection.

Template Parameters

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for *Iter*.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *Iter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *inplace_merge* algorithm *Iter*. The *inplace_merge* algorithm returns the source iterator *last*

hpx::ranges::remove

Defined in header [hpx/algorithm.hpp](#)⁶⁴².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::remove_if`

```
template<typename Iter, typename Sent, typename Proj = hpx::identity, typename T = typename  
hpx::parallel::traits::projected<Iter, Proj>::value_type>  
subrange_t<Iter, Sent> hpx::ranges::remove(Iter first, Sent last, T const &value, Proj &&proj = Proj())
```

Removes all elements that are equal to *value* from the range [first, last) and returns a subrange [ret, last), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the operator==() and the projection *proj*.

Template Parameters

- **Iter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove* algorithm returns a `subrange_t<FwdIter, Sent>`. The *remove* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename Rng, typename Proj = hpx::identity, typename T = typename  
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
```

⁶⁴² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
subrange_t<std::ranges::iterator_t<Rng>> hpx::ranges::remove(Rng &&rng, T const &value, Proj &&proj =
                                         Proj())
```

Removes all elements that are equal to *value* from the range *rng* and and returns a subrange [ret, util::end(rng)), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *util::end(rng)*

- *util::begin(rng)* assignments, exactly *util::end(rng) - util::begin(rng)* applications of the operator==() and the projection *proj*.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove* algorithm returns a *subrange_t<std::ranges::iterator_t<Rng>>*. The *remove* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Proj = hpx::identity, typename T =
typename hpx::parallel::traits::projected<FwdIter, Proj>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<FwdIter, Sent>>::type hpx::ranges::remove(ExPolicy
&&pol-
icy,
FwdIter
first,
Sent
last, T
const
&value,
Proj
&&proj
=
Proj())
```

Removes all elements that are equal to *value* from the range [first, last) and and returns a subrange [ret, last), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the `operator==()` and the projection *proj*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove* algorithm returns a `hpx::future<subrange_t<FwdIter, Sent>>`. The *remove* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename ExPolicy, typename Rng, typename Proj = hpx::identity, typename T = typename  
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
```

```

parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>>> hpx::ranges::remove(ExPolicy
                                                                    &&pol-
                                                                    icy,
                                                                    Rng
                                                                    &&rng,
                                                                    T
                                                                    const
                                                                    &value,
                                                                    Proj
                                                                    &&proj
                                                                    =
                                                                    Proj())

```

Removes all elements that are equal to *value* from the range *rng* and returns a subrange [ret, util::end(rng)), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *util::end(rng)*

- *util::begin(rng)* assignments, exactly *util::end(rng) - util::begin(rng)* applications of the operator==() and the projection *proj*.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove* algorithm returns a *hpx::future< subrange_t<std::ranges::iterator_t<Rng>>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *remove* algorithm returns the iterator to the new end of the range.

hpx::ranges::remove_if

Defined in header `hpx/algorithm.hpp`⁶⁴³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::remove`

```
template<typename Iter, typename Sent, typename Pred, typename Proj = hpx::identity>  
subrange_t<Iter, Sent> hpx::ranges::remove_if(Iter first, Sent sent, Pred &&pred, Proj &&proj = Proj())
```

Removes all elements for which predicate *pred* returns true from the range [first, last) and returns a subrange [ret, last), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred* and the projection *proj*.

Template Parameters

- **Iter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_if* requires *Pred* to meet the requirements of *Copy-Constructible*..
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove_if* algorithm returns a *subrange_t<FwdIter, Sent>*. The *remove_if* algorithm returns

⁶⁴³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename Rng, typename Pred, typename Proj = hpx::identity>
subrange_t<std::ranges::iterator_t<Rng>> hpx::ranges::remove_if(Rng &&rng, Pred &&pred, Proj &&proj =
    Proj())
```

Removes all elements that are equal to *value* from the range *rng* and returns a subrange [ret, util::end(rng)), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *util::end(rng)*

- *util::begin(rng)* assignments, exactly *util::end(rng) - util::begin(rng)* applications of the operator==() and the projection *proj*.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_if* requires *Pred* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove_if* algorithm returns a *subrange_t<std::ranges::iterator_t<Rng>>*. The *remove_if* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred, typename Proj =
hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<FwdIter, Sent>>::type hpx::ranges::remove_if(ExPolicy
&&pol-
icy,
FwdIter
first,
Sent
sent,
Pred
&&pred,
Proj
&&proj
=
Proj())
```

Removes all elements for which predicate *pred* returns true from the range [first, last) and returns a subrange [ret, last), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred* and the projection *proj*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_if* requires *Pred* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove_if* algorithm returns a `hpx::future<subrange_t<FwdIter, Sent>>`. The *remove_if* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

```
template<typename ExPolicy, typename Rng, typename Pred, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>>> hpx::ranges::remove_if(ExPolicy
&&pol-
icy,
Rng
&&rng,
Pred
&&pred,
Proj
&&proj
=
Proj())
```

Removes all elements that are equal to *value* from the range *rng* and returns a subrange [ret, util::end(rng)), where ret is a past-the-end iterator for the new end of the range.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than `util::end(rng)`

- `util::begin(rng)` assignments, exactly `util::end(rng) - util::begin(rng)` applications of the operator `==()` and the projection *proj*.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_if* requires *Pred* to meet the requirements of *Copy-Constructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *remove_if* algorithm returns a `hpx::future<subrange_t< std::ranges::iterator_t<Rng>>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *remove_if* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange of the values all in valid but unspecified state.

hpx::ranges::starts_with

Defined in header `hpx/algorithm.hpp`⁶⁴⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Pred =  
ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>  
bool hpx::ranges::starts_with(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2, Pred &&pred = Pred(), Proj1  
    &&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Checks whether the second range defined by [first1, last1) matches the prefix of the first range defined by [first2, last2)

The assignments in the parallel *starts_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **Iter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the begin destination iterators used (deduced). This iterator type must meet the requirements of an input iterator.

⁶⁴⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Sent2** – The type of the end destination iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate *is* invoked.

Returns

The *starts_with* algorithm returns *bool*. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2,
typename Pred = ranges::equal_to, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::starts_with(ExPolicy &&policy,
                                                                                          FwdIter1 first1, Sent1
                                                                                          last1, FwdIter2 first2,
                                                                                          Sent2 last2, Pred
                                                                                          &&pred = Pred(),
                                                                                          Proj1 &&proj1 =
                                                                                          Proj1(), Proj2
                                                                                          &&proj2 = Proj2())
```

Checks whether the second range defined by [first1, last1) matches the prefix of the first range defined by [first2, last2)

The assignments in the parallel *starts_with* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *starts_with* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate and both projections.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used(deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **FwdIter2** – The type of the begin destination iterators used deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the end destination iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate *is* invoked.

Returns

The *starts_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

```
template<typename Rng1, typename Rng2, typename Pred = ranges::equal_to, typename Proj1 = hpx::identity,
typename Proj2 = hpx::identity>
bool hpx::ranges::starts_with(Rng1 &&rng1, Rng2 &&rng2, Pred &&pred = Pred(), Proj1 &&proj1 =
    Proj1(), Proj2 &&proj2 = Proj2())
```

Checks whether the second range *rng2* matches the prefix of the first range *rng1*.

The assignments in the parallel *starts_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most $\min(N1, N2)$ applications of the predicate and both projections.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate *is* invoked.

Returns

The *starts_with* algorithm returns *bool*. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = ranges::equal_to, typename
Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, bool>::type hpx::ranges::starts_with(ExPolicy
&&policy, Rng1
&&rng1, Rng2
&&rng2, Pred
&&pred =
Pred(), Proj1
&&proj1 =
Proj1(), Proj2
&&proj2 =
Proj2())
```

Checks whether the second range *rng2* matches the prefix of the first range *rng1*.

The assignments in the parallel *starts_with* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *starts_with* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear: at most $\min(N1, N2)$ applications of the predicate and both projections.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The binary predicate that compares the projected elements.
- **Proj1** – The type of an optional projection function for the source range. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function for the destination range. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the in two ranges projected by proj1 and proj2 respectively.
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements in the source range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements in the destination range as a projection operation before the actual predicate *is* invoked.

Returns

The *starts_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

hpx::ranges::set_union

Defined in header `hpx/algorithm.hpp`⁶⁴⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Iter3, typename Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 =
hpx::identity>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, set_union_result<Iter1, Iter2, Iter3>>::type hpx::ranges::set_union(ExPolicy,
&&pol
icy,
Iter1,
first1,
Sent1,
last1,
Iter2,
first2,
Sent2,
last2,
Iter3,
dest,
Pred,
&&op
=
Pred(),
Proj1,
&&pro
=
Proj1(),
Proj2,
&&pro
=
Proj2(),
```

Constructs a sorted range beginning at `dest` consisting of all elements present in one or both sorted ranges `[first1, last1)` and `[first2, last2)`. This algorithm expects both input ranges to be sorted with the given binary predicate `f`.

If some element is found m times in `[first1, last1)` and n times in `[first2, last2)`, then all m elements will be copied from `[first1, last1)` to `dest`, preserving order, and then exactly `std::max(n-m, 0)` elements will be copied from `[first2, last2)` to `dest`, also preserving order.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

⁶⁴⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: At most $2*(N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_union* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_union* algorithm returns a `hpx::future<ranges::set_union_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *ranges::set_union_result<Iter1, Iter2, Iter3>* otherwise. The *set_union* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Iter3, typename Pred =
hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, set_union_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, It
```

Constructs a sorted range beginning at *dest* consisting of all elements present in one or both sorted ranges [*first1*, *last1*) and [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *f*.

If some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), then all *m* elements will be copied from [*first1*, *last1*) to *dest*, preserving order, and then exactly `std::max(n-m, 0)` elements will be copied from [*first2*, *last2*) to *dest*, also preserving order.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_union* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_union* algorithm returns a `hpx::future<ranges::set_union_result<Iter1, Iter2, Iter3>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::set_union_result<Iter1, Iter2, Iter3>` otherwise. where *Iter1* is `range_iterator_t<Rng1>`

and `Iter2` is `range_iterator_t<Rng2>`. The `set_union` algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2, typename Iter3, typename Pred = hpx::parallel::detail::less, typename
Proj1 = hpx::identity, typename Proj2 = hpx::identity>
set_union_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, Iter3> hpx::ranges::set_union(Rng1
&&rng1,
Rng2
&&rng2,
Iter3
dest,
Pred
&&op
=
Pred(),
Proj1
&&proj1
=
Proj1(),
Proj2
&&proj2
=
Proj2())
```

Constructs a sorted range beginning at `dest` consisting of all elements present in one or both sorted ranges `[first1, last1)` and `[first2, last2)`. This algorithm expects both input ranges to be sorted with the given binary predicate `f`.

If some element is found m times in `[first1, last1)` and n times in `[first2, last2)`, then all m elements will be copied from `[first1, last1)` to `dest`, preserving order, and then exactly `std::max(n-m, 0)` elements will be copied from `[first2, last2)` to `dest`, also preserving order.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of `set_union` requires `Pred` to meet the requirements of `CopyConstructible`. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *Iter* can be dereferenced and then implicitly converted to *Type1*

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *set_union* algorithm returns *ranges::set_union_result<Iter1, Iter2, Iter3>*. where *Iter1* is *range_iterator_t<Rng1>* and *Iter2* is *range_iterator_t<Rng2>* The *set_union* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::swap_ranges

Defined in header `hpx/algorithm.hpp`⁶⁴⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter1, typename Sent1, typename InIter2, typename Sent2>
swap_ranges_result<InIter1, InIter2> hpx::ranges::swap_ranges(InIter1 first1, Sent1 last1, InIter2 first2, Sent2
                                                             last2)
```

Exchanges elements between range `[first1, last1)` and another range starting at *first2*.

The swap operations in the parallel *swap_ranges* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first1* and *last1*

Template Parameters

- **InIter1** – The type of the first range of iterators to swap (deduced).
- **Sent1** – The type of the first sentinel (deduced). This sentinel type must be a sentinel for *InIter1*.
- **InIter2** – The type of the second range of iterators to swap (deduced).

⁶⁴⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Sent2** – The type of the second sentinel (deduced). This sentinel type must be a sentinel for `InIter2`.

Parameters

- **first1** – Refers to the beginning of the sequence of elements for the first range.
- **last1** – Refers to sentinel value denoting the end of the sequence of elements for the first range.
- **first2** – Refers to the beginning of the sequence of elements for the second range.
- **last2** – Refers to sentinel value denoting the end of the sequence of elements for the second range.

Returns

The `swap_ranges` algorithm returns `swap_ranges_result<InIter1, InIter2>`. The `swap_ranges` algorithm returns `in_in_result` with the first element as the iterator to the element past the last element exchanged in range beginning with `first1` and the second element as the iterator to the element past the last element exchanged in the range beginning with `first2`.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2>
parallel::util::detail::algorithm_result<ExPolicy, swap_ranges_result<FwdIter1, FwdIter2>>::type hpx::ranges::swap_ranges(Ex
```

&&
icy,
Fw
firs
Sen
last
Fw
firs
Sen
last

Exchanges elements between range `[first1, last1)` and another range starting at `first2`.

The swap operations in the parallel `swap_ranges` algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The swap operations in the parallel `swap_ranges` algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between `first1` and `last1`

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the first range of iterators to swap (deduced).
- **Sent1** – The type of the first sentinel (deduced). This sentinel type must be a sentinel for `FwdIter1`.
- **FwdIter2** – The type of the second range of iterators to swap (deduced).

- **Sent2** – The type of the second sentinel (deduced). This sentinel type must be a sentinel for `FwdIter2`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements for the first range.
- **last1** – Refers to sentinel value denoting the end of the sequence of elements for the first range.
- **first2** – Refers to the beginning of the sequence of elements for the second range.
- **last2** – Refers to sentinel value denoting the end of the sequence of elements for the second range.

Returns

The `swap_ranges` algorithm returns a `hpx::future<swap_ranges_result<FwdIter1, FwdIter2>>` if the execution policy is of type `parallel_task_policy` and returns `FwdIter2` otherwise. The `swap_ranges` algorithm returns `in_in_result` with the first element as the iterator to the element past the last element exchanged in range beginning with `first1` and the second element as the iterator to the element past the last element exchanged in the range beginning with `first2`.

```
template<typename Rng1, typename Rng2>
swap_ranges_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>> hpx::ranges::swap_ranges(Rng1
                                                                                                     &&rng1,
                                                                                                     Rng2
                                                                                                     &&rng2)
```

Exchanges elements between range `[first1, last1)` and another range starting at `first2`.

The swap operations in the parallel `swap_ranges` algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between `first1` and `last1`

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **rng1** – Refers to the sequence of elements of the first range.
- **rng2** – Refers to the sequence of elements of the second range.

Returns

The `swap_ranges` algorithm returns `swap_ranges_result< std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng1>>`. The `swap_ranges` algorithm returns `in_in_result` with the first element as the iterator to the element past the last element exchanged in range beginning with `first1` and the second element as the iterator to the element past the last element exchanged in the range beginning with `first2`.

```
template<typename ExPolicy, typename Rng1, typename Rng2>
```

```
parallel::util::detail::algorithm_result<ExPolicy, swap_ranges_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>>> h
```

Exchanges elements between range `[first1, last1)` and another range starting at *first2*.

The swap operations in the parallel *swap_ranges* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The swap operations in the parallel *swap_ranges* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first1* and *last1*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the sequence of elements of the first range.
- **rng2** – Refers to the sequence of elements of the second range.

Returns

The *swap_ranges* algorithm returns a `hpx::future<swap_ranges_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng1>>>` if the execution policy is of type *parallel_task_policy* and returns *swap_ranges_result< std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng1>>*. otherwise. The *swap_ranges* algorithm returns *in_in_result* with the first element as the iterator to the element past the last element exchanged in range beginning with *first1* and the second element as the iterator to the element past the last element exchanged in the range beginning with *first2*.

hpx::ranges::shift_right

Defined in header [hpx/algorithm.hpp](#)⁶⁴⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter, typename Sent, typename Size>
```

```
FwdIter hpx::ranges::shift_right(FwdIter first, Sent last, Size n)
```

Shifts the elements in the range [first, last) by n positions towards the end of the range. For every integer i in [0, last - first - n), moves the element originally at position first + i to position first

- n + i.

The assignment operations in the parallel *shift_right* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns *FwdIter*. The *shift_right* algorithm returns an iterator to the end of the resulting range.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Size>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::shift_right(ExPolicy  
                                                                                      &&policy,  
                                                                                      FwdIter first,  
                                                                                      Sent last, Size n)
```

Shifts the elements in the range [first, last) by n positions towards the end of the range. For every integer i in [0, last - first - n), moves the element originally at position first + i to position first

- n + i.

⁶⁴⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *shift_right* algorithm returns an iterator to the end of the resulting range.

```
template<typename Rng, typename Size>
```

```
std::ranges::iterator_t<Rng> hpx::ranges::shift_right(Rng &&rng, Size n)
```

Shifts the elements in the range [first, last) by n positions towards the end of the range. For every integer i in [0, last - first - n), moves the element originally at position first + i to position first

- n + i.

The assignment operations in the parallel *shift_right* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most (last - first) - n assignments.

Note: The type of dereferenced `std::ranges::iterator_t<Rng>` must meet the requirements of *MoveAssignable*.

Template Parameters

- **Rng** – The type of the range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **rng** – Refers to the range in which the elements will be shifted.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns `std::ranges::iterator_t<Rng>`. The *shift_right* algorithm returns an iterator to the end of the resulting range.

```
template<typename ExPolicy, typename Rng, typename Size>
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::shift_right(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     Rng
                                                                                                     &&rng,
                                                                                                     Size
                                                                                                     n)
```

Shifts the elements in the range `[first, last)` by `n` positions towards the end of the range. For every integer `i` in `[0, last - first - n)`, moves the element originally at position `first + i` to position `first`

- `n + i`.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `(last - first) - n` assignments.

Note: The type of dereferenced `std::ranges::iterator_t<Rng>` must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range in which the elements will be shifted.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::ranges::iterator_t<Rng>` otherwise. The *shift_right* algorithm returns an iterator to the end of the resulting range.

hpx::ranges::partial_sort

Defined in header `hpx/algorithm.hpp`⁶⁴⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename RandomIt, typename Sent, typename Comp = ranges::less, typename Proj = hpx::identity>
RandomIt hpx::ranges::partial_sort(RandomIt first, RandomIt middle, Sent last, Comp &&comp = Comp(),
                                   Proj &&proj = Proj())
```

Places the first middle - first elements from the range [first, last) as sorted with respect to comp into the range [first, middle). The rest of the elements in the range [middle, last) are placed in an unspecified order.

The assignments in the parallel *partial_sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Approximately (last - first) * log(middle - first) comparisons.

Template Parameters

- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for RandomIt.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to `detail::less`.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

⁶⁴⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator. Comp defaults to detail::less.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *partial_sort* algorithm returns *RandomIt*. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename ExPolicy, typename RandomIt, typename Sent, typename Comp = ranges::less, typename  
Proj = hpx::identity>  
parallel::util::detail::algorithm_result<ExPolicy, RandomIt>::type hpx::ranges::partial_sort(ExPolicy  
                                                                                               &&policy,  
                                                                                               RandomIt first,  
                                                                                               RandomIt  
                                                                                               middle, Sent  
                                                                                               last, Comp  
                                                                                               &&comp =  
                                                                                               Comp(), Proj  
                                                                                               &&proj =  
                                                                                               Proj())
```

Places the first middle - first elements from the range [first, last) as sorted with respect to comp into the range [first, middle). The rest of the elements in the range [middle, last) are placed in an unspecified order.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Approximately (last - first) * log(middle - first) comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for RandomIt.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to detail::less.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. `Comp` defaults to `detail::less`.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The *partial_sort* algorithm returns a `hpx::future<RandomIt>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandomIt* otherwise. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename Rng, typename Comp = ranges::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> hpx::ranges::partial_sort(Rng &&rng, std::ranges::iterator_t<Rng> middle,
                                                       Comp &&comp = Comp(), Proj &&proj = Proj())
```

Places the first `middle - first` elements from the range `[first, last)` as sorted with respect to `comp` into the range `[first, middle)`. The rest of the elements in the range `[middle, last)` are placed in an unspecified order.

The assignments in the parallel *partial_sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Approximately $(last - first) * \log(middle - first)$ comparisons.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced). `Comp` defaults to `detail::less`.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. `Comp` defaults to `detail::less`.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The *partial_sort* algorithm returns `std::ranges::iterator_t<Rng>`. It returns *last*.

```
template<typename ExPolicy, typename Rng, typename Comp = ranges::less, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::partial_sort(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     Rng
                                                                                                     &&rng,
                                                                                                     std::ranges::iterator,
                                                                                                     mid-
                                                                                                     dle,
                                                                                                     Comp
                                                                                                     &&comp
                                                                                                     =
                                                                                                     Comp(),
                                                                                                     Proj
                                                                                                     &&proj
                                                                                                     =
                                                                                                     Proj())
```

Sorts the elements in the range `[first, last)` in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object `comp` (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator `comp` and a projection `proj` if for every iterator `i` pointing to the sequence and every non-negative integer `n` such that `i + n` is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced). `Comp` defaults to `detail::less`;
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the `INVOKE` operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument

of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator. *Comp* defaults to `detail::less`.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *partial_sort* algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::ranges::iterator_t<Rng>` otherwise. It returns *last*.

hpx::ranges::partial_sort_copy

Defined in header `hpx/algorithm.hpp`⁶⁴⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter, typename Sent1, typename RandIter, typename Sent2, typename Comp =
ranges::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
partial_sort_copy_result<InIter, RandIter> hpx::ranges::partial_sort_copy(InIter first, Sent1 last, RandIter
                                                                    r_first, Sent2 r_last, Comp
                                                                    &&comp = Comp(), Proj1
                                                                    &&proj1 = Proj1(), Proj2
                                                                    &&proj2 = Proj2())
```

Sorts some of the elements in the range `[first, last)` in ascending order, storing the result in the range `[r_first, r_last)`. At most `r_last - r_first` of the elements are placed sorted to the range `[r_first, r_first + n)` where `n` is the number of elements to sort (`n = min(last - first, r_last - r_first)`).

The assignments in the parallel *partial_sort_copy* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{r_first}, \text{r_last})$ comparisons.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **RandIter** – The type of the destination iterators used (deduced). This iterator type must meet the requirements of a random iterator.
- **Sent2** – The type of the destination sentinel (deduced). This sentinel type must be a sentinel for *RandIter*.
- **Comp** – The type of the function/function object to use (deduced). *Comp* defaults to `detail::less`.
- **Proj1** – The type of an optional projection function for the input range. This defaults to `hpx::identity`.

⁶⁴⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Proj1** – The type of an optional projection function for the output range. This defaults to *hpx::identity*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the sentinel value denoting the end of the sequence of elements the algorithm will be applied to.
- **r_first** – Refers to the beginning of the destination range.
- **r_last** – Refers to the sentinel denoting the end of the destination range.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to *bool*, yields *true* if the first argument of the call is less than the second, and *false* otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator. This defaults to *detail::less*.
- **proj1** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation after the actual predicate *comp* is invoked.

Returns

The *partial_sort_copy* algorithm returns a *partial_sort_copy_result<InIter, RandIter>*.
The algorithm returns {*last*, *result_first* + *N*}.

```
template<typename ExPolicy, typename FwdIter, typename Sent1, typename RandIter, typename Sent2,  
        typename Comp = ranges::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>  
parallel::util::detail::algorithm_result_t<ExPolicy, partial_sort_copy_result<FwdIter, RandIter>> hpx::ranges::partial_sort_co
```

Sorts some of the elements in the range [*first*, *last*) in ascending order, storing the result in the range [*r_first*,

`r_last`). At most `r_last - r_first` of the elements are placed sorted to the range `[r_first, r_first + n)` where `n` is the number of elements to sort (`n = min(last - first, r_last - r_first)`).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{r_first}, \text{r_last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.
- **RandIter** – The type of the destination iterators used (deduced) This iterator type must meet the requirements of an random iterator.
- **Sent2** – The type of the destination sentinel (deduced). This sentinel type must be a sentinel for `RandIter`.
- **Comp** – The type of the function/function object to use (deduced). `Comp` defaults to `detail::less`.
- **Proj1** – The type of an optional projection function for the input range. This defaults to `hpx::identity`.
- **Proj2** – The type of an optional projection function for the output range. This defaults to `hpx::identity`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the sentinel value denoting the end of the sequence of elements the algorithm will be applied to.
- **r_first** – Refers to the beginning of the destination range.
- **r_last** – Refers to the sentinel denoting the end of the destination range.
- **comp** – `comp` is a callable object. The return value of the `INVOKE` operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. This defaults to `detail::less`.

- **proj1** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation after the actual predicate *comp* is invoked.

Returns

The *partial_sort_copy* algorithm returns a `hpx::future<partial_sort_copy_result<FwdIter, RandIter>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *partial_sort_copy_result<FwdIter, RandIter>* otherwise. The algorithm returns {last, result_first + N}.

```
template<typename Rng1, typename Rng2, typename Comp = ranges::less, typename Proj1 = hpx::identity,
typename Proj2 = hpx::identity>
```

```
partial_sort_copy_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>>> hpx::ranges::partial_sort_copy(Rng1
&&rng1, Rng1
&&rng2, Rng2
&&rng3, Comp
&&comp, Proj1
=
Comp(
Proj1
&&proj1,
=
Proj1(
Proj2
&&proj2,
=
Proj2(
```

Sorts some of the elements in the range [first, last) in ascending order, storing the result in the range [r_first, r_last). At most r_last - r_first of the elements are placed sorted to the range [r_first, r_first + n) where n is the number of elements to sort (n = min(last - first, r_last - r_first)).

The assignments in the parallel *partial_sort_copy* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{r_first}, \text{r_last})$ comparisons.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of a random iterator.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to `detail::less`.
- **Proj1** – The type of an optional projection function for the input range. This defaults to `hpx::identity`.

- **Proj2** – The type of an optional projection function for the output range. This defaults to *hpx::identity*.

Parameters

- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to *bool*, yields *true* if the first argument of the call is less than the second, and *false* otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator. This defaults to *detail::less*.
- **proj1** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation after the actual predicate *comp* is invoked.

Returns

The *partial_sort_copy* algorithm returns *partial_sort_copy_result<range_iterator_t<Rng1>, range_iterator_t<Rng2>>*. The algorithm returns {last, result_first + N}.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Comp = ranges::less, typename Proj1 =
hpx::identity, typename Proj2 = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, partial_sort_copy_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>
```

Sorts some of the elements in the range [first, last) in ascending order, storing the result in the range [r_first, r_last). At most r_last - r_first of the elements are placed sorted to the range [r_first, r_first + n) where n is the number of elements to sort (n = min(last - first, r_last - r_first)).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{r_first}, \text{r_last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of a random iterator.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to `detail::less`.
- **Proj1** – The type of an optional projection function for the input range. This defaults to `hpx::identity`.
- **Proj2** – The type of an optional projection function for the output range. This defaults to `hpx::identity`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the source range.
- **rng2** – Refers to the destination range.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. This defaults to `detail::less`.
- **proj1** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation after the actual predicate `comp` is invoked.

Returns

The `partial_sort_copy` algorithm returns a `hpx::future<partial_sort_copy_result<range_iterator_t<Rng1>, range_iterator_t<Rng2>>>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `partial_sort_copy_result<range_iterator_t<Rng1>, range_iterator_t<Rng2>>` otherwise. The algorithm returns `{last, result_first + N}`.

hpx::ranges::lexicographical_compare

Defined in header `hpx/algorithm.hpp`⁶⁵⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter1, typename Sent1, typename InIter2, typename Sent2, typename Proj1 =
hpx::identity, typename Proj2 = hpx::identity, typename Pred = hpx::parallel::detail::less>
bool hpx::ranges::lexicographical_compare(InIter1 first1, Sent1 last1, InIter2 first2, Sent2 last2, Pred
&&pred = Pred(), Proj1 &&proj1 = Proj1(), Proj2 &&proj2 =
Proj2())
```

Checks if the first range [first1, last1) is lexicographically less than the second range [first2, last2). uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{first1}, \text{last})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
 - The first mismatching element defines which range is lexicographically *less* or *greater* than the other
 - If one range is a prefix of another, the shorter range is lexicographically *less* than the other
 - If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **InIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter1.
- **InIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter2.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function for FwdIter1. This defaults to `hpx::identity`

⁶⁵⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Proj2** – The type of an optional projection function for `FwdIter2`. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *lexicographically_compare* algorithm returns *bool*. The *lexicographically_compare* algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2,
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity, typename Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::lexicographical_compare(ExPolicy
                                                                                                  &&pol-
                                                                                                  icy,
                                                                                                  FwdIter1
                                                                                                  first1,
                                                                                                  Sent1
                                                                                                  last1,
                                                                                                  FwdIter2
                                                                                                  first2,
                                                                                                  Sent2
                                                                                                  last2,
                                                                                                  Pred
                                                                                                  &&pred
                                                                                                  =
                                                                                                  Pred(),
                                                                                                  Proj1
                                                                                                  &&proj1
                                                                                                  =
                                                                                                  Proj1(),
                                                                                                  Proj2
                                                                                                  &&proj2
                                                                                                  =
                                                                                                  Proj2())
```

Checks if the first range [first1, last1) is lexicographically less than the second range [first2, last2). uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{first1}, \text{last})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
 - The first mismatching element defines which range is lexicographically *less* or *greater* than the other
 - If one range is a prefix of another, the shorter range is lexicographically *less* than the other
 - If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter1.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter2.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function for FwdIter1. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function for FwdIter2. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.

- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *lexicographically_compare* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *lexicographically_compare* algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

```
template<typename Rng1, typename Rng2, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity,
typename Pred = hpx::parallel::detail::less>
bool hpx::ranges::lexicographical_compare(Rng1 &&rng1, Rng2 &&rng2, Pred &&pred = Pred(), Proj1
&&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Checks if the first range rng1 is lexicographically less than the second range rng2. uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{std::begin}(\text{rng1}), \text{std::end}(\text{rng1}))$ and $N2 = \text{std::distance}(\text{std::begin}(\text{rng2}), \text{std::end}(\text{rng2}))$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
 - The first mismatching element defines which range is lexicographically *less* or *greater* than the other
 - If one range is a prefix of another, the shorter range is lexicographically *less* than the other
 - If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function for elements of the second range. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *lexicographically_compare* algorithm returns *bool*. The *lexicographically_compare* algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Proj1 = hpx::identity, typename Proj2
= hpx::identity, typename Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::lexicographical_compare(ExPolicy
&&pol-
icy,
Rng1
&&rng1,
Rng2
&&rng2,
Pred
&&pred
=
Pred(),
Proj1
&&proj1
=
Proj1(),
Proj2
&&proj2
=
Proj2())
```

Checks if the first range `rng1` is lexicographically less than the second range `rng2`. uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{std::begin}(\text{rng1}), \text{std::end}(\text{rng1}))$ and $N2 = \text{std::distance}(\text{std::begin}(\text{rng2}), \text{std::end}(\text{rng2}))$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
 - The first mismatching element defines which range is lexicographically *less* or *greater* than the other
 - If one range is a prefix of another, the shorter range is lexicographically *less* than the other
 - If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function for elements of the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function for elements of the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to
- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *lexicographically_compare* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *lexicographically_compare* algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

hpx::ranges::stable_sort

Defined in header [hpx/algorithm.hpp](#)⁶⁵¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename RandomIt, typename Sent, typename Comp = ranges::less, typename Proj = hpx::identity>
RandomIt hpx::ranges::stable_sort(RandomIt first, Sent last, Comp &&comp = Comp(), Proj &&proj =
    Proj())
```

Sorts the elements in the range [first, last) in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object comp (defaults to using operator<()).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i + n* is a valid iterator pointing to an element of the sequence, and INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false.

comp has to induce a strict weak ordering on the values.

The assignments in the parallel *stable_sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for RandomIt.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

⁶⁵¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *stable_sort* algorithm returns *RandomIt*. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename ExPolicy, typename RandomIt, typename Sent, typename Comp = ranges::less, typename  
Proj = hpx::identity>  
parallel::util::detail::algorithm_result<ExPolicy, RandomIt>::type hpx::ranges::stable_sort(ExPolicy  
                                                    &&policy,  
                                                    RandomIt first,  
                                                    Sent last, Comp  
                                                    &&comp =  
                                                    Comp(), Proj  
                                                    &&proj =  
                                                    Proj())
```

Sorts the elements in the range [first, last) in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object comp (defaults to using operator<()).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i + n* is a valid iterator pointing to an element of the sequence, and INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for RandomIt.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `stable_sort` algorithm returns a `hpx::future<RandomIt>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `RandomIt` otherwise. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename Rng, typename Comp = ranges::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> hpx::ranges::stable_sort(Rng &&rng, Comp &&comp = Comp(), Proj &&proj
                                                    = Proj())
```

Sorts the elements in the range `[first, last)` in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object `comp` (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator `comp` and a projection `proj` if for every iterator `i` pointing to the sequence and every non-negative integer `n` such that `i + n` is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

`comp` has to induce a strict weak ordering on the values.

The assignments in the parallel `stable_sort` algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `stable_sort` algorithm returns `std::ranges::iterator_t<Rng>`. It returns `last`.

```
template<typename ExPolicy, typename Rng, typename Comp = ranges::less, typename Proj = hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::stable_sort(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     Rng
                                                                                                     &&rng,
                                                                                                     Comp
                                                                                                     &&comp
                                                                                                     =
                                                                                                     Comp(),
                                                                                                     Proj
                                                                                                     &&proj
                                                                                                     =
                                                                                                     Proj())
```

Sorts the elements in the range [first, last) in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object *comp* (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the `INVOKE` operation applied to an object of type *Comp*, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *stable_sort* algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::ranges::iterator_t<Rng>` otherwise. It returns *last*.

hpx::ranges::partition

Defined in header `hpx/algorithm.hpp`⁶⁵².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::stable_partition`
- `hpx::ranges::partition_copy`

```
template<typename Rng, typename Pred, typename Proj = hpx::identity>
subrange_t<std::ranges::iterator_t<Rng>> hpx::ranges::partition(Rng &&rng, Pred &&pred, Proj &&proj =
    Proj())
```

Reorders the elements in the range *rng* in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs at most $2 * N$ swaps, exactly N applications of the predicate and projection, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by the range *rng*. This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

⁶⁵² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition* algorithm returns *subrange_t<std::ranges::iterator_t<Rng>>*. The *partition* algorithm returns a subrange starting with an iterator to the first element of the second group and finishing with an iterator equal to last.

```
template<typename ExPolicy, typename Rng, typename Pred, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>>>> hpx::ranges::partition(ExPolicy
                                                                 &&pol-
                                                                 icy,
                                                                 Rng
                                                                 &&rng,
                                                                 Pred
                                                                 &&pred,
                                                                 Proj
                                                                 &&proj
                                                                 =
                                                                 Proj())
```

Reorders the elements in the range *rng* in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs at most $2 * N$ swaps, exactly N applications of the predicate and projection, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by the range *rng*. This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition* algorithm returns a `hpx::future<subrange_t<std::ranges::iterator_t<Rng>>>` if the execution policy is of type *parallel_task_policy* and returns *subrange_t<std::ranges::iterator_t<Rng>>* The *partition* algorithm returns a subrange starting with an iterator to the first element of the second group and finishing with an iterator equal to last.

```
template<typename FwdIter, typename Sent, typename Pred, typename Proj = hpx::identity>
subrange_t<FwdIter> hpx::ranges::partition(FwdIter first, Sent last, Pred &&pred, Proj &&proj = Proj())
```

Reorders the elements in the range [first, last) in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: At most $2 * (\text{last} - \text{first})$ swaps. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

`bool pred(const Type &a);`

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition* algorithm returns *subrange_t<FwdIter>*. The *partition* algorithm returns a subrange starting with an iterator to the first element of the second group and finishing with an iterator equal to last.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred, typename Proj =  
hpx::identity>  
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<FwdIter>>::type hpx::ranges::partition(ExPolicy  
                                                    &&pol-  
                                                    icy,  
                                                    FwdIter  
                                                    first,  
                                                    Sent  
                                                    last,  
                                                    Pred  
                                                    &&pred,  
                                                    Proj  
                                                    &&proj  
                                                    =  
                                                    Proj())
```

Reorders the elements in the range [first, last) in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most 2 * (last - first) swaps. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.

- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition* algorithm returns a `hpx::future<subrange_t<FwdIter>>` if the execution policy is of type *parallel_task_policy* and returns *subrange_t<FwdIter>* otherwise. The *partition* algorithm returns a subrange starting with an iterator to the first element of the second group and finishing with an iterator equal to last.

hpx::ranges::stable_partition

Defined in header `hpx/algorithm.hpp`⁶⁵³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ranges::partition*
- *hpx::ranges::partition_copy*

```
template<typename Rng, typename Pred, typename Proj = hpx::identity>
subrange_t<std::ranges::iterator_t<Rng>> hpx::ranges::stable_partition(Rng &&rng, Pred &&pred, Proj
&&proj = Proj())
```

Permutes the elements in the range [first, last) such that there exists an iterator *i* such that for every iterator *j* in the range [first, *i*) `INVOKE(f, INVOKE(proj, *j)) != false`, and for every iterator *k* in the range [*i*, last), `INVOKE(f, INVOKE(proj, *k)) == false`

The invocations of *f* in the parallel *stable_partition* algorithm invoked without an execution policy object executes in sequential order in the calling thread.

⁶⁵³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: At most $(last - first) * \log(last - first)$ swaps, but only linear number of swaps if there is enough extra memory Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an bidirectional iterator
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *stable_partition* algorithm returns an iterator *i* such that for every iterator *j* in the range [first, i), $f(*j) \neq \text{false}$ INVOKE(*f*, INVOKE(*proj*, **j*)) $\neq \text{false}$, and for every iterator *k* in the range [i, last), $f(*k) == \text{false}$ INVOKE(*f*, INVOKE(*proj*, **k*)) $== \text{false}$. The relative order of the elements in both groups is preserved.

```
template<typename ExPolicy, typename Rng, typename Pred, typename Proj = hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>>> hpx::ranges::stable_partition(Ex
```

```
&&
icy
Rn
&&
Pr
&&
Pr
&&
=
Pr
```

Permutes the elements in the range [first, last) such that there exists an iterator *i* such that for every iterator *j* in the range [first, i) INVOKE(*f*, INVOKE(*proj*, **j*)) $\neq \text{false}$, and for every iterator *k* in the range [i, last), INVOKE(*f*, INVOKE(*proj*, **k*)) $== \text{false}$

The invocations of *f* in the parallel *stable_partition* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The invocations of f in the parallel *stable_partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(last - first) * \log(last - first)$ swaps, but only linear number of swaps if there is enough extra memory. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of f .
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an bidirectional iterator
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate f is invoked.

Returns

The *stable_partition* algorithm returns an iterator i such that for every iterator j in the range [first, i), $f(*j) != false$ INVOKE(f , INVOKE($proj$, $*j$)) $!= false$, and for every iterator k in the range [i , last), $f(*k) == false$ INVOKE(f , INVOKE($proj$, $*k$)) $== false$. The relative order of the elements in both groups is preserved. If the execution policy is of type *parallel_task_policy* the algorithm returns a future<> referring to this iterator.

```
template<typename BidirIter, typename Sent, typename Pred, typename Proj = hpx::identity>
subrange_t<BidirIter> hpx::ranges::stable_partition(BidirIter first, Sent last, Pred &&pred, Proj &&proj =
    Proj())
```

Permutes the elements in the range [first, last) such that there exists an iterator i such that for every iterator j in the range [first, i) INVOKE(f , INVOKE($proj$, $*j$)) $!= false$, and for every iterator k in the range [i , last), INVOKE(f , INVOKE($proj$, $*k$)) $== false$

The invocations of *f* in the parallel *stable_partition* algorithm invoked without an execution policy object executes in sequential order in the calling thread.

Note: Complexity: At most $(last - first) * \log(last - first)$ swaps, but only linear number of swaps if there is enough extra memory Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for BidirIter.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *stable_partition* algorithm returns an iterator *i* such that for every iterator *j* in the range [first, i), $f(*j) \neq \text{false}$ $\text{INVOKE}(f, \text{INVOKE}(\text{proj}, *j)) \neq \text{false}$, and for every iterator *k* in the range [i, last), $f(*k) == \text{false}$ $\text{INVOKE}(f, \text{INVOKE}(\text{proj}, *k)) == \text{false}$. The relative order of the elements in both groups is preserved.

```
template<typename ExPolicy, typename BidirIter, typename Sent, typename Pred, typename Proj =  
hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<BidirIter>>::type hpx::ranges::stable_partition(ExPolicy
&&pol-
icy,
BidirIter
first,
Sent
last,
Pred
&&pred,
Proj
&&proj
=
Proj())
```

Permutes the elements in the range `[first, last)` such that there exists an iterator `i` such that for every iterator `j` in the range `[first, i)` `INVOKE(f, INVOKE(proj, *j)) != false`, and for every iterator `k` in the range `[i, last)`, `INVOKE(f, INVOKE(proj, *k)) == false`

The invocations of `f` in the parallel `stable_partition` algorithm invoked with an execution policy object of type `sequenced_policy` executes in sequential order in the calling thread.

The invocations of `f` in the parallel `stable_partition` algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(last - first) * \log(last - first)$ swaps, but only linear number of swaps if there is enough extra memory Exactly `last - first` applications of the predicate and projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of `f`.
- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `BidirIter`.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of `partition` requires `Pred` to meet the requirements of `CopyConstructible`.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the

elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *stable_partition* algorithm returns an iterator *i* such that for every iterator *j* in the range [first, *i*), *f*(**j*) != false INVOKE(*f*, INVOKE(*proj*, **j*)) != false, and for every iterator *k* in the range [*i*, last), *f*(**k*) == false INVOKE(*f*, INVOKE(*proj*, **k*)) == false. The relative order of the elements in both groups is preserved. If the execution policy is of type *parallel_task_policy* the algorithm returns a `future<>` referring to this iterator.

hpx::ranges::partition_copy

Defined in header `hpx/algorithm.hpp`⁶⁵⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::partition*
- *hpx::ranges::stable_partition*

```
template<typename Rng, typename OutIter2, typename OutIter3, typename Pred, typename Proj =
hpx::identity>
partition_copy_result<std::ranges::iterator_t<Rng>, OutIter2, OutIter3> hpx::ranges::partition_copy(Rng
&&rng,
Out-
Iter2
dest_true,
Out-
Iter3
dest_false,
Pred
&&pred,
Proj
&&proj
=
Proj())
```

Copies the elements in the range *rng*, to two different ranges depending on the value returned by the predicate *pred*. The elements, that satisfy the predicate *pred* are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

⁶⁵⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs not more than N assignments, exactly N applications of the predicate *pred*, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **OutIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **OutIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns a `partition_copy_result<std::ranges::iterator_t<Rng>, FwdIter2, FwdIter3>>`. The *partition_copy* algorithm returns the tuple of the source iterator *last*, the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

```
template<typename ExPolicy, typename Rng, typename FwdIter2, typename FwdIter3, typename Pred,
typename Proj = hpx::identity>
```

`parallel::util::detail::algorithm_result<ExPolicy, partition_copy_result<std::ranges::iterator_t<Rng>, FwdIter2, FwdIter3>>::type hpx::`

Copies the elements in the range *rng*, to two different ranges depending on the value returned by the predicate *pred*. The elements, that satisfy the predicate *pred* are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than N assignments, exactly N applications of the predicate *pred*, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns a `hpx::future<partition_copy_result<std::ranges::iterator_t<Rng>, FwdIter2, FwdIter3>>` if the execution policy is of type *parallel_task_policy* and returns `partition_copy_result<std::ranges::iterator_t<Rng>, FwdIter2, FwdIter3>` otherwise. The *partition_copy* algorithm returns the tuple of the source iterator *last*, the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

```
template<typename InIter, typename Sent, typename OutIter2, typename OutIter3, typename Pred, typename Proj = hpx::identity>
```

```
partition_copy_result<InIter, OutIter2, OutIter3> hpx::ranges::partition_copy(InIter first, Sent last, OutIter2
                                                                    dest_true, OutIter3 dest_false,
                                                                    Pred &&pred, Proj &&proj =
                                                                    Proj())
```

Copies the elements in the range, defined by [first, last), to two different ranges depending on the value returned by the predicate *pred*. The elements, that satisfy the predicate *pred* are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *f*.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.

- **OutIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **OutIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns a *partition_copy_result*<*FwdIter*, *OutIter2*, *OutIter3*>. The *partition_copy* algorithm returns the tuple of the source iterator *last*, the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename OutIter2, typename OutIter3,  
typename Pred, typename Proj = hpx::identity>
```

`parallel::util::detail::algorithm_result<ExPolicy, partition_copy_result<FwdIter, OutIter2, OutIter3>>::type hpx::ranges::partiti`

Copies the elements in the range, defined by `[first, last)`, to two different ranges depending on the value returned by the predicate `pred`. The elements, that satisfy the predicate `pred` are copied to the range beginning at `dest_true`. The rest of the elements are copied to the range beginning at `dest_false`. The order of the elements is preserved.

The assignments in the parallel `partition_copy` algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The assignments in the parallel `partition_copy` algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than `last - first` assignments, exactly `last - first` applications of the predicate `f`.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.
- **OutIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate `pred` (deduced). This iterator type must meet the requirements of an forward iterator.
- **OutIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate `pred` (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form,

the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.

- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns a *hpx::future<partition_copy_result<FwdIter, OutIter2, OutIter3>>* if the execution policy is of type *parallel_task_policy* and returns *partition_copy_result<FwdIter, OutIter2, OutIter3>* otherwise. The *partition_copy* algorithm returns the tuple of the source iterator *last*, the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

hpx::ranges::experimental::for_loop

Defined in header `hpx/algorithm.hpp`⁶⁵⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ranges::experimental::for_loop_strided*
- *hpx::ranges::experimental::for_loop_n*
- *hpx::ranges::experimental::for_loop_n_strided*

template<typename **ExPolicy**, typename **Iter**, typename **Sent**, typename ...**Args**>

⁶⁵⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```

hpx::parallel::util::detail::algorithm_result<ExPolicy>::type hpx::ranges::experimental::for_loop(ExPolicy
                                                                &&pol-
                                                                icy, Iter
                                                                first,
                                                                Sent last,
                                                                Args&&...
                                                                args)

```

The `for_loop` implements loop functionality over a range specified by iterator bounds. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

Requires: *Iter* shall meet the requirements of a forward iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of Move-Constructible.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using `advance` and `distance`.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter** – The type of the iteration variable (forward iterator).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *Iter*.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

`<ignored> pred(Iter const& a, ...);`

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The `for_loop` algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

```
template<typename Iter, typename Sent, typename ...Args>  
void hpx::ranges::experimental::for_loop(Iter first, Sent last, Args&&... args)
```

The `for_loop` implements loop functionality over a range specified by iterator bounds. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *Iter* shall meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of Move-Constructible.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **Iter** – The type of the iteration variable (input iterator).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for Iter.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Iter const& a, ...);
```

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename R, typename ...Args>
hpx::parallel::util::detail::algorithm_result<ExPolicy>::type hpx::ranges::experimental::for_loop(ExPolicy
                                                                                               &&pol-
                                                                                               icy, R
                                                                                               &&rng,
                                                                                               Args&&...
                                                                                               args)
```

The `for_loop` implements loop functionality over a range specified by a range. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

Requires: `Rng::iterator` shall meet the requirements of a forward iterator type. The `args` parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, f . f shall meet the requirements of MoveConstructible.

Effects: Applies f to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the `args` parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **R** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Rng::iterator const& a, ...);
```

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The *for_loop* algorithm returns a *hpx::future<void>* if the execution policy is of type *hpx::execution::sequenced_task_policy* or *hpx::execution::parallel_task_policy* and returns *void* otherwise.

```
template<typename Rng, typename ...Args>
```

```
void hpx::ranges::experimental::for_loop(Rng &&rng, Args&&... args)
```

The `for_loop` implements loop functionality over a range specified by a range. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: `Rng::iterator` shall meet the requirements of an input iterator type. The `args` parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of `MoveConstructible`.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the `args` parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the `args` parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using `advance` and `distance`.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)` should expose a signature equivalent to:

```
<ignored> pred(Rng::iterator const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

`hpx::ranges::experimental::for_loop_strided`

Defined in header `hpx/algorithm.hpp`⁶⁵⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::experimental::for_loop`
- `hpx::ranges::experimental::for_loop_n`
- `hpx::ranges::experimental::for_loop_n_strided`

```
template<typename ExPolicy, typename Iter, typename Sent, typename S, typename ...Args>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::ranges::experimental::for_loop_strided(ExPolicy  
                                                         &&pol-  
                                                         icy,  
                                                         Iter  
                                                         first,  
                                                         Sent  
                                                         last,  
                                                         S  
                                                         stride,  
                                                         Args&&...  
                                                         args)
```

The `for_loop_strided` implements loop functionality over a range specified by iterator bounds. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

Requires: *Iter* shall meet the requirements of a forward iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of Move-Constructible.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

⁶⁵⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Complexity: Applies f exactly once for each element of the input sequence.

Remarks: If f returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter** – The type of the iteration variable (forward iterator).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for Iter.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if Iter meets the requirements a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Iter const& a, ...);
```

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The *for_loop_strided* algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

```
template<typename Iter, typename Sent, typename S, typename ...Args>
```

void `hpx::ranges::experimental::for_loop_strided`(*Iter* first, *Sent* last, *S* stride, *Args*&&... args)

The `for_loop_strided` implements loop functionality over a range specified by iterator bounds. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop_strided` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *Iter* shall meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of Move-Constructible.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using `advance` and `distance`.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **Iter** – The type of the iteration variable (input iterator).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *Iter*.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if *Iter* meets the requirements a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Iter const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename Rng, typename S, typename ...Args>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::ranges::experimental::for_loop_strided(ExPolicy
                                                         &&pol-
                                                         icy,
                                                         Rng
                                                         &&rng,
                                                         S
                                                         stride,
                                                         Args&&...
                                                         args)
```

The `for_loop_strided` implements loop functionality over a range specified by a range. These algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

Requires: *Rng::iterator* shall meet the requirements of a forward iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of `MoveConstructible`.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is `last - first`.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using `advance` and `distance`.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if `Rng::iterator` meets the requirements a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Rng::iterator const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The *for_loop_strided* algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

```
template<typename Rng, typename S, typename ...Args>
```

```
void hpx::ranges::experimental::for_loop_strided(Rng &&rng, S stride, Args&&... args)
```

The *for_loop_strided* implements loop functionality over a range specified by a range. These algorithms resemble *for_each* from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of *for_loop_strided* without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *Rng::iterator* shall meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of `MoveConstructible`.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is last - first.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if `Rng::iterator` meets the requirements a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(Rng::iterator const& a, ...);
```

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

hpx::ranges::experimental::for_loop_n

Defined in header [hpx/algorithm.hpp](#)⁶⁵⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::experimental::for_loop`
- `hpx::ranges::experimental::for_loop_strided`
- `hpx::ranges::experimental::for_loop_n_strided`

Warning: doxygenfunction: Cannot find function “hpx::ranges::experimental::for_loop_n” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::ranges::experimental::for_loop_n_strided

Defined in header [hpx/algorithm.hpp](#)⁶⁵⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::experimental::for_loop`
- `hpx::ranges::experimental::for_loop_strided`
- `hpx::ranges::experimental::for_loop_n`

Warning: doxygenfunction: Cannot find function “hpx::ranges::experimental::for_loop_n_strided” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::ranges::sort

Defined in header [hpx/algorithm.hpp](#)⁶⁵⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **RandomIt**, typename **Sent**, typename **Comp** = *ranges::less*, typename **Proj** = *hpx::identity*>
RandomIt **hpx::ranges::sort**(*RandomIt* first, *Sent* last, *Comp* &&comp = *Comp*(), *Proj* &&proj = *Proj*())

Sorts the elements in the range [first, last) in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object comp (defaults to using operator<()).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false.

comp has to induce a strict weak ordering on the values.

The assignments in the parallel *sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

⁶⁵⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

⁶⁵⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

⁶⁵⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: $O(N \log(N))$, where $N = \text{detail::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for **RandomIt**.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **comp** – **comp** is a callable object. The return value of the INVOKE operation applied to an object of type **Comp**, when contextually converted to **bool**, yields **true** if the first argument of the call is less than the second, and **false** otherwise. It is assumed that **comp** will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *sort* algorithm returns *RandomIt*. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename ExPolicy, typename RandomIt, typename Sent, typename Comp = ranges::less, typename
Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, RandomIt>::type hpx::ranges::sort(ExPolicy &&policy,
                                          RandomIt first, Sent last,
                                          Comp &&comp = Comp(),
                                          Proj &&proj = Proj())
```

Sorts the elements in the range $[\text{first}, \text{last})$ in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object **comp** (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{detail::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `RandomIt`.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **comp** – `comp` is a callable object. The return value of the `INVOKE` operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `sort` algorithm returns a `hpx::future<RandomIt>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `RandomIt` otherwise. The algorithm returns an iterator pointing to the first element after the last element in the input sequence.

```
template<typename Rng, typename Comp, typename Proj>
```

```
std::ranges::iterator_t<Rng> hpx::ranges::sort(Rng &&rng, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Sorts the elements in the range `rng` in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object `comp` (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator `comp` and a projection `proj` if for every iterator `i` pointing to the sequence and every non-negative integer `n` such that `i + n` is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

`comp` has to induce a strict weak ordering on the values.

The assignments in the parallel `sort` algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$ comparisons.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).

- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `sort` algorithm returns `std::ranges::iterator_t<Rng>`. It returns *last*.

```
template<typename ExPolicy, typename Rng, typename Comp = ranges::less, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::sort(ExPolicy
                                                                    &&policy,
                                                                    Rng &&rng,
                                                                    Comp
                                                                    &&comp =
                                                                    Comp(), Proj
                                                                    &&proj =
                                                                    Proj())
```

Sorts the elements in the range `rng` in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object `comp` (defaults to using `operator<()`).

A sequence is sorted with respect to a comparator `comp` and a projection `proj` if for every iterator `i` pointing to the sequence and every non-negative integer `n` such that `i + n` is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

`comp` has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{begin}(\text{rng}), \text{end}(\text{rng}))$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate `comp` is invoked.

Returns

The `sort` algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `std::ranges::iterator_t<Rng>` otherwise. It returns *last*.

`hpx::ranges::uninitialized_default_construct`

Defined in header `hpx/algorithm.hpp`⁶⁶⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::uninitialized_default_construct_n`

template<typename **FwdIter**, typename **Sent**>

FwdIter `hpx::ranges::uninitialized_default_construct`(*FwdIter* first, *Sent* last)

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel `uninitialized_default_construct` algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

⁶⁶⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *uninitialized_default_construct* algorithm returns a returns *FwdIter*. The *uninitialized_default_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

```
template<typename ExPolicy, typename FwdIter, typename Sent>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::uninitialized_default_construct(ExPolicy
&&pol-
icy,
FwdIter
first,
Sent
last)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

Returns

The *uninitialized_default_construct* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_default_construct* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename Rng>
```

`hpx::traits::range_traits<Rng>::iterator_type hpx::ranges::uninitialized_default_construct(Rng
&&rng)`

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

rng – Refers to the range to which will be default constructed.

Returns

The *uninitialized_default_construct* algorithm returns a `hpx::traits::range_traits<Rng>::iterator_type`. The *uninitialized_default_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

```
template<typename ExPolicy, typename Rng>
```

```
parallel::util::detail::algorithm_result<ExPolicy, typename hpx::traits::range_traits<Rng>::iterator_type>::type hpx::ranges::unini
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_default_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the range to which the value will be default constructed

Returns

The *uninitialized_default_construct* algorithm returns a `hpx::future<typename hpx::traits::range_traits<Rng>::iterator_type>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *typename hpx::traits::range_traits<Rng>::iterator_type* otherwise. The *uninitialized_default_construct* algorithm returns the output iterator to the element in the range, one past the last element constructed.

hpx::ranges::uninitialized_default_construct_n

Defined in header `hpx/algorithm.hpp`⁶⁶¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::uninitialized_default_construct*

```
template<typename FwdIter, typename Size>
```

```
FwdIter hpx::ranges::uninitialized_default_construct_n(FwdIter first, Size count)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range `[first, first + count)` by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct_n* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_default_construct_n* algorithm returns a `FwdIter`. The *uninitialized_default_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename ExPolicy, typename FwdIter, typename Size>
```

⁶⁶¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type *hpx::ranges::uninitialized_default_construct_n*(*ExPolicy* &&*policy*, *FwdIter* *first*, *Size* *count*)

Constructs objects of type *typename iterator_traits<ForwardIt>::value_type* in the uninitialized storage designated by the range [*first*, *first* + *count*) by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel *uninitialized_default_construct_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_default_construct_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_default_construct_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_default_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::ranges::transform_exclusive_scan

Defined in header [hpx/algorithm.hpp](#)⁶⁶².

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter, typename Sent, typename OutIter, typename BinOp, typename UnOp, typename T =
typename std::iterator_traits<InIter>::value_type>
transform_exclusive_scan_result<InIter, OutIter> hpx::ranges::transform_exclusive_scan(InIter first, Sent
                                                                    last, OutIter
                                                                    dest, T init,
                                                                    BinOp
                                                                    &&binary_op,
                                                                    UnOp
                                                                    &&unary_op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result) - 1))).

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The behavior of transform_exclusive_scan may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN) is defined as:

- a1 when N is 1
 - op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

⁶⁶² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_exclusive_scan* algorithm returns *transform_exclusive_scan_result<InIter, OutIter>*. The *transform_exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename BinOp,  
typename UnOp, typename T = typename std::iterator_traits<FwdIter1>::value_type>  
parallel::util::detail::algorithm_result<ExPolicy, transform_exclusive_result<FwdIter1, FwdIter2>>::type hpx::ranges::transform
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result) - 1))).

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The behavior of *transform_exclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aN*) is defined as:

- *a1* when *N* is 1
 - *op*(GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aK*), GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *aM*, ..., *aN*)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.

- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_exclusive_scan* algorithm returns a `hpx::future<transform_exclusive_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_exclusive_result<FwdIter1, FwdIter2>* otherwise. The *transform_exclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename BinOp, typename UnOp, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
transform_exclusive_scan_result<std::ranges::iterator_t<Rng>, O> hpx::ranges::transform_exclusive_scan(Rng
&&rng,
O
dest,
T
init,
BinOp
&&binary_op,
UnOp
&&unary_op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result) - 1))).

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The behavior of *transform_exclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **O** – The type of the iterator representing the destination range (deduced).
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The `transform_exclusive_scan` algorithm returns a `transform_exclusive_scan_result<std::ranges::iterator_t<Rng>, O>`. The `transform_exclusive_scan` algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename BinOp, typename UnOp, typename T =
typename std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, transform_exclusive_scan_result<std::ranges::iterator_t<Rng>, O>>::type hpx::rang
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result) - 1))).

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The behavior of *transform_exclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN) is defined as:

- a1 when N is 1
 - op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator. This iterator type must meet the requirements of an forward iterator.

- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_exclusive_scan* algorithm returns a `hpx::future<transform_exclusive_scan_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_exclusive_scan_result<std::ranges::iterator_t<Rng>, O>* otherwise. The *transform_exclusive_scan* algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::unique

Defined in header `hpx/algorithm.hpp`⁶⁶³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::unique_copy*

```
template<typename FwdIter, typename Sent, typename Pred = ranges::equal_to, typename Proj = hpx::identity>
```

⁶⁶³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
subrange_t<FwdIter, Sent> hpx::ranges::unique(FwdIter first, Sent last, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range [first, last) and returns a past-the-end iterator for the new logical end of the range.

The assignments in the parallel *unique* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique* algorithm returns *subrange_t*<*FwdIter*, *Sent*>. The *unique* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred = ranges::equal_to, typename Proj = hpx::identity>
```

```
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<FwdIter, Sent>>::type hpx::ranges::unique(ExPolicy
&&pol-
icy,
FwdIter
first,
Sent
last,
Pred
&&pred
=
Pred(),
Proj
&&proj
=
Proj())
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range [first, last) and returns a past-the-end iterator for the new logical end of the range.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique* algorithm returns *subrange_t<FwdIter, Sent>*. The *unique* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange.

```
template<typename Rng, typename Pred = ranges::equal_to, typename Proj = hpx::identity>
subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>> hpx::ranges::unique(Rng &&rng, Pred
&&pred = Pred(),
Proj &&proj =
Proj())
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range *rng* and returns a past-the-end iterator for the new logical end of the range.

The assignments in the parallel *unique* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs not more than N assignments, exactly N - 1 applications of the predicate *pred* and no more than twice as many applications of the projection *proj*, where N = `std::distance(begin(rng), end(rng))`.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique* algorithm returns *subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>*. The *unique* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange.

```
template<typename ExPolicy, typename Rng, typename Pred = ranges::equal_to, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>> hpx::range
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range *rng* and returns a past-the-end iterator for the new logical end of the range.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than N assignments, exactly N - 1 applications of the predicate *pred* and no more than twice as many applications of the projection *proj*, where N = std::distance(begin(rng), end(rng)).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to std::equal_to<>
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique* algorithm returns a `hpx::future <subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>* otherwise. The *unique* algorithm returns an object {ret, last}, where ret is a past-the-end iterator for a new subrange.

hpx::ranges::unique_copy

Defined in header `hpx/algorithm.hpp`⁶⁶⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::unique`

```
template<typename InIter, typename Sent, typename O, typename Pred = ranges::equal_to, typename Proj =  
hpx::identity>  
unique_copy_result<InIter, O> hpx::ranges::unique_copy(InIter first, Sent last, O dest, Pred &&pred = Pred(),  
Proj &&proj = Proj())
```

Copies the elements from the range [first, last), to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied.

The assignments in the parallel *unique_copy* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **O** – The type of the iterator representing the destination range (deduced).

⁶⁶⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique_copy* algorithm returns a `unique_copy_result<InIter, O>`. The *unique_copy* algorithm returns an `in_out_result` with the source iterator to one past the last element and out containing the destination iterator to the end of the *dest* range.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename O, typename Pred =
ranges::equal_to, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, unique_copy_result<FwdIter, O>>::type hpx::ranges::unique_copy(ExPolicy
&&policy,
FwdIter
first,
Sent
last,
O
dest,
Pred
&&pred
=
Pred(),
Proj
&&proj
=
Proj())
```

Copies the elements from the range [first, last), to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter1*.
- **O** – The type of the iterator representing the destination range (deduced).
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique_copy* algorithm returns returns a *hpx::future< unique_copy_result<FwdIter, O>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *unique_copy_result<FwdIter, O>* otherwise. The *unique_copy* algorithm returns an

`in_out_result` with the source iterator to one past the last element and out containing the destination iterator to the end of the *dest* range.

```
template<typename Rng, typename O, typename Pred = ranges::equal_to, typename Proj = hpx::identity>
unique_copy_result<std::ranges::iterator_t<Rng>, O> hpx::ranges::unique_copy(Rng &&rng, O dest, Pred
&&pred = Pred(), Proj
&&proj = Proj())
```

Copies the elements from the range *rng*, to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied.

The assignments in the parallel *unique_copy* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs not more than N assignments, exactly N - 1 applications of the predicate *pred*, where N = `std::distance(begin(rng), end(rng))`.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by the range *rng*. This is an binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique_copy* algorithm returns *unique_copy_result*< `std::ranges::iterator_t<Rng>`, O>. The *unique_copy* algorithm returns the pair of the source iterator to *last*, and the destination iterator to the end of the *dest* range.

```
template<typename ExPolicy, typename Rng, typename O, typename Pred = ranges::equal_to, typename Proj =
hpx::identity>
```

`parallel::util::detail::algorithm_result<ExPolicy, unique_copy_result<std::ranges::iterator_t<Rng>, O>> hpx::ranges::unique_cop`

Copies the elements from the range *rng*, to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than N assignments, exactly N - 1 applications of the predicate *pred*, where N = `std::distance(begin(rng), end(rng))`.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by the range *rng*. This is an binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *unique_copy* algorithm returns a `hpx::future<unique_copy_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *unique_copy_result<std::ranges::iterator_t<Rng>, O>* otherwise. The *unique_copy* algorithm returns the pair of the source iterator to *last*, and the destination iterator to the end of the *dest* range.

hpx::ranges::rotate

Defined in header `hpx/algorithm.hpp`⁶⁶⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::rotate_copy`

```
template<typename FwdIter, typename Sent>
```

```
subrange_t<FwdIter, Sent> hpx::ranges::rotate(FwdIter first, FwdIter middle, Sent last)
```

Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range `[first, last)` in such a way that the element *middle* becomes the first element of the new range and *middle - 1* becomes the last element.

The assignments in the parallel *rotate* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.

⁶⁶⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *rotate* algorithm returns a *subrange_t*<*FwdIter*, *Sent*>. The *rotate* algorithm returns the iterator equal to `pair(first + (last - middle), last)`.

```
template<typename ExPolicy, typename FwdIter, typename Sent>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<FwdIter, Sent>>::type hpx::ranges::rotate(ExPolicy
                                                                    &&pol-
                                                                    icy,
                                                                    FwdIter
                                                                    first,
                                                                    FwdIter
                                                                    mid-
                                                                    dle,
                                                                    Sent
                                                                    last)
```

Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range `[first, last)` in such a way that the element *middle* becomes the first element of the new range and *middle* - 1 becomes the last element.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *FwdIter*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *rotate* algorithm returns a `hpx::future<subrange_t<FwdIter, Sent>>` if the execution policy is of type *parallel_task_policy* and returns a `subrange_t<FwdIter, Sent>` otherwise. The *rotate* algorithm returns the iterator equal to `pair(first + (last - middle), last)`.

```
template<typename Rng>
subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>> hpx::ranges::rotate(Rng &&rng,
                                                                                          std::ranges::iterator_t<Rng>
                                                                                          middle)
```

Uses *rng* as the source range, as if using `util::begin(rng)` as *first* and `ranges::end(rng)` as *last*. Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range `[first, last)` in such a way that the element *middle* becomes the first element of the new range and *middle* - 1 becomes the last element.

The assignments in the parallel *rotate* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.

Returns

The *rotate* algorithm returns a `subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>`. The *rotate* algorithm returns the iterator equal to `pair(first + (last - middle), last)`.

```
template<typename ExPolicy, typename Rng>
parallel::util::detail::algorithm_result<ExPolicy, subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>> hpx::range
```

Uses *rng* as the source range, as if using `util::begin(rng)` as *first* and `ranges::end(rng)` as *last*. Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range `[first, last)` in such a way that the element *middle* becomes the first element of the new range and *middle* - 1 becomes the last element.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.

Returns

The *rotate* algorithm returns a `hpx::future <subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *subrange_t<std::ranges::iterator_t<Rng>, std::ranges::iterator_t<Rng>>*. otherwise. The *rotate* algorithm returns the iterator equal to `pair(first + (last - middle), last)`.

hpx::ranges::rotate_copy

Defined in header `hpx/algorithm.hpp`⁶⁶⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::rotate`

```
template<typename FwdIter, typename Sent, typename OutIter>
rotate_copy_result<FwdIter, OutIter> hpx::ranges::rotate_copy(FwdIter first, FwdIter middle, Sent last,
                                                             OutIter dest_first)
```

Copies the elements from the range `[first, last)`, to another range beginning at `dest_first` in such a way, that the element *middle* becomes the first element of the new range and *middle* - 1 becomes the last element.

The assignments in the parallel *rotate_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last* - *first* assignments.

⁶⁶⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_first** – Output iterator to the initial position of the range where the reversed range is stored. The pointed type shall support being assigned the value of an element in the range [first,last).

Returns

The *rotate_copy* algorithm returns a *rotate_copy_result<FwdIter, OutIter>*. The *rotate_copy* algorithm returns the output iterator to the element past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2>
parallel::util::detail::algorithm_result<ExPolicy, rotate_copy_result<FwdIter1, FwdIter2>>::type hpx::ranges::rotate_copy(ExPo
&&P
icy,
Fwd
first,
Fwd
mid-
dle,
Sent
last,
Fwd
dest,
```

Copies the elements from the range [first, last), to another range beginning at *dest_first* in such a way, that the element *middle* becomes the first element of the new range and *middle* - 1 becomes the last element.

The assignments in the parallel *rotate_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *rotate_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last* - *first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for FwdIter.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_first** – Output iterator to the initial position of the range where the reversed range is stored. The pointed type shall support being assigned the value of an element in the range [first,last).

Returns

The `rotate_copy` algorithm returns `areturns hpx::future< rotate_copy_result<FwdIter1, FwdIter2>>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `rotate_copy_result<FwdIter1, FwdIter2>` otherwise. The `rotate_copy` algorithm returns the output iterator to the element past the last element copied.

```
template<typename Rng, typename OutIter>
rotate_copy_result<std::ranges::iterator_t<Rng>, OutIter> hpx::ranges::rotate_copy(Rng &&rng,
                                                                                    std::ranges::iterator_t<Rng>
                                                                                    middle, OutIter
                                                                                    dest_first)
```

Uses `rng` as the source range, as if using `util::begin(rng)` as `first` and `ranges::end(rng)` as `last`. Copies the elements from the range [first, last), to another range beginning at `dest_first` in such a way, that the element `middle` becomes the first element of the new range and `middle - 1` becomes the last element.

The assignments in the parallel `rotate_copy` algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly `last - first` assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.

- **middle** – Refers to the element that should appear at the beginning of the rotated range.
- **dest_first** – Output iterator to the initial position of the range where the reversed range is stored. The pointed type shall support being assigned the value of an element in the range `[first,last)`.

Returns

The *rotate* algorithm returns a *rotate_copy_result*`<std::ranges::iterator_t<Rng>, OutIter>`. The *rotate_copy* algorithm returns the output iterator to the element past the last element copied.

```
template<typename ExPolicy, typename Rng, typename OutIter>
parallel::util::detail::algorithm_result<ExPolicy, rotate_copy_result<std::ranges::iterator_t<Rng>, OutIter>> hpx::ranges::rotate_
```

Uses *rng* as the source range, as if using *util::begin(rng)* as *first* and *ranges::end(rng)* as *last*. Copies the elements from the range `[first, last)`, to another range beginning at *dest_first* in such a way, that the element *new_first* becomes the first element of the new range and *new_first* - 1 becomes the last element.

The assignments in the parallel *rotate_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *rotate_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the element that should appear at the beginning of the rotated range.

- **dest_first** – Output iterator to the initial position of the range where the reversed range is stored. The pointed type shall support being assigned the value of an element in the range [first,last).

Returns

The `rotate_copy` algorithm returns a `hpx::future<rotate_copy_result<std::ranges::iterator_t<Rng>, OutIter>>` if the execution policy is of type `parallel_task_policy` and returns `rotate_copy_result<std::ranges::iterator_t<Rng>, OutIter>` otherwise. The `rotate_copy` algorithm returns the output iterator to the element past the last element copied.

hpx::ranges::transform_reduce

Defined in header [hpx/algorithm.hpp](#)⁶⁶⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Warning: doxygenfunction: Cannot find function “hpx::ranges::transform_reduce” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::ranges::transform

Defined in header [hpx/algorithm.hpp](#)⁶⁶⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **ExPolicy**, typename **FwdIter1**, typename **Sent1**, typename **FwdIter2**, typename **F**, typename **Proj** = `hpx::identity`>

`parallel::util::detail::algorithm_result<ExPolicy, ranges::unary_transform_result<FwdIter1, FwdIter2>>::type` `hpx::ranges::transform`

Applies the given function *f* to the given range *rng* and stores the result in another range, beginning at *dest*.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

⁶⁶⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

⁶⁶⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Exactly $\text{size}(\text{rng})$ applications of f

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of f .
- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for **FwdIter1**.
- **FwdIter2** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires F to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate. The signature of this predicate should be equivalent to:

Ret fun(const Type &a);

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *FwdIter2* can be dereferenced and assigned a value of type *Ret*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate f is invoked.

Returns

The *transform* algorithm returns a `hpx::future<ranges::unary_transform_result<FwdIter1, FwdIter2>>` if the execution policy is of type *parallel_task_policy* and returns `ranges::unary_transform_result<FwdIter1, FwdIter2>` otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename FwdIter, typename F, typename Proj = hpx::identity>
```

parallel::util::detail::algorithm_result<ExPolicy, ranges::unary_transform_result<std::ranges::iterator_t<Rng>, FwdIter>> hpx::rang

Applies the given function *f* to the given range *rng* and stores the result in another range, beginning at *dest*.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\text{size}(\text{rng})$ applications of *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *range_iterator<Rng>::type* can be dereferenced and then implicitly converted to *Type*.

The type *Ret* must be such that an object of type *OutIter* can be dereferenced and assigned a value of type *Ret*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns a `hpx::future<ranges::unary_transform_result<range_iterator<Rng>::type, FwdIter>>` if the execution policy is of type *parallel_task_policy* and returns `ranges::unary_transform_result<range_iterator<Rng>::type, FwdIter>` otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2,
        typename FwdIter3, typename F, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, ranges::binary_transform_result<FwdIter1, FwdIter2, FwdIter3>>::type hpx::range
```

Applies the given function *f* to pairs of elements from two ranges: one defined by *rng* and the other beginning at *first2*, and stores the result in another range, beginning at *dest*.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly `size(rng)` applications of *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for FwdIter1.
- **FwdIter2** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for FwdIter2.
- **FwdIter3** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj1** – The type of an optional projection function to be used for elements of the first sequence. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function to be used for elements of the second sequence. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.
- **last2** – Refers to the end of the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`. The types *Type1* and *Type2* must be such that objects of types FwdIter1 and FwdIter2 can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively. The type *Ret* must be such that an object of type *FwdIter3* can be dereferenced and assigned a value of type *Ret*.

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *f* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns `A hpx::future<ranges::binary_transform_result<FwdIter1, FwdIter2, FwdIter3>>` if the execution policy is of type *parallel_task_policy* and returns `ranges::binary_transform_result<FwdIter1, FwdIter2, FwdIter3>` otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename Sent1, typename FwdIter2, typename F, typename Proj = hpx::identity>
ranges::unary_transform_result<FwdIter1, FwdIter2> hpx::ranges::transform(FwdIter1 first, Sent1 last,
                                                                    FwdIter2 dest, F &&f, Proj
                                                                    &&proj = Proj())
```

Applies the given function *f* to the given range *rng* and stores the result in another range, beginning at *dest*.

Note: Complexity: Exactly `size(rng)` applications of *f*

Template Parameters

- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for *FwdIter1*.
- **FwdIter2** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *FwdIter2* can be dereferenced and assigned a value of type *Ret*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns `ranges::unary_transform_result<FwdIter1, FwdIter2>`. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the

input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename FwdIter, typename F, typename Proj = hpx::identity>
ranges::unary_transform_result<std::ranges::iterator_t<Rng>, FwdIter> hpx::ranges::transform(Rng &&rng,
                                                                                          FwdIter dest,
                                                                                          F &&f, Proj
                                                                                          &&proj =
                                                                                          Proj())
```

Applies the given function *f* to the given range *rng* and stores the result in another range, beginning at *dest*.

Note: Complexity: Exactly *size(rng)* applications of *f*

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *range_iterator<Rng>::type* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *OutIter* can be dereferenced and assigned a value of type *Ret*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns *ranges::unary_transform_result<range_iterator<Rng>::type, FwdIter>*. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2, typename FwdIter3,
typename F, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
```

```

ranges::binary_transform_result<FwdIter1, FwdIter2, FwdIter3> hpx::ranges::transform(FwdIter1 first1,
                                                                                      Sent1 last1,
                                                                                      FwdIter2 first2,
                                                                                      Sent2 last2,
                                                                                      FwdIter3 dest, F
                                                                                      &&f, Proj1
                                                                                      &&proj1 = Proj1(),
                                                                                      Proj2 &&proj2 =
                                                                                      Proj2())

```

Applies the given function *f* to pairs of elements from two ranges: one defined by *rng* and the other beginning at *first2*, and stores the result in another range, beginning at *dest*.

Note: Complexity: Exactly `size(rng)` applications of *f*

Template Parameters

- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for FwdIter1.
- **FwdIter2** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for FwdIter2.
- **FwdIter3** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj1** – The type of an optional projection function to be used for elements of the first sequence. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function to be used for elements of the second sequence. This defaults to *hpx::identity*

Parameters

- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.
- **last2** – Refers to the end of the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively. The type *Ret* must be such that an object of type *FwdIter3* can be dereferenced and assigned a value of type *Ret*.

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *f* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns `ranges::binary_transform_result<FwdIter1, FwdIter2, FwdIter3>`. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2, typename FwdIter, typename F, typename Proj1 = hpx::identity,
typename Proj2 = hpx::identity>
ranges::binary_transform_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, FwdIter> hpx::ranges::transform(
```

Applies the given function *f* to pairs of elements from two ranges: one defined by [first1, last1) and the other beginning at first2, and stores the result in another range, beginning at dest.

Note: Complexity: Exactly min(last2-first2, last1-first1) applications of *f*

Note: The algorithm will invoke the binary predicate until it reaches the end of the shorter of the two given input sequences

Template Parameters

- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj1** – The type of an optional projection function to be used for elements of the first sequence. This defaults to *hpx::identity*
- **Proj2** – The type of an optional projection function to be used for elements of the second sequence. This defaults to *hpx::identity*

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`. The types *Type1* and *Type2* must be such that objects of types `range_iterator<Rng1>::type` and `range_iterator<Rng2>::type` can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively. The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *f* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *f* is invoked.

Returns

The *transform* algorithm returns `ranges::binary_transform_result<std::ranges::iterator_t<Rng1>, std::ranges::iterator_t<Rng2>, FwdIter>`. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

hpx::ranges::count

Defined in header `hpx/algorithm.hpp`⁶⁶⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::count_if`

```
template<typename ExPolicy, typename Rng, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
```

⁶⁶⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<typename hpx::traits::range_traits<Rng>::iterator_t

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*.

The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* comparisons.

Note: The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to search for (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count* algorithm returns a *hpx::future<difference_type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *std::iterator_traits<FwdIter>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.


```
template<typename ExPolicy, typename Iter, typename Sent, typename Proj = hpx::identity, typename T =
typename hpx::parallel::traits::projected<Iter, Proj>::value_type>
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<Iter>::difference_type>::type hpx::ranges::count
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*.

The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* comparisons.

Note: The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **T** – The type of the value to search for (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count* algorithm returns a *hpx::future<difference_type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *std::iterator_traits<FwdIter>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename Rng, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
std::iterator_traits<typename hpx::traits::range_traits<Rng>::iterator_type>::difference_type hpx::ranges::count(Rng
&&rng,
T
const
&value,
Proj
&&proj
=
Proj())
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*.

Note: Complexity: Performs exactly *last - first* comparisons.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to search for (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename Iter, typename Sent, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<Iter, Proj>::value_type>
std::iterator_traits<Iter>::difference_type hpx::ranges::count(Iter first, Sent last, T const &value, Proj &&proj
= Proj())
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*.

Note: Complexity: Performs exactly *last - first* comparisons.

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **T** – The type of the value to search for (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count* algorithm returns the number of elements satisfying the given criteria.

`hpx::ranges::count_if`

Defined in header `hpx/algorithm.hpp`⁶⁷⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::count`

```
template<typename ExPolicy, typename Rng, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<typename hpx::traits::range_traits<Rng>::iterator_t
```

Returns the number of elements in the range `[first, last)` satisfying a specific criteria. This version counts elements for which predicate *f* returns true.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁶⁷⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *count_if* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count_if* algorithm returns *hpx::future<difference_type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *std::iterator_traits<FwdIter>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename ExPolicy, typename Iter, typename Sent, typename F, typename Proj = hpx::identity>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<Iter>::difference_type>::type hpx::ranges::count
```

Returns the number of elements in the range `[first, last)` satisfying a specific criteria. This version counts elements for which predicate *f* returns true.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *count_if* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count_if* algorithm returns *hpx::future<difference_type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *std::iterator_traits<FwdIter>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename Rng, typename F, typename Proj = hpx::identity>
std::iterator_traits<typename hpx::traits::range_traits<Rng>::iterator_type>::difference_type hpx::ranges::count_if(Rng
                                                                                                     &&rng,
                                                                                                     F
                                                                                                     &&f,
                                                                                                     Proj
                                                                                                     &&proj
                                                                                                     =
                                                                                                     Proj())
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts elements for which predicate *f* returns true.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *count_if* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
std::iterator_traits<Iter>::difference_type hpx::ranges::count_if(Iter first, Sent last, F &&f, Proj &&proj =
                                                                 Proj())
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts elements for which predicate *f* returns true.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).

- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of `count_if` requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The `count` algorithm returns the number of elements satisfying the given criteria.

`hpx::ranges::transform_inclusive_scan`

Defined in header `hpx/algorithm.hpp`⁶⁷¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename InIter, typename Sent, typename OutIter, typename BinOp, typename UnOp>
transform_inclusive_scan_result<InIter, OutIter> hpx::ranges::transform_inclusive_scan(InIter first, Sent
                                                                                          last, OutIter
                                                                                          dest, BinOp
                                                                                          &&binary_op,
                                                                                          UnOp
                                                                                          &&unary_op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result)))).

The reduce operations in the parallel `transform_inclusive_scan` algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The behavior of `transform_inclusive_scan` may be non-deterministic for a non-associative predicate.

⁶⁷¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The `transform_inclusive_scan` algorithm returns `transform_inclusive_scan_result<InIter, OutIter>`. The `transform_inclusive_scan` algorithm returns an input iterator to the point denoted by

the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename BinOp,
typename UnOp>
```

```
parallel::util::detail::algorithm_result<ExPolicy, transform_inclusive_result<FwdIter1, FwdIter2>>>::type hpx::ranges::transform
```

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - $op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, \dots, aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, \dots, aN))$ where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.

- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_inclusive_scan* algorithm returns a `hpx::future<transform_inclusive_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_inclusive_result<FwdIter1, FwdIter2>* otherwise. The *transform_inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename BinOp, typename UnOp>
transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O> hpx::ranges::transform_inclusive_scan(Rng
                                                                                                     &&rng,
                                                                                                     O
                                                                                                     dest,
                                                                                                     BinOp
                                                                                                     &&bi-
                                                                                                     nary_op,
                                                                                                     UnOp
                                                                                                     &&unary_op)
```

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - $op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, \dots, aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, \dots, aN))$ where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **O** – The type of the iterator representing the destination range (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by $[first, last)$. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_inclusive_scan* algorithm returns a *transform_inclusive_scan_result*<`std::ranges::iterator_t<Rng>`, *O*>. The *transform_inclusive_scan* algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename BinOp, typename UnOp>
parallel::util::detail::algorithm_result<ExPolicy, transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>>::type hpx::rang
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- *a1* when *N* is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator. This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_inclusive_scan* algorithm returns a `hpx::future<transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>* otherwise. The *transform_inclusive_scan* algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename Sent, typename OutIter, typename BinOp, typename UnOp, typename T =
typename std::iterator_traits<InIter>::value_type>
transform_inclusive_scan_result<InIter, OutIter> hpx::ranges::transform_inclusive_scan(InIter first, Sent
last, OutIter
dest, BinOp
&&binary_op,
UnOp
&&unary_op, T
init)
```

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns *transform_inclusive_scan_result<InIter, OutIter>*. The *transform_inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename BinOp,
typename UnOp, typename T = typename std::iterator_traits<FwdIter1>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, transform_inclusive_result<FwdIter1, FwdIter2>>::type hpx::ranges::transform
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The behavior of `transform_inclusive_scan` may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a unary predicate. The signature of this predicate should be equivalent to:


```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns a `hpx::future<transform_inclusive_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_inclusive_result<FwdIter1, FwdIter2>* otherwise. The *transform_inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename BinOp, typename UnOp, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O> hpx::ranges::transform_inclusive_scan(Rng
&&rng,
O
dest,
BinOp
&&binary_op,
UnOp
&&unary_op,
T
init)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *conv* nor *op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The behavior of *transform_inclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *op* and *conv*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when *N* is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **O** – The type of the iterator representing the destination range (deduced).
- **BinOp** – The type of the binary function object used for the reduction operation.
- **UnOp** – The type of the unary function object used for the conversion operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns a *transform_inclusive_scan_result*<`std::ranges::iterator_t<Rng>`, *O*>. The *transform_inclusive_scan* algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename BinOp, typename UnOp, typename T =  
typename std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
```

```
parallel::util::detail::algorithm_result<ExPolicy, transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>>::type hpx::rang
```

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel `transform_inclusive_scan` algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The reduce operations in the parallel `transform_inclusive_scan` algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither `conv` nor `op` shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of `transform_inclusive_scan` may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of the predicates `op` and `conv`.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - $op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, \dots, aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, \dots, aN))$ where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator. This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of the binary function object used for the reduction operation.

- **UnOp** – The type of the unary function object used for the conversion operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **unary_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns a `hpx::future<transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *transform_inclusive_scan_result<std::ranges::iterator_t<Rng>, O>* otherwise. The *transform_inclusive_scan* algorithm returns an input iterator to one past the end of the range and an output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::is_sorted

Defined in header `hpx/algorithm.hpp`⁶⁷².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::is_sorted_until*

template<typename **FwdIter**, typename **Sent**, typename **Pred** = *hpx::parallel::detail::less*, typename **Proj** = *hpx::identity*>

⁶⁷² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

bool `hpx::ranges::is_sorted`(*FwdIter* first, *Sent* last, *Pred* &&pred = *Pred*(), *Proj* &&proj = *Proj*())

Determines if the range [first, last) is sorted. Uses pred to compare elements.

The comparison operations in the parallel *is_sorted* algorithm executes in sequential order in the calling thread.

Note: Complexity: at most (N+S-1) comparisons where *N* = distance(first, last). *S* = number of partitions

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted* algorithm returns a *bool*. The *is_sorted* algorithm returns true if each element in the sequence [first, last) satisfies the predicate passed. If the range [first, last) contains less than two elements, the function always returns true.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred = hpx::parallel::detail::less,
typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::is_sorted(ExPolicy &&policy,
                                                                    FwdIter first, Sent last,
                                                                    Pred &&pred = Pred(),
                                                                    Proj &&proj = Proj())
```

Determines if the range [first, last) is sorted. Uses pred to compare elements.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = distance(first, last). S = number of partitions

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted* algorithm returns a `hpx::future<bool>` if the execution policy is of type *task_execution_policy* and returns `bool` otherwise. The *is_sorted* algorithm returns a `bool` if each element in the sequence [first, last) satisfies the predicate passed. If the range [first, last) contains less than two elements, the function always returns true.

```
template<typename Rng, typename Pred = hpx::parallel::detail::less, typename Proj = hpx::identity>  
bool hpx::ranges::is_sorted(Rng &&rng, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Determines if the range *rng* is sorted. Uses *pred* to compare elements.

The comparison operations in the parallel *is_sorted* algorithm executes in sequential order in the calling thread.

Note: Complexity: at most $(N+S-1)$ comparisons where $N = \text{size}(\text{rng})$. $S = \text{number of partitions}$

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted* algorithm returns a *bool*. The *is_sorted* algorithm returns true if each element in the *rng* satisfies the predicate passed. If the range *rng* contains less than two elements, the function always returns true.

```
template<typename ExPolicy, typename Rng, typename Pred = hpx::parallel::detail::less, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::is_sorted(ExPolicy &&policy,
                                                                                      Rng &&rng, Pred
                                                                                      &&pred = Pred(), Proj
                                                                                      &&proj = Proj())
```

Determines if the range *rng* is sorted. Uses *pred* to compare elements.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(N+S-1)$ comparisons where $N = \text{size}(\text{rng})$. $S = \text{number of partitions}$

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted* algorithm returns a `hpx::future<bool>` if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_sorted* algorithm returns a *bool* if each element in the range *rng* satisfies the predicate passed. If the range *rng* contains less than two elements, the function always returns true.

hpx::ranges::is_sorted_until

Defined in header `hpx/algorithm.hpp`⁶⁷³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ranges::is_sorted`

```
template<typename FwdIter, typename Sent, typename Pred = hpx::parallel::detail::less, typename Proj = hpx::identity>
```

```
FwdIter hpx::ranges::is_sorted_until(FwdIter first, Sent last, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Returns the first element in the range `[first, last)` that is not sorted. Uses a predicate to compare elements or the less than operator.

The comparison operations in the parallel *is_sorted_until* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = distance(first, last). S = number of partitions

Template Parameters

⁶⁷³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter** – The type of the source iterators used for the `This` iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.
- **Pred** – The type of an optional function/function object to use.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted_until* algorithm returns a *FwdIter*. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, *last* is returned.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename Pred = hpx::parallel::detail::less,
typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type hpx::ranges::is_sorted_until(ExPolicy
&&pol-
icy,
FwdIter
first,
Sent last,
Pred
&&pred
=
Pred(),
Proj
&&proj
=
Proj())
```

Returns the first element in the range `[first, last)` that is not sorted. Uses a predicate to compare elements or the less than operator.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = distance(first, last). S = number of partitions

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted_until* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted_until* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is returned.

```
template<typename Rng, typename Pred = hpx::parallel::detail::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> hpx::ranges::is_sorted_until(Rng &&rng, Pred &&pred = Pred(), Proj
&&proj = Proj())
```

Returns the first element in the range *rng* that is not sorted. Uses a predicate to compare elements or the less than operator.

Note: Complexity: at most $(N+S-1)$ comparisons where $N = \text{size}(\text{rng})$. $S = \text{number of partitions}$

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted_until* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted_until* returns *FwdIter*. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is returned.

```
template<typename ExPolicy, typename Rng, typename Pred = hpx::parallel::detail::less, typename Proj =  
hpx::identity>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::is_sorted_until(ExPolicy  
    &&pol-  
    icy,  
    Rng  
    &&rng,  
    Pred  
    &&pred  
    =  
    Pred(),  
    Proj  
    &&proj  
    =  
    Proj())
```

Returns the first element in the range *rng* that is not sorted. Uses a predicate to compare elements or the less than operator.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(N+S-1)$ comparisons where $N = \text{size}(\text{rng})$. $S = \text{number of partitions}$

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted_until* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *is_sorted_until* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is returned.

hpx::ranges::uninitialized_copy

Defined in header `hpx/algorithm.hpp`⁶⁷⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::uninitialized_copy_n`

template<typename **InIter**, typename **Sent1**, typename **FwdIter**, typename **Sent2**>

⁶⁷⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
hpx::parallel::util::in_out_result<InIter, FwdIter> hpx::ranges::uninitialized_copy(InIter first1, Sent1 last1,
                                                                                   FwdIter first2, Sent2
                                                                                   last2)
```

Copies the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter2.

Parameters

- **first1** – Refers to the beginning of the sequence of elements that will be copied from
- **last1** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_copy* algorithm returns an *in_out_result<InIter, FwdIter>*. The *uninitialized_copy* algorithm returns an input iterator to one past the last element copied from and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2>
parallel::util::detail::algorithm_result<ExPolicy, parallel::util::in_out_result<FwdIter1, FwdIter2>>::type hpx::ranges::uninitial
```

Copies the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter2*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements that will be copied from
- **last1** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_copy* algorithm returns a `hpx::future<in_out_result<InIter, FwdIter>>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *in_out_result<InIter, FwdIter>* otherwise. The *uninitialized_copy* algorithm returns an input iterator to one past the last element copied from and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng1, typename Rng2>
hpx::parallel::util::in_out_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typename hpx::traits::range_traits<Rng2>::it
```

Copies the elements in the range, defined by `[first, last)`, to an uninitialized memory area beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

Parameters

- **rng1** – Refers to the range from which the elements will be copied from
- **rng2** – Refers to the range to which the elements will be copied to

Returns

The *uninitialized_copy* algorithm returns an *in_out_result*<typename `hpx::traits::range_traits<Rng1>::iterator_type`, typename `hpx::traits::range_traits<Rng2>::iterator_type`>. The *uninitialized_copy* algorithm returns an input iterator to one past the last element copied from and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng1, typename Rng2>
parallel::util::detail::algorithm_result<ExPolicy, hpx::parallel::util::in_out_result<typename hpx::traits::range_traits<Rng1>::iterator_t
```

Copies the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the range from which the elements will be copied from
- **rng2** – Refers to the range to which the elements will be copied to

Returns

The *uninitialized_copy* algorithm returns a `hpx::future<in_out_result<InIter, FwdIter>>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `in_out_result< typename hpx::traits::range_traits<Rng1>::iterator_type , typename hpx::traits::range_traits<Rng2>::iterator_type>` otherwise. The *uninitialized_copy* algorithm returns the input iterator to one past the last element copied from and the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::uninitialized_copy_n

Defined in header `hpx/algorithm.hpp`⁶⁷⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::uninitialized_copy`

```
template<typename InIter, typename Size, typename FwdIter, typename Sent2>
hpx::parallel::util::in_out_result<InIter, FwdIter> hpx::ranges::uninitialized_copy_n(InIter first1, Size
                                                    count, FwdIter first2,
                                                    Sent2 last2)
```

Copies the elements in the range `[first, first + count)`, starting from `first` and proceeding to `first + count - 1.`, to another range beginning at `dest`. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.

Parameters

⁶⁷⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **first1** – Refers to the beginning of the sequence of elements that will be copied from
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_copy_n* algorithm returns *in_out_result<InIter, FwdIter>*. The *uninitialized_copy_n* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Size, typename FwdIter2, typename Sent2>
parallel::util::detail::algorithm_result<ExPolicy, parallel::util::in_out_result<FwdIter1, FwdIter2>>::type hpx::ranges::uninitial
```

Copies the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter2.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements that will be copied from
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_copy_n* algorithm returns a `hpx::future<in_out_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *uninitialized_copy_n* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::mismatch

Defined in header `hpx/algorithm.hpp`⁶⁷⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

template<typename **ExPolicy**, typename **Iter1**, typename **Sent1**, typename **Iter2**, typename **Sent2**, typename **Pred** = equal_to, typename **Proj1** = *hpx::identity*, typename **Proj2** = *hpx::identity*>

hpx::parallel::util::detail::algorithm_result<ExPolicy, mismatch_result<Iter1, Iter2>>::type **hpx::ranges::mismatch**(*ExPolicy* &&policy, *Iter1* first1, *Sent1* last1, *Iter2* first2, *Sent2* last2, *Pred* &&op = *Pred*(), *Proj1* &&proj1 = *Proj1*(), *Proj2* &&proj2 = *Proj2*())

Returns true if the range [first1, last1) is mismatch to the range [first2, last2), and false otherwise.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁶⁷⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate *f*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of the predicate *f* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range $[\text{first1}, \text{last1})$, **i* mismatches $*(\text{first2} + (i - \text{first1}))$. This overload of *mismatch* uses `operator==` to determine if two elements are mismatch.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source iterators used for the end of the second range (deduced).
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *mismatch* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `bool` otherwise. The *mismatch* algorithm returns true if the elements in the two ranges are mismatch, otherwise it returns false. If the length of the range [first1, last1) does not mismatch the length of the range [first2, last2), it returns false.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = equal_to, typename Proj1 =  
hpx::identity, typename Proj2 = hpx::identity>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, mismatch_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typen
```

Returns `std::pair` with iterators to the first two non-equivalent elements.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last1 - first1* applications of the predicate *f*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *mismatch* algorithm returns a `hpx::future<std::pair<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::pair<FwdIter1, FwdIter2>` otherwise. The *mismatch* algorithm returns the first mismatching pair of elements from two ranges: one defined by [first1, last1) and another defined by [first2, last2).

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Pred = equal_to,
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
mismatch_result<Iter1, Iter2> hpx::ranges::mismatch(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2, Pred
&&op = Pred(), Proj1 &&proj1 = Proj1(), Proj2
&&proj2 = Proj2())
```

Returns true if the range [first1, last1) is mismatch to the range [first2, last2), and false otherwise.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate *f*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of the predicate *f* are made.

Note: The two ranges are considered mismatch if, for every iterator i in the range $[first1, last1)$, $*i$ mismatches $*(first2 + (i - first1))$. This overload of `mismatch` uses `operator==` to determine if two elements are mismatch.

Template Parameters

- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the source iterators used for the end of the second range (deduced).
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of `mismatch` requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The `mismatch` algorithm returns *bool*. The `mismatch` algorithm returns true if the elements in the two ranges are mismatch, otherwise it returns false. If the length of the range $[first1, last1)$ does not mismatch the length of the range $[first2, last2)$, it returns false.

```
template<typename Rng1, typename Rng2, typename Pred = equal_to, typename Proj1 = hpx::identity, typename
Proj2 = hpx::identity>
mismatch_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typename hpx::traits::range_traits<Rng2>::iterator_type> hp
```

Returns `std::pair` with iterators to the first two non-equivalent elements.

Note: Complexity: At most *last1 - first1* applications of the predicate *f*.

Template Parameters

- **Rng1** – The type of the first source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Rng2** – The type of the second source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj1** – The type of an optional projection function applied to the first range. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second range. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first range as a projection operation before the actual predicate *is* invoked.

- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second range as a projection operation before the actual predicate *is* invoked.

Returns

The *mismatch* algorithm returns `std::pair<FwdIter1, FwdIter2>`. The *mismatch* algorithm returns the first mismatching pair of elements from two ranges: one defined by [first1, last1) and another defined by [first2, last2).

hpx::ranges::make_heap

Defined in header `hpx/algorithm.hpp`⁶⁷⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Comp, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> hpx::ranges::make_heap(ExPolicy &&policy, Iter
                                                                    first, Sent last, Comp
                                                                    &&comp, Proj &&proj
                                                                    = Proj{ })
```

Constructs a *max heap* in the range [first, last).

The predicate operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *sequential_execution_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *parallel_execution_policy* or *parallel_task_execution_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (3*N) comparisons where *N* = distance(first, last).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

⁶⁷⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Rng, typename Comp, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::make_heap(ExPolicy
&&pol-
icy,
Rng
&&rng,
Comp
&&comp,
Proj
&&proj
=
Proj{ })
```

Constructs a *max heap* in the range [first, last).

The predicate operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *sequential_execution_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *parallel_execution_policy* or *parallel_task_execution_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (3*N) comparisons where *N* = distance(first, last).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> hpx::ranges::make_heap(ExPolicy &&policy, Iter
                                                                    first, Sent last, Proj
                                                                    &&proj = Proj{ })
```

Constructs a *max heap* in the range [first, last).

The predicate operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *sequential_execution_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *parallel_execution_policy* or *parallel_task_execution_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (3*N) comparisons where *N* = distance(first, last).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter1*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Rng, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::make_heap(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     Rng
                                                                                                     &&rng,
                                                                                                     Proj
                                                                                                     &&proj
                                                                                                     =
                                                                                                     Proj{ })
```

Constructs a *max heap* in the range [first, last).

The predicate operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *sequential_execution_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *parallel_execution_policy* or *parallel_task_execution_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (3*N) comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise. It returns *last*.

```
template<typename Iter, typename Sent, typename Comp, typename Proj = hpx::identity>
Iter hpx::ranges::make_heap(Iter first, Sent last, Comp &&comp, Proj &&proj = Proj{ })
```

Constructs a *max heap* in the range [first, last).

Note: Complexity: at most (3*N) comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns *Iter*. It returns *last*.

```
template<typename Rng, typename Comp, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> hpx::ranges::make_heap(Rng &&rng, Comp &&comp, Proj &&proj = Proj{ })
    Constructs a max heap in the range [first, last).
```

Note: Complexity: at most $(3*N)$ comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns *Iter*. It returns *last*.

```
template<typename Iter, typename Sent, typename Proj = hpx::identity>
Iter hpx::ranges::make_heap(Iter first, Sent last, Proj &&proj = Proj{ })
```

Constructs a *max heap* in the range [first, last).

Note: Complexity: at most (3*N) comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **Iter** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter*1.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns *Iter*. It returns *last*.

```
template<typename Rng, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> hpx::ranges::make_heap(Rng &&rng, Proj &&proj = Proj{ })
```

Constructs a *max heap* in the range [first, last).

Note: Complexity: at most (3*N) comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *make_heap* algorithm returns *Iter*. It returns *last*.

hpx::ranges::nth_element

Defined in header `hpx/algorithm.hpp`⁶⁷⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename RandomIt, typename Sent, typename Pred = hpx::parallel::detail::less, typename Proj =  
hpx::identity>
```

```
RandomIt hpx::ranges::nth_element(RandomIt first, RandomIt nth, Sent last, Pred &&pred = Pred(), Proj  
                                &&proj = Proj())
```

`nth_element` is a partial sorting algorithm that rearranges elements in `[first, last)` such that the element pointed at by `nth` is changed to whatever element would occur in that position if `[first, last)` were sorted and all of the elements before this new `nth` element are less than or equal to the elements after the new `nth` element.

The comparison operations in the parallel `nth_element` algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

Template Parameters

- **RandomIt** – The type of the source begin, `nth`, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `RandomIt`.
- **Pred** – Comparison function object which returns true if the first argument is less than the second.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type `randomIt` can be dereferenced and then implicitly converted to `Type`. This defaults to `std::less<>`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked. This defaults to `hpx::identity`.

⁶⁷⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *nth_element* algorithm returns *RandomIt*. The *nth_element* algorithm returns an iterator equal to last.

```
template<typename ExPolicy, typename RandomIt, typename Sent, typename Pred = hpx::parallel::detail::less,
        typename Proj = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, RandomIt> hpx::ranges::nth_element(ExPolicy &&policy,
                                                                                      RandomIt first,
                                                                                      RandomIt nth, Sent
                                                                                      last, Pred &&pred =
                                                                                      Pred(), Proj &&proj
                                                                                      = Proj())
```

nth_element is a partial sorting algorithm that rearranges elements in *[first, last)* such that the element pointed at by *nth* is changed to whatever element would occur in that position if *[first, last)* were sorted and all of the elements before this new *nth* element are less than or equal to the elements after the new *nth* element.

The comparison operations in the parallel *nth_element* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *nth_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandomIt** – The type of the source begin, *nth*, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *RandomIt*.
- **Pred** – Comparison function object which returns true if the first argument is less than the second.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.

- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type *randomIt* can be dereferenced and then implicitly converted to `Type`. This defaults to `std::less<>`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked. This defaults to `hpx::identity`.

Returns

The *partition* algorithm returns a `hpx::future<RandomIt>` if the execution policy is of type *parallel_task_policy* and returns *RandomIt* otherwise. The *nth_element* algorithm returns an iterator equal to last.

```
template<typename Rng, typename Pred = hpx::parallel::detail::less, typename Proj = hpx::identity>
std::ranges::iterator_t<Rng> hpx::ranges::nth_element(Rng &&rng, std::ranges::iterator_t<Rng> nth, Pred
&&pred = Pred(), Proj &&proj = Proj())
```

nth_element is a partial sorting algorithm that rearranges elements in `[first, last)` such that the element pointed at by *nth* is changed to whatever element would occur in that position if `[first, last)` were sorted and all of the elements before this new *nth* element are less than or equal to the elements after the new *nth* element.

The comparison operations in the parallel *nth_element* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Pred** – Comparison function object which returns true if the first argument is less than the second.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```


The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type *randomIt* can be dereferenced and then implicitly converted to *Type*. This defaults to `std::less<>`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked. This defaults to `hpx::identity`.

Returns

The *nth_element* algorithm returns `std::ranges::iterator_t<Rng>`. The *nth_element* algorithm returns an iterator equal to last.

```
template<typename ExPolicy, typename Rng, typename Pred = hpx::parallel::detail::less, typename Proj =
hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::nth_element(ExPolicy
&&pol-
icy,
Rng
&&rng,
std::ranges::iterator_t<
nth,
Pred
&&pred
=
Pred(),
Proj
&&proj
=
Proj())
```

nth_element is a partial sorting algorithm that rearranges elements in `[first, last)` such that the element pointed at by *nth* is changed to whatever element would occur in that position if `[first, last)` were sorted and all of the elements before this new *nth* element are less than or equal to the elements after the new *nth* element.

The comparison operations in the parallel *nth_element* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *nth_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a random access iterator.
- **Pred** – Comparison function object which returns true if the first argument is less than the second.

- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type must be such that an object of type *randomIt* can be dereferenced and then implicitly converted to Type. This defaults to `std::less<>`.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked. This defaults to *hpx::identity*.

Returns

The *partition* algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>>` if the execution policy is of type *parallel_task_policy* and returns `std::ranges::iterator_t<Rng>` otherwise. The *nth_element* algorithm returns an iterator equal to last.

hpx::ranges::replace

Defined in header `hpx/algorithm.hpp`⁶⁷⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::replace_if*
- *hpx::ranges::replace_copy*
- *hpx::ranges::replace_copy_if*

```
template<typename Iter, typename Sent, typename Proj = hpx::identity, typename T1 = typename
hpx::parallel::traits::projected<Iter, Proj>::value_type, typename T2 = T1>
Iter hpx::ranges::replace(Iter first, Sent sent, T1 const &old_value, T2 const &new_value, Proj &&proj =
    Proj())
```

Replaces all elements satisfying specific criteria with *new_value* in the range [first, last).

Effects: Substitutes elements referred by the iterator *it* in the range [first,last) with *new_value*, when the following corresponding conditions hold: `INVOKE(proj, *i) == old_value`

The assignments in the parallel *replace* algorithm execute in sequential order in the calling thread.

⁶⁷⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for Iter.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace* algorithm returns an *Iter*.

```
template<typename Rng, typename Proj = hpx::identity, typename T1 = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type, typename T2 = T1>
std::ranges::iterator_t<Rng> hpx::ranges::replace(Rng &&rng, T1 const &old_value, T2 const &new_value,
Proj &&proj = Proj())
```

Replaces all elements satisfying specific criteria with *new_value* in the range *rng*.

Effects: Substitutes elements referred by the iterator it in the range *rng* with *new_value*, when the following corresponding conditions hold: `INVOKE(proj, *i) == old_value`

The assignments in the parallel *replace* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *util::end(rng) - util::begin(rng)* assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace* algorithm returns an `hpx::traits::range_iterator<Rng>::type`.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Proj = hpx::identity, typename T1 =  
typename hpx::parallel::traits::projected<Iter, Proj>::value_type, typename T2 = T1>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> hpx::ranges::replace(ExPolicy &&policy, Iter  
first, Sent sent, T1 const  
    &old_value, T2 const  
    &new_value, Proj &&proj  
    = Proj())
```

Replaces all elements satisfying specific criteria with *new_value* in the range [first, last).

Effects: Substitutes elements referred by the iterator *it* in the range [first,last) with *new_value*, when the following corresponding conditions hold: `INVOKE(proj, *i) == old_value`

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace* algorithm returns a `hpx::future<Iter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *Iter* otherwise.

```
template<typename ExPolicy, typename Rng, typename Proj = hpx::identity, typename T1 = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type, typename T2 = T1>
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::replace(ExPolicy
&&pol-
icy, Rng
&&rng,
T1 const
&old_value,
T2 const
&new_value,
Proj
&&proj =
Proj())
```

Replaces all elements satisfying specific criteria with *new_value* in the range *rng*.

Effects: Substitutes elements referred by the iterator *it* in the range *rng* with *new_value*, when the following corresponding conditions hold: `INVOKE(proj, *i) == old_value`

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `util::end(rng) - util::begin(rng)` assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked. The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Returns

The *replace* algorithm returns an `hpx::future<hpx::traits::range_iterator<Rng>::type>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `hpx::traits::range_iterator<Rng>::type` otherwise.

hpx::ranges::replace_if

Defined in header `hpx/algorithm.hpp`⁶⁸⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::replace`
- `hpx::ranges::replace_copy`
- `hpx::ranges::replace_copy_if`

template<typename **Iter**, typename **Sent**, typename **Pred**, typename **Proj** = `hpx::identity`, typename **T** = typename `hpx::parallel::traits::projected<Iter, Proj>::value_type`>

Iter `hpx::ranges::replace_if`(*Iter* first, *Sent* sent, *Pred* &&pred, *T* const &new_value, *Proj* &&proj = *Proj*())

Replaces all elements satisfying specific criteria (for which predicate *f* returns true) with *new_value* in the range [first, sent).

Effects: Substitutes elements referred by the iterator *it* in the range [first, sent) with *new_value*, when the following corresponding conditions hold: `INVOKE(f, INVOKE(proj, *it)) != false`

The assignments in the parallel *replace_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *sent - first* applications of the predicate.

Template Parameters

- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.

⁶⁸⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_if* algorithm returns *Iter*. It returns *last*.

```
template<typename Rng, typename Pred, typename Proj = hpx::identity, typename T = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
std::ranges::iterator_t<Rng> hpx::ranges::replace_if(Rng &&rng, Pred &&pred, T const &new_value, Proj
&&proj = Proj())
```

Replaces all elements satisfying specific criteria (for which predicate *pred* returns true) with *new_value* in the range *rng*.

Effects: Substitutes elements referred by the iterator *it* in the range *rng* with *new_value*, when the following corresponding conditions hold: `INVOKE(f, INVOKE(proj, *it)) != false`

Note: Complexity: Performs exactly *util::end(rng) - util::begin(rng)* applications of the predicate.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by *rng*. This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_if* algorithm returns an `hpx::traits::range_iterator<Rng>::type`. It returns *last*.

```
template<typename ExPolicy, typename Iter, typename Sent, typename Pred, typename Proj = hpx::identity,
typename T = typename hpx::parallel::traits::projected<Iter, Proj>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> hpx::ranges::replace_if(ExPolicy &&policy,
                                             Iter first, Sent sent,
                                             Pred &&pred, T const
                                             &new_value, Proj
                                             &&proj = Proj())
```

Replaces all elements satisfying specific criteria (for which predicate *pred* returns true) with *new_value* in the range *rng*.

Effects: Substitutes elements referred by the iterator *it* in the range *rng* with *new_value*, when the following corresponding conditions hold: `INVOKE(f, INVOKE(proj, *it)) != false`

The assignments in the parallel *replace_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `util::end(rng) - util::begin(rng)` applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of a forward iterator.

- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for `Iter`.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_if* algorithm returns a *hpx::future<Iter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy*. It returns *last*.

```
template<typename ExPolicy, typename Rng, typename Pred, typename Proj = hpx::identity, typename T =
typename hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::replace_if(ExPolicy
&&pol-
icy,
Rng
&&rng,
Pred
&&pred,
T
const
&new_value,
Proj
&&proj
=
Proj())
```

Replaces all elements satisfying specific criteria (for which predicate *pred* returns true) with *new_value* in the range *rng*.

Effects: Substitutes elements referred by the iterator *it* in the range *rng* with *new_value*, when the following corresponding conditions hold: `INVOKE(f, INVOKE(proj, *it)) != false`

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `util::end(rng) - util::begin(rng)` applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by *rng*. This is a unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_if* algorithm returns a `hpx::future<std::ranges::iterator_t<Rng>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy*. It returns *last*.

hpx::ranges::replace_copy

Defined in header [hpx/algorithm.hpp](#)⁶⁸¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::replace`
- `hpx::ranges::replace_if`
- `hpx::ranges::replace_copy_if`

```
template<typename InIter, typename Sent, typename OutIter, typename Proj = hpx::identity, typename T1 =
typename hpx::parallel::traits::projected<InIter, Proj>::value_type, typename T2 = T1>
replace_copy_result<InIter, OutIter> hpx::ranges::replace_copy(InIter first, Sent sent, OutIter dest, T1 const
&old_value, T2 const &new_value, Proj
&&proj = Proj())
```

Copies the all elements from the range [first, sent) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (sent - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: `INVOKE(proj, *(first + (i - result))) == old_value`

The assignments in the parallel *replace_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *sent - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for *Iter*.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.

⁶⁸¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy* algorithm returns an *in_out_result*<*InIter*, *OutIter*>. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename OutIter, typename Proj = hpx::identity, typename T1 = typename
hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type, typename T2 = T1>
replace_copy_result<std::ranges::iterator_t<Rng>, OutIter> hpx::ranges::replace_copy(Rng &&rng, OutIter
                                                                    dest, T1 const
                                                                    &old_value, T2 const
                                                                    &new_value, Proj
                                                                    &&proj = Proj())
```

Copies the all elements from the range *rbg* to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (util::end(rng) - util::begin(rng))) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: *INVOKE(proj, *(first + (i - result))) == old_value*

The assignments in the parallel *replace_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *util::end(rng) - util::begin(rng)* applications of the predicate.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy* algorithm returns an *in_out_result*<*std::ranges::iterator_t*<*Rng*>, *OutIter*>. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename Proj =
hpx::identity, typename T1 = typename hpx::parallel::traits::projected<FwdIter1, Proj>::value_type, typename T2 =
T1>
parallel::util::detail::algorithm_result<ExPolicy, replace_copy_result<FwdIter1, FwdIter2>>::type hpx::ranges::replace_copy(E
```

Copies the all elements from the range [first, sent) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (sent - first)) either *new_value* or $*(first + (it - result))$ depending on whether the following corresponding condition holds: `INVOKE(proj, *(first + (i - result))) == old_value`

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *sent - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for Iter.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T1** – The type of the old value to replace (deduced).

- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy* algorithm returns a `hpx::future<in_out_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `in_out_result<FwdIter1, FwdIter2>` otherwise. The *copy* algorithm returns the pair of the forward iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename FwdIter, typename Proj = hpx::identity, typename T1 =  
typename hpx::parallel::traits::projected<std::ranges::iterator_t<Rng>, Proj>::value_type, typename T2 = T1>  
parallel::util::detail::algorithm_result<ExPolicy, replace_copy_result<std::ranges::iterator_t<Rng>, FwdIter>>::type hpx::ranges::r
```

Copies the all elements from the range *rbg* to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator *it* in the range `[result, result + (util::end(rng) - util::begin(rng))]` either *new_value* or `*(first + (it - result))` depending on whether the following corresponding condition holds: `INVOKE(proj, *(first + (i - result))) == old_value`

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *util::end(rng) - util::begin(rng)* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T1** – The type of the old value to replace (deduced).
- **T2** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy* algorithm returns a *hpx::future<in_out_result< std::ranges::iterator_t<Rng>, FwdIter>>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *in_out_result< std::ranges::iterator_t<Rng>, FwdIter>>* The *copy* algorithm returns the pair of the input iterator *last* and the forward iterator to the element in the destination range, one past the last element copied.

hpx::ranges::replace_copy_if

Defined in header [hpx/algorithm.hpp](#)⁶⁸².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::replace*
- *hpx::ranges::replace_if*
- *hpx::ranges::replace_copy*

⁶⁸² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
template<typename InIter, typename Sent, typename OutIter, typename Pred, typename T = typename
std::iterator_traits<OutIter>::value_type, typename Proj = hpx::identity>
replace_copy_if_result<InIter, OutIter> hpx::ranges::replace_copy_if(InIter first, Sent sent, OutIter dest,
                                                                    Pred &&pred, T const &new_value,
                                                                    Proj &&proj = Proj())
```

Copies the all elements from the range [first, sent) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (sent - first)) either *new_value* or $*(first + (it - result))$ depending on whether the following corresponding condition holds: $INVOKE(f, INVOKE(proj, *(first + (i - result)))) \neq false$

The assignments in the parallel *replace_copy_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *sent - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterator used (deduced). The iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for **InIter**.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have *const&*, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy_if* algorithm returns a *in_out_result<InIter, OutIter>*. The *replace_copy_if* algorithm returns the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename OutIter, typename Pred, typename T = typename
std::iterator_traits<OutIter>::value_type, typename Proj = hpx::identity>
replace_copy_if_result<std::ranges::iterator_t<Rng>, OutIter> hpx::ranges::replace_copy_if(Rng &&rng,
                                                                                          OutIter dest,
                                                                                          Pred &&pred,
                                                                                          T const
                                                                                          &new_value,
                                                                                          Proj &&proj =
                                                                                          Proj())
```

Copies the all elements from the range *rng* to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range $[result, result + (util::end(rng) - util::begin(rng)))$ either *new_value* or $*(first + (it - result))$ depending on whether the following corresponding condition holds: $INVOKE(f, INVOKE(proj, *(first + (i - result)))) \neq false$

The assignments in the parallel *replace_copy_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly $util::end(rng) - util::begin(rng)$ applications of the predicate.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by $[first, last)$. This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy_if* algorithm returns an *in_out_result*<*std::ranges::iterator_t*<*Rng*>, *OutIter*>. The *replace_copy_if* algorithm returns the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename Pred,
typename T = typename std::iterator_traits<FwdIter2>::value_type, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, replace_copy_if_result<FwdIter1, FwdIter2>>::type hpx::ranges::replace_copy
```

Copies the all elements from the range [first, sent) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator *it* in the range [result, result + (sent - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: `INVOKE(f, INVOKE(proj, *(first + (i - result)))) != false`

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *sent - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes

the assignments.

- **FwdIter1** – The type of the source iterator used (deduced). The iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the end iterators used (deduced). This sentinel type must be a sentinel for InIter.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **sent** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy_if* algorithm returns an *hpx::future<FwdIter1, FwdIter2>*. The *replace_copy_if* algorithm returns the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename FwdIter, typename Pred, typename T = typename
std::iterator_traits<FwdIter>::value_type, typename Proj = hpx::identity>
```

parallel::util::detail::algorithm_result<ExPolicy, replace_copy_if_result<std::ranges::iterator_t<Rng>, FwdIter>>>::type hpx::ranges::

Copies the all elements from the range *rng* to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator *it* in the range $[result, result + (util::end(rng) - util::begin(rng))]$ either *new_value* or $*(first + (it - result))$ depending on whether the following corresponding condition holds: `INVOKE(f, INVOKE(proj, *(first + (i - result)))) != false`

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly $util::end(rng) - util::begin(rng)$ applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.
- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *replace_copy_if* algorithm returns an `hpx::future<in_out_result<std::ranges::iterator_t<Rng>, OutIter>>`. The *replace_copy_if* algorithm returns the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

hpx::ranges::includes

Defined in header `hpx/algorithm.hpp`⁶⁸³.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Pred = hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::includes(ExPolicy &&policy, Iter1
first1, Sent1 last1, Iter2
first2, Sent2 last2, Pred
&&op = Pred(), Proj1
&&proj1 = Proj1(),
Proj2 &&proj2 =
Proj2())
```

Returns true if every element from the sorted range [first2, last2) is found within the sorted range [first1, last1). Also returns true if [first2, last2) is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: At most $2*(N1+N2-1)$ comparisons, where $N1 = \text{std::distance}(\text{first1}, \text{last1})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

⁶⁸³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *includes* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *includes* algorithm returns true every element from the sorted range `[first2, last2)` is found within the sorted range `[first1, last1)`. Also returns true if `[first2, last2)` is empty.

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Pred =
hpx::parallel::detail::less, typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
bool hpx::ranges::includes(Iter1 first1, Sent1 last1, Iter2 first2, Sent2 last2, Pred &&op = Pred(), Proj1
&&proj1 = Proj1(), Proj2 &&proj2 = Proj2())
```

Returns true if every element from the sorted range `[first2, last2)` is found within the sorted range `[first1, last1)`. Also returns true if `[first2, last2)` is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*.

Note: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1 = \text{std::distance}(\text{first1}, \text{last1})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Template Parameters

- **Iter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter1.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an forward iterator.
- **Sent2** – The type of the end source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an sentinel for Iter2.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *includes* algorithm returns true every element from the sorted range [first2, last2) is found within the sorted range [first1, last1). Also returns true if [first2, last2) is empty.

```
template<typename ExPolicy, typename Rng1, typename Rng2, typename Pred = hpx::parallel::detail::less,
typename Proj1 = hpx::identity, typename Proj2 = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::includes(ExPolicy &&policy,
                                                                                      Rng1 &&rng1, Rng2
                                                                                      &&rng2, Pred &&op =
                                                                                      Pred(), Proj1 &&proj1 =
                                                                                      Proj1(), Proj2 &&proj2
                                                                                      = Proj2())
```

Returns true if every element from the sorted range [first2, last2) is found within the sorted range [first1, last1). Also returns true if [first2, last2) is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1 = \text{std::distance}(\text{first1}, \text{last1})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *CopyConstructible*.

This defaults to `std::less<>`

- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *includes* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `bool` otherwise. The *includes* algorithm returns true every element from the sorted range `[first2, last2)` is found within the sorted range `[first1, last1)`. Also returns true if `[first2, last2)` is empty.

```
template<typename Rng1, typename Rng2, typename Pred = hpx::parallel::detail::less, typename Proj1 =
hpx::identity, typename Proj2 = hpx::identity>
bool hpx::ranges::includes(Rng1 &&rng1, Rng2 &&rng2, Pred &&op = Pred(), Proj1 &&proj1 = Proj1(),
                          Proj2 &&proj2 = Proj2())
```

Returns true if every element from the sorted range `[first2, last2)` is found within the sorted range `[first1, last1)`. Also returns true if `[first2, last2)` is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*.

Note: At most $2*(N1+N2-1)$ comparisons, where $N1 = \text{std::distance}(\text{first1}, \text{last1})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`
- **Proj1** – The type of an optional projection function applied to the first sequence. This defaults to `hpx::identity`
- **Proj2** – The type of an optional projection function applied to the second sequence. This defaults to `hpx::identity`

Parameters

- **rng1** – Refers to the first sequence of elements the algorithm will be applied to.
- **rng2** – Refers to the second sequence of elements the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

- **proj1** – Specifies the function (or function object) which will be invoked for each of the elements of the first sequence as a projection operation before the actual predicate *op* is invoked.
- **proj2** – Specifies the function (or function object) which will be invoked for each of the elements of the second sequence as a projection operation before the actual predicate *op* is invoked.

Returns

The *includes* algorithm returns true every element from the sorted range [first2, last2) is found within the sorted range [first1, last1). Also returns true if [first2, last2) is empty.

hpx::ranges::move

Defined in header `hpx/algorithm.hpp`⁶⁸⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

template<typename **ExPolicy**, typename **Iter1**, typename **Sent1**, typename **Iter2**>

`hpx::parallel::util::detail::algorithm_result<ExPolicy, move_result<Iter1, Iter2>>::type` **hpx::ranges::move**(*ExPolicy* &&policy, *Iter1* first, *Sent1* last, *Iter2* dest)

Moves the elements in the range *rng* to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move.

⁶⁸⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns a `hpx::future<ranges::move_result<iterator_t<Rng>, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::move_result<iterator_t<Rng>, FwdIter2>` otherwise. The *move* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename ExPolicy, typename Rng, typename Iter2>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, move_result<std::ranges::iterator_t<Rng>, Iter2>>>::type hpx::ranges::move(
```

Moves the elements in the range *rng* to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns a `hpx::future<ranges::move_result<iterator_t<Rng>, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `ranges::move_result<iterator_t<Rng>, FwdIter2>` otherwise. The *move* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename Iter1, typename Sent1, typename Iter2>
move_result<Iter1, Iter2> hpx::ranges::move(Iter1 first, Sent1 last, Iter2 dest)
```

Moves the elements in the range *rng* to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **Iter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent1** – The type of the source iterators used for the end of the first range (deduced).
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns `ranges::move_result<iterator_t<Rng>, FwdIter2>`. The *move* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename Rng, typename Iter2>
```

```
move_result<std::ranges::iterator_t<Rng>, Iter2> hpx::ranges::move(Rng &&rng, Iter2 dest)
```

Moves the elements in the range *rng* to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move.

Note: Complexity: Performs exactly `std::distance(begin(rng), end(rng))` assignments.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns a `ranges::move_result<iterator_t<Rng>, FwdIter2>`. The *move* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element moved.

hpx::ranges::uninitialized_move

Defined in header `hpx/algorithm.hpp`⁶⁸⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::uninitialized_move_n`

```
template<typename InIter, typename Sent1, typename FwdIter, typename Sent2>
```

```
hpx::parallel::util::in_out_result<InIter, FwdIter> hpx::ranges::uninitialized_move(InIter first1, Sent1 last1,
                                                                                   FwdIter first2, Sent2
                                                                                   last2)
```

Moves the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in [first, last) are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

⁶⁸⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter2.

Parameters

- **first1** – Refers to the beginning of the sequence of elements that will be moved from
- **last1** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_move* algorithm returns an *in_out_result<InIter, FwdIter>*. The *uninitialized_move* algorithm returns an input iterator to one past the last element moved from and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename ExPolicy, typename FwdIter1, typename Sent1, typename FwdIter2, typename Sent2>  
parallel::util::detail::algorithm_result<ExPolicy, parallel::util::in_out_result<FwdIter1, FwdIter2>>::type hpx::ranges::uninitial
```

Moves the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in [first, last) are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent1** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter2`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements that will be moved from
- **last1** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_move* algorithm returns a `hpx::future<in_out_result<InIter, FwdIter>>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *in_out_result<InIter, FwdIter>* otherwise. The *uninitialized_move* algorithm returns an input iterator to one past the last element moved from and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename Rng1, typename Rng2>
hpx::parallel::util::in_out_result<typename hpx::traits::range_traits<Rng1>::iterator_type, typename hpx::traits::range_traits<Rng2>::it
```

Moves the elements in the range, defined by `[first, last)`, to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in `[first, last)` are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

Parameters

- **rng1** – Refers to the range from which the elements will be moved from
- **rng2** – Refers to the range to which the elements will be moved to

Returns

The *uninitialized_move* algorithm returns an *in_out_result*<typename `hpx::traits::range_traits<Rng1>::iterator_type`, typename `hpx::traits::range_traits<Rng2>::iterator_type`>. The *uninitialized_move* algorithm returns an input iterator to one past the last element moved from and the output iterator to the element in the destination range, one past the last element moved.

```
template<typename ExPolicy, typename Rng1, typename Rng2>  
parallel::util::detail::algorithm_result<ExPolicy, hpx::parallel::util::in_out_result<typename hpx::traits::range_traits<Rng1>::iterator_t
```

Moves the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in [first, last) are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng1** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Rng2** – The type of the destination range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng1** – Refers to the range from which the elements will be moved from
- **rng2** – Refers to the range to which the elements will be moved to

Returns

The *uninitialized_move* algorithm returns a `hpx::future<in_out_result<InIter, FwdIter>>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `in_out_result< typename hpx::traits::range_traits<Rng1>::iterator_type , typename hpx::traits::range_traits<Rng2>::iterator_type>` otherwise. The *uninitialized_move* algorithm returns the input iterator to one past the last element moved from and the output iterator to the element in the destination range, one past the last element moved.

hpx::ranges::uninitialized_move_n

Defined in header `hpx/algorithm.hpp`⁶⁸⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::uninitialized_move`

```
template<typename InIter, typename Size, typename FwdIter, typename Sent2>
hpx::parallel::util::in_out_result<InIter, FwdIter> hpx::ranges::uninitialized_move_n(InIter first1, Size
count, FwdIter first2,
Sent2 last2)
```

Moves the elements in the range `[first, first + count)`, starting from `first` and proceeding to `first + count - 1`, to another range beginning at `dest`. If an exception is thrown during the initialization, some objects in `[first, first + count)` are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *count* movements, if *count* > 0, no move operations otherwise.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `FwdIter`.

Parameters

- **first1** – Refers to the beginning of the sequence of elements that will be moved from
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

⁶⁸⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *uninitialized_move_n* algorithm returns *in_out_result<InIter, FwdIter>*. The *uninitialized_move_n* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

```
template<typename ExPolicy, typename FwdIter1, typename Size, typename FwdIter2, typename Sent2>
parallel::util::detail::algorithm_result<ExPolicy, parallel::util::in_out_result<FwdIter1, FwdIter2>>::type hpx::ranges::uninitial
```

Moves the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest. If an exception is thrown during the initialization, some objects in [first, first + count) are left in a valid but unspecified state.

The assignments in the parallel *uninitialized_move_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_move_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* movements, if count > 0, no move operations otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent2** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter2.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements that will be moved from
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **first2** – Refers to the beginning of the destination range.

- **last2** – Refers to sentinel value denoting the end of the second range the algorithm will be applied to.

Returns

The *uninitialized_move_n* algorithm returns a `hpx::future<in_out_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *uninitialized_move_n* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

hpx::ranges::reduce

Defined in header `hpx/algorithm.hpp`⁶⁸⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename F, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::ranges::reduce(ExPolicy &&policy, FwdIter
first, Sent last, T init, F &&f)
```

Returns GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1)).

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.

⁶⁸⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`. The types *Type1* *Ret* must be such that an object of type *FwdIterB* can be dereferenced and then implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename Rng, typename F, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::ranges::reduce(ExPolicy &&policy, Rng
&&rng, T init, F &&f)
```

Returns GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1)).

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
- op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:

- $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
- $1 < K+1 = M \leq N$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`. The types *Type1* *Ret* must be such that an object of type *FwdIterB* can be dereferenced and then implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::ranges::reduce(ExPolicy &&policy, FwdIter
first, Sent last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)).

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename Rng, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::ranges::reduce(ExPolicy &&policy, Rng
&&rng, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)).

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter, typename Sent>
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<FwdIter>::value_type>::type hpx::ranges::redu
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)).

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) *T* is determined from the *value_type* of the used *FwdIterB*.

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns T otherwise (where T is the *value_type* of *FwdIterB*). The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename Rng>
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<typename hpx::traits::range_traits<Rng>::iterator_ty
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)).

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) *T* is determined from the *value_type* of the used *FwdIterB*.

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise (where *T* is the *value_type* of *FwdIterB*). The *reduce* algorithm returns the result of the generalized sum (applying operator+) over the elements given by the input range [first, last).

```
template<typename FwdIter, typename Sent, typename F, typename T = typename
std::iterator_traits<FwdIter>::value_type>
```

```
T hpx::ranges::reduce(FwdIter first, Sent last, T init, F &&f)
```

Returns GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1)).

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate f .

Note: `GENERALIZED_SUM(op, a1, ..., aN)` is defined as follows:

- $a1$ when N is 1
 - `op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN))`, where:
 - $b1, \dots, bN$ may be any permutation of $a1, \dots, aN$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires F to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`. The types *Type1* *Ret* must be such that an object of type *FwdIterB* can be dereferenced and then implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns T . The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range `[first, last)`.

```
template<typename Rng, typename F, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
T hpx::ranges::reduce(Rng &&rng, T init, F &&f)
```

Returns `GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1))`.

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate f .

Note: GENERALIZED_SUM(op , $a_1, \dots, a_N$) is defined as follows:

- a_1 when N is 1
 - $\text{op}(\text{GENERALIZED_SUM}(\text{op}, b_1, \dots, b_K), \text{GENERALIZED_SUM}(\text{op}, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires F to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by $[\text{first}, \text{last})$. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`. The types *Type1* *Ret* must be such that an object of type *FwdIterB* can be dereferenced and then implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns T . The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range $[\text{first}, \text{last})$.

```
template<typename FwdIter, typename Sent, typename T = typename std::iterator_traits<FwdIter>::value_type>
T hpx::ranges::reduce(FwdIter first, Sent last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)).

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator $+$ ($\cdot$).

Note: GENERALIZED_SUM(+, $a_1, \dots, a_N$) is defined as follows:

- a_1 when N is 1

- $\text{op}(\text{GENERALIZED_SUM}(+, b_1, \dots, b_K), \text{GENERALIZED_SUM}(+, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns *T*. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename Rng, typename T = typename std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>  
T hpx::ranges::reduce(Rng &&rng, T init)
```

Returns $\text{GENERALIZED_SUM}(+, \text{init}, *first, \dots, *(first + (last - first) - 1))$.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: $\text{GENERALIZED_SUM}(+, a_1, \dots, a_N)$ is defined as follows:

- a_1 when N is 1
 - $\text{op}(\text{GENERALIZED_SUM}(+, b_1, \dots, b_K), \text{GENERALIZED_SUM}(+, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.

- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns *T*. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename FwdIter, typename Sent>
std::iterator_traits<FwdIter>::value_type hpx::ranges::reduce(FwdIter first, Sent last)
    Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)).
```

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) *T* is determined from the value_type of the used *FwdIterB*.

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel used (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns *T* (where T is the value_type of *FwdIterB*). The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename Rng>
std::iterator_traits<typename hpx::traits::range_traits<Rng>::iterator_type>::value_type hpx::ranges::reduce(Rng
                                                         &&rng)
    Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)).
```

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) T is determined from the `value_type` of the used *FwdIterB*.

Note: GENERALIZED_SUM(+, $a_1, \dots, a_N$) is defined as follows:

- a_1 when N is 1
 - $\text{op}(\text{GENERALIZED_SUM}(+, b_1, \dots, b_K), \text{GENERALIZED_SUM}(+, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

rng – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns T (where T is the `value_type` of *FwdIterB*). The *reduce* algorithm returns the result of the generalized sum (applying `operator+()`) over the elements given by the input range `[first, last)`.

hpx/parallel/container_algorithms/iota.hpp

Defined in header `hpx/parallel/container_algorithms/iota.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **ranges**

Functions

```
template<typename FwdIter, typename Sent, typename T>
iota_result<FwdIter, T> iota(FwdIter first, Sent last, T value)
```

Fills the range `[first, last)` with sequentially increasing values, starting with *value* and repetitively evaluating `++value`.

The assignments in the *iota* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Exactly *std::distance(first, last)* assignments and increments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input or output iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **T** – The type of the target value. This type must meet the requirements of weakly incrementable.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns a *hpx::ranges::iota_result* containing the final iterator and the final value.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, iota_result<FwdIter, T>> iota(ExPolicy
                                                    &&policy,
                                                    FwdIter first,
                                                    Sent last, T
                                                    value)
```

Fills the range [first, last) with sequentially increasing values, starting with *value* and repetitively evaluating ++*value*.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *std::distance(first, last)* assignments and increments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for FwdIter.
- **T** – The type of the target value. This type must meet the requirements of weakly incrementable.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns a *hpx::future<iota_result>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *iota_result* otherwise.

```
template<typename Range, typename T>
iota_result<typename hpx::traits::range_traits<Range>::iterator_type, T> iota(Range &&r, T value)
    Fills the range r with sequentially increasing values, starting with value and repetitively evaluating ++value.
```

The assignments in the *iota* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Exactly *std::ranges::distance(r)* assignments and increments.

Template Parameters

- **Range** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input or output iterator
- **T** – The type of the target value. This type must meet the requirements of weakly incrementable.

Parameters

- **r** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns a *hpx::ranges::iota_result* containing the final iterator and the final value.

```
template<typename ExPolicy, typename Range, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, iota_result<typename hpx::traits::range_traits<Range>::iterator_type
```

Fills the range *r* with sequentially increasing values, starting with *value* and repetitively evaluating ++*value*.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *std::ranges::distance(r)* assignments and increments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **Range** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of a forward iterator.
- **T** – The type of the target value. This type must meet the requirements of weakly incrementable.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **r** – Refers to the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns a *hpx::future<iota_result>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *iota_result* otherwise.

hpx::ranges::destroy

Defined in header [hpx/algorithm.hpp](#)⁶⁸⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::ranges::destroy_n*

template<typename **ExPolicy**, typename **Rng**>

hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> **hpx::ranges::destroy**(*ExPolicy* &&policy, *Rng* &&rng)

Destroys objects of type *typename iterator_traits<ForwardIt>::value_type* in the range [first, last).

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

⁶⁸⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *destroy* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

```
template<typename ExPolicy, typename Iter, typename Sent>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, Iter> hpx::ranges::destroy(ExPolicy &&policy, Iter  
first, Sent last)
```

Destroys objects of type *typename iterator_traits<ForwardIt>::value_type* in the range [first, last).

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

```
template<typename Rng>  
hpx::traits::range_iterator<Rng>::type hpx::ranges::destroy(Rng &&rng)
```

Destroys objects of type *typename iterator_traits<ForwardIt>::value_type* in the range [first, last).

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

Rng – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

Parameters

rng – Refers to the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns *void*.

```
template<typename Iter, typename Sent>
```

```
Iter hpx::ranges::destroy(Iter first, Sent last)
```

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range `[first, last)`.

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns *void*.

hpx::ranges::destroy_n

Defined in header `hpx/algorithm.hpp`⁶⁸⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ranges::destroy*

```
template<typename ExPolicy, typename FwdIter, typename Size>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type hpx::ranges::destroy_n(ExPolicy  
                                                                                               &&policy,  
                                                                                               FwdIter first,  
                                                                                               Size count)
```

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range `[first, first + count)`.

The operations in the parallel *destroy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *destroy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* operations, if *count* > 0, no assignments otherwise.

⁶⁸⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply this algorithm to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *destroy_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *destroy_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename FwdIter, typename Size>  
FwdIter hpx::ranges::destroy_n(FwdIter first, Size count)
```

Destroys objects of type *typename iterator_traits<ForwardIt>::value_type* in the range *[first, first + count)*.

Note: Complexity: Performs exactly *count* operations, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply this algorithm to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *destroy_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::ranges::all_of

Defined in header `hpx/algorithm.hpp`⁶⁹⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::any_of`
- `hpx::ranges::none_of`

```
template<typename ExPolicy, typename Rng, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::all_of(ExPolicy &&policy, Rng
&&rng, F &&f, Proj
&&proj = Proj())
```

Checks if unary predicate *f* returns true for all elements in the range *rng*.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

⁶⁹⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *all_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename ExPolicy, typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::all_of(ExPolicy &&policy, Iter
                                                                    first, Sent last, F &&f, Proj
                                                                    &&proj = Proj())
```

Checks if unary predicate *f* returns true for all elements in the range *rng*.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *all_of* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename Rng, typename F, typename Proj = hpx::identity>
bool hpx::ranges::all_of(Rng &&rng, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for all elements in the range *rng*.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
bool hpx::ranges::all_of(Iter first, Sent last, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for all elements in the range *rng*.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

hpx::ranges::any_of

Defined in header `hpx/algorithm.hpp`⁶⁹¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ranges::all_of*
- *hpx::ranges::none_of*

```
template<typename ExPolicy, typename Rng, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::any_of(ExPolicy &&policy, Rng
&&rng, F &&f, Proj
&&proj = Proj())
```

Checks if unary predicate *f* returns true for at least one element in the range *rng*.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁶⁹¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *any_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

```
template<typename ExPolicy, typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::any_of(ExPolicy &&policy, Iter
                                                                    first, Sent last, F &&f, Proj
                                                                    &&proj = Proj())
```

Checks if unary predicate *f* returns true for at least one element in the range *rng*.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *any_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

```
template<typename Rng, typename F, typename Proj = hpx::identity>  
bool hpx::ranges::any_of(Rng &&rng, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for at least one element in the range *rng*.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.

- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

```
template<typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
bool hpx::ranges::any_of(Iter first, Sent last, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for at least one element in the range *rng*.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

hpx::ranges::none_of

Defined in header `hpx/algorithm.hpp`⁶⁹².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::all_of`
- `hpx::ranges::any_of`

```
template<typename ExPolicy, typename Rng, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::none_of(ExPolicy &&policy, Rng
&&rng, F &&f, Proj
&&proj = Proj())
```

Checks if unary predicate *f* returns true for no elements in the range *rng*.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

⁶⁹² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *none_of* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename ExPolicy, typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::ranges::none_of(ExPolicy &&policy, Iter
                                                                    first, Sent last, F &&f,
                                                                    Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for no elements in the range [first, last).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *InIter*.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *none_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename Rng, typename F, typename Proj = hpx::identity>  
bool hpx::ranges::none_of(Rng &&rng, F &&f, Proj &&proj = Proj())  
    Checks if unary predicate f returns true for no elements in the range rng.
```

Note: Complexity: At most `std::distance(begin(rng), end(rng))` applications of the predicate *f*

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename Iter, typename Sent, typename F, typename Proj = hpx::identity>
bool hpx::ranges::none_of(Iter first, Sent last, F &&f, Proj &&proj = Proj())
```

Checks if unary predicate *f* returns true for no elements in the range [first, last).

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **Iter** – The type of the source iterators used for the range (deduced).
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

hpx::ranges::inclusive_scan

Defined in header [hpx/algorithm.hpp](#)⁶⁹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter, typename Sent, typename OutIter, typename Op = std::plus<typename  
std::iterator_traits<InIter>::value_type>>  
inclusive_scan_result<InIter, OutIter> hpx::ranges::inclusive_scan(InIter first, Sent last, OutIter dest, Op  
                                                                    &&op)
```

Assigns through each iterator i in $[\text{result}, \text{result} + (\text{last} - \text{first}))$ the value of GENERALIZED_NONCOMMUTATIVE_SUM($\text{op}, *first, \dots, *(first + (i - \text{result}))$).

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the i th input element in the i th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate op .

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, $a_1, \dots, a_N$) is defined as:

- a_1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, $a_1, \dots, a_K$)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, $a_M, \dots, a_N$) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.

⁶⁹³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns `util::in_out_result<InIter, OutIter>`. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename Op =  
std::plus<typename std::iterator_traits<FwdIter1>::value_type>>  
parallel::util::detail::algorithm_result<ExPolicy, inclusive_scan_result<FwdIter1, FwdIter2>>::type hpx::ranges::inclusive_scan
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN)` is defined as:

- `a1` when *N* is 1
 - `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK)`
 - `GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN)` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<util::in_out_result<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `util::in_out_result<FwdIter1, FwdIter2>` otherwise. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename Op = std::plus<typename  
hpx::traits::range_traits<Rng>::value_type>>  
inclusive_scan_result<std::ranges::iterator_t<Rng>, O> hpx::ranges::inclusive_scan(Rng &&rng, O dest, Op  
&&op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns `util::in_out_result<std::ranges::iterator_t<Rng>, O>`. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename Op = std::plus<typename
hpx::traits::range_traits<Rng>::value_type>>
parallel::util::detail::algorithm_result<ExPolicy, inclusive_scan_result<std::ranges::iterator_t<Rng>, O>> hpx::ranges::inclusive_scan
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<util::in_out_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `util::in_out_result<std::ranges::iterator_t<Rng>, O>` otherwise. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the

sentinel and an output iterator to the element in the destination range, one past the last element copied

```
template<typename InIter, typename Sent, typename OutIter, typename Op, typename T = typename
std::iterator_traits<InIter>::value_type>
inclusive_scan_result<InIter, OutIter> hpx::ranges::inclusive_scan(InIter first, Sent last, OutIter dest, Op
&&op, T init)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result))).

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN) is defined as:

- a1 when N is 1
 - op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns `util::in_out_result<InIter, OutIter>`. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename Sent, typename FwdIter2, typename Op, typename
T = typename std::iterator_traits<FwdIter1>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, inclusive_scan_result<FwdIter1, FwdIter2>>::type hpx::ranges::inclusive_scan
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when *N* is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for InIter.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to sentinel value denoting the end of the sequence of elements the algorithm will be applied.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<util::in_out_result<InIter, OutIter>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *util::in_out_result<InIter, OutIter>* otherwise. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename Rng, typename O, typename Op, typename T = typename
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
inclusive_scan_result<std::ranges::iterator_t<Rng>, O> hpx::ranges::inclusive_scan(Rng &&rng, O dest, Op
&&op, T init)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns `util::in_out_result<std::ranges::iterator_t<Rng>, O>`. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename Rng, typename O, typename Op, typename T = typename  
std::iterator_traits<std::ranges::iterator_t<Rng>>::value_type>
```

`parallel::util::detail::algorithm_result<ExPolicy, inclusive_scan_result<std::ranges::iterator_t<Rng>, O>> hpx::ranges::inclusive`

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the i th input element in the i th sum. If op is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(last - first)$ applications of the predicate op .

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - $op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, \dots, aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, \dots, aN))$ where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an forward iterator.
- **O** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<util::in_out_result<std::ranges::iterator_t<Rng>, O>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `util::in_out_result<std::ranges::iterator_t<Rng>, O>` otherwise. The *inclusive_scan* algorithm returns an input iterator to the point denoted by the sentinel and an output iterator to the element in the destination range, one past the last element copied

hpx::ranges::for_each

Defined in header `hpx/algorithm.hpp`⁶⁹⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ranges::for_each_n`

```
template<typename InIter, typename Sent, typename F, typename Proj = hpx::identity>  
for_each_result<InIter, F> hpx::ranges::for_each(InIter first, Sent last, F &&f, Proj &&proj = Proj())
```

Applies *f* to the result of dereferencing every iterator in the range [first, last).

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Note: Complexity: Applies *f* exactly *last - first* times.

Template Parameters

- **InIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

⁶⁹⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

{last, HPX_MOVE(f)} where last is the iterator corresponding to the input sentinel last.

```
template<typename Rng, typename F, typename Proj = hpx::identity>
for_each_result<std::ranges::iterator_t<Rng>, F> hpx::ranges::for_each(Rng &&rng, F &&f, Proj &&proj =
    Proj())
```

Applies *f* to the result of dereferencing every iterator in the given range *rng*.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Note: Complexity: Applies *f* exactly *size(rng)* times.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

{std::end(rng), HPX_MOVE(f)}

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::ranges::for_each(ExPolicy &&policy,
                                                                                          FwdIter first, Sent
                                                                                          last, F &&f, Proj
                                                                                          &&proj = Proj())
```

Applies *f* to the result of dereferencing every iterator in the range [first, last).

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Applies *f* exactly *last - first* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for `InIter`.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *for_each* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

```
template<typename ExPolicy, typename Rng, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, std::ranges::iterator_t<Rng>> hpx::ranges::for_each(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     Rng
                                                                                                     &&rng,
                                                                                                     F
                                                                                                     &&f,
                                                                                                     Proj
                                                                                                     &&proj
                                                                                                     =
                                                                                                     Proj())
```

Applies *f* to the result of dereferencing every iterator in the given range *rng*.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Applies *f* exactly *size(rng)* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

`<ignored> pred(const Type &a);`

The signature does not need to have `const&`. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *for_each* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

`hpx::ranges::for_each_n`

Defined in header `hpx/algorithm.hpp`⁶⁹⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ranges::for_each*

```
template<typename InIter, typename Size, typename F, typename Proj = hpx::identity>
for_each_n_result<InIter, F> hpx::ranges::for_each_n(InIter first, Size count, F &&f, Proj &&proj = Proj())
```

Applies *f* to the result of dereferencing every iterator in the range [first, first + count), starting from first and proceeding to first + count - 1.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

Note: Complexity: Applies *f* exactly *count* times.

Template Parameters

⁶⁹⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **InIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

It returns *last*.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename F, typename Proj = hpx::identity>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type hpx::ranges::for_each_n(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter first,
                                                                                               Size count, F
                                                                                               &&f, Proj
                                                                                               &&proj =
                                                                                               Proj())
```

Applies *f* to the result of dereferencing every iterator in the range [first, first + count), starting from first and proceeding to first + count - 1.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Applies f exactly *count* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply f to.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires F to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *for_each* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *last*.

hpx::ranges::remove_copy

Defined in header `hpx/algorithm.hpp`⁶⁹⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ranges::remove_copy_if*

Warning: doxygenfunction: Cannot find function “hpx::ranges::remove_copy” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

⁶⁹⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

hpx::ranges::remove_copy_if

Defined in header [hpx/algorithm.hpp](#)⁶⁹⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::ranges::remove_copy](#)

Warning: doxygenfunction: Cannot find function “hpx::ranges::remove_copy_if” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::fill

Defined in header [hpx/algorithm.hpp](#)⁶⁹⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::fill_n](#)

```
template<typename ExPolicy, typename FwdIter, typename T>
util::detail::algorithm_result_t<ExPolicy> hpx::fill(ExPolicy &&policy, FwdIter first, FwdIter last, T value)
```

Assigns the given value to the elements in the range [first, last). Executed according to the policy.

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

⁶⁹⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

⁶⁹⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename FwdIter, typename T>  
void hpx::fill(FwdIter first, FwdIter last, T value)
```

Assigns the given value to the elements in the range [first, last).

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill* algorithm returns a *void*.

hpx::fill_n

Defined in header [hpx/algorithm.hpp](#)⁶⁹⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::fill*

```
template<typename ExPolicy, typename FwdIter, typename Size, typename T>  
util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::fill_n(ExPolicy &&policy, FwdIter first, Size count, T  
value)
```

Assigns the given value value to the first count elements in the range beginning at first if count > 0. Does nothing otherwise. Executed according to the policy.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *fill_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

⁶⁹⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs exactly *count* assignments, for *count* > 0.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *void*).

```
template<typename FwdIter, typename Size, typename T>
FwdIter hpx::fill_n(FwdIter first, Size count, T value)
```

Assigns the given value *value* to the first *count* elements in the range beginning at *first* if *count* > 0. Does nothing otherwise.

Note: Complexity: Performs exactly *count* assignments, for *count* > 0.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *fill_n* algorithm returns a *FwdIter*.

hpx/parallel/algorithms/transform_reduce_binary.hpp

Defined in header `hpx/parallel/algorithms/transform_reduce_binary.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::find

Defined in header `hpx/algorithm.hpp`⁷⁰⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::find_if`
- `hpx::find_if_not`
- `hpx::find_end`
- `hpx::find_first_of`

```
template<typename ExPolicy, typename FwdIter, typename T>  
util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::find(ExPolicy &&policy, FwdIter first, FwdIter last, T  
                                                             const &val)
```

Returns the first element in the range `[first, last)` that is equal to value. Executed according to the policy.

The comparison operations in the parallel *find* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most last - first applications of the operator`==()`.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to find (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.

⁷⁰⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **val** – the value to compare the elements to

Returns

The *find* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *find* algorithm returns the first element in the range *[first,last)* that is equal to *val*. If no such element in the range of *[first,last)* is equal to *val*, then the algorithm returns *last*.

```
template<typename InIter, typename T>
InIter hpx::find(InIter first, InIter last, T const &val)
```

Returns the first element in the range *[first, last)* that is equal to value. Executed according to the policy.

Note: Complexity: At most last - first applications of the operator==().

Template Parameters

- **InIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to find (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **val** – the value to compare the elements to

Returns

The *find* algorithm returns a *InIter*. The *find* algorithm returns the first element in the range *[first,last)* that is equal to *val*. If no such element in the range of *[first,last)* is equal to *val*, then the algorithm returns *last*.

hpx::find_if

Defined in header [hpx/algorithm.hpp](#)⁷⁰¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::find*
- *hpx::find_if_not*
- *hpx::find_end*
- *hpx::find_first_of*

```
template<typename ExPolicy, typename FwdIter, typename F>
```

⁷⁰¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

`util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::find_if(ExPolicy &&policy, FwdIter first, FwdIter last, F &&f)`

Returns the first element in the range `[first, last)` for which predicate `f` returns true. Executed according to the policy.

The comparison operations in the parallel *find_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most last - first applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **f** – The unary predicate which returns true for the required element. The signature of the predicate should be equivalent to:

`bool pred(const Type &a);`

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *find_if* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *find_if* algorithm returns the first element in the range `[first,last)` that satisfies the predicate *f*. If no such element exists that satisfies the predicate *f*, the algorithm returns *last*.

```
template<typename InIter, typename F>
InIter hpx::find_if(InIter first, InIter last, F &&f)
```

Returns the first element in the range `[first, last)` for which predicate *f* returns true.

Note: Complexity: At most last - first applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **f** – The unary predicate which returns true for the required element. The signature of the predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *find_if* algorithm returns a *InIter*. The *find_if* algorithm returns the first element in the range [first,last) that satisfies the predicate *f*. If no such element exists that satisfies the predicate *f*, the algorithm returns *last*.

hpx::find_if_not

Defined in header `hpx/algorithm.hpp`⁷⁰².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::find`
- `hpx::find_if`
- `hpx::find_end`
- `hpx::find_first_of`

```
template<typename ExPolicy, typename FwdIter, typename F>
```

```
util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::find_if_not(ExPolicy &&policy, FwdIter first, FwdIter last, F &&f)
```

Returns the first element in the range [first, last) for which predicate *f* returns false. Executed according to the policy.

⁷⁰² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The comparison operations in the parallel *find_if_not* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_if_not* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most last - first applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **f** – The unary predicate which returns false for the required element. The signature of the predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *find_if_not* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *find_if_not* algorithm returns the first element in the range `[first, last)` that does **not** satisfy the predicate *f*. If no such element exists that does not satisfy the predicate *f*, the algorithm returns *last*.

```
template<typename FwdIter, typename F>  
FwdIter hpx::find_if_not(FwdIter first, FwdIter last, F &&f)
```

Returns the first element in the range `[first, last)` for which predicate *f* returns false.

Note: Complexity: At most last - first applications of the predicate.

Template Parameters

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.

- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **f** – The unary predicate which returns false for the required element. The signature of the predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *find_if_not* algorithm returns a *FwdIter*. The *find_if_not* algorithm returns the first element in the range [first, last) that does **not** satisfy the predicate *f*. If no such element exists that does not satisfy the predicate *f*, the algorithm returns *last*.

hpx::find_end

Defined in header `hpx/algorithm.hpp`⁷⁰³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::find`
- `hpx::find_if`
- `hpx::find_if_not`
- `hpx::find_first_of`

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
util::detail::algorithm_result_t<ExPolicy, FwdIter1> hpx::find_end(ExPolicy &&policy, FwdIter1 first1,
                                                                    FwdIter1 last1, FwdIter2 first2, FwdIter2
                                                                    last2, Pred &&op = Pred())
```

Returns the last subsequence of elements [first2, last2) found in the range [first, last) using the given predicate *op* to compare elements. Executed according to the policy.

The comparison operations in the parallel *find_end* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_end* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

This overload of *find_end* is available if the user decides to provide the algorithm their own predicate *op*.

⁷⁰³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: at most $S \cdot (N - S + 1)$ comparisons where $S = \text{distance}(\text{first2}, \text{last2})$ and $N = \text{distance}(\text{first1}, \text{last1})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *replace* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **last2** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively.

Returns

The *find_end* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *find_end* algorithm returns an iterator to the beginning of the last subsequence `[first2, last2)` in range `[first, last)`. If the length of the subsequence `[first2, last2)` is greater than the length of the range `[first1, last1)`, *last1* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last1* is also returned.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
util::detail::algorithm_result_t<ExPolicy, FwdIter1> hpx::find_end(ExPolicy &&policy, FwdIter1 first1,
                                                                    FwdIter1 last1, FwdIter2 first2, FwdIter2
                                                                    last2)
```

Returns the last subsequence of elements `[first2, last2)` found in the range `[first, last)`. Elements are compared using *operator==*. Executed according to the policy.

The comparison operations in the parallel *find_end* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_end* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $S \cdot (N - S + 1)$ comparisons where $S = \text{distance}(\text{first2}, \text{last2})$ and $N = \text{distance}(\text{first1}, \text{last1})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **last2** – Refers to the end of the sequence of elements of the algorithm will be searching for.

Returns

The *find_end* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *find_end* algorithm returns an iterator to the beginning of the last subsequence `[first2, last2)` in range `[first, last)`. If the length of the subsequence `[first2, last2)` is greater than the length of the range `[first1, last1)`, *last1* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last1* is also returned.

```
template<typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
FwdIter1 hpx::find_end(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, Pred &&op = Pred())
```

Returns the last subsequence of elements `[first2, last2)` found in the range `[first, last)` using the given predicate *op* to compare elements.

This overload of *find_end* is available if the user decides to provide the algorithm their own predicate *op*.

Note: Complexity: at most $S \cdot (N - S + 1)$ comparisons where $S = \text{distance}(\text{first2}, \text{last2})$ and $N = \text{distance}(\text{first1}, \text{last1})$.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *replace* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **last2** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively.

Returns

The *find_end* algorithm returns a *FwdIter1*. The *find_end* algorithm returns an iterator to the beginning of the last subsequence `[first2, last2)` in range `[first, last)`. If the length of the subsequence `[first2, last2)` is greater than the length of the range `[first1, last1)`, *last1* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last1* is also returned.

```
template<typename FwdIter1, typename FwdIter2>
```

```
FwdIter1 hpx::find_end(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2)
```

Returns the last subsequence of elements `[first2, last2)` found in the range `[first, last)`. Elements are compared using *operator==*.

Note: Complexity: at most $S \cdot (N - S + 1)$ comparisons where $S = \text{distance}(\text{first2}, \text{last2})$ and $N = \text{distance}(\text{first1}, \text{last1})$.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **last2** – Refers to the end of the sequence of elements of the algorithm will be searching for.

Returns

The *find_end* algorithm returns a *FwdIter1*. The *find_end* algorithm returns an iterator to the beginning of the last subsequence [first2, last2) in range [first, last). If the length of the subsequence [first2, last2) is greater than the length of the range [first1, last1), *last1* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last1* is also returned.

hpx::find_first_of

Defined in header `hpx/algorithm.hpp`⁷⁰⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::find`
- `hpx::find_if`
- `hpx::find_if_not`
- `hpx::find_end`

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
util::detail::algorithm_result_t<ExPolicy, FwdIter1> hpx::find_first_of(ExPolicy &&policy, FwdIter1 first,
                                                                    FwdIter1 last, FwdIter2 s_first,
                                                                    FwdIter2 s_last, Pred &&op = Pred())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses binary predicate *op* to compare elements. Executed according to the policy.

The comparison operations in the parallel *find_first_of* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_first_of* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

This overload of *find_first_of* is available if the user decides to provide the algorithm their own predicate *op*.

Note: Complexity: at most ($S \cdot N$) comparisons where S = distance(s_first, s_last) and N = distance(first, last).

Template Parameters

⁷⁰⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively.

Returns

The *find_first_of* algorithm returns a *hpx::future<FwdIter1>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter1* otherwise. The *find_first_of* algorithm returns an iterator to the first element in the range `[first, last)` that is equal to an element from the range `[s_first, s_last)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, last)`, *last* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last* is also returned.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
util::detail::algorithm_result_t<ExPolicy, FwdIter1> hpx::find_first_of(ExPolicy &&policy, FwdIter1 first,
                                                                    FwdIter1 last, FwdIter2 s_first,
                                                                    FwdIter2 s_last)
```

Searches the range `[first, last)` for any elements in the range `[s_first, s_last)`. Elements are compared using *operator==*. Executed according to the policy.

The comparison operations in the parallel *find_first_of* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *find_first_of* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(S*N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.

Returns

The *find_first_of* algorithm returns a *hpx::future<FwdIter1>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter1* otherwise. The *find_first_of* algorithm returns an iterator to the first element in the range $[first, last)$ that is equal to an element from the range $[s_first, s_last)$. If the length of the subsequence $[s_first, s_last)$ is greater than the length of the range $[first, last)$, *last* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last* is also returned.

```
template<typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
FwdIter1 hpx::find_first_of(FwdIter1 first, FwdIter1 last, FwdIter2 s_first, FwdIter2 s_last, Pred &&op =
    Pred())
```

Searches the range $[first, last)$ for any elements in the range $[s_first, s_last)$. Uses binary predicate *op* to compare elements.

This overload of *find_first_of* is available if the user decides to provide the algorithm their own predicate *op*.

Note: Complexity: at most $(S*N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively.

Returns

The *find_first_of* algorithm returns a *FwdIter1*. The *find_first_of* algorithm returns an iterator to the first element in the range `[first, last)` that is equal to an element from the range `[s_first, s_last)`. If the length of the subsequence `[s_first, s_last)` is greater than the length of the range `[first, last)`, *last* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last* is also returned.

```
template<typename FwdIter1, typename FwdIter2>
```

```
FwdIter1 hpx::find_first_of(FwdIter1 first, FwdIter1 last, FwdIter2 s_first, FwdIter2 s_last)
```

Searches the range `[first, last)` for any elements in the range `[s_first, s_last)`. Elements are compared using *operator==*.

Note: Complexity: at most $(S*N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.

- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.

Returns

The *find_first_of* algorithm returns a *FwdIter1*. The *find_first_of* algorithm returns an iterator to the first element in the range [first, last) that is equal to an element from the range [s_first, s_last). If the length of the subsequence [s_first, s_last) is greater than the length of the range [first, last), *last* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *last* is also returned.

hpx::exclusive_scan

Defined in header [hpx/algorithm.hpp](#)⁷⁰⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

template<typename **InIter**, typename **OutIter**, typename **T**>

OutIter **hpx::exclusive_scan**(*InIter* first, *InIter* last, *OutIter* dest, *T* init)

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(+, init, *first, ..., *(first + (i - result) - 1))

The reduce operations in the parallel *exclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *std::plus<T>*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

⁷⁰⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.

Returns

The *exclusive_scan* algorithm returns *OutIter*. The *exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T>  
util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::exclusive_scan(ExPolicy &&policy, FwdIter1 first,  
                                                                    FwdIter1 last, FwdIter2 dest, T init)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(+, init, *first, ..., *(first + (i - result) - 1))

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *std::plus<T>*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.

Returns

The *exclusive_scan* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename OutIter, typename T, typename Op>
OutIter hpx::exclusive_scan(InIter first, InIter last, OutIter dest, T init, Op &&op)
```

Assigns through each iterator *i* in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, *first, ..., *(first + (i - result) - 1))`.

The reduce operations in the parallel *exclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(last - first)$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - $op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, \dots, aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, \dots, aN))$ where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns *OutIter*. The *exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op, typename T>
util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::exclusive_scan(ExPolicy &&policy, FwdIter1 first,
                                                                    FwdIter1 last, FwdIter2 dest, T init,
                                                                    Op &&op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, *first, ..., *(first + (i - result) - 1))`.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.

- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *exclusive_scan* algorithm returns a `hpx::future<OutIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *OutIter* otherwise. The *exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::equal

Defined in header `hpx/algorithm.hpp`⁷⁰⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
util::detail::algorithm_result_t<ExPolicy, bool> hpx::equal(ExPolicy &&policy, FwdIter1 first1, FwdIter1 last1,
                                                         FwdIter2 first2, FwdIter2 last2, Pred &&op = Pred())
```

Returns true if the range `[first1, last1)` is equal to the range `[first2, last2)`, and false otherwise. Executed according to the policy.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

⁷⁰⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: $O(\min(\text{last1} - \text{first1}, \text{last2} - \text{first2}))$ applications of the predicate *op*.

Note: The two ranges are considered equal if, for every iterator *i* in the range $[\text{first1}, \text{last1})$, **i* equals $*(\text{first2} + (i - \text{first1}))$. This overload of *equal* uses `operator==` to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *equal* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range $[\text{first1}, \text{last1})$ does not equal the length of the range $[\text{first2}, \text{last2})$, it returns false.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
util::detail::algorithm_result_t<ExPolicy, bool> hpx::equal(ExPolicy &&policy, FwdIter1 first1, FwdIter1 last1,
                                                           FwdIter2 first2, FwdIter2 last2)
```

Returns true if the range $[first1, last1)$ is equal to the range $[first2, last2)$, and false otherwise. Executed according to policy.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\min(last1 - first1, last2 - first2))$ applications of the predicate *std::equal_to*.

Note: The two ranges are considered equal if, for every iterator *i* in the range $[first1, last1)$, **i* equals **(first2 + (i - first1))*. This overload of *equal* uses *operator==* to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *equal* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range $[first1, last1)$ does not equal the length of the range $[first2, last2)$, it returns false.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
util::detail::algorithm_result_t<ExPolicy, bool> hpx::equal(ExPolicy &&policy, FwdIter1 first1, FwdIter1 last1,
FwdIter2 first2, Pred &&op = Pred())
```

Returns true if the range $[first1, last1)$ is equal to the range starting at *first2*, and false otherwise. Executed according to policy.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\min(\text{last1} - \text{first1}, \text{last2} - \text{first2}))$ applications of the predicate *op*.

Note: The two ranges are considered equal if, for every iterator *i* in the range $[\text{first1}, \text{last1})$, **i* equals **(first2 + (i - first1))*. This overload of *equal* uses *operator==* to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *equal* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false.

template<typename **ExPolicy**, typename **FwdIter1**, typename **FwdIter2**>

```
util::detail::algorithm_result_t<ExPolicy, bool> hpx::equal(ExPolicy &&policy, FwdIter1 first1, FwdIter1 last1,
                                                         FwdIter2 first2)
```

Returns true if the range [first1, last1) is equal to the range [first2, last2), and false otherwise. Executed according to policy.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *equal* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last1 - first1* applications of the predicate *op*.

Note: The two ranges are considered equal if, for every iterator *i* in the range [first1, last1), **i* equals **(first2 + (i - first1))*. This overload of *equal* uses *operator==* to determine if two elements are equal.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *equal* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range [first1, last1) does not equal the length of the range [first2, last2), it returns false.

```
template<typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
bool hpx::equal(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, Pred &&op = Pred())
```

Returns true if the range [first1, last1) is equal to the range [first2, last2), and false otherwise.

Note: Complexity: At most min(last1 - first1, last2 - first2) applications of the predicate *op*.

Note: The two ranges are considered equal if, for every iterator *i* in the range `[first1,last1)`, **i* equals **(first2 + (i - first1))*. This overload of `equal` uses `operator==` to determine if two elements are equal.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *equal* algorithm returns a *bool* . The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range `[first1, last1)` does not equal the length of the range `[first2, last2)`, it returns false.

```
template<typename FwdIter1, typename FwdIter2>  
bool hpx::equal(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2)
```

Returns true if the range `[first1, last1)` is equal to the range `[first2, last2)`, and false otherwise.

Note: Complexity: At most `min(last1 - first1, last2 - first2)` applications of the predicate *std::equal_to*.

Note: The two ranges are considered equal if, for every iterator *i* in the range `[first1,last1)`, **i* equals **(first2 + (i - first1))*. This overload of `equal` uses `operator==` to determine if two elements are equal.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *equal* algorithm returns a *bool*. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range [first1, last1) does not equal the length of the range [first2, last2), it returns false.

```
template<typename FwdIter1, typename FwdIter2, typename Pred = detail::equal_to>
bool hpx::equal(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, Pred &&op = Pred())
```

Returns true if the range [first1, last1) is equal to the range [first2, first2 + (last1 - first1)), and false otherwise.

Note: Complexity: At most *last1 - first1* applications of the predicate *op*.

Note: The two ranges are considered equal if, for every iterator *i* in the range [first1,last1), **i* equals **(first2 + (i - first1))*. This overload of *equal* uses operator== to determine if two elements are equal.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.

- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *equal* algorithm returns a *bool*. The *equal* algorithm returns true if the elements in the two ranges are equal, otherwise it returns false. If the length of the range [first1, last1) does not equal the length of the range [first2, last2), it returns false.

hpx::is_partitioned

Defined in header `hpx/algorithm.hpp`⁷⁰⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter, typename Pred>
bool hpx::is_partitioned(FwdIter first, FwdIter last, Pred &&pred)
    Determines if the range [first, last) is partitioned.
```

Note: Complexity: at most (N) predicate evaluations where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_partitioned* algorithm returns *bool*. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range [first, last) contains less than two elements, the function is always true.

⁷⁰⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
template<typename ExPolicy, typename FwdIter, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::is_partitioned(ExPolicy &&policy,
                                                                                      FwdIter first, FwdIter last,
                                                                                      Pred &&pred)
```

Determines if the range [first, last) is partitioned. Executed according to the policy.

The predicate operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_partitioned* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (N) predicate evaluations where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). *Pred* must be *CopyConstructible* when using a parallel policy.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the unary predicate which returns true for elements expected to be found in the beginning of the range. The signature of the function should be equivalent to

```
bool pred(const Type &a);
```

The signature does not need to have const &, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_partitioned* algorithm returns a *hpx::future<bool>* if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_partitioned* algorithm returns true if each element in the sequence for which *pred* returns true precedes those for which *pred* returns false. Otherwise *is_partitioned* returns false. If the range [first, last) contains less than two elements, the function is always true.

hpx::set_intersection

Defined in header `hpx/algorithm.hpp`⁷⁰⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =  
hpx::parallel::detail::less>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter3> hpx::set_intersection(ExPolicy &&policy,  
FwdIter1 first1,  
FwdIter1 last1,  
FwdIter2 first2,  
FwdIter2 last2,  
FwdIter3 dest, Pred  
&&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges $[first1, last1)$ and $[first2, last2)$. This algorithm expects both input ranges to be sorted with the given binary predicate *pred*. Executed according to the policy.

If some element is found m times in $[first1, last1)$ and n times in $[first2, last2)$, the first $\text{std::min}(m, n)$ elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator with sequential execution.

⁷⁰⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_intersection* algorithm returns a *hpx::future<FwdIter3>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter3* otherwise. The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =
hpx::parallel::detail::less>
FwdIter3 hpx::set_intersection(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, FwdIter3 dest,
                             Pred &&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in both sorted ranges [*first1*, *last1*) and [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *pred*.

If some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), the first `std::min(m, n)` elements will be copied from the first range to the destination range. The order of equivalent elements is preserved. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N_1 + N_2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.

- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator with sequential execution.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_intersection* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_intersection* algorithm returns a *FwdIter3*. The *set_intersection* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::ends_with

Defined in header `hpx/algorithm.hpp`⁷⁰⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter1, typename InIter2, typename Pred = hpx::parallel::detail::equal_to>  
bool hpx::ends_with(InIter1 first1, InIter1 last1, InIter2 first2, InIter2 last2, Pred &&pred = Pred())
```

Checks whether the second range defined by `[first1, last1)` matches the suffix of the first range defined by `[first2, last2)`

The assignments in the parallel *ends_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most $\min(N1, N2)$ applications of the predicate.

⁷⁰⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **InIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the begin destination iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The binary predicate that compares the elements. This defaults to `hpx::parallel::detail::equal_to`.

Parameters

- **first1** – Refers to the beginning of the source range.
- **last1** – Refers to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the two ranges.

Returns

The `ends_with` algorithm returns *bool*. The `ends_with` algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred = ranges::equal_to>
hpx::parallel::util::detail::algorithm_result<ExPolicy, bool>::type hpx::ends_with(ExPolicy &&policy, FwdIter1
first1, FwdIter1 last1,
FwdIter2 first2, FwdIter2
last2, Pred &&pred = Pred())
```

Checks whether the second range defined by [first1, last1) matches the suffix of the first range defined by [first2, last2). Executed according to the policy.

The assignments in the parallel `ends_with` algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel `ends_with` algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the begin source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the begin destination iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The binary predicate that compares the elements. This defaults to `ranges::equal_to`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the source range.
- **last1** – Refers to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Refers to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the two ranges.

Returns

The *ends_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *ends_with* algorithm returns a boolean with the value true if the second range matches the suffix of the first range, false otherwise.

hpx::min_element

Defined in header [hpx/algorithm.hpp](#)⁷¹⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::max_element*
- *hpx::minmax_element*

```
template<typename FwdIter, typename F = hpx::parallel::detail::less>  
FwdIter hpx::min_element(FwdIter first, FwdIter last, F &&f)
```

Finds the smallest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *min_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

⁷¹⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *min_element* algorithm returns *FwdIter*. The *min_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

```
template<typename ExPolicy, typename FwdIter, typename F = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::min_element(ExPolicy &&policy, FwdIter
first, FwdIter last, F &&f)
```

Finds the smallest element in the range [first, last) using the given comparison function *f*. Executed according to the policy.

The comparisons in the parallel *min_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *min_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *min_element* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *min_element* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *min_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

hpx::max_element

Defined in header [hpx/algorithm.hpp](#)⁷¹¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::min_element*
- *hpx::minmax_element*

```
template<typename FwdIter, typename F = hpx::parallel::detail::less>  
FwdIter hpx::max_element(FwdIter first, FwdIter last, F &&f)
```

Finds the largest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *min_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: Exactly *max(N-1, 0)* comparisons, where *N* = *std::distance(first, last)*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if left argument is less than the right element. This argument is optional and defaults to *std::less*. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have *const &*, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *max_element* algorithm returns *FwdIter*. The *max_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

⁷¹¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
template<typename ExPolicy, typename FwdIter, typename F = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type hpx::max_element(ExPolicy &&policy,
                                                                                   FwdIter first, FwdIter
                                                                                   last, F &&f)
```

Removes all elements satisfying specific criteria from the range Finds the largest element in the range [first, last) using the given comparison function *f*. Executed according to the policy.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *max_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $\max(N-1, 0)$ comparisons, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *max_element* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if left argument is less than the right element. This argument is optional and defaults to `std::less`. the left argument is less than the right element. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *max_element* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *max_element* algorithm returns the iterator to the smallest element in the range [first, last). If several elements in the range are equivalent to the smallest element, returns the iterator to the first such element. Returns last if the range is empty.

hpx::minmax_element

Defined in header `hpx/algorithm.hpp`⁷¹².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::min_element`
- `hpx::max_element`

```
template<typename FwdIter, typename F = hpx::parallel::detail::less>  
minmax_element_result<FwdIter> hpx::minmax_element(FwdIter first, FwdIter last, F &&f)
```

Finds the largest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *minmax_element* algorithm execute in sequential order in the calling thread.

Note: Complexity: At most $\max(\text{floor}(3/2 * (N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the left argument is less than the right element. This argument is optional and defaults to `std::less`. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *minmax_element* algorithm returns a *minmax_element_result*<*FwdIter*>. The *min-max_element* algorithm returns a pair consisting of an iterator to the smallest element as the min element and an iterator to the largest element as the max element. Returns *min-max_element_result*<*FwdIter*>{*first*,*first*} if the range is empty. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

```
template<typename ExPolicy, typename FwdIter, typename F = hpx::parallel::detail::less>
```

⁷¹² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, minmax_element_result<FwdIter>> **hpx::minmax_element**(*ExPolicy* &&policy, *FwdIter* first, *FwdIter* last, *F* &&f)

Finds the largest element in the range [first, last) using the given comparison function *f*.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparisons in the parallel *minmax_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\max(\text{floor}(3/2 * (N-1)), 0)$ applications of the predicate, where $N = \text{std::distance}(\text{first}, \text{last})$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *minmax_element* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – The binary predicate which returns true if the left argument is less than the right element. This argument is optional and defaults to `std::less`. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *minmax_element* algorithm returns a `hpx::future<minmax_element_result<FwdIter>>` if

the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *minmax_element_result*<*FwdIter*> otherwise. The *minmax_element* algorithm returns a pair consisting of an iterator to the smallest element as the min element and an iterator to the largest element as the max element. Returns *std::make_pair(first,first)* if the range is empty. If several elements are equivalent to the smallest element, the iterator to the first such element is returned. If several elements are equivalent to the largest element, the iterator to the last such element is returned.

hpx::experimental::reduction_max

Defined in header [hpx/algorithm.hpp](#)⁷¹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

template<typename T>

constexpr *hpx::parallel::detail::reduction_helper*<*T*, *hpx::parallel::detail::max_of*<*T*>> *hpx::experimental::reduction_max*(*T* &va

The function template *reduction_max* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses *std::max_of{ }* as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_max* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the *std::max_of{ }* operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views

⁷¹³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
```

```
constexpr hpx::parallel::detail::reduction_helper<T, hpx::parallel::detail::max_of<T>> hpx::experimental::reduction_max(T
&va
T
con
&id
tity;
```

hpx::reduce_deterministic

Defined in header [hpx/algorithm.hpp](#)⁷¹⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter, typename F, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::reduce_deterministic(ExPolicy &&policy,
FwdIter first, FwdIter
last, T init, F &&f)
```

Returns GENERALIZED_SUM(f , $init$, $*first$, ..., $*(first + (last - first) - 1)$). Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(last - first)$ applications of the predicate f .

Note: GENERALIZED_SUM(op , a_1 , ..., a_N) is defined as follows:

- a_1 when N is 1
 - $op(GENERALIZED_SUM(op, b_1, \dots, b_K), GENERALIZED_SUM(op, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

⁷¹⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *reduce* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`. The types *Type1* *Ret* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to any of those types.

Returns

The *reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter, typename T = typename
std::iterator_traits<FwdIter>::value_type>
util::detail::algorithm_result_t<ExPolicy, T> hpx::reduce_deterministic(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter>
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<FwdIter>::value_type>::type hpx::reduce_deter
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator $+$ ().

Note: The type of the initial value (and the result type) T is determined from the `value_type` of the used `FwdIter`.

Note: `GENERALIZED_SUM(+, a1, ..., aN)` is defined as follows:

- $a1$ when N is 1
 - `op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN))`, where:
 - $b1, \dots, bN$ may be any permutation of $a1, \dots, aN$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns T otherwise (where T is the `value_type` of `FwdIter`). The *reduce* algorithm returns the result of the generalized sum (applying operator $+$ ()) over the elements given by the input range $[\text{first}, \text{last})$.

```
template<typename FwdIter, typename F, typename T = typename std::iterator_traits<FwdIter>::value_type>
T hpx::reduce_deterministic(FwdIter first, FwdIter last, T init, F &&f)
```

Returns `GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1))`. Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate f .

Note: `GENERALIZED_SUM(op, a1, ..., aN)` is defined as follows:

- $a1$ when N is 1
- `op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN))`, where:

- $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
- $1 < K+1 = M \leq N$.

Template Parameters

- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *reduce* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

Ret fun(const Type1 &a, const Type1 &b);

The signature does not need to have const&. The types *Type1* *Ret* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to any of those types.

Returns

The *reduce* algorithm returns *T*. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename FwdIter, typename T = typename std::iterator_traits<FwdIter>::value_type>
T hpx::reduce_deterministic(FwdIter first, FwdIter last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, $a_1, \dots, a_N$) is defined as follows:

- a_1 when N is 1
 - $\text{op}(\text{GENERALIZED_SUM}(+, b_1, \dots, b_K), \text{GENERALIZED_SUM}(+, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a *T*. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename FwdIter>
```

```
std::iterator_traits<FwdIter>::value_type hpx::reduce_deterministic(FwdIter first, FwdIter last)
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) *T* is determined from the value_type of the used *FwdIter*.

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

FwdIter – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns *T* (where *T* is the value_type of *FwdIter*). The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

hpx::set_difference

Defined in header `hpx/algorithm.hpp`⁷¹⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =
hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter3> hpx::set_difference(ExPolicy &&policy,
FwdIter1 first1,
FwdIter1 last1,
FwdIter2 first2,
FwdIter2 last2,
FwdIter3 dest, Pred
&&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in the range $[first1, last1)$ and not present in the range $[first2, last2)$. This algorithm expects both input ranges to be sorted with the given binary predicate *pred*. Executed according to the policy.

Equivalent elements are treated individually, that is, if some element is found m times in $[first1, last1)$ and n times in $[first2, last2)$, it will be copied to *dest* exactly $\text{std::max}(m-n, 0)$ times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a output iterator.

⁷¹⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_difference* algorithm returns a `hpx::future<FwdIter3>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter3* otherwise. The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =  
hpx::parallel::detail::less>  
FwdIter3 hpx::set_difference(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, FwdIter3 dest,  
Pred &&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in the range `[first1, last1)` and not present in the range `[first2, last2)`. This algorithm expects both input ranges to be sorted with the given binary predicate *pred*.

Equivalent elements are treated individually, that is, if some element is found *m* times in `[first1, last1)` and *n* times in `[first2, last2)`, it will be copied to *dest* exactly `std::max(m-n, 0)` times. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N_1 + N_2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_difference* algorithm returns a *FwdIter3*. The *set_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::uninitialized_value_construct

Defined in header `hpx/algorithm.hpp`⁷¹⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::uninitialized_value_construct_n`

```
template<typename FwdIter>
```

```
void hpx::uninitialized_value_construct(FwdIter first, FwdIter last)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range `[first, last)` by value-initialization. If an exception is thrown during the initialization, the function has no effects.

⁷¹⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

FwdIter – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *uninitialized_value_construct* algorithm returns nothing

```
template<typename ExPolicy, typename FwdIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::uninitialized_value_construct(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter first,
                                                                                               FwdIter last)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by value-initialization. If an exception is thrown during the initialization, the function has no effects. Executed according to the policy.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_value_construct* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *uninitialized_value_construct* algorithm returns a `hpx::future<void>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns nothing otherwise.

hpx::uninitialized_value_construct_n

Defined in header `hpx/algorithm.hpp`⁷¹⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::uninitialized_value_construct`

template<typename **FwdIter**, typename **Size**>

FwdIter **hpx::uninitialized_value_construct_n**(*FwdIter* first, *Size* count)

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range `[first, first + count)` by value-initialization. If an exception is thrown during the initialization, the function has no effects.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The `uninitialized_value_construct_n` algorithm returns a returns *FwdIter*. The `uninitialized_value_construct_n` algorithm returns the iterator to the element in the source range, one past the last element constructed.

template<typename **ExPolicy**, typename **FwdIter**, typename **Size**>

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> **hpx::uninitialized_value_construct_n**(*ExPolicy* &&policy, *FwdIter* first, *Size* count)

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range `[first, first + count)` by value-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel `uninitialized_value_construct_n` algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The assignments in the parallel `uninitialized_value_construct_n` algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

⁷¹⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_value_construct_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_value_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::experimental::reduction_bit_and

Defined in header [hpx/algorithm.hpp](#)⁷¹⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

template<typename T>

constexpr *hpx::parallel::detail::reduction_helper<T, std::bit_and<T>>* *hpx::experimental::reduction_bit_and*(T &var)

The function template *reduction_bit_and* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses *std::bit_and{ }* as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_bit_and* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the *std::bit_and{ }* operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

⁷¹⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The live-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::bit_and<T>> hpx::experimental::reduction_bit_and(T
                                                                    &var,
                                                                    T
                                                                    const
                                                                    &iden-
                                                                    tity)
```

hpx::shift_left

Defined in header [hpx/algorithm.hpp](#)⁷¹⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter, typename Size>
FwdIter hpx::shift_left(FwdIter first, FwdIter last, Size n)
```

Shifts the elements in the range [first, last) by *n* positions towards the beginning of the range. For every integer *i* in [0, last - first

- *n*), moves the element originally at position first + *n* + *i* to position first + *i*.

The assignment operations in the parallel *shift_left* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most (last - first) - *n* assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

⁷¹⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns *FwdIter*. The *shift_left* algorithm returns an iterator to the end of the resulting range. Specifically: If *n* is 0 or $n \geq (\text{last} - \text{first})$, does nothing and returns *last* and *first* respectively. Otherwise returns $\text{first} + ((\text{last} - \text{first}) - n)$.

```
template<typename ExPolicy, typename FwdIter, typename Size>  
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter> hpx:::shift_left(ExPolicy &&policy, FwdIter  
first, FwdIter last, Size n)
```

Shifts the elements in the range $[\text{first}, \text{last})$ by *n* positions towards the beginning of the range. For every integer *i* in $[0, \text{last} - \text{first})$

- *n*), moves the element originally at position $\text{first} + n + i$ to position $\text{first} + i$. Executed according to the policy.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_left* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(\text{last} - \text{first}) - n$ assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_left* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *shift_left* algorithm returns an iterator to the end of the resulting range. Specifically: If *n* is 0, does nothing and returns *last*. If *n* >= (last - first), does nothing and returns *first*. Otherwise returns *first* + ((last - first) - n).

hpx::adjacent_difference

Defined in header `hpx/algorithm.hpp`⁷²⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter1, typename FwdIter2>
FwdIter2 hpx::adjacent_difference(FwdIter1 first, FwdIter1 last, FwdIter2 dest)
```

Assigns each value in the range given by result its corresponding element in the range [first, last] and the one preceding it except *result, which is assigned *first.

Note: Complexity: Exactly (last - first) - 1 application of the binary operator and (last - first) assignments.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the input range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the output range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the sequence of elements the results will be assigned to.

Returns

The *adjacent_difference* algorithm returns a *FwdIter2*. The *adjacent_difference* algorithm returns an iterator to the element past the last element written.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::adjacent_difference(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter1 first,
                                                                                               FwdIter1 last,
                                                                                               FwdIter2 dest)
```

⁷²⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Assigns each value in the range given by result its corresponding element in the range [first, last] and the one preceding it except *result, which is assigned *first. Executed according to the policy.

The difference operations in the parallel *adjacent_difference* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The difference operations in the parallel *adjacent_difference* invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly (last - first) - 1 application of the binary operator and (last - first) assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the input range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the output range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the sequence of elements the results will be assigned to.

Returns

The *adjacent_difference* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *adjacent_difference* algorithm returns an iterator to the element past the last element written.

```
template<typename FwdIter1, typename FwdIter2, typename Op>
FwdIter2 hpx::adjacent_difference(FwdIter1 first, FwdIter1 last, FwdIter2 dest, Op &&op)
```

Assigns each value in the range given by result its corresponding element in the range [first, last] and the one preceding it except *result, which is assigned *first

Note: Complexity: Exactly (last - first) - 1 application of the binary operator and (last - first) assignments.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the input range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the output range (deduced). This iterator type must meet the requirements of a forward iterator.

- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the sequence of elements the results will be assigned to.
- **op** – The binary operator which returns the difference of elements. The signature should be equivalent to the following:

```
bool op(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter1* can be dereferenced and then implicitly converted to the dereferenced type of *dest*.

Returns

The *adjacent_difference* algorithm returns *FwdIter2*. The *adjacent_difference* algorithm returns an iterator to the element past the last element written.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::adjacent_difference(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter1 first,
                                                                                               FwdIter1 last,
                                                                                               FwdIter2 dest,
                                                                                               Op &&op)
```

Assigns each value in the range given by *result* its corresponding element in the range `[first, last]` and the one preceding it except **result*, which is assigned **first*

The difference operations in the parallel *adjacent_difference* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The difference operations in the parallel *adjacent_difference* invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly $(last - first) - 1$ application of the binary operator and $(last - first)$ assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the input range (deduced). This iterator type must meet the requirements of a forward iterator.

- **FwdIter2** – The type of the source iterators used for the output range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Op** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *adjacent_difference* requires *Op* to meet the requirements of *Copy-Constructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **dest** – Refers to the beginning of the sequence of elements the results will be assigned to.
- **op** – The binary operator which returns the difference of elements. The signature should be equivalent to the following:

```
bool op(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter1* can be dereferenced and then implicitly converted to the dereferenced type of *dest*.

Returns

The *adjacent_difference* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *adjacent_difference* algorithm returns an iterator to the element past the last element written.

hpx::adjacent_find

Defined in header [hpx/algorithm.hpp](#)⁷²¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter, typename Pred = hpx::parallel::detail::equal_to>  
InIter hpx::adjacent_find(InIter first, InIter last, Pred &&pred = Pred())
```

Searches the range [first, last) for two consecutive identical elements.

Note: Complexity: Exactly the smaller of $(result - first) + 1$ and $(last - first) - 1$ application of the predicate where *result* is the value returned

Template Parameters

- **InIter** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use.

Parameters

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.

⁷²¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *Iter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *adjacent_find* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

```
template<typename ExPolicy, typename FwdIter, typename Pred = hpx::parallel::detail::equal_to>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::adjacent_find(ExPolicy &&policy,
                                                                                      FwdIter first, FwdIter
                                                                                      last, Pred &&pred =
                                                                                      Pred())
```

Searches the range `[first, last)` for two consecutive identical elements. This version uses the given binary predicate *pred*

The comparison operations in the parallel *adjacent_find* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *adjacent_find* invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

This overload of *adjacent_find* is available if the user decides to provide their algorithm their own binary predicate *pred*.

Note: Complexity: Exactly the smaller of $(result - first) + 1$ and $(last - first) - 1$ application of the predicate where *result* is the value returned

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *adjacent_find* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements of the range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the range the algorithm will be applied to.
- **pred** – The binary predicate which returns *true* if the elements should be treated as equal. The signature should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *adjacent_find* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *adjacent_find* algorithm returns an iterator to the first of the identical elements. If no such elements are found, *last* is returned.

hpx::set_symmetric_difference

Defined in header [hpx/algorithm.hpp](#)⁷²².

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =
hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter3>::type hpx::set_symmetric_difference(ExPolicy
&&policy,
FwdIter1
first1,
FwdIter1
last1,
FwdIter2
first2,
FwdIter2
last2,
FwdIter3
dest,
Pred
&&op
=
Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges [*first1*, *last1*) and [*first2*, *last2*), but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *pred*. Executed according to the policy.

⁷²² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

If some element is found m times in $[first1, last1)$ and n times in $[first2, last2)$, it will be copied to *dest* exactly $\text{std::abs}(m-n)$ times. If $m > n$, then the last $m-n$ of those elements are copied from $[first1, last1)$, otherwise the last $n-m$ elements are copied from $[first2, last2)$. The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator and sequential execution.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *set_symmetric_difference* algorithm returns a *hpx::future<FwdIter3>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter3* otherwise. The *set_symmetric_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =  
hpx::parallel::detail::less>  
FwdIter3 hpx::set_symmetric_difference(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2,  
FwdIter3 dest, Pred &&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in either of the sorted ranges [*first1*, *last1*) and [*first2*, *last2*), but not in both of them are copied to the range beginning at *dest*. The resulting range is also sorted. This algorithm expects both input ranges to be sorted with the given binary predicate *pred*.

If some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), it will be copied to *dest* exactly `std::abs(m-n)` times. If *m*>*n*, then the last *m-n* of those elements are copied from [*first1*,*last1*), otherwise the last *n-m* elements are copied from [*first2*,*last2*). The resulting range cannot overlap with either of the input ranges.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N_1 + N_2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator and sequential execution.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_symmetric_difference* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.

- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *set_symmetric_difference* algorithm returns a *FwdIter3*. The *set_symmetric_difference* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::generate

Defined in header `hpx/algorithm.hpp`⁷²³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::generate_n*

```
template<typename ExPolicy, typename FwdIter, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::generate(ExPolicy &&policy, FwdIter
                                                                    first, FwdIter last, F &&f)
```

Assign each element in range $[first, last)$ a value generated by the given function object *f*. Executed according to the policy.

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *generate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

⁷²³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

`Ret fun();`

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *generate* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise.

```
template<typename FwdIter, typename F>  
void hpx::generate(FwdIter first, FwdIter last, F &&f)
```

Assign each element in range *[first, last)* a value generated by the given function object *f*.

Note: Complexity: Exactly *distance(first, last)* invocations of *f* and assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – generator function that will be called. signature of function should be equivalent to the following:

`Ret fun();`

The type *Ret* must be such that an object of type *FwdIter* can be dereferenced and assigned a value of type *Ret*.

Returns

The *generate* algorithm returns void.

hpx::generate_n

Defined in header `hpx/algorithm.hpp`⁷²⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::generate`

```
template<typename ExPolicy, typename FwdIter, typename Size, typename F>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::generate_n(ExPolicy &&policy, FwdIter
                                                                    first, Size count, F &&f)
```

Assigns each element in range $[first, first+)$ a value generated by the given function object f . Executed according to the policy.

The assignments in the parallel `generate_n` algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel `generate_n` algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *count* invocations of f and assignments, for $count > 0$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires F to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements in the sequence the algorithm will be applied to.
- **f** – Refers to the generator function object that will be called. The signature of the function should be equivalent to

Ret `fun()`;

The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

⁷²⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *generate_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. *generate_n* algorithm returns iterator one past the last element assigned if *count*>0, first otherwise.

```
template<typename FwdIter, typename Size, typename F>  
FwdIter hpx::generate_n(FwdIter first, Size count, F &&f)
```

Assigns each element in range [*first*, *first*+) a value generated by the given function object *f*.

Note: Complexity: Exactly *count* invocations of *f* and assignments, for *count* > 0.

Template Parameters

- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements in the sequence the algorithm will be applied to.
- **f** – Refers to the generator function object that will be called. The signature of the function should be equivalent to

```
Ret fun();
```

The type *Ret* must be such that an object of type *OutputIt* can be dereferenced and assigned a value of type *Ret*.

Returns

The *generate_n* algorithm returns a *FwdIter*. *generate_n* algorithm returns iterator one past the last element assigned if *count*>0, first otherwise.

hpx::reverse

Defined in header [hpx/algorithm.hpp](#)⁷²⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::reverse_copy*

```
template<typename BidirIter>
```

⁷²⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

void **hpx::reverse**(*BidirIter* first, *BidirIter* last)

Reverses the order of the elements in the range [first, last). Behaves as if applying *std::iter_swap* to every pair of iterators first+i, (last-i) - 1 for each non-negative i < (last-first)/2.

The assignments in the parallel *reverse* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

BidirIter – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns *void*.

template<typename **ExPolicy**, typename **BidirIter**>

hpx::parallel::util::detail::algorithm_result_t<*ExPolicy*, void> **hpx::reverse**(*ExPolicy* &&policy, *BidirIter* first, *BidirIter* last)

Reverses the order of the elements in the range [first, last). Behaves as if applying *std::iter_swap* to every pair of iterators first+i, (last-i) - 1 for each non-negative i < (last-first)/2. Executed according to the policy.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reverse* algorithm returns a `hpx::future<void>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

hpx::reverse_copy

Defined in header `hpx/algorithm.hpp`⁷²⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::reverse`

template<typename **BidirIter**, typename **OutIter**>

OutIter **hpx::reverse_copy**(*BidirIter* first, *BidirIter* last, *OutIter* dest)

Copies the elements from the range [first, last) to another range beginning at dest in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment $*(dest + (last - first) - 1 - i) = *(first + i)$ once for each non-negative $i < (last - first)$. If the source and destination ranges (that is, [first, last) and [dest, dest+(last-first)) respectively) overlap, the behavior is undefined.

The assignments in the parallel *reverse_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns an *OutIter*. The *reverse_copy* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

template<typename **ExPolicy**, typename **BidirIter**, typename **FwdIter**>

hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> **hpx::reverse_copy**(*ExPolicy* &&policy, *BidirIter* first, *BidirIter* last, *FwdIter* dest)

Copies the elements from the range [first, last) to another range beginning at dest in such a way that the elements in the new range are in reverse order. Behaves as if by executing the assignment $*(dest + (last - first) - 1 - i) = *(first + i)$ once for each non-negative $i < (last - first)$. If the source and destination ranges (that is, [first, last) and [dest, dest+(last-first)) respectively) overlap, the behavior is undefined. Executed according to the policy.

⁷²⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *reverse_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the begin of the destination range.

Returns

The *reverse_copy* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *reverse_copy* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::search

Defined in header [hpx/algorithm.hpp](#)⁷²⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::search_n*

```
template<typename FwdIter, typename FwdIter2, typename Pred = parallel::detail::equal_to>
FwdIter hpx::search(FwdIter first, FwdIter last, FwdIter2 s_first, FwdIter2 s_last, Pred &&op = Pred())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search* algorithm execute in sequential order in the calling thread.

⁷²⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: at most $(S*N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *search* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

<pre>bool pred(const Type1 &a, const Type2 &b);</pre>

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *search* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence $[s_first, s_last)$ in range $[first, last)$. If the length of the subsequence $[s_first, s_last)$ is greater than the length of the range $[first, last)$, *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename ExPolicy, typename FwdIter, typename FwdIter2, typename Pred =
parallel::detail::equal_to>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::search(ExPolicy &&policy, FwdIter first,
FwdIter last, FwdIter2 s_first,
FwdIter2 s_last, Pred &&op =
Pred())
```

Searches the range $[first, last)$ for any elements in the range $[s_first, s_last)$. Uses a provided predicate to compare elements. Executed according to the policy.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(S*N)$ comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{distance}(first, last)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *search* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *search* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search* algorithm returns an iterator to the beginning of the first subsequence $[s_first, s_last)$ in range $[first, last)$. If the length of the subsequence $[s_first, s_last)$ is greater than the length of the range $[first, last)$, *last* is returned. Additionally if the size of the subsequence is empty *first* is returned. If no subsequence is found, *last* is returned.

```
template<typename FwdIter, typename Searcher>
FwdIter hpx::search(FwdIter first, FwdIter last, Searcher &&searcher)
    Searches the range  $[first, last)$  using a searcher object.
```

Template Parameters

- **FwdIter** – The type of the source iterators (deduced). This iterator type must meet the requirements of a forward iterator.
- **Searcher** – A callable searcher object meeting the C++ Searcher requirements (e.g. `std::boyer_moore_searcher`).

Parameters

- **first** – Refers to the beginning of the sequence to search.
- **last** – Refers to the end of the sequence to search.
- **searcher** – A callable object performing the search.

Returns

An iterator to the beginning of the found subsequence, or *last* if no subsequence is found.

```
template<typename ExPolicy, typename FwdIter, typename Searcher>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::search(ExPolicy &&policy, FwdIter first,  
                                                                    FwdIter last, Searcher  
                                                                    &&searcher)
```

Searches the range [first, last) using a searcher object. Executed according to the policy.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced).
- **FwdIter** – The type of the source iterators (deduced).
- **Searcher** – A callable searcher object meeting the C++ Searcher requirements.

Parameters

- **policy** – The execution policy to use.
- **first** – Refers to the beginning of the sequence to search.
- **last** – Refers to the end of the sequence to search.
- **searcher** – A callable object performing the search.

Returns

The algorithm returns a *hpx::future<FwdIter>* if the execution policy is a task policy, or *FwdIter* otherwise.

`hpx::search_n`

Defined in header `hpx/algorithm.hpp`⁷²⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::search*

```
template<typename FwdIter, typename FwdIter2, typename Pred = parallel::detail::equal_to>
```

⁷²⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

FwdIter **hpx::search_n**(*FwdIter* first, *std::size_t* count, *FwdIter2* s_first, *FwdIter2* s_last, *Pred* &&op = *Pred*())

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements.

The comparison operations in the parallel *search_n* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most ($S \cdot N$) comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{count}$.

Template Parameters

- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *search_n* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to *std::equal_to*<>

Parameters

- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **count** – Refers to the range of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have const &, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *search_n* algorithm returns *FwdIter*. The *search_n* algorithm returns an iterator to the beginning of the last subsequence [s_first, s_last) in range [first, first+count). If the length of the subsequence [s_first, s_last) is greater than the length of the range [first, first+count), *first* is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *first* is also returned.

```
template<typename ExPolicy, typename FwdIter, typename FwdIter2, typename Pred =
parallel::detail::equal_to>
```

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::search_n(ExPolicy &&policy, FwdIter
first, std::size_t count, FwdIter2
s_first, FwdIter2 s_last, Pred
&&op = Pred())
```

Searches the range [first, last) for any elements in the range [s_first, s_last). Uses a provided predicate to compare elements. Executed according to the policy.

The comparison operations in the parallel *search_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *search_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most ($S \cdot N$) comparisons where $S = \text{distance}(s_first, s_last)$ and $N = \text{count}$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *search_n* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **count** – Refers to the range of elements of the first range the algorithm will be applied to.
- **s_first** – Refers to the beginning of the sequence of elements the algorithm will be searching for.
- **s_last** – Refers to the end of the sequence of elements of the algorithm will be searching for.
- **op** – Refers to the binary predicate which returns true if the elements should be treated as equal. the signature of the function should be equivalent to

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *search_n* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *search_n* algorithm returns an iterator to the beginning of the last subsequence [s_first, s_last) in range [first, first+count). If the length of the subsequence [s_first, s_last) is greater than the length of the range [first, first+count),

first is returned. Additionally if the size of the subsequence is empty or no subsequence is found, *first* is also returned.

hpx::experimental::reduction_multiplies

Defined in header `hpx/algorithm.hpp`⁷²⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::multiplies<T>> hpx::experimental::reduction_multiplies(T
&var)
```

The function template *reduction_multiplies* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::multiplies{ }` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_multiplies* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::multiplies{ }` operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of *identity*, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
```

⁷²⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
constexpr hpx::parallel::detail::reduction_helper<T, std::multiplies<T>> hpx::experimental::reduction_multiplies(T
                                                                    &var,
                                                                    T
                                                                    const
                                                                    &iden-
                                                                    tity)
```

hpx::uninitialized_fill

Defined in header [hpx/algorithm.hpp](#)⁷³⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::uninitialized_fill_n`

```
template<typename FwdIter, typename T>
void hpx::uninitialized_fill(FwdIter first, FwdIter last, T const &value)
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns nothing

```
template<typename ExPolicy, typename FwdIter, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::uninitialized_fill(ExPolicy &&policy, FwdIter
                                                                    first, FwdIter last, T const
                                                                    &value)
```

Copies the given *value* to an uninitialized memory area, defined by the range [first, last). If an exception is thrown during the initialization, the function has no effects. Executed according to the policy.

The initializations in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁷³⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The initializations in the parallel *uninitialized_fill* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns nothing otherwise.

hpx::uninitialized_fill_n

Defined in header [hpx/algorithm.hpp](#)⁷³¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::uninitialized_fill*

```
template<typename FwdIter, typename Size, typename T>
FwdIter hpx::uninitialized_fill_n(FwdIter first, Size count, T const &value)
```

Copies the given *value* value to the first count elements in an uninitialized memory area beginning at first. If an exception is thrown during the initialization, the function has no effects.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

⁷³¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **T** – The type of the value to be assigned (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill_n* algorithm returns a *FwdIter*. The *uninitialized_fill_n* algorithm returns the output iterator to the element in the range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename T>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::uninitialized_fill_n(ExPolicy  
                                                                                          &&policy,  
                                                                                          FwdIter first,  
                                                                                          Size count, T  
                                                                                          const &value)
```

Copies the given *value* value to the first count elements in an uninitialized memory area beginning at first. If an exception is thrown during the initialization, the function has no effects. Executed according to the policy.

The initializations in the parallel *uninitialized_fill_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The initializations in the parallel *uninitialized_fill_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **T** – The type of the value to be assigned (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **value** – The value to be assigned.

Returns

The *uninitialized_fill_n* algorithm returns a `hpx::future<FwdIter>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `FwdIter` otherwise. The *uninitialized_fill_n* algorithm returns the output iterator to the element in the range, one past the last element copied.

hpx::copy

Defined in header `hpx/algorithm.hpp`⁷³².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::copy_n`
- `hpx::copy_if`

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::copy(ExPolicy &&policy, FwdIter1 first,
                                                                              FwdIter1 last, FwdIter2 dest)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Executed according to the policy.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

⁷³² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *copy* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2>
FwdIter2 hpx::copy(FwdIter1 first, FwdIter1 last, FwdIter2 dest)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy* algorithm returns a *FwdIter2*. The *copy* algorithm returns the pair of the input iterator *last* and the output iterator to the element in the destination range, one past the last element copied.

hpx::copy_n

Defined in header [hpx/algorithm.hpp](#)⁷³³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::copy*
- *hpx::copy_if*

```
template<typename ExPolicy, typename FwdIter1, typename Size, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::copy_n(ExPolicy &&policy, FwdIter1
                                                                    first, Size count, FwdIter2 dest)
```

Copies the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at *dest*. Executed according to the policy.

The assignments in the parallel *copy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁷³³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *copy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy_n* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *copy_n* algorithm returns Iterator in the destination range, pointing past the last element copied if *count*>0 or result otherwise.

```
template<typename FwdIter1, typename Size, typename FwdIter2>
FwdIter2 hpx::copy_n(FwdIter1 first, Size count, FwdIter2 dest)
```

Copies the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.

- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *copy_n* algorithm returns a *FwdIter2*. The *copy_n* algorithm returns Iterator in the destination range, pointing past the last element copied if count>0 or result otherwise.

hpx::copy_if

Defined in header [hpx/algorithm.hpp](#)⁷³⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::copy*
- *hpx::copy_n*

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::copy_if(ExPolicy &&policy, FwdIter1  
first, FwdIter1 last, FwdIter2  
dest, Pred &&pred)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the predicate *f* returns true. The order of the elements that are not removed is preserved. Executed according to the policy.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *f*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

⁷³⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

Returns

The *copy_if* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *copy_if* algorithm returns output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename Pred>
FwdIter2 hpx::copy_if(FwdIter1 first, FwdIter1 last, FwdIter2 dest, Pred &&pred)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the predicate *f* returns true. The order of the elements that are not removed is preserved.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *f*.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *copy_if* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

Returns

The *copy_if* algorithm returns a *FwdIter2*. The *copy_if* algorithm returns output iterator to the element in the destination range, one past the last element copied.

hpx::is_heap

Defined in header `hpx/algorithm.hpp`⁷³⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::is_heap_until`

```
template<typename ExPolicy, typename RandIter, typename Comp = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::is_heap(ExPolicy &&policy, RandIter first,
                                     RandIter last, Comp &&comp =
                                     Comp())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using `operator<()`). Executed according to the policy.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

⁷³⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.

Returns

The *is_heap* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

```
template<typename RandIter, typename Comp = hpx::parallel::detail::less>
bool hpx::is_heap(RandIter first, RandIter last, Comp &&comp = Comp())
```

Returns whether the range is max heap. That is, true if the range is max heap, false otherwise. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.

Returns

The *is_heap* a *bool*. The *is_heap* algorithm returns whether the range is max heap. That is, true if the range is max heap, false otherwise.

hpx::is_heap_until

Defined in header [hpx/algorithm.hpp](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp)⁷³⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::is_heap*

```
template<typename ExPolicy, typename RandIter, typename Comp = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, RandIter> hpx::is_heap_until(ExPolicy &&policy,
                                                                                       RandIter first, RandIter
                                                                                       last, Comp &&comp =
                                                                                       Comp())
```

⁷³⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap. The function uses the given comparison function object *comp* (defaults to using operator<()). Executed according to the policy.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.

Returns

The *is_heap_until* algorithm returns a *hpx::future<RandIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandIter* otherwise. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap.

```
template<typename RandIter, typename Comp = hpx::parallel::detail::less>
```

```
RandIter hpx::is_heap_until(RandIter first, RandIter last, Comp &&comp = Comp())
```

Returns the upper bound of the largest range beginning at *first* which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap. The function uses the given comparison function object *comp* (defaults to using operator<()).

comp has to induce a strict weak ordering on the values.

Note: Complexity: Linear in the distance between *first* and *last*.

Template Parameters

- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.

Returns

The *is_heap_until* algorithm returns a *RandIter*. The *is_heap_until* algorithm returns the upper bound of the largest range beginning at first which is a max heap. That is, the last iterator *it* for which range [first, it) is a max heap.

hpx::merge

Defined in header [hpx/algorithm.hpp](#)⁷³⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::inplace_merge*

```
template<typename ExPolicy, typename RandIter1, typename RandIter2, typename RandIter3, typename
Comp = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, RandIter3> hpx::merge(ExPolicy &&policy, RandIter1
first1, RandIter1 last1, RandIter2
first2, RandIter2 last2, RandIter3
dest, Comp &&comp = Comp())
```

Merges two sorted ranges [first1, last1) and [first2, last2) into one sorted range beginning at *dest*. The order of equivalent elements in each of the original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges. Executed according to the policy.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and each projection.

⁷³⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandIter1** – The type of the source iterators used (deduced) representing the first sorted range. This iterator type must meet the requirements of a random access iterator.
- **RandIter2** – The type of the source iterators used (deduced) representing the second sorted range. This iterator type must meet the requirements of a random access iterator.
- **RandIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first range of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first range of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second range of elements the algorithm will be applied to.
- **last2** – Refers to the end of the second range of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *RandIter1* and *RandIter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

Returns

The *merge* algorithm returns a `hpx::future<RandIter3>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandIter3* otherwise. The *merge* algorithm returns the destination iterator to the end of the *dest* range.

```
template<typename RandIter1, typename RandIter2, typename RandIter3, typename Comp =  
hpx::parallel::detail::less>  
RandIter3 hpx::merge(RandIter1 first1, RandIter1 last1, RandIter2 first2, RandIter2 last2, RandIter3 dest, Comp  
                    &&comp = Comp())
```

Merges two sorted ranges `[first1, last1)` and `[first2, last2)` into one sorted range beginning at *dest*. The order of equivalent elements in each of the original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. The destination range cannot overlap with either of the input ranges.

Note: Complexity: Performs $O(\text{std::distance}(\text{first1}, \text{last1}) + \text{std::distance}(\text{first2}, \text{last2}))$ applications of the comparison *comp* and each projection.

Template Parameters

- **RandIter1** – The type of the source iterators used (deduced) representing the first sorted range. This iterator type must meet the requirements of a random access iterator.
- **RandIter2** – The type of the source iterators used (deduced) representing the second sorted range. This iterator type must meet the requirements of a random access iterator.
- **RandIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the first range of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first range of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second range of elements the algorithm will be applied to.
- **last2** – Refers to the end of the second range of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *RandIter1* and *RandIter2* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

Returns

The *merge* algorithm returns a *RandIter3*. The *merge* algorithm returns the destination iterator to the end of the *dest* range.

hpx::inplace_merge

Defined in header `hpx/algorithm.hpp`⁷³⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::merge*

template<typename **ExPolicy**, typename **RandIter**, typename **Comp** = *hpx::parallel::detail::less*>

⁷³⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::inplace_merge(ExPolicy &&policy, RandIter first,
                                                                              RandIter middle, RandIter last,
                                                                              Comp &&comp = Comp())
```

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in each of the original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range. Executed according to the policy.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *inplace_merge* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and each projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *RandIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

Returns

The *inplace_merge* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns void otherwise. The *inplace_merge* algorithm returns the source iterator *last*.

```
template<typename RandIter, typename Comp = hpx::parallel::detail::less>
```

void **hpx::inplace_merge**(*RandIter* first, *RandIter* middle, *RandIter* last, *Comp* &&comp = *Comp*())

Merges two consecutive sorted ranges [first, middle) and [middle, last) into one sorted range [first, last). The order of equivalent elements in each of the original two ranges is preserved. For equivalent elements in the original two ranges, the elements from the first range precede the elements from the second range.

Note: Complexity: Performs $O(\text{std::distance}(\text{first}, \text{last}))$ applications of the comparison *comp* and each projection.

Template Parameters

- **RandIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *inplace_merge* requires *Comp* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **middle** – Refers to the end of the first sorted range and the beginning of the second sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **comp** – *comp* is a callable object which returns true if the first argument is less than the second, and false otherwise. The signature of this comparison should be equivalent to:

```
bool comp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *RandIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

Returns

The *inplace_merge* algorithm returns a *void*. The *inplace_merge* algorithm returns the source iterator *last*.

hpx::remove

Defined in header `hpx/algorithm.hpp`⁷³⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::remove_if*

```
template<typename FwdIter, typename T = typename std::iterator_traits<FwdIter>::value_type>
FwdIter hpx::remove(FwdIter first, FwdIter last, T const &value)
```

Removes all elements satisfying specific criteria from the range [first, last) and returns a past-the-end iterator for the new end of the range. This version removes all elements that are equal to *value*.

The assignments in the parallel *remove* algorithm execute in sequential order in the calling thread.

⁷³⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the `operator==()`.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.

Returns

The *remove* algorithm returns a *FwdIter*. The *remove* algorithm returns the iterator to the new end of the range.

```
template<typename ExPolicy, typename FwdIter, typename T = typename  
std::iterator_traits<FwdIter::value_type>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::remove(ExPolicy &&policy, FwdIter first,  
                                         FwdIter last, T const &value)
```

Removes all elements satisfying specific criteria from the range [first, last) and returns a past-the-end iterator for the new end of the range. This version removes all elements that are equal to *value*. Executed according to the policy.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the `operator==()`.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to remove (deduced). This value type must meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – Specifies the value of elements to remove.

Returns

The *remove* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *remove* algorithm returns the iterator to the new end of the range.

hpx::remove_if

Defined in header [hpx/algorithm.hpp](#)⁷⁴⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::remove*

template<typename **FwdIter**, typename **Pred**>

FwdIter **hpx::remove_if**(*FwdIter* first, *FwdIter* last, *Pred* &&pred)

Removes all elements satisfying specific criteria from the range [first, last) and returns a past-the-end iterator for the new end of the range. This version removes all elements for which predicate *pred* returns true.

The assignments in the parallel *remove_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_if* requires *Pred* to meet the requirements of *Copy-Constructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

⁷⁴⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *remove_if* algorithm returns a *FwdIter*. The *remove_if* algorithm returns the iterator to the new end of the range.

```
template<typename ExPolicy, typename FwdIter, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::remove_if(ExPolicy &&policy, FwdIter
                                                                    first, FwdIter last, Pred
                                                                    &&pred)
```

Removes all elements satisfying specific criteria from the range [first, last) and returns a past-the-end iterator for the new end of the range. This version removes all elements for which predicate *pred* returns true. Executed according to the policy.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_if* requires *Pred* to meet the requirements of *Copy-Constructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *remove_if* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *remove_if* algorithm returns the iterator to the new end of the range.

hpx::starts_with

Defined in header `hpx/algorithm.hpp`⁷⁴¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter1, typename InIter2, typename Pred = hpx::parallel::detail::equal_to>
bool hpx::starts_with(InIter1 first1, InIter1 last1, InIter2 first2, InIter2 last2, Pred &&pred = Pred())
```

Checks whether the second range defined by `[first1, last1)` matches the prefix of the first range defined by `[first2, last2)`.

The assignments in the parallel *starts_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most $\min(N1, N2)$ applications of the predicate.

Template Parameters

- **InIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the destination iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The binary predicate that compares the elements. This defaults to `hpx::parallel::detail::equal_to`.

Parameters

- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the two ranges.

Returns

The *starts_with* algorithm returns *bool*. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

```
template<typename ExPolicy, typename InIter1, typename InIter2, typename Pred = ranges::equal_to>
```

⁷⁴¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::starts_with(ExPolicy &&policy, InIter1
                                                                    first1, InIter1 last1, InIter2
                                                                    first2, InIter2 last2, Pred
                                                                    &&pred = Pred())
```

Checks whether the second range defined by [first1, last1) matches the prefix of the first range defined by [first2, last2). Executed according to the policy.

The assignments in the parallel *starts_with* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear: at most min(N1, N2) applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **InIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the destination iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The binary predicate that compares the elements. This defaults to *ranges::equal_to*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the source range.
- **last1** – Sentinel value referring to the end of the source range.
- **first2** – Refers to the beginning of the destination range.
- **last2** – Sentinel value referring to the end of the destination range.
- **pred** – Specifies the binary predicate function (or function object) which will be invoked for comparison of the elements in the two ranges.

Returns

The *starts_with* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *starts_with* algorithm returns a boolean with the value true if the second range matches the prefix of the first range, false otherwise.

hpx::set_union

Defined in header [hpx/algorithm.hpp](#)⁷⁴².

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =
hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter3> hpx::set_union(ExPolicy &&policy, FwdIter1
first1, FwdIter1 last1,
FwdIter2 first2, FwdIter2
last2, FwdIter3 dest, Pred
&&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in one or both sorted ranges $[first1, last1)$ and $[first2, last2)$. This algorithm expects both input ranges to be sorted with the given binary predicate *pred*. Executed according to the policy.

If some element is found m times in $[first1, last1)$ and n times in $[first2, last2)$, then all m elements will be copied from $[first1, last1)$ to *dest*, preserving order, and then exactly $\text{std::max}(n-m, 0)$ elements will be copied from $[first2, last2)$ to *dest*, also preserving order.

The resulting range cannot overlap with either of the input ranges.

The application of function objects in parallel algorithm invoked with a sequential execution policy object execute in sequential order in the calling thread (*sequenced_policy*) or in a single new thread spawned from the current thread (for *sequenced_task_policy*).

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1$ is the length of the first sequence and $N2$ is the length of the second sequence.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator and sequential execution.
- **Op** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_union* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

⁷⁴² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*.

Returns

The *set_union* algorithm returns a *hpx::future<FwdIter3>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter3* otherwise. The *set_union* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred =  
hpx::parallel::detail::less>  
FwdIter3 hpx::set_union(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, FwdIter3 dest, Pred  
                        &&op = Pred())
```

Constructs a sorted range beginning at *dest* consisting of all elements present in one or both sorted ranges [*first1*, *last1*) and [*first2*, *last2*). This algorithm expects both input ranges to be sorted with the given binary predicate *pred*. Executed according to the policy.

If some element is found *m* times in [*first1*, *last1*) and *n* times in [*first2*, *last2*), then all *m* elements will be copied from [*first1*, *last1*) to *dest*, preserving order, and then exactly `std::max(n-m, 0)` elements will be copied from [*first2*, *last2*) to *dest*, also preserving order.

The resulting range cannot overlap with either of the input ranges.

Note: Complexity: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where *N1* is the length of the first sequence and *N2* is the length of the second sequence.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators used (deduced) representing the first sequence. This iterator type must meet the requirements of a forward iterator.

- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator or output iterator and sequential execution.
- **Op** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *set_union* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – The binary predicate which returns true if the elements should be treated as equal. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type1* must be such that objects of type *FwdIter* can be dereferenced and then implicitly converted to *Type1*

Returns

The *set_union* algorithm returns a *FwdIter3*. The *set_union* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::swap_ranges

Defined in header `hpx/algorithm.hpp`⁷⁴³.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter1, typename FwdIter2>
```

```
FwdIter2 hpx::swap_ranges(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2)
```

Exchanges elements between range `[first1, last1)` and another range starting at *first2*.

The swap operations in the parallel *swap_ranges* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first1* and *last1*.

Template Parameters

⁷⁴³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter1** – The type of the first range of iterators to swap (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the second range of iterators to swap (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.

Returns

The *swap_ranges* algorithm returns *FwdIter2*. The *swap_ranges* algorithm returns iterator to the element past the last element exchanged in the range beginning with *first2*.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::swap_ranges(ExPolicy &&policy,  
                                                                                      FwdIter1 first1, FwdIter1  
                                                                                      last1, FwdIter2 first2)
```

Exchanges elements between range [first1, last1) and another range starting at *first2*. Executed according to the policy.

The swap operations in the parallel *swap_ranges* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The swap operations in the parallel *swap_ranges* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first1* and *last1*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the swap operations.
- **FwdIter1** – The type of the first range of iterators to swap (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the second range of iterators to swap (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.

Returns

The *swap_ranges* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *parallel_task_policy* and returns *FwdIter2* otherwise. The *swap_ranges* algorithm returns iterator to the element past the last element exchanged in the range beginning with *first2*.

hpx::experimental::reduction_bit_xor

Defined in header [hpx/algorithm.hpp](#)⁷⁴⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

template<typename T>

constexpr *hpx::parallel::detail::reduction_helper<T, std::bit_xor<T>>* *hpx::experimental::reduction_bit_xor*(T &var)

The function template *reduction_bit_xor* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::bit_xor{ }` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_bit_xor* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::bit_xor{ }` operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

⁷⁴⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::bit_xor<T>> hpx::experimental::reduction_bit_xor(T
                                                                    &var,
                                                                    T
                                                                    const
                                                                    &identity)
```

hpx::shift_right

Defined in header [hpx/algorithm.hpp](#)⁷⁴⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter, typename Size>
FwdIter hpx::shift_right(FwdIter first, FwdIter last, Size n)
```

Shifts the elements in the range `[first, last)` by `n` positions towards the end of the range. For every integer `i` in `[0, last - first - n)`, moves the element originally at position `first + i` to position `first`

- `n + i`.

The assignment operations in the parallel *shift_right* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: At most $(last - first) - n$ assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns *FwdIter*. The *shift_right* algorithm returns an iterator to the beginning of the resulting range. Specifically: If `n` is 0 or `n >= (last - first)`, does nothing and returns *first* and *last* respectively. Otherwise returns *first + n*.

```
template<typename ExPolicy, typename FwdIter, typename Size>
```

⁷⁴⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter> hpx::shift_right(ExPolicy &&policy, FwdIter
                                                                    first, FwdIter last, Size n)
```

Shifts the elements in the range `[first, last)` by `n` positions towards the end of the range. For every integer `i` in `[0, last - first - n)`, moves the element originally at position `first + i` to position `first`

- `n + i`. Executed according to the policy.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignment operations in the parallel *shift_right* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(last - first) - n$ assignments.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of positions to shift by.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **n** – Refers to the number of positions to shift.

Returns

The *shift_right* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *shift_right* algorithm returns an iterator to the beginning of the resulting range. Specifically: If *n* is 0, does nothing and returns *first*. If $n \geq (last - first)$, does nothing and returns *last*. Otherwise returns *first + n*.

hpx::partial_sort

Defined in header [hpx/algorithm.hpp](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp)⁷⁴⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename RandIter, typename Comp = hpx::parallel::detail::less>
```

```
RandIter hpx::partial_sort(RandIter first, RandIter middle, RandIter last, Comp &&comp = Comp())
```

Places the first middle - first elements from the range [first, last) as sorted with respect to comp into the range [first, middle). The rest of the elements in the range [middle, last) are placed in an unspecified order.

Note: Complexity: Approximately (last - first) * log(middle - first) comparisons.

Template Parameters

- **RandIter** – The type of the source begin, middle, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). Comp defaults to detail::less.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator. It defaults to detail::less.

Returns

The *partial_sort* algorithm returns a *RandIter* that refers to *last*.

```
template<typename ExPolicy, typename RandIter, typename Comp = hpx::parallel::detail::less>
```

```
parallel::util::detail::algorithm_result_t<ExPolicy, RandIter> hpx::partial_sort(ExPolicy &&policy, RandIter  
first, RandIter middle,  
RandIter last, Comp &&comp  
= Comp())
```

Places the first middle - first elements from the range [first, last) as sorted with respect to comp into the range [first, middle). The rest of the elements in the range [middle, last) are placed in an unspecified order.

Note: Complexity: Approximately (last - first) * log(middle - first) comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.

⁷⁴⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **RandIter** – The type of the source begin, middle, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced). `Comp` defaults to `detail::less`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **middle** – Refers to the middle of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. It defaults to `detail::less`.

Returns

The *partial_sort* algorithm returns a `hpx::future<RandIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandIter* otherwise. The iterator returned refers to *last*.

hpx::partial_sort_copy

Defined in header `hpx/algorithm.hpp`⁷⁴⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter, typename RandIter, typename Comp = hpx::parallel::detail::less>
RandIter hpx::partial_sort_copy(InIter first, InIter last, RandIter d_first, RandIter d_last, Comp &&comp =
    Comp())
```

Sorts some of the elements in the range `[first, last)` in ascending order, storing the result in the range `[d_first, d_last)`. At most `d_last - d_first` of the elements are placed sorted to the range `[d_first, d_first + n)` where `n` is the number of elements to sort (`n = min(last - first, d_last - d_first)`).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{d_first}, \text{d_last})$ comparisons.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.

⁷⁴⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **RandIter** – The type of the destination iterators used (deduced). This iterator type must meet the requirements of a random iterator.
- **Comp** – The type of the function/function object to use (deduced). `Comp` defaults to `detail::less`.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **d_first** – Refers to the beginning of the destination range.
- **d_last** – Refers to the end of the destination range.
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. This defaults to `detail::less`.

Returns

The *partial_sort_copy* algorithm returns a *RandomIt*. The algorithm returns an iterator to the element defining the upper boundary of the sorted range i.e. `d_first + min(last - first, d_last - d_first)`

```
template<typename ExPolicy, typename FwdIter, typename RandIter, typename Comp =  
hpx::parallel::detail::less>  
parallel::util::detail::algorithm_result_t<ExPolicy, RandIter> hpx::partial_sort_copy(ExPolicy &&policy,  
FwdIter first, FwdIter  
last, RandIter d_first,  
RandIter d_last, Comp  
&&comp = Comp())
```

Sorts some of the elements in the range `[first, last)` in ascending order, storing the result in the range `[d_first, d_last)`. At most `d_last - d_first` of the elements are placed sorted to the range `[d_first, d_first + n)` where `n` is the number of elements to sort (`n = min(last - first, d_last - d_first)`). Executed according to the policy.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(\min(D, N)))$, where $N = \text{std::distance}(\text{first}, \text{last})$ and $D = \text{std::distance}(\text{d_first}, \text{d_last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

- **RandIter** – The type of the destination iterators used (deduced). This iterator type must meet the requirements of a random iterator.
- **Comp** – The type of the function/function object to use (deduced). `Comp` defaults to `detail::less`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **d_first** – Refers to the beginning of the destination range.
- **d_last** – Refers to the end of the destination range.
- **comp** – `comp` is a callable object. The return value of the `INVOKE` operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator. This defaults to `detail::less`.

Returns

The *partial_sort_copy* algorithm returns a `hpx::future<RandomIt>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *RandomIt* otherwise. The algorithm returns an iterator to the element defining the upper boundary of the sorted range i.e. `d_first + min(last - first, d_last - d_first)`

hpx::lexicographical_compare

Defined in header `hpx/algorithm.hpp`⁷⁴⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter1, typename InIter2, typename Pred = hpx::parallel::detail::less>
bool hpx::lexicographical_compare(InIter1 first1, InIter1 last1, InIter2 first2, InIter2 last2, Pred &&pred)
```

Checks if the first range `[first1, last1)` is lexicographically less than the second range `[first2, last2)`. uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{first1}, \text{last})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
- The first mismatching element defines which range is lexicographically *less* or *greater* than the other
- If one range is a prefix of another, the shorter range is lexicographically *less* than the other

⁷⁴⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **InIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to

Returns

The *lexicographically_compare* algorithm returns a *bool* if the execution policy object is not passed in. The *lexicographically_compare* algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred =  
hpx::parallel::detail::less>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::lexicographical_compare(ExPolicy  
                                                    &&policy,  
                                                    FwdIter1 first1,  
                                                    FwdIter1 last1,  
                                                    FwdIter2 first2,  
                                                    FwdIter2 last2,  
                                                    Pred &&pred)
```

Checks if the first range [first1, last1) is lexicographically less than the second range [first2, last2). uses a provided predicate to compare elements.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *lexicographical_compare* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 * \min(N1, N2)$ applications of the comparison operation, where $N1 = \text{std::distance}(\text{first1}, \text{last})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Note: Lexicographical comparison is an operation with the following properties

- Two ranges are compared element by element
 - The first mismatching element defines which range is lexicographically *less* or *greater* than the other
 - If one range is a prefix of another, the shorter range is lexicographically *less* than the other
 - If two ranges have equivalent elements and are of the same length, then the ranges are lexicographically *equal*
 - An empty range is lexicographically *less* than any non-empty range
 - Two empty ranges are lexicographically *equal*
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *lexicographical_compare* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **pred** – Refers to the comparison function that the first and second ranges will be applied to

Returns

The *lexicographically_compare* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *lexicographically_compare* algorithm returns true if the first range is lexicographically less, otherwise it returns false. range [first2, last2), it returns false.

hpx::stable_sort

Defined in header [hpx/algorithm.hpp](#)⁷⁴⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename RandomIt, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>  
void hpx::stable_sort(RandomIt first, RandomIt last, Comp &&comp = Comp(), Proj &&proj = Proj())
```

Sorts the elements in the range [first, last) in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object comp (defaults to using operator<()).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false.

comp has to induce a strict weak ordering on the values.

The assignments in the parallel *stable_sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type Comp, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *stable_sort* algorithm returns *void*.

```
template<typename ExPolicy, typename RandomIt, typename Comp = hpx::parallel::detail::less, typename Proj =  
hpx::identity>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::stable_sort(ExPolicy &&policy, RandomIt first,  
                                                                    RandomIt last, Comp &&comp =  
                                                                    Comp(), Proj &&proj = Proj())
```

Sorts the elements in the range [first, last) in ascending order. The relative order of equal elements is preserved. The function uses the given comparison function object comp (defaults to using operator<()). Executed according to the policy.

⁷⁴⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i + n* is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – `comp` is a callable object. The return value of the `INVOKE` operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *stable_sort* algorithm returns a `hpx::future<void>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

hpx::partition

Defined in header [hpx/algorithm.hpp](#)⁷⁵⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::stable_partition`
- `hpx::partition_copy`

template<typename **FwdIter**, typename **Pred**, typename **Proj** = `hpx::identity`>

FwdIter **hpx::partition**(*FwdIter* first, *FwdIter* last, *Pred* &&pred, *Proj* &&proj = *Proj*())

Reorders the elements in the range [first, last) in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: At most 2 * (last - first) swaps. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

`bool pred(const Type &a);`

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition* algorithm returns *FwdIter*. The *partition* algorithm returns the iterator to the first element of the second group.

⁷⁵⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>


```
template<typename ExPolicy, typename FwdIter, typename Pred, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::partition(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, Pred &&pred, Proj
                                                                    &&proj = Proj())
```

Reorders the elements in the range [first, last) in such a way that all elements for which the predicate *pred* returns true precede the elements for which the predicate *pred* returns false. Relative order of the elements is not preserved.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $2 * (\text{last} - \text{first})$ swaps. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *par-*

allel_task_policy and returns *FwdIter* otherwise. The *partition* algorithm returns the iterator to the first element of the second group.

hpx::stable_partition

Defined in header [hpx/algorithm.hpp](#)⁷⁵¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::partition*
- *hpx::partition_copy*

template<typename **BidirIter**, typename **F**, typename **Proj** = *hpx::identity*>

BidirIter **hpx::stable_partition**(*BidirIter* first, *BidirIter* last, *F* &&*f*, *Proj* &&*proj* = *Proj*())

Permutes the elements in the range [first, last) such that there exists an iterator *i* such that for every iterator *j* in the range [first, *i*) INVOKE(*f*, INVOKE(*proj*, **j*)) != false, and for every iterator *k* in the range [*i*, last), INVOKE(*f*, INVOKE(*proj*, **k*)) == false

The invocations of *f* in the parallel *stable_partition* algorithm invoked without an execution policy object executes in sequential order in the calling thread.

Note: Complexity: At most (last - first) * log(last - first) swaps, but only linear number of swaps if there is enough extra memory. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

⁷⁵¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate f is invoked.

Returns

The *stable_partition* algorithm returns an iterator i such that for every iterator j in the range $[first, i)$, $f(*j) != false$ INVOKE(f , INVOKE($proj$, $*j$)) $!= false$, and for every iterator k in the range $[i, last)$, $f(*k) == false$ INVOKE(f , INVOKE($proj$, $*k$)) $== false$. The relative order of the elements in both groups is preserved.

```
template<typename ExPolicy, typename BidirIter, typename F, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, BidirIter> hpx::stable_partition(ExPolicy &&policy,
                                                                 BidirIter first, BidirIter
                                                                 last, F &&f, Proj &&proj
                                                                 = Proj())
```

Permutes the elements in the range $[first, last)$ such that there exists an iterator i such that for every iterator j in the range $[first, i)$ INVOKE(f , INVOKE($proj$, $*j$)) $!= false$, and for every iterator k in the range $[i, last)$, INVOKE(f , INVOKE($proj$, $*k$)) $== false$

The invocations of f in the parallel *stable_partition* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The invocations of f in the parallel *stable_partition* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $(last - first) * \log(last - first)$ swaps, but only linear number of swaps if there is enough extra memory. Exactly *last - first* applications of the predicate and projection.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of f .
- **BidirIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a bidirectional iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires F to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Unary predicate which returns true if the element should be ordered before other elements. Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by $[first, last)$. The signature of this predicate should be equivalent to:

```
bool fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *BidirIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *f* is invoked.

Returns

The *stable_partition* algorithm returns an iterator *i* such that for every iterator *j* in the range `[first, i)`, `f(*j) != false` `INVOKE(f, INVOKE(proj, *j)) != false`, and for every iterator *k* in the range `[i, last)`, `f(*k) == false` `INVOKE(f, INVOKE(proj, *k)) == false`. The relative order of the elements in both groups is preserved. If the execution policy is of type *parallel_task_policy* the algorithm returns a *future<>* referring to this iterator.

hpx::partition_copy

Defined in header `hpx/algorithm.hpp`⁷⁵².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::partition*
- *hpx::stable_partition*

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred, typename Proj =  
hpx::identity>  
std::pair<FwdIter2, FwdIter3> hpx::partition_copy(FwdIter1 first, FwdIter1 last, FwdIter2 dest_true, FwdIter3  
dest_false, Pred &&pred, Proj &&proj = Proj())
```

Copies the elements in the range, defined by `[first, last)`, to two different ranges depending on the value returned by the predicate *pred*. The elements, that satisfy the predicate *pred* are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.

⁷⁵² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns `std::pair<OutIter1, OutIter2>`. The *partition_copy* algorithm returns the pair of the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename Pred,
typename Proj = hpx::identity>
parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<FwdIter2, FwdIter3>> hpx::partition_copy(ExPolicy
&&policy,
FwdIter1
first,
FwdIter1
last,
FwdIter2
dest_true,
FwdIter3
dest_false,
Pred
&&pred,
Proj
&&proj
=
Proj())
```

Copies the elements in the range, defined by [first, last), to two different ranges depending on the value returned

by the predicate *pred*. The elements, that satisfy the predicate *pred*, are copied to the range beginning at *dest_true*. The rest of the elements are copied to the range beginning at *dest_false*. The order of the elements is preserved.

The assignments in the parallel *partition_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *partition_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range for the elements that satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range for the elements that don't satisfy the predicate *pred* (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *partition_copy* requires *Pred* to meet the requirements of *CopyConstructible*.
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_true** – Refers to the beginning of the destination range for the elements that satisfy the predicate *pred*
- **dest_false** – Refers to the beginning of the destination range for the elements that don't satisfy the predicate *pred*.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate for partitioning the source iterators. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *is* invoked.

Returns

The *partition_copy* algorithm returns a `hpx::future<std::pair<OutIter1, OutIter2>>` if the execution policy is of type *parallel_task_policy* and returns `std::pair<OutIter1, OutIter2>` otherwise. The *partition_copy* algorithm returns the pair of the destination iterator to the end of the *dest_true* range, and the destination iterator to the end of the *dest_false* range.

hpx::experimental::for_loop

Defined in header `hpx/algorithm.hpp`⁷⁵³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::experimental::for_loop_strided`
- `hpx::experimental::for_loop_n`
- `hpx::experimental::for_loop_n_strided`

template<typename **I**, typename ...**Args**>

void **hpx::experimental::for_loop**(std::decay_t<*I*> first, *I* last, *Args*&&... args)

The `for_loop` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last* - *first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

⁷⁵³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Remarks: If f returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

`<ignored> pred(I const& a, ...);`

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename I, typename ...Args>  
auto hpx::experimental::for_loop(ExPolicy &&policy, std::decay_t<I> first, I last, Args&&... args)
```

The `for_loop` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator. Executed according to the policy.

Requires: I shall be an integral type or meet the requirements of an input iterator type. The $args$ parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, f . f shall meet the requirements of *MoveConstructible*.

Effects: Applies f to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the $args$ parameter pack. The length of the input sequence is $last - first$.

The first element in the input sequence is specified by $first$. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the $args$ parameter pack excluding f , an additional argument is passed to each application of f as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of f in the input sequence.

Complexity: Applies f exactly once for each element of the input sequence.

Remarks: If f returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(I const& a, ...);
```

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The *for_loop* algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

hpx::experimental::for_loop_strided

Defined in header `hpx/algorithm.hpp`⁷⁵⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::experimental::for_loop`
- `hpx::experimental::for_loop_n`
- `hpx::experimental::for_loop_n_strided`

template<typename **I**, typename **S**, typename ...**Args**>

void `hpx::experimental::for_loop_strided`(`std::decay_t<I>` first, `I` last, `S` stride, `Args&&...` args)

The `for_loop_strided` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last - first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

⁷⁵⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if I has integral type or meets the requirements of a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(I const& a, ...);
```

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename I, typename S, typename ...Args>
auto hpx::experimental::for_loop_strided(ExPolicy &&policy, std::decay_t<I> first, I last, S stride,
                                         Args&&... args)
```

The `for_loop_strided` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator. Executed according to the policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last - first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if I has integral type or meets the requirements of a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(I const& a, ...);
```

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The *for_loop_strided* algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

hpx::experimental::for_loop_n

Defined in header `hpx/algorithm.hpp`⁷⁵⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::experimental::for_loop`
- `hpx::experimental::for_loop_strided`
- `hpx::experimental::for_loop_n_strided`

```
template<typename I, typename Size, typename ...Args>
void hpx::experimental::for_loop_n(I first, Size size, Args&&... args)
```

The `for_loop_n` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop_n` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last - first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

⁷⁵⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **size** – Refers to the number of items the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

`<ignored> pred(I const& a, ...);`

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename I, typename Size, typename ...Args>  
auto hpx::experimental::for_loop_n(ExPolicy &&policy, I first, Size size, Args&&... args)
```

The `for_loop_n` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator. Executed according to the policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last - first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **size** – Refers to the number of items the algorithm will be applied to.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(I const& a, ...);
```

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The *for_loop_n* algorithm returns a *hpx::future<void>* if the execution policy is of type *hpx::execution::sequenced_task_policy* or *hpx::execution::parallel_task_policy* and returns *void* otherwise.

hpx::experimental::for_loop_n_strided

Defined in header `hpx/algorithm.hpp`⁷⁵⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::experimental::for_loop`
- `hpx::experimental::for_loop_strided`
- `hpx::experimental::for_loop_n`

template<typename **I**, typename **Size**, typename **S**, typename ...**Args**>

void `hpx::experimental::for_loop_n_strided`(*I* first, *Size* size, *S* stride, *Args*&&... args)

The `for_loop_n_strided` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator.

The execution of `for_loop` without specifying an execution policy is equivalent to specifying `hpx::execution::seq` as the execution policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last - first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If *f* returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of *f*, even though the applications themselves may be unordered.

Template Parameters

⁷⁵⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **size** – Refers to the number of items the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if I has integral type or meets the requirements of a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

```
<ignored> pred(I const& a, ...);
```

The signature does not need to have const&. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

```
template<typename ExPolicy, typename I, typename Size, typename S, typename ...Args>
auto hpx::experimental::for_loop_n_strided(ExPolicy &&policy, I first, Size size, S stride, Args&&... args)
```

The `for_loop_n_strided` implements loop functionality over a range specified by integral or iterator bounds. For the iterator case, these algorithms resemble `for_each` from the Parallelism TS, but leave to the programmer when and if to dereference the iterator. Executed according to the policy.

Requires: *I* shall be an integral type or meet the requirements of an input iterator type. The *args* parameter pack shall have at least one element, comprising objects returned by invocations of *reduction* and/or *induction* function templates followed by exactly one element invocable element-access function, *f*. *f* shall meet the requirements of *MoveConstructible*.

Effects: Applies *f* to each element in the input sequence, with additional arguments corresponding to the reductions and inductions in the *args* parameter pack. The length of the input sequence is *last - first*.

The first element in the input sequence is specified by *first*. Each subsequent element is generated by incrementing the previous element.

Along with an element from the input sequence, for each member of the *args* parameter pack excluding *f*, an additional argument is passed to each application of *f* as follows:

If the pack member is an object returned by a call to a reduction function listed in section, then the additional argument is a reference to a view of that reduction object. If the pack member is an object returned by a call to induction, then the additional argument is the induction value for that induction object corresponding to the position of the application of *f* in the input sequence.

Complexity: Applies *f* exactly once for each element of the input sequence.

Remarks: If f returns a result, the result is ignored.

Note: As described in the C++ standard, arithmetic on non-random-access iterators is performed using advance and distance.

Note: The order of the elements of the input sequence is important for determining ordinal position of an application of f , even though the applications themselves may be unordered.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **I** – The type of the iteration variable. This could be an (forward) iterator type or an integral type.
- **Size** – The type of a non-negative integral value specifying the number of items to iterate over.
- **S** – The type of the stride variable. This should be an integral type.
- **Args** – A parameter pack, it's last element is a function object to be invoked for each iteration, the others have to be either conforming to the induction or reduction concept.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **size** – Refers to the number of items the algorithm will be applied to.
- **stride** – Refers to the stride of the iteration steps. This shall have non-zero value and shall be negative only if I has integral type or meets the requirements of a bidirectional iterator.
- **args** – The last element of this parameter pack is the function (object) to invoke, while the remaining elements of the parameter pack are instances of either induction or reduction objects. The function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last) should expose a signature equivalent to:

`<ignored> pred(I const& a, ...);`

The signature does not need to have `const&`. It will receive the current value of the iteration variable and one argument for each of the induction or reduction objects passed to the algorithms, representing their current values.

Returns

The *for_loop_n_strided* algorithm returns a `hpx::future<void>` if the execution policy is of type `hpx::execution::sequenced_task_policy` or `hpx::execution::parallel_task_policy` and returns `void` otherwise.

hpx::sort

Defined in header [hpx/algorithm.hpp](#)⁷⁵⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename RandomIt, typename Comp = hpx::parallel::detail::less, typename Proj = hpx::identity>
void hpx::sort(RandomIt first, RandomIt last, Comp &&comp, Proj &&proj = Proj())
```

Sorts the elements in the range [first, last) in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object comp (defaults to using operator<()).

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false.

comp has to induce a strict weak ordering on the values.

The assignments in the parallel *sort* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: O(N log(N)), where N = std::distance(first, last) comparisons.

Template Parameters

- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – comp is a callable object. The return value of the INVOKE operation applied to an object of type *Comp*, when contextually converted to bool, yields true if the first argument of the call is less than the second, and false otherwise. It is assumed that comp will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *sort* algorithm returns *void*.

```
template<typename ExPolicy, typename RandomIt, typename Comp = hpx::parallel::detail::less, typename Proj =
hpx::identity>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::sort(ExPolicy &&policy, RandomIt first, RandomIt
last, Comp &&comp, Proj &&proj)
```

Sorts the elements in the range [first, last) in ascending order. The order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object comp (defaults to using operator<()). Executed according to the policy.

⁷⁵⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

A sequence is sorted with respect to a comparator *comp* and a projection *proj* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, INVOKE(proj, *(i + n)), INVOKE(proj, *i)) == false`.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **RandomIt** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Comp** – The type of the function/function object to use (deduced).
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **comp** – *comp* is a callable object. The return value of the `INVOKE` operation applied to an object of type *Comp*, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that *comp* will not apply any non-constant function through the dereferenced iterator.
- **proj** – Specifies the function (or function object) which will be invoked for each pair of elements as a projection operation before the actual predicate *comp* is invoked.

Returns

The *sort* algorithm returns a `hpx::future<void>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

hpx::uninitialized_default_construct

Defined in header `hpx/algorithm.hpp`⁷⁵⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::uninitialized_default_construct_n`

template<typename **FwdIter**>

void `hpx::uninitialized_default_construct`(*FwdIter* first, *FwdIter* last)

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects.

The assignments in the parallel `uninitialized_default_construct` algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

FwdIter – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The `uninitialized_default_construct` algorithm returns nothing

template<typename **ExPolicy**, typename **FwdIter**>

`hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::uninitialized_default_construct`(*ExPolicy* &&policy, *FwdIter* first, *FwdIter* last)

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range by default-initialization. If an exception is thrown during the initialization, the function has no effects. Executed according to the policy.

The assignments in the parallel `uninitialized_default_construct` algorithm invoked with an execution policy object of type `sequenced_policy` execute in sequential order in the calling thread.

The assignments in the parallel `uninitialized_default_construct` algorithm invoked with an execution policy object of type `parallel_policy` or `parallel_task_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

⁷⁵⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *uninitialized_default_construct* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns nothing otherwise.

hpx::uninitialized_default_construct_n

Defined in header [hpx/algorithm.hpp](#)⁷⁵⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::uninitialized_default_construct*

template<typename **FwdIter**, typename **Size**>

FwdIter **hpx::uninitialized_default_construct_n**(*FwdIter* first, *Size* count)

Constructs objects of type *typename iterator_traits<ForwardIt>::value_type* in the uninitialized storage designated by the range [first, first + count) by default-initialization. If an exception is thrown during the initialization, the function has no effects.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

⁷⁵⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *uninitialized_default_construct_n* algorithm returns a *FwdIter*. The *uninitialized_default_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename ExPolicy, typename FwdIter, typename Size>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::uninitialized_default_construct_n(ExPolicy
                                                                 &&pol-
                                                                 icy,
                                                                 FwdIter
                                                                 first,
                                                                 Size
                                                                 count)
```

Constructs objects of type `typename iterator_traits<ForwardIt>::value_type` in the uninitialized storage designated by the range `[first, first + count)` by default-initialization. If an exception is thrown during the initialization, the function has no effects. Executed according to the policy.

The assignments in the parallel *uninitialized_default_construct_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_default_construct_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *uninitialized_default_construct_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_default_construct_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::experimental::reduction_bit_or

Defined in header [hpx/algorithm.hpp](#)⁷⁶⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::bit_or<T>> hpx::experimental::reduction_bit_or(T
                                                                    &var)
```

The function template *reduction_bit_or* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::bit_or{ }` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_bit_or* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::bit_or{ }` operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of *identity*, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
```

⁷⁶⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>


```
constexpr hpx::parallel::detail::reduction_helper<T, std::bit_or<T>> hpx::experimental::reduction_bit_or(T
                                                                    &var,
                                                                    T
                                                                    const
                                                                    &iden-
                                                                    tity)
```

hpx::transform_exclusive_scan

Defined in header `hpx/algorithm.hpp`⁷⁶¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter, typename OutIter, typename BinOp, typename UnOp, typename T = typename
std::iterator_traits<InIter>::value_type>
OutIter hpx::transform_exclusive_scan(InIter first, InIter last, OutIter dest, T init, BinOp &&binary_op,
                                     UnOp &&unary_op)
```

Transforms each element in the range $[first, last)$ with *unary_op*, then computes an exclusive prefix sum operation using *binary_op* over the resulting range, with *init* as the initial value, and writes the results to the range beginning at *dest*. “exclusive” means that the *i*-th input element is not included in the *i*-th sum. Formally, assigns through each iterator *i* in $[dest, d_first + (last - first))$ the value of the generalized noncommutative sum of *init*, *unary_op*(**j*)... for every *j* in $[first, first + (i - d_first))$ over *binary_op*, where generalized noncommutative sum $GNSUM(op, a_1, \dots, a_N)$ is defined as follows:

- if $N=1$, a_1
- if $N > 1$, $op(GNSUM(op, a_1, \dots, a_K), GNSUM(op, a_M, \dots, a_N))$ for any K where $1 < K+1 = M \leq N$ In other words, the summation operations may be performed in arbitrary order, and the behavior is nondeterministic if *binary_op* is not associative.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *unary_op* nor *binary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The behavior of *transform_exclusive_scan* may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(last - first)$ applications of each of *binary_op* and *unary_op*.

Note: $GENERALIZED_NONCOMMUTATIVE_SUM(op, a_1, \dots, a_N)$ is defined as:

- a_1 when N is 1
 - $op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a_1, \dots, a_K), GENERALIZED_NONCOMMUTATIVE_SUM(op, a_M, \dots, a_N))$ where $1 < K+1 = M \leq N$.
-

Template Parameters

⁷⁶¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Binary *FunctionObject* that will be applied to the result of *unary_op*, the results of other *binary_op*, and *init*.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.

Returns

The *transform_exclusive_scan* algorithm returns a returns *OutIter*. The *transform_exclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename BinOp, typename UnOp,
typename T = typename std::iterator_traits<FwdIter1>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter2>::type hpx::transform_exclusive_scan(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter1
                                                                                               first,
                                                                                               FwdIter1
                                                                                               last,
                                                                                               FwdIter2
                                                                                               dest, T init,
                                                                                               BinOp
                                                                                               &&bi-
                                                                                               nary_op,
                                                                                               UnOp
                                                                                               &&unary_op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(binary_op, init, conv(*first), ..., conv(*(first + (i - result) - 1))). Executed according to the policy.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_exclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *unary_op* nor *binary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The behavior of `transform_exclusive_scan` may be non-deterministic for a non-associative predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of each of *binary_op* and *unary_op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **init** – The initial value for the generalized sum.
- **binary_op** – Binary *FunctionObject* that will be applied in to the result of *unary_op*, the results of other *binary_op*, and *init*.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.

Returns

The `transform_exclusive_scan` algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type `sequenced_task_policy` or `parallel_task_policy` and returns `FwdIter2` otherwise. The `transform_exclusive_scan` algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::unique

Defined in header [hpx/algorithm.hpp](#)⁷⁶².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::unique_copy*

```
template<typename FwdIter, typename Pred = hpx::parallel::detail::equal_to, typename Proj = hpx::identity>  
FwdIter hpx::unique(FwdIter first, FwdIter last, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range [first, last) and returns a past-the-end iterator for the new logical end of the range.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *pred* is invoked.

Returns

The *unique* algorithm returns *FwdIter*. The *unique* algorithm returns the iterator to the new end of the range.

```
template<typename ExPolicy, typename FwdIter, typename Pred = hpx::parallel::detail::equal_to, typename Proj = hpx::identity>
```

⁷⁶² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type hpx::unique(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, Pred &&pred =
                                                                    Pred(), Proj &&proj = Proj())
```

Eliminates all but the first element from every consecutive group of equivalent elements from the range [first, last) and returns a past-the-end iterator for the new logical end of the range. Executed according to the policy.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to *hpx::identity*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to both *Type1* and *Type2*

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *pred* is invoked.

Returns

The *unique* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *unique* algorithm returns the iterator to the new end of the range.

hpx::unique_copy

Defined in header `hpx/algorithm.hpp`⁷⁶³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::unique`

```
template<typename InIter, typename OutIter, typename Pred = hpx::parallel::detail::equal_to, typename Proj = hpx::identity>
```

```
OutIter hpx::unique_copy(InIter first, InIter last, OutIter dest, Pred &&pred = Pred(), Proj &&proj = Proj())
```

Copies the elements from the range `[first, last)`, to another range beginning at `dest` in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied.

Note: Complexity: Performs not more than `last - first` assignments, exactly `last - first - 1` applications of the predicate `pred` and no more than twice as many applications of the projection `proj`

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of `unique_copy` requires `Pred` to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate `pred` is invoked.

Returns

The `unique_copy` algorithm returns a returns *OutIter*. The `unique_copy` algorithm returns the destination iterator to the end of the `dest` range.

⁷⁶³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred =
hpx::parallel::detail::equal_to, typename Proj = hpx::identity>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter2>::type hpx::unique_copy(ExPolicy &&policy,
                                                                                   FwdIter1 first, FwdIter1
                                                                                   last, FwdIter2 dest, Pred
                                                                                   &&pred = Pred(), Proj
                                                                                   &&proj = Proj())
```

Copies the elements from the range `[first, last)`, to another range beginning at *dest* in such a way that there are no consecutive equal elements. Only the first element of each group of equal elements is copied. Executed according to the policy.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *unique_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first - 1* applications of the predicate *pred* and no more than twice as many applications of the projection *proj*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *unique_copy* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`
- **Proj** – The type of an optional projection function. This defaults to `hpx::identity`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a binary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **proj** – Specifies the function (or function object) which will be invoked for each of the elements as a projection operation before the actual predicate *pred* is invoked.

Returns

The *unique_copy* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *unique_copy* algorithm returns the pair of the source iterator to *last*, and the destination iterator to the end of the *dest* range.

hpx::rotate

Defined in header [hpx/algorithm.hpp](#)⁷⁶⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::rotate_copy*

template<typename **FwdIter**>

FwdIter **hpx::rotate**(*FwdIter* first, *FwdIter* new_first, *FwdIter* last)

Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range [first, last) in such a way that the element new_first becomes the first element of the new range and new_first - 1 becomes the last element.

The assignments in the parallel *rotate* algorithm execute in sequential order in the calling thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

FwdIter – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **new_first** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *rotate* algorithm returns a *FwdIter*. The *rotate* algorithm returns the iterator to the new location of the element pointed by first, equal to first + (last - new_first).

template<typename **ExPolicy**, typename **FwdIter**>

⁷⁶⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::rotate(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter new_first, FwdIter last)
```

Performs a left rotation on a range of elements. Specifically, *rotate* swaps the elements in the range `[first, last)` in such a way that the element `new_first` becomes the first element of the new range and `new_first - 1` becomes the last element. Executed according to the policy.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *rotate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in the distance between *first* and *last*.

Note: The type of dereferenced *FwdIter* must meet the requirements of *MoveAssignable* and *MoveConstructible*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **new_first** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *rotate* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *rotate* algorithm returns the iterator equal to `first + (last - new_first)`.

hpx::rotate_copy

Defined in header `hpx/algorithm.hpp`⁷⁶⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::rotate*

```
template<typename FwdIter, typename OutIter>
```

⁷⁶⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

OutIter **hpx::rotate_copy**(*FwdIter* first, *FwdIter* new_first, *FwdIter* last, *OutIter* dest_first)

Copies the elements from the range [first, last), to another range beginning at *dest_first* in such a way, that the element *new_first* becomes the first element of the new range and *new_first* - 1 becomes the last element.

The assignments in the parallel *rotate_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last* - *first* assignments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **OutIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a output iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **new_first** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_first** – Refers to the begin of the destination range.

Returns

The *rotate_copy* algorithm returns a output iterator, The *rotate_copy* algorithm returns the output iterator to the element past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::rotate_copy(ExPolicy &&policy,
                                                                                      FwdIter1 first, FwdIter1
                                                                                      new_first, FwdIter1 last,
                                                                                      FwdIter2 dest_first)
```

Copies the elements from the range [first, last), to another range beginning at *dest_first* in such a way, that the element *new_first* becomes the first element of the new range and *new_first* - 1 becomes the last element. Executed according to the policy.

The assignments in the parallel *rotate_copy* algorithm execute in sequential order in the calling thread.

The assignments in the parallel *rotate_copy* algorithm execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last* - *first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **new_first** – Refers to the element that should appear at the beginning of the rotated range.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest_first** – Refers to the begin of the destination range.

Returns

The *rotate_copy* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *parallel_task_policy* and returns `FwdIter2` otherwise. The *rotate_copy* algorithm returns the output iterator to the element past the last element copied.

hpx::transform_reduce

Defined in header `hpx/algorithm.hpp`⁷⁶⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter, typename T, typename Reduce, typename Convert>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::transform_reduce(ExPolicy &&policy,
                                                                                   FwdIter first, FwdIter last,
                                                                                   T init, Reduce &&red_op,
                                                                                   Convert &&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))). Executed according to the policy.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1

⁷⁶⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- $op(\text{GENERALIZED_SUM}(op, b1, \dots, bK), \text{GENERALIZED_SUM}(op, bM, \dots, bN))$, where:
 - $b1, \dots, bN$ may be any permutation of $a1, \dots, aN$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *parallel_task_policy* and returns *T* otherwise. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename InIter, typename T, typename Reduce, typename Convert>
```

T `hpx::transform_reduce(InIter first, InIter last, T init, Reduce &&red_op, Convert &&conv_op)`

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns a *T*. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range `[first, last)`.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::transform_reduce(ExPolicy &&policy,
                                          FwdIter1 first1, FwdIter1
                                          last1, FwdIter2 first2, T
                                          init)
```

Returns the result of accumulating `init` with the inner products of the pairs formed by the elements of two ranges starting at `first1` and `first2`. Executed according to the policy.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\text{last} - \text{first})$ applications each of *reduce* and *transform*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the first source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as return values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first sequence of elements the result will be calculated with.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise.

```
template<typename InIter1, typename InIter2, typename T>
T hpx::transform_reduce(InIter1 first1, InIter1 last1, InIter2 first2, T init)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

Note: Complexity: $O(\text{last} - \text{first})$ applications each of *reduce* and *transform*.

Template Parameters

- **InIter1** – The type of the first source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as return values (deduced).

Parameters

- **first1** – Refers to the beginning of the first sequence of elements the result will be calculated with.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.

Returns

The *transform_reduce* algorithm returns a *T*.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T, typename Reduce,
typename Convert>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::transform_reduce(ExPolicy &&policy,
                                                                                   FwdIter1 first1, FwdIter1
                                                                                   last1, FwdIter2 first2, T init,
                                                                                   Reduce &&red_op, Convert
                                                                                   &&conv_op)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*. Executed according to the policy.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\text{last} - \text{first})$ applications each of *reduce* and *transform*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the first source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as return values (deduced).
- **Reduce** – The type of the binary function object used for the multiplication operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the first sequence of elements the result will be calculated with.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.
- **red_op** – Specifies the function (or function object) which will be invoked for the initial value and each of the return values of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to a type of *T*.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the input values of the sequence. This is a binary predicate. The signature of this predicate should be equivalent to

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to an object for the second argument type of *red_op*.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise.

```
template<typename InIter1, typename InIter2, typename T, typename Reduce, typename Convert>  
T hpx::transform_reduce(ExPolicy &&policy, InIter1 first1, InIter1 last1, InIter2 first2, T init, Reduce  
                        &&red_op, Convert &&conv_op)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

Note: Complexity: $O(\text{last} - \text{first})$ applications each of *reduce* and *transform*.

Template Parameters

- **InIter1** – The type of the first source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as return) values (deduced).
- **Reduce** – The type of the binary function object used for the multiplication operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **first1** – Refers to the beginning of the first sequence of elements the result will be calculated with.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.
- **red_op** – Specifies the function (or function object) which will be invoked for the initial value and each of the return values of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to a type of *T*.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the input values of the sequence. This is a binary predicate. The signature of this predicate should be equivalent to

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to an object for the second argument type of *red_op*.

Returns

The *transform_reduce* algorithm returns a *T*.

```
template<typename ExPolicy, typename Iter, typename Sent, typename T, typename Reduce, typename
Convert>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::transform_reduce(ExPolicy &&policy, Iter
first, Sent last, T init,
Reduce &&red_op, Convert
&&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(*op*, *a1*, ..., *aN*) is defined as follows:

- *a1* when *N* is 1
 - *op*(GENERALIZED_SUM(*op*, *b1*, ..., *bK*), GENERALIZED_SUM(*op*, *bM*, ..., *bN*)), where:
 - *b1*, ..., *bN* may be any permutation of *a1*, ..., *aN* and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for *Iter*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *parallel_task_policy* and returns *T* otherwise. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range `[first, last)`.

```
template<typename Iter, typename Sent, typename T, typename Reduce, typename Convert>
```

```
T hpx::transform_reduce(Iter first, Sent last, T init, Reduce &&red_op, Convert &&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for *Iter*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns *T*. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename ExPolicy, typename Iter, typename Sent, typename Iter2, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::transform_reduce(ExPolicy &&policy, Iter
                                                                    first, Sent last, Iter2 first2, T
                                                                    init)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1

- $\text{op}(\text{GENERALIZED_SUM}(\text{op}, b_1, \dots, b_K), \text{GENERALIZED_SUM}(\text{op}, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for **Iter**.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an random access iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *transform_reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *parallel_task_policy* and returns *T* otherwise. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [*first*, *last*).

```
template<typename Iter, typename Sent, typename Iter2, typename T>
T hpx::transform_reduce(Iter first, Sent last, Iter2 first2, T init)
```

Returns $\text{GENERALIZED_SUM}(\text{red_op}, \text{init}, \text{conv_op}(*\text{first}), \dots, \text{conv_op}(*(\text{first} + (\text{last} - \text{first}) - 1)))$.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: $\text{GENERALIZED_SUM}(\text{op}, a_1, \dots, a_N)$ is defined as follows:

- a_1 when *N* is 1
- $\text{op}(\text{GENERALIZED_SUM}(\text{op}, b_1, \dots, b_K), \text{GENERALIZED_SUM}(\text{op}, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and

– $1 < K+1 = M \leq N$.

Template Parameters

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of a sentinel for **Iter**.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of a random access iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *transform_reduce* algorithm returns *T*. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [*first*, *last*).

```
template<typename ExPolicy, typename Iter, typename Sent, typename Iter2, typename T, typename Reduce,  
typename Convert>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::transform_reduce(ExPolicy &&policy, Iter  
first, Sent last, Iter2 first2, T  
init, Reduce &&red_op,  
Convert &&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1

- $\text{op}(\text{GENERALIZED_SUM}(\text{op}, b_1, \dots, b_K), \text{GENERALIZED_SUM}(\text{op}, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for **Iter**.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an random access iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *parallel_task_policy* and returns *T* otherwise. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [*first*, *last*).

```
template<typename Iter, typename Sent, typename Iter2, typename T, typename Reduce, typename Convert>  
T hpx::transform_reduce(Iter first, Sent last, Iter2 first2, T init, Reduce &&red_op, Convert &&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an random access iterator.
- **Sent** – The type of the end source iterators used (deduced). This iterator type must meet the requirements of an sentinel for Iter.
- **Iter2** – The type of the source iterators used (deduced) representing the second sequence. This iterator type must meet the requirements of an random access iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **first** – Refers to the beginning of the first sorted range the algorithm will be applied to.
- **last** – Refers to the end of the second sorted range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:


```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns *T*. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename ExPolicy, typename Rng, typename T, typename Reduce, typename Convert>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::transform_reduce(ExPolicy &&policy, Rng
&&rng, T init, Reduce
&&red_op, Convert
&&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of *conv_op*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from *conv_op* can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *parallel_task_policy* and returns *T* otherwise. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from *conv_op* when applied to the elements given by the input range [first, last).

```
template<typename Rng, typename T, typename Reduce, typename Convert>
```

```
T hpx::transform_reduce(Rng &&rng, T init, Reduce &&red_op, Convert &&conv_op)
```

Returns GENERALIZED_SUM(red_op, init, conv_op(*first), ..., conv_op(*(first + (last - first) - 1))).

The difference between *transform_reduce* and *accumulate* is that the behavior of *transform_reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicates *red_op* and *conv_op*.

Note: `GENERALIZED_SUM(op, a1, ..., aN)` is defined as follows:

- `a1` when `N` is 1
 - `op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN))`, where:
 - `b1, ..., bN` may be any permutation of `a1, ..., aN` and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).
- **Reduce** – The type of the binary function object used for the reduction operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **red_op** – Specifies the function (or function object) which will be invoked for each of the values returned from the invocation of `conv_op`. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1*, *Type2*, and *Ret* must be such that an object of a type as returned from `conv_op` can be implicitly converted to any of those types.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by `[first, last)`. This is a unary predicate. The signature of this predicate should be equivalent to:

```
R fun(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *Iter* can be dereferenced and then implicitly converted to *Type*. The type *R* must be such that an object of this type can be implicitly converted to *T*.

Returns

The *transform_reduce* algorithm returns *T*. The *transform_reduce* algorithm returns the result of the generalized sum over the values returned from `conv_op` when applied to the elements given by the input range `[first, last)`.

```
template<typename ExPolicy, typename Rng, typename Iter2, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::transform_reduce(ExPolicy &&policy, Rng
                                                                    &&rng, Iter2 first2, T init)
```

Returns the result of accumulating `init` with the inner products of the pairs formed by the elements of two ranges starting at `first1` and `first2`.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op2*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as return) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.

Returns

The *transform_reduce* algorithm returns a *hpx::future<T>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise.

```
template<typename Rng, typename Iter2, typename T>
T hpx::transform_reduce(Rng &&rng, Iter2 first2, T init)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op2*.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as return) values (deduced).

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.

Returns

The *transform_reduce* algorithm returns *T*.

```
template<typename ExPolicy, typename Rng, typename Iter2, typename T, typename Reduce, typename
Convert>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::transform_reduce(ExPolicy &&policy, Rng
&&rng, Iter2 first2, T init,
Reduce &&red_op, Convert
&&conv_op)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *transform_reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op2*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to be used as return) values (deduced).
- **Reduce** – The type of the binary function object used for the multiplication operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.

- **red_op** – Specifies the function (or function object) which will be invoked for the initial value and each of the return values of *op2*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to a type of *T*.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the input values of the sequence. This is a binary predicate. The signature of this predicate should be equivalent to

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to an object for the second argument type of *op1*.

Returns

The *transform_reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise.

```
template<typename Rng, typename Iter2, typename T, typename Reduce, typename Convert>
```

```
T hpx::transform_reduce(Rng &&rng, Iter2 first2, T init, Reduce &&red_op, Convert &&conv_op)
```

Returns the result of accumulating *init* with the inner products of the pairs formed by the elements of two ranges starting at *first1* and *first2*.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op2*.

Template Parameters

- **Rng** – The type of the source range used (deduced). The iterators extracted from this range type must meet the requirements of an input iterator.
- **Iter2** – The type of the second source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as return values (deduced).
- **Reduce** – The type of the binary function object used for the multiplication operation.
- **Convert** – The type of the unary function object used to transform the elements of the input sequence before invoking the reduce function.

Parameters

- **rng** – Refers to the sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the result will be calculated with.
- **init** – The initial value for the sum.
- **red_op** – Specifies the function (or function object) which will be invoked for the initial value and each of the return values of *op2*. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to a type of *T*.

- **conv_op** – Specifies the function (or function object) which will be invoked for each of the input values of the sequence. This is a binary predicate. The signature of this predicate should be equivalent to

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Ret* must be such that it can be implicitly converted to an object for the second argument type of *op1*.

Returns

The *transform_reduce* algorithm returns *T*.

hpx::experimental::reduction

Defined in header `hpx/algorithm.hpp`⁷⁶⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename T, typename Op>
constexpr hpx::parallel::detail::reduction_helper<T, std::decay_t<Op>> hpx::experimental::reduction(T
                                                                    &var,
                                                                    T
                                                                    const
                                                                    &iden-
                                                                    tity,
                                                                    Op
                                                                    &&com-
                                                                    biner)
```

The function template returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, a combiner function object, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses reduction objects by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the reduction object's combiner operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*. The expression

```
var = combiner(var, var)
```

⁷⁶⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

shall be well-formed.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation. For example if the combiner is `plus<T>`, incrementing the view would be consistent with the combiner but doubling it or assigning to it would not.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.
- **combiner** – [in] The binary function (object) used to perform a pairwise reduction on the elements.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T, typename Op>
constexpr hpx::parallel::detail::reduction_helper<T, std::decay_t<Op>> hpx::experimental::reduction(T
                                                                    &var,
                                                                    Op
                                                                    &&com-
                                                                    biner)
```

hpx::transform

Defined in header [hpx/algorithm.hpp](#)⁷⁶⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename FwdIter1, typename FwdIter2, typename F>
FwdIter2 hpx::transform(FwdIter1 first, FwdIter1 last, FwdIter2 dest, F &&f)
```

Applies the given function *f* to the range [first, last) and stores the result in another range, beginning at dest.

Note: Complexity: Exactly *last - first* applications of *f*

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

⁷⁶⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate. The signature of this predicate should be equivalent to:

Ret fun(const Type &a);

The signature does not need to have const&. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *FwdIter2* can be dereferenced and assigned a value of type *Ret*.

Returns

The *transform* algorithm returns a *FwdIter2*. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename F>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::transform(ExPolicy &&policy, FwdIter1 first,
                                                                              FwdIter1 last, FwdIter2 dest, F
                                                                              &&f)
```

Applies the given function *f* to the range [first, last) and stores the result in another range, beginning at dest. Executed according to the policy.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *last - first* applications of *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*. The type *Ret* must be such that an object of type *FwdIter2* can be dereferenced and assigned a value of type *Ret*.

Returns

The *transform* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *parallel_task_policy* and returns *FwdIter2* otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the input sequence and the output iterator to the element in the destination range, one past the last element copied.

```
template<typename FwdIter1, typename FwdIter2, typename FwdIter3, typename F>  
FwdIter3 hpx::transform(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter3 dest, F &&f)
```

Applies the given function *f* to pairs of elements from two ranges: one defined by [first1, last1) and the other beginning at first2, and stores the result in another range, beginning at dest.

Note: Complexity: Exactly *last - first* applications of *f*

Template Parameters

- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators for the second range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.

- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively. The type *Ret* must be such that an object of type *FwdIter3* can be dereferenced and assigned a value of type *Ret*.

Returns

The *transform* algorithm returns a *FwdIter3*. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename FwdIter3, typename F>
parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter3> hpx::transform(ExPolicy &&policy, FwdIter1
                                                                    first1, FwdIter1 last1, FwdIter2
                                                                    first2, FwdIter3 dest, F &&f)
```

Applies the given function *f* to pairs of elements from two ranges: one defined by [first1, last1) and the other beginning at first2, and stores the result in another range, beginning at dest. Executed according to the policy.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The invocations of *f* in the parallel *transform* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *last - first* applications of *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the invocations of *f*.
- **FwdIter1** – The type of the source iterators for the first range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the source iterators for the second range used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter3** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *transform* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first1** – Refers to the beginning of the first sequence of elements the algorithm will be applied to.
- **last1** – Refers to the end of the first sequence of elements the algorithm will be applied to.
- **first2** – Refers to the beginning of the second sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type2 &b);
```

The signature does not need to have const&. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively. The type *Ret* must be such that an object of type *FwdIter3* can be dereferenced and assigned a value of type *Ret*.

Returns

The *transform* algorithm returns a *hpx::future<FwdIter3>* if the execution policy is of type *parallel_task_policy* and returns *FwdIter3* otherwise. The *transform* algorithm returns a tuple holding an iterator referring to the first element after the first input sequence, an iterator referring to the first element after the second input sequence, and the output iterator referring to the element in the destination range, one past the last element copied.

hpx::count

Defined in header [hpx/algorithm.hpp](#)⁷⁶⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::count_if*

```
template<typename ExPolicy, typename FwdIter, typename T>
util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<FwdIter>::difference_type>::type hpx::count(ExPolicy
&&policy,
FwdIter
first,
FwdIter
last,
T
const
&value)
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*. Executed according to the policy.

The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁷⁶⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs exactly *last - first* comparisons.

Note: The comparisons in the parallel *count* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **FwdIter** – The type of the source iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the value to search for (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.

Returns

The *count* algorithm returns a *hpx::future<difference_type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *std::iterator_traits<FwdIterB>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename InIter, typename T>
std::iterator_traits<InIter>::difference_type hpx::count(InIter first, InIter last, T const &value)
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts the elements that are equal to the given *value*.

Note: Complexity: Performs exactly *last - first* comparisons.

Template Parameters

- **InIter** – The type of the source iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to search for (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to search for.

Returns

The *count* algorithm returns a *difference_type* (where *difference_type* is defined by *std::iterator_traits<Iter>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.

hpx::count_if

Defined in header [hpx/algorithm.hpp](#)⁷⁷⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::count*

```
template<typename ExPolicy, typename FwdIter, typename F>  
util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<FwdIter>::difference_type>::type hpx::count_if(ExPolicy  
    &&pol-  
    icy,  
    FwdIter  
    first,  
    FwdIter  
    last,  
    F  
    &&f)
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts elements for which predicate *f* returns true. Executed according to the policy.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Note: The assignments in the parallel *count_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the comparisons.
- **FwdIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *count_if* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

⁷⁷⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *count_if* algorithm returns *hpx::future<difference_type>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *difference_type* otherwise (where *difference_type* is defined by *std::iterator_traits<FwdIter>::difference_type*). The *count* algorithm returns the number of elements satisfying the given criteria.

```
template<typename InIter, typename F>
```

```
std::iterator_traits<InIter>::difference_type hpx::count_if(InIter first, InIter last, F &&f)
```

Returns the number of elements in the range [first, last) satisfying a specific criteria. This version counts elements for which predicate *f* returns true.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source begin iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *count_if* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the required elements. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *count_if* algorithm returns *difference_type* (where a *difference_type* is defined by

std::iterator_traits<InIter>::difference_type. The *count* algorithm returns the number of elements satisfying the given criteria.

hpx::transform_inclusive_scan

Defined in header `hpx/algorithm.hpp`⁷⁷¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InIter, typename OutIter, typename BinOp, typename UnOp>
OutIter hpx::transform_inclusive_scan(InIter first, InIter last, OutIter dest, BinOp &&binary_op, UnOp
&&unary_op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result))))`.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *binary_op* nor *unary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges `[first,last)` or `[result,result + (last - first))`.

The difference between *inclusive_scan* and *transform_inclusive_scan* is that *transform_inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of each of *binary_op* and *unary_op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

⁷⁷¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **binary_op** – Binary *FunctionObject* that will be applied in to the result of *unary_op*, the results of other *binary_op*, and *init* if provided.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.

Returns

The *transform_inclusive_scan* algorithm returns a returns *OutIter*. The *transform_inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename BinOp, typename UnOp>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter2>::type hpx::transform_inclusive_scan(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter1
                                                                                               first,
                                                                                               FwdIter1
                                                                                               last,
                                                                                               FwdIter2
                                                                                               dest, BinOp
                                                                                               &&bi-
                                                                                               nary_op,
                                                                                               UnOp
                                                                                               &&unary_op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, conv(*first), ..., conv(*(first + (i - result)))). Executed according to the policy.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *binary_op* nor *unary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The difference between *inclusive_scan* and *transform_inclusive_scan* is that *transform_inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of each of *binary_op* and *unary_op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN) is defined as:

- a1 when N is 1
 - op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Binary *FunctionObject* that will be applied in to the result of *unary_op*, the results of other *binary_op*, and *init* if provided.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.

Returns

The *transform_inclusive_scan* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *transform_inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename OutIter, typename BinOp, typename UnOp, typename T = typename
std::iterator_traits<InIter>::value_type>
OutIter hpx::transform_inclusive_scan(InIter first, InIter last, OutIter dest, BinOp &&binary_op, UnOp
&&unary_op, T init)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, init, conv(*first), ..., conv(*(first + (i - result)))).

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Neither *binary_op* nor *unary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges [first,last) or [result,result + (last - first)).

The difference between *inclusive_scan* and *transform_inclusive_scan* is that *transform_inclusive_scan* includes the *i*th input element in the *i*th sum. If *binary_op* is not mathematically associative, the behavior of *transform_inclusive_scan* may be non-deterministic.

Note: Complexity: O(last - first) applications of each of *binary_op* and *unary_op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN) is defined as:

- a1 when N is 1
 - op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN)) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **binary_op** – Binary *FunctionObject* that will be applied in to the result of *unary_op*, the results of other *binary_op*, and *init* if provided.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.
- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns a *returns OutIter*. The *transform_inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename BinOp, typename UnOp,
        typename T = typename std::iterator_traits<FwdIter1>::value_type>
parallel::util::detail::algorithm_result<ExPolicy, FwdIter2>::type hpx::transform_inclusive_scan(ExPolicy
                                                                                               &&policy,
                                                                                               FwdIter1
                                                                                               first,
                                                                                               FwdIter1
                                                                                               last,
                                                                                               FwdIter2
                                                                                               dest, BinOp
                                                                                               &&bi-
                                                                                               nary_op,
                                                                                               UnOp
                                                                                               &&unary_op,
                                                                                               T init)
```

Assigns through each iterator i in $[result, result + (last - first))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, init, conv(*first), ..., conv(*(first + (i - result))))`. Executed according to the policy.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *transform_inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Neither *binary_op* nor *unary_op* shall invalidate iterators or sub-ranges, or modify elements in the ranges $[first, last)$ or $[result, result + (last - first))$.

The difference between *inclusive_scan* and *transform_inclusive_scan* is that *transform_inclusive_scan* includes the i th input element in the i th sum. If *binary_op* is not mathematically associative, the behavior of *transform_inclusive_scan* may be non-deterministic.

Note: Complexity: $O(last - first)$ applications of each of *binary_op* and *unary_op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- $a1$ when N is 1
 - $op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, \dots, aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, \dots, aN))$ where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **BinOp** – The type of *binary_op*.
- **UnOp** – The type of *unary_op*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

- **binary_op** – Binary *FunctionObject* that will be applied in to the result of *unary_op*, the results of other *binary_op*, and *init* if provided.
- **unary_op** – Unary *FunctionObject* that will be applied to each element of the input range. The return type must be acceptable as input to *binary_op*.
- **init** – The initial value for the generalized sum.

Returns

The *transform_inclusive_scan* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *transform_inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::experimental::reduction_plus

Defined in header `hpx/algorithm.hpp`⁷⁷².

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::plus<T>> hpx::experimental::reduction_plus(T
                                                                    &var)
```

The function template *reduction_plus* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::plus{ }` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_plus* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::plus{ }` operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The life-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.

⁷⁷² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, std::plus<T>> hpx::experimental::reduction_plus(T
                                                                    &var,
                                                                    T
                                                                    const
                                                                    &iden-
                                                                    tity)
```

hpx::experimental::sort_by_key

Defined in header `hpx/algorithm.hpp`⁷⁷³.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename KeyIter, typename ValueIter, typename Compare = detail::less>
util::detail::algorithm_result_t<ExPolicy, sort_by_key_result<KeyIter, ValueIter>> hpx::experimental::sort_by_key(ExPolicy
                                                                 &&pol-
                                                                 icy,
                                                                 KeyIter
                                                                 key_first,
                                                                 KeyIter
                                                                 key_last,
                                                                 Val-
                                                                 ueIter
                                                                 value_first,
                                                                 Com-
                                                                 pare
                                                                 &&comp
                                                                 =
                                                                 Com-
                                                                 pare())
```

Sorts one range of data using keys supplied in another range. The key elements in the range [key_first, key_last) are sorted in ascending order with the corresponding elements in the value range moved to follow the sorted order. The algorithm is not stable, the order of equal elements is not guaranteed to be preserved. The function uses the given comparison function object *comp* (defaults to using operator<()). Executed according to the policy.

A sequence is sorted with respect to a comparator *comp* if for every iterator *i* pointing to the sequence and every non-negative integer *n* such that *i* + *n* is a valid iterator pointing to an element of the sequence, and `INVOKE(comp, *(i + n), *i) == false`.

comp has to induce a strict weak ordering on the values.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁷⁷³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: $O(N \log(N))$, where $N = \text{std::distance}(\text{first}, \text{last})$ comparisons.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **KeyIter** – The type of the key iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **ValueIter** – The type of the value iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Compare** – The type of the function/function object to use (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **key_first** – Refers to the beginning of the sequence of key elements the algorithm will be applied to.
- **key_last** – Refers to the end of the sequence of key elements the algorithm will be applied to.
- **value_first** – Refers to the beginning of the sequence of value elements the algorithm will be applied to, the range of elements must match `[key_first, key_last)`
- **comp** – `comp` is a callable object. The return value of the INVOKE operation applied to an object of type `Comp`, when contextually converted to `bool`, yields `true` if the first argument of the call is less than the second, and `false` otherwise. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.

Returns

The *sort_by_key* algorithm returns a `hpx::future<sort_by_key_result<KeyIter, ValueIter>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *otherwise*. The algorithm returns a pair holding an iterator pointing to the first element after the last element in the input key sequence and an iterator pointing to the first element after the last element in the input value sequence.

hpx::is_sorted

Defined in header `hpx/algorithm.hpp`⁷⁷⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::is_sorted_until*

template<typename **FwdIter**, typename **Pred** = *hpx::parallel::detail::less*>

⁷⁷⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

bool **hpx::is_sorted**(*FwdIter* first, *FwdIter* last, *Pred* &&pred = *Pred*())

Determines if the range [first, last) is sorted. Uses pred to compare elements.

The comparison operations in the parallel *is_sorted* algorithm executes in sequential order in the calling thread.

Note: Complexity: at most (N+S-1) comparisons where *N* = distance(first, last). *S* = number of partitions

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use.

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have const &, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_sorted* algorithm returns a *bool*. The *is_sorted* algorithm returns true if each element in the sequence [first, last) satisfies the predicate passed. If the range [first, last) contains less than two elements, the function always returns true.

```
template<typename ExPolicy, typename FwdIter, typename Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool> hpx::is_sorted(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, Pred &&pred =
                                                                    Pred())
```

Determines if the range [first, last) is sorted. Uses pred to compare elements. Executed according to the policy.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (N+S-1) comparisons where *N* = distance(first, last). *S* = number of partitions

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_sorted* algorithm returns a *hpx::future<bool>* if the execution policy is of type *task_execution_policy* and returns *bool* otherwise. The *is_sorted* algorithm returns a *bool* if each element in the sequence [first, last) satisfies the predicate passed. If the range [first, last) contains less than two elements, the function always returns true.

hpx::is_sorted_until

Defined in header `hpx/algorithm.hpp`⁷⁷⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::is_sorted*

```
template<typename FwdIter, typename Pred = hpx::parallel::detail::less>
FwdIter hpx::is_sorted_until(FwdIter first, FwdIter last, Pred &&pred = Pred())
```

Returns the first element in the range [first, last) that is not sorted. Uses a predicate to compare elements or the less than operator.

The comparison operations in the parallel *is_sorted_until* algorithm execute in sequential order in the calling thread.

Note: Complexity: at most (N+S-1) comparisons where *N* = distance(first, last). *S* = number of partitions

⁷⁷⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of an optional function/function object to use.

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_sorted_until* algorithm returns a *FwdIter*. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is returned.

```
template<typename ExPolicy, typename FwdIter, typename Pred = hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result<ExPolicy, FwdIter>::type hpx::is_sorted_until(ExPolicy
                                                                                          &&policy, FwdIter
                                                                                          first, FwdIter last,
                                                                                          Pred &&pred =
                                                                                          Pred())
```

Returns the first element in the range [first, last) that is not sorted. Uses a predicate to compare elements or the less than operator. Executed according to the policy.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *sequenced_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *is_sorted_until* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(N+S-1)$ comparisons where N = distance(first, last). S = number of partitions

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used for the This iterator type must meet the requirements of a forward iterator.

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *is_sorted_until* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **pred** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second argument. The signature of the function should be equivalent to

```
bool pred(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *is_sorted_until* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *task_execution_policy* and returns *FwdIter* otherwise. The *is_sorted_until* algorithm returns the first unsorted element. If the sequence has less than two elements or the sequence is sorted, last is returned.

hpx::uninitialized_copy

Defined in header `hpx/algorithm.hpp`⁷⁷⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::uninitialized_copy_n*

template<typename **InIter**, typename **FwdIter**>

FwdIter **hpx::uninitialized_copy**(*InIter* first, *InIter* last, *FwdIter* dest)

Copies the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.

⁷⁷⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_copy* algorithm returns *FwdIter*. The *uninitialized_copy* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::uninitialized_copy(ExPolicy  
                                                                                               &&policy,  
                                                                                               FwdIter1 first,  
                                                                                               FwdIter1 last,  
                                                                                               FwdIter2 dest)
```

Copies the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects. Executed according to the policy.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_copy* algorithm returns a *hpx::future<FwdIter2>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *uninitialized_copy* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::uninitialized_copy_n

Defined in header [hpx/algorithm.hpp](#)⁷⁷⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::uninitialized_copy*

template<typename **InIter**, typename **Size**, typename **FwdIter**>

FwdIter **hpx::uninitialized_copy_n**(*InIter* first, *Size* count, *FwdIter* dest)

Copies the elements in the range [first, first + count), starting from first and proceeding to first + count - 1., to another range beginning at dest. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *count* assignments, if count > 0, no assignments otherwise.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_copy_n* algorithm returns a *hpx::future<FwdIter>*. The *uninitialized_copy_n* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

template<typename **ExPolicy**, typename **FwdIter1**, typename **Size**, typename **FwdIter2**>

⁷⁷⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::uninitialized_copy_n(ExPolicy
                                                                 &&policy,
                                                                 FwdIter1 first,
                                                                 Size count,
                                                                 FwdIter2 dest)
```

Copies the elements in the range $[first, first + count)$, starting from *first* and proceeding to $first + count - 1$, to another range beginning at *dest*. If an exception is thrown during the copy operation, the function has no effects.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_copy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* assignments, if $count > 0$, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_copy_n* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *uninitialized_copy_n* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::mismatch

Defined in header `hpx/algorithm.hpp`⁷⁷⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

```

template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<FwdIter1, FwdIter2>>> hpx::mismatch(ExPolicy
&&policy,
FwdIter1
first1,
FwdIter1
last1,
FwdIter2
first2,
FwdIter2
last2,
Pred
&&op)

```

Returns the first mismatching pair of elements from two ranges: one defined by [first1, last1) and another defined by [first2, last2). If last2 is not provided, it denotes first2 + (last1 - first1). Executed according to the policy.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most min(last1 - first1, last2 - first2) applications of the predicate *op* or *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and (last1 - first1) != (last2 - first2) then no applications of the predicate *op* or *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range [first1, last1), **i* mismatches *(first2 + (i - first1)). This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

⁷⁷⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

`bool pred(const Type1 &a, const Type2 &b);`

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *mismatch* algorithm returns a `hpx::future<std::pair<FwdIter1,FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::pair<FwdIter1,FwdIter2>` otherwise. If no mismatches are found when the comparison reaches `last1` or `last2`, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<FwdIter1, FwdIter2>> hpx::mismatch(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     FwdIter1
                                                                                                     first1,
                                                                                                     FwdIter1
                                                                                                     last1,
                                                                                                     FwdIter2
                                                                                                     first2,
                                                                                                     FwdIter2
                                                                                                     last2)
```

Returns the first mismatching pair of elements from two ranges: one defined by `[first1, last1)` and another defined by `[first2,last2)`. If `last2` is not provided, it denotes `first2 + (last1 - first1)`. Executed according to the policy.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range $[\text{first1}, \text{last1})$, **i* mismatches $*(\text{first2} + (i - \text{first1}))$. This overload of mismatch uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *mismatch* algorithm returns a `hpx::future<std::pair<FwdIter1, FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::pair<FwdIter1, FwdIter2>` otherwise. If no mismatches are found when the comparison reaches *last1* or *last2*, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<FwdIter1, FwdIter2>> hpx::mismatch(ExPolicy
                                                                    &&pol-
                                                                    icy,
                                                                    FwdIter1
                                                                    first1,
                                                                    FwdIter1
                                                                    last1,
                                                                    FwdIter2
                                                                    first2,
                                                                    Pred
                                                                    &&op)
```

Returns the first mismatching pair of elements from two ranges: one defined by $[first1, last1)$ and another defined by $[first2, last2)$. If $last2$ is not provided, it denotes $first2 + (last1 - first1)$. Executed according to the policy.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most $last1 - first1$ applications of the predicate *op* or *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(last1 - first1) \neq (last2 - first2)$ then no applications of the predicate *op* or *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range $[first1, last1)$, **i* mismatches $*(first2 + (i - first1))$. This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *mismatch* algorithm returns a `hpx::future<std::pair<FwdIter1,FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::pair<FwdIter1,FwdIter2>` otherwise. If no mismatches are found when the comparison reaches `last1` or `last2`, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, std::pair<FwdIter1, FwdIter2>> hpx::mismatch(ExPolicy
                                                                                               &&pol-
                                                                                               icy,
                                                                                               FwdIter1
                                                                                               first1,
                                                                                               FwdIter1
                                                                                               last1,
                                                                                               FwdIter2
                                                                                               first2)
```

Returns the first mismatching pair of elements from two ranges: one defined by `[first1, last1)` and another defined by `[first2, last2)`. If `last2` is not provided, it denotes `first2 + (last1 - first1)`. Executed according to the policy.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *mismatch* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most `last1 - first1` applications of *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and `(last1 - first1) != (last2 - first2)` then no applications of *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range `[first1, last1)`, **i* mismatches **(first2 + (i - first1))*. This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *mismatch* algorithm returns a `hpx::future<std::pair<FwdIter1,FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::pair<FwdIter1,FwdIter2>` otherwise. If no mismatches are found when the comparison reaches `last1` or `last2`, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename FwdIter1, typename FwdIter2, typename Pred>
std::pair<FwdIter1, FwdIter2> hpx::mismatch(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2,
                                           Pred &&op)
```

Returns the first mismatching pair of elements from two ranges: one defined by `[first1, last1)` and another defined by `[first2,last2)`. If `last2` is not provided, it denotes `first2 + (last1 - first1)`.

Note: Complexity: At most $\min(\text{last1} - \text{first1}, \text{last2} - \text{first2})$ applications of the predicate *op* or *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of the predicate *op* or *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range `[first1,last1)`, **i* mismatches $\text{*}(\text{first2} + (i - \text{first1}))$. This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *mismatch* algorithm returns a `std::pair<FwdIter1,FwdIter2>`. If no mismatches are found when the comparison reaches `last1` or `last2`, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename FwdIter1, typename FwdIter2>
std::pair<FwdIter1, FwdIter2> hpx::mismatch(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2)
```

Returns the first mismatching pair of elements from two ranges: one defined by `[first1, last1)` and another defined by `[first2,last2)`. If `last2` is not provided, it denotes `first2 + (last1 - first1)`.

Note: Complexity: At most `min(last1 - first1, last2 - first2)` applications of `operator==`. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and `(last1 - first1) != (last2 - first2)` then no applications of `operator==` are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range `[first1,last1)`, **i* mismatches `*(first2 + (i - first1))`. This overload of *mismatch* uses `operator==` to determine if two elements are mismatch.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.

Returns

The *mismatch* algorithm returns a `std::pair<FwdIter1,FwdIter2>`. If no mismatches are found when the comparison reaches `last1` or `last2`, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename FwdIter1, typename FwdIter2, typename Pred>
std::pair<FwdIter1, FwdIter2> hpx::mismatch(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, Pred &&op)
```

Returns the first mismatching pair of elements from two ranges: one defined by `[first1, last1)` and another defined by `[first2,last2)`. If `last2` is not provided, it denotes `first2 + (last1 - first1)`.

Note: Complexity: At most $\text{last1} - \text{first1}$ applications of the predicate *op* or *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of the predicate *op* or *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range $[\text{first1}, \text{last1})$, **i* mismatches $\text{*(first2 + (i - first1))}$. This overload of *mismatch* uses *operator==* to determine if two elements are mismatch.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *mismatch* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as mismatch. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *mismatch* algorithm returns a `std::pair<FwdIter1, FwdIter2>`. If no mismatches are found when the comparison reaches *last1* or *last2*, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

```
template<typename FwdIter1, typename FwdIter2>
```

```
std::pair<FwdIter1, FwdIter2> hp::mismatch(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2)
```

Returns the first mismatching pair of elements from two ranges: one defined by $[\text{first1}, \text{last1})$ and another defined by $[\text{first2}, \text{last2})$. If *last2* is not provided, it denotes $\text{first2} + (\text{last1} - \text{first1})$.

Note: Complexity: At most $\text{last1} - \text{first1}$ applications of *operator==*. If *FwdIter1* and *FwdIter2* meet the requirements of *RandomAccessIterator* and $(\text{last1} - \text{first1}) \neq (\text{last2} - \text{first2})$ then no applications of *operator==* are made.

Note: The two ranges are considered mismatch if, for every iterator *i* in the range `[first1,last1)`, **i* mismatches `*(first2 + (i - first1))`. This overload of `mismatch` uses `operator==` to determine if two elements are mismatch.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of `mismatch` requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::equal_to<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.

Returns

The `mismatch` algorithm returns a `std::pair<FwdIter1,FwdIter2>`. If no mismatches are found when the comparison reaches `last1` or `last2`, whichever happens first, the pair holds the end iterator and the corresponding iterator from the other range.

hpx::make_heap

Defined in header `hpx/algorithm.hpp`⁷⁷⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename RndIter, typename Comp>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::make_heap(ExPolicy &&policy, RndIter first,
                                                                    RndIter last, Comp &&comp)
```

Constructs a *max heap* in the range `[first, last)`. Executed according to the policy.

The predicate operations in the parallel `make_heap` algorithm invoked with an execution policy object of type `sequential_execution_policy` executes in sequential order in the calling thread.

The comparison operations in the parallel `make_heap` algorithm invoked with an execution policy object of type `parallel_execution_policy` or `parallel_task_execution_policy` are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most $(3*N)$ comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

⁷⁷⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RndIter** – The type of the source iterators used for algorithm. This iterator must meet the requirements for a random access iterator.
- **Comp** – Comparison function object (i.e. an object that satisfies the requirements of Compare) which returns true if the first argument is less than the second. The signature of the comparison function should be equivalent to the following:

```
bool cmp(const Type1 &a, const Type2 &b);
```

While the signature does not need to have const &, the function must not modify the objects passed to it and must be able to accept all values of type (possibly *const*) *Type1* and *Type2* regardless of value category (thus, *Type1* & is not allowed, nor is *Type1* unless for *Type1* a move is equivalent to a copy. The types *Type1* and *Type2* must be such that an object of type *RandomIt* can be dereferenced and then implicitly converted to both of them.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have const &, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *make_heap* algorithm returns a *hpx::future<void>* if the execution policy is of type *task_execution_policy* and returns *void* otherwise.

```
template<typename ExPolicy, typename RndIter>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::make_heap(ExPolicy &&policy, RndIter first,  
                                                                           RndIter last)
```

Constructs a *max heap* in the range [first, last). Uses the operator < for comparisons. Executed according to the policy.

The predicate operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *sequential_execution_policy* executes in sequential order in the calling thread.

The comparison operations in the parallel *make_heap* algorithm invoked with an execution policy object of type *parallel_execution_policy* or *parallel_task_execution_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: at most (3*N) comparisons where *N* = distance(first, last).

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RndIter** – The type of the source iterators used for algorithm. This iterator must meet the requirements for a random access iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.

Returns

The *make_heap* algorithm returns a *hpx::future<void>* if the execution policy is of type *task_execution_policy* and returns *void* otherwise.

```
template<typename RndIter, typename Comp>
void hpx::make_heap(RndIter first, RndIter last, Comp &&comp)
```

Constructs a *max heap* in the range [first, last).

Note: Complexity: at most (3*N) comparisons where *N* = distance(first, last).

Template Parameters

- **RndIter** – The type of the source iterators used for algorithm. This iterator must meet the requirements for a random access iterator.
- **Comp** – Comparison function object (i.e. an object that satisfies the requirements of Compare) which returns true if the first argument is less than the second. The signature of the comparison function should be equivalent to the following:

```
bool cmp(const Type1 &a, const Type2 &b);
```

While the signature does not need to have const &, the function must not modify the objects passed to it and must be able to accept all values of type (possibly *const*) *Type1* and *Type2* regardless of value category (thus, *Type1* & is not allowed, nor is *Type1* unless for *Type1* a move is equivalent to a copy. The types *Type1* and *Type2* must be such that an object of type *RandomIt* can be dereferenced and then implicitly converted to both of them.

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.
- **comp** – Refers to the binary predicate which returns true if the first argument should be treated as less than the second. The signature of the function should be equivalent to

```
bool comp(const Type &a, const Type &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The type *Type* must be such that objects of types *RndIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *make_heap* algorithm returns a *void*.

```
template<typename RndIter>
void hpx::make_heap(RndIter first, RndIter last)
    Constructs a max heap in the range [first, last).
```

Note: Complexity: at most $(3*N)$ comparisons where $N = \text{distance}(\text{first}, \text{last})$.

Template Parameters

RndIter – The type of the source iterators used for algorithm. This iterator must meet the requirements for a random access iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements of that the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements of that the algorithm will be applied to.

Returns

The *make_heap* algorithm returns a *void*.

hpx::experimental::reduction_min

Defined in header [hpx/algorithm.hpp](#)⁷⁸⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, hpx::parallel::detail::min_of<T>> hpx::experimental::reduction_min(T
&va
```

The function template *reduction_min* returns a reduction object of unspecified type having a value type and encapsulating an identity value for the reduction, it uses `std::min_of{ }` as its combiner function, and a live-out object from which the initial value is obtained and into which the final value is stored.

A parallel algorithm uses the *reduction_min* object by allocating an unspecified number of instances, called views, of the reduction's value type. Each view is initialized with the reduction object's identity value, except that the live-out object (which was initialized by the caller) comprises one of the views. The algorithm passes a reference to a view to each application of an element-access function, ensuring that no two concurrently-executing invocations share the same view. A view can be shared between two applications that do not execute concurrently, but initialization is performed only once per view.

Modifications to the view by the application of element access functions accumulate as partial results. At some point before the algorithm returns, the partial results are combined, two at a time, using the `std::min_of{ }` operation until a single value remains, which is then assigned back to the live-out object.

T shall meet the requirements of *CopyConstructible* and *MoveAssignable*.

⁷⁸⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: In order to produce useful results, modifications to the view should be limited to commutative operations closely related to the combiner operation.

Template Parameters

- **T** – The value type to be used by the induction object.
- **Op** – The type of the binary function (object) used to perform the reduction operation.

Parameters

- **var** – [in,out] The live-out value to use for the reduction object. This will hold the reduced value after the algorithm is finished executing.
- **identity** – [in] The identity value to use for the reduction operation. This argument is optional and defaults to a copy of *var*.

Returns

This returns a reduction object of unspecified type having a value type of *T*. When the return value is used by an algorithm, the reference to *var* is used as the live-out object, new views are initialized to a copy of identity, and views are combined by invoking the copy of combiner, passing it the two views to be combined.

```
template<typename T>
constexpr hpx::parallel::detail::reduction_helper<T, hpx::parallel::detail::min_of<T>> hpx::experimental::reduction_min(T
&va
T
cons
&id
tity)
```

hpx::nth_element

Defined in header [hpx/algorithm.hpp](#)⁷⁸¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename RandomIt, typename Pred = hpx::parallel::detail::less>
void hpx::nth_element(RandomIt first, RandomIt nth, RandomIt last, Pred &&pred = Pred())
```

nth_element is a partial sorting algorithm that rearranges elements in [first, last) such that the element pointed at by *nth* is changed to whatever element would occur in that position if [first, last) were sorted and all of the elements before this new *nth* element are less than or equal to the elements after the new *nth* element. Executed according to the policy.

The comparison operations in the parallel *nth_element* algorithm invoked without an execution policy object execute in sequential order in the calling thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

⁷⁸¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **RandomIt** – The type of the source begin, nth, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.
- **Pred** – Comparison function object which returns true if the first argument is less than the second. This defaults to `std::less<>`.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type *randomIt* can be dereferenced and then implicitly converted to *Type*. This defaults to `std::less<>`.

Returns

The *nth_element* algorithms returns nothing.

```
template<typename ExPolicy, typename RandomIt, typename Pred = hpx::parallel::detail::less>
void hpx::nth_element(ExPolicy &&policy, RandomIt first, RandomIt nth, RandomIt last, Pred &&pred =
    Pred())
```

nth_element is a partial sorting algorithm that rearranges elements in `[first, last)` such that the element pointed at by *nth* is changed to whatever element would occur in that position if `[first, last)` were sorted and all of the elements before this new *nth* element are less than or equal to the elements after the new *nth* element.

The comparison operations in the parallel *nth_element* invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *nth_element* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Linear in `std::distance(first, last)` on average. $O(N)$ applications of the predicate, and $O(N \log N)$ swaps, where $N = \text{last} - \text{first}$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **RandomIt** – The type of the source begin, nth, and end iterators used (deduced). This iterator type must meet the requirements of a random access iterator.

- **Pred** – Comparison function object which returns true if the first argument is less than the second. This defaults to `std::less<>`.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **nth** – Refers to the iterator defining the sort partition point
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the comparison function object which returns true if the first argument is less than (i.e. is ordered before) the second. The signature of this comparison function should be equivalent to:

```
bool cmp(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type must be such that an object of type *randomIt* can be dereferenced and then implicitly converted to `Type`. This defaults to `std::less<>`.

Returns

The *nth_element* algorithms returns nothing.

hpx::replace

Defined in header `hpx/algorithm.hpp`⁷⁸².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::replace_if*
- *hpx::replace_copy*
- *hpx::replace_copy_if*

```
template<typename InIter, typename T = typename std::iterator_traits<InIter>::value_type>
void hpx::replace(InIter first, InIter last, T const &old_value, T const &new_value)
```

Replaces all elements satisfying specific criteria with *new_value* in the range `[first, last)`.

Effects: Substitutes elements referred by the iterator it in the range `[first, last)` with *new_value*, when the following corresponding conditions hold: `*it == old_value`

The assignments in the parallel *replace* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.

⁷⁸² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **T** – The type of the old and new values to replace (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace* algorithm returns a *void*.

```
template<typename ExPolicy, typename FwdIter, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, void> hpx::replace(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, T const &old_value, T
                                                                    const &new_value)
```

Replaces all elements satisfying specific criteria with *new_value* in the range [first, last). Executed according to the policy.

Effects: Substitutes elements referred by the iterator it in the range [first, last) with *new_value*, when the following corresponding conditions hold: **it == old_value*

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the old and new values to replace (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

hpx::replace_if

Defined in header [hpx/algorithm.hpp](#)⁷⁸³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::replace*
- *hpx::replace_copy*
- *hpx::replace_copy_if*

template<typename **Iter**, typename **Pred**, typename **T** = typename *std::iterator_traits<Iter>::value_type*>
void **hpx::replace_if**(*Iter* first, *Iter* last, *Pred* &&pred, *T* const &new_value)

Replaces all elements satisfying specific criteria (for which predicate *pred* returns true) with *new_value* in the range [first, last).

Effects: Substitutes elements referred by the iterator *it* in the range [first, last) with *new_value*, when the following corresponding conditions hold: INVOKE(*f*, **it*) != false

The assignments in the parallel *replace_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **Iter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

⁷⁸³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_if* algorithm returns *void*.

```
template<typename ExPolicy, typename FwdIter, typename Pred, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, void> hpx::replace_if(ExPolicy &&policy, FwdIter
first, FwdIter last, Pred &&pred,
T const &new_value)
```

Replaces all elements satisfying specific criteria (for which predicate *f* returns true) with *new_value* in the range [first, last). Executed according to the policy.

Effects: Substitutes elements referred by the iterator *it* in the range [first, last) with *new_value*, when the following corresponding conditions hold: `INVOKE(f, *it) != false`

The assignments in the parallel *replace_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:


```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_if* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

hpx::replace_copy

Defined in header [hpx/algorithm.hpp](#)⁷⁸⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::replace*
- *hpx::replace_if*
- *hpx::replace_copy_if*

```
template<typename InIter, typename OutIter, typename T = typename std::iterator_traits<OutIter>::value_type>
OutIter hpx::replace_copy(InIter first, InIter last, OutIter dest, T const &old_value, T const &new_value)
```

Copies the all elements from the range [first, last) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (last - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: **(first + (i - result)) == old_value*

The assignments in the parallel *replace_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T** – The type of the old and new values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

⁷⁸⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_copy* algorithm returns an *OutIter* The *replace_copy* algorithm returns the Iterator to the element past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T = typename
std::iterator_traits<FwdIter2>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::replace_copy(ExPolicy &&policy,
                                                                                      FwdIter1 first, FwdIter1
                                                                                      last, FwdIter2 dest, T
                                                                                      const &old_value, T
                                                                                      const &new_value)
```

Copies the all elements from the range [first, last) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*. Executed according to the policy.

Effects: Assigns to every iterator it in the range [result, result + (last - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: **(first + (i - result)) == old_value*

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type of the old and new values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **old_value** – Refers to the old value of the elements to replace.
- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_copy* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *replace_copy* algorithm returns the Iterator to the element past the last element copied.

hpx::replace_copy_if

Defined in header [hpx/algorithm.hpp](#)⁷⁸⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::replace*
- *hpx::replace_if*
- *hpx::replace_copy*

template<typename **InIter**, typename **OutIter**, typename **Pred**, typename **T** = typename *std::iterator_traits<OutIter>::value_type*>

OutIter **hpx::replace_copy_if**(*InIter* first, *InIter* last, *OutIter* dest, *Pred* &&pred, *T* const &new_value)

Copies the all elements from the range [first, last) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator it in the range [result, result + (last - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: *INVOKE(f, *(first + (i - result))) != false*

The assignments in the parallel *replace_copy_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *equal* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

⁷⁸⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_copy_if* algorithm returns an *OutIter*. The *replace_copy_if* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred, typename T = typename
std::iterator_traits<FwdIter2>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::replace_copy_if(ExPolicy &&policy,
                                                                                          FwdIter1 first,
                                                                                          FwdIter1 last,
                                                                                          FwdIter2 dest, Pred
                                                                                          &&pred, T const
                                                                                          &new_value)
```

Copies the all elements from the range [first, last) to another range beginning at *dest* replacing all elements satisfying a specific criteria with *new_value*.

Effects: Assigns to every iterator *it* in the range [result, result + (last - first)) either *new_value* or **(first + (it - result))* depending on whether the following corresponding condition holds: `INVOKE(f, *(first + (i - result))) != false`

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *replace_copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* applications of the predicate.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *replace_copy_if* requires *Pred* to meet the requirements of *CopyConstructible*. (deduced).
- **T** – The type of the new values to replace (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements which need to be replaced. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

- **new_value** – Refers to the new value to use as the replacement.

Returns

The *replace_copy_if* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *replace_copy_if* algorithm returns the iterator to the element in the destination range, one past the last element copied.

hpx::experimental::induction

Defined in header `hpx/algorithm.hpp`⁷⁸⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename T>
constexpr hpx::parallel::detail::induction_stride_helper<T> hpx::experimental::induction(T &&value,
                                                                                          std::size_t stride)
```

The function template returns an induction object of unspecified type having a value type and encapsulating an initial *value* of that type and, optionally, a stride.

For each element in the input range, a looping algorithm over input sequence *S* computes an induction value from an induction variable and ordinal position *p* within *S* by the formula $i + p * \text{stride}$ if a stride was specified or $i + p$ otherwise. This induction value is passed to the element access function.

If the *value* argument to *induction* is a non-const lvalue, then that lvalue becomes the live-out object for the returned induction object. For each induction object that has a live-out object, the looping algorithm assigns the value of $i + n * \text{stride}$ to the live-out object upon return, where *n* is the number of elements in the input range.

Template Parameters

T – The value type to be used by the induction object.

⁷⁸⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Parameters

- **value** – [in] The initial value to use for the induction object
- **stride** – [in] The (optional) stride to use for the induction object (default: 1)

Returns

This returns an induction object with value type *T*, initial *value*, and (if specified) *stride*. If *T* is a lvalue of non-const type, *value* is used as the live-out object for the induction object; otherwise there is no live-out object.

```
template<typename T>
constexpr hpx::parallel::detail::induction_helper<T> hpx::experimental::induction(T &&value)
```

hpx::includes

Defined in header [hpx/algorithm.hpp](#)⁷⁸⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred =
hpx::parallel::detail::less>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, bool>::type hpx::includes(ExPolicy &&policy, FwdIter1
first1, FwdIter1 last1,
FwdIter2 first2, FwdIter2
last2, Pred &&op = Pred())
```

Returns true if every element from the sorted range $[first2, last2)$ is found within the sorted range $[first1, last1)$. Also returns true if $[first2, last2)$ is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*. Executed according to the policy.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The comparison operations in the parallel *includes* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: At most $2*(N1+N2-1)$ comparisons, where $N1 = \text{std::distance}(first1, last1)$ and $N2 = \text{std::distance}(first2, last2)$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.

⁷⁸⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *includes* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *includes* algorithm returns true every element from the sorted range `[first2, last2)` is found within the sorted range `[first1, last1)`. Also returns true if `[first2, last2)` is empty.

```
template<typename FwdIter1, typename FwdIter2, typename Pred = hpx::parallel::detail::less>
bool hpx::includes(FwdIter1 first1, FwdIter1 last1, FwdIter2 first2, FwdIter2 last2, Pred &&op = Pred())
```

Returns true if every element from the sorted range `[first2, last2)` is found within the sorted range `[first1, last1)`. Also returns true if `[first2, last2)` is empty. The version expects both ranges to be sorted with the user supplied binary predicate *f*.

Note: At most $2 \cdot (N1 + N2 - 1)$ comparisons, where $N1 = \text{std::distance}(\text{first1}, \text{last1})$ and $N2 = \text{std::distance}(\text{first2}, \text{last2})$.

Template Parameters

- **FwdIter1** – The type of the source iterators used for the first range (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the source iterators used for the second range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of an optional function/function object to use. Unlike its sequential form, the parallel overload of *includes* requires *Pred* to meet the requirements of *CopyConstructible*. This defaults to `std::less<>`

Parameters

- **first1** – Refers to the beginning of the sequence of elements of the first range the algorithm will be applied to.
- **last1** – Refers to the end of the sequence of elements of the first range the algorithm will be applied to.
- **first2** – Refers to the beginning of the sequence of elements of the second range the algorithm will be applied to.
- **last2** – Refers to the end of the sequence of elements of the second range the algorithm will be applied to.
- **op** – The binary predicate which returns true if the elements should be treated as includes. The signature of the predicate function should be equivalent to the following:

```
bool pred(const Type1 &a, const Type2 &b);
```

The signature does not need to have `const &`, but the function must not modify the objects passed to it. The types *Type1* and *Type2* must be such that objects of types *FwdIter1* and *FwdIter2* can be dereferenced and then implicitly converted to *Type1* and *Type2* respectively

Returns

The *includes* algorithm returns a *bool*. The *includes* algorithm returns true every element from the sorted range [*first2*, *last2*) is found within the sorted range [*first1*, *last1*). Also returns true if [*first2*, *last2*) is empty.

hpx::move

Defined in header `hpx/algorithm.hpp`⁷⁸⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::move(ExPolicy &&policy, FwdIter1 first,
                                                                              FwdIter1 last, FwdIter2 dest)
```

Moves the elements in the range [*first*, *last*), to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move. Executed according to the policy.

The move assignments in the parallel *move* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The move assignments in the parallel *move* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* move assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the move assignments.

⁷⁸⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns a `hpx::future<FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *move* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

```
template<typename FwdIter1, typename FwdIter2>
FwdIter2 hpx::move(FwdIter1 first, FwdIter1 last, FwdIter2 dest)
```

Moves the elements in the range [first, last), to another range beginning at *dest*. After this operation the elements in the moved-from range will still contain valid values of the appropriate type, but not necessarily the same values as before the move.

Note: Complexity: Performs exactly *last - first* move assignments.

Template Parameters

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *move* algorithm returns a *FwdIter2*. The *move* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

hpx::uninitialized_move

Defined in header [hpx/algorithm.hpp](#)⁷⁸⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::uninitialized_move_n`

template<typename **InIter**, typename **FwdIter**>

FwdIter **hpx::uninitialized_move**(*InIter* first, *InIter* last, *FwdIter* dest)

Moves the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in [first, last) are left in a valid but unspecified state.

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_move* algorithm returns *FwdIter*. The *uninitialized_move* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

template<typename **ExPolicy**, typename **FwdIter1**, typename **FwdIter2**>

hpx::parallel::util::detail::algorithm_result_t<*ExPolicy*, *FwdIter2*> **hpx::uninitialized_move**(*ExPolicy* &&policy, *FwdIter1* first, *FwdIter1* last, *FwdIter2* dest)

Moves the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the initialization, some objects in [first, last) are left in a valid but unspecified state. Executed according to the policy.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_move* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

⁷⁸⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: Performs exactly *last - first* assignments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_move* algorithm returns a `hpx::future<FwdIter2>`, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *uninitialized_move* algorithm returns the output iterator to the element in the destination range, one past the last element moved.

hpx::uninitialized_move_n

Defined in header `hpx/algorithm.hpp`⁷⁹⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::uninitialized_move`

```
template<typename InIter, typename Size, typename FwdIter>
```

```
std::pair<InIter, FwdIter> hpx::uninitialized_move_n(InIter first, Size count, FwdIter dest)
```

Moves the elements in the range `[first, first + count)`, starting from `first` and proceeding to `first + count - 1`, to another range beginning at `dest`. If an exception is thrown during the initialization, some objects in `[first, first + count)` are left in a valid but unspecified state.

Note: Complexity: Performs exactly *count* movements, if *count* > 0, no move operations otherwise.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.

⁷⁹⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_move_n* algorithm returns a `std::pair<InIter,FwdIter>`. The *uninitialized_move_n* algorithm returns A pair whose first element is an iterator to the element past the last element moved in the source range, and whose second element is an iterator to the element past the last element moved in the destination range.

```
template<typename ExPolicy, typename FwdIter1, typename Size, typename FwdIter2>
parallel::util::detail::algorithm_result<ExPolicy, std::pair<FwdIter1, FwdIter2>>::type hpx::uninitialized_move_n(ExPolicy
                                                                                                     &&pol-
                                                                                                     icy,
                                                                                                     FwdIter1
                                                                                                     first,
                                                                                                     Size
                                                                                                     count,
                                                                                                     FwdIter2
                                                                                                     dest)
```

Moves the elements in the range `[first, first + count)`, starting from *first* and proceeding to *first* + *count* - 1., to another range beginning at *dest*. If an exception is thrown during the initialization, some objects in `[first, first + count)` are left in a valid but unspecified state. Executed according to the policy.

The assignments in the parallel *uninitialized_move_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_move_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* movements, if *count* > 0, no move operations otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply *f* to.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_move_n* algorithm returns a `hpx::future<std::pair<FwdIter1,FwdIter2>>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns `std::pair<FwdIter1,FwdIter2>` otherwise. The *uninitialized_move_n* algorithm returns A pair whose first element is an iterator to the element past the last element moved in the source range, and whose second element is an iterator to the element past the last element moved in the destination range.

hpx::reduce

Defined in header `hpx/algorithm.hpp`⁷⁹¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename ExPolicy, typename FwdIter, typename F, typename T = typename
std::iterator_traits<FwdIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, T> hpx::reduce(ExPolicy &&policy, FwdIter first,
                                                                    FwdIter last, T init, F &&f)
```

Returns GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *f*.

Note: GENERALIZED_SUM(op, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(op, b1, ..., bK), GENERALIZED_SUM(op, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

⁷⁹¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *reduce* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`. The types *Type1* *Ret* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to any of those types.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename ExPolicy, typename FwdIter, typename T = typename
std::iterator_traits<FwdIter>::value_type>
util::detail::algorithm_result_t<ExPolicy, T> hpx::reduce(ExPolicy &&policy, FwdIter first, FwdIter last, T init)
Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.
```

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: `GENERALIZED_SUM(+, a1, ..., aN)` is defined as follows:

- a_1 when N is 1
- $op(\text{GENERALIZED_SUM}(+, b_1, \dots, b_K), \text{GENERALIZED_SUM}(+, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *T* otherwise. The *reduce* algorithm returns the result of the generalized sum (applying operator`+`()) over the elements given by the input range `[first, last)`.

```
template<typename ExPolicy, typename FwdIter>
```

```
hpx::parallel::util::detail::algorithm_result<ExPolicy, typename std::iterator_traits<FwdIter>::value_type>::type hpx::reduce(ExPol
&&po
icy,
FwdIt
first,
FwdIt
last)
```

Returns `GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1))`. Executed according to the policy.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *reduce* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator $+$ ().

Note: The type of the initial value (and the result type) T is determined from the `value_type` of the used `FwdIter`.

Note: `GENERALIZED_SUM(+, a1, ..., aN)` is defined as follows:

- $a1$ when N is 1
 - $\text{op}(\text{GENERALIZED_SUM}(+, b1, \dots, bK), \text{GENERALIZED_SUM}(+, bM, \dots, bN))$, where:
 - $b1, \dots, bN$ may be any permutation of $a1, \dots, aN$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns a `hpx::future<T>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns T otherwise (where T is the `value_type` of `FwdIter`). The *reduce* algorithm returns the result of the generalized sum (applying operator $+$ ()) over the elements given by the input range $[\text{first}, \text{last})$.

```
template<typename FwdIter, typename F, typename T = typename std::iterator_traits<FwdIter>::value_type>
T hpx::reduce(FwdIter first, FwdIter last, T init, F &&f)
```

Returns `GENERALIZED_SUM(f, init, *first, ..., *(first + (last - first) - 1))`. Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate f .

Note: `GENERALIZED_SUM(op, a1, ..., aN)` is defined as follows:

- $a1$ when N is 1
- $\text{op}(\text{GENERALIZED_SUM}(\text{op}, b1, \dots, bK), \text{GENERALIZED_SUM}(\text{op}, bM, \dots, bN))$, where:

- $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
- $1 < K+1 = M \leq N$.

Template Parameters

- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *reduce* requires *F* to meet the requirements of *CopyConstructible*.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`. The types *Type1* *Ret* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to any of those types.

Returns

The *reduce* algorithm returns *T*. The *reduce* algorithm returns the result of the generalized sum over the elements given by the input range [first, last).

```
template<typename FwdIter, typename T = typename std::iterator_traits<FwdIter>::value_type>
T hpx::reduce(FwdIter first, FwdIter last, T init)
```

Returns GENERALIZED_SUM(+, init, *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of *reduce* may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: GENERALIZED_SUM(+, $a_1, \dots, a_N$) is defined as follows:

- a_1 when N is 1
 - $\text{op}(\text{GENERALIZED_SUM}(+, b_1, \dots, b_K), \text{GENERALIZED_SUM}(+, b_M, \dots, b_N))$, where:
 - $b_1, \dots, b_N$ may be any permutation of $a_1, \dots, a_N$ and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

- **FwdIter** – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **init** – The initial value for the generalized sum.

Returns

The *reduce* algorithm returns a *T*. The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

```
template<typename FwdIter>
```

```
std::iterator_traits<FwdIter>::value_type hpx::reduce(FwdIter first, FwdIter last)
```

Returns GENERALIZED_SUM(+, T(), *first, ..., *(first + (last - first) - 1)). Executed according to the policy.

The difference between *reduce* and *accumulate* is that the behavior of reduce may be non-deterministic for non-associative or non-commutative binary predicate.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the operator+().

Note: The type of the initial value (and the result type) *T* is determined from the value_type of the used *FwdIter*.

Note: GENERALIZED_SUM(+, a1, ..., aN) is defined as follows:

- a1 when N is 1
 - op(GENERALIZED_SUM(+, b1, ..., bK), GENERALIZED_SUM(+, bM, ..., bN)), where:
 - b1, ..., bN may be any permutation of a1, ..., aN and
 - $1 < K+1 = M \leq N$.
-

Template Parameters

FwdIter – The type of the source begin and end iterators used (deduced). This iterator type must meet the requirements of an input iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *reduce* algorithm returns *T* (where *T* is the value_type of *FwdIter*). The *reduce* algorithm returns the result of the generalized sum (applying operator+()) over the elements given by the input range [first, last).

hpx/parallel/algorithms/iota.hpp

Defined in header `hpx/parallel/algorithms/iota.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
template<typename FwdIter, typename Sent, typename T>
void iota(FwdIter first, Sent last, T value)
```

Fills the range `[first, last)` with sequentially increasing values, starting with *value* and repetitively evaluating `++value`.

The assignments in the *iota* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: Exactly `std::distance(first, last)` assignments and increments.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input or output iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **T** – The type of the value to be assigned (deduced). This type must be weakly incrementable.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns *void*.

```
template<typename ExPolicy, typename FwdIter, typename Sent, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> iota(ExPolicy &&policy, FwdIter first, Sent last, T
                                                                    value)
```

Fills the range `[first, last)` with sequentially increasing values, starting with *value* and repetitively evaluating `++value`.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *iota* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Exactly *std::distance(first, last)* assignments and increments.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of a forward iterator.
- **Sent** – The type of the source sentinel (deduced). This sentinel type must be a sentinel for *FwdIter*.
- **T** – The type of the value to be assigned (deduced). This type must be weakly incrementable.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **value** – The value to be stored in the first element.

Returns

The *iota* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

hpx::destroy

Defined in header [hpx/algorithm.hpp](#)⁷⁹².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::destroy_n*

```
template<typename ExPolicy, typename FwdIter>
util::detail::algorithm_result_t<ExPolicy> hpx::destroy(ExPolicy &&policy, FwdIter first, FwdIter last)
```

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range `[first, last)`. Executed according to the policy.

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

⁷⁹² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The operations in the parallel *destroy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns a *hpx::future<void>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *void* otherwise.

```
template<typename FwdIter>
void hpx::destroy(FwdIter first, FwdIter last)
```

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range `[first, last)`.

Note: Complexity: Performs exactly *last - first* operations.

Template Parameters

FwdIter – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

Returns

The *destroy* algorithm returns a *void*

hpx::destroy_n

Defined in header [hpx/algorithm.hpp](#)⁷⁹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::destroy*

```
template<typename ExPolicy, typename FwdIter, typename Size>  
util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::destroy_n(ExPolicy &&policy, FwdIter first, Size  
count)
```

Destroys objects of type `typename iterator_traits<FwdIter>::value_type` in the range `[first, first + count)`. Executed according to the policy.

The operations in the parallel *destroy_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The operations in the parallel *destroy_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs exactly *count* operations, if *count* > 0, no assignments otherwise.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply this algorithm to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *destroy_n* algorithm returns a *hpx::future<FwdIter>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *destroy_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

```
template<typename FwdIter, typename Size>
```

⁷⁹³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

FwdIter **hpx::destroy_n**(*FwdIter* first, *Size* count)

Destroys objects of type `typename iterator_traits<ForwardIt>::value_type` in the range `[first, first + count)`.

Note: Complexity: Performs exactly *count* operations, if *count* > 0, no assignments otherwise.

Template Parameters

- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply this algorithm to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.

Returns

The *destroy_n* algorithm returns a *FwdIter*. The *destroy_n* algorithm returns the iterator to the element in the source range, one past the last element constructed.

hpx::reduce_by_key

Defined in header `hpx/algorithm.hpp`⁷⁹⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Warning: doxygenfunction: Cannot find function “hpx::reduce_by_key” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

hpx::experimental::for_each_index

Defined in header `hpx/algorithm.hpp`⁷⁹⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **Mapping**, typename **Fun**>

constexpr void **hpx::experimental::for_each_index**(*Mapping* const &mapping, *Fun* fun)

Calls *fun* with every multidimensional index in the domain of *mapping* (i.e., its extents), in sequential order.

If *fun* returns a result, the result is ignored.

The layout mapping is a hint; implementations are encouraged to choose an iteration order that performs well for the given mapping.

Note: Complexity: Applies *fun* exactly the product of all extents of *mapping* times.

⁷⁹⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

⁷⁹⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **Mapping** – A type meeting the layout mapping requirements. Must expose *index_type*, *extents_type*, *static rank()*, and *extents()*.
- **Fun** – The type of the function/function object to use (deduced). *Fun* must meet *CopyConstructible* and be invocable with exactly *Mapping::rank()* arguments of type *Mapping::index_type*.

Parameters

- **mapping** – The layout mapping whose extents define the iteration domain.
- **fun** – Callable invoked as `fun(i0, i1, ...)` for every multidimensional index in the domain.

```
template<typename ExPolicy, typename Mapping, typename Fun>  
hpx::parallel::util::detail::algorithm_result_t<ExPolicy> hpx::experimental::for_each_index(ExPolicy  
                                                                                               &&policy,  
                                                                                               Mapping const  
                                                                                               &mapping,  
                                                                                               Fun fun)
```

Calls *fun* with every multidimensional index in the domain of *mapping* (i.e., its extents), executed according to *policy*.

If *fun* returns a result, the result is ignored.

Note: Complexity: Applies *fun* exactly the product of all extents of *mapping* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced).
- **Mapping** – A type meeting the layout mapping requirements. Must meet *CopyConstructible*.
- **Fun** – The type of the function/function object to use (deduced). Must meet *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for scheduling.
- **mapping** – The layout mapping whose extents define the iteration domain.
- **fun** – Callable invoked as `fun(i0, i1, ...)` for every multidimensional index in the domain.

Returns

hpx::future<void> if the execution policy is *sequenced_task_policy* or *parallel_task_policy*, *void* otherwise.

hpx::all_of

Defined in header `hpx/algorithm.hpp`⁷⁹⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::any_of`
- `hpx::none_of`

```
template<typename ExPolicy, typename FwdIter, typename F>
util::detail::algorithm_result_t<ExPolicy, bool> hpx::all_of(ExPolicy &&policy, FwdIter first, FwdIter last, F
&&f)
```

Checks if unary predicate *f* returns true for all elements in the range [first, last).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *all_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

⁷⁹⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Returns

The *all_of* algorithm returns a `hpx::future<bool>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename ExPolicy, typename InIter, typename F>  
bool hpx::all_of(InIter first, InIter last, F &&f)
```

Checks if unary predicate *f* returns true for all elements in the range [first, last).

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *all_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *all_of* algorithm returns a *bool*. The *all_of* algorithm returns true if the unary predicate *f* returns true for all elements in the range, false otherwise. It returns true if the range is empty.

hpx::any_of

Defined in header `hpx/algorithm.hpp`⁷⁹⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::all_of*
- *hpx::none_of*

```
template<typename ExPolicy, typename FwdIter, typename F>
```

⁷⁹⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
util::detail::algorithm_result_t<ExPolicy, bool> hpx::any_of(ExPolicy &&policy, FwdIter first, FwdIter last, F
&&f)
```

Checks if unary predicate *f* returns true for at least one element in the range [first, last).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *any_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *any_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

```
template<typename InIter, typename F>
bool hpx::any_of(InIter first, InIter last, F &&f)
```

Checks if unary predicate *f* returns true for at least one element in the range [first, last).

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *any_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *any_of* algorithm returns a *bool*. The *any_of* algorithm returns true if the unary predicate *f* returns true for at least one element in the range, false otherwise. It returns false if the range is empty.

hpx::none_of

Defined in header `hpx/algorithm.hpp`⁷⁹⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::all_of*
- *hpx::any_of*

```
template<typename ExPolicy, typename FwdIter, typename F>  
util::detail::algorithm_result_t<ExPolicy, bool> hpx::none_of(ExPolicy &&policy, FwdIter first, FwdIter last, F  
                                     &&f)
```

Checks if unary predicate *f* returns true for no elements in the range [first, last).

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: At most *last - first* applications of the predicate *f*

⁷⁹⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *none_of* algorithm returns a *hpx::future<bool>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *bool* otherwise. The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

```
template<typename InIter, typename F>
bool hpx::none_of(InIter first, InIter last, F &&f)
```

Checks if unary predicate *f* returns true for no elements in the range [first, last).

Note: Complexity: At most *last - first* applications of the predicate *f*

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *none_of* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.

- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have const&, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *none_of* algorithm returns a *bool*. The *none_of* algorithm returns true if the unary predicate *f* returns true for no elements in the range, false otherwise. It returns true if the range is empty.

hpx::inclusive_scan

Defined in header `hpx/algorithm.hpp`⁷⁹⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename InIter, typename OutIter>
```

```
OutIter hpx::inclusive_scan(InIter first, InIter last, OutIter dest)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(+, *first, ..., *(first + (i - result))).

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*, here `std::plus<>()`.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*1, ..., *a*N) is defined as:

- *a*1 when *N* is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*1, ..., *a*K)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, *a*M, ..., *a*N) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

Parameters

⁷⁹⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *inclusive_scan* algorithm returns *OutIter*. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::inclusive_scan(ExPolicy &&policy,
                                                                                          FwdIter1 first,
                                                                                          FwdIter1 last,
                                                                                          FwdIter2 dest)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(+, *first, ..., *(first + (i - result))). Executed according to the policy.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*, here `std::plus<>()`.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *inclusive_scan* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename OutIter, typename Op>
```

```
OutIter hpx::inclusive_scan(InIter first, InIter last, OutIter dest, Op &&op)
```

Assigns through each iterator *i* in [result, result + (last - first)) the value of GENERALIZED_NONCOMMUTATIVE_SUM(op, *first, ..., *(first + (i - result))).

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN) is defined as:

- a1 when N is 1
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aK)
 - GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN) where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:


```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns *OutIter*. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::inclusive_scan(ExPolicy &&policy,
                                                                                          FwdIter1 first,
                                                                                          FwdIter1 last,
                                                                                          FwdIter2 dest, Op
                                                                                          &&op)
```

Assigns through each iterator *i* in `[result, result + (last - first))` the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, *first, ..., *(first + (i - result)))`. Executed according to the policy.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(+, a1, ..., aN)` is defined as:

- `a1` when `N` is 1
 - `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK)`
 - `GENERALIZED_NONCOMMUTATIVE_SUM(+, aM, ..., aN)` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename InIter, typename OutIter, typename Op, typename T>  
OutIter hpx::inclusive_scan(InIter first, InIter last, OutIter dest, Op &&op, T init)
```

Assigns through each iterator *i* in $[\text{result}, \text{result} + (\text{last} - \text{first}))$ the value of `GENERALIZED_NONCOMMUTATIVE_SUM(op, init, *first, ..., *(first + (i - result)))`.

The reduce operations in the parallel *inclusive_scan* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: `GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aN)` is defined as:

- a_1 when N is 1
 - $op(\text{GENERALIZED_NONCOMMUTATIVE_SUM}(op, a_1, \dots, a_K), \text{GENERALIZED_NONCOMMUTATIVE_SUM}(op, a_M, \dots, a_N))$ where $1 < K+1 = M \leq N$.
-

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.

- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns *OutIter*. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Op, typename T>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::inclusive_scan(ExPolicy &&policy,
                                                                                          FwdIter1 first,
                                                                                          FwdIter1 last,
                                                                                          FwdIter2 dest, Op
                                                                                          &&op, T init)
```

Assigns through each iterator *i* in $[\text{result}, \text{result} + (\text{last} - \text{first}))$ the value of GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *init*, **first*, ..., **(first + (i - result))*). Executed according to the policy.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The reduce operations in the parallel *inclusive_scan* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

The difference between *exclusive_scan* and *inclusive_scan* is that *inclusive_scan* includes the *i*th input element in the *i*th sum. If *op* is not mathematically associative, the behavior of *inclusive_scan* may be non-deterministic.

Note: Complexity: $O(\text{last} - \text{first})$ applications of the predicate *op*.

Note: GENERALIZED_NONCOMMUTATIVE_SUM(*op*, *a1*, ..., *aN*) is defined as:

- *a1* when *N* is 1

- `op(GENERALIZED_NONCOMMUTATIVE_SUM(op, a1, ..., aK), GENERALIZED_NONCOMMUTATIVE_SUM(op, aM, ..., aN))` where $1 < K+1 = M \leq N$.
-

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Op** – The type of the binary function object used for the reduction operation.
- **T** – The type of the value to be used as initial (and intermediate) values (deduced).

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **op** – Specifies the function (or function object) which will be invoked for each of the values of the input sequence. This is a binary predicate. The signature of this predicate should be equivalent to:

```
Ret fun(const Type1 &a, const Type1 &b);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The types *Type1* and *Ret* must be such that an object of a type as given by the input sequence can be implicitly converted to any of those types.

- **init** – The initial value for the generalized sum.

Returns

The *inclusive_scan* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *inclusive_scan* algorithm returns the output iterator to the element in the destination range, one past the last element copied.

hpx::for_each

Defined in header `hpx/algorithm.hpp`⁸⁰⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::for_each_n`

template<typename **InIter**, typename **F**>

⁸⁰⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

F **hpx::for_each**(*InIter* first, *InIter* last, *F* &&*f*)

Applies *f* to the result of dereferencing every iterator in the range [first, last).

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Note: Complexity: Applies *f* exactly *last - first* times.

Template Parameters

- **InIter** – The type of the source begin and end iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **F** – The type of the function/function object to use (deduced). *F* must meet requirements of *MoveConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have const&. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

f.

```
template<typename ExPolicy, typename FwdIter, typename F>
util::detail::algorithm_result_t<ExPolicy, void> hpx::for_each(ExPolicy &&policy, FwdIter first, FwdIter last, F
&&f)
```

Applies *f* to the result of dereferencing every iterator in the range [first, last). Executed according to the policy.

If *f* returns a result, the result is ignored.

If the type of *first* satisfies the requirements of a mutable iterator, *f* may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Applies *f* exactly *last - first* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source begin and end iterator used (deduced). This iterator type must meet the requirements of a forward iterator.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each* requires *F* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

`<ignored> pred(const Type &a);`

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *for_each* algorithm returns a *hpx::future<void>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns void otherwise.

hpx::for_each_n

Defined in header `hpx/algorithm.hpp`⁸⁰¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::for_each*

template<typename **InIter**, typename **Size**, typename **F**>

InIter **hpx::for_each_n**(*InIter* first, *Size* count, *F* &&f)

Applies *f* to the result of dereferencing every iterator in the range [first, first + count), starting from first and proceeding to first + count - 1.

⁸⁰¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

If f returns a result, the result is ignored.

If the type of $first$ satisfies the requirements of a mutable iterator, f may apply non-constant functions through the dereferenced iterator.

Note: Complexity: Applies f exactly $count$ times.

Template Parameters

- **InIter** – The type of the source begin and end iterator used (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to apply f to.
- **F** – The type of the function/function object to use (deduced). F must meet requirements of *MoveConstructible*.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at $first$ the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by $[first, last)$. The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

$first + count$ for non-negative values of $count$ and $first$ for negative values.

```
template<typename ExPolicy, typename FwdIter, typename Size, typename F>
util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::for_each_n(ExPolicy &&policy, FwdIter first, Size
                                                                    count, F &&f)
```

Applies f to the result of dereferencing every iterator in the range $[first, first + count)$, starting from $first$ and proceeding to $first + count - 1$. Executed according to the policy.

If f returns a result, the result is ignored.

If the type of $first$ satisfies the requirements of a mutable iterator, f may apply non-constant functions through the dereferenced iterator.

Unlike its sequential form, the parallel overload of *for_each_n* does not return a copy of its *Function* parameter, since parallelization may not permit efficient state accumulation.

The application of function objects in parallel algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The application of function objects in parallel algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Applies f exactly *count* times.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it applies user-provided function objects.
- **FwdIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **Size** – The type of the argument specifying the number of elements to apply f to.
- **F** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *for_each_n* requires F to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **f** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). The signature of this predicate should be equivalent to:

```
<ignored> pred(const Type &a);
```

The signature does not need to have `const&`. The type *Type* must be such that an object of type *FwdIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *for_each_n* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. It returns *first* + *count* for non-negative values of *count* and *first* for negative values.

hpx::remove_copy

Defined in header `hpx/algorithm.hpp`⁸⁰².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::remove_copy_if`

```
template<typename InIter, typename OutIter, typename T = typename std::iterator_traits<InIter>::value_type>
OutIter hpx::remove_copy(InIter first, InIter last, OutIter dest, T const &value)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the comparison operator returns false when compare to value. The order of the elements that are not removed is preserved.

Effects: Copies all the elements referred to by the iterator it in the range [first,last) for which the following corresponding conditions do not hold: `*it == value`

⁸⁰² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

The assignments in the parallel *remove_copy* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*, here comparison operator.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.
- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **T** – The type that the result of dereferencing *FwdIter1* is compared to.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **value** – Value to be removed.

Returns

The *remove_copy* algorithm returns an *OutIter*. The *remove_copy* algorithm returns the iterator to the element past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename T = typename
std::iterator_traits<InIter>::value_type>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::remove_copy(ExPolicy &&policy,
                                                                    FwdIter1 first, FwdIter1
                                                                    last, FwdIter2 dest, T const
                                                                    &value)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the comparison operator returns false when compare to value. The order of the elements that are not removed is preserved. Executed according to the policy.

Effects: Copies all the elements referred to by the iterator it in the range [first,last) for which the following corresponding conditions do not hold: **it == value*

The assignments in the parallel *remove_copy* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove_copy* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*, here comparison operator.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **T** – The type that the result of dereferencing FwdIter1 is compared to.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **value** – Value to be removed.

Returns

The *remove_copy* algorithm returns a *hpx::future<FwdIter2>* if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *remove_copy* algorithm returns the iterator to the element past the last element copied.

hpx::remove_copy_if

Defined in header [hpx/algorithm.hpp](#)⁸⁰³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::remove_copy*

template<typename **InIter**, typename **OutIter**, typename **Pred**>

OutIter hpx::remove_copy_if(*InIter* first, *InIter* last, *OutIter* dest, *Pred* &&pred)

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the predicate *pred* returns false. The order of the elements that are not removed is preserved.

Effects: Copies all the elements referred to by the iterator it in the range [first,last) for which the following corresponding conditions do not hold: INVOKE(pred, *it) != false.

The assignments in the parallel *remove_copy_if* algorithm execute in sequential order in the calling thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **InIter** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an input iterator.

⁸⁰³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

- **OutIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an output iterator.
- **Pred** – The type of the function/function object to use (deduced).

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements to be removed. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *InIter* can be dereferenced and then implicitly converted to *Type*.

Returns

The *remove_copy_if* algorithm returns an *OutIter*. The *remove_copy_if* algorithm returns the iterator to the element past the last element copied.

```
template<typename ExPolicy, typename FwdIter1, typename FwdIter2, typename Pred>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter2> hpx::remove_copy_if(ExPolicy &&policy,
                                                                                      FwdIter1 first,
                                                                                      FwdIter1 last,
                                                                                      FwdIter2 dest, Pred
                                                                                      &&pred)
```

Copies the elements in the range, defined by [first, last), to another range beginning at *dest*. Copies only the elements for which the predicate *pred* returns false. The order of the elements that are not removed is preserved. Executed according to the policy.

Effects: Copies all the elements referred to by the iterator it in the range [first,last) for which the following corresponding conditions do not hold: `INVOKE(pred, *it) != false`.

The assignments in the parallel *remove_copy_if* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *remove_copy_if* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: Performs not more than *last - first* assignments, exactly *last - first* applications of the predicate *pred*.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.

- **FwdIter1** – The type of the source iterators used (deduced). This iterator type must meet the requirements of an forward iterator.
- **FwdIter2** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of an forward iterator.
- **Pred** – The type of the function/function object to use (deduced). Unlike its sequential form, the parallel overload of *remove_copy_if* requires *Pred* to meet the requirements of *CopyConstructible*.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.
- **pred** – Specifies the function (or function object) which will be invoked for each of the elements in the sequence specified by [first, last). This is an unary predicate which returns *true* for the elements to be removed. The signature of this predicate should be equivalent to:

```
bool pred(const Type &a);
```

The signature does not need to have `const&`, but the function must not modify the objects passed to it. The type *Type* must be such that an object of type *FwdIter1* can be dereferenced and then implicitly converted to *Type*.

Returns

The *remove_copy_if* algorithm returns a `hpx::future<FwdIter2>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter2* otherwise. The *remove_copy_if* algorithm returns the iterator to the element past the last element copied.

hpx::uninitialized_relocate

Defined in header `hpx/algorithm.hpp`⁸⁰⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::uninitialized_relocate_n`

```
template<typename InIter1, typename InIter2, typename FwdIter>  
FwdIter hpx::uninitialized_relocate(InIter1 first, InIter2 last, FwdIter dest)
```

Relocates the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the move-construction of an element, all elements left in the input range, as well as all objects already constructed in the destination range are destroyed. After this algorithm completes, the source range should be freed or reused without destroying the objects.

The assignments in the parallel *uninitialized_relocate* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

⁸⁰⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

Note: Complexity: time: $O(n)$, space: $O(1)$ 1) For “trivially relocatable” underlying types (T) and a contiguous iterator range [first, last): $\text{std::distance}(\text{first}, \text{last}) * \text{sizeof}(T)$ bytes are copied. 2) For “trivially relocatable” underlying types (T) and a non-contiguous iterator range [first, last): $\text{std::distance}(\text{first}, \text{last})$ memory copies of $\text{sizeof}(T)$ bytes each are performed. 3) For “non-trivially relocatable” underlying types (T): $\text{std::distance}(\text{first}, \text{last})$ move assignments and destructions are performed.

Note: Declare a type as “trivially relocatable” using the `HPX_DECLARE_TRIVIALY_RELOCATABLE` macros found in `<hpx/type_support/is_trivially_relocatable.hpp>`.

Template Parameters

- **InIter1** – The type of the source iterator first (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the source iterator last (deduced). This iterator type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_relocate* algorithm returns *FwdIter*. The *uninitialized_relocate* algorithm returns the output iterator to the element in the destination range, one past the last element relocated.

```
template<typename ExPolicy, typename InIter1, typename InIter2, typename FwdIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::uninitialized_relocate(ExPolicy
                                                                    &&policy,
                                                                    InIter1 first,
                                                                    InIter2 last,
                                                                    FwdIter dest)
```

Relocates the elements in the range defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the move-construction of an element, all elements left in the input range, as well as all objects already constructed in the destination range are destroyed. After this algorithm completes, the source range should be freed or reused without destroying the objects.

The assignments in the parallel *uninitialized_relocate* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: time: $O(n)$, space: $O(1)$ 1) For “trivially relocatable” underlying types (T) and a contiguous iterator range [first, last): $\text{std::distance}(\text{first}, \text{last}) * \text{sizeof}(T)$ bytes are copied. 2) For “trivially relocatable” underlying types (T) and a non-contiguous iterator range [first, last): $\text{std::distance}(\text{first}, \text{last})$ memory copies of

sizeof(T) bytes each are performed. 3) For “non-trivially relocatable” underlying types (T): std::distance(first, last) move assignments and destructions are performed.

Note: Declare a type as “trivially relocatable” using the HPX_DECLARE_TRIVIALY_RELOCATABLE macros found in <hpx/type_support/is_trivially_relocatable.hpp>.

Note: Parallel execution requires both *first* and *dest* to be contiguous iterators. If either iterator is non-contiguous, the algorithm cannot determine whether the source and destination ranges overlap, and will silently fall back to sequential execution regardless of the execution policy provided.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **InIter1** – The type of the source iterator first (deduced). This iterator type must meet the requirements of an input iterator.
- **InIter2** – The type of the source iterator last (deduced). This iterator type must meet the requirements of an input iterator.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **last** – Refers to the end of the sequence of elements the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range. The assignments in the parallel *uninitialized_relocate_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

Returns

The *uninitialized_relocate* algorithm returns a *hpx::future<FwdIter>*, if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_relocate* algorithm returns the output iterator to the element in the destination range, one past the last element relocated.

hpx::uninitialized_relocate_n

Defined in header [hpx/algorithm.hpp](#)⁸⁰⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::uninitialized_relocate*

⁸⁰⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/algorithm.hpp>

```
template<typename InIter, typename Size, typename FwdIter>
FwdIter hpx::uninitialized_relocate_n(InIter first, Size count, FwdIter dest)
```

Relocates the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the move-construction of an element, all elements left in the input range, as well as all objects already constructed in the destination range are destroyed. After this algorithm completes, the source range should be freed or reused without destroying the objects.

The assignments in the parallel *uninitialized_relocate_n* algorithm invoked without an execution policy object will execute in sequential order in the calling thread.

Note: Complexity: time: $O(n)$, space: $O(1)$ 1) For “trivially relocatable” underlying types (T) and a contiguous iterator range [first, first+count): $\text{count} * \text{sizeof}(T)$ bytes are copied. 2) For “trivially relocatable” underlying types (T) and a non-contiguous iterator range [first, first+count): count memory copies of $\text{sizeof}(T)$ bytes each are performed. 3) For “non-trivially relocatable” underlying types (T): count move assignments and destructions are performed.

Note: Declare a type as “trivially relocatable” using the `HPX_DECLARE_TRIVIALY_RELOCATABLE` macros found in `<hpx/type_support/is_trivially_relocatable.hpp>`.

Template Parameters

- **InIter** – The type of the source iterator first (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to relocate.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_relocate_n* algorithm returns *FwdIter*. The *uninitialized_relocate_n* algorithm returns the output iterator to the element in the destination range, one past the last element relocated.

```
template<typename ExPolicy, typename InIter, typename Size, typename FwdIter>
hpx::parallel::util::detail::algorithm_result_t<ExPolicy, FwdIter> hpx::uninitialized_relocate_n(ExPolicy
                                                                                               &&policy,
                                                                                               InIter first,
                                                                                               Size count,
                                                                                               FwdIter
                                                                                               dest)
```

Relocates the elements in the range, defined by [first, last), to an uninitialized memory area beginning at *dest*. If an exception is thrown during the move-construction of an element, all elements left in the input range, as well as

all objects already constructed in the destination range are destroyed. After this algorithm completes, the source range should be freed or reused without destroying the objects.

The assignments in the parallel *uninitialized_relocate_n* algorithm invoked with an execution policy object of type *sequenced_policy* execute in sequential order in the calling thread.

The assignments in the parallel *uninitialized_relocate_n* algorithm invoked with an execution policy object of type *parallel_policy* or *parallel_task_policy* are permitted to execute in an unordered fashion in unspecified threads, and indeterminately sequenced within each thread.

Note: Complexity: time: $O(n)$, space: $O(1)$ 1) For “trivially relocatable” underlying types (T) and a contiguous iterator range [first, first+count): `count* sizeof(T)` bytes are copied. 2) For “trivially relocatable” underlying types (T) and a non-contiguous iterator range [first, first+count): `count` memory copies of `sizeof(T)` bytes each are performed. 3) For “non-trivially relocatable” underlying types (T): `count` move assignments and destructions are performed.

Note: Declare a type as “trivially relocatable” using the `HPX_DECLARE_TRIVIALLY_RELOCATABLE` macros found in `<hpx/type_support/is_trivially_relocatable.hpp>`.

Note: Parallel execution requires both *first* and *dest* to be contiguous iterators. If either iterator is non-contiguous, the algorithm cannot determine whether the source and destination ranges overlap, and will silently fall back to sequential execution regardless of the execution policy provided.

Template Parameters

- **ExPolicy** – The type of the execution policy to use (deduced). It describes the manner in which the execution of the algorithm may be parallelized and the manner in which it executes the assignments.
- **InIter** – The type of the source iterator first (deduced). This iterator type must meet the requirements of an input iterator.
- **Size** – The type of the argument specifying the number of elements to relocate.
- **FwdIter** – The type of the iterator representing the destination range (deduced). This iterator type must meet the requirements of a forward iterator.

Parameters

- **policy** – The execution policy to use for the scheduling of the iterations.
- **first** – Refers to the beginning of the sequence of elements the algorithm will be applied to.
- **count** – Refers to the number of elements starting at *first* the algorithm will be applied to.
- **dest** – Refers to the beginning of the destination range.

Returns

The *uninitialized_relocate_n* algorithm returns a `hpx::future<FwdIter>` if the execution policy is of type *sequenced_task_policy* or *parallel_task_policy* and returns *FwdIter* otherwise. The *uninitialized_relocate_n* algorithm returns the output iterator to the element in the destination range, one past the last element relocated.

hpx/parallel/util/range.hpp

Defined in header `hpx/parallel/util/range.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **util**

Typedefs

```
template<typename Iterator, typename Sentinel = Iterator>
```

```
using range = hpx::util::iterator_range<Iterator, Sentinel>
```

Functions

```
template<typename Iter, typename Sent>
```

```
range<Iter, Sent> concat(range<Iter, Sent> const &it1, range<Iter, Sent> const &it2)
```

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2>
```

```
range<Iter2, Iter2> init_move(range<Iter2, Sent2> const &dest, range<Iter1, Sent1> const &src)
```

Move objects from the range `src` to `dest`.

Parameters

- **dest** – [in] : range where move the objects
- **src** – [in] : range from where move the objects

Returns

range with the objects moved and the size adjusted

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2>
```

```
range<Iter2, Sent2> uninit_move(range<Iter2, Sent2> const &dest, range<Iter1, Sent1> const  
                                &src)
```

Move objects from the range `src` creating them in `dest`.

Parameters

- **dest** – [in] : range where move and create the objects
- **src** – [in] : range from where move the objects

Returns

range with the objects moved and the size adjusted

```
template<typename Iter, typename Sent>
```

```
void destroy_range(range<Iter, Sent> r)
```

destroy a range of objects

Parameters

r – [in] : range to destroy

```
template<typename Iter, typename Sent>
```

```
range<Iter, Sent> init(range<Iter, Sent> const &r, typename std::iterator_traits<Iter>::value_type  
                      &val)
```

initialize a range of objects with the object `val` moving across them

Parameters

- **r** – [in] : range of elements not initialized
- **val** – [in] : object used for the initialization

Returns

range initialized

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Compare>
bool is_mergeable(range<Iter1, Sent1> const &src1, range<Iter2, Sent2> const &src2, Compare
comp)

: indicate if two ranges have a possible merge
```

Remark

Parameters

- **src1** – [in] : first range
- **src2** – [in] : second range
- **comp** – [in] : object for to compare elements

Returns

true : they can be merged false : they can't be merged

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3,
typename Sent3, typename Compare>
range<Iter3, Sent3> full_merge(range<Iter3, Sent3> const &dest, range<Iter1, Sent1> const
&src1, range<Iter2, Sent2> const &src2, Compare comp)
```

Merge two contiguous ranges src1 and src2 , and put the result in the range dest, returning the range merged.

Parameters

- **dest** – [in] : range where locate the elements merged. the size of dest must be greater or equal than the sum of the sizes of src1 and src2
- **src1** – [in] : first range to merge
- **src2** – [in] : second range to merge
- **comp** – [in] : comparison object

Returns

range with the elements merged and the size adjusted

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Value,
typename Compare>
range<Value*> uninit_full_merge(range<Value*> const &dest, range<Iter1, Sent1> const
&src1, range<Iter2, Sent2> const &src2, Compare comp)
```

Merge two contiguous ranges src1 and src2 , and create and move the result in the uninitialized range dest, returning the range merged.

Parameters

- **dest** – [in] : range where locate the elements merged. the size of dest must be greater or equal than the sum of the sizes of src1 and src2. Initially is un-initialize memory
- **src1** – [in] : first range to merge
- **src2** – [in] : second range to merge
- **comp** – [in] : comparison object

Returns

range with the elements merged and the size adjusted

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Compare>
range<Iter2, Sent2> half_merge(range<Iter2, Sent2> const &dest, range<Iter1, Sent1> const
&src1, range<Iter2, Sent2> const &src2, Compare comp)
```

: Merge two buffers. The first buffer is in a separate memory

Parameters

- **dest** – [in] : range where finish the two buffers merged
- **src1** – [in] : first range to merge in a separate memory
- **src2** – [in] : second range to merge, in the final part of the range where deposit the final results
- **comp** – [in] : object for compare two elements of the type pointed by the Iter1 and Iter2

Returns

: range with the two buffers merged

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename Iter3,
typename Sent3, typename Compare>
bool in_place_merge_uncontiguous(range<Iter1, Sent1> const &src1, range<Iter2, Sent2>
const &src2, range<Iter3, Sent3> &aux, Compare comp)
```

: merge two non contiguous buffers src1 , src2, using the range aux as auxiliary memory

Remark

Parameters

- **src1** – [in] : first range to merge
- **src2** – [in] : second range to merge
- **aux** – [in] : auxiliary range used in the merge
- **comp** – [in] : object for to compare elements

Returns

true : not changes done false : changes in the buffers

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Compare>
range<Iter1, Sent1> in_place_merge(range<Iter1, Sent1> const &src1, range<Iter1, Sent1> const
&src2, range<Iter2, Sent2> &buf, Compare comp)
```

: merge two contiguous buffers (src1, src2) using buf as auxiliary memory

Remark

Parameters

- **src1** – [in] : first range to merge
- **src2** – [in] : second range to merge
- **buf** – [in] : auxiliary memory used in the merge
- **comp** – [in] : object for to compare elements

Returns

true : not changes done false : changes in the buffers

```
template<typename Iter1, typename Sent1, typename Iter2, typename Sent2, typename
Compare>
void merge_flow(range<Iter1, Sent1> rng1, range<Iter2, Sent2> rbuf, range<Iter1, Sent1> rng2,
                Compare cmp)
```

asio

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/asio/asio_util.hpp

Defined in header `hpx/asio/asio_util.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

Functions

```
bool get_endpoint(std::string const &addr, std::uint16_t port, ::asio::ip::tcp::endpoint &ep, bool
force_ipv4 = false)
```

```
std::string get_endpoint_name(::asio::ip::tcp::endpoint const &ep)
```

```
::asio::ip::tcp::endpoint resolve_hostname(std::string const &hostname, std::uint16_t port,
::asio::io_context &io_service, bool force_ipv4 = false)
```

```
detail::endpoint_iterator_type connect_begin(std::string const &address, std::uint16_t port,
::asio::io_context &io_service)
```

```
template<typename Locality>
detail::endpoint_iterator_type connect_begin(Locality const &loc, ::asio::io_context &io_service)
```

Returns an iterator which when dereferenced will give an endpoint suitable for a call to `connect()` related to this locality.

```
inline detail::endpoint_iterator_type connect_end()
```

```
detail::endpoint_iterator_type accept_begin(std::string const &address, std::uint16_t port,
::asio::io_context &io_service)
```

```
template<typename Locality>
detail::endpoint_iterator_type accept_begin(Locality const &loc, ::asio::io_context &io_service)
```

Returns an iterator which when dereferenced will give an endpoint suitable for a call to `accept()` related to this locality.

```
inline detail::endpoint_iterator_type accept_end()
```

assertion

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/assertion/evaluate_assert.hpp

Defined in header `hpx/assertion/evaluate_assert.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **assertion**

hpx/assertion/api.hpp

Defined in header `hpx/assertion/api.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **assertion**

Typedefs

using **assertion_handler** = void (*)(hpx::source_location const &loc, char const *expr, std::string const &msg)

The signature for an assertion handler.

Functions

assertion_handler **set_assertion_handler**(*assertion_handler* handler)

Set the assertion handler to be used within a program. If the handler has been set already once, the call to this function will be ignored.

Note: This function is not thread safe

HPX_CURRENT_SOURCE_LOCATION

Defined in header [hpx/source_location.hpp](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/source_location.hpp)⁸⁰⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::source_location*

Warning: doxygenfunction: Cannot find function “HPX_CURRENT_SOURCE_LOCATION” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::source_location

Defined in header [hpx/source_location.hpp](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/source_location.hpp)⁸⁰⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *HPX_CURRENT_SOURCE_LOCATION*

Warning: doxygenfunction: Cannot find function “hpx::source_location” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

HPX_ASSERT

Defined in header [hpx/assert.hpp](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/assert.hpp).

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *HPX_ASSERT_MSG*

Warning: doxygenfunction: Cannot find function “HPX_ASSERT” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

⁸⁰⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/source_location.hpp

⁸⁰⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/source_location.hpp

HPX_ASSERT_MSG

Defined in header `hpx/assert.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *HPX_ASSERT*

Warning: doxygenfunction: Cannot find function “HPX_ASSERT_MSG” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

async_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::post

Defined in header `hpx/future.hpp`⁸⁰⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

hpx::post (distributed)

```
template<typename F, typename ...Ts>
bool hpx::post(F &&f, Ts&&... ts)
```

Runs the function `f` asynchronously (potentially in a separate thread which might be a part of a thread pool). This is done in a fire-and-forget manner, meaning there is no return value or way to synchronize with the function execution (it does not return an *hpx::future* that would hold the result of that function call).

hpx::post is particularly useful when synchronization mechanisms as heavyweight as futures are not desired, and instead, more lightweight mechanisms like latches or atomic variables are preferred. Essentially, the post function enables the launch of a new thread without the overhead of creating a future.

Note: *hpx::post* is similar to *hpx::async* but does not return a future. This is why there is no way of finding out the result/failure of the execution of this function.

```
template<typename Action, typename ...Ts>
bool hpx::post(hpx::id_type const &id, Ts&&... vs)
```

```
template<typename Action, typename Client, typename Stub, typename Data, typename ...Ts>
bool hpx::post(components::client_base<Client, Stub, Data> const &c, Ts&&... vs)
```

```
template<typename Action, typename DistPolicy, typename ...Ts>
bool hpx::post(DistPolicy const &policy, Ts&&... vs)
```

```
template<typename Action, typename Continuation, typename ...Ts>
```

⁸⁰⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

```
bool hpx::post(Continuation &&c, hpx::id_type const &gid, Ts&&... vs)
```

```
template<typename Action, typename Continuation, typename Client, typename Stub, typename Data,  
typename ...Ts>
```

```
bool hpx::post(Continuation &&cont, components::client_base<Client, Stub, Data> const &c, Ts&&... vs)
```

```
template<typename Action, typename Continuation, typename DistPolicy, typename ...Ts>
```

```
bool hpx::post(Continuation &&c, DistPolicy const &policy, Ts&&... vs)
```

```
template<typename Action, typename Target, typename ...Ts>
```

```
bool hpx::post(Action &&action, Target &&target, Ts&&... ts)
```

The distributed implementation of `hpx::post` can be used by giving an action instance as argument instead of a function, and also by providing another argument with the locality ID or the target ID.

Template Parameters

- **Action** – The type of action instance
- **Target** – The type of target where the action should be executed
- **Ts** – The type of any additional arguments

Parameters

- **action** – The action instance to be executed
- **target** – The target where the action should be executed
- **ts** – Additional arguments

Returns

true if the action was successfully posted, false otherwise.

hpx::launch

Defined in header [hpx/future.hpp](#)⁸⁰⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
struct launch : public hpx::detail::policy_holder<>
```

Launch policies for `hpx::async` etc.

hpx::dataflow

Defined in header [hpx/future.hpp](#)⁸¹⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

`hpx::dataflow` (distributed)

Warning: doxygenfunction: Unable to resolve function “hpx::dataflow” with arguments (F&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

⁸⁰⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁸¹⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>


```
- template<typename Action, typename Target, typename ...Ts> decltype(auto) ↵
↵dataflow(Action &&action, Target &&target, Ts&&... ts)
- template<typename F, typename ...Ts> decltype(auto) dataflow(F &&f, Ts&&... ts)
```

Warning: doxygenfunction: Unable to resolve function “hpx::dataflow” with arguments (Action&&, Target&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename Target, typename ...Ts> decltype(auto) ↵
↵dataflow(Action &&action, Target &&target, Ts&&... ts)
- template<typename F, typename ...Ts> decltype(auto) dataflow(F &&f, Ts&&... ts)
```

hpx::sync

Defined in header `hpx/future.hpp`⁸¹¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

hpx::sync (distributed)

```
template<typename Action, typename F, typename ...Ts>
auto hpx::sync(F &&f, Ts&&... ts) -> decltype(detail::sync_action_dispatch<Action,
std::decay_t<F>>::call(HPX_FORWARD(F, f), HPX_FORWARD(Ts, ts)...))
```

The function template *sync* runs the function *f* synchronously and returns a `hpx::future` that will eventually hold the result of that function call.

```
template<typename Action, typename F, typename ...Ts>
auto hpx::sync(F &&f, Ts&&... ts) -> decltype(detail::sync_action_dispatch<Action,
std::decay_t<F>>::call(HPX_FORWARD(F, f), HPX_FORWARD(Ts, ts)...))
```

The function template *sync* runs the function *f* synchronously and returns a `hpx::future` that will eventually hold the result of that function call.

Warning: doxygenfunction: Unable to resolve function “hpx::sync” with arguments (Action&&, Target&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename F, typename ...Ts> auto sync(F &&f, Ts&&... ts) -
↵> decltype(detail::sync_action_dispatch<Action, std::decay_t<F>>::call(HPX_
↵FORWARD(F, f), HPX_FORWARD(Ts, ts)...))
- template<typename Action, typename Target, typename ...Ts> decltype(auto) ↵
↵sync(Action &&action, Target &&target, Ts&&... ts)
- template<typename F, typename ...Ts> decltype(auto) sync(F &&f, Ts&&... ts)
```

⁸¹¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

hpx::async

Defined in header `hpx/future.hpp`⁸¹².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

hpx::async (distributed)

```
template<typename Action, typename F, typename ...Ts>
auto hpx::async(F &&f, Ts&&... ts) -> decltype(detail::async_action_dispatch<Action,
    std::decay_t<F>::call(HPX_FORWARD(F, f), HPX_FORWARD(Ts, ts)...))
```

The function template *async* runs the function *f* asynchronously (potentially in a separate thread which might be a part of a thread pool) and returns a `hpx::future` that will eventually hold the result of that function call. If no policy is defined, *async* behaves as if it is called with policy being *hpx::launch::async* | *hpx::launch::deferred*. Otherwise, it calls a function *f* with arguments *ts* according to a specific launch policy.

- If the *async* flag is set (i.e. (policy & *hpx::launch::async*) != 0), then *async* executes the callable object *f* on a new thread of execution (with all thread-locals initialized) as if spawned by *hpx::thread*(`std::forward<F>(f), std::forward<Ts>(ts)...), except that if the function f returns a value or throws an exception, it is stored in the shared state accessible through the hpx::future that async returns to the caller.`
- If the *deferred* flag is set (i.e. (policy & *hpx::launch::deferred*) != 0), then *async* converts *f* and *ts...* the same way as by *hpx::thread* constructor, but does not spawn a new thread of execution. Instead, lazy evaluation is performed: the first call to a non-timed wait function on the *hpx::future* that *async* returned to the caller will cause the copy of *f* to be invoked (as a rvalue) with the copies of *ts...* (also passed as rvalues) in the current thread (which does not have to be the thread that originally called *hpx::async*). The result or exception is placed in the shared state associated with the future and only then it is made ready. All further accesses to the same *hpx::future* will return the result immediately.
- If neither *hpx::launch::async* nor *hpx::launch::deferred*, nor any implementation-defined policy flag is set in policy, the behavior is undefined.

If more than one flag is set, it is implementation-defined which policy is selected. For the default (both the *hpx::launch::async* and *hpx::launch::deferred* flags are set in policy), standard recommends (but doesn't require) utilizing available concurrency, and deferring any additional tasks.

In any case, the call to *hpx::async* synchronizes-with (as defined in `std::memory_order`) the call to *f*, and the completion of *f* is sequenced-before making the shared state ready. If the *async* policy is chosen, the associated thread completion synchronizes-with the successful return from the first function that is waiting on the shared state, or with the return of the last function that releases the shared state, whichever comes first. If `std::decay<Function>::type` or each type in `std::decay<Ts>::type` is not constructible from its corresponding argument, the program is ill-formed.

Parameters

- **f** – Callable object to call
- **ts** – parameters to pass to *f*

Returns

hpx::future referring to the shared state created by this call to *hpx::async*.

```
template<typename Action, typename F, typename ...Ts>
auto hpx::async(F &&f, Ts&&... ts) -> decltype(detail::async_action_dispatch<Action,
    std::decay_t<F>::call(HPX_FORWARD(F, f), HPX_FORWARD(Ts, ts)...))
```

The function template *async* runs the function *f* asynchronously (potentially in a separate thread which might be

⁸¹² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

a part of a thread pool) and returns a `hpx::future` that will eventually hold the result of that function call. If no policy is defined, `async` behaves as if it is called with policy being `hpx::launch::async` | `hpx::launch::deferred`. Otherwise, it calls a function `f` with arguments `ts` according to a specific launch policy.

- If the `async` flag is set (i.e. `(policy & hpx::launch::async) != 0`), then `async` executes the callable object `f` on a new thread of execution (with all thread-locals initialized) as if spawned by `hpx::thread(std::forward<F>(f), std::forward<Ts>(ts)...)...`, except that if the function `f` returns a value or throws an exception, it is stored in the shared state accessible through the `hpx::future` that `async` returns to the caller.
- If the `deferred` flag is set (i.e. `(policy & hpx::launch::deferred) != 0`), then `async` converts `f` and `ts...` the same way as by `hpx::thread` constructor, but does not spawn a new thread of execution. Instead, lazy evaluation is performed: the first call to a non-timed wait function on the `hpx::future` that `async` returned to the caller will cause the copy of `f` to be invoked (as a rvalue) with the copies of `ts...` (also passed as rvalues) in the current thread (which does not have to be the thread that originally called `hpx::async`). The result or exception is placed in the shared state associated with the future and only then it is made ready. All further accesses to the same `hpx::future` will return the result immediately.
- If neither `hpx::launch::async` nor `hpx::launch::deferred`, nor any implementation-defined policy flag is set in policy, the behavior is undefined.

If more than one flag is set, it is implementation-defined which policy is selected. For the default (both the `hpx::launch::async` and `hpx::launch::deferred` flags are set in policy), standard recommends (but doesn't require) utilizing available concurrency, and deferring any additional tasks.

In any case, the call to `hpx::async` synchronizes-with (as defined in `std::memory_order`) the call to `f`, and the completion of `f` is sequenced-before making the shared state ready. If the `async` policy is chosen, the associated thread completion synchronizes-with the successful return from the first function that is waiting on the shared state, or with the return of the last function that releases the shared state, whichever comes first. If `std::decay<Function>::type` or each type in `std::decay<Ts>::type` is not constructible from its corresponding argument, the program is ill-formed.

Parameters

- **f** – Callable object to call
- **ts** – parameters to pass to `f`

Returns

`hpx::future` referring to the shared state created by this call to `hpx::async`.

Warning: doxygenfunction: Unable to resolve function “hpx::async” with arguments (Executor&&, hpx::sycl::experimental::sycl_executor::queue_function_ptr_t<Ts...>&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename F, typename ...Ts> auto async(F &&f, Ts&&... ts)
  ↳-> decltype(detail::async_action_dispatch<Action, std::decay_t<F>::call(HPX_
  ↳FORWARD(F, f), HPX_FORWARD(Ts, ts)...)
- template<typename Action, typename Target, typename ...Ts> auto async(Action &&
  ↳action, Target &&target, Ts&&... ts)
- template<typename Executor, typename ...Ts> decltype(auto) async(Executor &&exec,
  ↳hpx::sycl::experimental::sycl_executor::queue_function_ptr_t<Ts...> &&f, Ts&&... ts)
- template<typename F, typename ...Ts> decltype(auto) async(F &&f, Ts&&... ts)
```

```
template<typename Action, typename Target, typename ...Ts>
auto hpx::async(Action &&action, Target &&target, Ts&&... ts)
```

The distributed implementation of `hpx::async` can be used by giving an action instance as argument instead

of a function, and also by providing another argument with the locality ID or the target ID. The action executes asynchronously.

Template Parameters

- **Action** – The type of action instance
- **Target** – The type of target where the action should be executed
- **Ts** – The type of any additional arguments

Parameters

- **action** – The action instance to be executed
- **target** – The target where the action should be executed
- **ts** – Additional arguments

Returns

hpx::future referring to the shared state created by this call to *hpx::async*

async_combinators

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/async_combinators/split_future.hpp

Defined in header *hpx/async_combinators/split_future.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

Functions

template<typename ...Ts>

inline tuple<future<Ts>...> **split_future**(future<tuple<Ts...>> &&f)

The function *split_future* is an operator allowing to split a given future of a sequence of values (any tuple, *std::pair*, or *std::array*) into an equivalent container of futures where each future represents one of the values from the original future. In some sense this function provides the inverse operation of *when_all*.

Note: The following cases are special:

```
tuple<future<void> > split_future(future<tuple<> > && f);
array<future<void>, 1> split_future(future<array<T, 0> > && f);
```

here the returned futures are directly representing the futures which were passed to the function.

Parameters

f – [in] A future holding an arbitrary sequence of values stored in a tuple-like container. This facility supports *hpx::tuple<>*, *std::pair<T1, T2>*, and *std::array<T, N>*

Returns

Returns an equivalent container (same container type as passed as the argument) of futures, where each future refers to the corresponding value in the input parameter. All the returned futures become ready once the input future has become ready. If the input future is exceptional, all output futures will be exceptional as well.

```
template<typename T>
inline std::vector<future<T>> split_future(future<std::vector<T>> &&f, std::size_t size)
```

The function *split_future* is an operator allowing to split a given future of a sequence of values (any `std::vector`) into a `std::vector` of futures where each future represents one of the values from the original `std::vector`. In some sense this function provides the inverse operation of *when_all*.

Parameters

- **f** – [in] A future holding an arbitrary sequence of values stored in a `std::vector`.
- **size** – [in] The number of elements the vector will hold once the input future has become ready

Returns

Returns a `std::vector` of futures, where each future refers to the corresponding value in the input parameter. All the returned futures become ready once the input future has become ready. If the input future is exceptional, all output futures will be exceptional as well.

hpx::wait_some

Defined in header `hpx/future.hpp`⁸¹³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::wait_some_nothrow`
- `hpx::wait_some_n`
- `hpx::wait_some_n_nothrow`

```
template<typename InputIter>
void hpx::wait_some(std::size_t n, InputIter first, InputIter last)
```

The function *wait_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The function *wait_some* returns after *n* futures have become ready. All input futures are still valid after *wait_some* returns.

Note: The function *wait_some* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_some_nothrow* instead.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the function to return.

⁸¹³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.
- **last** – [in] The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.

```
template<typename R>  
void hpx::wait_some(std::size_t n, std::vector<future<R>> &&futures)
```

The function *wait_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The function *wait_some* returns after *n* futures have become ready. All input futures are still valid after *wait_some* returns.

Note: The function *wait_some* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_some_nothrow* instead.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **futures** – [in] A vector holding an arbitrary amount of *future* or *shared_future* objects for which *wait_some* should wait.

```
template<typename R, std::size_t N>  
void hpx::wait_some(std::size_t n, std::array<future<R>, N> &&futures)
```

The function *wait_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The function *wait_some* returns after *n* futures have become ready. All input futures are still valid after *wait_some* returns.

Note: The function *wait_some* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_some_nothrow* instead.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **futures** – [in] An array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_some* should wait.

```
template<typename ...T>
```

void `hpx::wait_some`(`std::size_t` n, `T&&...` futures)

The function `wait_some` is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after n of them finished executing.

Note: The function `wait_all` returns after *n* futures have become ready. All input futures are still valid after `wait_some` returns.

Note: The function `wait_some` will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use `wait_some_nothrow` instead.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **futures** – [in] An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which `wait_some` should wait.

`hpx::wait_some_nothrow`

Defined in header `hpx/future.hpp`⁸¹⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::wait_some`
- `hpx::wait_some_n`
- `hpx::wait_some_n_nothrow`

Warning: doxygenfunction: Cannot find function “`hpx::wait_some_nothrow`” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

`hpx::wait_some_n`

Defined in header `hpx/future.hpp`⁸¹⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::wait_some`
- `hpx::wait_some_nothrow`
- `hpx::wait_some_n_nothrow`

template<typename **InputIter**>

⁸¹⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁸¹⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

```
void hpx::wait_some_n(std::size_t n, InputIter first, std::size_t count)
```

The function `wait_some_n` is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after `n` of them finished executing.

Note: The function `wait_some_n` returns after `n` futures have become ready. All input futures are still valid after `wait_some_n` returns.

Note: The function `wait_some_n` will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use `wait_some_n_nothrow` instead.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.
- **count** – [in] The number of elements in the sequence starting at *first*.

hpx::wait_some_n_nothrow

Defined in header `hpx/future.hpp`⁸¹⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::wait_some`
- `hpx::wait_some_nothrow`
- `hpx::wait_some_n`

Warning: doxygenfunction: Cannot find function “`hpx::wait_some_n_nothrow`” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

hpx::when_any

Defined in header `hpx/future.hpp`⁸¹⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename InputIter, typename Container = vector<future<typename  
std::iterator_traits<InputIter>::value_type>>>
```

⁸¹⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁸¹⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

future<when_any_result<Container>> **hpx::when_any**(InputIter first, InputIter last)

function *when_any* creates a future object that becomes when at least one element in a set of *future* and *shared_future* objects becomes ready. It is a non-deterministic choice operator. It OR-composes all given future objects and returns a new future object representing the same list of futures after one future of that list finishes execution.

Parameters

- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_any* should wait.
- **last** – [in] The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *when_any* should wait.

Returns

Returns a *when_any_result* holding the same list of futures as has been passed to *when_any* and an index pointing to a ready future.

- *future*<when_any_result<Container<future<R>>>>: If the input cardinality is unknown at compile time and the futures are all have the same type. The order of the futures in the output container will be the same as given by the input iterator.

template<typename **Range**>

future<when_any_result<Range>> **hpx::when_any**(Range &values)

function *when_any* creates a future object that becomes when at least one element in a set of *future* and *shared_future* objects becomes ready. It is a non-deterministic choice operator. It OR-composes all given future objects and returns a new future object representing the same list of futures after one future of that list finishes execution.

Parameters

values – [in] A range holding an arbitrary amount of *futures* or *shared_future* objects for which *when_any* should wait.

Returns

Returns a *when_any_result* holding the same list of futures as has been passed to *when_any* and an index pointing to a ready future.

- *future*<when_any_result<Container<future<R>>>>: If the input cardinality is unknown at compile time and the futures are all have the same type. The order of the futures in the output container will be the same as given by the input iterator.

template<typename ...**T**>

future<when_any_result<tuple<future<T>...>>> **hpx::when_any**(T&&... futures)

function *when_any* creates a future object that becomes when at least one element in a set of *future* and *shared_future* objects becomes ready. It is a non-deterministic choice operator. It OR-composes all given future objects and returns a new future object representing the same list of futures after one future of that list finishes execution.

Parameters

futures – [in] An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *when_any* should wait.

Returns

Returns a *when_any_result* holding the same list of futures as has been passed to *when_any* and an index pointing to a ready future.

- *future*<when_any_result<tuple<future<T0>, future<T1>...>>>: If inputs are fixed in number and are of heterogeneous types. The inputs can be any arbitrary number of future objects.

- `future<when_any_result<tuple<>>>>` if *when_any* is called with zero arguments. The returned future will be initially ready.

hpx::when_all

Defined in header `hpx/future.hpp`⁸¹⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InputIter, typename Container = vector<future<typename  
std::iterator_traits<InputIter>::value_type>>>
```

```
hpx::future<Container> hpx::when_all(InputIter first, InputIter last)
```

function *when_all* creates a future object that becomes ready when all elements in a set of *future* and *shared_future* objects become ready. It is an operator allowing to join on the result of all given futures. It AND-composes all given future objects and returns a new future object representing the same list of futures after they finished executing.

Note: Calling this version of *when_all* where `first == last`, returns a future with an empty container that is immediately ready. Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_all* will not throw an exception, but the futures held in the output collection may.

Parameters

- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.
- **last** – [in] The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.

Returns

Returns a future holding the same list of futures as has been passed to *when_all*.

- `future<Container<future<R>>>>`: If the input cardinality is unknown at compile time and the futures are all have the same type. The order of the futures in the output container will be the same as given by the input iterator.

```
template<typename Range>
```

```
hpx::future<Range> hpx::when_all(Range &&values)
```

function *when_all* creates a future object that becomes ready when all elements in a set of *future* and *shared_future* objects become ready. It is an operator allowing to join on the result of all given futures. It AND-composes all given future objects and returns a new future object representing the same list of futures after they finished executing.

Note: Calling this version of *when_all* where the input container is empty, returns a future with an empty container that is immediately ready. Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_all* will not throw an exception, but the futures held in the output collection may.

⁸¹⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

Parameters

values – [in] A range holding an arbitrary amount of *future* or *shared_future* objects for which *when_all* should wait.

Returns

Returns a future holding the same list of futures as has been passed to *when_all*.

- `future<Container<future<R>>>`: If the input cardinality is unknown at compile time and the futures are all have the same type.

```
template<typename ...T>
```

```
hpx::future<hpx::tuple<hpx::future<T>...>> hpx::when_all(T&&... futures)
```

function *when_all* creates a future object that becomes ready when all elements in a set of *future* and *shared_future* objects become ready. It is an operator allowing to join on the result of all given futures. It AND-composes all given future objects and returns a new future object representing the same list of futures after they finished executing.

Note: Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_all* will not throw an exception, but the futures held in the output collection may.

Parameters

futures – [in] An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *when_all* should wait.

Returns

Returns a future holding the same list of futures as has been passed to *when_all*.

- `future<tuple<future<T0>, future<T1>, future<T2>...>>`: If inputs are fixed in number and are of heterogeneous types. The inputs can be any arbitrary number of future objects.
- `future<tuple<>>` if *when_all* is called with zero arguments. The returned future will be initially ready.

hpx::when_some

Defined in header `hpx/future.hpp`⁸¹⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename InputIter, typename Container = vector<future<typename
std::iterator_traits<InputIter>::value_type>>>
```

```
future<when_some_result<Container>> hpx::when_some(std::size_t n, Iterator first, Iterator last)
```

The function *when_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The future returned by the function *when_some* becomes ready when at least *n* argument futures have become ready.

⁸¹⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

Note: Calling this version of *when_some* where *first* == *last*, returns a future with an empty container that is immediately ready. Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_some* will not throw an exception, but the futures held in the output collection may.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.
- **last** – [in] The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *when_all* should wait.

Returns

Returns a *when_some_result* holding the same list of futures as has been passed to *when_some* and indices pointing to ready futures.

- *future*<*when_some_result*<Container<*future*<R>>>>>: If the input cardinality is unknown at compile time and the futures are all of the same type. The order of the futures in the output container will be the same as given by the input iterator.

```
template<typename Range>
```

```
future<when_some_result<Range>> hpx::when_some(std::size_t n, Range &&futures)
```

The function *when_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The future returned by the function *when_some* becomes ready when at least *n* argument futures have become ready.

Note: Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_some* will not throw an exception, but the futures held in the output collection may.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **futures** – [in] A container holding an arbitrary amount of *future* or *shared_future* objects for which *when_some* should wait.

Returns

Returns a *when_some_result* holding the same list of futures as has been passed to *when_some* and indices pointing to ready futures.

- *future*<*when_some_result*<Container<*future*<R>>>>>: If the input cardinality is unknown at compile time and the futures are all of the same type. The order of the futures in the output container will be the same as given by the input iterator.

```
template<typename ...Ts>
```

```
future<when_some_result<tuple<future<T>...>>> hpx::when_some(std::size_t n, Ts&&... futures)
```

The function *when_some* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns a new future object representing the same list of futures after *n* of them finished executing.

Note: The future returned by the function *when_some* becomes ready when at least *n* argument futures have become ready.

Note: Each future and *shared_future* is waited upon and then copied into the collection of the output (returned) future, maintaining the order of the futures in the input collection. The future returned by *when_some* will not throw an exception, but the futures held in the output collection may.

Parameters

- **n** – [in] The number of futures out of the arguments which have to become ready in order for the returned future to get ready.
- **futures** – [in] An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *when_some* should wait.

Returns

Returns a *when_some_result* holding the same list of futures as has been passed to *when_some* and an index pointing to a ready future..

- *future<when_some_result<tuple<future<T0>, future<T1>...>>>*: If inputs are fixed in number and are of heterogeneous types. The inputs can be any arbitrary number of future objects.
- *future<when_some_result<tuple<>>>* if *when_some* is called with zero arguments. The returned future will be initially ready.

hpx::wait_each

Defined in header [hpx/future.hpp](#)⁸²⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::wait_each_nothrow*
- *hpx::wait_each_n*
- *hpx::wait_each_n_nothrow*

```
template<typename F, typename Future>
```

```
void hpx::wait_each(F &&f, std::vector<Future> &&futures)
```

The function *wait_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns after they finished executing. Additionally, the supplied function is called for each of the passed futures as soon as the future has become ready. *wait_each* returns after all futures have been become ready.

⁸²⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that `std::size_t` is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **futures** – A vector holding an arbitrary amount of *future* or *shared_future* objects for which *wait_each* should wait.

```
template<typename F, typename Iterator>
void hpx::wait_each(F &&f, Iterator begin, Iterator end)
```

The function *wait_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns after they finished executing. Additionally, the supplied function is called for each of the passed futures as soon as the future has become ready. *wait_each* returns after all futures have been become ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that `std::size_t` is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_each* should wait.
- **end** – The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *wait_each* should wait.

```
template<typename F, typename ...T>
void hpx::wait_each(F &&f, T&&... futures)
```

The function *wait_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns after they finished executing. Additionally, the supplied function is called for each of the passed futures as soon as the future has become ready. *wait_each* returns after all futures have been become ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that `std::size_t` is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.

- **futures** – An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *wait_each* should wait.

hpx::wait_each_nothrow

Defined in header [hpx/future.hpp](#)⁸²¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::wait_each*
- *hpx::wait_each_n*
- *hpx::wait_each_n_nothrow*

Warning: doxygenfunction: Cannot find function “hpx::wait_each_nothrow” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::wait_each_n

Defined in header [hpx/future.hpp](#)⁸²².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::wait_each*
- *hpx::wait_each_nothrow*
- *hpx::wait_each_n_nothrow*

template<typename **F**, typename **Iterator**>

void **hpx::wait_each_n**(*F* &&*f*, *Iterator* *begin*, *std::size_t* *count*)

The function *wait_each* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing. Additionally, the supplied function is called for each of the passed futures as soon as the future has become ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_each_n* should wait.
- **count** – The number of elements in the sequence starting at *first*.

⁸²¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁸²² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

hpx::wait_each_n_nothrow

Defined in header [hpx/future.hpp](#)⁸²³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::wait_each*
- *hpx::wait_each_nothrow*
- *hpx::wait_each_n*

Warning: doxygenfunction: Cannot find function “hpx::wait_each_n_nothrow” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::wait_any

Defined in header [hpx/future.hpp](#)⁸²⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::wait_any_nothrow*
- *hpx::wait_any_n*
- *hpx::wait_any_n_nothrow*

template<typename **InputIter**>

void **hpx::wait_any**(InputIter first, InputIter last)

The function *wait_any* is a non-deterministic choice operator. It OR-composes all future objects given and returns after one future of that list finishes execution.

Note: The function *wait_any* returns after at least one future has become ready. All input futures are still valid after *wait_any* returns.

Note: The function *wait_any* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_any_nothrow* instead.

Parameters

- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_any* should wait.
- **last** – [in] The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *wait_any* should wait.

template<typename **R**>

⁸²³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁸²⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

```
void hpx::wait_any(std::vector<future<R>> &futures)
```

The function *wait_any* is a non-deterministic choice operator. It OR-composes all future objects given and returns after one future of that list finishes execution.

Note: The function *wait_any* returns after at least one future has become ready. All input futures are still valid after *wait_any* returns.

Note: The function *wait_any* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_any_nothrow* instead.

Parameters

futures – [in] A vector holding an arbitrary amount of *future* or *shared_future* objects for which *wait_any* should wait.

```
template<typename R, std::size_t N>
void hpx::wait_any(std::array<future<R>, N> &futures)
```

The function *wait_any* is a non-deterministic choice operator. It OR-composes all future objects given and returns after one future of that list finishes execution.

Note: The function *wait_any* returns after at least one future has become ready. All input futures are still valid after *wait_any* returns.

Note: The function *wait_any* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_any_nothrow* instead.

Parameters

futures – [in] An array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_any* should wait.

```
template<typename ...T>
void hpx::wait_any(T&&... futures)
```

The function *wait_any* is a non-deterministic choice operator. It OR-composes all future objects given and returns after one future of that list finishes execution.

Note: The function *wait_any* returns after at least one future has become ready. All input futures are still valid after *wait_any* returns.

Note: The function *wait_any* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_any_nothrow* instead.

Parameters

futures – [in] An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *wait_any* should wait.

hpx::wait_any_nothrow

Defined in header [hpx/future.hpp](#)⁸²⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::wait_any`
- `hpx::wait_any_n`
- `hpx::wait_any_n_nothrow`

Warning: doxygenfunction: Cannot find function “hpx::wait_any_nothrow” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::wait_any_n

Defined in header [hpx/future.hpp](#)⁸²⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::wait_any`
- `hpx::wait_any_nothrow`
- `hpx::wait_any_n_nothrow`

template<typename **InputIter**>

void **hpx::wait_any_n**(*InputIter* first, *std::size_t* count)

The function *wait_any_n* is a non-deterministic choice operator. It OR-composes all future objects given and returns after one future of that list finishes execution.

Note: The function *wait_any_n* returns after at least one future has become ready. All input futures are still valid after *wait_any_n* returns.

Note: The function *wait_any_n* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_any_n_nothrow* instead.

Parameters

- **first** – [in] The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_any_n* should wait.
- **count** – [in] The number of elements in the sequence starting at *first*.

⁸²⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁸²⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

hpx::wait_any_n_nothrow

Defined in header `hpx/future.hpp`⁸²⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::wait_any`
- `hpx::wait_any_nothrow`
- `hpx::wait_any_n`

Warning: doxygenfunction: Cannot find function “hpx::wait_any_n_nothrow” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::wait_all_for

Defined in header `hpx/future.hpp`⁸²⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::wait_all_for_nothrow`
- `hpx::wait_all_for_n`
- `hpx::wait_all_for_n_nothrow`

template<typename **InputIter**>

`hpx::future_status hpx::wait_all_for(hpx::chrono::steady_duration const &timeout, InputIter first, InputIter last)`

The function `wait_all_for` is an operator allowing to join on the result of all given futures, similar to `wait_all`. It differs from `wait_all` in that it will not suspend indefinitely if one or more of the given futures never become ready; instead it returns as soon as either all futures have become ready, or the given timeout has elapsed, whichever happens first.

Note: The function `wait_all_for` returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after `wait_all_for` returns, independently of the returned status, and can be inspected (e.g. using `is_ready()`) to determine which of the given futures have become ready.

Note: The function `wait_all_for` will rethrow any exceptions captured by the futures while becoming ready, as long as all the given futures became ready before the timeout elapsed. If this behavior is undesirable, use `wait_all_for_nothrow` instead.

Parameters

- **timeout** – The maximum duration to wait for all the given futures to become ready.

⁸²⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁸²⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

- **first** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_all_for* should wait.
- **last** – The iterator pointing to the element after the last one of a sequence of *future* or *shared_future* objects for which *wait_all_for* should wait.

Returns

Returns *hpx::future_status::ready* if all the given futures have become ready before *timeout* has elapsed, and *hpx::future_status::timeout* otherwise.

```
template<typename R>  
hpx::future_status hpx::wait_all_for(hpx::chrono::steady_duration const &timeout, std::vector<future<R>>  
                                   const &futures)
```

The function *wait_all_for* is an operator allowing to join on the result of all given futures, similar to *wait_all*. It differs from *wait_all* in that it will not suspend indefinitely if one or more of the given futures never become ready; instead it returns as soon as either all futures have become ready, or the given timeout has elapsed, whichever happens first.

Note: The function *wait_all_for* returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after *wait_all_for* returns, independently of the returned status, and can be inspected (e.g. using *is_ready()*) to determine which of the given futures have become ready.

Note: The function *wait_all_for* will rethrow any exceptions captured by the futures while becoming ready, as long as all the given futures became ready before the timeout elapsed. If this behavior is undesirable, use *wait_all_for_nothrow* instead.

Note: The function *wait_all_for* returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after *wait_all_for* returns, independently of the returned status, and can be inspected (e.g. using *is_ready()*) to determine which of the given futures have become ready.

Note: The caller is responsible for keeping the *futures* container itself (and, for the iterator-range overload, the underlying sequence) alive, unmoved, and unmodified until it is done inspecting the futures' state. If the timeout expires before all futures become ready, *wait_all_for* may leave asynchronous continuations attached to the not-yet-ready futures; destroying, moving, or reallocating the container before those futures settle results in undefined behavior.

Parameters

- **timeout** – The maximum duration to wait for all the given futures to become ready.
- **futures** – A vector or array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_all_for* should wait.

Returns

Returns *hpx::future_status::ready* if all the given futures have become ready before *timeout* has elapsed, and *hpx::future_status::timeout* otherwise.

```
template<typename R, std::size_t N>
```

```
hpx::future_status hpx::wait_all_for(hpx::chrono::steady_duration const &timeout, std::array<future<R>, N>
                                     const &futures)
```

The function *wait_all_for* is an operator allowing to join on the result of all given futures, similar to *wait_all*. It differs from *wait_all* in that it will not suspend indefinitely if one or more of the given futures never become ready; instead it returns as soon as either all futures have become ready, or the given timeout has elapsed, whichever happens first.

Note: The function *wait_all_for* returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after *wait_all_for* returns, independently of the returned status, and can be inspected (e.g. using *is_ready()*) to determine which of the given futures have become ready.

Note: The function *wait_all_for* will rethrow any exceptions captured by the futures while becoming ready, as long as all the given futures became ready before the timeout elapsed. If this behavior is undesirable, use *wait_all_for_nothrow* instead.

Note: The function *wait_all_for* returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after *wait_all_for* returns, independently of the returned status, and can be inspected (e.g. using *is_ready()*) to determine which of the given futures have become ready.

Note: The caller is responsible for keeping the *futures* container itself (and, for the iterator-range overload, the underlying sequence) alive, unmodified, and unmodified until it is done inspecting the futures' state. If the timeout expires before all futures become ready, *wait_all_for* may leave asynchronous continuations attached to the not-yet-ready futures; destroying, moving, or reallocating the container before those futures settle results in undefined behavior.

Parameters

- **timeout** – The maximum duration to wait for all the given futures to become ready.
- **futures** – A vector or array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_all_for* should wait.

Returns

Returns *hpx::future_status::ready* if all the given futures have become ready before *timeout* has elapsed, and *hpx::future_status::timeout* otherwise.

```
template<typename T>
hpx::future_status hpx::wait_all_for(hpx::chrono::steady_duration const &timeout, hpx::future<T> const &f)
```

The function *wait_all_for* is an operator allowing to join on the result of the given future, similar to *wait_all*. It differs from *wait_all* in that it will not suspend indefinitely if the given future never becomes ready; instead it returns as soon as either the future has become ready, or the given timeout has elapsed, whichever happens first.

Note: The function *wait_all_for* returns after the future has become ready, or after the given timeout has expired, whichever comes first. The input future is still valid after *wait_all_for* returns, independently of the returned status.

Note: The function `wait_all_for` will rethrow any exceptions captured by the future while becoming ready, as long as the given future became ready before the timeout elapsed. If this behavior is undesirable, use `wait_all_for_nothrow` instead.

Parameters

- **timeout** – The maximum duration to wait for the given future to become ready.
- **f** – A *future* or *shared_future* for which `wait_all_for` should wait.

Returns

Returns `hpx::future_status::ready` if the given future has become ready before *timeout* has elapsed, and `hpx::future_status::timeout` otherwise.

```
template<typename ...T>
```

```
hpx::future_status hpx::wait_all_for(hpx::chrono::steady_duration const &timeout, T const&... futures)
```

The function `wait_all_for` is an operator allowing to join on the result of all given futures, similar to `wait_all`. It differs from `wait_all` in that it will not suspend indefinitely if one or more of the given futures never become ready; instead it returns as soon as either all futures have become ready, or the given timeout has elapsed, whichever happens first.

Note: The function `wait_all_for` returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after `wait_all_for` returns, independently of the returned status, and can be inspected (e.g. using `is_ready()`) to determine which of the given futures have become ready.

Note: The function `wait_all_for` will rethrow any exceptions captured by the futures while becoming ready, as long as all the given futures became ready before the timeout elapsed. If this behavior is undesirable, use `wait_all_for_nothrow` instead.

Parameters

- **timeout** – The maximum duration to wait for all the given futures to become ready.
- **futures** – An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which `wait_all_for` should wait.

Returns

Returns `hpx::future_status::ready` if all the given futures have become ready before *timeout* has elapsed, and `hpx::future_status::timeout` otherwise.

`hpx::wait_all_for_nothrow`

Defined in header `hpx/future.hpp`⁸²⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::wait_all_for`

⁸²⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

- `hpx::wait_all_for_n`
- `hpx::wait_all_for_n_nothrow`

template<typename **InputIter**>

`hpx::wait_all_for_nothrow_result hpx::wait_all_for_nothrow(hpx::chrono::steady_duration const &timeout, InputIter first, InputIter last)`

The function `wait_all_for_nothrow` is an operator allowing to join on the result of all given futures, similar to `wait_all_for`. It differs from `wait_all_for` in that it will not rethrow any exceptions captured by the given futures while they became ready; instead it returns as soon as either all futures have become ready, or the given timeout has elapsed, whichever happens first.

Note: The function `wait_all_for_nothrow` returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after `wait_all_for_nothrow` returns, independently of the returned status, and can be inspected (e.g. using `is_ready()`) to determine which of the given futures have become ready.

Note: Unlike `wait_all_for_nothrow`, this function will not rethrow any exceptions captured by the futures while becoming ready. Any such exceptions are not rethrown by this call.

Parameters

- **timeout** – The maximum duration to wait for all the given futures to become ready.
- **first** – The iterator pointing to the first element of a sequence of `future` or `shared_future` objects for which `wait_all_for_nothrow` should wait.
- **last** – The iterator pointing to the element after the last one of a sequence of `future` or `shared_future` objects for which `wait_all_for_nothrow` should wait.

Returns

Returns a `wait_all_for_nothrow_result` object whose `status` member is `hpx::future_status::ready` if all the given futures have become ready before `timeout` has elapsed, and `hpx::future_status::timeout` otherwise; and whose `has_exceptional_results` member indicates whether any of the futures that became ready had captured an exception.

template<typename **R**>

`hpx::wait_all_for_nothrow_result hpx::wait_all_for_nothrow(hpx::chrono::steady_duration const &timeout, std::vector<future<R>> const &futures)`

The function `wait_all_for_nothrow` is an operator allowing to join on the result of all given futures, similar to `wait_all_for`. It differs from `wait_all_for` in that it will not rethrow any exceptions captured by the given futures while they became ready; instead it returns as soon as either all futures have become ready, or the given timeout has elapsed, whichever happens first.

Note: The function `wait_all_for_nothrow` returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after `wait_all_for_nothrow` returns, independently of the returned status, and can be inspected (e.g. using `is_ready()`) to determine which of the given futures have become ready.

Note: Unlike `wait_all_for`, this function will not rethrow any exceptions captured by the futures while becoming

ready. Any such exceptions are not rethrown by this call.

Note: The function `wait_all_for_nothrow` returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after `wait_all_for` returns, independently of the returned status, and can be inspected (e.g. using `is_ready()`) to determine which of the given futures have become ready.

Note: The caller is responsible for keeping the *futures* container itself (and, for the iterator-range overload, the underlying sequence) alive, unmodified, and unmodified until it is done inspecting the futures' state. If the timeout expires before all futures become ready, `wait_all_for` may leave asynchronous continuations attached to the not-yet-ready futures; destroying, moving, or reallocating the container before those futures settle results in undefined behavior.

Parameters

- **timeout** – The maximum duration to wait for all the given futures to become ready.
- **futures** – A vector or array holding an arbitrary amount of *future* or *shared_future* objects for which `wait_all_for_nothrow` should wait.

Returns

Returns a `wait_all_for_nothrow_result` object whose *status* member is `hpx::future_status::ready` if all the given futures have become ready before *timeout* has elapsed, and `hpx::future_status::timeout` otherwise; and whose *has_exceptional_results* member indicates whether any of the futures that became ready had captured an exception.

```
template<typename R, std::size_t N>
hpx::wait_all_for_nothrow_result hpx::wait_all_for_nothrow(hpx::chrono::steady_duration const &timeout,
                                                           std::array<future<R>, N> const &futures)
```

The function `wait_all_for_nothrow` is an operator allowing to join on the result of all given futures, similar to `wait_all_for`. It differs from `wait_all_for` in that it will not rethrow any exceptions captured by the given futures while they became ready; instead it returns as soon as either all futures have become ready, or the given timeout has elapsed, whichever happens first.

Note: The function `wait_all_for_nothrow` returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after `wait_all_for_nothrow` returns, independently of the returned status, and can be inspected (e.g. using `is_ready()`) to determine which of the given futures have become ready.

Note: Unlike `wait_all_for`, this function will not rethrow any exceptions captured by the futures while becoming ready. Any such exceptions are not rethrown by this call.

Note: The function `wait_all_for_nothrow` returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after `wait_all_for` returns, independently of the returned status, and can be inspected (e.g. using `is_ready()`) to determine which of the given futures have become ready.

Note: The caller is responsible for keeping the *futures* container itself (and, for the iterator-range overload, the underlying sequence) alive, unmove, and unmodified until it is done inspecting the futures' state. If the timeout expires before all futures become ready, *wait_all_for* may leave asynchronous continuations attached to the not-yet-ready futures; destroying, moving, or reallocating the container before those futures settle results in undefined behavior.

Parameters

- **timeout** – The maximum duration to wait for all the given futures to become ready.
- **futures** – A vector or array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_all_for_nothrow* should wait.

Returns

Returns a *wait_all_for_nothrow_result* object whose *status* member is *hpx::future_status::ready* if all the given futures have become ready before *timeout* has elapsed, and *hpx::future_status::timeout* otherwise; and whose *has_exceptional_results* member indicates whether any of the futures that became ready had captured an exception.

```
template<typename T>
hpx::wait_all_for_nothrow_result hpx::wait_all_for_nothrow(hpx::chrono::steady_duration const &timeout,
                                                         hpx::future<T> const &f)
```

The function *wait_all_for_nothrow* is an operator allowing to join on the result of the given future, similar to *wait_all_for*. It differs from *wait_all_for* in that it will not rethrow any exceptions captured by the given future while it became ready; instead it returns as soon as either the future has become ready, or the given timeout has elapsed, whichever happens first.

Note: The function *wait_all_for_nothrow* returns after the future has become ready, or after the given timeout has expired, whichever comes first. The input future is still valid after *wait_all_for_nothrow* returns, independently of the returned status.

Note: Unlike *wait_all_for*, this function will not rethrow any exceptions captured by the future while becoming ready. Any such exception is silently discarded.

Parameters

- **timeout** – The maximum duration to wait for the given future to become ready.
- **f** – A *future* or *shared_future* for which *wait_all_for_nothrow* should wait.

Returns

Returns a *wait_all_for_nothrow_result* object whose *status* member is *hpx::future_status::ready* if all the given futures have become ready before *timeout* has elapsed, and *hpx::future_status::timeout* otherwise; and whose *has_exceptional_results* member indicates whether any of the futures that became ready had captured an exception.

```
template<typename ...T>
hpx::wait_all_for_nothrow_result hpx::wait_all_for_nothrow(hpx::chrono::steady_duration const &timeout, T
                                                         const&... futures)
```

The function *wait_all_for_nothrow* is an operator allowing to join on the result of all given futures, similar to *wait_all_for*. It differs from *wait_all_for* in that it will not rethrow any exceptions captured by the given futures

while they became ready; instead it returns as soon as either all futures have become ready, or the given timeout has elapsed, whichever happens first.

Note: The function `wait_all_for_nothrow` returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after `wait_all_for_nothrow` returns, independently of the returned status, and can be inspected (e.g. using `is_ready()`) to determine which of the given futures have become ready.

Note: Unlike `wait_all_for`, this function will not rethrow any exceptions captured by the futures while becoming ready. Any such exceptions are not rethrown by this call.

Parameters

- **timeout** – The maximum duration to wait for all the given futures to become ready.
- **futures** – An arbitrary number of `future` or `shared_future` objects, possibly holding different types for which `wait_all_for_nothrow` should wait.

Returns

Returns a `wait_all_for_nothrow_result` object whose `status` member is `hpx::future_status::ready` if all the given futures have become ready before `timeout` has elapsed, and `hpx::future_status::timeout` otherwise; and whose `has_exceptional_results` member indicates whether any of the futures that became ready had captured an exception.

hpx::wait_all_for_n

Defined in header `hpx/future.hpp`⁸³⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::wait_all_for`
- `hpx::wait_all_for_nothrow`
- `hpx::wait_all_for_n_nothrow`

```
template<typename InputIter>
hpx::future_status hpx::wait_all_for_n(hpx::chrono::steady_duration const &timeout, InputIter begin,
                                       std::size_t count)
```

The function `wait_all_for_n` is an operator allowing to join on the result of all given futures, similar to `wait_all_n`. It differs from `wait_all_n` in that it will not suspend indefinitely if one or more of the given futures never become ready; instead it returns as soon as either all futures have become ready, or the given timeout has elapsed, whichever happens first.

Note: The function `wait_all_for_n` returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after `wait_all_for_n` returns, independently of the returned status, and can be inspected (e.g. using `is_ready()`) to determine which of the given futures have become ready.

⁸³⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

Note: The function `wait_all_for_n` will rethrow any exceptions captured by the futures while becoming ready, as long as all the given futures became ready before the timeout elapsed. If this behavior is undesirable, use `wait_all_for_n_nothrow` instead.

Parameters

- **timeout** – The maximum duration to wait for all the given futures to become ready.
- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which `wait_all_for_n` should wait.
- **count** – The number of elements in the sequence starting at *first*.

Returns

Returns `hpx::future_status::ready` if all the given futures have become ready before *timeout* has elapsed, and `hpx::future_status::timeout` otherwise.

`hpx::wait_all_for_n_nothrow`

Defined in header `hpx/future.hpp`⁸³¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::wait_all_for`
- `hpx::wait_all_for_nothrow`
- `hpx::wait_all_for_n`

template<typename **InputIter**>

`hpx::wait_all_for_n_nothrow_result hpx::wait_all_for_n_nothrow(hpx::chrono::steady_duration const &timeout, InputIter begin, std::size_t count)`

The function `wait_all_for_n_nothrow` is an operator allowing to join on the result of all given futures, similar to `wait_all_n`. It differs from `wait_all_for_n` in that it will not rethrow any exceptions captured by the given futures while they became ready; instead it returns as soon as either all futures have become ready, or the given timeout has elapsed, whichever happens first.

Note: The function `wait_all_for_n_nothrow` returns after all futures have become ready, or after the given timeout has expired, whichever comes first. All input futures are still valid after `wait_all_for_n_nothrow` returns, independently of the returned status, and can be inspected (e.g. using `is_ready()`) to determine which of the given futures have become ready.

Note: Unlike `wait_all_for_n`, this function will not rethrow any exceptions captured by the futures while becoming ready. Any such exceptions are not rethrown by this call.

Parameters

- **timeout** – The maximum duration to wait for all the given futures to become ready.

⁸³¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_all_for_n_nothrow* should wait.
- **count** – The number of elements in the sequence starting at *first*.

Returns

Returns a *wait_all_for_nothrow_result* object whose *status* member is *hpx::future_status::ready* if all the given futures have become ready before *timeout* has elapsed, and *hpx::future_status::timeout* otherwise; and whose *has_exceptional_results* member indicates whether any of the futures that became ready had captured an exception.

hpx::wait_all

Defined in header [hpx/future.hpp](#)⁸³².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::wait_all_nothrow*
- *hpx::wait_all_n*
- *hpx::wait_all_n_nothrow*

template<typename **InputIter**>

void **hpx::wait_all**(*InputIter* first, *InputIter* last)

The function *wait_all* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function *wait_all* returns after all futures have become ready. All input futures are still valid after *wait_all* returns.

Note: The function *wait_all* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_all_nothrow* instead.

Note: The caller is responsible for keeping the *futures* container alive, unmoved, and unmodified until *wait_all* returns and all inspection of the futures is complete.

Parameters

- **first** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_all* should wait.
- **last** – The iterator pointing to the element after the last one of a sequence of *future* or *shared_future* objects for which *wait_all* should wait.

template<typename **R**>

⁸³² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

```
void hpx::wait_all(std::vector<future<R>> &&futures)
```

The function *wait_all* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function *wait_all* returns after all futures have become ready. All input futures are still valid after *wait_all* returns.

Note: The function *wait_all* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_all_nothrow* instead.

Note: The caller is responsible for keeping the *futures* container alive, unmoved, and unmodified until *wait_all* returns and all inspection of the futures is complete.

Parameters

futures – A vector or array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_all* should wait.

```
template<typename R, std::size_t N>
```

```
void hpx::wait_all(std::array<future<R>, N> &&futures)
```

The function *wait_all* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function *wait_all* returns after all futures have become ready. All input futures are still valid after *wait_all* returns.

Note: The function *wait_all* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_all_nothrow* instead.

Note: The caller is responsible for keeping the *futures* container alive, unmoved, and unmodified until *wait_all* returns and all inspection of the futures is complete.

Parameters

futures – A vector or array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_all* should wait.

```
template<typename T>
```

```
void hpx::wait_all(hpx::future<T> const &f)
```

The function *wait_all* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function *wait_all* returns after the future has become ready. The input future is still valid after *wait_all* returns.

Note: The function `wait_all` will rethrow any exceptions captured by the future while becoming ready. If this behavior is undesirable, use `wait_all_nothrow` instead.

Parameters

f – A *future* or *shared_future* for which `wait_all` should wait.

```
template<typename ...T>
void hpx::wait_all(T&&... futures)
```

The function `wait_all` is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function `wait_all` returns after all futures have become ready. All input futures are still valid after `wait_all` returns.

Note: The function `wait_all` will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use `wait_all_nothrow` instead.

Parameters

futures – An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which `wait_all` should wait.

`hpx::wait_all_nothrow`

Defined in header `hpx/future.hpp`⁸³³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::wait_all`
- `hpx::wait_all_n`
- `hpx::wait_all_n_nothrow`

```
template<typename InputIter>
bool hpx::wait_all_nothrow(InputIter first, InputIter last)
```

The function `wait_all_nothrow` is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing, similar to `wait_all`. It differs from `wait_all` in that it will not rethrow any exceptions captured by the given futures while they became ready.

Note: The function `wait_all_nothrow` returns after all futures have become ready. All input futures are still valid after `wait_all_nothrow` returns.

Note: Unlike `wait_all`, this function will not rethrow any exceptions captured by the futures while becoming ready. Any such exceptions are not rethrown by this call; the caller can use the returned *bool* to detect their

⁸³³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

presence.

Note: The caller is responsible for keeping the *futures* container alive, unmodified, and unmodified until *wait_all* returns and all inspection of the futures is complete.

Parameters

- **first** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_all_nothrow* should wait.
- **last** – The iterator pointing to the element after the last one of a sequence of *future* or *shared_future* objects for which *wait_all_nothrow* should wait.

Returns

Returns *true* if any of the given futures held an exception once it became ready, and *false* otherwise.

```
template<typename R>
bool hpx::wait_all_nothrow(std::vector<future<R>> &&futures)
```

The function *wait_all_nothrow* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing, similar to *wait_all*. It differs from *wait_all* in that it will not rethrow any exceptions captured by the given futures while they became ready.

Note: The function *wait_all_nothrow* returns after all futures have become ready. All input futures are still valid after *wait_all_nothrow* returns.

Note: Unlike *wait_all*, this function will not rethrow any exceptions captured by the futures while becoming ready. Any such exceptions are not rethrown by this call; the caller can use the returned *bool* to detect their presence.

Parameters

futures – A vector or array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_all_nothrow* should wait.

Returns

Returns *true* if any of the given futures held an exception once it became ready, and *false* otherwise.

```
template<typename R, std::size_t N>
bool hpx::wait_all_nothrow(std::array<future<R>, N> &&futures)
```

The function *wait_all_nothrow* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing, similar to *wait_all*. It differs from *wait_all* in that it will not rethrow any exceptions captured by the given futures while they became ready.

Note: The function *wait_all_nothrow* returns after all futures have become ready. All input futures are still valid after *wait_all_nothrow* returns.

Note: Unlike *wait_all*, this function will not rethrow any exceptions captured by the futures while becoming ready. Any such exceptions are not rethrown by this call; the caller can use the returned *bool* to detect their presence.

Parameters

futures – A vector or array holding an arbitrary amount of *future* or *shared_future* objects for which *wait_all_nothrow* should wait.

Returns

Returns *true* if any of the given futures held an exception once it became ready, and *false* otherwise.

```
template<typename T>
bool hpx::wait_all_nothrow(hpx::future<T> const &f)
```

The function *wait_all_nothrow* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing, similar to *wait_all*. It differs from *wait_all* in that it will not rethrow any exceptions captured by the given future while it became ready.

Note: The function *wait_all_nothrow* returns after the future has become ready. The input future is still valid after *wait_all_nothrow* returns.

Note: Unlike *wait_all*, this function will not rethrow any exception captured by the future while becoming ready. Any such exception is silently discarded; the caller can use the returned *bool* to detect its presence.

Parameters

f – A *future* or *shared_future* for which *wait_all_nothrow* should wait.

Returns

Returns *true* if the given future held an exception once it became ready, and *false* otherwise.

```
template<typename ...T>
bool hpx::wait_all_nothrow(T&&... futures)
```

The function *wait_all_nothrow* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing, similar to *wait_all*. It differs from *wait_all* in that it will not rethrow any exceptions captured by the given futures while they became ready.

Note: The function *wait_all_nothrow* returns after all futures have become ready. All input futures are still valid after *wait_all_nothrow* returns.

Note: Unlike *wait_all*, this function will not rethrow any exceptions captured by the futures while becoming ready. Any such exceptions are not rethrown by this call; the caller can use the returned *bool* to detect their presence.

Parameters

futures – An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *wait_all_nothrow* should wait.

Returns

Returns *true* if any of the given futures held an exception once it became ready, and *false* otherwise.

hpx::wait_all_n

Defined in header [hpx/future.hpp](#)⁸³⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::wait_all*
- *hpx::wait_all_nothrow*
- *hpx::wait_all_n_nothrow*

template<typename **InputIter**>

void **hpx::wait_all_n**(*InputIter* begin, *std::size_t* count)

The function *wait_all_n* is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing.

Note: The function *wait_all_n* returns after all futures have become ready. All input futures are still valid after *wait_all_n* returns.

Note: The function *wait_all_n* will rethrow any exceptions captured by the futures while becoming ready. If this behavior is undesirable, use *wait_all_n_nothrow* instead.

Note: The caller is responsible for keeping the *futures* container alive, unmodified, and unmodified until *wait_all* returns and all inspection of the futures is complete.

Parameters

- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_all_n* should wait.
- **count** – The number of elements in the sequence starting at *first*.

Returns

The function *wait_all_n* will return an iterator referring to the first element in the input sequence after the last processed element.

⁸³⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

hpx::wait_all_n_nothrow

Defined in header `hpx/future.hpp`⁸³⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::wait_all`
- `hpx::wait_all_nothrow`
- `hpx::wait_all_n`

template<typename **InputIter**>

`std::pair<InputIter, bool> hpx::wait_all_n_nothrow(InputIter begin, std::size_t count)`

The function `wait_all_n_nothrow` is an operator allowing to join on the result of all given futures. It AND-composes all future objects given and returns after they finished executing, similar to `wait_all_n`. It differs from `wait_all_n` in that it will not rethrow any exceptions captured by the given futures while they became ready.

Note: The function `wait_all_n_nothrow` returns after all futures have become ready. All input futures are still valid after `wait_all_n_nothrow` returns.

Note: Unlike `wait_all_n`, this function will not rethrow any exceptions captured by the futures while becoming ready. Any such exceptions are not rethrown by this call; the caller can use the returned `bool` to detect their presence.

Note: The caller is responsible for keeping the *futures* container alive, unmoved, and unmodified until `wait_all` returns and all inspection of the futures is complete.

Parameters

- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which `wait_all_n_nothrow` should wait.
- **count** – The number of elements in the sequence starting at *first*.

Returns

The function `wait_all_n_nothrow` returns a pair consisting of an iterator referring to the first element in the input sequence after the last processed element, and a `bool` that is *true* if any of the given futures held an exception once it became ready, and *false* otherwise.

⁸³⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

hpx::when_each

Defined in header `hpx/future.hpp`⁸³⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename F, typename Future>
future<void> hpx::when_each(F &&f, std::vector<Future> &&futures)
```

The function *when_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns a new future object representing the event of all those futures having finished executing. It also calls the supplied callback for each of the futures which becomes ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **futures** – A vector holding an arbitrary amount of *future* or *shared_future* objects for which *wait_each* should wait.

Returns

Returns a future representing the event of all input futures being ready.

```
template<typename F, typename Iterator>
future<Iterator> hpx::when_each(F &&f, Iterator begin, Iterator end)
```

The function *when_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns a new future object representing the event of all those futures having finished executing. It also calls the supplied callback for each of the futures which becomes ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **begin** – The iterator pointing to the first element of a sequence of *future* or *shared_future* objects for which *wait_each* should wait.
- **end** – The iterator pointing to the last element of a sequence of *future* or *shared_future* objects for which *wait_each* should wait.

Returns

Returns a future representing the event of all input futures being ready.

⁸³⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

```
template<typename F, typename ...Ts>
future<void> hpx::when_each(F &&f, Ts&&... futures)
```

The function *when_each* is an operator allowing to join on the results of all given futures. It AND-composes all future objects given and returns a new future object representing the event of all those futures having finished executing. It also calls the supplied callback for each of the futures which becomes ready.

Note: This function consumes the futures as they are passed on to the supplied function. The callback should take one or two parameters, namely either a *future* to be processed or a type that *std::size_t* is implicitly convertible to as the first parameter and the *future* as the second parameter. The first parameter will correspond to the index of the current *future* in the collection.

Parameters

- **f** – The function which will be called for each of the input futures once the future has become ready.
- **futures** – An arbitrary number of *future* or *shared_future* objects, possibly holding different types for which *wait_each* should wait.

Returns

Returns a future representing the event of all input futures being ready.

async_cuda

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/async_cuda/cuda_executor.hpp

Defined in header `hpx/async_cuda/cuda_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

```
namespace cuda
```

```
namespace experimental
```

```
struct cuda_executor : public hpx::cuda::experimental::cuda_executor_base
```

Public Functions

```
inline explicit cuda_executor(std::size_t const device, bool const event_mode = true)
```

```
inline ~cuda_executor()
```

```
template<typename F, typename ...Ts>
```

```
inline void post(F &&f, Ts&&... ts) const
```

```
template<typename F, typename ...Ts>
```

```
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const
```

Protected Functions

```
template<typename R, typename ...Params, typename ...Args>
inline void post_impl(R (*cuda_function)(Params...), Args&&... args) const

template<typename R, typename ...Params, typename ...Args>
inline hpx::future<void> async_impl(R (*cuda_kernel)(Params...), Args&&... args) const
```

```
struct cuda_executor_base
```

Subclassed by *hpx::cuda::experimental::cuda_executor*

Public Types

```
using future_type = hpx::future<void>
```

Public Functions

```
inline cuda_executor_base(std::size_t device, bool const event_mode)

inline future_type get_future() const
```

Protected Attributes

```
int device_
```

```
bool event_mode_
```

```
cudaStream_t stream_
```

```
std::shared_ptr<hpx::cuda::experimental::target> target_
```

```
namespace execution
```

```
namespace experimental
```

hpx/async_cuda/cublas_executor.hpp

Defined in header `hpx/async_cuda/cublas_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

async_mpi

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/async_mpi/mpi_executor.hpp

Defined in header `hpx/async_mpi/mpi_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **mpi**

namespace **experimental**

struct **executor**

Public Types

using **execution_category** = *hpx::execution::parallel_execution_tag*

using **executor_parameters_type** = *hpx::execution::experimental::default_parameters*

Public Functions

inline explicit constexpr **executor**(MPI_Comm communicator = MPI_COMM_WORLD)

template<typename **F**, typename ...**Ts**>

inline decltype(auto) **async_execute**(*F* &&*f*, *Ts*&&... *ts*) const

inline *std::size_t* **in_flight_estimate**() const

Private Members

MPI_Comm **communicator_**

hpx/async_mpi/transform_mpi.hpp

Defined in header `hpx/async_mpi/transform_mpi.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **mpi**

namespace **experimental**

Variables

constexpr struct *hpx::mpi::experimental::transform_mpi_t* **transform_mpi**

struct **transform_mpi_t**

Public Functions

template<typename ...**Args**>
inline constexpr decltype(auto) **operator()** (*Args*&&... args) const

template<typename **Sender**, typename **F**>
inline constexpr auto **operator()** (*Sender* &&s, *F* &&f) const

template<typename **F**>
inline constexpr auto **operator()** (*F* &&f) const

async_sycl

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/async_sycl/sycl_executor.hpp

Defined in header `hpx/async_sycl/sycl_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

template<typename **Executor**, typename ...**Ts**>
decltype(auto) **async** (*Executor* &&exec, *hpx::sycl::experimental::sycl_executor::queue_function_ptr_t*<*Ts*...>
 &&f, *Ts*&&... ts)

hpx::async overload for launching sycl queue member functions with an sycl executor

template<typename **Executor**, typename ...**Ts**>
bool **apply** (*Executor* &&exec, *hpx::sycl::experimental::sycl_executor::queue_function_ptr_t*<*Ts*...> &&f,
 Ts&&... ts)

hpx::apply overload for launching sycl queue member functions with an sycl executor

namespace **execution**

```
namespace experimental
```

```
namespace sycl
```

```
namespace experimental
```

```
struct sycl_executor
```

Public Types

```
using future_type = hpx::future<void>
```

```
template<typename ...Params>
```

```
using queue_function_ptr_t = ::sycl::event  
(::sycl::queue::*)(std::conditional_t<std::is_trivial_v<std::remove_reference_t<Params>>,  
std::decay_t<Params>, Params>...)
```

Default Implementation without the extra intel code_location parameter. Removes the reference for trivial types to make the function matching easier (see `sycl_stream.cpp` test)

Public Functions

```
template<typename sycl_device_selector>  
inline explicit sycl_executor(sycl_device_selector const &selector)
```

Create a SYCL executor (based on a sycl queue)

```
~sycl_executor() = default
```

```
inline future_type get_future()
```

Get future for this command_queue (NOTE will be more efficient if an event is provided — otherwise a dummy kernel must be submitted to get an event)

```
inline future_type get_future(::sycl::event event)
```

Get future for that becomes ready when the given event completes.

```
template<typename ...Params>
```

```
inline void post(queue_function_ptr_t<Params...> &&queue_member_function, Params&&...  
args)
```

Invoke queue member function given queue and parameters — do not use event to return a `hpx::future` (One way)

```
template<typename ...Params>
```

```
inline hpx::future<void> async_execute(queue_function_ptr_t<Params...>  
&&queue_member_function, Params&&... args)
```

Invoke queue member function given queue and parameters — `hpx::future` tied to the sycl event / (two way)

```
inline ::sycl::device get_device() const
```

Return the device used by the underlying SYCL queue.


```
inline ::sycl::context get_context() const
    Return the context used by the underlying SYCL queue.

inline ::sycl::queue &get_queue()
    Return the underlying queue for direct access.
```

Protected Attributes

```
::sycl::queue command_queue
```

cache

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/cache/local_cache.hpp

Defined in header hpx/cache/local_cache.hpp.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

```
    namespace util
```

```
        namespace cache
```

```
        template<typename Key, typename Entry, typename UpdatePolicy = std::less<Entry>, typename
InsertPolicy = policies::always<Entry>, typename CacheStorage = std::map<Key, Entry>,
        typename Statistics = statistics::no_statistics>
        class local_cache
```

#include <hpx/cache/local_cache.hpp> The local_cache implements the basic functionality needed for a local (non-distributed) cache.

Template Parameters

- **Key** – The type of the keys to use to identify the entries stored in the cache
- **Entry** – The type of the items to be held in the cache, must model the CacheEntry concept
- **UpdatePolicy** – A (optional) type specifying a (binary) function object used to sort the cache entries based on their ‘age’. The ‘oldest’ entries (according to this sorting criteria) will be discarded first if the maximum capacity of the cache is reached. The default is std::less<Entry>. The function object will be invoked using 2 entry instances of the type Entry. This type must model the UpdatePolicy model.
- **InsertPolicy** – A (optional) type specifying a (unary) function object used to allow global decisions whether a particular entry should be added to the cache or not. The default is policies::always, imposing no global insert related criteria on the cache. The function object will be invoked using the entry instance to be inserted into the cache. This type must model the InsertPolicy model.
- **CacheStorage** – A (optional) container type used to store the cache items. The container must be an associative and STL compatible container. The default is a std::map<Key, Entry>.

- **Statistics** – A (optional) type allowing to collect some basic statistics about the operation of the cache instance. The type must conform to the `CacheStatistics` concept. The default value is the type `statistics::no_statistics` which does not collect any numbers, but provides empty stubs allowing the code to compile.

Public Types

```
using key_type = Key

using entry_type = Entry

using update_policy_type = UpdatePolicy

using insert_policy_type = InsertPolicy

using storage_type = CacheStorage

using statistics_type = Statistics

using value_type = typename entry_type::value_type

using size_type = typename storage_type::size_type

using storage_value_type = typename storage_type::value_type
```

Public Functions

```
inline explicit local_cache(size_type max_size = 0, update_policy_type const &up =  
    update_policy_type(), insert_policy_type const &ip =  
    insert_policy_type())
```

Construct an instance of a *local_cache*.

Parameters

- **max_size** – [in] The maximal size this cache is allowed to reach any time. The default is zero (no size limitation). The unit of this value is usually determined by the unit of the values returned by the entry's *get_size* function.
- **up** – [in] An instance of the *UpdatePolicy* to use for this cache. The default is to use a default constructed instance of the type as defined by the *UpdatePolicy* template parameter.
- **ip** – [in] An instance of the *InsertPolicy* to use for this cache. The default is to use a default constructed instance of the type as defined by the *InsertPolicy* template parameter.

```
local_cache(local_cache const &other) = default
```

```
local_cache(local_cache &&other) = default
```

```
local_cache &operator=(local_cache const &other) = default
```

local_cache &**operator**=(*local_cache* &&other) = default

~local_cache() = default

inline constexpr *size_type* **size**() const noexcept

Return current size of the cache.

Returns

The current size of this cache instance.

inline constexpr *size_type* **capacity**() const noexcept

Access the maximum size the cache is allowed to grow to.

Note: The unit of this value is usually determined by the unit of the return values of the entry's function *entry::get_size*.

Returns

The maximum size this cache instance is currently allowed to reach. If this number is zero the cache has no limitation with regard to a maximum size.

inline bool **reserve**(*size_type* max_size)

Change the maximum size this cache can grow to.

Parameters

max_size – [in] The new maximum size this cache will be allowed to grow to.

Returns

This function returns *true* if successful. It returns *false* if the new *max_size* is smaller than the current limit and the cache could not be shrunk to the new maximum size.

inline bool **holds_key**(*key_type* const &k) const

Check whether the cache currently holds an entry identified by the given key.

Note: This function does not call the entry's function *entry::touch*. It just checks if the cache contains an entry corresponding to the given key.

Parameters

k – [in] The key for the entry which should be looked up in the cache.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

inline bool **get_entry**(*key_type* const &k, *key_type* &realkey, *entry_type* &val)

Get a specific entry identified by the given key.

Note: The function will call the entry's *entry::touch* function if the value corresponding to the provided key is found in the cache.

Parameters

- **k** – [in] The key for the entry which should be retrieved from the cache.
- **realkey[out]** – Return the full real key found in the cache
- **val** – [out] If the entry indexed by the key is found in the cache this value on successful return will be a copy of the corresponding entry.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
inline bool get_entry(key_type const &k, entry_type &val)
```

Get a specific entry identified by the given key.

Note: The function will call the entry's `entry::touch` function if the value corresponding to the provided key is found in the cache.

Parameters

- **k** – [in] The key for the entry which should be retrieved from the cache.
- **val** – [out] If the entry indexed by the key is found in the cache this value on successful return will be a copy of the corresponding entry.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
inline bool get_entry(key_type const &k, value_type &val)
```

Get a specific entry identified by the given key.

Note: The function will call the entry's `entry::touch` function if the value corresponding to the provided is found in the cache.

Parameters

- **k** – [in] The key for the entry which should be retrieved from the cache
- **val** – [out] If the entry indexed by the key is found in the cache this value on successful return will be a copy of the corresponding value.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
inline bool insert(key_type const &k, value_type const &val)
```

Insert a new element into this cache.

Note: This function invokes both, the insert policy as provided to the constructor and the function `entry::insert` of the newly constructed entry instance. If either of these functions returns false the key/value pair doesn't get inserted into the cache and the `insert` function will return *false*. Other reasons for this function to fail (return *false*) are a) the key/value pair is already held in the cache or b) inserting the new value into the cache maxed out its capacity and it was not possible to free any of the existing entries.

Parameters

- **k** – [in] The key for the entry which should be added to the cache.
- **val** – [in] The value which should be added to the cache.

Returns

This function returns *true* if the entry has been successfully added to the cache, otherwise it returns *false*.

```
inline bool insert(key_type const &k, value_type &&val)
```

```
template<typename Entry_, std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>, entry_type>, int> = 0>
```

```
inline bool insert(key_type const &k, Entry_ &&e)
```

Insert a new entry into this cache.

Note: This function invokes both, the insert policy as provided to the constructor and the function `entry::insert` of the provided entry instance. If either of these functions returns false the key/value pair doesn't get inserted into the cache and the `insert` function will return *false*. Other reasons for this function to fail (return *false*) are a) the key/value pair is already held in the cache or b) inserting the new value into the cache maxed out its capacity and it was not possible to free any of the existing entries.

Parameters

- **k** – [in] The key for the entry which should be added to the cache.
- **e** – [in] The entry which should be added to the cache.

Returns

This function returns *true* if the entry has been successfully added to the cache, otherwise it returns *false*.

```
template<typename Value, std::enable_if_t<std::is_convertible_v<std::decay_t<Value>, value_type>, int> = 0>
```

```
inline bool update(key_type const &k, Value &&val)
```

Update an existing element in this cache.

Note: The function will call the entry's `entry::touch` function if the indexed value is found in the cache.

Note: The difference to the other overload of the `insert` function is that this overload replaces the cached value only, while the other overload replaces the whole cache entry, updating the cache entry properties.

Parameters

- **k** – [in] The key for the value which should be updated in the cache.
- **val** – [in] The value which should be used as a replacement for the existing value in the cache. Any existing cache entry is not changed except for its value.

Returns

This function returns *true* if the entry has been successfully updated, otherwise it returns *false*. If the entry currently is not held by the cache it is added and the return value reflects the outcome of the corresponding insert operation.

```
template<typename F, typename Value, typename = std::enable_if_t<std::is_convertible_v<std::decay_t<Value>, value_type>>>
```

```
inline bool update_if(key_type const &k, Value &&val, F &&f)
```

Update an existing element in this cache.

Note: The function will call the entry's `entry::touch` function if the indexed value is found in the cache.

Note: The difference to the other overload of the `insert` function is that this overload replaces the cached value only, while the other overload replaces the whole cache entry, updating the cache entry properties.

Parameters

- **k** – [in] The key for the value which should be updated in the cache.
- **val** – [in] The value which should be used as a replacement for the existing value in the cache. Any existing cache entry is not changed except for its value.
- **f** – [in] A callable taking two arguments, *k* and the key found in the cache (in that order). If *f* returns true, then the update will continue. If *f* returns false, then the update will not succeed.

Returns

This function returns *true* if the entry has been successfully updated, otherwise it returns *false*. If the entry currently is not held by the cache it is added and the return value reflects the outcome of the corresponding insert operation.

```
template<typename Entry_, std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>,
entry_type>, int> = 0>
```

```
inline bool update(key_type const &k, Entry_ &&e)
```

Update an existing entry in this cache.

Note: The function will call the entry's *entry::touch* function if the indexed value is found in the cache.

Note: The difference to the other overload of the *insert* function is that this overload replaces the whole cache entry, while the other overload replaces the cached value only, leaving the cache entry properties untouched.

Parameters

- **k** – [in] The key for the entry which should be updated in the cache.
- **e** – [in] The entry which should be used as a replacement for the existing entry in the cache. Any existing entry is first removed and then this entry is added.

Returns

This function returns *true* if the entry has been successfully updated, otherwise it returns *false*. If the entry currently is not held by the cache it is added and the return value reflects the outcome of the corresponding insert operation.

```
template<typename Func = policies::always<storage_value_type>>
```

```
inline size_type erase(Func &&ep = Func())
```

Remove stored entries from the cache for which the supplied function object returns true.

Parameters

ep – [in] This parameter has to be a (unary) function object. It is invoked for each of the entries currently held in the cache. An entry is considered for removal from the cache whenever the value returned from this invocation is *true*. Even then the entry might not be removed from the cache as its *entry::remove* function might return false.

Returns

This function returns the overall size of the removed entries (which is the sum of the values returned by the *entry::get_size* functions of the removed entries).

```
inline size_type erase()
```

Remove all stored entries from the cache.

Note: All entries are considered for removal, but in the end an entry might not be removed from the cache as its *entry::remove* function might return false. This function is very useful for instance in conjunction with an entry's *entry::remove* function enforcing additional criteria like entry expiration, etc.

Returns

This function returns the overall size of the removed entries (which is the sum of the values returned by the *entry::get_size* functions of the removed entries).

inline void **clear**()

Clear the cache.

Unconditionally removes all stored entries from the cache.

inline constexpr *statistics_type* const &**get_statistics**() const noexcept

Allow to access the embedded statistics instance.

Returns

This function returns a reference to the statistics instance embedded inside this cache

inline *statistics_type* &**get_statistics**() noexcept

Protected Functions

inline bool **free_space**(long num_free)

Private Types

using **iterator** = typename *storage_type*::iterator

using **const_iterator** = typename *storage_type*::const_iterator

using **heap_type** = std::deque<iterator>

using **heap_iterator** = typename *heap_type*::iterator

using **adapted_update_policy_type** = adapt<UpdatePolicy, iterator>

using **update_on_exit** = typename *statistics_type*::update_on_exit

Private Members

size_type **max_size_**

size_type **current_size_**

storage_type **store_**

heap_type **entry_heap_**

adapted_update_policy_type **update_policy_**

```
insert_policy_type insert_policy_  
  
statistics_type statistics_  
  
template<typename Func, typename Iterator>  
struct adapt
```

Public Functions

```
inline explicit adapt(Func const &f)  
  
inline explicit adapt(Func &&f) noexcept  
  
inline bool operator()(Iterator const &lhs, Iterator const &rhs) const
```

Public Members

```
Func f_
```

hpx/cache/lru_cache.hpp

Defined in header `hpx/cache/lru_cache.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace util
```

```
namespace cache
```

```
template<typename Key, typename Entry, typename Statistics = statistics::no_statistics>
```

```
class lru_cache
```

#include <hpx/cache/lru_cache.hpp> The `lru_cache` implements the basic functionality needed for a local (non-distributed) LRU cache.

Template Parameters

- **Key** – The type of the keys to use to identify the entries stored in the cache
- **Entry** – The type of the items to be held in the cache.
- **Statistics** – A (optional) type allowing to collect some basic statistics about the operation of the cache instance. The type must conform to the `CacheStatistics` concept. The default value is the type `statistics::no_statistics` which does not collect any numbers, but provides empty stubs allowing the code to compile.

Public Types

```
using key_type = Key

using entry_type = Entry

using statistics_type = Statistics

using entry_pair = std::pair<key_type, entry_type>

using storage_type = std::list<entry_pair>

using map_type = std::map<Key, typename storage_type::iterator>

using size_type = std::size_t
```

Public Functions

```
inline explicit lru_cache(size_type max_size = 0)
```

Construct an instance of a *lru_cache*.

Parameters

max_size – [in] The maximal size this cache is allowed to reach any time. The default is zero (no size limitation). The unit of this value is usually determined by the unit of the values returned by the entry's *get_size* function.

```
lru_cache(lru_cache const &other) = default
```

```
lru_cache(lru_cache &&other) = default
```

```
lru_cache &operator=(lru_cache const &other) = default
```

```
lru_cache &operator=(lru_cache &&other) = default
```

```
~lru_cache() = default
```

```
inline constexpr size_type size() const noexcept
```

Return current size of the cache.

Returns

The current size of this cache instance.

```
inline constexpr size_type capacity() const noexcept
```

Access the maximum size the cache is allowed to grow to.

Note: The unit of this value is usually determined by the unit of the return values of the entry's function *entry::get_size*.

Returns

The maximum size this cache instance is currently allowed to reach. If this number is zero the cache has no limitation with regard to a maximum size.

```
inline void reserve(size_type max_size)
```

Change the maximum size this cache can grow to.

Parameters

max_size – [in] The new maximum size this cache will be allowed to grow to.

```
inline bool holds_key(key_type const &key) const
```

Check whether the cache currently holds an entry identified by the given key.

Note: This function does not call the entry’s function *entry::touch*. It just checks if the cache contains an entry corresponding to the given key.

Parameters

key – [in] The key for the entry which should be looked up in the cache.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
inline bool get_entry(key_type const &key, key_type &realkey, entry_type &entry)
```

Get a specific entry identified by the given key.

Note: The function will “touch” the entry and mark it as recently used if the key was found in the cache.

Parameters

- **key** – [in] The key for the entry which should be retrieved from the cache.
- **realkey[out]** – Return the full real key found in the cache
- **entry** – [out] If the entry indexed by the key is found in the cache this value on successful return will be a copy of the corresponding entry.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
inline bool get_entry(key_type const &key, entry_type const &entry)
```

Get a specific entry identified by the given key.

Note: The function will “touch” the entry and mark it as recently used if the key was found in the cache.

Parameters

- **key** – [in] The key for the entry which should be retrieved from the cache.
- **entry** – [out] If the entry indexed by the key is found in the cache this value on successful return will be a copy of the corresponding entry.

Returns

This function returns *true* if the cache holds the referenced entry, otherwise it returns *false*.

```
template<typename Entry_, typename =  
std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>, entry_type>>>  
inline bool insert(key_type const &key, Entry_ &&entry)
```

Insert a new entry into this cache.

Note: This function assumes that the entry is not in the cache already. Inserting an already existing entry is considered undefined behavior

Parameters

- **key** – [in] The key for the entry which should be added to the cache.
- **entry** – [in] The entry which should be added to the cache.

```
template<typename Entry_, typename =
std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>, entry_type>>>
inline void update(key_type const &key, Entry_ &&entry)
```

Update an existing element in this cache.

Note: The function will “touch” the entry and mark it as recently used if the key was found in the cache.

Note: The difference to the other overload of the *insert* function is that this overload replaces the cached value only, while the other overload replaces the whole cache entry, updating the cache entry properties.

Parameters

- **key** – [in] The key for the value which should be updated in the cache.
- **entry** – [in] The entry which should be used as a replacement for the existing value in the cache. Any existing cache entry is not changed except for its value.

```
template<typename F, typename Entry_,
std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>, entry_type>, int> = 0>
inline bool update_if(key_type const &key, Entry_ &&entry, F &&f)
```

Update an existing element in this cache.

Note: The function will “touch” the entry and mark it as recently used if the key was found in the cache.

Note: The difference to the other overload of the *insert* function is that this overload replaces the cached value only, while the other overload replaces the whole cache entry, updating the cache entry properties.

Parameters

- **key** – [in] The key for the value which should be updated in the cache.
- **entry** – [in] The value which should be used as a replacement for the existing value in the cache. Any existing cache entry is not changed except for its value.
- **f** – [in] A callable taking two arguments, *k* and the key found in the cache (in that order). If *f* returns true, then the update will continue. If *f* returns false, then the update will not succeed.

Returns

This function returns *true* if the entry has been successfully updated, otherwise it returns *false*. If the entry currently is not held by the cache it is added and the return value reflects the outcome of the corresponding insert operation.

```
template<typename Func>
inline size_type erase(Func const &ep)
```

Remove stored entries from the cache for which the supplied function object returns true.

Parameters

ep – [in] This parameter has to be a (unary) function object. It is invoked for each of the entries currently held in the cache. An entry is considered for removal from the cache whenever the value returned from this invocation is *true*.

Returns

This function returns the overall size of the removed entries (which is the sum of the values returned by the *entry::get_size* functions of the removed entries).

```
inline size_type erase()
```

Remove all stored entries from the cache.

Returns

This function returns the overall size of the removed entries (which is the sum of the values returned by the *entry::get_size* functions of the removed entries).

```
inline size_type clear()
```

Clear the cache.

Unconditionally removes all stored entries from the cache.

```
inline constexpr statistics_type const &get_statistics() const noexcept
```

Allow to access the embedded statistics instance.

Returns

This function returns a reference to the statistics instance embedded inside this cache

```
inline statistics_type &get_statistics() noexcept
```

Private Types

```
using update_on_exit = typename statistics_type::update_on_exit
```

Private Functions

```
template<typename Entry_, typename =
std::enable_if_t<std::is_convertible_v<std::decay_t<Entry_>, entry_type>>>
inline void insert_nonexist(key_type const &key, Entry_ &&entry)
```

```
inline void touch(typename storage_type::iterator it)
```

```
inline void evict()
```

Private Members

```
size_type max_size_
```

```
size_type current_size_ = 0
```

```
storage_type storage_
```

map_type **map_**

statistics_type **statistics_**

hpx/cache/entries/lfu_entry.hpp

Defined in header `hpx/cache/entries/lfu_entry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

namespace **cache**

namespace **entries**

template<typename **Value**>

class **lfu_entry** : public `hpx::util::cache::entries::entry<Value>`

#include <hpx/cache/entries/lfu_entry.hpp> The `lfu_entry` type can be used to store arbitrary values in a cache. Using this type as the cache's entry type makes sure that the least frequently used entries are discarded from the cache first.

Note: The `lfu_entry` conforms to the `CacheEntry` concept.

Note: This type can be used to model a 'most frequently used' cache policy if it is used with a `std::greater` as the caches' `UpdatePolicy` (instead of the default `std::less`).

Template Parameters

Value – The data type to be stored in a cache. It has to be default constructible, copy constructible and `less_than_comparable`.

Public Functions

lfu_entry() = default

Any cache entry has to be default constructible.

inline explicit **lfu_entry**(*Value* const &val)
 noexcept(*std::is_nothrow_constructible_v<base_type, Value*
 const&>)

Construct a new instance of a cache entry holding the given value.

inline explicit **lfu_entry**(*Value* &&val) noexcept

Construct a new instance of a cache entry holding the given value.

```
inline bool touch() noexcept
```

The function *touch* is called by a cache holding this instance whenever it has been requested (touched).

In the case of the LFU entry we store the reference count tracking the number of times this entry has been requested. This which will be used to compare the age of an entry during the invocation of the *operator<()*.

Returns

This function should return true if the cache needs to update its internal heap. Usually this is needed if the entry has been changed by *touch()* in a way influencing the sort order as mandated by the cache's UpdatePolicy

```
inline constexpr unsigned long const &get_access_count() const noexcept
```

Private Types

```
using base_type = entry<Value>
```

Private Members

```
unsigned long ref_count_ = 0
```

Friends

```
inline friend auto operator<(lfu_entry const &lhs, lfu_entry const &rhs)
```

Compare the 'age' of two entries. An entry is 'older' than another entry if it has been accessed less frequently (LFU).

```
inline friend auto operator>(lfu_entry const &lhs, lfu_entry const &rhs)
```

```
inline friend auto operator<=(lfu_entry const &lhs, lfu_entry const &rhs)
```

```
inline friend auto operator>=(lfu_entry const &lhs, lfu_entry const &rhs)
```

```
inline friend auto operator==(lfu_entry const &lhs, lfu_entry const &rhs)
```

```
inline friend auto operator!=(lfu_entry const &lhs, lfu_entry const &rhs)
```

hpx/cache/entries/fifo_entry.hpp

Defined in header `hpx/cache/entries/fifo_entry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace util
```

```
        namespace cache
```

namespace **entries**

template<typename **Value**>

class **fifo_entry** : public *hpx::util::cache::entries::entry<Value>*

#include <hpx/cache/entries/fifo_entry.hpp> The `fifo_entry` type can be used to store arbitrary values in a cache. Using this type as the cache's entry type makes sure that the least recently inserted entries are discarded from the cache first.

Note: The `fifo_entry` conforms to the `CacheEntry` concept.

Note: This type can be used to model a 'last in first out' cache policy if it is used with a `std::greater` as the caches' `UpdatePolicy` (instead of the default `std::less`).

Template Parameters

Value – The data type to be stored in a cache. It has to be default constructible, copy constructible and `less_than_comparable`.

Public Functions

fifo_entry() = default

Any cache entry has to be default constructible.

inline explicit **fifo_entry**(*Value* const &val)
 noexcept(*std::is_nothrow_constructible_v<base_type, Value*
 const&>)

Construct a new instance of a cache entry holding the given value.

inline explicit **fifo_entry**(*Value* &&val) noexcept

Construct a new instance of a cache entry holding the given value.

inline constexpr bool **insert**()

The function *insert* is called by a cache whenever it is about to be inserted into the cache.

Note: This function is part of the `CacheEntry` concept

Returns

This function should return *true* if the entry should be added to the cache, otherwise it should return *false*.

inline constexpr *time_point* const &**get_creation_time**() const noexcept

Private Types

```
using base_type = entry<Value>

using time_point = std::chrono::steady_clock::time_point
```

Private Members

```
time_point insertion_time_
```

Friends

```
inline friend auto operator<(fifo_entry const &lhs, fifo_entry const &rhs)
    Compare the ‘age’ of two entries. An entry is ‘older’ than another entry if it has been created
    earlier (FIFO).

inline friend auto operator>(fifo_entry const &lhs, fifo_entry const &rhs)

inline friend auto operator<=(fifo_entry const &lhs, fifo_entry const &rhs)

inline friend auto operator>=(fifo_entry const &lhs, fifo_entry const &rhs)

inline friend auto operator==(fifo_entry const &lhs, fifo_entry const &rhs)

inline friend auto operator!=(fifo_entry const &lhs, fifo_entry const &rhs)
```

hpx/cache/entries/entry.hpp

Defined in header hpx/cache/entries/entry.hpp.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace util
```

```
        namespace cache
```

```
            namespace entries
```

```
                template<typename Value>
```

```
                class entry
```

```
                    #include <hpx/cache/entries/entry.hpp>
```

Template Parameters

Value – The data type to be stored in a cache. It has to be default constructible, copy constructible and less_than_comparable.

Subclassed by `hpx::util::cache::entries::fifo_entry< Value >`,
`hpx::util::cache::entries::lfu_entry< Value >`, `hpx::util::cache::entries::lru_entry< Value >`,
`hpx::util::cache::entries::size_entry< Value >`

Public Types

using **value_type** = *Value*

Public Functions

entry() = default

Any cache entry has to be default constructible.

inline explicit **entry**(*value_type* const &val)
noexcept(*std::is_nothrow_copy_constructible_v*<*value_type*>)

Construct a new instance of a cache entry holding the given value.

inline explicit **entry**(*value_type* &&val) noexcept

Construct a new instance of a cache entry holding the given value.

inline *value_type* &**get**() noexcept

Get a reference to the stored data value.

Note: This function is part of the CacheEntry concept

inline constexpr *value_type* const &**get**() const noexcept

Public Static Functions

static inline constexpr bool **touch**() noexcept

The function *touch* is called by a cache holding this instance whenever it has been requested (touched).

Note: It is possible to change the entry in a way influencing the sort criteria mandated by the UpdatePolicy. In this case the function should return *true* to indicate this to the cache, forcing to reorder the cache entries.

Note: This function is part of the CacheEntry concept

Returns

This function should return *true* if the cache needs to update its internal heap. Usually this is needed if the entry has been changed by *touch()* in a way influencing the sort order as mandated by the cache's UpdatePolicy

static inline constexpr bool **insert**() noexcept

The function *insert* is called by a cache whenever it is about to be inserted into the cache.

Note: This function is part of the CacheEntry concept

Returns

This function should return *true* if the entry should be added to the cache, otherwise it should return *false*.

static inline constexpr bool **remove**() noexcept

The function *remove* is called by a cache holding this instance whenever it is about to be removed from the cache.

Note: This function is part of the CacheEntry concept

Returns

The return value can be used to avoid removing this instance from the cache. If the value is *true* it is ok to remove the entry, otherwise it will stay in the cache.

static inline constexpr *std::size_t* **get_size**() noexcept

Return the 'size' of this entry. By default, the size of each entry is just one (1), which is sensible if the cache has a limit (capacity) measured in number of entries.

Private Members

value_type **value_**

Friends

friend auto operator (entry const &, entry const &)=default

Forwarding operator<=> allowing to compare entries instead of the values.

hpx/cache/entries/size_entry.hpp

Defined in header `hpx/cache/entries/size_entry.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **util**

namespace **cache**

namespace **entries**

template<typename **Value**>

class **size_entry** : public *hpx::util::cache::entries::entry*<*Value*>

#include <hpx/cache/entries/size_entry.hpp> The *size_entry* type can be used to store values in a cache which have a size associated (such as files, etc.). Using this type as the cache's entry type makes sure that the entries with the biggest size are discarded from the cache first.

Note: The *size_entry* conforms to the CacheEntry concept.

Note: This type can be used to model a ‘discard smallest first’ cache policy if it is used with a `std::greater` as the caches’ `UpdatePolicy` (instead of the default `std::less`).

Template Parameters

Value – The data type to be stored in a cache. It has to be default constructible, copy constructible and `less_than_comparable`.

Public Functions

size_entry() = default

Any cache entry has to be default constructible.

```
inline explicit size_entry(Value const &val, std::size_t size = 0)
    noexcept(std::is_nothrow_constructible_v<base_type, Value
             const&>)
```

Construct a new instance of a cache entry holding the given value.

```
inline explicit size_entry(Value &&val, std::size_t size = 0) noexcept
```

Construct a new instance of a cache entry holding the given value.

```
inline constexpr std::size_t get_size() const noexcept
```

Return the ‘size’ of this entry.

Private Types

```
using base_type = entry<Value>
```

Private Members

```
std::size_t size_ = 0
```

Friends

```
inline friend auto operator<(size_entry const &lhs, size_entry const &rhs) noexcept
```

Compare the ‘age’ of two entries. An entry is ‘older’ than another entry if it has a bigger size.

```
inline friend auto operator>(size_entry const &lhs, size_entry const &rhs) noexcept
```

```
inline friend auto operator<= (size_entry const &lhs, size_entry const &rhs) noexcept
```

```
inline friend auto operator>= (size_entry const &lhs, size_entry const &rhs) noexcept
```

```
inline friend auto operator== (size_entry const &lhs, size_entry const &rhs) noexcept
```

```
inline friend auto operator!= (size_entry const &lhs, size_entry const &rhs) noexcept
```

hpx/cache/entries/lru_entry.hpp

Defined in header `hpx/cache/entries/lru_entry.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace util
```

```
        namespace cache
```

```
            namespace entries
```

```
                template<typename Value>
```

```
                class lru_entry : public hpx::util::cache::entries::entry<Value>
```

```
                    #include <hpx/cache/entries/lru_entry.hpp> The lru_entry type can be used to store arbitrary values in a cache. Using this type as the cache's entry type makes sure that the least recently used entries are discarded from the cache first.
```

Note: The `lru_entry` conforms to the `CacheEntry` concept.

Note: This type can be used to model a 'most recently used' cache policy if it is used with a `std::greater` as the caches' `UpdatePolicy` (instead of the default `std::less`).

Template Parameters

Value – The data type to be stored in a cache. It has to be default constructible, copy constructible and `less_than_comparable`.

Public Functions

```
inline lru_entry()
```

Any cache entry has to be default constructible.

```
inline explicit lru_entry(Value const &val)
    noexcept(std::is_nothrow_constructible_v<base_type, Value>, Value
    const&>)
```

Construct a new instance of a cache entry holding the given value.

```
inline explicit lru_entry(Value &&val) noexcept
```

Construct a new instance of a cache entry holding the given value.

```
inline bool touch()
```

The function *touch* is called by a cache holding this instance whenever it has been requested (touched).

In the case of the LRU entry we store the time of the last access which will be used to compare the age of an entry during the invocation of the *operator<()*.

Returns

This function should return true if the cache needs to update its internal heap. Usually this is needed if the entry has been changed by *touch()* in a way influencing the sort order as mandated by the cache's UpdatePolicy

```
inline constexpr time_point const &get_access_time() const noexcept
```

Returns the last access time of the entry.

Private Types

```
using base_type = entry<Value>
```

```
using time_point = std::chrono::steady_clock::time_point
```

Private Members

```
time_point access_time_
```

Friends

```
inline friend auto operator<(lru_entry const &lhs, lru_entry const &rhs)
```

Compare the 'age' of two entries. An entry is 'older' than another entry if it has been accessed less recently (LRU).

```
inline friend auto operator>(lru_entry const &lhs, lru_entry const &rhs)
```

```
inline friend auto operator<=(lru_entry const &lhs, lru_entry const &rhs)
```

```
inline friend auto operator>=(lru_entry const &lhs, lru_entry const &rhs)
```

```
inline friend auto operator==(lru_entry const &lhs, lru_entry const &rhs)
```

```
inline friend auto operator!=(lru_entry const &lhs, lru_entry const &rhs)
```

hpx/cache/statistics/no_statistics.hpp

Defined in header `hpx/cache/statistics/no_statistics.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace util
```

```
        namespace cache
```

```
            namespace statistics
```

Enums

enum class **method**

Values:

enumerator **get_entry**

enumerator **insert_entry**

enumerator **update_entry**

enumerator **erase_entry**

class **no_statistics**

Subclassed by *hpx::util::cache::statistics::local_statistics*

Public Static Functions

static inline constexpr void **got_hit**() noexcept

The function *got_hit* will be called by a cache instance whenever an entry got touched.

static inline constexpr void **got_miss**() noexcept

The function *got_miss* will be called by a cache instance whenever a requested entry has not been found in the cache.

static inline constexpr void **got_insertion**() noexcept

The function *got_insertion* will be called by a cache instance whenever a new entry has been inserted.

static inline constexpr void **got_eviction**() noexcept

The function *got_eviction* will be called by a cache instance whenever an entry has been removed from the cache because a new inserted entry let the cache grow beyond its capacity.

static inline constexpr void **clear**() noexcept

Reset all statistics.

static inline constexpr std::int64_t **get_get_entry_count**(bool) noexcept

The function *get_get_entry_count* returns the number of invocations of the *get_entry*() API function of the cache.

static inline constexpr std::int64_t **get_insert_entry_count**(bool) noexcept

The function *get_insert_entry_count* returns the number of invocations of the *insert_entry*() API function of the cache.

static inline constexpr std::int64_t **get_update_entry_count**(bool) noexcept

The function *get_update_entry_count* returns the number of invocations of the *update_entry*() API function of the cache.

static inline constexpr std::int64_t **get_erase_entry_count**(bool) noexcept

The function *get_erase_entry_count* returns the number of invocations of the *erase*() API function of the cache.

```
static inline constexpr std::int64_t get_get_entry_time(bool) noexcept
```

The function *get_get_entry_time* returns the overall time spent executing of the *get_entry()* API function of the cache.

```
static inline constexpr std::int64_t get_insert_entry_time(bool) noexcept
```

The function *get_insert_entry_time* returns the overall time spent executing of the *insert_entry()* API function of the cache.

```
static inline constexpr std::int64_t get_update_entry_time(bool) noexcept
```

The function *get_update_entry_time* returns the overall time spent executing of the *update_entry()* API function of the cache.

```
static inline constexpr std::int64_t get_erase_entry_time(bool) noexcept
```

The function *get_erase_entry_time* returns the overall time spent executing of the *erase()* API function of the cache.

```
struct update_on_exit
```

#include <no_statistics.hpp> Helper class to update timings and counts on function exit.

Public Functions

```
inline constexpr update_on_exit(no_statistics const&, method) noexcept
```

```
~update_on_exit() = default
```

```
update_on_exit(update_on_exit const&) = delete
```

```
update_on_exit(update_on_exit&&) = delete
```

```
update_on_exit &operator=(update_on_exit const&) = delete
```

```
update_on_exit &operator=(update_on_exit&&) = delete
```

hpx/cache/statistics/local_statistics.hpp

Defined in header *hpx/cache/statistics/local_statistics.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace util
```

```
        namespace cache
```

```
            namespace statistics
```

```
                class local_statistics : public hpx::util::cache::statistics::no_statistics
```

Public Functions

local_statistics() = default

inline constexpr *std::size_t* **hits**() const noexcept

inline constexpr *std::size_t* **misses**() const noexcept

inline constexpr *std::size_t* **insertions**() const noexcept

inline constexpr *std::size_t* **evictions**() const noexcept

inline *std::size_t* **hits**(bool const reset) noexcept

inline *std::size_t* **misses**(bool const reset) noexcept

inline *std::size_t* **insertions**(bool const reset) noexcept

inline *std::size_t* **evictions**(bool const reset) noexcept

inline void **got_hit**() noexcept

The function *got_hit* will be called by a cache instance whenever an entry got touched.

inline void **got_miss**() noexcept

The function *got_miss* will be called by a cache instance whenever a requested entry has not been found in the cache.

inline void **got_insertion**() noexcept

The function *got_insertion* will be called by a cache instance whenever a new entry has been inserted.

inline void **got_eviction**() noexcept

The function *got_eviction* will be called by a cache instance whenever an entry has been removed from the cache because a new inserted entry let the cache grow beyond its capacity.

inline void **clear**() noexcept

Reset all statistics.

Private Members

std::size_t **hits_** = 0

std::size_t **misses_** = 0

std::size_t **insertions_** = 0

std::size_t **evictions_** = 0

Private Static Functions

```
static inline std::size_t get_and_reset(std::size_t &value, bool const reset) noexcept
```

checkpoint_base

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/checkpoint_base/checkpoint_data.hpp

Defined in header hpx/checkpoint_base/checkpoint_data.hpp.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

```
namespace util
```

Functions

```
template<typename Container, typename ...Ts>
void save_checkpoint_data(Container &data, Ts&&... ts)
    save_checkpoint_data
```

Save_checkpoint_data takes any number of objects which a user may wish to store in the given container.

Template Parameters

- **Container** – Container used to store the check-pointed data.
- **Ts** – Types of variables to checkpoint

Parameters

- **data** – Container instance used to store the checkpoint data
- **ts** – Variable instances to be inserted into the checkpoint.

```
template<typename ...Ts>
std::size_t prepare_checkpoint_data(Ts const&... ts)
    prepare_checkpoint_data
```

prepare_checkpoint_data takes any number of objects which a user may wish to store in a subsequent save_checkpoint_data operation. The function will return the number of bytes necessary to store the data that will be produced.

Template Parameters

Ts – Types of variables to checkpoint

Parameters

ts – Variable instances to be inserted into the checkpoint.

```
template<typename Container, typename ...Ts>
```

```
void restore_checkpoint_data(Container const &cont, Ts&... ts)
    restore_checkpoint_data
```

`restore_checkpoint_data` takes any number of objects which a user may wish to restore from the given container. The sequence of objects has to correspond to the sequence of objects for the corresponding call to `save_checkpoint_data` that had used the given container instance.

Template Parameters

- **Container** – Container used to restore the check-pointed data.
- **Ts** – Types of variables to restore

Parameters

- **cont** – Container instance used to restore the checkpoint data
- **ts** – Variable instances to be restored from the container

```
struct checkpointing_tag

template<>
struct extra_data_helper<checkpointing_tag>
```

Public Static Functions

```
static extra_data_id_type id() noexcept

static inline constexpr void reset(checkpointing_tag*) noexcept
```

compute_local

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/compute_local/vector.hpp

Defined in header `hpx/compute_local/vector.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **compute**

Functions

```
template<typename T, typename Allocator>
void swap(vector<T, Allocator> &x, vector<T, Allocator> &y) noexcept
    Effects: x.swap(y);

template<typename T, typename Allocator = std::allocator<T>>
class vector
```

Public Types

using **value_type** = *T*

Member types (FIXME: add reference to std.

using **allocator_type** = *Allocator*

using **access_target** = typename *alloc_traits::access_target*

using **size_type** = *std::size_t*

using **difference_type** = *std::ptrdiff_t*

using **reference** = typename *alloc_traits::reference*

using **const_reference** = typename *alloc_traits::const_reference*

using **pointer** = typename *alloc_traits::pointer*

using **const_pointer** = typename *alloc_traits::const_pointer*

using **iterator** = detail::iterator<*T*, *Allocator*>

using **const_iterator** = detail::iterator<*T* const, *Allocator*>

using **reverse_iterator** = *std::reverse_iterator<iterator>*

using **const_reverse_iterator** = *std::reverse_iterator<const_iterator>*

Public Functions

inline explicit **vector**(*Allocator* const &alloc = *Allocator*())

inline **vector**(*size_type* count, *T* const &value, *Allocator* const &alloc = *Allocator*())

inline explicit **vector**(*size_type* count, *Allocator* const &alloc = *Allocator*())

template<typename **InIter**>

inline **vector**(*InIter* first, *InIter* last, *Allocator* const &alloc = *Allocator*())

inline **vector**(*vector* const &other)

inline **vector**(*vector* const &other, *Allocator* const &alloc)

inline **vector**(*vector* &&other) noexcept

inline **vector**(*vector* &&other, *Allocator* const &alloc)

```
inline vector(std::initializer_list<T> init, Allocator const &alloc)

inline ~vector()

inline vector &operator=(vector const &other)

inline vector &operator=(vector &&other) noexcept

inline void assign(size_type count, T const &value)

template<typename InIter>
inline void assign(InIter first, InIter last)

inline void assign(std::initializer_list<T> ilist)

inline allocator_type get_allocator() const noexcept
    Returns the allocator associated with the container.

inline reference at(size_type pos)

inline const_reference at(size_type pos) const

inline reference operator[](size_type pos)

inline const_reference operator[](size_type pos) const

inline reference front()
    Returns a reference to the first element in the container. Calling front on an empty container is
    undefined.

inline const_reference front() const
    Returns a reference to the first element in the container. Calling front on an empty container is
    undefined.

inline reference back()
    Returns a reference to the last element in the container. Calling back on an empty container is
    undefined.

inline const_reference back() const
    Returns a reference to the last element in the container. Calling back on an empty container is
    undefined.

inline pointer data() noexcept
    Returns pointer to the underlying array serving as element storage. The pointer is such that range
    [data(); data() + size()) is always a valid range, even if the container is empty (data() is not
    dereference-able in that case).

inline const_pointer data() const noexcept
    Returns pointer to the underlying array serving as element storage. The pointer is such that range
    [data(); data() + size()) is always a valid range, even if the container is empty (data() is not
    dereference-able in that case).

inline T *device_data() const noexcept
    Returns a raw pointer corresponding to the address of the data allocated on the device.

inline std::size_t size() const noexcept

inline std::size_t capacity() const noexcept
```

inline bool **empty**() const noexcept

Returns: `size() == 0`.

inline void **resize**(*size_type*)

Effects: If `size <= size()`, equivalent to calling `pop_back()` `size()`

- `size` times. If `size() < size`, appends `size - size()` default-inserted elements to the sequence.

Requires: T shall be MoveInsertable and DefaultInsertable into *this.

Remarks: If an exception is thrown other than by the move constructor of a non-CopyInsertable T there are no effects.

inline void **resize**(*size_type*, T const&)

Effects: If `size <= size()`, equivalent to calling `pop_back()` `size() - size` times. If `size() < size`, appends `size - size()` copies of `val` to the sequence.

Requires: T shall be CopyInsertable into *this.

Remarks: If an exception is thrown there are no effects.

inline iterator **begin**() noexcept

inline iterator **end**() noexcept

inline const_iterator **cbegin**() const noexcept

inline const_iterator **cend**() const noexcept

inline const_iterator **begin**() const noexcept

inline const_iterator **end**() const noexcept

inline reverse_iterator **rbegin**() noexcept

inline reverse_iterator **rend**() noexcept

inline const_reverse_iterator **crbegin**() const noexcept

inline const_reverse_iterator **crend**() const noexcept

inline const_reverse_iterator **rbegin**() const noexcept

inline const_reverse_iterator **rend**() const noexcept

inline void **swap**(vector &other) noexcept

Effects: Exchanges the contents and capacity() of *this with that of x.

Complexity: Constant time.

inline void **clear**() noexcept

Effects: Erases all elements in the range `[begin(),end())`. Destroys all elements in 'a'. Invalidates all references, pointers, and iterators referring to the elements of a and may invalidate the past-the-end iterator.

Post: `a.empty()` returns true.

Complexity: Linear.

Private Types

using **alloc_traits** = *traits::allocator_traits*<*Allocator*>

Private Members

size_type **size_**

size_type **capacity_**

allocator_type **alloc_**

pointer **data_**

namespace **traits**

hpx/compute_local/host/block_fork_join_executor.hpp

Defined in header `hpx/compute_local/host/block_fork_join_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

namespace **experimental**

class **block_fork_join_executor**

#include <*block_fork_join_executor.hpp*> An executor with fork-join (blocking) semantics.

The *block_fork_join_executor* creates on construction a set of worker threads that are kept alive for the duration of the executor. Copying the executor has reference semantics, i.e. copies of a *fork_join_executor* hold a reference to the worker threads of the original instance. Scheduling work through the executor concurrently from different threads is undefined behaviour.

The executor keeps a set of worker threads alive for the lifetime of the executor, meaning other work will not be executed while the executor is busy or waiting for work. The executor has a customizable delay after which it will yield to other work. Since starting and resuming the worker threads is a slow operation the executor should be reused whenever possible for multiple adjacent parallel algorithms or invocations of *bulk_(a)sync_execute*.

This behaviour is similar to the plain *fork_join_executor* except that the *block_fork_join_executor* creates a hierarchy of *fork_join_executors*, one for each target used to initialize it.

Public Functions

```
inline explicit block_fork_join_executor(threads::thread_priority const priority =
                                         threads::thread_priority::bound,
                                         threads::thread_stacksize const stacksize =
                                         threads::thread_stacksize::small_,
                                         fork_join_executor::loop_schedule const
                                         schedule =
                                         fork_join_executor::loop_schedule::static_,
                                         std::chrono::nanoseconds const yield_delay =
                                         std::chrono::milliseconds(1))
```

Construct a *block_fork_join_executor*.

Note: This constructor will create one *fork_join_executor* for each numa domain

Parameters

- **priority** – The priority of the worker threads.
- **stacksize** – The stacksize of the worker threads. Must not be nostack.
- **schedule** – The loop schedule of the parallel regions.
- **yield_delay** – The time after which the executor yields to other work if it has not received any new work for execution.

```
inline explicit block_fork_join_executor(std::vector<compute::host::target> const
                                         &targets, threads::thread_priority const priority =
                                         threads::thread_priority::bound,
                                         threads::thread_stacksize const stacksize =
                                         threads::thread_stacksize::small_,
                                         fork_join_executor::loop_schedule const
                                         schedule =
                                         fork_join_executor::loop_schedule::static_,
                                         std::chrono::nanoseconds const yield_delay =
                                         std::chrono::milliseconds(1))
```

Construct a *block_fork_join_executor*.

Note: This constructor will create one *fork_join_executor* for each given target

Parameters

- **targets** – The list of targets to use for thread placement
- **priority** – The priority of the worker threads.
- **stacksize** – The stacksize of the worker threads. Must not be nostack.
- **schedule** – The loop schedule of the parallel regions.
- **yield_delay** – The time after which the executor yields to other work if it has not received any new work for execution.

Private Members

fork_join_executor **exec_**

std::vector<fork_join_executor> **block_execs_**

Private Static Functions

static inline *hpx::threads::mask_type* **cores_for_targets**(*std::vector*<*compute::host::target*>
const &targets)

hpx/compute_local/host/block_executor.hpp

Defined in header `hpx/compute_local/host/block_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **Executor**>

struct **executor_execution_category**<*compute::host::block_executor*<*Executor*>>

Public Types

using **type** = *hpx::execution::parallel_execution_tag*

template<typename **Executor**>

struct **is_never_blocking_one_way_executor**<*compute::host::block_executor*<*Executor*>> : public
is_never_blocking_one_way_executor<*Executor*>

template<typename **Executor**>

struct **is_one_way_executor**<*compute::host::block_executor*<*Executor*>> : public
is_one_way_executor<*Executor*>

template<typename **Executor**>

struct **is_two_way_executor**<*compute::host::block_executor*<*Executor*>> : public
is_two_way_executor<*Executor*>

template<typename **Executor**>

struct **is_bulk_one_way_executor**<*compute::host::block_executor*<*Executor*>> : public
is_bulk_one_way_executor<*Executor*>

template<typename **Executor**>

struct **is_bulk_two_way_executor**<*compute::host::block_executor*<*Executor*>> : public
is_bulk_two_way_executor<*Executor*>

namespace **hpx**

namespace **compute**

namespace **host**

```
template<typename Executor = hpx::execution::experimental::restricted_thread_pool_executor>
```

```
struct block_executor
```

#include <block_executor.hpp> The block executor can be used to build NUMA aware programs. It will distribute work evenly across the passed targets

Template Parameters

Executor – The underlying executor to use

Public Types

```
using executor_parameters_type = hpx::execution::experimental::default_parameters
```

Public Functions

```
inline explicit block_executor(std::vector<host::target> const &targets,  
                               threads::thread_priority priority =  
                               threads::thread_priority::high, threads::thread_stacksize  
                               stacksize = threads::thread_stacksize::default_,  
                               threads::thread_schedule_hint schedulehint = { })
```

```
inline explicit block_executor(std::vector<host::target> &&targets)
```

```
inline block_executor(block_executor const &other)
```

```
inline block_executor(block_executor &&other) noexcept
```

```
inline block_executor &operator=(block_executor const &other)
```

```
inline block_executor &operator=(block_executor &&other) noexcept
```

```
template<typename F, typename ...Ts>  
inline decltype(auto) post(F &&f, Ts&&... ts) const
```

```
template<typename F, typename ...Ts>  
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const
```

```
template<typename F, typename ...Ts>  
inline decltype(auto) sync_execute(F &&f, Ts&&... ts) const
```

```
template<typename F, typename Shape, typename ...Ts>  
inline decltype(auto) bulk_async_execute_impl(F &&f, Shape const &shape, Ts&&... ts)  
const
```

```
template<typename F, typename Shape, typename ...Ts>  
inline decltype(auto) bulk_async_execute(F &&f, Shape const &shape, Ts&&... ts) const
```

```
template<typename F, typename Shape, typename ...Ts>
```

```
inline decltype(auto) bulk_sync_execute_impl(F &&f, Shape const &shape, Ts&&... ts)
                                         const

template<typename F, typename Shape, typename ...Ts>
inline decltype(auto) bulk_sync_execute(F &&f, Shape const &shape, Ts&&... ts) const

inline std::vector<host::target> const &targets() const noexcept
```

Private Functions

```
inline auto get_next_executor() const

inline void init_executors()
```

Private Members

```
std::vector<host::target> targets_

mutable std::atomic<std::size_t> current_

std::vector<Executor> executors_

threads::thread_priority priority_ = threads::thread_priority::high

threads::thread_stacksize stacksize_ = threads::thread_stacksize::default_

threads::thread_schedule_hint schedulehint_ = { }
```

namespace **execution**

namespace **experimental**

```
template<typename Executor> block_executor< Executor > >
```

Public Types

```
using type = hpx::execution::parallel_execution_tag

template<typename Executor> block_executor< Executor > > : public is_bulk_one_way_executor<...

template<typename Executor> block_executor< Executor > > : public is_bulk_two_way_executor<...

template<typename Executor> block_executor< Executor > > : public is_never_blocking_one_way<...
```

```
template<typename Executor> block_executor< Executor > > : public is_one_way_executor< Executor >
template<typename Executor> block_executor< Executor > > : public is_two_way_executor< Executor >
```

config

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/config/endian.hpp

Defined in header `hpx/config/endian.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

contracts

See *Public API* for a list of names and headers that are part of the public *HPX* API.

HPX_PRE

Defined in header `hpx/contracts.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *HPX_POST*
- *HPX_CONTRACT_ASSERT*

Warning: doxygenfunction: Cannot find function “HPX_PRE” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

HPX_POST

Defined in header `hpx/contracts.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *HPX_PRE*
- *HPX_CONTRACT_ASSERT*

Warning: doxygenfunction: Cannot find function “HPX_POST” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

HPX_CONTRACT_ASSERT

Defined in header `hpx/contracts.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *HPX_PRE*
- *HPX_POST*

Warning: doxygenfunction: Cannot find function “HPX_CONTRACT_ASSERT” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

coroutines

See *Public API* for a list of names and headers that are part of the public *HPX* API.

`hpx/coroutines/thread_enums.hpp`

Defined in header `hpx/coroutines/thread_enums.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

Enums

enum class **thread_schedule_state** : `std::int8_t`

The *thread_schedule_state* enumerator encodes the current state of a *thread* instance

Task Lifecycle State Transitions:

```
stateDiagram-v2
    %% Creation Phase
    [*] --> Staged : task_staged
    [*] --> Pending : task_created
    [*] --> Suspended : task_created
    Staged --> Pending : task_created

    %% Execution Loop
    Pending --> Active : task_executing
    Active --> Pending : task_yielded

    %% Sleep / Wake Cycle
    Active --> Suspended : task_suspended
    Suspended --> Pending : task_resumed
```

(continues on next page)

(continued from previous page)

```

%% Termination Paths
Active --> Terminated : task_completed
Active --> Deleted : task_completed (Inline fast-path)
Pending --> Terminated : task_completed (Aborted)
Suspended --> Terminated : task_completed (Aborted)

%% Cleanup (Destruction / Recycling)
Terminated --> Deleted : task_deleted
Deleted --> [*]

```

*Values:*enumerator **unknown**enumerator **active**

thread is currently active (running, has resources)

enumerator **pending**

thread is pending (ready to run, but no hardware resource available)

enumerator **suspended**

thread has been suspended (waiting for synchronization event, but still known and under control of the thread-manager)

enumerator **depleted**

thread has been depleted (deeply suspended, it is not known to the thread-manager)

enumerator **terminated**

thread has been stopped and may be garbage collected

enumerator **staged**

this is not a real thread state, but allows to reference staged task descriptions, which eventually will be converted into thread objects

enumerator **pending_do_not_schedule**

this is not a real thread state, but allows to create a thread in pending state without scheduling it (internal, do not use)

enumerator **pending_boost**

this is not a real thread state, but allows to suspend a thread in pending state without high priority rescheduling

enumerator **deleted**

thread has been stopped and was deleted

enum class **thread_priority** : *std::int8_t*

This enumeration lists all possible thread-priorities for HPX threads.

Values:

enumerator **unknown**

enumerator **default_**

Will assign the priority of the task to the default (normal) priority.

enumerator **low**

Task goes onto a special low priority queue and will not be executed until all high/normal priority tasks are done, even if they are added after the low priority task.

enumerator **normal**

Task will be executed when it is taken from the normal priority queue, this is usually a first in-first-out ordering of tasks (depending on scheduler choice). This is the default priority.

enumerator **high_recursive**

The task is a high priority task and any child tasks spawned by this task will be made high priority as well - unless they are specifically flagged as non default priority.

enumerator **boost**

Same as *thread_priority_high* except that the thread will fall back to *thread_priority_normal* if resumed after being suspended.

enumerator **high**

Task goes onto a special high priority queue and will be executed before normal/low priority tasks are taken (some schedulers modify the behavior slightly and the documentation for those should be consulted).

enumerator **bound**

Task goes onto a special high priority queue and will never be stolen by another thread after initial assignment. This should be used for thread placement tasks such as OpenMP type for loops.

enumerator **initially_bound**

Task initially goes onto a special high priority queue and will never be stolen by another thread after initial assignment. If the thread is rescheduled later, it will use normal priority.

enum class **thread_restart_state** : *std::int8_t*

The *thread_restart_state* enumerator encodes the reason why a thread is being restarted

Values:

enumerator **unknown**

enumerator **signaled**

The thread has been signaled.

enumerator **timeout**

The thread has been reactivated after a timeout.

enumerator **terminate**

The thread needs to be terminated.

enumerator **abort**

The thread needs to be aborted.

enum class **thread_stacksize** : *std::int8_t*

A *thread_stacksize* references any of the possible stack-sizes for HPX threads.

Values:

enumerator **unknown**

enumerator **small_**

use small stack size (the underscore is to work around 'small' being defined to char on Windows)

enumerator **medium**

use medium sized stack size

enumerator **large**

use large stack size

enumerator **huge**

use very large stack size

enumerator **nostack**

this thread does not suspend (does not need a stack)

enumerator **current**

use size of current thread's stack

enumerator **default_**

use default stack size

enumerator **minimal**

use minimally stack size

enumerator **maximal**

use maximally stack size

enum class **thread_schedule_hint_mode** : *std::int8_t*

The type of hint given when creating new tasks.

Values:

enumerator **none**

A hint that leaves the choice of scheduling entirely up to the scheduler.

enumerator **thread**

A hint that tells the scheduler to prefer scheduling a task on the local thread number associated with this hint. Local thread numbers are indexed from zero. It is up to the scheduler to decide how to interpret thread numbers that are larger than the number of threads available to the scheduler. Typically, thread numbers will wrap around when too large.

enumerator **numa**

A hint that tells the scheduler to prefer scheduling a task on the NUMA domain associated with this hint. NUMA domains are indexed from zero. It is up to the scheduler to decide how to interpret NUMA domain indices that are larger than the number of available NUMA domains to the scheduler. Typically, indices will wrap around when too large.

enum class **thread_placement_hint** : *std::int8_t*

The type of hint given to the scheduler related to thread placement

The type of hint given to the scheduler related running a thread as a child directly in the context of the parent thread

Values:

enumerator **none**

No hint is specified. The implementation is free to chose what placement methods to use.

enumerator **depth_first**

A hint that tells the scheduler to prefer spreading thread placement on a depth-first basis (i.e. consecutively scheduled threads are placed on the same core).

enumerator **breadth_first**

A hint that tells the scheduler to prefer spreading thread placement on a breadth-first basis (i.e. consecutively scheduled threads are placed on the neighboring cores).

enumerator **depth_first_reverse**

A hint that tells the scheduler to prefer spreading thread placement on a depth-first basis (i.e. consecutively scheduled threads are placed on the same core). Threads are being scheduled in reverse order.

enumerator **breadth_first_reverse**

A hint that tells the scheduler to prefer spreading thread placement on a breadth-first basis (i.e. consecutively scheduled threads are placed on the neighboring cores). Threads are being scheduled in reverse order.

enum class **thread_sharing_hint** : *std::int8_t*

The type of hint given to the scheduler related to whether it is ok to share the invoked function object between threads

Values:

enumerator **none**

No hint is specified. The implementation is free to chose what sharing methods to use.

enumerator **do_not_share_function**

A hint that tells the scheduler to avoid sharing the given function (object) between threads.

enumerator **do_not_combine_tasks**

A hint that tells the scheduler to avoid combining tasks on the same thread. This is important for tasks that may synchronize between each other, which could lead to deadlocks if those tasks are combined running by the same thread.

enum class **thread_execution_hint** : *std::int8_t*

Values:

enumerator **none**

No hint is specified. Always run the thread in its own execution environment.

enumerator **run_as_child**

Attempt to run the thread in the execution context of the parent thread.

Functions

std::ostream &**operator<<**(*std::ostream* &os, *thread_schedule_state* t)

char const ***get_thread_state_name**(*thread_schedule_state* state) noexcept

Returns the name of the given state.

Get the readable string representing the name of the given *thread_state* constant.

Parameters

state – this represents the thread state.

std::ostream &**operator<<**(*std::ostream* &os, *thread_priority* t)

char const ***get_thread_priority_name**(*thread_priority* priority) noexcept

Return the thread priority name.

Get the readable string representing the name of the given *thread_priority* constant.

Parameters

priority – this represents the thread priority.

std::ostream &**operator<<**(*std::ostream* &os, *thread_restart_state* t)

char const ***get_thread_state_ex_name**(*thread_restart_state* state) noexcept

Get the readable string representing the name of the given *thread_restart_state* constant.

char const ***get_thread_state_name**(*thread_state* state) noexcept

Get the readable string representing the name of the given *thread_state* constant.

std::ostream &**operator<<**(*std::ostream* &os, *thread_stacksize* t)

char const ***get_stack_size_enum_name**(*thread_stacksize* size) noexcept

Returns the stack size name.

Get the readable string representing the given stack size constant.

Parameters

size – this represents the stack size

constexpr bool **do_not_share_function**(*thread_sharing_hint* hint) noexcept

constexpr bool **do_not_combine_tasks**(*thread_sharing_hint* hint) noexcept

constexpr *thread_sharing_hint* **operator|**(*thread_sharing_hint* lhs, *thread_sharing_hint* rhs) noexcept

constexpr bool **run_as_child**(*thread_execution_hint* hint) noexcept

Variables

constexpr *thread_execution_hint* **default_runs_as_child_hint** = *thread_execution_hint::none*

Default value to use for runs-as-child mode (if *true*, then futures will attempt to execute associated threads directly if they have not started running).

struct **thread_schedule_hint**

#include <thread_enums.hpp> A hint given to a scheduler to guide where a task should be scheduled.

A scheduler is free to ignore the hint, or modify the hint to suit the resources available to the scheduler.

Public Functions

inline constexpr **thread_schedule_hint**() noexcept

Construct a default hint with mode *thread_schedule_hint_mode::none*.

inline explicit constexpr **thread_schedule_hint**(*std::int16_t* const thread_hint,
 thread_placement_hint placement =
 thread_placement_hint::none,
 thread_execution_hint runs_as_child =
 default_runs_as_child_hint,
 thread_sharing_hint sharing =
 thread_sharing_hint::none) noexcept

Construct a hint with mode *thread_schedule_hint_mode::thread* and the given hint as the local thread number.

inline constexpr **thread_schedule_hint**(*thread_schedule_hint_mode* const mode, *std::int16_t*
 const hint, *thread_placement_hint* placement =
 thread_placement_hint::none, *thread_execution_hint*
 runs_as_child = *default_runs_as_child_hint*,
 thread_sharing_hint sharing =
 thread_sharing_hint::none) noexcept

Construct a hint with the given mode and hint. The numerical hint is unused when the mode is *thread_schedule_hint_mode::none*.

inline explicit constexpr **thread_schedule_hint**(*thread_placement_hint* placement) noexcept

Construct a hint with the given placement hint.

inline explicit constexpr **thread_schedule_hint**(*thread_execution_hint* runs_as_child) noexcept

Construct a hint with the given execution hint.

inline explicit constexpr **thread_schedule_hint**(*thread_sharing_hint* sharing) noexcept

Construct a hint with the given sharing hint.

inline constexpr *thread_placement_hint* **placement_mode**() const noexcept

inline constexpr void **placement_mode**(*thread_placement_hint* bits) noexcept

inline constexpr *thread_sharing_hint* **sharing_mode**() const noexcept

inline constexpr void **sharing_mode**(*thread_sharing_hint* bits) noexcept

inline constexpr *thread_execution_hint* **runs_as_child_mode**() const noexcept

inline constexpr void **runs_as_child_mode**(*thread_execution_hint* bits) noexcept

inline constexpr void **schedule_hint**(std::int16_t core) noexcept

Public Members

std::int16_t **hint** = -1

The hint associated with the mode. The interpretation of this hint depends on the given mode.

thread_schedule_hint_mode **mode** = *thread_schedule_hint_mode::none*

The mode of the scheduling hint.

std::uint8_t **placement_mode_bits**

The mode of the desired thread placement.

std::uint8_t **sharing_mode_bits**

The mode of the desired sharing hint.

std::uint8_t **runs_as_child_mode_bits**

The thread will run as a child directly in the context of the current thread

hpx/coroutines/thread_id_type.hpp

Defined in header `hpx/coroutines/thread_id_type.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

template<>

struct **hash**<::hpx::threads::thread_id>

Public Functions

```
inline std::size_t operator() (::hpx::threads::thread_id const &v) const noexcept  
template<>  
struct hash<::hpx::threads::thread_id_ref>
```

Public Functions

```
inline std::size_t operator() (::hpx::threads::thread_id_ref const &v) const noexcept  
  
namespace hpx  
  
    namespace threads
```

Enums

```
enum class thread_id_addrf : std::uint8_t  
    Values:  
  
    enumerator yes  
  
    enumerator no
```

Variables

```
constexpr const thread_id invalid_thread_id  
  
struct keep_alive_thread_id
```

Public Functions

```
inline explicit keep_alive_thread_id(hpx::threads::thread_id id, bool const add_ref) noexcept  
keep_alive_thread_id(keep_alive_thread_id const &other) = delete  
keep_alive_thread_id(keep_alive_thread_id &&other) = default  
keep_alive_thread_id &operator=(keep_alive_thread_id const &other) = delete  
inline keep_alive_thread_id &operator=(keep_alive_thread_id &&other) noexcept  
inline ~keep_alive_thread_id()  
inline void detach_if_needed() noexcept
```

Public Members

bool **add_ref**

hpx::threads::thread_id_ref **id**

struct **thread_id**

Public Functions

constexpr **thread_id**() noexcept = default

thread_id(*thread_id* const&) noexcept = default

thread_id &**operator**=(*thread_id* const&) noexcept = default

~thread_id() = default

inline constexpr **thread_id**(*thread_id* &&rhs) noexcept

inline constexpr *thread_id* &**operator**=(*thread_id* &&rhs) noexcept

inline explicit constexpr **thread_id**(*thread_id_repr* const thrd) noexcept

inline constexpr *thread_id* &**operator**=(*thread_id_repr* const rhs) noexcept

inline explicit constexpr **operator bool**() const noexcept

inline constexpr *thread_id_repr* **get**() const noexcept

inline constexpr void **reset**() noexcept

Private Types

using **thread_id_repr** = void*

Private Members

thread_id_repr **thrd_** = nullptr

Friends

inline friend constexpr friend bool **operator==** (std::nullptr_t,
thread_id const &rhs) noexcept

inline friend constexpr friend bool **operator!=** (std::nullptr_t,
thread_id const &rhs) noexcept

```
inline friend constexpr friend bool operator== (thread_id const &lhs,  
std::nullptr_t) noexcept
```

```
inline friend constexpr friend bool operator!= (thread_id const &lhs,  
std::nullptr_t) noexcept
```

```
inline friend constexpr friend bool operator== (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator!= (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator< (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator> (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator<= (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
inline friend constexpr friend bool operator>= (thread_id const &lhs,  
thread_id const &rhs) noexcept
```

```
friend std::ostream &operator<<(std::ostream &os, thread_id const &id)
```

```
friend void format_value(std::ostream &os, std::string_view spec, thread_id const &id)
```

```
struct thread_id_ref
```

Public Types

```
using thread_repr = detail::thread_data_reference_counting
```

Public Functions

```
thread_id_ref() noexcept = default
```

```
thread_id_ref(thread_id_ref const&) = default
```

```
thread_id_ref &operator=(thread_id_ref const&) = default
```

```
thread_id_ref(thread_id_ref &&rhs) noexcept = default
```

```
thread_id_ref &operator=(thread_id_ref &&rhs) noexcept = default
```

```
~thread_id_ref() = default
```

```

inline explicit thread_id_ref(thread_id_repr const &thrd) noexcept
inline explicit thread_id_ref(thread_id_repr &&thrd) noexcept
inline thread_id_ref &operator=(thread_id_repr const &rhs) noexcept
inline thread_id_ref &operator=(thread_id_repr &&rhs) noexcept
inline explicit thread_id_ref(thread_repr *thrd, thread_id_addrf const addrf =
                                thread_id_addrf::yes) noexcept

inline thread_id_ref &operator=(thread_repr *rhs) noexcept
inline thread_id_ref(thread_id const &noref)
inline thread_id_ref(thread_id &&noref, bool const add_ref = true) noexcept
inline thread_id_ref &operator=(thread_id const &noref)
inline thread_id_ref &operator=(thread_id &&noref) noexcept
inline explicit constexpr operator bool() const noexcept
inline constexpr thread_id noref() const noexcept
inline constexpr thread_id_repr &get() & noexcept
inline thread_id_repr &&get() && noexcept
inline constexpr thread_id_repr const &get() const & noexcept
inline void reset() noexcept
inline void reset(thread_repr *thrd, bool const add_ref = true) noexcept
inline constexpr thread_repr *detach() noexcept

```

Private Types

```
using thread_id_repr = hpx::intrusive_ptr<detail::thread_data_reference_counting>
```

Private Members

```
thread_id_repr thrd_
```

Friends

```

inline friend constexpr friend bool operator== (std::nullptr_t,
thread_id_ref const &rhs) noexcept

inline friend constexpr friend bool operator!= (std::nullptr_t,
thread_id_ref const &rhs) noexcept

```

```
inline friend constexpr friend bool operator== (thread_id_ref const &lhs,
std::nullptr_t) noexcept
```

```
inline friend constexpr friend bool operator!= (thread_id_ref const &lhs,
std::nullptr_t) noexcept
```

```
inline friend constexpr friend bool operator== (thread_id_ref const &lhs,
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator!= (thread_id_ref const &lhs,
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator< (thread_id_ref const &lhs,
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator> (thread_id_ref const &lhs,
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator<= (thread_id_ref const &lhs,
thread_id_ref const &rhs) noexcept
```

```
inline friend constexpr friend bool operator>= (thread_id_ref const &lhs,
thread_id_ref const &rhs) noexcept
```

```
friend std::ostream &operator<<(std::ostream &os, thread_id_ref const &id)
```

```
friend void format_value(std::ostream &os, std::string_view spec, thread_id_ref const &id)
```

namespace **std**

```
template<> thread_id >
```

Public Functions

```
inline std::size_t operator() (::hpx::threads::thread_id const &v) const noexcept
```

```
template<> thread_id_ref >
```

Public Functions

```
inline std::size_t operator() (::hpx::threads::thread_id_ref const &v) const noexcept
```


datastructures

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::any_nonser. hpx::bad_any_cast

Defined in header [hpx/any.hpp](#)⁸³⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::unique_any_nonser`
- `hpx::any_cast`
- `hpx::make_any_nonser`
- `hpx::make_unique_any_nonser`

Warning: doxygenfunction: Cannot find function “hpx::any_nonser. hpx::bad_any_cast” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::unique_any_nonser

Defined in header [hpx/any.hpp](#)⁸³⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::any_nonser. hpx::bad_any_cast`
- `hpx::any_cast`
- `hpx::make_any_nonser`
- `hpx::make_unique_any_nonser`

using `hpx::unique_any_nonser = util::basic_any<void, void, void, std::false_type>`

hpx::any_cast

Defined in header [hpx/any.hpp](#)⁸³⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::any_nonser. hpx::bad_any_cast`
- `hpx::unique_any_nonser`
- `hpx::make_any_nonser`

⁸³⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/any.hpp

⁸³⁸ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/any.hpp

⁸³⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/any.hpp

- *hpx::make_unique_any_nonser*

```
template<typename T, typename IArch, typename OArch, typename Char, typename Copyable>
T *hpx::any_cast(util::basic_any<IArch, OArch, Char, Copyable> *operand) noexcept
```

Performs type-safe access to the contained object.

Parameters

operand – target any object

Returns

If operand is not a null pointer, and the *typeid* of the requested *T* matches that of the contents of *operand*, a pointer to the value contained by *operand*, otherwise a null pointer.

```
template<typename T, typename IArch, typename OArch, typename Char, typename Copyable>
T const *hpx::any_cast(util::basic_any<IArch, OArch, Char, Copyable> const *operand) noexcept
```

Performs type-safe access to the contained object.

Parameters

operand – target any object

Returns

If operand is not a null pointer, and the *typeid* of the requested *T* matches that of the contents of *operand*, a pointer to the value contained by *operand*, otherwise a null pointer.

```
template<typename T, typename IArch, typename OArch, typename Char, typename Copyable>
T hpx::any_cast(util::basic_any<IArch, OArch, Char, Copyable> &operand)
```

Performs type-safe access to the contained object. Let *U* be *std::remove_cv_t<std::remove_reference_t<T>>*. The program is ill-formed if *std::is_constructible_v<T, U>* is false.

Parameters

operand – target any object

Returns

*static_cast<T>(*std::any_cast<U>(&operand))*

```
template<typename T, typename IArch, typename OArch, typename Char, typename Copyable>
T const &hpx::any_cast(util::basic_any<IArch, OArch, Char, Copyable> const &operand)
```

Performs type-safe access to the contained object. Let *U* be *std::remove_cv_t<std::remove_reference_t<T>>*. The program is ill-formed if *std::is_constructible_v<T, const U>* is false.

Parameters

operand – target any object

Returns

*static_cast<T>(*std::any_cast<U>(&operand))*

hpx::make_any_nonser

Defined in header [hpx/any.hpp](#)⁸⁴⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::any_nonser*, *hpx::bad_any_cast*
- *hpx::unique_any_nonser*
- *hpx::any_cast*

⁸⁴⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/any.hpp

- *hpx::make_unique_any_nonser*

```
template<typename T, typename ...Ts>
```

```
util::basic_any<void, void, void, std::true_type> hpx::make_any_nonser(Ts&&... ts)
```

```
template<typename T, typename U, typename ...Ts>
```

```
util::basic_any<void, void, void, std::true_type> hpx::make_any_nonser(std::initializer_list<U> il, Ts&&... ts)
```

```
template<typename T>
```

```
util::basic_any<void, void, void, std::true_type> hpx::make_any_nonser(T &&t)
```

hpx::make_unique_any_nonser

Defined in header [hpx/any.hpp](#)⁸⁴¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::any_nonser*, *hpx::bad_any_cast*
- *hpx::unique_any_nonser*
- *hpx::any_cast*
- *hpx::make_any_nonser*

```
template<typename T, typename ...Ts>
```

```
util::basic_any<void, void, void, std::false_type> hpx::make_unique_any_nonser(Ts&&... ts)
```

```
template<typename T, typename U, typename ...Ts>
```

```
util::basic_any<void, void, void, std::false_type> hpx::make_unique_any_nonser(std::initializer_list<U> il,
Ts&&... ts)
```

```
template<typename T>
```

```
util::basic_any<void, void, void, std::false_type> hpx::make_unique_any_nonser(T &&t)
```

hpx::ignore

Defined in header [hpx/tuple.hpp](#)⁸⁴².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::tuple*
- *hpx::tuple_size*
- *hpx::tuple_element*
- *hpx::make_tuple*
- *hpx::tie*
- *hpx::forward_as_tuple*
- *hpx::tuple_cat*

⁸⁴¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/any.hpp

⁸⁴² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/tuple.hpp

- `hpx::get`

constexpr `hpx::detail::ignore_type` `hpx::ignore` = { }

An object of unspecified type such that any value can be assigned to it with no effect. Intended for use with `hpx::tie` when unpacking a `hpx::tuple`, as a placeholder for the arguments that are not used. While the behavior of `hpx::ignore` outside of `hpx::tie` is not formally specified, some code guides recommend using `hpx::ignore` to avoid warnings from unused return values of `[[nodiscard]]` functions.

`hpx::tuple`

Defined in header `hpx/tuple.hpp`⁸⁴³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ignore`
- `hpx::tuple_size`
- `hpx::tuple_element`
- `hpx::make_tuple`
- `hpx::tie`
- `hpx::forward_as_tuple`
- `hpx::tuple_cat`
- `hpx::get`

template<typename ...**Ts**>

class **tuple**

Class template `hpx::tuple` is a fixed-size collection of heterogeneous values. It is a generalization of `hpx::pair`. If `std::is_trivially_destructible<Ti>::value` is true for every `Ti` in `Ts`, the destructor of tuple is trivial.

Param Ts...

the types of the elements that the tuple stores.

`hpx::tuple_size`

Defined in header `hpx/tuple.hpp`⁸⁴⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::ignore`
- `hpx::tuple`
- `hpx::tuple_element`
- `hpx::make_tuple`
- `hpx::tie`

⁸⁴³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/tuple.hpp

⁸⁴⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/tuple.hpp

- `hpx::forward_as_tuple`
- `hpx::tuple_cat`
- `hpx::get`

template<typename **T**>

struct **tuple_size**

Provides access to the number of elements in a tuple-like type as a compile-time constant expression.

The primary template is not defined. An explicit (full) or partial specialization is required to make a type tuple-like.

hpx::tuple_element

Defined in header [hpx/tuple.hpp](#)⁸⁴⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ignore`
- `hpx::tuple`
- `hpx::tuple_size`
- `hpx::make_tuple`
- `hpx::tie`
- `hpx::forward_as_tuple`
- `hpx::tuple_cat`
- `hpx::get`

template<std::size_t **I**, typename **T**, typename **Enable** = void>

struct **tuple_element**

Provides compile-time indexed access to the types of the elements of a tuple-like type.

The primary template is not defined. An explicit (full) or partial specialization is required to make a type tuple-like.

hpx::make_tuple

Defined in header [hpx/tuple.hpp](#)⁸⁴⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ignore`
- `hpx::tuple`
- `hpx::tuple_size`
- `hpx::tuple_element`

⁸⁴⁵ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/tuple.hpp

⁸⁴⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/tuple.hpp

- `hpx::tie`
- `hpx::forward_as_tuple`
- `hpx::tuple_cat`
- `hpx::get`

```
template<typename ...Ts>  
constexpr tuple<util::decay_unwrap_t<Ts>...> hpx::make_tuple(Ts&&... ts)  
    Provides compile-time indexed access to the types of the elements of the tuple.
```

`hpx::tie`

Defined in header [hpx/tuple.hpp](#)⁸⁴⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ignore`
- `hpx::tuple`
- `hpx::tuple_size`
- `hpx::tuple_element`
- `hpx::make_tuple`
- `hpx::forward_as_tuple`
- `hpx::tuple_cat`
- `hpx::get`

```
template<typename ...Ts>  
constexpr tuple<Ts&...> hpx::tie(Ts&... ts)  
    Creates a tuple of lvalue references to its arguments or instances of hpx::ignore.
```

Parameters

ts – zero or more lvalue arguments to construct the tuple from.

Returns

`hpx::tuple` object containing lvalue references.

`hpx::forward_as_tuple`

Defined in header [hpx/tuple.hpp](#)⁸⁴⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::ignore`
- `hpx::tuple`
- `hpx::tuple_size`
- `hpx::tuple_element`

⁸⁴⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/tuple.hpp

⁸⁴⁸ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/tuple.hpp

- *hpx::make_tuple*
- *hpx::tie*
- *hpx::tuple_cat*
- *hpx::get*

```
template<typename ...Ts>
constexpr tuple<Ts&&...> hpx::forward_as_tuple(Ts&&... ts)
```

Constructs a tuple of references to the arguments in *args* suitable for forwarding as an argument to a function. The tuple has rvalue reference data members when rvalues are used as arguments, and otherwise has lvalue reference data members.

Parameters

ts – zero or more arguments to construct the tuple from

Returns

hpx::tuple object created as if by

```
hpx::tuple<Ts&&...>(HPX_FORWARD(Ts, ts)...)

```

hpx::tuple_cat

Defined in header [hpx/tuple.hpp](#)⁸⁴⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ignore*
- *hpx::tuple*
- *hpx::tuple_size*
- *hpx::tuple_element*
- *hpx::make_tuple*
- *hpx::tie*
- *hpx::forward_as_tuple*
- *hpx::get*

```
template<typename ...Tuples>
constexpr auto hpx::tuple_cat(Tuples&&... tuples)
```

Constructs a tuple that is a concatenation of all tuples in *tuples*. The behavior is undefined if any type in `std::decay_t<Tuples>...` is not a specialization of *hpx::tuple*. However, an implementation may choose to support types (such as `std::array` and `std::pair`) that follow the tuple-like protocol.

Parameters

tuples – zero or more tuples to concatenate

Returns

hpx::tuple object composed of all elements of all argument tuples constructed from *hpx::get<Is>(HPX_FORWARD(UTuple,t))* for each individual element.

⁸⁴⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/tuple.hpp

hpx::get

Defined in header [hpx/tuple.hpp](#)⁸⁵⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::ignore*
- *hpx::tuple*
- *hpx::tuple_size*
- *hpx::tuple_element*
- *hpx::make_tuple*
- *hpx::tie*
- *hpx::forward_as_tuple*
- *hpx::tuple_cat*

template<std::size_t I>

util::at_index<I, Ts...>::type &hpx::get() noexcept

Extracts the Ith element from the tuple. I must be an integer value in [0, sizeof...(Ts)).

template<std::size_t I>

util::at_index<I, Ts...>::type const &hpx::get() const noexcept

Extracts the Ith element from the tuple. I must be an integer value in [0, sizeof...(Ts)).

hpx::any

Defined in header [hpx/any.hpp](#)⁸⁵¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::make_any*

using hpx::any = util::basic_any<serialization::input_archive, serialization::output_archive, char, std::true_type>

hpx::make_any

Defined in header [hpx/any.hpp](#)⁸⁵².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::any*

template<typename T, typename Char>

⁸⁵⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/tuple.hpp

⁸⁵¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/any.hpp

⁸⁵² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/any.hpp

`util::basic_any<serialization::input_archive, serialization::output_archive, Char> hpx::make_any(T &&t)`

Constructs an any object containing an object of type *T*, passing the provided arguments to *T*'s constructor. Equivalent to:

```
return std::any(std::in_place_type<T>, std::forward<Args>(args)...);
```

debugging

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/debugging/print.hpp

Defined in header `hpx/debugging/print.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

errors

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/errors/define_error_info.hpp

Defined in header `hpx/errors/define_error_info.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::error_code

Defined in header `hpx/system_error.hpp`⁸⁵³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

class **error_code** : public *error_code*

A *hpx::error_code* represents an arbitrary error condition.

The class *hpx::error_code* describes an object used to hold error code values, such as those originating from the operating system or other low-level application program interfaces.

Note: Class *hpx::error_code* is an adjunct to error reporting by exception

⁸⁵³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/system_error.hpp

hpx::exception

Defined in header [hpx/exception.hpp](#)⁸⁵⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

class **exception** : public `system_error`

A *hpx::exception* is the main exception type used by HPX to report errors.

The *hpx::exception* type is the main exception type used by HPX to report errors. Any exceptions thrown by functions in the HPX library are either of this type or of a type derived from it. This implies that it is always safe to use this type only in catch statements guarding HPX library calls.

Subclassed by `hpx::bad_alloc_exception`, `hpx::cuda::experimental::cuda_exception`, `hpx::exception_list`, `hpx::experimental::task_canceled_exception`, `hpx::mpi::experimental::mpi_exception`

hpx/errors/exception_list.hpp

Defined in header `hpx/errors/exception_list.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

class **exception_list** : public *hpx::exception*

#include <exception_list.hpp> The class *exception_list* is a container of *exception_ptr* objects parallel algorithms may use to communicate uncaught exceptions encountered during parallel execution to the caller of the algorithm

The type `exception_list::const_iterator` fulfills the requirements of a forward iterator.

Public Types

using **iterator** = `exception_list_type::const_iterator`
bidirectional iterator

Public Functions

inline `std::size_t` **size**() const noexcept

The number of *exception_ptr* objects contained within the *exception_list*.

Note: Complexity: Constant time.

inline `exception_list_type::const_iterator` **begin**() const noexcept

An iterator referring to the first *exception_ptr* object contained within the *exception_list*.

inline `exception_list_type::const_iterator` **end**() const noexcept

An iterator which is the past-the-end value for the *exception_list*.

⁸⁵⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/exception.hpp

HPX_THROW_EXCEPTION

Defined in header [hpx/exception.hpp](#)⁸⁵⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *HPX_THROW_BAD_ALLOC*
- *HPX_THROWS_IF*

Warning: doxygenfunction: Cannot find function “HPX_THROW_EXCEPTION” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

HPX_THROW_BAD_ALLOC

Defined in header [hpx/exception.hpp](#)⁸⁵⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *HPX_THROW_EXCEPTION*
- *HPX_THROWS_IF*

Warning: doxygenfunction: Cannot find function “HPX_THROW_BAD_ALLOC” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

HPX_THROWS_IF

Defined in header [hpx/exception.hpp](#)⁸⁵⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *HPX_THROW_EXCEPTION*
- *HPX_THROW_BAD_ALLOC*

Warning: doxygenfunction: Cannot find function “HPX_THROWS_IF” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

⁸⁵⁵ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/exception.hpp

⁸⁵⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/exception.hpp

⁸⁵⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/exception.hpp

hpx/errors/macros.hpp

Defined in header `hpx/errors/macros.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_THROW_EXCEPTION(errcode, f, ...)

Throw a `hpx::exception` initialized from the given parameters.

The macro `HPX_THROW_EXCEPTION` can be used to throw a `hpx::exception`. The purpose of this macro is to prepend the source file name and line number of the position where the exception is thrown to the error message. Moreover, this associates additional diagnostic information with the exception, such as file name and line number, locality id and thread id, and stack backtrace from the point where the exception was thrown.

The parameter `errcode` holds the `hpx::error` code the new exception should encapsulate. The parameter `f` is expected to hold the name of the function exception is thrown from and the parameter `msg` holds the error message the new exception should encapsulate.

```
void raise_exception()
{
    // Throw a hpx::exception initialized from the given parameters.
    // Additionally associate with this exception some detailed
    // diagnostic information about the throw-site.
    HPX_THROW_EXCEPTION(hpx::error::no_success, "raise_exception",
        "simulated error");
}
```

Example:

HPX_THROW_EXCEPTION_MODE(errcode, mode, f, ...)

Throw a `hpx::exception` initialized from the given parameters.

The macro `HPX_THROW_EXCEPTION_MODE` can be used to throw a `hpx::exception`. The purpose of this macro is to prepend the source file name and line number of the position where the exception is thrown to the error message. Moreover, this associates additional diagnostic information with the exception, such as file name and line number, locality id and thread id, and stack backtrace from the point where the exception was thrown.

The parameter `errcode` holds the `hpx::error` code the new exception should encapsulate. The parameter `f` is expected to hold the name of the function exception is thrown from and the parameter `msg` holds the error message the new exception should encapsulate. The `throwmode` parameter allows to specify the type of the thrown exception.

```
void raise_exception() {
    // Throw a hpx::exception initialized from the given parameters.
    HPX_THROW_EXCEPTION_MODE(hpx::error::no_success,
        hpx::throwmode::lighweight, "raise_exception",
        "simulated error");
}
```

Example:**HPX_THROW_BAD_ALLOC(f)**

Throw a `hpx::bad_alloc_exception` initialized from the given parameters.

The macro `HPX_THROW_BAD_ALLOC` can be used to throw a `hpx::exception`. The purpose of this macro is to prepend the source file name and line number of the position where the exception is thrown to the error message. Moreover, this associates additional diagnostic information with the exception, such as file name and line number, locality id and thread id, and stack backtrace from the point where the exception was thrown.

The parameter `errcode` holds the `hpx::error` code the new exception should encapsulate. The parameter `f` is expected to hold the name of the function exception is thrown from and the parameter `msg` holds the error message the new exception should encapsulate.

```
void raise_exception()
{
    // Throw a hpx::exception initialized from the given parameters.
    // Additionally associate with this exception some detailed
    // diagnostic information about the throw-site.
    HPX_THROW_BAD_ALLOC("raise_exception", "simulated error");
}
```

Example:**HPX_THROWS_IF(ec, errcode, f, ...)**

Either throw a `hpx::exception` or initialize `hpx::error_code` from the given parameters.

The macro `HPX_THROWS_IF` can be used to either throw a `hpx::exception` or to initialize a `hpx::error_code` from the given parameters. If `&ec == &hpx::throws`, the semantics of this macro are equivalent to `HPX_THROW_EXCEPTION`. If `&ec != &hpx::throws`, the `hpx::error_code` instance `ec` is initialized instead.

The parameter `errcode` holds the `hpx::error` code from which the new exception should be initialized. The parameter `f` is expected to hold the name of the function exception is thrown from and the parameter `msg` holds the error message the new exception should encapsulate.

HPX_THROWS_BAD_ALLOC_IF(ec, f)

Either throw a `hpx::bad_alloc_exception` or `hpx::error_code` to `out_of_memory`.

The macro `HPX_THROWS_BAD_ALLOC_IF` can be used to either throw a `hpx::bad_alloc_exception` or to initialize a `hpx::error_code` to `hpx::error::out_of_memory`. If `&ec == &hpx::throws`, the semantics of this macro are equivalent to `HPX_THROW_BAD_ALLOC`. If `&ec != &hpx::throws`, the `hpx::error_code` instance `ec` is initialized instead.

HPX_DEFINE_ERROR_INFO(NAME, TYPE)

hpx/errors/error.hpp

Defined in header `hpx/errors/error.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_ERROR_UNSCOPED_ENUM_DEPRECATION_MSG

namespace **hpx**

Enums

enum class **error** : `std::int16_t`

Possible error conditions.

This enumeration lists all possible error conditions which can be reported from any of the API functions.

Values:

enumerator **success**

The operation was successful.

enumerator **no_success**

The operation did failed, but not in an unexpected manner.

enumerator **not_implemented**

The operation is not implemented.

enumerator **out_of_memory**

The operation caused an out of memory condition.

enumerator **bad_action_code**

enumerator **bad_component_type**

The specified component type is not known or otherwise invalid.

enumerator **network_error**

A generic network error occurred.

enumerator **version_too_new**

The version of the network representation for this object is too new.

enumerator **version_too_old**

The version of the network representation for this object is too old.

enumerator **version_unknown**

The version of the network representation for this object is unknown.

enumerator **unknown_component_address**

enumerator **duplicate_component_address**

The given global id has already been registered.

enumerator **invalid_status**

The operation was executed in an invalid status.

enumerator **bad_parameter**

One of the supplied parameters is invalid.

enumerator **internal_server_error**

enumerator **service_unavailable**

enumerator **bad_request**

enumerator **repeated_request**

enumerator **lock_error**

enumerator **duplicate_console**

There is more than one console locality.

enumerator **no_registered_console**

There is no registered console locality available.

enumerator **startup_timed_out**

enumerator **uninitialized_value**

enumerator **bad_response_type**

enumerator **deadlock**

enumerator **assertion_failure**

enumerator **null_thread_id**

Attempt to invoke an API function from a non-HPX thread.

enumerator **invalid_data**

enumerator **yield_aborted**

The yield operation was aborted.

enumerator **dynamic_link_failure**

enumerator **commandline_option_error**

One of the options given on the command line is erroneous.

enumerator **serialization_error**

There was an error during serialization of this object.

enumerator **unhandled_exception**

An unhandled exception has been caught.

enumerator **kernel_error**

The OS kernel reported an error.

enumerator **broken_task**

The task associated with this future object is not available anymore.

enumerator **task_moved**

The task associated with this future object has been moved.

enumerator **task_already_started**

The task associated with this future object has already been started.

enumerator **future_already_retrieved**

The future object has already been retrieved.

enumerator **promise_already_satisfied**

The value for this future object has already been set.

enumerator **future_does_not_support_cancellation**

The future object does not support cancellation.

enumerator **future_can_not_be_cancelled**

The future can't be canceled at this time.

enumerator **no_state**

The future object has no valid shared state.

enumerator **broken_promise**

The promise has been deleted.

enumerator **thread_resource_error**

enumerator **future_cancelled**

enumerator **thread_cancelled**

enumerator **thread_not_interruptable**

enumerator **duplicate_component_id**

The component type has already been registered.

enumerator **unknown_error**

An unknown error occurred.

enumerator **bad_plugin_type**

The specified plugin type is not known or otherwise invalid.

enumerator **filesystem_error**

The specified file does not exist or other filesystem related error.

enumerator **bad_function_call**

equivalent of `std::bad_function_call`

enumerator **task_canceled_exception**

`parallel::task_canceled_exception`

enumerator **task_block_not_active**

`task_region` is not active

enumerator **out_of_range**

Equivalent to `std::out_of_range`.

enumerator **length_error**

Equivalent to `std::length_error`.

enumerator **migration_needs_retry**

migration failed because of global race, retry

enumerator **stale_state**

The queried state may be stale, e.g. because no state has been recorded yet or a preceding notification has not yet been delivered

enumerator **target_fenced**

A dispatch was deliberately and correctly refused because the target had already latched a terminal lifecycle event; this is a final rejection, not a staleness signal, and should not be retried

enumerator **future_wait_timed_out**

future wait timed out

enumerator **locality_was_disconnected**

the requested target locality was disconnected

Functions

constexpr bool **operator==**(int lhs, *error* rhs) noexcept

constexpr bool **operator==**(*error* lhs, int rhs) noexcept

constexpr bool **operator!=**(int lhs, *error* rhs) noexcept

constexpr bool **operator!=**(*error* lhs, int rhs) noexcept

constexpr bool **operator<**(int lhs, *error* rhs) noexcept

constexpr bool **operator>=**(int lhs, *error* rhs) noexcept

constexpr int **operator&**(*error* lhs, *error* rhs) noexcept

constexpr int **operator&**(int lhs, *error* rhs) noexcept

constexpr int **operator|**=(int &lhs, *error* rhs) noexcept

char const ***get_error_name**(*error* e) noexcept

Variables

constexpr *error* **success** = *error::success*

constexpr *error* **no_success** = *error::no_success*

constexpr *error* **not_implemented** = *error::not_implemented*

constexpr *error* **out_of_memory** = *error::out_of_memory*

constexpr *error* **bad_action_code** = *error::bad_action_code*

constexpr *error* **bad_component_type** = *error::bad_component_type*

constexpr *error* **network_error** = *error::network_error*

constexpr *error* **version_too_new** = *error::version_too_new*

constexpr *error* **version_too_old** = *error::version_too_old*

```
constexpr error version_unknown = error::version_unknown

constexpr error unknown_component_address = error::unknown_component_address

constexpr error duplicate_component_address = error::duplicate_component_address

constexpr error invalid_status = error::invalid_status

constexpr error bad_parameter = error::bad_parameter

constexpr error internal_server_error = error::internal_server_error

constexpr error service_unavailable = error::service_unavailable

constexpr error bad_request = error::bad_request

constexpr error repeated_request = error::repeated_request

constexpr error lock_error = error::lock_error

constexpr error duplicate_console = error::duplicate_console

constexpr error no_registered_console = error::no_registered_console

constexpr error startup_timed_out = error::startup_timed_out

constexpr error uninitialized_value = error::uninitialized_value

constexpr error bad_response_type = error::bad_response_type

constexpr error deadlock = error::deadlock

constexpr error assertion_failure = error::assertion_failure

constexpr error null_thread_id = error::null_thread_id

constexpr error invalid_data = error::invalid_data

constexpr error yield_aborted = error::yield_aborted

constexpr error dynamic_link_failure = error::dynamic_link_failure
```

```
constexpr error commandline_option_error = error::commandline_option_error

constexpr error serialization_error = error::serialization_error

constexpr error unhandled_exception = error::unhandled_exception

constexpr error kernel_error = error::kernel_error

constexpr error broken_task = error::broken_task

constexpr error task_moved = error::task_moved

constexpr error task_already_started = error::task_already_started

constexpr error future_already_retrieved = error::future_already_retrieved

constexpr error promise_already_satisfied = error::promise_already_satisfied

constexpr error future_does_not_support_cancellation =
error::future_does_not_support_cancellation

constexpr error future_can_not_be_cancelled = error::future_can_not_be_cancelled

constexpr error no_state = error::no_state

constexpr error broken_promise = error::broken_promise

constexpr error thread_resource_error = error::thread_resource_error

constexpr error future_cancelled = error::future_cancelled

constexpr error thread_cancelled = error::thread_cancelled

constexpr error thread_not_interruptable = error::thread_not_interruptable

constexpr error duplicate_component_id = error::duplicate_component_id

constexpr error unknown_error = error::unknown_error

constexpr error bad_plugin_type = error::bad_plugin_type

constexpr error filesystem_error = error::filesystem_error
```

```
constexpr error bad_function_call = error::bad_function_call
```

```
constexpr error task_canceled_exception = error::task_canceled_exception
```

```
constexpr error task_block_not_active = error::task_block_not_active
```

```
constexpr error out_of_range = error::out_of_range
```

```
constexpr error length_error = error::length_error
```

```
constexpr error migration_needs_retry = error::migration_needs_retry
```

hpx/errors/exception_fwd.hpp

Defined in header `hpx/errors/exception_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Enums

```
enum class throwmode : std::uint8_t
```

Encode error category for new *error_code*.

Values:

```
enumerator plain
```

```
enumerator rethrow
```

```
enumerator lightweight
```

Functions

```
constexpr bool operator&(throwmode lhs, throwmode rhs) noexcept
```

Variables

error_code throws

Predefined *error_code* object used as “throw on error” tag.

The predefined *hpx::error_code* object *hpx::throws* is supplied for use as a “throw on error” tag.

Functions that specify an argument in the form ‘*error_code*& ec=throws’ (with appropriate namespace qualifiers), have the following error handling semantics:

If *&ec != &throws* and an error occurred: *ec.value()* returns the implementation specific error number for the particular error that occurred and *ec.category()* returns the *error_category* for *ec.value()*.

If *&ec != &throws* and an error did not occur, *ec.clear()*.

If an error occurs and *&ec == &throws*, the function throws an exception of type *hpx::exception* or of a type derived from it. The exception’s *get_errorcode()* member function returns a reference to a *hpx::error_code* object with the behavior as specified above.

execution

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::execution::experimental::guided_chunk_size

Defined in header *hpx/execution.hpp*⁸⁵⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

struct *guided_chunk_size*

Iterations are dynamically assigned to threads in blocks as threads request those until no blocks remain to be assigned. Similar to *dynamic_chunk_size* except that the block size decreases each time a number of loop iterations is given to a thread. The size of the initial block is proportional to *number_of_iterations / number_of_cores*. Subsequent blocks are proportional to *number_of_iterations_remaining / number_of_cores*. The optional chunk size parameter defines the minimum block size. The default chunk size is 1.

Note: This executor parameters type is equivalent to OpenMP’s GUIDED scheduling directive.

hpx/execution/executors/execution_parameters_fwd.hpp

Defined in header *hpx/execution/executors/execution_parameters_fwd.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

⁸⁵⁸ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

namespace **experimental**

Variables

constexpr struct *hpx::execution::experimental::null_parameters_t* **null_parameters**

constexpr struct *hpx::execution::experimental::get_chunk_size_t* **get_chunk_size**

constexpr struct *hpx::execution::experimental::measure_iteration_t* **measure_iteration**

constexpr struct *hpx::execution::experimental::maximal_number_of_chunks_t*
maximal_number_of_chunks

constexpr struct *hpx::execution::experimental::reset_thread_distribution_t*
reset_thread_distribution

constexpr struct *hpx::execution::experimental::processing_units_count_t*
processing_units_count

constexpr struct *hpx::execution::experimental::with_processing_units_count_t*
with_processing_units_count

constexpr struct *hpx::execution::experimental::mark_begin_execution_t* **mark_begin_execution**

constexpr struct *hpx::execution::experimental::mark_end_of_scheduling_t*
mark_end_of_scheduling

constexpr struct *hpx::execution::experimental::mark_end_execution_t* **mark_end_execution**

constexpr struct *hpx::execution::experimental::mark_partition_t* **mark_partition**

constexpr struct *hpx::execution::experimental::collect_execution_parameters_t*
collect_execution_parameters

struct **collect_execution_parameters_t**

#include <execution_parameters_fwd.hpp> Collect various parameters of the chunking for this parallel algorithm execution

Note: This calls `params.mark_begin_execution(exec)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Param num_elements

[in] The overall number of elements for the algorithm.

Param num_cores

[in] The overall number of cores to utilize for the algorithm.

Param num_chunks

[in] The overall number of chunks for the algorithm.

Param chunk_size

[in] The size of the chunks created for the algorithm.

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator()(Parameters &&params, Executor &&exec, std::size_t
                                num_elements, std::size_t num_cores, std::size_t
                                num_chunks, std::size_t chunk_size) const
```

```
struct get_chunk_size_t
```

#include <execution_parameters_fwd.hpp> Return the number of invocations of the given function *f* which should be combined into a single task

Param params

[in] The executor parameters object to use for determining the chunk size for the given number of tasks *num_tasks*.

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Param iteration_duration

[in] The time one of the tasks require to be executed.

Param cores

[in] The number of cores the number of chunks should be determined for.

Param num_tasks

[in] The number of tasks the chunk size should be determined for

Return

The size of the chunks (number of iterations per chunk) that should be used for parallel execution.

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator()(Parameters &&params, Executor &&exec,
                                hpx::chrono::steady_duration const &iteration_duration,
                                std::size_t cores, std::size_t num_tasks) const
```

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator()(Parameters &&params, Executor &&exec, std::size_t cores,
                                std::size_t num_tasks) const
```

```
template<>
```

```
struct is_scheduling_property<with_processing_units_count_t> : public true_type
```

```
struct mark_begin_execution_t
```

#include <execution_parameters_fwd.hpp> Mark the begin of a parallel algorithm execution

Note: This calls `params.mark_begin_execution(exec)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator()(Parameters &&params, Executor &&exec) const
```

```
struct mark_end_execution_t
```

```
#include <execution_parameters_fwd.hpp> Mark the end of a parallel algorithm execution
```

Note: This calls `params.mark_end_execution(exec)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator()(Parameters &&params, Executor &&exec) const
```

```
struct mark_end_of_scheduling_t
```

```
#include <execution_parameters_fwd.hpp> Mark the end of scheduling tasks during parallel algorithm execution
```

Note: This calls `params.mark_begin_execution(exec)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Public Functions

```
template<typename Parameters, typename Executor>  
inline decltype(auto) operator() (Parameters &&params, Executor &&exec) const
```

```
struct mark_partition_t
```

```
#include <execution_parameters_fwd.hpp> Mark custom point in parallel algorithm execution
```

Note: This calls `params.mark_partition(exec, partition, args...)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Public Functions

```
template<typename Parameters, typename Executor, typename ...Args>  
inline decltype(auto) operator() (Parameters &&params, Executor &&exec, std::size_t  
partition, Args&&... args) const
```

```
struct maximal_number_of_chunks_t
```

```
#include <execution_parameters_fwd.hpp> Return the largest reasonable number of chunks to  
create for a single algorithm invocation.
```

Param params

[in] The executor parameters object to use for determining the number of chunks for the
given number of *cores*.

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Param cores

[in] The number of cores the number of chunks should be determined for.

Param num_tasks

[in] The number of tasks the chunk size should be determined for

Public Functions

```
template<typename Parameters, typename Executor>  
inline decltype(auto) operator() (Parameters &&params, Executor &&exec, std::size_t cores,  
std::size_t num_tasks) const
```

```
struct measure_iteration_t
```

```
#include <execution_parameters_fwd.hpp> Return the measured execution time for one iteration  
based on running the given function.
```

Note: The parameter *f* is expected to be a nullary function returning a `std::size_t` representing
the number of iteration the function has already executed (i.e. which don't have to be scheduled
anymore).

Param params

[in] The executor parameters object to use for determining the chunk size for the given number of tasks *num_tasks*.

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Param f

[in] The function which will be optionally scheduled using the given executor.

Param num_tasks

[in] The number of tasks the chunk size should be determined for

Return

The execution time for one of the tasks.

Public Functions

```
template<typename Parameters, typename Executor, typename F>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec, F &&f,
                                   std::size_t num_tasks) const
```

```
struct null_parameters_t
```

```
struct processing_units_count_t
```

#include <execution_parameters_fwd.hpp> Retrieve the number of (kernel-)threads used by the associated executor.

Note: This calls `params.processing_units_count(Executor&&)` if it exists; otherwise it forwards the request to the executor parameters object.

Param params

[in] The executor parameters object to use as a fallback if the executor does not expose

Param exec

[in] The executor object which will be used for scheduling of the loop iterations.

Param iteration_duration

[in] The time one of the tasks require to be executed.

Param num_tasks

[in] The number of tasks the number of cores should be determined for

Return

The number of cores to use

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec,
                                   hpx::chrono::steady_duration const &iteration_duration,
                                   std::size_t num_tasks) const
```

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec, std::size_t
                                   num_tasks) const
```

```
template<typename Executor>
```

```
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                   &iteration_duration, std::size_t num_tasks) const

template<typename Executor>
inline decltype(auto) operator() (Executor &&exec, std::size_t num_tasks) const

template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec) const

template<typename Executor>
inline decltype(auto) operator() (Executor &&exec) const

template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec,
                                   hpx::chrono::steady_duration const &iteration_duration,
                                   std::size_t num_tasks) const

template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec, std::size_t
                                   num_tasks = 0) const

template<typename Executor>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                   &iteration_duration, std::size_t num_tasks) const

template<typename Executor>
inline decltype(auto) operator() (Executor &&exec, std::size_t num_tasks = 0) const

template<typename ExPolicy>
inline decltype(auto) operator() (ExPolicy &&policy) const
```

struct **reset_thread_distribution_t**

#include <execution_parameters_fwd.hpp> Reset the internal round robin thread distribution scheme for the given executor.

Note: This calls `params.reset_thread_distribution(exec)` if it exists; otherwise it does nothing.

Param params

[in] The executor parameters object to use for resetting the thread distribution scheme.

Param exec

[in] The executor object to use.

Public Functions

```
template<typename Parameters, typename Executor>
inline decltype(auto) operator() (Parameters &&params, Executor &&exec) const
```

struct **with_processing_units_count_t**

#include <execution_parameters_fwd.hpp> Generate a policy that supports setting the number of cores for execution.

Public Functions

```
template<typename Executor>
inline decltype(auto) operator() (Executor &&exec, std::size_t num_cores) const

template<typename Policy, typename Property>
inline decltype(auto) operator() (Policy &&policy, Property &&property) const
```

hpx/execution/executors/default_parameters.hpp

Defined in header `hpx/execution/executors/default_parameters.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **execution**

namespace **experimental**

struct **default_parameters**

#include <default_parameters.hpp> Loop iterations are divided into pieces of size *chunk_size* and then assigned to threads. If *chunk_size* is not specified, the iterations are evenly (if possible) divided contiguously among the threads.

Note: This executor parameters type is equivalent to OpenMP's STATIC scheduling directive.

Public Functions

default_parameters() = default

Construct a default_parameters executor parameters object

Note: By default, the number of loop iterations is determined from the number of available cores and the overall number of loop iterations to schedule.

hpx::execution::experimental::collect_chunking_parameters

Defined in header `hpx/execution.hpp`⁸⁵⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

struct **collect_chunking_parameters**

Collect various parameters used for running a parallel algorithm.

⁸⁵⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

hpx/execution/executors/execution_parameters.hpp

Defined in header `hpx/execution/executors/execution_parameters.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

Functions

```
template<typename ...Params>
constexpr executor_parameters_join<Params...>::type join_executor_parameters(Params&&...
                                                                    params)
```

```
template<typename Param>
constexpr Param &&join_executor_parameters(Param &&param) noexcept
```

```
template<typename ...Params>
struct executor_parameters_join
```

Public Types

```
using type = detail::executor_parameters<std::decay_t<Params>...>

template<typename Param>
struct executor_parameters_join<Param>
```

Public Types

```
using type = Param
```

hpx/execution/executors/rebind_executor.hpp

Defined in header `hpx/execution/executors/rebind_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

Typedefs

```
template<typename ExPolicy, typename Executor, typename Parameters>
using rebind_executor_t = typename rebind_executor<ExPolicy, Executor, Parameters>::type
```

Variables

```
constexpr struct hpx::execution::experimental::create_rebound_policy_t create_rebound_policy
```

```
struct create_rebound_policy_t
```

Public Functions

```
template<typename ExPolicy, typename Executor, typename Parameters>
inline constexpr decltype(auto) operator() (ExPolicy&&, Executor &&exec, Parameters
&&parameters) const
```

```
template<typename ExPolicy, typename Executor>
inline constexpr decltype(auto) operator() (ExPolicy &&policy, Executor &&exec) const
```

```
template<typename ExPolicy, typename Parameters>
inline constexpr decltype(auto) operator() (ExPolicy &&policy, Parameters &&parameters)
const
```

```
template<typename ExPolicy, typename Executor, typename Parameters>
```

```
struct rebind_executor
```

#include <*rebind_executor.hpp*> Rebind the type of executor used by an execution policy. The execution category of *Executor* shall not be weaker than that of *ExecutionPolicy*.

Public Types

```
using type = typename policy_type::template rebind<executor_type, parameters_type>::type
```

The type of the rebound execution policy.

hpx::execution::experimental::max_num_chunks

Defined in header *hpx/execution.hpp*⁸⁶⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
struct max_num_chunks
```

Loop iterations are divided into not more than *num_chunks* partitions that are assigned to threads. If *num_chunks* is not specified, the number of chunks is determined based on the number of available cores.

⁸⁶⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

hpx::execution::experimental::auto_chunk_size

Defined in header [hpx/execution.hpp](#)⁸⁶¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

struct **auto_chunk_size**

Loop iterations are divided into pieces and then assigned to threads. The number of loop iterations combined is determined based on measurements of how long the execution of 1% of the overall number of iterations takes. This executor parameters type makes sure that as many loop iterations are combined as necessary to run for the amount of time specified.

hpx/execution/executors/execution_information.hpp

Defined in header `hpx/execution/executors/execution_information.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

namespace **experimental**

Variables

constexpr struct *hpx::execution::experimental::has_pending_closures_t* **has_pending_closures**

constexpr struct *hpx::execution::experimental::get_pu_mask_t* **get_pu_mask**

constexpr struct *hpx::execution::experimental::set_scheduler_mode_t* **set_scheduler_mode**

struct **get_pu_mask_t**

#include <execution_information.hpp> Retrieve the bitmask describing the processing units the given thread is allowed to run on

All threads::executors invoke `sched.get_pu_mask()`.

Note: If the executor does not support this operation, this call will always invoke `hpx::threads::get_pu_mask()`

Param exec

[in] The executor object to use for querying the number of pending tasks.

Param topo

[in] The topology object to use to extract the requested information.

⁸⁶¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

Param `thream_num`

[in] The sequence number of the thread to retrieve information for.

Public Functions

```
template<typename Executor>
inline decltype(auto) operator() (Executor &&exec, threads::topology &topo, std::size_t
                                     thread_num) const
```

```
template<typename Executor>
inline decltype(auto) operator() (Executor&&, threads::topology &topo, std::size_t
                                     thread_num) const
```

struct **has_pending_closures_t**

#include <execution_information.hpp> Retrieve whether this executor has operations pending or not.

Note: If the executor does not expose this information, this call will always return *false*

Param `exec`

[in] The executor object to use to extract the requested information for.

Public Functions

```
template<typename Executor>
inline decltype(auto) operator() (Executor &&exec) const
```

```
template<typename Executor>
inline decltype(auto) operator() (Executor&&) const
```

struct **set_scheduler_mode_t**

#include <execution_information.hpp> Set various modes of operation on the scheduler underneath the given executor.

Note: This calls `exec.set_scheduler_mode(mode)` if it exists; otherwise it does nothing.

Param `exec`

[in] The executor object to use.

Param `mode`

[in] The new mode for the scheduler to pick up

Public Functions

```
template<typename Executor, typename Mode>  
inline void operator() (Executor &&exec, Mode const &mode) const
```

```
template<typename Executor, typename Mode>  
inline void operator() (Executor&&, Mode const&) const
```

hpx::execution::experimental::num_cores

Defined in header [hpx/execution.hpp](#)⁸⁶².

See *Public API* for a list of names and headers that are part of the public HPX API.

struct **num_cores**

Control number of cores in executors which need a functionality for setting the number of cores to be used by an algorithm directly

hpx::execution::experimental::dynamic_chunk_size

Defined in header [hpx/execution.hpp](#)⁸⁶³.

See *Public API* for a list of names and headers that are part of the public HPX API.

struct **dynamic_chunk_size**

Loop iterations are divided into pieces of size *chunk_size* and then dynamically scheduled among the threads; when a thread finishes one chunk, it is dynamically assigned another. If *chunk_size* is not specified, the default chunk size is 1.

Note: This executor parameters type is equivalent to OpenMP's DYNAMIC scheduling directive.

hpx::execution::experimental::persistent_auto_chunk_size

Defined in header [hpx/execution.hpp](#)⁸⁶⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

struct **persistent_auto_chunk_size**

Loop iterations are divided into pieces and then assigned to threads. The number of loop iterations combined is determined based on measurements of how long the execution of 1% of the overall number of iterations takes. This executor parameters type makes sure that as many loop iterations are combined as necessary to run for the amount of time specified.

⁸⁶² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

⁸⁶³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

⁸⁶⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

hpx/execution/executors/execution.hpp

Defined in header `hpx/execution/executors/execution.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

```
        namespace execution
```

hpx/execution/executors/polymorphic_executor.hpp

Defined in header `hpx/execution/executors/polymorphic_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

```
            namespace parallel
```

```
                namespace execution
```

```
                    template<typename Sig>
```

```
                    class polymorphic_executor
```

```
                    template<typename R, typename ...Ts>
```

```
                    class polymorphic_executor<R(Ts...)> : private
```

```
                    hpx::parallel::execution::detail::polymorphic_executor_base
```

Public Types

```
        template<typename>
```

```
        using future_type = hpx::future<R>
```

Public Functions

```
inline constexpr polymorphic_executor() noexcept

inline polymorphic_executor(polymorphic_executor const &other)

inline polymorphic_executor(polymorphic_executor &&other) noexcept

inline polymorphic_executor &operator=(polymorphic_executor const &other)

inline polymorphic_executor &operator=(polymorphic_executor &&other) noexcept

template<typename Exec, typename PE = std::decay_t<Exec>, typename Enable =  
std::enable_if_t<!std::is_same_v<PE, polymorphic_executor>>>  
inline polymorphic_executor(Exec &&exec)

template<typename Exec, typename PE = std::decay_t<Exec>, typename Enable =  
std::enable_if_t<!std::is_same_v<PE, polymorphic_executor>>>  
inline polymorphic_executor &operator=(Exec &&exec)

inline void reset() noexcept

template<typename F>
inline void post(F &&f, Ts... ts) const

template<typename F>
inline R sync_execute(F &&f, Ts... ts) const

template<typename F>
inline hpx::future<R> async_execute(F &&f, Ts... ts) const

template<typename F, typename Future>
inline hpx::future<R> then_execute(F &&f, Future &&predecessor, Ts&&... ts) const

template<typename F, typename Shape>
inline std::vector<R> bulk_sync_execute(F &&f, Shape const &s, Ts&&... ts) const

template<typename F, typename Shape>
inline hpx::future<std::vector<R>> bulk_async_execute(F &&f, Shape const &s, Ts&&...  
ts) const

template<typename F, typename Shape>
inline hpx::future<std::vector<R>> bulk_then_execute(F &&f, Shape const &s,  
hpx::shared_future<void> const  
&predecessor, Ts&&... ts) const
```

Private Types

```
using base_type = detail::polymorphic_executor_base

using vtable = detail::polymorphic_executor_vtable<R(Ts...)>
```

Private Functions

```
inline void assign(std::nullptr_t) noexcept
```

```
template<typename Exec>
inline void assign(Exec &&exec)
```

Private Static Functions

```
static inline constexpr vtable const *get_empty_vtable() noexcept
```

```
template<typename T>
static inline constexpr vtable const *get_vtable() noexcept
```

hpx::execution::experimental::static_chunk_size

Defined in header `hpx/execution.hpp`⁸⁶⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
struct static_chunk_size
```

Loop iterations are divided into pieces of size *chunk_size* and then assigned to threads. If *chunk_size* is not specified, the iterations are evenly (if possible) divided contiguously among the threads.

Note: This executor parameters type is equivalent to OpenMP's *STATIC* scheduling directive.

hpx/execution/executors/adaptive_static_chunk_size.hpp

Defined in header `hpx/execution/executors/adaptive_static_chunk_size.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace execution
```

```
namespace experimental
```

```
struct adaptive_static_chunk_size
```

#include <adaptive_static_chunk_size.hpp> Loop iterations are divided into pieces of size *chunk_size* and then assigned to threads. If *chunk_size* is not specified, the iterations are evenly (if possible) divided contiguously among the threads.

Note: This executor parameters type is equivalent to OpenMP's *STATIC* scheduling directive.

⁸⁶⁵ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

Public Functions

adaptive_static_chunk_size() = default

Construct a `adaptive_static_chunk_size` executor parameters object

Note: By default the number of loop iterations is determined from the number of available cores and the overall number of loop iterations to schedule.

inline explicit constexpr **adaptive_static_chunk_size**(*std::size_t* const chunk_size)
noexcept

Construct a `adaptive_static_chunk_size` executor parameters object

Parameters

chunk_size – [in] The optional chunk size to use as the number of loop iterations to run on a single thread.

hpx/execution/traits/is_execution_policy.hpp

Defined in header `hpx/execution/traits/is_execution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Variables

template<typename T>

constexpr bool **is_execution_policy_v** = *is_execution_policy*<T>::value

template<typename T> concept execution_policy = is_execution_policy<T>::value

template<typename T>

constexpr bool **is_parallel_execution_policy_v** = *is_parallel_execution_policy*<T>::value

template<typename T>

constexpr bool **is_sequenced_execution_policy_v** = *is_sequenced_execution_policy*<T>::value

template<typename T>

constexpr bool **is_async_execution_policy_v** = *is_async_execution_policy*<T>::value

template<typename T>

struct **is_async_execution_policy** : public *hpx::detail::is_async_execution_policy*<*std::decay_t*<T>>

#include <is_execution_policy.hpp> Extension: Detect whether given execution policy makes algorithms asynchronous

- i. The type *is_async_execution_policy* can be used to detect asynchronous execution policies for the purpose of excluding function signatures from otherwise ambiguous overload resolution participation.

- ii. If `T` is the type of the standard or implementation-defined execution policy, `is_async_execution_policy<T>` shall be publicly derived from `integral_constant<bool, true>`, otherwise from `integral_constant<bool, false>`.

- iii. The behavior of a program that adds specializations for `is_async_execution_policy` is undefined.

template<typename `T`>

struct **is_execution_policy** : public `hpx::detail::is_execution_policy<std::decay_t<T>>`

`#include <is_execution_policy.hpp>`

- i. The type `is_execution_policy` can be used to detect execution policies for the purpose of excluding function signatures from otherwise ambiguous overload resolution participation.
- ii. If `T` is the type of the standard or implementation-defined execution policy, `is_execution_policy<T>` shall be publicly derived from `integral_constant<bool, true>`, otherwise from `integral_constant<bool, false>`.
- iii. The behavior of a program that adds specializations for `is_execution_policy` is undefined.

template<typename `T`>

struct **is_parallel_execution_policy** : public

`hpx::detail::is_parallel_execution_policy<std::decay_t<T>>`

`#include <is_execution_policy.hpp>` Extension: Detect whether given execution policy enables parallelization

- i. The type `is_parallel_execution_policy` can be used to detect parallel execution policies for the purpose of excluding function signatures from otherwise ambiguous overload resolution participation.
- ii. If `T` is the type of the standard or implementation-defined execution policy, `is_parallel_execution_policy<T>` shall be publicly derived from `integral_constant<bool, true>`, otherwise from `integral_constant<bool, false>`.
- iii. The behavior of a program that adds specializations for `is_parallel_execution_policy` is undefined.

template<typename `T`>

struct **is_sequenced_execution_policy** : public

`hpx::detail::is_sequenced_execution_policy<std::decay_t<T>>`

`#include <is_execution_policy.hpp>` Extension: Detect whether given execution policy does not enable parallelization

- i. The type `is_sequenced_execution_policy` can be used to detect non-parallel execution policies for the purpose of excluding function signatures from otherwise ambiguous overload resolution participation.
- ii. If `T` is the type of the standard or implementation-defined execution policy, `is_sequenced_execution_policy<T>` shall be publicly derived from `integral_constant<bool, true>`, otherwise from `integral_constant<bool, false>`.
- iii. The behavior of a program that adds specializations for `is_sequenced_execution_policy` is undefined.

hpx/execution/algorithms/sender_future.hpp

Defined in header `hpx/execution/algorithms/sender_future.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Converts any P2300 `stdexec` sender into an `hpx::future<T>`.

Usage:

```
// Explicit T:
auto sender = stdexec::just(42) | stdexec::then([](int x){ return x; });
hpx::future<int> f =
    hpx::execution::experimental::as_future<int>(std::move(sender));
int val = f.get();    // == 42
```

namespace **hpx**

namespace **execution**

namespace **experimental**

Variables

```
template<typename T>
constexpr as_future_t<T> as_future = {}

template<typename T>
struct as_future_t
```

Public Functions

```
template<typename Sender, typename =
    std::enable_if_t<hpx::execution::experimental::is_sender_v<std::decay_t<Sender>>>>
inline constexpr hpx::future<T> operator()(Sender &&sender) const
```

hpx/execution/algorithms/future_sender.hpp

Defined in header `hpx/execution/algorithms/future_sender.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Implementation details for adapting HPX futures as P2300 senders.

Usage:

```
hpx::future<int> f = hpx::async([]{ return 42; });
auto result = hpx::execution::experimental::as_sender(std::move(f))
    | hpx::execution::experimental::then([](int x){ return x * 2; })
    | hpx::execution::experimental::sync_wait();
```


namespace **hpx**

namespace **execution**

namespace **experimental**

execution_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/execution_base/execution.hpp

Defined in header `hpx/execution_base/execution.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

struct **parallel_execution_tag**

#include <execution.hpp> Function invocations executed by a group of parallel execution agents execute in unordered fashion. Any such invocations executing in the same thread are indeterminately sequenced with respect to each other.

Note: `parallel_execution_tag` is weaker than `sequenced_execution_tag`.

struct **sequenced_execution_tag**

#include <execution.hpp> Function invocations executed by a group of sequential execution agents execute in sequential order.

struct **unsequenced_execution_tag**

#include <execution.hpp> Function invocations executed by a group of vector execution agents are permitted to execute in unordered fashion when executed in different threads, and un-sequenced with respect to one another when executed in the same thread.

Note: `unsequenced_execution_tag` is weaker than `parallel_execution_tag`.

namespace **parallel**

namespace **execution**

Variables

constexpr struct *hpx::parallel::execution::sync_execute_t* **sync_execute**

constexpr struct *hpx::parallel::execution::async_execute_t* **async_execute**

constexpr struct *hpx::parallel::execution::then_execute_t* **then_execute**

constexpr struct *hpx::parallel::execution::post_t* **post**

constexpr struct *hpx::parallel::execution::bulk_sync_execute_t* **bulk_sync_execute**

constexpr struct *hpx::parallel::execution::bulk_async_execute_t* **bulk_async_execute**

constexpr struct *hpx::parallel::execution::bulk_then_execute_t* **bulk_then_execute**

constexpr struct *hpx::parallel::execution::async_invoke_t* **async_invoke**

constexpr struct *hpx::parallel::execution::sync_invoke_t* **sync_invoke**

struct **async_execute_t**

#include <execution.hpp> Customization point for asynchronous execution agent creation.

This asynchronously creates a single function invocation *f()* using the associated executor.

Note: Executors have to implement only `async_execute()`. All other functions will be emulated by this or other customization points in terms of this single basic primitive. However, some executors will naturally specialize all operations for maximum efficiency.

Note: This is valid for one way executors (calls `make_ready_future(exec.sync_execute(f, ts...))` if it exists) and for two-way executors (calls `exec.async_execute(f, ts...)` if it exists).

Param *exec*

[in] The executor object to use for scheduling of the function *f*.

Param *f*

[in] The function which will be scheduled using the given executor.

Param *ts*

[in] Additional arguments to use to invoke *f*.

Return

f(ts...)'s result through a future

Public Functions

```
template<typename Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

```
template<typename Executor, typename F, typename...
Ts> HPX_DEPRECATED_V (2, 0,
    "tag_invoke overloads for async_execute are deprecated. " "Define an .
    async_execute() member function instead.
    ") decltype(auto) operator() (Executor &&exec
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

Public Members

F &&f

```
F Ts &&const ts {return hpx::functional::tag_invoke_ns::tag_invoke(async_execute_t{}),
    std::forward< Executor >( exec ), std::forward< F >( f ),
    std::forward< Ts >( ts )...}
```

struct **async_invoke_t**

#include <execution.hpp> Asynchronously invoke the given set of nullary functions, each on its own execution agent

This creates a group of function invocations whose ordering is given by the `execution_category` associated with the executor.

All exceptions thrown by invocations of the functions are reported in a manner consistent with parallel algorithm execution through the returned future.

Note: This calls `exec.async_invoke(fs...)` if it exists; otherwise it executes `async_execute(fs)` for each `fs`.

Param **exec**

[in] The executor object to use for scheduling of the functions *fs*.

Param **fs**

[in] The functions which will be scheduled using the given executor.

Return

The return type of `executor_type::async_invoke` if defined by `executor_type`. Otherwise, a `future<void>` representing finishing the execution of all functions *fs*.

Public Functions

```
template<typename Executor, typename F, typename ...Fs>
inline decltype(auto) operator() (Executor &&exec, F &&f, Fs&&... fs) const
```

```
template<typename Executor, typename F, typename...
Fs> HPX_DEPRECATED_V (2, 0,
"tag_invoke overloads for async_invoke are deprecated. " "Define an .
async_invoke() member function instead.
") decltype(auto) operator() (Executor &&exec
```

```
template<executor_any Executor, typename F, typename ...Fs>
inline decltype(auto) operator() (Executor &&exec, F &&f, Fs&&... fs) const
```

Public Members

F &&f

```
F Fs &&const fs {return hpx::functional::tag_invoke_ns::tag_invoke(async_invoke_t{},
std::forward< Executor >( exec ), std::forward< F >( f ),
std::forward< Fs >( fs )...)
```

struct **bulk_async_execute_t**

#include <execution.hpp> Bulk form of asynchronous execution agent creation.

This asynchronously creates a group of function invocations $f(i)$ whose ordering is given by the `execution_category` associated with the executor.

Here i takes on all values in the index space implied by `shape`. All exceptions thrown by invocations of $f(i)$ are reported in a manner consistent with parallel algorithm execution through the returned future.

Note: This is deliberately different from the `bulk_async_execute` customization points specified in P0443. The `bulk_async_execute` customization point defined here is more generic and is used as the workhorse for implementing the specified APIs.

Note: This calls `exec.bulk_async_execute(f, shape, ts...)` if it exists; otherwise it executes `async_execute(f, shape, ts...)` as often as needed.

Param **exec**

[in] The executor object to use for scheduling of the function f .

Param **f**

[in] The function which will be scheduled using the given executor.

Param **shape**

[in] The shape objects which defines the iteration boundaries for the arguments to be passed to f .

Param **ts**

[in] Additional arguments to use to invoke f .

Return

The return type of `executor_type::bulk_async_execute` if defined by `executor_type`. Otherwise, a vector of futures holding the returned values of each invocation of `f`.

Public Functions

```
template<typename Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const

template<typename Executor, typename F, typename Shape, typename ...Ts>
inline auto operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts) const ->
    de-
    cltype(std::forward<Executor>(exec).bulk_async_execute(std::forward<F>(f),
    shape, std::forward<Ts>(ts)...))

template<typename Executor, typename F, typename Shape, typename...
Ts> HPX_DEPRECATED_V (2, 0,
    "tag_invoke overloads for bulk_async_execute are deprecated.
    " "Define a .bulk_async_execute() member function instead.
    ") decltype(auto) operator() (Executor &&exec

template<executor_any Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const

template<executor_any Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const
```

Public Members

F &&f

F Shape const & shape

```
F Shape const Ts &&const ts {return hpx::functional::tag_invoke_ns::tag_invoke(bulk_asyn
std::forward< Executor >( exec ),std::forward< F >( f ), shape,
std::forward< Ts >( ts )...)
```

struct **bulk_sync_execute_t**

#include <execution.hpp> Bulk form of synchronous execution agent creation.

This synchronously creates a group of function invocations `f(i)` whose ordering is given by the `execution_category` associated with the executor. The function synchronizes the execution of all scheduled functions with the caller.

Here *i* takes on all values in the index space implied by `shape`. All exceptions thrown by invocations of `f(i)` are reported in a manner consistent with parallel algorithm execution through the returned future.

Note: This is deliberately different from the `bulk_sync_execute` customization points specified in P0443. The `bulk_sync_execute` customization point defined here is more generic and is used as the workhorse for implementing the specified APIs.

Note: This calls `exec.bulk_sync_execute(f, shape, ts...)` if it exists; otherwise it executes `sync_execute(f, shape, ts...)` as often as needed.

Param `exec`

[in] The executor object to use for scheduling of the function *f*.

Param `f`

[in] The function which will be scheduled using the given executor.

Param `shape`

[in] The shape objects which defines the iteration boundaries for the arguments to be passed to *f*.

Param `ts`

[in] Additional arguments to use to invoke *f*.

Return

The return type of `executor_type::bulk_sync_execute` if defined by `executor_type`. Otherwise, a vector holding the returned values of each invocation of *f* except when *f* returns void, which case void is returned.

Public Functions

```
template<typename Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const
```

```
template<typename Executor, typename F, typename Shape, typename...
Ts> HPX_DEPRECATED_V (2, 0,
    "tag_invoke overloads for bulk_sync_execute are deprecated. " "Define a .
    bulk_sync_execute() member function instead.
    ") decltype(auto) operator() (Executor &&exec
```

```
template<executor_any Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const
```

```
template<executor_any Executor, typename F, typename Shape, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Ts&&... ts)
    const
```

Public Members

F &&**f**

F Shape **const** & **shape**

```
F Shape const Ts &&const ts {return hpx::functional::tag_invoke_ns::tag_invoke(bulk_sync,  
std::forward< Executor >( exec ),std::forward< F >( f ), shape,  
std::forward< Ts >( ts )...}
```

struct **bulk_then_execute_t**

#include <execution.hpp> Bulk form of execution agent creation depending on a given future.

This creates a group of function invocations $f(i)$ whose ordering is given by the `execution_category` associated with the executor.

Here i takes on all values in the index space implied by `shape`. All exceptions thrown by invocations of $f(i)$ are reported in a manner consistent with parallel algorithm execution through the returned future.

Note: This is deliberately different from the `then_sync_execute` customization points specified in P0443. The `bulk_then_execute` customization point defined here is more generic and is used as the workhorse for implementing the specified APIs.

Note: This calls `exec.bulk_then_execute(f, shape, pred, ts...)` if it exists; otherwise it executes `sync_execute(f, shape, pred.share(), ts...)` (if this executor is also an `OneWayExecutor`), or `async_execute(f, shape, pred.share(), ts...)` (if this executor is also a `TwoWayExecutor`) - as often as needed.

Param **exec**

[in] The executor object to use for scheduling of the function f .

Param **f**

[in] The function which will be scheduled using the given executor.

Param **shape**

[in] The shape objects which defines the iteration boundaries for the arguments to be passed to f .

Param **predecessor**

[in] The future object the execution of the given function depends on.

Param **ts**

[in] Additional arguments to use to invoke f .

Return

The return type of `executor_type::bulk_then_execute` if defined by `executor_type`. Otherwise, a vector holding the returned values of each invocation of f .

Public Functions

```
template<typename Executor, typename F, typename Shape, typename Future, typename
...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Future
&&predecessor, Ts&&... ts) const
```

```
template<typename Executor, typename F, typename Shape, typename Future,
typename... Ts> HPX_DEPRECATED_V (2, 0,
"tag_invoke overloads for bulk_then_execute are deprecated. " "Define a .
bulk_then_execute() member function instead.
") decltype(auto) operator() (Executor &&exec
```

```
template<executor_any Executor, typename F, typename Shape, typename Future, typename
...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Future
&&predecessor, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename Shape, typename Future, typename
...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Shape const &shape, Future
&&predecessor, Ts&&... ts) const
```

Public Members

F &&f

F Shape const & shape

F Shape const Future && predecessor

```
F Shape const Future Ts &&const ts {return hpx::functional::tag_invoke_ns::tag_invoke(
std::forward< Executor >( exec ),std::forward< F >( f ), shape,
std::forward< Future >( predecessor ),std::forward< Ts >( ts )...
}
```

struct **post_t**

#include <execution.hpp> Customization point for asynchronous fire & forget execution agent creation.

This asynchronously (fire & forget) creates a single function invocation *f()* using the associated executor.

Note: This is valid for two-way executors (calls *exec.post(f, ts...)*, if available, otherwise it calls *exec.async_execute(f, ts...)* while discarding the returned future), and for non-blocking two-way executors (calls *exec.post(f, ts...)* if it exists).

Param *exec*

[in] The executor object to use for scheduling of the function *f*.

Param *f*

[in] The function which will be scheduled using the given executor.

Param *ts*

[in] Additional arguments to use to invoke *f*.

Public Functions

```
template<typename Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

```
template<typename Executor, typename F, typename...
Ts> HPX_DEPRECATED_V (2, 0,
"tag_invoke overloads for post are deprecated. " "Define a .
post() member function instead.
") decltype(auto) operator() (Executor &&exec
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

Public Members

F &&*f*

```
F Ts &&const ts {return hpx::functional::tag_invoke_ns::tag_invoke(post_t{},
std::forward< Executor >( exec ), std::forward< F >( f ),
std::forward< Ts >( ts )...)
```

struct **sync_execute_t**

#include <execution.hpp> Customization point for synchronous execution agent creation.

This synchronously creates a single function invocation *f()* using the associated executor. The execution of the supplied function synchronizes with the caller

Note: It will call `exec.sync_execute(f, ts...)` if the executor exposes a corresponding member function. For two-way executors it will invoke `async_execute` and wait for the task's completion before returning.

Param *exec*

[in] The executor object to use for scheduling of the function *f*.

Param *f*

[in] The function which will be scheduled using the given executor.

Param *ts*

[in] Additional arguments to use to invoke *f*.

Return

f(*ts...*)'s result

Public Functions

```
template<typename Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

```
template<typename Executor, typename F, typename...
Ts> HPX_DEPRECATED_V (2, 0,
    "tag_invoke overloads for sync_execute are deprecated. " "Define a .
    sync_execute() member function instead.
    ") decltype(auto) operator() (Executor &&exec
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Ts&&... ts) const
```

Public Members

F &&f

```
F Ts &&const ts {return hpx::functional::tag_invoke_ns::tag_invoke(sync_execute_t{},
    std::forward< Executor >( exec ), std::forward< F >( f ),
    std::forward< Ts >( ts )...)
```

struct **sync_invoke_t**

#include <execution.hpp> Synchronously invoke the given set of nullary functions, each on its own execution agent

This creates a group of function invocations whose ordering is given by the `execution_category` associated with the executor.

All exceptions thrown by invocations of the functions are reported in a manner consistent with parallel algorithm execution through the returned future.

Note: This calls `exec.sync_invoke(fs...)` if it exists; otherwise it executes `sync_execute(fs)` for each `fs`.

Param **exec**

[in] The executor object to use for scheduling of the functions *fs*.

Param **fs**

[in] The functions which will be scheduled using the given executor.

Return

The return type of `executor_type::async_invoke` if defined by `executor_type`.

Public Functions

```
template<typename Executor, typename F, typename ...Fs>
inline decltype(auto) operator() (Executor &&exec, F &&f, Fs&&... fs) const
```

```
template<typename Executor, typename F, typename...
Fs> HPX_DEPRECATED_V (2, 0,
"tag_invoke overloads for sync_invoke are deprecated. " "Define a .
sync_invoke() member function instead.
") decltype(auto) operator() (Executor &&exec
```

```
template<executor_any Executor, typename F, typename ...Fs>
inline decltype(auto) operator() (Executor &&exec, F &&f, Fs&&... fs) const
```

Public Members

F &&f

```
F Fs &&const fs {return hpx::functional::tag_invoke_ns::tag_invoke(sync_invoke_t{}),
std::forward< Executor >( exec ), std::forward< F >( f ),
std::forward< Fs >( fs )...}
```

struct **then_execute_t**

#include <execution.hpp> Customization point for execution agent creation depending on a given future.

This creates a single function invocation *f()* using the associated executor after the given future object has become ready.

Note: This is valid for two-way executors (calls *exec.then_execute(f, predecessor, ts...)* if it exists) and for one way executors (calls *predecessor.then(bind(f, ts...))*).

Param **exec**

[in] The executor object to use for scheduling of the function *f*.

Param **f**

[in] The function which will be scheduled using the given executor.

Param **predecessor**

[in] The future object the execution of the given function depends on.

Param **ts**

[in] Additional arguments to use to invoke *f*.

Return

f(ts...)'s result through a future

Public Functions

```
template<typename Executor, typename F, typename Future, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Future &&predecessor, Ts&&...
                                   ts) const
```

```
template<typename Executor, typename F, typename Future, typename...
Ts> HPX_DEPRECATED_V (2, 0,
    "tag_invoke overloads for then_execute are deprecated. " "Define a .
    then_execute() member function instead.
    ") decltype(auto) operator() (Executor &&exec
```

```
template<executor_any Executor, typename F, typename Future, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, F &&f, Future &&predecessor, Ts&&...
                                   ts) const
```

Public Members

F &&**f**

F **Future** && predecessor

```
F Future Ts &&const ts {return hpx::functional::tag_invoke_ns::tag_invoke(then_execute,
std::forward< Executor >( exec ), std::forward< F >( f ),
std::forward< Future >( predecessor ), std::forward< Ts >( ts )..
.)
```

hpx/execution_base/traits/is_executor_parameters.hpp

Defined in header `hpx/execution_base/traits/is_executor_parameters.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename Executor>
```

```
struct extract_executor_parameters<Executor, std::void_t<typename Executor::executor_parameters_type>>
```

Public Types

```
using type = typename Executor::executor_parameters_type
```

```
template<typename Parameters>
```

```
struct extract_has_variable_chunk_size<Parameters, std::void_t<typename
Parameters::has_variable_chunk_size>> : public true_type
```

```
template<typename Parameters>
```

```

struct extract_has_variable_chunk_size<::std::reference_wrapper<Parameters>> : public
    hpx::execution::experimental::extract_has_variable_chunk_size<Parameters>

template<typename Parameters>

struct extract_invokes_testing_function<::std::reference_wrapper<Parameters>> : public
    hpx::execution::experimental::extract_invokes_testing_function<Parameters>

namespace hpx

```

Variables

```

template<typename Parameters> concept executor_parameters =hpx::traits::is_executor_parameters_v<Parameters>

```

```

namespace execution

```

```

    namespace experimental

```

Typedefs

```

template<typename Executor>

using extract_executor_parameters_t = typename
    extract_executor_parameters<Executor>::type

```

Variables

```

template<typename Parameters>

constexpr bool extract_has_variable_chunk_size_v =
    extract_has_variable_chunk_size<Parameters>::value

template<typename Parameters>

constexpr bool extract_invokes_testing_function_v =
    extract_invokes_testing_function<Parameters>::value

template<typename T>

constexpr bool is_executor_parameters_v = is_executor_parameters<T>::value

template<typename Executor, typename Enable = void>

struct extract_executor_parameters

```

Public Types

```
using type = sequential_executor_parameters
```

```
template<typename Executor> executor_parameters_type > >
```

Public Types

```
using type = typename Executor::executor_parameters_type
```

```
template<typename Parameters, typename Enable = void>
```

```
struct extract_has_variable_chunk_size : public false_type
```

```
template<typename Parameters> has_variable_chunk_size > > : public true_type
```

```
template<typename Parameters> reference_wrapper< Parameters > > : public hpx::execution::ex
```

```
template<typename Parameters, typename Enable = void>
```

```
struct extract_invokes_testing_function : public false_type
```

```
template<typename Parameters> reference_wrapper< Parameters > > : public hpx::execution::ex
```

```
template<typename T>
```

```
struct is_executor_parameters : public detail::is_executor_parameters<std::decay_t<T>>>
```

```
struct sequential_executor_parameters
```

```
namespace traits
```

Variables

```
template<typename T>
```

```
constexpr bool is_executor_parameters_v = is_executor_parameters<T>::value
```

```
template<typename Parameters, typename Enable>
```

```
struct is_executor_parameters
```

executors

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors/restricted_thread_pool_executor.hpp

Defined in header `hpx/executors/restricted_thread_pool_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

namespace **experimental**

Typedefs

using **restricted_thread_pool_executor** = *restricted_policy_executor*<*hpx::launch*>

template<typename **Policy**>

class **restricted_policy_executor**

Public Types

using **execution_category** = typename *embedded_executor*::*execution_category*

Associate the *parallel_execution_tag* executor tag type as a default with this executor.

using **executor_parameters_type** = typename
embedded_executor::*executor_parameters_type*

Public Functions

```
inline explicit restricted_policy_executor(std::size_t first_thread = 0, std::size_t
    num_threads = 1, threads::thread_priority
    priority = threads::thread_priority::default_,
    threads::thread_stacksize stacksize =
    threads::thread_stacksize::default_,
    threads::thread_schedule_hint schedulehint =
    { }, [[maybe_unused]] std::size_t
    hierarchical_threshold =
    hierarchical_threshold_default_)
```

Create a new parallel executor.

```
inline restricted_policy_executor(restricted_policy_executor const &other) noexcept(
    std::is_nothrow_copy_constructible_v<embedded_executor>)
```

```
inline restricted_policy_executor(restricted_policy_executor &&other) noexcept  
  
inline restricted_policy_executor &operator=(restricted_policy_executor const &rhs) noex-  
cept(std::is_nothrow_copy_assignable_v<embedded_executor>)  
  
inline restricted_policy_executor &operator=(restricted_policy_executor &&rhs) noexcept  
  
inline constexpr hpx::execution::experimental::executor_scheduler<restricted_policy_executor> query(hpx::execu  
const  
noex-  
cept(std::i
```

Private Types

```
using embedded_executor = hpx::execution::parallel_policy_executor<Policy>
```

Private Members

```
std::uint16_t first_thread_  
  
mutable std::atomic<std::size_t> os_thread_  
  
embedded_executor exec_
```

Private Static Attributes

```
static constexpr std::size_t hierarchical_threshold_default_ = 6
```

hpx/executors/fork_join_executor.hpp

Defined in header `hpx/executors/fork_join_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors/execution_policy_mappings.hpp

Defined in header `hpx/executors/execution_policy_mappings.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```


Variables

```

template<typename Tag>
constexpr bool is_execution_policy_mapping_v = is_execution_policy_mapping<Tag>::value

constexpr struct hpx::execution::experimental::to_non_par_t to_non_par

constexpr struct hpx::execution::experimental::to_par_t to_par

constexpr struct hpx::execution::experimental::to_non_task_t to_non_task

constexpr struct hpx::execution::experimental::to_task_t to_task

constexpr struct hpx::execution::experimental::to_non_unseq_t to_non_unseq

constexpr struct hpx::execution::experimental::to_unseq_t to_unseq

template<typename Tag>
struct is_execution_policy_mapping : public false_type

template<>
struct is_execution_policy_mapping<to_non_par_t> : public true_type

template<>
struct is_execution_policy_mapping<to_non_task_t> : public true_type

template<>
struct is_execution_policy_mapping<to_non_unseq_t> : public true_type

template<>
struct is_execution_policy_mapping<to_par_t> : public true_type

template<>
struct is_execution_policy_mapping<to_task_t> : public true_type

template<>
struct is_execution_policy_mapping<to_unseq_t> : public true_type

struct to_non_par_t

```

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
```

```
template<execution_policy ExPolicy>
```

```
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_non_par()
```

```
struct to_non_task_t
```

Subclassed by `hpx::execution::non_task_policy_tag`

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
```

```
template<execution_policy ExPolicy>
```

```
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_non_task()
```

```
struct to_non_unseq_t
```

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
```

```
template<execution_policy ExPolicy>
```

```
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_non_unseq()
```

```
struct to_par_t
```

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
```

```
template<execution_policy ExPolicy>
```

```
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_par()
```

```
struct to_task_t
```

Subclassed by `hpx::execution::task_policy_tag`

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
```

```
template<execution_policy ExPolicy>
```

```
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_task()
```

```
struct to_unseq_t
```

Public Functions

```
inline constexpr decltype(auto) operator() (Target const &target) const
```

```
template<execution_policy ExPolicy>
```

```
inline constexpr decltype(auto) operator() (ExPolicy &&policy) const noexcept
```

Public Members

```
template<typename Target> requires = { t.to_unseq()
```

hpx/executors/execution_policy_annotation.hpp

Defined in header `hpx/executors/execution_policy_annotation.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

hpx/executors/explicit_scheduler_executor.hpp

Defined in header `hpx/executors/explicit_scheduler_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

Functions

```
template<typename BaseScheduler>  
explicit explicit_scheduler_executor(BaseScheduler &&sched) -> ex-  
                                                                plicit_scheduler_executor<std::decay_t<BaseScheduler>>
```

```
template<typename BaseScheduler>  
struct explicit_scheduler_executor
```

hpx/executors/scheduler_executor.hpp

Defined in header `hpx/executors/scheduler_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

Functions

```
template<typename BaseScheduler>
explicit scheduler_executor(BaseScheduler &&sched) ->
    scheduler_executor<std::decay_t<BaseScheduler>>

template<typename BaseScheduler>

struct scheduler_executor
```

hpx/executors/sequenced_executor.hpp

Defined in header `hpx/executors/sequenced_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

struct **sequenced_executor**

#include <sequenced_executor.hpp> A *sequential_executor* creates groups of sequential execution agents which execute in the calling thread. The sequential order is given by the lexicographical order of indices in the index space.

Private Static Functions

```
template<typename F, typename ...Ts>
static inline decltype(auto) sync_execute_impl(F &&f, Ts&&... ts)

template<typename F, typename ...Ts>
static inline decltype(auto) async_execute_impl(hpx::threads::thread_description const &desc, F
    &&f, Ts&&... ts)

template<typename Archive>
static inline constexpr void serialize(Archive&, unsigned int const) noexcept
```

Friends

friend class `hpx::serialization::access`

namespace **experimental**


```
constexpr Executor to_non_hierarchical_spawning(Executor &&exec) noexcept

template<typename Policy, bool HierarchicalSpawning = false>

struct parallel_policy_executor : public hpx::execution::parallel_policy_executor_base<Policy>
```

Public Types

```
using base_type = parallel_policy_executor_base<Policy>
```

Public Functions

```
inline explicit constexpr parallel_policy_executor(threads::thread_priority priority,
                                                    threads::thread_stacksize stacksize =
                                                    threads::thread_stacksize::default_,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_stacksize stacksize,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_schedule_hint
                                                    schedulehint, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

inline explicit constexpr parallel_policy_executor(Policy l) noexcept

constexpr parallel_policy_executor() noexcept = default

inline explicit constexpr parallel_policy_executor(threads::thread_pool_base *pool, Policy l)
                                                    noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_pool_base *pool,
                                                    threads::thread_priority priority =
                                                    threads::thread_priority::default_,
                                                    threads::thread_stacksize stacksize =
                                                    threads::thread_stacksize::default_,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

parallel_policy_executor(parallel_policy_executor const&) = default

parallel_policy_executor(parallel_policy_executor&&) = default

parallel_policy_executor &operator=(parallel_policy_executor const&) = default
```

```
parallel_policy_executor &operator=(parallel_policy_executor&&) = default

inline auto query(experimental::with_processing_units_count_t, std::size_t num_cores) const

template<typename Parameters>
inline std::size_t query(experimental::processing_units_count_t, Parameters &&params,
                        hpx::chrono::steady_duration const &iter_dur = hpx::chrono::null_duration,
                        std::size_t num_tasks = 0) const

inline auto query(experimental::with_first_core_t, std::size_t first_core) const noexcept

inline constexpr std::size_t query(experimental::get_first_core_t) const noexcept

inline auto query(experimental::get_processing_units_mask_t) const

inline auto query(experimental::get_cores_mask_t) const

template<typename Tag, typename Property>
inline auto query(Tag tag, Property &&prop) const

template<typename Tag>
inline auto query(Tag tag) const

template<typename F, typename ...Ts>
inline decltype(auto) sync_execute(F &&f, Ts&&... ts) const

template<typename F, typename ...Ts>
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const

template<typename F, typename Future, typename ...Ts>
inline decltype(auto) then_execute(F &&f, Future &&predecessor, Ts&&... ts) const

template<typename F, typename ...Ts>
inline void post(F &&f, Ts&&... ts) const

template<typename F, typename S, typename Future, typename ...Ts>
inline decltype(auto) bulk_then_execute(F &&f, S const &shape, Future &&predecessor,
                                       Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_sync_execute(F &&f, S const &shape, Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_async_execute(F &&f, S const &shape, Ts&&... ts) const

inline decltype(auto) to_non_par() const

template<typename Policy, bool HierarchicalSpawning>
constexpr hpx::execution::experimental::executor_scheduler<parallel_policy_executor<Policy, HierarchicalSpawning>

template<typename Policy>

struct parallel_policy_executor<Policy, true> : public
hpx::execution::parallel_policy_executor_base<Policy>
```


Public Types

using **base_type** = *parallel_policy_executor_base*<Policy>

Public Functions

```

inline explicit constexpr parallel_policy_executor(threads::thread_priority priority,
                                                    threads::thread_stacksize stacksize =
                                                    threads::thread_stacksize::default_,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call(),
                                                    std::size_t const hierarchical_threshold =
                                                    hierarchical_threshold_default_) noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_stacksize stacksize,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_schedule_hint
                                                    schedulehint, Policy l = parallel::execution::detail::get_default_policy<Policy>::call())
                                                    noexcept

inline explicit constexpr parallel_policy_executor(Policy l) noexcept

constexpr parallel_policy_executor() noexcept = default

inline explicit constexpr parallel_policy_executor(threads::thread_pool_base *pool, Policy l,
                                                    std::size_t const hierarchical_threshold =
                                                    hierarchical_threshold_default_) noexcept

inline explicit constexpr parallel_policy_executor(threads::thread_pool_base *pool,
                                                    threads::thread_priority priority =
                                                    threads::thread_priority::default_,
                                                    threads::thread_stacksize stacksize =
                                                    threads::thread_stacksize::default_,
                                                    threads::thread_schedule_hint
                                                    schedulehint = { }, Policy l = parallel::execution::detail::get_default_policy<Policy>::call(),
                                                    std::size_t const hierarchical_threshold =
                                                    hierarchical_threshold_default_) noexcept

inline constexpr void set_hierarchical_threshold(std::size_t const threshold) noexcept

parallel_policy_executor(parallel_policy_executor const&) = default

parallel_policy_executor(parallel_policy_executor&&) = default

parallel_policy_executor &operator=(parallel_policy_executor const&) = default

parallel_policy_executor &operator=(parallel_policy_executor&&) = default

```

```
~parallel_policy_executor() = default

inline auto query(experimental::with_processing_units_count_t, std::size_t num_cores) const

template<typename Parameters>
inline std::size_t query(experimental::processing_units_count_t, Parameters &&params,
                        hpx::chrono::steady_duration const &iter_dur = hpx::chrono::null_duration,
                        std::size_t num_tasks = 0) const

inline auto query(experimental::with_first_core_t, std::size_t first_core) const noexcept

inline constexpr std::size_t query(experimental::get_first_core_t) const noexcept

inline auto query(experimental::get_processing_units_mask_t) const

inline auto query(experimental::get_cores_mask_t) const

template<typename Tag, typename Property>
inline auto query(Tag tag, Property &&prop) const

template<typename Tag>
inline auto query(Tag tag) const

template<typename F, typename ...Ts>
inline decltype(auto) sync_execute(F &&f, Ts&&... ts) const

template<typename F, typename ...Ts>
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const

template<typename F, typename Future, typename ...Ts>
inline decltype(auto) then_execute(F &&f, Future &&predecessor, Ts&&... ts) const

template<typename F, typename ...Ts>
inline void post(F &&f, Ts&&... ts) const

template<typename F, typename S, typename Future, typename ...Ts>
inline decltype(auto) bulk_then_execute(F &&f, S const &shape, Future &&predecessor,
                                       Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_sync_execute(F &&f, S const &shape, Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_async_execute(F &&f, S const &shape, Ts&&... ts) const

inline decltype(auto) to_non_par() const

template<typename Policy>

struct parallel_policy_executor_base

    #include <parallel_executor.hpp> A parallel_executor creates groups of parallel execution agents
    which execute in threads implicitly created by the executor. This executor prefers continuing with the
    creating thread first before executing newly created threads.

    This executor conforms to the concepts of a TwoWayExecutor, and a BulkTwoWayExecutor

    Subclassed      by      hpx::execution::parallel_policy_executor<      Policy,      Hierarchi-
    calSpawning      >,      hpx::execution::parallel_policy_executor<      Policy,      true      >,
    hpx::execution::parallel_policy_executor< Policy >
```

Public Types

using **execution_category** = *std::conditional_t<std::is_same_v<Policy, launch::sync_policy>, sequenced_execution_tag, parallel_execution_tag>*

Associate the parallel_execution_tag executor tag type as a default with this executor, except if the given launch policy is sync.

using **executor_parameters_type** = *experimental::default_parameters*

Associate the default_parameters executor parameters type as a default with this executor.

Public Functions

inline **parallel_policy_executor_base**(*parallel_policy_executor_base* const &rhs) noexcept

inline *parallel_policy_executor_base* &**operator=**(*parallel_policy_executor_base* const &rhs) noexcept

constexpr ~**parallel_policy_executor_base**() = default

template<typename **Parameters**>

inline *std::size_t* **processing_units_count**(*Parameters&&*, *hpx::chrono::steady_duration* const& = *hpx::chrono::null_duration*, *std::size_t* = 0) const

Public Static Functions

template<typename **Self**>

static inline *Self* **with_num_cores**(*Self* self, *std::size_t* num_cores)

template<typename **Self**>

static inline *Self* **with_first_core**(*Self* self, *std::size_t* first_core) noexcept

Protected Functions

inline explicit constexpr **parallel_policy_executor_base**(*threads::thread_priority* priority, *threads::thread_stacksize* stacksize = *threads::thread_stacksize::default_*, *threads::thread_schedule_hint* schedulehint = {}, *Policy* l = *parallel::execution::detail::get_default_policy<Policy>::call*) noexcept

Create a new parallel executor.

inline explicit constexpr **parallel_policy_executor_base**(*threads::thread_stacksize* stacksize, *threads::thread_schedule_hint* schedulehint = {}, *Policy* l = *parallel::execution::detail::get_default_policy<Policy>::call*) noexcept

```
inline explicit constexpr parallel_policy_executor_base(threads::thread_schedule_hint
                                                         schedulehint, Policy l = paral-
                                                         lel::execution::detail::get_default_policy<Policy>::call
                                                         noexcept

inline explicit constexpr parallel_policy_executor_base(Policy l) noexcept

inline constexpr parallel_policy_executor_base() noexcept

inline explicit constexpr parallel_policy_executor_base(threads::thread_pool_base *pool,
                                                         Policy l) noexcept

inline explicit constexpr parallel_policy_executor_base(threads::thread_pool_base *pool,
                                                         threads::thread_priority priority =
                                                         threads::thread_priority::default_,
                                                         threads::thread_stacksize stacksize =
                                                         threads::thread_stacksize::default_,
                                                         threads::thread_schedule_hint
                                                         schedulehint = {}, Policy l = paral-
                                                         lel::execution::detail::get_default_policy<Policy>::call
```

```
namespace experimental

    template<typename Executor>

    struct executor_scheduler
```

```
namespace parallel
```

```
    namespace execution
```

hpx::execution::seq

Defined in header [hpx/execution.hpp](#)⁸⁶⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::execution::par`
- `hpx::execution::par_unseq`
- `hpx::execution::task`
- `hpx::execution::sequenced_policy`
- `hpx::execution::parallel_policy`
- `hpx::execution::parallel_unsequenced_policy`
- `hpx::execution::sequenced_task_policy`
- `hpx::execution::parallel_task_policy`

⁸⁶⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

```
constexpr sequenced_policy hpx::execution::seq = {}
```

Default sequential execution policy object.

hpx::execution::par

Defined in header [hpx/execution.hpp](#)⁸⁶⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::execution::seq`
- `hpx::execution::par_unseq`
- `hpx::execution::task`
- `hpx::execution::sequenced_policy`
- `hpx::execution::parallel_policy`
- `hpx::execution::parallel_unsequenced_policy`
- `hpx::execution::sequenced_task_policy`
- `hpx::execution::parallel_task_policy`

```
constexpr parallel_policy hpx::execution::par = {}
```

Default parallel execution policy object.

hpx::execution::par_unseq

Defined in header [hpx/execution.hpp](#)⁸⁶⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::execution::seq`
- `hpx::execution::par`
- `hpx::execution::task`
- `hpx::execution::sequenced_policy`
- `hpx::execution::parallel_policy`
- `hpx::execution::parallel_unsequenced_policy`
- `hpx::execution::sequenced_task_policy`
- `hpx::execution::parallel_task_policy`

```
constexpr parallel_unsequenced_policy hpx::execution::par_unseq = {}
```

Default vector execution policy object.

⁸⁶⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

⁸⁶⁸ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

hpx::execution::task

Defined in header [hpx/execution.hpp](#)⁸⁶⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::execution::seq`
- `hpx::execution::par`
- `hpx::execution::par_unseq`
- `hpx::execution::sequenced_policy`
- `hpx::execution::parallel_policy`
- `hpx::execution::parallel_unsequenced_policy`
- `hpx::execution::sequenced_task_policy`
- `hpx::execution::parallel_task_policy`

```
constexpr task_policy_tag hpx::execution::task = {}
```

hpx::execution::sequenced_policy

Defined in header [hpx/execution.hpp](#)⁸⁷⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::execution::seq`
- `hpx::execution::par`
- `hpx::execution::par_unseq`
- `hpx::execution::task`
- `hpx::execution::parallel_policy`
- `hpx::execution::parallel_unsequenced_policy`
- `hpx::execution::sequenced_task_policy`
- `hpx::execution::parallel_task_policy`

```
using hpx::execution::sequenced_policy = detail::sequenced_policy_shim<sequenced_executor,  
hpx::traits::executor_parameters_type_t<sequenced_executor>>
```

The class `sequenced_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and require that a parallel algorithm's execution may not be parallelized.

⁸⁶⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.

⁸⁷⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.
hpp

hpx::execution::parallel_policy

Defined in header [hpx/execution.hpp](#)⁸⁷¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::execution::seq`
- `hpx::execution::par`
- `hpx::execution::par_unseq`
- `hpx::execution::task`
- `hpx::execution::sequenced_policy`
- `hpx::execution::parallel_unsequenced_policy`
- `hpx::execution::sequenced_task_policy`
- `hpx::execution::parallel_task_policy`

using `hpx::execution::parallel_policy = detail::parallel_policy_shim<parallel_executor, hpx::traits::executor_parameters_type_t<parallel_executor>>`

The class `parallel_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be parallelized.

hpx::execution::parallel_unsequenced_policy

Defined in header [hpx/execution.hpp](#)⁸⁷².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::execution::seq`
- `hpx::execution::par`
- `hpx::execution::par_unseq`
- `hpx::execution::task`
- `hpx::execution::sequenced_policy`
- `hpx::execution::parallel_policy`
- `hpx::execution::sequenced_task_policy`
- `hpx::execution::parallel_task_policy`

using `hpx::execution::parallel_unsequenced_policy = detail::parallel_unsequenced_policy_shim<parallel_executor, hpx::traits::executor_parameters_type_t<parallel_executor>>`

The class `parallel_unsequenced_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be parallelized and vectorized.

⁸⁷¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.

hpp

⁸⁷² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.

hpp

hpx::execution::sequenced_task_policy

Defined in header [hpx/execution.hpp](#)⁸⁷³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::execution::seq`
- `hpx::execution::par`
- `hpx::execution::par_unseq`
- `hpx::execution::task`
- `hpx::execution::sequenced_policy`
- `hpx::execution::parallel_policy`
- `hpx::execution::parallel_unsequenced_policy`
- `hpx::execution::parallel_task_policy`

using `hpx::execution::sequenced_task_policy = detail::sequenced_task_policy_shim<sequenced_executor, hpx::traits::executor_parameters_type_t<sequenced_executor>>`

Extension: The class `sequenced_task_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may not be parallelized (has to run sequentially).

The algorithm returns a future representing the result of the corresponding algorithm when invoked with the `sequenced_policy`.

hpx::execution::parallel_task_policy

Defined in header [hpx/execution.hpp](#)⁸⁷⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::execution::seq`
- `hpx::execution::par`
- `hpx::execution::par_unseq`
- `hpx::execution::task`
- `hpx::execution::sequenced_policy`
- `hpx::execution::parallel_policy`
- `hpx::execution::parallel_unsequenced_policy`
- `hpx::execution::sequenced_task_policy`

⁸⁷³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp

⁸⁷⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/execution.hpp


```
using hpx::execution::parallel_task_policy = detail::parallel_task_policy_shim<parallel_executor,
hpx::traits::executor_parameters_type_t<parallel_executor>>
```

Extension: The class `parallel_task_policy` is an execution policy type used as a unique type to disambiguate parallel algorithm overloading and indicate that a parallel algorithm's execution may be parallelized.

The algorithm returns a future representing the result of the corresponding algorithm when invoked with the `parallel_policy`.

hpx/executors/service_executors.hpp

Defined in header `hpx/executors/service_executors.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace parallel
```

```
namespace execution
```

hpx/executors/thread_pool_scheduler.hpp

Defined in header `hpx/executors/thread_pool_scheduler.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace execution
```

```
namespace experimental
```

Typedefs

```
using thread_pool_scheduler = thread_pool_policy_scheduler<hpx::launch>
```

Variables

```
template<typename Sender> concept bulk_chunked_or_unchunked_sender = sender_invokes_algorithm_v<Sender,
hpx::execution::experimental::bulk_t> || sender_invokes_algorithm_v<Sender,
hpx::execution::experimental::bulk_chunked_t> || sender_invokes_algorithm_v<Sender,
hpx::execution::experimental::bulk_unchunked_t>
```

```
template<typename Policy>
```

```
constexpr bool is_sequenced_policy_v = false

template<>

constexpr bool is_sequenced_policy_v<sequenced_policy> = true

template<>

constexpr bool is_sequenced_policy_v<unsequenced_policy> = true

template<typename Policy>

constexpr bool is_unsequenced_bulk_policy_v = false

template<>

constexpr bool is_unsequenced_bulk_policy_v<unsequenced_policy> = true

template<>

constexpr bool is_unsequenced_bulk_policy_v<parallel_unsequenced_policy> = true

template<typename Policy>

struct thread_pool_domain : public sync_wait_domain
```

Public Functions

```
template<bulk_chunked_or_unchunked_sender Sender, typename Env>
inline constexpr thread_pool_policy_scheduler<Policy> auto transform_sender(hpx::execution::experimental::
                                                                    Sender
                                                                    &&sndr,
                                                                    Env const
                                                                    &env) const
                                                                    noexcept

    template<typename Sender,
    typename Env> inline requires constexpr sender_invokes_algorithm_v< Sender,
    hpx::execution::experimental::continues_on_t > auto transform_sender (hpx::execution::ex
    Sender &&sndr, Env const &) const noexcept

template<typename Policy>

struct thread_pool_policy_scheduler
```

Public Types

```
using policy_type = Policy
```

```
using execution_category = std::conditional_t<std::is_same_v<Policy,  
launch::sync_policy>, sequenced_execution_tag, parallel_execution_tag>
```

Public Functions

```
inline explicit constexpr thread_pool_policy_scheduler(Policy l = experimen-  
tal::detail::get_default_scheduler_policy<Policy>::c
```

```
inline explicit thread_pool_policy_scheduler(hpx::threads::thread_pool_base *pool,  
Policy l = experimen-  
tal::detail::get_default_scheduler_policy<Policy>::call()  
noexcept
```

hpx/executors/executor_scheduler.hpp

Defined in header `hpx/executors/executor_scheduler.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace execution
```

```
namespace experimental
```

```
template<typename Executor>
```

```
struct executor_scheduler
```

hpx/executors/parallel_executor_aggregated.hpp

Defined in header `hpx/executors/parallel_executor_aggregated.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace parallel
```

```
namespace execution
```

Typedefs

```
typedef hpx::execution::parallel_policy_executor<Policy> instead
```

hpx/executors/annotating_executor.hpp

Defined in header `hpx/executors/annotating_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

```
            template<executor_any BaseExecutor>
```

```
            struct annotating_executor
```

```
                #include <annotating_executor.hpp> An annotating_executor wraps any other executor and adds  
                the capability to add annotations to the launched threads.
```

Public Functions

```
            template<executor_any Executor>
```

```
            inline explicit constexpr annotating_executor(Executor &&exec, char const *annotation =  
                                                            nullptr)
```

```
            template<executor_any Executor>
```

```
            inline explicit annotating_executor(Executor &&exec, std::string annotation)
```

hpx/executors/exception_list.hpp

Defined in header `hpx/executors/exception_list.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace parallel
```

hpx/executors/execution_policy_scheduling_property.hpp

Defined in header `hpx/executors/execution_policy_scheduling_property.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

hpx/executors/std_execution_policy.hpp

Defined in header `hpx/executors/std_execution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors/thread_pool_continues_on_sender.hpp

Defined in header `hpx/executors/thread_pool_continues_on_sender.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Domain-optimized `continues_on` sender for HPX thread pool schedulers.

When `stdexec::continues_on` is applied with an HPX `thread_pool_scheduler`, the generic `stdexec` implementation creates two operation states: one for the source sender and one for the scheduler hop (`schedule_from`). This double-state overhead adds ~1 us per task in microbenchmarks.

This header provides a custom sender that replaces the generic path by:

1. Connecting the source sender to a lightweight receiver that captures the downstream receiver and the scheduler.
2. On `set_value`: if we are already on the same HPX thread pool, forwarding inline; otherwise, posting a single HPX task to forward the values.

This eliminates the intermediate `__storage_for_t`, the second operation state, and the `run_loop` overhead.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

hpx/executors/current_executor.hpp

Defined in header `hpx/executors/current_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **execution**

namespace **this_thread**

Functions

`hpx::execution::parallel_executor get_executor(error_code &ec = throws)`

Returns a reference to the executor that was used to create the current thread.

Throws

If `&ec != &throws`, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw a *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

namespace **threads**

Functions

`hpx::execution::parallel_executor get_executor(thread_id_type const &id, error_code &ec = throws)`

Returns a reference to the executor that was used to create the given thread.

Throws

If `&ec != &throws`, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw a *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

hpx/executors/execution_policy_parameters.hpp

Defined in header `hpx/executors/execution_policy_parameters.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors/datapar/execution_policy_mappings.hpp

Defined in header `hpx/executors/datapar/execution_policy_mappings.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/executors/datapar/execution_policy.hpp

Defined in header `hpx/executors/datapar/execution_policy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

filesystem

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/filesystem/api.hpp

Defined in header `hpx/filesystem/api.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

This file provides a compatibility layer using Boost.Filesystem for the C++17 filesystem library. It is *not* intended to be a complete compatibility layer. It only contains functions required by the HPX codebase. It also provides some functions only available in Boost.Filesystem when using C++17 filesystem.

namespace **hpx**

namespace **filesystem**

Functions

inline path **initial_path**()

inline *std::string* **to_string**(path const &p)

inline *std::string* **basename**(path const &p)

inline path **canonical**(path const &p, path const &base)

inline path **canonical**(path const &p, path const &base, *std::error_code* &ec)

namespace **filesystem**

functional

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::mem_fn

Defined in header [hpx/functional.hpp](#)⁸⁷⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Warning: doxygenfunction: Unable to resolve function “hpx::mem_fn” with arguments “(M C::*)”. Candidate function could not be parsed. Parsing error is Invalid C++ declaration: Expected identifier in nested name. [error at 4] (C::*)(Ps...)> mem_fn(R (C::* pm)(Ps...)) noexcept ——^

Warning: doxygenfunction: Unable to resolve function “hpx::mem_fn” with arguments “(R (C::*)(Ps...))”. Candidate function could not be parsed. Parsing error is Invalid C++ declaration: Expected identifier in nested name. [error at 4] (C::*)(Ps...)> mem_fn(R (C::* pm)(Ps...)) noexcept ——^

Warning: doxygenfunction: Unable to resolve function “hpx::mem_fn” with arguments “(R (C::*)(Ps...) const)”. Candidate function could not be parsed. Parsing error is Invalid C++ declaration: Expected identifier in nested name. [error at 4] (C::*)(Ps...)> mem_fn(R (C::* pm)(Ps...)) noexcept ——^

hpx::reference_wrapper

Defined in header [hpx/functional.hpp](#)⁸⁷⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- [hpx::ref](#)
- [hpx::cref](#)

```
template<typename T>  
hpx::reference_wrapper(T&) -> reference_wrapper<T>
```

⁸⁷⁵ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

⁸⁷⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

hpx::ref

Defined in header [hpx/functional.hpp](#)⁸⁷⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::reference_wrapper](#)
- [hpx::cref](#)

```
template<typename T>
constexpr reference_wrapper<T> hpx::ref(T &val) noexcept
```

```
template<typename T>
void hpx::ref(T const&&) = delete
```

```
template<typename T>
constexpr reference_wrapper<T> hpx::ref(reference_wrapper<T> val) noexcept
```

```
template<typename T>
reference_wrapper<T> hpx::ref(T &&val) noexcept
```

hpx::cref

Defined in header [hpx/functional.hpp](#)⁸⁷⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::reference_wrapper](#)
- [hpx::ref](#)

```
template<typename T>
constexpr reference_wrapper<T const> hpx::cref(T const &val) noexcept
```

```
template<typename T>
void hpx::cref(T const&&) = delete
```

```
template<typename T>
constexpr reference_wrapper<T const> hpx::cref(reference_wrapper<T> val) noexcept
```

⁸⁷⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

⁸⁷⁸ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

hpx::function_ref

Defined in header `hpx/functionality.hpp`⁸⁷⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

template<typename **Sig**>

class **function_ref**

function_ref class is a vocabulary type with reference semantics for passing entities to call.

An example use case that benefits from higher-order functions is `retry(n, f)` which attempts to call `f` up to `n` times synchronously until success. This example might model the real-world scenario of repeatedly querying a flaky web service.

```
using payload = std::optional< /* ... */ >;
// Repeatedly invokes `action` up to `times` repetitions.
// Immediately returns if `action` returns a valid `payload`.
// Returns `std::nullopt` otherwise.
payload retry(size_t times, /* ????? */ action);
```

The passed-in action should be a callable entity that takes no arguments and returns a payload. This can be done with function pointers, `hpx::function` or a template but it is much simpler with *function_ref* as seen below:

```
payload retry(size_t times, function_ref<payload()> action);
```

hpx::bind_back

Defined in header `hpx/functionality.hpp`⁸⁸⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

Warning: doxygenfunction: Unable to resolve function “hpx::bind_back” with arguments (F&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename F, typename ...Ts> constexpr hpx::detail::bound_back<std::decay_t
  ↳<F>, util::make_index_pack_t<sizeof...(Ts)>, util::decay_unwrap_t<Ts>...> bind_
  ↳back(F &&f, Ts&&... vs)
- template<typename F> constexpr std::decay_t<F> bind_back(F &&f)
```

template<typename **F**>

constexpr `std::decay_t<F>` **bind_back**(`F &&f`)

⁸⁷⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functionality.hpp

⁸⁸⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functionality.hpp

hpx::invoke_fused

Defined in header [hpx/functional.hpp](#)⁸⁸¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::invoke_fused_r](#)

```
template<typename F, typename Tuple>
constexpr detail::invoke_fused_result_t<F, Tuple> hpx::invoke_fused(F &&f, Tuple &&t) noexcept(
    noexcept(detail::invoke_fused_impl(detail::fused_index_pack_t<Tuple>{ },
    HPX_FORWARD(F, f),
    HPX_FORWARD(Tuple, t))))
```

Invokes the given callable object *f* with the content of the sequenced type *t* (tuples, pairs).

Note: This function is similar to `std::apply` (C++17). The difference between `hpx::invoke` and `hpx::invoke_fused` is that the later unpacks the tuples while the former cannot. Turning a tuple into a parameter pack is not a trivial operation which makes `hpx::invoke_fused` rather useful.

Parameters

- **f** – Must be a callable object. If *f* is a member function pointer, the first argument in the sequenced type will be treated as the callee (this object).
- **t** – A type whose contents are accessible through a call to `hpx::get`.

Throws

`std::exception` – like objects thrown by call to object *f* with the arguments contained in the sequenceable type *t*.

Returns

The result of the callable object when it's called with the content of the given sequenced type.

hpx::invoke_fused_r

Defined in header [hpx/functional.hpp](#)⁸⁸².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::invoke_fused](#)

```
template<typename R, typename F, typename Tuple>
constexpr R hpx::invoke_fused_r(F &&f, Tuple &&t) noexcept(
    noexcept(detail::invoke_fused_impl(detail::fused_index_pack_t<Tuple>{ },
    HPX_FORWARD(F, f), HPX_FORWARD(Tuple, t))))
```

Invokes the given callable object *f* with the content of the sequenced type *t* (tuples, pairs).

⁸⁸¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

⁸⁸² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

Note: This function is similar to `std::apply` (C++17). The difference between `hpx::invoke` and `hpx::invoke_fused` is that the later unpacks the tuples while the former cannot. Turning a tuple into a parameter pack is not a trivial operation which makes `hpx::invoke_fused` rather useful.

Note: The difference between `hpx::invoke_fused` and `hpx::invoke_fused_r` is that the later allows to specify the return type as well.

Parameters

- **f** – Must be a callable object. If `f` is a member function pointer, the first argument in the sequenced type will be treated as the callee (this object).
- **t** – A type whose contents are accessible through a call to `hpx::get`.

Throws

`std::exception` – like objects thrown by call to object `f` with the arguments contained in the sequenceable type `t`.

Template Parameters

R – The result type of the function when it's called with the content of the given sequenced type.

Returns

The result of the callable object when it's called with the content of the given sequenced type.

`hpx::bind_front`

Defined in header `hpx/functional.hpp`⁸⁸³.

See *Public API* for a list of names and headers that are part of the public HPX API.

Warning: doxygenfunction: Unable to resolve function “`hpx::bind_front`” with arguments (`F&&`, `Ts&&...`) in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`. Potential matches:

```
- template<typename F, typename ...Ts> constexpr detail::bound_front<std::decay_t<F>,
  ↳ util::make_index_pack_t<sizeof...(Ts)>, util::decay_unwrap_t<Ts>...> bind_front(F &&
  ↳ f, Ts&&... vs)
- template<typename F> constexpr std::decay_t<F> bind_front(F &&f)
```

```
template<typename F>
constexpr std::decay_t<F> hpx::bind_front(F &&f)
```

⁸⁸³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

hpx::function

Defined in header [hpx/functional.hpp](#)⁸⁸⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename Sig, bool Serializable = false>
```

class **function**

Class template *hpx::function* is a general-purpose polymorphic function wrapper. Instances of *hpx::function* can store, copy, and invoke any CopyConstructible Callable target⁸⁸⁴; functions, lambda expressions, bind expressions, or other function objects, as well as pointers to member functions and pointers to data members. The stored callable object is called the target of *hpx::function*. If an *hpx::function* contains no target, it is called empty. Invoking the target of an empty *hpx::function* results in *hpx::error::bad_function_call* exception being thrown. *hpx::function* satisfies the requirements of CopyConstructible and CopyAssignable.

hpx::move_only_function

Defined in header [hpx/functional.hpp](#)⁸⁸⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename Sig, bool Serializable = false>
```

class **move_only_function**

Class template *hpx::move_only_function* is a general-purpose polymorphic function wrapper. *hpx::move_only_function* objects can store and invoke any constructible (not required to be move constructible) Callable target⁸⁸⁵; functions, lambda expressions, bind expressions, or other function objects, as well as pointers to member functions and pointers to member objects.

The stored callable object is called the target of *hpx::move_only_function*. If an *hpx::move_only_function* contains no target, it is called empty. Unlike *hpx::function*, invoking an empty *hpx::move_only_function* results in undefined behavior.

hpx::move_only_functions supports every possible combination of cv-qualifiers, ref-qualifiers, and noexcept-specifiers not including volatile provided in its template parameter. These qualifiers and specifier (if any) are added to its operator(). *hpx::move_only_function* satisfies the requirements of MoveConstructible and MoveAssignable, but does not satisfy CopyConstructible or CopyAssignable.

hpx::bind

Defined in header [hpx/functional.hpp](#)⁸⁸⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::placeholders::_1*
- *hpx::placeholders::_2*
- ...

⁸⁸⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

⁸⁸⁵ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

⁸⁸⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

- `hpx::placeholders::_9`

Warning: doxygenfunction: Unable to resolve function “hpx::bind” with arguments (F&&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename ...Ts> detail::bound_action<std::decay_t<Action>,
↳ util::make_index_pack_t<sizeof...(Ts)>, hpx::util::decay_unwrap_t<Ts>...> bind(Ts&&
↳... vs)
- template<typename Component, typename Signature, typename Derived, typename ...Ts>↳
↳detail::bound_action<Derived, util::make_index_pack_t<sizeof...(Ts)>, std::decay_t
↳<Ts>...> bind(hpx::actions::basic_action<Component, Signature, Derived> action, Ts&&
↳... vs)
- template<typename F, typename ...Ts> constexpr detail::bound<std::decay_t<F>,↳
↳util::make_index_pack_t<sizeof...(Ts)>, util::decay_unwrap_t<Ts>...> bind(F &&f, Ts&
↳&... vs)
```

Warning: doxygenfunction: Unable to resolve function “hpx::bind” with arguments (Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename ...Ts> detail::bound_action<std::decay_t<Action>,
↳ util::make_index_pack_t<sizeof...(Ts)>, hpx::util::decay_unwrap_t<Ts>...> bind(Ts&&
↳... vs)
- template<typename Component, typename Signature, typename Derived, typename ...Ts>↳
↳detail::bound_action<Derived, util::make_index_pack_t<sizeof...(Ts)>, std::decay_t
↳<Ts>...> bind(hpx::actions::basic_action<Component, Signature, Derived> action, Ts&&
↳... vs)
- template<typename F, typename ...Ts> constexpr detail::bound<std::decay_t<F>,↳
↳util::make_index_pack_t<sizeof...(Ts)>, util::decay_unwrap_t<Ts>...> bind(F &&f, Ts&
↳&... vs)
```

Warning: doxygenfunction: Unable to resolve function “hpx::bind” with arguments (hpx::actions::basic_action<Component, Signature, Derived>, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename ...Ts> detail::bound_action<std::decay_t<Action>,
↳ util::make_index_pack_t<sizeof...(Ts)>, hpx::util::decay_unwrap_t<Ts>...> bind(Ts&&
↳... vs)
- template<typename Component, typename Signature, typename Derived, typename ...Ts>↳
↳detail::bound_action<Derived, util::make_index_pack_t<sizeof...(Ts)>, std::decay_t
↳<Ts>...> bind(hpx::actions::basic_action<Component, Signature, Derived> action, Ts&&
↳... vs)
- template<typename F, typename ...Ts> constexpr detail::bound<std::decay_t<F>,↳
↳util::make_index_pack_t<sizeof...(Ts)>, util::decay_unwrap_t<Ts>...> bind(F &&f, Ts&
↳&... vs)
```

hpx::placeholders::_1

Defined in header [hpx/functional.hpp](#)⁸⁸⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::bind](#)
- [hpx::placeholders::_2](#)
- ...
- [hpx::placeholders::_9](#)

```
constexpr detail::placeholder<1> hpx::placeholders::_1 = {}
```

hpx::placeholders::_2

Defined in header [hpx/functional.hpp](#)⁸⁸⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::bind](#)
- [hpx::placeholders::_1](#)
- ...
- [hpx::placeholders::_9](#)

```
constexpr detail::placeholder<2> hpx::placeholders::_2 = {}
```

Defined in header [hpx/functional.hpp](#)⁸⁸⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::bind](#)
- [hpx::placeholders::_1](#)
- [hpx::placeholders::_2](#)
- [hpx::placeholders::_9](#)

⁸⁸⁷ [http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp)

⁸⁸⁸ [http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp)

⁸⁸⁹ [http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp)

Warning: doxygenfunction: Cannot find function “...” in doxygen xml output for project “hpx” from directory: ../hpx_autodoc

hpx::placeholders::_9

Defined in header [hpx/functional.hpp](#)⁸⁹⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::bind*
- *hpx::placeholders::_1*
- *hpx::placeholders::_2*
- ...

constexpr detail::placeholder<9> *hpx::placeholders::_9* = {}

hpx::experimental::scope_exit

Defined in header `hpx/experimental/scope.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **F**>

auto *hpx::experimental::scope_exit*(*F* &&*f*)

The class template `scope_exit` is a general-purpose scope guard intended to call its exit function when a scope is exited.

Template Parameters

F – type of stored exit function

Parameters

f – stored exit function

hpx::experimental::scope_fail

Defined in header `hpx/experimental/scope.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **F**>

auto *hpx::experimental::scope_fail*(*F* &&*f*)

The class template `scope_fail` is a general-purpose scope guard intended to call its exit function when a scope is exited via an exception.

Template Parameters

F – type of stored exit function

Parameters

f – stored exit function

⁸⁹⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

hpx::experimental::scope_success

Defined in header `hpx/experimental/scope.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename F>
auto hpx::experimental::scope_success(F &&f)
```

The class template `scope_success` is a general-purpose scope guard intended to call its exit function when a scope is normally exited.

Template Parameters

F – type of stored exit function

Parameters

f – stored exit function

hpx::is_bind_expression

Defined in header `hpx/functional.hpp`⁸⁹¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename T>
struct is_bind_expression : public std::is_bind_expression<T>
```

If `T` is the type produced by a call to `hpx::bind`, this template is derived from `std::true_type`. For any other type, this template is derived from `std::false_type`.

This template may be specialized for a user-defined type `T` to implement *UnaryTypeTrait* with base characteristic of `std::true_type` to indicate that `T` should be treated by `hpx::bind` as if it were the type of a bind sub-expression: when a bind-generated function object is invoked, a bound argument of this type will be invoked as a function object and will be given all the unbound arguments passed to the bind-generated object.

Subclassed by `hpx::is_bind_expression< T const >`

hpx::is_placeholder

Defined in header `hpx/functional.hpp`⁸⁹².

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename T>
```

```
struct is_placeholder
```

If `T` is a standard, Boost, or HPX placeholder (`_1`, `_2`, `_3`, ...) then this template is derived from `std::integral_constant<int,1>`, `std::integral_constant<int,2>`, `std::integral_constant<int,3>`, respectively. Otherwise, it is derived from `std::integral_constant<int,0>`.

The template may be specialized for any user-defined `T` type: the specialization must satisfy *UnaryTypeTrait* with base characteristic of `std::integral_constant<int,N>` with `N>0` to indicate that `T` should be treated as `N`'th placeholder type. `hpx::bind` uses `hpx::is_placeholder` to detect placeholders for unbound arguments.

⁸⁹¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

⁸⁹² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

futures

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::promise

Defined in header `hpx/future.hpp`⁸⁹³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **R**>

class **promise**

The class template `hpx::promise` provides a facility to store a value or an exception that is later acquired asynchronously via a `hpx::future` object created by the `hpx::promise` object. Note that the `hpx::promise` object is meant to be used only once. Each promise is associated with a shared state, which contains some state information and a result which may be not yet evaluated, evaluated to a value (possibly void) or evaluated to an exception. A promise may do three things with the shared state:

- **make ready**: the promise stores the result or the exception in the shared state. Marks the state ready and unblocks any thread waiting on a future associated with the shared state.
- **release**: the promise gives up its reference to the shared state. If this was the last such reference, the shared state is destroyed. Unless this was a shared state created by `hpx::async` which is not yet ready, this operation does not block.
- **abandon**: the promise stores the exception of type `hpx::future_error` with error code `hpx::error::broken_promise`, makes the shared state ready, and then releases it. The promise is the “push” end of the promise-future communication channel: the operation that stores a value in the shared state synchronizes-with (as defined in `hpx::memory_order`) the successful return from any function that is waiting on the shared state (such as `hpx::future::get`). Concurrent access to the same shared state may conflict otherwise: for example multiple callers of `hpx::shared_future::get` must either all be read-only or provide external synchronization.

hpx::future

Defined in header `hpx/future.hpp`⁸⁹⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::shared_future`
- `hpx::make_future`
- `hpx::make_shared_future`
- `hpx::make_ready_future`
- `hpx::make_ready_future_alloc`
- `hpx::make_ready_future_at`
- `hpx::make_ready_future_after`
- `hpx::make_exceptional_future`

⁸⁹³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁸⁹⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

template<typename R>

class **future** : public *hpx::lcos::detail::future_base<future<R>, R>*

The class template *hpx::future* provides a mechanism to access the result of asynchronous operations:

- An asynchronous operation (created via *hpx::async*, *hpx::packaged_task*, or *hpx::promise*) can provide a *hpx::future* object to the creator of that asynchronous operation.
- The creator of the asynchronous operation can then use a variety of methods to query, wait for, or extract a value from the *hpx::future*. These methods may block if the asynchronous operation has not yet provided a value.
- When the asynchronous operation is ready to send a result to the creator, it can do so by modifying shared state (e.g. *hpx::promise::set_value*) that is linked to the creator's *hpx::future*. Note that *hpx::future* references shared state that is not shared with any other asynchronous return objects (as opposed to *hpx::shared_future*).

hpx::shared_future

Defined in header [hpx/future.hpp](#)⁸⁹⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::future*
- *hpx::make_future*
- *hpx::make_shared_future*
- *hpx::make_ready_future*
- *hpx::make_ready_future_alloc*
- *hpx::make_ready_future_at*
- *hpx::make_ready_future_after*
- *hpx::make_exceptional_future*

template<typename R>

class **shared_future** : public *hpx::lcos::detail::future_base<shared_future<R>, R>*

The class template *hpx::shared_future* provides a mechanism to access the result of asynchronous operations, similar to *hpx::future*, except that multiple threads are allowed to wait for the same shared state. Unlike *hpx::future*, which is only moveable (so only one instance can refer to any particular asynchronous result), *hpx::shared_future* is copyable and multiple shared future objects may refer to the same shared state. Access to the same shared state from multiple threads is safe if each thread does it through its own copy of a *shared_future* object.

⁸⁹⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

hpx::make_future

Defined in header [hpx/future.hpp](#)⁸⁹⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::future`
- `hpx::shared_future`
- `hpx::make_shared_future`
- `hpx::make_ready_future`
- `hpx::make_ready_future_alloc`
- `hpx::make_ready_future_at`
- `hpx::make_ready_future_after`
- `hpx::make_exceptional_future`

template<typename **R**, typename **U**>

`hpx::future<R> hpx::make_future(hpx::future<U> &&f)`

Converts any future of type **U** to any other future of type **R** based on an existing conversion path from **U** to **R**.

template<typename **R**, typename **U**, typename **Conv**>

`hpx::future<R> hpx::make_future(hpx::future<U> &&f, Conv &&conv)`

Converts any future of type **U** to any other future of type **R** based on a given conversion function: **R** conv(**U**).

template<typename **R**, typename **U**>

`hpx::future<R> hpx::make_future(hpx::shared_future<U> f)`

Converts any *shared_future* of type **U** to any other future of type **R** based on an existing conversion path from **U** to **R**.

template<typename **R**, typename **U**, typename **Conv**>

`hpx::future<R> hpx::make_future(hpx::shared_future<U> f, Conv &&conv)`

Converts any future of type **U** to any other future of type **R** based on an existing conversion path from **U** to **R**.

hpx::make_shared_future

Defined in header [hpx/future.hpp](#)⁸⁹⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::future`
- `hpx::shared_future`
- `hpx::make_future`
- `hpx::make_ready_future`
- `hpx::make_ready_future_alloc`
- `hpx::make_ready_future_at`

⁸⁹⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁸⁹⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

- `hpx::make_ready_future_after`
- `hpx::make_exceptional_future`

template<typename R>

`hpx::shared_future<R> hpx::make_shared_future(hpx::future<R> &&f) noexcept`

Converts any future or `shared_future` of type T to a corresponding `shared_future` of type T.

template<typename R>

`hpx::shared_future<R> &hpx::make_shared_future(hpx::shared_future<R> &f) noexcept`

Converts any future or `shared_future` of type T to a corresponding `shared_future` of type T.

template<typename R>

`hpx::shared_future<R> &&hpx::make_shared_future(hpx::shared_future<R> &&f) noexcept`

Converts any future or `shared_future` of type T to a corresponding `shared_future` of type T.

template<typename R>

`hpx::shared_future<R> const &hpx::make_shared_future(hpx::shared_future<R> const &f) noexcept`

Converts any future or `shared_future` of type T to a corresponding `shared_future` of type T.

`hpx::make_ready_future`

Defined in header `hpx/future.hpp`⁸⁹⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::future`
- `hpx::shared_future`
- `hpx::make_future`
- `hpx::make_shared_future`
- `hpx::make_ready_future_alloc`
- `hpx::make_ready_future_at`
- `hpx::make_ready_future_after`
- `hpx::make_exceptional_future`

template<typename T, typename ...Ts>

`std::enable_if_t<std::is_constructible_v<T, Ts&&...> || std::is_void_v<T>, future<T>> hpx::make_ready_future(Ts&&... ts)`

The function creates a shared state that is immediately ready and returns a future associated with that shared state. For the returned future, `valid() == true` and `is_ready() == true`.

template<int DeductionGuard = 0, typename T>

`future<hpx::util::decay_unwrap_t<T>> hpx::make_ready_future(T &&init)`

The function creates a shared state that is immediately ready and returns a future associated with that shared state. For the returned future, `valid() == true` and `is_ready() == true`.

`future<void> hpx::make_ready_future()`

The function creates a shared state that is immediately ready and returns a future associated with that shared state. For the returned future, `valid() == true` and `is_ready() == true`.

⁸⁹⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

hpx::make_ready_future_alloc

Defined in header [hpx/future.hpp](#)⁸⁹⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::future`
- `hpx::shared_future`
- `hpx::make_future`
- `hpx::make_shared_future`
- `hpx::make_ready_future`
- `hpx::make_ready_future_at`
- `hpx::make_ready_future_after`
- `hpx::make_exceptional_future`

template<typename **T**, typename **Allocator**, typename ...**Ts**>

`std::enable_if_t<std::is_constructible_v<T, Ts&&...> || std::is_void_v<T>, future<T>>` `hpx::make_ready_future_alloc(Allocator const &a, Ts&&... ts)`

Creates a pre-initialized future object with allocator (extension)

template<int **DeductionGuard** = 0, typename **Allocator**, typename **T**>

`future<hpx::util::decay_unwrap_t<T>>` `hpx::make_ready_future_alloc(Allocator const &a, T &&init)`

template<typename **Allocator**>

inline `future<void>` `hpx::make_ready_future_alloc(Allocator const &a)`

hpx::make_ready_future_at

Defined in header [hpx/future.hpp](#)⁹⁰⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::future`
- `hpx::shared_future`
- `hpx::make_future`
- `hpx::make_shared_future`
- `hpx::make_ready_future`
- `hpx::make_ready_future_alloc`
- `hpx::make_ready_future_after`
- `hpx::make_exceptional_future`

⁸⁹⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁹⁰⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

```
template<int DeductionGuard = 0, typename T>
future<hpx::util::decay_unwrap_t<T>> hpx::make_ready_future_at(hpx::chrono::steady_time_point const
&abs_time, T &&init)
```

Creates a pre-initialized future object which gets ready at a given point in time (extension)

```
inline future<void> hpx::make_ready_future_at(hpx::chrono::steady_time_point const &abs_time)
```

Creates a pre-initialized future object which gets ready at a given point in time (extension)

hpx::make_ready_future_after

Defined in header [hpx/future.hpp](#)⁹⁰¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::future](#)
- [hpx::shared_future](#)
- [hpx::make_future](#)
- [hpx::make_shared_future](#)
- [hpx::make_ready_future](#)
- [hpx::make_ready_future_alloc](#)
- [hpx::make_ready_future_at](#)
- [hpx::make_exceptional_future](#)

```
template<int DeductionGuard = 0, typename T>
future<hpx::util::decay_unwrap_t<T>> hpx::make_ready_future_after(hpx::chrono::steady_duration const
&rel_time, T &&init)
```

Creates a pre-initialized future object which gets ready after a given point in time (extension)

```
inline future<void> hpx::make_ready_future_after(hpx::chrono::steady_duration const &rel_time)
```

Creates a pre-initialized future object which gets ready after a given point in time (extension)

hpx::make_exceptional_future

Defined in header [hpx/future.hpp](#)⁹⁰².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- [hpx::future](#)
- [hpx::shared_future](#)
- [hpx::make_future](#)
- [hpx::make_shared_future](#)
- [hpx::make_ready_future](#)
- [hpx::make_ready_future_alloc](#)

⁹⁰¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

⁹⁰² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

- `hpx::make_ready_future_at`
- `hpx::make_ready_future_after`

template<typename T>

`future<T> hpx::make_exceptional_future(std::exception_ptr const &e)`

Creates a pre-initialized future object which holds the given error (extension)

template<typename T, typename E>

`future<T> hpx::make_exceptional_future(E e)`

Creates a pre-initialized future object which holds the given error (extension)

hpx/futures/future_fwd.hpp

Defined in header `hpx/futures/future_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Top level HPX namespace.

template<typename R>

class **future** : public `hpx::lcos::detail::future_base<future<R>, R>`

`#include <future_fwd.hpp>`

template<typename R>

class **promise** : public `hpx::detail::promise_base<R>`

`#include <promise.hpp>`

template<typename R>

class **shared_future** : public `hpx::lcos::detail::future_base<shared_future<R>, R>`

`#include <future_fwd.hpp>`

namespace **lcos**

namespace **lcos**

hpx::packaged_task

Defined in header `hpx/future.hpp`⁹⁰³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename Sig>

class **packaged_task**

The class template `hpx::packaged_task` wraps any Callable⁹⁰³ target (function, lambda expression, bind expression, or another function object) so that it can be invoked asynchronously. Its return value or exception thrown is stored in a shared state which can be accessed through `hpx::future` objects. Just like `hpx::function`, `hpx::packaged_task` is a polymorphic, allocator-aware container: the stored callable target may be allocated on heap or with a provided allocator.

⁹⁰³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/future.hpp>

io_service

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/io_service/io_service_pool.hpp

Defined in header `hpx/io_service/io_service_pool.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

class **io_service_pool**

#include <io_service_pool.hpp> A pool of io_service objects.

Public Functions

explicit **io_service_pool**(*std::size_t* pool_size = 2, *threads::policies::callback_notifier* const ¬ifier = *threads::policies::callback_notifier*(), char const *pool_name = "", char const *name_postfix = "")

Construct the io_service pool.

Parameters

- **pool_size** – [in] The number of threads to run to serve incoming requests
- **notifier** – [in]
- **pool_name** – [in]
- **name_postfix** – [in]

explicit **io_service_pool**(*threads::policies::callback_notifier* const ¬ifier, char const *pool_name = "", char const *name_postfix = "")

Construct the io_service pool.

Parameters

- **notifier** – [in]
- **pool_name** – [in]
- **name_postfix** – [in]

io_service_pool(*io_service_pool* const&) = delete

io_service_pool(*io_service_pool*&&) = delete

io_service_pool &**operator**=(*io_service_pool* const&) = delete

io_service_pool &**operator**=(*io_service_pool*&&) = delete

~io_service_pool()

bool **run**(bool join_threads = true, *barrier* *startup = nullptr) const

Run all io_service objects in the pool. If join_threads is true this will also wait for all threads to complete

bool **run**(std::size_t num_threads, bool join_threads = true, *barrier* *startup = nullptr) const
Run all io_service objects in the pool. If join_threads is true this will also wait for all threads to complete

void **stop**() const
Stop all io_service objects in the pool.

void **join**() const
Join all io_service threads in the pool.

void **clear**() const
Clear all internal data structures.

void **wait**() const
Wait for all work to be done.

bool **stopped**() const

::asio::io_context &**get_io_service**(int index = -1) const
Get an io_service to use.

std::thread &**get_os_thread_handle**(std::size_t thread_num) const
access underlying thread handle

std::size_t **size**() const noexcept
Get number of threads associated with this I/O service.

void **thread_run**(std::size_t index, *barrier* *startup = nullptr) const
Activate the thread *index* for this thread pool.

char const ***get_name**() const noexcept
Return name of this pool.

void **init**(std::size_t pool_size) const

Private Members

detail::io_service_pool_base ***pool_**

lcos_local

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx::lcos::local::and_gate

Defined in header `hpx/modules/lcos_local.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
struct and_gate : public hpx::lcos::local::base_and_gate<hpx::no_mutex>
```

An AND-gate synchronization primitive that fires once all of its expected inputs have been received.

Note: This type is not thread-safe. It has to be protected from concurrent access by different threads by the code using instances of this type.

hpx/lcos_local/trigger.hpp

Defined in header `hpx/lcos_local/trigger.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace lcos
```

```
        namespace local
```

```
            template<typename Mutex = hpx::spinlock>
```

```
            struct base_trigger
```

Public Functions

```
            inline base_trigger() noexcept
```

```
            inline base_trigger(base_trigger &&rhs) noexcept
```

```
            inline base_trigger &operator=(base_trigger &&rhs) noexcept
```

```
            inline hpx::future<void> get_future(std::size_t *generation_value = nullptr, error_code &ec  
                                              = hpx::throws)
```

get a future allowing to wait for the trigger to fire

```
            inline bool set(error_code &ec = throws)
```

Trigger this object.

```
            inline void synchronize(std::size_t generation_value, char const *function_name =  
                                     "trigger::synchronize", error_code &ec = throws)
```

Wait for the generational counter to reach the requested stage.

```
            inline std::size_t next_generation()
```

```
            inline std::size_t generation() const
```

Protected Types

```
using mutex_type = Mutex
```

Protected Functions

```
inline bool trigger_conditions(error_code &ec = throws)
```

```
template<typename Lock>
```

```
inline void synchronize(std::size_t generation_value, Lock &l, char const *function_name =  
    "trigger::synchronize", error_code &ec = throws)
```

Private Types

```
using condition_list_type = hpx::detail::intrusive_list<condition_list_entry>
```

Private Functions

```
inline bool test_condition(std::size_t const generation_value) const noexcept
```

Private Members

```
mutable mutex_type mtx_
```

```
hpx::promise<void> promise_
```

```
std::size_t generation_
```

```
condition_list_type conditions_
```

```
struct condition_list_entry : public conditional_trigger
```

Public Functions

```
condition_list_entry() = default
```

Public Members

condition_list_entry ***prev** = nullptr

condition_list_entry ***next** = nullptr

struct **manage_condition**

Public Functions

inline **manage_condition**(*base_trigger* &gate, *condition_list_entry* &cond) noexcept

inline ~**manage_condition**()

template<typename **Condition**>

inline *hpx::future*<void> **get_future**(*Condition* &&func, *error_code* &ec = *hpx::throws*)

Public Members

base_trigger &**this_**

condition_list_entry &**e_**

struct **trigger** : public *hpx::lcos::local::base_trigger*<*hpx::no_mutex*>

Public Functions

trigger() = default

inline **trigger**(*trigger* &&rhs) noexcept

inline *trigger* &**operator=**(*trigger* &&rhs) noexcept

template<typename **Lock**>

inline void **synchronize**(*std::size_t* generation_value, *Lock* &l, char const *function_name =
"trigger::synchronize", *error_code* &ec = *throws*)

Private Types

using **base_type** = *base_trigger*<*hpx::no_mutex*>

pack_traversal

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/pack_traversal/pack_traversal_async.hpp

Defined in header `hpx/pack_traversal/pack_traversal_async.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

Functions

```
template<typename Visitor, typename ...T>
auto traverse_pack_async(Visitor &&visitor, T&&... pack) -> de-
    cltype(detail::apply_pack_transform_async(std::forward<Visitor>(visitor),
    std::forward<T>(pack)...))
```

Traverses the pack with the given visitor in an asynchronous way.

This function works in the same way as `traverse_pack`, however, we are able to suspend and continue the traversal at later time. Thus, we require a visitor callable object which provides three `operator()` overloads as depicted by the code sample below:

```
struct my_async_visitor {
    // The synchronous overload is called for each object. It may
    // return false to suspend the current control. In that case the
    // overload below is called.
    template <typename T>
    bool operator()(async_traverse_visit_tag, T&& element)
    {
        return true;
    }

    // The asynchronous overload is called when the synchronous
    // overload returned false. In addition to the current visited
    // element, the overload is called with a continuation callable
    // object which resumes the traversal when called later.
    template <typename T, typename N>
    void operator()(async_traverse_detach_tag, T&& element, N&& next)
    {
    }

    // The overload is called when the traversal was finished. The
    // whole pack which was traversed asynchronously is passed.
    template <typename T>
    void operator()(async_traverse_complete_tag, T&& pack)
    {
    }
};
```

See `traverse_pack` for a detailed description about the traversal behavior and capabilities.

Parameters

- **visitor** – A visitor object which provides the three `operator()` overloads that were described above. Additionally, the visitor must be compatible for referencing it from a `hpx::intrusive_ptr`. The visitor should have a virtual destructor!
- **pack** – The arbitrary parameter pack which is traversed asynchronously. Nested objects inside containers and tuple like types are traversed recursively.

Returns

A `hpx::intrusive_ptr` that references an instance of the given visitor object.

```
template<typename Allocator, typename Visitor, typename ...T>
auto traverse_pack_async_allocator(Allocator const &alloc, Visitor &&visitor, T&&... pack) ->
    de-
    cltype(detail::apply_pack_transform_async_allocator(alloc,
        std::forward<Visitor>(visitor), std::forward<T>(pack)...))
```

Traverses the pack with the given visitor in an asynchronous way.

This function works in the same way as `traverse_pack`, however, we are able to suspend and continue the traversal at later time. Thus, we require a visitor callable object which provides three `operator()` overloads as depicted by the code sample below:

```
struct my_async_visitor {
    // The synchronous overload is called for each object. It may
    // return false to suspend the current control. In that case the
    // overload below is called.
    template <typename T>
    bool operator()(async_traverse_visit_tag, T&& element)
    {
        return true;
    }

    // The asynchronous overload is called when the synchronous
    // overload returned false. In addition to the current visited
    // element, this overload receives a continuation callable object
    // which resumes the traversal when called later. The continuation
    // may be stored and called later or dropped completely to abort
    // the traversal early.
    template <typename T, typename N>
    void operator()(async_traverse_detach_tag, T&& element, N&& next)
    {
    }

    // This overload is called when the traversal is finished. The
    // complete pack that was traversed asynchronously is passed.
    template <typename T>
    void operator()(async_traverse_complete_tag, T&& pack)
    {
    }
};
```

See `traverse_pack` for a detailed description about the traversal behavior and capabilities.

Parameters

- **visitor** – A visitor object which provides the three `operator()` overloads that were described above. Additionally, the visitor must be compatible for referencing it from a `hpx::intrusive_ptr`. The visitor should have a virtual destructor!
- **pack** – The arbitrary parameter pack which is traversed asynchronously. Nested objects inside containers and tuple like types are traversed recursively.
- **alloc** – Allocator instance to use to create the traversal frame.

Returns

A `hpx::intrusive_ptr` that references an instance of the given visitor object.

`hpx::functional::unwrap`

Defined in header `hpx/unwrap.hpp`⁹⁰⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::functional::unwrap_n`
- `hpx::functional::unwrap_all`
- `hpx::unwrap`
- `hpx::unwrap_n`
- `hpx::unwrap_all`
- `hpx::unwrapping`
- `hpx::unwrapping_n`
- `hpx::unwrapping_all`

struct `unwrap`

A helper function object for functionally invoking `hpx::unwrap`. For more information please refer to its documentation.

`hpx::functional::unwrap_n`

Defined in header `hpx/unwrap.hpp`⁹⁰⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::functional::unwrap`
- `hpx::functional::unwrap_all`
- `hpx::unwrap`
- `hpx::unwrap_n`
- `hpx::unwrap_all`
- `hpx::unwrapping`
- `hpx::unwrapping_n`

⁹⁰⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/unwrap.hpp

⁹⁰⁵ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/unwrap.hpp

- `hpx::unwrapping_all`

template<std::size_t **Depth**>

struct **unwrap_n**

A helper function object for functionally invoking `hpx::unwrap_n`. For more information please refer to its documentation.

hpx::functional::unwrap_all

Defined in header `hpx/unwrap.hpp`⁹⁰⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::functional::unwrap`
- `hpx::functional::unwrap_n`
- `hpx::unwrap`
- `hpx::unwrap_n`
- `hpx::unwrap_all`
- `hpx::unwrapping`
- `hpx::unwrapping_n`
- `hpx::unwrapping_all`

struct **unwrap_all**

A helper function object for functionally invoking `hpx::unwrap_all`. For more information please refer to its documentation.

hpx::unwrap

Defined in header `hpx/unwrap.hpp`⁹⁰⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::functional::unwrap`
- `hpx::functional::unwrap_n`
- `hpx::functional::unwrap_all`
- `hpx::unwrap_n`
- `hpx::unwrap_all`
- `hpx::unwrapping`
- `hpx::unwrapping_n`
- `hpx::unwrapping_all`

⁹⁰⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/unwrap.hpp

⁹⁰⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/unwrap.hpp

```
template<typename ...Args>
auto hpx::unwrap(Args&&... args) -> decltype(util::detail::unwrap_depth_impl<1U>(HPX_FORWARD(Args,
    args)...))
```

A helper function for retrieving the actual result of any *hpx::future* like type which is wrapped in an arbitrary way.

Unwraps the given pack of arguments, so that any *hpx::future* object is replaced by its future result type in the argument pack:

- *hpx::future<int>* -> *int*
- *hpx::future<std::vector<float>>* -> *std::vector<float>*
- *std::vector<future<float>>* -> *std::vector<float>*

The function is capable of unwrapping *hpx::future* like objects that are wrapped inside any container or tuple like type, see *hpx::util::map_pack()* for a detailed description about which surrounding types are supported. Non *hpx::future* like types are permitted as arguments and passed through.

```
hpx::unwrap(hpx::make_ready_future(0));

// Multiple arguments hpx::tuple<int, int> i2 =
    hpx::unwrap(hpx::make_ready_future(1),
        hpx::make_ready_future(2));
```

Note: This function unwraps the given arguments until the first traversed nested *hpx::future* which corresponds to an unwrapping depth of one. See *hpx::unwrap_n()* for a function which unwraps the given arguments to a particular depth or *hpx::unwrap_all()* that unwraps all future like objects recursively which are contained in the arguments.

Parameters

args – the arguments that are unwrapped which may contain any arbitrary future or non-future type.

Throws

std::exception – like objects in case any of the given wrapped *hpx::future* objects were resolved through an exception. See *hpx::future::get()* for details.

Returns

Depending on the count of arguments this function returns a *hpx::tuple* containing the unwrapped arguments if multiple arguments are given. In case the function is called with a single argument, the argument is unwrapped and returned.

hpx::unwrap_n

Defined in header *hpx/unwrap.hpp*⁹⁰⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::functional::unwrap*
- *hpx::functional::unwrap_n*

⁹⁰⁸ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/unwrap.hpp

- `hpx::functional::unwrap_all`
- `hpx::unwrap`
- `hpx::unwrap_all`
- `hpx::unwrapping`
- `hpx::unwrapping_n`
- `hpx::unwrapping_all`

template<std::size_t **Depth**, typename ...**Args**>

```
auto hpx::unwrap_n(Args&&... args) ->
    decltype(util::detail::unwrap_depth_impl<Depth>(HPX_FORWARD(Args, args)...))
```

An alternative version of `hpx::unwrap()`, which unwraps the given arguments to a certain depth of `hpx::future` like objects.

See `unwrap` for a detailed description.

Template Parameters

Depth – The count of `hpx::future` like objects which are unwrapped maximally.

`hpx::unwrap_all`

Defined in header `hpx/unwrap.hpp`⁹⁰⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::functional::unwrap`
- `hpx::functional::unwrap_n`
- `hpx::functional::unwrap_all`
- `hpx::unwrap`
- `hpx::unwrap_n`
- `hpx::unwrapping`
- `hpx::unwrapping_n`
- `hpx::unwrapping_all`

template<typename ...**Args**>

```
auto hpx::unwrap_all(Args&&... args) ->
    decltype(util::detail::unwrap_depth_impl<0U>(HPX_FORWARD(Args, args)...))
```

An alternative version of `hpx::unwrap()`, which unwraps the given arguments recursively so that all contained `hpx::future` like objects are replaced by their actual value.

See `hpx::unwrap()` for a detailed description.

⁹⁰⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/unwrap.hpp

hpx::unwrapping

Defined in header [hpx/unwrap.hpp](#)⁹¹⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::functional::unwrap*
- *hpx::functional::unwrap_n*
- *hpx::functional::unwrap_all*
- *hpx::unwrap*
- *hpx::unwrap_n*
- *hpx::unwrap_all*
- *hpx::unwrapping_n*
- *hpx::unwrapping_all*

template<typename **T**>

```
auto hpx::unwrapping(T &&callable) ->  
    decltype(util::detail::functional_unwrap_depth_impl<1U>(HPX_FORWARD(T,  
    callable)))
```

Returns a callable object which unwraps its arguments upon invocation using the *hpx::unwrap()* function and then passes the result to the given callable object.

```
    return left + right;  
});  
  
int i1 = callable(hpx::make_ready_future(1),  
    hpx::make_ready_future(2));
```

See *hpx::unwrap()* for a detailed description.

Parameters

callable – the callable object which is called with the result of the corresponding unwrap function.

hpx::unwrapping_n

Defined in header [hpx/unwrap.hpp](#)⁹¹¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::functional::unwrap*
- *hpx::functional::unwrap_n*
- *hpx::functional::unwrap_all*
- *hpx::unwrap*
- *hpx::unwrap_n*

⁹¹⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/unwrap.hpp

⁹¹¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/unwrap.hpp

- `hpx::unwrap_all`
- `hpx::unwrapping`
- `hpx::unwrapping_all`

```
template<std::size_t Depth, typename T>
auto hpx::unwrapping_n(T &&callable) ->
    decltype(util::detail::functional_unwrap_depth_impl<Depth>(HPX_FORWARD(T,
        callable)))
```

Returns a callable object which unwraps its arguments upon invocation using the `hpx::unwrap_n()` function and then passes the result to the given callable object.

See `hpx::unwrapping()` for a detailed description.

`hpx::unwrapping_all`

Defined in header `hpx/unwrap.hpp`⁹¹².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::functional::unwrap`
- `hpx::functional::unwrap_n`
- `hpx::functional::unwrap_all`
- `hpx::unwrap`
- `hpx::unwrap_n`
- `hpx::unwrap_all`
- `hpx::unwrapping`
- `hpx::unwrapping_n`

```
template<typename T>
auto hpx::unwrapping_all(T &&callable) ->
    decltype(util::detail::functional_unwrap_depth_impl<0U>(HPX_FORWARD(T,
        callable)))
```

Returns a callable object which unwraps its arguments upon invocation using the `hpx::unwrap_all()` function and then passes the result to the given callable object.

See `hpx::unwrapping()` for a detailed description.

`hpx/pack_traversal/pack_traversal.hpp`

Defined in header `hpx/pack_traversal/pack_traversal.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **util**

⁹¹² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/unwrap.hpp

Functions

```
template<typename Mapper, typename...  
T> < unspecified > map_pack (Mapper &&mapper, T &&... pack)
```

Maps the pack with the given mapper.

This function tries to visit all plain elements which may be wrapped in:

- homogeneous containers (`std::vector`, `std::list`)
- heterogeneous containers (`hpx::tuple`, `std::pair`, `std::array`) and re-assembles the pack with the result of the mapper. Mapping from one type to a different one is supported.

Elements that aren't accepted by the mapper are routed through and preserved through the hierarchy.

```
// Maps all integers to floats  
map_pack([](int value) {  
    return float(value);  
},  
1, hpx::make_tuple(2, std::vector<int>{3, 4}), 5);
```

Throws

`std::exception` – like objects which are thrown by an invocation to the mapper.

Parameters

- **mapper** – A callable object, which accept an arbitrary type and maps it to another type or the same one.
- **pack** – An arbitrary variadic pack which may contain any type.

Returns

The mapped element or in case the pack contains multiple elements, the pack is wrapped into a `hpx::tuple`.

preprocessor

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/preprocessor/nargs.hpp

Defined in header `hpx/preprocessor/nargs.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PP_NARGS(...)

Expands to the number of arguments passed in

Example Usage:

```
HPX_PP_NARGS(hpx, pp, nargs)  
HPX_PP_NARGS(hpx, pp)  
HPX_PP_NARGS(hpx)
```

Expands to:

```
3
2
1
```

Parameters

- ... – The variadic number of arguments

hpx/preprocessor/expand.hpp

Defined in header `hpx/preprocessor/expand.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PP_EXPAND(X)

The `HPX_PP_EXPAND` macro performs a double macro-expansion on its argument.

This macro can be used to produce a delayed preprocessor expansion.

Example:

```
#define MACRO(a, b, c) (a)(b)(c)
#define ARGS() (1, 2, 3)

HPX_PP_EXPAND(MACRO ARGS()) // expands to (1)(2)(3)
```

Parameters

- **X** – Token to be expanded twice

hpx/preprocessor/stringize.hpp

Defined in header `hpx/preprocessor/stringize.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PP_STRINGIZE(X)

The `HPX_PP_STRINGIZE` macro stringizes its argument after it has been expanded.

The passed argument **X** will expand to "**X**". Note that the stringizing operator (`#`) prevents arguments from expanding. This macro circumvents this shortcoming.

Parameters

- **X** – The text to be converted to a string literal

hpx/preprocessor/strip_parens.hpp

Defined in header `hpx/preprocessor/strip_parens.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PP_STRIP_PARENS(X)

For any symbol *X*, this macro returns the same symbol from which potential outer parens have been removed. If no outer parens are found, this macros evaluates to *X* itself without error.

The original implementation of this macro is from Steven Watanbe as shown in <http://boost.2283326.n4.nabble.com/preprocessor-removing-parentheses-td2591973.html#a2591976>

```
HPX_PP_STRIP_PARENS(no_parens)
HPX_PP_STRIP_PARENS((with_parens))
```

Example Usage:

This produces the following output

```
no_parens
with_parens
```

Parameters

- **X** – Symbol to strip parens from

hpx/preprocessor/cat.hpp

Defined in header `hpx/preprocessor/cat.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Defines

HPX_PP_CAT(A, B)

Concatenates the tokens *A* and *B* into a single token. Evaluates to *AB*

Parameters

- **A** – First token
- **B** – Second token

resiliency

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/resiliency/async_replay.hpp

Defined in header `hpx/resiliency/async_replay.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **resiliency**

namespace **experimental**

Functions

```
template<typename Pred, typename F, typename ...Ts>
hpx::future<hpx::util::detail::invoke_deferred_result_t<F, Ts...>> hpx_invoke(async_replay_validate_t,
                                                                    std::size_t n, Pred
                                                                    &&pred, F &&f,
                                                                    Ts&&... ts)
```

ADL hook for `async_replay_validate` CPO.

Asynchronously launches *f*, validating results with *pred*. Repeats on error up to *n* times (aborts on `abort_replay_exception`).

Parameters

- **tag** – CPO tag (*async_replay_validate_t*).
- **n** – Maximum number of retry attempts.
- **pred** – Predicate validating each invocation result.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the first valid result of *f*.

```
template<typename F, typename ...Ts>
hpx::future<hpx::util::detail::invoke_deferred_result_t<F, Ts...>> hpx_invoke(async_replay_t,
                                                                    std::size_t n, F
                                                                    &&f, Ts&&... ts)
```

ADL hook for `async_replay` CPO.

Asynchronously launches *f*, repeating on error up to *n* times (aborts on `abort_replay_exception`).

Parameters

- **tag** – CPO tag (*async_replay_t*).
- **n** – Maximum number of retry attempts.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the first successful result of *f*.

hpx/resiliency/async_replicate.hpp

Defined in header `hpx/resiliency/async_replicate.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **resiliency**

namespace **experimental**

Functions

```
template<typename Vote, typename Pred, typename F, typename ...Ts>
hpx::future<hpx::util::detail::invoke_deferred_result_t<F, Ts...>> hpx_invoke(async_replicate_vote_validate_t,
                                                                    std::size_t n, Vote
                                                                    &&vote, Pred
                                                                    &&pred, F &&f,
                                                                    Ts&&... ts)
```

ADL hook for `async_replicate_vote_validate` CPO.

Asynchronously launches *f* exactly *n* times, validates results with *pred*, then runs valid results through *vote*.

Parameters

- **tag** – CPO tag (*async_replicate_vote_validate_t*).
- **n** – Number of replicated invocations.
- **vote** – Voting function selecting among valid results.
- **pred** – Predicate validating each invocation result.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the voted-upon result.

```
template<typename Vote, typename F, typename ...Ts>
hpx::future<hpx::util::detail::invoke_deferred_result_t<F, Ts...>> hpx_invoke(async_replicate_vote_t,
                                                                    std::size_t n, Vote
                                                                    &&vote, F &&f,
                                                                    Ts&&... ts)
```

ADL hook for `async_replicate_vote` CPO.

Asynchronously launches *f* exactly *n* times, runs valid results through *vote*. Validation uses the default exception check.

Parameters

- **tag** – CPO tag (*async_replicate_vote_t*).
- **n** – Number of replicated invocations.
- **vote** – Voting function selecting among valid results.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the voted-upon result.

```
template<typename Pred, typename F, typename ...Ts>
```

```
hpx::future<hpx::util::detail::invoke_deferred_result_t<F, Ts...>> hpx_invoke(async_replicate_validate_t,
                                                                    std::size_t n, Pred
                                                                    &&pred, F &&f,
                                                                    Ts&&... ts)
```

ADL hook for `async_replicate_validate` CPO.

Asynchronously launches *f* exactly *n* times, validates results with *pred*. Returns the first valid result.

Parameters

- **tag** – CPO tag (*async_replicate_validate_t*).
- **n** – Number of replicated invocations.
- **pred** – Predicate validating each invocation result.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the first valid result.

```
template<typename F, typename ...Ts>
hpx::future<hpx::util::detail::invoke_deferred_result_t<F, Ts...>> hpx_invoke(async_replicate_t,
                                                                    std::size_t n, F
                                                                    &&f, Ts&&... ts)
```

ADL hook for `async_replicate` CPO.

Asynchronously launches *f* exactly *n* times. Validates by checking for exceptions. Returns the first valid result.

Parameters

- **tag** – CPO tag (*async_replicate_t*).
- **n** – Number of replicated invocations.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the first non-throwing result.

hpx/resiliency/replay_executor.hpp

Defined in header `hpx/resiliency/replay_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename BaseExecutor, typename Validator>
```

```
struct is_two_way_executor<hpx::resiliency::experimental::replay_executor<BaseExecutor, Validator>> : public
true_type
```

```
template<typename BaseExecutor, typename Validator>
```

```
struct is_bulk_two_way_executor<hpx::resiliency::experimental::replay_executor<BaseExecutor, Validator>> :
public true_type
```

```
namespace hpx
```

```
    namespace execution
```

```
namespace experimental
```

```
    template<typename BaseExecutor,  
            typename Validator> replay_executor< BaseExecutor,  
            Validator > > : public true_type
```

```
    template<typename BaseExecutor,  
            typename Validator> replay_executor< BaseExecutor,  
            Validator > > : public true_type
```

```
namespace resiliency
```

```
namespace experimental
```

Functions

```
template<executor_any BaseExecutor, typename Validate>  
replay_executor<BaseExecutor, std::decay_t<Validate>>> make_replay_executor(BaseExecutor  
                                                                    &exec,  
                                                                    std::size_t n,  
                                                                    Validate  
                                                                    &&validate)
```

```
template<executor_any BaseExecutor>  
replay_executor<BaseExecutor, detail::replay_validator> make_replay_executor(BaseExecutor  
                                                                    &exec,  
                                                                    std::size_t n)
```

```
template<typename BaseExecutor, typename Validate>
```

```
class replay_executor
```

Public Types

```
using execution_category = hpx::traits::executor_execution_category_t<BaseExecutor>
```

```
using executor_parameters_type = hpx::traits::executor_parameters_type_t<BaseExecutor>
```

```
template<typename Result>
```

```
using future_type = hpx::traits::executor_future_t<BaseExecutor, Result>
```

Public Functions

```

template<typename BaseExecutor_, typename F>
inline explicit replay_executor(BaseExecutor_ &&exec, std::size_t n, F &&f)

inline bool operator==(replay_executor const &rhs) const noexcept

inline bool operator!=(replay_executor const &rhs) const noexcept

inline constexpr replay_executor const &context() const noexcept

template<typename F, typename ...Ts>
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_async_execute(F &&f, S const &shape, Ts&&... ts) const

inline BaseExecutor const &get_executor() const

inline std::size_t get_replay_count() const

inline Validate const &get_validator() const

template<typename Tag, typename ...Args>
inline auto query(Tag tag, Args&&... args) const -> decltype(replay_executor<BaseExecutor,
    Validate>(std::declval<Tag>())(std::declval<BaseExecutor>(),
    std::forward<Args>(args)...), std::declval<std::size_t>(),
    std::declval<Validate>()))

```

Public Static Attributes

```

static constexpr int num_spread = 4

static constexpr int num_tasks = 128

```

Private Members

```

BaseExecutor exec_

std::size_t replay_count_

Validate validator_

```

hpx/resiliency/async_replay_executor.hpp

Defined in header `hpx/resiliency/async_replay_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **resiliency**

namespace **experimental**

Functions

```
template<typename Executor, typename Pred, typename F, typename ...Ts>
decltype(auto) hpx_invoke(async_replay_validate_t, Executor &&exec, std::size_t n, Pred
&&pred, F &&f, Ts&&... ts)
```

ADL hook for `async_replay_validate` CPO with executor.

Asynchronously launches *f* on *exec*, validating results with *pred*. Repeats on error up to *n* times (aborts on `abort_replay_exception`).

Parameters

- **tag** – CPO tag (*async_replay_validate_t*).
- **exec** – Executor to run *f* on.
- **n** – Maximum number of retry attempts.
- **pred** – Predicate validating each invocation result.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the first valid result of *f*.

```
template<typename Executor, typename F, typename ...Ts>
decltype(auto) hpx_invoke(async_replay_t, Executor &&exec, std::size_t n, F &&f, Ts&&... ts)
```

ADL hook for `async_replay` CPO with executor.

Asynchronously launches *f* on *exec*, repeating on error up to *n* times (aborts on `abort_replay_exception`).

Parameters

- **tag** – CPO tag (*async_replay_t*).
- **exec** – Executor to run *f* on.
- **n** – Maximum number of retry attempts.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the first successful result of *f*.

hpx/resiliency/resiliency_cpos.hpp

Defined in header `hpx/resiliency/resiliency_cpos.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **resiliency**

namespace **experimental**

Variables

hpx::resiliency::experimental::async_replay_validate_t **async_replay_validate**

hpx::resiliency::experimental::async_replay_t **async_replay**

hpx::resiliency::experimental::dataflow_replay_validate_t **dataflow_replay_validate**

hpx::resiliency::experimental::dataflow_replay_t **dataflow_replay**

hpx::resiliency::experimental::async_replicate_vote_validate_t
async_replicate_vote_validate

hpx::resiliency::experimental::async_replicate_vote_t **async_replicate_vote**

hpx::resiliency::experimental::async_replicate_validate_t **async_replicate_validate**

hpx::resiliency::experimental::async_replicate_t **async_replicate**

hpx::resiliency::experimental::dataflow_replicate_vote_validate_t
dataflow_replicate_vote_validate

hpx::resiliency::experimental::dataflow_replicate_vote_t **dataflow_replicate_vote**

hpx::resiliency::experimental::dataflow_replicate_validate_t **dataflow_replicate_validate**

hpx::resiliency::experimental::dataflow_replicate_t **dataflow_replicate**

struct **async_replay_t** : public

hpx::resiliency::experimental::detail::dispatch_cpo<async_replay_t>

#include <resiliency_cpos.hpp> Customization point for asynchronously launching given function *f* repeatedly. Repeat launching on error exactly *n* times (except if `abort_replay_exception` is thrown).

```
struct async_replay_validate_t : public
hpx::resiliency::experimental::detail::dispatch_cpo<async_replay_validate_t>
    #include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
    function f. repeatedly. Verify the result of those invocations using the given predicate pred. Repeat
    launching on error exactly n times (except if abort_replay_exception is thrown).

struct async_replicate_t : public
hpx::resiliency::experimental::detail::dispatch_cpo<async_replicate_t>
    #include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
    function f exactly n times concurrently. Verify the result of those invocations by checking for
    exception. Return the first valid result.

struct async_replicate_validate_t : public
hpx::resiliency::experimental::detail::dispatch_cpo<async_replicate_validate_t>
    #include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
    function f exactly n times concurrently. Verify the result of those invocations using the given
    predicate pred. Return the first valid result.

struct async_replicate_vote_t : public
hpx::resiliency::experimental::detail::dispatch_cpo<async_replicate_vote_t>
    #include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
    function f exactly n times concurrently. Verify the result of those invocations using the given
    predicate pred. Run all the valid results against a user provided voting function. Return the valid
    output.

struct async_replicate_vote_validate_t : public
hpx::resiliency::experimental::detail::dispatch_cpo<async_replicate_vote_validate_t>
    #include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
    function f exactly n times concurrently. Verify the result of those invocations using the given
    predicate pred. Run all the valid results against a user provided voting function. Return the valid
    output.

struct dataflow_replay_t : public
hpx::resiliency::experimental::detail::tag_deferred<dataflow_replay_t, async_replay_t>
    #include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
    function f. repeatedly. Repeat launching on error exactly n times.

    Delay the invocation of f if any of the arguments to f are futures.

struct dataflow_replay_validate_t : public
hpx::resiliency::experimental::detail::tag_deferred<dataflow_replay_validate_t,
async_replay_validate_t>
    #include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
    function f. repeatedly. Verify the result of those invocations using the given predicate pred. Repeat
    launching on error exactly n times.

    Delay the invocation of f if any of the arguments to f are futures.

struct dataflow_replicate_t : public
hpx::resiliency::experimental::detail::tag_deferred<dataflow_replicate_t, async_replicate_t>
    #include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
    function f exactly n times concurrently. Return the first valid result.
```


Delay the invocation of f if any of the arguments to f are futures.

```
struct dataflow_replicate_validate_t : public
hpx::resiliency::experimental::detail::tag_deferred<dataflow_replicate_validate_t,
async_replicate_validate_t>
#include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
function  $f$  exactly  $n$  times concurrently. Verify the result of those invocations using the given
predicate  $pred$ . Return the first valid result.
```

Delay the invocation of f if any of the arguments to f are futures.

```
struct dataflow_replicate_vote_t : public
hpx::resiliency::experimental::detail::tag_deferred<dataflow_replicate_vote_t,
async_replicate_vote_t>
#include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
function  $f$  exactly  $n$  times concurrently. Run all the valid results against a user provided voting
function. Return the valid output.
```

Delay the invocation of f if any of the arguments to f are futures.

```
struct dataflow_replicate_vote_validate_t : public
hpx::resiliency::experimental::detail::tag_deferred<dataflow_replicate_vote_validate_t,
async_replicate_vote_validate_t>
#include <resiliency_cpos.hpp> Customization point for asynchronously launching the given
function  $f$  exactly  $n$  times concurrently. Run all the valid results against a user provided voting
function. Return the valid output.
```

Delay the invocation of f if any of the arguments to f are futures.

hpx/resiliency/async_replicate_executor.hpp

Defined in header `hpx/resiliency/async_replicate_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **resiliency**

namespace **experimental**

Functions

```
template<typename Executor, typename Vote, typename Pred, typename F, typename ...Ts>
decltype(auto) hpx_invoke(async_replicate_vote_validate_t, Executor &&exec, std::size_t n, Vote
&&vote, Pred &&pred, F &&f, Ts&&... ts)
```

ADL hook for `async_replicate_vote_validate` CPO with executor.

Asynchronously launches f exactly n times on $exec$, validates results with $pred$, then runs valid results through $vote$.

Parameters

- **tag** – CPO tag (`async_replicate_vote_validate_t`).

- **exec** – Executor to run *f* on.
- **n** – Number of replicated invocations.
- **vote** – Voting function selecting among valid results.
- **pred** – Predicate validating each invocation result.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the voted-upon result.

```
template<typename Executor, typename Vote, typename F, typename ...Ts>
decltype(auto) hpx_invoke(async_replicate_vote_t, Executor &&exec, std::size_t n, Vote &&vote,
                          F &&f, Ts&&... ts)
```

ADL hook for `async_replicate_vote` CPO with executor.

Asynchronously launches *f* exactly *n* times on *exec*, runs valid results through *vote*. Validation uses the default exception check.

Parameters

- **tag** – CPO tag (*async_replicate_vote_t*).
- **exec** – Executor to run *f* on.
- **n** – Number of replicated invocations.
- **vote** – Voting function selecting among valid results.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the voted-upon result.

```
template<typename Executor, typename Pred, typename F, typename ...Ts>
decltype(auto) hpx_invoke(async_replicate_validate_t, Executor &&exec, std::size_t n, Pred
                          &&pred, F &&f, Ts&&... ts)
```

ADL hook for `async_replicate_validate` CPO with executor.

Asynchronously launches *f* exactly *n* times on *exec*, validates results with *pred*. Returns the first valid result.

Parameters

- **tag** – CPO tag (*async_replicate_validate_t*).
- **exec** – Executor to run *f* on.
- **n** – Number of replicated invocations.
- **pred** – Predicate validating each invocation result.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the first valid result.

```
template<typename Executor, typename F, typename ...Ts>
decltype(auto) hpx_invoke(async_replicate_t, Executor &&exec, std::size_t n, F &&f, Ts&&... ts)
```

ADL hook for `async_replicate` CPO with executor.

Asynchronously launches *f* exactly *n* times on *exec*. Validates by checking for exceptions. Returns the first valid result.

Parameters

- **tag** – CPO tag (*async_replicate_t*).
- **exec** – Executor to run *f* on.
- **n** – Number of replicated invocations.
- **f** – Callable to invoke asynchronously.
- **ts** – Arguments forwarded to *f*.

Returns

future with the first non-throwing result.

hpx/resiliency/replicate_executor.hpp

Defined in header `hpx/resiliency/replicate_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename BaseExecutor, typename Voter, typename Validator>
```

```
struct is_two_way_executor<hpx::resiliency::experimental::replicate_executor<BaseExecutor, Voter,  
Validator>> : public true_type
```

```
template<typename BaseExecutor, typename Voter, typename Validator>
```

```
struct is_bulk_two_way_executor<hpx::resiliency::experimental::replicate_executor<BaseExecutor, Voter,  
Validator>> : public true_type
```

```
namespace hpx
```

```
namespace execution
```

```
namespace experimental
```

```
template<typename BaseExecutor, typename Voter,  
typename Validator> replicate_executor< BaseExecutor, Voter,  
Validator > > : public true_type
```

```
template<typename BaseExecutor, typename Voter,  
typename Validator> replicate_executor< BaseExecutor, Voter,  
Validator > > : public true_type
```

```
namespace resiliency
```

```
namespace experimental
```

Functions

```
template<executor_any BaseExecutor, typename Voter, typename Validate>  
replicate_executor<BaseExecutor, std::decay_t<Voter>, std::decay_t<Validate>> make_replicate_executor(Base  
&exe  
std::s  
n,  
Voter  
&&v  
Val-  
i-  
date  
&&v  
i-  
date)
```

```
template<executor_any BaseExecutor, typename Validate>
replicate_executor<BaseExecutor, detail::replicate_voter, std::decay_t<Validate>> make_replicate_executor(Bas
&ex
std:
n,
n,
Val-
i-
date
&&
i-
date
```

```
template<executor_any BaseExecutor>
replicate_executor<BaseExecutor, detail::replicate_voter, detail::replicate_validator> make_replicate_executor(B
&
st
n,
```

```
template<typename BaseExecutor, typename Vote, typename Validate>
class replicate_executor
```

Public Types

```
using execution_category = hpx::traits::executor_execution_category_t<BaseExecutor>

using executor_parameters_type = hpx::traits::executor_parameters_type_t<BaseExecutor>

template<typename Result>
using future_type = hpx::traits::executor_future_t<BaseExecutor, Result>
```

Public Functions

```
template<typename BaseExecutor_, typename V, typename F>
inline explicit replicate_executor(BaseExecutor_ &&exec, std::size_t n, V &&v, F &&f)

inline bool operator==(replicate_executor const &rhs) const noexcept

inline bool operator!=(replicate_executor const &rhs) const noexcept

inline constexpr replicate_executor const &context() const noexcept

template<typename F, typename ...Ts>
inline decltype(auto) async_execute(F &&f, Ts&&... ts) const

template<typename F, typename S, typename ...Ts>
inline decltype(auto) bulk_async_execute(F &&f, S const &shape, Ts&&... ts) const

inline BaseExecutor const &get_executor() const
```

```

inline std::size_t get_replicate_count() const

inline Vote const &get_voter() const

inline Validate const &get_validator() const

template<typename Tag, typename ...Args>
inline auto query(Tag tag, Args&&... args) const ->
    decltype(replicate_executor<BaseExecutor, Vote,
        Validate>(std::declval<Tag>()(std::declval<BaseExecutor>()),
        std::forward<Args>(args)...), std::declval<std::size_t>(),
        std::declval<Vote>(), std::declval<Validate>()))

```

Public Static Attributes

```
static constexpr int num_spread = 4
```

```
static constexpr int num_tasks = 128
```

Private Members

```
BaseExecutor exec_
```

```
std::size_t replicate_count_
```

```
Vote voter_
```

```
Validate validator_
```

runtime_configuration

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/runtime_configuration/component_registry_base.hpp

Defined in header `hpx/runtime_configuration/component_registry_base.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
namespace hpx
```

```
    namespace components
```

```
        struct component_registry_base
```

#include <component_registry_base.hpp> The `component_registry_base` has to be used as a base class for all component registries.

Public Functions

virtual `~component_registry_base()` = default

virtual bool `get_component_info`(`std::vector<std::string> &fillini`, `std::string const &filepath`,
bool `is_static = false`) = 0

Return the ini-information for all contained components.

Parameters

- **fillini** – [in, out] The module is expected to fill this vector with the ini-information (one line per vector element) for all components implemented in this module.
- **filepath** – [in]
- **is_static** – [in]

Returns

Returns *true* if the parameter *fillini* has been successfully initialized with the registry data of all implemented in this module.

virtual void `register_component_type()` = 0

Register the component type represented by this component.

hpx::components::component_commandline_base

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

struct **component_commandline_base**

The `component_commandline_base` has to be used as a base class for all component command-line line handling registries.

Subclassed by `hpx::components::component_commandline`

hpx::runtime_mode

Defined in header `hpx/init.hpp`⁹¹³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

enum class **hpx::runtime_mode** : `std::int8_t`

A *HPX* runtime can be executed in two different modes: console mode and worker mode.

Values:

enumerator **invalid**

enumerator **console**

The runtime is the console locality.

enumerator **worker**

The runtime is a worker locality.

⁹¹³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/init_runtime/include/hpx/init.hpp

enumerator **connect**

The runtime is a worker locality connecting late

enumerator **local**

The runtime is fully local.

enumerator **default_**

The runtime mode will be determined based on the command line arguments

enumerator **last**

hpx/runtime_configuration/plugin_registry_base.hpp

Defined in header `hpx/runtime_configuration/plugin_registry_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **plugins**

struct **plugin_registry_base**

#include <plugin_registry_base.hpp> The `plugin_registry_base` has to be used as a base class for all plugin registries.

Public Functions

virtual **~plugin_registry_base**() = default

virtual bool **get_plugin_info**(*std::vector<std::string> &fillini*) = 0

Return the configuration information for any plugin implemented by this module

Parameters

fillini – [in, out] The module is expected to fill this vector with the ini-information (one line per vector element) for all plugins implemented in this module.

Returns

Returns *true* if the parameter *fillini* has been successfully initialized with the registry data of all implemented in this module.

inline virtual void **init**(*int**, *char****, *util::runtime_configuration&*)

HPX_REGISTER_COMPONENT_MODULE

Defined in header `hpx/components.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

Warning: doxygenfunction: Cannot find function “HPX_REGISTER_COMPONENT_MODULE” in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`

runtime_local

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::get_thread_name

Defined in header `hpx/runtime.hpp`⁹¹⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

`std::string hpx::get_thread_name()`

Return the name of the calling thread.

This function returns the name of the calling thread. This name uniquely identifies the thread in the context of HPX. If the function is called while no HPX runtime system is active, the result will be “<unknown>”.

hpx::register_thread

Defined in header `hpx/runtime.hpp`⁹¹⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::unregister_thread`
- `hpx::get_os_thread_data`
- `hpx::enumerate_os_threads`
- `hpx::get_runtime_instance_number`
- `hpx::register_on_exit`
- `hpx::is_starting`
- `hpx::tolerate_node_faults`
- `hpx::is_running`
- `hpx::is_stopped`
- `hpx::is_stopped_or_shutting_down`
- `hpx::get_num_worker_threads`
- `hpx::get_system_uptime`

⁹¹⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

⁹¹⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

bool **hpx::register_thread**(runtime *rt, char const *name, error_code &ec = throws)

Register the current kernel thread with HPX, this should be done once for each external OS-thread intended to invoke HPX functionality. Calling this function more than once will return false.

hpx::unregister_thread

Defined in header [hpx/runtime.hpp](#)⁹¹⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::register_thread*
- *hpx::get_os_thread_data*
- *hpx::enumerate_os_threads*
- *hpx::get_runtime_instance_number*
- *hpx::register_on_exit*
- *hpx::is_starting*
- *hpx::tolerate_node_faults*
- *hpx::is_running*
- *hpx::is_stopped*
- *hpx::is_stopped_or_shutting_down*
- *hpx::get_num_worker_threads*
- *hpx::get_system_uptime*

void **hpx::unregister_thread**(runtime *rt)

Unregister the thread from HPX, this should be done once in the end before the external thread exists.

hpx::get_os_thread_data

Defined in header [hpx/runtime.hpp](#)⁹¹⁷.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::register_thread*
- *hpx::unregister_thread*
- *hpx::enumerate_os_threads*
- *hpx::get_runtime_instance_number*
- *hpx::register_on_exit*
- *hpx::is_starting*
- *hpx::tolerate_node_faults*
- *hpx::is_running*

⁹¹⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

⁹¹⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

- `hpx::is_stopped`
- `hpx::is_stopped_or_shutting_down`
- `hpx::get_num_worker_threads`
- `hpx::get_system_uptime`

runtime_local::os_thread_data **hpx::get_os_thread_data**(std::string const &label)

Access data for a given OS thread that was previously registered by `register_thread`. This function must be called from a thread that was previously registered with the runtime.

hpx::enumerate_os_threads

Defined in header [hpx/runtime.hpp](#)⁹¹⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::register_thread`
- `hpx::unregister_thread`
- `hpx::get_os_thread_data`
- `hpx::get_runtime_instance_number`
- `hpx::register_on_exit`
- `hpx::is_starting`
- `hpx::tolerate_node_faults`
- `hpx::is_running`
- `hpx::is_stopped`
- `hpx::is_stopped_or_shutting_down`
- `hpx::get_num_worker_threads`
- `hpx::get_system_uptime`

bool **hpx::enumerate_os_threads**(hpx::function<bool(os_thread_data const&)> const &f)

Enumerate all OS threads that have registered with the runtime.

hpx::get_runtime_instance_number

Defined in header [hpx/runtime.hpp](#)⁹¹⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::register_thread`
- `hpx::unregister_thread`
- `hpx::get_os_thread_data`
- `hpx::enumerate_os_threads`

⁹¹⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

⁹¹⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

- `hpx::register_on_exit`
- `hpx::is_starting`
- `hpx::tolerate_node_faults`
- `hpx::is_running`
- `hpx::is_stopped`
- `hpx::is_stopped_or_shutting_down`
- `hpx::get_num_worker_threads`
- `hpx::get_system_uptime`

`std::size_t hpx::get_runtime_instance_number()`

Return the runtime instance number associated with the runtime instance the current thread is running in.

`hpx::register_on_exit`

Defined in header `hpx/runtime.hpp`⁹²⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::register_thread`
- `hpx::unregister_thread`
- `hpx::get_os_thread_data`
- `hpx::enumerate_os_threads`
- `hpx::get_runtime_instance_number`
- `hpx::is_starting`
- `hpx::tolerate_node_faults`
- `hpx::is_running`
- `hpx::is_stopped`
- `hpx::is_stopped_or_shutting_down`
- `hpx::get_num_worker_threads`
- `hpx::get_system_uptime`

`bool hpx::register_on_exit(hpx::function<void()> const&)`

Register a function to be called during system shutdown.

⁹²⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

hpx::is_starting

Defined in header [hpx/runtime.hpp](#)⁹²¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::register_thread*
- *hpx::unregister_thread*
- *hpx::get_os_thread_data*
- *hpx::enumerate_os_threads*
- *hpx::get_runtime_instance_number*
- *hpx::register_on_exit*
- *hpx::tolerate_node_faults*
- *hpx::is_running*
- *hpx::is_stopped*
- *hpx::is_stopped_or_shutting_down*
- *hpx::get_num_worker_threads*
- *hpx::get_system_uptime*

bool **hpx::is_starting()**

Test whether the runtime system is currently being started.

This function returns whether the runtime system is currently being started or not, e.g. whether the current state of the runtime system is *hpx::state::startup*

Note: This function needs to be executed on a HPX-thread. It will return false otherwise.

hpx::tolerate_node_faults

Defined in header [hpx/runtime.hpp](#)⁹²².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::register_thread*
- *hpx::unregister_thread*
- *hpx::get_os_thread_data*
- *hpx::enumerate_os_threads*
- *hpx::get_runtime_instance_number*
- *hpx::register_on_exit*
- *hpx::is_starting*

⁹²¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

⁹²² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

- `hpx::is_running`
- `hpx::is_stopped`
- `hpx::is_stopped_or_shutting_down`
- `hpx::get_num_worker_threads`
- `hpx::get_system_uptime`

bool `hpx::tolerate_node_faults()`

Test if HPX runs in fault-tolerant mode.

This function returns whether the runtime system is running in fault-tolerant mode

`hpx::is_running`

Defined in header `hpx/runtime.hpp`⁹²³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::register_thread`
- `hpx::unregister_thread`
- `hpx::get_os_thread_data`
- `hpx::enumerate_os_threads`
- `hpx::get_runtime_instance_number`
- `hpx::register_on_exit`
- `hpx::is_starting`
- `hpx::tolerate_node_faults`
- `hpx::is_stopped`
- `hpx::is_stopped_or_shutting_down`
- `hpx::get_num_worker_threads`
- `hpx::get_system_uptime`

bool `hpx::is_running()`

Test whether the runtime system is currently running.

This function returns whether the runtime system is currently running or not, e.g. whether the current state of the runtime system is `hpx::state::running`

Note: This function needs to be executed on a HPX-thread. It will return false otherwise.

⁹²³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

hpx::is_stopped

Defined in header [hpx/runtime.hpp](#)⁹²⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::register_thread*
- *hpx::unregister_thread*
- *hpx::get_os_thread_data*
- *hpx::enumerate_os_threads*
- *hpx::get_runtime_instance_number*
- *hpx::register_on_exit*
- *hpx::is_starting*
- *hpx::tolerate_node_faults*
- *hpx::is_running*
- *hpx::is_stopped_or_shutting_down*
- *hpx::get_num_worker_threads*
- *hpx::get_system_uptime*

bool **hpx::is_stopped()**

Test whether the runtime system is currently stopped.

This function returns whether the runtime system is currently stopped or not, e.g. whether the current state of the runtime system is *hpx::state::stopped*

Note: This function needs to be executed on a HPX-thread. It will return false otherwise.

hpx::is_stopped_or_shutting_down

Defined in header [hpx/runtime.hpp](#)⁹²⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::register_thread*
- *hpx::unregister_thread*
- *hpx::get_os_thread_data*
- *hpx::enumerate_os_threads*
- *hpx::get_runtime_instance_number*
- *hpx::register_on_exit*
- *hpx::is_starting*

⁹²⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

⁹²⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

- `hpx::tolerate_node_faults`
- `hpx::is_running`
- `hpx::is_stopped`
- `hpx::get_num_worker_threads`
- `hpx::get_system_uptime`

bool `hpx::is_stopped_or_shutting_down()`

Test whether the runtime system is currently being shut down.

This function returns whether the runtime system is currently being shut down or not, e.g. whether the current state of the runtime system is `hpx::state::stopped` or `hpx::state::shutdown`

Note: This function needs to be executed on a HPX-thread. It will return false otherwise.

`hpx::get_num_worker_threads`

Defined in header `hpx/runtime.hpp`⁹²⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::register_thread`
- `hpx::unregister_thread`
- `hpx::get_os_thread_data`
- `hpx::enumerate_os_threads`
- `hpx::get_runtime_instance_number`
- `hpx::register_on_exit`
- `hpx::is_starting`
- `hpx::tolerate_node_faults`
- `hpx::is_running`
- `hpx::is_stopped`
- `hpx::is_stopped_or_shutting_down`
- `hpx::get_system_uptime`

`std::size_t hpx::get_num_worker_threads()`

Return the number of worker OS- threads used to execute HPX threads.

This function returns the number of OS-threads used to execute HPX threads. If the function is called while no HPX runtime system is active, it will return zero.

⁹²⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

hpx::get_system_uptime

Defined in header [hpx/runtime.hpp](#)⁹²⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::register_thread`
- `hpx::unregister_thread`
- `hpx::get_os_thread_data`
- `hpx::enumerate_os_threads`
- `hpx::get_runtime_instance_number`
- `hpx::register_on_exit`
- `hpx::is_starting`
- `hpx::tolerate_node_faults`
- `hpx::is_running`
- `hpx::is_stopped`
- `hpx::is_stopped_or_shutting_down`
- `hpx::get_num_worker_threads`

`std::uint64_t hpx::get_system_uptime()`

Return the system uptime measure on the thread executing this call.

This function returns the system uptime measured in nanoseconds for the thread executing this call. If the function is called while no HPX runtime system is active, it will return zero.

hpx::shutdown_function_type

Defined in header [hpx/runtime.hpp](#)⁹²⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::register_pre_shutdown_function`
- `hpx::register_shutdown_function`

using `hpx::shutdown_function_type = hpx::move_only_function<void()>`

The type of the function which is registered to be executed as a shutdown or pre-shutdown function.

⁹²⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

⁹²⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

hpx::register_pre_shutdown_function

Defined in header [hpx/runtime.hpp](#)⁹²⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::shutdown_function_type`
- `hpx::register_shutdown_function`

void **hpx::register_pre_shutdown_function**(*shutdown_function_type* f)

Add a function to be executed by a HPX thread during `hpx::finalize()` but guaranteed before any shutdown function is executed (system-wide)

Any of the functions registered with `register_pre_shutdown_function` are guaranteed to be executed by an HPX thread during the execution of `hpx::finalize()` before any of the registered shutdown functions are executed (see: `hpx::register_shutdown_function()`).

See also:

`hpx::register_shutdown_function()`

Note: If this function is called while the pre-shutdown functions are being executed, or after that point, it will raise an `invalid_status` exception.

Parameters

f – [in] The function to be registered to run by an HPX thread as a pre-shutdown function.

hpx::register_shutdown_function

Defined in header [hpx/runtime.hpp](#)⁹³⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::shutdown_function_type`
- `hpx::register_pre_shutdown_function`

void **hpx::register_shutdown_function**(*shutdown_function_type* f)

Add a function to be executed by a HPX thread during `hpx::finalize()` but guaranteed after any pre-shutdown function is executed (system-wide)

Any of the functions registered with `register_shutdown_function` are guaranteed to be executed by an HPX thread during the execution of `hpx::finalize()` after any of the registered pre-shutdown functions are executed (see: `hpx::register_pre_shutdown_function()`).

See also:

`hpx::register_pre_shutdown_function()`

⁹²⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

⁹³⁰ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

Note: If this function is called while the shutdown functions are being executed, or after that point, it will raise an `invalid_status` exception.

Parameters

f – [in] The function to be registered to run by an HPX thread as a shutdown function.

hpx/runtime_local/termination_detection.hpp

Defined in header `hpx/runtime_local/termination_detection.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **local**

Functions

void **termination_detection()**

Wait for all local HPX threads to complete execution.

This function blocks the calling thread until all HPX worker threads on the current locality have completed their work and become idle. It performs local termination detection by waiting for the thread manager to drain all pending tasks.

Example:

```
#include <hpx/hpx_init.hpp>
#include <hpx/runtime_local/termination_detection.hpp>

int hpx_main()
{
    // Launch some asynchronous work
    for (int i = 0; i < 100; ++i)
    {
        hpx::post([]{ /* do work */ });
    }

    // Wait for all local threads to complete
    hpx::local::termination_detection();

    return hpx::finalize();
}
```

Note: This function should be called from an HPX thread or after the HPX runtime has been initialized.

Throws

hpx::exception – if called when the runtime is not in a valid state (e.g., before initialization or after shutdown).

bool **termination_detection**(*hpx::chrono::steady_duration* const &timeout)

Wait for all local HPX threads to complete with a timeout.

This function blocks the calling thread until either all HPX worker threads have completed their work, or the specified timeout duration has elapsed.

See also:

termination_detection()

Example:

```
#include <hpx/hpx_init.hpp>
#include <hpx/runtime_local/termination_detection.hpp>
#include <chrono>

int hpx_main()
{
    // Launch some work
    hpx::post([]{ /* long running task */ });

    // Wait up to 5 seconds
    if (!hpx::local::termination_detection(std::chrono::seconds(5)))
    {
        std::cerr << "Warning: Work did not complete within timeout\n";
        // Implement fallback strategy
    }

    return hpx::finalize();
}
```

Parameters

timeout – Maximum duration to wait for termination. The function will return false if this duration elapses before all threads complete.

Throws

hpx::exception – if called when the runtime is not in a valid state.

Returns

true if all threads completed before the timeout, false if the timeout elapsed.

bool **termination_detection**(*hpx::chrono::steady_time_point* const &deadline)

Wait for all local HPX threads to complete until a deadline.

This function blocks the calling thread until either all HPX worker threads have completed their work, or the specified deadline time point is reached.

See also:

termination_detection(std::chrono::duration<double>)

Example:

```

#include <hpx/hpx_init.hpp>
#include <hpx/runtime_local/termination_detection.hpp>
#include <chrono>

int hpx_main()
{
    auto deadline = std::chrono::steady_clock::now() +
        std::chrono::seconds(10);

    hpx::post([]{ /* work */ });

    if (!hpx::local::termination_detection(deadline))
    {
        std::cerr << "Deadline reached\n";
    }

    return hpx::finalize();
}

```

Parameters

deadline – Absolute time point when waiting should stop. The function will return false if this time is reached before all threads complete.

Throws

hpx::exception – if called when the runtime is not in a valid state.

Returns

true if all threads completed before the deadline, false if the deadline was reached.

bool **termination_detection**(*hpx::stop_token* stop_token, *hpx::chrono::steady_duration* const &timeout = *hpx::chrono::steady_duration((hpx::chrono::steady_clock::duration::max)())*)

Wait for all local HPX threads with cancellation support.

This function blocks the calling thread until all HPX worker threads have completed, the timeout elapses, or a stop is requested via the stop_token. This enables cooperative cancellation of the wait operation.

See also:

termination_detection(std::chrono::duration<double>)

Example:

```

#include <hpx/hpx_init.hpp>
#include <hpx/runtime_local/termination_detection.hpp>
#include <hpx/stop_token.hpp>
#include <chrono>

int hpx_main()
{
    hpx::stop_source stop_src;

    // In shutdown handler
    hpx::thread shutdown_thread([&stop_src]() {

```

(continues on next page)

(continued from previous page)

```

        hpx::this_thread::sleep_for(std::chrono::seconds(30));
        stop_src.request_stop();
    });

    hpx::post([]{ /* work */ });

    // Wait with cancellation support
    bool completed = hpx::local::termination_detection(
        stop_src.get_token(),
        std::chrono::minutes(1)
    );

    if (!completed)
    {
        std::cerr << "Cancelled or timed out\n";
    }

    shutdown_thread.join();
    return hpx::finalize();
}

```

Parameters

- **stop_token** – Token that can be used to request cancellation of the wait operation.
- **timeout** – Maximum duration to wait. Defaults to maximum duration (effectively infinite).

Throws

hpx::exception – if called when the runtime is not in a valid state.

Returns

true if all threads completed, false if timeout elapsed or stop was requested.

hpx::get_locality_name

Defined in header `hpx/runtime.hpp`⁹³¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

std::string `hpx::get_locality_name()`

Return the name of the locality this function is called on.

This function returns the name for the locality on which this function is called.

See also:

future<std::string> get_locality_name(hpx::id_type const& id)

Returns

This function returns the name for the locality on which the function is called. The name is retrieved from the underlying networking layer and may be different for different parcelports.

⁹³¹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

```
future<std::string> hpx::get_locality_name(hpx::id_type const &id)
```

Return the name of the referenced locality.

This function returns a future referring to the name for the locality of the given id.

See also:

```
std::string get_locality_name()
```

Parameters

id – [in] The global id of the locality for which the name should be retrieved

Returns

This function returns the name for the locality of the given id. The name is retrieved from the underlying networking layer and may be different for different parcel ports.

hpx/runtime_local/report_error.hpp

Defined in header `hpx/runtime_local/report_error.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

```
void report_error(std::size_t num_thread, std::exception_ptr const &e)
```

The function `report_error` reports the given exception to the console.

```
void report_error(std::exception_ptr const &e)
```

The function `report_error` reports the given exception to the console.

hpx/runtime_local/component_startup_shutdown_base.hpp

Defined in header `hpx/runtime_local/component_startup_shutdown_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

```
struct component_startup_shutdown_base
```

#include <component_startup_shutdown_base.hpp> The `component_startup_shutdown_base` has to be used as a base class for all component startup/shutdown registries.

Public Functions

virtual `~component_startup_shutdown_base()` = default

virtual bool **get_startup_function**(*startup_function_type* &startup, bool &pre_startup) = 0

Return any startup function for this component.

Parameters

- **startup** – [in, out] The module is expected to fill this function object with a reference to a startup function. This function will be executed by the runtime system during system startup.
- **pre_startup** – [in, out] Will be set to true if the returned startup function is executed during the first round of calls.

Returns

Returns *true* if the parameter *startup* has been successfully initialized with the startup function.

virtual bool **get_shutdown_function**(*shutdown_function_type* &shutdown, bool &pre_shutdown) = 0

Return any startup function for this component.

Parameters

- **shutdown** – [in, out] The module is expected to fill this function object with a reference to a startup function. This function will be executed by the runtime system during system startup.
- **pre_shutdown** – [in, out] Will be set to true if the returned shutdown function is executed during the first round of calls.

Returns

Returns *true* if the parameter *shutdown* has been successfully initialized with the shutdown function.

hpx::get_locality_id

Defined in header `hpx/runtime.hpp`⁹³².

See *Public API* for a list of names and headers that are part of the public HPX API.

`std::uint32_t hpx::get_locality_id(error_code &ec = throws)`

Return the number of the locality this function is being called from.

This function returns the id of the current locality.

Note: The returned value is zero based and its maximum value is smaller than the overall number of localities the current application is running on (as returned by `get_num_localities()`).

Note: As long as *ec* is not pre-initialized to `hpx::throws` this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of `hpx::exception`.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

⁹³² <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx/runtime_local/get_worker_thread_num.hpp

Defined in header `hpx/runtime_local/get_worker_thread_num.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx::startup_function_type

Defined in header `hpx/runtime.hpp`⁹³³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::register_pre_startup_function*
- *hpx::register_startup_function*

using `hpx::startup_function_type = hpx::move_only_function<void()>`

The type of the function which is registered to be executed as a startup or pre-startup function.

hpx::register_pre_startup_function

Defined in header `hpx/runtime.hpp`⁹³⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::startup_function_type*
- *hpx::register_startup_function*

void `hpx::register_pre_startup_function`(*startup_function_type* f)

Add a function to be executed by a HPX thread before `hpx_main` but guaranteed before any startup function is executed (system-wide).

Any of the functions registered with *register_pre_startup_function* are guaranteed to be executed by an HPX thread before any of the registered startup functions are executed (see `hpx::register_startup_function()`).

This function is one of the few API functions which can be called before the runtime system has been fully initialized. It will automatically stage the provided startup function to the runtime system during its initialization (if necessary).

See also:

`hpx::register_startup_function()`

⁹³³ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

⁹³⁴ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

Note: If this function is called while the pre-startup functions are being executed or after that point, it will raise an `invalid_status` exception.

Parameters

f – [in] The function to be registered to run by an HPX thread as a pre-startup function.

`hpx::register_startup_function`

Defined in header `hpx/runtime.hpp`⁹³⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::startup_function_type`
- `hpx::register_pre_startup_function`

void `hpx::register_startup_function`(`startup_function_type f`)

Add a function to be executed by a HPX thread before `hpx_main` but guaranteed after any pre-startup function is executed (system-wide).

Any of the functions registered with `register_startup_function` are guaranteed to be executed by an HPX thread after any of the registered pre-startup functions are executed (see: `hpx::register_pre_startup_function()`), but before `hpx_main` is being called.

This function is one of the few API functions which can be called before the runtime system has been fully initialized. It will automatically stage the provided startup function to the runtime system during its initialization (if necessary).

See also:

`hpx::register_pre_startup_function()`

Note: If this function is called while the startup functions are being executed or after that point, it will raise an `invalid_status` exception.

Parameters

f – [in] The function to be registered to run by an HPX thread as a startup function.

⁹³⁵ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

hpx/runtime_local/service_executors.hpp

Defined in header `hpx/runtime_local/service_executors.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace execution
```

```
        namespace experimental
```

Enums

```
enum class service_executor_type : std::uint8_t
```

Values:

```
    enumerator io_thread_pool
```

Selects creating a service executor using the I/O pool of threads

```
    enumerator parcel_thread_pool
```

Selects creating a service executor using the parcel pool of threads

```
    enumerator timer_thread_pool
```

Selects creating a service executor using the timer pool of threads

```
    enumerator main_thread
```

Selects creating a service executor using the main thread

```
struct io_pool_executor : public hpx::execution::experimental::service_executor
```

Public Functions

```
io_pool_executor()
```

```
struct main_pool_executor : public hpx::execution::experimental::service_executor
```

Public Functions

main_pool_executor()

```
struct parcel_pool_executor : public hpx::execution::experimental::service_executor
```

Public Functions

explicit **parcel_pool_executor**(char const *name_suffix = "-tcp")

```
struct service_executor : public service_executor
```

Subclassed by *hpx::execution::experimental::io_pool_executor*,
hpx::execution::experimental::main_pool_executor, *hpx::execution::experimental::parcel_pool_executor*,
hpx::execution::experimental::timer_pool_executor

Public Functions

explicit **service_executor**(*service_executor_type* t, char const *name_suffix = "")

```
struct timer_pool_executor : public hpx::execution::experimental::service_executor
```

Public Functions

timer_pool_executor()

hpx/runtime_local/custom_exception_info.hpp

Defined in header `hpx/runtime_local/custom_exception_info.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

std::string **diagnostic_information**(exception_info const &xi)

Extract the diagnostic information embedded in the given exception and return a string holding a formatted message.

The function *hpx::diagnostic_information* can be used to extract all diagnostic information stored in the given exception instance as a formatted string. This simplifies debug output as it composes the diagnostics into one, easy to use function call. This includes the name of the source file and line number, the sequence number of the OS-thread and the HPX-thread id, the locality id and the stack backtrace of the point where the original exception was thrown.

See also:

hpx::get_error_locality_id(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_line_number()*,
hpx::get_error_os_thread(), *hpx::get_error_thread_id()*, *hpx::get_error_thread_description()*,
hpx::get_error(), *hpx::get_error_backtrace()*, *hpx::get_error_env()*, *hpx::get_error_what()*,
hpx::get_error_config(), *hpx::get_error_state()*

Parameters

xi – The parameter *e* will be inspected for all diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

std::bad_alloc – (if any of the required allocation operations fail)

Returns

The formatted string holding all the available diagnostic information stored in the given exception instance.

std::string **default_diagnostic_information**(*std::exception_ptr* const &*e*)

std::uint32_t **get_error_locality_id**(*hpx::exception_info* const &*xi*) noexcept

Return the locality id where the exception was thrown.

The function *hpx::get_error_locality_id* can be used to extract the diagnostic information element representing the locality id as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_line_number()*,
hpx::get_error_os_thread(), *hpx::get_error_thread_id()*, *hpx::get_error_thread_description()*,
hpx::get_error(), *hpx::get_error_backtrace()*, *hpx::get_error_env()*, *hpx::get_error_what()*,
hpx::get_error_config(), *hpx::get_error_state()*

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

nothing –

Returns

The locality id of the locality where the exception was thrown. If the exception instance does not hold this information, the function will return *hpx::naming::invalid_locality_id*.

std::string **get_error_host_name**(*hpx::exception_info* const &*xi*)

Return the hostname of the locality where the exception was thrown.

The function *hpx::get_error_host_name* can be used to extract the diagnostic information element representing the host name as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_process_id()*, *hpx::get_error_function_name()*,
hpx::get_error_file_name(), *hpx::get_error_line_number()*, *hpx::get_error_os_thread()*,
hpx::get_error_thread_id(), *hpx::get_error_thread_description()*, *hpx::get_error()*,
hpx::get_error_backtrace(), *hpx::get_error_env()*, *hpx::get_error_what()*, *hpx::get_error_config()*,
hpx::get_error_state()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

std::bad_alloc – (if one of the required allocations fails)

Returns

The hostname of the locality where the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

std::int64_t **get_error_process_id**(*hpx::exception_info* const &*xi*) noexcept

Return the (operating system) process id of the locality where the exception was thrown.

The function *hpx::get_error_process_id* can be used to extract the diagnostic information element representing the process id as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_function_name()*,
hpx::get_error_file_name(), *hpx::get_error_line_number()*, *hpx::get_error_os_thread()*,
hpx::get_error_thread_id(), *hpx::get_error_thread_description()*, *hpx::get_error()*,
hpx::get_error_backtrace(), *hpx::get_error_env()*, *hpx::get_error_what()*, *hpx::get_error_config()*,
hpx::get_error_state()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

nothing –

Returns

The process id of the OS-process which threw the exception. If the exception instance does not hold this information, the function will return 0.

std::string **get_error_env**(*hpx::exception_info* const &*xi*)

Return the environment of the OS-process at the point the exception was thrown.

The function *hpx::get_error_env* can be used to extract the diagnostic information element representing the environment of the OS-process collected at the point the exception was thrown.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_line_number()*,
hpx::get_error_os_thread(), *hpx::get_error_thread_id()*, *hpx::get_error_thread_description()*,
hpx::get_error(), *hpx::get_error_backtrace()*, *hpx::get_error_what()*, *hpx::get_error_config()*,
hpx::get_error_state()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

std::bad_alloc – (if one of the required allocations fails)

Returns

The environment from the point the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

std::string **get_error_backtrace**(*hpx::exception_info* const &xi)

Return the stack backtrace from the point the exception was thrown.

The function *hpx::get_error_backtrace* can be used to extract the diagnostic information element representing the stack backtrace collected at the point the exception was thrown.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_line_number()*,
hpx::get_error_os_thread(), *hpx::get_error_thread_id()*, *hpx::get_error_thread_description()*,
hpx::get_error(), *hpx::get_error_env()*, *hpx::get_error_what()*, *hpx::get_error_config()*,
hpx::get_error_state()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

std::bad_alloc – (if one of the required allocations fails)

Returns

The stack back trace from the point the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

std::size_t **get_error_os_thread**(*hpx::exception_info* const &xi) noexcept

Return the sequence number of the OS-thread used to execute HPX-threads from which the exception was thrown.

The function *hpx::get_error_os_thread* can be used to extract the diagnostic information element representing the sequence number of the OS-thread as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_line_number()*,
hpx::get_error_thread_id(), *hpx::get_error_thread_description()*, *hpx::get_error()*,
hpx::get_error_backtrace(), *hpx::get_error_env()*, *hpx::get_error_what()*, *hpx::get_error_config()*,
hpx::get_error_state()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

nothing –

Returns

The sequence number of the OS-thread used to execute the HPX-thread from which the exception was thrown. If the exception instance does not hold this information, the function will return *std::size(-1)*.

std::size_t **get_error_thread_id**(*hpx::exception_info* const &xi) noexcept

Return the unique thread id of the HPX-thread from which the exception was thrown.

The function *hpx::get_error_thread_id* can be used to extract the diagnostic information element representing the HPX-thread id as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_line_number()*,
hpx::get_error_os_thread(), *hpx::get_error_thread_description()*, *hpx::get_error()*,
hpx::get_error_backtrace(), *hpx::get_error_env()*, *hpx::get_error_what()*, *hpx::get_error_config()*,
hpx::get_error_state()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

nothing –

Returns

The unique thread id of the HPX-thread from which the exception was thrown. If the exception instance does not hold this information, the function will return *std::size_t(0)*.

std::string **get_error_thread_description**(*hpx::exception_info* const &xi)

Return any additionally available thread description of the HPX-thread from which the exception was thrown.

The function *hpx::get_error_thread_description* can be used to extract the diagnostic information element representing the additional thread description as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_line_number()*,
hpx::get_error_os_thread(), *hpx::get_error_thread_id()*, *hpx::get_error_backtrace()*,
hpx::get_error_env(), *hpx::get_error()*, *hpx::get_error_state()*, *hpx::get_error_what()*,
hpx::get_error_config()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

std::bad_alloc – (if one of the required allocations fails)

Returns

Any additionally available thread description of the HPX-thread from which the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

std::string **get_error_config**(*hpx::exception_info* const &xi)

Return the HPX configuration information point from which the exception was thrown.

The function *hpx::get_error_config* can be used to extract the HPX configuration information element representing the full HPX configuration information as stored in the given exception instance.

See also:

hpx::diagnostic_information(), *hpx::get_error_host_name()*, *hpx::get_error_process_id()*,
hpx::get_error_function_name(), *hpx::get_error_file_name()*, *hpx::get_error_line_number()*,
hpx::get_error_os_thread(), *hpx::get_error_thread_id()*, *hpx::get_error_backtrace()*,
hpx::get_error_env(), *hpx::get_error()*, *hpx::get_error_state()*, *hpx::get_error_what()*,
hpx::get_error_thread_description()

Parameters

xi – The parameter *e* will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: *hpx::exception_info*, *hpx::error_code*, *std::exception*, or *std::exception_ptr*.

Throws

std::bad_alloc – (if one of the required allocations fails)

Returns

Any additionally available HPX configuration information the point from which the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

std::string **get_error_state**(*hpx::exception_info* const &xi)

Return the HPX runtime state information at which the exception was thrown.

The function *hpx::get_error_state* can be used to extract the HPX runtime state information element representing the state the runtime system is currently in as stored in the given exception instance.

See also:

`hpx::diagnostic_information()`, `hpx::get_error_host_name()`, `hpx::get_error_process_id()`,
`hpx::get_error_function_name()`, `hpx::get_error_file_name()`, `hpx::get_error_line_number()`,
`hpx::get_error_os_thread()`, `hpx::get_error_thread_id()`, `hpx::get_error_backtrace()`,
`hpx::get_error_env()`, `hpx::get_error()`, `hpx::get_error_what()`, `hpx::get_error_thread_description()`

Parameters

xi – The parameter `e` will be inspected for the requested diagnostic information elements which have been stored at the point where the exception was thrown. This parameter can be one of the following types: `hpx::exception_info`, `hpx::error_code`, `std::exception`, or `std::exception_ptr`.

Throws

`std::bad_alloc` – (if one of the required allocations fails)

Returns

The point runtime state at the point at which the exception was thrown. If the exception instance does not hold this information, the function will return an empty string.

hpx/runtime_local/runtime_local.hpp

Defined in header `hpx/runtime_local/runtime_local.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

Functions

void **set_error_handlers**(`hpx::util::runtime_configuration const &cfg`)

class **runtime**

Public Types

using **notification_policy_type** = `threads::policies::callback_notifier`

Generate a new notification policy instance for the given thread name prefix

using **hpx_main_function_type** = `int()`

The `hpx_main_function_type` is the default function type usable as the main HPX thread function.

using **hpx_errorsink_function_type** = `void(std::uint32_t, std::string const&)`

Public Functions

virtual *notification_policy_type* **get_notification_policy**(char const *prefix,
runtime_local::os_thread_type type)

state **get_state**() const

void **set_state**(state s)

explicit **runtime**(hpx::util::runtime_configuration rtcfg, bool initialize)

Construct a new HPX runtime instance.

virtual **~runtime**()

The destructor makes sure all HPX runtime services are properly shut down before exiting.

void **on_exit**(hpx::function<void()> const &f)

Manage list of functions to call on exit.

void **starting**()

Manage runtime 'stopped' state.

void **stopping**()

Call all registered on_exit functions.

bool **stopped**() const

This accessor returns whether the runtime instance has been stopped.

hpx::util::runtime_configuration &**get_config**()

access configuration information

hpx::util::runtime_configuration const &**get_config**() const

std::size_t **get_instance_number**() const

util::thread_mapper &**get_thread_mapper**() const

Return a reference to the internal PAPI thread manager.

threads::topology const &**get_topology**() const

virtual int **run**(hpx::function<*hpx_main_function_type*> const &func)

Run the HPX runtime system, use the given function for the main *thread* and block waiting for all threads to finish.

Note: The parameter *func* is optional. If no function is supplied, the runtime system will simply wait for the shutdown action without explicitly executing any main thread.

Parameters

func – [in] This is the main function of an HPX application. It will be scheduled for execution by the thread manager as soon as the runtime has been initialized. This function is expected to expose an interface as defined by the typedef *hpx_main_function_type*. This parameter is optional and defaults to none main thread function, in which case all threads have to be scheduled explicitly.

Returns

This function will return the value as returned as the result of the invocation of the function object given by the parameter *func*.

virtual int **run**()

Run the HPX runtime system, initially use the given number of (OS) threads in the thread-manager and block waiting for all threads to finish.

Returns

This function will always return 0 (zero).

virtual void **rethrow_exception**()

Rethrow any stored exception (to be called after *stop()*)

virtual int **start**(*hpx::function<hpx_main_function_type>* const &func, bool blocking = false)

Start the runtime system.

Parameters

- **func** – [in] This is the main function of an HPX application. It will be scheduled for execution by the thread manager as soon as the runtime has been initialized. This function is expected to expose an interface as defined by the typedef *hpx_main_function_type*.
- **blocking** – [in] This allows to control whether this call blocks until the runtime system has been stopped. If this parameter is *true* the function runtime::start will call runtime::wait internally.

Returns

If a blocking is a true, this function will return the value as returned as the result of the invocation of the function object given by the parameter **func**. Otherwise, it will return zero.

virtual int **start**(bool blocking = false)

Start the runtime system.

Parameters

blocking – [in] This allows to control whether this call blocks until the runtime system has been stopped. If this parameter is *true* the function runtime::start will call runtime::wait internally .

Returns

If a blocking is a true, this function will return the value as returned as the result of the invocation of the function object given by the parameter **func**. Otherwise, it will return zero.

virtual int **wait**()

Wait for the shutdown action to be executed.

Returns

This function will return the value as returned as the result of the invocation of the function object given by the parameter **func**.

virtual void **stop**(bool blocking = true)

Initiate termination of the runtime system.

Parameters

blocking – [in] This allows to control whether this call blocks until the runtime system has been fully stopped. If this parameter is *false* then this call will initiate the stop action but will return immediately. Use a second call to stop with this parameter set to *true* to wait for all internal work to be completed.

virtual int **suspend**()

Suspend the runtime system.

virtual int **resume**()

Resume the runtime system.

virtual int **finalize**(double)

virtual bool **is_networking_enabled**()

Return true if networking is enabled.

virtual *hpx::threads::threadmanager* &**get_thread_manager**()

Allow access to the thread manager instance used by the HPX runtime.

virtual *std::string* **here**() const

Returns a string of the locality endpoints (usable in debug output)

virtual bool **report_error**(*std::size_t* num_thread, *std::exception_ptr* const &*e*, bool terminate_all = true)

Report a non-recoverable error to the runtime system.

Parameters

- **num_thread** – [in] The number of the operating system thread the error has been detected in.
- **e** – [in] This is an instance encapsulating an exception which lead to this function call.
- **terminate_all** – [in] signal whether all localities should be terminated

virtual bool **report_error**(*std::exception_ptr* const &*e*, bool terminate_all = true)

Report a non-recoverable error to the runtime system.

Note: This function will retrieve the number of the current shepherd thread and forward to the `report_error` function above.

Parameters

- **e** – [in] This is an instance encapsulating an exception which lead to this function call.
- **terminate_all** – [in] signal whether all localities should be terminated

virtual void **add_pre_startup_function**(*startup_function_type* *f*)

Add a function to be executed inside a HPX thread before `hpx_main` but guaranteed to be executed before any startup function registered with `add_startup_function`.

Note: The difference to a startup function is that all pre-startup functions will be (system-wide) executed before any startup function.

Parameters

f – The function ‘f’ will be called from inside a HPX thread before `hpx_main` is executed. This is very useful to set up the runtime environment of the application (install performance counters, etc.)

virtual void **add_startup_function**(*startup_function_type* *f*)

Add a function to be executed inside a HPX thread before `hpx_main`

Parameters

f – The function ‘f’ will be called from inside a HPX thread before `hpx_main` is executed. This is very useful to set up the runtime environment of the application (install performance counters, etc.)

virtual void **add_pre_shutdown_function**(*shutdown_function_type* *f*)

Add a function to be executed inside a HPX thread during `hpx::finalize`, but guaranteed before any of the shutdown functions is executed.

Note: The difference to a shutdown function is that all pre-shutdown functions will be (system-wide)

executed before any shutdown function.

Parameters

f – The function ‘f’ will be called from inside a HPX thread while `hpx::finalize` is executed. This is very useful to tear down the runtime environment of the application (uninstall performance counters, etc.)

virtual void **add_shutdown_function**(*shutdown_function_type* f)

Add a function to be executed inside a HPX thread during `hpx::finalize`

Parameters

f – The function ‘f’ will be called from inside a HPX thread while `hpx::finalize` is executed. This is very useful to tear down the runtime environment of the application (uninstall performance counters, etc.)

virtual *hpx::util::io_service_pool* ***get_thread_pool**(char const *name)

Access one of the internal thread pools (*io_service* instances) HPX is using to perform specific tasks. The three possible values for the argument **name** are “main_pool”, “io_pool”, “parcel_pool”, and “timer_pool”. For any other argument value the function will return zero.

virtual bool **register_thread**(char const *name, *std::size_t* num = 0, bool service_thread = true, *error_code* &ec = *throws*)

Register an external OS-thread with HPX.

This function should be called from any OS-thread which is external to HPX (not created by HPX), but which needs to access HPX functionality, such as setting a value on a promise or similar.

‘main’, ‘io’, ‘timer’, ‘parcel’, ‘worker’

Note: The function will compose a thread name of the form ‘<name>-thread#<num>’ which is used to register the thread. It is the user’s responsibility to ensure that each (composed) thread name is unique. HPX internally uses the following names for the threads it creates, do not reuse those:

Note: This function should be called for each thread exactly once. It will fail if it is called more than once.

Parameters

- **name** – [in] The name to use for thread registration.
- **num** – [in] The sequence number to use for thread registration. The default for this parameter is zero.
- **service_thread** – [in] The thread should be registered as a service thread. The default for this parameter is ‘true’. Any service threads will be pinned to cores not currently used by any of the HPX worker threads.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function will return whether the requested operation succeeded or not.

virtual bool **unregister_thread**()

Unregister an external OS-thread with HPX.

This function will unregister any external OS-thread from HPX.

Note: This function should be called for each thread exactly once. It will fail if it is called more than once. It will fail as well if the thread has not been registered before (see *register_thread*).

Returns

This function will return whether the requested operation succeeded or not.

virtual runtime_local::os_thread_data **get_os_thread_data**(std::string const &label) const

Access data for a given OS thread that was previously registered by *register_thread*.

virtual bool **enumerate_os_threads**(hpx::function<bool(runtime_local::os_thread_data const&)>
const &f) const

Enumerate all OS threads that have registered with the runtime.

notification_policy_type::on_startstop_type **on_start_func**() const

notification_policy_type::on_startstop_type **on_stop_func**() const

notification_policy_type::on_error_type **on_error_func**() const

notification_policy_type::on_startstop_type **on_start_func**(notification_policy_type::on_startstop_type&&)

notification_policy_type::on_startstop_type **on_stop_func**(notification_policy_type::on_startstop_type&&)

notification_policy_type::on_error_type **on_error_func**(notification_policy_type::on_error_type&&)

virtual std::uint32_t **get_locality_id**(error_code &ec) const

virtual std::size_t **get_num_worker_threads**() const

virtual std::uint32_t **get_num_localities**(hpx::launch::sync_policy, error_code &ec) const

virtual std::uint32_t **get_initial_num_localities**() const

virtual hpx::future<std::uint32_t> **get_num_localities**() const

virtual std::string **get_locality_name**() const

virtual std::uint32_t **assign_cores**(std::string const&, std::uint32_t)

virtual std::uint32_t **assign_cores**()

inline hpx::program_options::options_description const &**get_app_options**() const

inline void **set_app_options**(hpx::program_options::options_description const &app_options)

Public Static Functions

static std::uint64_t **get_system_uptime**()

Return the system uptime measure on the thread executing this call.

Protected Types

using **on_exit_type** = *std::vector<hpx::function<void()>>*

Protected Functions

explicit **runtime**(*hpx::util::runtime_configuration* rtcfg)

void **set_notification_policies**(*notification_policy_type* &¬ifier,
threads::detail::network_background_callback_type const
&network_background_callback)

void **init**()

Common initialization for different constructors.

void **init_global_data**()

threads::thread_result_type **run_helper**(*hpx::function<runtime::hpx_main_function_type>* const
&func, int &result, bool call_startup_functions, void
(*handle_print_bind)(*std::size_t*) = nullptr)

void **wait_helper**(*std::mutex* &mtx, *std::condition_variable* &cond, bool &running)

Protected Attributes

on_exit_type **on_exit_functions_**

mutable *std::mutex* **mtx_**

hpx::util::runtime_configuration **rtcfg_**

long **instance_number_**

std::unique_ptr<util::thread_mapper> **thread_support_**

threads::topology &**topology_**

std::atomic<state> **state_**

notification_policy_type::on_startstop_type **on_start_func_**

notification_policy_type::on_startstop_type **on_stop_func_**

notification_policy_type::on_error_type **on_error_func_**

int **result_**

```
std::exception_ptr exception_

notification_policy_type main_pool_notifier_

std::unique_ptr<util::io_service_pool> main_pool_

notification_policy_type notifier_

std::unique_ptr<hpx::threads::threadmanager> thread_manager_
```

Protected Static Functions

```
static void deinit_global_data()
```

Protected Static Attributes

```
static std::atomic<int> instance_number_counter_
```

Private Functions

```
void stop_helper(bool blocking, std::condition_variable &cond, std::mutex &mtx) const
```

Helper function to stop the runtime.

Parameters

- **blocking** – [in] This allows to control whether this call blocks until the runtime system has been fully stopped. If this parameter is *false* then this call will initiate the stop action but will return immediately. Use a second call to stop with this parameter set to *true* to wait for all internal work to be completed.
- **cond** –
- **mtx** –

```
void deinit_tss_helper(char const *context, std::size_t num) const
```

```
void init_tss_ex(char const *context, runtime_local::os_thread_type type, std::size_t  
local_thread_num, std::size_t global_thread_num, char const *pool_name, char  
const *postfix, bool service_thread, error_code &ec) const
```

```
void init_tss_helper(char const *context, runtime_local::os_thread_type type, std::size_t  
local_thread_num, std::size_t global_thread_num, char const *pool_name, char  
const *postfix, bool service_thread) const
```

```
void notify_finalize()
```

```
void wait_finalize()
```

```
void call_startup_functions(bool pre_startup)
```


Private Members

std::list<startup_function_type> **pre_startup_functions_**

std::list<startup_function_type> **startup_functions_**

std::list<shutdown_function_type> **pre_shutdown_functions_**

std::list<shutdown_function_type> **shutdown_functions_**

bool **stop_called_**

bool **stop_done_**

std::condition_variable **wait_condition_**

hpx::program_options::options_description **app_options_**

namespace **threads**

Functions

char const ***get_stack_size_name**(*std::ptrdiff_t* size)

Returns the stack size name.

Get the readable string representing the given stack size constant.

Parameters

size – this represents the stack size

std::ptrdiff_t **get_default_stack_size**()

Returns the default stack size.

Get the default stack size in bytes.

std::ptrdiff_t **get_stack_size**(*thread_stacksize* size)

Returns the stack size corresponding to the given stack size enumeration.

Get the stack size corresponding to the given stack size enumeration.

Parameters

size – this represents the stack size

namespace **util**

Functions

bool **retrieve_commandline_arguments**(*hpx::program_options::options_description* const &app_options, *hpx::program_options::variables_map* &vm)

bool **retrieve_commandline_arguments**(*std::string* const &app_name, *hpx::program_options::variables_map* &vm)

hpx/runtime_local/thread_pool_helpers.hpp

Defined in header `hpx/runtime_local/thread_pool_helpers.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **resource**

Functions

std::size_t **get_num_thread_pools**()

Return the number of thread pools currently managed by the *resource_partitioner*

std::size_t **get_num_threads**()

Return the number of threads in all thread pools currently managed by the *resource_partitioner*

std::size_t **get_num_threads**(*std::string* const &pool_name)

Return the number of threads in the given thread pool currently managed by the *resource_partitioner*

std::size_t **get_num_threads**(*std::size_t* pool_index)

Return the number of threads in the given thread pool currently managed by the *resource_partitioner*

std::size_t **get_pool_index**(*std::string* const &pool_name)

Return the internal index of the pool given its name.

std::string const &**get_pool_name**(*std::size_t* pool_index)

Return the name of the pool given its internal index.

threads::thread_pool_base &**get_thread_pool**(*std::string* const &pool_name)

Return the name of the pool given its name.

threads::thread_pool_base &**get_thread_pool**(*std::size_t* pool_index)

Return the thread pool given its internal index.

bool **pool_exists**(*std::string* const &pool_name)

Return true if the pool with the given name exists.

bool **pool_exists**(*std::size_t* pool_index)

Return true if the pool with the given index exists.

namespace **threads**

Functions

`std::int64_t get_thread_count(thread_schedule_state state = thread_schedule_state::unknown)`

The function `get_thread_count` returns the number of currently known threads.

Note: If `state == unknown` this function will not only return the number of currently existing threads, but will add the number of registered task descriptions (which have not been converted into threads yet).

Parameters

state – [in] This specifies the thread-state for which the number of threads should be retrieved.

`std::int64_t get_thread_count(thread_priority priority, thread_schedule_state state = thread_schedule_state::unknown)`

The function `get_thread_count` returns the number of currently known threads.

Note: If `state == unknown` this function will not only return the number of currently existing threads, but will add the number of registered task descriptions (which have not been converted into threads yet).

Parameters

- **priority** – [in] This specifies the thread-priority for which the number of threads should be retrieved.
- **state** – [in] This specifies the thread-state for which the number of threads should be retrieved.

`std::int64_t get_idle_core_count()`

The function `get_idle_core_count` returns the number of currently idling threads (cores).

`mask_type get_idle_core_mask()`

The function `get_idle_core_mask` returns a bit-mask representing the currently idling threads (cores).

`bool enumerate_threads(hpx::function<bool(thread_id_type)> const &f, thread_schedule_state state = thread_schedule_state::unknown)`

The function `enumerate_threads` will invoke the given function `f` for each thread with a matching thread state.

Parameters

- **f** – [in] The function which should be called for each matching thread. Returning ‘false’ from this function will stop the enumeration process.
- **state** – [in] This specifies the thread-state for which the threads should be enumerated.

hpx/runtime_local/thread_hooks.hpp

Defined in header `hpx/runtime_local/thread_hooks.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

threads::policies::callback_notifier::on_startstop_type **get_thread_on_start_func()**

Retrieve the currently installed start handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered start function chains into the previous one (see *register_thread_on_start_func*).

Note: This function can be called before the HPX runtime is initialized.

Returns

The currently installed error handler function.

threads::policies::callback_notifier::on_startstop_type **get_thread_on_stop_func()**

Retrieve the currently installed stop handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered stop function chains into the previous one (see *register_thread_on_stop_func*).

Note: This function can be called before the HPX runtime is initialized.

Returns

The currently installed error handler function.

threads::policies::callback_notifier::on_error_type **get_thread_on_error_func()**

Retrieve the currently installed error handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered error function chains into the previous one (see *register_thread_on_error_func*).

Note: This function can be called before the HPX runtime is initialized.

Returns

The currently installed error handler function.

threads::policies::callback_notifier::on_startstop_type **register_thread_on_start_func**(*threads::policies::callback_notifier::*
&&f)

Set the currently installed start handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered start function chains into the previous one (see *get_thread_on_start_func*).

Note: This function can be called before the HPX runtime is initialized.

Parameters

f – The function to install as the new start handler.

Returns

The previously registered function of this category. It is the user's responsibility to call that function if the callback is invoked by HPX.

threads::policies::callback_notifier::on_startstop_type **register_thread_on_stop_func**(*threads::policies::callback_notifier::on_startstop_type* &&f)

Set the currently installed stop handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered stop function chains into the previous one (see *get_thread_on_stop_func*).

Note: This function can be called before the HPX runtime is initialized.

Parameters

f – The function to install as the new stop handler.

Returns

The previously registered function of this category. It is the user's responsibility to call that function if the callback is invoked by HPX.

threads::policies::callback_notifier::on_error_type **register_thread_on_error_func**(*threads::policies::callback_notifier::on_error_type* &&f)

Set the currently installed error handler function. This is a function that will be called by HPX for each newly created thread that is made known to the runtime. HPX stores exactly one such function reference, thus the caller needs to make sure any newly registered error function chains into the previous one (see *get_thread_on_error_func*).

Note: This function can be called before the HPX runtime is initialized.

Parameters

f – The function to install as the new error handler.

Returns

The previously registered function of this category. It is the user's responsibility to call that function if the callback is invoked by HPX.

hpx::get_initial_num_localities

Defined in header [hpx/runtime.hpp](#)⁹³⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::get_num_localities*

std::uint32_t **hpx::get_initial_num_localities**()

Return the number of localities which were registered at startup for the running application.

The function *get_initial_num_localities* returns the number of localities which were connected to the console at application startup.

⁹³⁶ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

See also:

`hpx::find_all_localities`, `hpx::get_num_localities`

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

hpx::get_num_localities

Defined in header `hpx/runtime.hpp`⁹³⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::get_initial_num_localities`

`hpx::future<std::uint32_t> hpx::get_num_localities()`

Asynchronously return the number of localities which are currently registered for the running application.

The function `get_num_localities` asynchronously returns the number of localities currently connected to the console. The returned future represents the actual result.

See also:

`hpx::find_all_localities`, `hpx::get_num_localities`

Note: This function will return meaningful results only if called from an HPX-thread. It will return 0 otherwise.

`inline std::uint32_t hpx::get_num_localities(launch::sync_policy, error_code &ec = throws)`

Return the number of localities which are currently registered for the running application.

The function `get_num_localities` returns the number of localities currently connected to the console.

See also:

`hpx::find_all_localities`, `hpx::get_num_localities`

Note: This function will return meaningful results only if called from an HPX-thread. It will return 0 otherwise.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

⁹³⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

`std::uint32_t hpx::get_num_localities(hpx::launch::sync_policy, error_code &ec)`

Return the number of localities which are currently registered for the running application.

`hpx::future<std::uint32_t> hpx::get_num_localities(components::component_type t)`

Asynchronously return the number of localities which are currently registered for the running application.

The function `get_num_localities` asynchronously returns the number of localities currently connected to the console which support the creation of the given component type. The returned future represents the actual result.

See also:

`hpx::find_all_localities`, `hpx::get_num_localities`

Note: This function will return meaningful results only if called from an HPX-thread. It will return 0 otherwise.

Parameters

t – The component type for which the number of connected localities should be retrieved.

`std::uint32_t hpx::get_num_localities(launch::sync_policy, components::component_type t, error_code &ec = throws)`

Synchronously return the number of localities which are currently registered for the running application.

The function `get_num_localities` returns the number of localities currently connected to the console which support the creation of the given component type. The returned future represents the actual result.

See also:

`hpx::find_all_localities`, `hpx::get_num_localities`

Note: This function will return meaningful results only if called from an HPX-thread. It will return 0 otherwise.

Parameters

- **t** – The component type for which the number of connected localities should be retrieved.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to `hpx::throws` the function will throw on error instead.

`std::uint32_t hpx::get_num_localities(hpx::launch::sync_policy, components::component_type type, error_code &ec)`

hpx/runtime_local/get_os_thread_count.hpp

Defined in header `hpx/runtime_local/get_os_thread_count.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Functions

`std::size_t get_os_thread_count()`

Return the number of OS-threads running in the runtime instance the current HPX-thread is associated with.

`std::size_t get_os_thread_count(threads::executor const &exec)`

Return the number of worker OS- threads used by the given executor to execute HPX threads.

This function returns the number of cores used to execute HPX threads for the given executor. If the function is called while no HPX runtime system is active, it will return zero. If the executor is not valid, this function will fall back to retrieving the number of OS threads used by HPX.

Parameters

exec – [in] The executor to be used.

namespace **threads**

serialization

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/serialization/base_object.hpp

Defined in header `hpx/serialization/base_object.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **Derived**, typename **Base**>

struct **base_object_type**<*Derived*, *Base*, std::enable_if_t<hpx::traits::is_intrusive_polymorphic_v<*Derived*>>>

Public Functions

inline explicit constexpr **base_object_type**(*Derived* &d) noexcept

template<typename **Archive**>

inline void **save**(*Archive* &ar, unsigned) const

template<typename **Archive**>

inline void **load**(*Archive* &ar, unsigned)

HPX_SERIALIZATION_SPLIT_MEMBER()

Public Members

Derived &d_

namespace **hpx**

namespace **serialization**

Functions

```
template<typename Base, typename Derived>
constexpr base_object_type<Derived, Base> base_object(Derived &d) noexcept

template<typename D, typename B>
output_archive &operator<<(output_archive &ar, base_object_type<D, B> t)

template<typename D, typename B>
input_archive &operator>>(input_archive &ar, base_object_type<D, B> t)

template<typename D, typename B>
output_archive &operator&(output_archive &ar, base_object_type<D, B> t)

template<typename D, typename B>
input_archive &operator&(input_archive &ar, base_object_type<D, B> t)

template<typename Derived, typename Base, typename Enable = void>
struct base_object_type
```

Public Functions

```
inline explicit constexpr base_object_type(Derived &d) noexcept

template<typename Archive>
inline void serialize(Archive &ar, unsigned)
```

Public Members

Derived &d_

```
template<typename Derived,
typename Base> is_intrusive_polymorphic_v< Derived > > >
```

Public Functions

inline explicit constexpr **base_object_type**(Derived &d) noexcept

template<typename **Archive**>
inline void **save**(*Archive* &ar, unsigned) const

template<typename **Archive**>
inline void **load**(*Archive* &ar, unsigned)

HPX_SERIALIZATION_SPLIT_MEMBER()

Public Members

Derived &d_

synchronization

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::recursive_mutex

Defined in header [hpx/mutex.hpp](#)⁹³⁸.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

using **hpx::recursive_mutex** = detail::recursive_mutex_impl<>

hpx::mutex

Defined in header [hpx/mutex.hpp](#)⁹³⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::timed_mutex*

class **mutex**

mutex class is a synchronization primitive that can be used to protect shared data from being simultaneously accessed by multiple threads. *mutex* offers exclusive, non-recursive ownership semantics:

- A calling thread owns a mutex from the time that it successfully calls either *lock* or *try_lock* until it calls *unlock*.
- When a thread owns a *mutex*, all other threads will block (for calls to *lock*) or receive a *false* return value (for *try_lock*) if they attempt to claim ownership of the *mutex*.
- A calling thread must not own the *mutex* prior to calling *lock* or *try_lock*.

⁹³⁸ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/mutex.hpp

⁹³⁹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/mutex.hpp

The behavior of a program is undefined if a *mutex* is destroyed while still owned by any threads, or a thread terminates while owning a *mutex*. The *mutex* class satisfies all requirements of <a and <a.

`hpx::mutex` is neither copyable nor movable.

Subclassed by `hpx::timed_mutex`

`hpx::timed_mutex`

Defined in header `hpx/mutex.hpp`⁹⁴⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::mutex`

class **timed_mutex** : private `hpx::mutex`

The `timed_mutex` class is a synchronization primitive that can be used to protect shared data from being simultaneously accessed by multiple threads. In a manner similar to *mutex*, `timed_mutex` offers exclusive, non-recursive ownership semantics. In addition, `timed_mutex` provides the ability to attempt to claim ownership of a `timed_mutex` with a timeout via the member functions `try_lock_for()` and `try_lock_until()`. The `timed_mutex` class satisfies all requirements of <a and <a.

`hpx::timed_mutex` is neither copyable nor movable.

`hpx/synchronization/event.hpp`

Defined in header `hpx/synchronization/event.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **lcos**

namespace **local**

class **event**

#include <event.hpp> Event semaphores can be used for synchronizing multiple threads that need to wait for an event to occur. When the event occurs, all threads waiting for the event are woken up.

⁹⁴⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/mutex.hpp

Public Functions

inline **event**() noexcept
Construct a new event semaphore.

inline bool **occurred**() const noexcept
Check if the event has occurred.

inline void **wait**()
Wait for the event to occur.

inline void **set**()
Release all threads waiting on this semaphore.

inline void **reset**() noexcept
Reset the event.

Private Types

using **mutex_type** = *hpx::spinlock*

Private Functions

inline void **wait_locked**(*std::unique_lock*<*mutex_type*> &l)
inline void **set_locked**(*std::unique_lock*<*mutex_type*> l)

Private Members

mutex_type **mtx_**
This mutex protects the queue.

local::detail::condition_variable **cond_**

std::atomic<bool> **event_**

hpx::condition_variable

Defined in header [hpx/condition_variable.hpp](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/condition_variable.hpp)⁹⁴¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::condition_variable_any*
- *hpx::cv_status*

⁹⁴¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/condition_variable.hpp

class `condition_variable`

The `condition_variable` class is a synchronization primitive that can be used to block a thread, or multiple threads at the same time, until another thread both modifies a shared variable (the condition), and notifies the `condition_variable`.

The thread that intends to modify the shared variable has to

- a. acquire a `hpx::mutex` (typically via `std::lock_guard`)
- b. perform the modification while the lock is held
- c. execute `notify_one` or `notify_all` on the `condition_variable` (the lock does not need to be held for notification)

Even if the shared variable is atomic, it must be modified under the mutex in order to correctly publish the modification to the waiting thread. Any thread that intends to wait on `condition_variable` has to

- a. acquire a `std::unique_lock<hpx::mutex>`, on the same mutex as used to protect the shared variable
- b. either
 - i. check the condition, in case it was already updated and notified
 - ii. execute `wait`, `await_for`, or `wait_until`. The wait operations atomically release the mutex and suspend the execution of the thread.
 - iii. When the condition variable is notified, a timeout expires, or a spurious wakeup occurs, the thread is awakened, and the mutex is atomically reacquired. The thread should then check the condition and resume waiting if the wake-up was spurious. or
- i. use the predicated overload of `wait`, `wait_for`, and `wait_until`, which takes care of the three steps above.

`hpx::condition_variable` works only with `std::unique_lock<hpx::mutex>`. This restriction allows for maximal efficiency on some platforms. `hpx::condition_variable_any` provides a condition variable that works with any `<a` object, such as `std::shared_lock`.

Condition variables permit concurrent invocation of the `wait`, `wait_for`, `wait_until`, `notify_one` and `notify_all` member functions.

The class `hpx::condition_variable` is a `<a`. It is not `<a`, `<a`, `<a`, or `<a`.

`hpx::condition_variable_any`

Defined in header `hpx/condition_variable.hpp`⁹⁴².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::condition_variable`
- `hpx::cv_status`

class `condition_variable_any`

The `condition_variable_any` class is a generalization of `hpx::condition_variable`. Whereas `hpx::condition_variable` works only on `std::unique_lock<std::mutex>`, a `condition_variable_any` can operate on any lock that meets the `<a` requirements.

⁹⁴² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/condition_variable.hpp

See `hpx::condition_variable` for the description of the semantics of condition variables. It is not `<a`, `<a`, `<a`, or `<a`.

`hpx::cv_status`

Defined in header `hpx/condition_variable.hpp`⁹⁴³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::condition_variable`
- `hpx::condition_variable_any`

enum class `hpx::cv_status`

The scoped enumeration `hpx::cv_status` describes whether a timed wait returned because of timeout or not. `hpx::cv_status` is used by the `wait_for` and `wait_until` member functions of `hpx::condition_variable` and `hpx::condition_variable_any`.

Values:

enumerator **`no_timeout`**

The condition variable was awakened with `notify_all`, `notify_one`, or spuriously

enumerator **`timeout`**

the condition variable was awakened by timeout expiration

enumerator **`error`**

there was an error

`hpx::spinlock`

Defined in header `hpx/mutex.hpp`⁹⁴⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

using `hpx::spinlock` = detail::spinlock<true>

`spinlock` is a type of lock that causes a thread attempting to obtain it to check for its availability while waiting in a loop continuously.

⁹⁴³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/condition_variable.hpp

⁹⁴⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/mutex.hpp

hpx::once_flag

Defined in header `hpx/mutex.hpp`⁹⁴⁵.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::call_once`

struct `once_flag`

The class `hpx::once_flag` is a helper structure for `hpx::call_once`. An object of type `hpx::once_flag` that is passed to multiple calls to `hpx::call_once` allows those calls to coordinate with each other such that only one of the calls will actually run to completion. `hpx::once_flag` is neither copyable nor movable.

hpx::call_once

Defined in header `hpx/mutex.hpp`⁹⁴⁶.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::once_flag`

template<typename **F**, typename ...**Args**>

void `hpx::call_once`(`once_flag` &flag, *F* &&*f*, *Args*&&... args)

Executes the Callable object *f* exactly once, even if called concurrently, from several threads.

In detail:

- If, by the time `call_once` is called, flag indicates that *f* was already called, `call_once` returns right away (such a call to `call_once` is known as passive).
- Otherwise, `call_once` invokes `std::forward<Callable>(f)` with the arguments `std::forward<Args>(args)...` (as if by `hpx::invoke`). Unlike the `hpx::thread` constructor or `hpx::async`, the arguments are not moved or copied because they don't need to be transferred to another thread of execution. (such a call to `call_once` is known as active).
 - If that invocation throws an exception, it is propagated to the caller of `call_once`, and the flag is not flipped so that another call will be attempted (such a call to `call_once` is known as exceptional).
 - If that invocation returns normally (such a call to `call_once` is known as returning), the flag is flipped, and all other calls to `call_once` with the same flag are guaranteed to be passive. All active calls on the same flag form a single total order consisting of zero or more exceptional calls, followed by one returning call. The end of each active call synchronizes-with the next active call in that order. The return from the returning call synchronizes-with the returns from all passive calls on the same flag: this means that all concurrent calls to `call_once` are guaranteed to observe any side-effects made by the active call, with no additional synchronization.

Note: If concurrent calls to `call_once` pass different functions *f*, it is unspecified which *f* will be called. The selected function runs in the same thread as the `call_once` invocation it was passed to. Initialization of function-local statics is guaranteed to occur only once even when called from multiple threads, and may be more efficient than the equivalent code using `hpx::call_once`. The POSIX equivalent of this function is `pthread_once`.

⁹⁴⁵ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/mutex.hpp

⁹⁴⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/mutex.hpp

Parameters

- **flag** – an object, for which exactly one function gets executed
- **f** – Callable object to invoke
- **args** – arguments to pass to the function

Throws

`std::system_error` – if any condition prevents calls to *call_once* from executing as specified or any exception thrown by *f*

hpx::latch

Defined in header [hpx/latch.hpp](#)⁹⁴⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

class latch

Latches are a thread coordination mechanism that allow one or more threads to block until an operation is completed. An individual latch is a single-use object; once the operation has been completed, the latch cannot be reused.

Subclassed by `hpx::lcos::local::latch`

hpx::counting_semaphore

Defined in header [hpx/semaphore.hpp](#)⁹⁴⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

`template<std::ptrdiff_t LeastMaxValue = PTRDIFF_MAX>`

class counting_semaphore

A semaphore is a protected variable (an entity storing a value) or abstract data type (an entity grouping several variables that may or may not be numerical) which constitutes the classic method for restricting access to shared resources, such as shared memory, in a multiprogramming environment. Semaphores exist in many variants, though usually the term refers to a counting semaphore, since a binary semaphore is better known as a mutex. A counting semaphore is a counter for a set of available resources, rather than a locked/unlocked flag of a single resource. It was invented by Edsger Dijkstra. Semaphores are the classic solution to preventing race conditions in the dining philosophers problem, although they do not prevent resource deadlocks.

Counting semaphores can be used for synchronizing multiple threads as well: one thread waiting for several other threads to touch (signal) the semaphore, or several threads waiting for one other thread to touch this semaphore. Unlike `hpx::mutex` a `counting_semaphore` is not tied to threads of execution; acquiring a semaphore can occur on a different thread than releasing the semaphore, for example. All operations on `counting_semaphore` can be performed concurrently and without any relation to specific threads of execution, with the exception of the destructor which cannot be performed concurrently but can be performed on a different thread.

Semaphores are lightweight synchronization primitives used to constrain concurrent access to a shared resource. They are widely used to implement other synchronization primitives and, whenever both are applicable, can be more efficient than condition variables.

A counting semaphore is a semaphore object that models a non-negative resource count.

⁹⁴⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/latch.hpp>

⁹⁴⁸ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/semaphore.hpp

Class template `counting_semaphore` maintains an internal counter that is initialized when the semaphore is created. The counter is decremented when a thread acquires the semaphore, and is incremented when a thread releases the semaphore. If a thread tries to acquire the semaphore when the counter is zero, the thread will block until another thread increments the counter by releasing the semaphore.

Specializations of `hpx::counting_semaphore` are not `<a`, `<a`, `<a`, `<a`, or `<a`.

Note: `counting_semaphore`'s `try_acquire()` can spuriously fail.

Template Parameters

LeastMaxValue – `counting_semaphore` allows more than one concurrent access to the same resource, for at least *LeastMaxValue* concurrent accessors. As its name indicates, the *LeastMaxValue* is the minimum max value, not the actual max value. Thus `max()` can yield a number larger than *LeastMaxValue*.

`hpx::barrier`

Defined in header `hpx/barrier.hpp`⁹⁴⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

template<typename **OnCompletion** = detail::empty_oncompletion>

class **barrier**

A barrier is a thread coordination mechanism whose lifetime consists of a sequence of barrier phases, where each phase allows at most an expected number of threads to block until the expected number of threads arrive at the barrier. [Note: A barrier is useful for managing repeated tasks that are handled by multiple threads. - end note] Each barrier phase consists of the following steps:

- The expected count is decremented by each call to `arrive` or `arrive_and_drop`.
- When the expected count reaches zero, the phase completion step is run. For the specialization with the default value of the `CompletionFunction` template parameter, the completion step is run as part of the call to `arrive` or `arrive_and_drop` that caused the expected count to reach zero. For other specializations, the completion step is run on one of the threads that arrived at the barrier during the phase.
- When the completion step finishes, the expected count is reset to what was specified by the expected argument to the constructor, possibly adjusted by calls to `arrive_and_drop`, and the next phase starts.

Each phase defines a phase synchronization point. Threads that arrive at the barrier during the phase can block on the phase synchronization point by calling `wait`, and will remain blocked until the phase completion step is run. The phase completion step that is executed at the end of each phase has the following effects:

- Invokes the completion function, equivalent to `completion()`.
- Unblocks all threads that are blocked on the phase synchronization point.

The end of the completion step strongly happens before the returns from all calls that were unblocked by the completion step. For specializations that do not have the default value of the `CompletionFunction` template parameter, the behavior is undefined if any of the barrier object's member functions other than `wait` are called while the completion step is in progress.

⁹⁴⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/barrier.hpp>

Concurrent invocations of the member functions of `barrier`, other than its destructor, do not introduce data races. The member functions `arrive` and `arrive_and_drop` execute atomically.

`CompletionFunction` shall meet the `Cpp17MoveConstructible` (Table 28) and `Cpp17Destructible` (Table 32) requirements. `std::is_nothrow_invocable_v<CompletionFunction&>` shall be true.

The default value of the `CompletionFunction` template parameter is an unspecified type, such that, in addition to satisfying the requirements of `CompletionFunction`, it meets the `Cpp17DefaultConstructible` requirements (Table 27) and `completion()` has no effects.

`barrier::arrival_token` is an unspecified type, such that it meets the `Cpp17MoveConstructible` (Table 28), `Cpp17MoveAssignable` (Table 30), and `Cpp17Destructible` (Table 32) requirements.

`hpx::no_mutex`

Defined in header `hpx/mutex.hpp`⁹⁵⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

struct **no_mutex**

`no_mutex` class can be used in cases where the shared data between multiple threads can be accessed simultaneously without causing inconsistencies.

`hpx/synchronization/sliding_semaphore.hpp`

Defined in header `hpx/synchronization/sliding_semaphore.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

Typedefs

using **sliding_semaphore** = `sliding_semaphore_var<>`

template<typename **Mutex** = `hpx::spinlock`>

class **sliding_semaphore_var**

#include <sliding_semaphore.hpp> A semaphore is a protected variable (an entity storing a value) or abstract data type (an entity grouping several variables that may or may not be numerical) which constitutes the classic method for restricting access to shared resources, such as shared memory, in a multiprogramming environment. Semaphores exist in many variants, though usually the term refers to a counting semaphore, since a binary semaphore is better known as a mutex. A counting semaphore is a counter for a set of available resources, rather than a locked/unlocked flag of a single resource. It was invented by Edsger Dijkstra. Semaphores are the classic solution to preventing race conditions in the dining philosophers problem, although they do not prevent resource deadlocks.

Sliding semaphores can be used for synchronizing multiple threads as well: one thread waiting for several other threads to touch (signal) the semaphore, or several threads waiting for one other thread to touch this semaphore. The difference to a counting semaphore is that a sliding semaphore will not limit the number of threads which are allowed to proceed, but will make sure that the difference between the (arbitrary) number passed to `set` and `wait` does not exceed a given threshold.

⁹⁵⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/mutex.hpp

Public Functions

sliding_semaphore_var(*sliding_semaphore_var* const&) = delete

sliding_semaphore_var &**operator**=(*sliding_semaphore_var* const&) = delete

sliding_semaphore_var(*sliding_semaphore_var*&&) = delete

sliding_semaphore_var &**operator**=(*sliding_semaphore_var*&&) = delete

inline explicit **sliding_semaphore_var**(*std::int64_t* max_difference, *std::int64_t* lower_limit = 0)
noexcept

Construct a new sliding semaphore.

Parameters

- **max_difference** – [in] The max difference between the upper limit (as set by *wait()*) and the lower limit (as set by *signal()*) which is allowed without suspending any thread calling *wait()*.
- **lower_limit** – [in] The initial lower limit.

inline void **set_max_difference**(*std::int64_t* max_difference, *std::int64_t* lower_limit = 0) noexcept

Set/Change the difference that will cause the semaphore to trigger

Parameters

- **max_difference** – [in] The max difference between the upper limit (as set by *wait()*) and the lower limit (as set by *signal()*) which is allowed without suspending any thread calling *wait()*.
- **lower_limit** – [in] The initial lower limit.

inline void **wait**(*std::int64_t* upper_limit)

Wait for the semaphore to be signaled.

Parameters

- **upper_limit** – [in] The new upper limit. The calling thread will be suspended if the difference between this value and the largest lower_limit which was set by *signal()* is larger than the max_difference.

inline bool **try_wait**(*std::int64_t* upper_limit = 1)

Try to wait for the semaphore to be signaled.

Parameters

- **upper_limit** – [in] The new upper limit. The calling thread will be suspended if the difference between this value and the largest lower_limit which was set by *signal()* is larger than the max_difference.

Returns

The function returns true if the calling thread would not block if it was calling *wait()*.

inline void **signal**(*std::int64_t* lower_limit)

Signal the semaphore.

Parameters

- **lower_limit** – [in] The new lower limit. This will update the current lower limit of this semaphore. It will also re-schedule all suspended threads for which their associated upper limit is not larger than the lower limit plus the max_difference.

inline *std::int64_t* **signal_all**()

Private Types

```
using mutex_type = Mutex
```

```
using data_type = lcos::local::detail::sliding_semaphore_data<mutex_type>
```

Private Members

```
hpx::intrusive_ptr<data_type> data_
```

hpx::binary_semaphore

Defined in header [hpx/semaphore.hpp](#)⁹⁵¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

class **binary_semaphore**

A binary semaphore is a semaphore object that has only two states. `binary_semaphore` is an alias for specialization of `hpx::counting_semaphore` with *LeastMaxValue* being 1. HPX's implementation of `binary_semaphore` is more efficient than the default implementation of a counting semaphore with a unit resource count (`hpx::counting_semaphore`).

hpx::nostopstate

Defined in header [hpx/stop_token.hpp](#)⁹⁵².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::stop_callback`
- `hpx::stop_source`
- `hpx::stop_token`
- `hpx::nostopstate_t`

```
constexpr nostopstate_t hpx::nostopstate = { }
```

This is a constant object instance of `hpx::nostopstate_t` for use in constructing an empty `hpx::stop_source`, as a placeholder value in the non-default constructor.

⁹⁵¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/semaphore.hpp

⁹⁵² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/stop_token.hpp

hpx::stop_callback

Defined in header `hpx/stop_token.hpp`⁹⁵³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::nostopstate`
- `hpx::stop_source`
- `hpx::stop_token`
- `hpx::nostopstate_t`

template<typename **Callback**>

class **stop_callback**

hpx::stop_source

Defined in header `hpx/stop_token.hpp`⁹⁵⁴.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::nostopstate`
- `hpx::stop_callback`
- `hpx::stop_token`
- `hpx::nostopstate_t`

class **stop_source**

The `stop_source` class provides the means to issue a stop request, such as for `hpx::jthread` cancellation. A stop request made for one `stop_source` object is visible to all *stop_sources* and *hpx::stop_tokens* of the same associated stop-state; any `hpx::stop_callback(s)` registered for associated `hpx::stop_token(s)` will be invoked, and any *hpx::condition_variable_any* objects waiting on associated `hpx::stop_token(s)` will be awoken. Once a stop is requested, it cannot be withdrawn. Additional stop requests have no effect.

Note: For the purposes of `hpx::jthread` cancellation the `stop_source` object should be retrieved from the *hpx::jthread* object using `get_stop_source()`; or stop should be requested directly from the `hpx::jthread` object using `request_stop()`. This will then use the same associated stop-state as that passed into the `hpx::jthread`'s invoked function argument (i.e., the function being executed on its thread). For other uses, however, a `stop_source` can be constructed separately using the default constructor, which creates new stop-state.

⁹⁵³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/stop_token.hpp

⁹⁵⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/stop_token.hpp

hpx::stop_token

Defined in header [hpx/stop_token.hpp](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/stop_token.hpp)⁹⁵⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::nostopstate*
- *hpx::stop_callback*
- *hpx::stop_source*
- *hpx::nostopstate_t*

class **stop_token**

The `stop_token` class provides the means to check if a stop request has been made or can be made, for its associated `hpx::stop_source` object. It is essentially a thread-safe “view” of the associated stop-state. The *stop_token* can also be passed to the constructor of `hpx::stop_callback`, such that the callback will be invoked if the `stop_token`’s associated `hpx::stop_source` is requested to stop. And `stop_token` can be passed to the interruptible waiting functions of `hpx::condition_variable_any`, to interrupt the condition variable’s wait if stop is requested.

Note: A `stop_token` object is not generally constructed independently, but rather retrieved from a `hpx::jthread` or `hpx::stop_source`. This makes it share the same associated stop-state as the `hpx::jthread` or `hpx::stop_source`.

hpx::nostopstate_t

Defined in header [hpx/stop_token.hpp](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/stop_token.hpp)⁹⁵⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::nostopstate*
- *hpx::stop_callback*
- *hpx::stop_source*
- *hpx::stop_token*

struct **nostopstate_t**

Unit type intended for use as a placeholder in *hpx::stop_source* non-default constructor, that makes the constructed *hpx::stop_source* empty with no associated stop-state.

⁹⁵⁵ [http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/stop_token.](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/stop_token.hpp)

hpp

⁹⁵⁶ [http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/stop_token.](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/stop_token.hpp)

hpp

hpx::shared_mutex

Defined in header `hpx/shared_mutex.hpp`⁹⁵⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

using `hpx::shared_mutex = detail::shared_mutex<>`

The *shared_mutex* class is a synchronization primitive that can be used to protect shared data from being simultaneously accessed by multiple threads. In contrast to other mutex types which facilitate exclusive access, a *shared_mutex* has two levels of access:

- *shared* - several threads can share ownership of the same mutex.
- *exclusive* - only one thread can own the mutex.

If one thread has acquired the exclusive lock (through *lock*, *try_lock*), no other threads can acquire the lock (including the shared). If one thread has acquired the shared lock (through *lock_shared*, *try_lock_shared*), no other thread can acquire the exclusive lock, but can acquire the shared lock. Only when the exclusive lock has not been acquired by any thread, the shared lock can be acquired by multiple threads. Within one thread, only one lock (shared or exclusive) can be acquired at the same time. Shared mutexes are especially useful when shared data can be safely read by any number of threads simultaneously, but a thread may only write the same data when no other thread is reading or writing at the same time. The *shared_mutex* class satisfies all requirements of *SharedMutex* and *StandardLayoutType*.

tag_invoke

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx::invoke

Defined in header `hpx/functional.hpp`⁹⁵⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

```
template<typename F, typename ...Ts>
constexpr util::invoke_result_t<F, Ts&&...> hpx::invoke(F &&f, Ts&&... vs) noexcept(
    noexcept(HPX_INVOKE(HPX_FORWARD(F, f),
                        HPX_FORWARD(Ts, vs)...)))
```

Invokes the given callable object *f* with the content of the argument pack *vs*

Note: This function is similar to `std::invoke` (C++17)

Parameters

- **f** – Requires to be a callable object. If *f* is a member function pointer, the first argument in the pack will be treated as the callee (this object).
- **vs** – An arbitrary pack of arguments

⁹⁵⁷ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/shared_mutex.hpp

⁹⁵⁸ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

Throws

`std::exception` – like objects thrown by call to object `f` with the argument types vs.

Returns

The result of the callable object when it's called with the given argument types.

hpx::is_invocable

Defined in header `hpx/type_traits.hpp`⁹⁵⁹.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::is_invocable_r`

template<typename **F**, typename ...**Ts**>

struct **is_invocable** : public `hpx::detail::is_invocable_impl<F&&(Ts&&...)>`

Determines whether *F* can be invoked with the arguments *Ts*... Formally, determines whether

INVOKE(std::declval<F>(), std::declval<Ts>()...)

is well-formed when treated as an unevaluated operand, where *INVOKE* is the operation defined in *Callable*.

F, *R* and all types in the parameter pack *Ts* shall each be a complete type, (possibly cv-qualified) void, or an array of unknown bound. Otherwise, the behavior is undefined. If an instantiation of a template above depends, directly or indirectly, on an incomplete type, and that instantiation could yield a different result if that type were hypothetically completed, the behavior is undefined.

hpx::is_invocable_r

Defined in header `hpx/type_traits.hpp`⁹⁶⁰.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::is_invocable`

template<typename **R**, typename **F**, typename ...**Ts**>

struct **is_invocable_r** : public `hpx::detail::is_invocable_r_impl<F&&(Ts&&...), R>`

Determines whether *F* can be invoked with the arguments *Ts*... to yield a result that is convertible to *R* and the implicit conversion does not bind a reference to a temporary object (since C++23). If *R* is cv void, the result can be any type. Formally, determines whether

INVOKE<R>(std::declval<F>(), std::declval<Ts>()...)

is well-formed when treated as an unevaluated operand, where *INVOKE* is the operation defined in *Callable*. Determines whether *F* can be invoked with the arguments *Ts*... Formally, determines whether

⁹⁵⁹ [http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/type_traits.](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/type_traits.hpp)

hpx
⁹⁶⁰ [http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/type_traits.](http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/type_traits.hpp)
hpx

`INVOKE(std::declval<F>(), std::declval<Ts>()...)`

is well-formed when treated as an unevaluated operand, where *INVOKE* is the operation defined in *Callable*.

F, R and all types in the parameter pack Ts shall each be a complete type, (possibly cv-qualified) void, or an array of unknown bound. Otherwise, the behavior is undefined. If an instantiation of a template above depends, directly or indirectly, on an incomplete type, and that instantiation could yield a different result if that type were hypothetically completed, the behavior is undefined.

thread_pool_util

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/thread_pool_util/thread_pool_suspension_helpers.hpp

Defined in header `hpx/thread_pool_util/thread_pool_suspension_helpers.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **threads**

Functions

`hpx::future<void> resume_processing_unit(thread_pool_base &pool, std::size_t virt_core)`

Resumes the given processing unit. When the processing unit has been resumed the returned future will be ready.

Note: Can only be called from an HPX thread. Use `resume_processing_unit_cb` or to resume the processing unit from outside HPX. Requires that the pool has `threads::policies::enable_elasticity` set.

Parameters

- **pool** – [in] The thread pool to resume a processing unit on.
- **virt_core** – [in] The processing unit on the pool to be resumed. The processing units are indexed starting from 0.

Returns

A `future<void>` which is ready when the given processing unit has been resumed.

`void resume_processing_unit_cb(thread_pool_base &pool, hpx::function<void()> callback, std::size_t virt_core, error_code &ec = throws)`

Resumes the given processing unit. Takes a callback as a parameter which will be called when the processing unit has been resumed.

Note: Requires that the pool has `threads::policies::enable_elasticity` set.

Parameters

- **pool** – [in] The thread pool to resume a processing unit on.
- **callback** – [in] Callback which is called when the processing unit has been suspended.

- **virt_core** – [in] The processing unit to resume.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx::future<void> **suspend_processing_unit**(*thread_pool_base* &pool, *std::size_t* virt_core)

Suspends the given processing unit. When the processing unit has been suspended the returned future will be ready.

Note: Can only be called from an HPX thread. Use `suspend_processing_unit_cb` or `suspend_direct` to suspend the processing unit from outside HPX. Requires that the pool has `threads::policies::enable_elasticity` set.

Parameters

- **pool** – [in] The thread pool to suspend a processing unit from.
- **virt_core** – [in] The processing unit on the pool to be suspended. The processing units are indexed starting from 0.

Throws

hpx::exception – if called from outside the HPX runtime.

Returns

A *future<void>* which is ready when the given processing unit has been suspended.

void **suspend_processing_unit_cb**(*hpx::function<void()>* callback, *thread_pool_base* &pool, *std::size_t* virt_core, *error_code* &ec = *throws*)

Suspends the given processing unit. Takes a callback as a parameter which will be called when the processing unit has been suspended.

Note: Requires that the pool has `threads::policies::enable_elasticity` set.

Parameters

- **pool** – [in] The thread pool to suspend a processing unit from.
- **callback** – [in] Callback which is called when the processing unit has been suspended.
- **virt_core** – [in] The processing unit to suspend.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx::future<void> **resume_pool**(*thread_pool_base* &pool)

Resumes the thread pool. When the all OS threads on the thread pool have been resumed the returned future will be ready.

Note: Can only be called from an HPX thread. Use `resume_cb` or `resume_direct` to suspend the pool from outside HPX.

Parameters

pool – [in] The thread pool to resume.

Throws

hpx::exception – if called from outside the HPX runtime.

Returns

A *future<void>* which is ready when the thread pool has been resumed.

void **resume_pool_cb**(*thread_pool_base* &pool, *hpx::function<void()>* callback, *error_code* &ec = *throws*)

Resumes the thread pool. Takes a callback as a parameter which will be called when all OS threads on the thread pool have been resumed.

Parameters

- **pool** – [in] The thread pool to resume.
- **callback** – [in] called when the thread pool has been resumed.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

hpx::future<void> **suspend_pool**(*thread_pool_base* &pool)

Suspends the thread pool. When the all OS threads on the thread pool have been suspended the returned future will be ready.

Note: Can only be called from an HPX thread. Use `suspend_cb` or `suspend_direct` to suspend the pool from outside HPX. A thread pool cannot be suspended from an HPX thread running on the pool itself.

Parameters

pool – [in] The thread pool to suspend.

Throws

hpx::exception – if called from outside the HPX runtime.

Returns

A *future<void>* which is ready when the thread pool has been suspended.

void **suspend_pool_cb**(*thread_pool_base* &pool, *hpx::function<void()>* callback, *error_code* &ec = *throws*)

Suspends the thread pool. Takes a callback as a parameter which will be called when all OS threads on the thread pool have been suspended.

Note: A thread pool cannot be suspended from an HPX thread running on the pool itself.

Parameters

- **pool** – [in] The thread pool to suspend.
- **callback** – [in] called when the thread pool has been suspended.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if called from an HPX thread which is running on the pool itself.

thread_support

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::unlock_guard

Defined in header `hpx/mutex.hpp`⁹⁶¹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

template<typename **Lock**>

⁹⁶¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/mutex.hpp

class `unlock_guard`

The class `unlock_guard` is a mutex wrapper that provides a convenient mechanism for releasing a mutex for the duration of a scoped block.

`unlock_guard` performs the opposite functionality of `lock_guard`.

When a `lock_guard` object is created, it attempts to take ownership of the mutex it is given. When control leaves the scope in which the `lock_guard` object was created, the `lock_guard` is destructed and the mutex is released. Accordingly, when an `unlock_guard` object is created, it attempts to release the ownership of the mutex it is given. So, when control leaves the scope in which the `unlock_guard` object was created, the `unlock_guard` is destructed and the mutex is owned again. In this way, the mutex is unlocked in the constructor and locked in the destructor, so that one can have an unlocked section within a locked one.

Note: `unlock_guard` is non-copyable and non-movable.

Template Parameters

Lock – The type of the lockable object managed by the `unlock_guard`.

`hpx/thread_support/spinlock.hpp`

Defined in header `hpx/thread_support/spinlock.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

threading

See *Public API* for a list of names and headers that are part of the public *HPX* API.

`hpx::jthread`

Defined in header `hpx/jthread.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

class `jthread`

The class `jthread` represents a single thread of execution. It has the same general behavior as `hpx::thread`, except that `jthread` automatically rejoins on destruction, and can be cancelled/stopped in certain situations. Threads begin execution immediately upon construction of the associated thread object (pending any OS scheduling delays), starting at the top-level function provided as a constructor argument. The return value of the top-level function is ignored and if it terminates by throwing an exception, `hpx::terminate` is called. The top-level function may communicate its return value or an exception to the caller via `hpx::promise` or by modifying shared variables (which may require synchronization, see `hpx::mutex` and `hpx::atomic`). Unlike `hpx::thread`, the `jthread` logically holds an internal private member of type `hpx::stop_source`, which maintains a shared stop-state. The `jthread` constructor accepts a function that takes a `hpx::stop_token` as its first argument, which will be passed in by the `jthread` from its internal `stop_source`. This allows the function to check if stop has been requested during its

execution, and return if it has. `hpx::jthread` objects may also be in the state that does not represent any thread (after default construction, move from, detach, or join), and a thread of execution may be not associated with any `jthread` objects (after detach). No two `hpx::jthread` objects may represent the same thread of execution; `hpx::jthread` is not *CopyConstructible* or *CopyAssignable*, although it is *MoveConstructible* and *MoveAssignable*.

`hpx::thread`

Defined in header `hpx/thread.hpp`⁹⁶².

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::this_thread::yield`
- `hpx::this_thread::get_id`
- `hpx::this_thread::sleep_for`
- `hpx::this_thread::sleep_until`

class `thread`

The class `thread` represents a single thread of execution. Threads allow multiple functions to execute concurrently. Threads begin execution immediately upon construction of the associated thread object (pending any OS scheduling delays), starting at the top-level function provided as a constructor argument. The return value of the top-level function is ignored and if it terminates by throwing an exception, `hpx::terminate` is called. The top-level function may communicate its return value or an exception to the caller via `hpx::promise` or by modifying shared variables (which may require synchronization, see `hpx::mutex` and `hpx::atomic`) `hpx::thread` objects may also be in the state that does not represent any thread (after default construction, move from, detach, or join), and a thread of execution may not be associated with any thread objects (after detach). No two `hpx::thread` objects may represent the same thread of execution; `hpx::thread` is not *CopyConstructible* or *CopyAssignable*, although it is *MoveConstructible* and *MoveAssignable*.

`hpx::this_thread::yield`

Defined in header `hpx/thread.hpp`⁹⁶³.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::thread`
- `hpx::this_thread::get_id`
- `hpx::this_thread::sleep_for`
- `hpx::this_thread::sleep_until`

void `hpx::this_thread::yield()` noexcept

Provides a hint to the implementation to reschedule the execution of threads, allowing other threads to run.

Note: The exact behavior of this function depends on the implementation, in particular on the mechanics of the OS scheduler in use and the state of the system. For example, a first-in-first-out realtime scheduler (`SCHED_FIFO`)

⁹⁶² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/thread.hpp

⁹⁶³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/thread.hpp

in Linux) would suspend the current thread and put it on the back of the queue of the same-priority threads that are ready to run (and if there are no other threads at the same priority, yield has no effect).

`hpx::this_thread::get_id`

Defined in header `hpx/thread.hpp`⁹⁶⁴.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::thread`
- `hpx::this_thread::yield`
- `hpx::this_thread::sleep_for`
- `hpx::this_thread::sleep_until`

`thread::id` `hpx::this_thread::get_id()` noexcept

Returns the id of the current thread.

`hpx::this_thread::sleep_for`

Defined in header `hpx/thread.hpp`⁹⁶⁵.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::thread`
- `hpx::this_thread::yield`
- `hpx::this_thread::get_id`
- `hpx::this_thread::sleep_until`

inline void `hpx::this_thread::sleep_for`(`hpx::chrono::steady_duration` const &`rel_time`)

Blocks the execution of the current thread for at least the specified *rel_time*. This function may block for longer than *rel_time* due to scheduling or resource contention delays.

It is recommended to use a steady clock to measure the duration. If an implementation uses a system clock instead, the wait time may also be sensitive to clock adjustments.

Parameters

`rel_time` – time duration to sleep

⁹⁶⁴ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/thread.hpp

⁹⁶⁵ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/thread.hpp

hpx::this_thread::sleep_until

Defined in header `hpx/thread.hpp`⁹⁶⁶.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::thread`
- `hpx::this_thread::yield`
- `hpx::this_thread::get_id`
- `hpx::this_thread::sleep_for`

void `hpx::this_thread::sleep_until`(`hpx::chrono::steady_time_point` const &`abs_time`)

Blocks the execution of the current thread until specified *abs_time* has been reached.

It is recommended to use the clock tied to *abs_time*, in which case adjustments of the clock may be taken into account. Thus, the duration of the block might be more or less than `abs_time-Clock::now()` at the time of the call, depending on the direction of the adjustment and whether it is honored by the implementation. The function also may block until after *abs_time* has been reached due to process scheduling or resource contention delays.

Parameters

abs_time – absolute time to block until

threading_base

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/threading_base/thread_description.hpp

Defined in header `hpx/threading_base/thread_description.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

Functions

`std::ostream &operator<<`(`std::ostream&`, `thread_description` const&)

`std::string as_string`(`thread_description` const &`desc`)

`threads::thread_description get_thread_description`(`thread_id_type` const &`id`, `error_code` &`ec` = *throws*)

The function `get_thread_description` is part of the thread related API allows to query the description of one of the threads known to the thread-manager.

⁹⁶⁶ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/thread.hpp

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread being queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the description of the thread referenced by the *id* parameter. If the thread is not known to the thread-manager the return value will be the string “<unknown>”.

```
threads::thread_description set_thread_description(thread_id_type const &id,
                                                  threads::thread_description const &desc =
                                                  threads::thread_description(), error_code &ec
                                                  = throws)
```

```
threads::thread_description get_thread_lco_description(thread_id_type const &id, error_code
                                                         &ec = throws)
```

```
threads::thread_description set_thread_lco_description(thread_id_type const &id,
                                                         threads::thread_description const &desc
                                                         = threads::thread_description(),
                                                         error_code &ec = throws)
```

```
struct thread_description
```

Public Types

```
enum class data_type : std::uint8_t
```

Values:

```
enumerator description
```

```
enumerator address
```

Public Functions

```
thread_description() noexcept = default
```

```
inline constexpr thread_description(char const*) noexcept
```

```
inline explicit constexpr thread_description(std::string const&) noexcept
```

```
template<typename F, typename = std::enable_if_t<!std::is_same_v<F, thread_description> &&  
!traits::is_action_v<F>>>
```

```
inline explicit constexpr thread_description(F const&, char const* = nullptr) noexcept
```

```
template<typename Action, typename = std::enable_if_t<traits::is_action_v<Action>>>
```

```
inline explicit constexpr thread_description(Action, char const* = nullptr) noexcept
```

```
inline explicit constexpr operator bool() const noexcept
```


Public Static Functions

```
static inline constexpr data_type kind() noexcept
static inline constexpr char const *get_description() noexcept
static inline constexpr std::size_t get_address() noexcept
static inline constexpr bool valid() noexcept
```

Private Functions

```
void init_from_alternative_name(char const *altname)
```

```
namespace util
```

Typedefs

```
using instead = hpx::threads::thread_description
```

hpx/threading_base/threading_base_fwd.hpp

Defined in header `hpx/threading_base/threading_base_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace threads
```

Functions

```
thread_data *get_self_id_data() noexcept
```

The function *get_self_id_data* returns the data of the HPX thread id associated with the current thread (or nullptr if the current thread is not a HPX thread).

```
thread_self &get_self()
```

The function *get_self* returns a reference to the (OS thread specific) self reference to the current HPX thread.

```
thread_self *get_self_ptr() noexcept
```

The function *get_self_ptr* returns a pointer to the (OS thread specific) self reference to the current HPX thread.

```
thread_self_impl_type *get_ctx_ptr()
```

The function *get_ctx_ptr* returns a pointer to the internal data associated with each coroutine.

```
thread_self *get_self_ptr_checked(error_code &ec = throws)
```

The function *get_self_ptr_checked* returns a pointer to the (OS thread specific) self reference to the current HPX thread.

thread_id_type **get_self_id()** noexcept

The function *get_self_id* returns the HPX thread id of the current thread (or zero if the current thread is not a HPX thread).

HPX_DEPRECATED_V (2, 0, "hpx::threads::get_outer_self_id is deprecated, use " "hpx::threads::get_self_id instead") inline thread_id_type get_outer_self_id() noexcept

The function *get_outer_self_id* returns the HPX thread id of the current outer thread (or zero if the current thread is not a HPX thread). This now always returns the same as *get_self_id*, even for directly executed threads.

thread_id_type **get_parent_id()** noexcept

The function *get_parent_id* returns the HPX thread id of the current thread's parent (or zero if the current thread is not a HPX thread).

Note: This function will return a meaningful value only if the code was compiled with `HPX_HAVE_THREAD_PARENT_REFERENCE` being defined.

std::size_t **get_parent_phase()** noexcept

The function *get_parent_phase* returns the HPX phase of the current thread's parent (or zero if the current thread is not a HPX thread).

Note: This function will return a meaningful value only if the code was compiled with `HPX_HAVE_THREAD_PARENT_REFERENCE` being defined.

std::ptrdiff_t **get_self_stacksize()** noexcept

The function *get_self_stacksize* returns the stack size of the current thread (or zero if the current thread is not a HPX thread).

thread_stacksize **get_self_stacksize_enum()** noexcept

The function *get_self_stacksize_enum* returns the stack size of the /.

std::uint32_t **get_parent_locality_id()** noexcept

The function *get_parent_locality_id* returns the id of the locality of the current thread's parent (or zero if the current thread is not a HPX thread).

Note: This function will return a meaningful value only if the code was compiled with `HPX_HAVE_THREAD_PARENT_REFERENCE` being defined.

std::uint64_t **get_self_component_id()** noexcept

The function *get_self_component_id* returns the lva of the component the current thread is acting on

Note: This function will return a meaningful value only if the code was compiled with `HPX_HAVE_THREAD_TARGET_ADDRESS` being defined.

namespace **policies**

namespace **tracing**

hpx/threading_base/register_thread.hpp

Defined in header `hpx/threading_base/register_thread.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

Functions

```
template<typename F>
thread_function_type make_thread_function(F &&f)
```

```
template<typename F, typename ...Ts>
thread_function_type make_thread_function_nullary(F &&f, Ts&&... ts)
```

```
void register_thread(threads::thread_init_data &data, threads::thread_pool_base *pool,
                    threads::thread_id_ref_type &id, error_code &ec = hpx::throws)
```

Create a new *thread* using the given data.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **data** – [in] The data to use for creating the thread.
- **pool** – [in] The thread pool to use for launching the work.
- **id** – [out] The id of the newly created thread (if applicable)
- **ec** – [in,out] This represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

invalid_status – if the runtime system has not been started yet.

Returns

This function will return the internal id of the newly created HPX-thread.

```
threads::thread_id_ref_type register_thread(threads::thread_init_data &data,
                                           threads::thread_pool_base *pool, error_code &ec =
                                           hpx::throws)
```

```
void register_thread(threads::thread_init_data &data, threads::thread_id_ref_type &id, error_code
                    &ec = throws)
```

Create a new *thread* using the given data on the same thread pool as the calling thread, or on the default thread pool if not on an HPX thread.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **data** – [in] The data to use for creating the thread.
- **id** – [out] The id of the newly created thread (if applicable)

- **ec** – [in,out] This represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

invalid_status – if the runtime system has not been started yet.

Returns

This function will return the internal id of the newly created HPX-thread.

threads::thread_id_ref_type **register_thread**(*threads::thread_init_data* &data, *error_code* &ec = *throws*)

thread_id_ref_type **register_work**(*threads::thread_init_data* &data, *threads::thread_pool_base* *pool, *error_code* &ec = *hpx::throws*)

Create a new work item using the given data.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **data** – [in] The data to use for creating the thread.
- **pool** – [in] The thread pool to use for launching the work.
- **ec** – [in,out] This represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

invalid_status – if the runtime system has not been started yet.

thread_id_ref_type **register_work**(*threads::thread_init_data* &data, *error_code* &ec = *throws*)

Create a new work item using the given data on the same thread pool as the calling thread, or on the default thread pool if not on an HPX thread.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **data** – [in] The data to use for creating the thread.
- **ec** – [in,out] This represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

invalid_status – if the runtime system has not been started yet.

hpx::get_worker_thread_num

Defined in header [hpx/runtime.hpp](#)⁹⁶⁷.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- *hpx::get_local_worker_thread_num*
- *hpx::get_thread_pool_num*

⁹⁶⁷ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

`std::size_t hpx::get_worker_thread_num()` noexcept

Return the number of the current OS-thread running in the runtime instance the current HPX-thread is executed with.

This function returns the zero based index of the OS-thread which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the overall number of OS-threads executed (as returned by `get_os_thread_count()`).

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

`std::size_t hpx::get_worker_thread_num(error_code &ec)` noexcept

Return the number of the current OS-thread running in the runtime instance the current HPX-thread is executed with.

This function returns the zero based index of the OS-thread which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the overall number of OS-threads executed (as returned by `get_os_thread_count()`). It will return -1 if the current thread is not a known thread or if the runtime is not in running state.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

Parameters

ec – [in,out] this represents the error status on exit (obsolete, ignored).

`hpx::get_local_worker_thread_num`

Defined in header `hpx/runtime.hpp`⁹⁶⁸.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::get_worker_thread_num`
- `hpx::get_thread_pool_num`

`std::size_t hpx::get_local_worker_thread_num()` noexcept

Return the number of the current OS-thread running in the current thread pool the current HPX-thread is executed with.

This function returns the zero based index of the OS-thread on the current thread pool which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the number of OS-threads executed on the current thread pool. It will return -1 if the current thread is not a known thread or if the runtime is not in running state.

⁹⁶⁸ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

`std::size_t hpx::get_local_worker_thread_num(error_code &ec) noexcept`

Return the number of the current OS-thread running in the current thread pool the current HPX-thread is executed with.

This function returns the zero based index of the OS-thread on the current thread pool which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the number of OS-threads executed on the current thread pool. It will return -1 if the current thread is not a known thread or if the runtime is not in running state.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

Parameters

ec – [in,out] this represents the error status on exit (obsolete, ignored).

`hpx::get_thread_pool_num`

Defined in header `hpx/runtime.hpp`⁹⁶⁹.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::get_worker_thread_num`
- `hpx::get_local_worker_thread_num`

`std::size_t hpx::get_thread_pool_num() noexcept`

Return the number of the current thread pool the current HPX-thread is executed with.

This function returns the zero based index of the thread pool which executes the current HPX-thread.

Note: The returned value is zero based and its maximum value is smaller than the number of thread pools started by the runtime. It will return -1 if the current thread pool is not a known thread pool or if the runtime is not in running state.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

`std::size_t hpx::get_thread_pool_num(error_code &ec) noexcept`

Return the number of the current thread pool the current HPX-thread is executed with.

This function returns the zero based index of the thread pool which executes the current HPX-thread.

⁹⁶⁹ <http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/full/include/include/hpx/runtime.hpp>

Note: The returned value is zero based and its maximum value is smaller than the number of thread pools started by the runtime. It will return -1 if the current thread pool is not a known thread pool or if the runtime is not in running state.

Note: This function needs to be executed on a HPX-thread. It will fail otherwise (it will return -1).

Parameters

ec – [in,out] this represents the error status on exit (obsolete, ignored).

hpx/threading_base/print.hpp

Defined in header `hpx/threading_base/print.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::annotated_function

Defined in header `hpx/functional.hpp`⁹⁷⁰.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
template<typename F>
constexpr F &&hpx::annotated_function(F &&f, char const* = nullptr) noexcept
```

Returns a function annotated with the given annotation.

Annotating includes setting the thread description per thread id.

Parameters

f – Function to annotate

```
template<typename F>
constexpr F &&hpx::annotated_function(F &&f, std::string const&) noexcept
```

hpx/threading_base/thread_helpers.hpp

Defined in header `hpx/threading_base/thread_helpers.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **this_thread**

⁹⁷⁰ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

Functions

```
threads::thread_restart_state suspend(threads::thread_schedule_state state, threads::thread_id_type
                                     nextid, threads::thread_description const &description =
                                     threads::thread_description("this_thread::suspend"),
                                     hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to the thread state passed as the parameter.

Note: Must be called from within a HPX-thread.

Throws

If – &ec != &throws, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

```
inline threads::thread_restart_state suspend(threads::thread_schedule_state state =
                                             threads::thread_schedule_state::pending,
                                             threads::thread_description const &description =
                                             threads::thread_description("this_thread::suspend"),
                                             hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to the thread state passed as the parameter.

Note: Must be called from within a HPX-thread.

Throws

If – &ec != &throws, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

```
threads::thread_restart_state suspend(hpx::chrono::steady_time_point const &abs_time,
                                       threads::thread_id_type id, threads::thread_description const
                                       &description =
                                       threads::thread_description("this_thread::suspend"),
                                       hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to *suspended* and schedules a wakeup for this threads at the given time.

Note: Must be called from within a HPX-thread.

Throws

If – &ec != &throws, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error

code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

```
inline threads::thread_restart_state suspend(hpx::chrono::steady_time_point const &abs_time,
                                             threads::thread_description const &description =
                                             threads::thread_description("this_thread::suspend"),
                                             hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to *suspended* and schedules a wakeup for this threads at the given time.

Note: Must be called from within a HPX-thread.

Throws

If – &ec != &throws, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

```
inline threads::thread_restart_state suspend(hpx::chrono::steady_duration const &rel_time,
                                             threads::thread_description const &description =
                                             threads::thread_description("this_thread::suspend"),
                                             hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to *suspended* and schedules a wakeup for this threads after the given duration.

Note: Must be called from within a HPX-thread.

Throws

If – &ec != &throws, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

```
inline threads::thread_restart_state suspend(hpx::chrono::steady_duration const &rel_time,
                                             threads::thread_id_type const &id,
                                             threads::thread_description const &description =
                                             threads::thread_description("this_thread::suspend"),
                                             hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to *suspended* and schedules a wakeup for this threads after the given duration.

Note: Must be called from within a HPX-thread.

Throws

If – &ec != &throws, never throws, but will set *ec* to an appropriate value when

an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

```
inline threads::thread_restart_state suspend(std::uint64_t ms, threads::thread_description const
&description =
threads::thread_description("this_thread::suspend"),
hpx::error_code &ec = hpx::throws)
```

The function *suspend* will return control to the thread manager (suspends the current thread). It sets the new state of this thread to *suspended* and schedules a wakeup for this threads after the given time (specified in milliseconds).

Note: Must be called from within a HPX-thread.

Throws

If – &ec != &throws, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

```
threads::thread_pool_base *get_pool(hpx::error_code &ec = hpx::throws)
```

Returns a pointer to the pool that was used to run the current thread

Throws

If – &ec != &throws, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

namespace **threads**

Functions

```
thread_state set_thread_state(thread_id_type const &id, thread_schedule_state state =
thread_schedule_state::pending, thread_restart_state stateex =
thread_restart_state::signaled, thread_priority priority =
thread_priority::normal, bool retry_on_active = true, hpx::error_code
&ec = hpx::throws)
```

Set the thread state of the *thread* referenced by the thread_id *id*.

Note: If the thread referenced by the parameter *id* is in *thread_state::active* state this function schedules a new thread which will set the state of the thread as soon as it is not active anymore. The function returns *thread_state::active* in this case.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread the state should be modified for.
- **state** – [in] The new state to be set for the thread referenced by the *id* parameter.
- **stateex** – [in] The new extended state to be set for the thread referenced by the *id* parameter.
- **priority** – [in]
- **retry_on_active** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the previous state of the thread referenced by the *id* parameter. It will return one of the values as defined by the *thread_state* enumeration. If the thread is not known to the thread-manager the return value will be *thread_state::unknown*.

```
thread_id_ref_type set_thread_state(thread_id_type const &id, hpx::chrono::steady_time_point
                                     const &abs_time, std::atomic<bool> *started,
                                     thread_schedule_state state = thread_schedule_state::pending,
                                     thread_restart_state stateex = thread_restart_state::timeout,
                                     thread_priority priority = thread_priority::normal, bool
                                     retry_on_active = true, hpx::error_code &ec = hpx::throws)
```

Set the thread state of the *thread* referenced by the thread_id *id*.

Set a timer to set the state of the given *thread* to the given new value after it expired (at the given time)

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread the state should be modified for.
- **abs_time** – [in] Absolute point in time for the new thread to be run
- **started** – [in,out] A helper variable allowing to track the state of the timer helper thread
- **state** – [in] The new state to be set for the thread referenced by the *id* parameter.
- **stateex** – [in] The new extended state to be set for the thread referenced by the *id* parameter.
- **priority** – [in]
- **retry_on_active** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

```
inline thread_id_ref_type set_thread_state(thread_id_type const &id,
                                             hpx::chrono::steady_time_point const &abs_time,
                                             thread_schedule_state state =
                                             thread_schedule_state::pending, thread_restart_state
                                             stateex = thread_restart_state::timeout, thread_priority
                                             priority = thread_priority::normal, bool retry_on_active
                                             = true, hpx::error_code& = throws)
```

```
inline thread_id_ref_type set_thread_state(thread_id_type const &id, hpx::chrono::steady_duration
                                             const &rel_time, thread_schedule_state state =
                                             thread_schedule_state::pending, thread_restart_state
                                             stateex = thread_restart_state::timeout, thread_priority
                                             priority = thread_priority::normal, bool retry_on_active
                                             = true, hpx::error_code &ec = hpx::throws)
```

Set the thread state of the *thread* referenced by the thread_id *id*.

Set a timer to set the state of the given *thread* to the given new value after it expired (after the given duration)

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread the state should be modified for.
- **rel_time** – [in] Time duration after which the new thread should be run
- **state** – [in] The new state to be set for the thread referenced by the *id* parameter.
- **stateex** – [in] The new extended state to be set for the thread referenced by the *id* parameter.
- **priority** – [in]
- **retry_on_active** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

```
thread_state get_thread_state(thread_id_type const &id, hpx::error_code &ec = hpx::throws)
                             noexcept
```

The function `get_thread_backtrace` is part of the thread related API allows to query the currently stored thread back trace (which is captured during thread suspension).

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*. The function `get_thread_state` is part of the thread related API. It queries the state of one of the threads known to the thread-manager.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread being queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.
- **id** – [in] The thread id of the thread the state should be modified for.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the currently captured stack back trace of the thread referenced by the *id* parameter. If the thread is not known to the thread-manager the return value will be the zero.

Returns

This function returns the thread state of the thread referenced by the *id* parameter. If the thread is not known to the thread-manager the return value will be *terminated*.

`std::size_t get_thread_phase(thread_id_type const &id, hpx::error_code &ec = hpx::throws)` noexcept

The function `get_thread_phase` is part of the thread related API. It queries the phase of one of the threads known to the thread-manager.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread the phase should be modified for.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the thread phase of the thread referenced by the *id* parameter. If the thread is not known to the thread-manager the return value will be *~0*.

`bool get_thread_interruption_enabled(thread_id_type const &id, hpx::error_code &ec = hpx::throws)`

Returns whether the given thread can be interrupted at this point.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread which should be queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if the given thread can be interrupted at this point in time. It will return *false* otherwise.

`bool set_thread_interruption_enabled(thread_id_type const &id, bool enable, hpx::error_code &ec = hpx::throws)`

Set whether the given thread can be interrupted at this point.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread which should receive the new value.
- **enable** – [in] This value will determine the new interruption enabled status for the given thread.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns the previous value of whether the given thread could have been interrupted.

```
bool get_thread_interruption_requested(thread_id_type const &id, hpx::error_code &ec =  
                                         hpx::throws)
```

Returns whether the given thread has been flagged for interruption.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread which should be queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Returns

This function returns *true* if the given thread was flagged for interruption. It will return *false* otherwise.

```
void interrupt_thread(thread_id_type const &id, bool flag, hpx::error_code &ec = hpx::throws)
```

Flag the given thread for interruption.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread which should be interrupted.
- **flag** – [in] The flag encodes whether the thread should be interrupted (if it is *true*), or 'uninterrupted' (if it is *false*).
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
inline void interrupt_thread(thread_id_type const &id, hpx::error_code &ec = hpx::throws)
```

```
void interruption_point(thread_id_type const &id, hpx::error_code &ec = hpx::throws)
```

Interrupt the current thread at this point if it was canceled. This will throw a *thread_interrupted* exception, which will cancel the thread.

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread which should be interrupted.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
threads::thread_priority get_thread_priority(thread_id_type const &id, hpx::error_code &ec =  
                                              hpx::throws) noexcept
```

Return priority of the given thread

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread whose priority is queried.

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

`std::ptrdiff_t get_stack_size(thread_id_type const &id, hpx::error_code &ec = hpx::throws)` noexcept

Return stack size of the given thread

Note: As long as *ec* is not pre-initialized to *hpx::throws* this function doesn't throw but returns the result code using the parameter *ec*. Otherwise, it throws an instance of *hpx::exception*.

Parameters

- **id** – [in] The thread id of the thread whose priority is queried.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

`threads::thread_pool_base *get_pool(thread_id_type const &id, hpx::error_code &ec = hpx::throws)`

Returns a pointer to the pool that was used to run the current thread

Throws

If – `&ec != &throws`, never throws, but will set *ec* to an appropriate value when an error occurs. Otherwise, this function will throw an *hpx::exception* with an error code of *hpx::error::yield_aborted* if it is signaled with *wait_aborted*. If called outside a HPX-thread, this function will throw an *hpx::exception* with an error code of *hpx::error::null_thread_id*. If this function is called while the thread-manager is not running, it will throw an *hpx::exception* with an error code of *hpx::error::invalid_status*.

hpx::scoped_annotation

Defined in header `hpx/functional.hpp`⁹⁷¹.

See *Public API* for a list of names and headers that are part of the public HPX API.

struct **scoped_annotation**

scoped_annotation associates a **name** with a section of code (scope). It can be used to visualize code execution in profiling tools like *Intel VTune*, *Apex Profiler*, etc. That allows analyzing performance to figure out which part(s) of code is (are) responsible for performance degradation, etc.

hpx/threading_base/thread_data.hpp

Defined in header `hpx/threading_base/thread_data.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **threads**

⁹⁷¹ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/functional.hpp

Functions

```
constexpr thread_data *get_thread_id_data(thread_id_ref_type const &tid) noexcept  
constexpr thread_data *get_thread_id_data(thread_id_type const &tid) noexcept  
constexpr tracing::region_init_data get_region_init_data(thread_data const*) noexcept  
constexpr tracing::fiber_region_init_data get_fiber_region_init_data(thread_data const*)  
noexcept
```

class **thread_data** : public *thread_data_reference_counting*

#include <thread_data.hpp> A *thread* is the representation of a HPX thread. It's a first class object in HPX. In our implementation this is a user level thread running on top of one of the OS threads spawned by the *thread-manager*.

A *thread* encapsulates:

- A thread status word (see the functions *thread::get_state* and *thread::set_state*)
- A function to execute (the thread function)
- A frame (in this implementation this is a block of memory used as the threads stack)
- A block of registers (not implemented yet)

Generally, *threads* are not created or executed directly. All functionality related to the management of *threads* is implemented by the thread-manager.

Public Types

using **mutex_type** = *util::detail::spinlock_no_backoff*

Public Functions

thread_data(*thread_data* const&) = delete

thread_data(*thread_data*&&) = delete

thread_data &**operator**=(*thread_data* const&) = delete

thread_data &**operator**=(*thread_data*&&) = delete

inline thread_state **get_state**(*std::memory_order* const order = *std::memory_order_acquire*) const
noexcept

The *get_state* function queries the state of this thread instance.

Note: This function will seldom be used directly. Most of the time the state of a thread will be retrieved by using the function *threadmanager::get_state*.

Returns

This function returns the current state of this thread. It will return one of the values as defined by the *thread_state* enumeration.


```
inline thread_state set_state(thread_schedule_state const state, thread_restart_state state_ex =
    thread_restart_state::unknown, std::memory_order const load_order
    = std::memory_order_acquire, std::memory_order const
    exchange_order = std::memory_order_acq_rel) const noexcept
```

The `set_state` function changes the state of this thread instance.

Note: This function will seldom be used directly. Most of the time the state of a thread will have to be changed using the thread-manager. Moreover, changing the thread state using this function does not change its scheduling status. It only sets the thread's status word. To change the thread's scheduling status `threadmanager::set_state` should be used.

Parameters

- **state** – [in] The new state to be set for the thread.
- **state_ex** – [in]
- **load_order** – [in]
- **exchange_order** – [in]

```
inline bool set_state_tagged(thread_schedule_state const newstate, thread_state const
    &prev_state, thread_state &new_tagged_state, std::memory_order
    const exchange_order = std::memory_order_acq_rel) const
    noexcept
```

```
inline bool restore_state(thread_state const new_state, thread_state const old_state,
    std::memory_order const load_order = std::memory_order_relaxed,
    std::memory_order const load_exchange =
    std::memory_order_acq_rel) const noexcept
```

The `restore_state` function changes the state of this thread instance depending on its current state. It will change the state atomically only if the current state is still the same as passed as the second parameter. Otherwise, it won't touch the thread state of this instance.

Note: This function will seldom be used directly. Most of the time the state of a thread will have to be changed using the threadmanager. Moreover, changing the thread state using this function does not change its scheduling status. It only sets the thread's status word. To change the thread's scheduling status `threadmanager::set_state` should be used.

Parameters

- **new_state** – [in] The new state to be set for the thread.
- **old_state** – [in] The old state of the thread which still has to be the current state.
- **load_order** – [in]
- **load_exchange** – [in]

Returns

This function returns `true` if the state has been changed successfully

```
inline bool restore_state(thread_schedule_state const new_state, thread_restart_state const
    state_ex, thread_state old_state, std::memory_order const
    load_exchange = std::memory_order_acq_rel) const noexcept
```

```
char const *get_fiber_name() const noexcept
```

```
inline constexpr thread_priority get_priority() const noexcept
```

```
inline void set_priority(thread_priority const priority) noexcept
```

```
inline bool is_background() const noexcept

inline void set_is_background() noexcept

inline bool interruption_requested() const noexcept

inline bool interruption_enabled() const noexcept

inline bool set_interruption_enabled(bool const enable) noexcept

inline void interrupt(bool const flag = true)

bool interruption_point(bool throw_on_interrupt = true)

bool add_thread_exit_callback(function<void()> const &f)

void run_thread_exit_callbacks()

void free_thread_exit_callbacks()

inline bool runs_as_child(std::memory_order const mo = std::memory_order_acquire) const
    noexcept

inline bool is_stackless() const noexcept

void destroy_thread() override

inline constexpr policies::scheduler_base *get_scheduler_base() const noexcept

inline constexpr std::uint16_t get_last_worker_thread_num() const noexcept

inline void set_last_worker_thread_num(std::uint16_t const last_worker_thread_num)
    noexcept

inline constexpr std::ptrdiff_t get_stack_size() const noexcept

inline thread_stacksize get_stack_size_enum() const noexcept

template<typename ThreadQueue>
inline constexpr ThreadQueue &get_queue() noexcept

inline coroutine_type::result_type operator() (hpx::execution_base::this_thread::detail::agent_storage
    *agent_storage)
```

Execute the thread function.

Returns

This function returns the thread state the thread should be scheduled from this point on.
The thread manager will use the returned value to set the thread's scheduling status.

```
inline coroutine_type::result_type invoke_directly()
```

Directly execute the thread function (inline)

Returns

This function returns the thread state the thread should be scheduled from this point on.
The thread manager will use the returned value to set the thread's scheduling status.

```
inline virtual thread_id_type get_thread_id() const
```

```
inline virtual std::size_t get_thread_phase() const noexcept
```

```
virtual std::size_t get_thread_data() const = 0
```

```

virtual std::size_t set_thread_data(std::size_t data) = 0

virtual void init() = 0

virtual void rebind(thread_init_data &init_data) = 0

inline hpx::tracing::task_timer_data get_timer_data() const noexcept

inline void set_timer_data(hpx::tracing::task_timer_data data) noexcept

thread_data(thread_init_data &init_data, void *queue, std::ptrdiff_t stacksize, bool is_stackless =
    false, thread_id_addrf addrf = thread_id_addrf::yes)

~thread_data() override

virtual void destroy() noexcept = 0

```

Public Static Functions

```

static inline constexpr std::uint64_t get_component_id() noexcept
    Return the id of the component this thread is running in.

static inline constexpr threads::thread_description get_description() noexcept

static inline constexpr threads::thread_description set_description(threads::thread_description)
    noexcept

static inline constexpr threads::thread_description get_lco_description() noexcept

static inline constexpr threads::thread_description set_lco_description(threads::thread_description)
    noexcept

static char const *get_safe_description(threads::thread_description const &description, char
    const *fallback = "<unknown>") noexcept

static inline constexpr std::uint32_t get_parent_locality_id() noexcept
    Return the locality of the parent thread.

static inline constexpr thread_id_type get_parent_thread_id() noexcept
    Return the thread id of the parent thread.

static inline constexpr std::size_t get_parent_thread_phase() noexcept
    Return the phase of the parent thread.

static inline constexpr util::backtrace const *get_backtrace() noexcept

static inline constexpr util::backtrace const *set_backtrace(util::backtrace const*) noexcept

```

Protected Functions

```
inline thread_restart_state set_state_ex(thread_restart_state const new_state,  
                                         std::memory_order const load_order =  
                                         std::memory_order_acquire, std::memory_order const  
                                         load_exchange = std::memory_order_acq_rel) const  
                                         noexcept
```

The `set_state` function changes the extended state of this thread instance.

Note: This function will seldom be used directly. Most of the time the state of a thread will have to be changed using the threadmanager.

Parameters

- **new_state** – [in] The new extended state to be set for the thread.
- **load_order** – [in]
- **load_exchange** – [in]

```
void rebind_base(thread_init_data &init_data)
```

Private Types

```
using state = detail::thread_data_state
```

Private Members

```
mutable mutex_type mtx_
```

```
std::atomic<bool> runs_as_child_
```

```
state state_
```

```
thread_stacksize stacksize_enum_
```

```
std::int32_t stacksize_
```

```
std::uint16_t last_worker_thread_num_
```

```
thread_priority priority_
```

```
HPX_NO_UNIQUE_ADDRESS hpx::tracing::task_timer_data timer_data_
```

```
mutable std::atomic<thread_state> current_state_
```

```
hpx::detail::forward_list<hpx::function<void()>> exit_funcs_
```

```

policies::scheduler_base *scheduler_base_

void *queue_

```

hpx/threading_base/thread_pool_base.hpp

Defined in header `hpx/threading_base/thread_pool_base.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace threads
```

Functions

```
std::ostream &operator<<(std::ostream &os, thread_pool_base const &thread_pool)
```

```
class thread_pool_base
```

```
#include <thread_pool_base.hpp> The base class used to manage a pool of OS threads.
```

Public Functions

```
virtual void suspend_processing_unit_direct(std::size_t virt_core, error_code &ec = throws)
= 0
```

Suspends the given processing unit. Blocks until the processing unit has been suspended.

Parameters

- **virt_core** – [in] The processing unit on the pool to be suspended. The processing units are indexed starting from 0.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
virtual void resume_processing_unit_direct(std::size_t virt_core, error_code &ec = throws)
= 0
```

Resumes the given processing unit. Blocks until the processing unit has been resumed.

Parameters

- **virt_core** – [in] The processing unit on the pool to be resumed. The processing units are indexed starting from 0.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

```
virtual void resume_direct(error_code &ec = throws) = 0
```

Resumes the thread pool. Blocks until all OS threads on the thread pool have been resumed.

Parameters

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

virtual void **suspend_direct**(*error_code* &ec = *throws*) = 0

Suspends the thread pool. Blocks until all OS threads on the thread pool have been suspended.

Note: A thread pool cannot be suspended from an HPX thread running on the pool itself.

Parameters

ec – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

Throws

hpx::exception – if called from an HPX thread which is running on the pool itself.

struct **thread_pool_init_parameters**

Public Functions

```
inline thread_pool_init_parameters(std::string const &name, std::size_t index,
                                   policies::scheduler_mode mode, std::size_t num_threads,
                                   std::size_t thread_offset,
                                   hpx::threads::policies::callback_notifier &notifier,
                                   hpx::threads::policies::detail::affinity_data const
                                   &affinity_data,
                                   hpx::threads::detail::network_background_callback_type
                                   const &network_background_callback =
                                   hpx::threads::detail::network_background_callback_type(),
                                   std::size_t max_background_threads =
                                   static_cast<std::size_t>(-1), std::size_t
                                   max_idle_loop_count =
                                   HPX_IDLE_LOOP_COUNT_MAX, std::size_t
                                   max_busy_loop_count =
                                   HPX_BUSY_LOOP_COUNT_MAX, std::size_t
                                   shutdown_check_count = 10)
```

Public Members

std::string const &**name_**

std::size_t **index_**

policies::scheduler_mode **mode_**

std::size_t **num_threads_**

std::size_t **thread_offset_**

hpx::threads::policies::callback_notifier &**notifier_**

```
hpx::threads::policies::detail::affinity_data const &affinity_data_
```

```
hpx::threads::detail::network_background_callback_type const
&network_background_callback_
```

```
std::size_t max_background_threads_
```

```
std::size_t max_idle_loop_count_
```

```
std::size_t max_busy_loop_count_
```

```
std::size_t shutdown_check_count_
```

threadmanager

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/threadmanager/threadmanager.hpp

Defined in header `hpx/threadmanager/threadmanager.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

class **threadmanager**

#include <threadmanager.hpp> The *thread-manager* class is the central instance of management for all (non-depleted) threads

Public Types

```
using notification_policy_type = threads::policies::callback_notifier
```

```
using pool_type = std::unique_ptr<thread_pool_base>
```

```
using pool_vector = std::vector<pool_type>
```

Public Functions

threadmanager(*hpx::util::runtime_configuration* &rtcfg_, *notification_policy_type* ¬ifier, *detail::network_background_callback_type* network_background_callback = *detail::network_background_callback_type*())

threadmanager(*threadmanager* const&) = delete

threadmanager(*threadmanager*&&) = delete

threadmanager &**operator**=(*threadmanager* const&) = delete

threadmanager &**operator**=(*threadmanager*&&) = delete

~threadmanager()

void **init**() const

void **create_pools**()

void **print_pools**(*std::ostream*&) const

FIXME move to private and add `—hpx:printpools` cmd line option.

thread_pool_base &**default_pool**() const

thread_pool_base &**get_pool**(*std::string* const &pool_name) const

thread_pool_base &**get_pool**(*pool_id_type* const &pool_id) const

thread_pool_base &**get_pool**(*std::size_t* thread_index) const

bool **pool_exists**(*std::string* const &pool_name) const

bool **pool_exists**(*std::size_t* pool_index) const

thread_id_ref_type **register_work**(*thread_init_data* &data, *error_code* &ec = *throws*) const

The function *register_work* adds a new work item to the thread manager. It doesn't immediately create a new *thread*, it just adds the task parameters (function, initial state and description) to the internal management data structures. The thread itself will be created when the number of existing threads drops below the number of threads specified by the constructors *max_count* parameter.

Parameters

- **data** – [in] The value of this parameter allows to specify a description of the thread to create. This information is used for logging purposes mainly, but might be useful for debugging as well. This parameter is optional and defaults to an empty string.
- **ec** –

void **register_thread**(*thread_init_data* &data, *thread_id_ref_type* &id, *error_code* &ec = *throws*) const

The function *register_thread* adds a new work item to the thread manager. It creates a new *thread*, adds it to the internal management data structures, and schedules the new thread, if appropriate.

Parameters

- **data** – [in] The value of this parameter allows to specify a description of the thread to create. This information is used for logging purposes mainly, but might be useful for debugging as well. This parameter is optional and defaults to an empty string.
- **id** – [out] This parameter will hold the id of the created thread. This id is guaranteed to be validly initialized before the thread function is executed.
- **ec** –

bool **run**() const

Run the thread manager's work queue. This function instantiates the specified number of OS threads in each pool. All OS threads are started to execute the function *tfunc*.

Returns

The function returns *true* if the thread manager has been started successfully, otherwise it returns *false*.

void **stop**(bool blocking = true) const

Forcefully stop the thread-manager.

Parameters

blocking –

bool **is_busy**() const

bool **is_idle**() const

void **wait**() const

bool **wait_for**(hpx::chrono::steady_duration const &rel_time) const

template<typename **StopToken**>

inline bool **wait_for**(StopToken &&stop_token, hpx::chrono::steady_duration const &rel_time)
const

void **suspend**() const

void **resume**() const

hpx::state **status**() const

Return whether the thread manager is still running This returns the “minimal state”, i.e. the state of the least advanced thread pool

std::int64_t **get_thread_count**(thread_schedule_state state = thread_schedule_state::unknown,
thread_priority priority = thread_priority::default_, std::size_t
num_thread = static_cast<std::size_t>(-1), bool reset = false)
const

return the number of HPX-threads with the given state

Note: This function locks the internal OS lock in the thread manager

std::int64_t **get_idle_core_count**() const

mask_type **get_idle_core_mask**() const

std::int64_t **get_background_thread_count**() const

bool **enumerate_threads**(hpx::function<bool(thread_id_type)> const &f, thread_schedule_state
state = thread_schedule_state::unknown) const

void **abort_all_suspended_threads**() const

bool **cleanup_terminated**(bool delete_all) const

std::size_t **get_os_thread_count**() const

Return the number of OS threads running in this thread-manager.

This function will return correct results only if the thread-manager is running.

std::thread &**get_os_thread_handle**(*std::size_t* num_thread) const

void **report_error**(*std::size_t* num_thread, *std::exception_ptr* const &e) const

API functions forwarding to notification policy.

This notifies the thread manager that the passed exception has been raised. The exception will be routed through the notifier and the scheduler (which will result in it being passed to the runtime object, which in turn will report it to the console, etc.).

mask_type **get_used_processing_units**() const

Returns the mask identifying all processing units used by this thread manager.

hwloc_bitmap_ptr **get_pool_numa_bitmap**(*std::string* const &pool_name) const

void **set_scheduler_mode**(*threads::policies::scheduler_mode* mode,
hpx::threads::mask_cref_type pu_mask) const noexcept

void **add_scheduler_mode**(*threads::policies::scheduler_mode* mode,
hpx::threads::mask_cref_type pu_mask) const noexcept

void **add_remove_scheduler_mode**(*threads::policies::scheduler_mode* to_add_mode,
threads::policies::scheduler_mode to_remove_mode,
hpx::threads::mask_cref_type pu_mask) const noexcept

void **remove_scheduler_mode**(*threads::policies::scheduler_mode* mode,
hpx::threads::mask_cref_type pu_mask) const noexcept

void **reset_thread_distribution**() const noexcept

std::int64_t **get_queue_length**(bool reset) const

std::int64_t **get_cumulative_duration**(bool reset) const

std::int64_t **get_thread_count_unknown**(bool reset) const

std::int64_t **get_thread_count_active**(bool reset) const

std::int64_t **get_thread_count_pending**(bool reset) const

std::int64_t **get_thread_count_suspended**(bool reset) const

std::int64_t **get_thread_count_terminated**(bool reset) const

std::int64_t **get_thread_count_staged**(bool reset) const

Public Static Functions

static void **init_tss**(*std::size_t* global_thread_num)

static void **deinit_tss**()

Private Types

```
using mutex_type = std::mutex
```

Private Functions

```
policies::thread_queue_init_parameters get_init_parameters() const

void create_scheduler_user_defined(hpx::resource::scheduler_function const&,
                                   thread_pool_init_parameters const&,
                                   policies::thread_queue_init_parameters const&)

void create_scheduler_local(thread_pool_init_parameters const&,
                             policies::thread_queue_init_parameters const&, std::size_t)

void create_scheduler_local_priority_fifo(thread_pool_init_parameters const&,
                                           policies::thread_queue_init_parameters
                                           const&, std::size_t)

void create_scheduler_local_priority_fifo_double(thread_pool_init_parameters const&,
                                                  poli-
                                                  cies::thread_queue_init_parameters
                                                  const&, std::size_t)

void create_scheduler_local_priority_lifo(thread_pool_init_parameters const&,
                                           policies::thread_queue_init_parameters
                                           const&, std::size_t)

void create_scheduler_static(thread_pool_init_parameters const&,
                              policies::thread_queue_init_parameters const&, std::size_t)

void create_scheduler_static_priority(thread_pool_init_parameters const&,
                                       policies::thread_queue_init_parameters const&,
                                       std::size_t)

void create_scheduler_abp_priority_fifo(thread_pool_init_parameters const&,
                                          policies::thread_queue_init_parameters const&,
                                          std::size_t)

void create_scheduler_abp_priority_lifo(thread_pool_init_parameters const&,
                                          policies::thread_queue_init_parameters const&,
                                          std::size_t)

void create_scheduler_shared_priority(thread_pool_init_parameters const&,
                                       policies::thread_queue_init_parameters const&,
                                       std::size_t)

void create_scheduler_local_workrequesting_fifo(thread_pool_init_parameters const&,
                                                  policies::thread_queue_init_parameters
                                                  const&, std::size_t)

void create_scheduler_local_workrequesting_lifo(thread_pool_init_parameters const&,
                                                  policies::thread_queue_init_parameters
                                                  const&, std::size_t)
```

```
void create_scheduler_local_workrequesting_mc(thread_pool_init_parameters const&,
                                              policies::thread_queue_init_parameters
                                              const&, std::size_t)
```

Private Members

```
mutable mutex_type mtx_
```

```
hpx::util::runtime_configuration &rtcfg_
```

```
std::vector<pool_id_type> threads_lookup_
```

```
pool_vector pools_
```

```
notification_policy_type &notifier_
```

```
detail::network_background_callback_type network_background_callback_
```

thrust

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/thrust/algorithms.hpp

Defined in header `hpx/thrust/algorithms.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace thrust
```

Functions

```
template<typename Tag, typename ThrustPolicy, typename ...Args>
decltype(auto) hpx_invoke(Tag tag, ThrustPolicy &&policy, Args&&... args)
```

ADL hook dispatching HPX algorithm CPOs to Thrust backends.

When a Thrust execution policy is passed to an HPX algorithm CPO, this hook maps the call to the corresponding Thrust implementation. Async policies wrap the result in a future.

Template Parameters

- **Tag** – The algorithm CPO tag type.
- **ThrustPolicy** – A Thrust execution policy satisfying `is_thrust_execution_policy`.
- **Args** – Arguments forwarded to the Thrust algorithm.

Parameters

- **tag** – The algorithm CPO tag instance.
- **policy** – Thrust execution policy controlling dispatch.

- **args** – Arguments forwarded to the mapped algorithm.

Returns

The algorithm result, or a future thereof for async policies.

timed_execution

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/timed_execution/timed_execution_fwd.hpp

Defined in header `hpx/timed_execution/timed_execution_fwd.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **parallel**

namespace **execution**

Variables

constexpr struct `hpx::parallel::execution::post_at_t` **post_at**

constexpr struct `hpx::parallel::execution::post_after_t` **post_after**

constexpr struct `hpx::parallel::execution::async_execute_at_t` **async_execute_at**

constexpr struct `hpx::parallel::execution::async_execute_after_t` **async_execute_after**

constexpr struct `hpx::parallel::execution::sync_execute_at_t` **sync_execute_at**

constexpr struct `hpx::parallel::execution::sync_execute_after_t` **sync_execute_after**

struct **async_execute_after_t**

#include <timed_execution_fwd.hpp> Customization point of asynchronous execution agent creation supporting timed execution.

This asynchronously creates a single function invocation `f()` using the associated executor at the given point in time.

Note: This calls `exec.async_execute_after(rel_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::async_execute()` on the underlying non-time-scheduled execution agent.

Param exec

[in] The executor object to use for scheduling of the function *f*.

Param rel_time

[in] The duration of time after which the given function should be scheduled to run.

Param f

[in] The function which will be scheduled using the given executor.

Param ts...

[in] Additional arguments to use to invoke *f*.

Return

f(*ts...*)'s result through a future

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                   &rel_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                   &rel_time, F &&f, Ts&&... ts) const
```

struct **async_execute_at_t**

#include <timed_execution_fwd.hpp> Customization point of asynchronous execution agent creation supporting timed execution.

This asynchronously creates a single function invocation *f*() using the associated executor at the given point in time.

Note: This calls `exec.async_execute_at(abs_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::async_execute()` on the underlying non-time-scheduled execution agent.

Param exec

[in] The executor object to use for scheduling of the function *f*.

Param abs_time

[in] The point in time the given function should be scheduled at to run.

Param f

[in] The function which will be scheduled using the given executor.

Param ts...

[in] Additional arguments to use to invoke *f*.

Return

f(*ts...*)'s result through a future

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
                                     &abs_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
                                     &abs_time, F &&f, Ts&&... ts) const
```

struct **post_after_t**

#include <timed_execution_fwd.hpp> Customization point of asynchronous fire & forget execution agent creation supporting timed execution.

This asynchronously (fire & forget) creates a single function invocation *f*() using the associated executor at the given point in time.

Note: This calls `exec.post_after(rel_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::post()` on the underlying non-time-scheduled execution agent.

Param *exec*

[in] The executor object to use for scheduling of the function *f*.

Param *rel_time*

[in] The duration of time after which the given function should be scheduled to run.

Param *f*

[in] The function which will be scheduled using the given executor.

Param *ts...*

[in] Additional arguments to use to invoke *f*.

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                     &rel_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                     &rel_time, F &&f, Ts&&... ts) const
```

struct **post_at_t**

#include <timed_execution_fwd.hpp> Customization point of asynchronous fire & forget execution agent creation supporting timed execution.

This asynchronously (fire & forget) creates a single function invocation *f*() using the associated executor at the given point in time.

Note: This calls `exec.post_at(abs_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::post()` on the underlying non-time-scheduled execution agent.

Param exec

[in] The executor object to use for scheduling of the function *f*.

Param abs_time

[in] The point in time the given function should be scheduled at to run.

Param f

[in] The function which will be scheduled using the given executor.

Param ts...

[in] Additional arguments to use to invoke *f*.

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
                                     &abs_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
                                     &abs_time, F &&f, Ts&&... ts) const
```

struct **sync_execute_after_t**

#include <timed_execution_fwd.hpp> Customization point of synchronous execution agent creation supporting timed execution.

This synchronously creates a single function invocation *f*() using the associated executor at the given point in time.

Note: This calls `exec.sync_execute_after(rel_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::sync_execute()` on the underlying non-time-scheduled execution agent.

Param exec

[in] The executor object to use for scheduling of the function *f*.

Param rel_time

[in] The duration of time after which the given function should be scheduled to run.

Param f

[in] The function which will be scheduled using the given executor.

Param ts...

[in] Additional arguments to use to invoke *f*.

Return

f(*ts...*)'s result

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                     &rel_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_duration const
                                     &rel_time, F &&f, Ts&&... ts) const
```


struct **sync_execute_at_t**

#include <timed_execution_fwd.hpp> Customization point of synchronous execution agent creation supporting timed execution.

This synchronously creates a single function invocation *f*() using the associated executor at the given point in time.

Note: This calls `exec.sync_execute_at(abs_time, f, ts...)`, if available, otherwise it emulates timed scheduling by delaying calling `execution::sync_execute()` on the underlying non-time-scheduled execution agent.

Param exec

[in] The executor object to use for scheduling of the function *f*.

Param abs_time

[in] The point in time the given function should be scheduled at to run.

Param f

[in] The function which will be scheduled using the given executor.

Param ts...

[in] Additional arguments to use to invoke *f*.

Return

f(*ts...*)'s result

Public Functions

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
&abs_time, F &&f, Ts&&... ts) const
```

```
template<executor_any Executor, typename F, typename ...Ts>
inline decltype(auto) operator() (Executor &&exec, hpx::chrono::steady_time_point const
&abs_time, F &&f, Ts&&... ts) const
```

```
template<executor_any BaseExecutor>
```

```
struct timed_executor
```

hpx/timed_execution/timed_executors.hpp

Defined in header `hpx/timed_execution/timed_executors.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **execution**

namespace **experimental**

namespace **parallel**

```
namespace execution
```

Typedefs

```
using sequenced_timed_executor = timed_executor<hpx::execution::sequenced_executor>
```

```
using parallel_timed_executor = timed_executor<hpx::execution::parallel_executor>
```

```
template<executor_any BaseExecutor>
```

```
struct timed_executor
```

`hpx/timed_execution/timed_execution.hpp`

Defined in header `hpx/timed_execution/timed_execution.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
namespace parallel
```

```
namespace execution
```

`hpx/timed_execution/traits/is_timed_executor.hpp`

Defined in header `hpx/timed_execution/traits/is_timed_executor.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

Variables

```
template<typename Executor> concept timed_executor    = hpx::traits::is_timed_executor_v<Executor>
```

```
namespace parallel
```

```
namespace execution
```

Typedefs

```
template<typename T>
using is_timed_executor_t = typename is_timed_executor<T>::type
```

Variables

```
template<typename T>
constexpr bool is_timed_executor_v = is_timed_executor<T>::value

template<typename T>
struct is_timed_executor : public detail::is_timed_executor<std::decay_t<T>>>
```

namespace **traits**

Variables

```
template<typename T>
constexpr bool is_timed_executor_v = is_timed_executor<T>::value

template<typename Executor, typename Enable = void>
struct is_timed_executor : public hpx::parallel::execution::is_timed_executor<Executor>
```

timing

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::chrono::high_resolution_timer

Defined in header [hpx/chrono.hpp](#)⁹⁷².

See *Public API* for a list of names and headers that are part of the public *HPX* API.

class **high_resolution_timer**

high_resolution_timer is a timer object which measures the elapsed time

⁹⁷² http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/chrono.hpp

hpx::chrono::high_resolution_clock

Defined in header [hpx/chrono.hpp](#)⁹⁷³.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

struct **high_resolution_clock**

Class `hpx::chrono::high_resolution_clock` represents the clock with the smallest tick period provided by the implementation. It may be an alias of `std::chrono::system_clock` or `std::chrono::steady_clock`, or a third, independent clock. `hpx::chrono::high_resolution_clock` meets the requirements of *Trivial-Clock*.

topology

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/topology/cpu_mask.hpp

Defined in header `hpx/topology/cpu_mask.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

hpx/topology/topology.hpp

Defined in header `hpx/topology/topology.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **threads**

Typedefs

using **hwloc_bitmap_ptr** = `std::shared_ptr<hpx_hwloc_bitmap_wrapper>`

⁹⁷³ http://github.com/TheHPXProject/hpx/blob/5425060950dcd6db4f0999faf6e63fc2337be393/libs/core/include_local/include/hpx/chrono.hpp

Enums

enum **hpx_hwloc_membind_policy**

Please see hwloc documentation for the corresponding enums HWLOC_MEMBIND_XXX.

Values:

enumerator **membind_default**

enumerator **membind_firsttouch**

enumerator **membind_bind**

enumerator **membind_interleave**

enumerator **membind_replicate**

enumerator **membind_nexttouch**

enumerator **membind_mixed**

enumerator **membind_user**

Functions

topology &**create_topology**()

inline *topology* const &**get_topology**()

Get the global topology instance.

inline *std::size_t* **get_memory_page_size**()

struct **hpx_hwloc_bitmap_wrapper**

Public Functions

HPX_NON_COPYABLE(*hpx_hwloc_bitmap_wrapper*)

inline **hpx_hwloc_bitmap_wrapper**() noexcept

inline explicit **hpx_hwloc_bitmap_wrapper**(void *bmp) noexcept

inline ~**hpx_hwloc_bitmap_wrapper**()

inline void **reset**(hwloc_bitmap_t bmp) noexcept

inline explicit constexpr **operator bool**() const noexcept

inline hwloc_bitmap_t **get_bitmap**() const noexcept

Private Members

hwloc_bitmap_t **bmp_**

Friends

friend *std::ostream* &**operator**<<(*std::ostream* &os, *hpx_hwloc_bitmap_wrapper* const *bmp)

struct **topology**

Public Functions

topology()

topology(*topology* const&) = delete

topology(*topology*&&) = delete

topology &**operator**=(*topology* const&) = delete

topology &**operator**=(*topology*&&) = delete

~topology()

inline *std::size_t* **get_socket_number**(*std::size_t* num_thread, [[maybe_unused]] *error_code* &ec
= *throws*) const noexcept

Return the Socket number of the processing unit the given thread is running on.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

inline *std::size_t* **get_numa_node_number**(*std::size_t* num_thread, [[maybe_unused]] *error_code*
&ec = *throws*) const noexcept

Return the NUMA node number of the processing unit the given thread is running on.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

inline *std::size_t* **get_numa_distance**(*std::size_t* node_a, *std::size_t* node_b) const noexcept

Return the hardware latency distance between two NUMA nodes. Values are sourced from hwloc's distance matrix when available; otherwise a standard default (10 = local, 20 = remote) is returned.

Parameters

- **node_a** – [in] logical index of the first NUMA node
- **node_b** – [in] logical index of the second NUMA node

mask_cref_type **get_machine_affinity_mask**(*error_code* &ec = *throws*) const noexcept

Return a bit mask where each set bit corresponds to a processing unit available to the application.

Parameters

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_type **get_service_affinity_mask**(mask_cref_type used_processing_units, error_code &ec = throws) const

Return a bit mask where each set bit corresponds to a processing unit available to the service threads in the application.

Parameters

- **used_processing_units** – [in] This is the mask of processing units which are not available for service threads.
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_cref_type **get_socket_affinity_mask**(std::size_t num_thread, error_code &ec = throws) const

Return a bit mask where each set bit corresponds to a processing unit available to the given thread inside the socket it is running on.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_cref_type **get_numa_node_affinity_mask**(std::size_t num_thread, error_code &ec = throws) const

Return a bit mask where each set bit corresponds to a processing unit available to the given thread inside the NUMA domain it is running on.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_cref_type **get_core_affinity_mask**(std::size_t num_thread, error_code &ec = throws) const

Return a bit mask where each set bit corresponds to a processing unit available to the given thread inside the core it is running on.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_cref_type **get_thread_affinity_mask**(std::size_t num_thread, error_code &ec = throws) const

Return a bit mask where each set bit corresponds to a processing unit available to the given thread.

Parameters

- **num_thread** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

void **set_thread_affinity_mask**(mask_cref_type mask, error_code &ec = throws) const

Use the given bit mask to set the affinity of the given thread. Each set bit corresponds to a processing unit the thread will be allowed to run on.

Note: Use this function on systems where the affinity must be set from inside the thread itself.

Parameters

- **mask** – [in]

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

mask_type **get_thread_affinity_mask_from_lva**(void const *lva, error_code &ec = throws)
const

Return a bit mask where each set bit corresponds to a processing unit co-located with the memory the given address is currently allocated on.

Parameters

- **lva** – [in]
- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

void **print_affinity_mask**(std::ostream &os, std::size_t num_thread, mask_cref_type m,
std::string const &pool_name) const

Prints the given mask *m* to os in a human-readable form.

bool **reduce_thread_priority**(error_code &ec = throws) const

Reduce thread priority of the current thread.

Parameters

- **ec** – [in,out] this represents the error status on exit, if this is pre-initialized to *hpx::throws* the function will throw on error instead.

std::size_t **get_number_of_sockets**() const

Return the number of available NUMA domains.

std::size_t **get_number_of_numa_nodes**() const

Return the number of available NUMA domains.

std::size_t **get_number_of_cores**() const

Return the number of available cores.

std::size_t **get_number_of_pus**() const noexcept

Return the number of available hardware processing units.

std::size_t **get_number_of_numa_node_cores**(std::size_t numa) const

Return number of cores in given numa domain.

std::size_t **get_number_of_numa_node_pus**(std::size_t numa) const

Return number of processing units in a given numa domain.

std::size_t **get_number_of_socket_pus**(std::size_t socket) const

Return number of processing units in a given socket.

std::size_t **get_number_of_core_pus**(std::size_t core) const

Return number of processing units in given core.

std::size_t **get_number_of_socket_cores**(std::size_t socket) const

Return number of cores units in given socket.

inline std::size_t **get_core_number**(std::size_t num_thread, error_code& = throws) const

std::size_t **get_pu_number**(std::size_t num_core, std::size_t num_pu, error_code &ec = throws)
const

std::size_t **get_cache_size**(mask_cref_type mask, int level) const

Return the size of the cache associated with the given mask.


```

mask_type get_cpubind_mask(error_code &ec = throws) const

mask_type get_cpubind_mask(std::thread &handle, error_code &ec = throws) const

hwloc_bitmap_ptr cpuset_to_nodese(mask_cref_type mask) const
    convert a cpu mask into a numa node mask in hwloc bitmap form

void write_to_log() const

void *allocate(std::size_t len) const
    This is equivalent to malloc(), except that it tries to allocate page-aligned memory from the OS.

void *allocate_membind(std::size_t len, hwloc_bitmap_ptr const &bitmap,
    hpx_hwloc_membind_policy policy, int flags) const
    allocate memory with binding to a numa node set as specified by the policy and flags (see hwloc
    docs)

threads::mask_type get_area_membind_nodese(void const *addr, std::size_t len) const

bool set_area_membind_nodese(void const *addr, std::size_t len, void *nodese) const

int get_numa_domain(void const *addr) const

void deallocate(void *addr, std::size_t len) const noexcept
    Free memory that was previously allocated by allocate.

void print_hwloc(std::ostream&) const

mask_type init_socket_affinity_mask_from_socket(std::size_t num_socket) const

mask_type init_numa_node_affinity_mask_from_numa_node(std::size_t num_numa_node)
    const

mask_type init_core_affinity_mask_from_core(std::size_t num_core, mask_cref_type
    default_mask = empty_mask) const

mask_type init_thread_affinity_mask(std::size_t num_thread) const

mask_type init_thread_affinity_mask(std::size_t num_core, std::size_t num_pu) const

hwloc_bitmap_t mask_to_bitmap(mask_cref_type mask, hwloc_obj_type_t htype, unsigned
    *count = nullptr) const

mask_type bitmap_to_mask(hwloc_bitmap_t bitmap, hwloc_obj_type_t htype) const

```

Public Static Functions

```

static void print_vector(std::ostream &os, std::vector<std::size_t> const &v)

static void print_mask_vector(std::ostream &os, std::vector<mask_type> const &v)

```

Private Types

```
using mutex_type = hpx::util::spinlock
```

Private Functions

```
std::size_t init_node_number(std::size_t num_thread, hwloc_obj_type_t type) const  
inline std::size_t init_socket_number(std::size_t num_thread) const  
std::size_t init_numa_node_number(std::size_t num_thread) const  
inline std::size_t init_core_number(std::size_t num_thread) const  
void extract_node_mask(hwloc_obj_t parent, mask_type &mask) const  
std::size_t get_number_of_core_pus_locked(std::size_t core) const  
std::size_t extract_node_count(hwloc_obj_t parent, hwloc_obj_type_t type, std::size_t count)  
                                const  
std::size_t extract_node_count_locked(hwloc_obj_t parent, hwloc_obj_type_t type, std::size_t  
                                count) const  
  
mask_type init_machine_affinity_mask() const  
inline mask_type init_socket_affinity_mask(std::size_t num_thread) const  
inline mask_type init_numa_node_affinity_mask(std::size_t num_thread) const  
inline mask_type init_core_affinity_mask(std::size_t num_thread) const  
void init_num_of_pus()  
hwloc_obj_t get_pu_obj(std::size_t num_pu) const  
void init_numa_node_distances()
```

Private Members

```
hwloc_topology_t topo = nullptr  
  
std::size_t num_of_pus_ = 0  
  
bool use_pus_as_cores_ = false  
  
mutable mutex_type topo_mtx  
  
std::vector<std::size_t> socket_numbers_  
  
std::vector<std::size_t> numa_node_numbers_
```

```

std::vector<std::size_t> core_numbers_

mask_type machine_affinity_mask_ = mask_type()

std::vector<mask_type> socket_affinity_masks_

std::vector<mask_type> numa_node_affinity_masks_

std::vector<mask_type> core_affinity_masks_

std::vector<mask_type> thread_affinity_masks_

std::vector<std::vector<std::size_t>> numa_node_distances_

```

Private Static Attributes

```

static mask_type empty_mask

static std::size_t memory_page_size_

static constexpr std::size_t pu_offset = 0

static constexpr std::size_t core_offset = 0

```

Friends

```

friend std::size_t get_memory_page_size()

```

tracing

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/tracing/tracing.hpp

Defined in header `hpx/tracing/tracing.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

```
namespace hpx
```

```
    namespace threads
```

```
        namespace tracing
```

Functions

```
template<typename ThreadData>
constexpr void task_created([[maybe_unused]] ThreadData *thrdptr, [[maybe_unused]] void const
                             *parent_task_id = nullptr) noexcept
```

```
template<typename ThreadData>
constexpr void task_executing([[maybe_unused]] ThreadData *thrdptr) noexcept
```

```
template<typename ThreadId>
constexpr void task_yielded([[maybe_unused]] ThreadId const &id) noexcept
```

```
template<typename ThreadId, typename String>
constexpr void task_suspended([[maybe_unused]] ThreadId const &id, [[maybe_unused]] String const
                                &reason) noexcept
```

```
template<typename ThreadId, typename StateX>
constexpr void task_resumed([[maybe_unused]] ThreadId const &id, [[maybe_unused]] StateX statex)
                             noexcept
```

```
template<typename ThreadData>
constexpr void task_completed([[maybe_unused]] ThreadData *thrdptr) noexcept
```

struct **lock_context**

#include <tracing.hpp> Context for annotating lock acquisitions and releases.

This struct is used to provide tracing annotations for synchronization primitives such as spinlocks and mutexes. It registers the creation, acquisition, and release of locks to the active tracing backend.

Public Functions

explicit **lock_context**(char const *name = nullptr, void const *addr = nullptr) noexcept

Constructs a lock context.

Parameters

- **name** – The name or description of the lock.
- **addr** – The memory address of the lock, used to track it uniquely.

explicit **lock_context**(char const *prefix, char const *suffix, void const *addr = nullptr) noexcept

Constructs a lock context with a dynamic name.

Parameters

- **prefix** – The prefix for the lock name.
- **suffix** – The suffix for the lock name.
- **addr** – The memory address of the lock, used to track it uniquely.

bool **before_lock**() const noexcept

Called immediately before attempting to acquire the lock.

Returns

true if the prepare event was recorded and **after_lock** should be called.

void **after_lock**() const noexcept

Called immediately after the lock is successfully acquired.

void **after_try_lock**(bool success) const noexcept

Called after a try-lock operation completes.

Parameters

success – true if the lock was acquired, false if it failed.

void **before_unlock()** const noexcept

Called immediately before releasing the lock.

void **after_unlock()** const noexcept

Called immediately after releasing the lock.

namespace **util**

namespace **external_timer**

hpx/tracing/backends/apex.hpp

Defined in header `hpx/tracing/backends/apex.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **tracing**

Typedefs

bool(*)() **enable_parent_task_handler_type**

typedef char const ***annotation_handle**

Functions

inline constexpr *annotation_handle* **create_annotation_handle**(char const *name) noexcept

inline constexpr void **set_thread_name**(char const*) noexcept

constexpr char const ***rename_region**(char const*) noexcept

constexpr void **task_staged**(char const*, void const* = nullptr) noexcept

constexpr void **task_created**(char const*, void const*, void const* = nullptr) noexcept

constexpr void **task_executing**(void const*, char const*, *std::size_t*) noexcept

constexpr void **task_yielded**(void const*, char const*) noexcept

constexpr void **task_suspended**(void const*, char const*, char const* = nullptr) noexcept

constexpr void **task_resumed**(void const*, char const*, char const* = nullptr) noexcept

constexpr void **task_completed**(void const*, char const*) noexcept

constexpr void **task_deleted**(void const*) noexcept

constexpr void **future_fulfilled**(void const*, char const* = nullptr) noexcept

Producer-side signal: future state fulfilled (no-op stub for APEX).

Producer-side signal: a future shared state was set to a value.

Producer-side signal: future state fulfilled (no-op stub for ITTNotify).

Producer-side signal: future state fulfilled (no-op stub).

Parameters

- **future_id** – Pointer to the `future_data` shared state. Used as a stable identifier to correlate producer and consumer events in the Tracy message log.
- **desc** – Optional description of the producing context (e.g. the name of the promise or task).

constexpr void **future_exception_set**(void const*, char const* = nullptr) noexcept

Producer-side signal: future exception set (no-op stub for APEX).

Producer-side signal: a future shared state was set with an exception.

Producer-side signal: future exception set (no-op stub for ITTNotify).

Producer-side signal: future exception set (no-op stub).

Parameters

- **future_id** – Pointer to the `future_data` shared state.
- **desc** – Optional description of the producing context.

constexpr void **continuation_run**(void const* = nullptr) noexcept

Consumer-side signal: continuation started (no-op stub for APEX).

Consumer-side signal: a continuation has started executing, correlated with the source future state.

Consumer-side signal: continuation started (no-op stub for ITTNotify).

Consumer-side signal: continuation started (no-op stub).

constexpr void **continuation_finished**(void const* = nullptr) noexcept

Consumer-side signal: continuation finished (no-op stub for APEX).

Consumer-side signal: a continuation has finished executing.

Consumer-side signal: continuation finished (no-op stub for ITTNotify).

Consumer-side signal: continuation finished (no-op stub).

constexpr void **handle_on_completed_fired**(void const* = nullptr) noexcept

Consumer-side signal: `handle_on_completed` fired (no-op stub for APEX).

Consumer-side signal: `handle_on_completed` fired, dispatching registered continuations.

Consumer-side signal: `handle_on_completed` fired (no-op stub for ITTNotify).

Consumer-side signal: `handle_on_completed` fired (no-op stub).

constexpr void **frame_mark**(char const* = nullptr) noexcept

Frame boundary marker (no-op stub for APEX).

Emit a frame/stage boundary marker in Tracy timeline.

Frame boundary marker (no-op stub for ITTNotify).

Frame boundary marker (no-op stub).

Parameters

name – Optional name for the frame/stage.

struct **fiber_region**

Public Functions

inline explicit constexpr **fiber_region**(*fiber_region_init_data* const&, *std::size_t*) noexcept

struct **fiber_region_init_data**

struct **fiber_suspend_region**

Public Functions

inline explicit constexpr **fiber_suspend_region**(char const*) noexcept

struct **lock_context**

#include <tracing.hpp>

struct **loop_context**

Public Functions

inline explicit constexpr **loop_context**() noexcept

~loop_context() = default

loop_context(*loop_context* const&) = delete

loop_context &**operator=**(*loop_context* const&) = delete

struct **mark_event**

Public Functions

inline explicit constexpr **mark_event**(char const*) noexcept

struct **region**

Public Functions

inline explicit constexpr **region**(*loop_context*&, *region_init_data* const&, *std::size_t*) noexcept

struct **region_init_data**

struct **scoped_task_timer**

Public Functions

explicit **scoped_task_timer**(*task_timer_data* data) noexcept

~scoped_task_timer()

scoped_task_timer(*scoped_task_timer* const&) = delete

scoped_task_timer &**operator**=(*scoped_task_timer* const&) = delete

void **stop**() noexcept

void **yield**() noexcept

template<typename **T**, typename **State**>

inline void **handle_post_execution**(*T* *thrdptr, *State* s) noexcept

Private Members

bool **stopped_**

task_timer_data **data_**

struct **task_timer_data**

Public Functions

task_timer_data() noexcept = default

inline explicit **task_timer_data**(*std::shared_ptr<util::external_timer::task_wrapper>* data)
noexcept

inline **operator** *std::shared_ptr<util::external_timer::task_wrapper>*() const
noexcept

inline constexpr bool **valid**() const noexcept

Public Members

`std::shared_ptr<util::external_timer::task_wrapper> data`

hpx/tracing/backends/empty.hpp

Defined in header `hpx/tracing/backends/empty.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **tracing**

Functions

`task_timer_data` **create_task_timer**(*threads::thread_description* const &description, *std::uint32_t* parent_locality_id, *threads::thread_id* const &parent_task)

void **update_task_timer**(*task_timer_data* &timer, char const *new_name)

void **tracing_init**(char const *name, int argc, char **argv, *std::uint32_t* rank = 0, *std::uint32_t* size = 1)

void **tracing_finalize**()

void **register_thread**(char const *name)

void **create_counter**(*std::string* const &full_name, *std::string* const &short_name) noexcept

void **sample_counter**(*std::string* const &name, *std::string* const &short_name, double value) noexcept

void **send_parcel**(*std::uint64_t* tag, *std::uint64_t* size, *std::uint64_t* target_locality_id) noexcept

void **recv_parcel**(*std::uint64_t* tag, *std::uint64_t* size, *std::uint64_t* source_locality_id, *std::uint64_t* source_thread_id) noexcept

void **set_enable_parent_task_handler**(enable_parent_task_handler_type f)

struct **annotation_handle**

struct **fiber_region**

struct **fiber_region_init_data**

struct **fiber_suspend_region**

struct **lock_context**

`#include <tracing.hpp>`

```
struct loop_context

struct mark_event

struct region

struct region_init_data

struct scoped_task_timer

struct task_timer_data
```

hpx/tracing/backends/ittnotify.hpp

Defined in header `hpx/tracing/backends/ittnotify.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **tracing**

```
struct fiber_region

struct fiber_region_init_data

struct fiber_suspend_region

struct lock_context
    #include <tracing.hpp>

struct loop_context

struct mark_event

struct region

struct region_init_data

struct scoped_task_timer

struct task_timer_data
```

hpx/tracing/backends/tracy.hpp

Defined in header `hpx/tracing/backends/tracy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **tracing**

struct **fiber_region**

struct **fiber_region_init_data**

struct **fiber_suspend_region**

struct **lock_context**
 #include <tracing.hpp>

struct **loop_context**

struct **mark_event**

struct **region**

struct **region_init_data**

struct **scoped_task_timer**

struct **task_timer_data**

tracy

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/tracy/tracy_tls.hpp

Defined in header `hpx/tracy/tracy_tls.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/tracy/tracy.hpp

Defined in header `hpx/tracy/tracy.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

util

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/util/insert_checked.hpp

Defined in header `hpx/util/insert_checked.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

Functions

template<typename **Iterator**>

constexpr bool **insert_checked**(std::pair<*Iterator*, bool> const &r) noexcept

Helper function for writing predicates that test whether an std::map insertion succeeded. This inline template function negates the need to explicitly write the sometimes lengthy std::pair<*Iterator*, bool> type.

Parameters

r – [in] The return value of a std::map insert operation.

Returns

This function returns **r.second**.

template<typename **Iterator**>

bool **insert_checked**(std::pair<*Iterator*, bool> const &r, *Iterator* &it)

Helper function for writing predicates that test whether an std::map insertion succeeded. This inline template function negates the need to explicitly write the sometimes lengthy std::pair<*Iterator*, bool> type.

Parameters

- **r** – [in] The return value of a std::map insert operation.
- **r** – [out] A reference to an *Iterator*, which is set to **r.first**.
- **it** – [out] on exit, will hold the iterator referring to the inserted element

Returns

This function returns **r.second**.

hpx/util/sed_transform.hpp

Defined in header `hpx/util/sed_transform.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **util**

Functions

bool **parse_sed_expression**(*std::string* const &input, *std::string* &search, *std::string* &replace)

Parse a sed command.

Note: Currently, only supports search and replace syntax (s/search/replace/)

Parameters

- **input** – [in] The content to parse.
- **search** – [out] If the parsing is successful, this string is set to the search expression.
- **replace** – [out] If the parsing is successful, this string is set to the replace expression.

Returns

true if the parsing was successful, *false* otherwise.

struct **sed_transform**

#include <sed_transform.hpp> An unary function object which applies a sed command to its subject and returns the resulting string.

Note: Currently, only supports search and replace syntax (s/search/replace/)

Public Functions

sed_transform(*std::string* const &search, *std::string* replace)

explicit **sed_transform**(*std::string* const &expression)

std::string **operator()**(*std::string* const &input) const

inline explicit **operator bool**() const noexcept

inline bool **operator!**() const noexcept

Private Members

`std::shared_ptr<command> command_`

component_storage

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx/components/component_storage/migrate_from_storage.hpp

Defined in header `hpx/components/component_storage/migrate_from_storage.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

Functions

```
template<typename Component>
future<hpx::id_type> migrate_from_storage(hpx::id_type const &to_resurrect, hpx::id_type const
&target = hpx::invalid_id)
```

Migrate the component with the given id from the specified target storage (resurrect the object)

The function `migrate_from_storage<Component>` will migrate the component referenced by `to_resurrect` from the storage facility specified where the object is currently stored on. It returns a future referring to the migrated component instance. The component instance is resurrected on the locality specified by `target_locality`.

Parameters

- **to_resurrect** – [in] The global id of the component to migrate.
- **target** – [in] The optional locality to resurrect the object on. By default the object is resurrected on the locality it was located on last.

Template Parameters

The – only template argument specifies the component type of the component to migrate from the given storage facility.

Returns

A future representing the global id of the migrated component instance. This should be the same as `to_resurrect`.

hpx/components/component_storage/migrate_to_storage.hpp

Defined in header `hpx/components/component_storage/migrate_to_storage.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

namespace **hpx**

namespace **components**

Functions

```
template<typename Component>
future<hpx::id_type> migrate_to_storage(hpx::id_type const &to_migrate, hpx::id_type const
                                     &target_storage)
```

Migrate the component with the given id to the specified target storage

The function *migrate_to_storage*<*Component*> will migrate the component referenced by *to_migrate* to the storage facility specified with *target_storage*. It returns a future referring to the migrated component instance.

Parameters

- **to_migrate** – [in] The global id of the component to migrate.
- **target_storage** – [in] The id of the storage facility to migrate this object to.

Template Parameters

The – only template argument specifies the component type of the component to migrate to the given storage facility.

Returns

A future representing the global id of the migrated component instance. This should be the same as *migrate_to*.

```
template<typename Derived, typename Stub, typename Data>
inline Derived migrate_to_storage(client_base<Derived, Stub, Data> const &to_migrate,
                                hpx::components::component_storage const &target_storage)
```

Migrate the given component to the specified target storage

The function *migrate_to_storage* will migrate the component referenced by *to_migrate* to the storage facility specified with *target_storage*. It returns a future referring to the migrated component instance.

Parameters

- **to_migrate** – [in] The client side representation of the component to migrate.
- **target_storage** – [in] The id of the storage facility to migrate this object to.

Returns

A client side representation of representing of the migrated component instance. This should be the same as *migrate_to*.

process

See *Public API* for a list of names and headers that are part of the public HPX API.

hpx/components/process/process.hpp

Defined in header `hpx/components/process/process.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **components**

namespace **process**

Functions

```
template<typename ...Ts>  
child execute(hpx::id_type const &id, Ts&&... ts)
```

```
HPX_PROCESS_EXPORT child launch_connecting_locality (std::string const &to_launch,  
std::vector< std::string > const &outer_args={},  
std::vector< std::string > const &outer_env={},  
std::optional< std::uint64_t > spawn_id=nullopt)
```

Launch an executable as a new HPX locality that connects to the currently running (bootstrap) locality via TCP.

This function spawns `to_launch` as a child process configured to join the calling HPX runtime as an additional, connecting locality. It forces the TCP parcellport for bootstrapping, forwards AGAS server address/port information from the current runtime's configuration, lets the operating system pick an ephemeral parcel port for the new locality, and blocks the caller until the spawned locality signals that it has finished starting up (via a named latch derived from the executable name and, optionally, `spawn_id`).

Note: The following environment variables are set (overriding any inherited values) before launching:

- `HPX_AGAS_SERVER_ADDRESS` / `HPX_AGAS_SERVER_PORT` ? taken from the current runtime's `hpx.agas.address` / `hpx.agas.port` configuration entries.
 - `HPX_PARCEL_SERVER_ADDRESS` ? same address as the AGAS server.
 - `HPX_PARCEL_SERVER_PORT` ? set to "0" so the OS assigns an ephemeral port.
 - `HPX_ON_STARTUP_WAIT_ON_LATCH` ? the startup latch name described above, used to synchronize with the caller.
-

Parameters

- **to_launch** – Path to the executable to launch as the connecting locality.
- **outer_args** – Additional command-line arguments appended after the mandatory HPX bootstrap arguments (`--hpx:ignore-batch-env`, `--hpx:ini=hpx.parcel.tcp.priority=1000`, `--hpx:ini=hpx.parcel.bootstrap=tcp`). Defaults to an empty list.
- **outer_env** – Additional environment variable entries in "NAME=value" form (or just "NAME" to set an empty value) that are merged into (and override) the inherited environment before launching the child process. Defaults to an empty list.
- **spawn_id** – Optional identifier used to disambiguate the startup latch name when multiple instances of the same executable are launched concurrently. When present, the latch name is "<exe-stem>/<spawn_id>"; otherwise it is just "<exe-stem>".

Throws

`hpx::exception` – (or a derived type) if the child process could not be started (`process::throw_on_error()` is used).

Returns

A child object representing the launched connecting-locality process, once it has signaled startup completion.

supervision_dispatch

See *Public API* for a list of names and headers that are part of the public *HPX* API.

hpx::supervision::init

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::supervision::finalize`
- `hpx::supervision::is_initialized`

`hpx::shared_future<registry> hpx::supervision::init(hpx::chrono::steady_duration const &discovery_timeout = default_discovery_timeout)`

Performs one-shot, idempotent initialization of the supervision-dispatch runtime for this locality. On the first successful call, this function atomically transitions the internal lifecycle state from *uninitialized* to *initializing*, after incrementing the internal epoch, then owns the entire startup sequence: it creates a local *registry* for `hpx::find_here()`, publishes *event::started* for this locality *before* the registry's symbol name is registered (so that no peer can discover and join a not-yet-started locality), registers that symbol name, and finally performs a single *discover_and_join()* pass to join every currently reachable peer registry. On success the state transitions to *active*; if any step throws, all partial state is rolled back and the lifecycle reverts to *uninitialized* so that a subsequent call can retry from scratch.

Calling `init()` while already *active* is a no-op that resolves immediately without repeating any side effect. Calling it while another call is still *initializing* attaches the caller to the in-flight operation's outcome rather than racing it, so concurrent callers never create more than one registry. Calling it while *finalizing* is in progress is rejected; callers should wait for *finalize()* to complete before re-initializing.

Note: This function has no effect on any state that has not yet been created by a successful call - in particular, no symbol name is ever registered and no event is ever published unless this function (or a concurrent call it is attached to) actually runs the initialization sequence.

Parameters

discovery_timeout – The maximum duration to wait, across all discovery candidates combined, for peer registry symbol names to resolve during the *discover_and_join()* step (see *discover_peers()*).

Returns

A shared future that becomes ready, holding the *registry* owned by this *init()* cycle, once the supervision runtime has reached the *active* state, or that becomes exceptional if initialization fails.

`registry hpx::supervision::init(hpx::launch::sync_policy policy, hpx::chrono::steady_duration const &discovery_timeout = default_discovery_timeout)`

Performs one-shot, idempotent initialization of the supervision-dispatch runtime for this locality, blocking the calling thread until the operation completes. This is the synchronous counterpart of `init(hpx::chrono::steady_duration const&)`: it carries out the exact same lifecycle transition and startup sequence (registry creation, *event::started* publication, symbol name registration, and a single *discover_and_join()* pass), but waits for the resulting future to become ready (or exceptional) before returning, rather than handing the future back to the caller.

Note: As with the asynchronous overload, no symbol name is registered and no event is published unless this call (or a concurrent call it attaches to) actually performs the initialization sequence.

Parameters

- **policy** – Tag selecting the blocking overload of `init()`.
- **discovery_timeout** – The maximum duration to wait, across all discovery candidates combined, for peer registry symbol names to resolve during the *discover_and_join()* step (see *discover_peers()*).

Throws

hpx::exception – if initialization could not complete (e.g. due to a concurrent *finalize()* still in progress). Calling this while already *active* is a no-op that returns immediately.

Returns

The *registry* owned by this *init()* cycle.

hpx::supervision::finalize

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::supervision::init*
- *hpx::supervision::is_initialized*

void **hpx::supervision::finalize()**

Performs one-shot, idempotent teardown of the supervision-dispatch runtime previously started by *init()*. On the first call observing the *active* state, this function atomically transitions the lifecycle to *finalizing*, publishes *event::completed* for the local locality at the current epoch, unregisters the registry's symbol name, and then releases ownership of the registry (relying on *client_base*'s default lifetime management to destroy it once no other references remain) before resetting the lifecycle back to *uninitialized*, allowing a subsequent *init()* call to re-arm the runtime from scratch.

Calling *finalize()* when the runtime is *uninitialized*, still *initializing*, or already *finalizing* is a documented no-op: it resolves immediately without publishing any event, unregistering any symbol name, or otherwise touching component state.

Note: Because *finalize()* is a no-op unless the runtime is currently *active*, it is always safe to call speculatively, e.g. during shutdown, without first checking *is_initialized()*.

hpx::supervision::is_initialized

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::supervision::init`
- `hpx::supervision::finalize`

bool `hpx::supervision::is_initialized()` noexcept

Returns whether the supervision-dispatch runtime for this locality is currently *active*, i.e. has completed *init()* and has not yet been torn down by *finalize()*.

Note: This function never blocks and performs a single atomic load; it is safe to call from any thread, including while *init()* or *finalize()* is concurrently in flight.

Returns

true if the lifecycle state is *active*, *false* if it is *uninitialized*, *initializing*, or *finalizing*.

hpx::supervision::registry

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

class **registry** : public `hpx::components::client_base<registry, server::registry>`

A registry is a lightweight, self-supervising handle for pairing with peer localities. It mirrors a peer's lifecycle state locally via *join()*, and can itself be discovered by name in AGAS like other *supervision_dispatch* components.

hpx::supervision::testing::local_snapshot_peers

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::supervision::testing::set_failure_detection_poll_timeout_for_testing`
- `hpx::supervision::testing::last_join_locality`
- `hpx::supervision::testing::suspend_heartbeat_for_testing`
- `hpx::supervision::testing::failure_detection_sweep_in_flight_for_testing`
- `hpx::supervision::testing::stop_background_loops`

`std::vector<server::peer_snapshot> hpx::supervision::testing::local_snapshot_peers()`

Returns a snapshot of this locality's currently-joined, ready peers, as tracked by the local registry. Not part of the public dispatch API - exists so tests can inspect registry state directly.

hpx::supervision::testing::set_failure_detection_poll_timeout_for_testing

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::supervision::testing::local_snapshot_peers`
- `hpx::supervision::testing::last_join_locality`
- `hpx::supervision::testing::suspend_heartbeat_for_testing`
- `hpx::supervision::testing::failure_detection_sweep_in_flight_for_testing`
- `hpx::supervision::testing::stop_background_loops`

```
void hpx::supervision::testing::set_failure_detection_poll_timeout_for_testing(hpx::chrono::steady_duration
                                                                              const
                                                                              &timeout)
```

Overrides the timeout `failure_detection_loop()` passes to `await_terminal()` on each sweep. Must be called before `init()` starts the loop to take effect for that lifecycle; has no effect on a sweep already in flight. Not part of the public dispatch API - exists only to make failure-detection tests deterministic and fast instead of bound by the real 60s `default_discovery_timeout`.

Parameters

timeout – The new poll timeout.

hpx::supervision::testing::last_join_locality

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::supervision::testing::local_snapshot_peers`
- `hpx::supervision::testing::set_failure_detection_poll_timeout_for_testing`
- `hpx::supervision::testing::suspend_heartbeat_for_testing`
- `hpx::supervision::testing::failure_detection_sweep_in_flight_for_testing`
- `hpx::supervision::testing::stop_background_loops`

```
hpx::id_type hpx::supervision::testing::last_join_locality()
```

Returns the locality most recently returned by `join()`, regardless of whether the `register_observers()` call that followed it went on to succeed or fail. Lets tests verify that a failed `join()` does not leak that locality's local supervision state (see `registry::register_observers()`'s catch block).

hpx::supervision::testing::suspend_heartbeat_for_testing

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::supervision::testing::local_snapshot_peers`
- `hpx::supervision::testing::set_failure_detection_poll_timeout_for_testing`
- `hpx::supervision::testing::last_join_locality`
- `hpx::supervision::testing::failure_detection_sweep_in_flight_for_testing`
- `hpx::supervision::testing::stop_background_loops`

void `hpx::supervision::testing::suspend_heartbeat_for_testing()`

Stops this locality's own `heartbeat_loop()` without finalizing the dispatcher, simulating a hard crash (all lifecycle activity ceases, including the periodic event::running pulse) while staying joined in peers' registries. Idempotent; no-op if `init()` was never called or the loop is already stopped. Not part of the public dispatch API - exists only so failure-detection tests can deterministically simulate silence instead of relying on the absence of explicit calls, which no longer implies silence now that heartbeats are mirrored onto observers' local supervision state.

hpx::supervision::testing::failure_detection_sweep_in_flight_for_testing

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::supervision::testing::local_snapshot_peers`
- `hpx::supervision::testing::set_failure_detection_poll_timeout_for_testing`
- `hpx::supervision::testing::last_join_locality`
- `hpx::supervision::testing::suspend_heartbeat_for_testing`
- `hpx::supervision::testing::stop_background_loops`

bool `hpx::supervision::testing::failure_detection_sweep_in_flight_for_testing()`

Reports whether `failure_detection_loop()` currently has one or more `await_terminal()` calls outstanding against unresponsive peers (i.e. a sweep is mid-flight). Returns false before `init()` is called, between sweeps, and after `finalize()`. Not part of the public dispatch API - exists only so tests can deterministically synchronize on a real in-flight sweep instead of sleeping and hoping the loop got there first.

hpx::supervision::testing::stop_background_loops

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::supervision::testing::local_snapshot_peers`
- `hpx::supervision::testing::set_failure_detection_poll_timeout_for_testing`
- `hpx::supervision::testing::last_join_locality`

- `hpx::supervision::testing::suspend_heartbeat_for_testing`
- `hpx::supervision::testing::failure_detection_sweep_in_flight_for_testing`

void `hpx::supervision::testing::stop_background_loops()`

Stops this locality's `failure_detection_loop()` and `heartbeat_loop()` background tasks (joining both) without otherwise finalizing the dispatcher: unlike `finalize()`, this never publishes `event::completed`, never unregisters the registry symbol name, and never resets the lifecycle state back to uninitialized, so the sentinel's last published event stays stale and peers' `failure_detection_loop()` still eventually times out and observes `target_fenced/rejected_fenced` against this locality. Lets a caller depart the HPX runtime cleanly (e.g. via `hpx::disconnect()`) afterwards without leaving either background `hpx::async` task still running - simulating a worker that dies mid-epoch without corrupting AGAS or hanging runtime shutdown, as opposed to a true crash (no call at all) or a fully graceful departure (`finalize()`). Idempotent; no-op if `init()` was never called or the loops are already stopped. Not part of the public dispatch API - exists only for examples/tests that need to simulate this exact scenario deterministically.

`hpx::supervision::dispatch_work`

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::supervision::invoke_fenced_action`

Warning: doxygenfunction: Unable to resolve function “`hpx::supervision::dispatch_work`” with arguments (`hpx::id_type const&`, `std::uint64_t const`, `Ts&&...`) in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`. Potential matches:

```
- template<typename Action, typename ...Ts> decltype(auto) dispatch_work(Action,
↪discovered_peer const &peer, Ts&&... ts)
- template<typename Action, typename ...Ts> decltype(auto) dispatch_work(Action,
↪hpx::id_type const &target, std::uint64_t const epoch, Ts&&... ts)
- template<typename Action, typename ...Ts> decltype(auto) dispatch_work(hpx::id_type
↪const &target, std::uint64_t const epoch, Ts&&... ts)
```

Warning: doxygenfunction: Unable to resolve function “`hpx::supervision::dispatch_work`” with arguments (`Action`, `hpx::id_type const&`, `std::uint64_t const`, `Ts&&...`) in doxygen xml output for project “hpx” from directory: `../hpx_autodoc`. Potential matches:

```
- template<typename Action, typename ...Ts> decltype(auto) dispatch_work(Action,
↪discovered_peer const &peer, Ts&&... ts)
- template<typename Action, typename ...Ts> decltype(auto) dispatch_work(Action,
↪hpx::id_type const &target, std::uint64_t const epoch, Ts&&... ts)
- template<typename Action, typename ...Ts> decltype(auto) dispatch_work(hpx::id_type
↪const &target, std::uint64_t const epoch, Ts&&... ts)
```

Warning: doxygenfunction: Unable to resolve function “hpx::supervision::dispatch_work” with arguments (Action, discovered_peer const&, Ts&&...) in doxygen xml output for project “hpx” from directory: ../hpx_autodoc. Potential matches:

```
- template<typename Action, typename ...Ts> decltype(auto) dispatch_work(Action,
↳discovered_peer const &peer, Ts&&... ts)
- template<typename Action, typename ...Ts> decltype(auto) dispatch_work(Action,
↳hpx::id_type const &target, std::uint64_t const epoch, Ts&&... ts)
- template<typename Action, typename ...Ts> decltype(auto) dispatch_work(hpx::id_type
↳const &target, std::uint64_t const epoch, Ts&&... ts)
```

hpx::supervision::invoke_fenced_action

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

See also:

- `hpx::supervision::dispatch_work`

```
template<typename Action, typename IdType, typename Epoch, typename ...Ts>
decltype(auto) hpx::supervision::invoke_fenced_action(Action act, IdType target, Epoch const epoch, Ts...
ts)
```

Remote dispatch point that performs the authoritative admission re-check and invokes the wrapped action.

This is the function body that actually runs as the action on the *destination* locality (the target’s own locality, reached via `hpx::colocated` in `dispatch_work()`). It is invoked by `fenced_action` once the action has been dispatched.

The admission check performed here runs on the same locality/thread that owns the target’s *supervision_manager* state, so there is no suspension point between this check and the actual invocation below. This is what closes the client-side/dispatch race: even if the client’s own (non-authoritative) *check_admission()* in `dispatch_work()` returned `admitted`, the target may have latched a terminal event for this epoch in the meantime, and this re-check will catch it.

This re-check is authoritative only because a joining registry (see `components/supervision_dispatch/src/server/registry_server.cpp`) dual-publishes lifecycle mirrors for a joined peer onto that peer’s own locality, in addition to the joining registry’s local copy: `target` must resolve to that same peer locality for this guarantee to hold. Dispatching `target` against an unrelated third locality - one that never received the dual-published mirror for this target - remains out of contract; the re-check performed there consults a *supervision_manager* state that was never seeded for `target` and so cannot detect fencing.

Template Parameters

- **Action** – The wrapped HPX action type to invoke on admission.
- **IdType** – Type of the target identifier forwarded to `act` (this type is always `hpx::id_type`).
- **Epoch** – Type of the fencing epoch value (this type is always `std::uint64_t`).
- **Ts** – Types of the additional arguments forwarded to `act`.

Parameters

- **act** – The action instance to invoke once admission succeeds.
- **target** – Identifier of the component instance being dispatched to; forwarded to `act` (the epoch is fencing metadata only and is not part of `act`’s argument list).

- **epoch** – The fencing epoch to check admission for.
- **ts** – Additional arguments forwarded to `act`.

Throws

`hpx::exception` – with `hpx::error::target_fenced` if the target has latched a terminal event for epoch since the client's own admission check, in which case the wrapped action is not invoked.

Returns

The result of invoking `act`, obtained via `hpx::sync` (run directly/locally, without an extra parcel hop, since this function already executes on the target's locality).

`hpx::supervision::discover_peers`

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::supervision::fan_out_join`
- `hpx::supervision::discover_and_join`

`std::vector<discovered_peer> hpx::supervision::discover_peers(chrono::steady_duration const &timeout = default_discovery_timeout)`

Performs a one-time discovery pull for `supervision_dispatch` peers: concurrently resolves the pinned registry name (see `register_name()`) of every remote locality (`hpx::find_remote_localities()`, which already excludes this locality), bounded by a single wait for `timeout` across all candidates.

Because constructing a registry client from a symbolic name (see `client_base`'s symbolic-name constructor) waits/resolves once the symbol is bound rather than failing fast on one that is not (yet) registered, localities that never called `register_name()` (e.g. because they have not run `init_supervision()` yet) would otherwise hang this call indefinitely. Instead, once `timeout` elapses, only the candidates whose registry client was resolved by then (checked via the non-blocking `is_ready()`) are returned; every other candidate is simply excluded as not currently participating in supervision - `discover_peers()` itself never fails or throws on their account.

Parameters

timeout – The maximum duration to wait, across all candidates combined, for their registry names to resolve.

Returns

The peers whose registry client was resolved within `timeout`, as `discovered_peer` values carrying the `hpx::id_type` locality it is pinned to.

`hpx::supervision::fan_out_join`

Defined in header `hpx/supervision_dispatch.hpp`.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- `hpx::supervision::discover_peers`
- `hpx::supervision::discover_and_join`


```
std::vector<discovered_peer> hpx::supervision::fan_out_join(registry const &local_registry,
                                                           std::vector<discovered_peer> const &peers,
                                                           chrono::steady_duration const &timeout =
                                                           default_discovery_timeout)
```

Reactively fans out join() calls from *local_registry* to every peer in *peers* (typically the result of a prior *discover_peers()* call): for each entry, this calls *local_registry.join(peer.locality)*.

This reuses *registry::join()*'s existing reservation/idempotency machinery unchanged (see *server::registry::reserve_ownership()*) rather than duplicating any of it, so calling *fan_out_join()* more than once with (partially) overlapping peer lists - or racing with an inbound join() call from one of those same peers, e.g. because that peer is concurrently running its own *fan_out_join()* against this locality - is safe and never creates more than one registry entry per peer locality.

fan_out_join() itself is reactive only: it performs exactly one round of join() calls for the given *peers* and starts no background/polling activity of its own.

Parameters

- **local_registry** – The registry to join every peer in *peers* to.
- **peers** – The peers to join, typically returned by a prior *discover_peers()* call.
- **timeout** – The maximum duration to wait, across all peers combined, for their join() calls to settle. Peers whose join() has not settled (or failed) within this bound are silently dropped from the result, rather than hanging or throwing.

Returns

The *discovered_peer* values (locality + join_epoch) for peers whose join() calls settled successfully within *timeout*, in the same relative order as *peers* (with unsuccessful/ timed-out peers omitted, rather than left as gaps). Each returned *discovered_peer::join_epoch* is populated from the corresponding join() call, so callers can dispatch against {*peer.locality*, *peer.join_epoch*} directly, without needing a separate join() call to obtain it.

hpx::supervision::discover_and_join

Defined in header *hpx/supervision_dispatch.hpp*.

See *Public API* for a list of names and headers that are part of the public *HPX* API.

See also:

- *hpx::supervision::discover_peers*
- *hpx::supervision::fan_out_join*

```
std::vector<discovered_peer> hpx::supervision::discover_and_join(registry const &local_registry,
                                                                chrono::steady_duration const
                                                                &timeout =
                                                                default_discovery_timeout)
```

Composes a single reactive discovery-and-join pass for *supervision_dispatch* peers: performs exactly one *discover_peers()* pull to resolve the pinned registry name of every remote locality (*hpx::find_remote_localities()* already excludes this locality, so no separate self-exclusion is needed here), then fans the resulting peer list out to *local_registry* via a single *fan_out_join()* pass.

discover_and_join() introduces no state, polling thread, timer, or repeated broadcast of its own - it is a pure composition of *discover_peers()* and *fan_out_join()*, each of which is itself bounded to a single round of resolution/join calls. Because *fan_out_join()* reuses *registry::join()*'s existing reservation/idempotency machinery unchanged (see *server::registry::reserve_ownership()*), calling *discover_and_join()* more than once - whether to pick up newly started peers or purely by accident - is safe and never creates more than one registry entry per peer

locality; repeated invocations simply return the (stable) join epochs already owned for peers that were previously joined.

Parameters

- **local_registry** – The registry to join every discovered peer to.
- **timeout** – The maximum duration to wait, across all discovery candidates combined, for their registry name to resolve (see *discover_peers()*).

Returns

The *discovered_peer* value that *local_registry* created (or already had) for each peer discovered and successfully joined within *timeout*, in the same relative order as returned by *discover_peers()*.

hpx/supervision_dispatch/server/registry.hpp

Defined in header `hpx/supervision_dispatch/server/registry.hpp`.

See *Public API* for a list of names and headers that are part of the public HPX API.

namespace **hpx**

namespace **supervision**

Fenced action dispatch for the supervision subsystem.

This header provides the machinery to dispatch an HPX action to a target component while enforcing supervision “fencing” semantics: once a target has latched a terminal event for a given epoch, no further actions for that epoch may execute against it. Dispatch performs a cheap, non-authoritative admission check on the caller’s locality and an authoritative re-check on the target’s own locality (via `hpx::colocated`), immediately before invoking the wrapped action, closing the race between admission and invocation.

Types and functions implementing HPX’s supervision and fenced dispatch facilities.

Functions

```
inline bool operator==(joined_peer const &lhs, joined_peer const &rhs) noexcept
```

```
inline bool operator!=(joined_peer const &lhs, joined_peer const &rhs) noexcept
```

```
std::ostream &operator<<(std::ostream &strm, joined_peer const &peer)
```

```
struct joined_peer
```

#include <registry.hpp> Pairs the two values a caller obtains from a successful `registry::join()` and needs to perform a fenced dispatch.

See also:

`dispatch_work()`

See also:

`server::registry::join()`

Public Members

hpx::id_type **target**

The real, colocatable destination for the wrapped action.

The peer's locality id (i.e. `peer_locality`, the value originally passed into `registry::join()`). Forwarded to `hpx::colocated()` and used as the destination of `hpx::sync(act, target, ts...)` inside `dispatch_work()`.

std::uint64_t **join_epoch** = 0

The epoch at which this peer was joined.

Recorded by `registry::join()` and used to identify which registry entry a later `registry::leave()` call refers to - so that a racing re-join of the same peer locality (which mints a fresh `join_epoch` of its own) cannot be mistaken for the join this *joined_peer* was returned from.

namespace **server**

struct **peer_snapshot**

#include <registry.hpp> Plain-data view of a single joined peer, safe to hand out to callers outside the registry (unlike `peer_entry`, does not expose the ready/evict_pending bookkeeping used internally to coordinate concurrent `join()/evict_peer()` calls).

Public Members

hpx::id_type **peer_locality**

The peer locality this entry was joined against.

std::uint64_t **join_epoch**

The epoch at which `peer_locality` was joined.

class **registry** : public *hpx::components::component_base<registry>*

Public Functions

registry()

joined_peer **join**(*hpx::id_type* const &*peer_locality*)

Joins a peer locality and creates or reuses its local supervision state.

Parameters

peer_locality – The peer locality to observe.

std::vector<peer_snapshot> **snapshot_peers**() const

Returns a point-in-time snapshot of all fully joined, non-evicting peers.

Intended for a future failure-detection poller (or other local consumers) that needs a stable, lock-safe list of peers to iterate over without reaching into `peers_` directly. Entries mid-join (`ready == false`) or already scheduled for eviction (`evict_pending == true`) are excluded, so a poller never observes a half-registered or torn-down peer.

Returns

A snapshot of every peer entry with `ready == true` and `evict_pending == false` at the time of the call.

void **leave**(*hpx::id_type* const &peer_locality, *std::uint64_t* join_epoch)

Removes a previously joined peer.

Parameters

- **peer_locality** – The peer locality to leave.
- **join_epoch** – Must match the join epoch currently recorded for **peer_locality** (i.e. the epoch returned by the corresponding *join()*). If **peer_locality** has since been re-joined (fresh epoch) or already evicted, this call is a no-op.

Protected Functions

std::tuple<*hpx::id_type*, *std::uint64_t*, bool> **reserve_ownership**(*hpx::id_type* const &peer_locality)

std::pair<*hpx::id_type*, *hpx::id_type*> **register_observers**(*hpx::id_type* const &peer_locality, *std::uint64_t* join_epoch)

void **evict_peer**(*hpx::id_type* const &peer_locality, *std::uint64_t* join_epoch, *hpx::id_type* keep_alive, bool preserve_terminal_state)

Protected Static Functions

static void **cleanup_peer**(*hpx::id_type* const &peer_locality, *hpx::id_type* const &lifecycle_observer, *hpx::id_type* const &activity_observer, bool preserve_terminal_state)

Unregisters a peer's observers and, unless **preserve_terminal_state** is set, removes its locally tracked supervision state.

Performs the actual peer teardown deferred by *evict_peer()*: unregisters **lifecycle_observer** and **activity_observer** on **peer_locality**, and removes **peer_locality**'s locally tracked supervision state unless **preserve_terminal_state** is true, in which case that state - which was last set to the peer's terminal event by *register_observers()*'s lifecycle callback - is left in place as a tombstone rather than reset to "unknown". This lets any admission check still in flight against **peer_locality** (e.g. *check_admission()*) keep observing the fenced/terminal outcome after eviction has run, instead of racing against it. A subsequent *join()* re-seeding this locality with a fresh epoch naturally overwrites the tombstone. Kept separate from *evict_peer()* because *evict_peer()* only posts this work as a task (via *hpx::post()*) rather than performing it inline.

Parameters

- **peer_locality** – The locality that owns the observers, and whose local supervision state is removed.
- **lifecycle_observer** – The lifecycle observer id to unregister.
- **activity_observer** – The activity observer id to unregister.
- **preserve_terminal_state** – If true, leave **peer_locality**'s local supervision state in place instead of removing it.

Private Members

mutable *hpx::spinlock* **mtx_**

hpx::lcos::local::detail::condition_variable **cond_**

std::map<hpx::id_type, peer_entry> **peers_**

struct **peer_entry**

Internal bookkeeping for a single joined (or joining) peer.

Not exposed outside the registry; see *peer_snapshot* for the plain-data subset safe to hand to external callers.

Public Functions

inline explicit **peer_entry**(*hpx::id_type* const &peer_locality)

Public Members

const *hpx::id_type* **peer_locality**

The locality that owns this peer's. Surfaced read-only via *peer_snapshot::peer_locality*.

hpx::id_type **lifecycle_observer**

The observer id registered on *peer_locality* to receive this peer's terminal lifecycle notification (drives *evict_peer()* via *hpx::post()*).

hpx::id_type **activity_observer**

The observer id registered on *peer_locality* to receive this peer's activity notifications (used to keep *peer_locality*'s local state current between terminal events).

std::uint64_t **join_epoch** = 0

The epoch at which this peer was joined, recorded by *join()* and used by *evict_peer()* (instead of shadow) to identify and used by *evict_peer()* to identify which entry a deferred eviction refers to.

bool **ready** = false

False while a *join()* call has reserved ownership of this peer's locality (i.e. is in the process of performing the remote observer registrations) but has not yet filled in the rest of the entry. Concurrent *join()* calls for the same peer wait on *cond_* instead of racing to register duplicate observers.

bool **evict_pending** = false

True once a terminal notification has been observed for this peer but eviction has not yet completed (deferred via *hpx::post()* to *evict_peer()*). Ensures a terminal notification racing ahead of *join()* completion is deferred instead of dropped, and lets *snapshot_peers()* exclude a peer that is already tearing down.

```
bool evict_preserve_terminal_state = false
```

The `preserve_terminal_state` argument `evict_peer()` was called with when it set `evict_pending` above, remembered so that `join()`'s deferred `cleanup_peer()` call (once the join in progress completes) preserves or drops `peer_locality`'s local supervision state consistently with what the racing terminal notification requested.

2.10 Contributing to HPX

HPX development happens on Github. The following sections are a collection of useful information related to HPX development.

2.10.1 Contributing to HPX

The main source of information to understand the process of how to contribute to HPX can be found in [this document](#)⁹⁷⁴. This is a living document that is constantly updated with relevant information.

2.10.2 HPX governance model

The HPX project is a meritocratic, consensus-based community project. Anyone with an interest in the project can join the community, contribute to the project design and participate in the decision making process. [This document](#)⁹⁷⁵ describes how that participation takes place and how to set about earning merit within the project community.

2.10.3 Release procedure for HPX

Below is a step by step procedure for making an HPX release. We aim to produce two releases per year: one in March-April, and one in September-October.

This is a living document and may not be totally current or accurate. It is an attempt to capture current practices in making an HPX release. Please update it as appropriate.

One way to use this procedure is to print a copy and check off the lines as they are completed to avoid confusion.

1. Notify developers that a release is imminent.
2. For minor and major releases: create and check out a new branch at an appropriate point on `master` with the name `release-major.minor.X`. `major` and `minor` should be the major and minor versions of the release. For patch releases: check out the corresponding `release-major.minor.X` branch.
3. Write release notes in `docs/sphinx/releases/whats_new_${VERSION}.rst`. Keep adding merged PRs and closed issues to this until just before the release is made. Use `tools/generate_pr_issue_list.sh` to generate the lists. Add the new release notes to the table of contents in `docs/sphinx/releases.rst`.
4. Build the docs, and proof-read them. Update any documentation that may have changed, and correct any typos. Pay special attention to:
 - `$HPX_SOURCE/README.rst`
 - Update grant information
 - `docs/sphinx/releases/whats_new_${VERSION}.rst`

⁹⁷⁴ <https://github.com/TheHPXProject/hpx/blob/master/.github/CONTRIBUTING.md>

⁹⁷⁵ <http://hpx.stellar-group.org/documents/governance/>

- docs/sphinx/about_hpx/people.rst
 - Update collaborators
 - Update grant information
5. This step does not apply to patch releases. For APEX:
 - Change the release branch to be the most current release tag available in the APEX `git_external` section in the main `CMakeLists.txt`. Please contact the maintainers of the respective packages to generate a new release to synchronize with the *HPX* release ([APEX⁹⁷⁶](#)).
 6. Make sure `HPX_VERSION_MAJOR/MINOR/SUBMINOR` in `CMakeLists.txt` contain the correct values. Change them if needed.
 7. Change version references in `CITATION.cff`. There are two occurrences. Change year in the copyright file under `/libs/core/version/src/version.cpp`.
 8. This step does not apply to patch releases. Remove features which have been deprecated for at least 2 releases. This involves removing build options which enable those features from the main `CMakeLists.txt` and also deleting all related code and tests from the main source tree.

The general deprecation policy involves a three-step process we have to go through in order to introduce a breaking change:

 - a. First release cycle: add a build option that allows for explicitly disabling any old (now deprecated) code.
 - b. Second release cycle: turn this build option OFF by default.
 - c. Third release cycle: completely remove the old code.

The main `CMakeLists.txt` contains a comment indicating for which version the breaking change was introduced first. In the case of deprecated features which don't have a replacement yet, we keep them around in case (like `Vc` for example).
 9. Update the minimum required versions if necessary (compilers, dependencies, etc.) in `prerequisites.rst`. Update latest tested versions.
 10. Verify that the Jenkins setups for the release branch on Rostam are running and do not display any errors.
 11. Repeat the following steps until satisfied with the release.
 1. Change `HPX_VERSION_TAG` in `CMakeLists.txt` to `-rcN`, where `N` is the current iteration of this step. Start with `-rc1`.
 2. Create a pre-release on GitHub using the script `tools/roll_release.sh`. This script automatically tag with the corresponding release number. The script requires that you have the STE||AR Group signing key.
 3. This step is not necessary for patch releases. Notify hpx-users@stellar-group.org of the availability of the release candidate. Ask users to test the candidate by checking out the release candidate tag.
 4. Allow at least a week for testing of the release candidate.
 - Use `git merge` when possible, and fall back to `git cherry-pick` when needed. For patch releases `git cherry-pick` is most likely your only choice if there have been significant unrelated changes on master since the previous release.
 - Go back to the first step when enough patches have been added.
 - If there are no more patches, continue to make the final release.
 12. Update any occurrences of the latest stable release to refer to the version about to be released. For example, `quickstart.rst` contains instructions to check out the latest stable tag. Make sure that refers to the new version.

⁹⁷⁶ <http://github.com/UO-OACISS/xpress-apex>

13. Add a new entry to the RPM changelog (`cmake/packaging/rpm/Changelog.txt`) with the new version number and a link to the corresponding changelog.
14. Change `HPX_VERSION_TAG` in `CMakeLists.txt` to an empty string.
15. Add the release date to the caption of the current “What’s New” section in the docs, and change the value of `HPX_VERSION_DATE` in `CMakeLists.txt`.
16. Create a release on GitHub using the script `tools/roll_release.sh`. This script automatically tag the with the corresponding release number. The script requires that you have the STELLAR Group signing key.
17. Update the websites (hpx.stellar-group.org⁹⁷⁷ and stellar-group.org <<https://stellar-group.org>>). You can login on wordpress through *this page* <<https://hpx.stellar-group.org/wp-login.php>>. You can update the pages with the following:
 - Update links on the downloads page. Link to the release on GitHub.
 - Documentation links on the docs page (link to generated documentation on GitHub Pages). Follow the style of previous releases.
 - A new blog post announcing the release, which links to downloads and the “What’s New” section in the documentation (see previous releases for examples).
18. Merge release branch into master.
19. Post-release cleanup. Create a new pull request against master with the following changes:
 1. Modify the release procedure if necessary.
 2. Change `HPX_VERSION_TAG` in `CMakeLists.txt` back to `-trunk`.
 3. Increment `HPX_VERSION_MINOR` in `CMakeLists.txt`.
20. Update Vcpkg (<https://github.com/Microsoft/vcpkg>) to pull from latest release.
 - Update version number in `CONTROL`
 - Update tag and SHA512 to that of the new release
21. Update spack (<https://github.com/spack/spack>) with the latest HPX package.
 - Update version number in `hpx/package.py` and SHA256 to that of the new release
22. Announce the release on hpx-users@stellar-group.org, stellar@cct.lsu.edu, allcct@cct.lsu.edu, faculty@csc.lsu.edu, faculty@ece.lsu.edu, the *HPX* Slack channel, the STELLAR-GROUP Discord channel, our list of external collaborators, isocpp.org, reddit.com, HPC Wire, Inside HPC, Heise Online, and a CCT press release.
23. Beer and pizza.

2.10.4 Testing *HPX*

To ensure correctness of *HPX*, we ship a large variety of unit and regression tests. The tests are driven by the `CTest`⁹⁷⁸ tool and are executed automatically on each commit to the *HPX* [GitHub](https://github.com)⁹⁷⁹ repository. In addition, it is encouraged to run the test suite manually to ensure proper operation on your target system. If a test fails for your platform, we highly recommend submitting an issue on our *HPX Issues*⁹⁸⁰ tracker with detailed information about the target system.

⁹⁷⁷ <https://hpx.stellar-group.org>

⁹⁷⁸ <https://gitlab.kitware.com/cmake/community/wikis/doc/ctest/Testing-With-CTest>

⁹⁷⁹ <https://github.com/TheHPXProject/hpx/>

⁹⁸⁰ <https://github.com/TheHPXProject/hpx/issues>

Running tests manually

Running the tests manually is as easy as typing `make tests` && `make test`. This will build all tests and run them once the tests are built successfully. After the tests have been built, you can invoke separate tests with the help of the `ctest` command. You can list all available test targets using `make help | grep tests`. Please see the [CTest Documentation](#)⁹⁸¹ for further details.

Running performance tests

We run performance tests on Piz Daint for each pull request using Jenkins. To run those performance tests locally or on Piz Daint, a script is provided under `tools/perftests_ci/local_run.sh` (to be run in the build directory specifying the *HPX* source directory as the argument to the script, default is `$HOME/projects/hpx_perftests_ci`).

Adding new performance tests

To add a new performance test, you need to wrap the portion of code to benchmark with `hpx::util::perftests_report`, passing the test name, the executor name and the function to time (can be a lambda). This facility is used to output the time results in a json format (format needed to compare the results and plot them). To effectively print them at the end of your test, call `hpx::util::perftests_print_times`. To see an example of use, see `future_overhead_report.cpp`. Finally, you can add the test to the CI report editing the `hpx_targets` variable for the executable name and the `hpx_test_options` variable for the corresponding options to use for the run in the performance test script `.jenkins/cscs-perftests/launch_perftests.sh`. And then run the `tools/perftests_ci/local_run.sh` script to get a reference json run (use the name of the test) to be added in the `tools/perftests_ci/perftest/references/daint_default` directory.

Issue tracker

If you stumble over a bug or missing feature in *HPX*, please submit an issue to our [HPX Issues](#)⁹⁸² page. For more information on how to submit support requests or other means of getting in contact with the developers, please see the [Support Website](#)⁹⁸³ page.

Continuous testing

In addition to manual testing, we run automated tests on various platforms. We also run tests on all pull requests using both [\[github\]](#). You can see the dashboards [CDash HPX dashboard](#)⁹⁸⁴.

2.10.5 Using docker for development

Although it can often be useful to set up a local development environment with system-provided or self-built dependencies, [Docker](#)⁹⁸⁵ provides a convenient alternative to quickly get all the dependencies needed to start development of *HPX*. Our testing setup on [\[github\]](#) uses a docker image to run all tests.

⁹⁸¹ <https://www.cmake.org/cmake/help/latest/manual/ctest.1.html>

⁹⁸² <https://github.com/TheHPXProject/hpx/issues>

⁹⁸³ <https://stellar.cct.lsu.edu/support/>

⁹⁸⁴ <https://cdash.rostam.cct.lsu.edu/index.php?project=HPX>

⁹⁸⁵ <https://www.docker.com>

To get started you need to install [Docker](#)⁹⁸⁶ using whatever means is most convenient on your system. Once you have [Docker](#)⁹⁸⁷ installed, you can pull or directly run the docker image. The image is based on Debian and Clang, and can be found on [Docker Hub](#)⁹⁸⁸. To start a container using the *HPX* build environment, run:

```
$ docker run --interactive --tty stellargroup/build_env:latest bash
```

You are now in an environment where all the *HPX* build and runtime dependencies are present. You can install additional packages according to your own needs. Please see the [Docker Documentation](#)⁹⁸⁹ for more information on using [Docker](#)⁹⁹⁰.

Warning: All changes made within the container are lost when the container is closed. If you want files to persist (e.g., the *HPX* source tree) after closing the container, you can bind directories from the host system into the container (see [Docker Documentation \(Bind mounts\)](#)⁹⁹¹).

2.10.6 Documentation

This documentation is built using [Sphinx](#)⁹⁹², and an automatically generated API reference using [Doxygen](#)⁹⁹³ and [Breathe](#)⁹⁹⁴.

We always welcome suggestions on how to improve our documentation, as well as pull requests with corrections and additions.

Prerequisites

To build the *HPX* documentation, you need recent versions of the following packages:

- python3
- sphinx 4.5.0 (Python package)
- sphinx-book-theme (Python package)
- breathe 4.33.1 (Python package)
- doxygen
- sphinxcontrib-bibtex
- sphinx-copybutton

If the [Python](#)⁹⁹⁵ dependencies are not available through your system package manager, you can install them using the Python package manager `pip`:

```
pip install --user "sphinx<5" sphinx-book-theme breathe sphinxcontrib-bibtex sphinx-  
↪ copybutton
```

You may need to set the following CMake variables to make sure CMake can find the required dependencies.

⁹⁸⁶ <https://www.docker.com>

⁹⁸⁷ <https://www.docker.com>

⁹⁸⁸ https://hub.docker.com/r/stellargroup/build_env/

⁹⁸⁹ <https://docs.docker.com/>

⁹⁹⁰ <https://www.docker.com>

⁹⁹¹ <https://docs.docker.com/storage/bind-mounts/>

⁹⁹² <http://www.sphinx-doc.org>

⁹⁹³ <https://www.doxygen.org>

⁹⁹⁴ <https://breathe.readthedocs.io/en/latest>

⁹⁹⁵ <https://www.python.org>

Doxygen_ROOT:PATH

Specifies where to look for the installation of the [Doxygen](https://www.doxygen.org)⁹⁹⁶ tool.

Sphinx_ROOT:PATH

Specifies where to look for the installation of the [Sphinx](http://www.sphinx-doc.org)⁹⁹⁷ tool.

Breathe_APIDOC_ROOT:PATH

Specifies where to look for the installation of the [Breathe](https://breathe.readthedocs.io/en/latest)⁹⁹⁸ tool.

Building documentation

Enable building of the documentation by setting `HPX_WITH_DOCUMENTATION=ON` during [CMake](https://www.cmake.org)⁹⁹⁹ configuration. To build the documentation, build the `docs` target using your build tool. The default output format is HTML documentation. You can choose alternative output formats (single-page HTML, PDF, and man) with the `HPX_WITH_DOCUMENTATION_OUTPUT_FORMATS` CMake option.

Note: If you add new source files to the Sphinx documentation, you have to run CMake again to have the files included in the build.

Style guide

The documentation is written using reStructuredText. These are the conventions used for formatting the documentation:

- Use, at most, 80 characters per line.
- Top-level headings use over- and underlines with `=`.
- Sub-headings use only underlines with characters in decreasing level of importance: `=`, `-` and `..`
- Use sentence case in headings.
- Refer to common terminology using `:term:`Component``.
- Indent content of directives (`.. directive::`) by three spaces.
- For C++ code samples at the end of paragraphs, use `::` and indent the code sample by 4 spaces.
 - For other languages (or if you don't want a colon at the end of the paragraph), use `.. code-block:: language` and indent by three spaces as with other directives.
- Use `.. list-table::` to wrap tables with a lot of text in cells.

⁹⁹⁶ <https://www.doxygen.org>

⁹⁹⁷ <http://www.sphinx-doc.org>

⁹⁹⁸ <https://breathe.readthedocs.io/en/latest>

⁹⁹⁹ <https://www.cmake.org>

API documentation

The source code is documented using Doxygen. If you add new API documentation either to existing or new source files, make sure that you add the documented source files to the `doxygen_dependencies` variable in `docs/CMakeLists.txt`.

Adding new API documentation

When you add new public APIs to *HPX*, follow these guidelines to ensure the documentation is correctly generated and easy to use.

Documenting headers

At the top of a new header file, include the standard Doxygen documentation block. For example, if the new feature is called *my_new_feature*, you should:

- List the name of the new file under `\file`.
- Specify the page name with `\page` (e.g., `hpx:my_new_feature`).
- Reference the existing header that will include your new file under `\headerfile`.

```
/// \file my_new_feature.hpp
/// \page hpx:my_new_feature
/// \headerfile hpx/existing_header_of_new_feature.hpp
```

Adding to the public API reference

For the documentation to appear in the generated API reference, add your new API to `docs/sphinx/api/public_api.rst` under the appropriate table (usually “Functions”) for the relevant header (for example, `hpx/existing_header_of_new_feature.hpp`).

Including examples

Do **not** inline examples in the API reference. If you want to provide an example of how to use the new API, there are two recommended options:

1. **Documentation page option** Edit an existing relevant manual page to explain the new functionality and include a code example. Use this option if you want to provide additional context about how the API works.
2. **Standalone examples option** Create a separate example under `docs/sphinx/examples/`. Examples in this directory are typically more comprehensive and executable, making them suitable for richer or more complex scenarios.

2.10.7 Module structure

This section explains the structure of an *HPX* module.

The tool `create_library_skeleton.py`¹⁰⁰⁰ can be used to generate a basic skeleton. To create a library skeleton, run the tool in the `libs` subdirectory with the module name as an argument:

```
$ ./create_library_skeleton <lib_name>
```

This creates a skeleton with the necessary files for an *HPX* module. It will not create any actual source files. The structure of this skeleton is as follows:

- `<lib_name>/`
 - `README.rst`
 - `CMakeLists.txt`
 - `cmake`
 - `docs/`
 - * `index.rst`
 - `examples/`
 - * `CMakeLists.txt`
 - `include/`
 - * `hpx/`
 - `<lib_name>`
 - `src/`
 - * `CMakeLists.txt`
 - `tests/`
 - * `CMakeLists.txt`
 - * `unit/`
 - `CMakeLists.txt`
 - * `regressions/`
 - `CMakeLists.txt`
 - * `performance/`
 - `CMakeLists.txt`

A `README.rst` should be always included which explains the basic purpose of the library and a link to the generated documentation.

A main `CMakeLists.txt` is created in the root directory of the module. By default it contains a call to `add_hpx_module` which takes care of most of the boilerplate required for a module. You only need to fill in the source and header files in most cases.

`add_hpx_module` requires a module name. Optional flags are:

Optional single-value arguments are:

- `INSTALL_BINARIES`: Install the resulting library.

¹⁰⁰⁰ https://github.com/TheHPXProject/hpx/blob/master/libs/create_module_skeleton.py

Optional multi-value arguments-are:

- SOURCES: List of source files.
- HEADERS: List of header files.
- COMPAT_HEADERS: List of compatibility header files.
- DEPENDENCIES: Libraries that this module depends on, such as other modules.
- CMAKE_SUBDIRS: List of subdirectories to add to the module.

The `include` directory should contain only headers that other libraries need. For each of those headers, an automatic header test to check for self containment will be generated. Private headers should be placed under the `src` directory. This allows for clear separation. The `cmake` subdirectory may include additional [CMake](https://www.cmake.org)¹⁰⁰¹ scripts needed to generate the respective build configurations.

Compatibility headers (forwarding headers for headers whose location is changed when creating a module, if moving them from the main library) should be placed in an `include_compatibility` directory. This directory is not created by default.

Documentation is placed in the `docs` folder. A empty skeleton for the index is created, which is picked up by the main build system and will be part of the generated documentation. Each header inside the `include` directory will automatically be processed by Doxygen and included into the documentation.

Tests are placed in suitable subdirectories of `tests`.

When in doubt, consult existing modules for examples on how to structure the module.

Finding circular dependencies

Our CI will perform a check to see if there are circular dependencies between modules. In cases where it's not clear what is causing the circular dependency, running the `cpp-dependencies`¹⁰⁰² tool manually can be helpful. It can give you detailed information on exactly which files are causing the circular dependency. If you do not have the `cpp-dependencies` tool already installed, one way of obtaining it is by using our docker image. This way you will have exactly the same environment as on the CI. See *Using docker for development* for details on how to use the docker image.

To produce the graph produced by CI run the following command (HPX_SOURCE is assumed to hold the path to the HPX source directory):

```
$ cpp-dependencies --dir $HPX_SOURCE/libs --graph-cycles circular_dependencies.dot
```

This will produce a `dot` file in the current directory. You can inspect this manually with a text editor. You can also convert this to an image if you have `graphviz` installed:

```
$ dot circular_dependencies.dot -Tsvg -o circular_dependencies.svg
```

This produces an `svg` file in the current directory which shows the circular dependencies. Note that if there are no cycles the image will be empty.

You can use `cpp-dependencies` to print the include paths between two modules.

```
$ cpp-dependencies --dir $HPX_SOURCE/libs --shortest <from> <to>
```

prints all possible paths from the module `<from>` to the module `<to>`. For example, as most modules depend on `config`, the following should give you a long list of paths from `algorithms` to `config`:

¹⁰⁰¹ <https://www.cmake.org>

¹⁰⁰² <https://github.com/tomtom-international/cpp-dependencies>

```
$ cpp-dependencies --dir $HPX_SOURCE/libs --shortest algorithms config
```

The following should report that it can't find a path between the two modules:

```
$ cpp-dependencies --dir $HPX_SOURCE/libs --shortest config algorithms
```

2.11 Releases

2.11.1 List of supported releases

HPX V2.0.0 (TBD)

General changes

Breaking changes

Closed issues

Closed pull requests

HPX V1.11.0 (Jun 30, 2025)

This release is the last version of HPX that supports C++17. Future versions of HPX will require compilation using C++20 or above.

General changes

- Added synchronous versions of all collective operations. Added global predefined communicator objects that are accessible through new APIs: `hpx::collectives::get_world_communicator()` refers to all localities and `hpx::collectives::get_local_communicator()` refers to all threads on the calling locality. We unified the interfaces of the different communicator objects.
- Added `hpx::experimental::run_on_all` allowing to run a given function (possibly concurrently) using a given execution policy.
- Added a helper object `hpx::runtime_manager` that simplifies the initialization of HPX without needing to modify the main function of the application.
- We improved the compatibility with various accelerator frameworks (SYCL, OneAPI).
- Applied build system changes that allow building HPX without any prerequisites. This requires to pass `-DHPX_WITH_FETCH_HWLOC=On` and `-DHPX_WITH_FETCH_BOOST=On` to the [CMake](https://www.cmake.org)¹⁰⁰³ configuration.
- We have performed a lot of code cleanup and refactoring to improve the overall code quality and decrease compile times.
- Added the `hpx::contains` and `hpx::contains_subrange` parallel algorithms.
- Adapted many of HPX' parallel algorithms to be usable with senders/receivers.

¹⁰⁰³ <https://www.cmake.org>

Breaking changes

- We have moved most of the APIs that were defined in the namespace `hpx::parallel::execution` to the namespace `hpx::execution::experimental`. It was not possible to add compatibility facilities that will allow to continue using the old APIs, applications will have to be changed in order to continue functioning correctly.
- The CMake configuration parameter `HPX_WITH_RUN_MAIN_EVERYWHERE` is now deprecated and will be removed in the future. Use the preprocessor macro `HPX_HAVE_RUN_MAIN_EVERYWHERE` on a target-by-target case instead.
- Removed the dysfunctional libfabric parcelport.
- Removed features that were long deprecated (starting V1.8): - `hpx::flush`, `hpx::endl`, `hpx::async_flush`, `hpx::async_endl` - Various enumerator types are now only available as `class enum` requiring explicit scoped use of the enumerator values - Various non-conforming overloads of parallel algorithms - `hpx::for_loop` and friends (now only available as

`hpx::experimental::for_loop`)

- `hpx::parallel::induction` is now only available as `hpx::experimental::induction`
- `hpx::parallel::reduction` and friends are now only available as `hpx::experimental::reduction`
- `hpx::assertion::source_location` is now only available as `hpx::source_location`
- `hpx::lcos::split_future` is now only available as `hpx::split_future`
- `hpx::lcos::wait` and friends have been removed altogether
- `hpx::lcos::wait_any` and friends are now only available as `hpx::wait_any`
- `hpx::lcos::wait_some` and friends are now only available as `hpx::wait_some`
- `hpx::lcos::wait_each` and friends are now only available as `hpx::wait_each`
- `hpx::lcos::wait_all` and friends are now only available as `hpx::wait_all`
- `hpx::lcos::when_all` and friends are now only available as `hpx::when_all`
- `hpx::lcos::when_any` and friends are now only available as `hpx::when_any`
- `hpx::lcos::when_each` and friends are now only available as `hpx::when_each`
- `hpx::lcos::when_some` and friends are now only available as `hpx::when_some`
- `hpx::util::optional` and related facilities are now only available as `hpx::optional`
- `hpx::util::bind` and related facilities are now only available as `hpx::bind`
- `hpx::util::function` and friends are now only available as `hpx::function`
- `hpx::traits::is_bound_action` and related facilities are now only available as `hpx::is_bound_action`
- `hpx::traits::is_bind_expression` and related facilities are now only available as `hpx::is_bind_expression`
- `hpx::traits::is_placeholder` and related facilities are now only available as `hpx::is_placeholder`
- `hpx::lcos::future` and related facilities are now only available as `hpx::future`
- `hpx::memory::intrusive_ptr` is now only available as `hpx::intrusive_ptr`
- `hpx::lcos::local::barrier` is now only available as `hpx::barrier`
- `hpx::lcos::barrier` is now only available as `hpx::distributed::barrier`

- `hpx::lcos::local::cpp20_binary_semaphore` is now only available as `hpx::detail::binary_semaphore`
- `hpx::lcos::local::condition_variable` and friends are now only available as `hpx::condition_variable`
- `hpx::lcos::local::counting_semaphore` and friends are now only available as `hpx::counting_semaphore`
- `hpx::lcos::local::cpp20_latch` and is now only available as `hpx::latch`
- `hpx::lcos::latch` and is now only available as `hpx::distributed::latch`
- `hpx::lcos::local::upgrade_lock` and friends are now only available as `hpx::upgrade_lock`
- `hpx::lcos::local::mutex` and friends are now only available as `hpx::mutex`
- `hpx::lcos::local::spinlock` and friends are now only available as `hpx::spinlock`
- `hpx::lcos::local::call_once` and friends are now only available as `hpx::call_once`
- `hpx::util::annotated_function` and is now only available as `hpx::annotated_function`
- `hpx::components::abstract_simple_component_base` and is now only available as `hpx::components::abstract_component_base`
- `hpx::naming::id_type` and is now only available as `hpx::id_type`

Closed issues

- [Issue #6699¹⁰⁰⁴](#) - Catch lower-level runtime error
- [Issue #6696¹⁰⁰⁵](#) - HPX master breaks with Kokkos
- [Issue #6691¹⁰⁰⁶](#) - `minimum_category` doesn't work with custom iterator categories
- [Issue #6681¹⁰⁰⁷](#) - build break - missing `;`
- [Issue #6658¹⁰⁰⁸](#) - CMake error upon building HPX manually
- [Issue #6648¹⁰⁰⁹](#) - Asio V1.34 deprecates `io_context::work`
- [Issue #6640¹⁰¹⁰](#) - `iterator_facade` doesn't work with custom iterator categories
- [Issue #6636¹⁰¹¹](#) - problem with `hpx::collectives::exclusive_scan`
- [Issue #6623¹⁰¹²](#) - HPX serialization error with `std::vector<std::vector<std::vector<float>>>`
- [Issue #6616¹⁰¹³](#) - Add flux support to HPX to run on El Cap
- [Issue #6615¹⁰¹⁴](#) - Too many fails test after installed hpx
- [Issue #6605¹⁰¹⁵](#) - Partitionend vector copy constructor is broken

¹⁰⁰⁴ <https://github.com/TheHPXProject/hpx/issues/6699>

¹⁰⁰⁵ <https://github.com/TheHPXProject/hpx/issues/6696>

¹⁰⁰⁶ <https://github.com/TheHPXProject/hpx/issues/6691>

¹⁰⁰⁷ <https://github.com/TheHPXProject/hpx/issues/6681>

¹⁰⁰⁸ <https://github.com/TheHPXProject/hpx/issues/6658>

¹⁰⁰⁹ <https://github.com/TheHPXProject/hpx/issues/6648>

¹⁰¹⁰ <https://github.com/TheHPXProject/hpx/issues/6640>

¹⁰¹¹ <https://github.com/TheHPXProject/hpx/issues/6636>

¹⁰¹² <https://github.com/TheHPXProject/hpx/issues/6623>

¹⁰¹³ <https://github.com/TheHPXProject/hpx/issues/6616>

¹⁰¹⁴ <https://github.com/TheHPXProject/hpx/issues/6615>

¹⁰¹⁵ <https://github.com/TheHPXProject/hpx/issues/6605>

- [Issue #6586](#)¹⁰¹⁶ - Bullet points in quick start/installing HPX section in documentation incorrectly rendered
- [Issue #6563](#)¹⁰¹⁷ - Compilation issues on Grace Hopper
- [Issue #6544](#)¹⁰¹⁸ - Errors in Public Distributed Api for all_to_all and gather_there
- [Issue #6519](#)¹⁰¹⁹ - Option `-hpx:queuing=local-priority-lifo` is not configured
- [Issue #6501](#)¹⁰²⁰ - HPX 1.10 Failed Linking CXX executable for arm64-osx
- [Issue #5728](#)¹⁰²¹ - Add optional `fetch_content` support for needed Boost libraries

Closed pull requests

- [PR #6716](#)¹⁰²² - Fixing some of the reported linker warnings
- [PR #6705](#)¹⁰²³ - Adding gcc/15 to jenkins
- [PR #6701](#)¹⁰²⁴ - Attempting to fix shutdown hang on `exception_info`
- [PR #6698](#)¹⁰²⁵ - Making sure `.hpp.in` files are not being installed
- [PR #6697](#)¹⁰²⁶ - Minor docs fix
- [PR #6695](#)¹⁰²⁷ - Adding missing `‘;’`
- [PR #6693](#)¹⁰²⁸ - Adding `llvm/19` and `20` and `cmake/4` Jenkins
- [PR #6692](#)¹⁰²⁹ - Better implementation of `minimal_category`
- [PR #6690](#)¹⁰³⁰ - Fixing bad `#include` in example
- [PR #6689](#)¹⁰³¹ - Fix unreachable code warning in `wait_all`
- [PR #6687](#)¹⁰³² - `lci pp`: change default `ndevices=2` and `progress_type=worker`; improve document
- [PR #6686](#)¹⁰³³ - `lci pp`: upgrade LCI `autofetch` target to `1.7.9`
- [PR #6685](#)¹⁰³⁴ - Improve `run_on_all` implementation and tests
- [PR #6683](#)¹⁰³⁵ - Fix bad element comparison for `reduce_by_key`
- [PR #6682](#)¹⁰³⁶ - Add C++23 `std::generator` equivalence test and fix missing semicolon
- [PR #6680](#)¹⁰³⁷ - Add `oneapi` device init workaround

¹⁰¹⁶ <https://github.com/TheHPXProject/hpx/issues/6586>

¹⁰¹⁷ <https://github.com/TheHPXProject/hpx/issues/6563>

¹⁰¹⁸ <https://github.com/TheHPXProject/hpx/issues/6544>

¹⁰¹⁹ <https://github.com/TheHPXProject/hpx/issues/6519>

¹⁰²⁰ <https://github.com/TheHPXProject/hpx/issues/6501>

¹⁰²¹ <https://github.com/TheHPXProject/hpx/issues/5728>

¹⁰²² <https://github.com/TheHPXProject/hpx/pull/6716>

¹⁰²³ <https://github.com/TheHPXProject/hpx/pull/6705>

¹⁰²⁴ <https://github.com/TheHPXProject/hpx/pull/6701>

¹⁰²⁵ <https://github.com/TheHPXProject/hpx/pull/6698>

¹⁰²⁶ <https://github.com/TheHPXProject/hpx/pull/6697>

¹⁰²⁷ <https://github.com/TheHPXProject/hpx/pull/6695>

¹⁰²⁸ <https://github.com/TheHPXProject/hpx/pull/6693>

¹⁰²⁹ <https://github.com/TheHPXProject/hpx/pull/6692>

¹⁰³⁰ <https://github.com/TheHPXProject/hpx/pull/6690>

¹⁰³¹ <https://github.com/TheHPXProject/hpx/pull/6689>

¹⁰³² <https://github.com/TheHPXProject/hpx/pull/6687>

¹⁰³³ <https://github.com/TheHPXProject/hpx/pull/6686>

¹⁰³⁴ <https://github.com/TheHPXProject/hpx/pull/6685>

¹⁰³⁵ <https://github.com/TheHPXProject/hpx/pull/6683>

¹⁰³⁶ <https://github.com/TheHPXProject/hpx/pull/6682>

¹⁰³⁷ <https://github.com/TheHPXProject/hpx/pull/6680>

- PR #6679¹⁰³⁸ - Fix sycl deprecations
- PR #6678¹⁰³⁹ - Fix oneapi overloads
- PR #6677¹⁰⁴⁰ - Offer a runtime manager object
- PR #6676¹⁰⁴¹ - Mention the HPX book
- PR #6675¹⁰⁴² - Bump required version of JSON library
- PR #6674¹⁰⁴³ - Issue 6631
- PR #6673¹⁰⁴⁴ - Fix: FindTBB.cmake cannot find correct TBB library. #6504
- PR #6672¹⁰⁴⁵ - Update modules.rst
- PR #6670¹⁰⁴⁶ - Add base template template param to execution_policy
- PR #6669¹⁰⁴⁷ - Add execution policy support to run_on_all
- PR #6667¹⁰⁴⁸ - Making sure bound threads are rescheduled on their original core
- PR #6666¹⁰⁴⁹ - Improve documentation for reduction operations
- PR #6664¹⁰⁵⁰ - Fix CMake template when fetching Boost
- PR #6663¹⁰⁵¹ - More run_on_all overloads
- PR #6662¹⁰⁵² - Fix “unary minus operator applied to unsigned type” warning
- PR #6661¹⁰⁵³ - Adding simple experimental::run_on_all
- PR #6659¹⁰⁵⁴ - fix(reduce): Initialize accumulator with init instead of first element
- PR #6656¹⁰⁵⁵ - Add missing channel_communicator::get_info
- PR #6652¹⁰⁵⁶ - Adding channel-based ping-pong example
- PR #6650¹⁰⁵⁷ - Adding constructor overloads to partitioned_vector
- PR #6649¹⁰⁵⁸ - Remove the use of deprecated asio::io_context::work
- PR #6645¹⁰⁵⁹ - Fixing collectives::exclusive_scan
- PR #6644¹⁰⁶⁰ - Update result_type in set_union.hpp

¹⁰³⁸ <https://github.com/TheHPXProject/hpx/pull/6679>

¹⁰³⁹ <https://github.com/TheHPXProject/hpx/pull/6678>

¹⁰⁴⁰ <https://github.com/TheHPXProject/hpx/pull/6677>

¹⁰⁴¹ <https://github.com/TheHPXProject/hpx/pull/6676>

¹⁰⁴² <https://github.com/TheHPXProject/hpx/pull/6675>

¹⁰⁴³ <https://github.com/TheHPXProject/hpx/pull/6674>

¹⁰⁴⁴ <https://github.com/TheHPXProject/hpx/pull/6673>

¹⁰⁴⁵ <https://github.com/TheHPXProject/hpx/pull/6672>

¹⁰⁴⁶ <https://github.com/TheHPXProject/hpx/pull/6670>

¹⁰⁴⁷ <https://github.com/TheHPXProject/hpx/pull/6669>

¹⁰⁴⁸ <https://github.com/TheHPXProject/hpx/pull/6667>

¹⁰⁴⁹ <https://github.com/TheHPXProject/hpx/pull/6666>

¹⁰⁵⁰ <https://github.com/TheHPXProject/hpx/pull/6664>

¹⁰⁵¹ <https://github.com/TheHPXProject/hpx/pull/6663>

¹⁰⁵² <https://github.com/TheHPXProject/hpx/pull/6662>

¹⁰⁵³ <https://github.com/TheHPXProject/hpx/pull/6661>

¹⁰⁵⁴ <https://github.com/TheHPXProject/hpx/pull/6659>

¹⁰⁵⁵ <https://github.com/TheHPXProject/hpx/pull/6656>

¹⁰⁵⁶ <https://github.com/TheHPXProject/hpx/pull/6652>

¹⁰⁵⁷ <https://github.com/TheHPXProject/hpx/pull/6650>

¹⁰⁵⁸ <https://github.com/TheHPXProject/hpx/pull/6649>

¹⁰⁵⁹ <https://github.com/TheHPXProject/hpx/pull/6645>

¹⁰⁶⁰ <https://github.com/TheHPXProject/hpx/pull/6644>

- PR #6643¹⁰⁶¹ - Update result_type in set_union.hpp
- PR #6642¹⁰⁶² - Allowing to use custom iterator tags with iterator_facade
- PR #6641¹⁰⁶³ - Allowing for zip-iterator to refer to sequences of different length
- PR #6639¹⁰⁶⁴ - docs: Fix spelling in example dictionary
- PR #6638¹⁰⁶⁵ - Update set_union.hpp
- PR #6637¹⁰⁶⁶ - lci/mpi pp: fix the case when non-zero-copy data is larger than INT_MAX
- PR #6635¹⁰⁶⁷ - Adding simplified reduction overload
- PR #6634¹⁰⁶⁸ - Fixed issue 6634: Unqualified calls to insertion_sort
- PR #6633¹⁰⁶⁹ - Increase timeouts for CircleCI tests
- PR #6630¹⁰⁷⁰ - Fix CPUId test
- PR #6628¹⁰⁷¹ - Link acllocal with acllocal-1.16 as hwloc asks for it
- PR #6626¹⁰⁷² - Fixing MPI parcel port issue exposed by #6623
- PR #6622¹⁰⁷³ - Newbranch:HPX-Based Task Scheduler with CUDA-Quantum Integration & Benchmarking
- PR #6621¹⁰⁷⁴ - HPX-Based Task Scheduler with CUDA-Quantum Integration & Benchmarking
- PR #6620¹⁰⁷⁵ - new test: very big tchunk
- PR #6619¹⁰⁷⁶ - mpi pp: fix transmission chunk send
- PR #6617¹⁰⁷⁷ - Adding support for the Flux job scheduling environment
- PR #6614¹⁰⁷⁸ - Fix fallback to module mode for CMake finding Boost
- PR #6613¹⁰⁷⁹ - Fix partitioned_vector_handle_values test
- PR #6612¹⁰⁸⁰ - Fixing naming convention for pp constant
- PR #6611¹⁰⁸¹ - Fix Hwloc fetch content
- PR #6610¹⁰⁸² - Add docs for synchronous collective operations
- PR #6609¹⁰⁸³ - Update perfest CI reference measurements

¹⁰⁶¹ <https://github.com/TheHPXProject/hpx/pull/6643>

¹⁰⁶² <https://github.com/TheHPXProject/hpx/pull/6642>

¹⁰⁶³ <https://github.com/TheHPXProject/hpx/pull/6641>

¹⁰⁶⁴ <https://github.com/TheHPXProject/hpx/pull/6639>

¹⁰⁶⁵ <https://github.com/TheHPXProject/hpx/pull/6638>

¹⁰⁶⁶ <https://github.com/TheHPXProject/hpx/pull/6637>

¹⁰⁶⁷ <https://github.com/TheHPXProject/hpx/pull/6635>

¹⁰⁶⁸ <https://github.com/TheHPXProject/hpx/pull/6634>

¹⁰⁶⁹ <https://github.com/TheHPXProject/hpx/pull/6633>

¹⁰⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6630>

¹⁰⁷¹ <https://github.com/TheHPXProject/hpx/pull/6628>

¹⁰⁷² <https://github.com/TheHPXProject/hpx/pull/6626>

¹⁰⁷³ <https://github.com/TheHPXProject/hpx/pull/6622>

¹⁰⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6621>

¹⁰⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6620>

¹⁰⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6619>

¹⁰⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6617>

¹⁰⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6614>

¹⁰⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6613>

¹⁰⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6612>

¹⁰⁸¹ <https://github.com/TheHPXProject/hpx/pull/6611>

¹⁰⁸² <https://github.com/TheHPXProject/hpx/pull/6610>

¹⁰⁸³ <https://github.com/TheHPXProject/hpx/pull/6609>

- PR #6608¹⁰⁸⁴ - Partially support data parallel for_loop
- PR #6607¹⁰⁸⁵ - Cleaning up copy_component facility
- PR #6606¹⁰⁸⁶ - Making sure copy_component creates a new gid
- PR #6600¹⁰⁸⁷ - Fixing sync collectives
- PR #6599¹⁰⁸⁸ - Make HPX_HAVE_RUN_MAIN_EVERYWHERE application specific
- PR #6598¹⁰⁸⁹ - Adding synchronous collective operations
- PR #6596¹⁰⁹⁰ - Minor fixes and optimizations
- PR #6595¹⁰⁹¹ - Rfa parallel
- PR #6594¹⁰⁹² - Move get_stack_ptr to source
- PR #6593¹⁰⁹³ - Fix outdated documentation and missing flags
- PR #6592¹⁰⁹⁴ - HPX_HAVE_THREADS_GET_STACK_POINTER to match builtin_frame_address feature test
- PR #6591¹⁰⁹⁵ - Feature test for __builtin_frame_address
- PR #6590¹⁰⁹⁶ - Add device guard for noexcept
- PR #6587¹⁰⁹⁷ - Fix bullet points in Quickstart
- PR #6585¹⁰⁹⁸ - Fixed escape characters format to handle warning due to misinterpretation of syntax
- PR #6583¹⁰⁹⁹ - Execute feature test for at_quick_exit
- PR #6582¹¹⁰⁰ - Accommodate for CircleCI reduce available number of cores to two
- PR #6581¹¹⁰¹ - Attempting to work around a Boost.Spirit problem
- PR #6580¹¹⁰² - mpi pp: fix messages larger than INT_MAX
- PR #6578¹¹⁰³ - Remove leftovers from libfabric parcelport
- PR #6577¹¹⁰⁴ - Download Boost from their own archives, not from Sourceforge
- PR #6576¹¹⁰⁵ - Fix CMake warning issued since CMake V3.30
- PR #6575¹¹⁰⁶ - Replace previously downloaded CDash conv.xml with local version

¹⁰⁸⁴ <https://github.com/TheHPXProject/hpx/pull/6608>

¹⁰⁸⁵ <https://github.com/TheHPXProject/hpx/pull/6607>

¹⁰⁸⁶ <https://github.com/TheHPXProject/hpx/pull/6606>

¹⁰⁸⁷ <https://github.com/TheHPXProject/hpx/pull/6600>

¹⁰⁸⁸ <https://github.com/TheHPXProject/hpx/pull/6599>

¹⁰⁸⁹ <https://github.com/TheHPXProject/hpx/pull/6598>

¹⁰⁹⁰ <https://github.com/TheHPXProject/hpx/pull/6596>

¹⁰⁹¹ <https://github.com/TheHPXProject/hpx/pull/6595>

¹⁰⁹² <https://github.com/TheHPXProject/hpx/pull/6594>

¹⁰⁹³ <https://github.com/TheHPXProject/hpx/pull/6593>

¹⁰⁹⁴ <https://github.com/TheHPXProject/hpx/pull/6592>

¹⁰⁹⁵ <https://github.com/TheHPXProject/hpx/pull/6591>

¹⁰⁹⁶ <https://github.com/TheHPXProject/hpx/pull/6590>

¹⁰⁹⁷ <https://github.com/TheHPXProject/hpx/pull/6587>

¹⁰⁹⁸ <https://github.com/TheHPXProject/hpx/pull/6585>

¹⁰⁹⁹ <https://github.com/TheHPXProject/hpx/pull/6583>

¹¹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/6582>

¹¹⁰¹ <https://github.com/TheHPXProject/hpx/pull/6581>

¹¹⁰² <https://github.com/TheHPXProject/hpx/pull/6580>

¹¹⁰³ <https://github.com/TheHPXProject/hpx/pull/6578>

¹¹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/6577>

¹¹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/6576>

¹¹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/6575>

- PR #6570¹¹⁰⁷ - Update exception_list.hpp
- PR #6569¹¹⁰⁸ - Update exception_list.hpp
- PR #6567¹¹⁰⁹ - Fix vectorization error on copy algorithm
- PR #6566¹¹¹⁰ - lci pp: fix messages larger than INT_MAX
- PR #6565¹¹¹¹ - Moving most of APIs from hpx::parallel::execution to hpx::execution::experimental
- PR #6564¹¹¹² - Remove superfluous HPX_MOVE()
- PR #6562¹¹¹³ - Fix doc return type of broadcast_to
- PR #6560¹¹¹⁴ - Fixes for bit_cast on 32bit systems
- PR #6559¹¹¹⁵ - Making sure that all parcellport counters are unavailable if no networking is needed or configured
- PR #6558¹¹¹⁶ - Remove CSCS CI's
- PR #6556¹¹¹⁷ - Set copyright year in generated files
- PR #6553¹¹¹⁸ - Fix omp vectorization pragma errors
- PR #6551¹¹¹⁹ - Update building_hpx.rst
- PR #6550¹¹²⁰ - Partitioned vector updates
- PR #6549¹¹²¹ - Fix CMake conditionals checking ENV variables
- PR #6548¹¹²² - Update CONTRIBUTING.md
- PR #6546¹¹²³ - Fix incorrect signature of distributed API functions
- PR #6543¹¹²⁴ - Throwing an exception derived from std::bad_alloc on OOM conditions
- PR #6539¹¹²⁵ - Use thread-safe cache in thread_local_caching_allocator
- PR #6537¹¹²⁶ - Update README.rst
- PR #6531¹¹²⁷ - More fixes for the Boost package
- PR #6527¹¹²⁸ - Improve the LCI parcellport documentation
- PR #6525¹¹²⁹ - Addressing cmake warnings issued starting V3.30

¹¹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/6570>

¹¹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/6569>

¹¹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/6567>

¹¹¹⁰ <https://github.com/TheHPXProject/hpx/pull/6566>

¹¹¹¹ <https://github.com/TheHPXProject/hpx/pull/6565>

¹¹¹² <https://github.com/TheHPXProject/hpx/pull/6564>

¹¹¹³ <https://github.com/TheHPXProject/hpx/pull/6562>

¹¹¹⁴ <https://github.com/TheHPXProject/hpx/pull/6560>

¹¹¹⁵ <https://github.com/TheHPXProject/hpx/pull/6559>

¹¹¹⁶ <https://github.com/TheHPXProject/hpx/pull/6558>

¹¹¹⁷ <https://github.com/TheHPXProject/hpx/pull/6556>

¹¹¹⁸ <https://github.com/TheHPXProject/hpx/pull/6553>

¹¹¹⁹ <https://github.com/TheHPXProject/hpx/pull/6551>

¹¹²⁰ <https://github.com/TheHPXProject/hpx/pull/6550>

¹¹²¹ <https://github.com/TheHPXProject/hpx/pull/6549>

¹¹²² <https://github.com/TheHPXProject/hpx/pull/6548>

¹¹²³ <https://github.com/TheHPXProject/hpx/pull/6546>

¹¹²⁴ <https://github.com/TheHPXProject/hpx/pull/6543>

¹¹²⁵ <https://github.com/TheHPXProject/hpx/pull/6539>

¹¹²⁶ <https://github.com/TheHPXProject/hpx/pull/6537>

¹¹²⁷ <https://github.com/TheHPXProject/hpx/pull/6531>

¹¹²⁸ <https://github.com/TheHPXProject/hpx/pull/6527>

¹¹²⁹ <https://github.com/TheHPXProject/hpx/pull/6525>

- PR #6522¹¹³⁰ - Fixing distance test
- PR #6520¹¹³¹ - Adding optional handshakes to acknowledge the received data
- PR #6518¹¹³² - Make sure that `-hpx:ini` log settings take effect
- PR #6512¹¹³³ - Minor cleanup of `future_data`
- PR #6510¹¹³⁴ - Include Boost as CMake subproject
- PR #6509¹¹³⁵ - Add components documentation
- PR #6508¹¹³⁶ - Fix typo: `s/unititialized/uninitialized/`
- PR #6507¹¹³⁷ - Update LSU Jenkins libraries to match Rostam 3.0 with RHEL9
- PR #6503¹¹³⁸ - Fix 2 tests on FreeBSD by initializing `freebsd_envron`
- PR #6499¹¹³⁹ - Fix crash in `get_executable_filename` on FreeBSD
- PR #6498¹¹⁴⁰ - Avoid rewriting `defines.hpp`
- PR #6497¹¹⁴¹ - Contains and `contains_subrange` parallel algorithm implementation GSOC 2024
- PR #6496¹¹⁴² - Prevent usage of CMake `try_run` on crosscompiling
- PR #6494¹¹⁴³ - Add unit test cases and fixes for the S/R versions of the parallel algorithms
- PR #6487¹¹⁴⁴ - Fixing security vulnerabilities reported by MSVC security checks
- PR #6486¹¹⁴⁵ - Create `codeql.yml`
- PR #6474¹¹⁴⁶ - Remove remnants of `libfabric` `parcelport`
- PR #6473¹¹⁴⁷ - Add documentation for distributed implementations of `post`, `async`, `sync` and `dataflow`
- PR #6471¹¹⁴⁸ - Add `distance.cpp` test in CMake
- PR #6468¹¹⁴⁹ - Small vector relocation
- PR #6448¹¹⁵⁰ - Standardising Benchmarks, with support for `nanobench` as an option for its backend
- PR #6365¹¹⁵¹ - Release V1.10.0
- PR #6089¹¹⁵² - Implementing p2079

¹¹³⁰ <https://github.com/TheHPXProject/hpx/pull/6522>

¹¹³¹ <https://github.com/TheHPXProject/hpx/pull/6520>

¹¹³² <https://github.com/TheHPXProject/hpx/pull/6518>

¹¹³³ <https://github.com/TheHPXProject/hpx/pull/6512>

¹¹³⁴ <https://github.com/TheHPXProject/hpx/pull/6510>

¹¹³⁵ <https://github.com/TheHPXProject/hpx/pull/6509>

¹¹³⁶ <https://github.com/TheHPXProject/hpx/pull/6508>

¹¹³⁷ <https://github.com/TheHPXProject/hpx/pull/6507>

¹¹³⁸ <https://github.com/TheHPXProject/hpx/pull/6503>

¹¹³⁹ <https://github.com/TheHPXProject/hpx/pull/6499>

¹¹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/6498>

¹¹⁴¹ <https://github.com/TheHPXProject/hpx/pull/6497>

¹¹⁴² <https://github.com/TheHPXProject/hpx/pull/6496>

¹¹⁴³ <https://github.com/TheHPXProject/hpx/pull/6494>

¹¹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/6487>

¹¹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/6486>

¹¹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/6474>

¹¹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/6473>

¹¹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/6471>

¹¹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/6468>

¹¹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/6448>

¹¹⁵¹ <https://github.com/TheHPXProject/hpx/pull/6365>

¹¹⁵² <https://github.com/TheHPXProject/hpx/pull/6089>

2.11.2 List of older releases

HPX V1.10.0 (May 29, 2024)

General changes

- The HPX documentation has seen a major overhaul for this release. We finished documenting the public local HPX API, we have added migration guides from widely used parallelization platforms to HPX (OpenMP, TBB, and MPI).
- We have added facilities enabling optimizations for trivially-relocatable types (see [P1144](#)¹¹⁵³ for more details).
- We have added (and use) the `scope_xxx` helper facilities as specified by the C++ library fundamentals TS v3 (see: [N4948](#)¹¹⁵⁴).
- We have added configuration options that allow to build HPX without pre-installing any prerequisites. Use `HPX_WITH_FETCH_HWLOC=On` to have [Portable Hardware Locality \(HWLOC\)](#)¹¹⁵⁵ installed for you. Similarly, setting `HPX_WITH_FETCH_BOOST=On` during configuration time will install the necessary [Boost](#)¹¹⁵⁶ libraries (currently V1.84.0).
- We have performed a lot of code cleanup and refactoring to improve the overall code quality and decrease compile times.
- The collective operations APIs have seen an unification, we have fixed issues and performance problems for the collectives.
- The HPX executors have seen a streamlining and some consistency changes. We have applied many performance improvements to the executor implementations that directly positively impact the performance of our parallel algorithms.
- We have added a new parcelport allowing to use Gasnet as a communication platform.
- We have added optimizations to various parcelports improving overall communication performance. This includes - amongst other things - send immediate optimizations and receiver-side zero-copy optimizations.
- Futures will now execute the associated task eagerly and inline on any wait operation if the task has not started running yet. This feature can be enabled using the `HPX_COROUTINES_WITH_THREAD_SCHEDULE_HINT_RUNS_AS_CHILD=On` configuration setting (which is *Off* by default).
- We have enabled using json files to supply configuration information through the command line. This feature can be enabled with the configuration option `HPX_COMMAND_LINE_HANDLING_WITH_JSON_CONFIGURATION_FILES=On`. This functionality depends on the external [JSON library](#)¹¹⁵⁷, which can be built at configuration time by supplying `HPX_WITH_FETCH_JSON=On` to [CMake](#)¹¹⁵⁸.
- We have applied many fixes to our CUDA, ROCm, and SYCL build environments.

¹¹⁵³ <https://wg21.link/p1144>

¹¹⁵⁴ <http://wg21.link/n4948>

¹¹⁵⁵ <https://www.open-mpi.org/projects/hwloc/>

¹¹⁵⁶ <https://www.boost.org/>

¹¹⁵⁷ <https://github.com/nlohmann/json>

¹¹⁵⁸ <https://www.cmake.org>

Breaking changes

- The `CMake`¹¹⁵⁹ configuration keys `SOMELIB_ROOT` (e.g., `BOOST_ROOT`) have been renamed to `Somelib_ROOT` (e.g., `Boost_ROOT`) to avoid warnings when using newer versions of `CMake`¹¹⁶⁰. Please update your scripts accordingly. For now, the old variable names are re-assigned to the new names and unset in the `CMake`¹¹⁶¹ cache.

Closed issues

- [Issue #6466](#)¹¹⁶² - No access limitations to Wiki
- [Issue #6461](#)¹¹⁶³ - `handle_received_parcel`s may never return
- [Issue #6459](#)¹¹⁶⁴ - Building HPX
- [Issue #6451](#)¹¹⁶⁵ - HPX hangs at the very end
- [Issue #6446](#)¹¹⁶⁶ - Issue on page `/manual/getting_hpx.html`
- [Issue #6443](#)¹¹⁶⁷ - PR #6435 (`parcel_layer_tweaks`) broke Octo-Tiger
- [Issue #6440](#)¹¹⁶⁸ - HPX does not compile with MSVC of Visual Studio 2022 17.9+
- [Issue #6437](#)¹¹⁶⁹ - HPX 1.9.1 does not compile on Fedora with `#pragma message: [Parallel STL message]: "Vectorized algorithm unimplemented, redirected to serial"`
- [Issue #6419](#)¹¹⁷⁰ - Enhancement of the macro functionalities within `hpx`
- [Issue #6417](#)¹¹⁷¹ - The current HPX master branch is still not compatible with Kokkos 4.0.1
- [Issue #6414](#)¹¹⁷² - Current HPX master causes segfaults within Octo-Tiger
- [Issue #6412](#)¹¹⁷³ - Clangd (Language Server) throws error for `__integer_pack` at `pack.hpp`
- [Issue #6407](#)¹¹⁷⁴ - Cannot build Kokkos 4.0.01 with current HPX master
- [Issue #6405](#)¹¹⁷⁵ - Spack Build Error with ROCm 5.7.0
- [Issue #6398](#)¹¹⁷⁶ - HPX sets affinity wrong with multiple processes per node and LCI `parcelport` enabled
- [Issue #6392](#)¹¹⁷⁷ - [Feature] Install dependencies using `CMake`
- [Issue #6388](#)¹¹⁷⁸ - HPX error: "Host not found" when running on Expanse with 128 nodes

¹¹⁵⁹ <https://www.cmake.org>

¹¹⁶⁰ <https://www.cmake.org>

¹¹⁶¹ <https://www.cmake.org>

¹¹⁶² <https://github.com/TheHPXProject/hpx/issues/6466>

¹¹⁶³ <https://github.com/TheHPXProject/hpx/issues/6461>

¹¹⁶⁴ <https://github.com/TheHPXProject/hpx/issues/6459>

¹¹⁶⁵ <https://github.com/TheHPXProject/hpx/issues/6451>

¹¹⁶⁶ <https://github.com/TheHPXProject/hpx/issues/6446>

¹¹⁶⁷ <https://github.com/TheHPXProject/hpx/issues/6443>

¹¹⁶⁸ <https://github.com/TheHPXProject/hpx/issues/6440>

¹¹⁶⁹ <https://github.com/TheHPXProject/hpx/issues/6437>

¹¹⁷⁰ <https://github.com/TheHPXProject/hpx/issues/6419>

¹¹⁷¹ <https://github.com/TheHPXProject/hpx/issues/6417>

¹¹⁷² <https://github.com/TheHPXProject/hpx/issues/6414>

¹¹⁷³ <https://github.com/TheHPXProject/hpx/issues/6412>

¹¹⁷⁴ <https://github.com/TheHPXProject/hpx/issues/6407>

¹¹⁷⁵ <https://github.com/TheHPXProject/hpx/issues/6405>

¹¹⁷⁶ <https://github.com/TheHPXProject/hpx/issues/6398>

¹¹⁷⁷ <https://github.com/TheHPXProject/hpx/issues/6392>

¹¹⁷⁸ <https://github.com/TheHPXProject/hpx/issues/6388>

- [Issue #6366](#)¹¹⁷⁹ - serialize_buffer allocator support needs adjustments
- [Issue #6361](#)¹¹⁸⁰ - HPX 1.9.1 does not compile on Fedora 40
- [Issue #6355](#)¹¹⁸¹ - Single page documentation is broken
- [Issue #6334](#)¹¹⁸² - Segmentation fault after adding a padding in one_size_heap_list
- [Issue #6329](#)¹¹⁸³ - Log hpx threads on forced shutdown
- [Issue #6316](#)¹¹⁸⁴ - Build breaks on FreeBSD
- [Issue #6299](#)¹¹⁸⁵ - HPX does not use distributed localities on Fugaku
- [Issue #6298](#)¹¹⁸⁶ - Update config for coroutines on ARM
- [Issue #6291](#)¹¹⁸⁷ - Zero-copy receive optimization disabled the invocation of direct actions
- [Issue #6261](#)¹¹⁸⁸ - Add optional reading of json files for command line options
- [Issue #6087](#)¹¹⁸⁹ - Support for vcpkg on Linux is broken
- [Issue #5921](#)¹¹⁹⁰ - hpx::info claims that async_mpi was not built, while cmake assures its existence
- [Issue #5893](#)¹¹⁹¹ - Tests fail on FreeBSD: Executable copyn_test does not exist
- [Issue #5833](#)¹¹⁹² - barrier lockup
- [Issue #5799](#)¹¹⁹³ - Investigate CUDA compilation problems
- [Issue #5340](#)¹¹⁹⁴ - Examples do not run on Mac OSX using the M1 chip

Closed pull requests

- [PR #6493](#)¹¹⁹⁵ - Fix distributed latch documentation
- [PR #6492](#)¹¹⁹⁶ - Fix kokkos hpx nvcc compilation
- [PR #6491](#)¹¹⁹⁷ - More fixes to handling bool arguments for collective operations
- [PR #6490](#)¹¹⁹⁸ - Remove the default max cpu count
- [PR #6489](#)¹¹⁹⁹ - Ensure TCP parcelport is deactivated if not needed
- [PR #6488](#)¹²⁰⁰ - Fixing handling of bool value type for collective operations

¹¹⁷⁹ <https://github.com/TheHPXProject/hpx/issues/6366>

¹¹⁸⁰ <https://github.com/TheHPXProject/hpx/issues/6361>

¹¹⁸¹ <https://github.com/TheHPXProject/hpx/issues/6355>

¹¹⁸² <https://github.com/TheHPXProject/hpx/issues/6334>

¹¹⁸³ <https://github.com/TheHPXProject/hpx/issues/6329>

¹¹⁸⁴ <https://github.com/TheHPXProject/hpx/issues/6316>

¹¹⁸⁵ <https://github.com/TheHPXProject/hpx/issues/6299>

¹¹⁸⁶ <https://github.com/TheHPXProject/hpx/issues/6298>

¹¹⁸⁷ <https://github.com/TheHPXProject/hpx/issues/6291>

¹¹⁸⁸ <https://github.com/TheHPXProject/hpx/issues/6261>

¹¹⁸⁹ <https://github.com/TheHPXProject/hpx/issues/6087>

¹¹⁹⁰ <https://github.com/TheHPXProject/hpx/issues/5921>

¹¹⁹¹ <https://github.com/TheHPXProject/hpx/issues/5893>

¹¹⁹² <https://github.com/TheHPXProject/hpx/issues/5833>

¹¹⁹³ <https://github.com/TheHPXProject/hpx/issues/5799>

¹¹⁹⁴ <https://github.com/TheHPXProject/hpx/issues/5340>

¹¹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/6493>

¹¹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/6492>

¹¹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/6491>

¹¹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/6490>

¹¹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/6489>

¹²⁰⁰ <https://github.com/TheHPXProject/hpx/pull/6488>

- PR #6485¹²⁰¹ - Destructive interference size
- PR #6484¹²⁰² - Improve performance counter error handling
- PR #6482¹²⁰³ - Generalize the notion of bitwise serialization
- PR #6481¹²⁰⁴ - Fixing use of HPX_WITH_CXX_STANDARD
- PR #6480¹²⁰⁵ - Remove equal_to from hpx::any
- PR #6479¹²⁰⁶ - Remove optimizations for certain built-in compiler intrinsics
- PR #6478¹²⁰⁷ - Fixing issues on MacOS
- PR #6477¹²⁰⁸ - lci pp: lci's github repo name changed from LC to lci
- PR #6476¹²⁰⁹ - Fixing binary filter test target names
- PR #6475¹²¹⁰ - Fix mac os github actions
- PR #6472¹²¹¹ - Troubleshoot CI hangs
- PR #6469¹²¹² - improve(lci pp): more options to control the LCI parcelport
- PR #6467¹²¹³ - Bump jwlawson/actions-setup-cmake from 1.14 to 2.0
- PR #6464¹²¹⁴ - Update docs of "Writing distributed applications" page
- PR #6463¹²¹⁵ - Revert "Always return outermost thread id"
- PR #6458¹²¹⁶ - Reduce test workload to fix CI/CD time-out
- PR #6457¹²¹⁷ - replace boost::array with std::array and update file name
- PR #6456¹²¹⁸ - Move APEX CI to rostam
- PR #6455¹²¹⁹ - Fixing compilation if HPX_HAVE_THREAD_QUEUE_WAITTIME is defined
- PR #6454¹²²⁰ - Update perf tests reference measurements
- PR #6453¹²²¹ - Update supported platforms of Manual/Prerequisites page
- PR #6452¹²²² - Fix nvcc crashes in transform_stream.cu and synchronize.cu
- PR #6450¹²²³ - Fix git tag name in Getting HPX page

¹²⁰¹ <https://github.com/TheHPXProject/hpx/pull/6485>

¹²⁰² <https://github.com/TheHPXProject/hpx/pull/6484>

¹²⁰³ <https://github.com/TheHPXProject/hpx/pull/6482>

¹²⁰⁴ <https://github.com/TheHPXProject/hpx/pull/6481>

¹²⁰⁵ <https://github.com/TheHPXProject/hpx/pull/6480>

¹²⁰⁶ <https://github.com/TheHPXProject/hpx/pull/6479>

¹²⁰⁷ <https://github.com/TheHPXProject/hpx/pull/6478>

¹²⁰⁸ <https://github.com/TheHPXProject/hpx/pull/6477>

¹²⁰⁹ <https://github.com/TheHPXProject/hpx/pull/6476>

¹²¹⁰ <https://github.com/TheHPXProject/hpx/pull/6475>

¹²¹¹ <https://github.com/TheHPXProject/hpx/pull/6472>

¹²¹² <https://github.com/TheHPXProject/hpx/pull/6469>

¹²¹³ <https://github.com/TheHPXProject/hpx/pull/6467>

¹²¹⁴ <https://github.com/TheHPXProject/hpx/pull/6464>

¹²¹⁵ <https://github.com/TheHPXProject/hpx/pull/6463>

¹²¹⁶ <https://github.com/TheHPXProject/hpx/pull/6458>

¹²¹⁷ <https://github.com/TheHPXProject/hpx/pull/6457>

¹²¹⁸ <https://github.com/TheHPXProject/hpx/pull/6456>

¹²¹⁹ <https://github.com/TheHPXProject/hpx/pull/6455>

¹²²⁰ <https://github.com/TheHPXProject/hpx/pull/6454>

¹²²¹ <https://github.com/TheHPXProject/hpx/pull/6453>

¹²²² <https://github.com/TheHPXProject/hpx/pull/6452>

¹²²³ <https://github.com/TheHPXProject/hpx/pull/6450>

- PR #6449¹²²⁴ - LCI parcelport: add yield to potentially infinite retry loop
- PR #6447¹²²⁵ - Use compressed ptr in schedulers when 128 atomics are not lockfree
- PR #6445¹²²⁶ - Fix agas addressing cache
- PR #6444¹²²⁷ - Update CTestConfig.cmake
- PR #6442¹²²⁸ - Update CMakeLists.txt
- PR #6441¹²²⁹ - Minor documentation fixes
- PR #6439¹²³⁰ - Optimizing use of certain #includes
- PR #6438¹²³¹ - Bump jwlawson/actions-setup-cmake from 1.14 to 2.0
- PR #6436¹²³² - Update docs
- PR #6435¹²³³ - Parcel layer tweaks
- PR #6434¹²³⁴ - improve termination detection: removing lock from critical path
- PR #6433¹²³⁵ - Use shared mutex for resolve_locality procedure
- PR #6432¹²³⁶ - Module cleanup up to level 30
- PR #6429¹²³⁷ - Making sure HPX_WITH_ASYNC_MPI is reported properly
- PR #6427¹²³⁸ - Modifying CMakeLists to copy libhwloc-15.dll to the binary folder in Windows, independently
- PR #6425¹²³⁹ - Fix macOS failing test
- PR #6424¹²⁴⁰ - Adding option for downloading Boost using CMake FetchContent
- PR #6423¹²⁴¹ - Move adjacent_difference to numeric header file
- PR #6422¹²⁴² - Adding steal-half functionalities to work-requesting scheduler
- PR #6421¹²⁴³ - Bump actions/checkout from 2 to 4
- PR #6418¹²⁴⁴ - Working around nvcc problems to use CTAD
- PR #6416¹²⁴⁵ - Change run_as_os_thread deprecation forwarding due to hipcc compilation issue
- PR #6415¹²⁴⁶ - Attempting to avoid segfault in OctoTiger during initialization

¹²²⁴ <https://github.com/TheHPXProject/hpx/pull/6449>

¹²²⁵ <https://github.com/TheHPXProject/hpx/pull/6447>

¹²²⁶ <https://github.com/TheHPXProject/hpx/pull/6445>

¹²²⁷ <https://github.com/TheHPXProject/hpx/pull/6444>

¹²²⁸ <https://github.com/TheHPXProject/hpx/pull/6442>

¹²²⁹ <https://github.com/TheHPXProject/hpx/pull/6441>

¹²³⁰ <https://github.com/TheHPXProject/hpx/pull/6439>

¹²³¹ <https://github.com/TheHPXProject/hpx/pull/6438>

¹²³² <https://github.com/TheHPXProject/hpx/pull/6436>

¹²³³ <https://github.com/TheHPXProject/hpx/pull/6435>

¹²³⁴ <https://github.com/TheHPXProject/hpx/pull/6434>

¹²³⁵ <https://github.com/TheHPXProject/hpx/pull/6433>

¹²³⁶ <https://github.com/TheHPXProject/hpx/pull/6432>

¹²³⁷ <https://github.com/TheHPXProject/hpx/pull/6429>

¹²³⁸ <https://github.com/TheHPXProject/hpx/pull/6427>

¹²³⁹ <https://github.com/TheHPXProject/hpx/pull/6425>

¹²⁴⁰ <https://github.com/TheHPXProject/hpx/pull/6424>

¹²⁴¹ <https://github.com/TheHPXProject/hpx/pull/6423>

¹²⁴² <https://github.com/TheHPXProject/hpx/pull/6422>

¹²⁴³ <https://github.com/TheHPXProject/hpx/pull/6421>

¹²⁴⁴ <https://github.com/TheHPXProject/hpx/pull/6418>

¹²⁴⁵ <https://github.com/TheHPXProject/hpx/pull/6416>

¹²⁴⁶ <https://github.com/TheHPXProject/hpx/pull/6415>

- PR #6413¹²⁴⁷ - Always return outermost thread id
- PR #6411¹²⁴⁸ - Minor refactoring and fixes to the LCI parcelport and pingpong_performance2 benchmark
- PR #6410¹²⁴⁹ - Adding scope_xxx from library fundamentals TS v3
- PR #6409¹²⁵⁰ - Working around CUDA issue
- PR #6408¹²⁵¹ - Tightening up collective operation semantics
- PR #6406¹²⁵² - Working around ROCm compiler issue
- PR #6404¹²⁵³ - Allow to disable use of [[no_unique_address]] attribute
- PR #6403¹²⁵⁴ - Fixing copyright year
- PR #6402¹²⁵⁵ - fix(lci pp): fix deadlocks with too many failed sends
- PR #6401¹²⁵⁶ - fix(lci pp): fix the null_thread_id bug in the LCI parcelport
- PR #6400¹²⁵⁷ - Fix the affinity setting bug when using LCI pp and multiple localities per node
- PR #6397¹²⁵⁸ - Change API header titles and info
- PR #6396¹²⁵⁹ - Making is_bitwise_serializable SFINAE-friendly
- PR #6395¹²⁶⁰ - Adapt amount of collective testing
- PR #6394¹²⁶¹ - Adding option for installing Hwloc using CMake FetchContent
- PR #6393¹²⁶² - Optionally disable caching allocator
- PR #6391¹²⁶³ - Cleaning up collective operations
- PR #6390¹²⁶⁴ - Making function local constexpr variables non-static
- PR #6389¹²⁶⁵ - Disable resolving hostnames if TCP is disabled
- PR #6387¹²⁶⁶ - Need to break out of the loop when searching the suffixes.
- PR #6384¹²⁶⁷ - Fixing allocation/deallocation mismatch in serialize_buffer
- PR #6383¹²⁶⁸ - Enable fork_join_executor to handle return values from scheduled functions
- PR #6381¹²⁶⁹ - Consistently treat conflicting parameters provided by executors and parameter objects

¹²⁴⁷ <https://github.com/TheHPXProject/hpx/pull/6413>

¹²⁴⁸ <https://github.com/TheHPXProject/hpx/pull/6411>

¹²⁴⁹ <https://github.com/TheHPXProject/hpx/pull/6410>

¹²⁵⁰ <https://github.com/TheHPXProject/hpx/pull/6409>

¹²⁵¹ <https://github.com/TheHPXProject/hpx/pull/6408>

¹²⁵² <https://github.com/TheHPXProject/hpx/pull/6406>

¹²⁵³ <https://github.com/TheHPXProject/hpx/pull/6404>

¹²⁵⁴ <https://github.com/TheHPXProject/hpx/pull/6403>

¹²⁵⁵ <https://github.com/TheHPXProject/hpx/pull/6402>

¹²⁵⁶ <https://github.com/TheHPXProject/hpx/pull/6401>

¹²⁵⁷ <https://github.com/TheHPXProject/hpx/pull/6400>

¹²⁵⁸ <https://github.com/TheHPXProject/hpx/pull/6397>

¹²⁵⁹ <https://github.com/TheHPXProject/hpx/pull/6396>

¹²⁶⁰ <https://github.com/TheHPXProject/hpx/pull/6395>

¹²⁶¹ <https://github.com/TheHPXProject/hpx/pull/6394>

¹²⁶² <https://github.com/TheHPXProject/hpx/pull/6393>

¹²⁶³ <https://github.com/TheHPXProject/hpx/pull/6391>

¹²⁶⁴ <https://github.com/TheHPXProject/hpx/pull/6390>

¹²⁶⁵ <https://github.com/TheHPXProject/hpx/pull/6389>

¹²⁶⁶ <https://github.com/TheHPXProject/hpx/pull/6387>

¹²⁶⁷ <https://github.com/TheHPXProject/hpx/pull/6384>

¹²⁶⁸ <https://github.com/TheHPXProject/hpx/pull/6383>

¹²⁶⁹ <https://github.com/TheHPXProject/hpx/pull/6381>

- PR #6380¹²⁷⁰ - Fixing setting an annotation for an execution policy
- PR #6378¹²⁷¹ - Allowing to disable signal handlers
- PR #6377¹²⁷² - Fix gasnet-related test failures
- PR #6375¹²⁷³ - Update LSU Jenkins with 2023-10 libraries
- PR #6374¹²⁷⁴ - Investigate builder gasnet failure
- PR #6373¹²⁷⁵ - Fixing communicator API, adding docs
- PR #6372¹²⁷⁶ - Fix resource partitioner tests for small thread count
- PR #6371¹²⁷⁷ - Fix jacobi omp examples.
- PR #6370¹²⁷⁸ - improve one_size_heap_list: use rwlock to speedup the allocation/free
- PR #6369¹²⁷⁹ - working issue with MPI_CC / CC conflict in automake
- PR #6368¹²⁸⁰ - Making sure serialize_buffer properly destroys buffer, if needed.
- PR #6367¹²⁸¹ - Fix parallel relocation test
- PR #6364¹²⁸² - Relocation variants
- PR #6363¹²⁸³ - Update the lci parcelport to use LCI v1.7.6
- PR #6362¹²⁸⁴ - Fixing compilation problems on 32 Linux systems
- PR #6360¹²⁸⁵ - Fix broken links in docs: PDF, Single HTML page, Dependency report
- PR #6359¹²⁸⁶ - Fix header file links in Public API page
- PR #6358¹²⁸⁷ - Fix CMake find_library for HWLOC
- PR #6357¹²⁸⁸ - Replace Custom Benchmarking Code with Nanobench
- PR #6356¹²⁸⁹ - Fixed matrix multiplication example output
- PR #6354¹²⁹⁰ - Fix broken links for header files in Public API page
- PR #6353¹²⁹¹ - Enable using std::reference_wrapper with executor parameters
- PR #6352¹²⁹² - Add Public distributed API documentation

¹²⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6380>

¹²⁷¹ <https://github.com/TheHPXProject/hpx/pull/6378>

¹²⁷² <https://github.com/TheHPXProject/hpx/pull/6377>

¹²⁷³ <https://github.com/TheHPXProject/hpx/pull/6375>

¹²⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6374>

¹²⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6373>

¹²⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6372>

¹²⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6371>

¹²⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6370>

¹²⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6369>

¹²⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6368>

¹²⁸¹ <https://github.com/TheHPXProject/hpx/pull/6367>

¹²⁸² <https://github.com/TheHPXProject/hpx/pull/6364>

¹²⁸³ <https://github.com/TheHPXProject/hpx/pull/6363>

¹²⁸⁴ <https://github.com/TheHPXProject/hpx/pull/6362>

¹²⁸⁵ <https://github.com/TheHPXProject/hpx/pull/6360>

¹²⁸⁶ <https://github.com/TheHPXProject/hpx/pull/6359>

¹²⁸⁷ <https://github.com/TheHPXProject/hpx/pull/6358>

¹²⁸⁸ <https://github.com/TheHPXProject/hpx/pull/6357>

¹²⁸⁹ <https://github.com/TheHPXProject/hpx/pull/6356>

¹²⁹⁰ <https://github.com/TheHPXProject/hpx/pull/6354>

¹²⁹¹ <https://github.com/TheHPXProject/hpx/pull/6353>

¹²⁹² <https://github.com/TheHPXProject/hpx/pull/6352>

- PR #6350¹²⁹³ - Make coverage work with Jenkins Github Branch Source plugin
- PR #6349¹²⁹⁴ - Moving hpx::threads::run_as_xxx to namespace hpx
- PR #6348¹²⁹⁵ - Adding `--exclusive` to launching tests on rostam
- PR #6346¹²⁹⁶ - changed chat link to discord
- PR #6344¹²⁹⁷ - uninitialized_relocate w/ type_support primitive
- PR #6343¹²⁹⁸ - Bump actions/checkout from 3 to 4
- PR #6342¹²⁹⁹ - Fix HPX-APEX cmake integration
- PR #6341¹³⁰⁰ - Fix shared_future_continuation_order regression test
- PR #6340¹³⁰¹ - Log alive hpx threads on exit
- PR #6339¹³⁰² - Add coverage testing on Jenkins
- PR #6338¹³⁰³ - Fixing HPX_CURRENT_SOURCE_LOCATION when std::source_location exists
- PR #6337¹³⁰⁴ - Remove aurianer, biddisco, and msimberg from codeowners
- PR #6336¹³⁰⁵ - More cleaning up for module levels 19-20
- PR #6335¹³⁰⁶ - Finalize the MPI docs of the Migration Guide
- PR #6332¹³⁰⁷ - More fixes for CMake V3.27
- PR #6330¹³⁰⁸ - Adding basic logging to collective operations
- PR #6328¹³⁰⁹ - Cleanup previous patch adapting to CMake V3.27
- PR #6327¹³¹⁰ - Modernize modules in level 17 and 18
- PR #6324¹³¹¹ - P1144 Relocation primitives
- PR #6321¹³¹² - Ensure hpx_main is a proper thread_function
- PR #6320¹³¹³ - Fixing cyclic dependencies in naming and agas modules
- PR #6319¹³¹⁴ - Generate git tag if needed but it is not available
- PR #6317¹³¹⁵ - Fixing linker problem on FreeBSD

¹²⁹³ <https://github.com/TheHPXProject/hpx/pull/6350>

¹²⁹⁴ <https://github.com/TheHPXProject/hpx/pull/6349>

¹²⁹⁵ <https://github.com/TheHPXProject/hpx/pull/6348>

¹²⁹⁶ <https://github.com/TheHPXProject/hpx/pull/6346>

¹²⁹⁷ <https://github.com/TheHPXProject/hpx/pull/6344>

¹²⁹⁸ <https://github.com/TheHPXProject/hpx/pull/6343>

¹²⁹⁹ <https://github.com/TheHPXProject/hpx/pull/6342>

¹³⁰⁰ <https://github.com/TheHPXProject/hpx/pull/6341>

¹³⁰¹ <https://github.com/TheHPXProject/hpx/pull/6340>

¹³⁰² <https://github.com/TheHPXProject/hpx/pull/6339>

¹³⁰³ <https://github.com/TheHPXProject/hpx/pull/6338>

¹³⁰⁴ <https://github.com/TheHPXProject/hpx/pull/6337>

¹³⁰⁵ <https://github.com/TheHPXProject/hpx/pull/6336>

¹³⁰⁶ <https://github.com/TheHPXProject/hpx/pull/6335>

¹³⁰⁷ <https://github.com/TheHPXProject/hpx/pull/6332>

¹³⁰⁸ <https://github.com/TheHPXProject/hpx/pull/6330>

¹³⁰⁹ <https://github.com/TheHPXProject/hpx/pull/6328>

¹³¹⁰ <https://github.com/TheHPXProject/hpx/pull/6327>

¹³¹¹ <https://github.com/TheHPXProject/hpx/pull/6324>

¹³¹² <https://github.com/TheHPXProject/hpx/pull/6321>

¹³¹³ <https://github.com/TheHPXProject/hpx/pull/6320>

¹³¹⁴ <https://github.com/TheHPXProject/hpx/pull/6319>

¹³¹⁵ <https://github.com/TheHPXProject/hpx/pull/6317>

- PR #6315¹³¹⁶ - acknowledge triv-rel and nothrow-rel types
- PR #6314¹³¹⁷ - Relocation algorithms Clean
- PR #6313¹³¹⁸ - Trivial relocation of c-v-ref-array types
- PR #6312¹³¹⁹ - Fixing warning/error
- PR #6311¹³²⁰ - Adding executor parallel invoke CPOs
- PR #6310¹³²¹ - Define HPX_COMPUTE_CODE in builds with SYCL
- PR #6309¹³²² - Making sure changed number of cores is propagated to executor
- PR #6308¹³²³ - openshmem-parcelport initial import
- PR #6306¹³²⁴ - The hpxcxx script was broken such that it could only compile for _release
- PR #6305¹³²⁵ - Adapting build system for CMake V3.27
- PR #6304¹³²⁶ - Fixing an integral type mismatch warning
- PR #6303¹³²⁷ - omp for default vectorization
- PR #6301¹³²⁸ - Add MPI migration guide
- PR #6294¹³²⁹ - Add internal reference counting to semaphores
- PR #6286¹³³⁰ - Simd helpers
- PR #6280¹³³¹ - Add TBB to HPX documentation in Migration Guide
- PR #6276¹³³² - Add dependabot.yml
- PR #6275¹³³³ - Revert “Move dependabot.yml into correct directory”
- PR #6272¹³³⁴ - set thread name for linux
- PR #6271¹³³⁵ - Uninitialised algorithms, move using std::memcpy
- PR #6270¹³³⁶ - Bump jwlawson/actions-setup-cmake from 1.9 to 1.14
- PR #6269¹³³⁷ - Bump actions/checkout from 2 to 3
- PR #6268¹³³⁸ - Move dependabot.yml into correct directory

¹³¹⁶ <https://github.com/TheHPXProject/hpx/pull/6315>

¹³¹⁷ <https://github.com/TheHPXProject/hpx/pull/6314>

¹³¹⁸ <https://github.com/TheHPXProject/hpx/pull/6313>

¹³¹⁹ <https://github.com/TheHPXProject/hpx/pull/6312>

¹³²⁰ <https://github.com/TheHPXProject/hpx/pull/6311>

¹³²¹ <https://github.com/TheHPXProject/hpx/pull/6310>

¹³²² <https://github.com/TheHPXProject/hpx/pull/6309>

¹³²³ <https://github.com/TheHPXProject/hpx/pull/6308>

¹³²⁴ <https://github.com/TheHPXProject/hpx/pull/6306>

¹³²⁵ <https://github.com/TheHPXProject/hpx/pull/6305>

¹³²⁶ <https://github.com/TheHPXProject/hpx/pull/6304>

¹³²⁷ <https://github.com/TheHPXProject/hpx/pull/6303>

¹³²⁸ <https://github.com/TheHPXProject/hpx/pull/6301>

¹³²⁹ <https://github.com/TheHPXProject/hpx/pull/6294>

¹³³⁰ <https://github.com/TheHPXProject/hpx/pull/6286>

¹³³¹ <https://github.com/TheHPXProject/hpx/pull/6280>

¹³³² <https://github.com/TheHPXProject/hpx/pull/6276>

¹³³³ <https://github.com/TheHPXProject/hpx/pull/6275>

¹³³⁴ <https://github.com/TheHPXProject/hpx/pull/6272>

¹³³⁵ <https://github.com/TheHPXProject/hpx/pull/6271>

¹³³⁶ <https://github.com/TheHPXProject/hpx/pull/6270>

¹³³⁷ <https://github.com/TheHPXProject/hpx/pull/6269>

¹³³⁸ <https://github.com/TheHPXProject/hpx/pull/6268>

- PR #6265¹³³⁹ - Create dependabot.yml
- PR #6264¹³⁴⁰ - `hpx::is_trivially_relocatable` trait implementation
- PR #6263¹³⁴¹ - Adding support for reading json configuration files for command line options
- PR #6249¹³⁴² - Implement the send immediate optimization for the MPI parcelport.
- PR #6237¹³⁴³ - Improve compilation performance
- PR #6234¹³⁴⁴ - Adding release notes page for next release
- PR #6233¹³⁴⁵ - Moving `is_relocatable` to namespace `hpx`
- PR #6230¹³⁴⁶ - gasnet based parcelport
- PR #6226¹³⁴⁷ - Re-enable dependency on segmented algorithms on CircleCI
- PR #6220¹³⁴⁸ - Add execution on
- PR #6212¹³⁴⁹ - Initial trait definition for *relocatable*
- PR #6199¹³⁵⁰ - added support for `unseq`, `par_unseq` for `hpx::make_heap` algorithm
- PR #6173¹³⁵¹ - C++ modules
- PR #6122¹³⁵² - Add Module support
- PR #6099¹³⁵³ - Futures attempt to execute threads directly if those have not started executing
- PR #6050¹³⁵⁴ - Investigating `partitioned_vector` problems
- PR #5988¹³⁵⁵ - Adding CI configuration for DGX-A100 at LSU
- PR #5910¹³⁵⁶ - Improve MPI initialization
- PR #5845¹³⁵⁷ - Adding local work requesting scheduler that is based on message passing internally

¹³³⁹ <https://github.com/TheHPXProject/hpx/pull/6265>

¹³⁴⁰ <https://github.com/TheHPXProject/hpx/pull/6264>

¹³⁴¹ <https://github.com/TheHPXProject/hpx/pull/6263>

¹³⁴² <https://github.com/TheHPXProject/hpx/pull/6249>

¹³⁴³ <https://github.com/TheHPXProject/hpx/pull/6237>

¹³⁴⁴ <https://github.com/TheHPXProject/hpx/pull/6234>

¹³⁴⁵ <https://github.com/TheHPXProject/hpx/pull/6233>

¹³⁴⁶ <https://github.com/TheHPXProject/hpx/pull/6230>

¹³⁴⁷ <https://github.com/TheHPXProject/hpx/pull/6226>

¹³⁴⁸ <https://github.com/TheHPXProject/hpx/pull/6220>

¹³⁴⁹ <https://github.com/TheHPXProject/hpx/pull/6212>

¹³⁵⁰ <https://github.com/TheHPXProject/hpx/pull/6199>

¹³⁵¹ <https://github.com/TheHPXProject/hpx/pull/6173>

¹³⁵² <https://github.com/TheHPXProject/hpx/pull/6122>

¹³⁵³ <https://github.com/TheHPXProject/hpx/pull/6099>

¹³⁵⁴ <https://github.com/TheHPXProject/hpx/pull/6050>

¹³⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5988>

¹³⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5910>

¹³⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5845>

HPX V1.9.1 (August 4, 2023)

General changes

This point release fixes a couple of problems reported for the V1.9.0 release. Most importantly, we fixed various occasional hanging during startup and shutdown in distributed scenarios. We also added support for zero-copy serialization on the receiving side to the TCP, MPI, and LCI parcelports. Last but not least, we have added support for Visual Studio 2019 and gcc using MINGW on Windows, and also support for gcc V13 and clang V15.

HPX headers are now made consistently named the same as their standard library counterparts, e.g. `#include <thread>` now corresponds to `#include <hpx/thread.hpp>`. This significantly simplifies porting existing standards conforming codes to HPX.

A lot of work has been done to improve and optimize our network communication layers. Primary focus of this work was on the LCI parcelport, but we have also cleaned up and improved the MPI parcelport.

Additionally, we have continued working on our documentation. The main focus here was on completing the API documentation of the most important API functions. We have started adding migration guides for people interested in moving their codes away from other, commonplace parallelization frameworks like OpenMP.

Breaking changes

None

Closed issues

- [Issue #6155](#)¹³⁵⁸ - `hpxcxx` and `hpxrun.py` do not work if `HPX_WITH_TESTS=OFF`
- [Issue #6164](#)¹³⁵⁹ - `HPX_WITH_DATAPAR_BACKEND=EVE` causes compile errors with C++17
- [Issue #6175](#)¹³⁶⁰ - Make sure all our parallel algorithms accept the predicates by value
- [Issue #6194](#)¹³⁶¹ - `tests.regressions.threads.threads_all_1422` failed at Perlmutter
- [Issue #6198](#)¹³⁶² - `set_intersection/set_difference` fails when run with `execution::par`
- [Issue #6214](#)¹³⁶³ - Broken Links to the Documentation page in `readme.rst`
- [Issue #6217](#)¹³⁶⁴ - `hpx::make_heap` does not terminate when `exPolicy` is `par` (or `par_unseq`) and size of vector is 4
- [Issue #6246](#)¹³⁶⁵ - HPX fails to compile under `cxx 20` (fresh system)
- [Issue #6247](#)¹³⁶⁶ - HPX 1.9.0 does not compile with GCC on Windows
- [Issue #6282](#)¹³⁶⁷ - The “attach-debugger” option is broken on the current master branch.

¹³⁵⁸ <https://github.com/TheHPXProject/hpx/issues/6155>

¹³⁵⁹ <https://github.com/TheHPXProject/hpx/issues/6164>

¹³⁶⁰ <https://github.com/TheHPXProject/hpx/issues/6175>

¹³⁶¹ <https://github.com/TheHPXProject/hpx/issues/6194>

¹³⁶² <https://github.com/TheHPXProject/hpx/issues/6198>

¹³⁶³ <https://github.com/TheHPXProject/hpx/issues/6214>

¹³⁶⁴ <https://github.com/TheHPXProject/hpx/issues/6217>

¹³⁶⁵ <https://github.com/TheHPXProject/hpx/issues/6246>

¹³⁶⁶ <https://github.com/TheHPXProject/hpx/issues/6247>

¹³⁶⁷ <https://github.com/TheHPXProject/hpx/issues/6282>

Closed pull requests

- PR #6219¹³⁶⁸ - Cleaning up #includes in hpx/ folder
- PR #6223¹³⁶⁹ - Move documentation from README.rst to index.rst files under libs directory
- PR #6229¹³⁷⁰ - Adding zero-copy support on the receiving end of the TCP and MPI parcel ports
- PR #6231¹³⁷¹ - Remove deprecated email from release procedure
- PR #6235¹³⁷² - Modernize more modules (levels 12-16)
- PR #6236¹³⁷³ - Attempt to resolve occasional shutdown hangs in distributed operation
- PR #6239¹³⁷⁴ - Fix Optimizing HPX applications page of Manual
- PR #6241¹³⁷⁵ - LCI parcelport: Refactor, add more variants, zero copy receives.
- PR #6242¹³⁷⁶ - updated deprecated headers
- PR #6243¹³⁷⁷ - Adding github action builders using VS2019
- PR #6248¹³⁷⁸ - Fix CUDA/HIP Jenkins pipelines
- PR #6250¹³⁷⁹ - Resolve gcc problems on Windows
- PR #6251¹³⁸⁰ - Attempting to fix problems in barrier causing hangs
- PR #6253¹³⁸¹ - Modernize set_thread_name on Windows
- PR #6256¹³⁸² - Fix nvcc/gcc-10 (Octo-Tiger) compilation issue
- PR #6257¹³⁸³ - Cmake Tests: Delete operator check for size_t arg
- PR #6258¹³⁸⁴ - Rewriting wait_some to circumvent data races causing hangs
- PR #6260¹³⁸⁵ - Add migration guide to manual
- PR #6262¹³⁸⁶ - Fixing wrong command line options in local command line handling
- PR #6266¹³⁸⁷ - Attempt to resolve occasional hang in run_loop
- PR #6267¹³⁸⁸ - Attempting to fix migration tests
- PR #6278¹³⁸⁹ - Making sure the future's shared state doesn't go out of scope prematurely

¹³⁶⁸ <https://github.com/TheHPXProject/hpx/pull/6219>

¹³⁶⁹ <https://github.com/TheHPXProject/hpx/pull/6223>

¹³⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6229>

¹³⁷¹ <https://github.com/TheHPXProject/hpx/pull/6231>

¹³⁷² <https://github.com/TheHPXProject/hpx/pull/6235>

¹³⁷³ <https://github.com/TheHPXProject/hpx/pull/6236>

¹³⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6239>

¹³⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6241>

¹³⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6242>

¹³⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6243>

¹³⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6248>

¹³⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6250>

¹³⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6251>

¹³⁸¹ <https://github.com/TheHPXProject/hpx/pull/6253>

¹³⁸² <https://github.com/TheHPXProject/hpx/pull/6256>

¹³⁸³ <https://github.com/TheHPXProject/hpx/pull/6257>

¹³⁸⁴ <https://github.com/TheHPXProject/hpx/pull/6258>

¹³⁸⁵ <https://github.com/TheHPXProject/hpx/pull/6260>

¹³⁸⁶ <https://github.com/TheHPXProject/hpx/pull/6262>

¹³⁸⁷ <https://github.com/TheHPXProject/hpx/pull/6266>

¹³⁸⁸ <https://github.com/TheHPXProject/hpx/pull/6267>

¹³⁸⁹ <https://github.com/TheHPXProject/hpx/pull/6278>

- [PR #6279](#)¹³⁹⁰ - Re-expose error names
- [PR #6281](#)¹³⁹¹ - Creating directory for file copy
- [PR #6283](#)¹³⁹² - Consistently `#include unistd.h` for `_POSIX_VERSION`

HPX V1.9.0 (May 2, 2023)

General changes

- Added RISC-V 64bit support. HPX is now compatible with RISC-V architectures which have revolutionized the HPC world.
- LCI parcelport has been optimized to transfer parcels with fewer messages and use the HPX resource partitioner for its progress thread allocation. It should generally provide better performance than before. It also removes its dependency on the MPI library.
- HPX dependency on Boost was further relaxed by replacing headers from `Boost.Range`, `Boost.Tokenizer` and `Boost.Lockfree`.
- Improvements took place on our parallel algorithms implementation.
- Our Senders/Receivers (P2300) integration was extended:
 - Coroutines were integrated with senders/receivers.
- `get_completion_signatures` now works with awaitable senders. - `with_awaitable_senders` allows the passed senders to retrieve the value i.e. senders are transparently awaitable from within a coroutine. - `when_all_vector` was added.
- `sync_wait` and `sync_wait_with_variant` sender consumers were added. The user can now initiate the execution of their asynchronous pipeline by blocking the current thread that executes the `main()` function until the result is retrieved.
- The combinators for futures (a.k.a. `async_combinators`) `when_*`, `wait_*`, `wait_*_nothrow` were turned into CPOs allowing for end-user customization. For more information on the `async_combinators` refer to the documentation, https://hpx-docs.stellar-group.org/latest/html/libs/core/async_combinators/docs/index.html?highlight=combinators.
- The new datapar backend SVE allows `simd` and `par_simd` execution policies to exploit dataparallelism in the processors that have SVE vector registers like A64FX and Neoverse V1.
- The documentation for parallel algorithms, container algorithms was further improved. The Public API page was vastly enriched.
- Copy button shortkey was added at the top-right of code-blocks.
- Pragma directive that reports warnings as errors on MSVC was fixed.
- Command line argument `--hpx:loopback_network` was added to facilitate debugging with networks.
- We added an HPX-SYCL integration, allowing users to obtain HPX futures for SYCL events. This effectively enables the integration of arbitrary asynchronous SYCL operations into the HPX task graph. Bolted on top of this integration, we further added an HPX-SYCL executor for ease of use.

¹³⁹⁰ <https://github.com/TheHPXProject/hpx/pull/6279>

¹³⁹¹ <https://github.com/TheHPXProject/hpx/pull/6281>

¹³⁹² <https://github.com/TheHPXProject/hpx/pull/6283>

Breaking changes

- Stopped supporting Clang V8, the minimal version supported is now Clang V10.
- Stopped supporting gcc V8, the minimal version supported is now gcc V9.
- Stopped supporting Visual Studio 2015, the minimal version supported is now Visual Studio 2019.
- `tag_policy_tag` et.al. were re-added after HPX V1.8.1 deprecation.
- `get_chunk_size` and `processing_units_count` API is now expecting the time for one iteration as an argument.
- The list of all the namespace changes can be found here: *HPX V1.9.0 Namespace changes*.

Closed issues

- Issue #6203¹³⁹³ - Compilation error with `-mcpu=a64fx` on Oookami
- Issue #6196¹³⁹⁴ - Incorrect log destination
- Issue #6191¹³⁹⁵ - installing HPX
- Issue #6184¹³⁹⁶ - Wrong `processing_units_count` of `restricted_thread_pool_executor`
- Issue #6171¹³⁹⁷ - Release Tag Name Request
- Issue #6162¹³⁹⁸ - Current master does not compile on ROSTAM
- Issue #6156¹³⁹⁹ - `hpxcxx` does not work if `HPX_WITH_PKGCONFIG=OFF`
- Issue #6108¹⁴⁰⁰ - `cxx17_aligned_new.cpp` on `msvc` fails due to wrong pragma directive
- Issue #6045¹⁴⁰¹ - Can't call nullary callables wrapped with `hpx::unwrapping`
- Issue #6013¹⁴⁰² - Unable to build subprojects `hpx_collectives/hpx_compute` with MSVC
- Issue #6008¹⁴⁰³ - Missing `constexpr` default constructor for `hpx::mutex`
- Issue #5999¹⁴⁰⁴ - Add HPX Conda package to conda-forge
- Issue #5998¹⁴⁰⁵ - Serializing multiple arguments when applying distributed action results in segfault
- Issue #5958¹⁴⁰⁶ - HPX 1.8.0 and Blaze issues
- Issue #5908¹⁴⁰⁷ - Windows: duplicated symbols in static builds
- Issue #5802¹⁴⁰⁸ - Lost status `is_ready` from future

¹³⁹³ <https://github.com/TheHPXProject/hpx/issues/6203>

¹³⁹⁴ <https://github.com/TheHPXProject/hpx/issues/6196>

¹³⁹⁵ <https://github.com/TheHPXProject/hpx/issues/6191>

¹³⁹⁶ <https://github.com/TheHPXProject/hpx/issues/6184>

¹³⁹⁷ <https://github.com/TheHPXProject/hpx/issues/6171>

¹³⁹⁸ <https://github.com/TheHPXProject/hpx/issues/6162>

¹³⁹⁹ <https://github.com/TheHPXProject/hpx/issues/6156>

¹⁴⁰⁰ <https://github.com/TheHPXProject/hpx/issues/6108>

¹⁴⁰¹ <https://github.com/TheHPXProject/hpx/issues/6045>

¹⁴⁰² <https://github.com/TheHPXProject/hpx/issues/6013>

¹⁴⁰³ <https://github.com/TheHPXProject/hpx/issues/6008>

¹⁴⁰⁴ <https://github.com/TheHPXProject/hpx/issues/5999>

¹⁴⁰⁵ <https://github.com/TheHPXProject/hpx/issues/5998>

¹⁴⁰⁶ <https://github.com/TheHPXProject/hpx/issues/5958>

¹⁴⁰⁷ <https://github.com/TheHPXProject/hpx/issues/5908>

¹⁴⁰⁸ <https://github.com/TheHPXProject/hpx/issues/5802>

- [Issue #5767¹⁴⁰⁹](#) - Performance drop on Piz Daint
- [Issue #5752¹⁴¹⁰](#) - Implement `stride_view` from P1899 (experimental)
- [Issue #5744¹⁴¹¹](#) - `HPX_WITH_FETCH_ASIO` not working on Ookami
- [Issue #5561¹⁴¹²](#) - Possible race condition in helper thread / `hpx::cout`

Closed pull requests

- [PR #6228¹⁴¹³](#) - Fixing algorithms for zero length sequences when run with s/r scheduler
- [PR #6227¹⁴¹⁴](#) - Reliably disable background work when no networking is enabled
- [PR #6225¹⁴¹⁵](#) - Make heap fails in par for small sized heaps #6217
- [PR #6222¹⁴¹⁶](#) - Add documentation for `hpx::post`
- [PR #6221¹⁴¹⁷](#) - Fix segmented algorithms tests
- [PR #6218¹⁴¹⁸](#) - Creating `INSTALL` component 'runtime' to enable installing binaries only
- [PR #6216¹⁴¹⁹](#) - added tests for `set_difference`, updated `set_operation.hpp` to fix #6198
- [PR #6213¹⁴²⁰](#) - Modernize and streamline MPI parcellport
- [PR #6211¹⁴²¹](#) - Modernize modules of level 11, 12, and 13
- [PR #6210¹⁴²²](#) - Fixing MPI parcellport initialization if MPI is initialized outside of HPX
- [PR #6209¹⁴²³](#) - Prevent thread stealing during scheduler shutdown
- [PR #6208¹⁴²⁴](#) - Fix the compilation warning in the MPI parcellport with gcc 11.2
- [PR #6207¹⁴²⁵](#) - Automatically enable `Boost.Context` when compiling for arm64.
- [PR #6206¹⁴²⁶](#) - Update `CMakeLists.txt`
- [PR #6205¹⁴²⁷](#) - Do not generate `hpxcxx` if support for `pkgconfig` was disabled
- [PR #6204¹⁴²⁸](#) - Use **LRT_** instead of **LAPP_** logging in barrier implementation
- [PR #6202¹⁴²⁹](#) - Fixing Fedora build errors on Power systems
- [PR #6201¹⁴³⁰](#) - Update the LCI parcellport documents

¹⁴⁰⁹ <https://github.com/TheHPXProject/hpx/issues/5767>

¹⁴¹⁰ <https://github.com/TheHPXProject/hpx/issues/5752>

¹⁴¹¹ <https://github.com/TheHPXProject/hpx/issues/5744>

¹⁴¹² <https://github.com/TheHPXProject/hpx/issues/5561>

¹⁴¹³ <https://github.com/TheHPXProject/hpx/pull/6228>

¹⁴¹⁴ <https://github.com/TheHPXProject/hpx/pull/6227>

¹⁴¹⁵ <https://github.com/TheHPXProject/hpx/pull/6225>

¹⁴¹⁶ <https://github.com/TheHPXProject/hpx/pull/6222>

¹⁴¹⁷ <https://github.com/TheHPXProject/hpx/pull/6221>

¹⁴¹⁸ <https://github.com/TheHPXProject/hpx/pull/6218>

¹⁴¹⁹ <https://github.com/TheHPXProject/hpx/pull/6216>

¹⁴²⁰ <https://github.com/TheHPXProject/hpx/pull/6213>

¹⁴²¹ <https://github.com/TheHPXProject/hpx/pull/6211>

¹⁴²² <https://github.com/TheHPXProject/hpx/pull/6210>

¹⁴²³ <https://github.com/TheHPXProject/hpx/pull/6209>

¹⁴²⁴ <https://github.com/TheHPXProject/hpx/pull/6208>

¹⁴²⁵ <https://github.com/TheHPXProject/hpx/pull/6207>

¹⁴²⁶ <https://github.com/TheHPXProject/hpx/pull/6206>

¹⁴²⁷ <https://github.com/TheHPXProject/hpx/pull/6205>

¹⁴²⁸ <https://github.com/TheHPXProject/hpx/pull/6204>

¹⁴²⁹ <https://github.com/TheHPXProject/hpx/pull/6202>

¹⁴³⁰ <https://github.com/TheHPXProject/hpx/pull/6201>

- PR #6200¹⁴³¹ - Par link jobs
- PR #6197¹⁴³² - LCI parcelport: add doc, upgrade to v1.7.4, refactor cmake autofetch.
- PR #6195¹⁴³³ - Change the default tag of autofetch LCI to v1.7.3.
- PR #6192¹⁴³⁴ - Fix page *Writing single-node applications*
- PR #6189¹⁴³⁵ - Making sure restricted_thread_pool_executor properly reports used number of cores
- PR #6187¹⁴³⁶ - Enable using for_loop with range generators
- PR #6186¹⁴³⁷ - thread_support/CMakeLists: Fix build issue
- PR #6185¹⁴³⁸ - Fix EVE datapar with cxx_standard less than 20
- PR #6183¹⁴³⁹ - Update CI integration for EVE
- PR #6182¹⁴⁴⁰ - Fixing performance regressions
- PR #6181¹⁴⁴¹ - LCI parcelport: backlog queue, aggregation, separate devices, and more
- PR #6180¹⁴⁴² - Fixing use of for_loop with rebound execution policy (using *.with()*)
- PR #6179¹⁴⁴³ - Taking predicates for algorithms by value
- PR #6178¹⁴⁴⁴ - Changes needed to make chapel_hpx examples work
- PR #6176¹⁴⁴⁵ - Fixing warnings that were generated by PVS Studio
- PR #6174¹⁴⁴⁶ - Replace boost::integer::gcd with std::gcd
- PR #6172¹⁴⁴⁷ - [Docs] Fix example of how to run single/specific test(s)
- PR #6170¹⁴⁴⁸ - Adding missing fallback for processing_units_count customization point
- PR #6169¹⁴⁴⁹ - LCI parcelport: bypass the parcel queue and connection cache.
- PR #6167¹⁴⁵⁰ - Add create_local_communicator API function
- PR #6166¹⁴⁵¹ - Add missing header for std::intmax_t
- PR #6165¹⁴⁵² - Attempt to work around MSVC problem
- PR #6161¹⁴⁵³ - Update EVE integration

¹⁴³¹ <https://github.com/TheHPXProject/hpx/pull/6200>

¹⁴³² <https://github.com/TheHPXProject/hpx/pull/6197>

¹⁴³³ <https://github.com/TheHPXProject/hpx/pull/6195>

¹⁴³⁴ <https://github.com/TheHPXProject/hpx/pull/6192>

¹⁴³⁵ <https://github.com/TheHPXProject/hpx/pull/6189>

¹⁴³⁶ <https://github.com/TheHPXProject/hpx/pull/6187>

¹⁴³⁷ <https://github.com/TheHPXProject/hpx/pull/6186>

¹⁴³⁸ <https://github.com/TheHPXProject/hpx/pull/6185>

¹⁴³⁹ <https://github.com/TheHPXProject/hpx/pull/6183>

¹⁴⁴⁰ <https://github.com/TheHPXProject/hpx/pull/6182>

¹⁴⁴¹ <https://github.com/TheHPXProject/hpx/pull/6181>

¹⁴⁴² <https://github.com/TheHPXProject/hpx/pull/6180>

¹⁴⁴³ <https://github.com/TheHPXProject/hpx/pull/6179>

¹⁴⁴⁴ <https://github.com/TheHPXProject/hpx/pull/6178>

¹⁴⁴⁵ <https://github.com/TheHPXProject/hpx/pull/6176>

¹⁴⁴⁶ <https://github.com/TheHPXProject/hpx/pull/6174>

¹⁴⁴⁷ <https://github.com/TheHPXProject/hpx/pull/6172>

¹⁴⁴⁸ <https://github.com/TheHPXProject/hpx/pull/6170>

¹⁴⁴⁹ <https://github.com/TheHPXProject/hpx/pull/6169>

¹⁴⁵⁰ <https://github.com/TheHPXProject/hpx/pull/6167>

¹⁴⁵¹ <https://github.com/TheHPXProject/hpx/pull/6166>

¹⁴⁵² <https://github.com/TheHPXProject/hpx/pull/6165>

¹⁴⁵³ <https://github.com/TheHPXProject/hpx/pull/6161>

- PR #6160¹⁴⁵⁴ - More cleanup for module levels 0 to 10
- PR #6159¹⁴⁵⁵ - Fix minor spelling mistake in generate_issue_pr_list.sh
- PR #6158¹⁴⁵⁶ - Update documentation in *writing single-node applications* page
- PR #6157¹⁴⁵⁷ - Improve index_queue_spawning
- PR #6154¹⁴⁵⁸ - Avoid performing late command line handling twice in distributed runtime
- PR #6152¹⁴⁵⁹ - The -rd and -mr options didn't work, and they should have been -rd and -mr
- PR #6151¹⁴⁶⁰ - Refactoring the Manual page in documentation
- PR #6148¹⁴⁶¹ - Investigate the failure of the LCI parcelport.
- PR #6147¹⁴⁶² - Make posix co-routine stacks non-executable
- PR #6146¹⁴⁶³ - Avoid ambiguities wrt tag_invoke
- PR #6144¹⁴⁶⁴ - General improvements to scheduling and related fixes
- PR #6143¹⁴⁶⁵ - Add list of new namespaces for new release
- PR #6140¹⁴⁶⁶ - Fixing background scheduler to properly exit in the end
- PR #6139¹⁴⁶⁷ - [P2300] execution: Cleanup coroutines integration and improve ADL isolation
- PR #6137¹⁴⁶⁸ - Adding example of a simple master/slave distributed application
- PR #6136¹⁴⁶⁹ - Deprecate *execution::experimental::task_group* in favor of *experimental::task_group*
- PR #6135¹⁴⁷⁰ - Fixing warnings reported by MSVC analysis
- PR #6134¹⁴⁷¹ - Adding notification function for parcelports to be called after early parcel handling
- PR #6132¹⁴⁷² - Fixing to_non_par() for parallel simd policies
- PR #6131¹⁴⁷³ - modernize modules from level 25
- PR #6130¹⁴⁷⁴ - Remove the mutex lock in the critical path of get_partitioner.
- PR #6129¹⁴⁷⁵ - Modernize module from levels 22, 23
- PR #6127¹⁴⁷⁶ - Working around gccV9 problem that prevent us from storing enum classes in bit fields

¹⁴⁵⁴ <https://github.com/TheHPXProject/hpx/pull/6160>

¹⁴⁵⁵ <https://github.com/TheHPXProject/hpx/pull/6159>

¹⁴⁵⁶ <https://github.com/TheHPXProject/hpx/pull/6158>

¹⁴⁵⁷ <https://github.com/TheHPXProject/hpx/pull/6157>

¹⁴⁵⁸ <https://github.com/TheHPXProject/hpx/pull/6154>

¹⁴⁵⁹ <https://github.com/TheHPXProject/hpx/pull/6152>

¹⁴⁶⁰ <https://github.com/TheHPXProject/hpx/pull/6151>

¹⁴⁶¹ <https://github.com/TheHPXProject/hpx/pull/6148>

¹⁴⁶² <https://github.com/TheHPXProject/hpx/pull/6147>

¹⁴⁶³ <https://github.com/TheHPXProject/hpx/pull/6146>

¹⁴⁶⁴ <https://github.com/TheHPXProject/hpx/pull/6144>

¹⁴⁶⁵ <https://github.com/TheHPXProject/hpx/pull/6143>

¹⁴⁶⁶ <https://github.com/TheHPXProject/hpx/pull/6140>

¹⁴⁶⁷ <https://github.com/TheHPXProject/hpx/pull/6139>

¹⁴⁶⁸ <https://github.com/TheHPXProject/hpx/pull/6137>

¹⁴⁶⁹ <https://github.com/TheHPXProject/hpx/pull/6136>

¹⁴⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6135>

¹⁴⁷¹ <https://github.com/TheHPXProject/hpx/pull/6134>

¹⁴⁷² <https://github.com/TheHPXProject/hpx/pull/6132>

¹⁴⁷³ <https://github.com/TheHPXProject/hpx/pull/6131>

¹⁴⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6130>

¹⁴⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6129>

¹⁴⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6127>

- PR #6126¹⁴⁷⁷ - Deprecate `hpx::parallel::task_block` in favor of `hpx::experimental::task_block`
- PR #6125¹⁴⁷⁸ - Making sure `sync_wait` compiles when used with an lvalue sender involving bulk
- PR #6124¹⁴⁷⁹ - Fixing use of `any_sender` in combination with `when_all`
- PR #6123¹⁴⁸⁰ - Fixed issues found by PVS-Studio
- PR #6121¹⁴⁸¹ - Modernize modules of level 21, 22
- PR #6120¹⁴⁸² - Use `index_queue` for parallel executors `bulk_async_execute`
- PR #6119¹⁴⁸³ - Update `CMakeLists.txt`
- PR #6118¹⁴⁸⁴ - Modernize modules from level 17, 18, 19, and 20
- PR #6117¹⁴⁸⁵ - Initialize `buffer_allocate_time_` to 0
- PR #6116¹⁴⁸⁶ - Add new command line argument `-hpx:loopback_network`
- PR #6115¹⁴⁸⁷ - Modernize modules of levels 14, 15, and 16
- PR #6114¹⁴⁸⁸ - Enhance the formatting of the documentation
- PR #6113¹⁴⁸⁹ - Modernize modules in module level 11, 12, and 13
- PR #6112¹⁴⁹⁰ - Modernize modules from levels 9 and 10
- PR #6111¹⁴⁹¹ - Modernize all modules from module level 8
- PR #6110¹⁴⁹² - Use pragma error directive to report warnings as errors on msvc
- PR #6109¹⁴⁹³ - Modernize serialization module
- PR #6107¹⁴⁹⁴ - Modernize error module
- PR #6106¹⁴⁹⁵ - Modernizing modules of levels 0 to 5
- PR #6105¹⁴⁹⁶ - Optimizations on LCI parcelport: merge small messages; remove sender mutex lock.
- PR #6104¹⁴⁹⁷ - Adding parameters API: `measure_iteration`
- PR #6103¹⁴⁹⁸ - Document `task_group` and include in Public API
- PR #6102¹⁴⁹⁹ - Prevent warnings generated by clang-cl

¹⁴⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6126>

¹⁴⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6125>

¹⁴⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6124>

¹⁴⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6123>

¹⁴⁸¹ <https://github.com/TheHPXProject/hpx/pull/6121>

¹⁴⁸² <https://github.com/TheHPXProject/hpx/pull/6120>

¹⁴⁸³ <https://github.com/TheHPXProject/hpx/pull/6119>

¹⁴⁸⁴ <https://github.com/TheHPXProject/hpx/pull/6118>

¹⁴⁸⁵ <https://github.com/TheHPXProject/hpx/pull/6117>

¹⁴⁸⁶ <https://github.com/TheHPXProject/hpx/pull/6116>

¹⁴⁸⁷ <https://github.com/TheHPXProject/hpx/pull/6115>

¹⁴⁸⁸ <https://github.com/TheHPXProject/hpx/pull/6114>

¹⁴⁸⁹ <https://github.com/TheHPXProject/hpx/pull/6113>

¹⁴⁹⁰ <https://github.com/TheHPXProject/hpx/pull/6112>

¹⁴⁹¹ <https://github.com/TheHPXProject/hpx/pull/6111>

¹⁴⁹² <https://github.com/TheHPXProject/hpx/pull/6110>

¹⁴⁹³ <https://github.com/TheHPXProject/hpx/pull/6109>

¹⁴⁹⁴ <https://github.com/TheHPXProject/hpx/pull/6107>

¹⁴⁹⁵ <https://github.com/TheHPXProject/hpx/pull/6106>

¹⁴⁹⁶ <https://github.com/TheHPXProject/hpx/pull/6105>

¹⁴⁹⁷ <https://github.com/TheHPXProject/hpx/pull/6104>

¹⁴⁹⁸ <https://github.com/TheHPXProject/hpx/pull/6103>

¹⁴⁹⁹ <https://github.com/TheHPXProject/hpx/pull/6102>

- PR #6101¹⁵⁰⁰ - Using more fold expressions
- PR #6100¹⁵⁰¹ - Deprecate `hpx::parallel::reduce_by_key` in favor of `hpx::experimental::reduce_by_key`
- PR #6098¹⁵⁰² - Forking Boost.Lockfree
- PR #6096¹⁵⁰³ - Forking Boost.Tokenizer
- PR #6095¹⁵⁰⁴ - Replacing facilities from Boost.Range
- PR #6094¹⁵⁰⁵ - Removing object_semaphore
- PR #6093¹⁵⁰⁶ - Replace `boost::string_ref` with `std::string_view`
- PR #6092¹⁵⁰⁷ - Use C++17 `static_assert` where possible
- PR #6091¹⁵⁰⁸ - Replace artificial sequencing with fold expressions
- PR #6090¹⁵⁰⁹ - Fixing use of `get_chunk_size` customization point
- PR #6088¹⁵¹⁰ - Add/fix Public API documentation
- PR #6086¹⁵¹¹ - Deprecate `hpx::util::unlock_guard` in favor of `hpx::unlock_guard`
- PR #6085¹⁵¹² - Add experimental `sycl` integration/executor
- PR #6084¹⁵¹³ - Renaming `hpx::apply` and friends to `hpx::post`
- PR #6083¹⁵¹⁴ - Using `if constexpr` instead of tag-dispatching, where possible
- PR #6082¹⁵¹⁵ - Replace `util::always_void_t` with `std::void_t`
- PR #6081¹⁵¹⁶ - Update github actions to avoid warnings
- PR #6080¹⁵¹⁷ - Disable some tests that fail on LCI
- PR #6079¹⁵¹⁸ - Adding more `natvis` files, correct existing
- PR #6078¹⁵¹⁹ - Changing target name of `memory_counters` component
- PR #6077¹⁵²⁰ - Making default constructor of `hpx::mutex constexpr`
- PR #6076¹⁵²¹ - Cleaning up functionality that was deprecated in V1.7
- PR #6075¹⁵²² - Remove conditional code for gcc V7 and below

¹⁵⁰⁰ <https://github.com/TheHPXProject/hpx/pull/6101>

¹⁵⁰¹ <https://github.com/TheHPXProject/hpx/pull/6100>

¹⁵⁰² <https://github.com/TheHPXProject/hpx/pull/6098>

¹⁵⁰³ <https://github.com/TheHPXProject/hpx/pull/6096>

¹⁵⁰⁴ <https://github.com/TheHPXProject/hpx/pull/6095>

¹⁵⁰⁵ <https://github.com/TheHPXProject/hpx/pull/6094>

¹⁵⁰⁶ <https://github.com/TheHPXProject/hpx/pull/6093>

¹⁵⁰⁷ <https://github.com/TheHPXProject/hpx/pull/6092>

¹⁵⁰⁸ <https://github.com/TheHPXProject/hpx/pull/6091>

¹⁵⁰⁹ <https://github.com/TheHPXProject/hpx/pull/6090>

¹⁵¹⁰ <https://github.com/TheHPXProject/hpx/pull/6088>

¹⁵¹¹ <https://github.com/TheHPXProject/hpx/pull/6086>

¹⁵¹² <https://github.com/TheHPXProject/hpx/pull/6085>

¹⁵¹³ <https://github.com/TheHPXProject/hpx/pull/6084>

¹⁵¹⁴ <https://github.com/TheHPXProject/hpx/pull/6083>

¹⁵¹⁵ <https://github.com/TheHPXProject/hpx/pull/6082>

¹⁵¹⁶ <https://github.com/TheHPXProject/hpx/pull/6081>

¹⁵¹⁷ <https://github.com/TheHPXProject/hpx/pull/6080>

¹⁵¹⁸ <https://github.com/TheHPXProject/hpx/pull/6079>

¹⁵¹⁹ <https://github.com/TheHPXProject/hpx/pull/6078>

¹⁵²⁰ <https://github.com/TheHPXProject/hpx/pull/6077>

¹⁵²¹ <https://github.com/TheHPXProject/hpx/pull/6076>

¹⁵²² <https://github.com/TheHPXProject/hpx/pull/6075>

- PR #6074¹⁵²³ - Fixing compilation issues on gcc V8
- PR #6073¹⁵²⁴ - Fixing PAPI counter component compilation
- PR #6072¹⁵²⁵ - Adding `ex::when_all_vector`
- PR #6071¹⁵²⁶ - Making `get_forward_progress_guarantee_t` specializations constexpr
- PR #6070¹⁵²⁷ - Implement P2690 for our algorithms
- PR #6069¹⁵²⁸ - Do not check for cancellation during each iteration but only once per partition
- PR #6068¹⁵²⁹ - Prevent using `task` and `non_task` as a CPO
- PR #6067¹⁵³⁰ - Deprecated `hpx::util::mem_fn` in favor of `hpx::mem_fn`
- PR #6066¹⁵³¹ - Create `codeql.yml`
- PR #6064¹⁵³² - Adapting `adjacent_difference` for S/R execution
- PR #6063¹⁵³³ - Modernize `iterator_support` module
- PR #6062¹⁵³⁴ - Make sure wrapping executor does not go out of scope prematurely
- PR #6061¹⁵³⁵ - Minor fix in `small_vector` (from upstream)
- PR #6060¹⁵³⁶ - Allow to disable registering signal handlers
- PR #6059¹⁵³⁷ - [P2300] Fix: `declval` cannot be ODR used
- PR #6058¹⁵³⁸ - Avoid ambiguity for `hpx::get` used with `std::variant`
- PR #6057¹⁵³⁹ - Create a dedicated thread pool to run `LCI_progress`.
- PR #6056¹⁵⁴⁰ - Fix coroutine test for clang
- PR #6055¹⁵⁴¹ - Patches needed to be able to build HPX 1.8.1 on various platforms
- PR #6054¹⁵⁴² - Use MSVC specific attribute `[[msvc::no_unique_address]]`
- PR #6052¹⁵⁴³ - Deprecated `hpx::util::invoke_fused` in favor of `hpx::invoke_fused`
- PR #6051¹⁵⁴⁴ - Add non-contiguous index queue and use it in `thread_pool_bulk_scheduler`
- PR #6049¹⁵⁴⁵ - Crosscompile arm sve

¹⁵²³ <https://github.com/TheHPXProject/hpx/pull/6074>

¹⁵²⁴ <https://github.com/TheHPXProject/hpx/pull/6073>

¹⁵²⁵ <https://github.com/TheHPXProject/hpx/pull/6072>

¹⁵²⁶ <https://github.com/TheHPXProject/hpx/pull/6071>

¹⁵²⁷ <https://github.com/TheHPXProject/hpx/pull/6070>

¹⁵²⁸ <https://github.com/TheHPXProject/hpx/pull/6069>

¹⁵²⁹ <https://github.com/TheHPXProject/hpx/pull/6068>

¹⁵³⁰ <https://github.com/TheHPXProject/hpx/pull/6067>

¹⁵³¹ <https://github.com/TheHPXProject/hpx/pull/6066>

¹⁵³² <https://github.com/TheHPXProject/hpx/pull/6064>

¹⁵³³ <https://github.com/TheHPXProject/hpx/pull/6063>

¹⁵³⁴ <https://github.com/TheHPXProject/hpx/pull/6062>

¹⁵³⁵ <https://github.com/TheHPXProject/hpx/pull/6061>

¹⁵³⁶ <https://github.com/TheHPXProject/hpx/pull/6060>

¹⁵³⁷ <https://github.com/TheHPXProject/hpx/pull/6059>

¹⁵³⁸ <https://github.com/TheHPXProject/hpx/pull/6058>

¹⁵³⁹ <https://github.com/TheHPXProject/hpx/pull/6057>

¹⁵⁴⁰ <https://github.com/TheHPXProject/hpx/pull/6056>

¹⁵⁴¹ <https://github.com/TheHPXProject/hpx/pull/6055>

¹⁵⁴² <https://github.com/TheHPXProject/hpx/pull/6054>

¹⁵⁴³ <https://github.com/TheHPXProject/hpx/pull/6052>

¹⁵⁴⁴ <https://github.com/TheHPXProject/hpx/pull/6051>

¹⁵⁴⁵ <https://github.com/TheHPXProject/hpx/pull/6049>

- PR #6048¹⁵⁴⁶ - Deprecated `hpx::util::invoke` in favor of `hpx::invoke`
- PR #6047¹⁵⁴⁷ - Separating `binary_semaphore` into its own file
- PR #6046¹⁵⁴⁸ - Support using unwrapping with nullary function objects
- PR #6044¹⁵⁴⁹ - Generalize the use of `then()` and dataflow
- PR #6043¹⁵⁵⁰ - Clean up `scan_partitioner`
- PR #6042¹⁵⁵¹ - Modernize dataflow API
- PR #6041¹⁵⁵² - docs: document semaphores
- PR #6040¹⁵⁵³ - Add/Fix documentation of Public API page
- PR #6039¹⁵⁵⁴ - remove MPI dependency when only using LCI parcelport
- PR #6038¹⁵⁵⁵ - Clean up command line handling
- PR #6037¹⁵⁵⁶ - Avoid performing parcel related background work if networking is disabled
- PR #6036¹⁵⁵⁷ - Support new datapar backend : SVE
- PR #6035¹⁵⁵⁸ - Simplify datapar replace copy if
- PR #6034¹⁵⁵⁹ - Add/Fix documentation of Public API
- PR #6033¹⁵⁶⁰ - Support for data-parallelism for `replace`, `replace_if`, `replace_copy`, `replace_copy_if` algorithms
- PR #6032¹⁵⁶¹ - Add documentation in public API
- PR #6031¹⁵⁶² - Expose available cache sizes from topology object
- PR #6030¹⁵⁶³ - Adding parcelport initialization hook for resource partitioner operation
- PR #6029¹⁵⁶⁴ - Simplify startup code
- PR #6027¹⁵⁶⁵ - Add/Fix documentation in Public API page
- PR #6026¹⁵⁶⁶ - add option `hpx:force_ipv4` to force resolving hostnames to ipv4 addresses
- PR #6025¹⁵⁶⁷ - `build(docs)`: remove leftover sections
- PR #6023¹⁵⁶⁸ - Minor fixes on “How to build on Windows”

¹⁵⁴⁶ <https://github.com/TheHPXProject/hpx/pull/6048>

¹⁵⁴⁷ <https://github.com/TheHPXProject/hpx/pull/6047>

¹⁵⁴⁸ <https://github.com/TheHPXProject/hpx/pull/6046>

¹⁵⁴⁹ <https://github.com/TheHPXProject/hpx/pull/6044>

¹⁵⁵⁰ <https://github.com/TheHPXProject/hpx/pull/6043>

¹⁵⁵¹ <https://github.com/TheHPXProject/hpx/pull/6042>

¹⁵⁵² <https://github.com/TheHPXProject/hpx/pull/6041>

¹⁵⁵³ <https://github.com/TheHPXProject/hpx/pull/6040>

¹⁵⁵⁴ <https://github.com/TheHPXProject/hpx/pull/6039>

¹⁵⁵⁵ <https://github.com/TheHPXProject/hpx/pull/6038>

¹⁵⁵⁶ <https://github.com/TheHPXProject/hpx/pull/6037>

¹⁵⁵⁷ <https://github.com/TheHPXProject/hpx/pull/6036>

¹⁵⁵⁸ <https://github.com/TheHPXProject/hpx/pull/6035>

¹⁵⁵⁹ <https://github.com/TheHPXProject/hpx/pull/6034>

¹⁵⁶⁰ <https://github.com/TheHPXProject/hpx/pull/6033>

¹⁵⁶¹ <https://github.com/TheHPXProject/hpx/pull/6032>

¹⁵⁶² <https://github.com/TheHPXProject/hpx/pull/6031>

¹⁵⁶³ <https://github.com/TheHPXProject/hpx/pull/6030>

¹⁵⁶⁴ <https://github.com/TheHPXProject/hpx/pull/6029>

¹⁵⁶⁵ <https://github.com/TheHPXProject/hpx/pull/6027>

¹⁵⁶⁶ <https://github.com/TheHPXProject/hpx/pull/6026>

¹⁵⁶⁷ <https://github.com/TheHPXProject/hpx/pull/6025>

¹⁵⁶⁸ <https://github.com/TheHPXProject/hpx/pull/6023>

- PR #6022¹⁵⁶⁹ - build(doxy): don't extract private members
- PR #6021¹⁵⁷⁰ - Adding pu_mask to thread_pool_bulk_scheduler
- PR #6020¹⁵⁷¹ - docs: add cppref NamedRequirements support
- PR #6018¹⁵⁷² - Unseq adaptation for for_each, transform, reduce, transform_reduce, etc.
- PR #6017¹⁵⁷³ - loop and transform_loop unseq adaptation
- PR #6016¹⁵⁷⁴ - Config and structural updates to support unseq implementation
- PR #6015¹⁵⁷⁵ - Integrating sync_wait & sync_wait_with_variant
- PR #6012¹⁵⁷⁶ - docs: add missing links to public api
- PR #6009¹⁵⁷⁷ - Fixing sender&receiver integration with for_each and for_loop
- PR #6007¹⁵⁷⁸ - docs: add docs for mutex.hpp
- PR #6006¹⁵⁷⁹ - Relax future::is_ready where possible
- PR #6005¹⁵⁸⁰ - reshuffle header tests to different instances
- PR #6004¹⁵⁸¹ - Add documentation Public API
- PR #6003¹⁵⁸² - Always exporting get_component_name implementations
- PR #6002¹⁵⁸³ - Making sure that default constructible arguments are properly constructed during deserialization
- PR #5996¹⁵⁸⁴ - Add back explicit template parameters to lock_guards for nvcc
- PR #5994¹⁵⁸⁵ - Fix CTRL+C on windows
- PR #5993¹⁵⁸⁶ - Using EVE requires C++20
- PR #5992¹⁵⁸⁷ - This properly terminates an application on Ctrl-C on Windows
- PR #5991¹⁵⁸⁸ - Support IPV6 on command line for explicit network initialization
- PR #5990¹⁵⁸⁹ - P2300 enhancements
- PR #5989¹⁵⁹⁰ - Fix missing documentation in Public API page
- PR #5987¹⁵⁹¹ - Attempting to fix timed executor API

¹⁵⁶⁹ <https://github.com/TheHPXProject/hpx/pull/6022>

¹⁵⁷⁰ <https://github.com/TheHPXProject/hpx/pull/6021>

¹⁵⁷¹ <https://github.com/TheHPXProject/hpx/pull/6020>

¹⁵⁷² <https://github.com/TheHPXProject/hpx/pull/6018>

¹⁵⁷³ <https://github.com/TheHPXProject/hpx/pull/6017>

¹⁵⁷⁴ <https://github.com/TheHPXProject/hpx/pull/6016>

¹⁵⁷⁵ <https://github.com/TheHPXProject/hpx/pull/6015>

¹⁵⁷⁶ <https://github.com/TheHPXProject/hpx/pull/6012>

¹⁵⁷⁷ <https://github.com/TheHPXProject/hpx/pull/6009>

¹⁵⁷⁸ <https://github.com/TheHPXProject/hpx/pull/6007>

¹⁵⁷⁹ <https://github.com/TheHPXProject/hpx/pull/6006>

¹⁵⁸⁰ <https://github.com/TheHPXProject/hpx/pull/6005>

¹⁵⁸¹ <https://github.com/TheHPXProject/hpx/pull/6004>

¹⁵⁸² <https://github.com/TheHPXProject/hpx/pull/6003>

¹⁵⁸³ <https://github.com/TheHPXProject/hpx/pull/6002>

¹⁵⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5996>

¹⁵⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5994>

¹⁵⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5993>

¹⁵⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5992>

¹⁵⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5991>

¹⁵⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5990>

¹⁵⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5989>

¹⁵⁹¹ <https://github.com/TheHPXProject/hpx/pull/5987>

- PR #5986¹⁵⁹² - Fix warnings when building docs
- PR #5985¹⁵⁹³ - Re-add deprecated tag_policy_tag et.al. types that were removed in V1.8.1
- PR #5981¹⁵⁹⁴ - docs: add docs for condition_variable.hpp
- PR #5980¹⁵⁹⁵ - More work on execution::read
- PR #5979¹⁵⁹⁶ - Remove support for clang-v8 and clang-v9, switch LSU clang-v13 to C++17
- PR #5977¹⁵⁹⁷ - fix: Compilation errors for -std=c++17 builders
- PR #5975¹⁵⁹⁸ - docs: fix & improve parallel algorithms documentation 5
- PR #5974¹⁵⁹⁹ - [P2300] Adapt get completion signatures for awaitable senders
- PR #5973¹⁶⁰⁰ - defaults boost.context on riscv64
- PR #5972¹⁶⁰¹ - Fix documentation for container algorithms
- PR #5971¹⁶⁰² - added logic to detect riscv compiler configured for 64 bit target
- PR #5968¹⁶⁰³ - adds risc-v 64 bit support
- PR #5967¹⁶⁰⁴ - Adding missing pieces to sync_wait, adding run_loop
- PR #5966¹⁶⁰⁵ - docs: fix & improve parallel algorithms documentation 4
- PR #5965¹⁶⁰⁶ - Fixing inspect problems, adding missing header file
- PR #5962¹⁶⁰⁷ - Changes in html page of documentation
- PR #5961¹⁶⁰⁸ - Prevent stalling during shutdown when running hello_world_distributed
- PR #5955¹⁶⁰⁹ - Fix documentation for container algorithms
- PR #5952¹⁶¹⁰ - docs: fix & improve parallel algorithms documentation 3
- PR #5950¹⁶¹¹ - Change executors to directly implement the executor CPOs
- PR #5949¹⁶¹² - Converting async combinators into CPOs
- PR #5948¹⁶¹³ - Adding support for pure sender/receiver based executors to parallel algorithms
- PR #5945¹⁶¹⁴ - [P2300] Added fundamental coroutine_traits for S/R

¹⁵⁹² <https://github.com/TheHPXProject/hpx/pull/5986>

¹⁵⁹³ <https://github.com/TheHPXProject/hpx/pull/5985>

¹⁵⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5981>

¹⁵⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5980>

¹⁵⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5979>

¹⁵⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5977>

¹⁵⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5975>

¹⁵⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5974>

¹⁶⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5973>

¹⁶⁰¹ <https://github.com/TheHPXProject/hpx/pull/5972>

¹⁶⁰² <https://github.com/TheHPXProject/hpx/pull/5971>

¹⁶⁰³ <https://github.com/TheHPXProject/hpx/pull/5968>

¹⁶⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5967>

¹⁶⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5966>

¹⁶⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5965>

¹⁶⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5962>

¹⁶⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5961>

¹⁶⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5955>

¹⁶¹⁰ <https://github.com/TheHPXProject/hpx/pull/5952>

¹⁶¹¹ <https://github.com/TheHPXProject/hpx/pull/5950>

¹⁶¹² <https://github.com/TheHPXProject/hpx/pull/5949>

¹⁶¹³ <https://github.com/TheHPXProject/hpx/pull/5948>

¹⁶¹⁴ <https://github.com/TheHPXProject/hpx/pull/5945>

- PR #5883¹⁶¹⁵ - Optimization on LCI parcelport: uses LCI_putva
- PR #5872¹⁶¹⁶ - Block fork join executor
- PR #5855¹⁶¹⁷ - Adding performance test Jenkins builder at LSU

HPX V1.8.1 (Aug 5, 2022)

This is a bugfix release with a few minor additions and resolved problems.

General changes

This patch release adds a number of small new features and fixes a handful of problems discovered since the last release, in particular:

- A lot of work has been done to improve vectorization support for our parallel algorithms. HPX now supports using EVE - the Expressive Vector Engine as a vectorization backend.
- Added a simple average power consumption performance counter.
- Added performance counters related to the use of zero-copy chunks in the networking layer.
- More work was done towards full compatibility with the sender/receivers proposal P2300.
- Fixing `sync_wait` to decay the result types
- Fixed collective operations to properly avoid overlapping consecutive operations on the same communicator.
- Simplified the implementation of our execution policies and added mapping functions between those.
- Fixed performance issues with our implementation of *small_vector*.
- Serialization now works with buffers of unsigned characters.
- Fixing dangling reference in serialization of non-default constructible types
- Fixed static linking on Windows.
- Fixed support for M1/MacOS based architectures.
- Fixed support for gentoo/musl.
- Fixed `hpx::counting_semaphore_var`.
- Properly check start and end bounds for `hpx::for_loop`
- A lot of changes and fixes to the documentation (see <https://hpx-docs.stellar-group.org>).

¹⁶¹⁵ <https://github.com/TheHPXProject/hpx/pull/5883>

¹⁶¹⁶ <https://github.com/TheHPXProject/hpx/pull/5872>

¹⁶¹⁷ <https://github.com/TheHPXProject/hpx/pull/5855>

Breaking changes

- No breaking changes have been introduced.

Closed issues

- [Issue #5964](#)¹⁶¹⁸ - component with multiple inheritance
- [Issue #5946](#)¹⁶¹⁹ - `dll_dlopen.hpp`: error: `RTLD_DI_ORIGIN` was not declared in this scope with `musl` libc
- [Issue #5925](#)¹⁶²⁰ - Simplify implementation of execution policies
- [Issue #5924](#)¹⁶²¹ - `{what}`: `mmap()` failed to allocate thread stack: `HPX(unhandled_exception)`
- [Issue #5912](#)¹⁶²² - collectives all gather hangs if rank 0 is not involved
- [Issue #5902](#)¹⁶²³ - MPI `parcelport` issue on Fugaku
- [Issue #5900](#)¹⁶²⁴ - Unable to build `hello_world_distributed.cpp`.
- [Issue #5892](#)¹⁶²⁵ - Problems with HPX serialization as a standalone feature. Testcase provided.
- [Issue #5886](#)¹⁶²⁶ - Segfault when serializing non default constructible class with `stl` containers data members
- [Issue #5832](#)¹⁶²⁷ - Distributed execution crash
- [Issue #5768](#)¹⁶²⁸ - HPX hangs on `Perlmutter`
- [Issue #5735](#)¹⁶²⁹ - `hpx::for_loop` executes without checking start and end bounds
- [Issue #5700](#)¹⁶³⁰ - `HPX(serialization_error)`

Closed pull requests

- [PR #5970](#)¹⁶³¹ - Fixing component multiple inheritance
- [PR #5969](#)¹⁶³² - Fixing `sync_wait` to avoid dangling references
- [PR #5963](#)¹⁶³³ - Fixing `sync_wait` to decay the result types
- [PR #5960](#)¹⁶³⁴ - docs: added name to documentation contributors list
- [PR #5959](#)¹⁶³⁵ - Fixing `sync_wait` to decay the result types

¹⁶¹⁸ <https://github.com/TheHPXProject/hpx/issues/5964>

¹⁶¹⁹ <https://github.com/TheHPXProject/hpx/issues/5946>

¹⁶²⁰ <https://github.com/TheHPXProject/hpx/issues/5925>

¹⁶²¹ <https://github.com/TheHPXProject/hpx/issues/5924>

¹⁶²² <https://github.com/TheHPXProject/hpx/issues/5912>

¹⁶²³ <https://github.com/TheHPXProject/hpx/issues/5902>

¹⁶²⁴ <https://github.com/TheHPXProject/hpx/issues/5900>

¹⁶²⁵ <https://github.com/TheHPXProject/hpx/issues/5892>

¹⁶²⁶ <https://github.com/TheHPXProject/hpx/issues/5886>

¹⁶²⁷ <https://github.com/TheHPXProject/hpx/issues/5832>

¹⁶²⁸ <https://github.com/TheHPXProject/hpx/issues/5768>

¹⁶²⁹ <https://github.com/TheHPXProject/hpx/issues/5735>

¹⁶³⁰ <https://github.com/TheHPXProject/hpx/issues/5700>

¹⁶³¹ <https://github.com/TheHPXProject/hpx/pull/5970>

¹⁶³² <https://github.com/TheHPXProject/hpx/pull/5969>

¹⁶³³ <https://github.com/TheHPXProject/hpx/pull/5963>

¹⁶³⁴ <https://github.com/TheHPXProject/hpx/pull/5960>

¹⁶³⁵ <https://github.com/TheHPXProject/hpx/pull/5959>

- PR #5954¹⁶³⁶ - refactor: rename itr to correct type (*reduce*)
- PR #5954¹⁶³⁷ - refactor: rename itr to correct type (*reduce*)
- PR #5953¹⁶³⁸ - Fixed property handling in hierarchical_spawning
- PR #5951¹⁶³⁹ - Fixing static linking (for Windows)
- PR #5947¹⁶⁴⁰ - Fix building on musl.
- PR #5944¹⁶⁴¹ - added adaptive_static_chunk_size
- PR #5943¹⁶⁴² - Fix sync_wait
- PR #5942¹⁶⁴³ - Fix doc warnings
- PR #5941¹⁶⁴⁴ - Fix sync_wait
- PR #5940¹⁶⁴⁵ - Protect collective operations against std::vector<bool> idiosyncrasies
- PR #5939¹⁶⁴⁶ - docs: fix & improve parallel algorithms documentation 2
- PR #5938¹⁶⁴⁷ - Properly implement generation support for collective operations
- PR #5937¹⁶⁴⁸ - Remove leftover files from PMR based small_vector
- PR #5936¹⁶⁴⁹ - Adding mapping functions between execution policies
- PR #5935¹⁶⁵⁰ - Fixing serialization to work with buffers of unsigned chars
- PR #5934¹⁶⁵¹ - Attempting to fix datapar issues on CircleCI
- PR #5933¹⁶⁵² - Fix documentation for ranges algorithms
- PR #5932¹⁶⁵³ - Remove mimalloc version constraint
- PR #5931¹⁶⁵⁴ - docs: fix & improve parallel algorithms documentation
- PR #5930¹⁶⁵⁵ - Add boost to hip builder
- PR #5929¹⁶⁵⁶ - Apply fixes to M1/MacOS related stack allocation to all relevant spots
- PR #5928¹⁶⁵⁷ - updated context_generic_context to accommodate arm64_arch_8/Apple architecture
- PR #5927¹⁶⁵⁸ - Public derivation for counting_semaphore_var

¹⁶³⁶ <https://github.com/TheHPXProject/hpx/pull/5954>

¹⁶³⁷ <https://github.com/TheHPXProject/hpx/pull/5954>

¹⁶³⁸ <https://github.com/TheHPXProject/hpx/pull/5953>

¹⁶³⁹ <https://github.com/TheHPXProject/hpx/pull/5951>

¹⁶⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5947>

¹⁶⁴¹ <https://github.com/TheHPXProject/hpx/pull/5944>

¹⁶⁴² <https://github.com/TheHPXProject/hpx/pull/5943>

¹⁶⁴³ <https://github.com/TheHPXProject/hpx/pull/5942>

¹⁶⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5941>

¹⁶⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5940>

¹⁶⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5939>

¹⁶⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5938>

¹⁶⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5937>

¹⁶⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5936>

¹⁶⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5935>

¹⁶⁵¹ <https://github.com/TheHPXProject/hpx/pull/5934>

¹⁶⁵² <https://github.com/TheHPXProject/hpx/pull/5933>

¹⁶⁵³ <https://github.com/TheHPXProject/hpx/pull/5932>

¹⁶⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5931>

¹⁶⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5930>

¹⁶⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5929>

¹⁶⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5928>

¹⁶⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5927>

- PR #5926¹⁶⁵⁹ - Fix doxygen warnings when building documentation
- PR #5923¹⁶⁶⁰ - Fixing git checkout to reflect latest version tag
- PR #5922¹⁶⁶¹ - A couple of unrelated changes in support of implementing P1673
- PR #5920¹⁶⁶² - [P2300] enhancements: receiver_of, sender_of improvements
- PR #5917¹⁶⁶³ - Fixing various ‘held lock while suspending’ problems
- PR #5916¹⁶⁶⁴ - Fix minor doxygen parsing typo
- PR #5915¹⁶⁶⁵ - docs: fix broken api algo links
- PR #5914¹⁶⁶⁶ - Remove CSS rules - update sphinx version
- PR #5911¹⁶⁶⁷ - Removed references to hpx::vector in comments
- PR #5909¹⁶⁶⁸ - Remove stuff which is defined in the header
- PR #5906¹⁶⁶⁹ - Use BUILD_SHARED_LIBS correctly
- PR #5905¹⁶⁷⁰ - Fix incorrect usage of generator expressions
- PR #5904¹⁶⁷¹ - Delete FindBZip2.cmake
- PR #5901¹⁶⁷² - Fix #5900
- PR #5899¹⁶⁷³ - Replace PMR based version of small_vector
- PR #5897¹⁶⁷⁴ - Add missing “”
- PR #5896¹⁶⁷⁵ - Docs: Add serialization tutorial.
- PR #5895¹⁶⁷⁶ - Update to V1.9.0 on master
- PR #5894¹⁶⁷⁷ - Fix executor_with_thread_hooks example
- PR #5890¹⁶⁷⁸ - Adding simple average power consumption performance counter
- PR #5889¹⁶⁷⁹ - Par unseq/unseq adding
- PR #5888¹⁶⁸⁰ - Support for data-parallelism for reduce, transform reduce, transform_binary_reduce algorithms
- PR #5887¹⁶⁸¹ - Fixing dangling reference in serialization of non-default constructible types

¹⁶⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5926>

¹⁶⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5923>

¹⁶⁶¹ <https://github.com/TheHPXProject/hpx/pull/5922>

¹⁶⁶² <https://github.com/TheHPXProject/hpx/pull/5920>

¹⁶⁶³ <https://github.com/TheHPXProject/hpx/pull/5917>

¹⁶⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5916>

¹⁶⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5915>

¹⁶⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5914>

¹⁶⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5911>

¹⁶⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5909>

¹⁶⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5906>

¹⁶⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5905>

¹⁶⁷¹ <https://github.com/TheHPXProject/hpx/pull/5904>

¹⁶⁷² <https://github.com/TheHPXProject/hpx/pull/5901>

¹⁶⁷³ <https://github.com/TheHPXProject/hpx/pull/5899>

¹⁶⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5897>

¹⁶⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5896>

¹⁶⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5895>

¹⁶⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5894>

¹⁶⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5890>

¹⁶⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5889>

¹⁶⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5888>

¹⁶⁸¹ <https://github.com/TheHPXProject/hpx/pull/5887>

- PR #5879¹⁶⁸² - New performance counters related to zero-copy chunks.

HPX V1.8.0 (May 18, 2022)

With HPX parallel algorithms been fully adapted to C++20 the new release achieves full conformance with C++20 concurrency and parallelism facilities. HPX now supports all of the algorithms as specified by C++20. We have added support for vectorization to more of our algorithms. Much work has been done towards implementing P2300 (“std::execution”) and implementing the underlying senders/receivers facilities. Finally, The new release comes with a brand new documentation interface!

General changes

- The new documentation can now be found on our webpage: <https://hpx-docs.stellar-group.org>. This includes a completely new and user-friendly interface environment along with restructuring of certain components. The content in the “Quick start”, “Manual” and “Examples” was improved, while the “Build system” page was adapted to include necessary information for newcomers.
- With the vectorization support available in modern hardware architectures HPX now provides new data-parallel vector execution policies `hpx::execution::simd` and `hpx::execution::par_simd` that enable significant speed-up of our parallel algorithm implementations. The following algorithms now support SIMD execution:
 - `copy`, `copy_n`
 - `generate`
 - `adjacent_difference`, `adjacent_find`
 - `all_of`, `any_of`, `none_of`
 - `equal`, `mismatch`,
 - `inner_product`
 - `count`, `count_if`
 - `fill`, `fill_n`
 - `find`, `find_end`, `find_first_of`, `find_if`, `find_if_not`
 - `for_each`, `for_each_n`
 - `generate`, `generate_n`.
- Based on top of P2300 the HPX parallel algorithms now support the pipeline syntax towards an effort to unify their usage along with senders/receivers. The HPX parallel algorithms can now bind with senders/receivers using the pipeline operator.
- Several changes took place on the executors provided by HPX:
- The executors now support the `num_cores` options in order for the user to be able to specify the desired number of cores to be used in the corresponding execution.
- The `scheduler` executor was implemented on top of senders/receivers and can be used with all HPX facilities that schedule new work, such as parallel algorithms, `hpx::async`, `hpx::dataflow`, etc.
- The performance of `fork_join_executor` was improved.
- The following algorithms have been added/adapted to be C++20 conformant:
 - `min_element`

¹⁶⁸² <https://github.com/TheHPXProject/hpx/pull/5879>

- `max_element`
 - `minmax_element`
 - `starts_with`
 - `ends_with`
 - `swap_ranges`
 - `unique`
 - `unique_copy`
 - `rotate`
 - `rotate_copy`
 - `sort`
 - `shift_left`
 - `shift_right`
 - `stable_sort`
 - `partition`
 - `partition_copy`
 - `stable_partition`
 - `adjacent_difference`
 - `nth_element`
 - `partial_sort`
 - `partial_sort_copy`.
- HPX_FORWARD/HPX_MOVE macros were introduced that replaced the `std::move` and `std::forward` facilities that in the library code.
 - Hangs on distributed barrier were fixed.
 - The performance of `scan_partitioner` was improved.
 - Support was added for `thread_priority` to the `parallel_execution_policy`
 - Regarding senders/receivers and the P2300 proposal various actions took place. `stop_token` was adapted to the recent proposal version (`in_place_stop_token` was introduced). Also hint, annotation, priority and stacksize properties were added to the scheduler executor. Stop support was added to `when_all`. Support for completion signatures was added. The following schedulers and algorithms were added:
 - `get_completion_scheduler`
 - `any_sender` and `unique_any_sender`
 - `split` sender
 - `transform_mpi` sender
 - `transfer` sender
 - `let_error`, `let_stopped`
 - `get_env` and related environment queries
 - `schedule`, `set_value`, `set_error`, `set_done`, `start` and `connect` are now proper customization points as defined in P2300.

- Several namespaces were altered towards conformance with C++20. Compatibility layers have been added and the old versions will be removed in next releases. The namespace changes are the following:
 - `hpx::parallel::induction/reduction` were moved into namespace `hpx::experimental`
 - `for_loop` and friends were moved into namespace `hpx::experimental`.
 - `hpx::util::optional` and friends were moved into namespace `hpx`.
 - `hpx::lcos::barrier` has been moved into the `hpx::distributed` namespace and `hpx::lcos::local::cpp20_barrier` has been renamed to `barrier` and moved into the `hpx` namespace.
 - `hpx::lcos::latch` has been moved into the `hpx::distributed` namespace and `lcos::local::latch` has been moved into the `hpx` namespace. The `count_down_and_wait()` functionality of `latch` has been renamed to `arrive_and_wait()`.
 - `hpx::util::unique_function_nonsr` has been renamed to `hpx::move_only_function`.
 - `hpx::util::unique_function` has been renamed to `hpx::distributed::move_only_function`.
 - `hpx::util::function` has been renamed to `hpx::distributed::function`.
 - `hpx::util::function_nonsr` has been renamed to `hpx::function`.
 - `hpx::util::function_ref` have been moved to namespace `hpx`.
 - `hpx::lcos::split_future` changed namespace and is now used as `hpx::split_future`.
 - `hpx::lcos::local::counting_semaphore` has been deprecated and `hpx::lcos::local::cpp20_counting_semaphore` has been renamed to `hpx::counting_semaphore`.
 - `hpx::lcos::local::cpp20_binary_semaphore` has been renamed to `hpx::binary_semaphore`.
 - `hpx::lcos::local::sliding_semaphore` has been renamed to `hpx::sliding_semaphore` and
 - `hpx::lcos::local::sliding_semaphore_var` has been renamed to `hpx::sliding_semaphore_var`.
 - `hpx::lcos::local::spinlock` has been renamed to `hpx::spinlock`.
 - `hpx::lcos::local::mutex` has been renamed to `hpx::mutex`.
 - `hpx::lcos::local::timed_mutex` has been renamed to `hpx::timed_mutex`.
 - `hpx::lcos::local::no_mutex` has been renamed to `hpx::no_mutex`.
 - `hpx::lcos::local::recursive_mutex` has been renamed to `hpx::recursive_mutex`.
 - `hpx::lcos::local::shared_mutex` has been renamed to `hpx::shared_mutex`.
 - `hpx::lcos::local::upgrade_lock` has been renamed to `hpx::upgrade_lock`.
 - `hpx::lcos::local::upgrade_to_unique_lock` has been renamed to `hpx::upgrade_to_unique_lock`.
 - `hpx::lcos::local::condition_variable` has been renamed to `hpx::condition_variable`. `hpx::lcos::local::condition_variable_var` has been renamed to `hpx::condition_variable_var`.
 - `hpx::lcos::local::once_flag` has been renamed to `hpx::once_flag`, and `hpx::lcos::local::call_once` has been renamed to `hpx::call_once`.
- The new LCI (Lightweight Communication Interface) `parcelport` was added that supports irregular and asynchronous applications like graph analysis, sparse linear algebra, modern parallel architectures etc. Major features include:

- Support for advanced communication primitives like two sided send/recv and one sided remote put.
- Better multi-threaded performance.
- Explicit user control of communication resource.
- Flexible signaling mechanisms (synchronizer, completion queue, active message handler).
- The following CMake flags were added, mostly to support using HPX as a backend for SHAD (<https://github.com/pnnl/SHAD>). Please note that these options enable questionable functionalities, partially they even enable undefined behavior. Please only use any of them if you know what you're doing:
 - HPX_SERIALIZATION_WITH_ALLOW_RAW_POINTER_SERIALIZATION
 - HPX_SERIALIZATION_WITH_ALL_TYPES_ARE_BITWISE_SERIALIZABLE
 - HPX_SERIALIZATION_WITH_ALLOW_CONST_TUPLE_MEMBERS

Breaking changes

- Minimum required C++ standard library is C++17.
- Support for GCC 7 and Clang 8.0.0 and below has been removed.
- CUDA version required updated to 11.4.
- CMake version required updated to 3.18.
- The default version of Asio used was updated to 1.20.0.
- The default version of APEX used was updated to 2.5.1.
- APEX version was updated to 2.5.1.
- `tagged_pair` and `tagged_tuple` were removed.
- `tag_dispatch` was renamed to `tag_invoke`.
- `hpx.max_backgroud_threads` was renamed to `hpx.parcel.max_background_threads`.
- The following CMake flags were removed after being deprecated for at least two releases:
 - HPX_SCHEDULER_MAX_TERMINATED_THREADS
 - HPX_WITH_GOOGLE_PERFTOOLS
 - HPX_WITH_INIT_START_OVERLOADS_COMPATIBILITY
 - HPX_HAVE_{COROUTINE,PLUGIN}_GCC_HIDDEN_VISIBILITY
 - HPX_TOP_LEVEL
 - HPX_WITH_COMPUTE_CUDA
 - HPX_WITH_ASYNC_CUDA
- `annotate_function` was renamed to `scoped_annotation`.
- `execution::transform` was renamed to `execution::then`.
- `execution::detach` was renamed to `execution::start_detached`.
- `execution::on_sender` was renamed to `execution::schedule_on`.
- `execution::just_on` was renamed to `execution::just_transfer`.
- `execution::set_done` was renamed to `execution::set_stopped`.

Closed issues

- [Issue #5871](#)¹⁶⁸³ - distributed::channel.regisiter_as terminates the active task.
- [Issue #5856](#)¹⁶⁸⁴ - Performance counters do not compile
- [Issue #5828](#)¹⁶⁸⁵ - hpx::distributed:barrier errors
- [Issue #5812](#)¹⁶⁸⁶ - OctoTiger does not compile with HPX master and CUDA 11.5
- [Issue #5784](#)¹⁶⁸⁷ - HPX failing with co_await and hpx::when_all(futures)
- [Issue #5774](#)¹⁶⁸⁸ - CMake can't find HPXCacheVariables.cmake
- [Issue #5764](#)¹⁶⁸⁹ - Fix HIP problem
- [Issue #5724](#)¹⁶⁹⁰ - Missing binary filter compression header
- [Issue #5721](#)¹⁶⁹¹ - Cleanup after repository split
- [Issue #5701](#)¹⁶⁹² - It seems that the tcp parcelport is running, and the MPI parcelport is ignored
- [Issue #5692](#)¹⁶⁹³ - Kokkos compilation fails when using both HPX and CUDA execution spaces with gcc 9.3.0
- [Issue #5686](#)¹⁶⁹⁴ - Rename *annotate_function*
- [Issue #5668](#)¹⁶⁹⁵ - HPX does not detect the C++ 20 standard using gcc 11.2
- [Issue #5666](#)¹⁶⁹⁶ - Compilation error using boost 1.76 and gcc 11.2.1
- [Issue #5653](#)¹⁶⁹⁷ - Implement P2248 for our algorithms
- [Issue #5647](#)¹⁶⁹⁸ - [User input needed] Remove (CUDA) compute functionality?
- [Issue #5590](#)¹⁶⁹⁹ - hello_world_distributed fails on startup with HPX stable, MPICH 3.3.2, on Deep Bayou
- [Issue #5570](#)¹⁷⁰⁰ - Rename tag_dispatch to tag_invoke
- [Issue #5566](#)¹⁷⁰¹ - can't build simple example: "Cannot use the dummy implementation of future_then_dispatch"
- [Issue #5565](#)¹⁷⁰² - build failure: hpx::string_util::trim()
- [Issue #5553](#)¹⁷⁰³ - Github action to validate the cff file refs #5471
- [Issue #5504](#)¹⁷⁰⁴ - CMake does not work for HPX 1.7.0 on Piz Daint

¹⁶⁸³ <https://github.com/TheHPXProject/hpx/issues/5871>

¹⁶⁸⁴ <https://github.com/TheHPXProject/hpx/issues/5856>

¹⁶⁸⁵ <https://github.com/TheHPXProject/hpx/issues/5828>

¹⁶⁸⁶ <https://github.com/TheHPXProject/hpx/issues/5812>

¹⁶⁸⁷ <https://github.com/TheHPXProject/hpx/issues/5784>

¹⁶⁸⁸ <https://github.com/TheHPXProject/hpx/issues/5774>

¹⁶⁸⁹ <https://github.com/TheHPXProject/hpx/issues/5764>

¹⁶⁹⁰ <https://github.com/TheHPXProject/hpx/issues/5724>

¹⁶⁹¹ <https://github.com/TheHPXProject/hpx/issues/5721>

¹⁶⁹² <https://github.com/TheHPXProject/hpx/issues/5701>

¹⁶⁹³ <https://github.com/TheHPXProject/hpx/issues/5692>

¹⁶⁹⁴ <https://github.com/TheHPXProject/hpx/issues/5686>

¹⁶⁹⁵ <https://github.com/TheHPXProject/hpx/issues/5668>

¹⁶⁹⁶ <https://github.com/TheHPXProject/hpx/issues/5666>

¹⁶⁹⁷ <https://github.com/TheHPXProject/hpx/issues/5653>

¹⁶⁹⁸ <https://github.com/TheHPXProject/hpx/issues/5647>

¹⁶⁹⁹ <https://github.com/TheHPXProject/hpx/issues/5590>

¹⁷⁰⁰ <https://github.com/TheHPXProject/hpx/issues/5570>

¹⁷⁰¹ <https://github.com/TheHPXProject/hpx/issues/5566>

¹⁷⁰² <https://github.com/TheHPXProject/hpx/issues/5565>

¹⁷⁰³ <https://github.com/TheHPXProject/hpx/issues/5553>

¹⁷⁰⁴ <https://github.com/TheHPXProject/hpx/issues/5504>

- [Issue #5503](#)¹⁷⁰⁵ - Use contiguous index queue in bulk execution to reduce number of spawned tasks
- [Issue #5502](#)¹⁷⁰⁶ - C++20 `std::coroutine` cmake detection
- [Issue #5478](#)¹⁷⁰⁷ - `hpx.dll` built with `vcpkg` got functions pointing to the same location
- [Issue #5472](#)¹⁷⁰⁸ - Compilation error with `cuda/11.3`
- [Issue #5469](#)¹⁷⁰⁹ - Compiler warning about `HPX_NODISCARD` when building with APEX
- [Issue #5463](#)¹⁷¹⁰ - Address minor comments of the C++17 PR bump
- [Issue #5456](#)¹⁷¹¹ - Use `std::ranges::iter_swap` where available
- [Issue #5404](#)¹⁷¹² - Build fails with error “Cannot open include file `asio/io_context.hpp`”
- [Issue #5381](#)¹⁷¹³ - Add `starts_with` and `ends_with` algorithms
- [Issue #5344](#)¹⁷¹⁴ - Further simplify `tag_invoke` helpers
- [Issue #5269](#)¹⁷¹⁵ - Allow setting a label on executors/policies
- [Issue #5219](#)¹⁷¹⁶ - (Re-)Implement executor API on top of sender/receiver infrastructure
- [Issue #5216](#)¹⁷¹⁷ - Performance counter module not loading
- [Issue #5162](#)¹⁷¹⁸ - Require C++17 support
- [Issue #5156](#)¹⁷¹⁹ - Disentangle segmented algorithms
- [Issue #5118](#)¹⁷²⁰ - Lock held while suspending
- [Issue #5111](#)¹⁷²¹ - Tests fail to build with `binary_filter` plugins enabled
- [Issue #5110](#)¹⁷²² - Tests don’t get built
- [Issue #5105](#)¹⁷²³ - PAPI performance counters not available
- [Issue #5002](#)¹⁷²⁴ - `hpx::lcos::barrier()` results in deadlock
- [Issue #4992](#)¹⁷²⁵ - Clang-format the rest of the files
- [Issue #4987](#)¹⁷²⁶ - Use `std::function` in public APIs
- [Issue #4871](#)¹⁷²⁷ - HEP: conformance to C++20

¹⁷⁰⁵ <https://github.com/TheHPXProject/hpx/issues/5503>

¹⁷⁰⁶ <https://github.com/TheHPXProject/hpx/issues/5502>

¹⁷⁰⁷ <https://github.com/TheHPXProject/hpx/issues/5478>

¹⁷⁰⁸ <https://github.com/TheHPXProject/hpx/issues/5472>

¹⁷⁰⁹ <https://github.com/TheHPXProject/hpx/issues/5469>

¹⁷¹⁰ <https://github.com/TheHPXProject/hpx/issues/5463>

¹⁷¹¹ <https://github.com/TheHPXProject/hpx/issues/5456>

¹⁷¹² <https://github.com/TheHPXProject/hpx/issues/5404>

¹⁷¹³ <https://github.com/TheHPXProject/hpx/issues/5381>

¹⁷¹⁴ <https://github.com/TheHPXProject/hpx/issues/5344>

¹⁷¹⁵ <https://github.com/TheHPXProject/hpx/issues/5269>

¹⁷¹⁶ <https://github.com/TheHPXProject/hpx/issues/5219>

¹⁷¹⁷ <https://github.com/TheHPXProject/hpx/issues/5216>

¹⁷¹⁸ <https://github.com/TheHPXProject/hpx/issues/5162>

¹⁷¹⁹ <https://github.com/TheHPXProject/hpx/issues/5156>

¹⁷²⁰ <https://github.com/TheHPXProject/hpx/issues/5118>

¹⁷²¹ <https://github.com/TheHPXProject/hpx/issues/5111>

¹⁷²² <https://github.com/TheHPXProject/hpx/issues/5110>

¹⁷²³ <https://github.com/TheHPXProject/hpx/issues/5105>

¹⁷²⁴ <https://github.com/TheHPXProject/hpx/issues/5002>

¹⁷²⁵ <https://github.com/TheHPXProject/hpx/issues/4992>

¹⁷²⁶ <https://github.com/TheHPXProject/hpx/issues/4987>

¹⁷²⁷ <https://github.com/TheHPXProject/hpx/issues/4871>

- Issue #4822¹⁷²⁸ - Adapt parallel algorithms to C++20
- Issue #4736¹⁷²⁹ - Deprecate `hpx::flush` and `hpx::endl`
- Issue #4558¹⁷³⁰ - Prevent work-stealing from stalling
- Issue #4495¹⁷³¹ - Add anchor links to table rows in documentation
- Issue #4469¹⁷³² - New thread state: *pending_low*
- Issue #4321¹⁷³³ - After the modularization the `libfabric` `parcelport` does not compile
- Issue #4308¹⁷³⁴ - Using APEX on multinode jobs when `HPX_WITH_NETWORKING = OFF`
- Issue #3995¹⁷³⁵ - Use C++20 `std::source_location` where available, adapt ours to conform
- Issue #3861¹⁷³⁶ - Selected processor does not support ‘yield’ in ARM mode
- Issue #3706¹⁷³⁷ - Add `shift_left` and `shift_right` algorithms
- Issue #3646¹⁷³⁸ - Parallel algorithms should accept iterator/sentinel pairs
- Issue #3636¹⁷³⁹ - HPX Modularization
- Issue #3546¹⁷⁴⁰ - Modularization of HPX
- Issue #3474¹⁷⁴¹ - Modernize CMake used in HPX
- Issue #1836¹⁷⁴² - `hpx::parallel` does not have a sort implementation
- Issue #1668¹⁷⁴³ - Adapt all parallel algorithms to Ranges TS
- Issue #1141¹⁷⁴⁴ - Implement N4409 on top of HPX

Closed pull requests

- PR #5885¹⁷⁴⁵ - Testing newer ASIO version
- PR #5884¹⁷⁴⁶ - Fix miscellaneous doc sections
- PR #5882¹⁷⁴⁷ - Fixing OctoTiger incompatibility introduced recently
- PR #5881¹⁷⁴⁸ - Fixing recent patch that disables `ATOMIC_FLAG_INIT` for C++20 and up
- PR #5880¹⁷⁴⁹ - refactor: convert *counter_status* enum to enum class

¹⁷²⁸ <https://github.com/TheHPXProject/hpx/issues/4822>

¹⁷²⁹ <https://github.com/TheHPXProject/hpx/issues/4736>

¹⁷³⁰ <https://github.com/TheHPXProject/hpx/issues/4558>

¹⁷³¹ <https://github.com/TheHPXProject/hpx/issues/4495>

¹⁷³² <https://github.com/TheHPXProject/hpx/issues/4469>

¹⁷³³ <https://github.com/TheHPXProject/hpx/issues/4321>

¹⁷³⁴ <https://github.com/TheHPXProject/hpx/issues/4308>

¹⁷³⁵ <https://github.com/TheHPXProject/hpx/issues/3995>

¹⁷³⁶ <https://github.com/TheHPXProject/hpx/issues/3861>

¹⁷³⁷ <https://github.com/TheHPXProject/hpx/issues/3706>

¹⁷³⁸ <https://github.com/TheHPXProject/hpx/issues/3646>

¹⁷³⁹ <https://github.com/TheHPXProject/hpx/issues/3636>

¹⁷⁴⁰ <https://github.com/TheHPXProject/hpx/issues/3546>

¹⁷⁴¹ <https://github.com/TheHPXProject/hpx/issues/3474>

¹⁷⁴² <https://github.com/TheHPXProject/hpx/issues/1836>

¹⁷⁴³ <https://github.com/TheHPXProject/hpx/issues/1668>

¹⁷⁴⁴ <https://github.com/TheHPXProject/hpx/issues/1141>

¹⁷⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5885>

¹⁷⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5884>

¹⁷⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5882>

¹⁷⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5881>

¹⁷⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5880>

- [PR #5878](#)¹⁷⁵⁰ - Docs: Replaced non-existent `create_reducer` function with `create_communicator`
- [PR #5877](#)¹⁷⁵¹ - Doc updates hpx runtime and resources
- [PR #5876](#)¹⁷⁵² - Updates to documentation; grammar edits.
- [PR #5875](#)¹⁷⁵³ - Doc updates starting the hpx runtime
- [PR #5874](#)¹⁷⁵⁴ - Doc updates launching configuring
- [PR #5873](#)¹⁷⁵⁵ - Prevent certain generated files from being deleted on reconfigure
- [PR #5870](#)¹⁷⁵⁶ - Adding support for the PJM batch environment
- [PR #5867](#)¹⁷⁵⁷ - Update CMakeLists.txt
- [PR #5866](#)¹⁷⁵⁸ - add cmake option `HPX_WITH_PARCELPORNT_COUNTERS`
- [PR #5864](#)¹⁷⁵⁹ - `ATOMIC_INIT_FLAG` is deprecated starting C++20
- [PR #5863](#)¹⁷⁶⁰ - Adding llvm 14.0.0 with boost 1.79.0 to Jenkins
- [PR #5861](#)¹⁷⁶¹ - Let install step proceed on CircleCI even if the segmented algorithms fail
- [PR #5860](#)¹⁷⁶² - Updating APEX tag
- [PR #5859](#)¹⁷⁶³ - Splitting documentation generation steps on CircleCI
- [PR #5854](#)¹⁷⁶⁴ - Fixing left-overs from changing `counter_type` to enum class
- [PR #5853](#)¹⁷⁶⁵ - Adding HPX dependency tool (adapted from Boostdep tool)
- [PR #5852](#)¹⁷⁶⁶ - Optimize LCI parcellport
- [PR #5851](#)¹⁷⁶⁷ - Forking `dynamic_bitset` from Boost
- [PR #5850](#)¹⁷⁶⁸ - Convert `perf_counters::counter_type` enum to enum class.
- [PR #5849](#)¹⁷⁶⁹ - Update LCI parcellport to LCI v1.7.1
- [PR #5848](#)¹⁷⁷⁰ - Fedora related fixes
- [PR #5847](#)¹⁷⁷¹ - Fix API, troubleshooting & people
- [PR #5844](#)¹⁷⁷² - Attempting to fix timeouts of segmented iterator tests

¹⁷⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5878>

¹⁷⁵¹ <https://github.com/TheHPXProject/hpx/pull/5877>

¹⁷⁵² <https://github.com/TheHPXProject/hpx/pull/5876>

¹⁷⁵³ <https://github.com/TheHPXProject/hpx/pull/5875>

¹⁷⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5874>

¹⁷⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5873>

¹⁷⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5870>

¹⁷⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5867>

¹⁷⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5866>

¹⁷⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5864>

¹⁷⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5863>

¹⁷⁶¹ <https://github.com/TheHPXProject/hpx/pull/5861>

¹⁷⁶² <https://github.com/TheHPXProject/hpx/pull/5860>

¹⁷⁶³ <https://github.com/TheHPXProject/hpx/pull/5859>

¹⁷⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5854>

¹⁷⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5853>

¹⁷⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5852>

¹⁷⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5851>

¹⁷⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5850>

¹⁷⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5849>

¹⁷⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5848>

¹⁷⁷¹ <https://github.com/TheHPXProject/hpx/pull/5847>

¹⁷⁷² <https://github.com/TheHPXProject/hpx/pull/5844>

- PR #5842¹⁷⁷³ - change the default value of HPX_WITH_LCI_TAG to v1.7
- PR #5841¹⁷⁷⁴ - Move the split_future facilities into the namespace hpx
- PR #5840¹⁷⁷⁵ - wait_XXX_nothrow functions return whether one of the futures is exceptional
- PR #5839¹⁷⁷⁶ - Moving a list of synchronization primitives into namespace hpx
- PR #5837¹⁷⁷⁷ - Moving latch types to hpx and hpx::distributed namespaces
- PR #5835¹⁷⁷⁸ - Add missing compatibility layer for id_type::management_type values
- PR #5834¹⁷⁷⁹ - API docs changes
- PR #5831¹⁷⁸⁰ - Further improvement actions to rotate
- PR #5830¹⁷⁸¹ - Exposing zero-copy serialization threshold through configuration option
- PR #5829¹⁷⁸² - Attempting to fix failing barrier test
- PR #5827¹⁷⁸³ - Add back explicit template parameter to *ignore_while_checking* to compile with nvcc
- PR #5826¹⁷⁸⁴ - Reduce number of allocations while calling *async_bulk_execute*
- PR #5825¹⁷⁸⁵ - Steal from neighboring NUMA domain only
- PR #5823¹⁷⁸⁶ - Remove obsolete directories and adjust build system
- PR #5822¹⁷⁸⁷ - Clang-format remaining files
- PR #5821¹⁷⁸⁸ - Enable permissive- flag on Windows GitHub actions builders
- PR #5820¹⁷⁸⁹ - Convert throwmode enum to enum class
- PR #5819¹⁷⁹⁰ - Marking customization points for intrusive_ptr as noexcept
- PR #5818¹⁷⁹¹ - Unconditionally use C++17 attributes
- PR #5817¹⁷⁹² - Modernize naming modules
- PR #5816¹⁷⁹³ - Modernize cache module
- PR #5815¹⁷⁹⁴ - Reapply flyby changes from #5467
- PR #5814¹⁷⁹⁵ - Avoid test timeouts by reducing test sizes

¹⁷⁷³ <https://github.com/TheHPXProject/hpx/pull/5842>

¹⁷⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5841>

¹⁷⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5840>

¹⁷⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5839>

¹⁷⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5837>

¹⁷⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5835>

¹⁷⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5834>

¹⁷⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5831>

¹⁷⁸¹ <https://github.com/TheHPXProject/hpx/pull/5830>

¹⁷⁸² <https://github.com/TheHPXProject/hpx/pull/5829>

¹⁷⁸³ <https://github.com/TheHPXProject/hpx/pull/5827>

¹⁷⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5826>

¹⁷⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5825>

¹⁷⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5823>

¹⁷⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5822>

¹⁷⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5821>

¹⁷⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5820>

¹⁷⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5819>

¹⁷⁹¹ <https://github.com/TheHPXProject/hpx/pull/5818>

¹⁷⁹² <https://github.com/TheHPXProject/hpx/pull/5817>

¹⁷⁹³ <https://github.com/TheHPXProject/hpx/pull/5816>

¹⁷⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5815>

¹⁷⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5814>

- PR #5813¹⁷⁹⁶ - The CUDA problem is not fixed in V11.5 yet...
- PR #5811¹⁷⁹⁷ - Make sure reduction value is properly moved, when possible
- PR #5810¹⁷⁹⁸ - Improve error reporting during device initialization in HIP environments
- PR #5809¹⁷⁹⁹ - Converting scheduler enums into enum class
- PR #5808¹⁸⁰⁰ - Deprecate `hpx::flush` and friends
- PR #5807¹⁸⁰¹ - Use C++20 `std::source_location`, if available
- PR #5806¹⁸⁰² - Moving `promise` and `packaged_task` to new namespaces
- PR #5805¹⁸⁰³ - Attempting to fix a test failure when using the LCI `parcelpor`
- PR #5803¹⁸⁰⁴ - Attempt to fix CUDA related OctoTiger problems
- PR #5800¹⁸⁰⁵ - Add option to restrict MPI background work to subset of cores
- PR #5798¹⁸⁰⁶ - Adding MPI as a dependency to APEX
- PR #5797¹⁸⁰⁷ - Extend Sphinx role to support arbitrary text to display on a link
- PR #5796¹⁸⁰⁸ - Disable CUDA tests that cause NVCC to silently fail without error messages
- PR #5795¹⁸⁰⁹ - Avoid writing path and directories into `HPXCacheVariables.cmake`
- PR #5793¹⁸¹⁰ - Remove features that are deprecated since V1.6
- PR #5792¹⁸¹¹ - Making sure `num_cores` is properly handled by `parallel_executor`
- PR #5791¹⁸¹² - Moving `bind`, `bind_front`, `bind_back` to namespace `hpx`
- PR #5790¹⁸¹³ - Moving serializable function/`move_only_function` into namespace `hpx::distributed`
- PR #5787¹⁸¹⁴ - Remove unneeded (and commented) tests
- PR #5786¹⁸¹⁵ - Attempting to fix hangs in distributed barrier
- PR #5785¹⁸¹⁶ - add `cmake` code to detect arm64 on macOS
- PR #5783¹⁸¹⁷ - Moving `function` and `function_ref` into namespace `hpx`
- PR #5781¹⁸¹⁸ - Updating used version of Visual Studio

¹⁷⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5813>

¹⁷⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5811>

¹⁷⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5810>

¹⁷⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5809>

¹⁸⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5808>

¹⁸⁰¹ <https://github.com/TheHPXProject/hpx/pull/5807>

¹⁸⁰² <https://github.com/TheHPXProject/hpx/pull/5806>

¹⁸⁰³ <https://github.com/TheHPXProject/hpx/pull/5805>

¹⁸⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5803>

¹⁸⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5800>

¹⁸⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5798>

¹⁸⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5797>

¹⁸⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5796>

¹⁸⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5795>

¹⁸¹⁰ <https://github.com/TheHPXProject/hpx/pull/5793>

¹⁸¹¹ <https://github.com/TheHPXProject/hpx/pull/5792>

¹⁸¹² <https://github.com/TheHPXProject/hpx/pull/5791>

¹⁸¹³ <https://github.com/TheHPXProject/hpx/pull/5790>

¹⁸¹⁴ <https://github.com/TheHPXProject/hpx/pull/5787>

¹⁸¹⁵ <https://github.com/TheHPXProject/hpx/pull/5786>

¹⁸¹⁶ <https://github.com/TheHPXProject/hpx/pull/5785>

¹⁸¹⁷ <https://github.com/TheHPXProject/hpx/pull/5783>

¹⁸¹⁸ <https://github.com/TheHPXProject/hpx/pull/5781>

- PR #5780¹⁸¹⁹ - Update Piz Daint Jenkins configurations from gcc/clang 7 to 8
- PR #5778¹⁸²⁰ - Updated for_loop.hpp
- PR #5777¹⁸²¹ - Update reference for foreach benchmark
- PR #5775¹⁸²² - Move optional into namespace hpx
- PR #5773¹⁸²³ - Moving barrier to consolidated namespaces
- PR #5772¹⁸²⁴ - Adding missing docs for ranges::find_if and find_if_not algorithms
- PR #5771¹⁸²⁵ - Moving for_loop into namespace hpx::experimental
- PR #5770¹⁸²⁶ - Fixing HIP issues
- PR #5769¹⁸²⁷ - Slight improvement of small_vector performance
- PR #5766¹⁸²⁸ - Fixing a integral conversion warning
- PR #5765¹⁸²⁹ - Adding a sphinx role allowing to link to a file directly in github
- PR #5763¹⁸³⁰ - add num_cores facility
- PR #5762¹⁸³¹ - Fix Public API main page
- PR #5761¹⁸³² - Add missing inline to mpi_exception.hpp error_message function
- PR #5760¹⁸³³ - Update cdash build url
- PR #5759¹⁸³⁴ - Switch to use generic rostam SLURM partitions
- PR #5758¹⁸³⁵ - Adding support for P2300 completion signatures
- PR #5757¹⁸³⁶ - Fix missing links in Public API
- PR #5756¹⁸³⁷ - Add stop support to when_all
- PR #5755¹⁸³⁸ - Support for data-parallelism for mismatch algorithm
- PR #5754¹⁸³⁹ - Support for data-parallelism for equal algorithm
- PR #5751¹⁸⁴⁰ - Propagate MPI dependencies to command line handling
- PR #5750¹⁸⁴¹ - Make sure required MPI initialization flags are properly applied and supported

¹⁸¹⁹ <https://github.com/TheHPXProject/hpx/pull/5780>

¹⁸²⁰ <https://github.com/TheHPXProject/hpx/pull/5778>

¹⁸²¹ <https://github.com/TheHPXProject/hpx/pull/5777>

¹⁸²² <https://github.com/TheHPXProject/hpx/pull/5775>

¹⁸²³ <https://github.com/TheHPXProject/hpx/pull/5773>

¹⁸²⁴ <https://github.com/TheHPXProject/hpx/pull/5772>

¹⁸²⁵ <https://github.com/TheHPXProject/hpx/pull/5771>

¹⁸²⁶ <https://github.com/TheHPXProject/hpx/pull/5770>

¹⁸²⁷ <https://github.com/TheHPXProject/hpx/pull/5769>

¹⁸²⁸ <https://github.com/TheHPXProject/hpx/pull/5766>

¹⁸²⁹ <https://github.com/TheHPXProject/hpx/pull/5765>

¹⁸³⁰ <https://github.com/TheHPXProject/hpx/pull/5763>

¹⁸³¹ <https://github.com/TheHPXProject/hpx/pull/5762>

¹⁸³² <https://github.com/TheHPXProject/hpx/pull/5761>

¹⁸³³ <https://github.com/TheHPXProject/hpx/pull/5760>

¹⁸³⁴ <https://github.com/TheHPXProject/hpx/pull/5759>

¹⁸³⁵ <https://github.com/TheHPXProject/hpx/pull/5758>

¹⁸³⁶ <https://github.com/TheHPXProject/hpx/pull/5757>

¹⁸³⁷ <https://github.com/TheHPXProject/hpx/pull/5756>

¹⁸³⁸ <https://github.com/TheHPXProject/hpx/pull/5755>

¹⁸³⁹ <https://github.com/TheHPXProject/hpx/pull/5754>

¹⁸⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5751>

¹⁸⁴¹ <https://github.com/TheHPXProject/hpx/pull/5750>

- PR #5749¹⁸⁴² - P2300 stop token
- PR #5748¹⁸⁴³ - Adding environmental query CPOs
- PR #5747¹⁸⁴⁴ - Renaming set_done to set_stopped (as per P2300)
- PR #5745¹⁸⁴⁵ - Modernize serialization module
- PR #5743¹⁸⁴⁶ - Add check for MPICH and set the correct env to support multi-threaded
- PR #5742¹⁸⁴⁷ - Remove obsolete files related to cpuid, etc.
- PR #5741¹⁸⁴⁸ - Support for data-parallelism for adjacent find
- PR #5740¹⁸⁴⁹ - Support for data-parallelism for find algorithms
- PR #5739¹⁸⁵⁰ - Enable the option to attach a debugger on a segmentation fault (linux)
- PR #5738¹⁸⁵¹ - Fixing spell-checking errors
- PR #5737¹⁸⁵² - Attempt to fix migrate_component issue
- PR #5736¹⁸⁵³ - Set commit status from Jenkins also for special branches
- PR #5734¹⁸⁵⁴ - Revert #5586
- PR #5732¹⁸⁵⁵ - Attempt to improve build-id reporting to cdash
- PR #5731¹⁸⁵⁶ - Randomly delay execution of bash scripts launched by Jenkins
- PR #5729¹⁸⁵⁷ - Workaround for CMake/Ninja generator OOM problem
- PR #5727¹⁸⁵⁸ - Moving compression plugins to components directory
- PR #5726¹⁸⁵⁹ - Moving/consolidating parcel coalescing plugin sources
- PR #5725¹⁸⁶⁰ - Making sure headers for serialization filters are being installed
- PR #5723¹⁸⁶¹ - Moving more tests to modules
- PR #5722¹⁸⁶² - Removing superfluous semicolons
- PR #5720¹⁸⁶³ - Moving parcelports into modules
- PR #5719¹⁸⁶⁴ - Moving more files to parcelset module

¹⁸⁴² <https://github.com/TheHPXProject/hpx/pull/5749>

¹⁸⁴³ <https://github.com/TheHPXProject/hpx/pull/5748>

¹⁸⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5747>

¹⁸⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5745>

¹⁸⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5743>

¹⁸⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5742>

¹⁸⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5741>

¹⁸⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5740>

¹⁸⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5739>

¹⁸⁵¹ <https://github.com/TheHPXProject/hpx/pull/5738>

¹⁸⁵² <https://github.com/TheHPXProject/hpx/pull/5737>

¹⁸⁵³ <https://github.com/TheHPXProject/hpx/pull/5736>

¹⁸⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5734>

¹⁸⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5732>

¹⁸⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5731>

¹⁸⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5729>

¹⁸⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5727>

¹⁸⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5726>

¹⁸⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5725>

¹⁸⁶¹ <https://github.com/TheHPXProject/hpx/pull/5723>

¹⁸⁶² <https://github.com/TheHPXProject/hpx/pull/5722>

¹⁸⁶³ <https://github.com/TheHPXProject/hpx/pull/5720>

¹⁸⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5719>

- PR #5718¹⁸⁶⁵ - build: refactor sphinx config file
- PR #5717¹⁸⁶⁶ - Creating parcelset modules
- PR #5716¹⁸⁶⁷ - Avoid duplicate definition error
- PR #5715¹⁸⁶⁸ - The new LCI parcelport for HPX
- PR #5714¹⁸⁶⁹ - Refine propagation of **HPX_WITH**... options
- PR #5713¹⁸⁷⁰ - Significantly reduce CI jobs run on Piz Daint
- PR #5712¹⁸⁷¹ - Updating jenkins configuration for Rostam2.2
- PR #5711¹⁸⁷² - Refactor manual sections
- PR #5710¹⁸⁷³ - Making task_group serializable
- PR #5709¹⁸⁷⁴ - Update the MPI cmake setup
- PR #5707¹⁸⁷⁵ - Better diagnose parcel bootstrap problems
- PR #5704¹⁸⁷⁶ - Test with hwloc 2.7.0 with GCC 11
- PR #5703¹⁸⁷⁷ - Fix *counting_iterator* container tests
- PR #5702¹⁸⁷⁸ - Attempting to fix CircleCI timeouts
- PR #5699¹⁸⁷⁹ - Update CI to use Boost 1.78.0
- PR #5697¹⁸⁸⁰ - Adding fork_join_executor to foreach_benchmark
- PR #5696¹⁸⁸¹ - Modernize when_all and friends (when_any, when_some, when_each)
- PR #5693¹⁸⁸² - Fix test errors with *_GLIBCXX_DEBUG* defined
- PR #5691¹⁸⁸³ - Rename *annotate_function* to *scoped_annotation*
- PR #5690¹⁸⁸⁴ - Replace tag_dispatch with tag_invoke in minmax segmented
- PR #5688¹⁸⁸⁵ - Remove more deprecated macros
- PR #5687¹⁸⁸⁶ - Add most important CMake options
- PR #5685¹⁸⁸⁷ - Fix future API

¹⁸⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5718>

¹⁸⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5717>

¹⁸⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5716>

¹⁸⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5715>

¹⁸⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5714>

¹⁸⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5713>

¹⁸⁷¹ <https://github.com/TheHPXProject/hpx/pull/5712>

¹⁸⁷² <https://github.com/TheHPXProject/hpx/pull/5711>

¹⁸⁷³ <https://github.com/TheHPXProject/hpx/pull/5710>

¹⁸⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5709>

¹⁸⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5707>

¹⁸⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5704>

¹⁸⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5703>

¹⁸⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5702>

¹⁸⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5699>

¹⁸⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5697>

¹⁸⁸¹ <https://github.com/TheHPXProject/hpx/pull/5696>

¹⁸⁸² <https://github.com/TheHPXProject/hpx/pull/5693>

¹⁸⁸³ <https://github.com/TheHPXProject/hpx/pull/5691>

¹⁸⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5690>

¹⁸⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5688>

¹⁸⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5687>

¹⁸⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5685>

- PR #5684¹⁸⁸⁸ - Move lock registration to separate module and remove global lock registration
- PR #5683¹⁸⁸⁹ - Make `hpx::wait_all` etc. throw exceptions when waited futures hold exceptions and deprecate `hpx::lcos::wait_all[_n]` in favor of `hpx::wait_all[_n]`
- PR #5682¹⁸⁹⁰ - Fix macOS test exceptions
- PR #5681¹⁸⁹¹ - docs: add links to hpx recepies
- PR #5680¹⁸⁹² - Embed base execution policies to datapar execution policies
- PR #5679¹⁸⁹³ - Fix *fork_join_executor* with dynamic schedule
- PR #5678¹⁸⁹⁴ - Fix compilation of service executors with nvcc
- PR #5677¹⁸⁹⁵ - Remove `compute_cuda` module
- PR #5676¹⁸⁹⁶ - Don't require up-to-date approvals for bors
- PR #5675¹⁸⁹⁷ - Add default template type parameters for algorithms
- PR #5674¹⁸⁹⁸ - Allow using *any_sender* in global variables
- PR #5671¹⁸⁹⁹ - Making sure `task_group` can be reused
- PR #5670¹⁹⁰⁰ - Relax constraints on *execution::when_all*
- PR #5669¹⁹⁰¹ - Use `HPX_WITH_CXX_STANDARD` for controlling C++ version
- PR #5667¹⁹⁰² - Attempt to fix compilation issues with Boost V1.76
- PR #5664¹⁹⁰³ - Change logging errors to warnings in schedulers
- PR #5663¹⁹⁰⁴ - Use dynamic bitsets by default for CPU masks
- PR #5662¹⁹⁰⁵ - Disambiguate namespace for MSVC
- PR #5660¹⁹⁰⁶ - Replacing remaining `std::forward` and `std::move` with `HPX_FORWARD` and `HPX_MOVE`
- PR #5659¹⁹⁰⁷ - Modernize `hpx::future` and related facilities
- PR #5658¹⁹⁰⁸ - Replace `HPX_INLINE_CONSTEXPR_VARIABLE` with `inline constexpr`
- PR #5657¹⁹⁰⁹ - Remove `tagged`, `tagged_pair` and `tagged_tuple`, remove `tuple/pair` specializations
- PR #5656¹⁹¹⁰ - Rename `on_execution::schedule_from`, rename `just_on` to `just_transfer`, and add `transfer`

¹⁸⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5684>

¹⁸⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5683>

¹⁸⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5682>

¹⁸⁹¹ <https://github.com/TheHPXProject/hpx/pull/5681>

¹⁸⁹² <https://github.com/TheHPXProject/hpx/pull/5680>

¹⁸⁹³ <https://github.com/TheHPXProject/hpx/pull/5679>

¹⁸⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5678>

¹⁸⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5677>

¹⁸⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5676>

¹⁸⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5675>

¹⁸⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5674>

¹⁸⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5671>

¹⁹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5670>

¹⁹⁰¹ <https://github.com/TheHPXProject/hpx/pull/5669>

¹⁹⁰² <https://github.com/TheHPXProject/hpx/pull/5667>

¹⁹⁰³ <https://github.com/TheHPXProject/hpx/pull/5664>

¹⁹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5663>

¹⁹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5662>

¹⁹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5660>

¹⁹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5659>

¹⁹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5658>

¹⁹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5657>

¹⁹¹⁰ <https://github.com/TheHPXProject/hpx/pull/5656>

- PR #5655¹⁹¹¹ - Avoid for module lists to grow indefinitely in cmake cache
- PR #5649¹⁹¹² - build: replace usage of Python's reserved words and functions as variable names
- PR #5648¹⁹¹³ - Modernize action modules and related code
- PR #5646¹⁹¹⁴ - Fix ends_with test
- PR #5645¹⁹¹⁵ - Add matrix multiplication example
- PR #5644¹⁹¹⁶ - Rename execution::transform to execution::then and execution::detach to execution::start_detached
- PR #5643¹⁹¹⁷ - Update performance test references
- PR #5642¹⁹¹⁸ - Adapting adjacent_difference to work with proxy iterators
- PR #5641¹⁹¹⁹ - Factorize perftests scripts
- PR #5640¹⁹²⁰ - Fixed links to sources in Sphinx documentation
- PR #5639¹⁹²¹ - Fix generate datapar tests for Vc
- PR #5638¹⁹²² - Simd all any none
- PR #5637¹⁹²³ - Use bors for merging pull requests
- PR #5636¹⁹²⁴ - Fix leftover std::holds_alternative usage
- PR #5635¹⁹²⁵ - Update container image tag in GitHub actions HIP configuration
- PR #5633¹⁹²⁶ - Moving packaged_task to module futures
- PR #5632¹⁹²⁷ - Tell Asio to use std::aligned_new only if available
- PR #5631¹⁹²⁸ - Adding tag parameter to channel communicator get/set
- PR #5630¹⁹²⁹ - Add partial_sort_copy and adapt partial sort to c++ 20
- PR #5629¹⁹³⁰ - Set HPX_WITH_FETCH_ASIO to OFF as available in the docker image
- PR #5628¹⁹³¹ - Add Clang 13 CI configuration
- PR #5627¹⁹³² - Replace alternative keyword
- PR #5626¹⁹³³ - docs: add support for BibTeX references in Sphinx docs

¹⁹¹¹ <https://github.com/TheHPXProject/hpx/pull/5655>

¹⁹¹² <https://github.com/TheHPXProject/hpx/pull/5649>

¹⁹¹³ <https://github.com/TheHPXProject/hpx/pull/5648>

¹⁹¹⁴ <https://github.com/TheHPXProject/hpx/pull/5646>

¹⁹¹⁵ <https://github.com/TheHPXProject/hpx/pull/5645>

¹⁹¹⁶ <https://github.com/TheHPXProject/hpx/pull/5644>

¹⁹¹⁷ <https://github.com/TheHPXProject/hpx/pull/5643>

¹⁹¹⁸ <https://github.com/TheHPXProject/hpx/pull/5642>

¹⁹¹⁹ <https://github.com/TheHPXProject/hpx/pull/5641>

¹⁹²⁰ <https://github.com/TheHPXProject/hpx/pull/5640>

¹⁹²¹ <https://github.com/TheHPXProject/hpx/pull/5639>

¹⁹²² <https://github.com/TheHPXProject/hpx/pull/5638>

¹⁹²³ <https://github.com/TheHPXProject/hpx/pull/5637>

¹⁹²⁴ <https://github.com/TheHPXProject/hpx/pull/5636>

¹⁹²⁵ <https://github.com/TheHPXProject/hpx/pull/5635>

¹⁹²⁶ <https://github.com/TheHPXProject/hpx/pull/5633>

¹⁹²⁷ <https://github.com/TheHPXProject/hpx/pull/5632>

¹⁹²⁸ <https://github.com/TheHPXProject/hpx/pull/5631>

¹⁹²⁹ <https://github.com/TheHPXProject/hpx/pull/5630>

¹⁹³⁰ <https://github.com/TheHPXProject/hpx/pull/5629>

¹⁹³¹ <https://github.com/TheHPXProject/hpx/pull/5628>

¹⁹³² <https://github.com/TheHPXProject/hpx/pull/5627>

¹⁹³³ <https://github.com/TheHPXProject/hpx/pull/5626>

- [PR #5624](#)¹⁹³⁴ - Fix pkgconfig replacements involving CMAKE_INSTALL_PREFIX
- [PR #5623](#)¹⁹³⁵ - build: remove unused import from conf.py.in
- [PR #5622](#)¹⁹³⁶ - Remove HPX_WITH_VCPKG CMake option
- [PR #5621](#)¹⁹³⁷ - Replacing boost::container::small_vector
- [PR #5620](#)¹⁹³⁸ - Update Asio tag from 1.18.2 to 1.20.0
- [PR #5619](#)¹⁹³⁹ - Fix block_os_threads_1036 test
- [PR #5618](#)¹⁹⁴⁰ - Make sure condition variables are notified under a lock in the thread_pool_scheduler test
- [PR #5617](#)¹⁹⁴¹ - Use advance_and_get_distance where required
- [PR #5616](#)¹⁹⁴² - Remove separately building segmented algorithms on CircleCI
- [PR #5613](#)¹⁹⁴³ - Fix Vc datapar adjacent_difference
- [PR #5609](#)¹⁹⁴⁴ - docs: add anchor links to performance counter tables
- [PR #5608](#)¹⁹⁴⁵ - Fix header test error by adding missing numeric
- [PR #5607](#)¹⁹⁴⁶ - Fix simd adj diff
- [PR #5605](#)¹⁹⁴⁷ - Fix usage of HPX_INVOKE macro
- [PR #5604](#)¹⁹⁴⁸ - Make use of shell-session to allow non-copyable \$
- [PR #5603](#)¹⁹⁴⁹ - Suppress some MSVC warnings in C++20 mode
- [PR #5602](#)¹⁹⁵⁰ - Test HPX_DATASTRUCTURES_WITH_ADAPT_STD_TUPLE=OFF to one CI configuration
- [PR #5601](#)¹⁹⁵¹ - Test case for any_sender should use hpx::tuple
- [PR #5600](#)¹⁹⁵² - Rename tag_dispatch back to tag_invoke
- [PR #5599](#)¹⁹⁵³ - Change theme, fix Quickstart & Examples
- [PR #5596](#)¹⁹⁵⁴ - Use precompiled headers in tests
- [PR #5595](#)¹⁹⁵⁵ - Drop semicolons for macro calls
- [PR #5594](#)¹⁹⁵⁶ - Adapt datapar generate

¹⁹³⁴ <https://github.com/TheHPXProject/hpx/pull/5624>

¹⁹³⁵ <https://github.com/TheHPXProject/hpx/pull/5623>

¹⁹³⁶ <https://github.com/TheHPXProject/hpx/pull/5622>

¹⁹³⁷ <https://github.com/TheHPXProject/hpx/pull/5621>

¹⁹³⁸ <https://github.com/TheHPXProject/hpx/pull/5620>

¹⁹³⁹ <https://github.com/TheHPXProject/hpx/pull/5619>

¹⁹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5618>

¹⁹⁴¹ <https://github.com/TheHPXProject/hpx/pull/5617>

¹⁹⁴² <https://github.com/TheHPXProject/hpx/pull/5616>

¹⁹⁴³ <https://github.com/TheHPXProject/hpx/pull/5613>

¹⁹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5609>

¹⁹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5608>

¹⁹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5607>

¹⁹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5605>

¹⁹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5604>

¹⁹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5603>

¹⁹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5602>

¹⁹⁵¹ <https://github.com/TheHPXProject/hpx/pull/5601>

¹⁹⁵² <https://github.com/TheHPXProject/hpx/pull/5600>

¹⁹⁵³ <https://github.com/TheHPXProject/hpx/pull/5599>

¹⁹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5596>

¹⁹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5595>

¹⁹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5594>

- PR #5593¹⁹⁵⁷ - Update any_sender to use tag_dispatch for execution customizations
- PR #5592¹⁹⁵⁸ - Add nth_element
- PR #5591¹⁹⁵⁹ - Remove unnecessary checks for C++17 for tests
- PR #5589¹⁹⁶⁰ - Add HPX_FORWARD/HPX_MOVE macros
- PR #5588¹⁹⁶¹ - Fixing the output formatting for id_types
- PR #5586¹⁹⁶² - Remove local functionality
- PR #5585¹⁹⁶³ - Delete GitExternal.cmake
- PR #5584¹⁹⁶⁴ - Serialization of hpx::tuple must use hpx::get
- PR #5583¹⁹⁶⁵ - fix coroutine_traits allocate calls, add unhandled_exception() implementation.
- PR #5582¹⁹⁶⁶ - Make more examples work with local runtime
- PR #5581¹⁹⁶⁷ - Add support for several performance tests in CI
- PR #5580¹⁹⁶⁸ - Adapt simd adj diff
- PR #5579¹⁹⁶⁹ - Split absolute paths for generated pkg-config files into -L/-I parts
- PR #5577¹⁹⁷⁰ - fix unit fill test for datapar with Vc
- PR #5576¹⁹⁷¹ - Update forgotten “Full” names
- PR #5575¹⁹⁷² - Change scan partitioner implementation
- PR #5574¹⁹⁷³ - Remove a few deprecated and unused CMake options
- PR #5572¹⁹⁷⁴ - Remove more guards for the distributed runtime
- PR #5571¹⁹⁷⁵ - Add workaround for libstc++ in string_util trim
- PR #5569¹⁹⁷⁶ - Use no_unique_address in sender adaptors
- PR #5568¹⁹⁷⁷ - Change try catch block to try_catch_exception_ptr
- PR #5567¹⁹⁷⁸ - Make default_agent::yield actually yield
- PR #5564¹⁹⁷⁹ - Adjacent

¹⁹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5593>

¹⁹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5592>

¹⁹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5591>

¹⁹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5589>

¹⁹⁶¹ <https://github.com/TheHPXProject/hpx/pull/5588>

¹⁹⁶² <https://github.com/TheHPXProject/hpx/pull/5586>

¹⁹⁶³ <https://github.com/TheHPXProject/hpx/pull/5585>

¹⁹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5584>

¹⁹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5583>

¹⁹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5582>

¹⁹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5581>

¹⁹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5580>

¹⁹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5579>

¹⁹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5577>

¹⁹⁷¹ <https://github.com/TheHPXProject/hpx/pull/5576>

¹⁹⁷² <https://github.com/TheHPXProject/hpx/pull/5575>

¹⁹⁷³ <https://github.com/TheHPXProject/hpx/pull/5574>

¹⁹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5572>

¹⁹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5571>

¹⁹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5569>

¹⁹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5568>

¹⁹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5567>

¹⁹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5564>

- PR #5562¹⁹⁸⁰ - More changes to overcome build problems on Windows after recent module rearrangements
- PR #5560¹⁹⁸¹ - Update tests and examples
- PR #5559¹⁹⁸² - Fixing cmake folder names after module restructuring
- PR #5558¹⁹⁸³ - Fixing wrong module dependencies
- PR #5557¹⁹⁸⁴ - Adding an example for the new channel_communicator API
- PR #5556¹⁹⁸⁵ - Remove leftover thread pool os executor tests
- PR #5555¹⁹⁸⁶ - Add option enabling serializing raw pointers
- PR #5554¹⁹⁸⁷ - Make sure command line aliasing is properly handled
- PR #5552¹⁹⁸⁸ - Modernizing some of the async facilities
- PR #5551¹⁹⁸⁹ - Fixing for local executions of actions to properly set task names
- PR #5550¹⁹⁹⁰ - Update CUDA module in clang-cuda configuration
- PR #5549¹⁹⁹¹ - Fixing agent_ref::yield_k to actually call yield_k
- PR #5548¹⁹⁹² - Making get_action_name() noexcept
- PR #5547¹⁹⁹³ - Fixing communication set
- PR #5546¹⁹⁹⁴ - Fixing shutdown problems caused by missing ref-counting
- PR #5545¹⁹⁹⁵ - Remove wrong move in thread_pool_scheduler_bulk.hpp
- PR #5543¹⁹⁹⁶ - Extend launch policy to carry stack size and scheduling hint in addition to priority
- PR #5542¹⁹⁹⁷ - Simplify execution CPOs
- PR #5540¹⁹⁹⁸ - Adapt partition, partition_copy and stable_partition to C++ 20
- PR #5539¹⁹⁹⁹ - Adapt mismatch to support sentinels
- PR #5538²⁰⁰⁰ - Document specific sphinx version required for the documentation
- PR #5537²⁰⁰¹ - Test release and debug builds on Piz Daint
- PR #5536²⁰⁰² - This fixes referencing stale iterators during the execution of binary mismatch

¹⁹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5562>

¹⁹⁸¹ <https://github.com/TheHPXProject/hpx/pull/5560>

¹⁹⁸² <https://github.com/TheHPXProject/hpx/pull/5559>

¹⁹⁸³ <https://github.com/TheHPXProject/hpx/pull/5558>

¹⁹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5557>

¹⁹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5556>

¹⁹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5555>

¹⁹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5554>

¹⁹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5552>

¹⁹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5551>

¹⁹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5550>

¹⁹⁹¹ <https://github.com/TheHPXProject/hpx/pull/5549>

¹⁹⁹² <https://github.com/TheHPXProject/hpx/pull/5548>

¹⁹⁹³ <https://github.com/TheHPXProject/hpx/pull/5547>

¹⁹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5546>

¹⁹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5545>

¹⁹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5543>

¹⁹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5542>

¹⁹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5540>

¹⁹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5539>

²⁰⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5538>

²⁰⁰¹ <https://github.com/TheHPXProject/hpx/pull/5537>

²⁰⁰² <https://github.com/TheHPXProject/hpx/pull/5536>

- PR #5535²⁰⁰³ - Rename `simdpar` to `par_simd`
- PR #5534²⁰⁰⁴ - Fix Quick start & Manual Docs
- PR #5533²⁰⁰⁵ - Fix `annotate_function` for `std::string`
- PR #5532²⁰⁰⁶ - Update two remaining apex links from khuck to UO-OACISS
- PR #5531²⁰⁰⁷ - Use `contiguous_index_queue` in `thread_pool_scheduler`
- PR #5530²⁰⁰⁸ - Eagerly initialize a configurable number of threads on scheduler/thread queue init
- PR #5529²⁰⁰⁹ - Update benchmarks and add support for `scheduler_executor`
- PR #5528²⁰¹⁰ - Add missing properties to executors/schedulers
- PR #5527²⁰¹¹ - Set local thread/pool number in `local/static_queue_scheduler`
- PR #5526²⁰¹² - Update Rostam HIP configuration to use 4.3.0
- PR #5525²⁰¹³ - Fix Building HPX in Quick start
- PR #5524²⁰¹⁴ - Upload image on cdash
- PR #5523²⁰¹⁵ - Modernize facilities related to `hpx::sync`
- PR #5522²⁰¹⁶ - Add sender overloads for remaining algorithms
- PR #5521²⁰¹⁷ - Minor changes that improve performance
- PR #5520²⁰¹⁸ - Update reference as perftests failing regularly
- PR #5519²⁰¹⁹ - Add `transform_mpi` sender adapter
- PR #5518²⁰²⁰ - Add sender overloads to `rotate/rotate_copy`
- PR #5517²⁰²¹ - Fix coroutine integration
- PR #5515²⁰²² - Avoid deadlock in `ignore_while_locked_1485` test
- PR #5514²⁰²³ - Add split sender adapter
- PR #5512²⁰²⁴ - Update Rostam HIP configuration
- PR #5511²⁰²⁵ - Fix Asio target name for precompiled headers

²⁰⁰³ <https://github.com/TheHPXProject/hpx/pull/5535>

²⁰⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5534>

²⁰⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5533>

²⁰⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5532>

²⁰⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5531>

²⁰⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5530>

²⁰⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5529>

²⁰¹⁰ <https://github.com/TheHPXProject/hpx/pull/5528>

²⁰¹¹ <https://github.com/TheHPXProject/hpx/pull/5527>

²⁰¹² <https://github.com/TheHPXProject/hpx/pull/5526>

²⁰¹³ <https://github.com/TheHPXProject/hpx/pull/5525>

²⁰¹⁴ <https://github.com/TheHPXProject/hpx/pull/5524>

²⁰¹⁵ <https://github.com/TheHPXProject/hpx/pull/5523>

²⁰¹⁶ <https://github.com/TheHPXProject/hpx/pull/5522>

²⁰¹⁷ <https://github.com/TheHPXProject/hpx/pull/5521>

²⁰¹⁸ <https://github.com/TheHPXProject/hpx/pull/5520>

²⁰¹⁹ <https://github.com/TheHPXProject/hpx/pull/5519>

²⁰²⁰ <https://github.com/TheHPXProject/hpx/pull/5518>

²⁰²¹ <https://github.com/TheHPXProject/hpx/pull/5517>

²⁰²² <https://github.com/TheHPXProject/hpx/pull/5515>

²⁰²³ <https://github.com/TheHPXProject/hpx/pull/5514>

²⁰²⁴ <https://github.com/TheHPXProject/hpx/pull/5512>

²⁰²⁵ <https://github.com/TheHPXProject/hpx/pull/5511>

- PR #5510²⁰²⁶ - Add any_sender and unique_any_sender
- PR #5509²⁰²⁷ - Test with Boost 1.77 on gcc/clang-newest configurations
- PR #5508²⁰²⁸ - Minor release changes from 1.7.1
- PR #5507²⁰²⁹ - Add missing commits from scheduler_executor PR
- PR #5506²⁰³⁰ - Fix condition for checking if we should use our own variant
- PR #5501²⁰³¹ - Attempt to fix thread_pool_scheduler test
- PR #5493²⁰³² - Update Jenkins GitHub token to use StellarBot GitHub account
- PR #5490²⁰³³ - Fix clang-format error on master
- PR #5487²⁰³⁴ - Add get_completion_scheduler CPO and customize bulk for thread_pool_scheduler
- PR #5484²⁰³⁵ - Add missing header to jacobi_component/server/solver.hpp
- PR #5481²⁰³⁶ - Changing the APEX repository to the new location
- PR #5479²⁰³⁷ - Fix version check for CUDA noexcept/result_of bug
- PR #5477²⁰³⁸ - Require cxx17 minor comments
- PR #5476²⁰³⁹ - Fix cmake format error
- PR #5475²⁰⁴⁰ - Require CMake 3.18 as it is already a requirement for CUDA
- PR #5474²⁰⁴¹ - Make the cuda parameters of try_compile optional
- PR #5473²⁰⁴² - Update cuda arch and change cuda version
- PR #5471²⁰⁴³ - Add corrected citation.cff
- PR #5470²⁰⁴⁴ - Adapt stable_sort to C++ 20
- PR #5468²⁰⁴⁵ - Experimentation to make the perfctest report public
- PR #5466²⁰⁴⁶ - Add shift_left and shift_right algorithms
- PR #5465²⁰⁴⁷ - Adapt datapar fill
- PR #5464²⁰⁴⁸ - Moving tag_dispatch to separate module

²⁰²⁶ <https://github.com/TheHPXProject/hpx/pull/5510>

²⁰²⁷ <https://github.com/TheHPXProject/hpx/pull/5509>

²⁰²⁸ <https://github.com/TheHPXProject/hpx/pull/5508>

²⁰²⁹ <https://github.com/TheHPXProject/hpx/pull/5507>

²⁰³⁰ <https://github.com/TheHPXProject/hpx/pull/5506>

²⁰³¹ <https://github.com/TheHPXProject/hpx/pull/5501>

²⁰³² <https://github.com/TheHPXProject/hpx/pull/5493>

²⁰³³ <https://github.com/TheHPXProject/hpx/pull/5490>

²⁰³⁴ <https://github.com/TheHPXProject/hpx/pull/5487>

²⁰³⁵ <https://github.com/TheHPXProject/hpx/pull/5484>

²⁰³⁶ <https://github.com/TheHPXProject/hpx/pull/5481>

²⁰³⁷ <https://github.com/TheHPXProject/hpx/pull/5479>

²⁰³⁸ <https://github.com/TheHPXProject/hpx/pull/5477>

²⁰³⁹ <https://github.com/TheHPXProject/hpx/pull/5476>

²⁰⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5475>

²⁰⁴¹ <https://github.com/TheHPXProject/hpx/pull/5474>

²⁰⁴² <https://github.com/TheHPXProject/hpx/pull/5473>

²⁰⁴³ <https://github.com/TheHPXProject/hpx/pull/5471>

²⁰⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5470>

²⁰⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5468>

²⁰⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5466>

²⁰⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5465>

²⁰⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5464>

- PR #5461²⁰⁴⁹ - Rename HPX_WITH_CUDA_COMPUTE with HPX_WITH_COMPUTE_CUDA
- PR #5460²⁰⁵⁰ - Adapt sort to C++ 20
- PR #5459²⁰⁵¹ - Adapt rotate/rotate_copy to C++20
- PR #5458²⁰⁵² - Adapt unique and unique_copy to C++ 20
- PR #5455²⁰⁵³ - Remove and clean up fallback sender implementations
- PR #5454²⁰⁵⁴ - Make performance plot show even if similar performance
- PR #5453²⁰⁵⁵ - Post 1.7.0 version bump
- PR #5452²⁰⁵⁶ - Fix find_end parallel overload
- PR #5450²⁰⁵⁷ - Change the print-bind output to be more precise
- PR #5449²⁰⁵⁸ - Adapt swap_ranges to C++ 20
- PR #5446²⁰⁵⁹ - Use more verbose names in sender algorithms
- PR #5443²⁰⁶⁰ - Properly support ASAN with MSVC
- PR #5441²⁰⁶¹ - Adding reference counting to thread_data
- PR #5429²⁰⁶² - Scheduler executor
- PR #5428²⁰⁶³ - Adapt datapar copy
- PR #5421²⁰⁶⁴ - Update CI base image to use clang-format 11
- PR #5410²⁰⁶⁵ - Add ranges starts_with and ends_with algorithms
- PR #5383²⁰⁶⁶ - Tentatively remove runtime_registration_wrapper from cuda futures
- PR #5377²⁰⁶⁷ - Fewer Asio includes and more precompiled headers
- PR #5329²⁰⁶⁸ - Sender overloads for parallel algorithms
- PR #5313²⁰⁶⁹ - Rearrange modules between libraries
- PR #5283²⁰⁷⁰ - Require minimum C++17 and change CUDA handling
- PR #5241²⁰⁷¹ - Adapt min_element, max_element and minmax_element to C++20

²⁰⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5461>

²⁰⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5460>

²⁰⁵¹ <https://github.com/TheHPXProject/hpx/pull/5459>

²⁰⁵² <https://github.com/TheHPXProject/hpx/pull/5458>

²⁰⁵³ <https://github.com/TheHPXProject/hpx/pull/5455>

²⁰⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5454>

²⁰⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5453>

²⁰⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5452>

²⁰⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5450>

²⁰⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5449>

²⁰⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5446>

²⁰⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5443>

²⁰⁶¹ <https://github.com/TheHPXProject/hpx/pull/5441>

²⁰⁶² <https://github.com/TheHPXProject/hpx/pull/5429>

²⁰⁶³ <https://github.com/TheHPXProject/hpx/pull/5428>

²⁰⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5421>

²⁰⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5410>

²⁰⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5383>

²⁰⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5377>

²⁰⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5329>

²⁰⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5313>

²⁰⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5283>

²⁰⁷¹ <https://github.com/TheHPXProject/hpx/pull/5241>

HPX V1.7.1 (Aug 12, 2021)

This is a bugfix release with a few minor fixes.

General changes

- Added a CMake option to assume that all types are bitwise serializable by default: `HPX_SERIALIZATION_WITH_ALL_TYPES_ARE_BITWISE_SERIALIZABLE`. The default value `OFF` corresponds to the old behaviour.
- Added a version check for Asio. The minimum Asio version supported by *HPX* is 1.12.0.
- Fixed a bug affecting usage of actions, where the internals of *HPX* relied on function addresses being unique. This was fixed by relying on variable addresses being unique instead.
- Made `hpx::util::bind` more strict in checking the validity of placeholders.
- Small performance improvement to spinlocks.
- Adapted the following parallel algorithms to C++20: `inclusive_scan`, `exclusive_scan`, `transform_inclusive_scan`, `transform_exclusive_scan`.

Breaking changes

- The experimental `hpx::execution::simdpair` execution policy (introduced in 1.7.0) was renamed to `hpx::execution::par_simd` for consistency with the other parallel policies.

Closed issues

- [Issue #5494²⁰⁷²](#) - Rename *simdpair* execution policy to *par_simd*
- [Issue #5488²⁰⁷³](#) - `hpx::util::bind` doesn't bounds-check placeholders
- [Issue #5486²⁰⁷⁴](#) - Possible V1.7.1 release

Closed pull requests

- [PR #5500²⁰⁷⁵](#) - Minor bug fix in transform exclusive and inclusive scan tests
- [PR #5499²⁰⁷⁶](#) - Rename *simdpair* to *par_simd*
- [PR #5489²⁰⁷⁷](#) - Adding bound-checking for bind placeholders
- [PR #5485²⁰⁷⁸](#) - Add Asio version check
- [PR #5482²⁰⁷⁹](#) - Change extra archive data to rely on uniqueness of a variable address, not a function address
- [PR #5448²⁰⁸⁰](#) - More fixes to enable for all types to be assumed to be bitwise copyable

²⁰⁷² <https://github.com/TheHPXProject/hpx/issues/5494>

²⁰⁷³ <https://github.com/TheHPXProject/hpx/issues/5488>

²⁰⁷⁴ <https://github.com/TheHPXProject/hpx/issues/5486>

²⁰⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5500>

²⁰⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5499>

²⁰⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5489>

²⁰⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5485>

²⁰⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5482>

²⁰⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5448>

- PR #5445²⁰⁸¹ - Improve performance of Spinlocks
- PR #5444²⁰⁸² - Adapt transform_inclusive_scan to C++ 20
- PR #5440²⁰⁸³ - Adapt transform_exclusive_scan to C++ 20
- PR #5439²⁰⁸⁴ - Adapt inclusive_scan to C++ 20
- PR #5436²⁰⁸⁵ - Adapt exclusive_scan to C++20

HPX V1.7.0 (Jul 14, 2021)

This release is again focused on C++20 conformance of algorithms. Additionally, many new experimental sender-based algorithms have been added based on the latest proposals.

General changes

- The following algorithms have been adapted to be C++20 conformant:
 - `remove`,
 - `remove_if`,
 - `remove_copy`,
 - `remove_copy_if`,
 - `replace`,
 - `replace_if`,
 - `reverse`, and
 - `lexicographical_compare`.
- When the compiler and standard library support the standard execution policies `std::execution::seq`, `std::execution::par`, and `std::execution::par_unseq` they can now be used in all *HPX* parallel algorithms with equivalent behaviour to the non-task policies `hpx::execution::seq`, `hpx::execution::par`, and `hpx::execution::par_unseq`.
- Vc support has been fixed, after being broken in 1.6.0. In addition, *HPX* now experimentally supports GCC's SIMD implementation, when available. The implementation can be used through the `hpx::execution::simd` and `hpx::execution::simdp` execution policies.
- The customization points `sync_execute`, `async_execute`, `then_execute`, `post`, `bulk_sync_execute`, `bulk_async_execute`, and `bulk_then_execute` are now implemented using `tag_dispatch` (previously `tag_invoke`). Executors can still be implemented by providing the aforementioned functions as member functions of an executor.
- New functionality, enhancements, and fixes based on P0443r14 (executors proposal) and P1897 (sender-based algorithms) have been added to the `hpx::execution::experimental` namespace. These can be accessed through the `hpx/execution.hpp` and `hpx/local/execution.hpp` headers. In particular, the following sender-based algorithms have been added:
 - `detach`,

²⁰⁸¹ <https://github.com/TheHPXProject/hpx/pull/5445>

²⁰⁸² <https://github.com/TheHPXProject/hpx/pull/5444>

²⁰⁸³ <https://github.com/TheHPXProject/hpx/pull/5440>

²⁰⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5439>

²⁰⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5436>

- `ensure_started`,
- `just`,
- `just_on`,
- `let_error`,
- `let_value`,
- `on`,
- `transform`, and
- `when_all`.

Additionally, futures now implement the sender concept. `make_future` can be used to turn a sender into a future. All functionality is experimental and can change without notice.

- All `hpx::init` and `hpx::start` overloads now take `std::functions` instead of `hpx::util::function_nonser`. No changes should be required in user code to accommodate this change.
- `hpx::util::unwrapping` and other related unwrapping functionality has been moved up into the `hpx` namespace. Names in `hpx::util` are still usable with a deprecation warning. This functionality can now be accessed through the `hpx/unwrap.hpp` and `hpx/local/unwrap.hpp` headers.
- The default tag for APEX has been update from 2.3.1 to 2.4.0. In particular, this fixes a bug which could lead to hangs in distributed runs.
- The dependency on Boost.Asio has been replaced with the standalone Asio available at <https://github.com/chriskohlhoff/asio>. By default, a system-installed Asio will be used. `ASIO_ROOT` can be given as a hint to tell CMake where to find Asio. Alternatively, Asio can be fetched automatically using CMake's `fetchcontent` by setting `HPX_WITH_FETCH_ASIO=ON`. In general, dependencies on Boost have again been reduced.
- Modularization of the library has continued. In this release almost all functionality has been moved into modules. These changes do not generally affect user code. Warnings are still issued for headers that have moved.
- `hipBLAS` is now optional when compiling with `hipcc`. A warning instead of an error will be printed if `hipBLAS` is not found during configuration.
- Previously `HPX_COMPUTE_HOST_CODE` was defined in host code only if HPX was configured with CUDA or HIP. In this release `HPX_COMPUTE_HOST_CODE` is always defined in host code.
- An experimental `HPX_WITH_PRECOMPILED_HEADERS` CMake option has been added to use precompiled headers when building *HPX*. This option should not be used on Windows.
- Numerous bug fixes.

Breaking changes

- The minimum required CMake version is now 3.17.
- The minimum required Boost version is now 1.71.0.
- The customization mechanism used to implement and extend sender functionality and algorithms has been re-named from `tag_invoke` to `tag_dispatch`. All customization of sender functionality should be done by overloading `tag_dispatch`.
- The following compatibility options have been removed, along with their compatibility implementations:
 - `HPX_PROGRAM_OPTIONS_WITH_BOOST_PROGRAM_OPTIONS_COMPATIBILITY`
 - `HPX_WITH_ACTION_BASE_COMPATIBILITY`
 - `HPX_WITH_EMBEDDED_THREAD_POOLS_COMPATIBILITY`
 - `HPX_WITH_POOL_EXECUTOR_COMPATIBILITY`
 - `HPX_WITH_PROMISE_ALIAS_COMPATIBILITY`

HPX_WITH_REGISTER_THREAD_COMPATIBILITY - HPX_WITH_REGISTER_THREAD_OVERLOADS_COMPATIBILITY
 - HPX_WITH_THREAD_AWARE_TIMER_COMPATIBILITY - HPX_WITH_THREAD_EXECUTORS_COMPATIBILITY -
 HPX_WITH_THREAD_POOL_OS_EXECUTOR_COMPATIBILITY

- The HPX_WITH_THREAD_SCHEDULERS CMake option has been removed. All schedulers are now enabled when possible.
- HPX_WITH_INIT_START_OVERLOADS_COMPATIBILITY has been turned off by default.

Closed issues

- [Issue #5423²⁰⁸⁶](#) - Fix lvalue-ref qualified connect for when_all-sender
- [Issue #5412²⁰⁸⁷](#) - Link error
- [Issue #5397²⁰⁸⁸](#) - Performance regression in thread annotations
- [Issue #5395²⁰⁸⁹](#) - HPX 1.7.0-rc1 fails to build icw APEX + OTF2
- [Issue #5385²⁰⁹⁰](#) - HPX 1.7 crashes on Piz Daint > 64 nodes
- [Issue #5380²⁰⁹¹](#) - CMake should search for asio package installed on the system
- [Issue #5378²⁰⁹²](#) - HPX 1.7.0 stopped building on Fedora
- [Issue #5369²⁰⁹³](#) - HPX 1.6 and master hangs on Summit for > 64 nodes
- [Issue #5358²⁰⁹⁴](#) - HPX init fails for single-core environments
- [Issue #5345²⁰⁹⁵](#) - Rename P2220 property CPOs?
- [Issue #5333²⁰⁹⁶](#) - HPX does not compile on the new Mac OSX using the M1 chip
- [Issue #5317²⁰⁹⁷](#) - Consider making hipblas optional
- [Issue #5306²⁰⁹⁸](#) - asio fails to build with CUDA 10.0
- [Issue #5294²⁰⁹⁹](#) - `execution::on` should be based on `execution::schedule`
- [Issue #5275²¹⁰⁰](#) - HPX V1.6.0 fails on Fedora release
- [Issue #5270²¹⁰¹](#) - HPX-1.6.0 fails to build on Windows 10
- [Issue #5257²¹⁰²](#) - Allow triggering the output of OS thread affinity from configuration settings
- [Issue #5246²¹⁰³](#) - HPX fails to build on ppc64le

²⁰⁸⁶ <https://github.com/TheHPXProject/hpx/issues/5423>

²⁰⁸⁷ <https://github.com/TheHPXProject/hpx/issues/5412>

²⁰⁸⁸ <https://github.com/TheHPXProject/hpx/issues/5397>

²⁰⁸⁹ <https://github.com/TheHPXProject/hpx/issues/5395>

²⁰⁹⁰ <https://github.com/TheHPXProject/hpx/issues/5385>

²⁰⁹¹ <https://github.com/TheHPXProject/hpx/issues/5380>

²⁰⁹² <https://github.com/TheHPXProject/hpx/issues/5378>

²⁰⁹³ <https://github.com/TheHPXProject/hpx/issues/5369>

²⁰⁹⁴ <https://github.com/TheHPXProject/hpx/issues/5358>

²⁰⁹⁵ <https://github.com/TheHPXProject/hpx/issues/5345>

²⁰⁹⁶ <https://github.com/TheHPXProject/hpx/issues/5333>

²⁰⁹⁷ <https://github.com/TheHPXProject/hpx/issues/5317>

²⁰⁹⁸ <https://github.com/TheHPXProject/hpx/issues/5306>

²⁰⁹⁹ <https://github.com/TheHPXProject/hpx/issues/5294>

²¹⁰⁰ <https://github.com/TheHPXProject/hpx/issues/5275>

²¹⁰¹ <https://github.com/TheHPXProject/hpx/issues/5270>

²¹⁰² <https://github.com/TheHPXProject/hpx/issues/5257>

²¹⁰³ <https://github.com/TheHPXProject/hpx/issues/5246>

- [Issue #5232](#)²¹⁰⁴ - Annotation using `hpx::util::annotated_function` not working
- [Issue #5222](#)²¹⁰⁵ - Build and link errors with `itnotify` enabled
- [Issue #5204](#)²¹⁰⁶ - Move algorithms to `tag_fallback_dispatch`
- [Issue #5163](#)²¹⁰⁷ - Remove module-specific compatibility and deprecation options
- [Issue #5161](#)²¹⁰⁸ - Bump required CMake version to 3.17
- [Issue #5143](#)²¹⁰⁹ - Searching for HPX-Application to generate work on multiple Nodes

Closed pull requests

- [PR #5438](#)²¹¹⁰ - Delete `datapar/foreach_tests.hpp`
- [PR #5437](#)²¹¹¹ - Add back explicit `-pthread` flags when available
- [PR #5435](#)²¹¹² - This adds support for systems that assume all types are bitwise serializable by default
- [PR #5434](#)²¹¹³ - Update CUDA polling logging to be more verbose
- [PR #5433](#)²¹¹⁴ - Fix `when_all_sender` connect for references
- [PR #5432](#)²¹¹⁵ - Add deprecation warnings for v1.8
- [PR #5431](#)²¹¹⁶ - Rename the new P0443/P2300 executor to `thread_pool_scheduler`
- [PR #5430](#)²¹¹⁷ - Revert “Adding the missing defined for `HPX_HAVE_DEPRECATED_WARNINGS`”
- [PR #5427](#)²¹¹⁸ - Removing unneeded `typedef`
- [PR #5426](#)²¹¹⁹ - Adding more concept checks for sender/receiver algorithms
- [PR #5425](#)²¹²⁰ - Adding the missing defined for `HPX_HAVE_DEPRECATED_WARNINGS`
- [PR #5424](#)²¹²¹ - Disable `Vc` in final docker image created in CI
- [PR #5422](#)²¹²² - Adding `execution::experimental::bulk` algorithm
- [PR #5420](#)²¹²³ - Update logic to find threading library
- [PR #5418](#)²¹²⁴ - Reduce max size and number of files in `ccache` cache

²¹⁰⁴ <https://github.com/TheHPXProject/hpx/issues/5232>

²¹⁰⁵ <https://github.com/TheHPXProject/hpx/issues/5222>

²¹⁰⁶ <https://github.com/TheHPXProject/hpx/issues/5204>

²¹⁰⁷ <https://github.com/TheHPXProject/hpx/issues/5163>

²¹⁰⁸ <https://github.com/TheHPXProject/hpx/issues/5161>

²¹⁰⁹ <https://github.com/TheHPXProject/hpx/issues/5143>

²¹¹⁰ <https://github.com/TheHPXProject/hpx/pull/5438>

²¹¹¹ <https://github.com/TheHPXProject/hpx/pull/5437>

²¹¹² <https://github.com/TheHPXProject/hpx/pull/5435>

²¹¹³ <https://github.com/TheHPXProject/hpx/pull/5434>

²¹¹⁴ <https://github.com/TheHPXProject/hpx/pull/5433>

²¹¹⁵ <https://github.com/TheHPXProject/hpx/pull/5432>

²¹¹⁶ <https://github.com/TheHPXProject/hpx/pull/5431>

²¹¹⁷ <https://github.com/TheHPXProject/hpx/pull/5430>

²¹¹⁸ <https://github.com/TheHPXProject/hpx/pull/5427>

²¹¹⁹ <https://github.com/TheHPXProject/hpx/pull/5426>

²¹²⁰ <https://github.com/TheHPXProject/hpx/pull/5425>

²¹²¹ <https://github.com/TheHPXProject/hpx/pull/5424>

²¹²² <https://github.com/TheHPXProject/hpx/pull/5422>

²¹²³ <https://github.com/TheHPXProject/hpx/pull/5420>

²¹²⁴ <https://github.com/TheHPXProject/hpx/pull/5418>

- PR #5417²¹²⁵ - Final release notes for 1.7.0
- PR #5416²¹²⁶ - Adapt `uninitialized_value_construct` and `uninitialized_value_construct_n` to C++ 20
- PR #5415²¹²⁷ - Adapt `uninitialized_default_construct` and `uninitialized_default_construct_n` to C++ 20
- PR #5414²¹²⁸ - Improve integration of futures and senders
- PR #5413²¹²⁹ - Fixing sender/receiver code base to compile with MSVC
- PR #5407²¹³⁰ - Handle exceptions thrown during initialization of parcel handler
- PR #5406²¹³¹ - Simplify dispatching to annotation handlers
- PR #5405²¹³² - Fetch Asio automatically in perf tests CI
- PR #5403²¹³³ - Create generic executor that adds annotations to any other executor
- PR #5402²¹³⁴ - Adapt `uninitialized_fill` and `uninitialized_fill_n` to C++ 20
- PR #5401²¹³⁵ - Modernize a variety of facilities related to parallel algorithms
- PR #5400²¹³⁶ - Fix sliding semaphore test
- PR #5399²¹³⁷ - Rename leftover `tag_fallback_invoke` to `tag_fallback_dispatch`
- PR #5398²¹³⁸ - Improve logging in AGAS symbol namespace
- PR #5396²¹³⁹ - Introduce compatibility layer for collective operations
- PR #5394²¹⁴⁰ - Enable OTF2 in APEX CI configuration
- PR #5393²¹⁴¹ - Update APEX tag
- PR #5392²¹⁴² - Fixing wrong usage of `std::forward`
- PR #5391²¹⁴³ - Fix forwarding in `transform_receiver` constructor
- PR #5390²¹⁴⁴ - Make sure shared priority scheduler steals tasks on the current NUMA domain when (core) stealing is enabled
- PR #5389²¹⁴⁵ - Adapt `uninitialized_move` and `uninitialized_move_n` to C++ 20
- PR #5388²¹⁴⁶ - Fixing `gather_there` for used with lvalue reference argument

²¹²⁵ <https://github.com/TheHPXProject/hpx/pull/5417>

²¹²⁶ <https://github.com/TheHPXProject/hpx/pull/5416>

²¹²⁷ <https://github.com/TheHPXProject/hpx/pull/5415>

²¹²⁸ <https://github.com/TheHPXProject/hpx/pull/5414>

²¹²⁹ <https://github.com/TheHPXProject/hpx/pull/5413>

²¹³⁰ <https://github.com/TheHPXProject/hpx/pull/5407>

²¹³¹ <https://github.com/TheHPXProject/hpx/pull/5406>

²¹³² <https://github.com/TheHPXProject/hpx/pull/5405>

²¹³³ <https://github.com/TheHPXProject/hpx/pull/5403>

²¹³⁴ <https://github.com/TheHPXProject/hpx/pull/5402>

²¹³⁵ <https://github.com/TheHPXProject/hpx/pull/5401>

²¹³⁶ <https://github.com/TheHPXProject/hpx/pull/5400>

²¹³⁷ <https://github.com/TheHPXProject/hpx/pull/5399>

²¹³⁸ <https://github.com/TheHPXProject/hpx/pull/5398>

²¹³⁹ <https://github.com/TheHPXProject/hpx/pull/5396>

²¹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5394>

²¹⁴¹ <https://github.com/TheHPXProject/hpx/pull/5393>

²¹⁴² <https://github.com/TheHPXProject/hpx/pull/5392>

²¹⁴³ <https://github.com/TheHPXProject/hpx/pull/5391>

²¹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5390>

²¹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5389>

²¹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5388>

- PR #5387²¹⁴⁷ - Extend thread state logging and change default stealing parameters
- PR #5386²¹⁴⁸ - Attempt to fix the startup hang with nodes > 32
- PR #5384²¹⁴⁹ - Remove HPX 1.5.0 deprecations
- PR #5382²¹⁵⁰ - Prefer installed Asio before considering FetchContent
- PR #5379²¹⁵¹ - Allow using pre-downloaded (not installed) versions of Asio and/or Apex
- PR #5376²¹⁵² - Remove unnecessary explicit listing of library modules.rst files in CMakeLists.txt
- PR #5375²¹⁵³ - Slight performance improvement for `hpx::copy` and `hpx::move` et.al.
- PR #5374²¹⁵⁴ - Remove unnecessary moves from future sender implementations
- PR #5373²¹⁵⁵ - More changes to clang-cuda Jenkins configuration
- PR #5372²¹⁵⁶ - Slight improvements to `min/max/minmax_element` algorithms
- PR #5371²¹⁵⁷ - Adapt `uninitialized_copy` and `uninitialized_copy_n` to C++ 20
- PR #5370²¹⁵⁸ - Decay types in `just_sender value_types` to match stored types
- PR #5367²¹⁵⁹ - Disable `pkgconfig` by default again on macOS
- PR #5365²¹⁶⁰ - Use `ccache` for Jenkins builds on Piz Daint
- PR #5363²¹⁶¹ - Update `cuda toolkit` module name in clang-cuda Jenkins configuration
- PR #5362²¹⁶² - Adding `channel_communicator`
- PR #5361²¹⁶³ - Fix compilation with MPI enabled
- PR #5360²¹⁶⁴ - Update APEX and asio tags
- PR #5359²¹⁶⁵ - Fix check for `pu-step` in single-core case
- PR #5357²¹⁶⁶ - Making sure collective operations can be reused by preallocating communicator
- PR #5356²¹⁶⁷ - Update API documentation
- PR #5355²¹⁶⁸ - Make the `sequenced_executor processing_units_count` member function `const`
- PR #5354²¹⁶⁹ - Making sure `default_stack_size` is defined whenever declared

²¹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5387>

²¹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5386>

²¹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5384>

²¹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5382>

²¹⁵¹ <https://github.com/TheHPXProject/hpx/pull/5379>

²¹⁵² <https://github.com/TheHPXProject/hpx/pull/5376>

²¹⁵³ <https://github.com/TheHPXProject/hpx/pull/5375>

²¹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5374>

²¹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5373>

²¹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5372>

²¹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5371>

²¹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5370>

²¹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5367>

²¹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5365>

²¹⁶¹ <https://github.com/TheHPXProject/hpx/pull/5363>

²¹⁶² <https://github.com/TheHPXProject/hpx/pull/5362>

²¹⁶³ <https://github.com/TheHPXProject/hpx/pull/5361>

²¹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5360>

²¹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5359>

²¹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5357>

²¹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5356>

²¹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5355>

²¹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5354>

- PR #5353²¹⁷⁰ - Add CUDA timestamp support to HPX Hardware Clock
- PR #5352²¹⁷¹ - Adding missing includes
- PR #5351²¹⁷² - Adding `enable_logging/disable_logging` API functions
- PR #5350²¹⁷³ - Adapt `lexicographical_compare` to C++20
- PR #5349²¹⁷⁴ - Update minimum boost version needed on the docs
- PR #5348²¹⁷⁵ - Rename `tag_invoke` and related facilities to `tag_dispatch`
- PR #5347²¹⁷⁶ - Remove `make_` prefix for executor properties
- PR #5346²¹⁷⁷ - Remove and disable compatibility options for 1.7.0
- PR #5343²¹⁷⁸ - Fix `timed_executor` static cast conversion
- PR #5342²¹⁷⁹ - Refactor CUDA event polling
- PR #5341²¹⁸⁰ - Adding `make_with_annotation` and `get_annotation` properties
- PR #5339²¹⁸¹ - Making sure `hpx::util::hardware::timestamp()` is always defined
- PR #5338²¹⁸² - Fixing `timed_executor` specializations of customization points
- PR #5335²¹⁸³ - Make `partial_algorithm` work with any number of arguments
- PR #5334²¹⁸⁴ - Follow up `iter_sent` include on #5225
- PR #5332²¹⁸⁵ - Simplify `tag_invoke` and friends
- PR #5331²¹⁸⁶ - More work on cleaning up executor CPOs
- PR #5330²¹⁸⁷ - Add option to disable `pkgconfig` generation
- PR #5328²¹⁸⁸ - Adapt data parallel support using `std-simd`
- PR #5327²¹⁸⁹ - Fix missing `ifdef HPX_SMT_PAUSE`
- PR #5326²¹⁹⁰ - Adding `resize()` to `serialize_buffer` allowing to shrink its size
- PR #5324²¹⁹¹ - Add get member functions to `async_rw_mutex` proxy objects for explicitly getting the wrapped value
- PR #5323²¹⁹² - Add `keep_future` algorithm

²¹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5353>

²¹⁷¹ <https://github.com/TheHPXProject/hpx/pull/5352>

²¹⁷² <https://github.com/TheHPXProject/hpx/pull/5351>

²¹⁷³ <https://github.com/TheHPXProject/hpx/pull/5350>

²¹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5349>

²¹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5348>

²¹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5347>

²¹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5346>

²¹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5343>

²¹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5342>

²¹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5341>

²¹⁸¹ <https://github.com/TheHPXProject/hpx/pull/5339>

²¹⁸² <https://github.com/TheHPXProject/hpx/pull/5338>

²¹⁸³ <https://github.com/TheHPXProject/hpx/pull/5335>

²¹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5334>

²¹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5332>

²¹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5331>

²¹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5330>

²¹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5328>

²¹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5327>

²¹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5326>

²¹⁹¹ <https://github.com/TheHPXProject/hpx/pull/5324>

²¹⁹² <https://github.com/TheHPXProject/hpx/pull/5323>

- PR #5322²¹⁹³ - Replace executor customization point implementations with `tag_invoke`
- PR #5321²¹⁹⁴ - Separate segmented algorithms for `reduce`
- PR #5320²¹⁹⁵ - Fix `is_sender` trait and other small fixes to p0443 traits
- PR #5319²¹⁹⁶ - gcc 11.1 c++20 build fixes
- PR #5318²¹⁹⁷ - Make hipblas dependency optional as not always available
- PR #5316²¹⁹⁸ - Attempt to fix checking for `libatomic`
- PR #5315²¹⁹⁹ - Add `explicit` keyword to fixture constructor
- PR #5314²²⁰⁰ - Fix a race condition in `async_mpi` affecting limiting executor
- PR #5312²²⁰¹ - Use local runtime and local headers in local-only modules and tests
- PR #5311²²⁰² - Add GCC 11 builder to jenkins
- PR #5310²²⁰³ - Adding `hpx::execution::experimental::task_group`
- PR #5309²²⁰⁴ - Separate `datapar`
- PR #5308²²⁰⁵ - Separate segmented algorithms for `find`, `find_if`, `find_if_not`
- PR #5307²²⁰⁶ - Separate segmented algorithms for `fill` and `generate`
- PR #5304²²⁰⁷ - Fix compilation of sender CPOs with `nvcc`
- PR #5300²²⁰⁸ - Remove `PRIVATE` flag that was propagated into the `LANGUAGES`
- PR #5298²²⁰⁹ - Separate `datapar`
- PR #5297²²¹⁰ - Specify exact `cmake` and `ninja` versions when loading them in jenkins jobs
- PR #5295²²¹¹ - Update `clang-newest` configuration to use clang 12 and Boost 1.76.0
- PR #5293²²¹² - Fix Clang 11 `cuda_future` test bug
- PR #5292²²¹³ - Add `async_rw_mutex` based on senders
- PR #5291²²¹⁴ - “Fix” termination detection
- PR #5290²²¹⁵ - Fixed source file line statements in examples documentation

²¹⁹³ <https://github.com/TheHPXProject/hpx/pull/5322>

²¹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5321>

²¹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5320>

²¹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5319>

²¹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5318>

²¹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5316>

²¹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5315>

²²⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5314>

²²⁰¹ <https://github.com/TheHPXProject/hpx/pull/5312>

²²⁰² <https://github.com/TheHPXProject/hpx/pull/5311>

²²⁰³ <https://github.com/TheHPXProject/hpx/pull/5310>

²²⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5309>

²²⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5308>

²²⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5307>

²²⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5304>

²²⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5300>

²²⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5298>

²²¹⁰ <https://github.com/TheHPXProject/hpx/pull/5297>

²²¹¹ <https://github.com/TheHPXProject/hpx/pull/5295>

²²¹² <https://github.com/TheHPXProject/hpx/pull/5293>

²²¹³ <https://github.com/TheHPXProject/hpx/pull/5292>

²²¹⁴ <https://github.com/TheHPXProject/hpx/pull/5291>

²²¹⁵ <https://github.com/TheHPXProject/hpx/pull/5290>

- PR #5289²²¹⁶ - Allow splitting of futures holding `std::tuple`
- PR #5288²²¹⁷ - Move algorithms to `tag_fallback_invoke`
- PR #5287²²¹⁸ - Move algorithms to `tag_fallback_invoke`
- PR #5285²²¹⁹ - Fix clang-format failure on master
- PR #5284²²²⁰ - Replacing `util::function_nonsr` on `std::function` in `hpx_init`
- PR #5282²²²¹ - Update Boost for daint 20.11 after update
- PR #5281²²²² - Fix Segmentation fault on `foreach_datapar_zipiter`
- PR #5280²²²³ - Avoid modulo by zero in `counting_iterator` test
- PR #5279²²²⁴ - Fix more GCC 10 deprecation warnings
- PR #5277²²²⁵ - Small fixes and improvements to CUDA/MPI polling
- PR #5276²²²⁶ - Fix typo in docs
- PR #5274²²²⁷ - More P1897 algorithms
- PR #5273²²²⁸ - Retry CDash submissions on failure
- PR #5272²²²⁹ - Fix bogus deprecation warnings with GCC 10
- PR #5271²²³⁰ - Correcting target ids for `symbol_namespace::iterate`
- PR #5268²²³¹ - Adding generic `require`, `require_concept`, and `query` properties
- PR #5267²²³² - Support annotations in `hpx::transform_reduce`
- PR #5266²²³³ - Making late command line options available for local runtime
- PR #5265²²³⁴ - Leverage `no_unique_address` for `member_pack`
- PR #5264²²³⁵ - Adopt format in more places
- PR #5262²²³⁶ - Install HPX in Rostam Jenkins jobs
- PR #5261²²³⁷ - Limit Rostam Jenkins jobs to marvin partition temporarily
- PR #5260²²³⁸ - Separate segmented algorithms for `transform_reduce`

²²¹⁶ <https://github.com/TheHPXProject/hpx/pull/5289>

²²¹⁷ <https://github.com/TheHPXProject/hpx/pull/5288>

²²¹⁸ <https://github.com/TheHPXProject/hpx/pull/5287>

²²¹⁹ <https://github.com/TheHPXProject/hpx/pull/5285>

²²²⁰ <https://github.com/TheHPXProject/hpx/pull/5284>

²²²¹ <https://github.com/TheHPXProject/hpx/pull/5282>

²²²² <https://github.com/TheHPXProject/hpx/pull/5281>

²²²³ <https://github.com/TheHPXProject/hpx/pull/5280>

²²²⁴ <https://github.com/TheHPXProject/hpx/pull/5279>

²²²⁵ <https://github.com/TheHPXProject/hpx/pull/5277>

²²²⁶ <https://github.com/TheHPXProject/hpx/pull/5276>

²²²⁷ <https://github.com/TheHPXProject/hpx/pull/5274>

²²²⁸ <https://github.com/TheHPXProject/hpx/pull/5273>

²²²⁹ <https://github.com/TheHPXProject/hpx/pull/5272>

²²³⁰ <https://github.com/TheHPXProject/hpx/pull/5271>

²²³¹ <https://github.com/TheHPXProject/hpx/pull/5268>

²²³² <https://github.com/TheHPXProject/hpx/pull/5267>

²²³³ <https://github.com/TheHPXProject/hpx/pull/5266>

²²³⁴ <https://github.com/TheHPXProject/hpx/pull/5265>

²²³⁵ <https://github.com/TheHPXProject/hpx/pull/5264>

²²³⁶ <https://github.com/TheHPXProject/hpx/pull/5262>

²²³⁷ <https://github.com/TheHPXProject/hpx/pull/5261>

²²³⁸ <https://github.com/TheHPXProject/hpx/pull/5260>

- PR #5259²²³⁹ - Making sure late command line options are recognized as configuration options
- PR #5258²²⁴⁰ - Allow for HPX algorithms being invoked with std execution policies
- PR #5256²²⁴¹ - Separate segmented algorithms for transform
- PR #5255²²⁴² - Future/sender adapters
- PR #5254²²⁴³ - Fixing datapar
- PR #5253²²⁴⁴ - Add utility to format ranges
- PR #5252²²⁴⁵ - Remove uses of Boost.Bimap
- PR #5251²²⁴⁶ - Banish <iostream> from library headers
- PR #5250²²⁴⁷ - Try fixing vc circle ci
- PR #5249²²⁴⁸ - Adding missing header
- PR #5248²²⁴⁹ - Use old Piz Daint modules after upgrade
- PR #5247²²⁵⁰ - Significantly speedup simple for_each, for_loop, and transform
- PR #5245²²⁵¹ - P1897 operator| overloads
- PR #5244²²⁵² - P1897 when_all
- PR #5243²²⁵³ - Make sure HPX_DEBUG is set based on HPX's build type, not consuming project's build type
- PR #5242²²⁵⁴ - Moving last files unrelated to parcel layer to modules
- PR #5240²²⁵⁵ - change namespace for transform_loop.hpp
- PR #5238²²⁵⁶ - Make sure annotations are used in the binary transform
- PR #5237²²⁵⁷ - Add P1897 just, just_on, and on algorithms
- PR #5236²²⁵⁸ - Add an example demonstrating the use of the invoke_function_action facility
- PR #5235²²⁵⁹ - Attempting to fix datapar compilation issues
- PR #5234²²⁶⁰ - Fix small typo in --hpx:local option description
- PR #5233²²⁶¹ - Only find Boost.Iostreams if required for plugins

²²³⁹ <https://github.com/TheHPXProject/hpx/pull/5259>

²²⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5258>

²²⁴¹ <https://github.com/TheHPXProject/hpx/pull/5256>

²²⁴² <https://github.com/TheHPXProject/hpx/pull/5255>

²²⁴³ <https://github.com/TheHPXProject/hpx/pull/5254>

²²⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5253>

²²⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5252>

²²⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5251>

²²⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5250>

²²⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5249>

²²⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5248>

²²⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5247>

²²⁵¹ <https://github.com/TheHPXProject/hpx/pull/5245>

²²⁵² <https://github.com/TheHPXProject/hpx/pull/5244>

²²⁵³ <https://github.com/TheHPXProject/hpx/pull/5243>

²²⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5242>

²²⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5240>

²²⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5238>

²²⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5237>

²²⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5236>

²²⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5235>

²²⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5234>

²²⁶¹ <https://github.com/TheHPXProject/hpx/pull/5233>

- PR #5231²²⁶² - Sort printed config options
- PR #5230²²⁶³ - Fix C++20 replace algo adaptation misses
- PR #5229²²⁶⁴ - Remove leftover Boost include from `sync_wait.hpp`
- PR #5228²²⁶⁵ - Print module name only if it has custom configuration settings
- PR #5227²²⁶⁶ - Update `.codespell_whitelist`
- PR #5226²²⁶⁷ - Use new docker image in all CircleCI steps
- PR #5225²²⁶⁸ - Adapt reverse to C++20
- PR #5224²²⁶⁹ - Separate segmented algorithms for `none_of`, `any_of` and `all_of`
- PR #5223²²⁷⁰ - Fixing build system for `itnotify`
- PR #5221²²⁷¹ - Moving LCO related files to modules
- PR #5220²²⁷² - Separate segmented algorithms for `count` and `count_if`
- PR #5218²²⁷³ - Separate segmented algorithms for `adjacent_find`
- PR #5217²²⁷⁴ - Add a HIP github action
- PR #5215²²⁷⁵ - Update ROCm to 4.0.1 on Rostam
- PR #5214²²⁷⁶ - Fix clang-format error in `sender.hpp`
- PR #5213²²⁷⁷ - Removing ESSENTIAL option to the doc example
- PR #5212²²⁷⁸ - Separate segmented algorithms for `for_each_n`
- PR #5211²²⁷⁹ - Minor adapted algos fixes
- PR #5210²²⁸⁰ - Fixing `is_invocable` deprecation warnings
- PR #5209²²⁸¹ - Moving more files into modules (actions, components, `init_runtime`, etc.)
- PR #5208²²⁸² - Add examples and explanation on when `tag_fallback/priority` are useful
- PR #5207²²⁸³ - Always define `HPX_COMPUTE_HOST_CODE` for host code
- PR #5206²²⁸⁴ - Add formatting exceptions for `libhpx` to `create_module_skeleton.py`

²²⁶² <https://github.com/TheHPXProject/hpx/pull/5231>

²²⁶³ <https://github.com/TheHPXProject/hpx/pull/5230>

²²⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5229>

²²⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5228>

²²⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5227>

²²⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5226>

²²⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5225>

²²⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5224>

²²⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5223>

²²⁷¹ <https://github.com/TheHPXProject/hpx/pull/5221>

²²⁷² <https://github.com/TheHPXProject/hpx/pull/5220>

²²⁷³ <https://github.com/TheHPXProject/hpx/pull/5218>

²²⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5217>

²²⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5215>

²²⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5214>

²²⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5213>

²²⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5212>

²²⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5211>

²²⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5210>

²²⁸¹ <https://github.com/TheHPXProject/hpx/pull/5209>

²²⁸² <https://github.com/TheHPXProject/hpx/pull/5208>

²²⁸³ <https://github.com/TheHPXProject/hpx/pull/5207>

²²⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5206>

- [PR #5205](#)²²⁸⁵ - Moving all distribution policies into modules
- [PR #5203](#)²²⁸⁶ - Move copy algorithms to `tag_fallback_invoke`
- [PR #5202](#)²²⁸⁷ - Make `HPX_WITH_PSEUDO_DEPENDENCIES` a cache variable
- [PR #5201](#)²²⁸⁸ - Replaced `tag_invoke` with `tag_fallback_invoke` for `adjacent_find` algorithm
- [PR #5200](#)²²⁸⁹ - Moving files to (distributed) runtime module
- [PR #5199](#)²²⁹⁰ - Update ICC module name on Piz Daint Jenkins configuration
- [PR #5198](#)²²⁹¹ - Add doxygen documentation for `thread_schedule_hint`
- [PR #5197](#)²²⁹² - Attempt to fix compilation of context implementations with unity build enabled
- [PR #5196](#)²²⁹³ - Re-enable component tests
- [PR #5195](#)²²⁹⁴ - Moving files related to colocation logic
- [PR #5194](#)²²⁹⁵ - Another attempt at fixing the Fedora 35 problem
- [PR #5193](#)²²⁹⁶ - Components module
- [PR #5192](#)²²⁹⁷ - Adapt `replace(_if)` to C++20
- [PR #5190](#)²²⁹⁸ - Set compatibility headers by default to on
- [PR #5188](#)²²⁹⁹ - Bump Boost minimum version to 1.71.0
- [PR #5187](#)²³⁰⁰ - Force CMake to set the `-std=c++XX` flag
- [PR #5186](#)²³⁰¹ - Remove message to print `.cu` extension whenever `.cu` files are encountered
- [PR #5185](#)²³⁰² - Remove some minor unnecessary CMake options
- [PR #5184](#)²³⁰³ - Remove some leftover `HPX_WITH_*_SCHEDULER` uses
- [PR #5183](#)²³⁰⁴ - Remove dependency on `boost/iterators/iterator_categories.hpp`
- [PR #5182](#)²³⁰⁵ - Fixing Fedora 35 for Power architectures
- [PR #5181](#)²³⁰⁶ - Bump version number and tag post 1.6.0 release
- [PR #5180](#)²³⁰⁷ - Fix `htts_v2` tests linking

²²⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5205>

²²⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5203>

²²⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5202>

²²⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5201>

²²⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5200>

²²⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5199>

²²⁹¹ <https://github.com/TheHPXProject/hpx/pull/5198>

²²⁹² <https://github.com/TheHPXProject/hpx/pull/5197>

²²⁹³ <https://github.com/TheHPXProject/hpx/pull/5196>

²²⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5195>

²²⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5194>

²²⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5193>

²²⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5192>

²²⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5190>

²²⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5188>

²³⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5187>

²³⁰¹ <https://github.com/TheHPXProject/hpx/pull/5186>

²³⁰² <https://github.com/TheHPXProject/hpx/pull/5185>

²³⁰³ <https://github.com/TheHPXProject/hpx/pull/5184>

²³⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5183>

²³⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5182>

²³⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5181>

²³⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5180>

- PR #5179²³⁰⁸ - Make sure `--hpx:local` command line option is respected with networking is off but distributed runtime is on
- PR #5177²³⁰⁹ - Remove module cmake options
- PR #5176²³¹⁰ - Starting to separate segmented algorithms: `for_each`
- PR #5174²³¹¹ - Don't run segmented algorithms twice on CircleCI
- PR #5173²³¹² - Fetching APEX using cmake `FetchContent`
- PR #5172²³¹³ - Add separate local-only entry point
- PR #5171²³¹⁴ - Remove `HPX_WITH_THREAD_SCHEDULERS` CMake option
- PR #5170²³¹⁵ - Add `HPX_WITH_PRECOMPILED_HEADERS` option
- PR #5166²³¹⁶ - Moving some action tests to modules
- PR #5165²³¹⁷ - Require cmake 3.17
- PR #5164²³¹⁸ - Move `thread_pool_suspension_helper` files to small utility module
- PR #5160²³¹⁹ - Adding checks ensuring modules are not cross-referenced from other module categories
- PR #5158²³²⁰ - Replace `boost::asio` with standalone `asio`
- PR #5155²³²¹ - Allow logging when distributed runtime is off
- PR #5153²³²² - Components module
- PR #5152²³²³ - Move more files to performance counter module
- PR #5150²³²⁴ - Adapt `remove_copy(_if)` to C++20
- PR #5144²³²⁵ - AGAS module
- PR #5125²³²⁶ - Adapt `remove` and `remove_if` to C++20
- PR #5117²³²⁷ - Attempt to fix segfaults assumed to be caused by `future_data` instances going out of scope.
- PR #5099²³²⁸ - Allow mixing debug and release builds
- PR #5092²³²⁹ - Replace `spirit.qi` with `x3`
- PR #5053²³³⁰ - Add P0443r14 executor and a few P1897 algorithms

²³⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5179>

²³⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5177>

²³¹⁰ <https://github.com/TheHPXProject/hpx/pull/5176>

²³¹¹ <https://github.com/TheHPXProject/hpx/pull/5174>

²³¹² <https://github.com/TheHPXProject/hpx/pull/5173>

²³¹³ <https://github.com/TheHPXProject/hpx/pull/5172>

²³¹⁴ <https://github.com/TheHPXProject/hpx/pull/5171>

²³¹⁵ <https://github.com/TheHPXProject/hpx/pull/5170>

²³¹⁶ <https://github.com/TheHPXProject/hpx/pull/5166>

²³¹⁷ <https://github.com/TheHPXProject/hpx/pull/5165>

²³¹⁸ <https://github.com/TheHPXProject/hpx/pull/5164>

²³¹⁹ <https://github.com/TheHPXProject/hpx/pull/5160>

²³²⁰ <https://github.com/TheHPXProject/hpx/pull/5158>

²³²¹ <https://github.com/TheHPXProject/hpx/pull/5155>

²³²² <https://github.com/TheHPXProject/hpx/pull/5153>

²³²³ <https://github.com/TheHPXProject/hpx/pull/5152>

²³²⁴ <https://github.com/TheHPXProject/hpx/pull/5150>

²³²⁵ <https://github.com/TheHPXProject/hpx/pull/5144>

²³²⁶ <https://github.com/TheHPXProject/hpx/pull/5125>

²³²⁷ <https://github.com/TheHPXProject/hpx/pull/5117>

²³²⁸ <https://github.com/TheHPXProject/hpx/pull/5099>

²³²⁹ <https://github.com/TheHPXProject/hpx/pull/5092>

²³³⁰ <https://github.com/TheHPXProject/hpx/pull/5053>

- [PR #5044](#)²³³¹ - Add performance test in jenkins and reports

HPX V1.6.0 (Feb 17, 2021)

General changes

This release continues the focus on C++20 conformance with multiple new algorithms adapted to be C++20 conformant and becoming customization point objects (CPOs). We have also added experimental support for HIP, allowing previous CUDA features to now be compiled with `hipcc` and run on AMD GPUs.

- The following algorithms have been adapted to be C++20 conformant: `adjacent_find`, `includes`, `inplace_merge`, `is_heap`, `is_heap_until`, `is_partitioned`, `is_sorted`, `is_sorted_until`, `merge`, `set_difference`, `set_intersection`, `set_symmetric_difference`, `set_union`.
- Experimental HIP support can be enabled by compiling *HPX* with `hipcc`. All CUDA functionality in *HPX* can now be used with HIP. The HIP functionality is for the time being exposed through the same API as the CUDA functionality, i.e. no changes are required in user code. The CUDA, and now HIP, functionality is in the `hpx::cuda` namespace.
- We have added `partial_sort` based on Francisco Tapia's implementation.
- `hpx::init` and `hpx::start` gained new overloads taking an `hpx::init_params` struct in 1.5.0. All overloads not taking an `hpx::init_params` are now deprecated.
- We have added an experimental `fork_join_executor`. This executor can be used for OpenMP-style fork-join parallelism, where the latency of a parallel region is important for performance.
- The `parallel_executor` now uses a hierarchical spawning scheme for bulk execution, which improves data locality and performance.
- `hpx::dataflow` can now be used with executors that inject additional parameters into the call of the user-provided function.
- We have added experimental support for properties as proposed in [P2220](#)²³³². Currently the only supported property is the scheduling hint on `parallel_executor`.
- `hpx::util::annotated_function` can now be passed a dynamically generated `std::string`.
- In moving functionality to new namespaces, old names have been deprecated. A deprecation warning will be issued if you are using deprecated functionality, with instructions on how to correct or ignore the warning.
- We have removed all support for C and Fortran from our build system.
- We have further reduced the use of Boost types within *HPX* (`boost::system::error_code` and `boost::detail::spinlock`).
- We have enabled more warnings in our CI builds (unused variables and unused typedefs).

²³³¹ <https://github.com/TheHPXProject/hpx/pull/5044>

²³³² <https://wg21.link/p2220>

Breaking changes

- hpxMP support has been completely removed.
- The verbs parcelport has been removed.
- The following compatibility options have been disabled by default: `HPX_WITH_ACTION_BASE_COMPATIBILITY`, `HPX_WITH_REGISTER_THREAD_COMPATIBILITY`, `HPX_WITH_PROMISE_ALIAS_COMPATIBILITY`, `HPX_WITH_UNSCOPED_ENUM_COMPATIBILITY`, `HPX_PROGRAM_OPTIONS_WITH_BOOST_PROGRAM_OPTIONS_COMPATIBILITY`, `HPX_WITH_EMBEDDED_THREAD_POOLS_COMPATIBILITY`, `HPX_WITH_THREAD_POOL_OS_EXECUTOR_COMPATIBILITY`, `HPX_WITH_THREAD_EXECUTORS_COMPATIBILITY`, `HPX_THREAD_AWARE_TIMER_COMPATIBILITY`, `HPX_WITH_POOL_EXECUTOR_COMPATIBILITY`. Unless noted here, the above functionalities do not come with replacements. Unscoped enumerations have been replaced by scoped enumerations. Previously deprecated unscoped enumerations are disabled by `HPX_WITH_UNSCOPED_ENUM_COMPATIBILITY`. Newly deprecated unscoped enumerations have been given deprecation warnings and replaced by scoped enumerations. `hpx::promise` has been replaced with `hpx::distributed::promise`. `hpx::program_options` is a drop-in replacement for `boost::program_options`. `hpx::execution::parallel_executor` now has constructors which take a thread pool, covering the use case of `hpx::threads::executors::pool_executor`. A pool can be supplied with `hpx::resource::get_thread_pool`.

Closed issues

- Issue #5148²³³³ - `runtime_support.hpp` does not work with newer clang
- Issue #5147²³³⁴ - Wrong results with parallel reduce
- Issue #5129²³³⁵ - Missing specialization for `std::hash<hpx::thread::id>`
- Issue #5126²³³⁶ - Use `std::string` for task annotations
- Issue #5115²³³⁷ - Don't expect hwloc to always report Cores
- Issue #5113²³³⁸ - Handle threadmanager exceptions during startup
- Issue #5112²³³⁹ - libatomic problems causing unexpected fails
- Issue #5089²³⁴⁰ - Remove non-BSL files
- Issue #5088²³⁴¹ - Unwrapping problem
- Issue #5087²³⁴² - Remove hpxMP support
- Issue #5077²³⁴³ - PAPI counters are not accessible when HPX is installed
- Issue #5075²³⁴⁴ - Make the structs in all `iter_sent.hpp` lower case
- Issue #5067²³⁴⁵ - Bug `string_util/split.hpp`

²³³³ <https://github.com/TheHPXProject/hpx/issues/5148>

²³³⁴ <https://github.com/TheHPXProject/hpx/issues/5147>

²³³⁵ <https://github.com/TheHPXProject/hpx/issues/5129>

²³³⁶ <https://github.com/TheHPXProject/hpx/issues/5126>

²³³⁷ <https://github.com/TheHPXProject/hpx/issues/5115>

²³³⁸ <https://github.com/TheHPXProject/hpx/issues/5113>

²³³⁹ <https://github.com/TheHPXProject/hpx/issues/5112>

²³⁴⁰ <https://github.com/TheHPXProject/hpx/issues/5089>

²³⁴¹ <https://github.com/TheHPXProject/hpx/issues/5088>

²³⁴² <https://github.com/TheHPXProject/hpx/issues/5087>

²³⁴³ <https://github.com/TheHPXProject/hpx/issues/5077>

²³⁴⁴ <https://github.com/TheHPXProject/hpx/issues/5075>

²³⁴⁵ <https://github.com/TheHPXProject/hpx/issues/5067>

- [Issue #5049](#)²³⁴⁶ - Change back the hipcc jenkins config to the fury partition on rostam
- [Issue #5038](#)²³⁴⁷ - Not all examples link in the latest HPX master
- [Issue #5035](#)²³⁴⁸ - Build with HPX_WITH_EXAMPLES fails
- [Issue #5019](#)²³⁴⁹ - Broken help string for hpx
- [Issue #5016](#)²³⁵⁰ - `hpx::parallel::fill` fails compiling
- [Issue #5014](#)²³⁵¹ - Rename all `.cc` to `.cpp` and `.hh` to `.hpp`
- [Issue #4988](#)²³⁵² - MPI is not finalized if running with only one locality
- [Issue #4978](#)²³⁵³ - Change feature test macros to expand to zero/one
- [Issue #4949](#)²³⁵⁴ - Crash when not enabling TCP parcelport
- [Issue #4933](#)²³⁵⁵ - Improve test coverage for unused variable warnings etc.
- [Issue #4878](#)²³⁵⁶ - HPX mpi async might call `MPI_FINALIZE` before app calls it
- [Issue #4127](#)²³⁵⁷ - Local runtime entry-points

Closed pull requests

- [PR #5178](#)²³⁵⁸ - Fix parallel `remove/remove_copy/transform` namespace references in docs
- [PR #5169](#)²³⁵⁹ - Attempt to get Piz Daint jenkins setup running after maintenance
- [PR #5168](#)²³⁶⁰ - Remove include of itself
- [PR #5167](#)²³⁶¹ - Fixing deprecation warnings that slipped through the net
- [PR #5159](#)²³⁶² - Update APEX tag to 2.3.1
- [PR #5154](#)²³⁶³ - Splitting unit tests on circleci to avoid timeouts
- [PR #5151](#)²³⁶⁴ - Use C++20 on clang-newest Jenkins CI configuration
- [PR #5149](#)²³⁶⁵ - Rename 'module' symbols to avoid keyword conflict
- [PR #5145](#)²³⁶⁶ - Adjust handling of CUDA/HIP options in CMake
- [PR #5142](#)²³⁶⁷ - Store annotated_function annotations as `std::strings`

²³⁴⁶ <https://github.com/TheHPXProject/hpx/issues/5049>

²³⁴⁷ <https://github.com/TheHPXProject/hpx/issues/5038>

²³⁴⁸ <https://github.com/TheHPXProject/hpx/issues/5035>

²³⁴⁹ <https://github.com/TheHPXProject/hpx/issues/5019>

²³⁵⁰ <https://github.com/TheHPXProject/hpx/issues/5016>

²³⁵¹ <https://github.com/TheHPXProject/hpx/issues/5014>

²³⁵² <https://github.com/TheHPXProject/hpx/issues/4988>

²³⁵³ <https://github.com/TheHPXProject/hpx/issues/4978>

²³⁵⁴ <https://github.com/TheHPXProject/hpx/issues/4949>

²³⁵⁵ <https://github.com/TheHPXProject/hpx/issues/4933>

²³⁵⁶ <https://github.com/TheHPXProject/hpx/issues/4878>

²³⁵⁷ <https://github.com/TheHPXProject/hpx/issues/4127>

²³⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5178>

²³⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5169>

²³⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5168>

²³⁶¹ <https://github.com/TheHPXProject/hpx/pull/5167>

²³⁶² <https://github.com/TheHPXProject/hpx/pull/5159>

²³⁶³ <https://github.com/TheHPXProject/hpx/pull/5154>

²³⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5151>

²³⁶⁵ <https://github.com/TheHPXProject/hpx/pull/5149>

²³⁶⁶ <https://github.com/TheHPXProject/hpx/pull/5145>

²³⁶⁷ <https://github.com/TheHPXProject/hpx/pull/5142>

- PR #5140²³⁶⁸ - Scheduler mode
- PR #5139²³⁶⁹ - Fix path problem in pre-commit hook, add summary commit line
- PR #5138²³⁷⁰ - Add program options variable map to resource partitioner init
- PR #5137²³⁷¹ - Remove the use of `boost::throw_exception`
- PR #5136²³⁷² - Make sure codespell checks run on CircleCI
- PR #5132²³⁷³ - Fixing spelling errors
- PR #5131²³⁷⁴ - Mark `counting_iterator` member functions as `HPX_HOST_DEVICE`
- PR #5130²³⁷⁵ - Adding specialization for `std::hash<hpx::thread::id>`
- PR #5128²³⁷⁶ - Fixing environment handling for FreeBSD
- PR #5127²³⁷⁷ - Fix typo in fibonacci documentation
- PR #5123²³⁷⁸ - Reduce vector sizes in partial sort benchmarks when running in debug mode
- PR #5122²³⁷⁹ - Making sure exceptions during runtime initialization are correctly reported
- PR #5121²³⁸⁰ - Working around hwloc limitation on certain platforms
- PR #5120²³⁸¹ - Fixing compatibility warnings in `hpx::transform` implementation
- PR #5119²³⁸² - Use `sequential_find` and friends from separate detail header
- PR #5116²³⁸³ - Fix compilation with timer pool off
- PR #5114²³⁸⁴ - Fix 5112 - make sure `libatomic` is used when needed
- PR #5109²³⁸⁵ - Remove default runtime mode argument from `init` overload, again
- PR #5108²³⁸⁶ - Refactor `iter_sent.hpp` to make structs lowercase
- PR #5107²³⁸⁷ - Relax `dataflow` internals
- PR #5106²³⁸⁸ - Change initialization of property CPOs to satisfy older `nvcc` versions
- PR #5104²³⁸⁹ - Fix regeneration of two files that trigger unnecessary rebuilds
- PR #5103²³⁹⁰ - Remove default runtime mode argument from `start/init` overloads

²³⁶⁸ <https://github.com/TheHPXProject/hpx/pull/5140>

²³⁶⁹ <https://github.com/TheHPXProject/hpx/pull/5139>

²³⁷⁰ <https://github.com/TheHPXProject/hpx/pull/5138>

²³⁷¹ <https://github.com/TheHPXProject/hpx/pull/5137>

²³⁷² <https://github.com/TheHPXProject/hpx/pull/5136>

²³⁷³ <https://github.com/TheHPXProject/hpx/pull/5132>

²³⁷⁴ <https://github.com/TheHPXProject/hpx/pull/5131>

²³⁷⁵ <https://github.com/TheHPXProject/hpx/pull/5130>

²³⁷⁶ <https://github.com/TheHPXProject/hpx/pull/5128>

²³⁷⁷ <https://github.com/TheHPXProject/hpx/pull/5127>

²³⁷⁸ <https://github.com/TheHPXProject/hpx/pull/5123>

²³⁷⁹ <https://github.com/TheHPXProject/hpx/pull/5122>

²³⁸⁰ <https://github.com/TheHPXProject/hpx/pull/5121>

²³⁸¹ <https://github.com/TheHPXProject/hpx/pull/5120>

²³⁸² <https://github.com/TheHPXProject/hpx/pull/5119>

²³⁸³ <https://github.com/TheHPXProject/hpx/pull/5116>

²³⁸⁴ <https://github.com/TheHPXProject/hpx/pull/5114>

²³⁸⁵ <https://github.com/TheHPXProject/hpx/pull/5109>

²³⁸⁶ <https://github.com/TheHPXProject/hpx/pull/5108>

²³⁸⁷ <https://github.com/TheHPXProject/hpx/pull/5107>

²³⁸⁸ <https://github.com/TheHPXProject/hpx/pull/5106>

²³⁸⁹ <https://github.com/TheHPXProject/hpx/pull/5104>

²³⁹⁰ <https://github.com/TheHPXProject/hpx/pull/5103>

- PR #5102²³⁹¹ - Untie deprecated thread enums from the CMake option
- PR #5101²³⁹² - Update APEX tag for 1.6.0
- PR #5100²³⁹³ - Bump minimum required Boost version to 1.66 and update CI configurations
- PR #5098²³⁹⁴ - Minor fixes to public API listing
- PR #5097²³⁹⁵ - Remove hpxMP support
- PR #5096²³⁹⁶ - Remove fractals examples
- PR #5095²³⁹⁷ - Use all AMD nodes again on rostam
- PR #5094²³⁹⁸ - Attempt to remove macOS workaround for GH actions environment
- PR #5093²³⁹⁹ - Remove verbs parcelport
- PR #5091²⁴⁰⁰ - Avoid moving from lvalues
- PR #5090²⁴⁰¹ - Adopt C++20 `std::endian`
- PR #5085²⁴⁰² - Update daint CI to use Boost 1.75.0
- PR #5084²⁴⁰³ - Disable compatibility options for 1.6.0 release
- PR #5083²⁴⁰⁴ - Remove duplicated call to the `limiting_executor` in `future_overhead` test
- PR #5079²⁴⁰⁵ - Add checks to make sure that MPI/CUDA polling is enabled/not disabled too early
- PR #5078²⁴⁰⁶ - Add install lib directory to list of component search paths
- PR #5076²⁴⁰⁷ - Fix a typo in the jenkins `clang-newest` cmake config
- PR #5074²⁴⁰⁸ - Fixing warnings generated by MSVC
- PR #5073²⁴⁰⁹ - Allow using noncopyable types with unwrapping
- PR #5072²⁴¹⁰ - Fix `is_convertible` args in `result_types`
- PR #5071²⁴¹¹ - Fix unused parameters
- PR #5070²⁴¹² - Fix unused variables warnings in `hipcc`
- PR #5069²⁴¹³ - Add support for sentinels to `adjacent_find`

²³⁹¹ <https://github.com/TheHPXProject/hpx/pull/5102>

²³⁹² <https://github.com/TheHPXProject/hpx/pull/5101>

²³⁹³ <https://github.com/TheHPXProject/hpx/pull/5100>

²³⁹⁴ <https://github.com/TheHPXProject/hpx/pull/5098>

²³⁹⁵ <https://github.com/TheHPXProject/hpx/pull/5097>

²³⁹⁶ <https://github.com/TheHPXProject/hpx/pull/5096>

²³⁹⁷ <https://github.com/TheHPXProject/hpx/pull/5095>

²³⁹⁸ <https://github.com/TheHPXProject/hpx/pull/5094>

²³⁹⁹ <https://github.com/TheHPXProject/hpx/pull/5093>

²⁴⁰⁰ <https://github.com/TheHPXProject/hpx/pull/5091>

²⁴⁰¹ <https://github.com/TheHPXProject/hpx/pull/5090>

²⁴⁰² <https://github.com/TheHPXProject/hpx/pull/5085>

²⁴⁰³ <https://github.com/TheHPXProject/hpx/pull/5084>

²⁴⁰⁴ <https://github.com/TheHPXProject/hpx/pull/5083>

²⁴⁰⁵ <https://github.com/TheHPXProject/hpx/pull/5079>

²⁴⁰⁶ <https://github.com/TheHPXProject/hpx/pull/5078>

²⁴⁰⁷ <https://github.com/TheHPXProject/hpx/pull/5076>

²⁴⁰⁸ <https://github.com/TheHPXProject/hpx/pull/5074>

²⁴⁰⁹ <https://github.com/TheHPXProject/hpx/pull/5073>

²⁴¹⁰ <https://github.com/TheHPXProject/hpx/pull/5072>

²⁴¹¹ <https://github.com/TheHPXProject/hpx/pull/5071>

²⁴¹² <https://github.com/TheHPXProject/hpx/pull/5070>

²⁴¹³ <https://github.com/TheHPXProject/hpx/pull/5069>

- PR #5068²⁴¹⁴ - Fix string split function
- PR #5066²⁴¹⁵ - Adapt search to C++20 and Range TS
- PR #5065²⁴¹⁶ - Fix `hpx::range::adjacent_find` doxygen function signatures
- PR #5064²⁴¹⁷ - Refactor runtime configuration, command line handling, and resource partitioner
- PR #5063²⁴¹⁸ - Limit the device code guards to the distributed parts of the `future_overhead` bench
- PR #5061²⁴¹⁹ - Remove hipcc guards in examples and tests
- PR #5060²⁴²⁰ - Fix deprecation warnings generated by msvc
- PR #5059²⁴²¹ - Add warning about suspending/resuming the runtime in multi-locality scenarios
- PR #5057²⁴²² - Fix unused variable warnings
- PR #5056²⁴²³ - Fix `hpx::util::get`
- PR #5055²⁴²⁴ - Remove hipcc guards
- PR #5054²⁴²⁵ - Fix typo
- PR #5051²⁴²⁶ - Adapt transform to C++20
- PR #5050²⁴²⁷ - Replace old init overloads in tests and examples
- PR #5048²⁴²⁸ - Limit jenkins hipcc to the reno node
- PR #5047²⁴²⁹ - Limit cuda jenkins run to nodes with exclusively Nvidia GPUs
- PR #5046²⁴³⁰ - Convert thread and future enums to class enums
- PR #5043²⁴³¹ - Improve `hpxrun.py` for Phylanx
- PR #5042²⁴³² - Add missing header to partial sort test
- PR #5041²⁴³³ - Adding Francisco Tapia's implementation of `partial_sort`
- PR #5040²⁴³⁴ - Remove generated headers left behind from a previous configuration
- PR #5039²⁴³⁵ - Fix GCC 10 release builds
- PR #5037²⁴³⁶ - Add `is_invocable` typedefs to top-level `hpx` namespace and public API list

²⁴¹⁴ <https://github.com/TheHPXProject/hpx/pull/5068>

²⁴¹⁵ <https://github.com/TheHPXProject/hpx/pull/5066>

²⁴¹⁶ <https://github.com/TheHPXProject/hpx/pull/5065>

²⁴¹⁷ <https://github.com/TheHPXProject/hpx/pull/5064>

²⁴¹⁸ <https://github.com/TheHPXProject/hpx/pull/5063>

²⁴¹⁹ <https://github.com/TheHPXProject/hpx/pull/5061>

²⁴²⁰ <https://github.com/TheHPXProject/hpx/pull/5060>

²⁴²¹ <https://github.com/TheHPXProject/hpx/pull/5059>

²⁴²² <https://github.com/TheHPXProject/hpx/pull/5057>

²⁴²³ <https://github.com/TheHPXProject/hpx/pull/5056>

²⁴²⁴ <https://github.com/TheHPXProject/hpx/pull/5055>

²⁴²⁵ <https://github.com/TheHPXProject/hpx/pull/5054>

²⁴²⁶ <https://github.com/TheHPXProject/hpx/pull/5051>

²⁴²⁷ <https://github.com/TheHPXProject/hpx/pull/5050>

²⁴²⁸ <https://github.com/TheHPXProject/hpx/pull/5048>

²⁴²⁹ <https://github.com/TheHPXProject/hpx/pull/5047>

²⁴³⁰ <https://github.com/TheHPXProject/hpx/pull/5046>

²⁴³¹ <https://github.com/TheHPXProject/hpx/pull/5043>

²⁴³² <https://github.com/TheHPXProject/hpx/pull/5042>

²⁴³³ <https://github.com/TheHPXProject/hpx/pull/5041>

²⁴³⁴ <https://github.com/TheHPXProject/hpx/pull/5040>

²⁴³⁵ <https://github.com/TheHPXProject/hpx/pull/5039>

²⁴³⁶ <https://github.com/TheHPXProject/hpx/pull/5037>

- [PR #5036](#)²⁴³⁷ - Deprecate `hpx::util::decay` in favor of `std::decay`
- [PR #5034](#)²⁴³⁸ - Use versioned container image on CircleCI
- [PR #5033](#)²⁴³⁹ - Implement P2220 properties module
- [PR #5032](#)²⁴⁴⁰ - Do codespell comparison only on files changed from common ancestor
- [PR #5031](#)²⁴⁴¹ - Moving traits files to `actions_base`
- [PR #5030](#)²⁴⁴² - Add codespell version print in circleci
- [PR #5029](#)²⁴⁴³ - Work around problems in GitHub actions macOS builder
- [PR #5028](#)²⁴⁴⁴ - Moving move files to naming and `naming_base`
- [PR #5027](#)²⁴⁴⁵ - Lessen constraints on certain algorithm arguments
- [PR #5025](#)²⁴⁴⁶ - Adapt `is_sorted` and `is_sorted_until` to C++20
- [PR #5024](#)²⁴⁴⁷ - Moving `naming_base` to full modules
- [PR #5022](#)²⁴⁴⁸ - Remove C language from `CMakeLists.txt`
- [PR #5021](#)²⁴⁴⁹ - Warn about unused arguments given to `add_hpx_module`
- [PR #5020](#)²⁴⁵⁰ - Fixing help string
- [PR #5018](#)²⁴⁵¹ - Update CSCS jenkins configuration to clang 11
- [PR #5017](#)²⁴⁵² - Fixing broken backwards compatibility for `hpx::parallel::fill`
- [PR #5015](#)²⁴⁵³ - Detect if generated global header conflicts with explicitly listed module headers
- [PR #5012](#)²⁴⁵⁴ - Properly reset pointer tracking data in `output_archive`
- [PR #5011](#)²⁴⁵⁵ - Inspect command line tweaks
- [PR #5010](#)²⁴⁵⁶ - Creating AGAS module
- [PR #5009](#)²⁴⁵⁷ - Replace `boost::system::error_code` with `std::error_code`
- [PR #5008](#)²⁴⁵⁸ - Replace uses of `boost::detail::spinlock`
- [PR #5007](#)²⁴⁵⁹ - Bump minimal Boost version to 1.65.0

²⁴³⁷ <https://github.com/TheHPXProject/hpx/pull/5036>

²⁴³⁸ <https://github.com/TheHPXProject/hpx/pull/5034>

²⁴³⁹ <https://github.com/TheHPXProject/hpx/pull/5033>

²⁴⁴⁰ <https://github.com/TheHPXProject/hpx/pull/5032>

²⁴⁴¹ <https://github.com/TheHPXProject/hpx/pull/5031>

²⁴⁴² <https://github.com/TheHPXProject/hpx/pull/5030>

²⁴⁴³ <https://github.com/TheHPXProject/hpx/pull/5029>

²⁴⁴⁴ <https://github.com/TheHPXProject/hpx/pull/5028>

²⁴⁴⁵ <https://github.com/TheHPXProject/hpx/pull/5027>

²⁴⁴⁶ <https://github.com/TheHPXProject/hpx/pull/5025>

²⁴⁴⁷ <https://github.com/TheHPXProject/hpx/pull/5024>

²⁴⁴⁸ <https://github.com/TheHPXProject/hpx/pull/5022>

²⁴⁴⁹ <https://github.com/TheHPXProject/hpx/pull/5021>

²⁴⁵⁰ <https://github.com/TheHPXProject/hpx/pull/5020>

²⁴⁵¹ <https://github.com/TheHPXProject/hpx/pull/5018>

²⁴⁵² <https://github.com/TheHPXProject/hpx/pull/5017>

²⁴⁵³ <https://github.com/TheHPXProject/hpx/pull/5015>

²⁴⁵⁴ <https://github.com/TheHPXProject/hpx/pull/5012>

²⁴⁵⁵ <https://github.com/TheHPXProject/hpx/pull/5011>

²⁴⁵⁶ <https://github.com/TheHPXProject/hpx/pull/5010>

²⁴⁵⁷ <https://github.com/TheHPXProject/hpx/pull/5009>

²⁴⁵⁸ <https://github.com/TheHPXProject/hpx/pull/5008>

²⁴⁵⁹ <https://github.com/TheHPXProject/hpx/pull/5007>

- PR #5006²⁴⁶⁰ - Adapt `is_partitioned` to C++20
- PR #5005²⁴⁶¹ - Making sure `reduce_by_key` compiles again
- PR #5004²⁴⁶² - Fixing template specializations that make extra archive data types unique across module boundaries
- PR #5003²⁴⁶³ - Relax `dataflow` argument constraints
- PR #5001²⁴⁶⁴ - Add `<random>` inspect check
- PR #4999²⁴⁶⁵ - Attempt to fix MacOS Github action error
- PR #4997²⁴⁶⁶ - Fix unused variable and typedef warnings
- PR #4996²⁴⁶⁷ - Adapt `adjacent_find` to C++20
- PR #4995²⁴⁶⁸ - Test all schedulers in `cross_pool_injection` test except `shared_priority_queue_scheduler`
- PR #4993²⁴⁶⁹ - Fix deprecation warnings
- PR #4991²⁴⁷⁰ - Avoid unnecessarily including entire modules
- PR #4990²⁴⁷¹ - Fixing some warnings from HPX complaining about use of obsolete types
- PR #4989²⁴⁷² - add a `*destroy*` trait for `ParcelPort` plugins
- PR #4986²⁴⁷³ - Remove serialization to functional module dependency
- PR #4985²⁴⁷⁴ - Compatibility header generation
- PR #4980²⁴⁷⁵ - Add ranges overloads to `for_loop` (and variants)
- PR #4979²⁴⁷⁶ - Actually enable unity builds on Jenkins
- PR #4977²⁴⁷⁷ - Cleaning up `debug::print` functionalities
- PR #4976²⁴⁷⁸ - Remove indirection layer in `at_index_impl`
- PR #4975²⁴⁷⁹ - Remove indirection layer in `at_index_impl`
- PR #4973²⁴⁸⁰ - Avoid warnings/errors for older gcc complaining about multi-line comments
- PR #4970²⁴⁸¹ - Making set algorithms conform to C++20

²⁴⁶⁰ <https://github.com/TheHPXProject/hpx/pull/5006>

²⁴⁶¹ <https://github.com/TheHPXProject/hpx/pull/5005>

²⁴⁶² <https://github.com/TheHPXProject/hpx/pull/5004>

²⁴⁶³ <https://github.com/TheHPXProject/hpx/pull/5003>

²⁴⁶⁴ <https://github.com/TheHPXProject/hpx/pull/5001>

²⁴⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4999>

²⁴⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4997>

²⁴⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4996>

²⁴⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4995>

²⁴⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4993>

²⁴⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4991>

²⁴⁷¹ <https://github.com/TheHPXProject/hpx/pull/4990>

²⁴⁷² <https://github.com/TheHPXProject/hpx/pull/4989>

²⁴⁷³ <https://github.com/TheHPXProject/hpx/pull/4986>

²⁴⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4985>

²⁴⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4980>

²⁴⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4979>

²⁴⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4977>

²⁴⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4976>

²⁴⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4975>

²⁴⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4973>

²⁴⁸¹ <https://github.com/TheHPXProject/hpx/pull/4970>

- PR #4969²⁴⁸² - Moving `is_execution_policy` and friends into namespace `hpx`
- PR #4968²⁴⁸³ - Enable deprecation warnings for 1.6.0 and move any functionality to `hpx` namespace
- PR #4967²⁴⁸⁴ - Define deprecation macros conditionally
- PR #4966²⁴⁸⁵ - Add `clang-format` and `cmake-format` version prints
- PR #4965²⁴⁸⁶ - Making `is_heap` and `is_heap_until` conforming to C++20
- PR #4964²⁴⁸⁷ - Adding parallel `make_heap`
- PR #4962²⁴⁸⁸ - Fix external timer function pointer exports
- PR #4960²⁴⁸⁹ - Fixing folder names for module tests and examples
- PR #4959²⁴⁹⁰ - Adding communications set
- PR #4958²⁴⁹¹ - Deprecate tuple and timing functionality in `hpx::util`
- PR #4957²⁴⁹² - Fixing unity build option for `parcelpoints`
- PR #4953²⁴⁹³ - Fixing MSVC problems after recent restructurings
- PR #4952²⁴⁹⁴ - Make `parallel_executor` use `thread_pool_executor` spawning mechanism
- PR #4948²⁴⁹⁵ - Clean up old artifacts better and more aggressively on Jenkins
- PR #4947²⁴⁹⁶ - Add HIP support for AMD GPUs
- PR #4945²⁴⁹⁷ - Enable `HPX_WITH_UNITY_BUILD` option on one of the Jenkins configurations
- PR #4943²⁴⁹⁸ - Move public `hpx::parallel::execution` functionality to `hpx::execution`
- PR #4938²⁴⁹⁹ - Post release cleanup
- PR #4858²⁵⁰⁰ - Extending resilience APIs to support distributed invocations
- PR #4744²⁵⁰¹ - Fork-join executor
- PR #4665²⁵⁰² - Implementing sender, receiver, and `operation_state` concepts in terms of P0443r13
- PR #4649²⁵⁰³ - Split `libhpx` into multiple libraries
- PR #4642²⁵⁰⁴ - Implementing `operation_state` concept in terms of P0443r13

²⁴⁸² <https://github.com/TheHPXProject/hpx/pull/4969>

²⁴⁸³ <https://github.com/TheHPXProject/hpx/pull/4968>

²⁴⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4967>

²⁴⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4966>

²⁴⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4965>

²⁴⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4964>

²⁴⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4962>

²⁴⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4960>

²⁴⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4959>

²⁴⁹¹ <https://github.com/TheHPXProject/hpx/pull/4958>

²⁴⁹² <https://github.com/TheHPXProject/hpx/pull/4957>

²⁴⁹³ <https://github.com/TheHPXProject/hpx/pull/4953>

²⁴⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4952>

²⁴⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4948>

²⁴⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4947>

²⁴⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4945>

²⁴⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4943>

²⁴⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4938>

²⁵⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4858>

²⁵⁰¹ <https://github.com/TheHPXProject/hpx/pull/4744>

²⁵⁰² <https://github.com/TheHPXProject/hpx/pull/4665>

²⁵⁰³ <https://github.com/TheHPXProject/hpx/pull/4649>

²⁵⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4642>

- [PR #4640²⁵⁰⁵](#) - Implementing receiver concept in terms of P0443r13
- [PR #4622²⁵⁰⁶](#) - Sanitizer fixes

HPX V1.5.1 (Sep 30, 2020)

General changes

This is a patch release. It contains the following changes:

- Remove restriction on suspending runtime with multiple localities, users are now responsible for synchronizing work between localities before suspending.
- Fixes several compilation problems and warnings.
- Adds notes in the documentation explaining how to cite HPX.

Closed issues

- [Issue #4971²⁵⁰⁷](#) - Parallel sort fails to compile with C++20
- [Issue #4950²⁵⁰⁸](#) - Build with `HPX_WITH_PARCELPORT_ACTION_COUNTERS_ON` fails
- [Issue #4940²⁵⁰⁹](#) - Codespell report for “HPX” (on fossies.org)
- [Issue #4937²⁵¹⁰](#) - Allow suspension of runtime for multiple localities

Closed pull requests

- [PR #4982²⁵¹¹](#) - Add page about citing HPX to documentation
- [PR #4981²⁵¹²](#) - Adding the missing include
- [PR #4974²⁵¹³](#) - Remove leftover format export hack
- [PR #4972²⁵¹⁴](#) - Removing use of `get_temporary_buffer` and `return_temporary_buffer`
- [PR #4963²⁵¹⁵](#) - Renaming files to avoid warnings from the vs build system
- [PR #4951²⁵¹⁶](#) - Fixing build if `HPX_WITH_PARCELPORT_ACTION_COUNTERS=On`
- [PR #4946²⁵¹⁷](#) - Allow suspension on multiple localities
- [PR #4944²⁵¹⁸](#) - Fix typos reported by fossies codespell report
- [PR #4941²⁵¹⁹](#) - Adding some explanation to README about how to cite HPX

²⁵⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4640>

²⁵⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4622>

²⁵⁰⁷ <https://github.com/TheHPXProject/hpx/issues/4971>

²⁵⁰⁸ <https://github.com/TheHPXProject/hpx/issues/4950>

²⁵⁰⁹ <https://github.com/TheHPXProject/hpx/issues/4940>

²⁵¹⁰ <https://github.com/TheHPXProject/hpx/issues/4937>

²⁵¹¹ <https://github.com/TheHPXProject/hpx/pull/4982>

²⁵¹² <https://github.com/TheHPXProject/hpx/pull/4981>

²⁵¹³ <https://github.com/TheHPXProject/hpx/pull/4974>

²⁵¹⁴ <https://github.com/TheHPXProject/hpx/pull/4972>

²⁵¹⁵ <https://github.com/TheHPXProject/hpx/pull/4963>

²⁵¹⁶ <https://github.com/TheHPXProject/hpx/pull/4951>

²⁵¹⁷ <https://github.com/TheHPXProject/hpx/pull/4946>

²⁵¹⁸ <https://github.com/TheHPXProject/hpx/pull/4944>

²⁵¹⁹ <https://github.com/TheHPXProject/hpx/pull/4941>

- [PR #4939](#)²⁵²⁰ - Small changes

HPX V1.5.0 (Sep 02, 2020)

General changes

The main focus of this release is on APIs and C++20 conformance. We have added many new C++20 features and adapted multiple algorithms to be fully C++20 conformant. As part of the modularization we have begun specifying the public API of *HPX* in terms of headers and functionality, and aligning it more closely to the C++ standard. All non-distributed modules are now in place, along with an experimental option to completely disable distributed features in *HPX*. We have also added experimental asynchronous MPI and CUDA executors. Lastly this release introduces CMake targets for depending projects, performance improvements, and many bug fixes.

- We have added the C++20 features `hpx::jthread` and `hpx::stop_token`. `hpx::condition_variable_any` now exposes new functions supporting `hpx::stop_token`.
- We have added `hpx::stable_sort` based on Francisco Tapia's implementation.
- We have adapted existing synchronization primitives to be fully conformant C++20: `hpx::barrier`, `hpx::latch`, `hpx::counting_semaphore`, and `hpx::binary_semaphore`.
- We have started using customization point objects (CPOs) to make the corresponding algorithms fully conformant to C++20 as well as to make algorithm extension easier for the user. `all_of/any_of/none_of`, `copy`, `count`, `destroy`, `equal`, `fill`, `find`, `for_each`, `generate`, `mismatch`, `move`, `reduce`, `transform_reduce` are using those CPOs (all in namespace `hpx`). We also have adapted their corresponding `hpx::ranges` versions to be conforming to C++20 in this release.
- We have adapted support for `co_await` to C++20, in addition to `hpx::future` it now also supports `hpx::shared_future`. We have also added allocator support for futures returned by `co_return`. It is no longer in the `experimental` namespace.
- We added serialization support for `std::variant` and `std::tuple`.
- `result_of` and `is_callable` are now deprecated and replaced by `invoke_result` and `is_invocable` to conform to C++20.
- We continued with the modularization, making it easier for us to add the new experimental `HPX_WITH_DISTRIBUTED_RUNTIME` CMake option (see below) . A significant amount of headers have been deprecated. We adapted the namespaces and headers we could to be closer to the standard ones (*Public API*). Depending code should still compile, however warnings are now generated instructing to change the include statements accordingly.
- It is now possible to have a basic CUDA support including a helper function to get a future from a CUDA stream and target handling. They are available under the `hpx::cuda::experimental` namespace and they can be enabled with the `-DHPX_WITH_ASYNC_CUDA=ON` CMake option.
- We added a new `hpx::mpi::experimental` namespace for getting futures from an asynchronous MPI call and a new minimal MPI executor `hpx::mpi::experimental::executor`. These can be enabled with the `-DHPX_WITH_ASYNC_MPI=On` CMake option.
- A polymorphic executor has been implemented to reduce compile times as a function accepting executors can potentially be instantiated only once instead of multiple times with different executors. It accepts the function signature as a template argument. It needs to be constructed from any other executor. Please note, that the function signatures that can be scheduled using `then_execute`, `bulk_sync_execute`, `bulk_async_execute` and `bulk_then_execute` are slightly different (See the comment in [PR #4514](#)²⁵²¹ for more details).
- The underlying executor of `block_executor` has been updated to a newer one.

²⁵²⁰ <https://github.com/TheHPXProject/hpx/pull/4939>

²⁵²¹ <https://github.com/TheHPXProject/hpx/pull/4514>

- We have added a parameter to `auto_chunk_size` to control the amount of iterations to measure.
- All executor parameter hooks can now be exposed through the executor itself. This will allow to deprecate the `.with()` functionality on execution policies in the future. This is also a first step towards simplifying our executor APIs in preparation for the upcoming C++23 executors (senders/receivers).
- We have moved all of the existing APIs related to resiliency into the namespace `hpx::resiliency::experimental`. Please note this is a breaking change without backwards-compatibility option. We have converted all of those APIs to be based on customization point objects. Two new executors have been added to enable easy integration of the existing resiliency features with other facilities (like the parallel algorithms): `replay_executor` and `replicate_executor`.
- We have added performance counters type information (aggregating, monotonically increasing, average count, average timer, etc.).
- HPX threads are now re-scheduled on the same worker thread they were suspended on to avoid cache misses from moving from one thread to the other. This behavior doesn't prevent the thread from being stolen, however.
- We have added a new configuration option `hpx.exception_verbosity` to allow to control the level of verbosity of the exceptions (3 levels available).
- `broadcast_to`, `broadcast_from`, `scatter_to` and `scatter_from` have been added to the collectives, modernization of `gather_here` and `gather_there` with futures taken by rvalue references. See the breaking change on `all_to_all` in the next section. None of the collectives need supporting macros anymore (e.g. specifying the data types used for a collective operation using `HPX_REGISTER_ALLGATHER` and similar is not needed anymore).
- New API functions have been added: a) to get the number of cores which are idle (`hpx::get_idle_core_count`) and b) returning a bitmask representing the currently idle cores (`hpx::get_idle_core_mask`).
- We have added an experimental option to only enable the local runtime, you can disable the distributed runtime with `HPX_WITH_DISTRIBUTED_RUNTIME=OFF`. You can also enable the local runtime by using the `--hpx:local` runtime option.
- We fixed task annotations for actions.
- The alias `hpx::promise` to `hpx::lcos::promise` is now deprecated. You can use `hpx::lcos::promise` directly instead. `hpx::promise` will refer to the local-only promise in the future.
- We have added a `prepare_checkpoint` API function that calculates the amount of necessary buffer space for a particular set of arguments checkpointed.
- We have added `hpx::upgrade_lock` and `hpx::upgrade_to_unique_lock`, which make `hpx::shared_mutex` (and similar) usable in more flexible ways.
- We have changed the CMake targets exposed to the user, it now includes `HPX:hpx`, `HPX:wrap_main` (int main as the first HPX thread of the application, see *Starting the HPX runtime*), `HPX:plugin`, `HPX:component`. The CMake variables `HPX_INCLUDE_DIRS` and `HPX_LIBRARIES` are deprecated and will be removed in a future release, you should now link directly to the `HPX:hpx` CMake target.
- A new example is demonstrating how to create and use a wrapping executor (`quickstart/executor_with_thread_hooks.cpp`)
- A new example is demonstrating how to disable thread stealing during the execution of parallel algorithms (`quickstart/disable_thread_stealing_executor.cpp`)
- We now require for our CMake build system configuration files to be formatted using `cmake-format`.
- We have removed more dependencies on various Boost libraries.
- We have added an experimental option enabling unity builds of HPX using the `-DHPX_WITH_UNITY_BUILD=On` CMake option.

- Many bug fixes.

Breaking changes

- *HPX* now requires a C++14 capable compiler. We have set the *HPX* C++ standard automatically to C++14 and if it needs to be set explicitly, it should be specified through the `CMAKE_CXX_STANDARD` setting as mandated by CMake. The `HPX_WITH_CXX*` variables are now deprecated and will be removed in the future.
- Building and using *HPX* is now supported only when using CMake V3.13 or later, Boost V1.64 or newer, and when compiling with clang V5, gcc V7, or VS2019, or later. Other compilers might still work but have not been tested thoroughly.
- We have added a `hpx::init_params` struct to pass parameters for *HPX* initialization e.g. the resource partitioner callback to initialize thread pools (*Using the resource partitioner*).
- The `all_to_all` algorithm is renamed to `all_gather`, and the new `all_to_all` algorithm is not compatible with the old one.
- We have moved all of the existing APIs related to resiliency into the namespace `hpx::resiliency::experimental`.

Closed issues

- [Issue #4918](#)²⁵²² - Rename `distributed_executors` module
- [Issue #4900](#)²⁵²³ - Adding JOSS status badge to README
- [Issue #4897](#)²⁵²⁴ - Compiler warning, deprecated header used by *HPX* itself
- [Issue #4886](#)²⁵²⁵ - A future bound to an action executing on a different locality doesn't capture exception state
- [Issue #4880](#)²⁵²⁶ - Undefined reference to main build error when `HPX_WITH_DYNAMIC_HP_X_MAIN=OFF`
- [Issue #4877](#)²⁵²⁷ - `hpx_main` might not able to start *hpx* runtime properly
- [Issue #4850](#)²⁵²⁸ - Issues creating templated component
- [Issue #4829](#)²⁵²⁹ - Spack package & `HPX_WITH_GENERIC_CONTEXT_COROUTINES`
- [Issue #4820](#)²⁵³⁰ - PAPI counters don't work
- [Issue #4818](#)²⁵³¹ - *HPX* can't be used with IO pool turned off
- [Issue #4816](#)²⁵³² - Build of *HPX* fails when `find_package(Boost)` is called before `FetchContent_MakeAvailable(hpx)`
- [Issue #4813](#)²⁵³³ - *HPX* MPI Future failed
- [Issue #4811](#)²⁵³⁴ - Remove `HPX::hpx_no_wrap_main` target before 1.5.0 release

²⁵²² <https://github.com/TheHPXProject/hpx/issues/4918>

²⁵²³ <https://github.com/TheHPXProject/hpx/issues/4900>

²⁵²⁴ <https://github.com/TheHPXProject/hpx/issues/4897>

²⁵²⁵ <https://github.com/TheHPXProject/hpx/issues/4886>

²⁵²⁶ <https://github.com/TheHPXProject/hpx/issues/4880>

²⁵²⁷ <https://github.com/TheHPXProject/hpx/issues/4877>

²⁵²⁸ <https://github.com/TheHPXProject/hpx/issues/4850>

²⁵²⁹ <https://github.com/TheHPXProject/hpx/issues/4829>

²⁵³⁰ <https://github.com/TheHPXProject/hpx/issues/4820>

²⁵³¹ <https://github.com/TheHPXProject/hpx/issues/4818>

²⁵³² <https://github.com/TheHPXProject/hpx/issues/4816>

²⁵³³ <https://github.com/TheHPXProject/hpx/issues/4813>

²⁵³⁴ <https://github.com/TheHPXProject/hpx/issues/4811>

- Issue #4810²⁵³⁵ - In `hpx::for_each::invoke_projected` the `hpx::util::decay` is misguided
- Issue #4787²⁵³⁶ - `transform_inclusive_scan` gives incorrect results for non-commutative operator
- Issue #4786²⁵³⁷ - `transform_inclusive_scan` tries to implicitly convert between types, instead of using the provided `conv` function
- Issue #4779²⁵³⁸ - HPX build error with GCC 10.1
- Issue #4766²⁵³⁹ - Move HPX.Compute functionality to experimental namespace
- Issue #4763²⁵⁴⁰ - License file name
- Issue #4758²⁵⁴¹ - CMake profiling results
- Issue #4755²⁵⁴² - Building HPX with support for PAPI fails
- Issue #4754²⁵⁴³ - CMake cache creation breaks when using HPX with mimalloc
- Issue #4752²⁵⁴⁴ - HPX MPI Future build failed
- Issue #4746²⁵⁴⁵ - Memory leak when using dataflow icw components
- Issue #4731²⁵⁴⁶ - Bug in stencil example, calculation of locality IDs
- Issue #4723²⁵⁴⁷ - Build fail with NETWORKING OFF
- Issue #4720²⁵⁴⁸ - Add compatibility headers for modules that had their module headers implicitly generated in 1.4.1
- Issue #4719²⁵⁴⁹ - Undeprecate some module headers
- Issue #4712²⁵⁵⁰ - Rename HPX_MPI_WITH_FUTURES option
- Issue #4709²⁵⁵¹ - Make deprecation warnings overridable in dependent projects
- Issue #4691²⁵⁵² - Suggestion to fix and enhance the `thread_mapper` API
- Issue #4686²⁵⁵³ - Fix tutorials examples
- Issue #4685²⁵⁵⁴ - HPX distributed map fails to compile
- Issue #4680²⁵⁵⁵ - Build error with `HPX_WITH_DYNAMIC_HPX_MAIN=OFF`
- Issue #4679²⁵⁵⁶ - Build error for hpx w/ Apex on Summit

²⁵³⁵ <https://github.com/TheHPXProject/hpx/issues/4810>

²⁵³⁶ <https://github.com/TheHPXProject/hpx/issues/4787>

²⁵³⁷ <https://github.com/TheHPXProject/hpx/issues/4786>

²⁵³⁸ <https://github.com/TheHPXProject/hpx/issues/4779>

²⁵³⁹ <https://github.com/TheHPXProject/hpx/issues/4766>

²⁵⁴⁰ <https://github.com/TheHPXProject/hpx/issues/4763>

²⁵⁴¹ <https://github.com/TheHPXProject/hpx/issues/4758>

²⁵⁴² <https://github.com/TheHPXProject/hpx/issues/4755>

²⁵⁴³ <https://github.com/TheHPXProject/hpx/issues/4754>

²⁵⁴⁴ <https://github.com/TheHPXProject/hpx/issues/4752>

²⁵⁴⁵ <https://github.com/TheHPXProject/hpx/issues/4746>

²⁵⁴⁶ <https://github.com/TheHPXProject/hpx/issues/4731>

²⁵⁴⁷ <https://github.com/TheHPXProject/hpx/issues/4723>

²⁵⁴⁸ <https://github.com/TheHPXProject/hpx/issues/4720>

²⁵⁴⁹ <https://github.com/TheHPXProject/hpx/issues/4719>

²⁵⁵⁰ <https://github.com/TheHPXProject/hpx/issues/4712>

²⁵⁵¹ <https://github.com/TheHPXProject/hpx/issues/4709>

²⁵⁵² <https://github.com/TheHPXProject/hpx/issues/4691>

²⁵⁵³ <https://github.com/TheHPXProject/hpx/issues/4686>

²⁵⁵⁴ <https://github.com/TheHPXProject/hpx/issues/4685>

²⁵⁵⁵ <https://github.com/TheHPXProject/hpx/issues/4680>

²⁵⁵⁶ <https://github.com/TheHPXProject/hpx/issues/4679>

- Issue #4675²⁵⁵⁷ - build error with HPX_WITH_NETWORKING=OFF
- Issue #4674²⁵⁵⁸ - Error running Quickstart tests on OS X
- Issue #4662²⁵⁵⁹ - MPI initialization broken when networking off
- Issue #4652²⁵⁶⁰ - How to fix distributed action annotation
- Issue #4650²⁵⁶¹ - thread descriptions are broken... again
- Issue #4648²⁵⁶² - Thread stacksize not properly set
- Issue #4647²⁵⁶³ - Rename generated collective headers in modules
- Issue #4639²⁵⁶⁴ - Update deprecation warnings in compatibility headers to point to collective headers
- Issue #4628²⁵⁶⁵ - mpi parcellport totally broken
- Issue #4619²⁵⁶⁶ - Fully document hpx_wrap behaviour and targets
- Issue #4612²⁵⁶⁷ - Compilation issue with HPX 1.4.1 and 1.4.0
- Issue #4594²⁵⁶⁸ - Rename modules
- Issue #4578²⁵⁶⁹ - Default value for HPX_WITH_THREAD_BACKTRACE_DEPTH
- Issue #4572²⁵⁷⁰ - Thread manager should be given a runtime_configuration
- Issue #4571²⁵⁷¹ - Add high-level documentation to new modules
- Issue #4569²⁵⁷² - Annoying warning when compiling - pls suppress or fix it.
- Issue #4555²⁵⁷³ - HPX_HAVE_THREAD_BACKTRACE_ON_SUSPENSION compilation error
- Issue #4543²⁵⁷⁴ - Segfaults in Release builds using *sleep_for*
- Issue #4539²⁵⁷⁵ - Compilation Error when HPX_MPI_WITH_FUTURES=ON
- Issue #4537²⁵⁷⁶ - Linking issue with libhpx_initd.a
- Issue #4535²⁵⁷⁷ - API for checking if pool with a given name exists
- Issue #4523²⁵⁷⁸ - Build of PR #4311 (git tag 9955e8e) fails
- Issue #4519²⁵⁷⁹ - Documentation problem

²⁵⁵⁷ <https://github.com/TheHPXProject/hpx/issues/4675>

²⁵⁵⁸ <https://github.com/TheHPXProject/hpx/issues/4674>

²⁵⁵⁹ <https://github.com/TheHPXProject/hpx/issues/4662>

²⁵⁶⁰ <https://github.com/TheHPXProject/hpx/issues/4652>

²⁵⁶¹ <https://github.com/TheHPXProject/hpx/issues/4650>

²⁵⁶² <https://github.com/TheHPXProject/hpx/issues/4648>

²⁵⁶³ <https://github.com/TheHPXProject/hpx/issues/4647>

²⁵⁶⁴ <https://github.com/TheHPXProject/hpx/issues/4639>

²⁵⁶⁵ <https://github.com/TheHPXProject/hpx/issues/4628>

²⁵⁶⁶ <https://github.com/TheHPXProject/hpx/issues/4619>

²⁵⁶⁷ <https://github.com/TheHPXProject/hpx/issues/4612>

²⁵⁶⁸ <https://github.com/TheHPXProject/hpx/issues/4594>

²⁵⁶⁹ <https://github.com/TheHPXProject/hpx/issues/4578>

²⁵⁷⁰ <https://github.com/TheHPXProject/hpx/issues/4572>

²⁵⁷¹ <https://github.com/TheHPXProject/hpx/issues/4571>

²⁵⁷² <https://github.com/TheHPXProject/hpx/issues/4569>

²⁵⁷³ <https://github.com/TheHPXProject/hpx/issues/4555>

²⁵⁷⁴ <https://github.com/TheHPXProject/hpx/issues/4543>

²⁵⁷⁵ <https://github.com/TheHPXProject/hpx/issues/4539>

²⁵⁷⁶ <https://github.com/TheHPXProject/hpx/issues/4537>

²⁵⁷⁷ <https://github.com/TheHPXProject/hpx/issues/4535>

²⁵⁷⁸ <https://github.com/TheHPXProject/hpx/issues/4523>

²⁵⁷⁹ <https://github.com/TheHPXProject/hpx/issues/4519>

- [Issue #4513](#)²⁵⁸⁰ - HPXConfig.cmake contains ill-formed paths when library paths use backslashes
- [Issue #4507](#)²⁵⁸¹ - User-polling introduced by MPI futures module should be more generally usable
- [Issue #4506](#)²⁵⁸² - Make sure force_linking.hpp is not included in main module header
- [Issue #4501](#)²⁵⁸³ - Fix compilation of PAPI tests
- [Issue #4497](#)²⁵⁸⁴ - Add modules CI checks
- [Issue #4489](#)²⁵⁸⁵ - Polymorphic executor
- [Issue #4476](#)²⁵⁸⁶ - Use CMake targets defined by FindBoost
- [Issue #4473](#)²⁵⁸⁷ - Add vcpkg installation instructions
- [Issue #4470](#)²⁵⁸⁸ - Adapt hpx::future to C++20 co_await
- [Issue #4468](#)²⁵⁸⁹ - Compile error on Raspberry Pi 4
- [Issue #4466](#)²⁵⁹⁰ - Compile error on Windows, current stable:
- [Issue #4453](#)²⁵⁹¹ - Installing HPX on fedora with dnf is not adding cmake files
- [Issue #4448](#)²⁵⁹² - New std::variant serialization broken
- [Issue #4438](#)²⁵⁹³ - Add performance counter flag is monotonically increasing
- [Issue #4436](#)²⁵⁹⁴ - Build problem: same code build and works with 1.4.0 but it doesn't with 1.4.1
- [Issue #4429](#)²⁵⁹⁵ - Function descriptions not supported in distributed
- [Issue #4423](#)²⁵⁹⁶ - `-hpx:ini=hpx.lock_detection=0` has no effect
- [Issue #4422](#)²⁵⁹⁷ - Add performance counter metadata
- [Issue #4419](#)²⁵⁹⁸ - Weird behavior for `-hpx:print-counter-interval` with large numbers
- [Issue #4401](#)²⁵⁹⁹ - Create module repository
- [Issue #4400](#)²⁶⁰⁰ - Command line options conflict related to performance counters
- [Issue #4349](#)²⁶⁰¹ - `-hpx:use-process-mask` option throw an exception on OS X
- [Issue #4345](#)²⁶⁰² - Move gh-pages branch out of hpx repo

²⁵⁸⁰ <https://github.com/TheHPXProject/hpx/issues/4513>

²⁵⁸¹ <https://github.com/TheHPXProject/hpx/issues/4507>

²⁵⁸² <https://github.com/TheHPXProject/hpx/issues/4506>

²⁵⁸³ <https://github.com/TheHPXProject/hpx/issues/4501>

²⁵⁸⁴ <https://github.com/TheHPXProject/hpx/issues/4497>

²⁵⁸⁵ <https://github.com/TheHPXProject/hpx/issues/4489>

²⁵⁸⁶ <https://github.com/TheHPXProject/hpx/issues/4476>

²⁵⁸⁷ <https://github.com/TheHPXProject/hpx/issues/4473>

²⁵⁸⁸ <https://github.com/TheHPXProject/hpx/issues/4470>

²⁵⁸⁹ <https://github.com/TheHPXProject/hpx/issues/4468>

²⁵⁹⁰ <https://github.com/TheHPXProject/hpx/issues/4466>

²⁵⁹¹ <https://github.com/TheHPXProject/hpx/issues/4453>

²⁵⁹² <https://github.com/TheHPXProject/hpx/issues/4448>

²⁵⁹³ <https://github.com/TheHPXProject/hpx/issues/4438>

²⁵⁹⁴ <https://github.com/TheHPXProject/hpx/issues/4436>

²⁵⁹⁵ <https://github.com/TheHPXProject/hpx/issues/4429>

²⁵⁹⁶ <https://github.com/TheHPXProject/hpx/issues/4423>

²⁵⁹⁷ <https://github.com/TheHPXProject/hpx/issues/4422>

²⁵⁹⁸ <https://github.com/TheHPXProject/hpx/issues/4419>

²⁵⁹⁹ <https://github.com/TheHPXProject/hpx/issues/4401>

²⁶⁰⁰ <https://github.com/TheHPXProject/hpx/issues/4400>

²⁶⁰¹ <https://github.com/TheHPXProject/hpx/issues/4349>

²⁶⁰² <https://github.com/TheHPXProject/hpx/issues/4345>

- [Issue #4323](#)²⁶⁰³ - Const-correctness error in assignment operator of `compute::vector`
- [Issue #4318](#)²⁶⁰⁴ - ASIO breaks with C++2a concepts
- [Issue #4317](#)²⁶⁰⁵ - Application runs even if `-hpx:help` is specified
- [Issue #4063](#)²⁶⁰⁶ - Document `hpxcxx` compiler wrapper
- [Issue #3983](#)²⁶⁰⁷ - Implement the C++20 Synchronization Library
- [Issue #3696](#)²⁶⁰⁸ - C++11 `constexpr` support is now required
- [Issue #3623](#)²⁶⁰⁹ - Modular HPX branch and an alternative project layout
- [Issue #2836](#)²⁶¹⁰ - The worst-case time complexity of `parallel::sort` seems to be $O(N^2)$.

Closed pull requests

- [PR #4936](#)²⁶¹¹ - Minor documentation fixes part 2
- [PR #4935](#)²⁶¹² - Add copyright and license to joss paper file
- [PR #4934](#)²⁶¹³ - Adding Semicolon in Documentation
- [PR #4932](#)²⁶¹⁴ - Fixing compiler warnings
- [PR #4931](#)²⁶¹⁵ - Small documentation formatting fixes
- [PR #4930](#)²⁶¹⁶ - Documentation Distributed HPX applications `localvv` with `local_vv`
- [PR #4929](#)²⁶¹⁷ - Add final version of the JOSS paper
- [PR #4928](#)²⁶¹⁸ - Add `HPX_NODISCARD` to `enable_user_polling` structs
- [PR #4926](#)²⁶¹⁹ - Rename `distributed_executors` module to `executors_distributed`
- [PR #4925](#)²⁶²⁰ - Making `transform_reduce` conforming to C++20
- [PR #4923](#)²⁶²¹ - Don't acquire lock if not needed
- [PR #4921](#)²⁶²² - Update the release notes for the release candidate 3
- [PR #4920](#)²⁶²³ - Disable `libcdis` release
- [PR #4919](#)²⁶²⁴ - Make `cuda` event pool dynamic instead of fixed size

²⁶⁰³ <https://github.com/TheHPXProject/hpx/issues/4323>

²⁶⁰⁴ <https://github.com/TheHPXProject/hpx/issues/4318>

²⁶⁰⁵ <https://github.com/TheHPXProject/hpx/issues/4317>

²⁶⁰⁶ <https://github.com/TheHPXProject/hpx/issues/4063>

²⁶⁰⁷ <https://github.com/TheHPXProject/hpx/issues/3983>

²⁶⁰⁸ <https://github.com/TheHPXProject/hpx/issues/3696>

²⁶⁰⁹ <https://github.com/TheHPXProject/hpx/issues/3623>

²⁶¹⁰ <https://github.com/TheHPXProject/hpx/issues/2836>

²⁶¹¹ <https://github.com/TheHPXProject/hpx/pull/4936>

²⁶¹² <https://github.com/TheHPXProject/hpx/pull/4935>

²⁶¹³ <https://github.com/TheHPXProject/hpx/pull/4934>

²⁶¹⁴ <https://github.com/TheHPXProject/hpx/pull/4932>

²⁶¹⁵ <https://github.com/TheHPXProject/hpx/pull/4931>

²⁶¹⁶ <https://github.com/TheHPXProject/hpx/pull/4930>

²⁶¹⁷ <https://github.com/TheHPXProject/hpx/pull/4929>

²⁶¹⁸ <https://github.com/TheHPXProject/hpx/pull/4928>

²⁶¹⁹ <https://github.com/TheHPXProject/hpx/pull/4926>

²⁶²⁰ <https://github.com/TheHPXProject/hpx/pull/4925>

²⁶²¹ <https://github.com/TheHPXProject/hpx/pull/4923>

²⁶²² <https://github.com/TheHPXProject/hpx/pull/4921>

²⁶²³ <https://github.com/TheHPXProject/hpx/pull/4920>

²⁶²⁴ <https://github.com/TheHPXProject/hpx/pull/4919>

- PR #4917²⁶²⁵ - Move chrono functionality to hpx::chrono namespace
- PR #4916²⁶²⁶ - HPX_HAVE_DEPRECATED_WARNINGS needs to be set even when disabled
- PR #4915²⁶²⁷ - Moving more action related files to actions modules
- PR #4914²⁶²⁸ - Add alias targets with namespaces used for exporting
- PR #4912²⁶²⁹ - Aggregate initialize CPOs
- PR #4910²⁶³⁰ - Explicitly specify hwloc root on Jenkins CSCS builds
- PR #4908²⁶³¹ - Fix algorithms documentation
- PR #4907²⁶³² - Remove HPX::hpx_no_wrap_main target
- PR #4906²⁶³³ - Fixing unused variable warning
- PR #4905²⁶³⁴ - Adding specializations for simple for_loops
- PR #4904²⁶³⁵ - Update boost to 1.74.0 for the newest jenkins configs
- PR #4903²⁶³⁶ - Hide GITHUB_TOKEN environment variables from environment variable output
- PR #4902²⁶³⁷ - Cancel previous pull requests builds before starting a new one with Jenkins
- PR #4901²⁶³⁸ - Update public API list with updated algorithms
- PR #4899²⁶³⁹ - Suggested changes for HPX V1.5 release notes
- PR #4898²⁶⁴⁰ - Minor tweak to hpx::equal implementation
- PR #4896²⁶⁴¹ - Making generate() and generate_n conforming to C++20
- PR #4895²⁶⁴² - Update apex tag
- PR #4894²⁶⁴³ - Fix exception handling for tasks
- PR #4893²⁶⁴⁴ - Remove last use of std::result_of, removed in C++20
- PR #4892²⁶⁴⁵ - Adding replay_executor and replicate_executor
- PR #4889²⁶⁴⁶ - Restore old behaviour of not requiring linking to hpx_wrap when HPX_WITH_DYNAMIC_HP_X_MAIN=OFF
- PR #4887²⁶⁴⁷ - Making sure remotely thrown (non-hpx) exceptions are properly marshaled back to invocation

²⁶²⁵ <https://github.com/TheHPXProject/hpx/pull/4917>

²⁶²⁶ <https://github.com/TheHPXProject/hpx/pull/4916>

²⁶²⁷ <https://github.com/TheHPXProject/hpx/pull/4915>

²⁶²⁸ <https://github.com/TheHPXProject/hpx/pull/4914>

²⁶²⁹ <https://github.com/TheHPXProject/hpx/pull/4912>

²⁶³⁰ <https://github.com/TheHPXProject/hpx/pull/4910>

²⁶³¹ <https://github.com/TheHPXProject/hpx/pull/4908>

²⁶³² <https://github.com/TheHPXProject/hpx/pull/4907>

²⁶³³ <https://github.com/TheHPXProject/hpx/pull/4906>

²⁶³⁴ <https://github.com/TheHPXProject/hpx/pull/4905>

²⁶³⁵ <https://github.com/TheHPXProject/hpx/pull/4904>

²⁶³⁶ <https://github.com/TheHPXProject/hpx/pull/4903>

²⁶³⁷ <https://github.com/TheHPXProject/hpx/pull/4902>

²⁶³⁸ <https://github.com/TheHPXProject/hpx/pull/4901>

²⁶³⁹ <https://github.com/TheHPXProject/hpx/pull/4899>

²⁶⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4898>

²⁶⁴¹ <https://github.com/TheHPXProject/hpx/pull/4896>

²⁶⁴² <https://github.com/TheHPXProject/hpx/pull/4895>

²⁶⁴³ <https://github.com/TheHPXProject/hpx/pull/4894>

²⁶⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4893>

²⁶⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4892>

²⁶⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4889>

²⁶⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4887>

site

- [PR #4885](#)²⁶⁴⁸ - Adapting `hpx::find` and `friends` to C++20
- [PR #4884](#)²⁶⁴⁹ - Adapting `mismatch` to C++20
- [PR #4883](#)²⁶⁵⁰ - Adapting `hpx::equal` to be conforming to C++20
- [PR #4882](#)²⁶⁵¹ - Fixing exception handling for `hpx::copy` and adding missing tests
- [PR #4881](#)²⁶⁵² - Adds different runtime exception when registering thread with the HPX runtime
- [PR #4876](#)²⁶⁵³ - Adding example demonstrating how to disable thread stealing during the execution of parallel algorithms
- [PR #4874](#)²⁶⁵⁴ - Adding non-policy tests to `all_of`, `any_of`, and `none_of`
- [PR #4873](#)²⁶⁵⁵ - Set CUDA compute capability on rostam Jenkins builds
- [PR #4872](#)²⁶⁵⁶ - Force partitioned vector scan tests to run serially
- [PR #4870](#)²⁶⁵⁷ - Making `move` conforming with C++20
- [PR #4869](#)²⁶⁵⁸ - Making `destroy` and `destroy_n` conforming to C++20
- [PR #4868](#)²⁶⁵⁹ - Fix miscellaneous header problems
- [PR #4867](#)²⁶⁶⁰ - Add CPOs for `for_each`
- [PR #4865](#)²⁶⁶¹ - Adapting `count` and `count_if` to be conforming to C++20
- [PR #4864](#)²⁶⁶² - Release notes 1.5.0
- [PR #4863](#)²⁶⁶³ - adding `libcds-hpx` tag to prepare for `hpx1.5` release
- [PR #4862](#)²⁶⁶⁴ - Adding version specific deprecation options
- [PR #4861](#)²⁶⁶⁵ - Limiting executor improvements
- [PR #4860](#)²⁶⁶⁶ - Making `fill` and `fill_n` compatible with C++20
- [PR #4859](#)²⁶⁶⁷ - Adapting `all_of`, `any_of`, and `none_of` to C++20
- [PR #4857](#)²⁶⁶⁸ - Improve `libCDS` integration
- [PR #4856](#)²⁶⁶⁹ - Correct typos in the documentation of the `hpx` performance counters

²⁶⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4885>

²⁶⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4884>

²⁶⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4883>

²⁶⁵¹ <https://github.com/TheHPXProject/hpx/pull/4882>

²⁶⁵² <https://github.com/TheHPXProject/hpx/pull/4881>

²⁶⁵³ <https://github.com/TheHPXProject/hpx/pull/4876>

²⁶⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4874>

²⁶⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4873>

²⁶⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4872>

²⁶⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4870>

²⁶⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4869>

²⁶⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4868>

²⁶⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4867>

²⁶⁶¹ <https://github.com/TheHPXProject/hpx/pull/4865>

²⁶⁶² <https://github.com/TheHPXProject/hpx/pull/4864>

²⁶⁶³ <https://github.com/TheHPXProject/hpx/pull/4863>

²⁶⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4862>

²⁶⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4861>

²⁶⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4860>

²⁶⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4859>

²⁶⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4857>

²⁶⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4856>

- PR #4854²⁶⁷⁰ - Removing obsolete code
- PR #4853²⁶⁷¹ - Adding test that derives component from two other components
- PR #4852²⁶⁷² - Fix mpi_ring test in distributed mode by ensuring all ranks run hpx_main
- PR #4851²⁶⁷³ - Converting resiliency APIs to tag_invoke based CPOs
- PR #4849²⁶⁷⁴ - Enable use of future_overhead test when DISTRIBUTED_RUNTIME is OFF
- PR #4847²⁶⁷⁵ - Fixing 'error prone' constructs as reported by Codacy
- PR #4846²⁶⁷⁶ - Disable Boost.Asio concepts support
- PR #4845²⁶⁷⁷ - Fix PAPI counters
- PR #4843²⁶⁷⁸ - Remove dependency on various Boost headers
- PR #4841²⁶⁷⁹ - Rearrange public API headers
- PR #4840²⁶⁸⁰ - Fixing TSS problems during thread termination
- PR #4839²⁶⁸¹ - Fix async_cuda build problems when distributed runtime is disabled
- PR #4837²⁶⁸² - Restore compatibility for old (now deprecated) copy algorithms
- PR #4836²⁶⁸³ - Adding CPOs for hpx::reduce
- PR #4835²⁶⁸⁴ - Remove *using util::result_of* from namespace hpx
- PR #4834²⁶⁸⁵ - Fixing the calculation of the number of idle cores and the corresponding idle masks
- PR #4833²⁶⁸⁶ - Allow thread function destructors to yield
- PR #4832²⁶⁸⁷ - Fixing assertion in split_gids and memory leaks in 1d_stencil_7
- PR #4831²⁶⁸⁸ - Making sure MPI_CXX_COMPILE_FLAGS is interpreted as a sequence of options
- PR #4830²⁶⁸⁹ - Update documentation on using HPX::wrap_main
- PR #4827²⁶⁹⁰ - Update clang-newest configuration to use clang 10
- PR #4826²⁶⁹¹ - Add Jenkins configuration for rostam
- PR #4825²⁶⁹² - Move all CUDA functionality to hpx::cuda::experimental namespace

²⁶⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4854>

²⁶⁷¹ <https://github.com/TheHPXProject/hpx/pull/4853>

²⁶⁷² <https://github.com/TheHPXProject/hpx/pull/4852>

²⁶⁷³ <https://github.com/TheHPXProject/hpx/pull/4851>

²⁶⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4849>

²⁶⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4847>

²⁶⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4846>

²⁶⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4845>

²⁶⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4843>

²⁶⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4841>

²⁶⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4840>

²⁶⁸¹ <https://github.com/TheHPXProject/hpx/pull/4839>

²⁶⁸² <https://github.com/TheHPXProject/hpx/pull/4837>

²⁶⁸³ <https://github.com/TheHPXProject/hpx/pull/4836>

²⁶⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4835>

²⁶⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4834>

²⁶⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4833>

²⁶⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4832>

²⁶⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4831>

²⁶⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4830>

²⁶⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4827>

²⁶⁹¹ <https://github.com/TheHPXProject/hpx/pull/4826>

²⁶⁹² <https://github.com/TheHPXProject/hpx/pull/4825>

- PR #4824²⁶⁹³ - Add support for building master/release branches to Jenkins configuration
- PR #4821²⁶⁹⁴ - Implement customization point for `hpx::copy` and `hpx::ranges::copy`
- PR #4819²⁶⁹⁵ - Allow finding Boost components before finding HPX
- PR #4817²⁶⁹⁶ - Adding range version of stable sort
- PR #4815²⁶⁹⁷ - Fix a wrong `#ifdef` for IO/TIMER pools causing build errors
- PR #4814²⁶⁹⁸ - Replace `hpx::function_nonsr` with `std::function` in error module
- PR #4809²⁶⁹⁹ - Foreach adapt
- PR #4808²⁷⁰⁰ - Make internal algorithms functions const
- PR #4807²⁷⁰¹ - Add Jenkins configuration for running on Piz Daint
- PR #4806²⁷⁰² - Update documentation links to new domain name
- PR #4805²⁷⁰³ - Applying changes that resolve time complexity issues in sort
- PR #4803²⁷⁰⁴ - Adding implementation of `stable_sort`
- PR #4802²⁷⁰⁵ - Fix datapar header paths
- PR #4801²⁷⁰⁶ - Replace `boost::shared_array<T>` with `std::shared_ptr<T[]>` if supported
- PR #4799²⁷⁰⁷ - Fixing `#include` paths in compatibility headers
- PR #4798²⁷⁰⁸ - Include the main module header (fixes partially #4488)
- PR #4797²⁷⁰⁹ - Change cmake targets
- PR #4794²⁷¹⁰ - Removing 128bit integer emulation
- PR #4793²⁷¹¹ - Make sure global variable is handled properly
- PR #4792²⁷¹² - Replace `enable_if` with **HPX_CONCEPT_REQUIRES_** and add `is_sentinel_for` constraint
- PR #4790²⁷¹³ - Move deprecation warnings from base template to template specializations for `result_of` etc. structs
- PR #4789²⁷¹⁴ - Fix hangs during assertion handling and distributed runtime construction
- PR #4788²⁷¹⁵ - Fixing inclusive transform scan algorithm to properly handle initial value

²⁶⁹³ <https://github.com/TheHPXProject/hpx/pull/4824>

²⁶⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4821>

²⁶⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4819>

²⁶⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4817>

²⁶⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4815>

²⁶⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4814>

²⁶⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4809>

²⁷⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4808>

²⁷⁰¹ <https://github.com/TheHPXProject/hpx/pull/4807>

²⁷⁰² <https://github.com/TheHPXProject/hpx/pull/4806>

²⁷⁰³ <https://github.com/TheHPXProject/hpx/pull/4805>

²⁷⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4803>

²⁷⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4802>

²⁷⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4801>

²⁷⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4799>

²⁷⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4798>

²⁷⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4797>

²⁷¹⁰ <https://github.com/TheHPXProject/hpx/pull/4794>

²⁷¹¹ <https://github.com/TheHPXProject/hpx/pull/4793>

²⁷¹² <https://github.com/TheHPXProject/hpx/pull/4792>

²⁷¹³ <https://github.com/TheHPXProject/hpx/pull/4790>

²⁷¹⁴ <https://github.com/TheHPXProject/hpx/pull/4789>

²⁷¹⁵ <https://github.com/TheHPXProject/hpx/pull/4788>

- PR #4785²⁷¹⁶ - Fixing barrier test
- PR #4784²⁷¹⁷ - Fixing deleter argument bindings in `serialize_buffer`
- PR #4783²⁷¹⁸ - Add coveralls badge
- PR #4782²⁷¹⁹ - Make header tests parallel again
- PR #4780²⁷²⁰ - Remove outdated comment about `hpx::stop` in documentation
- PR #4776²⁷²¹ - debug print improvements
- PR #4775²⁷²² - Checkpoint cleanup
- PR #4771²⁷²³ - Fix compilation with `HPX_WITH_NETWORKING=OFF`
- PR #4767²⁷²⁴ - Remove all force linking leftovers
- PR #4765²⁷²⁵ - Fix 1d stencil index calculation
- PR #4764²⁷²⁶ - Force some tests to run serially
- PR #4762²⁷²⁷ - Update pointees in compatibility headers
- PR #4761²⁷²⁸ - Fix running and building of execution module tests on CircleCI
- PR #4760²⁷²⁹ - Storing `hpx_options` in global property to speed up summary report
- PR #4759²⁷³⁰ - Reduce memory requirements for our main shared state
- PR #4757²⁷³¹ - Fix `mimalloc` linking on Windows
- PR #4756²⁷³² - Fix compilation issues
- PR #4753²⁷³³ - Re-adding API functions that were lost during merges
- PR #4751²⁷³⁴ - Revert “Create coverage reports and upload them to `codecov.io`”
- PR #4750²⁷³⁵ - Fixing possible race condition during termination detection
- PR #4749²⁷³⁶ - Deprecate `result_of` and friends
- PR #4748²⁷³⁷ - Create coverage reports and upload them to `codecov.io`
- PR #4747²⁷³⁸ - Changing `#include` for MPI `parcelpport`

²⁷¹⁶ <https://github.com/TheHPXProject/hpx/pull/4785>

²⁷¹⁷ <https://github.com/TheHPXProject/hpx/pull/4784>

²⁷¹⁸ <https://github.com/TheHPXProject/hpx/pull/4783>

²⁷¹⁹ <https://github.com/TheHPXProject/hpx/pull/4782>

²⁷²⁰ <https://github.com/TheHPXProject/hpx/pull/4780>

²⁷²¹ <https://github.com/TheHPXProject/hpx/pull/4776>

²⁷²² <https://github.com/TheHPXProject/hpx/pull/4775>

²⁷²³ <https://github.com/TheHPXProject/hpx/pull/4771>

²⁷²⁴ <https://github.com/TheHPXProject/hpx/pull/4767>

²⁷²⁵ <https://github.com/TheHPXProject/hpx/pull/4765>

²⁷²⁶ <https://github.com/TheHPXProject/hpx/pull/4764>

²⁷²⁷ <https://github.com/TheHPXProject/hpx/pull/4762>

²⁷²⁸ <https://github.com/TheHPXProject/hpx/pull/4761>

²⁷²⁹ <https://github.com/TheHPXProject/hpx/pull/4760>

²⁷³⁰ <https://github.com/TheHPXProject/hpx/pull/4759>

²⁷³¹ <https://github.com/TheHPXProject/hpx/pull/4757>

²⁷³² <https://github.com/TheHPXProject/hpx/pull/4756>

²⁷³³ <https://github.com/TheHPXProject/hpx/pull/4753>

²⁷³⁴ <https://github.com/TheHPXProject/hpx/pull/4751>

²⁷³⁵ <https://github.com/TheHPXProject/hpx/pull/4750>

²⁷³⁶ <https://github.com/TheHPXProject/hpx/pull/4749>

²⁷³⁷ <https://github.com/TheHPXProject/hpx/pull/4748>

²⁷³⁸ <https://github.com/TheHPXProject/hpx/pull/4747>

- PR #4745²⁷³⁹ - Add *is_sentinel_for* trait implementation and test
- PR #4743²⁷⁴⁰ - Fix *init_globally* example after runtime mode changes
- PR #4742²⁷⁴¹ - Update SUPPORT.md
- PR #4741²⁷⁴² - Fixing a warning generated for unity builds with msvc
- PR #4740²⁷⁴³ - Rename *local_lcos* and *basic_execution* modules
- PR #4739²⁷⁴⁴ - Undeprecate a couple of *hpx/modulename.hpp* headers
- PR #4738²⁷⁴⁵ - Conditionally test schedulers in *thread_stacksize_current* test
- PR #4734²⁷⁴⁶ - Fixing a bunch of codacy warnings
- PR #4733²⁷⁴⁷ - Add experimental unity build option to CMake configuration
- PR #4730²⁷⁴⁸ - Fixing compilation problems with *unordered_map*
- PR #4729²⁷⁴⁹ - Fix APEX build
- PR #4727²⁷⁵⁰ - Fix missing runtime includes for distributed runtime
- PR #4726²⁷⁵¹ - Add more API headers
- PR #4725²⁷⁵² - Add more compatibility headers for deprecated module headers
- PR #4724²⁷⁵³ - Fix 4723
- PR #4721²⁷⁵⁴ - Attempt to fixing migration tests
- PR #4717²⁷⁵⁵ - Make the compatibility headers macro conditional
- PR #4716²⁷⁵⁶ - Add *hpx/runtime.hpp* and *hpx/distributed/runtime.hpp* API headers
- PR #4714²⁷⁵⁷ - Add *hpx/future.hpp* header
- PR #4713²⁷⁵⁸ - Remove *hpx/runtime/threads_fwd.hpp* and *hpx/util_fwd.hpp*
- PR #4711²⁷⁵⁹ - Make module deprecation warnings overridable
- PR #4710²⁷⁶⁰ - Add compatibility headers and other fixes after module header renaming
- PR #4708²⁷⁶¹ - Add termination handler for parallel algorithms

²⁷³⁹ <https://github.com/TheHPXProject/hpx/pull/4745>

²⁷⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4743>

²⁷⁴¹ <https://github.com/TheHPXProject/hpx/pull/4742>

²⁷⁴² <https://github.com/TheHPXProject/hpx/pull/4741>

²⁷⁴³ <https://github.com/TheHPXProject/hpx/pull/4740>

²⁷⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4739>

²⁷⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4738>

²⁷⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4734>

²⁷⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4733>

²⁷⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4730>

²⁷⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4729>

²⁷⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4727>

²⁷⁵¹ <https://github.com/TheHPXProject/hpx/pull/4726>

²⁷⁵² <https://github.com/TheHPXProject/hpx/pull/4725>

²⁷⁵³ <https://github.com/TheHPXProject/hpx/pull/4724>

²⁷⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4721>

²⁷⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4717>

²⁷⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4716>

²⁷⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4714>

²⁷⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4713>

²⁷⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4711>

²⁷⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4710>

²⁷⁶¹ <https://github.com/TheHPXProject/hpx/pull/4708>

- PR #4707²⁷⁶² - Use `hpx::function_nonser` instead of `std::function` internally
- PR #4706²⁷⁶³ - Move header file to module
- PR #4705²⁷⁶⁴ - Fix incorrect behaviour of `cmake-format` check
- PR #4704²⁷⁶⁵ - Fix resource tests
- PR #4701²⁷⁶⁶ - Fix missing includes for `future::then` specializations
- PR #4700²⁷⁶⁷ - Removing obsolete memory component
- PR #4699²⁷⁶⁸ - Add short descriptions to modules missing documentation
- PR #4696²⁷⁶⁹ - Rename generated modules headers
- PR #4693²⁷⁷⁰ - Overhauling `thread_mapper` for public consumption
- PR #4688²⁷⁷¹ - Fix thread stack size handling
- PR #4687²⁷⁷² - Adding `all_gather` and fixing `all_to_all`
- PR #4684²⁷⁷³ - Miscellaneous compilation fixes
- PR #4683²⁷⁷⁴ - Fix `HPX_WITH_DYNAMIC_HPX_MAIN=OFF`
- PR #4682²⁷⁷⁵ - Fix compilation of `pack_traversal_rebind_container.hpp`
- PR #4681²⁷⁷⁶ - Add missing `hpx/execution.hpp` includes for `future::then`
- PR #4678²⁷⁷⁷ - Typeless communicator
- PR #4677²⁷⁷⁸ - Forcing registry option to be accepted without checks.
- PR #4676²⁷⁷⁹ - Adding `scatter_to/scatter_from` collective operations
- PR #4673²⁷⁸⁰ - Fix PAPI counters compilation
- PR #4671²⁷⁸¹ - Deprecate `hpx::promise` alias to `hpx::lcos::promise`
- PR #4670²⁷⁸² - Explicitly instantiate `get_exception`
- PR #4667²⁷⁸³ - Add `stopValue` in *Sentinel* struct instead of *Iterator*
- PR #4666²⁷⁸⁴ - Add release build on Windows to GitHub actions

²⁷⁶² <https://github.com/TheHPXProject/hpx/pull/4707>

²⁷⁶³ <https://github.com/TheHPXProject/hpx/pull/4706>

²⁷⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4705>

²⁷⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4704>

²⁷⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4701>

²⁷⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4700>

²⁷⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4699>

²⁷⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4696>

²⁷⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4693>

²⁷⁷¹ <https://github.com/TheHPXProject/hpx/pull/4688>

²⁷⁷² <https://github.com/TheHPXProject/hpx/pull/4687>

²⁷⁷³ <https://github.com/TheHPXProject/hpx/pull/4684>

²⁷⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4683>

²⁷⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4682>

²⁷⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4681>

²⁷⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4678>

²⁷⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4677>

²⁷⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4676>

²⁷⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4673>

²⁷⁸¹ <https://github.com/TheHPXProject/hpx/pull/4671>

²⁷⁸² <https://github.com/TheHPXProject/hpx/pull/4670>

²⁷⁸³ <https://github.com/TheHPXProject/hpx/pull/4667>

²⁷⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4666>

- PR #4664²⁷⁸⁵ - Creating itt_notify module.
- PR #4663²⁷⁸⁶ - Mpi fixes
- PR #4659²⁷⁸⁷ - Making sure declarations match definitions in register_locks implementation
- PR #4655²⁷⁸⁸ - Fixing task annotations for actions
- PR #4653²⁷⁸⁹ - Making sure APEX is linked into every application, if needed
- PR #4651²⁷⁹⁰ - Update get_function_annotation.hpp
- PR #4646²⁷⁹¹ - Runtime type
- PR #4645²⁷⁹² - Add a few more API headers
- PR #4644²⁷⁹³ - Fixing support for mpirun (and similar)
- PR #4643²⁷⁹⁴ - Fixing the fix for get_idle_core_count() API
- PR #4638²⁷⁹⁵ - Remove HPX_API_EXPORT missed in previous cleanup
- PR #4636²⁷⁹⁶ - Adding C++20 barrier
- PR #4635²⁷⁹⁷ - Adding C++20 latch API
- PR #4634²⁷⁹⁸ - Adding C++20 counting semaphore API
- PR #4633²⁷⁹⁹ - Unify execution parameters customization points
- PR #4632²⁸⁰⁰ - Adding missing bulk_sync_execute wrapper to example executor
- PR #4631²⁸⁰¹ - Updates to documentation; grammar edits.
- PR #4630²⁸⁰² - Updates to documentation; moved hyperlink
- PR #4624²⁸⁰³ - Export set_self_ptr in thread_data.hpp instead of with forward declarations where used
- PR #4623²⁸⁰⁴ - Clean up export macros
- PR #4621²⁸⁰⁵ - Trigger an error for older boost versions on power architectures
- PR #4617²⁸⁰⁶ - Ignore user-set compatibility header options if the module does not have compatibility headers
- PR #4616²⁸⁰⁷ - Fix cmake-format warning

²⁷⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4664>

²⁷⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4663>

²⁷⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4659>

²⁷⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4655>

²⁷⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4653>

²⁷⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4651>

²⁷⁹¹ <https://github.com/TheHPXProject/hpx/pull/4646>

²⁷⁹² <https://github.com/TheHPXProject/hpx/pull/4645>

²⁷⁹³ <https://github.com/TheHPXProject/hpx/pull/4644>

²⁷⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4643>

²⁷⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4638>

²⁷⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4636>

²⁷⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4635>

²⁷⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4634>

²⁷⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4633>

²⁸⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4632>

²⁸⁰¹ <https://github.com/TheHPXProject/hpx/pull/4631>

²⁸⁰² <https://github.com/TheHPXProject/hpx/pull/4630>

²⁸⁰³ <https://github.com/TheHPXProject/hpx/pull/4624>

²⁸⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4623>

²⁸⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4621>

²⁸⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4617>

²⁸⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4616>

- PR #4615²⁸⁰⁸ - Add handler for serializing custom exceptions
- PR #4614²⁸⁰⁹ - Fix error message when HPX_IGNORE_CMAKE_BUILD_TYPE_COMPATIBILITY=OFF
- PR #4613²⁸¹⁰ - Make partitioner constructor private
- PR #4611²⁸¹¹ - Making auto_chunk_size execute the given function using the given executor
- PR #4610²⁸¹² - Making sure the thread-local lock registration data is moving to the core the suspended HPX thread is resumed on
- PR #4609²⁸¹³ - Adding an API function that exposes the number of idle cores
- PR #4608²⁸¹⁴ - Fixing moodycamel namespace
- PR #4607²⁸¹⁵ - Moving winsocket initialization to core library
- PR #4606²⁸¹⁶ - Local runtime module etc.
- PR #4604²⁸¹⁷ - Add config_registry module
- PR #4603²⁸¹⁸ - Deal with distributed modules in their respective CMakeLists.txt
- PR #4602²⁸¹⁹ - Small module fixes
- PR #4598²⁸²⁰ - Making sure current_executor and service_executor functions are linked into the core library
- PR #4597²⁸²¹ - Adding broadcast_to/broadcast_from to collectives module
- PR #4596²⁸²² - Fix performance regression in block_executor
- PR #4595²⁸²³ - Making sure main.cpp is built as a library if HPX_WITH_DYNAMIC_MAIN=OFF
- PR #4592²⁸²⁴ - Futures module
- PR #4591²⁸²⁵ - Adapting co_await support for C++20
- PR #4590²⁸²⁶ - Adding missing exception test for for_loop()
- PR #4587²⁸²⁷ - Move traits headers to hpx/modulename/traits directory
- PR #4586²⁸²⁸ - Remove Travis CI config
- PR #4585²⁸²⁹ - Update macOS test blacklist
- PR #4584²⁸³⁰ - Attempting to fix missing symbols in stack trace

²⁸⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4615>

²⁸⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4614>

²⁸¹⁰ <https://github.com/TheHPXProject/hpx/pull/4613>

²⁸¹¹ <https://github.com/TheHPXProject/hpx/pull/4611>

²⁸¹² <https://github.com/TheHPXProject/hpx/pull/4610>

²⁸¹³ <https://github.com/TheHPXProject/hpx/pull/4609>

²⁸¹⁴ <https://github.com/TheHPXProject/hpx/pull/4608>

²⁸¹⁵ <https://github.com/TheHPXProject/hpx/pull/4607>

²⁸¹⁶ <https://github.com/TheHPXProject/hpx/pull/4606>

²⁸¹⁷ <https://github.com/TheHPXProject/hpx/pull/4604>

²⁸¹⁸ <https://github.com/TheHPXProject/hpx/pull/4603>

²⁸¹⁹ <https://github.com/TheHPXProject/hpx/pull/4602>

²⁸²⁰ <https://github.com/TheHPXProject/hpx/pull/4598>

²⁸²¹ <https://github.com/TheHPXProject/hpx/pull/4597>

²⁸²² <https://github.com/TheHPXProject/hpx/pull/4596>

²⁸²³ <https://github.com/TheHPXProject/hpx/pull/4595>

²⁸²⁴ <https://github.com/TheHPXProject/hpx/pull/4592>

²⁸²⁵ <https://github.com/TheHPXProject/hpx/pull/4591>

²⁸²⁶ <https://github.com/TheHPXProject/hpx/pull/4590>

²⁸²⁷ <https://github.com/TheHPXProject/hpx/pull/4587>

²⁸²⁸ <https://github.com/TheHPXProject/hpx/pull/4586>

²⁸²⁹ <https://github.com/TheHPXProject/hpx/pull/4585>

²⁸³⁰ <https://github.com/TheHPXProject/hpx/pull/4584>

- [PR #4583](#)²⁸³¹ - Fixing bad static_cast
- [PR #4582](#)²⁸³² - Changing download url for Windows prerequisites to circumvent bandwidth limitations
- [PR #4581](#)²⁸³³ - Adding missing using placeholder::_X
- [PR #4579](#)²⁸³⁴ - Move get_stack_size_name and related functions
- [PR #4575](#)²⁸³⁵ - Excluding unconditional definition of class backtrace from global header
- [PR #4574](#)²⁸³⁶ - Changing return type of hardware_concurrency() to unsigned int
- [PR #4570](#)²⁸³⁷ - Move tests to modules
- [PR #4564](#)²⁸³⁸ - Reshuffle internal targets and add HPX::hpx_no_wrap_main target
- [PR #4563](#)²⁸³⁹ - fix CMake option typo
- [PR #4562](#)²⁸⁴⁰ - Unregister lock earlier to avoid holding it while suspending
- [PR #4561](#)²⁸⁴¹ - Adding test macros supporting custom output stream
- [PR #4560](#)²⁸⁴² - Making sure hash_any::operator()() is linked into core library
- [PR #4559](#)²⁸⁴³ - Fixing compilation if HPX_WITH_THREAD_BACKTRACE_ON_SUSPENSION=On
- [PR #4557](#)²⁸⁴⁴ - Improve spinlock implementation to perform better in high-contention situations
- [PR #4553](#)²⁸⁴⁵ - Fix a runtime_ptr problem at shutdown when apex is enabled
- [PR #4552](#)²⁸⁴⁶ - Add configuration option for making exceptions less noisy
- [PR #4551](#)²⁸⁴⁷ - Clean up thread creation parameters
- [PR #4549](#)²⁸⁴⁸ - Test FetchContent build on GitHub actions
- [PR #4548](#)²⁸⁴⁹ - Fix stack size
- [PR #4545](#)²⁸⁵⁰ - Fix header tests
- [PR #4544](#)²⁸⁵¹ - Fix a typo in sanitizer build
- [PR #4541](#)²⁸⁵² - Add API to check if a thread pool exists
- [PR #4540](#)²⁸⁵³ - Making sure MPI support is enabled if MPI futures are used but networking is disabled

²⁸³¹ <https://github.com/TheHPXProject/hpx/pull/4583>

²⁸³² <https://github.com/TheHPXProject/hpx/pull/4582>

²⁸³³ <https://github.com/TheHPXProject/hpx/pull/4581>

²⁸³⁴ <https://github.com/TheHPXProject/hpx/pull/4579>

²⁸³⁵ <https://github.com/TheHPXProject/hpx/pull/4575>

²⁸³⁶ <https://github.com/TheHPXProject/hpx/pull/4574>

²⁸³⁷ <https://github.com/TheHPXProject/hpx/pull/4570>

²⁸³⁸ <https://github.com/TheHPXProject/hpx/pull/4564>

²⁸³⁹ <https://github.com/TheHPXProject/hpx/pull/4563>

²⁸⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4562>

²⁸⁴¹ <https://github.com/TheHPXProject/hpx/pull/4561>

²⁸⁴² <https://github.com/TheHPXProject/hpx/pull/4560>

²⁸⁴³ <https://github.com/TheHPXProject/hpx/pull/4559>

²⁸⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4557>

²⁸⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4553>

²⁸⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4552>

²⁸⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4551>

²⁸⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4549>

²⁸⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4548>

²⁸⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4545>

²⁸⁵¹ <https://github.com/TheHPXProject/hpx/pull/4544>

²⁸⁵² <https://github.com/TheHPXProject/hpx/pull/4541>

²⁸⁵³ <https://github.com/TheHPXProject/hpx/pull/4540>

- PR #4538²⁸⁵⁴ - Move channel documentation examples to examples directory
- PR #4536²⁸⁵⁵ - Add generic allocator for execution policies
- PR #4534²⁸⁵⁶ - Enable compatibility headers for thread_executors module
- PR #4532²⁸⁵⁷ - Fixing broken url in README.rst
- PR #4531²⁸⁵⁸ - Update scripts
- PR #4530²⁸⁵⁹ - Make sure module API docs show up in correct order
- PR #4529²⁸⁶⁰ - Adding missing template code to module creation script
- PR #4528²⁸⁶¹ - Make sure version module uses HPX's binary dir, not the parent's
- PR #4527²⁸⁶² - Creating actions_base and actions module
- PR #4526²⁸⁶³ - Shared state for cv
- PR #4525²⁸⁶⁴ - Changing sub-name sequencing for experimental namespace
- PR #4524²⁸⁶⁵ - Add API guarantee notes to API reference documentation
- PR #4522²⁸⁶⁶ - Enable and fix deprecation warnings in execution module
- PR #4521²⁸⁶⁷ - Moves more miscellaneous files to modules
- PR #4520²⁸⁶⁸ - Skip execution customization points when executor is known
- PR #4518²⁸⁶⁹ - Module distributed lcos
- PR #4516²⁸⁷⁰ - Fix various builds
- PR #4515²⁸⁷¹ - Replace backslashes by slashes in windows paths
- PR #4514²⁸⁷² - Adding polymorphic_executor
- PR #4512²⁸⁷³ - Adding C++20 jthread and stop_token
- PR #4510²⁸⁷⁴ - Attempt to fix APEX linking in external packages again
- PR #4508²⁸⁷⁵ - Only test pull requests (not all branches) with GitHub actions
- PR #4505²⁸⁷⁶ - Fix duplicate linking in tests (ODR violations)

²⁸⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4538>

²⁸⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4536>

²⁸⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4534>

²⁸⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4532>

²⁸⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4531>

²⁸⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4530>

²⁸⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4529>

²⁸⁶¹ <https://github.com/TheHPXProject/hpx/pull/4528>

²⁸⁶² <https://github.com/TheHPXProject/hpx/pull/4527>

²⁸⁶³ <https://github.com/TheHPXProject/hpx/pull/4526>

²⁸⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4525>

²⁸⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4524>

²⁸⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4522>

²⁸⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4521>

²⁸⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4520>

²⁸⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4518>

²⁸⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4516>

²⁸⁷¹ <https://github.com/TheHPXProject/hpx/pull/4515>

²⁸⁷² <https://github.com/TheHPXProject/hpx/pull/4514>

²⁸⁷³ <https://github.com/TheHPXProject/hpx/pull/4512>

²⁸⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4510>

²⁸⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4508>

²⁸⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4505>

- PR #4504²⁸⁷⁷ - Fix C++ standard handling
- PR #4503²⁸⁷⁸ - Add CMakeLists file check
- PR #4500²⁸⁷⁹ - Fix .clang-format version requirement comment
- PR #4499²⁸⁸⁰ - Attempting to fix hpx_init linking on macOS
- PR #4498²⁸⁸¹ - Fix compatibility of *pool_executor*
- PR #4496²⁸⁸² - Removing superfluous SPDX tags
- PR #4494²⁸⁸³ - Module executors
- PR #4493²⁸⁸⁴ - Pack traversal module
- PR #4492²⁸⁸⁵ - Update copyright year in documentation
- PR #4491²⁸⁸⁶ - Add missing current_executor header
- PR #4490²⁸⁸⁷ - Update GitHub actions configs
- PR #4487²⁸⁸⁸ - Properly dispatch exceptions thrown from hpx_main to be rethrown from hpx::init/hpx::stop
- PR #4486²⁸⁸⁹ - Fixing an initialization order problem
- PR #4485²⁸⁹⁰ - Move miscellaneous files to their rightful modules
- PR #4483²⁸⁹¹ - Clean up imported CMake target naming
- PR #4481²⁸⁹² - Add vcpkg installation instructions
- PR #4479²⁸⁹³ - Add hints to allow to specify MIMALLOC_ROOT
- PR #4478²⁸⁹⁴ - Async modules
- PR #4475²⁸⁹⁵ - Fix rp init changes
- PR #4474²⁸⁹⁶ - Use #pragma once in headers
- PR #4472²⁸⁹⁷ - Add more descriptive error message when using x86 coroutines on non-x86 platforms
- PR #4467²⁸⁹⁸ - Add mimalloc find cmake script
- PR #4465²⁸⁹⁹ - Add thread_executors module

²⁸⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4504>

²⁸⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4503>

²⁸⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4500>

²⁸⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4499>

²⁸⁸¹ <https://github.com/TheHPXProject/hpx/pull/4498>

²⁸⁸² <https://github.com/TheHPXProject/hpx/pull/4496>

²⁸⁸³ <https://github.com/TheHPXProject/hpx/pull/4494>

²⁸⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4493>

²⁸⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4492>

²⁸⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4491>

²⁸⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4490>

²⁸⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4487>

²⁸⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4486>

²⁸⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4485>

²⁸⁹¹ <https://github.com/TheHPXProject/hpx/pull/4483>

²⁸⁹² <https://github.com/TheHPXProject/hpx/pull/4481>

²⁸⁹³ <https://github.com/TheHPXProject/hpx/pull/4479>

²⁸⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4478>

²⁸⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4475>

²⁸⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4474>

²⁸⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4472>

²⁸⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4467>

²⁸⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4465>

- PR #4464²⁹⁰⁰ - Include module
- PR #4462²⁹⁰¹ - Merge hpx_init and hpx_wrap into one static library
- PR #4461²⁹⁰² - Making thread_data test more realistic
- PR #4460²⁹⁰³ - Suppress MPI warnings in version.cpp
- PR #4459²⁹⁰⁴ - Make sure pkgconfig applications link with hpx_init
- PR #4458²⁹⁰⁵ - Added example demonstrating how to create and use a wrapping executor
- PR #4457²⁹⁰⁶ - Fixing execution of thread exit functions
- PR #4456²⁹⁰⁷ - Move backtrace files to debugging module
- PR #4455²⁹⁰⁸ - Move deadlock_detection and maintain_queue_wait_times source files into schedulers module
- PR #4450²⁹⁰⁹ - Fixing compilation with std::filesystem enabled
- PR #4449²⁹¹⁰ - Fixing build system to actually build variant test
- PR #4447²⁹¹¹ - This fixes an obsolete #include
- PR #4446²⁹¹² - Resume tasks where they were suspended
- PR #4444²⁹¹³ - Minor CUDA fixes
- PR #4443²⁹¹⁴ - Add missing tests to CircleCI config
- PR #4442²⁹¹⁵ - Adding a tag to all auto-generated files allowing for tools to visually distinguish those
- PR #4441²⁹¹⁶ - Adding performance counter type information
- PR #4440²⁹¹⁷ - Fixing MSVC build
- PR #4439²⁹¹⁸ - Link HPX::plugin and component privately in hpx_setup_target
- PR #4437²⁹¹⁹ - Adding a test that verifies the problem can be solved using a trait specialization
- PR #4434²⁹²⁰ - Clean up Boost dependencies and copy string algorithms to new module
- PR #4433²⁹²¹ - Fixing compilation issues (!) if MPI parcelport is enabled
- PR #4431²⁹²² - Ignore warnings about name mangling changing

²⁹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4464>

²⁹⁰¹ <https://github.com/TheHPXProject/hpx/pull/4462>

²⁹⁰² <https://github.com/TheHPXProject/hpx/pull/4461>

²⁹⁰³ <https://github.com/TheHPXProject/hpx/pull/4460>

²⁹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4459>

²⁹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4458>

²⁹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4457>

²⁹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4456>

²⁹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4455>

²⁹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4450>

²⁹¹⁰ <https://github.com/TheHPXProject/hpx/pull/4449>

²⁹¹¹ <https://github.com/TheHPXProject/hpx/pull/4447>

²⁹¹² <https://github.com/TheHPXProject/hpx/pull/4446>

²⁹¹³ <https://github.com/TheHPXProject/hpx/pull/4444>

²⁹¹⁴ <https://github.com/TheHPXProject/hpx/pull/4443>

²⁹¹⁵ <https://github.com/TheHPXProject/hpx/pull/4442>

²⁹¹⁶ <https://github.com/TheHPXProject/hpx/pull/4441>

²⁹¹⁷ <https://github.com/TheHPXProject/hpx/pull/4440>

²⁹¹⁸ <https://github.com/TheHPXProject/hpx/pull/4439>

²⁹¹⁹ <https://github.com/TheHPXProject/hpx/pull/4437>

²⁹²⁰ <https://github.com/TheHPXProject/hpx/pull/4434>

²⁹²¹ <https://github.com/TheHPXProject/hpx/pull/4433>

²⁹²² <https://github.com/TheHPXProject/hpx/pull/4431>

- PR #4430²⁹²³ - Add performance_counters module
- PR #4428²⁹²⁴ - Don't add compatibility headers to module API reference
- PR #4426²⁹²⁵ - Add currently failing tests on GitHub actions to blacklist
- PR #4425²⁹²⁶ - Clean up and correct minimum required versions
- PR #4424²⁹²⁷ - Making sure hpx.lock_detection=0 works as advertized
- PR #4421²⁹²⁸ - Making sure interval time stops underlying timer thread on termination
- PR #4417²⁹²⁹ - Adding serialization support for std::variant (if available) and std::tuple
- PR #4415²⁹³⁰ - Partially reverting changes applied by PR 4373
- PR #4414²⁹³¹ - Added documentation for the compiler-wrapper script hpxcxx.in in creating_hpx_projects.rst
- PR #4413²⁹³² - Merging from V1.4.1 release
- PR #4412²⁹³³ - Making sure to issue a warning if a file specified using -hpx:options-file is not found
- PR #4411²⁹³⁴ - Make test specific to HPX_WITH_SHARED_PRIORITY_SCHEDULER
- PR #4407²⁹³⁵ - Adding minimal MPI executor
- PR #4405²⁹³⁶ - Fix cross pool injection test, use default scheduler as fallback
- PR #4404²⁹³⁷ - Fix a race condition and clean-up usage of scheduler mode
- PR #4399²⁹³⁸ - Add more threading modules
- PR #4398²⁹³⁹ - Add CODEOWNERS file
- PR #4395²⁹⁴⁰ - Adding a parameter to auto_chunk_size allowing to control the amount of iterations to measure
- PR #4393²⁹⁴¹ - Use appropriate cache-line size defaults for different platforms
- PR #4391²⁹⁴² - Fixing use of allocator for C++20
- PR #4390²⁹⁴³ - Making -hpx:help behavior consistent
- PR #4388²⁹⁴⁴ - Change the resource partitioner initialization
- PR #4387²⁹⁴⁵ - Fix roll_release.sh

²⁹²³ <https://github.com/TheHPXProject/hpx/pull/4430>

²⁹²⁴ <https://github.com/TheHPXProject/hpx/pull/4428>

²⁹²⁵ <https://github.com/TheHPXProject/hpx/pull/4426>

²⁹²⁶ <https://github.com/TheHPXProject/hpx/pull/4425>

²⁹²⁷ <https://github.com/TheHPXProject/hpx/pull/4424>

²⁹²⁸ <https://github.com/TheHPXProject/hpx/pull/4421>

²⁹²⁹ <https://github.com/TheHPXProject/hpx/pull/4417>

²⁹³⁰ <https://github.com/TheHPXProject/hpx/pull/4415>

²⁹³¹ <https://github.com/TheHPXProject/hpx/pull/4414>

²⁹³² <https://github.com/TheHPXProject/hpx/pull/4413>

²⁹³³ <https://github.com/TheHPXProject/hpx/pull/4412>

²⁹³⁴ <https://github.com/TheHPXProject/hpx/pull/4411>

²⁹³⁵ <https://github.com/TheHPXProject/hpx/pull/4407>

²⁹³⁶ <https://github.com/TheHPXProject/hpx/pull/4405>

²⁹³⁷ <https://github.com/TheHPXProject/hpx/pull/4404>

²⁹³⁸ <https://github.com/TheHPXProject/hpx/pull/4399>

²⁹³⁹ <https://github.com/TheHPXProject/hpx/pull/4398>

²⁹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4395>

²⁹⁴¹ <https://github.com/TheHPXProject/hpx/pull/4393>

²⁹⁴² <https://github.com/TheHPXProject/hpx/pull/4391>

²⁹⁴³ <https://github.com/TheHPXProject/hpx/pull/4390>

²⁹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4388>

²⁹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4387>

- PR #4386²⁹⁴⁶ - Add warning messages for using thread binding options on macOS
- PR #4385²⁹⁴⁷ - Cuda futures
- PR #4384²⁹⁴⁸ - Make enabling dynamic hpx_main on non-Linux systems a configuration error
- PR #4383²⁹⁴⁹ - Use configure_file for HPXCacheVariables.cmake
- PR #4382²⁹⁵⁰ - Update spellchecking whitelist and fix more typos
- PR #4380²⁹⁵¹ - Add a helper function to get a future from a cuda stream
- PR #4379²⁹⁵² - Add Windows and macOS CI with GitHub actions
- PR #4378²⁹⁵³ - Change C++ standard handling
- PR #4377²⁹⁵⁴ - Remove Python scripts
- PR #4374²⁹⁵⁵ - Adding overload for *hpx::init/hpx::start* for use with resource partitioner
- PR #4373²⁹⁵⁶ - Adding test that verifies for 4369 to be fixed
- PR #4372²⁹⁵⁷ - Another attempt at fixing the integral mismatch and conversion warnings
- PR #4370²⁹⁵⁸ - Doc updates quick start
- PR #4368²⁹⁵⁹ - Add a whitelist of words for weird spelling suggestions
- PR #4366²⁹⁶⁰ - Suppress or fix clang-tidy-9 warnings
- PR #4365²⁹⁶¹ - Removing more Boost dependencies
- PR #4363²⁹⁶² - Update clang-format config file for version 9
- PR #4362²⁹⁶³ - Fix indices typo
- PR #4361²⁹⁶⁴ - Boost cleanup
- PR #4360²⁹⁶⁵ - Move plugins
- PR #4358²⁹⁶⁶ - Doc updates; generating documentation. Will likely need heavy editing.
- PR #4356²⁹⁶⁷ - Remove some minor unused and unnecessary Boost includes
- PR #4355²⁹⁶⁸ - Fix spellcheck step in CircleCI config

²⁹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4386>

²⁹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4385>

²⁹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4384>

²⁹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4383>

²⁹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4382>

²⁹⁵¹ <https://github.com/TheHPXProject/hpx/pull/4380>

²⁹⁵² <https://github.com/TheHPXProject/hpx/pull/4379>

²⁹⁵³ <https://github.com/TheHPXProject/hpx/pull/4378>

²⁹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4377>

²⁹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4374>

²⁹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4373>

²⁹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4372>

²⁹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4370>

²⁹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4368>

²⁹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4366>

²⁹⁶¹ <https://github.com/TheHPXProject/hpx/pull/4365>

²⁹⁶² <https://github.com/TheHPXProject/hpx/pull/4363>

²⁹⁶³ <https://github.com/TheHPXProject/hpx/pull/4362>

²⁹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4361>

²⁹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4360>

²⁹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4358>

²⁹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4356>

²⁹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4355>

- PR #4354²⁹⁶⁹ - Lightweight utility to hold a pack as members
- PR #4352²⁹⁷⁰ - Minor fixes to the C++ standard detection for MSVC
- PR #4351²⁹⁷¹ - Move generated documentation to hpx-docs repo
- PR #4347²⁹⁷² - Add cmake policy - CMP0074
- PR #4346²⁹⁷³ - Remove file committed by mistake
- PR #4342²⁹⁷⁴ - Remove HCC and SYCL options from CMakeLists.txt
- PR #4341²⁹⁷⁵ - Fix launch process test with APEX enabled
- PR #4340²⁹⁷⁶ - Testing Cirrus CI
- PR #4339²⁹⁷⁷ - Post 1.4.0 updates
- PR #4338²⁹⁷⁸ - Spelling corrections and CircleCI spell check
- PR #4333²⁹⁷⁹ - Flatten bound callables
- PR #4332²⁹⁸⁰ - This is a collection of mostly minor (cleanup) fixes
- PR #4331²⁹⁸¹ - This adds the missing tests for `async_colocated` and `async_continue_colocated`
- PR #4330²⁹⁸² - Remove `HPX.Compute` host default_executor
- PR #4328²⁹⁸³ - Generate global header for `basic_execution` module
- PR #4327²⁹⁸⁴ - Use `INTERNAL_FLAGS` option for all examples and components
- PR #4326²⁹⁸⁵ - Usage of temporary allocator in assignment operator of `compute::vector`
- PR #4325²⁹⁸⁶ - Use `hpx::threads::get_cache_line_size` in `prefetching.hpp`
- PR #4324²⁹⁸⁷ - Enable compatibility headers option for execution module
- PR #4316²⁹⁸⁸ - Add clang format indentppdirectives
- PR #4313²⁹⁸⁹ - Introduce `index_pack` alias to pack of `size_t`
- PR #4312²⁹⁹⁰ - Fixing compatibility header for `pack.hpp`
- PR #4311²⁹⁹¹ - Dataflow annotations for APEX

²⁹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4354>

²⁹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4352>

²⁹⁷¹ <https://github.com/TheHPXProject/hpx/pull/4351>

²⁹⁷² <https://github.com/TheHPXProject/hpx/pull/4347>

²⁹⁷³ <https://github.com/TheHPXProject/hpx/pull/4346>

²⁹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4342>

²⁹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4341>

²⁹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4340>

²⁹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4339>

²⁹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4338>

²⁹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4333>

²⁹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4332>

²⁹⁸¹ <https://github.com/TheHPXProject/hpx/pull/4331>

²⁹⁸² <https://github.com/TheHPXProject/hpx/pull/4330>

²⁹⁸³ <https://github.com/TheHPXProject/hpx/pull/4328>

²⁹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4327>

²⁹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4326>

²⁹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4325>

²⁹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4324>

²⁹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4316>

²⁹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4313>

²⁹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4312>

²⁹⁹¹ <https://github.com/TheHPXProject/hpx/pull/4311>

- PR #4309²⁹⁹² - Update launching_and_configuring_hpx_applications.rst
- PR #4306²⁹⁹³ - Fix schedule hint not being taken from executor
- PR #4305²⁹⁹⁴ - Implementing *hpx::functional::tag_invoke*
- PR #4304²⁹⁹⁵ - Improve pack support utilities
- PR #4303²⁹⁹⁶ - Remove errors module dependency on datastructures
- PR #4301²⁹⁹⁷ - Clean up thread executors
- PR #4294²⁹⁹⁸ - Logging revamp
- PR #4292²⁹⁹⁹ - Remove SPDX tag from Boost License file to allow for github to recognize it
- PR #4291³⁰⁰⁰ - Add format support for std::tm
- PR #4290³⁰⁰¹ - Simplify compatible tuples check
- PR #4288³⁰⁰² - A lightweight take on boost::lexical_cast
- PR #4287³⁰⁰³ - Forking boost::lexical_cast as a new module
- PR #4277³⁰⁰⁴ - MPI_futures
- PR #4270³⁰⁰⁵ - Refactor future implementation
- PR #4265³⁰⁰⁶ - Threading module
- PR #4259³⁰⁰⁷ - Module naming base
- PR #4251³⁰⁰⁸ - Local workrequesting scheduler
- PR #4250³⁰⁰⁹ - Inline execution of scoped tasks, if possible
- PR #4247³⁰¹⁰ - Add execution in module headers
- PR #4246³⁰¹¹ - Expose CMake targets officially
- PR #4239³⁰¹² - Doc updates miscellaneous (partially completed during Google Season of Docs)
- PR #4233³⁰¹³ - Remove project() from modules + fix CMAKE_SOURCE_DIR issue
- PR #4231³⁰¹⁴ - Module local lcos

²⁹⁹² <https://github.com/TheHPXProject/hpx/pull/4309>

²⁹⁹³ <https://github.com/TheHPXProject/hpx/pull/4306>

²⁹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4305>

²⁹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4304>

²⁹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4303>

²⁹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4301>

²⁹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4294>

²⁹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4292>

³⁰⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4291>

³⁰⁰¹ <https://github.com/TheHPXProject/hpx/pull/4290>

³⁰⁰² <https://github.com/TheHPXProject/hpx/pull/4288>

³⁰⁰³ <https://github.com/TheHPXProject/hpx/pull/4287>

³⁰⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4277>

³⁰⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4270>

³⁰⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4265>

³⁰⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4259>

³⁰⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4251>

³⁰⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4250>

³⁰¹⁰ <https://github.com/TheHPXProject/hpx/pull/4247>

³⁰¹¹ <https://github.com/TheHPXProject/hpx/pull/4246>

³⁰¹² <https://github.com/TheHPXProject/hpx/pull/4239>

³⁰¹³ <https://github.com/TheHPXProject/hpx/pull/4233>

³⁰¹⁴ <https://github.com/TheHPXProject/hpx/pull/4231>

- [PR #4207](#)³⁰¹⁵ - Command line handling module
- [PR #4206](#)³⁰¹⁶ - Runtime configuration module
- [PR #4141](#)³⁰¹⁷ - Doc updates examples local to remote (partially completed during Google Season of Docs)
- [PR #4091](#)³⁰¹⁸ - Split runtime into local and distributed parts
- [PR #4017](#)³⁰¹⁹ - Require C++14

HPX V1.4.1 (Feb 12, 2020)

General changes

This is a bugfix release. It contains the following changes:

- Fix compilation issues on Windows, macOS, FreeBSD, and with gcc 10
- Install missing pdb files on Windows
- Allow running tests using an installed version of *HPX*
- Skip MPI finalization if HPX has not initialized MPI
- Give a hard error when attempting to use IO counters on Windows

Closed issues

- [Issue #4320](#)³⁰²⁰ - HPX 1.4.0 does not compile with gcc 10
- [Issue #4336](#)³⁰²¹ - Building HPX 1.4.0 with IO Counters breaks (Windows)
- [Issue #4334](#)³⁰²² - HPX Debug and RelWithDebinfo builds on Windows not installing .pdb files
- [Issue #4322](#)³⁰²³ - Undefine VT1 and VT2 after boost includes
- [Issue #4314](#)³⁰²⁴ - Compile error on 1.4.0
- [Issue #4307](#)³⁰²⁵ - `ld: error: duplicate symbol: freebsd_envron`

³⁰¹⁵ <https://github.com/TheHPXProject/hpx/pull/4207>

³⁰¹⁶ <https://github.com/TheHPXProject/hpx/pull/4206>

³⁰¹⁷ <https://github.com/TheHPXProject/hpx/pull/4141>

³⁰¹⁸ <https://github.com/TheHPXProject/hpx/pull/4091>

³⁰¹⁹ <https://github.com/TheHPXProject/hpx/pull/4017>

³⁰²⁰ <https://github.com/TheHPXProject/hpx/issues/4320>

³⁰²¹ <https://github.com/TheHPXProject/hpx/issues/4336>

³⁰²² <https://github.com/TheHPXProject/hpx/issues/4334>

³⁰²³ <https://github.com/TheHPXProject/hpx/issues/4322>

³⁰²⁴ <https://github.com/TheHPXProject/hpx/issues/4314>

³⁰²⁵ <https://github.com/TheHPXProject/hpx/issues/4307>

Closed pull requests

- [PR #4376](#)³⁰²⁶ - Attempt to fix some test build errors on Windows
- [PR #4357](#)³⁰²⁷ - Adding missing `#includes` to fix gcc V10 linker problems
- [PR #4353](#)³⁰²⁸ - Skip `MPI_Finalize` if `MPI_Init` is not called from HPX
- [PR #4343](#)³⁰²⁹ - Give a hard error if IO counters are enabled on non-Linux systems
- [PR #4337](#)³⁰³⁰ - Installing `pdb` files on Windows
- [PR #4335](#)³⁰³¹ - Adding capability to `buildsystem` to use an installed version of HPX
- [PR #4315](#)³⁰³² - Forcing exported symbols from `composable_guard` to be linked into core library
- [PR #4310](#)³⁰³³ - Remove environment handling from `exception.cpp`

HPX V1.4.0 (January 15, 2020)

General changes

- We have added the collectives `all_to_all` and `all_reduce`.
- We have added APIs for resiliency, which allows replication and replay for failed tasks. See the *documentation* for more details.
- Components can now be checkpointed.
- Performance improvements to schedulers and coroutines. A significant change is the addition of stackless coroutines. These are to be used for tasks that do not need to be suspended and can reduce overheads noticeably in applications with short tasks. A stackless coroutine can be created with the new `stack_size_thread_stacksize_nostack`.
- We have added an implementation of `unique_any`, which is a non-copyable version of `any`.
- The `shared_priority_queue_scheduler` has been improved. It now has lower overheads than the default scheduler in many situations. Unlike the default scheduler it fully supports NUMA scheduling hints. Enable it with the command line option `--hpx:queuing=shared-priority`. This scheduler should still be considered experimental, but its use is encouraged in real applications to help us make it production ready.
- We have added the performance counters `background-receive-duration` and `background-receive-overhead` for inspecting the time and overhead spent on receiving parcels in the background.
- Compilation time has been further improved when `HPX_WITH_NETWORKING=OFF`.
- We no longer require compiled Boost dependencies in certain configurations. This requires at least Boost 1.70, compiling on x86 with GCC 9, clang (libc++) 9, or VS2019 in C++17 mode. The dependency on `Boost.Filesystem` can explicitly be turned on with `HPX_FILESYSTEM_WITH_BOOST_FILESYSTEM_COMPATIBILITY=ON` (it is off by default if the standard library supports `std::filesystem`). `Boost.ProgramOptions` has been copied into the HPX repository. We have a compatibility layer for users who must explicitly use

³⁰²⁶ <https://github.com/TheHPXProject/hpx/pull/4376>

³⁰²⁷ <https://github.com/TheHPXProject/hpx/pull/4357>

³⁰²⁸ <https://github.com/TheHPXProject/hpx/pull/4353>

³⁰²⁹ <https://github.com/TheHPXProject/hpx/pull/4343>

³⁰³⁰ <https://github.com/TheHPXProject/hpx/pull/4337>

³⁰³¹ <https://github.com/TheHPXProject/hpx/pull/4335>

³⁰³² <https://github.com/TheHPXProject/hpx/pull/4315>

³⁰³³ <https://github.com/TheHPXProject/hpx/pull/4310>

Boost.ProgramOptions instead of the ProgramOptions provided by HPX. To remove the dependency HPX_PROGRAM_OPTIONS_WITH_BOOST_PROGRAM_OPTIONS_COMPATIBILITY must be explicitly set to OFF. This option will be removed in a future release. We have also removed several other header-only dependencies on Boost.

- It is now possible to use the process affinity mask set by tools like `numactl` and various batch environments with the command line option `--hpx:use-process-mask`. Enabling this option implies `--hpx:ignore-batch-env`.
- It is now possible to create standalone thread pools without starting the runtime. See the `standalone_thread_pool_executor.cpp` test in the `execution` module for an example.
- Tasks annotated with `hpx::util::annotated_function` now have their correct name when using APEX to generate OTF2 files.
- Cloning of APEX was defective in previous releases (it required manual intervention to check out the correct tag or branch). This has been fixed.
- The option `HPX_WITH_MORE_THAN_64_THREADS` is now ignored and will be removed in a future release. The value is instead derived directly from `HPX_WITH_MAX_CPU_COUNT` option.
- We have deprecated compiling in C++11 mode. The next release will require a C++14 capable compiler.
- We have deprecated support for the Vc library. This option will be replaced with SIMD support from the standard library in a future release.
- We have significantly refactored our CMake setup. This is intended to be a non-breaking change and will allow for using HPX through CMake targets in the future.
- We have continued modularizing the HPX library. In the process we have rearranged many header files into module-specific directories. All moved headers have compatibility headers which forward from the old location to the new location, together with a deprecation warning. The compatibility headers will eventually be removed.
- We now enforce formatting with `clang-format` on the majority of our source files.
- We have added SPDX license tags to all files.
- Many bugfixes.

Breaking changes

- The `HPX_WITH_THREAD_COMPATIBILITY` option and the associated compatibility layer has been removed.
- The `HPX_WITH_INCLUSIVE_SCAN_COMPATIBILITY` option and the associated compatibility layer has been removed.
- The `HPX_WITH_UNWRAPPED_COMPATIBILITY` option and the associated compatibility layer has been removed.

Closed issues

- [Issue #4282](#)³⁰³⁴ - Build Issues with Release on Windows
- [Issue #4278](#)³⁰³⁵ - Build Issues with CMake 3.14.4
- [Issue #4273](#)³⁰³⁶ - Clients of HPX 1.4.0-rc2 with APEX are not linked to `libhpx-apex`
- [Issue #4269](#)³⁰³⁷ - Building HPX 1.4.0-rc2 with support for APEX fails

³⁰³⁴ <https://github.com/TheHPXProject/hpx/issues/4282>

³⁰³⁵ <https://github.com/TheHPXProject/hpx/issues/4278>

³⁰³⁶ <https://github.com/TheHPXProject/hpx/issues/4273>

³⁰³⁷ <https://github.com/TheHPXProject/hpx/issues/4269>

- Issue #4263³⁰³⁸ - Compilation fail on latest master
- Issue #4232³⁰³⁹ - Configure of HPX project using CMake FetchContent fails
- Issue #4223³⁰⁴⁰ - “Re-using the main() function as the main HPX entry point” doesn’t work
- Issue #4220³⁰⁴¹ - HPX won’t compile - error building resource_partitioner
- Issue #4215³⁰⁴² - HPX 1.4.0rc1 does not link on s390x
- Issue #4204³⁰⁴³ - Trouble compiling HPX with Intel compiler
- Issue #4199³⁰⁴⁴ - Refactor APEX to eliminate circular dependency
- Issue #4187³⁰⁴⁵ - HPX can’t build on OSX
- Issue #4185³⁰⁴⁶ - Simple debug output for development
- Issue #4182³⁰⁴⁷ - @HPX_CONF_PREFIX@ is the empty string
- Issue #4169³⁰⁴⁸ - HPX won’t build with APEX
- Issue #4163³⁰⁴⁹ - Add back HPX_LIBRARIES and HPX_INCLUDE_DIRS
- Issue #4161³⁰⁵⁰ - It should be possible to call find_package(HPX) multiple times
- Issue #4155³⁰⁵¹ - get_self_id() for stackless threads returns invalid_thread_id
- Issue #4151³⁰⁵² - build error with MPI code
- Issue #4150³⁰⁵³ - hpx won’t build on POWER9 with clang 8
- Issue #4148³⁰⁵⁴ - cacheline_data delivers poor performance with C++17 compared to C++14
- Issue #4144³⁰⁵⁵ - target general in HPX_LIBRARIES does not exist
- Issue #4134³⁰⁵⁶ - CMake Error when -DHPX_WITH_HPXMP=ON
- Issue #4132³⁰⁵⁷ - parallel fill leaves elements unfilled
- Issue #4123³⁰⁵⁸ - PAPI performance counters are inaccessible
- Issue #4118³⁰⁵⁹ - static_chunk_size is not obeyed in scan algorithms
- Issue #4115³⁰⁶⁰ - dependency chaining error with APEX

³⁰³⁸ <https://github.com/TheHPXProject/hpx/issues/4263>

³⁰³⁹ <https://github.com/TheHPXProject/hpx/issues/4232>

³⁰⁴⁰ <https://github.com/TheHPXProject/hpx/issues/4223>

³⁰⁴¹ <https://github.com/TheHPXProject/hpx/issues/4220>

³⁰⁴² <https://github.com/TheHPXProject/hpx/issues/4215>

³⁰⁴³ <https://github.com/TheHPXProject/hpx/issues/4204>

³⁰⁴⁴ <https://github.com/TheHPXProject/hpx/issues/4199>

³⁰⁴⁵ <https://github.com/TheHPXProject/hpx/issues/4187>

³⁰⁴⁶ <https://github.com/TheHPXProject/hpx/issues/4185>

³⁰⁴⁷ <https://github.com/TheHPXProject/hpx/issues/4182>

³⁰⁴⁸ <https://github.com/TheHPXProject/hpx/issues/4169>

³⁰⁴⁹ <https://github.com/TheHPXProject/hpx/issues/4163>

³⁰⁵⁰ <https://github.com/TheHPXProject/hpx/issues/4161>

³⁰⁵¹ <https://github.com/TheHPXProject/hpx/issues/4155>

³⁰⁵² <https://github.com/TheHPXProject/hpx/issues/4151>

³⁰⁵³ <https://github.com/TheHPXProject/hpx/issues/4150>

³⁰⁵⁴ <https://github.com/TheHPXProject/hpx/issues/4148>

³⁰⁵⁵ <https://github.com/TheHPXProject/hpx/issues/4144>

³⁰⁵⁶ <https://github.com/TheHPXProject/hpx/issues/4134>

³⁰⁵⁷ <https://github.com/TheHPXProject/hpx/issues/4132>

³⁰⁵⁸ <https://github.com/TheHPXProject/hpx/issues/4123>

³⁰⁵⁹ <https://github.com/TheHPXProject/hpx/issues/4118>

³⁰⁶⁰ <https://github.com/TheHPXProject/hpx/issues/4115>

- [Issue #4107](#)³⁰⁶¹ - Initializing runtime without entry point function and command line arguments
- [Issue #4105](#)³⁰⁶² - Bug in `hpx:bind=numa-balanced`
- [Issue #4101](#)³⁰⁶³ - Bound tasks
- [Issue #4100](#)³⁰⁶⁴ - Add SPDX identifier to all files
- [Issue #4085](#)³⁰⁶⁵ - `hpx_topology` library should depend on `hwloc`
- [Issue #4067](#)³⁰⁶⁶ - HPX fails to build on macOS
- [Issue #4056](#)³⁰⁶⁷ - Building without thread manager idle backoff fails
- [Issue #4052](#)³⁰⁶⁸ - Enforce `clang-format` style for modules
- [Issue #4032](#)³⁰⁶⁹ - Simple hello world fails to launch correctly
- [Issue #4030](#)³⁰⁷⁰ - Allow threads to skip context switching
- [Issue #4029](#)³⁰⁷¹ - Add support for `mimalloc`
- [Issue #4005](#)³⁰⁷² - Can't link HPX when APEX enabled
- [Issue #4002](#)³⁰⁷³ - Missing header for algorithm module
- [Issue #3989](#)³⁰⁷⁴ - conversion from `long` to `unsigned int` requires a narrowing conversion on MSVC
- [Issue #3958](#)³⁰⁷⁵ - `/statistics/average@` perf counter can't be created
- [Issue #3953](#)³⁰⁷⁶ - CMake errors from `HPX_AddPseudoDependencies`
- [Issue #3941](#)³⁰⁷⁷ - CMake error for APEX install target
- [Issue #3940](#)³⁰⁷⁸ - Convert pseudo-doxygen function documentation into actual doxygen documentation
- [Issue #3935](#)³⁰⁷⁹ - HPX compiler match too strict?
- [Issue #3929](#)³⁰⁸⁰ - Buildbot failures on latest HPX stable
- [Issue #3912](#)³⁰⁸¹ - I recommend publishing a version that does not depend on the boost library
- [Issue #3890](#)³⁰⁸² - `hpx.ini` not working
- [Issue #3883](#)³⁰⁸³ - cuda compilation fails because of `-faligned-new`

³⁰⁶¹ <https://github.com/TheHPXProject/hpx/issues/4107>

³⁰⁶² <https://github.com/TheHPXProject/hpx/issues/4105>

³⁰⁶³ <https://github.com/TheHPXProject/hpx/issues/4101>

³⁰⁶⁴ <https://github.com/TheHPXProject/hpx/issues/4100>

³⁰⁶⁵ <https://github.com/TheHPXProject/hpx/issues/4085>

³⁰⁶⁶ <https://github.com/TheHPXProject/hpx/issues/4067>

³⁰⁶⁷ <https://github.com/TheHPXProject/hpx/issues/4056>

³⁰⁶⁸ <https://github.com/TheHPXProject/hpx/issues/4052>

³⁰⁶⁹ <https://github.com/TheHPXProject/hpx/issues/4032>

³⁰⁷⁰ <https://github.com/TheHPXProject/hpx/issues/4030>

³⁰⁷¹ <https://github.com/TheHPXProject/hpx/issues/4029>

³⁰⁷² <https://github.com/TheHPXProject/hpx/issues/4005>

³⁰⁷³ <https://github.com/TheHPXProject/hpx/issues/4002>

³⁰⁷⁴ <https://github.com/TheHPXProject/hpx/issues/3989>

³⁰⁷⁵ <https://github.com/TheHPXProject/hpx/issues/3958>

³⁰⁷⁶ <https://github.com/TheHPXProject/hpx/issues/3953>

³⁰⁷⁷ <https://github.com/TheHPXProject/hpx/issues/3941>

³⁰⁷⁸ <https://github.com/TheHPXProject/hpx/issues/3940>

³⁰⁷⁹ <https://github.com/TheHPXProject/hpx/issues/3935>

³⁰⁸⁰ <https://github.com/TheHPXProject/hpx/issues/3929>

³⁰⁸¹ <https://github.com/TheHPXProject/hpx/issues/3912>

³⁰⁸² <https://github.com/TheHPXProject/hpx/issues/3890>

³⁰⁸³ <https://github.com/TheHPXProject/hpx/issues/3883>

- Issue #3879³⁰⁸⁴ - HPX fails to configure with `-DHPX_WITH_TESTS=OFF`
- Issue #3871³⁰⁸⁵ - `dataflow` does not support void allocators
- Issue #3867³⁰⁸⁶ - Latest HTML docs placed in wrong directory on GitHub pages
- Issue #3866³⁰⁸⁷ - Make sure all tests use `HPX_TEST*` macros and not `HPX_ASSERT`
- Issue #3857³⁰⁸⁸ - CMake all-keyword or all-plain for `target_link_libraries`
- Issue #3856³⁰⁸⁹ - `hpx_setup_target` adds rogue flags
- Issue #3850³⁰⁹⁰ - HPX fails to build on POWER8 with Clang7
- Issue #3848³⁰⁹¹ - Remove `lva` member from `thread_init_data`
- Issue #3838³⁰⁹² - `hpx::parallel::count/count_if` failing tests
- Issue #3651³⁰⁹³ - `hpx::parallel::transform_reduce` with non const reference as lambda parameter
- Issue #3560³⁰⁹⁴ - Apex integration with HPX not working properly
- Issue #3322³⁰⁹⁵ - No warning when mixing debug/release builds

Closed pull requests

- PR #4300³⁰⁹⁶ - Checks for `MPI_Init` being called twice
- PR #4299³⁰⁹⁷ - Small CMake fixes
- PR #4298³⁰⁹⁸ - Remove extra call to annotate function that messes up traces
- PR #4296³⁰⁹⁹ - Fixing collectives locking problem
- PR #4295³¹⁰⁰ - Do not check `LICENSE_1_0.txt` for inspect violations
- PR #4293³¹⁰¹ - Applying two small changes fixing carious MSVC/Windows problems
- PR #4285³¹⁰² - Delete `apex.hpp`
- PR #4276³¹⁰³ - Disable doxygen generation for `hpx/debugging/print.hpp` file
- PR #4275³¹⁰⁴ - Make sure APEX is linked to even when not explicitly referenced
- PR #4272³¹⁰⁵ - Fix pushing of documentation

³⁰⁸⁴ <https://github.com/TheHPXProject/hpx/issues/3879>

³⁰⁸⁵ <https://github.com/TheHPXProject/hpx/issues/3871>

³⁰⁸⁶ <https://github.com/TheHPXProject/hpx/issues/3867>

³⁰⁸⁷ <https://github.com/TheHPXProject/hpx/issues/3866>

³⁰⁸⁸ <https://github.com/TheHPXProject/hpx/issues/3857>

³⁰⁸⁹ <https://github.com/TheHPXProject/hpx/issues/3856>

³⁰⁹⁰ <https://github.com/TheHPXProject/hpx/issues/3850>

³⁰⁹¹ <https://github.com/TheHPXProject/hpx/issues/3848>

³⁰⁹² <https://github.com/TheHPXProject/hpx/issues/3838>

³⁰⁹³ <https://github.com/TheHPXProject/hpx/issues/3651>

³⁰⁹⁴ <https://github.com/TheHPXProject/hpx/issues/3560>

³⁰⁹⁵ <https://github.com/TheHPXProject/hpx/issues/3322>

³⁰⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4300>

³⁰⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4299>

³⁰⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4298>

³⁰⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4296>

³¹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4295>

³¹⁰¹ <https://github.com/TheHPXProject/hpx/pull/4293>

³¹⁰² <https://github.com/TheHPXProject/hpx/pull/4285>

³¹⁰³ <https://github.com/TheHPXProject/hpx/pull/4276>

³¹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4275>

³¹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4272>

- PR #4271³¹⁰⁶ - Updating APEX tag, don't create new task_wrapper on operator= of hpx_thread object
- PR #4268³¹⁰⁷ - Testing for noexcept function specializations in C++11/14 mode
- PR #4267³¹⁰⁸ - Fixing MSVC warning
- PR #4266³¹⁰⁹ - Make sure macOS Travis CI fails if build step fails
- PR #4264³¹¹⁰ - Clean up compatibility header options
- PR #4262³¹¹¹ - Cleanup modules CMakeLists.txt
- PR #4261³¹¹² - Fixing HPX/APEX linking and dependencies for external projects like Phylanx
- PR #4260³¹¹³ - Fix docs compilation problems
- PR #4258³¹¹⁴ - Couple of minor changes
- PR #4257³¹¹⁵ - Fix apex annotation for async dispatch
- PR #4256³¹¹⁶ - Remove lambdas from assert expressions
- PR #4255³¹¹⁷ - Ignoring lock in all_to_all and all_reduce
- PR #4254³¹¹⁸ - Adding action specializations for noexcept functions
- PR #4253³¹¹⁹ - Move partlit.hpp to affinity module
- PR #4252³¹²⁰ - Make mismatching build types a hard error in CMake
- PR #4249³¹²¹ - Scheduler improvement
- PR #4248³¹²² - update hpxmp tag to v0.3.0
- PR #4245³¹²³ - Adding high performance channels
- PR #4244³¹²⁴ - Ignore lock in ignore_while_locked_1485 test
- PR #4243³¹²⁵ - Fix PAPI command line option documentation
- PR #4242³¹²⁶ - Ignore lock in target_distribution_policy
- PR #4241³¹²⁷ - Fix start_stop_callbacks test
- PR #4240³¹²⁸ - Mostly fix clang CUDA compilation

³¹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4271>

³¹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4268>

³¹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4267>

³¹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4266>

³¹¹⁰ <https://github.com/TheHPXProject/hpx/pull/4264>

³¹¹¹ <https://github.com/TheHPXProject/hpx/pull/4262>

³¹¹² <https://github.com/TheHPXProject/hpx/pull/4261>

³¹¹³ <https://github.com/TheHPXProject/hpx/pull/4260>

³¹¹⁴ <https://github.com/TheHPXProject/hpx/pull/4258>

³¹¹⁵ <https://github.com/TheHPXProject/hpx/pull/4257>

³¹¹⁶ <https://github.com/TheHPXProject/hpx/pull/4256>

³¹¹⁷ <https://github.com/TheHPXProject/hpx/pull/4255>

³¹¹⁸ <https://github.com/TheHPXProject/hpx/pull/4254>

³¹¹⁹ <https://github.com/TheHPXProject/hpx/pull/4253>

³¹²⁰ <https://github.com/TheHPXProject/hpx/pull/4252>

³¹²¹ <https://github.com/TheHPXProject/hpx/pull/4249>

³¹²² <https://github.com/TheHPXProject/hpx/pull/4248>

³¹²³ <https://github.com/TheHPXProject/hpx/pull/4245>

³¹²⁴ <https://github.com/TheHPXProject/hpx/pull/4244>

³¹²⁵ <https://github.com/TheHPXProject/hpx/pull/4243>

³¹²⁶ <https://github.com/TheHPXProject/hpx/pull/4242>

³¹²⁷ <https://github.com/TheHPXProject/hpx/pull/4241>

³¹²⁸ <https://github.com/TheHPXProject/hpx/pull/4240>

- PR #4238³¹²⁹ - Google Season of Docs updates to documentation; grammar edits.
- PR #4237³¹³⁰ - fixing annotated task to use the name, not the desc
- PR #4236³¹³¹ - Move module print summary to modules
- PR #4235³¹³² - Don't use alignas in cache_{aligned,line}_data
- PR #4234³¹³³ - Add basic overview sentence to all modules
- PR #4230³¹³⁴ - Add OS X builds to Travis CI
- PR #4229³¹³⁵ - Remove leftover queue compatibility checks
- PR #4226³¹³⁶ - Fixing APEX shutdown by explicitly shutting down throttling
- PR #4225³¹³⁷ - Allow CMAKE_INSTALL_PREFIX to be a relative path
- PR #4224³¹³⁸ - Deprecate verbs parcelport
- PR #4222³¹³⁹ - Update register_{thread,work} namespaces
- PR #4221³¹⁴⁰ - Changing HPX_GCC_VERSION check from 70000 to 70300
- PR #4218³¹⁴¹ - Google Season of Docs updates to documentation; grammar edits.
- PR #4217³¹⁴² - Google Season of Docs updates to documentation; grammar edits.
- PR #4216³¹⁴³ - Fixing gcc warning on 32bit platforms (integer truncation)
- PR #4214³¹⁴⁴ - Apex callback refactoring
- PR #4213³¹⁴⁵ - Clean up allocator checks for dependent projects
- PR #4212³¹⁴⁶ - Google Season of Docs updates to documentation; grammar edits.
- PR #4211³¹⁴⁷ - Google Season of Docs updates to documentation; contributing to hpx
- PR #4210³¹⁴⁸ - Attempting to fix Intel compilation
- PR #4209³¹⁴⁹ - Fix CUDA 10 build
- PR #4205³¹⁵⁰ - Making sure that differences in CMAKE_BUILD_TYPE are not reported on multi-configuration cmake generators
- PR #4203³¹⁵¹ - Deprecate Vc

³¹²⁹ <https://github.com/TheHPXProject/hpx/pull/4238>

³¹³⁰ <https://github.com/TheHPXProject/hpx/pull/4237>

³¹³¹ <https://github.com/TheHPXProject/hpx/pull/4236>

³¹³² <https://github.com/TheHPXProject/hpx/pull/4235>

³¹³³ <https://github.com/TheHPXProject/hpx/pull/4234>

³¹³⁴ <https://github.com/TheHPXProject/hpx/pull/4230>

³¹³⁵ <https://github.com/TheHPXProject/hpx/pull/4229>

³¹³⁶ <https://github.com/TheHPXProject/hpx/pull/4226>

³¹³⁷ <https://github.com/TheHPXProject/hpx/pull/4225>

³¹³⁸ <https://github.com/TheHPXProject/hpx/pull/4224>

³¹³⁹ <https://github.com/TheHPXProject/hpx/pull/4222>

³¹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4221>

³¹⁴¹ <https://github.com/TheHPXProject/hpx/pull/4218>

³¹⁴² <https://github.com/TheHPXProject/hpx/pull/4217>

³¹⁴³ <https://github.com/TheHPXProject/hpx/pull/4216>

³¹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4214>

³¹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4213>

³¹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4212>

³¹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4211>

³¹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4210>

³¹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4209>

³¹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4205>

³¹⁵¹ <https://github.com/TheHPXProject/hpx/pull/4203>

- PR #4202³¹⁵² - Fix CUDA configuration
- PR #4200³¹⁵³ - Making sure `hpx_wrap` is not passed on to linker on non-Linux systems
- PR #4198³¹⁵⁴ - Fix `execution_agent.cpp` compilation with GCC 5
- PR #4197³¹⁵⁵ - Remove deprecated options for 1.4.0 release
- PR #4196³¹⁵⁶ - minor fixes for building on OSX Darwin
- PR #4195³¹⁵⁷ - Use full clone on CircleCI for pushing stable tag
- PR #4193³¹⁵⁸ - Add scheduling hints to `hello_world_distributed`
- PR #4192³¹⁵⁹ - Set up CUDA in `HPXConfig.cmake`
- PR #4191³¹⁶⁰ - Export allocators root variables
- PR #4190³¹⁶¹ - Don't use `constexpr` in `thread_data` with GCC <= 6
- PR #4189³¹⁶² - Only use `quick_exit` if available
- PR #4188³¹⁶³ - Google Season of Docs updates to documentation; writing single node hpx applications
- PR #4186³¹⁶⁴ - correct `vc` to `cuda` in `cuda` `cmake`
- PR #4184³¹⁶⁵ - Resetting some cached variables to make sure those are re-filled
- PR #4183³¹⁶⁶ - Fix `hpxcxx` configuration
- PR #4181³¹⁶⁷ - Rename base libraries var
- PR #4180³¹⁶⁸ - Move header left behind earlier to plugin module
- PR #4179³¹⁶⁹ - Moving `zip_iterator` and `transform_iterator` to `iterator_support` module
- PR #4178³¹⁷⁰ - Move checkpointing support to its own module
- PR #4177³¹⁷¹ - Small `const` fix to `basic_execution` module
- PR #4176³¹⁷² - Add back `HPX_LIBRARIES` and friends to `HPXConfig.cmake`
- PR #4175³¹⁷³ - Make `Vc` public and add it to `HPXConfig.cmake`
- PR #4173³¹⁷⁴ - Wait for runtime to be running before returning from `hpx::start`

³¹⁵² <https://github.com/TheHPXProject/hpx/pull/4202>

³¹⁵³ <https://github.com/TheHPXProject/hpx/pull/4200>

³¹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4198>

³¹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4197>

³¹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4196>

³¹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4195>

³¹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4193>

³¹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4192>

³¹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4191>

³¹⁶¹ <https://github.com/TheHPXProject/hpx/pull/4190>

³¹⁶² <https://github.com/TheHPXProject/hpx/pull/4189>

³¹⁶³ <https://github.com/TheHPXProject/hpx/pull/4188>

³¹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4186>

³¹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4184>

³¹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4183>

³¹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4181>

³¹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4180>

³¹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4179>

³¹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4178>

³¹⁷¹ <https://github.com/TheHPXProject/hpx/pull/4177>

³¹⁷² <https://github.com/TheHPXProject/hpx/pull/4176>

³¹⁷³ <https://github.com/TheHPXProject/hpx/pull/4175>

³¹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4173>

- PR #4172³¹⁷⁵ - More protection against shutdown problems in error handling scenarios.
- PR #4171³¹⁷⁶ - Ignore lock in `condition_variable::wait`
- PR #4170³¹⁷⁷ - Adding APEX dependency to MPI parcellport
- PR #4168³¹⁷⁸ - Adding utility include
- PR #4167³¹⁷⁹ - Add a condition to setup the external libraries
- PR #4166³¹⁸⁰ - Add an `INTERNAL_FLAGS` option to link to `hpx_internal_flags`
- PR #4165³¹⁸¹ - Forward `HPX_*` cmake cache variables to external projects
- PR #4164³¹⁸² - Affinity and batch environment modules
- PR #4162³¹⁸³ - Handle quick `exit`
- PR #4160³¹⁸⁴ - Using `target_link_libraries` for cmake versions ≥ 3.12
- PR #4159³¹⁸⁵ - Make sure `HPX_WITH_NATIVE_TLS` is forwarded to dependent projects
- PR #4158³¹⁸⁶ - Adding allocator imported target as a dependency of allocator module
- PR #4157³¹⁸⁷ - Add `hpx_memory` as a dependency of parcellport plugins
- PR #4156³¹⁸⁸ - Stackless coroutines now can refer to themselves (through `get_self()` and friends)
- PR #4154³¹⁸⁹ - Added CMake policy CMP0060 for HPX applications.
- PR #4153³¹⁹⁰ - add header `iomanip` to tests and tool
- PR #4152³¹⁹¹ - Casting MPI tag value
- PR #4149³¹⁹² - Add back private `m_desc` member variable in `program_options` module
- PR #4147³¹⁹³ - Resource partitioner and threadmanager modules
- PR #4146³¹⁹⁴ - Google Season of Docs updates to documentation; creating hpx projects
- PR #4145³¹⁹⁵ - Adding basic support for stackless threads
- PR #4143³¹⁹⁶ - Exclude `test_client_1950` from all target
- PR #4142³¹⁹⁷ - Add a new `thread_pool_executor`

³¹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4172>

³¹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4171>

³¹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4170>

³¹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4168>

³¹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4167>

³¹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4166>

³¹⁸¹ <https://github.com/TheHPXProject/hpx/pull/4165>

³¹⁸² <https://github.com/TheHPXProject/hpx/pull/4164>

³¹⁸³ <https://github.com/TheHPXProject/hpx/pull/4162>

³¹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4160>

³¹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4159>

³¹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4158>

³¹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4157>

³¹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4156>

³¹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4154>

³¹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4153>

³¹⁹¹ <https://github.com/TheHPXProject/hpx/pull/4152>

³¹⁹² <https://github.com/TheHPXProject/hpx/pull/4149>

³¹⁹³ <https://github.com/TheHPXProject/hpx/pull/4147>

³¹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4146>

³¹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4145>

³¹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4143>

³¹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4142>

- [PR #4140](#)³¹⁹⁸ - Google Season of Docs updates to documentation; why hpx
- [PR #4139](#)³¹⁹⁹ - Remove runtime includes from coroutines module
- [PR #4138](#)³²⁰⁰ - Forking `boost::intrusive_ptr` and adding it as `hpx::intrusive_ptr`
- [PR #4137](#)³²⁰¹ - Fixing TSS destruction
- [PR #4136](#)³²⁰² - HPX.Compute modules
- [PR #4133](#)³²⁰³ - Fix `block_executor`
- [PR #4131](#)³²⁰⁴ - Applying fixes based on reports from PVS Studio
- [PR #4130](#)³²⁰⁵ - Adding missing header to build system
- [PR #4129](#)³²⁰⁶ - Fixing compilation if `HPX_WITH_DATAPAR_VC` is enabled
- [PR #4128](#)³²⁰⁷ - Renaming `moveonly_any` to `unique_any`
- [PR #4126](#)³²⁰⁸ - Attempt to fix `basic_any` constructor for gcc 7
- [PR #4125](#)³²⁰⁹ - Changing `extra_archive_data` implementation
- [PR #4124](#)³²¹⁰ - Don't link to Boost.System unless required
- [PR #4122](#)³²¹¹ - Add kernel launch helper utility (+saxpy demo) and merge in octotiger changes
- [PR #4121](#)³²¹² - Fixing migration test if networking is disabled.
- [PR #4120](#)³²¹³ - Google Season of Docs updates to documentation; hpx build system v1
- [PR #4119](#)³²¹⁴ - Making sure `chunk_size` and `max_chunk` are actually applied to parallel algorithms if specified
- [PR #4117](#)³²¹⁵ - Make CircleCI formatting check store diff
- [PR #4116](#)³²¹⁶ - Fix automatically setting C++ standard
- [PR #4114](#)³²¹⁷ - Module serialization
- [PR #4113](#)³²¹⁸ - Module datastructures
- [PR #4111](#)³²¹⁹ - Fixing performance regression introduced earlier
- [PR #4110](#)³²²⁰ - Adding missing SPDX tags

³¹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4140>

³¹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4139>

³²⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4138>

³²⁰¹ <https://github.com/TheHPXProject/hpx/pull/4137>

³²⁰² <https://github.com/TheHPXProject/hpx/pull/4136>

³²⁰³ <https://github.com/TheHPXProject/hpx/pull/4133>

³²⁰⁴ <https://github.com/TheHPXProject/hpx/pull/4131>

³²⁰⁵ <https://github.com/TheHPXProject/hpx/pull/4130>

³²⁰⁶ <https://github.com/TheHPXProject/hpx/pull/4129>

³²⁰⁷ <https://github.com/TheHPXProject/hpx/pull/4128>

³²⁰⁸ <https://github.com/TheHPXProject/hpx/pull/4126>

³²⁰⁹ <https://github.com/TheHPXProject/hpx/pull/4125>

³²¹⁰ <https://github.com/TheHPXProject/hpx/pull/4124>

³²¹¹ <https://github.com/TheHPXProject/hpx/pull/4122>

³²¹² <https://github.com/TheHPXProject/hpx/pull/4121>

³²¹³ <https://github.com/TheHPXProject/hpx/pull/4120>

³²¹⁴ <https://github.com/TheHPXProject/hpx/pull/4119>

³²¹⁵ <https://github.com/TheHPXProject/hpx/pull/4117>

³²¹⁶ <https://github.com/TheHPXProject/hpx/pull/4116>

³²¹⁷ <https://github.com/TheHPXProject/hpx/pull/4114>

³²¹⁸ <https://github.com/TheHPXProject/hpx/pull/4113>

³²¹⁹ <https://github.com/TheHPXProject/hpx/pull/4111>

³²²⁰ <https://github.com/TheHPXProject/hpx/pull/4110>

- PR #4109³²²¹ - Overload for start without entry point/argv.
- PR #4108³²²² - Making sure C++ standard is properly detected and propagated
- PR #4106³²²³ - use `std::round` for guaranteed rounding without errors
- PR #4104³²²⁴ - Extend `scheduler_mode` with new `work_stealing` and task assignment modes
- PR #4103³²²⁵ - Add this to lambda capture list
- PR #4102³²²⁶ - Add spdx license and check
- PR #4099³²²⁷ - Module coroutines
- PR #4098³²²⁸ - Fix append module path in module CMakeLists template
- PR #4097³²²⁹ - Function tests
- PR #4096³²³⁰ - Removing return of `thread_result_type` from functions not needing them
- PR #4095³²³¹ - Stop-gap measure until cmake overhaul is in place
- PR #4094³²³² - Deprecate `HPX_WITH_MORE_THAN_64_THREADS`
- PR #4093³²³³ - Fix initialization of `global_num_tasks` in `parallel_executor`
- PR #4092³²³⁴ - Add support for mi-malloc
- PR #4090³²³⁵ - Execution context
- PR #4089³²³⁶ - Make counters in coroutines optional
- PR #4087³²³⁷ - Making `hpx::util::any` compatible with C++17
- PR #4084³²³⁸ - Making sure destination array for `std::transform` is properly resized
- PR #4083³²³⁹ - Adapting `thread_queue_mc` to behave even if no 128bit atomics are available
- PR #4082³²⁴⁰ - Fix compilation on GCC 5
- PR #4081³²⁴¹ - Adding option allowing to force using Boost.FileSystem
- PR #4080³²⁴² - Updating module dependencies
- PR #4079³²⁴³ - Add missing tests for `iterator_support` module

³²²¹ <https://github.com/TheHPXProject/hpx/pull/4109>

³²²² <https://github.com/TheHPXProject/hpx/pull/4108>

³²²³ <https://github.com/TheHPXProject/hpx/pull/4106>

³²²⁴ <https://github.com/TheHPXProject/hpx/pull/4104>

³²²⁵ <https://github.com/TheHPXProject/hpx/pull/4103>

³²²⁶ <https://github.com/TheHPXProject/hpx/pull/4102>

³²²⁷ <https://github.com/TheHPXProject/hpx/pull/4099>

³²²⁸ <https://github.com/TheHPXProject/hpx/pull/4098>

³²²⁹ <https://github.com/TheHPXProject/hpx/pull/4097>

³²³⁰ <https://github.com/TheHPXProject/hpx/pull/4096>

³²³¹ <https://github.com/TheHPXProject/hpx/pull/4095>

³²³² <https://github.com/TheHPXProject/hpx/pull/4094>

³²³³ <https://github.com/TheHPXProject/hpx/pull/4093>

³²³⁴ <https://github.com/TheHPXProject/hpx/pull/4092>

³²³⁵ <https://github.com/TheHPXProject/hpx/pull/4090>

³²³⁶ <https://github.com/TheHPXProject/hpx/pull/4089>

³²³⁷ <https://github.com/TheHPXProject/hpx/pull/4087>

³²³⁸ <https://github.com/TheHPXProject/hpx/pull/4084>

³²³⁹ <https://github.com/TheHPXProject/hpx/pull/4083>

³²⁴⁰ <https://github.com/TheHPXProject/hpx/pull/4082>

³²⁴¹ <https://github.com/TheHPXProject/hpx/pull/4081>

³²⁴² <https://github.com/TheHPXProject/hpx/pull/4080>

³²⁴³ <https://github.com/TheHPXProject/hpx/pull/4079>

- PR #4078³²⁴⁴ - Disable parcel-layer if networking is disabled
- PR #4077³²⁴⁵ - Add missing include that causes build fails
- PR #4076³²⁴⁶ - Enable compatibility headers for functional module
- PR #4075³²⁴⁷ - Coroutines module
- PR #4073³²⁴⁸ - Use `configure_file` for generated files in modules
- PR #4071³²⁴⁹ - Fixing MPI detection for PMIx
- PR #4070³²⁵⁰ - Fix macOS builds
- PR #4069³²⁵¹ - Moving more facilities to the collectives module
- PR #4068³²⁵² - Adding main HPX `#include` directory to modules
- PR #4066³²⁵³ - Switching the use of `message(STATUS "...")` to `hpx_info`
- PR #4065³²⁵⁴ - Move Boost.Filesystem handling to filesystem module
- PR #4064³²⁵⁵ - Fix `program_options` test with older boost versions
- PR #4062³²⁵⁶ - The `cpu_features` tool fails to compile on anything but x86 architectures
- PR #4061³²⁵⁷ - Add `clang-format` checking step for modules
- PR #4060³²⁵⁸ - Making sure `HPX_IDLE_BACKOFF_TIME_MAX` is always defined (even if its unused)
- PR #4059³²⁵⁹ - Renaming module `hpx_parallel_executors` into `hpx_execution`
- PR #4058³²⁶⁰ - Do not build networking tests when networking disabled
- PR #4057³²⁶¹ - Printing configuration summary for modules as well
- PR #4055³²⁶² - Google Season of Docs updates to documentation; hpx build systems
- PR #4054³²⁶³ - Add troubleshooting section to manual
- PR #4051³²⁶⁴ - Add more variations to `future_overhead` test
- PR #4050³²⁶⁵ - Creating plugin module
- PR #4049³²⁶⁶ - Move missing modules tests

³²⁴⁴ <https://github.com/TheHPXProject/hpx/pull/4078>

³²⁴⁵ <https://github.com/TheHPXProject/hpx/pull/4077>

³²⁴⁶ <https://github.com/TheHPXProject/hpx/pull/4076>

³²⁴⁷ <https://github.com/TheHPXProject/hpx/pull/4075>

³²⁴⁸ <https://github.com/TheHPXProject/hpx/pull/4073>

³²⁴⁹ <https://github.com/TheHPXProject/hpx/pull/4071>

³²⁵⁰ <https://github.com/TheHPXProject/hpx/pull/4070>

³²⁵¹ <https://github.com/TheHPXProject/hpx/pull/4069>

³²⁵² <https://github.com/TheHPXProject/hpx/pull/4068>

³²⁵³ <https://github.com/TheHPXProject/hpx/pull/4066>

³²⁵⁴ <https://github.com/TheHPXProject/hpx/pull/4065>

³²⁵⁵ <https://github.com/TheHPXProject/hpx/pull/4064>

³²⁵⁶ <https://github.com/TheHPXProject/hpx/pull/4062>

³²⁵⁷ <https://github.com/TheHPXProject/hpx/pull/4061>

³²⁵⁸ <https://github.com/TheHPXProject/hpx/pull/4060>

³²⁵⁹ <https://github.com/TheHPXProject/hpx/pull/4059>

³²⁶⁰ <https://github.com/TheHPXProject/hpx/pull/4058>

³²⁶¹ <https://github.com/TheHPXProject/hpx/pull/4057>

³²⁶² <https://github.com/TheHPXProject/hpx/pull/4055>

³²⁶³ <https://github.com/TheHPXProject/hpx/pull/4054>

³²⁶⁴ <https://github.com/TheHPXProject/hpx/pull/4051>

³²⁶⁵ <https://github.com/TheHPXProject/hpx/pull/4050>

³²⁶⁶ <https://github.com/TheHPXProject/hpx/pull/4049>

- PR #4047³²⁶⁷ - Add boost/filesystem headers to inspect deprecated headers
- PR #4045³²⁶⁸ - Module functional
- PR #4043³²⁶⁹ - Fix preconditions and error messages for suspension functions
- PR #4041³²⁷⁰ - Pass HPX_STANDARD on to dependent projects via HPXConfig.cmake
- PR #4040³²⁷¹ - Program options module
- PR #4039³²⁷² - Moving non-serializable any (any_nonser) to datastructures module
- PR #4038³²⁷³ - Adding MPark's variant (V1.4.0) to HPX
- PR #4037³²⁷⁴ - Adding resiliency module
- PR #4036³²⁷⁵ - Add C++17 filesystem compatibility header
- PR #4035³²⁷⁶ - Fixing support for mpirun
- PR #4028³²⁷⁷ - CMake to target based directives
- PR #4027³²⁷⁸ - Remove GitLab CI configuration
- PR #4026³²⁷⁹ - Threading refactoring
- PR #4025³²⁸⁰ - Refactoring thread queue configuration options
- PR #4024³²⁸¹ - Fix padding calculation in cache_aligned_data.hpp
- PR #4023³²⁸² - Fixing Codacy issues
- PR #4022³²⁸³ - Make sure process mask option is passed to affinity_data
- PR #4021³²⁸⁴ - Warn about compiling in C++11 mode
- PR #4020³²⁸⁵ - Module concurrency
- PR #4019³²⁸⁶ - Module topology
- PR #4018³²⁸⁷ - Update deprecated header in thread_queue_mc.hpp
- PR #4015³²⁸⁸ - Avoid overwriting artifacts
- PR #4014³²⁸⁹ - Future overheads

³²⁶⁷ <https://github.com/TheHPXProject/hpx/pull/4047>

³²⁶⁸ <https://github.com/TheHPXProject/hpx/pull/4045>

³²⁶⁹ <https://github.com/TheHPXProject/hpx/pull/4043>

³²⁷⁰ <https://github.com/TheHPXProject/hpx/pull/4041>

³²⁷¹ <https://github.com/TheHPXProject/hpx/pull/4040>

³²⁷² <https://github.com/TheHPXProject/hpx/pull/4039>

³²⁷³ <https://github.com/TheHPXProject/hpx/pull/4038>

³²⁷⁴ <https://github.com/TheHPXProject/hpx/pull/4037>

³²⁷⁵ <https://github.com/TheHPXProject/hpx/pull/4036>

³²⁷⁶ <https://github.com/TheHPXProject/hpx/pull/4035>

³²⁷⁷ <https://github.com/TheHPXProject/hpx/pull/4028>

³²⁷⁸ <https://github.com/TheHPXProject/hpx/pull/4027>

³²⁷⁹ <https://github.com/TheHPXProject/hpx/pull/4026>

³²⁸⁰ <https://github.com/TheHPXProject/hpx/pull/4025>

³²⁸¹ <https://github.com/TheHPXProject/hpx/pull/4024>

³²⁸² <https://github.com/TheHPXProject/hpx/pull/4023>

³²⁸³ <https://github.com/TheHPXProject/hpx/pull/4022>

³²⁸⁴ <https://github.com/TheHPXProject/hpx/pull/4021>

³²⁸⁵ <https://github.com/TheHPXProject/hpx/pull/4020>

³²⁸⁶ <https://github.com/TheHPXProject/hpx/pull/4019>

³²⁸⁷ <https://github.com/TheHPXProject/hpx/pull/4018>

³²⁸⁸ <https://github.com/TheHPXProject/hpx/pull/4015>

³²⁸⁹ <https://github.com/TheHPXProject/hpx/pull/4014>

- PR #4013³²⁹⁰ - Update URL to test output conversion script
- PR #4012³²⁹¹ - Fix CUDA compilation
- PR #4011³²⁹² - Fixing cyclic dependencies between modules
- PR #4010³²⁹³ - Ignore stable tag on CircleCI
- PR #4009³²⁹⁴ - Check circular dependencies in a circle ci step
- PR #4008³²⁹⁵ - Extend cache aligned data to handle tuple-like data
- PR #4007³²⁹⁶ - Fixing migration for components that have actions returning a client
- PR #4006³²⁹⁷ - Move is_value_proxy.hpp to algorithms module
- PR #4004³²⁹⁸ - Shorten CTest timeout on CircleCI
- PR #4003³²⁹⁹ - Refactoring to remove (internal) dependencies
- PR #4001³³⁰⁰ - Exclude tests from all target
- PR #4000³³⁰¹ - Module errors
- PR #3999³³⁰² - Enable support for compatibility headers for logging module
- PR #3998³³⁰³ - Add process thread binding option
- PR #3997³³⁰⁴ - Export handle_assert function
- PR #3996³³⁰⁵ - Attempt to solve issue where -latomic does not support 128bit atomics
- PR #3993³³⁰⁶ - Make sure __LINE__ is an unsigned
- PR #3991³³⁰⁷ - Fix dependencies and flags for header tests
- PR #3990³³⁰⁸ - Documentation tags fixes
- PR #3988³³⁰⁹ - Adding missing solution folder for format module test
- PR #3987³³¹⁰ - Move runtime-dependent functions out of command line handling
- PR #3986³³¹¹ - Fix CMake configuration with PAPI on
- PR #3985³³¹² - Module timing

³²⁹⁰ <https://github.com/TheHPXProject/hpx/pull/4013>

³²⁹¹ <https://github.com/TheHPXProject/hpx/pull/4012>

³²⁹² <https://github.com/TheHPXProject/hpx/pull/4011>

³²⁹³ <https://github.com/TheHPXProject/hpx/pull/4010>

³²⁹⁴ <https://github.com/TheHPXProject/hpx/pull/4009>

³²⁹⁵ <https://github.com/TheHPXProject/hpx/pull/4008>

³²⁹⁶ <https://github.com/TheHPXProject/hpx/pull/4007>

³²⁹⁷ <https://github.com/TheHPXProject/hpx/pull/4006>

³²⁹⁸ <https://github.com/TheHPXProject/hpx/pull/4004>

³²⁹⁹ <https://github.com/TheHPXProject/hpx/pull/4003>

³³⁰⁰ <https://github.com/TheHPXProject/hpx/pull/4001>

³³⁰¹ <https://github.com/TheHPXProject/hpx/pull/4000>

³³⁰² <https://github.com/TheHPXProject/hpx/pull/3999>

³³⁰³ <https://github.com/TheHPXProject/hpx/pull/3998>

³³⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3997>

³³⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3996>

³³⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3993>

³³⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3991>

³³⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3990>

³³⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3988>

³³¹⁰ <https://github.com/TheHPXProject/hpx/pull/3987>

³³¹¹ <https://github.com/TheHPXProject/hpx/pull/3986>

³³¹² <https://github.com/TheHPXProject/hpx/pull/3985>

- PR #3984³³¹³ - Fix default behaviour of paths in `add_hpx_component`
- PR #3982³³¹⁴ - Parallel executors module
- PR #3981³³¹⁵ - Segmented algorithms module
- PR #3980³³¹⁶ - Module logging
- PR #3979³³¹⁷ - Module util
- PR #3978³³¹⁸ - Fix `clang-tidy` step on CircleCI
- PR #3977³³¹⁹ - Fixing solution folders for moved components
- PR #3976³³²⁰ - Module format
- PR #3975³³²¹ - Enable deprecation warnings on CircleCI
- PR #3974³³²² - Fix typos in documentation
- PR #3973³³²³ - Fix compilation with GCC 9
- PR #3972³³²⁴ - Add condition to clone apex + use of new cmake var `APEX_ROOT`
- PR #3971³³²⁵ - Add testing module
- PR #3968³³²⁶ - Remove unneeded file in hardware module
- PR #3967³³²⁷ - Remove leftover PIC settings from main `CMakeLists.txt`
- PR #3966³³²⁸ - Add missing export option in `add_hpx_module`
- PR #3965³³²⁹ - Change `current_function_helper` back to non-constexpr
- PR #3964³³³⁰ - Fixing merge problems
- PR #3962³³³¹ - Add a trait for `std::array` for unwrapping
- PR #3961³³³² - Making `hpx::util::tuple<Ts...>` and `std::tuple<Ts...>` convertible
- PR #3960³³³³ - fix compilation with CUDA 10 and GCC 6
- PR #3959³³³⁴ - Fix C++11 incompatibility
- PR #3957³³³⁵ - Algorithms module

³³¹³ <https://github.com/TheHPXProject/hpx/pull/3984>

³³¹⁴ <https://github.com/TheHPXProject/hpx/pull/3982>

³³¹⁵ <https://github.com/TheHPXProject/hpx/pull/3981>

³³¹⁶ <https://github.com/TheHPXProject/hpx/pull/3980>

³³¹⁷ <https://github.com/TheHPXProject/hpx/pull/3979>

³³¹⁸ <https://github.com/TheHPXProject/hpx/pull/3978>

³³¹⁹ <https://github.com/TheHPXProject/hpx/pull/3977>

³³²⁰ <https://github.com/TheHPXProject/hpx/pull/3976>

³³²¹ <https://github.com/TheHPXProject/hpx/pull/3975>

³³²² <https://github.com/TheHPXProject/hpx/pull/3974>

³³²³ <https://github.com/TheHPXProject/hpx/pull/3973>

³³²⁴ <https://github.com/TheHPXProject/hpx/pull/3972>

³³²⁵ <https://github.com/TheHPXProject/hpx/pull/3971>

³³²⁶ <https://github.com/TheHPXProject/hpx/pull/3968>

³³²⁷ <https://github.com/TheHPXProject/hpx/pull/3967>

³³²⁸ <https://github.com/TheHPXProject/hpx/pull/3966>

³³²⁹ <https://github.com/TheHPXProject/hpx/pull/3965>

³³³⁰ <https://github.com/TheHPXProject/hpx/pull/3964>

³³³¹ <https://github.com/TheHPXProject/hpx/pull/3962>

³³³² <https://github.com/TheHPXProject/hpx/pull/3961>

³³³³ <https://github.com/TheHPXProject/hpx/pull/3960>

³³³⁴ <https://github.com/TheHPXProject/hpx/pull/3959>

³³³⁵ <https://github.com/TheHPXProject/hpx/pull/3957>

- PR #3956³³³⁶ - [HPX_AddModule] Fix lower name var to upper
- PR #3955³³³⁷ - Fix CMake configuration with examples off and tests on
- PR #3954³³³⁸ - Move components to separate subdirectory in root of repository
- PR #3952³³³⁹ - Update `papi.cpp`
- PR #3951³³⁴⁰ - Exclude modules header tests from all target
- PR #3950³³⁴¹ - Adding `all_reduce` facility to collectives module
- PR #3949³³⁴² - This adds a configuration file that will cause for stale issues to be automatically closed
- PR #3948³³⁴³ - Fixing ALPS environment
- PR #3947³³⁴⁴ - Add major compiler version check for building hpx as a binary package
- PR #3946³³⁴⁵ - [Modules] Move the location of the generated headers
- PR #3945³³⁴⁶ - Simplify tests and examples cmake
- PR #3943³³⁴⁷ - Remove example module
- PR #3942³³⁴⁸ - Add `NOEXPORT` option to `add_hpx_{component,library}`
- PR #3938³³⁴⁹ - Use https for CDash submissions
- PR #3937³³⁵⁰ - Add `HPX_WITH_BUILD_BINARY_PACKAGE` to the compiler check (refs #3935)
- PR #3936³³⁵¹ - Fixing installation of binaries on windows
- PR #3934³³⁵² - Add set function for `sliding_semaphore_max_difference`
- PR #3933³³⁵³ - Remove `cuDart` from compile/link flags as it breaks downstream projects
- PR #3932³³⁵⁴ - Fixing 3929
- PR #3931³³⁵⁵ - Adding `all_to_all`
- PR #3930³³⁵⁶ - Add test demonstrating the use of broadcast with component actions
- PR #3928³³⁵⁷ - fixed number of tasks and number of threads for heterogeneous slurm environments
- PR #3927³³⁵⁸ - Moving Cache module's tests into separate solution folder

³³³⁶ <https://github.com/TheHPXProject/hpx/pull/3956>

³³³⁷ <https://github.com/TheHPXProject/hpx/pull/3955>

³³³⁸ <https://github.com/TheHPXProject/hpx/pull/3954>

³³³⁹ <https://github.com/TheHPXProject/hpx/pull/3952>

³³⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3951>

³³⁴¹ <https://github.com/TheHPXProject/hpx/pull/3950>

³³⁴² <https://github.com/TheHPXProject/hpx/pull/3949>

³³⁴³ <https://github.com/TheHPXProject/hpx/pull/3948>

³³⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3947>

³³⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3946>

³³⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3945>

³³⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3943>

³³⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3942>

³³⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3938>

³³⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3937>

³³⁵¹ <https://github.com/TheHPXProject/hpx/pull/3936>

³³⁵² <https://github.com/TheHPXProject/hpx/pull/3934>

³³⁵³ <https://github.com/TheHPXProject/hpx/pull/3933>

³³⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3932>

³³⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3931>

³³⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3930>

³³⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3928>

³³⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3927>

- PR #3926³³⁵⁹ - Move unit tests to cache module
- PR #3925³³⁶⁰ - Move version check to config module
- PR #3924³³⁶¹ - Add schedule hint executor parameters
- PR #3923³³⁶² - Allow aligning objects bigger than the cache line size
- PR #3922³³⁶³ - Add Windows builds with Travis CI
- PR #3921³³⁶⁴ - Add ccls cache directory to gitignore
- PR #3920³³⁶⁵ - Fix `git_external` fetching of tags
- PR #3905³³⁶⁶ - Correct rostambod url. Fix typo in doc
- PR #3904³³⁶⁷ - Fix bug in `context_base.hpp`
- PR #3903³³⁶⁸ - Adding new performance counters
- PR #3902³³⁶⁹ - Add `add_hpx_module` function
- PR #3901³³⁷⁰ - Factoring out container remapping into a separate trait
- PR #3900³³⁷¹ - Making sure errors during command line processing are properly reported and will not cause assertions
- PR #3899³³⁷² - Remove old compatibility bases from `make_action`
- PR #3898³³⁷³ - Make parameter size be of type `size_t`
- PR #3897³³⁷⁴ - Making sure all tests are disabled if `HPX_WITH_TESTS=OFF`
- PR #3895³³⁷⁵ - Add documentation for `annotated_function`
- PR #3894³³⁷⁶ - Working around VS2019 problem with `make_action`
- PR #3892³³⁷⁷ - Avoid MSVC compatibility warning in internal allocator
- PR #3891³³⁷⁸ - Removal of the default intel config include
- PR #3888³³⁷⁹ - Fix `async_customization` dataflow example and Clarify what's being tested
- PR #3887³³⁸⁰ - Add Doxygen documentation
- PR #3882³³⁸¹ - Minor docs fixes

³³⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3926>

³³⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3925>

³³⁶¹ <https://github.com/TheHPXProject/hpx/pull/3924>

³³⁶² <https://github.com/TheHPXProject/hpx/pull/3923>

³³⁶³ <https://github.com/TheHPXProject/hpx/pull/3922>

³³⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3921>

³³⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3920>

³³⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3905>

³³⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3904>

³³⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3903>

³³⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3902>

³³⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3901>

³³⁷¹ <https://github.com/TheHPXProject/hpx/pull/3900>

³³⁷² <https://github.com/TheHPXProject/hpx/pull/3899>

³³⁷³ <https://github.com/TheHPXProject/hpx/pull/3898>

³³⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3897>

³³⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3895>

³³⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3894>

³³⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3892>

³³⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3891>

³³⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3888>

³³⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3887>

³³⁸¹ <https://github.com/TheHPXProject/hpx/pull/3882>

- PR #3880³³⁸² - Updating APEX version tag
- PR #3878³³⁸³ - Making sure symbols are properly exported from modules (needed for Windows/MacOS)
- PR #3877³³⁸⁴ - Documentation
- PR #3876³³⁸⁵ - Module hardware
- PR #3875³³⁸⁶ - Converted typedefs in actions submodule to using directives
- PR #3874³³⁸⁷ - Allow one to suppress target keywords in `hpx_setup_target` for backwards compatibility
- PR #3873³³⁸⁸ - Add scripts to create releases and generate lists of PRs and issues
- PR #3872³³⁸⁹ - Fix latest HTML docs location
- PR #3870³³⁹⁰ - Module cache
- PR #3869³³⁹¹ - Post 1.3.0 version bumps
- PR #3868³³⁹² - Replace the macro `HPX_ASSERT` by `HPX_TEST` in tests
- PR #3845³³⁹³ - Assertion module
- PR #3839³³⁹⁴ - Make tuple serialization non-intrusive
- PR #3832³³⁹⁵ - Config module
- PR #3799³³⁹⁶ - Remove compat namespace and its contents
- PR #3701³³⁹⁷ - MoodyCamel lockfree
- PR #3496³³⁹⁸ - Disabling MPI's (deprecated) C++ interface
- PR #3192³³⁹⁹ - Move type info into `hpx::debug` namespace and add print helper functions
- PR #3159³⁴⁰⁰ - Support Checkpointing Components

³³⁸² <https://github.com/TheHPXProject/hpx/pull/3880>

³³⁸³ <https://github.com/TheHPXProject/hpx/pull/3878>

³³⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3877>

³³⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3876>

³³⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3875>

³³⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3874>

³³⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3873>

³³⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3872>

³³⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3870>

³³⁹¹ <https://github.com/TheHPXProject/hpx/pull/3869>

³³⁹² <https://github.com/TheHPXProject/hpx/pull/3868>

³³⁹³ <https://github.com/TheHPXProject/hpx/pull/3845>

³³⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3839>

³³⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3832>

³³⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3799>

³³⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3701>

³³⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3496>

³³⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3192>

³⁴⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3159>

HPX V1.3.0 (May 23, 2019)

General changes

- Performance improvements: the schedulers have significantly reduced overheads from removing false sharing and the parallel executor has been updated to create fewer futures.
- HPX now defaults to not turning on networking when running on one locality. This means that you can run multiple instances on the same system without adding command line options.
- Multiple issues reported by Clang sanitizers have been fixed.
- We have added (back) single-page HTML documentation and PDF documentation.
- We have started modularizing the HPX library. This is useful both for developers and users. In the long term users will be able to consume only parts of the HPX libraries if they do not require all the functionality that HPX currently provides.
- We have added an implementation of `function_ref`.
- The `barrier` and `latch` classes have gained a few additional member functions.

Breaking changes

- Executable and library targets are now created without the `_exe` and `_lib` suffix respectively. For example, the target `1d_stencil_1_exe` is now simply called `1d_stencil_1`.
- We have removed the following deprecated functionality: `queue`, `scoped_unlock`, and support for input iterators in algorithms.
- We have turned off the compatibility layer for `unwrapped` by default. The functionality will be removed in the next release. The option can still be turned on using the [CMake](https://www.cmake.org)³⁴⁰¹ option `HPX_WITH_UNWRAPPED_SUPPORT`. Likewise, `inclusive_scan` compatibility overloads have been turned off by default. They can still be turned on with `HPX_WITH_INCLUSIVE_SCAN_COMPATIBILITY`.
- The minimum compiler and dependency versions have been updated. We now support GCC from version 5 onwards, Clang from version 4 onwards, and Boost from version 1.61.0 onwards.
- The headers for preprocessor macros have moved as a result of the functionality being moved to a separate module. The old headers are deprecated and will be removed in a future version of HPX. You can turn off the warnings by setting `HPX_PREPROCESSOR_WITH_DEPRECATION_WARNINGS=OFF` or turn off the compatibility headers completely with `HPX_PREPROCESSOR_WITH_COMPATIBILITY_HEADERS=OFF`.

Closed issues

- [Issue #3863](https://github.com/TheHPXProject/hpx/issues/3863)³⁴⁰² - shouldn't “-faligned-new” be a usage requirement?
- [Issue #3841](https://github.com/TheHPXProject/hpx/issues/3841)³⁴⁰³ - Build error with msvc 19 caused by SFINAE and C++17
- [Issue #3836](https://github.com/TheHPXProject/hpx/issues/3836)³⁴⁰⁴ - master branch does not build with idle rate counters enabled
- [Issue #3819](https://github.com/TheHPXProject/hpx/issues/3819)³⁴⁰⁵ - Add debug suffix to modules built in debug mode

³⁴⁰¹ <https://www.cmake.org>

³⁴⁰² <https://github.com/TheHPXProject/hpx/issues/3863>

³⁴⁰³ <https://github.com/TheHPXProject/hpx/issues/3841>

³⁴⁰⁴ <https://github.com/TheHPXProject/hpx/issues/3836>

³⁴⁰⁵ <https://github.com/TheHPXProject/hpx/issues/3819>

- Issue #3817³⁴⁰⁶ - HPX_INCLUDE_DIRS contains non-existent directory
- Issue #3810³⁴⁰⁷ - Source groups are not created for files in modules
- Issue #3805³⁴⁰⁸ - HPX won't compile with -DHPX_WITH_APEX=TRUE
- Issue #3792³⁴⁰⁹ - Barrier Hangs When Locality Zero not included
- Issue #3778³⁴¹⁰ - Replace throw() with noexcept
- Issue #3763³⁴¹¹ - configurable sort limit per task
- Issue #3758³⁴¹² - dataflow doesn't convert future<future<T>> to future<T>
- Issue #3757³⁴¹³ - When compiling undefined reference to hpx::hpx_check_version_1_2 HPX V1.2.1, Ubuntu 18.04.01 Server Edition
- Issue #3753³⁴¹⁴ - --hpx:list-counters=full crashes
- Issue #3746³⁴¹⁵ - Detection of MPI with pmix
- Issue #3744³⁴¹⁶ - Separate spinlock from same cacheline as internal data for all LCOs
- Issue #3743³⁴¹⁷ - hpxcxx's shebang doesn't specify the python version
- Issue #3738³⁴¹⁸ - Unable to debug parcellport on a single node
- Issue #3735³⁴¹⁹ - Latest master: Can't compile in MSVC
- Issue #3731³⁴²⁰ - util::bound seems broken on Clang with older libstdc++
- Issue #3724³⁴²¹ - Allow to pre-set command line options through environment
- Issue #3723³⁴²² - examples/resource_partitioner build issue on master branch / ubuntu 18
- Issue #3721³⁴²³ - faced a building error
- Issue #3720³⁴²⁴ - Hello World example fails to link
- Issue #3719³⁴²⁵ - pkg-config produces invalid output: -l-pthread
- Issue #3718³⁴²⁶ - Please make the python executable configurable through cmake
- Issue #3717³⁴²⁷ - interested to contribute to the organisation
- Issue #3699³⁴²⁸ - Remove 'HPX runtime' executable

³⁴⁰⁶ <https://github.com/TheHPXProject/hpx/issues/3817>

³⁴⁰⁷ <https://github.com/TheHPXProject/hpx/issues/3810>

³⁴⁰⁸ <https://github.com/TheHPXProject/hpx/issues/3805>

³⁴⁰⁹ <https://github.com/TheHPXProject/hpx/issues/3792>

³⁴¹⁰ <https://github.com/TheHPXProject/hpx/issues/3778>

³⁴¹¹ <https://github.com/TheHPXProject/hpx/issues/3763>

³⁴¹² <https://github.com/TheHPXProject/hpx/issues/3758>

³⁴¹³ <https://github.com/TheHPXProject/hpx/issues/3757>

³⁴¹⁴ <https://github.com/TheHPXProject/hpx/issues/3753>

³⁴¹⁵ <https://github.com/TheHPXProject/hpx/issues/3746>

³⁴¹⁶ <https://github.com/TheHPXProject/hpx/issues/3744>

³⁴¹⁷ <https://github.com/TheHPXProject/hpx/issues/3743>

³⁴¹⁸ <https://github.com/TheHPXProject/hpx/issues/3738>

³⁴¹⁹ <https://github.com/TheHPXProject/hpx/issues/3735>

³⁴²⁰ <https://github.com/TheHPXProject/hpx/issues/3731>

³⁴²¹ <https://github.com/TheHPXProject/hpx/issues/3724>

³⁴²² <https://github.com/TheHPXProject/hpx/issues/3723>

³⁴²³ <https://github.com/TheHPXProject/hpx/issues/3721>

³⁴²⁴ <https://github.com/TheHPXProject/hpx/issues/3720>

³⁴²⁵ <https://github.com/TheHPXProject/hpx/issues/3719>

³⁴²⁶ <https://github.com/TheHPXProject/hpx/issues/3718>

³⁴²⁷ <https://github.com/TheHPXProject/hpx/issues/3717>

³⁴²⁸ <https://github.com/TheHPXProject/hpx/issues/3699>

- Issue #3698³⁴²⁹ - Ignore all locks while handling asserts
- Issue #3689³⁴³⁰ - Incorrect and inconsistent website structure <http://stellar.cct.lsu.edu/downloads/>.
- Issue #3681³⁴³¹ - Broken links on <http://stellar.cct.lsu.edu/2015/05/hpx-archives-now-on-gmane/>
- Issue #3676³⁴³² - HPX master built from source, cmake fails to link main.cpp example in docs
- Issue #3673³⁴³³ - HPX build fails with `std::atomic` missing error
- Issue #3670³⁴³⁴ - Generate PDF again from documentation (with Sphinx)
- Issue #3643³⁴³⁵ - Warnings when compiling HPX 1.2.1 with gcc 9
- Issue #3641³⁴³⁶ - Trouble with using ranges-v3 and `hpx::parallel::reduce`
- Issue #3639³⁴³⁷ - `util::unwrapping` does not work well with member functions
- Issue #3634³⁴³⁸ - The build fails if `shared_future<>::then` is called with a thread executor
- Issue #3622³⁴³⁹ - VTune Amplifier 2019 not working with `use_itt_notify=1`
- Issue #3616³⁴⁴⁰ - HPX Fails to Build with CUDA 10
- Issue #3612³⁴⁴¹ - False sharing of scheduling counters
- Issue #3609³⁴⁴² - `executor_parameters` timeout with gcc <= 7 and Debug mode
- Issue #3601³⁴⁴³ - Misleading error message on power pc for `rdtsc` and `rdtscp`
- Issue #3598³⁴⁴⁴ - Build of some examples fails when using Vc
- Issue #3594³⁴⁴⁵ - Error: The number of OS threads requested (20) does not match the number of threads to bind (12): HPX(bad_parameter)
- Issue #3592³⁴⁴⁶ - Undefined Reference Error
- Issue #3589³⁴⁴⁷ - include could not find load file: HPX_Utils.cmake
- Issue #3587³⁴⁴⁸ - HPX won't compile on POWER8 with Clang 7
- Issue #3583³⁴⁴⁹ - Fedora and openSUSE instructions missing on “Distribution Packages” page
- Issue #3578³⁴⁵⁰ - Build error when configuring with `HPX_HAVE_ALGORITHM_INPUT_ITERATOR_SUPPORT=ON`
- Issue #3575³⁴⁵¹ - Merge openSUSE reproducible patch

³⁴²⁹ <https://github.com/TheHPXProject/hpx/issues/3698>

³⁴³⁰ <https://github.com/TheHPXProject/hpx/issues/3689>

³⁴³¹ <https://github.com/TheHPXProject/hpx/issues/3681>

³⁴³² <https://github.com/TheHPXProject/hpx/issues/3676>

³⁴³³ <https://github.com/TheHPXProject/hpx/issues/3673>

³⁴³⁴ <https://github.com/TheHPXProject/hpx/issues/3670>

³⁴³⁵ <https://github.com/TheHPXProject/hpx/issues/3643>

³⁴³⁶ <https://github.com/TheHPXProject/hpx/issues/3641>

³⁴³⁷ <https://github.com/TheHPXProject/hpx/issues/3639>

³⁴³⁸ <https://github.com/TheHPXProject/hpx/issues/3634>

³⁴³⁹ <https://github.com/TheHPXProject/hpx/issues/3622>

³⁴⁴⁰ <https://github.com/TheHPXProject/hpx/issues/3616>

³⁴⁴¹ <https://github.com/TheHPXProject/hpx/issues/3612>

³⁴⁴² <https://github.com/TheHPXProject/hpx/issues/3609>

³⁴⁴³ <https://github.com/TheHPXProject/hpx/issues/3601>

³⁴⁴⁴ <https://github.com/TheHPXProject/hpx/issues/3598>

³⁴⁴⁵ <https://github.com/TheHPXProject/hpx/issues/3594>

³⁴⁴⁶ <https://github.com/TheHPXProject/hpx/issues/3592>

³⁴⁴⁷ <https://github.com/TheHPXProject/hpx/issues/3589>

³⁴⁴⁸ <https://github.com/TheHPXProject/hpx/issues/3587>

³⁴⁴⁹ <https://github.com/TheHPXProject/hpx/issues/3583>

³⁴⁵⁰ <https://github.com/TheHPXProject/hpx/issues/3578>

³⁴⁵¹ <https://github.com/TheHPXProject/hpx/issues/3575>

- [Issue #3570](#)³⁴⁵² - Update HPX to work with the latest VC version
- [Issue #3567](#)³⁴⁵³ - Build succeed and make failed for `hpx:cout`
- [Issue #3565](#)³⁴⁵⁴ - Polymorphic simple component destructor not getting called
- [Issue #3559](#)³⁴⁵⁵ - 1.2.0 is missing from download page
- [Issue #3554](#)³⁴⁵⁶ - Clang 6.0 warning of hiding overloaded virtual function
- [Issue #3510](#)³⁴⁵⁷ - Build on ppc64 fails
- [Issue #3482](#)³⁴⁵⁸ - Improve error message when `HPX_WITH_MAX_CPU_COUNT` is too low for given system
- [Issue #3453](#)³⁴⁵⁹ - Two HPX applications can't run at the same time.
- [Issue #3452](#)³⁴⁶⁰ - Scaling issue on the change to 2 NUMA domains
- [Issue #3442](#)³⁴⁶¹ - HPX `set_difference`, `set_intersection` failure cases
- [Issue #3437](#)³⁴⁶² - Ensure `parent_task` pointer when child task is created and child/parent are on same locality
- [Issue #3255](#)³⁴⁶³ - Suspension with lock for `--hpx:list-component-types`
- [Issue #3034](#)³⁴⁶⁴ - Use C++17 structured bindings for serialization
- [Issue #2999](#)³⁴⁶⁵ - Change thread scheduling use of `size_t` for thread indexing

Closed pull requests

- [PR #3865](#)³⁴⁶⁶ - adds `hpx_target_compile_option_if_available`
- [PR #3864](#)³⁴⁶⁷ - Helper functions that are useful in numa binding and testing of allocator
- [PR #3862](#)³⁴⁶⁸ - Temporary fix to `local_dataflow_boost_small_vector` test
- [PR #3860](#)³⁴⁶⁹ - Add cache line padding to intermediate results in for loop reduction
- [PR #3859](#)³⁴⁷⁰ - Remove `HPX_TLL_PUBLIC` and `HPX_TLL_PRIVATE` from CMake files
- [PR #3858](#)³⁴⁷¹ - Add compile flags and definitions to modules
- [PR #3851](#)³⁴⁷² - update `hpxmp` release tag to v0.2.0
- [PR #3849](#)³⁴⁷³ - Correct `BOOST_ROOT` variable name in quick start guide

³⁴⁵² <https://github.com/TheHPXProject/hpx/issues/3570>

³⁴⁵³ <https://github.com/TheHPXProject/hpx/issues/3567>

³⁴⁵⁴ <https://github.com/TheHPXProject/hpx/issues/3565>

³⁴⁵⁵ <https://github.com/TheHPXProject/hpx/issues/3559>

³⁴⁵⁶ <https://github.com/TheHPXProject/hpx/issues/3554>

³⁴⁵⁷ <https://github.com/TheHPXProject/hpx/issues/3510>

³⁴⁵⁸ <https://github.com/TheHPXProject/hpx/issues/3482>

³⁴⁵⁹ <https://github.com/TheHPXProject/hpx/issues/3453>

³⁴⁶⁰ <https://github.com/TheHPXProject/hpx/issues/3452>

³⁴⁶¹ <https://github.com/TheHPXProject/hpx/issues/3442>

³⁴⁶² <https://github.com/TheHPXProject/hpx/issues/3437>

³⁴⁶³ <https://github.com/TheHPXProject/hpx/issues/3255>

³⁴⁶⁴ <https://github.com/TheHPXProject/hpx/issues/3034>

³⁴⁶⁵ <https://github.com/TheHPXProject/hpx/issues/2999>

³⁴⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3865>

³⁴⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3864>

³⁴⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3862>

³⁴⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3860>

³⁴⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3859>

³⁴⁷¹ <https://github.com/TheHPXProject/hpx/pull/3858>

³⁴⁷² <https://github.com/TheHPXProject/hpx/pull/3851>

³⁴⁷³ <https://github.com/TheHPXProject/hpx/pull/3849>

- PR #3847³⁴⁷⁴ - Fix attach_debugger configuration option
- PR #3846³⁴⁷⁵ - Add tests for libs header tests
- PR #3844³⁴⁷⁶ - Fixing source_groups in preprocessor module to properly handle compatibility headers
- PR #3843³⁴⁷⁷ - This fixes the launch_process/launched_process pair of tests
- PR #3842³⁴⁷⁸ - Fix macro call with ITTNOTIFY enabled
- PR #3840³⁴⁷⁹ - Fixing SLURM environment parsing
- PR #3837³⁴⁸⁰ - Fixing misplaced #endif
- PR #3835³⁴⁸¹ - make all latch members protected for consistency
- PR #3834³⁴⁸² - Disable transpose_block_numa example on CircleCI
- PR #3833³⁴⁸³ - make latch **counter_** protected for deriving latch in hpxmp
- PR #3831³⁴⁸⁴ - Fix CircleCI config for modules
- PR #3830³⁴⁸⁵ - minor fix: option HPX_WITH_TEST was not working correctly
- PR #3828³⁴⁸⁶ - Avoid for binaries that depend on HPX to directly link against internal modules
- PR #3827³⁴⁸⁷ - Adding shortcut for `hpx::get_ptr<>(sync, id)` for a local, non-migratable objects
- PR #3826³⁴⁸⁸ - Fix and update modules documentation
- PR #3825³⁴⁸⁹ - Updating default APEX version to 2.1.3 with HPX
- PR #3823³⁴⁹⁰ - Fix pkgconfig libs handling
- PR #3822³⁴⁹¹ - Change includes in hpx_wrap.cpp to more specific includes
- PR #3821³⁴⁹² - Disable barrier_3792 test when networking is disabled
- PR #3820³⁴⁹³ - Assorted CMake fixes
- PR #3815³⁴⁹⁴ - Removing left-over debug output
- PR #3814³⁴⁹⁵ - Allow setting default scheduler mode via the configuration database
- PR #3813³⁴⁹⁶ - Make the deprecation warnings issued by the old pp headers optional

³⁴⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3847>

³⁴⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3846>

³⁴⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3844>

³⁴⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3843>

³⁴⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3842>

³⁴⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3840>

³⁴⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3837>

³⁴⁸¹ <https://github.com/TheHPXProject/hpx/pull/3835>

³⁴⁸² <https://github.com/TheHPXProject/hpx/pull/3834>

³⁴⁸³ <https://github.com/TheHPXProject/hpx/pull/3833>

³⁴⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3831>

³⁴⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3830>

³⁴⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3828>

³⁴⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3827>

³⁴⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3826>

³⁴⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3825>

³⁴⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3823>

³⁴⁹¹ <https://github.com/TheHPXProject/hpx/pull/3822>

³⁴⁹² <https://github.com/TheHPXProject/hpx/pull/3821>

³⁴⁹³ <https://github.com/TheHPXProject/hpx/pull/3820>

³⁴⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3815>

³⁴⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3814>

³⁴⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3813>

- PR #3812³⁴⁹⁷ - Windows requires to handle symlinks to directories differently from those linking files
- PR #3811³⁴⁹⁸ - Clean up PP module and library skeleton
- PR #3806³⁴⁹⁹ - Moving include path configuration to before APEX
- PR #3804³⁵⁰⁰ - Fix latch
- PR #3803³⁵⁰¹ - Update hpxcxx to look at lib64 and use python3
- PR #3802³⁵⁰² - Numa binding allocator
- PR #3801³⁵⁰³ - Remove duplicated includes
- PR #3800³⁵⁰⁴ - Attempt to fix Posix context switching after lazy init changes
- PR #3798³⁵⁰⁵ - count and count_if accepts different iterator types
- PR #3797³⁵⁰⁶ - Adding a couple of `override` keywords to overloaded virtual functions
- PR #3796³⁵⁰⁷ - Re-enable testing all schedulers in `shutdown_suspended_test`
- PR #3795³⁵⁰⁸ - Change `std::terminate` to `std::abort` in SIGSEGV handler
- PR #3794³⁵⁰⁹ - Fixing #3792
- PR #3793³⁵¹⁰ - Extending `migrate_polymorphic_component` unit test
- PR #3791³⁵¹¹ - Change `throw()` to `noexcept`
- PR #3790³⁵¹² - Remove deprecated options for 1.3.0 release
- PR #3789³⁵¹³ - Remove Boost filesystem compatibility header
- PR #3788³⁵¹⁴ - Disabled even more spots that should not execute if networking is disabled
- PR #3787³⁵¹⁵ - Bump minimal boost supported version to 1.61.0
- PR #3786³⁵¹⁶ - Bump minimum required versions for 1.3.0 release
- PR #3785³⁵¹⁷ - Explicitly set number of jobs for all ninja invocations on CircleCI
- PR #3784³⁵¹⁸ - Fix leak and address sanitizer problems
- PR #3783³⁵¹⁹ - Disabled even more spots that should not execute is networking is disabled

³⁴⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3812>

³⁴⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3811>

³⁴⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3806>

³⁵⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3804>

³⁵⁰¹ <https://github.com/TheHPXProject/hpx/pull/3803>

³⁵⁰² <https://github.com/TheHPXProject/hpx/pull/3802>

³⁵⁰³ <https://github.com/TheHPXProject/hpx/pull/3801>

³⁵⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3800>

³⁵⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3798>

³⁵⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3797>

³⁵⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3796>

³⁵⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3795>

³⁵⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3794>

³⁵¹⁰ <https://github.com/TheHPXProject/hpx/pull/3793>

³⁵¹¹ <https://github.com/TheHPXProject/hpx/pull/3791>

³⁵¹² <https://github.com/TheHPXProject/hpx/pull/3790>

³⁵¹³ <https://github.com/TheHPXProject/hpx/pull/3789>

³⁵¹⁴ <https://github.com/TheHPXProject/hpx/pull/3788>

³⁵¹⁵ <https://github.com/TheHPXProject/hpx/pull/3787>

³⁵¹⁶ <https://github.com/TheHPXProject/hpx/pull/3786>

³⁵¹⁷ <https://github.com/TheHPXProject/hpx/pull/3785>

³⁵¹⁸ <https://github.com/TheHPXProject/hpx/pull/3784>

³⁵¹⁹ <https://github.com/TheHPXProject/hpx/pull/3783>

- PR #3782³⁵²⁰ - Cherry-picked tuple and thread_init_data fixes from #3701
- PR #3781³⁵²¹ - Fix generic context coroutines after lazy stack allocation changes
- PR #3780³⁵²² - Rename hello world examples
- PR #3776³⁵²³ - Sort algorithms now use the supplied chunker to determine the required minimal chunk size
- PR #3775³⁵²⁴ - Disable Boost auto-linking
- PR #3774³⁵²⁵ - Tag and push stable builds
- PR #3773³⁵²⁶ - Enable migration of polymorphic components
- PR #3771³⁵²⁷ - Fix link to stackoverflow in documentation
- PR #3770³⁵²⁸ - Replacing constexpr if in brace-serialization code
- PR #3769³⁵²⁹ - Fix SIGSEGV handler
- PR #3768³⁵³⁰ - Adding flags to scheduler allowing to control thread stealing and idle back-off
- PR #3767³⁵³¹ - Fix help formatting in hpxrun.py
- PR #3765³⁵³² - Fix a couple of bugs in the thread test
- PR #3764³⁵³³ - Workaround for SFINAE regression in msvc14.2
- PR #3762³⁵³⁴ - Prevent MSVC from prematurely instantiating things
- PR #3761³⁵³⁵ - Update python scripts to work with python 3
- PR #3760³⁵³⁶ - Fix callable vtable for GCC4.9
- PR #3759³⁵³⁷ - Rename PAGE_SIZE to PAGE_SIZE_ because AppleClang
- PR #3755³⁵³⁸ - Making sure locks are not held during suspension
- PR #3754³⁵³⁹ - Disable more code if networking is not available/not enabled
- PR #3752³⁵⁴⁰ - Move util::format implementation to source file
- PR #3751³⁵⁴¹ - Fixing problems with lcos::barrier and iostreams
- PR #3750³⁵⁴² - Change error message to take into account use_guard_page setting

³⁵²⁰ <https://github.com/TheHPXProject/hpx/pull/3782>

³⁵²¹ <https://github.com/TheHPXProject/hpx/pull/3781>

³⁵²² <https://github.com/TheHPXProject/hpx/pull/3780>

³⁵²³ <https://github.com/TheHPXProject/hpx/pull/3776>

³⁵²⁴ <https://github.com/TheHPXProject/hpx/pull/3775>

³⁵²⁵ <https://github.com/TheHPXProject/hpx/pull/3774>

³⁵²⁶ <https://github.com/TheHPXProject/hpx/pull/3773>

³⁵²⁷ <https://github.com/TheHPXProject/hpx/pull/3771>

³⁵²⁸ <https://github.com/TheHPXProject/hpx/pull/3770>

³⁵²⁹ <https://github.com/TheHPXProject/hpx/pull/3769>

³⁵³⁰ <https://github.com/TheHPXProject/hpx/pull/3768>

³⁵³¹ <https://github.com/TheHPXProject/hpx/pull/3767>

³⁵³² <https://github.com/TheHPXProject/hpx/pull/3765>

³⁵³³ <https://github.com/TheHPXProject/hpx/pull/3764>

³⁵³⁴ <https://github.com/TheHPXProject/hpx/pull/3762>

³⁵³⁵ <https://github.com/TheHPXProject/hpx/pull/3761>

³⁵³⁶ <https://github.com/TheHPXProject/hpx/pull/3760>

³⁵³⁷ <https://github.com/TheHPXProject/hpx/pull/3759>

³⁵³⁸ <https://github.com/TheHPXProject/hpx/pull/3755>

³⁵³⁹ <https://github.com/TheHPXProject/hpx/pull/3754>

³⁵⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3752>

³⁵⁴¹ <https://github.com/TheHPXProject/hpx/pull/3751>

³⁵⁴² <https://github.com/TheHPXProject/hpx/pull/3750>

- PR #3749³⁵⁴³ - Fix lifetime problem in `run_as_hpx_thread`
- PR #3748³⁵⁴⁴ - Fixed unusable behavior of the clang code analyzer.
- PR #3747³⁵⁴⁵ - Added `PMIX_RANK` to the defaults of `HPX_WITH_PARCELPORTRT_MPI_ENV`.
- PR #3745³⁵⁴⁶ - Introduced `cache_aligned_data` and `cache_line_data` helper structure
- PR #3742³⁵⁴⁷ - Remove more unused functionality from `util/logging`
- PR #3740³⁵⁴⁸ - Fix includes in partitioned vector tests
- PR #3739³⁵⁴⁹ - More fixes to make sure that `std::flush` really flushes all output
- PR #3737³⁵⁵⁰ - Fix potential shutdown problems
- PR #3736³⁵⁵¹ - Fix `guided_pool_executor` after dataflow changes caused compilation fail
- PR #3734³⁵⁵² - Limiting executor
- PR #3732³⁵⁵³ - More constrained bound constructors
- PR #3730³⁵⁵⁴ - Attempt to fix deadlocks during component loading
- PR #3729³⁵⁵⁵ - Add latch member function `count_up` and `reset`, requested by `hpxMP`
- PR #3728³⁵⁵⁶ - Send even empty buffers on `hpx::endl` and `hpx::flush`
- PR #3727³⁵⁵⁷ - Adding example demonstrating how to customize the memory management for a component
- PR #3726³⁵⁵⁸ - Adding support for passing command line options through the `HPX_COMMANDLINE_OPTIONS` environment variable
- PR #3722³⁵⁵⁹ - Document known broken OpenMPI builds
- PR #3716³⁵⁶⁰ - Add barrier reset function, requested by `hpxMP` for reusing barrier
- PR #3715³⁵⁶¹ - More work on functions and `vtables`
- PR #3714³⁵⁶² - Generate single-page HTML, PDF, manpage from documentation
- PR #3713³⁵⁶³ - Updating default APEX version to 2.1.2
- PR #3712³⁵⁶⁴ - Update release procedure
- PR #3710³⁵⁶⁵ - Fix the C++11 build, after #3704

³⁵⁴³ <https://github.com/TheHPXProject/hpx/pull/3749>

³⁵⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3748>

³⁵⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3747>

³⁵⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3745>

³⁵⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3742>

³⁵⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3740>

³⁵⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3739>

³⁵⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3737>

³⁵⁵¹ <https://github.com/TheHPXProject/hpx/pull/3736>

³⁵⁵² <https://github.com/TheHPXProject/hpx/pull/3734>

³⁵⁵³ <https://github.com/TheHPXProject/hpx/pull/3732>

³⁵⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3730>

³⁵⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3729>

³⁵⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3728>

³⁵⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3727>

³⁵⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3726>

³⁵⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3722>

³⁵⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3716>

³⁵⁶¹ <https://github.com/TheHPXProject/hpx/pull/3715>

³⁵⁶² <https://github.com/TheHPXProject/hpx/pull/3714>

³⁵⁶³ <https://github.com/TheHPXProject/hpx/pull/3713>

³⁵⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3712>

³⁵⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3710>

- PR #3709³⁵⁶⁶ - Move some component_registry functionality to source file
- PR #3708³⁵⁶⁷ - Ignore all locks while handling assertions
- PR #3707³⁵⁶⁸ - Remove obsolete hpx runtime executable
- PR #3705³⁵⁶⁹ - Fix and simplify make_ready_future overload sets
- PR #3704³⁵⁷⁰ - Reduce use of binders
- PR #3703³⁵⁷¹ - Ini
- PR #3702³⁵⁷² - Fixing CUDA compiler errors
- PR #3700³⁵⁷³ - Added barrier::increment function to increase total number of thread
- PR #3697³⁵⁷⁴ - One more attempt to fix migration...
- PR #3694³⁵⁷⁵ - Fixing component migration
- PR #3693³⁵⁷⁶ - Print thread state when getting disallowed value in set_thread_state
- PR #3692³⁵⁷⁷ - Only disable constexpr with clang-cuda, not nvcc+gcc
- PR #3691³⁵⁷⁸ - Link with libsupc++ if needed for thread_local
- PR #3690³⁵⁷⁹ - Remove thousands separators in set_operations_3442 to comply with C++11
- PR #3688³⁵⁸⁰ - Decouple serialization from function vtables
- PR #3687³⁵⁸¹ - Fix a couple of test failures
- PR #3686³⁵⁸² - Make sure tests.unit.build are run after install on CircleCI
- PR #3685³⁵⁸³ - Revise quickstart CMakeLists.txt explanation
- PR #3684³⁵⁸⁴ - Provide concept emulation for Ranges-TS concepts
- PR #3683³⁵⁸⁵ - Ignore uninitialized chunks
- PR #3682³⁵⁸⁶ - Ignore uninitialized chunks. Check proper indices.
- PR #3680³⁵⁸⁷ - Ignore uninitialized chunks. Check proper range indices
- PR #3679³⁵⁸⁸ - Simplify basic action implementations

³⁵⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3709>

³⁵⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3708>

³⁵⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3707>

³⁵⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3705>

³⁵⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3704>

³⁵⁷¹ <https://github.com/TheHPXProject/hpx/pull/3703>

³⁵⁷² <https://github.com/TheHPXProject/hpx/pull/3702>

³⁵⁷³ <https://github.com/TheHPXProject/hpx/pull/3700>

³⁵⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3697>

³⁵⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3694>

³⁵⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3693>

³⁵⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3692>

³⁵⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3691>

³⁵⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3690>

³⁵⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3688>

³⁵⁸¹ <https://github.com/TheHPXProject/hpx/pull/3687>

³⁵⁸² <https://github.com/TheHPXProject/hpx/pull/3686>

³⁵⁸³ <https://github.com/TheHPXProject/hpx/pull/3685>

³⁵⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3684>

³⁵⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3683>

³⁵⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3682>

³⁵⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3680>

³⁵⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3679>

- PR #3678³⁵⁸⁹ - Making sure HPX_HAVE_LIBATOMIC is unset before checking
- PR #3677³⁵⁹⁰ - Fix generated full version number to be usable in expressions
- PR #3674³⁵⁹¹ - Reduce functional utilities call depth
- PR #3672³⁵⁹² - Change new build system to use existing macros related to pseudo dependencies
- PR #3669³⁵⁹³ - Remove indirection in `function_ref` when thread description is disabled
- PR #3668³⁵⁹⁴ - Unbreaking `async_*cb*` tests
- PR #3667³⁵⁹⁵ - Generate `version.hpp`
- PR #3665³⁵⁹⁶ - Enabling MPI parcelport for gitlab runners
- PR #3664³⁵⁹⁷ - making clang-tidy work properly again
- PR #3662³⁵⁹⁸ - Attempt to fix exception handling
- PR #3661³⁵⁹⁹ - Move `lcos::latch` to source file
- PR #3660³⁶⁰⁰ - Fix accidentally explicit `gid_type` default constructor
- PR #3659³⁶⁰¹ - Parallel executor latch
- PR #3658³⁶⁰² - Fixing `execution_parameters`
- PR #3657³⁶⁰³ - Avoid dangling references in `wait_all`
- PR #3656³⁶⁰⁴ - Avoiding lifetime problems with `sync_put_parcel`
- PR #3655³⁶⁰⁵ - Fixing `nullptr` dereference inside of function
- PR #3652³⁶⁰⁶ - Attempt to fix `thread_map_type` definition with C++11
- PR #3650³⁶⁰⁷ - Allowing for end iterator being different from begin iterator
- PR #3649³⁶⁰⁸ - Added architecture identification to cmake to be able to detect timestamp support
- PR #3645³⁶⁰⁹ - Enabling sanitizers on gitlab runner
- PR #3644³⁶¹⁰ - Attempt to tackle timeouts during startup
- PR #3642³⁶¹¹ - Cleanup parallel partitioners

³⁵⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3678>

³⁵⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3677>

³⁵⁹¹ <https://github.com/TheHPXProject/hpx/pull/3674>

³⁵⁹² <https://github.com/TheHPXProject/hpx/pull/3672>

³⁵⁹³ <https://github.com/TheHPXProject/hpx/pull/3669>

³⁵⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3668>

³⁵⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3667>

³⁵⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3665>

³⁵⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3664>

³⁵⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3662>

³⁵⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3661>

³⁶⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3660>

³⁶⁰¹ <https://github.com/TheHPXProject/hpx/pull/3659>

³⁶⁰² <https://github.com/TheHPXProject/hpx/pull/3658>

³⁶⁰³ <https://github.com/TheHPXProject/hpx/pull/3657>

³⁶⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3656>

³⁶⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3655>

³⁶⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3652>

³⁶⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3650>

³⁶⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3649>

³⁶⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3645>

³⁶¹⁰ <https://github.com/TheHPXProject/hpx/pull/3644>

³⁶¹¹ <https://github.com/TheHPXProject/hpx/pull/3642>

- PR #3640³⁶¹² - Dataflow now works with functions that return a reference
- PR #3637³⁶¹³ - Merging the executor-enabled overloads of `shared_future<>::then`
- PR #3633³⁶¹⁴ - Replace deprecated boost endian macros
- PR #3632³⁶¹⁵ - Add instructions on getting HPX to documentation
- PR #3631³⁶¹⁶ - Simplify parcel creation
- PR #3630³⁶¹⁷ - Small additions and fixes to release procedure
- PR #3629³⁶¹⁸ - Modular pp
- PR #3627³⁶¹⁹ - Implement `util::function_ref`
- PR #3626³⁶²⁰ - Fix cancelable_action_client example
- PR #3625³⁶²¹ - Added automatic serialization for simple structs (see #3034)
- PR #3624³⁶²² - Updating the default order of priority for `thread_description`
- PR #3621³⁶²³ - Update copyright year and other small formatting fixes
- PR #3620³⁶²⁴ - Adding support for gitlab runner
- PR #3619³⁶²⁵ - Store debug logs and core dumps on CircleCI
- PR #3618³⁶²⁶ - Various optimizations
- PR #3617³⁶²⁷ - Fix link to the gpg key (#2)
- PR #3615³⁶²⁸ - Fix unused variable warnings with networking off
- PR #3614³⁶²⁹ - Restructuring counter data in scheduler to reduce false sharing
- PR #3613³⁶³⁰ - Adding support for gitlab runners
- PR #3610³⁶³¹ - Don't wait for `stop_condition` in main thread
- PR #3608³⁶³² - Add inline keyword to `invalid_thread_id` definition for nvcc
- PR #3607³⁶³³ - Adding configuration key that allows one to explicitly add a directory to the component search path
- PR #3606³⁶³⁴ - Add nvcc to exclude constexpress since is it not supported by nvcc

³⁶¹² <https://github.com/TheHPXProject/hpx/pull/3640>

³⁶¹³ <https://github.com/TheHPXProject/hpx/pull/3637>

³⁶¹⁴ <https://github.com/TheHPXProject/hpx/pull/3633>

³⁶¹⁵ <https://github.com/TheHPXProject/hpx/pull/3632>

³⁶¹⁶ <https://github.com/TheHPXProject/hpx/pull/3631>

³⁶¹⁷ <https://github.com/TheHPXProject/hpx/pull/3630>

³⁶¹⁸ <https://github.com/TheHPXProject/hpx/pull/3629>

³⁶¹⁹ <https://github.com/TheHPXProject/hpx/pull/3627>

³⁶²⁰ <https://github.com/TheHPXProject/hpx/pull/3626>

³⁶²¹ <https://github.com/TheHPXProject/hpx/pull/3625>

³⁶²² <https://github.com/TheHPXProject/hpx/pull/3624>

³⁶²³ <https://github.com/TheHPXProject/hpx/pull/3621>

³⁶²⁴ <https://github.com/TheHPXProject/hpx/pull/3620>

³⁶²⁵ <https://github.com/TheHPXProject/hpx/pull/3619>

³⁶²⁶ <https://github.com/TheHPXProject/hpx/pull/3618>

³⁶²⁷ <https://github.com/TheHPXProject/hpx/pull/3617>

³⁶²⁸ <https://github.com/TheHPXProject/hpx/pull/3615>

³⁶²⁹ <https://github.com/TheHPXProject/hpx/pull/3614>

³⁶³⁰ <https://github.com/TheHPXProject/hpx/pull/3613>

³⁶³¹ <https://github.com/TheHPXProject/hpx/pull/3610>

³⁶³² <https://github.com/TheHPXProject/hpx/pull/3608>

³⁶³³ <https://github.com/TheHPXProject/hpx/pull/3607>

³⁶³⁴ <https://github.com/TheHPXProject/hpx/pull/3606>

- PR #3605³⁶³⁵ - Add `inline` to definition of checkpoint stream operators to fix link error
- PR #3604³⁶³⁶ - Use format for string formatting
- PR #3603³⁶³⁷ - Improve the error message for using to less `MAX_CPU_COUNT`
- PR #3602³⁶³⁸ - Improve the error message for to small values of `MAX_CPU_COUNT`
- PR #3600³⁶³⁹ - Parallel executor aggregated
- PR #3599³⁶⁴⁰ - Making sure networking is disabled for default one-locality-runs
- PR #3596³⁶⁴¹ - Store thread exit functions in `forward_list` instead of `deque` to avoid allocations
- PR #3590³⁶⁴² - Fix typo/mistake in thread queue `cleanup_terminated`
- PR #3588³⁶⁴³ - Fix formatting errors in `launching_and_configuring_hpx_applications.rst`
- PR #3586³⁶⁴⁴ - Make `bind` propagate value category
- PR #3585³⁶⁴⁵ - Extend Cmake for building `hpx` as distribution packages (refs #3575)
- PR #3584³⁶⁴⁶ - Untangle function storage from object pointer
- PR #3582³⁶⁴⁷ - Towards Modularized HPX
- PR #3580³⁶⁴⁸ - Remove extra `||` in `merge.hpp`
- PR #3577³⁶⁴⁹ - Partially revert “Remove vtable empty flag”
- PR #3576³⁶⁵⁰ - Make sure empty startup/shutdown functions are not being used
- PR #3574³⁶⁵¹ - Make sure `DATAPAR` settings are conveyed to depending projects
- PR #3573³⁶⁵² - Make sure HPX is usable with latest released version of Vc (V1.4.1)
- PR #3572³⁶⁵³ - Adding test ensuring ticket 3565 is fixed
- PR #3571³⁶⁵⁴ - Make empty `[unique_]` function vtable non-dependent
- PR #3566³⁶⁵⁵ - Fix compilation with dynamic bitset for CPU masks
- PR #3563³⁶⁵⁶ - Drop `util::[unique_]` function `target_type`
- PR #3562³⁶⁵⁷ - Removing the target suffixes

³⁶³⁵ <https://github.com/TheHPXProject/hpx/pull/3605>

³⁶³⁶ <https://github.com/TheHPXProject/hpx/pull/3604>

³⁶³⁷ <https://github.com/TheHPXProject/hpx/pull/3603>

³⁶³⁸ <https://github.com/TheHPXProject/hpx/pull/3602>

³⁶³⁹ <https://github.com/TheHPXProject/hpx/pull/3600>

³⁶⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3599>

³⁶⁴¹ <https://github.com/TheHPXProject/hpx/pull/3596>

³⁶⁴² <https://github.com/TheHPXProject/hpx/pull/3590>

³⁶⁴³ <https://github.com/TheHPXProject/hpx/pull/3588>

³⁶⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3586>

³⁶⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3585>

³⁶⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3584>

³⁶⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3582>

³⁶⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3580>

³⁶⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3577>

³⁶⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3576>

³⁶⁵¹ <https://github.com/TheHPXProject/hpx/pull/3574>

³⁶⁵² <https://github.com/TheHPXProject/hpx/pull/3573>

³⁶⁵³ <https://github.com/TheHPXProject/hpx/pull/3572>

³⁶⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3571>

³⁶⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3566>

³⁶⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3563>

³⁶⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3562>

- PR #3561³⁶⁵⁸ - Replace executor traits return type deduction (keep non-SFINAE)
- PR #3557³⁶⁵⁹ - Replace the last usages of boost::atomic
- PR #3556³⁶⁶⁰ - Replace boost::scoped_array with std::unique_ptr
- PR #3552³⁶⁶¹ - (Re)move APEX readme
- PR #3548³⁶⁶² - Replace boost::scoped_ptr with std::unique_ptr
- PR #3547³⁶⁶³ - Remove last use of Boost.Signals2
- PR #3544³⁶⁶⁴ - Post 1.2.0 version bumps
- PR #3543³⁶⁶⁵ - added Ubuntu dependency list to readme
- PR #3531³⁶⁶⁶ - Warnings, warnings...
- PR #3527³⁶⁶⁷ - Add CircleCI filter for building all tags
- PR #3525³⁶⁶⁸ - Segmented algorithms
- PR #3517³⁶⁶⁹ - Replace boost::regex with C++11 <regex>
- PR #3514³⁶⁷⁰ - Cleaning up the build system
- PR #3505³⁶⁷¹ - Fixing type attribute warning for transfer_action
- PR #3504³⁶⁷² - Add support for rpm packaging
- PR #3499³⁶⁷³ - Improving spinlock pools
- PR #3498³⁶⁷⁴ - Remove thread specific ptr
- PR #3486³⁶⁷⁵ - Fix comparison for expect_connecting_localities config entry
- PR #3469³⁶⁷⁶ - Enable (existing) code for extracting stack pointer on Power platform

³⁶⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3561>

³⁶⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3557>

³⁶⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3556>

³⁶⁶¹ <https://github.com/TheHPXProject/hpx/pull/3552>

³⁶⁶² <https://github.com/TheHPXProject/hpx/pull/3548>

³⁶⁶³ <https://github.com/TheHPXProject/hpx/pull/3547>

³⁶⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3544>

³⁶⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3543>

³⁶⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3531>

³⁶⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3527>

³⁶⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3525>

³⁶⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3517>

³⁶⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3514>

³⁶⁷¹ <https://github.com/TheHPXProject/hpx/pull/3505>

³⁶⁷² <https://github.com/TheHPXProject/hpx/pull/3504>

³⁶⁷³ <https://github.com/TheHPXProject/hpx/pull/3499>

³⁶⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3498>

³⁶⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3486>

³⁶⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3469>

HPX V1.2.1 (Feb 19, 2019)

General changes

This is a bugfix release. It contains the following changes:

- Fix compilation on ARM, s390x and 32-bit architectures.
- Fix a critical bug in the `future` implementation.
- Fix several problems in the CMake configuration which affects external projects.
- Add support for Boost 1.69.0.

Closed issues

- Issue #3638³⁶⁷⁷ - Build HPX 1.2 with boost 1.69
- Issue #3635³⁶⁷⁸ - Non-deterministic crashing on Stampede2
- Issue #3550³⁶⁷⁹ - `1>e:000workhpxsrcthrow_exception.cpp(54): error C2440: '<function-style-cast>': cannot convert from 'boost::system::error_code' to 'hpx::exception'`
- Issue #3549³⁶⁸⁰ - HPX 1.2.0 does not build on i686, but release candidate did
- Issue #3511³⁶⁸¹ - Build on s390x fails
- Issue #3509³⁶⁸² - Build on armv7l fails

Closed pull requests

- PR #3695³⁶⁸³ - Don't install CMake templates and packaging files
- PR #3666³⁶⁸⁴ - Fixing yet another race in `future_data`
- PR #3663³⁶⁸⁵ - Fixing race between setting and getting the value inside `future_data`
- PR #3648³⁶⁸⁶ - Adding timestamp option for S390x platform
- PR #3647³⁶⁸⁷ - Blind attempt to fix warnings issued by gcc V9
- PR #3611³⁶⁸⁸ - Include `GNUInstallDirs` earlier to have it available for subdirectories
- PR #3595³⁶⁸⁹ - Use `GNUInstallDirs` lib path in `pkgconfig` config file
- PR #3593³⁶⁹⁰ - Add `include(GNUInstallDirs)` to `HPXMacros.cmake`

³⁶⁷⁷ <https://github.com/TheHPXProject/hpx/issues/3638>

³⁶⁷⁸ <https://github.com/TheHPXProject/hpx/issues/3635>

³⁶⁷⁹ <https://github.com/TheHPXProject/hpx/issues/3550>

³⁶⁸⁰ <https://github.com/TheHPXProject/hpx/issues/3549>

³⁶⁸¹ <https://github.com/TheHPXProject/hpx/issues/3511>

³⁶⁸² <https://github.com/TheHPXProject/hpx/issues/3509>

³⁶⁸³ <https://github.com/TheHPXProject/hpx/pull/3695>

³⁶⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3666>

³⁶⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3663>

³⁶⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3648>

³⁶⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3647>

³⁶⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3611>

³⁶⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3595>

³⁶⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3593>

- PR #3591³⁶⁹¹ - Fix compilation error on arm7 architecture. Compiles and runs on Fedora 29 on Pi 3.
- PR #3558³⁶⁹² - Adding constructor *exception(boost::system::error_code const&)*
- PR #3555³⁶⁹³ - cmake: make install locations configurable
- PR #3551³⁶⁹⁴ - Fix uint64_t causing compilation fail on i686

HPX V1.2.0 (Nov 12, 2018)

General changes

Here are some of the main highlights and changes for this release:

- Thanks to the work of our Google Summer of Code student, Nikunj Gupta, we now have a new implementation of `hpx_main.hpp` on supported platforms (Linux, BSD and MacOS). This is intended to be a less fragile drop-in replacement for the old implementation relying on preprocessor macros. The new implementation does not require changes if you are using the `CMake`³⁶⁹⁵ or `pkg-config`. The old behaviour can be restored by setting `HPX_WITH_DYNAMIC_HPX_MAIN=OFF` during `CMake`³⁶⁹⁶ configuration. The implementation on Windows is unchanged.
- We have added functionality to allow passing scheduling hints to our schedulers. These will allow us to create executors that for example target a specific NUMA domain or allow for *HPX* threads to be pinned to a particular worker thread.
- We have significantly improved the performance of our futures implementation by making the shared state atomic.
- We have replaced Boostbook by Sphinx for our documentation. This means the documentation is easier to navigate with built-in search and table of contents. We have also added a quick start section and restructured the documentation to be easier to follow for new users.
- We have added a new option to the `--hpx:threads` command line option. It is now possible to use `cores` to tell *HPX* to only use one worker thread per core, unlike the existing option `all` which uses one worker thread per processing unit (processing unit can be a hyperthread if hyperthreads are available). The default value of `--hpx:threads` has also been changed to `cores` as this leads to better performance in most cases.
- All command line options can now be passed alongside configuration options when initializing *HPX*. This means that some options that were previously only available on the command line can now be set as configuration options.
- *HPXMP* is a portable, scalable, and flexible application programming interface using the OpenMP specification that supports multi-platform shared memory multiprocessing programming in C and C++. *HPXMP* can be enabled within *HPX* by setting `DHPX_WITH_HPXM=ON` during `CMake`³⁶⁹⁷ configuration.
- Two new performance counters were added for measuring the time spent doing background work. `/threads/time/background-work-duration` returns the time spent doing background on a given thread or locality, while `/threads/time/background-overhead` returns the fraction of time spent doing background work with respect to the overall time spent running the scheduler. The new performance counters are disabled by default and can be turned on by setting `HPX_WITH_BACKGROUND_THREAD_COUNTERS=ON` during `CMake`³⁶⁹⁸ configuration.

³⁶⁹¹ <https://github.com/TheHPXProject/hpx/pull/3591>

³⁶⁹² <https://github.com/TheHPXProject/hpx/pull/3558>

³⁶⁹³ <https://github.com/TheHPXProject/hpx/pull/3555>

³⁶⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3551>

³⁶⁹⁵ <https://www.cmake.org>

³⁶⁹⁶ <https://www.cmake.org>

³⁶⁹⁷ <https://www.cmake.org>

³⁶⁹⁸ <https://www.cmake.org>

- The idling behaviour of *HPX* has been tweaked to allow for faster idling. This is useful in interactive applications where the *HPX* worker threads may not have work all the time. This behaviour can be tweaked and turned off as before with `HPX_WITH_THREAD_MANAGER_IDLE_BACKOFF=OFF` during [CMake](#)³⁶⁹⁹ configuration.
- It is now possible to register callback functions for *HPX* worker thread events. Callbacks can be registered for starting and stopping worker threads, and for when errors occur.

Breaking changes

- The implementation of `hpx_main.hpp` has changed. If you are using custom Makefiles you will need to make changes. Please see the documentation on *using Makefiles* for more details.
- The default value of `--hpx:threads` has changed from `all` to `cores`. The new option `cores` only starts one worker thread per core.
- We have dropped support for Boost 1.56 and 1.57. The minimal version of Boost we now test is 1.58.
- Our `boost::format`-based formatting implementation has been revised and replaced with a custom implementation. This changes the formatting syntax and requires changes if you are relying on `hpx::util::format` or `hpx::util::format_to`. The pull request for this change contains more information: [PR #3266](#)³⁷⁰⁰.
- The following deprecated options have now been completely removed:
`HPX_WITH_ASYNC_FUNCTION_COMPATIBILITY`, `HPX_WITH_LOCAL_DATAFLOW`,
`HPX_WITH_GENERIC_EXECUTION_POLICY`, `HPX_WITH_BOOST_CHRONO_COMPATIBILITY`,
`HPX_WITH_EXECUTOR_COMPATIBILITY`, `HPX_WITH_EXECUTION_POLICY_COMPATIBILITY`, and
`HPX_WITH_TRANSFORM_REDUCE_COMPATIBILITY`.

Closed issues

- [Issue #3538](#)³⁷⁰¹ - numa handling incorrect for hwloc 2
- [Issue #3533](#)³⁷⁰² - Cmake version 3.5.1 does not work (git ff26b35 2018-11-06)
- [Issue #3526](#)³⁷⁰³ - Failed building hpx-1.2.0-rc1 on Ubuntu16.04 x86-64 Virtualbox VM
- [Issue #3512](#)³⁷⁰⁴ - Build on aarch64 fails
- [Issue #3475](#)³⁷⁰⁵ - HPX fails to link if the MPI parcellport is enabled
- [Issue #3462](#)³⁷⁰⁶ - CMake configuration shows a minor and inconsequential failure to create a symlink
- [Issue #3461](#)³⁷⁰⁷ - Compilation Problems with the most recent Clang
- [Issue #3460](#)³⁷⁰⁸ - Deadlock when `create_partitioner` fails (assertion fails) in debug mode
- [Issue #3455](#)³⁷⁰⁹ - HPX build failing with HWLOC errors on POWER8 with hwloc 1.8
- [Issue #3438](#)³⁷¹⁰ - HPX no longer builds on IBM POWER8

³⁶⁹⁹ <https://www.cmake.org>

³⁷⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3266>

³⁷⁰¹ <https://github.com/TheHPXProject/hpx/issues/3538>

³⁷⁰² <https://github.com/TheHPXProject/hpx/issues/3533>

³⁷⁰³ <https://github.com/TheHPXProject/hpx/issues/3526>

³⁷⁰⁴ <https://github.com/TheHPXProject/hpx/issues/3512>

³⁷⁰⁵ <https://github.com/TheHPXProject/hpx/issues/3475>

³⁷⁰⁶ <https://github.com/TheHPXProject/hpx/issues/3462>

³⁷⁰⁷ <https://github.com/TheHPXProject/hpx/issues/3461>

³⁷⁰⁸ <https://github.com/TheHPXProject/hpx/issues/3460>

³⁷⁰⁹ <https://github.com/TheHPXProject/hpx/issues/3455>

³⁷¹⁰ <https://github.com/TheHPXProject/hpx/issues/3438>

- Issue #3426³⁷¹¹ - hpx build failed on MacOS
- Issue #3424³⁷¹² - CircleCI builds broken for forked repositories
- Issue #3422³⁷¹³ - Benchmarks in tests.performance.local are not run nightly
- Issue #3408³⁷¹⁴ - CMake Targets for HPX
- Issue #3399³⁷¹⁵ - processing unit out of bounds
- Issue #3395³⁷¹⁶ - Floating point bug in hpx/runtime/threads/policies/scheduler_base.hpp
- Issue #3378³⁷¹⁷ - compile error with lcos::communicator
- Issue #3376³⁷¹⁸ - Failed to build HPX with APEX using clang
- Issue #3366³⁷¹⁹ - Adapted Safe_Object example fails for `-hpx:threads > 1`
- Issue #3360³⁷²⁰ - Segmentation fault when passing component id as parameter
- Issue #3358³⁷²¹ - HPX runtime hangs after multiple (~thousands) start-stop sequences
- Issue #3352³⁷²² - Support TCP provider in libfabric ParcelPort
- Issue #3342³⁷²³ - undefined reference to `__atomic_load_16`
- Issue #3339³⁷²⁴ - setting command line options/flags from init cfg is not obvious
- Issue #3325³⁷²⁵ - AGAS migrates components prematurely
- Issue #3321³⁷²⁶ - hpx bad_parameter handling is awful
- Issue #3318³⁷²⁷ - Benchmarks fail to build with C++11
- Issue #3304³⁷²⁸ - `hpx::threads::run_as_hpx_thread` does not properly handle exceptions
- Issue #3300³⁷²⁹ - Setting pu step or offset results in no threads in default pool
- Issue #3297³⁷³⁰ - Crash with APEX when running Phylax lra_csv with > 1 thread
- Issue #3296³⁷³¹ - Building HPX with APEX configuration gives compiler warnings
- Issue #3290³⁷³² - make tests failing at hello_world_component
- Issue #3285³⁷³³ - possible compilation error when “using namespace std;” is defined before including “hpx” headers files

³⁷¹¹ <https://github.com/TheHPXProject/hpx/issues/3426>

³⁷¹² <https://github.com/TheHPXProject/hpx/issues/3424>

³⁷¹³ <https://github.com/TheHPXProject/hpx/issues/3422>

³⁷¹⁴ <https://github.com/TheHPXProject/hpx/issues/3408>

³⁷¹⁵ <https://github.com/TheHPXProject/hpx/issues/3399>

³⁷¹⁶ <https://github.com/TheHPXProject/hpx/issues/3395>

³⁷¹⁷ <https://github.com/TheHPXProject/hpx/issues/3378>

³⁷¹⁸ <https://github.com/TheHPXProject/hpx/issues/3376>

³⁷¹⁹ <https://github.com/TheHPXProject/hpx/issues/3366>

³⁷²⁰ <https://github.com/TheHPXProject/hpx/issues/3360>

³⁷²¹ <https://github.com/TheHPXProject/hpx/issues/3358>

³⁷²² <https://github.com/TheHPXProject/hpx/issues/3352>

³⁷²³ <https://github.com/TheHPXProject/hpx/issues/3342>

³⁷²⁴ <https://github.com/TheHPXProject/hpx/issues/3339>

³⁷²⁵ <https://github.com/TheHPXProject/hpx/issues/3325>

³⁷²⁶ <https://github.com/TheHPXProject/hpx/issues/3321>

³⁷²⁷ <https://github.com/TheHPXProject/hpx/issues/3318>

³⁷²⁸ <https://github.com/TheHPXProject/hpx/issues/3304>

³⁷²⁹ <https://github.com/TheHPXProject/hpx/issues/3300>

³⁷³⁰ <https://github.com/TheHPXProject/hpx/issues/3297>

³⁷³¹ <https://github.com/TheHPXProject/hpx/issues/3296>

³⁷³² <https://github.com/TheHPXProject/hpx/issues/3290>

³⁷³³ <https://github.com/TheHPXProject/hpx/issues/3285>

- Issue #3280³⁷³⁴ - HPX fails on OSX
- Issue #3272³⁷³⁵ - CircleCI does not upload generated docker image any more
- Issue #3270³⁷³⁶ - Error when compiling CUDA examples
- Issue #3267³⁷³⁷ - `tests.unit.host_.block_allocator` fails occasionally
- Issue #3264³⁷³⁸ - Possible move to Sphinx for documentation
- Issue #3263³⁷³⁹ - Documentation improvements
- Issue #3259³⁷⁴⁰ - `set_parcel_write_handler` test fails occasionally
- Issue #3258³⁷⁴¹ - Links to source code in documentation are broken
- Issue #3247³⁷⁴² - Rare `tests.unit.host_.block_allocator` test failure on 1.1.0-rc1
- Issue #3244³⁷⁴³ - Slowing down and speeding up an `interval_timer`
- Issue #3215³⁷⁴⁴ - Cannot build both tests and examples on MSVC with pseudo-dependencies enabled
- Issue #3195³⁷⁴⁵ - Unnecessary customization point route causing performance penalty
- Issue #3088³⁷⁴⁶ - A strange thing in `parallel::sort`.
- Issue #2650³⁷⁴⁷ - libfabric support for passive endpoints
- Issue #1205³⁷⁴⁸ - TSS is broken

Closed pull requests

- PR #3542³⁷⁴⁹ - Fix numa lookup from pu when using hwloc 2.x
- PR #3541³⁷⁵⁰ - Fixing the build system of the MPI parcelport
- PR #3540³⁷⁵¹ - Updating HPX people section
- PR #3539³⁷⁵² - Splitting test to avoid OOM on CircleCI
- PR #3537³⁷⁵³ - Fix guided exec
- PR #3536³⁷⁵⁴ - Updating grants which support the LSU team
- PR #3535³⁷⁵⁵ - Fix hiding of docker credentials

³⁷³⁴ <https://github.com/TheHPXProject/hpx/issues/3280>

³⁷³⁵ <https://github.com/TheHPXProject/hpx/issues/3272>

³⁷³⁶ <https://github.com/TheHPXProject/hpx/issues/3270>

³⁷³⁷ <https://github.com/TheHPXProject/hpx/issues/3267>

³⁷³⁸ <https://github.com/TheHPXProject/hpx/issues/3264>

³⁷³⁹ <https://github.com/TheHPXProject/hpx/issues/3263>

³⁷⁴⁰ <https://github.com/TheHPXProject/hpx/issues/3259>

³⁷⁴¹ <https://github.com/TheHPXProject/hpx/issues/3258>

³⁷⁴² <https://github.com/TheHPXProject/hpx/issues/3247>

³⁷⁴³ <https://github.com/TheHPXProject/hpx/issues/3244>

³⁷⁴⁴ <https://github.com/TheHPXProject/hpx/issues/3215>

³⁷⁴⁵ <https://github.com/TheHPXProject/hpx/issues/3195>

³⁷⁴⁶ <https://github.com/TheHPXProject/hpx/issues/3088>

³⁷⁴⁷ <https://github.com/TheHPXProject/hpx/issues/2650>

³⁷⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1205>

³⁷⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3542>

³⁷⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3541>

³⁷⁵¹ <https://github.com/TheHPXProject/hpx/pull/3540>

³⁷⁵² <https://github.com/TheHPXProject/hpx/pull/3539>

³⁷⁵³ <https://github.com/TheHPXProject/hpx/pull/3537>

³⁷⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3536>

³⁷⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3535>

- PR #3534³⁷⁵⁶ - Fixing #3533
- PR #3532³⁷⁵⁷ - fixing minor doc typo `-hpx:print-counter-at` arg
- PR #3530³⁷⁵⁸ - Changing APEX default tag to v2.1.0
- PR #3529³⁷⁵⁹ - Remove leftover security options and documentation
- PR #3528³⁷⁶⁰ - Fix hwloc version check
- PR #3524³⁷⁶¹ - Do not build guided pool examples with older GCC compilers
- PR #3523³⁷⁶² - Fix logging regression
- PR #3522³⁷⁶³ - Fix more warnings
- PR #3521³⁷⁶⁴ - Fixing argument handling in induction and reduction clauses for `parallel::for_loop`
- PR #3520³⁷⁶⁵ - Remove docs symlink and versioned docs folders
- PR #3519³⁷⁶⁶ - hpxMP release
- PR #3518³⁷⁶⁷ - Change all steps to use new docker image on CircleCI
- PR #3516³⁷⁶⁸ - Drop usage of deprecated facilities removed in C++17
- PR #3515³⁷⁶⁹ - Remove remaining uses of `Boost.TypeTraits`
- PR #3513³⁷⁷⁰ - Fixing a CMake problem when trying to use `libfabric`
- PR #3508³⁷⁷¹ - Remove `memory_block` component
- PR #3507³⁷⁷² - Propagating the MPI compile definitions to all relevant targets
- PR #3503³⁷⁷³ - Update documentation colors and logo
- PR #3502³⁷⁷⁴ - Fix bogus ``throws`` bindings in `scheduled_thread_pool_impl`
- PR #3501³⁷⁷⁵ - Split `parallel::remove_if` tests to avoid OOM on CircleCI
- PR #3500³⁷⁷⁶ - Support `NONAMEPREFIX` in `add_hpx_library()`
- PR #3497³⁷⁷⁷ - Note that cuda support requires cmake 3.9
- PR #3495³⁷⁷⁸ - Fixing dataflow

³⁷⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3534>

³⁷⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3532>

³⁷⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3530>

³⁷⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3529>

³⁷⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3528>

³⁷⁶¹ <https://github.com/TheHPXProject/hpx/pull/3524>

³⁷⁶² <https://github.com/TheHPXProject/hpx/pull/3523>

³⁷⁶³ <https://github.com/TheHPXProject/hpx/pull/3522>

³⁷⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3521>

³⁷⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3520>

³⁷⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3519>

³⁷⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3518>

³⁷⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3516>

³⁷⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3515>

³⁷⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3513>

³⁷⁷¹ <https://github.com/TheHPXProject/hpx/pull/3508>

³⁷⁷² <https://github.com/TheHPXProject/hpx/pull/3507>

³⁷⁷³ <https://github.com/TheHPXProject/hpx/pull/3503>

³⁷⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3502>

³⁷⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3501>

³⁷⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3500>

³⁷⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3497>

³⁷⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3495>

- PR #3493³⁷⁷⁹ - Remove deprecated options for 1.2.0 part 2
- PR #3492³⁷⁸⁰ - Add CUDA_LINK_LIBRARIES_KEYWORD to allow PRIVATE keyword in linkage t...
- PR #3491³⁷⁸¹ - Changing Base docker image
- PR #3490³⁷⁸² - Don't create tasks immediately with hpx::apply
- PR #3489³⁷⁸³ - Remove deprecated options for 1.2.0
- PR #3488³⁷⁸⁴ - Revert "Use BUILD_INTERFACE generator expression to fix cmake flag exports"
- PR #3487³⁷⁸⁵ - Revert "Fixing type attribute warning for transfer_action"
- PR #3485³⁷⁸⁶ - Use BUILD_INTERFACE generator expression to fix cmake flag exports
- PR #3483³⁷⁸⁷ - Fixing type attribute warning for transfer_action
- PR #3481³⁷⁸⁸ - Remove unused variables
- PR #3480³⁷⁸⁹ - Towards a more lightweight transfer action
- PR #3479³⁷⁹⁰ - Fix FLAGS - Use correct version of target_compile_options
- PR #3478³⁷⁹¹ - Making sure the application's exit code is properly propagated back to the OS
- PR #3476³⁷⁹² - Don't print docker credentials as part of the environment.
- PR #3473³⁷⁹³ - Fixing invalid cmake code if no jemalloc prefix was given
- PR #3472³⁷⁹⁴ - Attempting to work around recent clang test compilation failures
- PR #3471³⁷⁹⁵ - Enable jemalloc on windows
- PR #3470³⁷⁹⁶ - Updates readme
- PR #3468³⁷⁹⁷ - Avoid hang if there is an exception thrown during startup
- PR #3467³⁷⁹⁸ - Add compiler specific fallback attributes if C++17 attribute is not available
- PR #3466³⁷⁹⁹ - - bugfix : fix compilation with llvm-7.0
- PR #3465³⁸⁰⁰ - This patch adds various optimizations extracted from the thread_local_allocator work
- PR #3464³⁸⁰¹ - Check for forked repos in CircleCI docker push step

³⁷⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3493>

³⁷⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3492>

³⁷⁸¹ <https://github.com/TheHPXProject/hpx/pull/3491>

³⁷⁸² <https://github.com/TheHPXProject/hpx/pull/3490>

³⁷⁸³ <https://github.com/TheHPXProject/hpx/pull/3489>

³⁷⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3488>

³⁷⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3487>

³⁷⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3485>

³⁷⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3483>

³⁷⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3481>

³⁷⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3480>

³⁷⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3479>

³⁷⁹¹ <https://github.com/TheHPXProject/hpx/pull/3478>

³⁷⁹² <https://github.com/TheHPXProject/hpx/pull/3476>

³⁷⁹³ <https://github.com/TheHPXProject/hpx/pull/3473>

³⁷⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3472>

³⁷⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3471>

³⁷⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3470>

³⁷⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3468>

³⁷⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3467>

³⁷⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3466>

³⁸⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3465>

³⁸⁰¹ <https://github.com/TheHPXProject/hpx/pull/3464>

- PR #3463³⁸⁰² - - cmake : create the parent directory before symlinking
- PR #3459³⁸⁰³ - Remove unused/incomplete functionality from util/logging
- PR #3458³⁸⁰⁴ - Fix a problem with scope of CMAKE_CXX_FLAGS and hpx_add_compile_flag
- PR #3457³⁸⁰⁵ - Fixing more size_t -> int16_t (and similar) warnings
- PR #3456³⁸⁰⁶ - Add #ifdefs to topology.cpp to support old hwloc versions again
- PR #3454³⁸⁰⁷ - Fixing warnings related to silent conversion of size_t -> int16_t
- PR #3451³⁸⁰⁸ - Add examples as unit tests
- PR #3450³⁸⁰⁹ - Constexpr-fying bind and other functional facilities
- PR #3446³⁸¹⁰ - Fix some thread suspension timeouts
- PR #3445³⁸¹¹ - Fix various warnings
- PR #3443³⁸¹² - Only enable service pool config options if pools are enabled
- PR #3441³⁸¹³ - Fix missing closing brackets in documentation
- PR #3439³⁸¹⁴ - Use correct MPI CXX libraries for MPI parcelport
- PR #3436³⁸¹⁵ - Add projection function to find_* (and fix very bad bug)
- PR #3435³⁸¹⁶ - Fixing 1205
- PR #3434³⁸¹⁷ - Fix threads cores
- PR #3433³⁸¹⁸ - Add Heise Online to release announcement list
- PR #3432³⁸¹⁹ - Don't track task dependencies for distributed runs
- PR #3431³⁸²⁰ - Circle CI setting changes for hpxMP
- PR #3430³⁸²¹ - Fix unused params warning
- PR #3429³⁸²² - One thread per core
- PR #3428³⁸²³ - This suppresses a deprecation warning that is being issued by MSVC 19.15.26726
- PR #3427³⁸²⁴ - Fixes #3426

³⁸⁰² <https://github.com/TheHPXProject/hpx/pull/3463>

³⁸⁰³ <https://github.com/TheHPXProject/hpx/pull/3459>

³⁸⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3458>

³⁸⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3457>

³⁸⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3456>

³⁸⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3454>

³⁸⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3451>

³⁸⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3450>

³⁸¹⁰ <https://github.com/TheHPXProject/hpx/pull/3446>

³⁸¹¹ <https://github.com/TheHPXProject/hpx/pull/3445>

³⁸¹² <https://github.com/TheHPXProject/hpx/pull/3443>

³⁸¹³ <https://github.com/TheHPXProject/hpx/pull/3441>

³⁸¹⁴ <https://github.com/TheHPXProject/hpx/pull/3439>

³⁸¹⁵ <https://github.com/TheHPXProject/hpx/pull/3436>

³⁸¹⁶ <https://github.com/TheHPXProject/hpx/pull/3435>

³⁸¹⁷ <https://github.com/TheHPXProject/hpx/pull/3434>

³⁸¹⁸ <https://github.com/TheHPXProject/hpx/pull/3433>

³⁸¹⁹ <https://github.com/TheHPXProject/hpx/pull/3432>

³⁸²⁰ <https://github.com/TheHPXProject/hpx/pull/3431>

³⁸²¹ <https://github.com/TheHPXProject/hpx/pull/3430>

³⁸²² <https://github.com/TheHPXProject/hpx/pull/3429>

³⁸²³ <https://github.com/TheHPXProject/hpx/pull/3428>

³⁸²⁴ <https://github.com/TheHPXProject/hpx/pull/3427>

- PR #3425³⁸²⁵ - Use source cache and workspace between job steps on CircleCI
- PR #3421³⁸²⁶ - Add CDash timing output to future overhead test (for graphs)
- PR #3420³⁸²⁷ - Add guided_pool_executor
- PR #3419³⁸²⁸ - Fix typo in CircleCI config
- PR #3418³⁸²⁹ - Add sphinx documentation
- PR #3415³⁸³⁰ - Scheduler NUMA hint and shared priority scheduler
- PR #3414³⁸³¹ - Adding step to synchronize the APEX release
- PR #3413³⁸³² - Fixing multiple defines of APEX_HAVE_HPX
- PR #3412³⁸³³ - Fixes linking with libhpx_wrap error with BSD and Windows based systems
- PR #3410³⁸³⁴ - Fix typo in CMakeLists.txt
- PR #3409³⁸³⁵ - Fix brackets and indentation in existing_performance_counters.qbk
- PR #3407³⁸³⁶ - Fix unused param and extra ; warnings emitted by gcc 8.x
- PR #3406³⁸³⁷ - Adding thread local allocator and use it for future shared states
- PR #3405³⁸³⁸ - Adding DHPX_HAVE_THREAD_LOCAL_STORAGE=ON to builds
- PR #3404³⁸³⁹ - fixing multiple definition of main() in linux
- PR #3402³⁸⁴⁰ - Allow debug option to be enabled only for Linux systems with dynamic main on
- PR #3401³⁸⁴¹ - Fix cuda_future_helper.h when compiling with C++11
- PR #3400³⁸⁴² - Fix floating point exception scheduler_base idle backoff
- PR #3398³⁸⁴³ - Atomic future state
- PR #3397³⁸⁴⁴ - Fixing code for older gcc versions
- PR #3396³⁸⁴⁵ - Allowing to register thread event functions (start/stop/error)
- PR #3394³⁸⁴⁶ - Fix small mistake in primary_namespace_server.cpp
- PR #3393³⁸⁴⁷ - Explicitly instantiate configured schedulers

³⁸²⁵ <https://github.com/TheHPXProject/hpx/pull/3425>

³⁸²⁶ <https://github.com/TheHPXProject/hpx/pull/3421>

³⁸²⁷ <https://github.com/TheHPXProject/hpx/pull/3420>

³⁸²⁸ <https://github.com/TheHPXProject/hpx/pull/3419>

³⁸²⁹ <https://github.com/TheHPXProject/hpx/pull/3418>

³⁸³⁰ <https://github.com/TheHPXProject/hpx/pull/3415>

³⁸³¹ <https://github.com/TheHPXProject/hpx/pull/3414>

³⁸³² <https://github.com/TheHPXProject/hpx/pull/3413>

³⁸³³ <https://github.com/TheHPXProject/hpx/pull/3412>

³⁸³⁴ <https://github.com/TheHPXProject/hpx/pull/3410>

³⁸³⁵ <https://github.com/TheHPXProject/hpx/pull/3409>

³⁸³⁶ <https://github.com/TheHPXProject/hpx/pull/3407>

³⁸³⁷ <https://github.com/TheHPXProject/hpx/pull/3406>

³⁸³⁸ <https://github.com/TheHPXProject/hpx/pull/3405>

³⁸³⁹ <https://github.com/TheHPXProject/hpx/pull/3404>

³⁸⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3402>

³⁸⁴¹ <https://github.com/TheHPXProject/hpx/pull/3401>

³⁸⁴² <https://github.com/TheHPXProject/hpx/pull/3400>

³⁸⁴³ <https://github.com/TheHPXProject/hpx/pull/3398>

³⁸⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3397>

³⁸⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3396>

³⁸⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3394>

³⁸⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3393>

- PR #3392³⁸⁴⁸ - Add performance counters background overhead and background work duration
- PR #3391³⁸⁴⁹ - Adapt integration of HPXMP to latest build system changes
- PR #3390³⁸⁵⁰ - Make AGAS measurements optional
- PR #3389³⁸⁵¹ - Fix deadlock during shutdown
- PR #3388³⁸⁵² - Add several functionalities allowing to optimize synchronous action invocation
- PR #3387³⁸⁵³ - Add cmake option to opt out of fail-compile tests
- PR #3386³⁸⁵⁴ - Adding support for boost::container::small_vector to dataflow
- PR #3385³⁸⁵⁵ - Adds Debug option for hpx initializing from main
- PR #3384³⁸⁵⁶ - This hopefully fixes two tests that occasionally fail
- PR #3383³⁸⁵⁷ - Making sure thread local storage is enable for hpxMP
- PR #3382³⁸⁵⁸ - Fix usage of HPX_CAPTURE together with default value capture [=]
- PR #3381³⁸⁵⁹ - Replace undefined instantiations of uniform_int_distribution
- PR #3380³⁸⁶⁰ - Add missing semicolons to uses of HPX_COMPILER_FENCE
- PR #3379³⁸⁶¹ - Fixing #3378
- PR #3377³⁸⁶² - Adding build system support to integrate hpxmp into hpx at the user's machine
- PR #3375³⁸⁶³ - Replacing wrapper for __libc_start_main with main
- PR #3374³⁸⁶⁴ - Adds hpx_wrap to HPX_LINK_LIBRARIES which links only when specified.
- PR #3373³⁸⁶⁵ - Forcing cache settings in HPXConfig.cmake to guarantee updated values
- PR #3372³⁸⁶⁶ - Fix some more c++11 build problems
- PR #3371³⁸⁶⁷ - Adds HPX_LINKER_FLAGS to HPX applications without editing their source codes
- PR #3370³⁸⁶⁸ - util::format: add type_specifier<> specializations for %!s(MISSING) and %!l(MISSING)s
- PR #3369³⁸⁶⁹ - Adding configuration option to allow explicit disable of the new hpx_main feature on Linux
- PR #3368³⁸⁷⁰ - Updates doc with recent hpx_wrap implementation

³⁸⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3392>

³⁸⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3391>

³⁸⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3390>

³⁸⁵¹ <https://github.com/TheHPXProject/hpx/pull/3389>

³⁸⁵² <https://github.com/TheHPXProject/hpx/pull/3388>

³⁸⁵³ <https://github.com/TheHPXProject/hpx/pull/3387>

³⁸⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3386>

³⁸⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3385>

³⁸⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3384>

³⁸⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3383>

³⁸⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3382>

³⁸⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3381>

³⁸⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3380>

³⁸⁶¹ <https://github.com/TheHPXProject/hpx/pull/3379>

³⁸⁶² <https://github.com/TheHPXProject/hpx/pull/3377>

³⁸⁶³ <https://github.com/TheHPXProject/hpx/pull/3375>

³⁸⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3374>

³⁸⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3373>

³⁸⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3372>

³⁸⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3371>

³⁸⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3370>

³⁸⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3369>

³⁸⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3368>

- PR #3367³⁸⁷¹ - Adds Mac OS implementation to hpx_main.hpp
- PR #3365³⁸⁷² - Fix order of hpx libs in HPX_CONF_LIBRARIES.
- PR #3363³⁸⁷³ - Apex fixing null wrapper
- PR #3361³⁸⁷⁴ - Making sure all parcels get destroyed on an HPX thread (TCP pp)
- PR #3359³⁸⁷⁵ - Feature/improve error for compiler
- PR #3357³⁸⁷⁶ - Static/dynamic executable implementation
- PR #3355³⁸⁷⁷ - Reverting changes introduced by #3283 as those make applications hang
- PR #3354³⁸⁷⁸ - Add external dependencies to HPX_LIBRARY_DIR
- PR #3353³⁸⁷⁹ - Fix libfabric tcp
- PR #3351³⁸⁸⁰ - Move obsolete header to tests directory.
- PR #3350³⁸⁸¹ - Renaming two functions to avoid problem described in #3285
- PR #3349³⁸⁸² - Make idle backoff exponential with maximum sleep time
- PR #3347³⁸⁸³ - Replace *simple_component** with *component** in the Documentation
- PR #3346³⁸⁸⁴ - Fix CMakeLists.txt example in quick start
- PR #3345³⁸⁸⁵ - Fix automatic setting of HPX_MORE_THAN_64_THREADS
- PR #3344³⁸⁸⁶ - Reduce amount of information printed for unknown command line options
- PR #3343³⁸⁸⁷ - Safeguard HPX against destruction in global contexts
- PR #3341³⁸⁸⁸ - Allowing for all command line options to be used as configuration settings
- PR #3340³⁸⁸⁹ - Always convert inspect results to JUnit XML
- PR #3336³⁸⁹⁰ - Only run docker push on master on CircleCI
- PR #3335³⁸⁹¹ - Update description of hpx.os_threads config parameter.
- PR #3334³⁸⁹² - Making sure early logging settings don't get mixed with others
- PR #3333³⁸⁹³ - Update CMake links and versions in documentation

³⁸⁷¹ <https://github.com/TheHPXProject/hpx/pull/3367>

³⁸⁷² <https://github.com/TheHPXProject/hpx/pull/3365>

³⁸⁷³ <https://github.com/TheHPXProject/hpx/pull/3363>

³⁸⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3361>

³⁸⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3359>

³⁸⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3357>

³⁸⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3355>

³⁸⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3354>

³⁸⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3353>

³⁸⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3351>

³⁸⁸¹ <https://github.com/TheHPXProject/hpx/pull/3350>

³⁸⁸² <https://github.com/TheHPXProject/hpx/pull/3349>

³⁸⁸³ <https://github.com/TheHPXProject/hpx/pull/3347>

³⁸⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3346>

³⁸⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3345>

³⁸⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3344>

³⁸⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3343>

³⁸⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3341>

³⁸⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3340>

³⁸⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3336>

³⁸⁹¹ <https://github.com/TheHPXProject/hpx/pull/3335>

³⁸⁹² <https://github.com/TheHPXProject/hpx/pull/3334>

³⁸⁹³ <https://github.com/TheHPXProject/hpx/pull/3333>

- PR #3332³⁸⁹⁴ - Add notes on target suffixes to CMake documentation
- PR #3331³⁸⁹⁵ - Add quickstart section to documentation
- PR #3330³⁸⁹⁶ - Rename resource_partitioner test to avoid conflicts with pseudodependencies
- PR #3328³⁸⁹⁷ - Making sure object is pinned while executing actions, even if action returns a future
- PR #3327³⁸⁹⁸ - Add missing std::forward to tuple.hpp
- PR #3326³⁸⁹⁹ - Make sure logging is up and running while modules are being discovered.
- PR #3324³⁹⁰⁰ - Replace C++14 overload of std::equal with C++11 code.
- PR #3323³⁹⁰¹ - Fix a missing apex thread data (wrapper) initialization
- PR #3320³⁹⁰² - Adding support for -std=c++2a (define *HPX_WITH_CXX2A=On*)
- PR #3319³⁹⁰³ - Replacing C++14 feature with equivalent C++11 code
- PR #3317³⁹⁰⁴ - Fix compilation with VS 15.7.1 and /std:c++latest
- PR #3316³⁹⁰⁵ - Fix includes for 1d_stencil_*_omp examples
- PR #3314³⁹⁰⁶ - Remove some unused parameter warnings
- PR #3313³⁹⁰⁷ - Fix pu-step and pu-offset command line options
- PR #3312³⁹⁰⁸ - Add conversion of inspect reports to JUnit XML
- PR #3311³⁹⁰⁹ - Fix escaping of closing braces in format specification syntax
- PR #3310³⁹¹⁰ - Don't overwrite user settings with defaults in registration database
- PR #3309³⁹¹¹ - Fixing potential stack overflow for dataflow
- PR #3308³⁹¹² - This updates the .clang-format configuration file to utilize newer features
- PR #3306³⁹¹³ - Marking migratable objects in their gid to allow not handling migration in AGAS
- PR #3305³⁹¹⁴ - Add proper exception handling to run_as_hpx_thread
- PR #3303³⁹¹⁵ - Changed std::rand to a better inbuilt PRNG Generator
- PR #3302³⁹¹⁶ - All non-migratable (simple) components now encode their lva and component type in their gid

³⁸⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3332>

³⁸⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3331>

³⁸⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3330>

³⁸⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3328>

³⁸⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3327>

³⁸⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3326>

³⁹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3324>

³⁹⁰¹ <https://github.com/TheHPXProject/hpx/pull/3323>

³⁹⁰² <https://github.com/TheHPXProject/hpx/pull/3320>

³⁹⁰³ <https://github.com/TheHPXProject/hpx/pull/3319>

³⁹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3317>

³⁹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3316>

³⁹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3314>

³⁹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3313>

³⁹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3312>

³⁹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3311>

³⁹¹⁰ <https://github.com/TheHPXProject/hpx/pull/3310>

³⁹¹¹ <https://github.com/TheHPXProject/hpx/pull/3309>

³⁹¹² <https://github.com/TheHPXProject/hpx/pull/3308>

³⁹¹³ <https://github.com/TheHPXProject/hpx/pull/3306>

³⁹¹⁴ <https://github.com/TheHPXProject/hpx/pull/3305>

³⁹¹⁵ <https://github.com/TheHPXProject/hpx/pull/3303>

³⁹¹⁶ <https://github.com/TheHPXProject/hpx/pull/3302>

- PR #3301³⁹¹⁷ - Add nullptr_t overloads to resource partitioner
- PR #3298³⁹¹⁸ - Apex task wrapper memory bug
- PR #3295³⁹¹⁹ - Fix mistakes after merge of CircleCI config
- PR #3294³⁹²⁰ - Fix partitioned vector include in partitioned_vector_find tests
- PR #3293³⁹²¹ - Adding emplace support to promise and make_ready_future
- PR #3292³⁹²² - Add new cuda kernel synchronization with hpx::future demo
- PR #3291³⁹²³ - Fixes #3290
- PR #3289³⁹²⁴ - Fixing Docker image creation
- PR #3288³⁹²⁵ - Avoid allocating shared state for wait_all
- PR #3287³⁹²⁶ - Fixing /scheduler/utilization/instantaneous performance counter
- PR #3286³⁹²⁷ - dataflow() and future::then() use sync policy where possible
- PR #3284³⁹²⁸ - Background thread can use relaxed atomics to manipulate thread state
- PR #3283³⁹²⁹ - Do not unwrap ready future
- PR #3282³⁹³⁰ - Fix virtual method override warnings in static schedulers
- PR #3281³⁹³¹ - Disable set_area_membind_nodeset for OSX
- PR #3279³⁹³² - Add two variations to the future_overhead benchmark
- PR #3278³⁹³³ - Fix circleci workspace
- PR #3277³⁹³⁴ - Support external plugins
- PR #3276³⁹³⁵ - Fix missing parenthesis in hello_compute.cu.
- PR #3274³⁹³⁶ - Reinit counters synchronously in reinit_counters test
- PR #3273³⁹³⁷ - Splitting tests to avoid compiler OOM
- PR #3271³⁹³⁸ - Remove leftover code from context_generic_context.hpp
- PR #3269³⁹³⁹ - Fix bulk_construct with count = 0

³⁹¹⁷ <https://github.com/TheHPXProject/hpx/pull/3301>

³⁹¹⁸ <https://github.com/TheHPXProject/hpx/pull/3298>

³⁹¹⁹ <https://github.com/TheHPXProject/hpx/pull/3295>

³⁹²⁰ <https://github.com/TheHPXProject/hpx/pull/3294>

³⁹²¹ <https://github.com/TheHPXProject/hpx/pull/3293>

³⁹²² <https://github.com/TheHPXProject/hpx/pull/3292>

³⁹²³ <https://github.com/TheHPXProject/hpx/pull/3291>

³⁹²⁴ <https://github.com/TheHPXProject/hpx/pull/3289>

³⁹²⁵ <https://github.com/TheHPXProject/hpx/pull/3288>

³⁹²⁶ <https://github.com/TheHPXProject/hpx/pull/3287>

³⁹²⁷ <https://github.com/TheHPXProject/hpx/pull/3286>

³⁹²⁸ <https://github.com/TheHPXProject/hpx/pull/3284>

³⁹²⁹ <https://github.com/TheHPXProject/hpx/pull/3283>

³⁹³⁰ <https://github.com/TheHPXProject/hpx/pull/3282>

³⁹³¹ <https://github.com/TheHPXProject/hpx/pull/3281>

³⁹³² <https://github.com/TheHPXProject/hpx/pull/3279>

³⁹³³ <https://github.com/TheHPXProject/hpx/pull/3278>

³⁹³⁴ <https://github.com/TheHPXProject/hpx/pull/3277>

³⁹³⁵ <https://github.com/TheHPXProject/hpx/pull/3276>

³⁹³⁶ <https://github.com/TheHPXProject/hpx/pull/3274>

³⁹³⁷ <https://github.com/TheHPXProject/hpx/pull/3273>

³⁹³⁸ <https://github.com/TheHPXProject/hpx/pull/3271>

³⁹³⁹ <https://github.com/TheHPXProject/hpx/pull/3269>

- PR #3268³⁹⁴⁰ - Replace constexpr with HPX_CXX14_CONSTEXPR and HPX_CONSTEXPR
- PR #3266³⁹⁴¹ - Replace boost::format with custom sprintf-based implementation
- PR #3265³⁹⁴² - Split parallel tests on CircleCI
- PR #3262³⁹⁴³ - Making sure documentation correctly links to source files
- PR #3261³⁹⁴⁴ - Apex refactoring fix rebind
- PR #3260³⁹⁴⁵ - Isolate performance counter parser into a separate TU
- PR #3256³⁹⁴⁶ - Post 1.1.0 version bumps
- PR #3254³⁹⁴⁷ - Adding trait for actions allowing to make runtime decision on whether to execute it directly
- PR #3253³⁹⁴⁸ - Bump minimal supported Boost to 1.58.0
- PR #3251³⁹⁴⁹ - Adds new feature: changing interval used in interval_timer (issue 3244)
- PR #3239³⁹⁵⁰ - Changing std::rand() to a better inbuilt PRNG generator.
- PR #3234³⁹⁵¹ - Disable background thread when networking is off
- PR #3232³⁹⁵² - Clean up suspension tests
- PR #3230³⁹⁵³ - Add optional scheduler mode parameter to create_thread_pool function
- PR #3228³⁹⁵⁴ - Allow suspension also on static schedulers
- PR #3163³⁹⁵⁵ - libfabric parcelport w/o HPX_PARCELPORTR_LIBFABRIC_ENDPOINT_RDM
- PR #3036³⁹⁵⁶ - Switching to CircleCI 2.0

HPX V1.1.0 (Mar 24, 2018)

General changes

Here are some of the main highlights and changes for this release (in no particular order):

- We have changed the way *HPX* manages the processing units on a node. We do not longer implicitly bind all available cores to a single thread pool. The user has now full control over what processing units are bound to what thread pool, each with a separate scheduler. It is now also possible to create your own scheduler implementation and control what processing units this scheduler should use. We added the `hpx::resource::partitioner` that manages all available processing units and assigns resources to the used thread pools. Thread pools can be

³⁹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3268>

³⁹⁴¹ <https://github.com/TheHPXProject/hpx/pull/3266>

³⁹⁴² <https://github.com/TheHPXProject/hpx/pull/3265>

³⁹⁴³ <https://github.com/TheHPXProject/hpx/pull/3262>

³⁹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3261>

³⁹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3260>

³⁹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3256>

³⁹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3254>

³⁹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3253>

³⁹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3251>

³⁹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3239>

³⁹⁵¹ <https://github.com/TheHPXProject/hpx/pull/3234>

³⁹⁵² <https://github.com/TheHPXProject/hpx/pull/3232>

³⁹⁵³ <https://github.com/TheHPXProject/hpx/pull/3230>

³⁹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3228>

³⁹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3163>

³⁹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3036>

now be suspended/resumed independently. This functionality helps in running *HPX* concurrently to code that is directly relying on [OpenMP](https://openmp.org/wp/)³⁹⁵⁷ and/or [MPI](https://en.wikipedia.org/wiki/Message_Passing_Interface)³⁹⁵⁸.

- We have continued to implement various parallel algorithms. *HPX* now almost completely implements all of the parallel algorithms as specified by the [C++17 Standard](http://www.open-std.org/jtc1/sc22/wg21)³⁹⁵⁹. We have also continued to implement these algorithms for the distributed use case (for segmented data structures, such as `hpx::partitioned_vector`).
- Added a compatibility layer for `std::thread`, `std::mutex`, and `std::condition_variable` allowing for the code to use those facilities where available and to fall back to the corresponding Boost facilities otherwise. The [CMake](https://www.cmake.org)³⁹⁶⁰ configuration option `-DHPX_WITH_THREAD_COMPATIBILITY=On` can be used to force using the Boost equivalents.
- The parameter sequence for the `hpx::parallel::transform_inclusive_scan` overload taking one iterator range has changed (again) to match the changes this algorithm has undergone while being moved to C++17. The old overloads can be still enabled at configure time by passing `-DHPX_WITH_TRANSFORM_REDUCE_COMPATIBILITY=On` to [CMake](https://www.cmake.org)³⁹⁶¹.
- The parameter sequence for the `hpx::parallel::inclusive_scan` overload taking one iterator range has changed to match the changes this algorithm has undergone while being moved to C++17. The old overloads can be still enabled at configure time by passing `-DHPX_WITH_INCLUSIVE_SCAN_COMPATIBILITY=On` to [CMake](https://www.cmake.org).
- Added a helper facility `hpx::local_new` which is equivalent to `hpx::new_` except that it creates components locally only. As a consequence, the used component constructor may accept non-serializable argument types and/or non-const references or pointers.
- Removed the (broken) component type `hpx::lcos::queue<T>`. The old type is still available at configure time by passing `-DHPX_WITH_QUEUE_COMPATIBILITY=On` to [CMake](https://www.cmake.org).
- The parallel algorithms adopted for C++17 restrict the iterator categories usable with those to at least forward iterators. Our implementation of the parallel algorithms was supporting input iterators (and output iterators) as well by simply falling back to sequential execution. We have now made our implementations conforming by requiring at least forward iterators. In order to enable the old behavior use the compatibility option `-DHPX_WITH_ALGORITHM_INPUT_ITERATOR_SUPPORT=On` on the [CMake](https://www.cmake.org)³⁹⁶² command line.
- We have added the functionalities allowing for LCOs being implemented using (simple) components. Before LCOs had to always be implemented using managed components.
- User defined components don't have to be default-constructible anymore. Return types from actions don't have to be default-constructible anymore either. Our serialization layer now in general supports non-default-constructible types.
- We have added a new launch policy `hpx::launch::lazy` that allows one to defer the decision on what launch policy to use to the point of execution. This policy is initialized with a function (object) that – when invoked – is expected to produce the desired launch policy.

³⁹⁵⁷ <https://openmp.org/wp/>

³⁹⁵⁸ https://en.wikipedia.org/wiki/Message_Passing_Interface

³⁹⁵⁹ <http://www.open-std.org/jtc1/sc22/wg21>

³⁹⁶⁰ <https://www.cmake.org>

³⁹⁶¹ <https://www.cmake.org>

³⁹⁶² <https://www.cmake.org>

Breaking changes

- We have dropped support for the gcc compiler version V4.8. The minimal gcc version we now test on is gcc V4.9. The minimally required version of [CMake](https://www.cmake.org)³⁹⁶³ is now V3.3.2.
- We have dropped support for the Visual Studio 2013 compiler version. The minimal Visual Studio version we now test on is Visual Studio 2015.5.
- We have dropped support for the Boost V1.51-V1.54. The minimal version of Boost we now test is Boost V1.55.
- We have dropped support for the `hpx::util::unwrapped` API. `hpx::util::unwrapped` will stay functional to some degree, until it finally gets removed in a later version of HPX. The functional usage of `hpx::util::unwrapped` should be changed to the new `hpx::util::unwrapping` function whereas the immediate usage should be replaced to `hpx::util::unwrap`.
- The performance counter names referring to properties as exposed by the threading subsystem have changes as those now additionally have to specify the thread-pool. See the corresponding documentation for more details.
- The overloads of `hpx::async` that invoke an action do not perform implicit unwrapping of the returned future anymore in case the invoked function does return a future in the first place. In this case `hpx::async` now returns a `hpx::future<future<T>>` making its behavior conforming to its local counterpart.
- We have replaced the use of `boost::exception_ptr` in our APIs with the equivalent `std::exception_ptr`. Please change your codes accordingly. No compatibility settings are provided.
- We have removed the compatibility settings for `HPX_WITH_COLOCATED_BACKWARDS_COMPATIBILITY` and `HPX_WITH_COMPONENT_GET_GID_COMPATIBILITY` as their life-cycle has reached its end.
- We have removed the experimental thread schedulers `hierarchy_scheduler`, `periodic_priority_scheduler` and `throttling_scheduler` in an effort to clean up and consolidate our thread schedulers.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [PR #3250](#)³⁹⁶⁴ - Apex refactoring with guides
- [PR #3249](#)³⁹⁶⁵ - Updating People.qbk
- [PR #3246](#)³⁹⁶⁶ - Assorted fixes for CUDA
- [PR #3245](#)³⁹⁶⁷ - Apex refactoring with guides
- [PR #3242](#)³⁹⁶⁸ - Modify task counting in `thread_queue.hpp`
- [PR #3240](#)³⁹⁶⁹ - Fixed typos
- [PR #3238](#)³⁹⁷⁰ - Readding accidentally removed `std::abort`
- [PR #3237](#)³⁹⁷¹ - Adding Pipeline example
- [PR #3236](#)³⁹⁷² - Fixing `memory_block`

³⁹⁶³ <https://www.cmake.org>

³⁹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3250>

³⁹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3249>

³⁹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3246>

³⁹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3245>

³⁹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3242>

³⁹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3240>

³⁹⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3238>

³⁹⁷¹ <https://github.com/TheHPXProject/hpx/pull/3237>

³⁹⁷² <https://github.com/TheHPXProject/hpx/pull/3236>

- PR #3233³⁹⁷³ - Make `schedule_thread` take suspended threads into account
- Issue #3226³⁹⁷⁴ - `memory_block` is breaking, signaling SIGSEGV on a thread on creation and freeing
- PR #3225³⁹⁷⁵ - Applying quick fix for `hwloc-2.0`
- Issue #3224³⁹⁷⁶ - HPX counters crashing the application
- PR #3223³⁹⁷⁷ - Fix returns when setting config entries
- Issue #3222³⁹⁷⁸ - Errors linking `libhpx.so`
- Issue #3221³⁹⁷⁹ - HPX on Mac OS X with `HWLoc 2.0.0` fails to run
- PR #3216³⁹⁸⁰ - Reorder a variadic array to satisfy VS 2017 15.6
- PR #3214³⁹⁸¹ - Changed `prerequisites.qbk` to avoid confusion while building boost
- PR #3213³⁹⁸² - Relax locks for thread suspension to avoid holding locks when yielding
- PR #3212³⁹⁸³ - Fix check in `sequenced_executor` test
- PR #3211³⁹⁸⁴ - Use `preinit_array` to set `argc/argv` in `init_globally` example
- PR #3210³⁹⁸⁵ - Adapted `parallel::{search | search_n}` for Ranges TS (see #1668)
- PR #3209³⁹⁸⁶ - Fix locking problems during shutdown
- Issue #3208³⁹⁸⁷ - `init_globally` throwing a run-time error
- PR #3206³⁹⁸⁸ - Addition of new arithmetic performance counter “Count”
- PR #3205³⁹⁸⁹ - Fixing return type calculation for `bulk_then_execute`
- PR #3204³⁹⁹⁰ - Changing `std::rand()` to a better inbuilt PRNG generator
- PR #3203³⁹⁹¹ - Resolving problems during shutdown for VS2015
- PR #3202³⁹⁹² - Making sure resource partitioner is not accessed if its not valid
- PR #3201³⁹⁹³ - Fixing `optional::swap`
- Issue #3200³⁹⁹⁴ - `hpx::util::optional` fails
- PR #3199³⁹⁹⁵ - Fix `sliding_semaphore` test

³⁹⁷³ <https://github.com/TheHPXProject/hpx/pull/3233>

³⁹⁷⁴ <https://github.com/TheHPXProject/hpx/issues/3226>

³⁹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3225>

³⁹⁷⁶ <https://github.com/TheHPXProject/hpx/issues/3224>

³⁹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3223>

³⁹⁷⁸ <https://github.com/TheHPXProject/hpx/issues/3222>

³⁹⁷⁹ <https://github.com/TheHPXProject/hpx/issues/3221>

³⁹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3216>

³⁹⁸¹ <https://github.com/TheHPXProject/hpx/pull/3214>

³⁹⁸² <https://github.com/TheHPXProject/hpx/pull/3213>

³⁹⁸³ <https://github.com/TheHPXProject/hpx/pull/3212>

³⁹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3211>

³⁹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3210>

³⁹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3209>

³⁹⁸⁷ <https://github.com/TheHPXProject/hpx/issues/3208>

³⁹⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3206>

³⁹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3205>

³⁹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3204>

³⁹⁹¹ <https://github.com/TheHPXProject/hpx/pull/3203>

³⁹⁹² <https://github.com/TheHPXProject/hpx/pull/3202>

³⁹⁹³ <https://github.com/TheHPXProject/hpx/pull/3201>

³⁹⁹⁴ <https://github.com/TheHPXProject/hpx/issues/3200>

³⁹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/3199>

- PR #3198³⁹⁹⁶ - Set pre_main status before launching run_helper
- PR #3197³⁹⁹⁷ - Update README.rst
- PR #3194³⁹⁹⁸ - parallel::{fill|fill_n} updated for Ranges TS
- PR #3193³⁹⁹⁹ - Updating Runtime.cpp by adding correct description of Performance counters during register
- PR #3191⁴⁰⁰⁰ - Fix sliding_semaphore_2338 test
- PR #3190⁴⁰⁰¹ - Topology improvements
- PR #3189⁴⁰⁰² - Deleting one include of median from BOOST library to arithmetics_counter file
- PR #3188⁴⁰⁰³ - Optionally disable printing of diagnostics during terminate
- PR #3187⁴⁰⁰⁴ - Suppressing cmake warning issued by cmake > V3.11
- PR #3185⁴⁰⁰⁵ - Remove unused scoped_unlock, unlock_guard_try
- PR #3184⁴⁰⁰⁶ - Fix nqueen example
- PR #3183⁴⁰⁰⁷ - Add runtime start/stop, resume/suspend and OpenMP benchmarks
- Issue #3182⁴⁰⁰⁸ - bulk_then_execute has unexpected return type/does not compile
- Issue #3181⁴⁰⁰⁹ - hwloc 2.0 breaks topo class and cannot be used
- Issue #3180⁴⁰¹⁰ - Schedulers that don't support suspend/resume are unusable
- PR #3179⁴⁰¹¹ - Various minor changes to support FLeCSI
- PR #3178⁴⁰¹² - Fix #3124
- PR #3177⁴⁰¹³ - Removed allgather
- PR #3176⁴⁰¹⁴ - Fixed Documentation for "using_hpx_pkgconfig"
- PR #3174⁴⁰¹⁵ - Add hpx::iostream::ostream overload to format_to
- PR #3172⁴⁰¹⁶ - Fix lifo queue backend
- PR #3171⁴⁰¹⁷ - adding the missing unset() function to cpu_mask() for case of more than 64 threads
- PR #3170⁴⁰¹⁸ - Add cmake flag -DHPX_WITH_FAULT_TOLERANCE=ON (OFF by default)

³⁹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3198>

³⁹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3197>

³⁹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3194>

³⁹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3193>

⁴⁰⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3191>

⁴⁰⁰¹ <https://github.com/TheHPXProject/hpx/pull/3190>

⁴⁰⁰² <https://github.com/TheHPXProject/hpx/pull/3189>

⁴⁰⁰³ <https://github.com/TheHPXProject/hpx/pull/3188>

⁴⁰⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3187>

⁴⁰⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3185>

⁴⁰⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3184>

⁴⁰⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3183>

⁴⁰⁰⁸ <https://github.com/TheHPXProject/hpx/issues/3182>

⁴⁰⁰⁹ <https://github.com/TheHPXProject/hpx/issues/3181>

⁴⁰¹⁰ <https://github.com/TheHPXProject/hpx/issues/3180>

⁴⁰¹¹ <https://github.com/TheHPXProject/hpx/pull/3179>

⁴⁰¹² <https://github.com/TheHPXProject/hpx/pull/3178>

⁴⁰¹³ <https://github.com/TheHPXProject/hpx/pull/3177>

⁴⁰¹⁴ <https://github.com/TheHPXProject/hpx/pull/3176>

⁴⁰¹⁵ <https://github.com/TheHPXProject/hpx/pull/3174>

⁴⁰¹⁶ <https://github.com/TheHPXProject/hpx/pull/3172>

⁴⁰¹⁷ <https://github.com/TheHPXProject/hpx/pull/3171>

⁴⁰¹⁸ <https://github.com/TheHPXProject/hpx/pull/3170>

- PR #3169⁴⁰¹⁹ - Adapted parallel::{count|count_if} for Ranges TS (see #1668)
- PR #3168⁴⁰²⁰ - Changing used namespace for seq execution policy
- Issue #3167⁴⁰²¹ - Update GSoC projects
- Issue #3166⁴⁰²² - Application (Octotiger) gets stuck on hpx::finalize when only using one thread
- Issue #3165⁴⁰²³ - Compilation of parallel algorithms with HPX_WITH_DATAPAR is broken
- PR #3164⁴⁰²⁴ - Fixing component migration
- PR #3162⁴⁰²⁵ - regex_from_pattern: escape regex special characters to avoid misinterpretation
- Issue #3161⁴⁰²⁶ - Building HPX with hwloc 2.0.0 fails
- PR #3160⁴⁰²⁷ - Fixing the handling of quoted command line arguments.
- PR #3158⁴⁰²⁸ - Fixing a race with timed suspension (second attempt)
- PR #3157⁴⁰²⁹ - Revert “Fixing a race with timed suspension”
- PR #3156⁴⁰³⁰ - Fixing serialization of classes with incompatible serialize signature
- PR #3154⁴⁰³¹ - More refactorings based on clang-tidy reports
- PR #3153⁴⁰³² - Fixing a race with timed suspension
- PR #3152⁴⁰³³ - Documentation for runtime suspension
- PR #3151⁴⁰³⁴ - Use small_vector only from boost version 1.59 onwards
- PR #3150⁴⁰³⁵ - Avoiding more stack overflows
- PR #3148⁴⁰³⁶ - Refactoring component_base and base_action/transfer_base_action
- PR #3147⁴⁰³⁷ - Move yield_while out of detail namespace and into own file
- PR #3145⁴⁰³⁸ - Remove a leftover of the cxx11 std array cleanup
- PR #3144⁴⁰³⁹ - Minor changes to how actions are executed
- PR #3143⁴⁰⁴⁰ - Fix stack overhead
- PR #3142⁴⁰⁴¹ - Fix typo in config.hpp

⁴⁰¹⁹ <https://github.com/TheHPXProject/hpx/pull/3169>

⁴⁰²⁰ <https://github.com/TheHPXProject/hpx/pull/3168>

⁴⁰²¹ <https://github.com/TheHPXProject/hpx/issues/3167>

⁴⁰²² <https://github.com/TheHPXProject/hpx/issues/3166>

⁴⁰²³ <https://github.com/TheHPXProject/hpx/issues/3165>

⁴⁰²⁴ <https://github.com/TheHPXProject/hpx/pull/3164>

⁴⁰²⁵ <https://github.com/TheHPXProject/hpx/pull/3162>

⁴⁰²⁶ <https://github.com/TheHPXProject/hpx/issues/3161>

⁴⁰²⁷ <https://github.com/TheHPXProject/hpx/pull/3160>

⁴⁰²⁸ <https://github.com/TheHPXProject/hpx/pull/3158>

⁴⁰²⁹ <https://github.com/TheHPXProject/hpx/pull/3157>

⁴⁰³⁰ <https://github.com/TheHPXProject/hpx/pull/3156>

⁴⁰³¹ <https://github.com/TheHPXProject/hpx/pull/3154>

⁴⁰³² <https://github.com/TheHPXProject/hpx/pull/3153>

⁴⁰³³ <https://github.com/TheHPXProject/hpx/pull/3152>

⁴⁰³⁴ <https://github.com/TheHPXProject/hpx/pull/3151>

⁴⁰³⁵ <https://github.com/TheHPXProject/hpx/pull/3150>

⁴⁰³⁶ <https://github.com/TheHPXProject/hpx/pull/3148>

⁴⁰³⁷ <https://github.com/TheHPXProject/hpx/pull/3147>

⁴⁰³⁸ <https://github.com/TheHPXProject/hpx/pull/3145>

⁴⁰³⁹ <https://github.com/TheHPXProject/hpx/pull/3144>

⁴⁰⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3143>

⁴⁰⁴¹ <https://github.com/TheHPXProject/hpx/pull/3142>

- PR #3141⁴⁰⁴² - Fixing small_vector compatibility with older boost version
- PR #3140⁴⁰⁴³ - is_heap_text fix
- Issue #3139⁴⁰⁴⁴ - Error in is_heap_tests.hpp
- PR #3138⁴⁰⁴⁵ - Partially reverting #3126
- PR #3137⁴⁰⁴⁶ - Suspend speedup
- PR #3136⁴⁰⁴⁷ - Revert “Fixing #2325”
- PR #3135⁴⁰⁴⁸ - Improving destruction of threads
- Issue #3134⁴⁰⁴⁹ - HPX_SERIALIZATION_SPLIT_FREE does not stop compiler from looking for serialize() method
- PR #3133⁴⁰⁵⁰ - Make hwloc compulsory
- PR #3132⁴⁰⁵¹ - Update CXX14 constexpr feature test
- PR #3131⁴⁰⁵² - Fixing #2325
- PR #3130⁴⁰⁵³ - Avoid completion handler allocation
- PR #3129⁴⁰⁵⁴ - Suspend runtime
- PR #3128⁴⁰⁵⁵ - Make docbook dtd and xsl path names consistent
- PR #3127⁴⁰⁵⁶ - Add hpx::start nullptr overloads
- PR #3126⁴⁰⁵⁷ - Cleaning up coroutine implementation
- PR #3125⁴⁰⁵⁸ - Replacing nullptr with hpx::threads::invalid_thread_id
- Issue #3124⁴⁰⁵⁹ - Add hello_world_component to CI builds
- PR #3123⁴⁰⁶⁰ - Add new constructor.
- PR #3122⁴⁰⁶¹ - Fixing #3121
- Issue #3121⁴⁰⁶² - HPX_SMT_PAUSE is broken on non-x86 platforms when __GNUC__ is defined
- PR #3120⁴⁰⁶³ - Don't use boost::intrusive_ptr for thread_id_type
- PR #3119⁴⁰⁶⁴ - Disable default executor compatibility with V1 executors

⁴⁰⁴² <https://github.com/TheHPXProject/hpx/pull/3141>

⁴⁰⁴³ <https://github.com/TheHPXProject/hpx/pull/3140>

⁴⁰⁴⁴ <https://github.com/TheHPXProject/hpx/issues/3139>

⁴⁰⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3138>

⁴⁰⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3137>

⁴⁰⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3136>

⁴⁰⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3135>

⁴⁰⁴⁹ <https://github.com/TheHPXProject/hpx/issues/3134>

⁴⁰⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3133>

⁴⁰⁵¹ <https://github.com/TheHPXProject/hpx/pull/3132>

⁴⁰⁵² <https://github.com/TheHPXProject/hpx/pull/3131>

⁴⁰⁵³ <https://github.com/TheHPXProject/hpx/pull/3130>

⁴⁰⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3129>

⁴⁰⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3128>

⁴⁰⁵⁶ <https://github.com/TheHPXProject/hpx/pull/3127>

⁴⁰⁵⁷ <https://github.com/TheHPXProject/hpx/pull/3126>

⁴⁰⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3125>

⁴⁰⁵⁹ <https://github.com/TheHPXProject/hpx/issues/3124>

⁴⁰⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3123>

⁴⁰⁶¹ <https://github.com/TheHPXProject/hpx/pull/3122>

⁴⁰⁶² <https://github.com/TheHPXProject/hpx/issues/3121>

⁴⁰⁶³ <https://github.com/TheHPXProject/hpx/pull/3120>

⁴⁰⁶⁴ <https://github.com/TheHPXProject/hpx/pull/3119>

- PR #3118⁴⁰⁶⁵ - Adding performance_counter::reinit to allow for dynamically changing counter sets
- PR #3117⁴⁰⁶⁶ - Replace uses of boost/experimental::optional with util::optional
- PR #3116⁴⁰⁶⁷ - Moving background thread APEX timer #2980
- PR #3115⁴⁰⁶⁸ - Fixing race condition in channel test
- PR #3114⁴⁰⁶⁹ - Avoid using util::function for thread function wrappers
- PR #3113⁴⁰⁷⁰ - cmake V3.10.2 has changed the variable names used for MPI
- PR #3112⁴⁰⁷¹ - Minor fixes to exclusive_scan algorithm
- PR #3111⁴⁰⁷² - Revert “fix detection of cxx11_std_atomic”
- PR #3110⁴⁰⁷³ - Suspend thread pool
- PR #3109⁴⁰⁷⁴ - Fixing thread scheduling when yielding a thread id
- PR #3108⁴⁰⁷⁵ - Revert “Suspend thread pool”
- PR #3107⁴⁰⁷⁶ - Remove UB from thread::id relational operators
- PR #3106⁴⁰⁷⁷ - Add cmake test for std::decay_t to fix cuda build
- PR #3105⁴⁰⁷⁸ - Fixing refcount for async traversal frame
- PR #3104⁴⁰⁷⁹ - Local execution of direct actions is now actually performed directly
- PR #3103⁴⁰⁸⁰ - Adding support for generic counter_raw_values performance counter type
- Issue #3102⁴⁰⁸¹ - Introduce generic performance counter type returning an array of values
- PR #3101⁴⁰⁸² - Revert “Adapting stack overhead limit for gcc 4.9”
- PR #3100⁴⁰⁸³ - Fix #3068 (condition_variable deadlock)
- PR #3099⁴⁰⁸⁴ - Fixing lock held during suspension in papi counter component
- PR #3098⁴⁰⁸⁵ - Unbreak broadcast_wait_for_2822 test
- PR #3097⁴⁰⁸⁶ - Adapting stack overhead limit for gcc 4.9
- PR #3096⁴⁰⁸⁷ - fix detection of cxx11_std_atomic

⁴⁰⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3118>
⁴⁰⁶⁶ <https://github.com/TheHPXProject/hpx/pull/3117>
⁴⁰⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3116>
⁴⁰⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3115>
⁴⁰⁶⁹ <https://github.com/TheHPXProject/hpx/pull/3114>
⁴⁰⁷⁰ <https://github.com/TheHPXProject/hpx/pull/3113>
⁴⁰⁷¹ <https://github.com/TheHPXProject/hpx/pull/3112>
⁴⁰⁷² <https://github.com/TheHPXProject/hpx/pull/3111>
⁴⁰⁷³ <https://github.com/TheHPXProject/hpx/pull/3110>
⁴⁰⁷⁴ <https://github.com/TheHPXProject/hpx/pull/3109>
⁴⁰⁷⁵ <https://github.com/TheHPXProject/hpx/pull/3108>
⁴⁰⁷⁶ <https://github.com/TheHPXProject/hpx/pull/3107>
⁴⁰⁷⁷ <https://github.com/TheHPXProject/hpx/pull/3106>
⁴⁰⁷⁸ <https://github.com/TheHPXProject/hpx/pull/3105>
⁴⁰⁷⁹ <https://github.com/TheHPXProject/hpx/pull/3104>
⁴⁰⁸⁰ <https://github.com/TheHPXProject/hpx/pull/3103>
⁴⁰⁸¹ <https://github.com/TheHPXProject/hpx/issues/3102>
⁴⁰⁸² <https://github.com/TheHPXProject/hpx/pull/3101>
⁴⁰⁸³ <https://github.com/TheHPXProject/hpx/pull/3100>
⁴⁰⁸⁴ <https://github.com/TheHPXProject/hpx/pull/3099>
⁴⁰⁸⁵ <https://github.com/TheHPXProject/hpx/pull/3098>
⁴⁰⁸⁶ <https://github.com/TheHPXProject/hpx/pull/3097>
⁴⁰⁸⁷ <https://github.com/TheHPXProject/hpx/pull/3096>

- PR #3095⁴⁰⁸⁸ - Add ciso646 header to get `_LIBCPP_VERSION` for testing inplace merge
- PR #3094⁴⁰⁸⁹ - Relax atomic operations on performance counter values
- PR #3093⁴⁰⁹⁰ - Short-circuit `all_of/any_of/none_of` instantiations
- PR #3092⁴⁰⁹¹ - Take advantage of C++14 lambda capture initialization syntax, where possible
- PR #3091⁴⁰⁹² - Remove more references to Boost from logging code
- PR #3090⁴⁰⁹³ - Unify use of `yield/yield_k`
- PR #3089⁴⁰⁹⁴ - Fix a strange thing in `parallel::detail::handle_exception`. (Fix #2834.)
- Issue #3088⁴⁰⁹⁵ - A strange thing in `parallel::sort`.
- PR #3087⁴⁰⁹⁶ - Fixing assertion in `default_distribution_policy`
- PR #3086⁴⁰⁹⁷ - Implement `parallel::remove` and `parallel::remove_if`
- PR #3085⁴⁰⁹⁸ - Addressing breaking changes in Boost V1.66
- PR #3084⁴⁰⁹⁹ - Ignore build warnings round 2
- PR #3083⁴¹⁰⁰ - Fix typo `HPX_WITH_MM_PREFECTH`
- PR #3081⁴¹⁰¹ - Pre-decay template arguments early
- PR #3080⁴¹⁰² - Suspend thread pool
- PR #3079⁴¹⁰³ - Ignore build warnings
- PR #3078⁴¹⁰⁴ - Don't test `inplace_merge` with `libc++`
- PR #3076⁴¹⁰⁵ - Fixing 3075: Part 1
- PR #3074⁴¹⁰⁶ - Fix more build warnings
- PR #3073⁴¹⁰⁷ - Suspend thread cleanup
- PR #3072⁴¹⁰⁸ - Change existing `symbol_namespace::iterate` to return all data instead of invoking a callback
- PR #3071⁴¹⁰⁹ - Fixing `pack_traversal_async` test
- PR #3070⁴¹¹⁰ - Fix `dynamic_counters_loaded_1508` test by adding dependency to `memory_component`

⁴⁰⁸⁸ <https://github.com/TheHPXProject/hpx/pull/3095>
⁴⁰⁸⁹ <https://github.com/TheHPXProject/hpx/pull/3094>
⁴⁰⁹⁰ <https://github.com/TheHPXProject/hpx/pull/3093>
⁴⁰⁹¹ <https://github.com/TheHPXProject/hpx/pull/3092>
⁴⁰⁹² <https://github.com/TheHPXProject/hpx/pull/3091>
⁴⁰⁹³ <https://github.com/TheHPXProject/hpx/pull/3090>
⁴⁰⁹⁴ <https://github.com/TheHPXProject/hpx/pull/3089>
⁴⁰⁹⁵ <https://github.com/TheHPXProject/hpx/issues/3088>
⁴⁰⁹⁶ <https://github.com/TheHPXProject/hpx/pull/3087>
⁴⁰⁹⁷ <https://github.com/TheHPXProject/hpx/pull/3086>
⁴⁰⁹⁸ <https://github.com/TheHPXProject/hpx/pull/3085>
⁴⁰⁹⁹ <https://github.com/TheHPXProject/hpx/pull/3084>
⁴¹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/3083>
⁴¹⁰¹ <https://github.com/TheHPXProject/hpx/pull/3081>
⁴¹⁰² <https://github.com/TheHPXProject/hpx/pull/3080>
⁴¹⁰³ <https://github.com/TheHPXProject/hpx/pull/3079>
⁴¹⁰⁴ <https://github.com/TheHPXProject/hpx/pull/3078>
⁴¹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/3076>
⁴¹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/3074>
⁴¹⁰⁷ <https://github.com/TheHPXProject/hpx/pull/3073>
⁴¹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/3072>
⁴¹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/3071>
⁴¹¹⁰ <https://github.com/TheHPXProject/hpx/pull/3070>

- PR #3069⁴¹¹¹ - Fix scheduling loop exit
- Issue #3068⁴¹¹² - `hpx::lcos::condition_variable` could be suspect to deadlocks
- PR #3067⁴¹¹³ - `#ifdef` out `random_shuffle` deprecated in later c++
- PR #3066⁴¹¹⁴ - Make coalescing test depend on coalescing library to ensure it gets built
- PR #3065⁴¹¹⁵ - Workaround for `minimal_timed_async_executor_test` compilation failures, attempts to copy a deferred call (in unevaluated context)
- PR #3064⁴¹¹⁶ - Fixing wrong condition in `wrapper_heap`
- PR #3062⁴¹¹⁷ - Fix exception handling for `execution::seq`
- PR #3061⁴¹¹⁸ - Adapt MSVC C++ mode handling to VS15.5
- PR #3060⁴¹¹⁹ - Fix compiler problem in MSVC release mode
- PR #3059⁴¹²⁰ - Fixing #2931
- Issue #3058⁴¹²¹ - `minimal_timed_async_executor_test_exe` fails to compile on master (d6f505c)
- PR #3057⁴¹²² - Fix `stable_merge_2964` compilation problems
- PR #3056⁴¹²³ - Fix some build warnings caused by unused variables/unnecessary tests
- PR #3055⁴¹²⁴ - Update documentation for running tests
- Issue #3054⁴¹²⁵ - Assertion failure when using bulk `hpx::new_` in asynchronous mode
- PR #3052⁴¹²⁶ - Do not bind test running to `cmake` test build rule
- PR #3051⁴¹²⁷ - Fix HPX-Qt interaction in Qt example.
- Issue #3048⁴¹²⁸ - `nqueen` example fails occasionally
- PR #3047⁴¹²⁹ - Fixing #3044
- PR #3046⁴¹³⁰ - Add OS thread suspension
- PR #3042⁴¹³¹ - PyCicle - first attempt at a build tool for checking PR's
- PR #3041⁴¹³² - Fix a problem about asynchronous execution of `parallel::merge` and `parallel::partition`.
- PR #3040⁴¹³³ - Fix a mistake about exception handling in asynchronous execution of `scan_partitioner`.

⁴¹¹¹ <https://github.com/TheHPXProject/hpx/pull/3069>

⁴¹¹² <https://github.com/TheHPXProject/hpx/issues/3068>

⁴¹¹³ <https://github.com/TheHPXProject/hpx/pull/3067>

⁴¹¹⁴ <https://github.com/TheHPXProject/hpx/pull/3066>

⁴¹¹⁵ <https://github.com/TheHPXProject/hpx/pull/3065>

⁴¹¹⁶ <https://github.com/TheHPXProject/hpx/pull/3064>

⁴¹¹⁷ <https://github.com/TheHPXProject/hpx/pull/3062>

⁴¹¹⁸ <https://github.com/TheHPXProject/hpx/pull/3061>

⁴¹¹⁹ <https://github.com/TheHPXProject/hpx/pull/3060>

⁴¹²⁰ <https://github.com/TheHPXProject/hpx/pull/3059>

⁴¹²¹ <https://github.com/TheHPXProject/hpx/issues/3058>

⁴¹²² <https://github.com/TheHPXProject/hpx/pull/3057>

⁴¹²³ <https://github.com/TheHPXProject/hpx/pull/3056>

⁴¹²⁴ <https://github.com/TheHPXProject/hpx/pull/3055>

⁴¹²⁵ <https://github.com/TheHPXProject/hpx/issues/3054>

⁴¹²⁶ <https://github.com/TheHPXProject/hpx/pull/3052>

⁴¹²⁷ <https://github.com/TheHPXProject/hpx/pull/3051>

⁴¹²⁸ <https://github.com/TheHPXProject/hpx/issues/3048>

⁴¹²⁹ <https://github.com/TheHPXProject/hpx/pull/3047>

⁴¹³⁰ <https://github.com/TheHPXProject/hpx/pull/3046>

⁴¹³¹ <https://github.com/TheHPXProject/hpx/pull/3042>

⁴¹³² <https://github.com/TheHPXProject/hpx/pull/3041>

⁴¹³³ <https://github.com/TheHPXProject/hpx/pull/3040>

- PR #3039⁴¹³⁴ - Consistently use executors to schedule work
- PR #3038⁴¹³⁵ - Fixing local direct function execution and lambda actions perfect forwarding
- PR #3035⁴¹³⁶ - Make parallel unit test names match build target/folder names
- PR #3033⁴¹³⁷ - Fix setting of default build type
- Issue #3032⁴¹³⁸ - Fix partitioner arg copy found in #2982
- Issue #3031⁴¹³⁹ - Errors linking libhpx.so due to missing references (master branch, commit 6679a8882)
- PR #3030⁴¹⁴⁰ - Revert “implement executor then interface with && forwarding reference”
- PR #3029⁴¹⁴¹ - Run CI inspect checks before building
- PR #3028⁴¹⁴² - Added range version of parallel::move
- Issue #3027⁴¹⁴³ - Implement all scheduling APIs in terms of executors
- PR #3026⁴¹⁴⁴ - implement executor then interface with && forwarding reference
- PR #3025⁴¹⁴⁵ - Fix typo uninitialized to uninitialized
- PR #3024⁴¹⁴⁶ - Inspect fixes
- PR #3023⁴¹⁴⁷ - P0356 Simplified partial function application
- PR #3022⁴¹⁴⁸ - Master fixes
- PR #3021⁴¹⁴⁹ - Segfault fix
- PR #3020⁴¹⁵⁰ - Disable command-line aliasing for applications that use user_main
- PR #3019⁴¹⁵¹ - Adding enable_elasticity option to pool configuration
- PR #3018⁴¹⁵² - Fix stack overflow detection configuration in header files
- PR #3017⁴¹⁵³ - Speed up local action execution
- PR #3016⁴¹⁵⁴ - Unify stack-overflow detection options, remove reference to libsigsegv
- PR #3015⁴¹⁵⁵ - Speeding up accessing the resource partitioner and the topology info
- Issue #3014⁴¹⁵⁶ - HPX does not compile on POWER8 with gcc 5.4

⁴¹³⁴ <https://github.com/TheHPXProject/hpx/pull/3039>

⁴¹³⁵ <https://github.com/TheHPXProject/hpx/pull/3038>

⁴¹³⁶ <https://github.com/TheHPXProject/hpx/pull/3035>

⁴¹³⁷ <https://github.com/TheHPXProject/hpx/pull/3033>

⁴¹³⁸ <https://github.com/TheHPXProject/hpx/issues/3032>

⁴¹³⁹ <https://github.com/TheHPXProject/hpx/issues/3031>

⁴¹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/3030>

⁴¹⁴¹ <https://github.com/TheHPXProject/hpx/pull/3029>

⁴¹⁴² <https://github.com/TheHPXProject/hpx/pull/3028>

⁴¹⁴³ <https://github.com/TheHPXProject/hpx/issues/3027>

⁴¹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/3026>

⁴¹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/3025>

⁴¹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/3024>

⁴¹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/3023>

⁴¹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/3022>

⁴¹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/3021>

⁴¹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/3020>

⁴¹⁵¹ <https://github.com/TheHPXProject/hpx/pull/3019>

⁴¹⁵² <https://github.com/TheHPXProject/hpx/pull/3018>

⁴¹⁵³ <https://github.com/TheHPXProject/hpx/pull/3017>

⁴¹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/3016>

⁴¹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/3015>

⁴¹⁵⁶ <https://github.com/TheHPXProject/hpx/issues/3014>

- [Issue #3013](#)⁴¹⁵⁷ - hello_world occasionally prints multiple lines from a single OS-thread
- [PR #3012](#)⁴¹⁵⁸ - Silence warning about casting away qualifiers in itt_notify.hpp
- [PR #3011](#)⁴¹⁵⁹ - Fix cpuset leak in hwloc_topology_info.cpp
- [PR #3010](#)⁴¹⁶⁰ - Remove useless decay_copy
- [PR #3009](#)⁴¹⁶¹ - Fixing 2996
- [PR #3008](#)⁴¹⁶² - Remove unused internal function
- [PR #3007](#)⁴¹⁶³ - Fixing wrapper_heap alignment problems
- [Issue #3006](#)⁴¹⁶⁴ - hwloc memory leak
- [PR #3004](#)⁴¹⁶⁵ - Silence C4251 (needs to have dll-interface) for future_data_void
- [Issue #3003](#)⁴¹⁶⁶ - Suspension of runtime
- [PR #3001](#)⁴¹⁶⁷ - Attempting to avoid data races in async_traversal while evaluating dataflow()
- [PR #3000](#)⁴¹⁶⁸ - Adding hpx::util::optional as a first step to replace experimental::optional
- [PR #2998](#)⁴¹⁶⁹ - Cleanup up and Fixing component creation and deletion
- [Issue #2996](#)⁴¹⁷⁰ - Build fails with HPX_WITH_HWLOC=OFF
- [PR #2995](#)⁴¹⁷¹ - Push more future_data functionality to source file
- [PR #2994](#)⁴¹⁷² - WIP: Fix throttle test
- [PR #2993](#)⁴¹⁷³ - Making sure -hpx:help does not throw for required (but missing) arguments
- [PR #2992](#)⁴¹⁷⁴ - Adding non-blocking (on destruction) service executors
- [Issue #2991](#)⁴¹⁷⁵ - run_as_os_thread locks up
- [Issue #2990](#)⁴¹⁷⁶ - -help will not work until all required options are provided
- [PR #2989](#)⁴¹⁷⁷ - Improve error messages caused by misuse of dataflow
- [PR #2988](#)⁴¹⁷⁸ - Improve error messages caused by misuse of .then
- [Issue #2987](#)⁴¹⁷⁹ - stack overflow detection producing false positives

⁴¹⁵⁷ <https://github.com/TheHPXProject/hpx/issues/3013>

⁴¹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/3012>

⁴¹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/3011>

⁴¹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/3010>

⁴¹⁶¹ <https://github.com/TheHPXProject/hpx/pull/3009>

⁴¹⁶² <https://github.com/TheHPXProject/hpx/pull/3008>

⁴¹⁶³ <https://github.com/TheHPXProject/hpx/pull/3007>

⁴¹⁶⁴ <https://github.com/TheHPXProject/hpx/issues/3006>

⁴¹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/3004>

⁴¹⁶⁶ <https://github.com/TheHPXProject/hpx/issues/3003>

⁴¹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/3001>

⁴¹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/3000>

⁴¹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2998>

⁴¹⁷⁰ <https://github.com/TheHPXProject/hpx/issues/2996>

⁴¹⁷¹ <https://github.com/TheHPXProject/hpx/pull/2995>

⁴¹⁷² <https://github.com/TheHPXProject/hpx/pull/2994>

⁴¹⁷³ <https://github.com/TheHPXProject/hpx/pull/2993>

⁴¹⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2992>

⁴¹⁷⁵ <https://github.com/TheHPXProject/hpx/issues/2991>

⁴¹⁷⁶ <https://github.com/TheHPXProject/hpx/issues/2990>

⁴¹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2989>

⁴¹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2988>

⁴¹⁷⁹ <https://github.com/TheHPXProject/hpx/issues/2987>

- PR #2986⁴¹⁸⁰ - Deduplicate non-dependent thread_info logging types
- PR #2985⁴¹⁸¹ - Adapted parallel::{all_of|any_of|none_of} for Ranges TS (see #1668)
- PR #2984⁴¹⁸² - Refactor one_size_heap code to simplify code
- PR #2983⁴¹⁸³ - Fixing local_new_component
- PR #2982⁴¹⁸⁴ - Clang tidy
- PR #2981⁴¹⁸⁵ - Simplify allocator rebinding in pack traversal
- PR #2979⁴¹⁸⁶ - Fixing integer overflows
- PR #2978⁴¹⁸⁷ - Implement parallel::inplace_merge
- Issue #2977⁴¹⁸⁸ - Make hwloc compulsory instead of optional
- PR #2976⁴¹⁸⁹ - Making sure client_base instance that registered the component does not unregister it when being destructed
- PR #2975⁴¹⁹⁰ - Change version of pulled APEX to master
- PR #2974⁴¹⁹¹ - Fix domain not being freed at the end of scheduling loop
- PR #2973⁴¹⁹² - Fix small typos
- PR #2972⁴¹⁹³ - Adding uintstd.h header
- PR #2971⁴¹⁹⁴ - Fall back to creating local components using local_new
- PR #2970⁴¹⁹⁵ - Improve is_tuple_like trait
- PR #2969⁴¹⁹⁶ - Fix HPX_WITH_MORE_THAN_64_THREADS default value
- PR #2968⁴¹⁹⁷ - Cleaning up dataflow overload set
- PR #2967⁴¹⁹⁸ - Make parallel::merge is stable. (Fix #2964.)
- PR #2966⁴¹⁹⁹ - Fixing a couple of held locks during exception handling
- PR #2965⁴²⁰⁰ - Adding missing #include
- Issue #2964⁴²⁰¹ - parallel merge is not stable
- PR #2963⁴²⁰² - Making sure any function object passed to dataflow is released after being invoked

⁴¹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2986>
⁴¹⁸¹ <https://github.com/TheHPXProject/hpx/pull/2985>
⁴¹⁸² <https://github.com/TheHPXProject/hpx/pull/2984>
⁴¹⁸³ <https://github.com/TheHPXProject/hpx/pull/2983>
⁴¹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2982>
⁴¹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2981>
⁴¹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2979>
⁴¹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2978>
⁴¹⁸⁸ <https://github.com/TheHPXProject/hpx/issues/2977>
⁴¹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2976>
⁴¹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2975>
⁴¹⁹¹ <https://github.com/TheHPXProject/hpx/pull/2974>
⁴¹⁹² <https://github.com/TheHPXProject/hpx/pull/2973>
⁴¹⁹³ <https://github.com/TheHPXProject/hpx/pull/2972>
⁴¹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/2971>
⁴¹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2970>
⁴¹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2969>
⁴¹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2968>
⁴¹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2967>
⁴¹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2966>
⁴²⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2965>
⁴²⁰¹ <https://github.com/TheHPXProject/hpx/issues/2964>
⁴²⁰² <https://github.com/TheHPXProject/hpx/pull/2963>

- PR #2962⁴²⁰³ - Partially reverting #2891
- PR #2961⁴²⁰⁴ - Attempt to fix the gcc 4.9 problem with the async pack traversal
- Issue #2959⁴²⁰⁵ - Program terminates during error handling
- Issue #2958⁴²⁰⁶ - HPX_PLAIN_ACTION breaks due to missing include
- PR #2957⁴²⁰⁷ - Fixing errors generated by mixing different attribute syntaxes
- Issue #2956⁴²⁰⁸ - Mixing attribute syntaxes leads to compiler errors
- Issue #2955⁴²⁰⁹ - Fix OS-Thread throttling
- PR #2953⁴²¹⁰ - Making sure any hpx.os_threads=N supplied through a -hpx::config file is taken into account
- PR #2952⁴²¹¹ - Removing wrong call to cleanup_terminated_locked
- PR #2951⁴²¹² - Revert “Make sure the function vtables are initialized before use”
- PR #2950⁴²¹³ - Fix a namespace compilation error when some schedulers are disabled
- Issue #2949⁴²¹⁴ - master branch giving lockups on shutdown
- Issue #2947⁴²¹⁵ - hpx.ini is not used correctly at initialization
- PR #2946⁴²¹⁶ - Adding explicit feature test for thread_local
- PR #2945⁴²¹⁷ - Make sure the function vtables are initialized before use
- PR #2944⁴²¹⁸ - Attempting to solve affinity problems on CircleCI
- PR #2943⁴²¹⁹ - Changing channel actions to be direct
- PR #2942⁴²²⁰ - Adding split_future for std::vector
- PR #2941⁴²²¹ - Add a feature test to test for CXX11 override
- Issue #2940⁴²²² - Add split_future for future<vector<T>>
- PR #2939⁴²²³ - Making error reporting during problems with setting affinity masks more verbose
- PR #2938⁴²²⁴ - Fix this various executors
- PR #2937⁴²²⁵ - Fix some typos in documentation

⁴²⁰³ <https://github.com/TheHPXProject/hpx/pull/2962>

⁴²⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2961>

⁴²⁰⁵ <https://github.com/TheHPXProject/hpx/issues/2959>

⁴²⁰⁶ <https://github.com/TheHPXProject/hpx/issues/2958>

⁴²⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2957>

⁴²⁰⁸ <https://github.com/TheHPXProject/hpx/issues/2956>

⁴²⁰⁹ <https://github.com/TheHPXProject/hpx/issues/2955>

⁴²¹⁰ <https://github.com/TheHPXProject/hpx/pull/2953>

⁴²¹¹ <https://github.com/TheHPXProject/hpx/pull/2952>

⁴²¹² <https://github.com/TheHPXProject/hpx/pull/2951>

⁴²¹³ <https://github.com/TheHPXProject/hpx/pull/2950>

⁴²¹⁴ <https://github.com/TheHPXProject/hpx/issues/2949>

⁴²¹⁵ <https://github.com/TheHPXProject/hpx/issues/2947>

⁴²¹⁶ <https://github.com/TheHPXProject/hpx/pull/2946>

⁴²¹⁷ <https://github.com/TheHPXProject/hpx/pull/2945>

⁴²¹⁸ <https://github.com/TheHPXProject/hpx/pull/2944>

⁴²¹⁹ <https://github.com/TheHPXProject/hpx/pull/2943>

⁴²²⁰ <https://github.com/TheHPXProject/hpx/pull/2942>

⁴²²¹ <https://github.com/TheHPXProject/hpx/pull/2941>

⁴²²² <https://github.com/TheHPXProject/hpx/issues/2940>

⁴²²³ <https://github.com/TheHPXProject/hpx/pull/2939>

⁴²²⁴ <https://github.com/TheHPXProject/hpx/pull/2938>

⁴²²⁵ <https://github.com/TheHPXProject/hpx/pull/2937>

- PR #2934⁴²²⁶ - Remove the need for “complete” SFINAE checks
- PR #2933⁴²²⁷ - Making sure parallel::for_loop is executed in parallel if requested
- PR #2932⁴²²⁸ - Classify chunk_size_iterator to input iterator tag. (Fix #2866)
- Issue #2931⁴²²⁹ - --hpx:help triggers unusual error with clang build
- PR #2930⁴²³⁰ - Add #include files needed to set _POSIX_VERSION for debug check
- PR #2929⁴²³¹ - Fix a couple of deprecated c++ features
- PR #2928⁴²³² - Fixing execution parameters
- Issue #2927⁴²³³ - CMake warning: ... cycle in constraint graph
- PR #2926⁴²³⁴ - Default pool rename
- Issue #2925⁴²³⁵ - Default pool cannot be renamed
- Issue #2924⁴²³⁶ - hpx:attach-debugger=startup does not work any more
- PR #2923⁴²³⁷ - Alloc membind
- PR #2922⁴²³⁸ - This fixes CircleCI errors when running with --hpx:bind=none
- PR #2921⁴²³⁹ - Custom pool executor was missing priority and stacksize options
- PR #2920⁴²⁴⁰ - Adding test to trigger problem reported in #2916
- PR #2919⁴²⁴¹ - Make sure the resource_partitioner is properly destructed on hpx::finalize
- Issue #2918⁴²⁴² - hpx::init calls wrong (first) callback when called multiple times
- PR #2917⁴²⁴³ - Adding util::checkpoint
- Issue #2916⁴²⁴⁴ - Weird runtime failures when using a channel and chained continuations
- PR #2915⁴²⁴⁵ - Introduce executor parameters customization points
- Issue #2914⁴²⁴⁶ - Task assignment to current Pool has unintended consequences
- PR #2913⁴²⁴⁷ - Fix rp hang
- PR #2912⁴²⁴⁸ - Update contributors

⁴²²⁶ <https://github.com/TheHPXProject/hpx/pull/2934>
⁴²²⁷ <https://github.com/TheHPXProject/hpx/pull/2933>
⁴²²⁸ <https://github.com/TheHPXProject/hpx/pull/2932>
⁴²²⁹ <https://github.com/TheHPXProject/hpx/issues/2931>
⁴²³⁰ <https://github.com/TheHPXProject/hpx/pull/2930>
⁴²³¹ <https://github.com/TheHPXProject/hpx/pull/2929>
⁴²³² <https://github.com/TheHPXProject/hpx/pull/2928>
⁴²³³ <https://github.com/TheHPXProject/hpx/issues/2927>
⁴²³⁴ <https://github.com/TheHPXProject/hpx/pull/2926>
⁴²³⁵ <https://github.com/TheHPXProject/hpx/issues/2925>
⁴²³⁶ <https://github.com/TheHPXProject/hpx/issues/2924>
⁴²³⁷ <https://github.com/TheHPXProject/hpx/pull/2923>
⁴²³⁸ <https://github.com/TheHPXProject/hpx/pull/2922>
⁴²³⁹ <https://github.com/TheHPXProject/hpx/pull/2921>
⁴²⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2920>
⁴²⁴¹ <https://github.com/TheHPXProject/hpx/pull/2919>
⁴²⁴² <https://github.com/TheHPXProject/hpx/issues/2918>
⁴²⁴³ <https://github.com/TheHPXProject/hpx/pull/2917>
⁴²⁴⁴ <https://github.com/TheHPXProject/hpx/issues/2916>
⁴²⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2915>
⁴²⁴⁶ <https://github.com/TheHPXProject/hpx/issues/2914>
⁴²⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2913>
⁴²⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2912>

- [PR #2911⁴²⁴⁹](#) - Fixing CUDA problems
- [PR #2910⁴²⁵⁰](#) - Improve error reporting for process component on POSIX systems
- [PR #2909⁴²⁵¹](#) - Fix typo in include path
- [PR #2908⁴²⁵²](#) - Use proper container according to iterator tag in benchmarks of parallel algorithms
- [PR #2907⁴²⁵³](#) - Optionally force-delete remaining channel items on close
- [PR #2906⁴²⁵⁴](#) - Making sure generated performance counter names are correct
- [Issue #2905⁴²⁵⁵](#) - collecting idle-rate performance counters on multiple localities produces an error
- [Issue #2904⁴²⁵⁶](#) - build broken for Intel 17 compilers
- [PR #2903⁴²⁵⁷](#) - Documentation Updates– Adding New People
- [PR #2902⁴²⁵⁸](#) - Fixing service_executor
- [PR #2901⁴²⁵⁹](#) - Fixing partitioned_vector creation
- [PR #2900⁴²⁶⁰](#) - Add numa-balanced mode to hpx::bind, spread cores over numa domains
- [Issue #2899⁴²⁶¹](#) - hpx::bind does not have a mode that balances cores over numa domains
- [PR #2898⁴²⁶²](#) - Adding missing #include and missing guard for optional code section
- [PR #2897⁴²⁶³](#) - Removing dependency on Boost.ICL
- [Issue #2896⁴²⁶⁴](#) - Debug build fails without -fpermissive with GCC 7.1 and Boost 1.65
- [PR #2895⁴²⁶⁵](#) - Fixing SLURM environment parsing
- [PR #2894⁴²⁶⁶](#) - Fix incorrect handling of compile definition with value 0
- [Issue #2893⁴²⁶⁷](#) - Disabling schedulers causes build errors
- [PR #2892⁴²⁶⁸](#) - added list serializer
- [PR #2891⁴²⁶⁹](#) - Resource Partitioner Fixes
- [Issue #2890⁴²⁷⁰](#) - Destroying a non-empty channel causes an assertion failure
- [PR #2889⁴²⁷¹](#) - Add check for libatomic

⁴²⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2911>

⁴²⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2910>

⁴²⁵¹ <https://github.com/TheHPXProject/hpx/pull/2909>

⁴²⁵² <https://github.com/TheHPXProject/hpx/pull/2908>

⁴²⁵³ <https://github.com/TheHPXProject/hpx/pull/2907>

⁴²⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2906>

⁴²⁵⁵ <https://github.com/TheHPXProject/hpx/issues/2905>

⁴²⁵⁶ <https://github.com/TheHPXProject/hpx/issues/2904>

⁴²⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2903>

⁴²⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2902>

⁴²⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2901>

⁴²⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2900>

⁴²⁶¹ <https://github.com/TheHPXProject/hpx/issues/2899>

⁴²⁶² <https://github.com/TheHPXProject/hpx/pull/2898>

⁴²⁶³ <https://github.com/TheHPXProject/hpx/pull/2897>

⁴²⁶⁴ <https://github.com/TheHPXProject/hpx/issues/2896>

⁴²⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2895>

⁴²⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2894>

⁴²⁶⁷ <https://github.com/TheHPXProject/hpx/issues/2893>

⁴²⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2892>

⁴²⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2891>

⁴²⁷⁰ <https://github.com/TheHPXProject/hpx/issues/2890>

⁴²⁷¹ <https://github.com/TheHPXProject/hpx/pull/2889>

- PR #2888⁴²⁷² - Fix compilation problems if HPX_WITH_ITT_NOTIFY=ON
- PR #2887⁴²⁷³ - Adapt broadcast() to non-unwrapping async<Action>
- PR #2886⁴²⁷⁴ - Replace Boost.Random with C++11 <random>
- Issue #2885⁴²⁷⁵ - regression in broadcast?
- Issue #2884⁴²⁷⁶ - linking -latomic is not portable
- PR #2883⁴²⁷⁷ - Explicitly set -pthread flag if available
- PR #2882⁴²⁷⁸ - Wrap boost::format uses
- Issue #2881⁴²⁷⁹ - hpx not compiling with HPX_WITH_ITTNOTIFY=On
- Issue #2880⁴²⁸⁰ - hpx::bind scatter/balanced give wrong pu masks
- PR #2878⁴²⁸¹ - Fix incorrect pool usage masks setup in RP/thread manager
- PR #2877⁴²⁸² - Require std::array by default
- PR #2875⁴²⁸³ - Deprecate use of BOOST_ASSERT
- PR #2874⁴²⁸⁴ - Changed serialization of boost.variant to use variadic templates
- Issue #2873⁴²⁸⁵ - building with parcelport_mpi fails on cori
- PR #2871⁴²⁸⁶ - Adding missing support for throttling scheduler
- PR #2870⁴²⁸⁷ - Disambiguate use of base_lco_with_value macros with channel
- Issue #2869⁴²⁸⁸ - Difficulty compiling HPX_REGISTER_CHANNEL_DECLARATION(double)
- PR #2868⁴²⁸⁹ - Removing unneeded assert
- PR #2867⁴²⁹⁰ - Implement parallel::unique
- Issue #2866⁴²⁹¹ - The chunk_size_iterator violates multipass guarantee
- PR #2865⁴²⁹² - Only use sched_getcpu on linux machines
- PR #2864⁴²⁹³ - Create redistribution archive for successful builds
- PR #2863⁴²⁹⁴ - Replace casts/assignments with hard-coded memcpy operations

⁴²⁷² <https://github.com/TheHPXProject/hpx/pull/2888>

⁴²⁷³ <https://github.com/TheHPXProject/hpx/pull/2887>

⁴²⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2886>

⁴²⁷⁵ <https://github.com/TheHPXProject/hpx/issues/2885>

⁴²⁷⁶ <https://github.com/TheHPXProject/hpx/issues/2884>

⁴²⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2883>

⁴²⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2882>

⁴²⁷⁹ <https://github.com/TheHPXProject/hpx/issues/2881>

⁴²⁸⁰ <https://github.com/TheHPXProject/hpx/issues/2880>

⁴²⁸¹ <https://github.com/TheHPXProject/hpx/pull/2878>

⁴²⁸² <https://github.com/TheHPXProject/hpx/pull/2877>

⁴²⁸³ <https://github.com/TheHPXProject/hpx/pull/2875>

⁴²⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2874>

⁴²⁸⁵ <https://github.com/TheHPXProject/hpx/issues/2873>

⁴²⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2871>

⁴²⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2870>

⁴²⁸⁸ <https://github.com/TheHPXProject/hpx/issues/2869>

⁴²⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2868>

⁴²⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2867>

⁴²⁹¹ <https://github.com/TheHPXProject/hpx/issues/2866>

⁴²⁹² <https://github.com/TheHPXProject/hpx/pull/2865>

⁴²⁹³ <https://github.com/TheHPXProject/hpx/pull/2864>

⁴²⁹⁴ <https://github.com/TheHPXProject/hpx/pull/2863>

- [Issue #2862](#)⁴²⁹⁵ - sched_getcpu not available on MacOS
- [PR #2861](#)⁴²⁹⁶ - Fixing unmatched header defines and recursive inclusion of threadmanager
- [Issue #2860](#)⁴²⁹⁷ - Master program fails with assertion 'type == data_type_address' failed: HPX(assertion_failure)
- [Issue #2852](#)⁴²⁹⁸ - Support for ARM64
- [PR #2858](#)⁴²⁹⁹ - Fix misplaced #if #endif's that cause build failure without THREAD_CUMULATIVE_COUNTS
- [PR #2857](#)⁴³⁰⁰ - Fix some listing in documentation
- [PR #2856](#)⁴³⁰¹ - Fixing component handling for lcos
- [PR #2855](#)⁴³⁰² - Add documentation for coarrays
- [PR #2854](#)⁴³⁰³ - Support ARM64 in timestamps
- [PR #2853](#)⁴³⁰⁴ - Update Table 17. Non-modifying Parallel Algorithms in Documentation
- [PR #2851](#)⁴³⁰⁵ - Allowing for non-default-constructible component types
- [PR #2850](#)⁴³⁰⁶ - Enable returning future<R> from actions where R is not default-constructible
- [PR #2849](#)⁴³⁰⁷ - Unify serialization of non-default-constructable types
- [Issue #2848](#)⁴³⁰⁸ - Components have to be default constructible
- [Issue #2847](#)⁴³⁰⁹ - Returning a future<R> where R is not default-constructable broken
- [Issue #2846](#)⁴³¹⁰ - Unify serialization of non-default-constructible types
- [PR #2845](#)⁴³¹¹ - Add Visual Studio 2015 to the tested toolchains in Appveyor
- [Issue #2844](#)⁴³¹² - Change the appveyor build to use the minimal required MSVC version
- [Issue #2843](#)⁴³¹³ - multi node hello_world hangs
- [PR #2842](#)⁴³¹⁴ - Correcting Spelling mistake in docs
- [PR #2841](#)⁴³¹⁵ - Fix usage of std::aligned_storage
- [PR #2840](#)⁴³¹⁶ - Remove constexpr from a void function
- [Issue #2839](#)⁴³¹⁷ - memcpy buffer overflow: load_construct_data() and std::complex members

⁴²⁹⁵ <https://github.com/TheHPXProject/hpx/issues/2862>

⁴²⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2861>

⁴²⁹⁷ <https://github.com/TheHPXProject/hpx/issues/2860>

⁴²⁹⁸ <https://github.com/TheHPXProject/hpx/issues/2852>

⁴²⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2858>

⁴³⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2857>

⁴³⁰¹ <https://github.com/TheHPXProject/hpx/pull/2856>

⁴³⁰² <https://github.com/TheHPXProject/hpx/pull/2855>

⁴³⁰³ <https://github.com/TheHPXProject/hpx/pull/2854>

⁴³⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2853>

⁴³⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2851>

⁴³⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2850>

⁴³⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2849>

⁴³⁰⁸ <https://github.com/TheHPXProject/hpx/issues/2848>

⁴³⁰⁹ <https://github.com/TheHPXProject/hpx/issues/2847>

⁴³¹⁰ <https://github.com/TheHPXProject/hpx/issues/2846>

⁴³¹¹ <https://github.com/TheHPXProject/hpx/pull/2845>

⁴³¹² <https://github.com/TheHPXProject/hpx/issues/2844>

⁴³¹³ <https://github.com/TheHPXProject/hpx/issues/2843>

⁴³¹⁴ <https://github.com/TheHPXProject/hpx/pull/2842>

⁴³¹⁵ <https://github.com/TheHPXProject/hpx/pull/2841>

⁴³¹⁶ <https://github.com/TheHPXProject/hpx/pull/2840>

⁴³¹⁷ <https://github.com/TheHPXProject/hpx/issues/2839>

- [Issue #2835](#)⁴³¹⁸ - `constexpr` functions with void return type break compilation with CUDA 8.0
- [Issue #2834](#)⁴³¹⁹ - One suspicion in `parallel::detail::handle_exception`
- [PR #2833](#)⁴³²⁰ - Implement `parallel::merge`
- [PR #2832](#)⁴³²¹ - Fix a strange thing in `parallel::util::detail::handle_local_exceptions`. (Fix #2818)
- [PR #2830](#)⁴³²² - Break the debugger when a test failed
- [Issue #2831](#)⁴³²³ - `parallel/executors/execution_fwd.hpp` causes compilation failure in C++11 mode.
- [PR #2829](#)⁴³²⁴ - Implement an API for asynchronous pack traversal
- [PR #2828](#)⁴³²⁵ - Split unit test builds on CircleCI to avoid timeouts
- [Issue #2827](#)⁴³²⁶ - failure to compile `hello_world` example with `-Werror`
- [PR #2824](#)⁴³²⁷ - Making sure promises are marked as started when used as continuations
- [PR #2823](#)⁴³²⁸ - Add documentation for `partitioned_vector_view`
- [Issue #2822](#)⁴³²⁹ - Yet another issue with `wait_for` similar to #2796
- [PR #2821](#)⁴³³⁰ - Fix bugs and improve that about `HPX_HAVE_CXX11_AUTO_RETURN_VALUE` of CMake
- [PR #2820](#)⁴³³¹ - Support C++11 in benchmark codes of `parallel::partition` and `parallel::partition_copy`
- [PR #2819](#)⁴³³² - Fix compile errors in unit test of container version of `parallel::partition`
- [Issue #2818](#)⁴³³³ - A strange thing in `parallel::util::detail::handle_local_exceptions`
- [Issue #2815](#)⁴³³⁴ - HPX fails to compile with `HPX_WITH_CUDA=ON` and the new CUDA 9.0 RC
- [Issue #2814](#)⁴³³⁵ - Using 'gmakeN' after 'cmake' produces error in `src/CMakeFiles/hpx.dir/runtime/agas/addressing_service.cpp.o`
- [PR #2813](#)⁴³³⁶ - Properly support `[[noreturn]]` attribute if available
- [Issue #2812](#)⁴³³⁷ - Compilation fails with gcc 7.1.1
- [PR #2811](#)⁴³³⁸ - Adding `hpx::launch::lazy` and support for `async`, `dataflow`, and `future::then`
- [PR #2810](#)⁴³³⁹ - Add option allowing to disable deprecation warning
- [PR #2809](#)⁴³⁴⁰ - Disable throttling scheduler if HWLOC is not found/used

⁴³¹⁸ <https://github.com/TheHPXProject/hpx/issues/2835>

⁴³¹⁹ <https://github.com/TheHPXProject/hpx/issues/2834>

⁴³²⁰ <https://github.com/TheHPXProject/hpx/pull/2833>

⁴³²¹ <https://github.com/TheHPXProject/hpx/pull/2832>

⁴³²² <https://github.com/TheHPXProject/hpx/pull/2830>

⁴³²³ <https://github.com/TheHPXProject/hpx/issues/2831>

⁴³²⁴ <https://github.com/TheHPXProject/hpx/pull/2829>

⁴³²⁵ <https://github.com/TheHPXProject/hpx/pull/2828>

⁴³²⁶ <https://github.com/TheHPXProject/hpx/issues/2827>

⁴³²⁷ <https://github.com/TheHPXProject/hpx/pull/2824>

⁴³²⁸ <https://github.com/TheHPXProject/hpx/pull/2823>

⁴³²⁹ <https://github.com/TheHPXProject/hpx/issues/2822>

⁴³³⁰ <https://github.com/TheHPXProject/hpx/pull/2821>

⁴³³¹ <https://github.com/TheHPXProject/hpx/pull/2820>

⁴³³² <https://github.com/TheHPXProject/hpx/pull/2819>

⁴³³³ <https://github.com/TheHPXProject/hpx/issues/2818>

⁴³³⁴ <https://github.com/TheHPXProject/hpx/issues/2815>

⁴³³⁵ <https://github.com/TheHPXProject/hpx/issues/2814>

⁴³³⁶ <https://github.com/TheHPXProject/hpx/pull/2813>

⁴³³⁷ <https://github.com/TheHPXProject/hpx/issues/2812>

⁴³³⁸ <https://github.com/TheHPXProject/hpx/pull/2811>

⁴³³⁹ <https://github.com/TheHPXProject/hpx/pull/2810>

⁴³⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2809>

- PR #2808⁴³⁴¹ - Fix compile errors on some environments of `parallel::partition`
- Issue #2807⁴³⁴² - Difficulty building with `HPX_WITH_HWLOC=Off`
- PR #2806⁴³⁴³ - Partitioned vector
- PR #2805⁴³⁴⁴ - Serializing collections with non-default constructible data
- PR #2802⁴³⁴⁵ - Fix FreeBSD 11
- Issue #2801⁴³⁴⁶ - Rate limiting techniques in `io_service`
- Issue #2800⁴³⁴⁷ - New Launch Policy: `async_if`
- PR #2799⁴³⁴⁸ - Fix a unit test failure on GCC in `tuple_cat`
- PR #2798⁴³⁴⁹ - bump minimum required cmake to 3.0 in test
- PR #2797⁴³⁵⁰ - Making sure `future::wait_for` et.al. work properly for action results
- Issue #2796⁴³⁵¹ - `wait_for` does always in “deferred” state for calls on remote localities
- Issue #2795⁴³⁵² - Serialization of types without default constructor
- PR #2794⁴³⁵³ - Fixing test for `partitioned_vector` iteration
- PR #2792⁴³⁵⁴ - Implemented segmented find and its variations for partitioned vector
- PR #2791⁴³⁵⁵ - Circumvent scary warning about placement new
- PR #2790⁴³⁵⁶ - Fix OSX build
- PR #2789⁴³⁵⁷ - Resource partitioner
- PR #2788⁴³⁵⁸ - Adapt `parallel::is_heap` and `parallel::is_heap_until` to Ranges TS
- PR #2787⁴³⁵⁹ - Unwrap hotfixes
- PR #2786⁴³⁶⁰ - Update CMake Minimum Version to 3.3.2 (refs #2565)
- Issue #2785⁴³⁶¹ - Issues with masks and `cpuset`
- PR #2784⁴³⁶² - Error with reduce and transform reduce fixed
- PR #2783⁴³⁶³ - StackOverflow integration with `libsigsegv`

⁴³⁴¹ <https://github.com/TheHPXProject/hpx/pull/2808>

⁴³⁴² <https://github.com/TheHPXProject/hpx/issues/2807>

⁴³⁴³ <https://github.com/TheHPXProject/hpx/pull/2806>

⁴³⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2805>

⁴³⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2802>

⁴³⁴⁶ <https://github.com/TheHPXProject/hpx/issues/2801>

⁴³⁴⁷ <https://github.com/TheHPXProject/hpx/issues/2800>

⁴³⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2799>

⁴³⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2798>

⁴³⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2797>

⁴³⁵¹ <https://github.com/TheHPXProject/hpx/issues/2796>

⁴³⁵² <https://github.com/TheHPXProject/hpx/issues/2795>

⁴³⁵³ <https://github.com/TheHPXProject/hpx/pull/2794>

⁴³⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2792>

⁴³⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2791>

⁴³⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2790>

⁴³⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2789>

⁴³⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2788>

⁴³⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2787>

⁴³⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2786>

⁴³⁶¹ <https://github.com/TheHPXProject/hpx/issues/2785>

⁴³⁶² <https://github.com/TheHPXProject/hpx/pull/2784>

⁴³⁶³ <https://github.com/TheHPXProject/hpx/pull/2783>

- PR #2782⁴³⁶⁴ - Replace boost::atomic with std::atomic (where possible)
- PR #2781⁴³⁶⁵ - Check for and optionally use [[deprecated]] attribute
- PR #2780⁴³⁶⁶ - Adding empty (but non-trivial) destructor to circumvent warnings
- PR #2779⁴³⁶⁷ - Exception info tweaks
- PR #2778⁴³⁶⁸ - Implement parallel::partition
- PR #2777⁴³⁶⁹ - Improve error handling in gather_here/gather_there
- PR #2776⁴³⁷⁰ - Fix a bug in compiler version check
- PR #2775⁴³⁷¹ - Fix compilation when HPX_WITH_LOGGING is OFF
- PR #2774⁴³⁷² - Removing dependency on Boost.Date_Time
- PR #2773⁴³⁷³ - Add sync_images() method to spmd_block class
- PR #2772⁴³⁷⁴ - Adding documentation for PAPI counters
- PR #2771⁴³⁷⁵ - Removing boost preprocessor dependency
- PR #2770⁴³⁷⁶ - Adding test, fixing deadlock in config registry
- PR #2769⁴³⁷⁷ - Remove some other warnings and errors detected by clang 5.0
- Issue #2768⁴³⁷⁸ - Is there iterator tag for HPX?
- PR #2767⁴³⁷⁹ - Improvements to continuation annotation
- PR #2765⁴³⁸⁰ - gcc split stack support for HPX threads #620
- PR #2764⁴³⁸¹ - Fix some uses of begin/end, remove unnecessary includes
- PR #2763⁴³⁸² - Bump minimal Boost version to 1.55.0
- PR #2762⁴³⁸³ - hpx::partitioned_vector serializer
- PR #2761⁴³⁸⁴ - Adding configuration summary to cmake output and -hpx:info
- PR #2760⁴³⁸⁵ - Removing 1d_hydro example as it is broken
- PR #2758⁴³⁸⁶ - Remove various warnings detected by clang 5.0

⁴³⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2782>
⁴³⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2781>
⁴³⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2780>
⁴³⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2779>
⁴³⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2778>
⁴³⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2777>
⁴³⁷⁰ <https://github.com/TheHPXProject/hpx/pull/2776>
⁴³⁷¹ <https://github.com/TheHPXProject/hpx/pull/2775>
⁴³⁷² <https://github.com/TheHPXProject/hpx/pull/2774>
⁴³⁷³ <https://github.com/TheHPXProject/hpx/pull/2773>
⁴³⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2772>
⁴³⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2771>
⁴³⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2770>
⁴³⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2769>
⁴³⁷⁸ <https://github.com/TheHPXProject/hpx/issues/2768>
⁴³⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2767>
⁴³⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2765>
⁴³⁸¹ <https://github.com/TheHPXProject/hpx/pull/2764>
⁴³⁸² <https://github.com/TheHPXProject/hpx/pull/2763>
⁴³⁸³ <https://github.com/TheHPXProject/hpx/pull/2762>
⁴³⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2761>
⁴³⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2760>
⁴³⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2758>

- [Issue #2757](#)⁴³⁸⁷ - In case of a “raw thread” is needed per core for implementing parallel algorithm, what is good practice in HPX?
- [PR #2756](#)⁴³⁸⁸ - Allowing for LCOs to be simple components
- [PR #2755](#)⁴³⁸⁹ - Removing `make_index_pack_unrolled`
- [PR #2754](#)⁴³⁹⁰ - Implement `parallel::unique_copy`
- [PR #2753](#)⁴³⁹¹ - Fixing detection of `[[fallthrough]]` attribute
- [PR #2752](#)⁴³⁹² - New thread priority names
- [PR #2751](#)⁴³⁹³ - Replace `boost::exception` with proposed `exception_info`
- [PR #2750](#)⁴³⁹⁴ - Replace `boost::iterator_range`
- [PR #2749](#)⁴³⁹⁵ - Fixing hdf5 examples
- [Issue #2748](#)⁴³⁹⁶ - HPX fails to build with enabled hdf5 examples
- [Issue #2747](#)⁴³⁹⁷ - Inherited task priorities break certain DAG optimizations
- [Issue #2746](#)⁴³⁹⁸ - HPX segfaulting with valgrind
- [PR #2745](#)⁴³⁹⁹ - Adding extended arithmetic performance counters
- [PR #2744](#)⁴⁴⁰⁰ - Adding ability to statistics counters to reset base counter
- [Issue #2743](#)⁴⁴⁰¹ - Statistics counter does not support resetting
- [PR #2742](#)⁴⁴⁰² - Making sure Vc V2 builds without additional HPX configuration flags
- [PR #2741](#)⁴⁴⁰³ - Deprecate `unwrapped` and implement `unwrap` and `unwrapping`
- [PR #2740](#)⁴⁴⁰⁴ - Coroutine stackoverflow detection for linux/posix; [Issue #2408](#)
- [PR #2739](#)⁴⁴⁰⁵ - Add files via upload
- [PR #2738](#)⁴⁴⁰⁶ - Appveyor support
- [PR #2737](#)⁴⁴⁰⁷ - Fixing 2735
- [Issue #2736](#)⁴⁴⁰⁸ - `1d_hydro` example doesn't work
- [Issue #2735](#)⁴⁴⁰⁹ - `partitioned_vector_subview` test failing

⁴³⁸⁷ <https://github.com/TheHPXProject/hpx/issues/2757>

⁴³⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2756>

⁴³⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2755>

⁴³⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2754>

⁴³⁹¹ <https://github.com/TheHPXProject/hpx/pull/2753>

⁴³⁹² <https://github.com/TheHPXProject/hpx/pull/2752>

⁴³⁹³ <https://github.com/TheHPXProject/hpx/pull/2751>

⁴³⁹⁴ <https://github.com/TheHPXProject/hpx/pull/2750>

⁴³⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2749>

⁴³⁹⁶ <https://github.com/TheHPXProject/hpx/issues/2748>

⁴³⁹⁷ <https://github.com/TheHPXProject/hpx/issues/2747>

⁴³⁹⁸ <https://github.com/TheHPXProject/hpx/issues/2746>

⁴³⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2745>

⁴⁴⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2744>

⁴⁴⁰¹ <https://github.com/TheHPXProject/hpx/issues/2743>

⁴⁴⁰² <https://github.com/TheHPXProject/hpx/pull/2742>

⁴⁴⁰³ <https://github.com/TheHPXProject/hpx/pull/2741>

⁴⁴⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2740>

⁴⁴⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2739>

⁴⁴⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2738>

⁴⁴⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2737>

⁴⁴⁰⁸ <https://github.com/TheHPXProject/hpx/issues/2736>

⁴⁴⁰⁹ <https://github.com/TheHPXProject/hpx/issues/2735>

- PR #2734⁴⁴¹⁰ - Add C++11 range utilities
- PR #2733⁴⁴¹¹ - Adapting iterator requirements for parallel algorithms
- PR #2732⁴⁴¹² - Integrate C++ Co-arrays
- PR #2731⁴⁴¹³ - Adding on_migrated event handler to migratable component instances
- Issue #2729⁴⁴¹⁴ - Add on_migrated() event handler to migratable components
- Issue #2728⁴⁴¹⁵ - Why Projection is needed in parallel algorithms?
- PR #2727⁴⁴¹⁶ - Cmake files for StackOverflow Detection
- PR #2726⁴⁴¹⁷ - CMake for Stack Overflow Detection
- PR #2725⁴⁴¹⁸ - Implemented segmented algorithms for partitioned vector
- PR #2724⁴⁴¹⁹ - Fix examples in Action documentation
- PR #2723⁴⁴²⁰ - Enable lcos::channel<T>::register_as
- Issue #2722⁴⁴²¹ - channel register_as() failing on compilation
- PR #2721⁴⁴²² - Mind map
- PR #2720⁴⁴²³ - reorder forward declarations to get rid of C++14-only auto return types
- PR #2719⁴⁴²⁴ - Add documentation for partitioned_vector and add features in pack.hpp
- Issue #2718⁴⁴²⁵ - Some forward declarations in execution_fwd.hpp aren't C++11-compatible
- PR #2717⁴⁴²⁶ - Config support for fallthrough attribute
- PR #2716⁴⁴²⁷ - Implement parallel::partition_copy
- PR #2715⁴⁴²⁸ - initial import of icu string serializer
- PR #2714⁴⁴²⁹ - initial import of valarray serializer
- PR #2713⁴⁴³⁰ - Remove slashes before CMAKE_FILES_DIRECTORY variables
- PR #2712⁴⁴³¹ - Fixing wait for 1751
- PR #2711⁴⁴³² - Adjust code for minimal supported GCC having being bumped to 4.9

⁴⁴¹⁰ <https://github.com/TheHPXProject/hpx/pull/2734>
⁴⁴¹¹ <https://github.com/TheHPXProject/hpx/pull/2733>
⁴⁴¹² <https://github.com/TheHPXProject/hpx/pull/2732>
⁴⁴¹³ <https://github.com/TheHPXProject/hpx/pull/2731>
⁴⁴¹⁴ <https://github.com/TheHPXProject/hpx/issues/2729>
⁴⁴¹⁵ <https://github.com/TheHPXProject/hpx/issues/2728>
⁴⁴¹⁶ <https://github.com/TheHPXProject/hpx/pull/2727>
⁴⁴¹⁷ <https://github.com/TheHPXProject/hpx/pull/2726>
⁴⁴¹⁸ <https://github.com/TheHPXProject/hpx/pull/2725>
⁴⁴¹⁹ <https://github.com/TheHPXProject/hpx/pull/2724>
⁴⁴²⁰ <https://github.com/TheHPXProject/hpx/pull/2723>
⁴⁴²¹ <https://github.com/TheHPXProject/hpx/issues/2722>
⁴⁴²² <https://github.com/TheHPXProject/hpx/pull/2721>
⁴⁴²³ <https://github.com/TheHPXProject/hpx/pull/2720>
⁴⁴²⁴ <https://github.com/TheHPXProject/hpx/pull/2719>
⁴⁴²⁵ <https://github.com/TheHPXProject/hpx/issues/2718>
⁴⁴²⁶ <https://github.com/TheHPXProject/hpx/pull/2717>
⁴⁴²⁷ <https://github.com/TheHPXProject/hpx/pull/2716>
⁴⁴²⁸ <https://github.com/TheHPXProject/hpx/pull/2715>
⁴⁴²⁹ <https://github.com/TheHPXProject/hpx/pull/2714>
⁴⁴³⁰ <https://github.com/TheHPXProject/hpx/pull/2713>
⁴⁴³¹ <https://github.com/TheHPXProject/hpx/pull/2712>
⁴⁴³² <https://github.com/TheHPXProject/hpx/pull/2711>

- PR #2710⁴⁴³³ - Adding code of conduct
- PR #2709⁴⁴³⁴ - Fixing UB in destroy tests
- PR #2708⁴⁴³⁵ - Add inline to prevent multiple definition issue
- Issue #2707⁴⁴³⁶ - Multiple defined symbols for task_block.hpp in VS2015
- PR #2706⁴⁴³⁷ - Adding .clang-format file
- PR #2704⁴⁴³⁸ - Add a synchronous mapping API
- Issue #2703⁴⁴³⁹ - Request: Add the .clang-format file to the repository
- Issue #2702⁴⁴⁴⁰ - STELLAR-GROUP/Vc slower than VCv1 possibly due to wrong instructions generated
- Issue #2701⁴⁴⁴¹ - Datapar with STELLAR-GROUP/Vc requires obscure flag
- Issue #2700⁴⁴⁴² - Naming inconsistency in parallel algorithms
- Issue #2699⁴⁴⁴³ - Iterator requirements are different from standard in parallel copy_if.
- PR #2698⁴⁴⁴⁴ - Properly releasing parcelport write handlers
- Issue #2697⁴⁴⁴⁵ - Compile error in addressing_service.cpp
- Issue #2696⁴⁴⁴⁶ - Building and using HPX statically: undefined references from runtime_support_server.cpp
- Issue #2695⁴⁴⁴⁷ - Executor changes cause compilation failures
- PR #2694⁴⁴⁴⁸ - Refining C++ language mode detection for MSVC
- PR #2693⁴⁴⁴⁹ - P0443 r2
- PR #2692⁴⁴⁵⁰ - Partially reverting changes to parcel_await
- Issue #2689⁴⁴⁵¹ - HPX build fails when HPX_WITH_CUDA is enabled
- PR #2688⁴⁴⁵² - Make Cuda Clang builds pass
- PR #2687⁴⁴⁵³ - Add an is_tuple_like trait for sequenceable type detection
- PR #2686⁴⁴⁵⁴ - Allowing throttling scheduler to be used without idle backoff
- PR #2685⁴⁴⁵⁵ - Add support of std::array to hpx::util::tuple_size and tuple_element

⁴⁴³³ <https://github.com/TheHPXProject/hpx/pull/2710>

⁴⁴³⁴ <https://github.com/TheHPXProject/hpx/pull/2709>

⁴⁴³⁵ <https://github.com/TheHPXProject/hpx/pull/2708>

⁴⁴³⁶ <https://github.com/TheHPXProject/hpx/issues/2707>

⁴⁴³⁷ <https://github.com/TheHPXProject/hpx/pull/2706>

⁴⁴³⁸ <https://github.com/TheHPXProject/hpx/pull/2704>

⁴⁴³⁹ <https://github.com/TheHPXProject/hpx/issues/2703>

⁴⁴⁴⁰ <https://github.com/TheHPXProject/hpx/issues/2702>

⁴⁴⁴¹ <https://github.com/TheHPXProject/hpx/issues/2701>

⁴⁴⁴² <https://github.com/TheHPXProject/hpx/issues/2700>

⁴⁴⁴³ <https://github.com/TheHPXProject/hpx/issues/2699>

⁴⁴⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2698>

⁴⁴⁴⁵ <https://github.com/TheHPXProject/hpx/issues/2697>

⁴⁴⁴⁶ <https://github.com/TheHPXProject/hpx/issues/2696>

⁴⁴⁴⁷ <https://github.com/TheHPXProject/hpx/issues/2695>

⁴⁴⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2694>

⁴⁴⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2693>

⁴⁴⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2692>

⁴⁴⁵¹ <https://github.com/TheHPXProject/hpx/issues/2689>

⁴⁴⁵² <https://github.com/TheHPXProject/hpx/pull/2688>

⁴⁴⁵³ <https://github.com/TheHPXProject/hpx/pull/2687>

⁴⁴⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2686>

⁴⁴⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2685>

- PR #2684⁴⁴⁵⁶ - Adding new statistics performance counters
- PR #2683⁴⁴⁵⁷ - Replace boost::exception_ptr with std::exception_ptr
- Issue #2682⁴⁴⁵⁸ - HPX does not compile with HPX_WITH_THREAD_MANAGER_IDLE_BACKOFF=OFF
- PR #2681⁴⁴⁵⁹ - Attempt to fix problem in managed_component_base
- PR #2680⁴⁴⁶⁰ - Fix bad size during archive creation
- Issue #2679⁴⁴⁶¹ - Mismatch between size of archive and container
- Issue #2678⁴⁴⁶² - In parallel algorithm, other tasks are executed to the end even if an exception occurs in any task.
- PR #2677⁴⁴⁶³ - Adding include check for std::addressof
- PR #2676⁴⁴⁶⁴ - Adding parallel::destroy and destroy_n
- PR #2675⁴⁴⁶⁵ - Making sure statistics counters work as expected
- PR #2674⁴⁴⁶⁶ - Turning assertions into exceptions
- PR #2673⁴⁴⁶⁷ - Inhibit direct conversion from future<future<T>> -> future<void>
- PR #2672⁴⁴⁶⁸ - C++17 invoke forms
- PR #2671⁴⁴⁶⁹ - Adding uninitialized_value_construct and uninitialized_value_construct_n
- PR #2670⁴⁴⁷⁰ - Integrate spmd multidimensional views for partitioned_vectors
- PR #2669⁴⁴⁷¹ - Adding uninitialized_default_construct and uninitialized_default_construct_n
- PR #2668⁴⁴⁷² - Fixing documentation index
- Issue #2667⁴⁴⁷³ - Ambiguity of nested hpx::future<void>'s
- Issue #2666⁴⁴⁷⁴ - Statistics Performance counter is not working
- PR #2664⁴⁴⁷⁵ - Adding uninitialized_move and uninitialized_move_n
- Issue #2663⁴⁴⁷⁶ - Seg fault in managed_component::get_base_gid, possibly cause by util::reinitializable_static
- Issue #2662⁴⁴⁷⁷ - Crash in managed_component::get_base_gid due to problem with util::reinitializable_static
- PR #2665⁴⁴⁷⁸ - Hide the detail namespace in doxygen per default

⁴⁴⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2684>

⁴⁴⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2683>

⁴⁴⁵⁸ <https://github.com/TheHPXProject/hpx/issues/2682>

⁴⁴⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2681>

⁴⁴⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2680>

⁴⁴⁶¹ <https://github.com/TheHPXProject/hpx/issues/2679>

⁴⁴⁶² <https://github.com/TheHPXProject/hpx/issues/2678>

⁴⁴⁶³ <https://github.com/TheHPXProject/hpx/pull/2677>

⁴⁴⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2676>

⁴⁴⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2675>

⁴⁴⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2674>

⁴⁴⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2673>

⁴⁴⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2672>

⁴⁴⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2671>

⁴⁴⁷⁰ <https://github.com/TheHPXProject/hpx/pull/2670>

⁴⁴⁷¹ <https://github.com/TheHPXProject/hpx/pull/2669>

⁴⁴⁷² <https://github.com/TheHPXProject/hpx/pull/2668>

⁴⁴⁷³ <https://github.com/TheHPXProject/hpx/issues/2667>

⁴⁴⁷⁴ <https://github.com/TheHPXProject/hpx/issues/2666>

⁴⁴⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2664>

⁴⁴⁷⁶ <https://github.com/TheHPXProject/hpx/issues/2663>

⁴⁴⁷⁷ <https://github.com/TheHPXProject/hpx/issues/2662>

⁴⁴⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2665>

- PR #2660⁴⁴⁷⁹ - Add documentation to `hpx::util::unwrapped` and `hpx::util::unwrapped2`
- PR #2659⁴⁴⁸⁰ - Improve integration with `vcpkg`
- PR #2658⁴⁴⁸¹ - Unify `access_data` trait for use in both, serialization and de-serialization
- PR #2657⁴⁴⁸² - Removing `hpx::lcos::queue<T>`
- PR #2656⁴⁴⁸³ - Reduce `MAX_TERMINATED_THREADS` default, improve memory use on manycore cpus
- PR #2655⁴⁴⁸⁴ - Maintenance for emulate-deleted macros
- PR #2654⁴⁴⁸⁵ - Implement parallel `is_heap` and `is_heap_until`
- PR #2653⁴⁴⁸⁶ - Drop support for VS2013
- PR #2652⁴⁴⁸⁷ - This patch makes sure that all parcels in a batch are properly handled
- PR #2649⁴⁴⁸⁸ - Update docs (Table 18) - move `transform` to end
- Issue #2647⁴⁴⁸⁹ - `hpx::parcels::detail::parcel_data::has_continuation_` is uninitialized
- Issue #2644⁴⁴⁹⁰ - Some `.vcxproj` in the `HPX.sln` fail to build
- Issue #2641⁴⁴⁹¹ - `hpx::lcos::queue` should be deprecated
- PR #2640⁴⁴⁹² - A new throttling policy with public APIs to suspend/resume
- PR #2639⁴⁴⁹³ - Fix a tiny typo in tutorial.
- Issue #2638⁴⁴⁹⁴ - Invalid return type 'void' of `constexpr` function
- PR #2636⁴⁴⁹⁵ - Add and use `HPX_MSVC_WARNING_PRAGMA` for `#pragma` warning
- PR #2633⁴⁴⁹⁶ - Distributed `define_spmd_block`
- PR #2632⁴⁴⁹⁷ - Making sure container serialization uses size-compatible types
- PR #2631⁴⁴⁹⁸ - Add `lcos::local::one_element_channel`
- PR #2629⁴⁴⁹⁹ - Move `unordered_map` out of `parcels` into `hpx/concurrent`
- PR #2628⁴⁵⁰⁰ - Making sure that shutdown does not hang
- PR #2627⁴⁵⁰¹ - Fix serialization

⁴⁴⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2660>

⁴⁴⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2659>

⁴⁴⁸¹ <https://github.com/TheHPXProject/hpx/pull/2658>

⁴⁴⁸² <https://github.com/TheHPXProject/hpx/pull/2657>

⁴⁴⁸³ <https://github.com/TheHPXProject/hpx/pull/2656>

⁴⁴⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2655>

⁴⁴⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2654>

⁴⁴⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2653>

⁴⁴⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2652>

⁴⁴⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2649>

⁴⁴⁸⁹ <https://github.com/TheHPXProject/hpx/issues/2647>

⁴⁴⁹⁰ <https://github.com/TheHPXProject/hpx/issues/2644>

⁴⁴⁹¹ <https://github.com/TheHPXProject/hpx/issues/2641>

⁴⁴⁹² <https://github.com/TheHPXProject/hpx/pull/2640>

⁴⁴⁹³ <https://github.com/TheHPXProject/hpx/pull/2639>

⁴⁴⁹⁴ <https://github.com/TheHPXProject/hpx/issues/2638>

⁴⁴⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2636>

⁴⁴⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2633>

⁴⁴⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2632>

⁴⁴⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2631>

⁴⁴⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2629>

⁴⁵⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2628>

⁴⁵⁰¹ <https://github.com/TheHPXProject/hpx/pull/2627>

- PR #2626⁴⁵⁰² - Generate `cmake_variables.qbk` and `cmake_toolchains.qbk` outside of the source tree
- PR #2625⁴⁵⁰³ - Supporting `-std=c++17` flag
- PR #2624⁴⁵⁰⁴ - Fixing a small `cmake` typo
- PR #2622⁴⁵⁰⁵ - Update CMake minimum required version to 3.0.2 (closes #2621)
- Issue #2621⁴⁵⁰⁶ - Compiling `hpx` master fails with `/usr/bin/ld: final link failed: Bad value`
- PR #2620⁴⁵⁰⁷ - Remove warnings due to some captured variables
- PR #2619⁴⁵⁰⁸ - LF multiple parcels
- PR #2618⁴⁵⁰⁹ - Some fixes to `libfabric` that didn't get caught before the merge
- PR #2617⁴⁵¹⁰ - Adding `hpx::local_new`
- PR #2616⁴⁵¹¹ - Documentation: Extract all entities in order to autolink functions correctly
- Issue #2615⁴⁵¹² - Documentation: Linking functions is broken
- PR #2614⁴⁵¹³ - Adding serialization for `std::deque`
- PR #2613⁴⁵¹⁴ - We need to link with `boost.thread` and `boost.chrono` if we use `boost.context`
- PR #2612⁴⁵¹⁵ - Making sure `for_loop_n(par, ...)` is actually executed in parallel
- PR #2611⁴⁵¹⁶ - Add documentation to `invoke_fused` and `friends NFC`
- PR #2610⁴⁵¹⁷ - Added reduction templates using an identity value
- PR #2608⁴⁵¹⁸ - Fixing some unused vars in `inspect`
- PR #2607⁴⁵¹⁹ - Fixed build for `mingw`
- PR #2606⁴⁵²⁰ - Supporting generic context for `boost >= 1.61`
- PR #2605⁴⁵²¹ - `Parcelport libfabric3`
- PR #2604⁴⁵²² - Adding allocator support to `promise` and `friends`
- PR #2603⁴⁵²³ - Barrier hang
- PR #2602⁴⁵²⁴ - Changes to scheduler to steal from one high-priority queue

⁴⁵⁰² <https://github.com/TheHPXProject/hpx/pull/2626>
⁴⁵⁰³ <https://github.com/TheHPXProject/hpx/pull/2625>
⁴⁵⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2624>
⁴⁵⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2622>
⁴⁵⁰⁶ <https://github.com/TheHPXProject/hpx/issues/2621>
⁴⁵⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2620>
⁴⁵⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2619>
⁴⁵⁰⁹ <https://github.com/TheHPXProject/hpx/pull/2618>
⁴⁵¹⁰ <https://github.com/TheHPXProject/hpx/pull/2617>
⁴⁵¹¹ <https://github.com/TheHPXProject/hpx/pull/2616>
⁴⁵¹² <https://github.com/TheHPXProject/hpx/issues/2615>
⁴⁵¹³ <https://github.com/TheHPXProject/hpx/pull/2614>
⁴⁵¹⁴ <https://github.com/TheHPXProject/hpx/pull/2613>
⁴⁵¹⁵ <https://github.com/TheHPXProject/hpx/pull/2612>
⁴⁵¹⁶ <https://github.com/TheHPXProject/hpx/pull/2611>
⁴⁵¹⁷ <https://github.com/TheHPXProject/hpx/pull/2610>
⁴⁵¹⁸ <https://github.com/TheHPXProject/hpx/pull/2608>
⁴⁵¹⁹ <https://github.com/TheHPXProject/hpx/pull/2607>
⁴⁵²⁰ <https://github.com/TheHPXProject/hpx/pull/2606>
⁴⁵²¹ <https://github.com/TheHPXProject/hpx/pull/2605>
⁴⁵²² <https://github.com/TheHPXProject/hpx/pull/2604>
⁴⁵²³ <https://github.com/TheHPXProject/hpx/pull/2603>
⁴⁵²⁴ <https://github.com/TheHPXProject/hpx/pull/2602>

- Issue #2601⁴⁵²⁵ - High priority tasks are not executed first
- PR #2600⁴⁵²⁶ - Compat fixes
- PR #2599⁴⁵²⁷ - Compatibility layer for threading support
- PR #2598⁴⁵²⁸ - V1.1
- PR #2597⁴⁵²⁹ - Release V1.0
- PR #2592⁴⁵³⁰ - First attempt to introduce `spmd_block` in `hpx`
- PR #2586⁴⁵³¹ - `local_segment` in `segmented_iterator_traits`
- Issue #2584⁴⁵³² - Add allocator support to `promise`, `packaged_task` and friends
- PR #2576⁴⁵³³ - Add missing dependencies of `cuda` based tests
- PR #2575⁴⁵³⁴ - Remove warnings due to some captured variables
- Issue #2574⁴⁵³⁵ - MSVC 2015 Compiler crash when building HPX
- Issue #2568⁴⁵³⁶ - Remove `throttle_scheduler` as it has been abandoned
- Issue #2566⁴⁵³⁷ - Add an inline versioning namespace before 1.0 release
- Issue #2565⁴⁵³⁸ - Raise minimal `cmake` version requirement
- PR #2556⁴⁵³⁹ - Fixing scan partitioner
- PR #2546⁴⁵⁴⁰ - Broadcast `async`
- Issue #2543⁴⁵⁴¹ - `make install` fails due to a non-existing `.so` file
- PR #2495⁴⁵⁴² - `wait_or_add_new` returning `thread_id_type`
- Issue #2480⁴⁵⁴³ - Unable to register new performance counter
- Issue #2471⁴⁵⁴⁴ - no type named `'fcontext_t'` in namespace
- Issue #2456⁴⁵⁴⁵ - Re-implement `hpx::util::unwrapped`
- Issue #2455⁴⁵⁴⁶ - Add more arithmetic performance counters
- PR #2454⁴⁵⁴⁷ - Fix a couple of warnings and compiler errors

⁴⁵²⁵ <https://github.com/TheHPXProject/hpx/issues/2601>

⁴⁵²⁶ <https://github.com/TheHPXProject/hpx/pull/2600>

⁴⁵²⁷ <https://github.com/TheHPXProject/hpx/pull/2599>

⁴⁵²⁸ <https://github.com/TheHPXProject/hpx/pull/2598>

⁴⁵²⁹ <https://github.com/TheHPXProject/hpx/pull/2597>

⁴⁵³⁰ <https://github.com/TheHPXProject/hpx/pull/2592>

⁴⁵³¹ <https://github.com/TheHPXProject/hpx/pull/2586>

⁴⁵³² <https://github.com/TheHPXProject/hpx/issues/2584>

⁴⁵³³ <https://github.com/TheHPXProject/hpx/pull/2576>

⁴⁵³⁴ <https://github.com/TheHPXProject/hpx/pull/2575>

⁴⁵³⁵ <https://github.com/TheHPXProject/hpx/issues/2574>

⁴⁵³⁶ <https://github.com/TheHPXProject/hpx/issues/2568>

⁴⁵³⁷ <https://github.com/TheHPXProject/hpx/issues/2566>

⁴⁵³⁸ <https://github.com/TheHPXProject/hpx/issues/2565>

⁴⁵³⁹ <https://github.com/TheHPXProject/hpx/pull/2556>

⁴⁵⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2546>

⁴⁵⁴¹ <https://github.com/TheHPXProject/hpx/issues/2543>

⁴⁵⁴² <https://github.com/TheHPXProject/hpx/pull/2495>

⁴⁵⁴³ <https://github.com/TheHPXProject/hpx/issues/2480>

⁴⁵⁴⁴ <https://github.com/TheHPXProject/hpx/issues/2471>

⁴⁵⁴⁵ <https://github.com/TheHPXProject/hpx/issues/2456>

⁴⁵⁴⁶ <https://github.com/TheHPXProject/hpx/issues/2455>

⁴⁵⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2454>

- PR #2453⁴⁵⁴⁸ - Timed executor support
- PR #2447⁴⁵⁴⁹ - Implementing new executor API (P0443)
- Issue #2439⁴⁵⁵⁰ - Implement executor proposal
- Issue #2408⁴⁵⁵¹ - Stackoverflow detection for linux, e.g. based on libsigsegv
- PR #2377⁴⁵⁵² - Add a customization point for put_parcel so we can override actions
- Issue #2368⁴⁵⁵³ - HPX_ASSERT problem
- Issue #2324⁴⁵⁵⁴ - Change default number of threads used to the maximum of the system
- Issue #2266⁴⁵⁵⁵ - hpx_0.9.99 make tests fail
- PR #2195⁴⁵⁵⁶ - Support for code completion in VIM
- Issue #2137⁴⁵⁵⁷ - Hpx does not compile over osx
- Issue #2092⁴⁵⁵⁸ - make tests should just build the tests
- Issue #2026⁴⁵⁵⁹ - Build HPX with Apple's clang
- Issue #1932⁴⁵⁶⁰ - hpx with PBS fails on multiple localities
- PR #1914⁴⁵⁶¹ - Parallel heap algorithm implementations WIP
- Issue #1598⁴⁵⁶² - Disconnecting a locality results in segfault using heartbeat example
- Issue #1404⁴⁵⁶³ - unwrapped doesn't work with movable only types
- Issue #1400⁴⁵⁶⁴ - hpx::util::unwrapped doesn't work with non-future types
- Issue #1205⁴⁵⁶⁵ - TSS is broken
- Issue #1126⁴⁵⁶⁶ - vector<future<T> > does not work gracefully with dataflow, when_all and unwrapped
- Issue #1056⁴⁵⁶⁷ - Thread manager cleanup
- Issue #863⁴⁵⁶⁸ - Futures should not require a default constructor
- Issue #856⁴⁵⁶⁹ - Allow runtime_mode_connect to be used with security enabled
- Issue #726⁴⁵⁷⁰ - Valgrind

⁴⁵⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2453>
⁴⁵⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2447>
⁴⁵⁵⁰ <https://github.com/TheHPXProject/hpx/issues/2439>
⁴⁵⁵¹ <https://github.com/TheHPXProject/hpx/issues/2408>
⁴⁵⁵² <https://github.com/TheHPXProject/hpx/pull/2377>
⁴⁵⁵³ <https://github.com/TheHPXProject/hpx/issues/2368>
⁴⁵⁵⁴ <https://github.com/TheHPXProject/hpx/issues/2324>
⁴⁵⁵⁵ <https://github.com/TheHPXProject/hpx/issues/2266>
⁴⁵⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2195>
⁴⁵⁵⁷ <https://github.com/TheHPXProject/hpx/issues/2137>
⁴⁵⁵⁸ <https://github.com/TheHPXProject/hpx/issues/2092>
⁴⁵⁵⁹ <https://github.com/TheHPXProject/hpx/issues/2026>
⁴⁵⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1932>
⁴⁵⁶¹ <https://github.com/TheHPXProject/hpx/pull/1914>
⁴⁵⁶² <https://github.com/TheHPXProject/hpx/issues/1598>
⁴⁵⁶³ <https://github.com/TheHPXProject/hpx/issues/1404>
⁴⁵⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1400>
⁴⁵⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1205>
⁴⁵⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1126>
⁴⁵⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1056>
⁴⁵⁶⁸ <https://github.com/TheHPXProject/hpx/issues/863>
⁴⁵⁶⁹ <https://github.com/TheHPXProject/hpx/issues/856>
⁴⁵⁷⁰ <https://github.com/TheHPXProject/hpx/issues/726>

- [Issue #701](#)⁴⁵⁷¹ - Add RCR performance counter component
- [Issue #528](#)⁴⁵⁷² - Add support for known failures and warning count/comparisons to `hpx_run_tests.py`

HPX V1.0.0 (Apr 24, 2017)

General changes

Here are some of the main highlights and changes for this release (in no particular order):

- Added the facility `hpx::split_future` which allows one to convert a `future<tuple<Ts...>>` into a `tuple<future<Ts>...>`. This functionality is not available when compiling *HPX* with VS2012.
- Added a new type of performance counter which allows one to return a list of values for each invocation. We also added a first counter of this type which collects a histogram of the times between parcels being created.
- Added new LCOs: `hpx::lcos::channel` and `hpx::lcos::local::channel` which are very similar to the well known channel constructs used in the Go language.
- Added new performance counters reporting the amount of data handled by the networking layer on a action-by-action basis (please see [PR #2289](#)⁴⁵⁷³ for more details).
- Added a new facility `hpx::lcos::barrier`, replacing the equally named older one. The new facility has a slightly changed API and is much more efficient. Most notable, the new facility exposes a (global) function `hpx::lcos::barrier::synchronize()` which represents a global barrier across all localities.
- We have started to add support for vectorization to our parallel algorithm implementations. This support depends on using an external library, currently either Vc Library or `|boost_simd|`. Please see [Issue #2333](#)⁴⁵⁷⁴ for a list of currently supported algorithms. This is an experimental feature and its implementation and/or API might change in the future. Please see this [blog-post](#)⁴⁵⁷⁵ for more information.
- The parameter sequence for the `hpx::parallel::transform_reduce` overload taking one iterator range has changed to match the changes this algorithm has undergone while being moved to C++17. The old overload can be still enabled at configure time by specifying `-DHPX_WITH_TRANSFORM_REDUCE_COMPATIBILITY=On` to CMake.
- The algorithm `hpx::parallel::inner_product` has been renamed to `hpx::parallel::transform_reduce` to match the changes this algorithm has undergone while being moved to C++17. The old `inner_product` names can be still enabled at configure time by specifying `-DHPX_WITH_TRANSFORM_REDUCE_COMPATIBILITY=On` to CMake.
- Added versions of `hpx::get_ptr` taking client side representations for component instances as their parameter (instead of a global id).
- Added the helper utility `hpx::performance_counters::performance_counter_set` helping to encapsulate a set of performance counters to be managed concurrently.
- All execution policies and related classes have been renamed to be consistent with the naming changes applied for C++17. All policies now live in the namespace `hpx::parallel::execution`. The old names can be still enabled at configure time by specifying `-DHPX_WITH_EXECUTION_POLICY_COMPATIBILITY=On` to CMake.
- The thread scheduling subsystem has undergone a major refactoring which results in significant performance improvements. We have also improved the performance of creating `hpx::future` and of various facilities handling those.

⁴⁵⁷¹ <https://github.com/TheHPXProject/hpx/issues/701>

⁴⁵⁷² <https://github.com/TheHPXProject/hpx/issues/528>

⁴⁵⁷³ <https://github.com/TheHPXProject/hpx/pull/2289>

⁴⁵⁷⁴ <https://github.com/TheHPXProject/hpx/issues/2333>

⁴⁵⁷⁵ <http://stellar-group.org/2016/09/vectorized-cpp-parallel-algorithms-with-hpx/>

- We have consolidated all of the code in `HPX.Compute` related to the integration of CUDA. `hpx::partitioned_vector` has been enabled to be usable with `hpx::compute::vector` which allows one to place the partitions on one or more GPU devices.
- Added new performance counters exposing various internals of the thread scheduling subsystem, such as the current idle- and busy-loop counters and instantaneous scheduler utilization.
- Extended and improved the use of the ITTNotify hooks allowing to collect performance counter data and function annotation information from within the Intel Amplifier tool.

Breaking changes

- We have dropped support for the gcc compiler versions V4.6 and 4.7. The minimal gcc version we now test on is gcc V4.8.
- We have removed (default) support for `boost::chrono` in interfaces, uses of it have been replaced with `std::chrono`. This facility can be still enabled at configure time by specifying `-DHPX_WITH_BOOST_CHRONO_COMPATIBILITY=On` to CMake.
- The parameter sequence for the `hpx::parallel::transform_reduce` overload taking one iterator range has changed to match the changes this algorithm has undergone while being moved to C++17.
- The algorithm `hpx::parallel::inner_product` has been renamed to `hpx::parallel::transform_reduce` to match the changes this algorithm has undergone while being moved to C++17.
- the build options `HPX_WITH_COLOCATED_BACKWARDS_COMPATIBILITY` and `HPX_WITH_COMPONENT_GET_GID_COMPATIBILITY` are now disabled by default. Please change your code still depending on the deprecated interfaces.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [PR #2596](#)⁴⁵⁷⁶ - Adding apex data
- [PR #2595](#)⁴⁵⁷⁷ - Remove obsolete file
- [Issue #2594](#)⁴⁵⁷⁸ - FindOpenCL.cmake mismatch with the official cmake module
- [PR #2592](#)⁴⁵⁷⁹ - First attempt to introduce `spmd_block` in `hpx`
- [Issue #2591](#)⁴⁵⁸⁰ - Feature request: continuation (then) which does not require the callable object to take a future<R> as parameter
- [PR #2588](#)⁴⁵⁸¹ - Daint fixes
- [PR #2587](#)⁴⁵⁸² - Fixing `transfer_(continuation)_action::schedule`
- [PR #2585](#)⁴⁵⁸³ - Work around MSVC having an ICE when compiling with `-Ob2`
- [PR #2583](#)⁴⁵⁸⁴ - changing 7zip command to 7za in `roll_release.sh`

⁴⁵⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2596>

⁴⁵⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2595>

⁴⁵⁷⁸ <https://github.com/TheHPXProject/hpx/issues/2594>

⁴⁵⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2592>

⁴⁵⁸⁰ <https://github.com/TheHPXProject/hpx/issues/2591>

⁴⁵⁸¹ <https://github.com/TheHPXProject/hpx/pull/2588>

⁴⁵⁸² <https://github.com/TheHPXProject/hpx/pull/2587>

⁴⁵⁸³ <https://github.com/TheHPXProject/hpx/pull/2585>

⁴⁵⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2583>

- [PR #2582](#)⁴⁵⁸⁵ - First attempt to introduce `spmd_block` in `hpx`
- [PR #2581](#)⁴⁵⁸⁶ - Enable annotated function for parallel algorithms
- [PR #2580](#)⁴⁵⁸⁷ - First attempt to introduce `spmd_block` in `hpx`
- [PR #2579](#)⁴⁵⁸⁸ - Make thread NICE level setting an option
- [PR #2578](#)⁴⁵⁸⁹ - Implementing `enqueue` instead of busy wait when no sender is available
- [PR #2577](#)⁴⁵⁹⁰ - Retrieve `-std=c++11` consistent `nvcc` flag
- [PR #2576](#)⁴⁵⁹¹ - Add missing dependencies of `cuda` based tests
- [PR #2575](#)⁴⁵⁹² - Remove warnings due to some captured variables
- [PR #2573](#)⁴⁵⁹³ - Attempt to resolve `resolve_locality`
- [PR #2572](#)⁴⁵⁹⁴ - Adding APEX hooks to background thread
- [PR #2571](#)⁴⁵⁹⁵ - Pick up `hpx.ignore_batch_env` from config map
- [PR #2570](#)⁴⁵⁹⁶ - Add cmdline options `-hpx:print-counters-locally`
- [PR #2569](#)⁴⁵⁹⁷ - Fix `computeapi` unit tests
- [PR #2567](#)⁴⁵⁹⁸ - This adds another `barrier::synchronize` before registering performance counters
- [PR #2564](#)⁴⁵⁹⁹ - Cray static toolchain support
- [PR #2563](#)⁴⁶⁰⁰ - Fixed unhandled exception during startup
- [PR #2562](#)⁴⁶⁰¹ - Remove `partitioned_vector.cu` from build tree when `nvcc` is used
- [Issue #2561](#)⁴⁶⁰² - octo-tiger crash with commit `6e921495ff6c26f125d62629cbaad0525f14f7ab`
- [PR #2560](#)⁴⁶⁰³ - Prevent `-Wundef` warnings on `Vc` version checks
- [PR #2559](#)⁴⁶⁰⁴ - Allowing `CUDA` callback to set the future directly from an OS thread
- [PR #2558](#)⁴⁶⁰⁵ - Remove warnings due to float precisions
- [PR #2557](#)⁴⁶⁰⁶ - Removing bogus handling of compile flags for `CUDA`
- [PR #2556](#)⁴⁶⁰⁷ - Fixing scan partitioner

⁴⁵⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2582>
⁴⁵⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2581>
⁴⁵⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2580>
⁴⁵⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2579>
⁴⁵⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2578>
⁴⁵⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2577>
⁴⁵⁹¹ <https://github.com/TheHPXProject/hpx/pull/2576>
⁴⁵⁹² <https://github.com/TheHPXProject/hpx/pull/2575>
⁴⁵⁹³ <https://github.com/TheHPXProject/hpx/pull/2573>
⁴⁵⁹⁴ <https://github.com/TheHPXProject/hpx/pull/2572>
⁴⁵⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2571>
⁴⁵⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2570>
⁴⁵⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2569>
⁴⁵⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2567>
⁴⁵⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2564>
⁴⁶⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2563>
⁴⁶⁰¹ <https://github.com/TheHPXProject/hpx/pull/2562>
⁴⁶⁰² <https://github.com/TheHPXProject/hpx/issues/2561>
⁴⁶⁰³ <https://github.com/TheHPXProject/hpx/pull/2560>
⁴⁶⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2559>
⁴⁶⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2558>
⁴⁶⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2557>
⁴⁶⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2556>

- PR #2554⁴⁶⁰⁸ - Add more diagnostics to error thrown from find_appropriate_destination
- Issue #2555⁴⁶⁰⁹ - No valid parcellport configured
- PR #2553⁴⁶¹⁰ - Add cmake cuda_arch option
- PR #2552⁴⁶¹¹ - Remove incomplete datapar bindings to libflatarray
- PR #2551⁴⁶¹² - Rename hwloc_topology to hwloc_topology_info
- PR #2550⁴⁶¹³ - Apex api updates
- PR #2549⁴⁶¹⁴ - Pre-include defines.hpp to get the macro HPX_HAVE_CUDA value
- PR #2548⁴⁶¹⁵ - Fixing issue with disconnect
- PR #2546⁴⁶¹⁶ - Some fixes around cuda clang partitioned_vector example
- PR #2545⁴⁶¹⁷ - Fix uses of the Vc2 datapar flags; the value, not the type, should be passed to functions
- PR #2542⁴⁶¹⁸ - Make HPX_WITH_MALLOC easier to use
- PR #2541⁴⁶¹⁹ - avoid recompiles when enabling/disabling examples
- PR #2540⁴⁶²⁰ - Fixing usage of target_link_libraries()
- PR #2539⁴⁶²¹ - fix RPATH behaviour
- Issue #2538⁴⁶²² - HPX_WITH_CUDA corrupts compilation flags
- PR #2537⁴⁶²³ - Add output of a Bazel Skylark extension for paths and compile options
- PR #2536⁴⁶²⁴ - Add counter exposing total available memory to Windows as well
- PR #2535⁴⁶²⁵ - Remove obsolete support for security
- Issue #2534⁴⁶²⁶ - Remove command line option --hpx:run-agas-server
- PR #2533⁴⁶²⁷ - Pre-cache locality endpoints during bootstrap
- PR #2532⁴⁶²⁸ - Fixing handling of GIDs during serialization preprocessing
- PR #2531⁴⁶²⁹ - Amend uses of the term “functor”
- PR #2529⁴⁶³⁰ - added counter for reading available memory

⁴⁶⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2554>

⁴⁶⁰⁹ <https://github.com/TheHPXProject/hpx/issues/2555>

⁴⁶¹⁰ <https://github.com/TheHPXProject/hpx/pull/2553>

⁴⁶¹¹ <https://github.com/TheHPXProject/hpx/pull/2552>

⁴⁶¹² <https://github.com/TheHPXProject/hpx/pull/2551>

⁴⁶¹³ <https://github.com/TheHPXProject/hpx/pull/2550>

⁴⁶¹⁴ <https://github.com/TheHPXProject/hpx/pull/2549>

⁴⁶¹⁵ <https://github.com/TheHPXProject/hpx/pull/2548>

⁴⁶¹⁶ <https://github.com/TheHPXProject/hpx/pull/2546>

⁴⁶¹⁷ <https://github.com/TheHPXProject/hpx/pull/2545>

⁴⁶¹⁸ <https://github.com/TheHPXProject/hpx/pull/2542>

⁴⁶¹⁹ <https://github.com/TheHPXProject/hpx/pull/2541>

⁴⁶²⁰ <https://github.com/TheHPXProject/hpx/pull/2540>

⁴⁶²¹ <https://github.com/TheHPXProject/hpx/pull/2539>

⁴⁶²² <https://github.com/TheHPXProject/hpx/issues/2538>

⁴⁶²³ <https://github.com/TheHPXProject/hpx/pull/2537>

⁴⁶²⁴ <https://github.com/TheHPXProject/hpx/pull/2536>

⁴⁶²⁵ <https://github.com/TheHPXProject/hpx/pull/2535>

⁴⁶²⁶ <https://github.com/TheHPXProject/hpx/issues/2534>

⁴⁶²⁷ <https://github.com/TheHPXProject/hpx/pull/2533>

⁴⁶²⁸ <https://github.com/TheHPXProject/hpx/pull/2532>

⁴⁶²⁹ <https://github.com/TheHPXProject/hpx/pull/2531>

⁴⁶³⁰ <https://github.com/TheHPXProject/hpx/pull/2529>

- PR #2527⁴⁶³¹ - Facilities to create actions from lambdas
- PR #2526⁴⁶³² - Updated docs: HPX_WITH_EXAMPLES
- PR #2525⁴⁶³³ - Remove warnings related to unused captured variables
- Issue #2524⁴⁶³⁴ - CMAKE failed because it is missing: TCMALLOC_LIBRARY TCMALLOC_INCLUDE_DIR
- PR #2523⁴⁶³⁵ - Fixing compose_cb stack overflow
- PR #2522⁴⁶³⁶ - Instead of unlocking, ignore the lock while creating the message handler
- PR #2521⁴⁶³⁷ - Create LPROGRESS_ logging macro to simplify progress tracking and timings
- PR #2520⁴⁶³⁸ - Intel 17 support
- PR #2519⁴⁶³⁹ - Fix components example
- PR #2518⁴⁶⁴⁰ - Fixing parcel scheduling
- Issue #2517⁴⁶⁴¹ - Race condition during Parcel Coalescing Handler creation
- Issue #2516⁴⁶⁴² - HPX locks up when using at least 256 localities
- Issue #2515⁴⁶⁴³ - error: Install cannot find “/lib/hpx/libparcel_coalescing.so.0.9.99” but I can see that file
- PR #2514⁴⁶⁴⁴ - Making sure that all continuations of a shared_future are invoked in order
- PR #2513⁴⁶⁴⁵ - Fixing locks held during suspension
- PR #2512⁴⁶⁴⁶ - MPI Parcelport improvements and fixes related to the background work changes
- PR #2511⁴⁶⁴⁷ - Fixing bit-wise (zero-copy) serialization
- Issue #2509⁴⁶⁴⁸ - Linking errors in hwloc_topology
- PR #2508⁴⁶⁴⁹ - Added documentation for debugging with core files
- PR #2506⁴⁶⁵⁰ - Fixing background work invocations
- PR #2505⁴⁶⁵¹ - Fix tuple serialization
- Issue #2504⁴⁶⁵² - Ensure continuations are called in the order they have been attached
- PR #2503⁴⁶⁵³ - Adding serialization support for Vc v2 (datapar)

⁴⁶³¹ <https://github.com/TheHPXProject/hpx/pull/2527>

⁴⁶³² <https://github.com/TheHPXProject/hpx/pull/2526>

⁴⁶³³ <https://github.com/TheHPXProject/hpx/pull/2525>

⁴⁶³⁴ <https://github.com/TheHPXProject/hpx/issues/2524>

⁴⁶³⁵ <https://github.com/TheHPXProject/hpx/pull/2523>

⁴⁶³⁶ <https://github.com/TheHPXProject/hpx/pull/2522>

⁴⁶³⁷ <https://github.com/TheHPXProject/hpx/pull/2521>

⁴⁶³⁸ <https://github.com/TheHPXProject/hpx/pull/2520>

⁴⁶³⁹ <https://github.com/TheHPXProject/hpx/pull/2519>

⁴⁶⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2518>

⁴⁶⁴¹ <https://github.com/TheHPXProject/hpx/issues/2517>

⁴⁶⁴² <https://github.com/TheHPXProject/hpx/issues/2516>

⁴⁶⁴³ <https://github.com/TheHPXProject/hpx/issues/2515>

⁴⁶⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2514>

⁴⁶⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2513>

⁴⁶⁴⁶ <https://github.com/TheHPXProject/hpx/pull/2512>

⁴⁶⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2511>

⁴⁶⁴⁸ <https://github.com/TheHPXProject/hpx/issues/2509>

⁴⁶⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2508>

⁴⁶⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2506>

⁴⁶⁵¹ <https://github.com/TheHPXProject/hpx/pull/2505>

⁴⁶⁵² <https://github.com/TheHPXProject/hpx/issues/2504>

⁴⁶⁵³ <https://github.com/TheHPXProject/hpx/pull/2503>

- PR #2502⁴⁶⁵⁴ - Resolve various, minor compiler warnings
- PR #2501⁴⁶⁵⁵ - Some other fixes around cuda examples
- Issue #2500⁴⁶⁵⁶ - nvcc / cuda clang issue due to a missing -DHPX_WITH_CUDA flag
- PR #2499⁴⁶⁵⁷ - Adding support for std::array to wait_all and friends
- PR #2498⁴⁶⁵⁸ - Execute background work as HPX thread
- PR #2497⁴⁶⁵⁹ - Fixing configuration options for spinlock-deadlock detection
- PR #2496⁴⁶⁶⁰ - Accounting for different compilers in CrayKNL toolchain file
- PR #2494⁴⁶⁶¹ - Adding component base class which ties a component instance to a given executor
- PR #2493⁴⁶⁶² - Enable controlling amount of pending threads which must be available to allow thread stealing
- PR #2492⁴⁶⁶³ - Adding new command line option -hpx:print-counter-reset
- PR #2491⁴⁶⁶⁴ - Resolve ambiguities when compiling with APEX
- PR #2490⁴⁶⁶⁵ - Resuming threads waiting on future with higher priority
- Issue #2489⁴⁶⁶⁶ - nvcc issue because -std=c++11 appears twice
- PR #2488⁴⁶⁶⁷ - Adding performance counters exposing the internal idle and busy-loop counters
- PR #2487⁴⁶⁶⁸ - Allowing for plain suspend to reschedule thread right away
- PR #2486⁴⁶⁶⁹ - Only flag HPX code for CUDA if HPX_WITH_CUDA is set
- PR #2485⁴⁶⁷⁰ - Making thread-queue parameters runtime-configurable
- PR #2484⁴⁶⁷¹ - Added atomic counter for parcel-destinations
- PR #2483⁴⁶⁷² - Added priority-queue lifo scheduler
- PR #2482⁴⁶⁷³ - Changing scheduler to steal only if more than a minimal number of tasks are available
- PR #2481⁴⁶⁷⁴ - Extending command line option -hpx:print-counter-destination to support value 'none'
- PR #2479⁴⁶⁷⁵ - Added option to disable signal handler
- PR #2478⁴⁶⁷⁶ - Making sure the sine performance counter module gets loaded only for the corresponding example

⁴⁶⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2502>
⁴⁶⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2501>
⁴⁶⁵⁶ <https://github.com/TheHPXProject/hpx/issues/2500>
⁴⁶⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2499>
⁴⁶⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2498>
⁴⁶⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2497>
⁴⁶⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2496>
⁴⁶⁶¹ <https://github.com/TheHPXProject/hpx/pull/2494>
⁴⁶⁶² <https://github.com/TheHPXProject/hpx/pull/2493>
⁴⁶⁶³ <https://github.com/TheHPXProject/hpx/pull/2492>
⁴⁶⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2491>
⁴⁶⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2490>
⁴⁶⁶⁶ <https://github.com/TheHPXProject/hpx/issues/2489>
⁴⁶⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2488>
⁴⁶⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2487>
⁴⁶⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2486>
⁴⁶⁷⁰ <https://github.com/TheHPXProject/hpx/pull/2485>
⁴⁶⁷¹ <https://github.com/TheHPXProject/hpx/pull/2484>
⁴⁶⁷² <https://github.com/TheHPXProject/hpx/pull/2483>
⁴⁶⁷³ <https://github.com/TheHPXProject/hpx/pull/2482>
⁴⁶⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2481>
⁴⁶⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2479>
⁴⁶⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2478>

- [Issue #2477⁴⁶⁷⁷](#) - Breaking at a throw statement
- [PR #2476⁴⁶⁷⁸](#) - Annotated function
- [PR #2475⁴⁶⁷⁹](#) - Ensure that using `%osthread%` during logging will not throw for non-hpx threads
- [PR #2474⁴⁶⁸⁰](#) - Remove now superficial `non_direct` actions from `base_lco` and friends
- [PR #2473⁴⁶⁸¹](#) - Refining support for `ITTNotify`
- [PR #2472⁴⁶⁸²](#) - Some fixes around hpx compute
- [Issue #2470⁴⁶⁸³](#) - redefinition of `boost::detail::spinlock`
- [Issue #2469⁴⁶⁸⁴](#) - Dataflow performance issue
- [PR #2468⁴⁶⁸⁵](#) - Perf docs update
- [PR #2466⁴⁶⁸⁶](#) - Guarantee to execute remote direct actions on HPX-thread
- [PR #2465⁴⁶⁸⁷](#) - Improve demo : Async copy and fixed device handling
- [PR #2464⁴⁶⁸⁸](#) - Adding performance counter exposing instantaneous scheduler utilization
- [PR #2463⁴⁶⁸⁹](#) - Downcast to `future<void>`
- [PR #2462⁴⁶⁹⁰](#) - Fixed usage of `ITT-Notify` API with Intel Amplifier
- [PR #2461⁴⁶⁹¹](#) - Cublas demo
- [PR #2460⁴⁶⁹²](#) - Fixing thread bindings
- [PR #2459⁴⁶⁹³](#) - Make `-std=c++11` nvcc flag consistent for in-build and installed versions
- [Issue #2457⁴⁶⁹⁴](#) - Segmentation fault when registering a partitioned vector
- [PR #2452⁴⁶⁹⁵](#) - Properly releasing global barrier for unhandled exceptions
- [PR #2451⁴⁶⁹⁶](#) - Fixing long shutdown times
- [PR #2450⁴⁶⁹⁷](#) - Attempting to fix initialization errors on newer platforms (Boost V1.63)
- [PR #2449⁴⁶⁹⁸](#) - Replace `BOOST_COMPILER_FENCE` with an HPX version
- [PR #2448⁴⁶⁹⁹](#) - This fixes a possible race in the migration code

⁴⁶⁷⁷ <https://github.com/TheHPXProject/hpx/issues/2477>

⁴⁶⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2476>

⁴⁶⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2475>

⁴⁶⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2474>

⁴⁶⁸¹ <https://github.com/TheHPXProject/hpx/pull/2473>

⁴⁶⁸² <https://github.com/TheHPXProject/hpx/pull/2472>

⁴⁶⁸³ <https://github.com/TheHPXProject/hpx/issues/2470>

⁴⁶⁸⁴ <https://github.com/TheHPXProject/hpx/issues/2469>

⁴⁶⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2468>

⁴⁶⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2466>

⁴⁶⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2465>

⁴⁶⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2464>

⁴⁶⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2463>

⁴⁶⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2462>

⁴⁶⁹¹ <https://github.com/TheHPXProject/hpx/pull/2461>

⁴⁶⁹² <https://github.com/TheHPXProject/hpx/pull/2460>

⁴⁶⁹³ <https://github.com/TheHPXProject/hpx/pull/2459>

⁴⁶⁹⁴ <https://github.com/TheHPXProject/hpx/issues/2457>

⁴⁶⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2452>

⁴⁶⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2451>

⁴⁶⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2450>

⁴⁶⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2449>

⁴⁶⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2448>

- **PR #2445⁴⁷⁰⁰ - Fixing dataflow et.al. for futures or future-ranges wrapped into ref()**
- PR #2444⁴⁷⁰¹ - Fix segfaults
- PR #2443⁴⁷⁰² - Issue 2442
- Issue #2442⁴⁷⁰³ - Mismatch between #if/#endif and namespace scope brackets in this_thread_executors.hpp
- Issue #2441⁴⁷⁰⁴ - undeclared identifier BOOST_COMPILER_FENCE
- PR #2440⁴⁷⁰⁵ - Knl build
- PR #2438⁴⁷⁰⁶ - Datapar backend
- PR #2437⁴⁷⁰⁷ - Adapt algorithm parameter sequence changes from C++17
- PR #2436⁴⁷⁰⁸ - Adapt execution policy name changes from C++17
- Issue #2435⁴⁷⁰⁹ - Trunk broken, undefined reference to hpx::thread::interrupt(hpx::thread::id, bool)
- PR #2434⁴⁷¹⁰ - More fixes to resource manager
- PR #2433⁴⁷¹¹ - Added versions of `hpx::get_ptr` taking client side representations
- PR #2432⁴⁷¹² - Warning fixes
- PR #2431⁴⁷¹³ - Adding facility representing set of performance counters
- PR #2430⁴⁷¹⁴ - Fix parallel_executor thread spawning
- PR #2429⁴⁷¹⁵ - Fix attribute warning for gcc
- Issue #2427⁴⁷¹⁶ - Seg fault running octo-tiger with latest HPX commit
- Issue #2426⁴⁷¹⁷ - Bug in 9592f5c0bc29806fce0dbe73f35b6ca7e027edcb causes immediate crash in Octo-tiger
- PR #2425⁴⁷¹⁸ - Fix nvcc errors due to constexpr specifier
- Issue #2424⁴⁷¹⁹ - Async action on component present on `hpx::find_here` is executing synchronously
- PR #2423⁴⁷²⁰ - Fix nvcc errors due to constexpr specifier
- PR #2422⁴⁷²¹ - Implementing `hpx::this_thread` thread data functions
- PR #2421⁴⁷²² - Adding benchmark for `wait_all`

⁴⁷⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2445>

⁴⁷⁰¹ <https://github.com/TheHPXProject/hpx/pull/2444>

⁴⁷⁰² <https://github.com/TheHPXProject/hpx/pull/2443>

⁴⁷⁰³ <https://github.com/TheHPXProject/hpx/issues/2442>

⁴⁷⁰⁴ <https://github.com/TheHPXProject/hpx/issues/2441>

⁴⁷⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2440>

⁴⁷⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2438>

⁴⁷⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2437>

⁴⁷⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2436>

⁴⁷⁰⁹ <https://github.com/TheHPXProject/hpx/issues/2435>

⁴⁷¹⁰ <https://github.com/TheHPXProject/hpx/pull/2434>

⁴⁷¹¹ <https://github.com/TheHPXProject/hpx/pull/2433>

⁴⁷¹² <https://github.com/TheHPXProject/hpx/pull/2432>

⁴⁷¹³ <https://github.com/TheHPXProject/hpx/pull/2431>

⁴⁷¹⁴ <https://github.com/TheHPXProject/hpx/pull/2430>

⁴⁷¹⁵ <https://github.com/TheHPXProject/hpx/pull/2429>

⁴⁷¹⁶ <https://github.com/TheHPXProject/hpx/issues/2427>

⁴⁷¹⁷ <https://github.com/TheHPXProject/hpx/issues/2426>

⁴⁷¹⁸ <https://github.com/TheHPXProject/hpx/pull/2425>

⁴⁷¹⁹ <https://github.com/TheHPXProject/hpx/issues/2424>

⁴⁷²⁰ <https://github.com/TheHPXProject/hpx/pull/2423>

⁴⁷²¹ <https://github.com/TheHPXProject/hpx/pull/2422>

⁴⁷²² <https://github.com/TheHPXProject/hpx/pull/2421>

- [Issue #2420⁴⁷²³](#) - Returning object of a component client from another component action fails
- [PR #2419⁴⁷²⁴](#) - Infiniband parcellport
- [Issue #2418⁴⁷²⁵](#) - gcc + nvcc fails to compile code that uses `partitioned_vector`
- [PR #2417⁴⁷²⁶](#) - Fixing context switching
- [PR #2416⁴⁷²⁷](#) - Adding fixes and workarounds to allow compilation with nvcc/msvc (VS2015up3)
- [PR #2415⁴⁷²⁸](#) - Fix errors coming from hpx compute examples
- [PR #2414⁴⁷²⁹](#) - Fixing msvc12
- [PR #2413⁴⁷³⁰](#) - Enable cuda/nvcc or cuda/clang when using `add_hpx_executable()`
- [PR #2412⁴⁷³¹](#) - Fix issue in `HPX_SetupTarget.cmake` when cuda is used
- [PR #2411⁴⁷³²](#) - This fixes the core compilation issues with MSVC12
- [Issue #2410⁴⁷³³](#) - `undefined reference to opal_hwloc191_hwloc_.....`
- [PR #2409⁴⁷³⁴](#) - Fixing locking for channel and `receive_buffer`
- [PR #2407⁴⁷³⁵](#) - Solving #2402 and #2403
- [PR #2406⁴⁷³⁶](#) - Improve guards
- [PR #2405⁴⁷³⁷](#) - Enable `parallel::for_each` for iterators returning proxy types
- [PR #2404⁴⁷³⁸](#) - Forward the explicitly given `result_type` in the hpx invoke
- [Issue #2403⁴⁷³⁹](#) - `datapar_execution + zip` iterator: lambda arguments aren't references
- [Issue #2402⁴⁷⁴⁰](#) - `datapar` algorithm instantiated with wrong type #2402
- [PR #2401⁴⁷⁴¹](#) - Added support for imported libraries to `HPX_Libraries.cmake`
- [PR #2400⁴⁷⁴²](#) - Use CMake policy `CMP0060`
- [Issue #2399⁴⁷⁴³](#) - Error trying to push back vector of futures to vector
- [PR #2398⁴⁷⁴⁴](#) - Allow config `#defines` to be written out to custom `config/defines.hpp`
- [Issue #2397⁴⁷⁴⁵](#) - CMake generated config defines can cause tedious rebuilds category

⁴⁷²³ <https://github.com/TheHPXProject/hpx/issues/2420>

⁴⁷²⁴ <https://github.com/TheHPXProject/hpx/pull/2419>

⁴⁷²⁵ <https://github.com/TheHPXProject/hpx/issues/2418>

⁴⁷²⁶ <https://github.com/TheHPXProject/hpx/pull/2417>

⁴⁷²⁷ <https://github.com/TheHPXProject/hpx/pull/2416>

⁴⁷²⁸ <https://github.com/TheHPXProject/hpx/pull/2415>

⁴⁷²⁹ <https://github.com/TheHPXProject/hpx/pull/2414>

⁴⁷³⁰ <https://github.com/TheHPXProject/hpx/pull/2413>

⁴⁷³¹ <https://github.com/TheHPXProject/hpx/pull/2412>

⁴⁷³² <https://github.com/TheHPXProject/hpx/pull/2411>

⁴⁷³³ <https://github.com/TheHPXProject/hpx/issues/2410>

⁴⁷³⁴ <https://github.com/TheHPXProject/hpx/pull/2409>

⁴⁷³⁵ <https://github.com/TheHPXProject/hpx/pull/2407>

⁴⁷³⁶ <https://github.com/TheHPXProject/hpx/pull/2406>

⁴⁷³⁷ <https://github.com/TheHPXProject/hpx/pull/2405>

⁴⁷³⁸ <https://github.com/TheHPXProject/hpx/pull/2404>

⁴⁷³⁹ <https://github.com/TheHPXProject/hpx/issues/2403>

⁴⁷⁴⁰ <https://github.com/TheHPXProject/hpx/issues/2402>

⁴⁷⁴¹ <https://github.com/TheHPXProject/hpx/pull/2401>

⁴⁷⁴² <https://github.com/TheHPXProject/hpx/pull/2400>

⁴⁷⁴³ <https://github.com/TheHPXProject/hpx/issues/2399>

⁴⁷⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2398>

⁴⁷⁴⁵ <https://github.com/TheHPXProject/hpx/issues/2397>

- Issue #2396⁴⁷⁴⁶ - BOOST_ROOT paths are not used at link time
- PR #2395⁴⁷⁴⁷ - Fix target_link_libraries() issue when HPX Cuda is enabled
- Issue #2394⁴⁷⁴⁸ - Template compilation error using HPX_WITH_DATAPAR_LIBFLATARRAY
- PR #2393⁴⁷⁴⁹ - Fixing lock registration for recursive mutex
- PR #2392⁴⁷⁵⁰ - Add keywords in target_link_libraries in hpx_setup_target
- PR #2391⁴⁷⁵¹ - Clang goroutines
- Issue #2390⁴⁷⁵² - Adapt execution policy name changes from C++17
- PR #2389⁴⁷⁵³ - Chunk allocator and pool are not used and are obsolete
- PR #2388⁴⁷⁵⁴ - Adding functionalities to datapar needed by octotiger
- PR #2387⁴⁷⁵⁵ - Fixing race condition for early parcels
- Issue #2386⁴⁷⁵⁶ - Lock registration broken for recursive_mutex
- PR #2385⁴⁷⁵⁷ - Datapar zip iterator
- PR #2384⁴⁷⁵⁸ - Fixing race condition in for_loop_reduction
- PR #2383⁴⁷⁵⁹ - Continuations
- PR #2382⁴⁷⁶⁰ - add LibFlatArray-based backend for datapar
- PR #2381⁴⁷⁶¹ - remove unused typedef to get rid of compiler warnings
- PR #2380⁴⁷⁶² - Tau cleanup
- PR #2379⁴⁷⁶³ - Can send immediate
- PR #2378⁴⁷⁶⁴ - Renaming copy_helper/copy_n_helper/move_helper/move_n_helper
- Issue #2376⁴⁷⁶⁵ - Boost trunk's spinlock initializer fails to compile
- PR #2375⁴⁷⁶⁶ - Add support for minimal thread local data
- PR #2374⁴⁷⁶⁷ - Adding API functions set_config_entry_callback
- PR #2373⁴⁷⁶⁸ - Add a simple utility for debugging that gives suspended task backtraces

⁴⁷⁴⁶ <https://github.com/TheHPXProject/hpx/issues/2396>

⁴⁷⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2395>

⁴⁷⁴⁸ <https://github.com/TheHPXProject/hpx/issues/2394>

⁴⁷⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2393>

⁴⁷⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2392>

⁴⁷⁵¹ <https://github.com/TheHPXProject/hpx/pull/2391>

⁴⁷⁵² <https://github.com/TheHPXProject/hpx/issues/2390>

⁴⁷⁵³ <https://github.com/TheHPXProject/hpx/pull/2389>

⁴⁷⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2388>

⁴⁷⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2387>

⁴⁷⁵⁶ <https://github.com/TheHPXProject/hpx/issues/2386>

⁴⁷⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2385>

⁴⁷⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2384>

⁴⁷⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2383>

⁴⁷⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2382>

⁴⁷⁶¹ <https://github.com/TheHPXProject/hpx/pull/2381>

⁴⁷⁶² <https://github.com/TheHPXProject/hpx/pull/2380>

⁴⁷⁶³ <https://github.com/TheHPXProject/hpx/pull/2379>

⁴⁷⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2378>

⁴⁷⁶⁵ <https://github.com/TheHPXProject/hpx/issues/2376>

⁴⁷⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2375>

⁴⁷⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2374>

⁴⁷⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2373>

- PR #2372⁴⁷⁶⁹ - Barrier Fixes
- Issue #2370⁴⁷⁷⁰ - Can't wait on a wrapped future
- PR #2369⁴⁷⁷¹ - Fixing stable_partition
- PR #2367⁴⁷⁷² - Fixing find_prefixes for Windows platforms
- PR #2366⁴⁷⁷³ - Testing for experimental/optional only in C++14 mode
- PR #2364⁴⁷⁷⁴ - Adding set_config_entry
- PR #2363⁴⁷⁷⁵ - Fix papi
- PR #2362⁴⁷⁷⁶ - Adding missing macros for new non-direct actions
- PR #2361⁴⁷⁷⁷ - Improve cmake output to help debug compiler incompatibility check
- PR #2360⁴⁷⁷⁸ - Fixing race condition in condition_variable
- PR #2359⁴⁷⁷⁹ - Fixing shutdown when parcels are still in flight
- Issue #2357⁴⁷⁸⁰ - failed to insert console_print_action into typename_to_id_t registry
- PR #2356⁴⁷⁸¹ - Fixing return type of get_iterator_tuple
- PR #2355⁴⁷⁸² - Fixing compilation against Boost 1.62
- PR #2354⁴⁷⁸³ - Adding serialization for mask_type if CPU_COUNT > 64
- PR #2353⁴⁷⁸⁴ - Adding hooks to tie in APEX into the parcel layer
- Issue #2352⁴⁷⁸⁵ - Compile errors when using intel 17 beta (for KNL) on edison
- PR #2351⁴⁷⁸⁶ - Fix function vtable get_function_address implementation
- Issue #2350⁴⁷⁸⁷ - Build failure - master branch (4de09f5) with Intel Compiler v17
- PR #2349⁴⁷⁸⁸ - Enabling zero-copy serialization support for std::vector<>
- PR #2348⁴⁷⁸⁹ - Adding test to verify #2334 is fixed
- PR #2347⁴⁷⁹⁰ - Bug fixes for hpx.compute and hpx::lcos::channel
- PR #2346⁴⁷⁹¹ - Removing cmake "find" files that are in the APEX cmake Modules

⁴⁷⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2372>
⁴⁷⁷⁰ <https://github.com/TheHPXProject/hpx/issues/2370>
⁴⁷⁷¹ <https://github.com/TheHPXProject/hpx/pull/2369>
⁴⁷⁷² <https://github.com/TheHPXProject/hpx/pull/2367>
⁴⁷⁷³ <https://github.com/TheHPXProject/hpx/pull/2366>
⁴⁷⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2364>
⁴⁷⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2363>
⁴⁷⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2362>
⁴⁷⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2361>
⁴⁷⁷⁸ <https://github.com/TheHPXProject/hpx/pull/2360>
⁴⁷⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2359>
⁴⁷⁸⁰ <https://github.com/TheHPXProject/hpx/issues/2357>
⁴⁷⁸¹ <https://github.com/TheHPXProject/hpx/pull/2356>
⁴⁷⁸² <https://github.com/TheHPXProject/hpx/pull/2355>
⁴⁷⁸³ <https://github.com/TheHPXProject/hpx/pull/2354>
⁴⁷⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2353>
⁴⁷⁸⁵ <https://github.com/TheHPXProject/hpx/issues/2352>
⁴⁷⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2351>
⁴⁷⁸⁷ <https://github.com/TheHPXProject/hpx/issues/2350>
⁴⁷⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2349>
⁴⁷⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2348>
⁴⁷⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2347>
⁴⁷⁹¹ <https://github.com/TheHPXProject/hpx/pull/2346>

- PR #2345⁴⁷⁹² - Implemented `parallel::stable_partition`
- PR #2344⁴⁷⁹³ - Making `hpx::lcos::channel` usable with basename registration
- PR #2343⁴⁷⁹⁴ - Fix a couple of examples that failed to compile after recent api changes
- Issue #2342⁴⁷⁹⁵ - Enabling APEX causes link errors
- PR #2341⁴⁷⁹⁶ - Removing cmake “find” files that are in the APEX cmake Modules
- PR #2340⁴⁷⁹⁷ - Implemented all existing datapar algorithms using Boost.SIMD
- PR #2339⁴⁷⁹⁸ - Fixing 2338
- PR #2338⁴⁷⁹⁹ - Possible race in sliding semaphore
- PR #2337⁴⁸⁰⁰ - Adjust `osu_latency` test to measure `window_size` parcels in flight at once
- PR #2336⁴⁸⁰¹ - Allowing remote direct actions to be executed without spawning a task
- PR #2335⁴⁸⁰² - Making sure multiple components are properly initialized from arguments
- Issue #2334⁴⁸⁰³ - Cannot construct component with large vector on a remote locality
- PR #2332⁴⁸⁰⁴ - Fixing `hpx::lcos::local::barrier`
- PR #2331⁴⁸⁰⁵ - Updating APEX support to include OTF2
- PR #2330⁴⁸⁰⁶ - Support for data-parallelism for parallel algorithms
- Issue #2329⁴⁸⁰⁷ - Coordinate settings in cmake
- PR #2328⁴⁸⁰⁸ - fix LibGeoDecomp builds with HPX + GCC 5.3.0 + CUDA 8RC
- PR #2326⁴⁸⁰⁹ - Making `scan_partitioner` work (for now)
- Issue #2323⁴⁸¹⁰ - Constructing a vector of components only correctly initializes the first component
- PR #2322⁴⁸¹¹ - Fix problems that bubbled up after merging #2278
- PR #2321⁴⁸¹² - Scalable barrier
- PR #2320⁴⁸¹³ - Std flag fixes
- Issue #2319⁴⁸¹⁴ - -std=c++14 and -std=c++1y with Intel can't build recent Boost builds due to insufficient C++14 support; don't enable these flags by default for Intel

⁴⁷⁹² <https://github.com/TheHPXProject/hpx/pull/2345>

⁴⁷⁹³ <https://github.com/TheHPXProject/hpx/pull/2344>

⁴⁷⁹⁴ <https://github.com/TheHPXProject/hpx/pull/2343>

⁴⁷⁹⁵ <https://github.com/TheHPXProject/hpx/issues/2342>

⁴⁷⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2341>

⁴⁷⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2340>

⁴⁷⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2339>

⁴⁷⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2338>

⁴⁸⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2337>

⁴⁸⁰¹ <https://github.com/TheHPXProject/hpx/pull/2336>

⁴⁸⁰² <https://github.com/TheHPXProject/hpx/pull/2335>

⁴⁸⁰³ <https://github.com/TheHPXProject/hpx/issues/2334>

⁴⁸⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2332>

⁴⁸⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2331>

⁴⁸⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2330>

⁴⁸⁰⁷ <https://github.com/TheHPXProject/hpx/issues/2329>

⁴⁸⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2328>

⁴⁸⁰⁹ <https://github.com/TheHPXProject/hpx/pull/2326>

⁴⁸¹⁰ <https://github.com/TheHPXProject/hpx/issues/2323>

⁴⁸¹¹ <https://github.com/TheHPXProject/hpx/pull/2322>

⁴⁸¹² <https://github.com/TheHPXProject/hpx/pull/2321>

⁴⁸¹³ <https://github.com/TheHPXProject/hpx/pull/2320>

⁴⁸¹⁴ <https://github.com/TheHPXProject/hpx/issues/2319>

- PR #2318⁴⁸¹⁵ - Improve handling of `-hpx:bind=<bind-spec>`
- PR #2317⁴⁸¹⁶ - Making sure command line warnings are printed once only
- PR #2316⁴⁸¹⁷ - Fixing command line handling for default bind mode
- PR #2315⁴⁸¹⁸ - Set `id_retrieved` if `set_id` is present
- Issue #2314⁴⁸¹⁹ - Warning for requested/allocated thread discrepancy is printed twice
- Issue #2313⁴⁸²⁰ - `-hpx:print-bind` doesn't work with `-hpx:pu-step`
- Issue #2312⁴⁸²¹ - `-hpx:bind` range specifier restrictions are overly restrictive
- Issue #2311⁴⁸²² - `hpx_0.9.99` out of project build fails
- PR #2310⁴⁸²³ - Simplify function registration
- PR #2309⁴⁸²⁴ - Spelling and grammar revisions in documentation (and some code)
- PR #2306⁴⁸²⁵ - Correct minor typo in the documentation
- PR #2305⁴⁸²⁶ - Cleaning up and fixing parcel coalescing
- PR #2304⁴⁸²⁷ - Inspect checks for stream related includes
- PR #2303⁴⁸²⁸ - Add functionality allowing to enumerate threads of given state
- PR #2301⁴⁸²⁹ - Algorithm overloads fix for VS2013
- PR #2300⁴⁸³⁰ - Use `<cstdint>`, add inspect checks
- PR #2299⁴⁸³¹ - Replace `boost::[c]ref` with `std::[c]ref`, add inspect checks
- PR #2297⁴⁸³² - Fixing compilation with no `hw_loc`
- PR #2296⁴⁸³³ - `Hpx compute`
- PR #2295⁴⁸³⁴ - Making sure `for_loop(execution::par, 0, N, ...)` is actually executed in parallel
- PR #2294⁴⁸³⁵ - Throwing exceptions if the runtime is not up and running
- PR #2293⁴⁸³⁶ - Removing unused parcel port code
- PR #2292⁴⁸³⁷ - Refactor function vttables

⁴⁸¹⁵ <https://github.com/TheHPXProject/hpx/pull/2318>

⁴⁸¹⁶ <https://github.com/TheHPXProject/hpx/pull/2317>

⁴⁸¹⁷ <https://github.com/TheHPXProject/hpx/pull/2316>

⁴⁸¹⁸ <https://github.com/TheHPXProject/hpx/pull/2315>

⁴⁸¹⁹ <https://github.com/TheHPXProject/hpx/issues/2314>

⁴⁸²⁰ <https://github.com/TheHPXProject/hpx/issues/2313>

⁴⁸²¹ <https://github.com/TheHPXProject/hpx/issues/2312>

⁴⁸²² <https://github.com/TheHPXProject/hpx/issues/2311>

⁴⁸²³ <https://github.com/TheHPXProject/hpx/pull/2310>

⁴⁸²⁴ <https://github.com/TheHPXProject/hpx/pull/2309>

⁴⁸²⁵ <https://github.com/TheHPXProject/hpx/pull/2306>

⁴⁸²⁶ <https://github.com/TheHPXProject/hpx/pull/2305>

⁴⁸²⁷ <https://github.com/TheHPXProject/hpx/pull/2304>

⁴⁸²⁸ <https://github.com/TheHPXProject/hpx/pull/2303>

⁴⁸²⁹ <https://github.com/TheHPXProject/hpx/pull/2301>

⁴⁸³⁰ <https://github.com/TheHPXProject/hpx/pull/2300>

⁴⁸³¹ <https://github.com/TheHPXProject/hpx/pull/2299>

⁴⁸³² <https://github.com/TheHPXProject/hpx/pull/2297>

⁴⁸³³ <https://github.com/TheHPXProject/hpx/pull/2296>

⁴⁸³⁴ <https://github.com/TheHPXProject/hpx/pull/2295>

⁴⁸³⁵ <https://github.com/TheHPXProject/hpx/pull/2294>

⁴⁸³⁶ <https://github.com/TheHPXProject/hpx/pull/2293>

⁴⁸³⁷ <https://github.com/TheHPXProject/hpx/pull/2292>

- PR #2291⁴⁸³⁸ - Fixing 2286
- PR #2290⁴⁸³⁹ - Simplify algorithm overloads
- PR #2289⁴⁸⁴⁰ - Adding performance counters reporting parcel related data on a per-action basis
- Issue #2288⁴⁸⁴¹ - Remove dormant parcelports
- Issue #2286⁴⁸⁴² - adjustments to parcel handling to support parcelports that do not need a connection cache
- PR #2285⁴⁸⁴³ - add CMake option to disable package export
- PR #2283⁴⁸⁴⁴ - Add more inspect checks for use of deprecated components
- Issue #2282⁴⁸⁴⁵ - Arithmetic exception in executor static chunker
- Issue #2281⁴⁸⁴⁶ - For loop doesn't parallelize
- PR #2280⁴⁸⁴⁷ - Fixing 2277: build failure with PAPI
- PR #2279⁴⁸⁴⁸ - Child vs parent stealing
- Issue #2277⁴⁸⁴⁹ - master branch build failure (53c5b4f) with papi
- PR #2276⁴⁸⁵⁰ - Compile time launch policies
- PR #2275⁴⁸⁵¹ - Replace boost::chrono with std::chrono in interfaces
- PR #2274⁴⁸⁵² - Replace most uses of Boost.Assign with initializer list
- PR #2273⁴⁸⁵³ - Fixed typos
- PR #2272⁴⁸⁵⁴ - Inspect checks
- PR #2270⁴⁸⁵⁵ - Adding test verifying -lhp.os_threads=all
- PR #2269⁴⁸⁵⁶ - Added inspect check for now obsolete boost type traits
- PR #2268⁴⁸⁵⁷ - Moving more code into source files
- Issue #2267⁴⁸⁵⁸ - Add inspect support to deprecate Boost.TypeTraits
- PR #2265⁴⁸⁵⁹ - Adding channel LCO
- PR #2264⁴⁸⁶⁰ - Make support for std::ref mandatory

⁴⁸³⁸ <https://github.com/TheHPXProject/hpx/pull/2291>
⁴⁸³⁹ <https://github.com/TheHPXProject/hpx/pull/2290>
⁴⁸⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2289>
⁴⁸⁴¹ <https://github.com/TheHPXProject/hpx/issues/2288>
⁴⁸⁴² <https://github.com/TheHPXProject/hpx/issues/2286>
⁴⁸⁴³ <https://github.com/TheHPXProject/hpx/pull/2285>
⁴⁸⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2283>
⁴⁸⁴⁵ <https://github.com/TheHPXProject/hpx/issues/2282>
⁴⁸⁴⁶ <https://github.com/TheHPXProject/hpx/issues/2281>
⁴⁸⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2280>
⁴⁸⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2279>
⁴⁸⁴⁹ <https://github.com/TheHPXProject/hpx/issues/2277>
⁴⁸⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2276>
⁴⁸⁵¹ <https://github.com/TheHPXProject/hpx/pull/2275>
⁴⁸⁵² <https://github.com/TheHPXProject/hpx/pull/2274>
⁴⁸⁵³ <https://github.com/TheHPXProject/hpx/pull/2273>
⁴⁸⁵⁴ <https://github.com/TheHPXProject/hpx/pull/2272>
⁴⁸⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2270>
⁴⁸⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2269>
⁴⁸⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2268>
⁴⁸⁵⁸ <https://github.com/TheHPXProject/hpx/issues/2267>
⁴⁸⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2265>
⁴⁸⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2264>

- PR #2263⁴⁸⁶¹ - Constrain tuple_member forwarding constructor
- Issue #2262⁴⁸⁶² - Test hpx.os_threads=all
- Issue #2261⁴⁸⁶³ - OS X: Error: no matching constructor for initialization of 'hpx::lcos::local::condition_variable_any'
- Issue #2260⁴⁸⁶⁴ - Make support for std::ref mandatory
- PR #2259⁴⁸⁶⁵ - Remove most of Boost.MPL, Boost.EnableIf and Boost.TypeTraits
- PR #2258⁴⁸⁶⁶ - Fixing #2256
- PR #2257⁴⁸⁶⁷ - Fixing launch process
- Issue #2256⁴⁸⁶⁸ - Actions are not registered if not invoked
- PR #2255⁴⁸⁶⁹ - Coalescing histogram
- PR #2254⁴⁸⁷⁰ - Silence explicit initialization in copy-constructor warnings
- PR #2253⁴⁸⁷¹ - Drop support for GCC 4.6 and 4.7
- PR #2252⁴⁸⁷² - Prepare V1.0
- PR #2251⁴⁸⁷³ - Convert to 0.9.99
- PR #2249⁴⁸⁷⁴ - Adding iterator_facade and iterator_adaptor
- Issue #2248⁴⁸⁷⁵ - Need a feature to yield to a new task immediately
- PR #2246⁴⁸⁷⁶ - Adding split_future
- PR #2245⁴⁸⁷⁷ - Add an example for handing over a component instance to a dynamically launched locality
- Issue #2243⁴⁸⁷⁸ - Add example demonstrating AGAS symbolic name registration
- Issue #2242⁴⁸⁷⁹ - pkgconfig test broken on CentOS 7 / Boost 1.61
- Issue #2241⁴⁸⁸⁰ - Compilation error for partitioned vector in hpx_compute branch
- PR #2240⁴⁸⁸¹ - Fixing termination detection on one locality
- Issue #2239⁴⁸⁸² - Create a new facility lcos::split_all
- Issue #2236⁴⁸⁸³ - hpx::cout vs. std::cout

⁴⁸⁶¹ <https://github.com/TheHPXProject/hpx/pull/2263>

⁴⁸⁶² <https://github.com/TheHPXProject/hpx/issues/2262>

⁴⁸⁶³ <https://github.com/TheHPXProject/hpx/issues/2261>

⁴⁸⁶⁴ <https://github.com/TheHPXProject/hpx/issues/2260>

⁴⁸⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2259>

⁴⁸⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2258>

⁴⁸⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2257>

⁴⁸⁶⁸ <https://github.com/TheHPXProject/hpx/issues/2256>

⁴⁸⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2255>

⁴⁸⁷⁰ <https://github.com/TheHPXProject/hpx/pull/2254>

⁴⁸⁷¹ <https://github.com/TheHPXProject/hpx/pull/2253>

⁴⁸⁷² <https://github.com/TheHPXProject/hpx/pull/2252>

⁴⁸⁷³ <https://github.com/TheHPXProject/hpx/pull/2251>

⁴⁸⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2249>

⁴⁸⁷⁵ <https://github.com/TheHPXProject/hpx/issues/2248>

⁴⁸⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2246>

⁴⁸⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2245>

⁴⁸⁷⁸ <https://github.com/TheHPXProject/hpx/issues/2243>

⁴⁸⁷⁹ <https://github.com/TheHPXProject/hpx/issues/2242>

⁴⁸⁸⁰ <https://github.com/TheHPXProject/hpx/issues/2241>

⁴⁸⁸¹ <https://github.com/TheHPXProject/hpx/pull/2240>

⁴⁸⁸² <https://github.com/TheHPXProject/hpx/issues/2239>

⁴⁸⁸³ <https://github.com/TheHPXProject/hpx/issues/2236>

- PR #2232⁴⁸⁸⁴ - Implement local-only primary namespace service
- Issue #2147⁴⁸⁸⁵ - would like to know how much data is being routed by particular actions
- Issue #2109⁴⁸⁸⁶ - Warning while compiling hpx
- Issue #1973⁴⁸⁸⁷ - Setting INTERFACE_COMPILE_OPTIONS for hpx_init in CMake taints Fortran_FLAGS
- Issue #1864⁴⁸⁸⁸ - run_guarded using bound function ignores reference
- Issue #1754⁴⁸⁸⁹ - Running with TCP parcelport causes immediate crash or freeze
- Issue #1655⁴⁸⁹⁰ - Enable zip_iterator to be used with Boost traversal iterator categories
- Issue #1591⁴⁸⁹¹ - Optimize AGAS for shared memory only operation
- Issue #1401⁴⁸⁹² - Need an efficient infiniband parcelport
- Issue #1125⁴⁸⁹³ - Fix the IPC parcelport
- Issue #839⁴⁸⁹⁴ - Refactor ibverbs and shmем parcelport
- Issue #702⁴⁸⁹⁵ - Add instrumentation of parcel layer
- Issue #668⁴⁸⁹⁶ - Implement ispc task interface
- Issue #533⁴⁸⁹⁷ - Thread queue/dequeue internal parameters should be runtime configurable
- Issue #475⁴⁸⁹⁸ - Create a means of combining performance counters into querysets

HPX V0.9.99 (Jul 15, 2016)

General changes

As the version number of this release hints, we consider this release to be a preview for the upcoming *HPX* V1.0. All of the functionalities we set out to implement for V1.0 are in place; all of the features we wanted to have exposed are ready. We are very happy with the stability and performance of *HPX* and we would like to present this release to the community in order for us to gather broad feedback before releasing V1.0. We still expect for some minor details to change, but on the whole this release represents what we would like to have in a V1.0.

Overall, since the last release we have had almost 1600 commits while closing almost 400 tickets. These numbers reflect the incredible development activity we have seen over the last couple of months. We would like to express a big ‘Thank you!’ to all contributors and those who helped to make this release happen.

The most notable addition in terms of new functionality available with this release is the full implementation of object migration (i.e. the ability to transparently move *HPX* components to a different compute node). Additionally, this release of *HPX* cleans up many minor issues and some API inconsistencies.

Here are some of the main highlights and changes for this release (in no particular order):

- ⁴⁸⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2232>
- ⁴⁸⁸⁵ <https://github.com/TheHPXProject/hpx/issues/2147>
- ⁴⁸⁸⁶ <https://github.com/TheHPXProject/hpx/issues/2109>
- ⁴⁸⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1973>
- ⁴⁸⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1864>
- ⁴⁸⁸⁹ <https://github.com/TheHPXProject/hpx/issues/1754>
- ⁴⁸⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1655>
- ⁴⁸⁹¹ <https://github.com/TheHPXProject/hpx/issues/1591>
- ⁴⁸⁹² <https://github.com/TheHPXProject/hpx/issues/1401>
- ⁴⁸⁹³ <https://github.com/TheHPXProject/hpx/issues/1125>
- ⁴⁸⁹⁴ <https://github.com/TheHPXProject/hpx/issues/839>
- ⁴⁸⁹⁵ <https://github.com/TheHPXProject/hpx/issues/702>
- ⁴⁸⁹⁶ <https://github.com/TheHPXProject/hpx/issues/668>
- ⁴⁸⁹⁷ <https://github.com/TheHPXProject/hpx/issues/533>
- ⁴⁸⁹⁸ <https://github.com/TheHPXProject/hpx/issues/475>

- We have fixed a couple of issues in AGAS and the parcel layer which have caused hangs, segmentation faults at exit, and a slowdown of applications over time. Fixing those has significantly increased the overall stability and performance of distributed runs.
- We have started to add parallel algorithm overloads based on the C++ Extensions for Ranges (N4560⁴⁸⁹⁹) proposal. This also includes the addition of projections to the existing algorithms. Please see Issue #1668⁴⁹⁰⁰ for a list of algorithms which have been adapted to N4560⁴⁹⁰¹.
- We have implemented index-based parallel for-loops based on a corresponding standardization proposal (P0075R1⁴⁹⁰²). Please see Issue #2016⁴⁹⁰³ for a list of available algorithms.
- We have added implementations for more parallel algorithms as proposed for the upcoming C++ 17 Standard. See Issue #1141⁴⁹⁰⁴ for an overview of which algorithms are available by now.
- We have started to implement a new prototypical functionality with *HPX.Compute* which uniformly exposes some of the higher level APIs to heterogeneous architectures (currently CUDA). This functionality is an early preview and should not be considered stable. It may change considerably in the future.
- We have pervasively added (optional) executor arguments to all API functions which schedule new work. Executors are now used throughout the code base as the main means of executing tasks.
- Added `hpx::make_future<R>(future<T> &&)` allowing to convert a future of any type T into a future of any other type R, either based on default conversion rules of the embedded types or using a given explicit conversion function.
- We finally finished the implementation of transparent migration of components to another locality. It is now possible to trigger a migration operation without ‘stopping the world’ for the object to migrate. *HPX* will make sure that no work is being performed on an object before it is migrated and that all subsequently scheduled work for the migrated object will be transparently forwarded to the new locality. Please note that the global id of the migrated object does not change, thus the application will not have to be changed in any way to support this new functionality. Please note that this feature is currently considered experimental. See Issue #559⁴⁹⁰⁵ and PR #1966⁴⁹⁰⁶ for more details.
- The `hpx::dataflow` facility is now usable with actions. Similarly to `hpx::async`, actions can be specified as an explicit template argument (`hpx::dataflow<Action>(target, ...)`) or as the first argument (`hpx::dataflow(Action(), target, ...)`). We have also enabled the use of distribution policies as the target for dataflow invocations. Please see Issue #1265⁴⁹⁰⁷ and PR #1912⁴⁹⁰⁸ for more information.
- Adding overloads of `gather_here` and `gather_there` to accept the plain values of the data to gather (in addition to the existing overloads expecting futures).
- We have cleaned up and refactored large parts of the code base. This helped reducing compile and link times of *HPX* itself and also of applications depending on it. We have further decreased the dependency of *HPX* on the Boost libraries by replacing part of those with facilities available from the standard libraries.
- Wherever possible we have removed dependencies of our API on Boost by replacing those with the equivalent facility from the C++11 standard library.
- We have added new performance counters for parcel coalescing, file-IO, the AGAS cache, and overall scheduler time. Resetting performance counters has been overhauled and fixed.

⁴⁸⁹⁹ <http://wg21.link/n4560>

⁴⁹⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1668>

⁴⁹⁰¹ <http://wg21.link/n4560>

⁴⁹⁰² <http://wg21.link/p0075r1>

⁴⁹⁰³ <https://github.com/TheHPXProject/hpx/issues/2016>

⁴⁹⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1141>

⁴⁹⁰⁵ <https://github.com/TheHPXProject/hpx/issues/559>

⁴⁹⁰⁶ <https://github.com/TheHPXProject/hpx/pull/1966>

⁴⁹⁰⁷ <https://github.com/TheHPXProject/hpx/issues/1265>

⁴⁹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/1912>

- We have introduced a generic client type `hpx::components::client<>` and added support for using it with `hpx::async`. This removes the necessity to implement specific client types for every component type without losing type safety. This deemphasizes the need for using the low level `hpx::id_type` for referencing (possibly remote) component instances. The plan is to deprecate the direct use of `hpx::id_type` in user code in the future.
- We have added a special iterator which supports automatic prefetching of one or more arrays for speeding up loop-like code (see `hpx::parallel::util::make_prefetcher_context()`).
- We have extended the interfaces exposed from executors (as proposed by [N4406](http://wg21.link/n4406)⁴⁹⁰⁹) to accept an arbitrary number of arguments.

Breaking changes

- In order to move the dataflow facility to namespace `hpx` we added a definition of `hpx::dataflow` which might create ambiguities in existing codes. The previous definition of this facility (`hpx::lcos::local::dataflow`) has been deprecated and is available only if the constant `-DHPX_WITH_LOCAL_DATAFLOW_COMPATIBILITY=On` to `CMake`⁴⁹¹⁰ is defined at configuration time. Please explicitly qualify all uses of the dataflow facility if you enable this compatibility setting and encounter ambiguities.
- The adaptation of the C++ Extensions for Ranges ([N4560](http://wg21.link/n4560)⁴⁹¹¹) proposal imposes some breaking changes related to the return types of some of the parallel algorithms. Please see [Issue #1668](https://github.com/TheHPXProject/hpx/issues/1668)⁴⁹¹² for a list of algorithms which have already been adapted.
- The facility `hpx::lcos::make_future_void()` has been replaced by `hpx::make_future<void>()`.
- We have removed support for Intel V13 and gcc 4.4.x.
- We have removed (default) support for the generic `hpx::parallel::execution_policy` because it was removed from the Parallelism TS (`__cpp11_n4104__`) while it was being added to the upcoming C++17 Standard. This facility can be still enabled at configure time by specifying `-DHPX_WITH_GENERIC_EXECUTION_POLICY=On` to `CMake`.
- Uses of `boost::shared_ptr` and related facilities have been replaced with `std::shared_ptr` and friends. Uses of `boost::unique_lock`, `boost::lock_guard` etc. have also been replaced by the equivalent (and equally named) tools available from the C++11 standard library.
- Facilities that used to expect an explicit `boost::unique_lock` now take an `std::unique_lock`. Additionally, `condition_variable` no longer aliases `condition_variable_any`; its interface now only works with `std::unique_lock<local::mutex>`.
- Uses of `boost::function`, `boost::bind`, `boost::tuple` have been replaced by the corresponding facilities in *HPX* (`hpx::util::function`, `hpx::util::bind`, and `hpx::util::tuple`, respectively).

⁴⁹⁰⁹ <http://wg21.link/n4406>

⁴⁹¹⁰ <https://www.cmake.org>

⁴⁹¹¹ <http://wg21.link/n4560>

⁴⁹¹² <https://github.com/TheHPXProject/hpx/issues/1668>

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [PR #2250⁴⁹¹³](#) - change default chunker of parallel executor to static one
- [PR #2247⁴⁹¹⁴](#) - HPX on ppc64le
- [PR #2244⁴⁹¹⁵](#) - Fixing MSVC problems
- [PR #2238⁴⁹¹⁶](#) - Fixing small typos
- [PR #2237⁴⁹¹⁷](#) - Fixing small typos
- [PR #2234⁴⁹¹⁸](#) - Fix broken add test macro when extra args are passed in
- [PR #2231⁴⁹¹⁹](#) - Fixing possible race during future awaiting in serialization
- [PR #2230⁴⁹²⁰](#) - Fix stream nvcc
- [PR #2229⁴⁹²¹](#) - Fixed run_as_hpx_thread
- [PR #2228⁴⁹²²](#) - On prefetching_test branch : adding prefetching_iterator and related tests used for prefetching containers within lambda functions
- [PR #2227⁴⁹²³](#) - Support for HPXCL's opencil::event
- [PR #2226⁴⁹²⁴](#) - Preparing for release of V0.9.99
- [PR #2225⁴⁹²⁵](#) - fix issue when compiling components with hpxcxx
- [PR #2224⁴⁹²⁶](#) - Compute alloc fix
- [PR #2223⁴⁹²⁷](#) - Simplify promise
- [PR #2222⁴⁹²⁸](#) - Replace last uses of boost::function by util::function_nonsr
- [PR #2221⁴⁹²⁹](#) - Fix config tests
- [PR #2220⁴⁹³⁰](#) - Fixing gcc 4.6 compilation issues
- [PR #2219⁴⁹³¹](#) - nullptr support for [unique_] function
- [PR #2218⁴⁹³²](#) - Introducing clang tidy
- [PR #2216⁴⁹³³](#) - Replace NULL with nullptr

⁴⁹¹³ <https://github.com/TheHPXProject/hpx/pull/2250>

⁴⁹¹⁴ <https://github.com/TheHPXProject/hpx/pull/2247>

⁴⁹¹⁵ <https://github.com/TheHPXProject/hpx/pull/2244>

⁴⁹¹⁶ <https://github.com/TheHPXProject/hpx/pull/2238>

⁴⁹¹⁷ <https://github.com/TheHPXProject/hpx/pull/2237>

⁴⁹¹⁸ <https://github.com/TheHPXProject/hpx/pull/2234>

⁴⁹¹⁹ <https://github.com/TheHPXProject/hpx/pull/2231>

⁴⁹²⁰ <https://github.com/TheHPXProject/hpx/pull/2230>

⁴⁹²¹ <https://github.com/TheHPXProject/hpx/pull/2229>

⁴⁹²² <https://github.com/TheHPXProject/hpx/pull/2228>

⁴⁹²³ <https://github.com/TheHPXProject/hpx/pull/2227>

⁴⁹²⁴ <https://github.com/TheHPXProject/hpx/pull/2226>

⁴⁹²⁵ <https://github.com/TheHPXProject/hpx/pull/2225>

⁴⁹²⁶ <https://github.com/TheHPXProject/hpx/pull/2224>

⁴⁹²⁷ <https://github.com/TheHPXProject/hpx/pull/2223>

⁴⁹²⁸ <https://github.com/TheHPXProject/hpx/pull/2222>

⁴⁹²⁹ <https://github.com/TheHPXProject/hpx/pull/2221>

⁴⁹³⁰ <https://github.com/TheHPXProject/hpx/pull/2220>

⁴⁹³¹ <https://github.com/TheHPXProject/hpx/pull/2219>

⁴⁹³² <https://github.com/TheHPXProject/hpx/pull/2218>

⁴⁹³³ <https://github.com/TheHPXProject/hpx/pull/2216>

- Issue #2214⁴⁹³⁴ - Let inspect flag use of NULL, suggest nullptr instead
- PR #2213⁴⁹³⁵ - Require support for nullptr
- PR #2212⁴⁹³⁶ - Properly find jemalloc through pkg-config
- PR #2211⁴⁹³⁷ - Disable a couple of warnings reported by Intel on Windows
- PR #2210⁴⁹³⁸ - Fixed host::block_allocator::bulk_construct
- PR #2209⁴⁹³⁹ - Started to clean up new sort algorithms, made things compile for sort_by_key
- PR #2208⁴⁹⁴⁰ - A couple of fixes that were exposed by a new sort algorithm
- PR #2207⁴⁹⁴¹ - Adding missing includes in /hpx/include/serialization.hpp
- PR #2206⁴⁹⁴² - Call package_action::get_future before package_action::apply
- PR #2205⁴⁹⁴³ - The indirect_packaged_task::operator() needs to be run on a HPX thread
- PR #2204⁴⁹⁴⁴ - Variadic executor parameters
- PR #2203⁴⁹⁴⁵ - Delay-initialize members of partitioned iterator
- PR #2202⁴⁹⁴⁶ - Added segmented fill for hpx::vector
- Issue #2201⁴⁹⁴⁷ - Null Thread id encountered on partitioned_vector
- PR #2200⁴⁹⁴⁸ - Fix hangs
- PR #2199⁴⁹⁴⁹ - Deprecating hpx/traits.hpp
- PR #2198⁴⁹⁵⁰ - Making explicit inclusion of external libraries into build
- PR #2197⁴⁹⁵¹ - Fix typo in QT CMakeLists
- PR #2196⁴⁹⁵² - Fixing a gcc warning about attributes being ignored
- PR #2194⁴⁹⁵³ - Fixing partitioned_vector_spmf_foreach example
- Issue #2193⁴⁹⁵⁴ - partitioned_vector_spmf_foreach seg faults
- PR #2192⁴⁹⁵⁵ - Support Boost.Thread v4
- PR #2191⁴⁹⁵⁶ - HPX.Compute prototype

⁴⁹³⁴ <https://github.com/TheHPXProject/hpx/issues/2214>

⁴⁹³⁵ <https://github.com/TheHPXProject/hpx/pull/2213>

⁴⁹³⁶ <https://github.com/TheHPXProject/hpx/pull/2212>

⁴⁹³⁷ <https://github.com/TheHPXProject/hpx/pull/2211>

⁴⁹³⁸ <https://github.com/TheHPXProject/hpx/pull/2210>

⁴⁹³⁹ <https://github.com/TheHPXProject/hpx/pull/2209>

⁴⁹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2208>

⁴⁹⁴¹ <https://github.com/TheHPXProject/hpx/pull/2207>

⁴⁹⁴² <https://github.com/TheHPXProject/hpx/pull/2206>

⁴⁹⁴³ <https://github.com/TheHPXProject/hpx/pull/2205>

⁴⁹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2204>

⁴⁹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2203>

⁴⁹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/2202>

⁴⁹⁴⁷ <https://github.com/TheHPXProject/hpx/issues/2201>

⁴⁹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/2200>

⁴⁹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2199>

⁴⁹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2198>

⁴⁹⁵¹ <https://github.com/TheHPXProject/hpx/pull/2197>

⁴⁹⁵² <https://github.com/TheHPXProject/hpx/pull/2196>

⁴⁹⁵³ <https://github.com/TheHPXProject/hpx/pull/2194>

⁴⁹⁵⁴ <https://github.com/TheHPXProject/hpx/issues/2193>

⁴⁹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2192>

⁴⁹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2191>

- [PR #2190⁴⁹⁵⁷](#) - Spawning operation on new thread if remaining stack space becomes too small
- [PR #2189⁴⁹⁵⁸](#) - Adding callback taking index and future to when_each
- [PR #2188⁴⁹⁵⁹](#) - Adding new example demonstrating receive_buffer
- [PR #2187⁴⁹⁶⁰](#) - Mask 128-bit ints if CUDA is being used
- [PR #2186⁴⁹⁶¹](#) - Make startup & shutdown functions unique_function
- [PR #2185⁴⁹⁶²](#) - Fixing logging output not to cause hang on shutdown
- [PR #2184⁴⁹⁶³](#) - Allowing component clients as action return types
- [Issue #2183⁴⁹⁶⁴](#) - Enabling logging output causes hang on shutdown
- [Issue #2182⁴⁹⁶⁵](#) - 1d_stencil seg fault
- [Issue #2181⁴⁹⁶⁶](#) - Setting small stack size does not change default
- [PR #2180⁴⁹⁶⁷](#) - Changing default bind mode to balanced
- [PR #2179⁴⁹⁶⁸](#) - adding prefetching_iterator and related tests used for prefetching containers within lambda functions
- [PR #2177⁴⁹⁶⁹](#) - Fixing 2176
- [Issue #2176⁴⁹⁷⁰](#) - Launch process test fails on OSX
- [PR #2175⁴⁹⁷¹](#) - Fix unbalanced config/warnings includes, add some new ones
- [PR #2174⁴⁹⁷²](#) - Fix test categorization : regression not unit
- [Issue #2172⁴⁹⁷³](#) - Different performance results
- [Issue #2171⁴⁹⁷⁴](#) - “negative entry in reference count table” running octotiger on 32 nodes on queenbee
- [Issue #2170⁴⁹⁷⁵](#) - Error while compiling on Mac + boost 1.60
- [PR #2168⁴⁹⁷⁶](#) - Fixing problems with is_bitwise_serializable
- [Issue #2167⁴⁹⁷⁷](#) - startup & shutdown function should accept unique_function
- [Issue #2166⁴⁹⁷⁸](#) - Simple receive_buffer example
- [PR #2165⁴⁹⁷⁹](#) - Fix wait all

⁴⁹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2190>
⁴⁹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2189>
⁴⁹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2188>
⁴⁹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2187>
⁴⁹⁶¹ <https://github.com/TheHPXProject/hpx/pull/2186>
⁴⁹⁶² <https://github.com/TheHPXProject/hpx/pull/2185>
⁴⁹⁶³ <https://github.com/TheHPXProject/hpx/pull/2184>
⁴⁹⁶⁴ <https://github.com/TheHPXProject/hpx/issues/2183>
⁴⁹⁶⁵ <https://github.com/TheHPXProject/hpx/issues/2182>
⁴⁹⁶⁶ <https://github.com/TheHPXProject/hpx/issues/2181>
⁴⁹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2180>
⁴⁹⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2179>
⁴⁹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2177>
⁴⁹⁷⁰ <https://github.com/TheHPXProject/hpx/issues/2176>
⁴⁹⁷¹ <https://github.com/TheHPXProject/hpx/pull/2175>
⁴⁹⁷² <https://github.com/TheHPXProject/hpx/pull/2174>
⁴⁹⁷³ <https://github.com/TheHPXProject/hpx/issues/2172>
⁴⁹⁷⁴ <https://github.com/TheHPXProject/hpx/issues/2171>
⁴⁹⁷⁵ <https://github.com/TheHPXProject/hpx/issues/2170>
⁴⁹⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2168>
⁴⁹⁷⁷ <https://github.com/TheHPXProject/hpx/issues/2167>
⁴⁹⁷⁸ <https://github.com/TheHPXProject/hpx/issues/2166>
⁴⁹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2165>

- PR #2164⁴⁹⁸⁰ - Fix wait all
- PR #2163⁴⁹⁸¹ - Fix some typos in config tests
- PR #2162⁴⁹⁸² - Improve #includes
- PR #2160⁴⁹⁸³ - Add inspect check for missing #include <list>
- PR #2159⁴⁹⁸⁴ - Add missing finalize call to stop test hanging
- PR #2158⁴⁹⁸⁵ - Algo fixes
- PR #2157⁴⁹⁸⁶ - Stack check
- Issue #2156⁴⁹⁸⁷ - OSX reports stack space incorrectly (generic context coroutines)
- Issue #2155⁴⁹⁸⁸ - Race condition suspected in runtime
- PR #2154⁴⁹⁸⁹ - Replace boost::detail::atomic_count with the new util::atomic_count
- PR #2153⁴⁹⁹⁰ - Fix stack overflow on OSX
- PR #2152⁴⁹⁹¹ - Define is_bitwise_serializable as is_trivially_copyable when available
- PR #2151⁴⁹⁹² - Adding missing <cstring> for std::mem* functions
- Issue #2150⁴⁹⁹³ - Unable to use component clients as action return types
- PR #2149⁴⁹⁹⁴ - std::memmove copies bytes, use bytes*sizeof(type) when copying larger types
- PR #2146⁴⁹⁹⁵ - Adding customization point for parallel copy/move
- PR #2145⁴⁹⁹⁶ - Applying changes to address warnings issued by latest version of PVS Studio
- Issue #2148⁴⁹⁹⁷ - hpx::parallel::copy is broken after trivially copyable changes
- PR #2144⁴⁹⁹⁸ - Some minor tweaks to compute prototype
- PR #2143⁴⁹⁹⁹ - Added Boost version support information over OSX platform
- PR #2142⁵⁰⁰⁰ - Fixing memory leak in example
- PR #2141⁵⁰⁰¹ - Add missing specializations in execution policies
- PR #2139⁵⁰⁰² - This PR fixes a few problems reported by Clang's Undefined Behavior sanitizer

⁴⁹⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2164>

⁴⁹⁸¹ <https://github.com/TheHPXProject/hpx/pull/2163>

⁴⁹⁸² <https://github.com/TheHPXProject/hpx/pull/2162>

⁴⁹⁸³ <https://github.com/TheHPXProject/hpx/pull/2160>

⁴⁹⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2159>

⁴⁹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2158>

⁴⁹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2157>

⁴⁹⁸⁷ <https://github.com/TheHPXProject/hpx/issues/2156>

⁴⁹⁸⁸ <https://github.com/TheHPXProject/hpx/issues/2155>

⁴⁹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2154>

⁴⁹⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2153>

⁴⁹⁹¹ <https://github.com/TheHPXProject/hpx/pull/2152>

⁴⁹⁹² <https://github.com/TheHPXProject/hpx/pull/2151>

⁴⁹⁹³ <https://github.com/TheHPXProject/hpx/issues/2150>

⁴⁹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/2149>

⁴⁹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2146>

⁴⁹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2145>

⁴⁹⁹⁷ <https://github.com/TheHPXProject/hpx/issues/2148>

⁴⁹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2144>

⁴⁹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/2143>

⁵⁰⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2142>

⁵⁰⁰¹ <https://github.com/TheHPXProject/hpx/pull/2141>

⁵⁰⁰² <https://github.com/TheHPXProject/hpx/pull/2139>

- PR #2138⁵⁰⁰³ - Revert “Adding fedora docs”
- PR #2136⁵⁰⁰⁴ - Removed double semicolon
- PR #2135⁵⁰⁰⁵ - Add deprecated #include check for hpx_fwd.hpp
- PR #2134⁵⁰⁰⁶ - Resolved memory leak in stencil_8
- PR #2133⁵⁰⁰⁷ - Replace uses of boost pointer containers
- PR #2132⁵⁰⁰⁸ - Removing unused typedef
- PR #2131⁵⁰⁰⁹ - Add several include checks for std facilities
- PR #2130⁵⁰¹⁰ - Fixing parcel compression, adding test
- PR #2129⁵⁰¹¹ - Fix invalid attribute warnings
- Issue #2128⁵⁰¹² - hpx::init seems to segfault
- PR #2127⁵⁰¹³ - Making executor_traits N-nary
- PR #2126⁵⁰¹⁴ - GCC 4.6 fails to deduce the correct type in lambda
- PR #2125⁵⁰¹⁵ - Making parcel coalescing test actually test something
- Issue #2124⁵⁰¹⁶ - Make a testcase for parcel compression
- Issue #2123⁵⁰¹⁷ - hpx/hpx/runtime/applier_fwd.hpp - Multiple defined types
- Issue #2122⁵⁰¹⁸ - Exception in primary_namespace::resolve_free_list
- Issue #2121⁵⁰¹⁹ - Possible memory leak in 1d_stencil_8
- PR #2120⁵⁰²⁰ - Fixing 2119
- Issue #2119⁵⁰²¹ - reduce_by_key compilation problems
- Issue #2118⁵⁰²² - Premature unwrapping of boost::ref'ed arguments
- PR #2117⁵⁰²³ - Added missing initializer on last constructor for thread_description
- PR #2116⁵⁰²⁴ - Use a lightweight bind implementation when no placeholders are given
- PR #2115⁵⁰²⁵ - Replace boost::shared_ptr with std::shared_ptr

⁵⁰⁰³ <https://github.com/TheHPXProject/hpx/pull/2138>
⁵⁰⁰⁴ <https://github.com/TheHPXProject/hpx/pull/2136>
⁵⁰⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2135>
⁵⁰⁰⁶ <https://github.com/TheHPXProject/hpx/pull/2134>
⁵⁰⁰⁷ <https://github.com/TheHPXProject/hpx/pull/2133>
⁵⁰⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2132>
⁵⁰⁰⁹ <https://github.com/TheHPXProject/hpx/pull/2131>
⁵⁰¹⁰ <https://github.com/TheHPXProject/hpx/pull/2130>
⁵⁰¹¹ <https://github.com/TheHPXProject/hpx/pull/2129>
⁵⁰¹² <https://github.com/TheHPXProject/hpx/issues/2128>
⁵⁰¹³ <https://github.com/TheHPXProject/hpx/pull/2127>
⁵⁰¹⁴ <https://github.com/TheHPXProject/hpx/pull/2126>
⁵⁰¹⁵ <https://github.com/TheHPXProject/hpx/pull/2125>
⁵⁰¹⁶ <https://github.com/TheHPXProject/hpx/issues/2124>
⁵⁰¹⁷ <https://github.com/TheHPXProject/hpx/issues/2123>
⁵⁰¹⁸ <https://github.com/TheHPXProject/hpx/issues/2122>
⁵⁰¹⁹ <https://github.com/TheHPXProject/hpx/issues/2121>
⁵⁰²⁰ <https://github.com/TheHPXProject/hpx/pull/2120>
⁵⁰²¹ <https://github.com/TheHPXProject/hpx/issues/2119>
⁵⁰²² <https://github.com/TheHPXProject/hpx/issues/2118>
⁵⁰²³ <https://github.com/TheHPXProject/hpx/pull/2117>
⁵⁰²⁴ <https://github.com/TheHPXProject/hpx/pull/2116>
⁵⁰²⁵ <https://github.com/TheHPXProject/hpx/pull/2115>

- PR #2114⁵⁰²⁶ - Adding hook functions for executor_parameter_traits supporting timers
- Issue #2113⁵⁰²⁷ - Compilation error with gcc version 4.9.3 (MacPorts gcc49 4.9.3_0)
- PR #2112⁵⁰²⁸ - Replace uses of safe_bool with explicit operator bool
- Issue #2111⁵⁰²⁹ - Compilation error on QT example
- Issue #2110⁵⁰³⁰ - Compilation error when passing non-future argument to unwrapped continuation in dataflow
- Issue #2109⁵⁰³¹ - Warning while compiling hpx
- Issue #2109⁵⁰³² - Stack trace of last bug causing issues with octotiger
- Issue #2108⁵⁰³³ - Stack trace of last bug causing issues with octotiger
- PR #2107⁵⁰³⁴ - Making sure that a missing parcel_coalescing module does not cause startup exceptions
- PR #2106⁵⁰³⁵ - Stop using hpx_fwd.hpp
- Issue #2105⁵⁰³⁶ - coalescing plugin handler is not optional any more
- Issue #2104⁵⁰³⁷ - Make executor_traits N-nary
- Issue #2103⁵⁰³⁸ - Build error with octotiger and hpx commit e657426d
- PR #2102⁵⁰³⁹ - Combining thread data storage
- PR #2101⁵⁰⁴⁰ - Added repartition version of 1d stencil that uses any performance counter
- PR #2100⁵⁰⁴¹ - Drop obsolete TR1 result_of protocol
- PR #2099⁵⁰⁴² - Replace uses of boost::bind with util::bind
- PR #2098⁵⁰⁴³ - Deprecated inspect checks
- PR #2097⁵⁰⁴⁴ - Reduce by key, extends #1141
- PR #2096⁵⁰⁴⁵ - Moving local cache from external to hpx/util
- PR #2095⁵⁰⁴⁶ - Bump minimum required Boost to 1.50.0
- PR #2094⁵⁰⁴⁷ - Add include checks for several Boost utilities
- Issue #2093⁵⁰⁴⁸ - ./.../local_cache.hpp(89): error #303: explicit type is missing (“int” assumed)

⁵⁰²⁶ <https://github.com/TheHPXProject/hpx/pull/2114>

⁵⁰²⁷ <https://github.com/TheHPXProject/hpx/issues/2113>

⁵⁰²⁸ <https://github.com/TheHPXProject/hpx/pull/2112>

⁵⁰²⁹ <https://github.com/TheHPXProject/hpx/issues/2111>

⁵⁰³⁰ <https://github.com/TheHPXProject/hpx/issues/2110>

⁵⁰³¹ <https://github.com/TheHPXProject/hpx/issues/2109>

⁵⁰³² <https://github.com/TheHPXProject/hpx/issues/2109>

⁵⁰³³ <https://github.com/TheHPXProject/hpx/issues/2108>

⁵⁰³⁴ <https://github.com/TheHPXProject/hpx/pull/2107>

⁵⁰³⁵ <https://github.com/TheHPXProject/hpx/pull/2106>

⁵⁰³⁶ <https://github.com/TheHPXProject/hpx/issues/2105>

⁵⁰³⁷ <https://github.com/TheHPXProject/hpx/issues/2104>

⁵⁰³⁸ <https://github.com/TheHPXProject/hpx/issues/2103>

⁵⁰³⁹ <https://github.com/TheHPXProject/hpx/pull/2102>

⁵⁰⁴⁰ <https://github.com/TheHPXProject/hpx/pull/2101>

⁵⁰⁴¹ <https://github.com/TheHPXProject/hpx/pull/2100>

⁵⁰⁴² <https://github.com/TheHPXProject/hpx/pull/2099>

⁵⁰⁴³ <https://github.com/TheHPXProject/hpx/pull/2098>

⁵⁰⁴⁴ <https://github.com/TheHPXProject/hpx/pull/2097>

⁵⁰⁴⁵ <https://github.com/TheHPXProject/hpx/pull/2096>

⁵⁰⁴⁶ <https://github.com/TheHPXProject/hpx/pull/2095>

⁵⁰⁴⁷ <https://github.com/TheHPXProject/hpx/pull/2094>

⁵⁰⁴⁸ <https://github.com/TheHPXProject/hpx/issues/2093>

- PR #2091⁵⁰⁴⁹ - Fix for Raspberry pi build
- PR #2090⁵⁰⁵⁰ - Fix storage size for util::function<>
- PR #2089⁵⁰⁵¹ - Fix #2088
- Issue #2088⁵⁰⁵² - More verbose output from cmake configuration
- PR #2087⁵⁰⁵³ - Making sure init_globally always executes hpx_main
- Issue #2086⁵⁰⁵⁴ - Race condition with recent HPX
- PR #2085⁵⁰⁵⁵ - Adding #include checker
- PR #2084⁵⁰⁵⁶ - Replace boost lock types with standard library ones
- PR #2083⁵⁰⁵⁷ - Simplify packaged task
- PR #2082⁵⁰⁵⁸ - Updating APEX version for testing
- PR #2081⁵⁰⁵⁹ - Cleanup exception headers
- PR #2080⁵⁰⁶⁰ - Make call_once variadic
- Issue #2079⁵⁰⁶¹ - With GNU C++, line 85 of hpx/config/version.hpp causes link failure when linking application
- Issue #2078⁵⁰⁶² - Simple test fails with _GLIBCXX_DEBUG defined
- PR #2077⁵⁰⁶³ - Instantiate board in nqueen client
- PR #2076⁵⁰⁶⁴ - Moving coalescing registration to TUs
- PR #2075⁵⁰⁶⁵ - Fixed some documentation typos
- PR #2074⁵⁰⁶⁶ - Adding flush-mode to message handler flush
- PR #2073⁵⁰⁶⁷ - Fixing performance regression introduced lately
- PR #2072⁵⁰⁶⁸ - Refactor local::condition_variable
- PR #2071⁵⁰⁶⁹ - Timer based on boost::asio::deadline_timer
- PR #2070⁵⁰⁷⁰ - Refactor tuple based functionality
- PR #2069⁵⁰⁷¹ - Fixed typos

⁵⁰⁴⁹ <https://github.com/TheHPXProject/hpx/pull/2091>
⁵⁰⁵⁰ <https://github.com/TheHPXProject/hpx/pull/2090>
⁵⁰⁵¹ <https://github.com/TheHPXProject/hpx/pull/2089>
⁵⁰⁵² <https://github.com/TheHPXProject/hpx/issues/2088>
⁵⁰⁵³ <https://github.com/TheHPXProject/hpx/pull/2087>
⁵⁰⁵⁴ <https://github.com/TheHPXProject/hpx/issues/2086>
⁵⁰⁵⁵ <https://github.com/TheHPXProject/hpx/pull/2085>
⁵⁰⁵⁶ <https://github.com/TheHPXProject/hpx/pull/2084>
⁵⁰⁵⁷ <https://github.com/TheHPXProject/hpx/pull/2083>
⁵⁰⁵⁸ <https://github.com/TheHPXProject/hpx/pull/2082>
⁵⁰⁵⁹ <https://github.com/TheHPXProject/hpx/pull/2081>
⁵⁰⁶⁰ <https://github.com/TheHPXProject/hpx/pull/2080>
⁵⁰⁶¹ <https://github.com/TheHPXProject/hpx/issues/2079>
⁵⁰⁶² <https://github.com/TheHPXProject/hpx/issues/2078>
⁵⁰⁶³ <https://github.com/TheHPXProject/hpx/pull/2077>
⁵⁰⁶⁴ <https://github.com/TheHPXProject/hpx/pull/2076>
⁵⁰⁶⁵ <https://github.com/TheHPXProject/hpx/pull/2075>
⁵⁰⁶⁶ <https://github.com/TheHPXProject/hpx/pull/2074>
⁵⁰⁶⁷ <https://github.com/TheHPXProject/hpx/pull/2073>
⁵⁰⁶⁸ <https://github.com/TheHPXProject/hpx/pull/2072>
⁵⁰⁶⁹ <https://github.com/TheHPXProject/hpx/pull/2071>
⁵⁰⁷⁰ <https://github.com/TheHPXProject/hpx/pull/2070>
⁵⁰⁷¹ <https://github.com/TheHPXProject/hpx/pull/2069>

- Issue #2068⁵⁰⁷² - Seg fault with octotiger
- PR #2067⁵⁰⁷³ - Algorithm cleanup
- PR #2066⁵⁰⁷⁴ - Split credit fixes
- PR #2065⁵⁰⁷⁵ - Rename HPX_MOVABLE_BUT_NOT_COPYABLE to HPX_MOVABLE_ONLY
- PR #2064⁵⁰⁷⁶ - Fixed some typos in docs
- PR #2063⁵⁰⁷⁷ - Adding example demonstrating template components
- Issue #2062⁵⁰⁷⁸ - Support component templates
- PR #2061⁵⁰⁷⁹ - Replace some uses of lexical_cast<string> with C++11 std::to_string
- PR #2060⁵⁰⁸⁰ - Replace uses of boost::noncopyable with HPX_NON_COPYABLE
- PR #2059⁵⁰⁸¹ - Adding missing for_loop algorithms
- PR #2058⁵⁰⁸² - Move several definitions to more appropriate headers
- PR #2057⁵⁰⁸³ - Simplify assert_owns_lock and ignore_while_checking
- PR #2056⁵⁰⁸⁴ - Replacing std::result_of with util::result_of
- PR #2055⁵⁰⁸⁵ - Fix process launching/connecting back
- PR #2054⁵⁰⁸⁶ - Add a forwarding coroutine header
- PR #2053⁵⁰⁸⁷ - Replace uses of boost::unordered_map with std::unordered_map
- PR #2052⁵⁰⁸⁸ - Rewrite tuple unwrap
- PR #2050⁵⁰⁸⁹ - Replace uses of BOOST_SCOPED_ENUM with C++11 scoped enums
- PR #2049⁵⁰⁹⁰ - Attempt to narrow down split_credit problem
- PR #2048⁵⁰⁹¹ - Fixing gcc startup hangs
- PR #2047⁵⁰⁹² - Fixing when_xxx and wait_xxx for MSVC12
- PR #2046⁵⁰⁹³ - adding persistent_auto_chunk_size and related tests for for_each
- PR #2045⁵⁰⁹⁴ - Fixing HPX_HAVE_THREAD_BACKTRACE_DEPTH build time configuration

⁵⁰⁷² <https://github.com/TheHPXProject/hpx/issues/2068>

⁵⁰⁷³ <https://github.com/TheHPXProject/hpx/pull/2067>

⁵⁰⁷⁴ <https://github.com/TheHPXProject/hpx/pull/2066>

⁵⁰⁷⁵ <https://github.com/TheHPXProject/hpx/pull/2065>

⁵⁰⁷⁶ <https://github.com/TheHPXProject/hpx/pull/2064>

⁵⁰⁷⁷ <https://github.com/TheHPXProject/hpx/pull/2063>

⁵⁰⁷⁸ <https://github.com/TheHPXProject/hpx/issues/2062>

⁵⁰⁷⁹ <https://github.com/TheHPXProject/hpx/pull/2061>

⁵⁰⁸⁰ <https://github.com/TheHPXProject/hpx/pull/2060>

⁵⁰⁸¹ <https://github.com/TheHPXProject/hpx/pull/2059>

⁵⁰⁸² <https://github.com/TheHPXProject/hpx/pull/2058>

⁵⁰⁸³ <https://github.com/TheHPXProject/hpx/pull/2057>

⁵⁰⁸⁴ <https://github.com/TheHPXProject/hpx/pull/2056>

⁵⁰⁸⁵ <https://github.com/TheHPXProject/hpx/pull/2055>

⁵⁰⁸⁶ <https://github.com/TheHPXProject/hpx/pull/2054>

⁵⁰⁸⁷ <https://github.com/TheHPXProject/hpx/pull/2053>

⁵⁰⁸⁸ <https://github.com/TheHPXProject/hpx/pull/2052>

⁵⁰⁸⁹ <https://github.com/TheHPXProject/hpx/pull/2050>

⁵⁰⁹⁰ <https://github.com/TheHPXProject/hpx/pull/2049>

⁵⁰⁹¹ <https://github.com/TheHPXProject/hpx/pull/2048>

⁵⁰⁹² <https://github.com/TheHPXProject/hpx/pull/2047>

⁵⁰⁹³ <https://github.com/TheHPXProject/hpx/pull/2046>

⁵⁰⁹⁴ <https://github.com/TheHPXProject/hpx/pull/2045>

- PR #2044⁵⁰⁹⁵ - Adding missing service executor types
- PR #2043⁵⁰⁹⁶ - Removing ambiguous definitions for `is_future_range` and `future_range_traits`
- PR #2042⁵⁰⁹⁷ - Clarify that HPX builds can use (much) more than 2GB per process
- PR #2041⁵⁰⁹⁸ - Changing `future_iterator_traits` to support pointers
- Issue #2040⁵⁰⁹⁹ - Improve documentation memory usage warning?
- PR #2039⁵¹⁰⁰ - Coroutine cleanup
- PR #2038⁵¹⁰¹ - Fix cmake policy CMP0042 warning MACOSX_RPATH
- PR #2037⁵¹⁰² - Avoid redundant specialization of `[unique_]function_nonser`
- PR #2036⁵¹⁰³ - nvcc dies with an internal error upon pushing/popping warnings inside templates
- Issue #2035⁵¹⁰⁴ - Use a less restrictive iterator definition in `hpx::lcos::detail::future_iterator_traits`
- PR #2034⁵¹⁰⁵ - Fixing compilation error with thread queue wait time performance counter
- Issue #2033⁵¹⁰⁶ - Compilation error when compiling with thread queue waittime performance counter
- Issue #2032⁵¹⁰⁷ - Ambiguous template instantiation for `is_future_range` and `future_range_traits`.
- PR #2031⁵¹⁰⁸ - Don't restart timer on every incoming parcel
- PR #2030⁵¹⁰⁹ - Unify handling of execution policies in parallel algorithms
- PR #2029⁵¹¹⁰ - Make pkg-config .pc files use .dylib on OSX
- PR #2028⁵¹¹¹ - Adding process component
- PR #2027⁵¹¹² - Making check for compiler compatibility independent on compiler path
- PR #2025⁵¹¹³ - Fixing inspect tool
- PR #2024⁵¹¹⁴ - Intel13 removal
- PR #2023⁵¹¹⁵ - Fix errors related to older boost versions and parameter pack expansions in lambdas
- Issue #2022⁵¹¹⁶ - gmake fail: "No rule to make target /usr/lib46/libboost_context-mt.so"
- PR #2021⁵¹¹⁷ - Added Sudoku example

⁵⁰⁹⁵ <https://github.com/TheHPXProject/hpx/pull/2044>

⁵⁰⁹⁶ <https://github.com/TheHPXProject/hpx/pull/2043>

⁵⁰⁹⁷ <https://github.com/TheHPXProject/hpx/pull/2042>

⁵⁰⁹⁸ <https://github.com/TheHPXProject/hpx/pull/2041>

⁵⁰⁹⁹ <https://github.com/TheHPXProject/hpx/issues/2040>

⁵¹⁰⁰ <https://github.com/TheHPXProject/hpx/pull/2039>

⁵¹⁰¹ <https://github.com/TheHPXProject/hpx/pull/2038>

⁵¹⁰² <https://github.com/TheHPXProject/hpx/pull/2037>

⁵¹⁰³ <https://github.com/TheHPXProject/hpx/pull/2036>

⁵¹⁰⁴ <https://github.com/TheHPXProject/hpx/issues/2035>

⁵¹⁰⁵ <https://github.com/TheHPXProject/hpx/pull/2034>

⁵¹⁰⁶ <https://github.com/TheHPXProject/hpx/issues/2033>

⁵¹⁰⁷ <https://github.com/TheHPXProject/hpx/issues/2032>

⁵¹⁰⁸ <https://github.com/TheHPXProject/hpx/pull/2031>

⁵¹⁰⁹ <https://github.com/TheHPXProject/hpx/pull/2030>

⁵¹¹⁰ <https://github.com/TheHPXProject/hpx/pull/2029>

⁵¹¹¹ <https://github.com/TheHPXProject/hpx/pull/2028>

⁵¹¹² <https://github.com/TheHPXProject/hpx/pull/2027>

⁵¹¹³ <https://github.com/TheHPXProject/hpx/pull/2025>

⁵¹¹⁴ <https://github.com/TheHPXProject/hpx/pull/2024>

⁵¹¹⁵ <https://github.com/TheHPXProject/hpx/pull/2023>

⁵¹¹⁶ <https://github.com/TheHPXProject/hpx/issues/2022>

⁵¹¹⁷ <https://github.com/TheHPXProject/hpx/pull/2021>

- [Issue #2020⁵¹¹⁸](#) - Make errors related to `init_globally.cpp` example while building HPX out of the box
- [PR #2019⁵¹¹⁹](#) - Fixed some compilation and cmake errors encountered in `nqueen` example
- [PR #2018⁵¹²⁰](#) - For loop algorithms
- [PR #2017⁵¹²¹](#) - Non-recursive `at_index` implementation
- [Issue #2016⁵¹²²](#) - Add index-based for-loops
- [Issue #2015⁵¹²³](#) - Change default bind-mode to balanced
- [PR #2014⁵¹²⁴](#) - Fixed dataflow if invoked action returns a future
- [PR #2013⁵¹²⁵](#) - Fixing compilation issues with external example
- [PR #2012⁵¹²⁶](#) - Added Sierpinski Triangle example
- [Issue #2011⁵¹²⁷](#) - Compilation error while running sample `hello_world_component` code
- [PR #2010⁵¹²⁸](#) - Segmented move implemented for `hpx::vector`
- [Issue #2009⁵¹²⁹](#) - pkg-config order incorrect on 14.04 / GCC 4.8
- [Issue #2008⁵¹³⁰](#) - Compilation error in dataflow of action returning a future
- [PR #2007⁵¹³¹](#) - Adding new performance counter exposing overall scheduler time
- [PR #2006⁵¹³²](#) - Function includes
- [PR #2005⁵¹³³](#) - Adding an example demonstrating how to initialize HPX from a global object
- [PR #2004⁵¹³⁴](#) - Fixing 2000
- [PR #2003⁵¹³⁵](#) - Adding generation parameter to `gather` to enable using it more than once
- [PR #2002⁵¹³⁶](#) - Turn on position independent code to solve link problem with `hpx_init`
- [Issue #2001⁵¹³⁷](#) - Gathering more than once segfaults
- [Issue #2000⁵¹³⁸](#) - Undefined reference to `hpx::assertion_failed`
- [Issue #1999⁵¹³⁹](#) - Seg fault in `hpx::lcos::base_lco_with_value<*>::set_value_nonvirt()` when running octo-tiger
- [PR #1998⁵¹⁴⁰](#) - Detect unknown command line options

⁵¹¹⁸ <https://github.com/TheHPXProject/hpx/issues/2020>

⁵¹¹⁹ <https://github.com/TheHPXProject/hpx/pull/2019>

⁵¹²⁰ <https://github.com/TheHPXProject/hpx/pull/2018>

⁵¹²¹ <https://github.com/TheHPXProject/hpx/pull/2017>

⁵¹²² <https://github.com/TheHPXProject/hpx/issues/2016>

⁵¹²³ <https://github.com/TheHPXProject/hpx/issues/2015>

⁵¹²⁴ <https://github.com/TheHPXProject/hpx/pull/2014>

⁵¹²⁵ <https://github.com/TheHPXProject/hpx/pull/2013>

⁵¹²⁶ <https://github.com/TheHPXProject/hpx/pull/2012>

⁵¹²⁷ <https://github.com/TheHPXProject/hpx/issues/2011>

⁵¹²⁸ <https://github.com/TheHPXProject/hpx/pull/2010>

⁵¹²⁹ <https://github.com/TheHPXProject/hpx/issues/2009>

⁵¹³⁰ <https://github.com/TheHPXProject/hpx/issues/2008>

⁵¹³¹ <https://github.com/TheHPXProject/hpx/pull/2007>

⁵¹³² <https://github.com/TheHPXProject/hpx/pull/2006>

⁵¹³³ <https://github.com/TheHPXProject/hpx/pull/2005>

⁵¹³⁴ <https://github.com/TheHPXProject/hpx/pull/2004>

⁵¹³⁵ <https://github.com/TheHPXProject/hpx/pull/2003>

⁵¹³⁶ <https://github.com/TheHPXProject/hpx/pull/2002>

⁵¹³⁷ <https://github.com/TheHPXProject/hpx/issues/2001>

⁵¹³⁸ <https://github.com/TheHPXProject/hpx/issues/2000>

⁵¹³⁹ <https://github.com/TheHPXProject/hpx/issues/1999>

⁵¹⁴⁰ <https://github.com/TheHPXProject/hpx/pull/1998>

- PR #1997⁵¹⁴¹ - Extending thread description
- PR #1996⁵¹⁴² - Adding natvis files to solution (MSVC only)
- Issue #1995⁵¹⁴³ - Command line handling does not produce error
- PR #1994⁵¹⁴⁴ - Possible missing include in test_utils.hpp
- PR #1993⁵¹⁴⁵ - Add missing LANGUAGES tag to a hpx_add_compile_flag_if_available() call in CMakeLists.txt
- PR #1992⁵¹⁴⁶ - Fixing shared_executor_test
- PR #1991⁵¹⁴⁷ - Making sure the winsock library is properly initialized
- PR #1990⁵¹⁴⁸ - Fixing bind_test placeholder ambiguity coming from boost-1.60
- PR #1989⁵¹⁴⁹ - Performance tuning
- PR #1987⁵¹⁵⁰ - Make configurable size of internal storage in util::function
- PR #1986⁵¹⁵¹ - AGAS Refactoring+1753 Cache mods
- PR #1985⁵¹⁵² - Adding missing task_block::run() overload taking an executor
- PR #1984⁵¹⁵³ - Adding an optimized LRU Cache implementation (for AGAS)
- PR #1983⁵¹⁵⁴ - Avoid invoking migration table look up for all objects
- PR #1981⁵¹⁵⁵ - Replacing uintptr_t (which is not defined everywhere) with std::size_t
- PR #1980⁵¹⁵⁶ - Optimizing LCO continuations
- PR #1979⁵¹⁵⁷ - Fixing Cori
- PR #1978⁵¹⁵⁸ - Fix test check that got broken in hasty fix to memory overflow
- PR #1977⁵¹⁵⁹ - Refactor action traits
- PR #1976⁵¹⁶⁰ - Fixes typo in README.rst
- PR #1975⁵¹⁶¹ - Reduce size of benchmark timing arrays to fix test failures
- PR #1974⁵¹⁶² - Add action to update data owned by the partitioned_vector component
- PR #1972⁵¹⁶³ - Adding partitioned_vector SPMD example

⁵¹⁴¹ <https://github.com/TheHPXProject/hpx/pull/1997>

⁵¹⁴² <https://github.com/TheHPXProject/hpx/pull/1996>

⁵¹⁴³ <https://github.com/TheHPXProject/hpx/issues/1995>

⁵¹⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1994>

⁵¹⁴⁵ <https://github.com/TheHPXProject/hpx/pull/1993>

⁵¹⁴⁶ <https://github.com/TheHPXProject/hpx/pull/1992>

⁵¹⁴⁷ <https://github.com/TheHPXProject/hpx/pull/1991>

⁵¹⁴⁸ <https://github.com/TheHPXProject/hpx/pull/1990>

⁵¹⁴⁹ <https://github.com/TheHPXProject/hpx/pull/1989>

⁵¹⁵⁰ <https://github.com/TheHPXProject/hpx/pull/1987>

⁵¹⁵¹ <https://github.com/TheHPXProject/hpx/pull/1986>

⁵¹⁵² <https://github.com/TheHPXProject/hpx/pull/1985>

⁵¹⁵³ <https://github.com/TheHPXProject/hpx/pull/1984>

⁵¹⁵⁴ <https://github.com/TheHPXProject/hpx/pull/1983>

⁵¹⁵⁵ <https://github.com/TheHPXProject/hpx/pull/1981>

⁵¹⁵⁶ <https://github.com/TheHPXProject/hpx/pull/1980>

⁵¹⁵⁷ <https://github.com/TheHPXProject/hpx/pull/1979>

⁵¹⁵⁸ <https://github.com/TheHPXProject/hpx/pull/1978>

⁵¹⁵⁹ <https://github.com/TheHPXProject/hpx/pull/1977>

⁵¹⁶⁰ <https://github.com/TheHPXProject/hpx/pull/1976>

⁵¹⁶¹ <https://github.com/TheHPXProject/hpx/pull/1975>

⁵¹⁶² <https://github.com/TheHPXProject/hpx/pull/1974>

⁵¹⁶³ <https://github.com/TheHPXProject/hpx/pull/1972>

- PR #1971⁵¹⁶⁴ - Fixing 1965
- PR #1970⁵¹⁶⁵ - Papi fixes
- PR #1969⁵¹⁶⁶ - Fixing continuation recursions to not depend on fixed amount of recursions
- PR #1968⁵¹⁶⁷ - More segmented algorithms
- Issue #1967⁵¹⁶⁸ - Simplify component implementations
- PR #1966⁵¹⁶⁹ - Migrate components
- Issue #1964⁵¹⁷⁰ - fatal error: 'boost/lockfree/detail/branch_hints.hpp' file not found
- Issue #1962⁵¹⁷¹ - parallel::copy_if has race condition when used on in place arrays
- PR #1963⁵¹⁷² - Fixing Static Parcelport initialization
- PR #1961⁵¹⁷³ - Fix function target
- Issue #1960⁵¹⁷⁴ - Papi counters don't reset
- PR #1959⁵¹⁷⁵ - Fixing 1958
- Issue #1958⁵¹⁷⁶ - inclusive_scan gives incorrect results with non-commutative operator
- PR #1957⁵¹⁷⁷ - Fixing #1950
- PR #1956⁵¹⁷⁸ - Sort by key example
- PR #1955⁵¹⁷⁹ - Adding regression test for #1946: Hang in wait_all() in distributed run
- Issue #1954⁵¹⁸⁰ - HPX releases should not use -Werror
- PR #1953⁵¹⁸¹ - Adding performance analysis for AGAS cache
- PR #1952⁵¹⁸² - Adapting test for explicit variadics to fail for gcc 4.6
- PR #1951⁵¹⁸³ - Fixing memory leak
- Issue #1950⁵¹⁸⁴ - Simplify external builds
- PR #1949⁵¹⁸⁵ - Fixing yet another lock that is being held during suspension
- PR #1948⁵¹⁸⁶ - Fixed container algorithms for Intel

⁵¹⁶⁴ <https://github.com/TheHPXProject/hpx/pull/1971>

⁵¹⁶⁵ <https://github.com/TheHPXProject/hpx/pull/1970>

⁵¹⁶⁶ <https://github.com/TheHPXProject/hpx/pull/1969>

⁵¹⁶⁷ <https://github.com/TheHPXProject/hpx/pull/1968>

⁵¹⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1967>

⁵¹⁶⁹ <https://github.com/TheHPXProject/hpx/pull/1966>

⁵¹⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1964>

⁵¹⁷¹ <https://github.com/TheHPXProject/hpx/issues/1962>

⁵¹⁷² <https://github.com/TheHPXProject/hpx/pull/1963>

⁵¹⁷³ <https://github.com/TheHPXProject/hpx/pull/1961>

⁵¹⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1960>

⁵¹⁷⁵ <https://github.com/TheHPXProject/hpx/pull/1959>

⁵¹⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1958>

⁵¹⁷⁷ <https://github.com/TheHPXProject/hpx/pull/1957>

⁵¹⁷⁸ <https://github.com/TheHPXProject/hpx/pull/1956>

⁵¹⁷⁹ <https://github.com/TheHPXProject/hpx/pull/1955>

⁵¹⁸⁰ <https://github.com/TheHPXProject/hpx/issues/1954>

⁵¹⁸¹ <https://github.com/TheHPXProject/hpx/pull/1953>

⁵¹⁸² <https://github.com/TheHPXProject/hpx/pull/1952>

⁵¹⁸³ <https://github.com/TheHPXProject/hpx/pull/1951>

⁵¹⁸⁴ <https://github.com/TheHPXProject/hpx/issues/1950>

⁵¹⁸⁵ <https://github.com/TheHPXProject/hpx/pull/1949>

⁵¹⁸⁶ <https://github.com/TheHPXProject/hpx/pull/1948>

- [PR #1947⁵¹⁸⁷](#) - Adding workaround for tagged_tuple
- [Issue #1946⁵¹⁸⁸](#) - Hang in wait_all() in distributed run
- [PR #1945⁵¹⁸⁹](#) - Fixed container algorithm tests
- [Issue #1944⁵¹⁹⁰](#) - assertion 'p.destination_locality() == hpx::get_locality()' failed
- [PR #1943⁵¹⁹¹](#) - Fix a couple of compile errors with clang
- [PR #1942⁵¹⁹²](#) - Making parcel coalescing functional
- [Issue #1941⁵¹⁹³](#) - Re-enable parcel coalescing
- [PR #1940⁵¹⁹⁴](#) - Touching up make_future
- [PR #1939⁵¹⁹⁵](#) - Fixing problems in over-subscription management in the resource manager
- [PR #1938⁵¹⁹⁶](#) - Removing use of unified Boost.Thread header
- [PR #1937⁵¹⁹⁷](#) - Cleaning up the use of Boost.Accumulator headers
- [PR #1936⁵¹⁹⁸](#) - Making sure interval timer is started for aggregating performance counters
- [PR #1935⁵¹⁹⁹](#) - Tagged results
- [PR #1934⁵²⁰⁰](#) - Fix remote async with deferred launch policy
- [Issue #1933⁵²⁰¹](#) - Floating point exception in statistics_counter<boost::accumulators::tag::mean>::get_counter_v
- [PR #1932⁵²⁰²](#) - Removing superfluous includes of boost/lockfree/detail/branch_hints.hpp
- [PR #1931⁵²⁰³](#) - fix compilation with clang 3.8.0
- [Issue #1930⁵²⁰⁴](#) - Missing online documentation for HPX 0.9.11
- [PR #1929⁵²⁰⁵](#) - LWG2485: get() should be overloaded for const tuple&&
- [PR #1928⁵²⁰⁶](#) - Revert "Using ninja for circle-ci builds"
- [PR #1927⁵²⁰⁷](#) - Using ninja for circle-ci builds
- [PR #1926⁵²⁰⁸](#) - Fixing serialization of std::array
- [Issue #1925⁵²⁰⁹](#) - Issues with static HPX libraries

⁵¹⁸⁷ <https://github.com/TheHPXProject/hpx/pull/1947>
⁵¹⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1946>
⁵¹⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1945>
⁵¹⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1944>
⁵¹⁹¹ <https://github.com/TheHPXProject/hpx/pull/1943>
⁵¹⁹² <https://github.com/TheHPXProject/hpx/pull/1942>
⁵¹⁹³ <https://github.com/TheHPXProject/hpx/issues/1941>
⁵¹⁹⁴ <https://github.com/TheHPXProject/hpx/pull/1940>
⁵¹⁹⁵ <https://github.com/TheHPXProject/hpx/pull/1939>
⁵¹⁹⁶ <https://github.com/TheHPXProject/hpx/pull/1938>
⁵¹⁹⁷ <https://github.com/TheHPXProject/hpx/pull/1937>
⁵¹⁹⁸ <https://github.com/TheHPXProject/hpx/pull/1936>
⁵¹⁹⁹ <https://github.com/TheHPXProject/hpx/pull/1935>
⁵²⁰⁰ <https://github.com/TheHPXProject/hpx/pull/1934>
⁵²⁰¹ <https://github.com/TheHPXProject/hpx/issues/1933>
⁵²⁰² <https://github.com/TheHPXProject/hpx/pull/1932>
⁵²⁰³ <https://github.com/TheHPXProject/hpx/pull/1931>
⁵²⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1930>
⁵²⁰⁵ <https://github.com/TheHPXProject/hpx/pull/1929>
⁵²⁰⁶ <https://github.com/TheHPXProject/hpx/pull/1928>
⁵²⁰⁷ <https://github.com/TheHPXProject/hpx/pull/1927>
⁵²⁰⁸ <https://github.com/TheHPXProject/hpx/pull/1926>
⁵²⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1925>

- Issue #1924⁵²¹⁰ - Performance degrading over time
- Issue #1923⁵²¹¹ - serialization of std::array appears broken in latest commit
- PR #1922⁵²¹² - Container algorithms
- PR #1921⁵²¹³ - Tons of smaller quality improvements
- Issue #1920⁵²¹⁴ - Seg fault in hpx::serialization::output_archive::add_gid when running octotiger
- Issue #1919⁵²¹⁵ - Intel 15 compiler bug preventing HPX build
- PR #1918⁵²¹⁶ - Address sanitizer fixes
- PR #1917⁵²¹⁷ - Fixing compilation problems of parallel::sort with Intel compilers
- PR #1916⁵²¹⁸ - Making sure code compiles if HPX_WITH_HWLOC=Off
- Issue #1915⁵²¹⁹ - max_cores undefined if HPX_WITH_HWLOC=Off
- PR #1913⁵²²⁰ - Add utility member functions for partitioned_vector
- PR #1912⁵²²¹ - Adding support for invoking actions to dataflow
- PR #1911⁵²²² - Adding first batch of container algorithms
- PR #1910⁵²²³ - Keep cmake_module_path
- PR #1909⁵²²⁴ - Fix mpirun with pbs
- PR #1908⁵²²⁵ - Changing parallel::sort to return the last iterator as proposed by N4560
- PR #1907⁵²²⁶ - Adding a minimum version for Open MPI
- PR #1906⁵²²⁷ - Updates to the Release Procedure
- PR #1905⁵²²⁸ - Fixing #1903
- PR #1904⁵²²⁹ - Making sure std containers are cleared before serialization loads data
- Issue #1903⁵²³⁰ - When running octotiger, I get: assertion '(*new_gids_)[gid].size() == 1' failed: HPX(assertion_failure)
- Issue #1902⁵²³¹ - Immediate crash when running hpx/octotiger with _GLIBCXX_DEBUG defined.
- PR #1901⁵²³² - Making non-serializable classes non-serializable

⁵²¹⁰ <https://github.com/TheHPXProject/hpx/issues/1924>

⁵²¹¹ <https://github.com/TheHPXProject/hpx/issues/1923>

⁵²¹² <https://github.com/TheHPXProject/hpx/pull/1922>

⁵²¹³ <https://github.com/TheHPXProject/hpx/pull/1921>

⁵²¹⁴ <https://github.com/TheHPXProject/hpx/issues/1920>

⁵²¹⁵ <https://github.com/TheHPXProject/hpx/issues/1919>

⁵²¹⁶ <https://github.com/TheHPXProject/hpx/pull/1918>

⁵²¹⁷ <https://github.com/TheHPXProject/hpx/pull/1917>

⁵²¹⁸ <https://github.com/TheHPXProject/hpx/pull/1916>

⁵²¹⁹ <https://github.com/TheHPXProject/hpx/issues/1915>

⁵²²⁰ <https://github.com/TheHPXProject/hpx/pull/1913>

⁵²²¹ <https://github.com/TheHPXProject/hpx/pull/1912>

⁵²²² <https://github.com/TheHPXProject/hpx/pull/1911>

⁵²²³ <https://github.com/TheHPXProject/hpx/pull/1910>

⁵²²⁴ <https://github.com/TheHPXProject/hpx/pull/1909>

⁵²²⁵ <https://github.com/TheHPXProject/hpx/pull/1908>

⁵²²⁶ <https://github.com/TheHPXProject/hpx/pull/1907>

⁵²²⁷ <https://github.com/TheHPXProject/hpx/pull/1906>

⁵²²⁸ <https://github.com/TheHPXProject/hpx/pull/1905>

⁵²²⁹ <https://github.com/TheHPXProject/hpx/pull/1904>

⁵²³⁰ <https://github.com/TheHPXProject/hpx/issues/1903>

⁵²³¹ <https://github.com/TheHPXProject/hpx/issues/1902>

⁵²³² <https://github.com/TheHPXProject/hpx/pull/1901>

- [Issue #1900](#)⁵²³³ - Two possible issues with `std::list` serialization
- [PR #1899](#)⁵²³⁴ - Fixing a problem with credit splitting as revealed by #1898
- [Issue #1898](#)⁵²³⁵ - Accessing component from locality where it was not created segfaults
- [PR #1897](#)⁵²³⁶ - Changing `parallel::sort` to return the last iterator as proposed by N4560
- [Issue #1896](#)⁵²³⁷ - version 1.0?
- [Issue #1895](#)⁵²³⁸ - Warning comment on `numa_allocator` is not very clear
- [PR #1894](#)⁵²³⁹ - Add support for compilers that have `thread_local`
- [PR #1893](#)⁵²⁴⁰ - Fixing 1890
- [PR #1892](#)⁵²⁴¹ - Adds typed `future_type` for `executor_traits`
- [PR #1891](#)⁵²⁴² - Fix wording in certain parallel algorithm docs
- [Issue #1890](#)⁵²⁴³ - Invoking papi counters give segfault
- [PR #1889](#)⁵²⁴⁴ - Fixing problems as reported by clang-check
- [PR #1888](#)⁵²⁴⁵ - WIP parallel `is_heap`
- [PR #1887](#)⁵²⁴⁶ - Fixed resetting performance counters related to idle-rate, etc
- [Issue #1886](#)⁵²⁴⁷ - Run hpx with `qsub` does not work
- [PR #1885](#)⁵²⁴⁸ - Warning cleaning pass
- [PR #1884](#)⁵²⁴⁹ - Add missing parallel algorithm header
- [PR #1883](#)⁵²⁵⁰ - Add feature test for `thread_local` on Clang for TLS
- [PR #1882](#)⁵²⁵¹ - Fix some redundant qualifiers
- [Issue #1881](#)⁵²⁵² - Unable to compile Octotiger using HPX and Intel MPI on SuperMIC
- [Issue #1880](#)⁵²⁵³ - clang with `libc++` on Linux needs TLS case
- [PR #1879](#)⁵²⁵⁴ - Doc fixes for #1868
- [PR #1878](#)⁵²⁵⁵ - Simplify functions

⁵²³³ <https://github.com/TheHPXProject/hpx/issues/1900>

⁵²³⁴ <https://github.com/TheHPXProject/hpx/pull/1899>

⁵²³⁵ <https://github.com/TheHPXProject/hpx/issues/1898>

⁵²³⁶ <https://github.com/TheHPXProject/hpx/pull/1897>

⁵²³⁷ <https://github.com/TheHPXProject/hpx/issues/1896>

⁵²³⁸ <https://github.com/TheHPXProject/hpx/issues/1895>

⁵²³⁹ <https://github.com/TheHPXProject/hpx/pull/1894>

⁵²⁴⁰ <https://github.com/TheHPXProject/hpx/pull/1893>

⁵²⁴¹ <https://github.com/TheHPXProject/hpx/pull/1892>

⁵²⁴² <https://github.com/TheHPXProject/hpx/pull/1891>

⁵²⁴³ <https://github.com/TheHPXProject/hpx/issues/1890>

⁵²⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1889>

⁵²⁴⁵ <https://github.com/TheHPXProject/hpx/pull/1888>

⁵²⁴⁶ <https://github.com/TheHPXProject/hpx/pull/1887>

⁵²⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1886>

⁵²⁴⁸ <https://github.com/TheHPXProject/hpx/pull/1885>

⁵²⁴⁹ <https://github.com/TheHPXProject/hpx/pull/1884>

⁵²⁵⁰ <https://github.com/TheHPXProject/hpx/pull/1883>

⁵²⁵¹ <https://github.com/TheHPXProject/hpx/pull/1882>

⁵²⁵² <https://github.com/TheHPXProject/hpx/issues/1881>

⁵²⁵³ <https://github.com/TheHPXProject/hpx/issues/1880>

⁵²⁵⁴ <https://github.com/TheHPXProject/hpx/pull/1879>

⁵²⁵⁵ <https://github.com/TheHPXProject/hpx/pull/1878>

- PR #1877⁵²⁵⁶ - Removing most usage of Boost.Config
- PR #1876⁵²⁵⁷ - Add missing parallel algorithms to algorithm.hpp
- PR #1875⁵²⁵⁸ - Simplify callables
- PR #1874⁵²⁵⁹ - Address long standing FIXME on using `std::unique_ptr` with incomplete types
- PR #1873⁵²⁶⁰ - Fixing 1871
- PR #1872⁵²⁶¹ - Making sure PBS environment uses specified node list even if no PBS_NODEFILE env is available
- Issue #1871⁵²⁶² - Fortran checks should be optional
- PR #1870⁵²⁶³ - Touch local::mutex
- PR #1869⁵²⁶⁴ - Documentation refactoring based off #1868
- PR #1867⁵²⁶⁵ - Embrace static_assert
- PR #1866⁵²⁶⁶ - Fix #1803 with documentation refactoring
- PR #1865⁵²⁶⁷ - Setting OUTPUT_NAME as target properties
- PR #1863⁵²⁶⁸ - Use SYSTEM for boost includes
- PR #1862⁵²⁶⁹ - Minor cleanups
- PR #1861⁵²⁷⁰ - Minor Corrections for Release
- PR #1860⁵²⁷¹ - Fixing hpx gdb script
- Issue #1859⁵²⁷² - reset_active_counters resets times and thread counts before some of the counters are evaluated
- PR #1858⁵²⁷³ - Release V0.9.11
- PR #1857⁵²⁷⁴ - removing diskperf example from 9.11 release
- PR #1856⁵²⁷⁵ - fix return in packaged_task_base::reset()
- Issue #1842⁵²⁷⁶ - Install error: file INSTALL cannot find libhpx_parcel_coalescing.so.0.9.11
- PR #1839⁵²⁷⁷ - Adding fedora docs
- PR #1824⁵²⁷⁸ - Changing version on master to V0.9.12

⁵²⁵⁶ <https://github.com/TheHPXProject/hpx/pull/1877>
⁵²⁵⁷ <https://github.com/TheHPXProject/hpx/pull/1876>
⁵²⁵⁸ <https://github.com/TheHPXProject/hpx/pull/1875>
⁵²⁵⁹ <https://github.com/TheHPXProject/hpx/pull/1874>
⁵²⁶⁰ <https://github.com/TheHPXProject/hpx/pull/1873>
⁵²⁶¹ <https://github.com/TheHPXProject/hpx/pull/1872>
⁵²⁶² <https://github.com/TheHPXProject/hpx/issues/1871>
⁵²⁶³ <https://github.com/TheHPXProject/hpx/pull/1870>
⁵²⁶⁴ <https://github.com/TheHPXProject/hpx/pull/1869>
⁵²⁶⁵ <https://github.com/TheHPXProject/hpx/pull/1867>
⁵²⁶⁶ <https://github.com/TheHPXProject/hpx/pull/1866>
⁵²⁶⁷ <https://github.com/TheHPXProject/hpx/pull/1865>
⁵²⁶⁸ <https://github.com/TheHPXProject/hpx/pull/1863>
⁵²⁶⁹ <https://github.com/TheHPXProject/hpx/pull/1862>
⁵²⁷⁰ <https://github.com/TheHPXProject/hpx/pull/1861>
⁵²⁷¹ <https://github.com/TheHPXProject/hpx/pull/1860>
⁵²⁷² <https://github.com/TheHPXProject/hpx/issues/1859>
⁵²⁷³ <https://github.com/TheHPXProject/hpx/pull/1858>
⁵²⁷⁴ <https://github.com/TheHPXProject/hpx/pull/1857>
⁵²⁷⁵ <https://github.com/TheHPXProject/hpx/pull/1856>
⁵²⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1842>
⁵²⁷⁷ <https://github.com/TheHPXProject/hpx/pull/1839>
⁵²⁷⁸ <https://github.com/TheHPXProject/hpx/pull/1824>

- PR #1818⁵²⁷⁹ - Fixing #1748
- Issue #1815⁵²⁸⁰ - seg fault in AGAS
- Issue #1803⁵²⁸¹ - wait_all documentation
- Issue #1796⁵²⁸² - Outdated documentation to be revised
- Issue #1759⁵²⁸³ - glibc munmap_chunk or free(): invalid pointer on SuperMIC
- Issue #1753⁵²⁸⁴ - HPX performance degrades with time since execution begins
- Issue #1748⁵²⁸⁵ - All public HPX headers need to be self contained
- PR #1719⁵²⁸⁶ - How to build HPX with Visual Studio
- Issue #1684⁵²⁸⁷ - Race condition when using -hpx:connect?
- PR #1658⁵²⁸⁸ - Add serialization for std::set (as there is for std::vector and std::map)
- PR #1641⁵²⁸⁹ - Generic client
- Issue #1632⁵²⁹⁰ - heartbeat example fails on separate nodes
- PR #1603⁵²⁹¹ - Adds preferred namespace check to inspect tool
- Issue #1559⁵²⁹² - Extend inspect tool
- Issue #1523⁵²⁹³ - Remote async with deferred launch policy never executes
- Issue #1472⁵²⁹⁴ - Serialization issues
- Issue #1457⁵²⁹⁵ - Implement N4392: C++ Latches and Barriers
- PR #1444⁵²⁹⁶ - Enabling usage of moveonly types for component construction
- Issue #1407⁵²⁹⁷ - The Intel 13 compiler has failing unit tests
- Issue #1405⁵²⁹⁸ - Allow component constructors to take movable only types
- Issue #1265⁵²⁹⁹ - Enable dataflow() to be usable with actions
- Issue #1236⁵³⁰⁰ - NUMA aware allocators
- Issue #802⁵³⁰¹ - Fix Broken Examples

⁵²⁷⁹ <https://github.com/TheHPXProject/hpx/pull/1818>

⁵²⁸⁰ <https://github.com/TheHPXProject/hpx/issues/1815>

⁵²⁸¹ <https://github.com/TheHPXProject/hpx/issues/1803>

⁵²⁸² <https://github.com/TheHPXProject/hpx/issues/1796>

⁵²⁸³ <https://github.com/TheHPXProject/hpx/issues/1759>

⁵²⁸⁴ <https://github.com/TheHPXProject/hpx/issues/1753>

⁵²⁸⁵ <https://github.com/TheHPXProject/hpx/issues/1748>

⁵²⁸⁶ <https://github.com/TheHPXProject/hpx/pull/1719>

⁵²⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1684>

⁵²⁸⁸ <https://github.com/TheHPXProject/hpx/pull/1658>

⁵²⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1641>

⁵²⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1632>

⁵²⁹¹ <https://github.com/TheHPXProject/hpx/pull/1603>

⁵²⁹² <https://github.com/TheHPXProject/hpx/issues/1559>

⁵²⁹³ <https://github.com/TheHPXProject/hpx/issues/1523>

⁵²⁹⁴ <https://github.com/TheHPXProject/hpx/issues/1472>

⁵²⁹⁵ <https://github.com/TheHPXProject/hpx/issues/1457>

⁵²⁹⁶ <https://github.com/TheHPXProject/hpx/pull/1444>

⁵²⁹⁷ <https://github.com/TheHPXProject/hpx/issues/1407>

⁵²⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1405>

⁵²⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1265>

⁵³⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1236>

⁵³⁰¹ <https://github.com/TheHPXProject/hpx/issues/802>

- [Issue #559](#)⁵³⁰² - Add `hpx::migrate` facility
- [Issue #449](#)⁵³⁰³ - Make actions with template arguments usable and add documentation
- [Issue #279](#)⁵³⁰⁴ - Refactor `addressing_service` into a base class and two derived classes
- [Issue #224](#)⁵³⁰⁵ - Changing thread state metadata is not thread safe
- [Issue #55](#)⁵³⁰⁶ - Uniform syntax for enums should be implemented

HPX V0.9.11 (Nov 11, 2015)

Our main focus for this release was the design and development of a coherent set of higher-level APIs exposing various types of parallelism to the application programmer. We introduced the concepts of an `executor`, which can be used to customize the `where` and `when` of execution of tasks in the context of parallelizing codes. We extended all APIs related to managing parallel tasks to support executors which gives the user the choice of either using one of the predefined executor types or to provide its own, possibly application specific, executor. We paid very close attention to align all of these changes with the existing C++ Standards documents or with the ongoing proposals for standardization.

This release is the first after our change to a new development policy. We switched all development to be strictly performed on branches only, all direct commits to our main branch (`master`) are prohibited. Any change has to go through a peer review before it will be merged to `master`. As a result the overall stability of our code base has significantly increased, the development process itself has been simplified. This change manifests itself in a large number of pull-requests which have been merged (please see below for a full list of closed issues and pull-requests). All in all for this release, we closed almost 100 issues and merged over 290 pull-requests. There have been over 1600 commits to the master branch since the last release.

General changes

- We are moving into the direction of unifying managed and simple components. As such, the classes `hpx::components::component` and `hpx::components::component_base` have been added which currently just forward to the currently existing simple component facilities. The examples have been converted to only use those two classes.
- Added integration with the [CircleCI](#)⁵³⁰⁷ hosted continuous integration service. This gives us constant and immediate feedback on the health of our master branch.
- The compiler configuration subsystem in the build system has been reimplemented. Instead of using `Boost.Config` we now use our own lightweight set of `cmake` scripts to determine the available language and library features supported by the used compiler.
- The API for creating instances of components has been consolidated. All component instances should be created using the `hpx::new_` only. It allows one to instantiate both, single component instances and multiple component instances. The placement of the created components can be controlled by special distribution policies. Please see the corresponding documentation outlining the use of `hpx::new_`.
- Introduced four new distribution policies which can be used with many API functions which traditionally expected to be used with a locality id. The new distribution policies are:
 - `hpx::components::default_distribution_policy` which tries to place multiple component instances as evenly as possible.

⁵³⁰² <https://github.com/TheHPXProject/hpx/issues/559>

⁵³⁰³ <https://github.com/TheHPXProject/hpx/issues/449>

⁵³⁰⁴ <https://github.com/TheHPXProject/hpx/issues/279>

⁵³⁰⁵ <https://github.com/TheHPXProject/hpx/issues/224>

⁵³⁰⁶ <https://github.com/TheHPXProject/hpx/issues/55>

⁵³⁰⁷ <https://circleci.com/gh/TheHPXProject/hpx>

- `hpx::components::colocating_distribution_policy` which will refer to the locality where a given component instance is currently placed.
 - `hpx::components::binpacking_distribution_policy` which will place multiple component instances as evenly as possible based on any performance counter.
 - `hpx::components::target_distribution_policy` which allows one to represent a given locality in the context of a distribution policy.
- The new distribution policies can now be also used with `hpx::async`. This change also deprecates `hpx::async_colocated(id, ...)` which now is replaced by a distribution policy: `hpx::async(hpx::colocated(id), ...)`.
 - The `hpx::vector` and `hpx::unordered_map` data structures can now be used with the new distribution policies as well.
 - The parallel facility `hpx::parallel::task_region` has been renamed to `hpx::parallel::task_block` based on the changes in the corresponding standardization proposal [N4411](#)⁵³⁰⁸.
 - Added extensions to the parallel facility `hpx::parallel::task_block` allowing to combine a `task_block` with an execution policy. This implies a minor breaking change as the `hpx::parallel::task_block` is now a template.
 - Added new LCOs: `hpx::lcos::latch` and `hpx::lcos::local::latch` which semantically conform to the proposed `std::latch` (see [N4399](#)⁵³⁰⁹).
 - Added performance counters exposing data related to data transferred by input/output (filesystem) operations (thanks to Maciej Brodowicz).
 - Added performance counters allowing to track the number of action invocations (local and remote invocations).
 - Added new command line options `-hpx:print-counter-at` and `-hpx:reset-counters`.
 - The `hpx::vector` component has been renamed to `hpx::partitioned_vector` to make it explicit that the underlying memory is not contiguous.
 - Introduced a completely new and uniform higher-level parallelism API which is based on executors. All existing parallelism APIs have been adapted to this. We have added a large number of different executor types, such as a numa-aware executor, a this-thread executor, etc.
 - Added support for the MingW toolchain on Windows (thanks to Eric Lemanissier).
 - HPX now includes support for APEX, (Autonomic Performance Environment for eXascale). APEX is an instrumentation and software adaptation library that provides an interface to TAU profiling / tracing as well as runtime adaptation of HPX applications through policy definitions. For more information and documentation, please see <https://github.com/UO-OACISS/xpress-apex>. To enable APEX at configuration time, specify `-DHPX_WITH_APEX=On`. To also include support for TAU profiling, specify `-DHPX_WITH_TAU=On` and specify the `-DTAU_ROOT`, `-DTAU_ARCH` and `-DTAU_OPTIONS` cmake parameters.
 - We have implemented many more of the *Using parallel algorithms*. Please see [Issue #1141](#)⁵³¹⁰ for the list of all available parallel algorithms (thanks to Daniel Bourgeois and John Biddiscombe for contributing their work).

⁵³⁰⁸ <http://wg21.link/n4411>

⁵³⁰⁹ <http://wg21.link/n4399>

⁵³¹⁰ <https://github.com/TheHPXProject/hpx/issues/1141>

Breaking changes

- We are moving into the direction of unifying managed and simple components. In order to stop exposing the old facilities, all examples have been converted to use the new classes. The breaking change in this release is that performance counters are now a `hpx::components::component_base` instead of `hpx::components::managed_component_base`.
- We removed the support for stackless threads. It turned out that there was no performance benefit when using stackless threads. As such, we decided to clean up our codebase. This feature was not documented.
- The CMake project name has changed from 'hpx' to 'HPX' for consistency and compatibility with naming conventions and other CMake projects. Generated config files go into `<prefix>/lib/cmake/HPX` and not `<prefix>/lib/cmake/hpx`.
- The macro `HPX_REGISTER_MINIMAL_COMPONENT_FACTORY` has been deprecated. Please use `HPX_REGISTER_COMPONENT` instead. The old macro will be removed in the next release.
- The obsolete `distributing_factory` and `binpacking_factory` components have been removed. The corresponding functionality is now provided by the `hpx::new_` API function in conjunction with the `hpx::default_layout` and `hpx::binpacking` distribution policies (`hpx::components::default_distribution_policy` and `hpx::components::binpacking_distribution_policy`).
- The API function `hpx::new_colocated` has been deprecated. Please use the consolidated API `hpx::new_` in conjunction with the new `hpx::colocated` distribution policy (`hpx::components::colocating_distribution_policy`) instead. The old API function will still be available for at least one release of HPX if the configuration variable `HPX_WITH_COLOCATED_BACKWARDS_COMPATIBILITY` is enabled.
- The API function `hpx::async_colocated` has been deprecated. Please use the consolidated API `hpx::async` in conjunction with the new `hpx::colocated` distribution policy (`hpx::components::colocating_distribution_policy`) instead. The old API function will still be available for at least one release of HPX if the configuration variable `HPX_WITH_COLOCATED_BACKWARDS_COMPATIBILITY` is enabled.
- The obsolete `remote_object` component has been removed.
- Replaced the use of Boost.Serialization with our own solution. While the new version is mostly compatible with Boost.Serialization, this change requires some minor code modifications in user code. For more information, please see the corresponding [announcement](#)⁵³¹¹ on the `hpx-users@stellar.cct.lsu.edu` mailing list.
- The names used by cmake to influence various configuration options have been unified. The new naming scheme relies on all configuration constants to start with `HPX_WITH_...`, while the preprocessor constant which is used at build time starts with `HPX_HAVE_...`. For instance, the former cmake command line `-DHPX_MALLOC=...` now has to be specified as `-DHPX_WITH_MALLOC=...` and will cause the preprocessor constant `HPX_HAVE_MALLOC` to be defined. The actual name of the constant (i.e. `MALLOC`) has not changed. Please see the corresponding documentation for more details (*CMake options*).
- The `get_gid()` functions exposed by the component base classes `hpx::components::server::simple_component_base`, `hpx::components::server::managed_component_base`, and `hpx::components::server::fixed_component_base` have been replaced by two new functions: `get_unmanaged_id()` and `get_id()`. To enable the old function name for backwards compatibility, use the cmake configuration option `HPX_WITH_COMPONENT_GET_GID_COMPATIBILITY=On`.
- All functions which were named `get_gid()` but were returning `hpx::id_type` have been renamed to `get_id()`. To enable the old function names for backwards compatibility, use the cmake configuration option `HPX_WITH_COMPONENT_GET_GID_COMPATIBILITY=On`.

⁵³¹¹ <http://thread.gmane.org/gmane.comp.lib.hpx.devel/196>

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- PR #1855⁵³¹² - Completely removing external/endian
- PR #1854⁵³¹³ - Don't pollute CMAKE_CXX_FLAGS through find_package()
- PR #1853⁵³¹⁴ - Updating CMake configuration to get correct version of TAU library
- PR #1852⁵³¹⁵ - Fixing Performance Problems with MPI Parcelport
- PR #1851⁵³¹⁶ - Fixing hpx_add_link_flag() and hpx_remove_link_flag()
- PR #1850⁵³¹⁷ - Fixing 1836, adding parallel::sort
- PR #1849⁵³¹⁸ - Fixing configuration for use of more than 64 cores
- PR #1848⁵³¹⁹ - Change default APEX version for release
- PR #1847⁵³²⁰ - Fix client_base::then on release
- PR #1846⁵³²¹ - Removing broken lcos::local::channel from release
- PR #1845⁵³²² - Adding example demonstrating a possible safe-object implementation to release
- PR #1844⁵³²³ - Removing stubs from accumulator examples
- PR #1843⁵³²⁴ - Don't pollute CMAKE_CXX_FLAGS through find_package()
- PR #1841⁵³²⁵ - Fixing client_base<>::then
- PR #1840⁵³²⁶ - Adding example demonstrating a possible safe-object implementation
- PR #1838⁵³²⁷ - Update version rc1
- PR #1837⁵³²⁸ - Removing broken lcos::local::channel
- PR #1835⁵³²⁹ - Adding explicit move constructor and assignment operator to hpx::lcos::promise
- PR #1834⁵³³⁰ - Making hpx::lcos::promise move-only
- PR #1833⁵³³¹ - Adding fedora docs
- Issue #1832⁵³³² - hpx::lcos::promise<> must be move-only

⁵³¹² <https://github.com/TheHPXProject/hpx/pull/1855>

⁵³¹³ <https://github.com/TheHPXProject/hpx/pull/1854>

⁵³¹⁴ <https://github.com/TheHPXProject/hpx/pull/1853>

⁵³¹⁵ <https://github.com/TheHPXProject/hpx/pull/1852>

⁵³¹⁶ <https://github.com/TheHPXProject/hpx/pull/1851>

⁵³¹⁷ <https://github.com/TheHPXProject/hpx/pull/1850>

⁵³¹⁸ <https://github.com/TheHPXProject/hpx/pull/1849>

⁵³¹⁹ <https://github.com/TheHPXProject/hpx/pull/1848>

⁵³²⁰ <https://github.com/TheHPXProject/hpx/pull/1847>

⁵³²¹ <https://github.com/TheHPXProject/hpx/pull/1846>

⁵³²² <https://github.com/TheHPXProject/hpx/pull/1845>

⁵³²³ <https://github.com/TheHPXProject/hpx/pull/1844>

⁵³²⁴ <https://github.com/TheHPXProject/hpx/pull/1843>

⁵³²⁵ <https://github.com/TheHPXProject/hpx/pull/1841>

⁵³²⁶ <https://github.com/TheHPXProject/hpx/pull/1840>

⁵³²⁷ <https://github.com/TheHPXProject/hpx/pull/1838>

⁵³²⁸ <https://github.com/TheHPXProject/hpx/pull/1837>

⁵³²⁹ <https://github.com/TheHPXProject/hpx/pull/1835>

⁵³³⁰ <https://github.com/TheHPXProject/hpx/pull/1834>

⁵³³¹ <https://github.com/TheHPXProject/hpx/pull/1833>

⁵³³² <https://github.com/TheHPXProject/hpx/issues/1832>

- PR #1831⁵³³³ - Fixing resource manager gcc5.2
- PR #1830⁵³³⁴ - Fix intel13
- PR #1829⁵³³⁵ - Unbreaking thread test
- PR #1828⁵³³⁶ - Fixing #1620
- PR #1827⁵³³⁷ - Fixing a memory management issue for the Parquet application
- Issue #1826⁵³³⁸ - Memory management issue in hpx::lcos::promise
- PR #1825⁵³³⁹ - Adding hpx::components::component and hpx::components::component_base
- PR #1823⁵³⁴⁰ - Adding git commit id to circleci build
- PR #1822⁵³⁴¹ - applying fixes suggested by clang 3.7
- PR #1821⁵³⁴² - Hyperlink fixes
- PR #1820⁵³⁴³ - added parallel multi-locality sanity test
- PR #1819⁵³⁴⁴ - Fixing #1667
- Issue #1817⁵³⁴⁵ - Hyperlinks generated by inspect tool are wrong
- PR #1816⁵³⁴⁶ - Support hpxrx
- PR #1814⁵³⁴⁷ - Fix async to dispatch to the correct locality in all cases
- Issue #1813⁵³⁴⁸ - async(launch::..., action(), ...) always invokes locally
- PR #1812⁵³⁴⁹ - fixed syntax error in CMakeLists.txt
- PR #1811⁵³⁵⁰ - Agas optimizations
- PR #1810⁵³⁵¹ - drop superfluous typedefs
- PR #1809⁵³⁵² - Allow HPX to be used as an optional package in 3rd party code
- PR #1808⁵³⁵³ - Fixing #1723
- PR #1807⁵³⁵⁴ - Making sure resolve_localities does not hang during normal operation
- Issue #1806⁵³⁵⁵ - Spinlock no longer movable and deletes operator '=', breaks MiniGhost

⁵³³³ <https://github.com/TheHPXProject/hpx/pull/1831>
⁵³³⁴ <https://github.com/TheHPXProject/hpx/pull/1830>
⁵³³⁵ <https://github.com/TheHPXProject/hpx/pull/1829>
⁵³³⁶ <https://github.com/TheHPXProject/hpx/pull/1828>
⁵³³⁷ <https://github.com/TheHPXProject/hpx/pull/1827>
⁵³³⁸ <https://github.com/TheHPXProject/hpx/issues/1826>
⁵³³⁹ <https://github.com/TheHPXProject/hpx/pull/1825>
⁵³⁴⁰ <https://github.com/TheHPXProject/hpx/pull/1823>
⁵³⁴¹ <https://github.com/TheHPXProject/hpx/pull/1822>
⁵³⁴² <https://github.com/TheHPXProject/hpx/pull/1821>
⁵³⁴³ <https://github.com/TheHPXProject/hpx/pull/1820>
⁵³⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1819>
⁵³⁴⁵ <https://github.com/TheHPXProject/hpx/issues/1817>
⁵³⁴⁶ <https://github.com/TheHPXProject/hpx/pull/1816>
⁵³⁴⁷ <https://github.com/TheHPXProject/hpx/pull/1814>
⁵³⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1813>
⁵³⁴⁹ <https://github.com/TheHPXProject/hpx/pull/1812>
⁵³⁵⁰ <https://github.com/TheHPXProject/hpx/pull/1811>
⁵³⁵¹ <https://github.com/TheHPXProject/hpx/pull/1810>
⁵³⁵² <https://github.com/TheHPXProject/hpx/pull/1809>
⁵³⁵³ <https://github.com/TheHPXProject/hpx/pull/1808>
⁵³⁵⁴ <https://github.com/TheHPXProject/hpx/pull/1807>
⁵³⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1806>

- Issue #1804⁵³⁵⁶ - register_with_basename causes hangs
- PR #1801⁵³⁵⁷ - Enhanced the inspect tool to take user directly to the problem with hyperlinks
- Issue #1800⁵³⁵⁸ - Problems compiling application on smic
- PR #1799⁵³⁵⁹ - Fixing cv exceptions
- PR #1798⁵³⁶⁰ - Documentation refactoring & updating
- PR #1797⁵³⁶¹ - Updating the activeharmony CMake module
- PR #1795⁵³⁶² - Fixing cv
- PR #1794⁵³⁶³ - Fix connect with hpx::runtime_mode_connect
- PR #1793⁵³⁶⁴ - fix a wrong use of HPX_MAX_CPU_COUNT instead of HPX_HAVE_MAX_CPU_COUNT
- PR #1792⁵³⁶⁵ - Allow for default constructed parcel instances to be moved
- PR #1791⁵³⁶⁶ - Fix connect with hpx::runtime_mode_connect
- Issue #1790⁵³⁶⁷ - assertion action_.get() failed: HPX(assertion_failure) when running Octotiger with pull request 1786
- PR #1789⁵³⁶⁸ - Fixing discover_counter_types API function
- Issue #1788⁵³⁶⁹ - connect with hpx::runtime_mode_connect
- Issue #1787⁵³⁷⁰ - discover_counter_types not working
- PR #1786⁵³⁷¹ - Changing addressing_service to use std::unordered_map instead of std::map
- PR #1785⁵³⁷² - Fix is_iterator for container algorithms
- PR #1784⁵³⁷³ - Adding new command line options:
- PR #1783⁵³⁷⁴ - Minor changes for APEX support
- PR #1782⁵³⁷⁵ - Drop legacy forwarding action traits
- PR #1781⁵³⁷⁶ - Attempt to resolve the race between cv::wait_xxx and cv::notify_all
- PR #1780⁵³⁷⁷ - Removing serialize_sequence
- PR #1779⁵³⁷⁸ - Fixed #1501: hwloc configuration options are wrong for MIC

⁵³⁵⁶ <https://github.com/TheHPXProject/hpx/issues/1804>

⁵³⁵⁷ <https://github.com/TheHPXProject/hpx/pull/1801>

⁵³⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1800>

⁵³⁵⁹ <https://github.com/TheHPXProject/hpx/pull/1799>

⁵³⁶⁰ <https://github.com/TheHPXProject/hpx/pull/1798>

⁵³⁶¹ <https://github.com/TheHPXProject/hpx/pull/1797>

⁵³⁶² <https://github.com/TheHPXProject/hpx/pull/1795>

⁵³⁶³ <https://github.com/TheHPXProject/hpx/pull/1794>

⁵³⁶⁴ <https://github.com/TheHPXProject/hpx/pull/1793>

⁵³⁶⁵ <https://github.com/TheHPXProject/hpx/pull/1792>

⁵³⁶⁶ <https://github.com/TheHPXProject/hpx/pull/1791>

⁵³⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1790>

⁵³⁶⁸ <https://github.com/TheHPXProject/hpx/pull/1789>

⁵³⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1788>

⁵³⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1787>

⁵³⁷¹ <https://github.com/TheHPXProject/hpx/pull/1786>

⁵³⁷² <https://github.com/TheHPXProject/hpx/pull/1785>

⁵³⁷³ <https://github.com/TheHPXProject/hpx/pull/1784>

⁵³⁷⁴ <https://github.com/TheHPXProject/hpx/pull/1783>

⁵³⁷⁵ <https://github.com/TheHPXProject/hpx/pull/1782>

⁵³⁷⁶ <https://github.com/TheHPXProject/hpx/pull/1781>

⁵³⁷⁷ <https://github.com/TheHPXProject/hpx/pull/1780>

⁵³⁷⁸ <https://github.com/TheHPXProject/hpx/pull/1779>

- PR #1778⁵³⁷⁹ - Removing ability to enable/disable parcel handling
- PR #1777⁵³⁸⁰ - Completely removing stackless threads
- PR #1776⁵³⁸¹ - Cleaning up util/plugin
- PR #1775⁵³⁸² - Agas fixes
- PR #1774⁵³⁸³ - Action invocation count
- PR #1773⁵³⁸⁴ - replaced MSVC variable with WIN32
- PR #1772⁵³⁸⁵ - Fixing Problems in MPI parcelport and future serialization.
- PR #1771⁵³⁸⁶ - Fixing intel 13 compiler errors related to variadic template template parameters for `lcos::when_` tests
- PR #1770⁵³⁸⁷ - Forwarding decay to `std::`
- PR #1769⁵³⁸⁸ - Add more characters with special regex meaning to the existing patch
- PR #1768⁵³⁸⁹ - Adding test for `receive_buffer`
- PR #1767⁵³⁹⁰ - Making sure that uptime counter throws exception on any attempt to be reset
- PR #1766⁵³⁹¹ - Cleaning up code related to throttling scheduler
- PR #1765⁵³⁹² - Restricting `thread_data` to creating only with `intrusive_pointers`
- PR #1764⁵³⁹³ - Fixing 1763
- Issue #1763⁵³⁹⁴ - UB in `thread_data::operator delete`
- PR #1762⁵³⁹⁵ - Making sure all serialization registries/factories are unique
- PR #1761⁵³⁹⁶ - Fixed #1751: `hpx::future::wait_for` fails a simple test
- PR #1758⁵³⁹⁷ - Fixing #1757
- Issue #1757⁵³⁹⁸ - pinning not correct using `-hpx:bind`
- Issue #1756⁵³⁹⁹ - compilation error with MinGW
- PR #1755⁵⁴⁰⁰ - Making output serialization const-correct
- Issue #1753⁵⁴⁰¹ - HPX performance degrades with time since execution begins

⁵³⁷⁹ <https://github.com/TheHPXProject/hpx/pull/1778>
⁵³⁸⁰ <https://github.com/TheHPXProject/hpx/pull/1777>
⁵³⁸¹ <https://github.com/TheHPXProject/hpx/pull/1776>
⁵³⁸² <https://github.com/TheHPXProject/hpx/pull/1775>
⁵³⁸³ <https://github.com/TheHPXProject/hpx/pull/1774>
⁵³⁸⁴ <https://github.com/TheHPXProject/hpx/pull/1773>
⁵³⁸⁵ <https://github.com/TheHPXProject/hpx/pull/1772>
⁵³⁸⁶ <https://github.com/TheHPXProject/hpx/pull/1771>
⁵³⁸⁷ <https://github.com/TheHPXProject/hpx/pull/1770>
⁵³⁸⁸ <https://github.com/TheHPXProject/hpx/pull/1769>
⁵³⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1768>
⁵³⁹⁰ <https://github.com/TheHPXProject/hpx/pull/1767>
⁵³⁹¹ <https://github.com/TheHPXProject/hpx/pull/1766>
⁵³⁹² <https://github.com/TheHPXProject/hpx/pull/1765>
⁵³⁹³ <https://github.com/TheHPXProject/hpx/pull/1764>
⁵³⁹⁴ <https://github.com/TheHPXProject/hpx/issues/1763>
⁵³⁹⁵ <https://github.com/TheHPXProject/hpx/pull/1762>
⁵³⁹⁶ <https://github.com/TheHPXProject/hpx/pull/1761>
⁵³⁹⁷ <https://github.com/TheHPXProject/hpx/pull/1758>
⁵³⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1757>
⁵³⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1756>
⁵⁴⁰⁰ <https://github.com/TheHPXProject/hpx/pull/1755>
⁵⁴⁰¹ <https://github.com/TheHPXProject/hpx/issues/1753>

- Issue #1752⁵⁴⁰² - Error in AGAS
- Issue #1751⁵⁴⁰³ - `hpx::future::wait_for` fails a simple test
- PR #1750⁵⁴⁰⁴ - Removing `hpx_fwd.hpp` includes
- PR #1749⁵⁴⁰⁵ - Simplify `result_of` and friends
- PR #1747⁵⁴⁰⁶ - Removed superfluous code from `message_buffer.hpp`
- PR #1746⁵⁴⁰⁷ - Tuple dependencies
- Issue #1745⁵⁴⁰⁸ - Broken when `_some` which takes iterators
- PR #1744⁵⁴⁰⁹ - Refining archive interface
- PR #1743⁵⁴¹⁰ - Fixing when `_all` when only a single future is passed
- PR #1742⁵⁴¹¹ - Config includes
- PR #1741⁵⁴¹² - Os executors
- Issue #1740⁵⁴¹³ - `hpx::promise` has some problems
- PR #1739⁵⁴¹⁴ - Parallel composition with generic containers
- Issue #1738⁵⁴¹⁵ - After building program and successfully linking to a version of `hpx` `DHPX_DIR` seems to be ignored
- Issue #1737⁵⁴¹⁶ - Uptime problems
- PR #1736⁵⁴¹⁷ - added convenience `c-tor` and `begin()/end()` to `serialize_buffer`
- PR #1735⁵⁴¹⁸ - Config includes
- PR #1734⁵⁴¹⁹ - Fixed #1688: Add timer counters for `tfunc_total` and `exec_total`
- Issue #1733⁵⁴²⁰ - Add unit test for `hpx/lcos/local/receive_buffer.hpp`
- PR #1732⁵⁴²¹ - Renaming `get_os_thread_count`
- PR #1731⁵⁴²² - Basename registration
- Issue #1730⁵⁴²³ - Use after move of `thread_init_data`
- PR #1729⁵⁴²⁴ - Rewriting channel based on new gate component

⁵⁴⁰² <https://github.com/TheHPXProject/hpx/issues/1752>

⁵⁴⁰³ <https://github.com/TheHPXProject/hpx/issues/1751>

⁵⁴⁰⁴ <https://github.com/TheHPXProject/hpx/pull/1750>

⁵⁴⁰⁵ <https://github.com/TheHPXProject/hpx/pull/1749>

⁵⁴⁰⁶ <https://github.com/TheHPXProject/hpx/pull/1747>

⁵⁴⁰⁷ <https://github.com/TheHPXProject/hpx/pull/1746>

⁵⁴⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1745>

⁵⁴⁰⁹ <https://github.com/TheHPXProject/hpx/pull/1744>

⁵⁴¹⁰ <https://github.com/TheHPXProject/hpx/pull/1743>

⁵⁴¹¹ <https://github.com/TheHPXProject/hpx/pull/1742>

⁵⁴¹² <https://github.com/TheHPXProject/hpx/pull/1741>

⁵⁴¹³ <https://github.com/TheHPXProject/hpx/issues/1740>

⁵⁴¹⁴ <https://github.com/TheHPXProject/hpx/pull/1739>

⁵⁴¹⁵ <https://github.com/TheHPXProject/hpx/issues/1738>

⁵⁴¹⁶ <https://github.com/TheHPXProject/hpx/issues/1737>

⁵⁴¹⁷ <https://github.com/TheHPXProject/hpx/pull/1736>

⁵⁴¹⁸ <https://github.com/TheHPXProject/hpx/pull/1735>

⁵⁴¹⁹ <https://github.com/TheHPXProject/hpx/pull/1734>

⁵⁴²⁰ <https://github.com/TheHPXProject/hpx/issues/1733>

⁵⁴²¹ <https://github.com/TheHPXProject/hpx/pull/1732>

⁵⁴²² <https://github.com/TheHPXProject/hpx/pull/1731>

⁵⁴²³ <https://github.com/TheHPXProject/hpx/issues/1730>

⁵⁴²⁴ <https://github.com/TheHPXProject/hpx/pull/1729>

- PR #1728⁵⁴²⁵ - Fixing #1722
- PR #1727⁵⁴²⁶ - Fixing compile problems with `apply_colocated`
- PR #1726⁵⁴²⁷ - Apex integration
- PR #1725⁵⁴²⁸ - fixed test timeouts
- PR #1724⁵⁴²⁹ - Renaming vector
- Issue #1723⁵⁴³⁰ - Drop support for intel compilers and gcc 4.4. based standard libs
- Issue #1722⁵⁴³¹ - Add support for detecting non-ready futures before serialization
- PR #1721⁵⁴³² - Unifying parallel executors, initializing from launch policy
- PR #1720⁵⁴³³ - dropped superfluous typedef
- Issue #1718⁵⁴³⁴ - Windows 10 x64, VS 2015 - Unknown CMake command “`add_hpx_pseudo_target`”.
- PR #1717⁵⁴³⁵ - Timed executor traits for thread-executors
- PR #1716⁵⁴³⁶ - serialization of arrays didn’t work with non-pod types. fixed
- PR #1715⁵⁴³⁷ - List serialization
- PR #1714⁵⁴³⁸ - changing misspellings
- PR #1713⁵⁴³⁹ - Fixed distribution policy executors
- PR #1712⁵⁴⁴⁰ - Moving library detection to be executed after feature tests
- PR #1711⁵⁴⁴¹ - Simplify parcel
- PR #1710⁵⁴⁴² - Compile only tests
- PR #1709⁵⁴⁴³ - Implemented timed executors
- PR #1708⁵⁴⁴⁴ - Implement `parallel::executor_traits` for thread-executors
- PR #1707⁵⁴⁴⁵ - Various fixes to `threads::executors` to make custom schedulers work
- PR #1706⁵⁴⁴⁶ - Command line option `-hpx:cores` does not work as expected
- Issue #1705⁵⁴⁴⁷ - command line option `-hpx:cores` does not work as expected

⁵⁴²⁵ <https://github.com/TheHPXProject/hpx/pull/1728>
⁵⁴²⁶ <https://github.com/TheHPXProject/hpx/pull/1727>
⁵⁴²⁷ <https://github.com/TheHPXProject/hpx/pull/1726>
⁵⁴²⁸ <https://github.com/TheHPXProject/hpx/pull/1725>
⁵⁴²⁹ <https://github.com/TheHPXProject/hpx/pull/1724>
⁵⁴³⁰ <https://github.com/TheHPXProject/hpx/issues/1723>
⁵⁴³¹ <https://github.com/TheHPXProject/hpx/issues/1722>
⁵⁴³² <https://github.com/TheHPXProject/hpx/pull/1721>
⁵⁴³³ <https://github.com/TheHPXProject/hpx/pull/1720>
⁵⁴³⁴ <https://github.com/TheHPXProject/hpx/issues/1718>
⁵⁴³⁵ <https://github.com/TheHPXProject/hpx/pull/1717>
⁵⁴³⁶ <https://github.com/TheHPXProject/hpx/pull/1716>
⁵⁴³⁷ <https://github.com/TheHPXProject/hpx/pull/1715>
⁵⁴³⁸ <https://github.com/TheHPXProject/hpx/pull/1714>
⁵⁴³⁹ <https://github.com/TheHPXProject/hpx/pull/1713>
⁵⁴⁴⁰ <https://github.com/TheHPXProject/hpx/pull/1712>
⁵⁴⁴¹ <https://github.com/TheHPXProject/hpx/pull/1711>
⁵⁴⁴² <https://github.com/TheHPXProject/hpx/pull/1710>
⁵⁴⁴³ <https://github.com/TheHPXProject/hpx/pull/1709>
⁵⁴⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1708>
⁵⁴⁴⁵ <https://github.com/TheHPXProject/hpx/pull/1707>
⁵⁴⁴⁶ <https://github.com/TheHPXProject/hpx/pull/1706>
⁵⁴⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1705>

- PR #1704⁵⁴⁴⁸ - vector deserialization is speeded up a little
- PR #1703⁵⁴⁴⁹ - Fixing shared_mutes
- Issue #1702⁵⁴⁵⁰ - Shared_mutex does not compile with no_mutex cond_var
- PR #1701⁵⁴⁵¹ - Add distribution_policy_executor
- PR #1700⁵⁴⁵² - Executor parameters
- PR #1699⁵⁴⁵³ - Readers writer lock
- PR #1698⁵⁴⁵⁴ - Remove leftovers
- PR #1697⁵⁴⁵⁵ - Fixing held locks
- PR #1696⁵⁴⁵⁶ - Modified Scan Partitioner for Algorithms
- PR #1695⁵⁴⁵⁷ - This thread executors
- PR #1694⁵⁴⁵⁸ - Fixed #1688: Add timer counters for tfunc_total and exec_total
- PR #1693⁵⁴⁵⁹ - Fix #1691: is_executor template specification fails for inherited executors
- PR #1692⁵⁴⁶⁰ - Fixed #1662: Possible exception source in coalescing_message_handler
- Issue #1691⁵⁴⁶¹ - is_executor template specification fails for inherited executors
- PR #1690⁵⁴⁶² - added macro for non-intrusive serialization of classes without a default c-tor
- PR #1689⁵⁴⁶³ - Replace value_or_error with custom storage, unify future_data state
- Issue #1688⁵⁴⁶⁴ - Add timer counters for tfunc_total and exec_total
- PR #1687⁵⁴⁶⁵ - Fixed interval timer
- PR #1686⁵⁴⁶⁶ - Fixing cmake warnings about not existing pseudo target dependencies
- PR #1685⁵⁴⁶⁷ - Converting partitioners to use bulk async execute
- PR #1683⁵⁴⁶⁸ - Adds a tool for inspect that checks for character limits
- PR #1682⁵⁴⁶⁹ - Change project name to (uppercase) HPX
- PR #1681⁵⁴⁷⁰ - Counter shortnames

⁵⁴⁴⁸ <https://github.com/TheHPXProject/hpx/pull/1704>

⁵⁴⁴⁹ <https://github.com/TheHPXProject/hpx/pull/1703>

⁵⁴⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1702>

⁵⁴⁵¹ <https://github.com/TheHPXProject/hpx/pull/1701>

⁵⁴⁵² <https://github.com/TheHPXProject/hpx/pull/1700>

⁵⁴⁵³ <https://github.com/TheHPXProject/hpx/pull/1699>

⁵⁴⁵⁴ <https://github.com/TheHPXProject/hpx/pull/1698>

⁵⁴⁵⁵ <https://github.com/TheHPXProject/hpx/pull/1697>

⁵⁴⁵⁶ <https://github.com/TheHPXProject/hpx/pull/1696>

⁵⁴⁵⁷ <https://github.com/TheHPXProject/hpx/pull/1695>

⁵⁴⁵⁸ <https://github.com/TheHPXProject/hpx/pull/1694>

⁵⁴⁵⁹ <https://github.com/TheHPXProject/hpx/pull/1693>

⁵⁴⁶⁰ <https://github.com/TheHPXProject/hpx/pull/1692>

⁵⁴⁶¹ <https://github.com/TheHPXProject/hpx/issues/1691>

⁵⁴⁶² <https://github.com/TheHPXProject/hpx/pull/1690>

⁵⁴⁶³ <https://github.com/TheHPXProject/hpx/pull/1689>

⁵⁴⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1688>

⁵⁴⁶⁵ <https://github.com/TheHPXProject/hpx/pull/1687>

⁵⁴⁶⁶ <https://github.com/TheHPXProject/hpx/pull/1686>

⁵⁴⁶⁷ <https://github.com/TheHPXProject/hpx/pull/1685>

⁵⁴⁶⁸ <https://github.com/TheHPXProject/hpx/pull/1683>

⁵⁴⁶⁹ <https://github.com/TheHPXProject/hpx/pull/1682>

⁵⁴⁷⁰ <https://github.com/TheHPXProject/hpx/pull/1681>

- PR #1680⁵⁴⁷¹ - Extended Non-intrusive Serialization to Ease Usage for Library Developers
- PR #1679⁵⁴⁷² - Working on 1544: More executor changes
- PR #1678⁵⁴⁷³ - Transpose fixes
- PR #1677⁵⁴⁷⁴ - Improve Boost compatibility check
- PR #1676⁵⁴⁷⁵ - 1d stencil fix
- Issue #1675⁵⁴⁷⁶ - hpx project name is not HPX
- PR #1674⁵⁴⁷⁷ - Fixing the MPI parcellport
- PR #1673⁵⁴⁷⁸ - added move semantics to map/vector deserialization
- PR #1672⁵⁴⁷⁹ - Vs2015 await
- PR #1671⁵⁴⁸⁰ - Adapt transform for #1668
- PR #1670⁵⁴⁸¹ - Started to work on #1668
- PR #1669⁵⁴⁸² - Add this_thread_executors
- Issue #1667⁵⁴⁸³ - Apple build instructions in docs are out of date
- PR #1666⁵⁴⁸⁴ - Apex integration
- PR #1665⁵⁴⁸⁵ - Fixes an error with the whitespace check that showed the incorrect location of the error
- Issue #1664⁵⁴⁸⁶ - Inspect tool found incorrect endline whitespace
- PR #1663⁵⁴⁸⁷ - Improve use of locks
- Issue #1662⁵⁴⁸⁸ - Possible exception source in coalescing_message_handler
- PR #1661⁵⁴⁸⁹ - Added support for 128bit number serialization
- PR #1660⁵⁴⁹⁰ - Serialization 128bits
- PR #1659⁵⁴⁹¹ - Implemented inner_product and adjacent_diff algos
- PR #1658⁵⁴⁹² - Add serialization for std::set (as there is for std::vector and std::map)
- PR #1657⁵⁴⁹³ - Use of shared_ptr in io_service_pool changed to unique_ptr

⁵⁴⁷¹ <https://github.com/TheHPXProject/hpx/pull/1680>
⁵⁴⁷² <https://github.com/TheHPXProject/hpx/pull/1679>
⁵⁴⁷³ <https://github.com/TheHPXProject/hpx/pull/1678>
⁵⁴⁷⁴ <https://github.com/TheHPXProject/hpx/pull/1677>
⁵⁴⁷⁵ <https://github.com/TheHPXProject/hpx/pull/1676>
⁵⁴⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1675>
⁵⁴⁷⁷ <https://github.com/TheHPXProject/hpx/pull/1674>
⁵⁴⁷⁸ <https://github.com/TheHPXProject/hpx/pull/1673>
⁵⁴⁷⁹ <https://github.com/TheHPXProject/hpx/pull/1672>
⁵⁴⁸⁰ <https://github.com/TheHPXProject/hpx/pull/1671>
⁵⁴⁸¹ <https://github.com/TheHPXProject/hpx/pull/1670>
⁵⁴⁸² <https://github.com/TheHPXProject/hpx/pull/1669>
⁵⁴⁸³ <https://github.com/TheHPXProject/hpx/issues/1667>
⁵⁴⁸⁴ <https://github.com/TheHPXProject/hpx/pull/1666>
⁵⁴⁸⁵ <https://github.com/TheHPXProject/hpx/pull/1665>
⁵⁴⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1664>
⁵⁴⁸⁷ <https://github.com/TheHPXProject/hpx/pull/1663>
⁵⁴⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1662>
⁵⁴⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1661>
⁵⁴⁹⁰ <https://github.com/TheHPXProject/hpx/pull/1660>
⁵⁴⁹¹ <https://github.com/TheHPXProject/hpx/pull/1659>
⁵⁴⁹² <https://github.com/TheHPXProject/hpx/pull/1658>
⁵⁴⁹³ <https://github.com/TheHPXProject/hpx/pull/1657>

- Issue #1656⁵⁴⁹⁴ - 1d_stencil codes all have wrong factor
- PR #1654⁵⁴⁹⁵ - When using runtime_mode_connect, find the correct localhost public ip address
- PR #1653⁵⁴⁹⁶ - Fixing 1617
- PR #1652⁵⁴⁹⁷ - Remove traits::action_may_require_id_splitting
- PR #1651⁵⁴⁹⁸ - Fixed performance counters related to AGAS cache timings
- PR #1650⁵⁴⁹⁹ - Remove leftovers of traits::type_size
- PR #1649⁵⁵⁰⁰ - Shorten target names on Windows to shorten used path names
- PR #1648⁵⁵⁰¹ - Fixing problems introduced by merging #1623 for older compilers
- PR #1647⁵⁵⁰² - Simplify running automatic builds on Windows
- Issue #1646⁵⁵⁰³ - Cache insert and update performance counters are broken
- Issue #1644⁵⁵⁰⁴ - Remove leftovers of traits::type_size
- Issue #1643⁵⁵⁰⁵ - Remove traits::action_may_require_id_splitting
- PR #1642⁵⁵⁰⁶ - Adds spell checker to the inspect tool for qbk and doxygen comments
- PR #1640⁵⁵⁰⁷ - First step towards fixing 688
- PR #1639⁵⁵⁰⁸ - Re-apply remaining changes from limit_dataflow_recursion branch
- PR #1638⁵⁵⁰⁹ - This fixes possible deadlock in the test ignore_while_locked_1485
- PR #1637⁵⁵¹⁰ - Fixing hpx::wait_all() invoked with two vector<future<T>>
- PR #1636⁵⁵¹¹ - Partially re-apply changes from limit_dataflow_recursion branch
- PR #1635⁵⁵¹² - Adding missing test for #1572
- PR #1634⁵⁵¹³ - Revert “Limit recursion-depth in dataflow to a configurable constant”
- PR #1633⁵⁵¹⁴ - Add command line option to ignore batch environment
- PR #1631⁵⁵¹⁵ - hpx::lcos::queue exhibits strange behavior
- PR #1630⁵⁵¹⁶ - Fixed endline_whitespace_check.cpp to detect lines with only whitespace

⁵⁴⁹⁴ <https://github.com/TheHPXProject/hpx/issues/1656>

⁵⁴⁹⁵ <https://github.com/TheHPXProject/hpx/pull/1654>

⁵⁴⁹⁶ <https://github.com/TheHPXProject/hpx/pull/1653>

⁵⁴⁹⁷ <https://github.com/TheHPXProject/hpx/pull/1652>

⁵⁴⁹⁸ <https://github.com/TheHPXProject/hpx/pull/1651>

⁵⁴⁹⁹ <https://github.com/TheHPXProject/hpx/pull/1650>

⁵⁵⁰⁰ <https://github.com/TheHPXProject/hpx/pull/1649>

⁵⁵⁰¹ <https://github.com/TheHPXProject/hpx/pull/1648>

⁵⁵⁰² <https://github.com/TheHPXProject/hpx/pull/1647>

⁵⁵⁰³ <https://github.com/TheHPXProject/hpx/issues/1646>

⁵⁵⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1644>

⁵⁵⁰⁵ <https://github.com/TheHPXProject/hpx/issues/1643>

⁵⁵⁰⁶ <https://github.com/TheHPXProject/hpx/pull/1642>

⁵⁵⁰⁷ <https://github.com/TheHPXProject/hpx/pull/1640>

⁵⁵⁰⁸ <https://github.com/TheHPXProject/hpx/pull/1639>

⁵⁵⁰⁹ <https://github.com/TheHPXProject/hpx/pull/1638>

⁵⁵¹⁰ <https://github.com/TheHPXProject/hpx/pull/1637>

⁵⁵¹¹ <https://github.com/TheHPXProject/hpx/pull/1636>

⁵⁵¹² <https://github.com/TheHPXProject/hpx/pull/1635>

⁵⁵¹³ <https://github.com/TheHPXProject/hpx/pull/1634>

⁵⁵¹⁴ <https://github.com/TheHPXProject/hpx/pull/1633>

⁵⁵¹⁵ <https://github.com/TheHPXProject/hpx/pull/1631>

⁵⁵¹⁶ <https://github.com/TheHPXProject/hpx/pull/1630>

- [Issue #1629⁵⁵¹⁷](#) - Inspect trailing whitespace checker problem
- [PR #1628⁵⁵¹⁸](#) - Removed meaningless const qualifiers. Minor icpc fix.
- [PR #1627⁵⁵¹⁹](#) - Fixing the queue LCO and add example demonstrating its use
- [PR #1626⁵⁵²⁰](#) - Deprecating `get_gid()`, add `get_id()` and `get_unmanaged_id()`
- [PR #1625⁵⁵²¹](#) - Allowing to specify whether to send credits along with message
- [Issue #1624⁵⁵²²](#) - Lifetime issue
- [Issue #1623⁵⁵²³](#) - `hpx::wait_all()` invoked with two `vector<future<T>>` fails
- [PR #1622⁵⁵²⁴](#) - Executor partitioners
- [PR #1621⁵⁵²⁵](#) - Clean up coroutines implementation
- [Issue #1620⁵⁵²⁶](#) - Revert #1535
- [PR #1619⁵⁵²⁷](#) - Fix result type calculation for `hpx::make_continuation`
- [PR #1618⁵⁵²⁸](#) - Fixing RDTSC on Xeon/Phi
- [Issue #1617⁵⁵²⁹](#) - `hpx cmake` not working when run as a subproject
- [Issue #1616⁵⁵³⁰](#) - `cmake` problem resulting in RDTSC not working correctly for Xeon Phi creates very strange results for duration counters
- [Issue #1615⁵⁵³¹](#) - `hpx::make_continuation` requires input and output to be the same
- [PR #1614⁵⁵³²](#) - Fixed remove copy test
- [Issue #1613⁵⁵³³](#) - Dataflow causes stack overflow
- [PR #1612⁵⁵³⁴](#) - Modified foreach partitioner to use bulk execute
- [PR #1611⁵⁵³⁵](#) - Limit recursion-depth in dataflow to a configurable constant
- [PR #1610⁵⁵³⁶](#) - Increase timeout for CircleCI
- [PR #1609⁵⁵³⁷](#) - Refactoring thread manager, mainly extracting thread pool
- [PR #1608⁵⁵³⁸](#) - Fixed running multiple localities without localities parameter
- [PR #1607⁵⁵³⁹](#) - More algorithm fixes to `adjacentfind`

⁵⁵¹⁷ <https://github.com/TheHPXProject/hpx/issues/1629>

⁵⁵¹⁸ <https://github.com/TheHPXProject/hpx/pull/1628>

⁵⁵¹⁹ <https://github.com/TheHPXProject/hpx/pull/1627>

⁵⁵²⁰ <https://github.com/TheHPXProject/hpx/pull/1626>

⁵⁵²¹ <https://github.com/TheHPXProject/hpx/pull/1625>

⁵⁵²² <https://github.com/TheHPXProject/hpx/issues/1624>

⁵⁵²³ <https://github.com/TheHPXProject/hpx/issues/1623>

⁵⁵²⁴ <https://github.com/TheHPXProject/hpx/pull/1622>

⁵⁵²⁵ <https://github.com/TheHPXProject/hpx/pull/1621>

⁵⁵²⁶ <https://github.com/TheHPXProject/hpx/issues/1620>

⁵⁵²⁷ <https://github.com/TheHPXProject/hpx/pull/1619>

⁵⁵²⁸ <https://github.com/TheHPXProject/hpx/pull/1618>

⁵⁵²⁹ <https://github.com/TheHPXProject/hpx/issues/1617>

⁵⁵³⁰ <https://github.com/TheHPXProject/hpx/issues/1616>

⁵⁵³¹ <https://github.com/TheHPXProject/hpx/issues/1615>

⁵⁵³² <https://github.com/TheHPXProject/hpx/pull/1614>

⁵⁵³³ <https://github.com/TheHPXProject/hpx/issues/1613>

⁵⁵³⁴ <https://github.com/TheHPXProject/hpx/pull/1612>

⁵⁵³⁵ <https://github.com/TheHPXProject/hpx/pull/1611>

⁵⁵³⁶ <https://github.com/TheHPXProject/hpx/pull/1610>

⁵⁵³⁷ <https://github.com/TheHPXProject/hpx/pull/1609>

⁵⁵³⁸ <https://github.com/TheHPXProject/hpx/pull/1608>

⁵⁵³⁹ <https://github.com/TheHPXProject/hpx/pull/1607>

- [Issue #1606](#)⁵⁵⁴⁰ - Running without localities parameter binds to bogus port range
- [Issue #1605](#)⁵⁵⁴¹ - Too many serializations
- [PR #1604](#)⁵⁵⁴² - Changes the HPX image into a hyperlink
- [PR #1601](#)⁵⁵⁴³ - Fixing problems with remove_copy algorithm tests
- [PR #1600](#)⁵⁵⁴⁴ - Actions with ids cleanup
- [PR #1599](#)⁵⁵⁴⁵ - Duplicate binding of global ids should fail
- [PR #1598](#)⁵⁵⁴⁶ - Fixing array access
- [PR #1597](#)⁵⁵⁴⁷ - Improved the reliability of connecting/disconnecting localities
- [Issue #1596](#)⁵⁵⁴⁸ - Duplicate id binding should fail
- [PR #1595](#)⁵⁵⁴⁹ - Fixing more cmake config constants
- [PR #1594](#)⁵⁵⁵⁰ - Fixing preprocessor constant used to enable C++11 chrono
- [PR #1593](#)⁵⁵⁵¹ - Adding operator|() for hpx::launch
- [Issue #1592](#)⁵⁵⁵² - Error (typo) in the docs
- [Issue #1590](#)⁵⁵⁵³ - CMake fails when CMAKE_BINARY_DIR contains '+'
- [Issue #1589](#)⁵⁵⁵⁴ - Disconnecting a locality results in segfault using heartbeat example
- [PR #1588](#)⁵⁵⁵⁵ - Fix doc string for config option HPX_WITH_EXAMPLES
- [PR #1586](#)⁵⁵⁵⁶ - Fixing 1493
- [PR #1585](#)⁵⁵⁵⁷ - Additional Check for Inspect Tool to detect Endline Whitespace
- [Issue #1584](#)⁵⁵⁵⁸ - Clean up coroutines implementation
- [PR #1583](#)⁵⁵⁵⁹ - Adding a check for end line whitespace
- [PR #1582](#)⁵⁵⁶⁰ - Attempt to fix assert firing after scheduling loop was exited
- [PR #1581](#)⁵⁵⁶¹ - Fixed adjacentfind_binary test
- [PR #1580](#)⁵⁵⁶² - Prevent some of the internal cmake lists from growing indefinitely

⁵⁵⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1606>

⁵⁵⁴¹ <https://github.com/TheHPXProject/hpx/issues/1605>

⁵⁵⁴² <https://github.com/TheHPXProject/hpx/pull/1604>

⁵⁵⁴³ <https://github.com/TheHPXProject/hpx/pull/1601>

⁵⁵⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1600>

⁵⁵⁴⁵ <https://github.com/TheHPXProject/hpx/pull/1599>

⁵⁵⁴⁶ <https://github.com/TheHPXProject/hpx/pull/1598>

⁵⁵⁴⁷ <https://github.com/TheHPXProject/hpx/pull/1597>

⁵⁵⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1596>

⁵⁵⁴⁹ <https://github.com/TheHPXProject/hpx/pull/1595>

⁵⁵⁵⁰ <https://github.com/TheHPXProject/hpx/pull/1594>

⁵⁵⁵¹ <https://github.com/TheHPXProject/hpx/pull/1593>

⁵⁵⁵² <https://github.com/TheHPXProject/hpx/issues/1592>

⁵⁵⁵³ <https://github.com/TheHPXProject/hpx/issues/1590>

⁵⁵⁵⁴ <https://github.com/TheHPXProject/hpx/issues/1589>

⁵⁵⁵⁵ <https://github.com/TheHPXProject/hpx/pull/1588>

⁵⁵⁵⁶ <https://github.com/TheHPXProject/hpx/pull/1586>

⁵⁵⁵⁷ <https://github.com/TheHPXProject/hpx/pull/1585>

⁵⁵⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1584>

⁵⁵⁵⁹ <https://github.com/TheHPXProject/hpx/pull/1583>

⁵⁵⁶⁰ <https://github.com/TheHPXProject/hpx/pull/1582>

⁵⁵⁶¹ <https://github.com/TheHPXProject/hpx/pull/1581>

⁵⁵⁶² <https://github.com/TheHPXProject/hpx/pull/1580>

- PR #1579⁵⁵⁶³ - Removing type_size trait, replacing it with special archive type
- Issue #1578⁵⁵⁶⁴ - Remove demangle_helper
- PR #1577⁵⁵⁶⁵ - Get ptr problems
- Issue #1576⁵⁵⁶⁶ - Refactor async, dataflow, and future::then
- PR #1575⁵⁵⁶⁷ - Fixing tests for parallel rotate
- PR #1574⁵⁵⁶⁸ - Cleaning up schedulers
- PR #1573⁵⁵⁶⁹ - Fixing thread pool executor
- PR #1572⁵⁵⁷⁰ - Fixing number of configured localities
- PR #1571⁵⁵⁷¹ - Reimplement decay
- PR #1570⁵⁵⁷² - Refactoring async, apply, and dataflow APIs
- PR #1569⁵⁵⁷³ - Changed range for mach-o library lookup
- PR #1568⁵⁵⁷⁴ - Mark decltype support as required
- PR #1567⁵⁵⁷⁵ - Removed const from algorithms
- Issue #1566⁵⁵⁷⁶ - CMAKE Configuration Test Failures for clang 3.5 on debian
- PR #1565⁵⁵⁷⁷ - Dylib support
- PR #1564⁵⁵⁷⁸ - Converted partitioners and some algorithms to use executors
- PR #1563⁵⁵⁷⁹ - Fix several #includes for Boost.Preprocessor
- PR #1562⁵⁵⁸⁰ - Adding configuration option disabling/enabling all message handlers
- PR #1561⁵⁵⁸¹ - Removed all occurrences of boost::move replacing it with std::move
- Issue #1560⁵⁵⁸² - Leftover HPX_REGISTER_ACTION_DECLARATION_2
- PR #1558⁵⁵⁸³ - Revisit async/apply SFINAE conditions
- PR #1557⁵⁵⁸⁴ - Removing type_size trait, replacing it with special archive type
- PR #1556⁵⁵⁸⁵ - Executor algorithms

⁵⁵⁶³ <https://github.com/TheHPXProject/hpx/pull/1579>

⁵⁵⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1578>

⁵⁵⁶⁵ <https://github.com/TheHPXProject/hpx/pull/1577>

⁵⁵⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1576>

⁵⁵⁶⁷ <https://github.com/TheHPXProject/hpx/pull/1575>

⁵⁵⁶⁸ <https://github.com/TheHPXProject/hpx/pull/1574>

⁵⁵⁶⁹ <https://github.com/TheHPXProject/hpx/pull/1573>

⁵⁵⁷⁰ <https://github.com/TheHPXProject/hpx/pull/1572>

⁵⁵⁷¹ <https://github.com/TheHPXProject/hpx/pull/1571>

⁵⁵⁷² <https://github.com/TheHPXProject/hpx/pull/1570>

⁵⁵⁷³ <https://github.com/TheHPXProject/hpx/pull/1569>

⁵⁵⁷⁴ <https://github.com/TheHPXProject/hpx/pull/1568>

⁵⁵⁷⁵ <https://github.com/TheHPXProject/hpx/pull/1567>

⁵⁵⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1566>

⁵⁵⁷⁷ <https://github.com/TheHPXProject/hpx/pull/1565>

⁵⁵⁷⁸ <https://github.com/TheHPXProject/hpx/pull/1564>

⁵⁵⁷⁹ <https://github.com/TheHPXProject/hpx/pull/1563>

⁵⁵⁸⁰ <https://github.com/TheHPXProject/hpx/pull/1562>

⁵⁵⁸¹ <https://github.com/TheHPXProject/hpx/pull/1561>

⁵⁵⁸² <https://github.com/TheHPXProject/hpx/issues/1560>

⁵⁵⁸³ <https://github.com/TheHPXProject/hpx/pull/1558>

⁵⁵⁸⁴ <https://github.com/TheHPXProject/hpx/pull/1557>

⁵⁵⁸⁵ <https://github.com/TheHPXProject/hpx/pull/1556>

- [PR #1555⁵⁵⁸⁶](#) - Remove the necessity to specify archive flags on the receiving end
- [PR #1554⁵⁵⁸⁷](#) - Removing obsolete Boost.Serialization macros
- [PR #1553⁵⁵⁸⁸](#) - Properly fix HPX_DEFINE_*_ACTION macros
- [PR #1552⁵⁵⁸⁹](#) - Fixed algorithms relying on copy_if implementation
- [PR #1551⁵⁵⁹⁰](#) - Pxfs - Modifying FindOrangeFS.cmake based on OrangeFS 2.9.X
- [Issue #1550⁵⁵⁹¹](#) - Passing plain identifier inside HPX_DEFINE_PLAIN_ACTION_1
- [PR #1549⁵⁵⁹²](#) - Fixing intel14/libstdc++4.4
- [PR #1548⁵⁵⁹³](#) - Moving raw_ptr to detail namespace
- [PR #1547⁵⁵⁹⁴](#) - Adding support for executors to future.then
- [PR #1546⁵⁵⁹⁵](#) - Executor traits result types
- [PR #1545⁵⁵⁹⁶](#) - Integrate executors with dataflow
- [PR #1543⁵⁵⁹⁷](#) - Fix potential zero-copy for primarynamespace::bulk_service_async et.al.
- [PR #1542⁵⁵⁹⁸](#) - Merging HPX0.9.10 into pxfs branch
- [PR #1541⁵⁵⁹⁹](#) - Removed stale cmake tests, unused since the great cmake refactoring
- [PR #1540⁵⁶⁰⁰](#) - Fix idle-rate on platforms without TSC
- [PR #1539⁵⁶⁰¹](#) - Reporting situation if zero-copy-serialization was performed by a parcel generated from a plain apply/async
- [PR #1538⁵⁶⁰²](#) - Changed return type of bulk executors and added test
- [Issue #1537⁵⁶⁰³](#) - Incorrect cpuid config tests
- [PR #1536⁵⁶⁰⁴](#) - Changed return type of bulk executors and added test
- [PR #1535⁵⁶⁰⁵](#) - Make sure promise::get_gid() can be called more than once
- [PR #1534⁵⁶⁰⁶](#) - Fixed async_callback with bound callback
- [PR #1533⁵⁶⁰⁷](#) - Updated the link in the documentation to a publically- accessible URL
- [PR #1532⁵⁶⁰⁸](#) - Make sure sync primitives are not copyable nor movable

⁵⁵⁸⁶ <https://github.com/TheHPXProject/hpx/pull/1555>
⁵⁵⁸⁷ <https://github.com/TheHPXProject/hpx/pull/1554>
⁵⁵⁸⁸ <https://github.com/TheHPXProject/hpx/pull/1553>
⁵⁵⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1552>
⁵⁵⁹⁰ <https://github.com/TheHPXProject/hpx/pull/1551>
⁵⁵⁹¹ <https://github.com/TheHPXProject/hpx/issues/1550>
⁵⁵⁹² <https://github.com/TheHPXProject/hpx/pull/1549>
⁵⁵⁹³ <https://github.com/TheHPXProject/hpx/pull/1548>
⁵⁵⁹⁴ <https://github.com/TheHPXProject/hpx/pull/1547>
⁵⁵⁹⁵ <https://github.com/TheHPXProject/hpx/pull/1546>
⁵⁵⁹⁶ <https://github.com/TheHPXProject/hpx/pull/1545>
⁵⁵⁹⁷ <https://github.com/TheHPXProject/hpx/pull/1543>
⁵⁵⁹⁸ <https://github.com/TheHPXProject/hpx/pull/1542>
⁵⁵⁹⁹ <https://github.com/TheHPXProject/hpx/pull/1541>
⁵⁶⁰⁰ <https://github.com/TheHPXProject/hpx/pull/1540>
⁵⁶⁰¹ <https://github.com/TheHPXProject/hpx/pull/1539>
⁵⁶⁰² <https://github.com/TheHPXProject/hpx/pull/1538>
⁵⁶⁰³ <https://github.com/TheHPXProject/hpx/issues/1537>
⁵⁶⁰⁴ <https://github.com/TheHPXProject/hpx/pull/1536>
⁵⁶⁰⁵ <https://github.com/TheHPXProject/hpx/pull/1535>
⁵⁶⁰⁶ <https://github.com/TheHPXProject/hpx/pull/1534>
⁵⁶⁰⁷ <https://github.com/TheHPXProject/hpx/pull/1533>
⁵⁶⁰⁸ <https://github.com/TheHPXProject/hpx/pull/1532>

- PR #1531⁵⁶⁰⁹ - Fix unwrapped issue with future ranges of void type
- PR #1530⁵⁶¹⁰ - Serialization complex
- Issue #1528⁵⁶¹¹ - Unwrapped issue with future<void>
- Issue #1527⁵⁶¹² - HPX does not build with Boost 1.58.0
- PR #1526⁵⁶¹³ - Added support for boost.multi_array serialization
- PR #1525⁵⁶¹⁴ - Properly handle deferred futures, fixes #1506
- PR #1524⁵⁶¹⁵ - Making sure invalid action argument types generate clear error message
- Issue #1522⁵⁶¹⁶ - Need serialization support for boost multi array
- Issue #1521⁵⁶¹⁷ - Remote async and zero-copy serialization optimizations don't play well together
- PR #1520⁵⁶¹⁸ - Fixing UB while registering polymorphic classes for serialization
- PR #1519⁵⁶¹⁹ - Making detail::condition_variable safe to use
- PR #1518⁵⁶²⁰ - Fix when_some bug missing indices in its result
- Issue #1517⁵⁶²¹ - Typo may affect CMake build system tests
- PR #1516⁵⁶²² - Fixing Posix context
- PR #1515⁵⁶²³ - Fixing Posix context
- PR #1514⁵⁶²⁴ - Correct problems with loading dynamic components
- PR #1513⁵⁶²⁵ - Fixing intel glibc4 4
- Issue #1508⁵⁶²⁶ - memory and papi counters do not work
- Issue #1507⁵⁶²⁷ - Unrecognized Command Line Option Error causing exit status 0
- Issue #1506⁵⁶²⁸ - Properly handle deferred futures
- PR #1505⁵⁶²⁹ - Adding #include - would not compile without this
- Issue #1502⁵⁶³⁰ - boost::filesystem::exists throws unexpected exception
- Issue #1501⁵⁶³¹ - hwloc configuration options are wrong for MIC

⁵⁶⁰⁹ <https://github.com/TheHPXProject/hpx/pull/1531>
⁵⁶¹⁰ <https://github.com/TheHPXProject/hpx/pull/1530>
⁵⁶¹¹ <https://github.com/TheHPXProject/hpx/issues/1528>
⁵⁶¹² <https://github.com/TheHPXProject/hpx/issues/1527>
⁵⁶¹³ <https://github.com/TheHPXProject/hpx/pull/1526>
⁵⁶¹⁴ <https://github.com/TheHPXProject/hpx/pull/1525>
⁵⁶¹⁵ <https://github.com/TheHPXProject/hpx/pull/1524>
⁵⁶¹⁶ <https://github.com/TheHPXProject/hpx/issues/1522>
⁵⁶¹⁷ <https://github.com/TheHPXProject/hpx/issues/1521>
⁵⁶¹⁸ <https://github.com/TheHPXProject/hpx/pull/1520>
⁵⁶¹⁹ <https://github.com/TheHPXProject/hpx/pull/1519>
⁵⁶²⁰ <https://github.com/TheHPXProject/hpx/pull/1518>
⁵⁶²¹ <https://github.com/TheHPXProject/hpx/issues/1517>
⁵⁶²² <https://github.com/TheHPXProject/hpx/pull/1516>
⁵⁶²³ <https://github.com/TheHPXProject/hpx/pull/1515>
⁵⁶²⁴ <https://github.com/TheHPXProject/hpx/pull/1514>
⁵⁶²⁵ <https://github.com/TheHPXProject/hpx/pull/1513>
⁵⁶²⁶ <https://github.com/TheHPXProject/hpx/issues/1508>
⁵⁶²⁷ <https://github.com/TheHPXProject/hpx/issues/1507>
⁵⁶²⁸ <https://github.com/TheHPXProject/hpx/issues/1506>
⁵⁶²⁹ <https://github.com/TheHPXProject/hpx/pull/1505>
⁵⁶³⁰ <https://github.com/TheHPXProject/hpx/issues/1502>
⁵⁶³¹ <https://github.com/TheHPXProject/hpx/issues/1501>

- PR #1504⁵⁶³² - Making sure `boost::filesystem::exists()` does not throw
- PR #1500⁵⁶³³ - Exit application on `--hpx:version/-v` and `--hpx:info`
- PR #1498⁵⁶³⁴ - Extended task block
- PR #1497⁵⁶³⁵ - Unique ptr serialization
- PR #1496⁵⁶³⁶ - Unique ptr serialization (closed)
- PR #1495⁵⁶³⁷ - Switching `circuleci` build type to debug
- Issue #1494⁵⁶³⁸ - `--hpx:version/-v` does not exit after printing version information
- Issue #1493⁵⁶³⁹ - add an `hpx_` prefix to libraries and components to avoid name conflicts
- Issue #1492⁵⁶⁴⁰ - Define and ensure limitations for arguments to `async/apply`
- PR #1489⁵⁶⁴¹ - Enable idle rate counter on demand
- PR #1488⁵⁶⁴² - Made sure `detail::condition_variable` can be safely destroyed
- PR #1487⁵⁶⁴³ - Introduced default (main) template implementation for `ignore_while_checking`
- PR #1486⁵⁶⁴⁴ - Add HPX inspect tool
- Issue #1485⁵⁶⁴⁵ - `ignore_while_locked` doesn't support all Lockable types
- PR #1484⁵⁶⁴⁶ - Docker image generation
- PR #1483⁵⁶⁴⁷ - Move external endian library into HPX
- PR #1482⁵⁶⁴⁸ - Actions with integer type ids
- Issue #1481⁵⁶⁴⁹ - Sync primitives safe destruction
- Issue #1480⁵⁶⁵⁰ - Move external/boost/endian into `hpx/util`
- Issue #1478⁵⁶⁵¹ - Boost inspect violations
- PR #1479⁵⁶⁵² - Adds serialization for arrays; some further/minor fixes
- PR #1477⁵⁶⁵³ - Fixing problems with the Intel compiler using a GCC 4.4 std library
- PR #1476⁵⁶⁵⁴ - Adding `hpx::lcos::latch` and `hpx::lcos::local::latch`

⁵⁶³² <https://github.com/TheHPXProject/hpx/pull/1504>

⁵⁶³³ <https://github.com/TheHPXProject/hpx/pull/1500>

⁵⁶³⁴ <https://github.com/TheHPXProject/hpx/pull/1498>

⁵⁶³⁵ <https://github.com/TheHPXProject/hpx/pull/1497>

⁵⁶³⁶ <https://github.com/TheHPXProject/hpx/pull/1496>

⁵⁶³⁷ <https://github.com/TheHPXProject/hpx/pull/1495>

⁵⁶³⁸ <https://github.com/TheHPXProject/hpx/issues/1494>

⁵⁶³⁹ <https://github.com/TheHPXProject/hpx/issues/1493>

⁵⁶⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1492>

⁵⁶⁴¹ <https://github.com/TheHPXProject/hpx/pull/1489>

⁵⁶⁴² <https://github.com/TheHPXProject/hpx/pull/1488>

⁵⁶⁴³ <https://github.com/TheHPXProject/hpx/pull/1487>

⁵⁶⁴⁴ <https://github.com/TheHPXProject/hpx/pull/1486>

⁵⁶⁴⁵ <https://github.com/TheHPXProject/hpx/issues/1485>

⁵⁶⁴⁶ <https://github.com/TheHPXProject/hpx/pull/1484>

⁵⁶⁴⁷ <https://github.com/TheHPXProject/hpx/pull/1483>

⁵⁶⁴⁸ <https://github.com/TheHPXProject/hpx/pull/1482>

⁵⁶⁴⁹ <https://github.com/TheHPXProject/hpx/issues/1481>

⁵⁶⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1480>

⁵⁶⁵¹ <https://github.com/TheHPXProject/hpx/issues/1478>

⁵⁶⁵² <https://github.com/TheHPXProject/hpx/pull/1479>

⁵⁶⁵³ <https://github.com/TheHPXProject/hpx/pull/1477>

⁵⁶⁵⁴ <https://github.com/TheHPXProject/hpx/pull/1476>

- Issue #1475⁵⁶⁵⁵ - Boost inspect violations
- PR #1473⁵⁶⁵⁶ - Fixing action move tests
- Issue #1471⁵⁶⁵⁷ - Sync primitives should not be movable
- PR #1470⁵⁶⁵⁸ - Removing `hpx::util::polymorphic_factory`
- PR #1468⁵⁶⁵⁹ - Fixed container creation
- Issue #1467⁵⁶⁶⁰ - HPX application fail during finalization
- Issue #1466⁵⁶⁶¹ - HPX doesn't pick up Torque's nodefile on SuperMIC
- Issue #1464⁵⁶⁶² - HPX option for pre and post bootstrap performance counters
- PR #1463⁵⁶⁶³ - Replacing `async_colocated(id, ...)` with `async(colocated(id), ...)`
- PR #1462⁵⁶⁶⁴ - Consolidated `task_region` with N4411
- PR #1461⁵⁶⁶⁵ - Consolidate inconsistent CMake option names
- Issue #1460⁵⁶⁶⁶ - Which `malloc` is actually used? or at least which one is HPX built with
- Issue #1459⁵⁶⁶⁷ - Make `cmake` configure step fail explicitly if compiler version is not supported
- Issue #1458⁵⁶⁶⁸ - Update `parallel::task_region` with N4411
- PR #1456⁵⁶⁶⁹ - Consolidating `new_<>()`
- Issue #1455⁵⁶⁷⁰ - Replace `async_colocated(id, ...)` with `async(colocated(id), ...)`
- PR #1454⁵⁶⁷¹ - Removed harmful `std::moves` from return statements
- PR #1453⁵⁶⁷² - Use range-based for-loop instead of `Boost.Foreach`
- PR #1452⁵⁶⁷³ - C++ feature tests
- PR #1451⁵⁶⁷⁴ - When serializing, pass archive flags to `traits::get_type_size`
- Issue #1450⁵⁶⁷⁵ - `traits::get_type_size` needs archive flags to enable `zero_copy` optimizations
- Issue #1449⁵⁶⁷⁶ - "couldn't create performance counter" - AGAS
- Issue #1448⁵⁶⁷⁷ - Replace distributing factories with `new_<T[]>(...)`

⁵⁶⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1475>

⁵⁶⁵⁶ <https://github.com/TheHPXProject/hpx/pull/1473>

⁵⁶⁵⁷ <https://github.com/TheHPXProject/hpx/issues/1471>

⁵⁶⁵⁸ <https://github.com/TheHPXProject/hpx/pull/1470>

⁵⁶⁵⁹ <https://github.com/TheHPXProject/hpx/pull/1468>

⁵⁶⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1467>

⁵⁶⁶¹ <https://github.com/TheHPXProject/hpx/issues/1466>

⁵⁶⁶² <https://github.com/TheHPXProject/hpx/issues/1464>

⁵⁶⁶³ <https://github.com/TheHPXProject/hpx/pull/1463>

⁵⁶⁶⁴ <https://github.com/TheHPXProject/hpx/pull/1462>

⁵⁶⁶⁵ <https://github.com/TheHPXProject/hpx/pull/1461>

⁵⁶⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1460>

⁵⁶⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1459>

⁵⁶⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1458>

⁵⁶⁶⁹ <https://github.com/TheHPXProject/hpx/pull/1456>

⁵⁶⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1455>

⁵⁶⁷¹ <https://github.com/TheHPXProject/hpx/pull/1454>

⁵⁶⁷² <https://github.com/TheHPXProject/hpx/pull/1453>

⁵⁶⁷³ <https://github.com/TheHPXProject/hpx/pull/1452>

⁵⁶⁷⁴ <https://github.com/TheHPXProject/hpx/pull/1451>

⁵⁶⁷⁵ <https://github.com/TheHPXProject/hpx/issues/1450>

⁵⁶⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1449>

⁵⁶⁷⁷ <https://github.com/TheHPXProject/hpx/issues/1448>

- [PR #1447](#)⁵⁶⁷⁸ - Removing obsolete `remote_object` component
- [PR #1446](#)⁵⁶⁷⁹ - Hpx serialization
- [PR #1445](#)⁵⁶⁸⁰ - Replacing travis with circleci
- [PR #1443](#)⁵⁶⁸¹ - Always stripping HPX command line arguments before executing start function
- [PR #1442](#)⁵⁶⁸² - Adding `-hpx:bind=none` to disable thread affinities
- [Issue #1439](#)⁵⁶⁸³ - Libraries get linked in multiple times, `RPATH` is not properly set
- [PR #1438](#)⁵⁶⁸⁴ - Removed superfluous typedefs
- [Issue #1437](#)⁵⁶⁸⁵ - `hpx::init()` should strip HPX-related flags from argv
- [Issue #1436](#)⁵⁶⁸⁶ - Add strong scaling option to `htts`
- [PR #1435](#)⁵⁶⁸⁷ - Adding `async_cb`, `async_continue_cb`, and `async_colocated_cb`
- [PR #1434](#)⁵⁶⁸⁸ - Added missing install rule, removed some dead CMake code
- [PR #1433](#)⁵⁶⁸⁹ - Add `GitExternal` and `SubProject` cmake scripts from `eyescale/cmake` repo
- [Issue #1432](#)⁵⁶⁹⁰ - Add command line flag to disable thread pinning
- [PR #1431](#)⁵⁶⁹¹ - Fix #1423
- [Issue #1430](#)⁵⁶⁹² - Inconsistent CMake option names
- [Issue #1429](#)⁵⁶⁹³ - Configure setting `HPX_HAVE_PARCELPOR_MPI` is ignored
- [PR #1428](#)⁵⁶⁹⁴ - Fixes #1419 (closed)
- [PR #1427](#)⁵⁶⁹⁵ - Adding `stencil_iterator` and `transform_iterator`
- [PR #1426](#)⁵⁶⁹⁶ - Fixes #1419
- [PR #1425](#)⁵⁶⁹⁷ - During serialization memory allocation should honour allocator chunk size
- [Issue #1424](#)⁵⁶⁹⁸ - chunk allocation during serialization does not use memory pool/allocator chunk size
- [Issue #1423](#)⁵⁶⁹⁹ - Remove `HPX_STD_UNIQUE_PTR`
- [Issue #1422](#)⁵⁷⁰⁰ - `hpx:threads=all` allocates too many os threads

⁵⁶⁷⁸ <https://github.com/TheHPXProject/hpx/pull/1447>

⁵⁶⁷⁹ <https://github.com/TheHPXProject/hpx/pull/1446>

⁵⁶⁸⁰ <https://github.com/TheHPXProject/hpx/pull/1445>

⁵⁶⁸¹ <https://github.com/TheHPXProject/hpx/pull/1443>

⁵⁶⁸² <https://github.com/TheHPXProject/hpx/pull/1442>

⁵⁶⁸³ <https://github.com/TheHPXProject/hpx/issues/1439>

⁵⁶⁸⁴ <https://github.com/TheHPXProject/hpx/pull/1438>

⁵⁶⁸⁵ <https://github.com/TheHPXProject/hpx/issues/1437>

⁵⁶⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1436>

⁵⁶⁸⁷ <https://github.com/TheHPXProject/hpx/pull/1435>

⁵⁶⁸⁸ <https://github.com/TheHPXProject/hpx/pull/1434>

⁵⁶⁸⁹ <https://github.com/TheHPXProject/hpx/pull/1433>

⁵⁶⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1432>

⁵⁶⁹¹ <https://github.com/TheHPXProject/hpx/pull/1431>

⁵⁶⁹² <https://github.com/TheHPXProject/hpx/issues/1430>

⁵⁶⁹³ <https://github.com/TheHPXProject/hpx/issues/1429>

⁵⁶⁹⁴ <https://github.com/TheHPXProject/hpx/pull/1428>

⁵⁶⁹⁵ <https://github.com/TheHPXProject/hpx/pull/1427>

⁵⁶⁹⁶ <https://github.com/TheHPXProject/hpx/pull/1426>

⁵⁶⁹⁷ <https://github.com/TheHPXProject/hpx/pull/1425>

⁵⁶⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1424>

⁵⁶⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1423>

⁵⁷⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1422>

- PR #1420⁵⁷⁰¹ - added .travis.yml
- Issue #1419⁵⁷⁰² - Unify enums: `hpx::runtime::state` and `hpx::state`
- PR #1416⁵⁷⁰³ - Adding travis builder
- Issue #1414⁵⁷⁰⁴ - Correct directory for `dispatch_gcc46.hpp` iteration
- Issue #1410⁵⁷⁰⁵ - Set operation algorithms
- Issue #1389⁵⁷⁰⁶ - Parallel algorithms relying on scan partitioner break for small number of elements
- Issue #1325⁵⁷⁰⁷ - Exceptions thrown during parcel handling are not handled correctly
- Issue #1315⁵⁷⁰⁸ - Errors while running performance tests
- Issue #1309⁵⁷⁰⁹ - `hpx::vector` partitions are not easily extendable by applications
- PR #1300⁵⁷¹⁰ - Added serialization/de-serialization to `examples.tuplespace`
- Issue #1251⁵⁷¹¹ - `hpx::threads::get_thread_count` doesn't consider pending threads
- Issue #1008⁵⁷¹² - Decrease in application performance overtime; occasional spikes of major slowdown
- Issue #1001⁵⁷¹³ - Zero copy serialization raises assert
- Issue #721⁵⁷¹⁴ - Make HPX usable for Xeon Phi
- Issue #524⁵⁷¹⁵ - Extend scheduler to support threads which can't be stolen

HPX V0.9.10 (Mar 24, 2015)

General changes

This is the 12th official release of *HPX*. It coincides with the 7th anniversary of the first commit to our source code repository. Since then, we have seen over 12300 commits amounting to more than 220000 lines of C++ code.

The major focus of this release was to improve the reliability of large scale runs. We believe to have achieved this goal as we now can reliably run *HPX* applications on up to ~24k cores. We have also shown that HPX can be used with success for symmetric runs (applications using both, host cores and Intel Xeon/Phi coprocessors). This is a huge step forward in terms of the usability of *HPX*. The main focus of this work involved isolating the causes of the segmentation faults at start up and shut down. Many of these issues were discovered to be the result of the suspension of threads which hold locks.

A very important improvement introduced with this release is the refactoring of the code representing our parcel-port implementation. Parcel- ports can now be implemented by 3rd parties as independent plugins which are dynamically loaded at runtime (static linking of parcel-ports is also supported). This refactoring also includes a massive improvement of the performance of our existing parcel-ports. We were able to significantly reduce the networking latencies

⁵⁷⁰¹ <https://github.com/TheHPXProject/hpx/pull/1420>

⁵⁷⁰² <https://github.com/TheHPXProject/hpx/issues/1419>

⁵⁷⁰³ <https://github.com/TheHPXProject/hpx/pull/1416>

⁵⁷⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1414>

⁵⁷⁰⁵ <https://github.com/TheHPXProject/hpx/issues/1410>

⁵⁷⁰⁶ <https://github.com/TheHPXProject/hpx/issues/1389>

⁵⁷⁰⁷ <https://github.com/TheHPXProject/hpx/issues/1325>

⁵⁷⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1315>

⁵⁷⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1309>

⁵⁷¹⁰ <https://github.com/TheHPXProject/hpx/pull/1300>

⁵⁷¹¹ <https://github.com/TheHPXProject/hpx/issues/1251>

⁵⁷¹² <https://github.com/TheHPXProject/hpx/issues/1008>

⁵⁷¹³ <https://github.com/TheHPXProject/hpx/issues/1001>

⁵⁷¹⁴ <https://github.com/TheHPXProject/hpx/issues/721>

⁵⁷¹⁵ <https://github.com/TheHPXProject/hpx/issues/524>

and to improve the available networking bandwidth. Please note that in this release we disabled the `ibverbs` and `ipc` parcel ports as those have not been ported to the new plugin system yet (see [Issue #839](#)⁵⁷¹⁶).

Another corner stone of this release is our work towards a complete implementation of `__cpp11_n4104__` (Working Draft, Technical Specification for C++ Extensions for Parallelism). This document defines a set of parallel algorithms to be added to the C++ standard library. We now have implemented about 75% of all specified parallel algorithms (see [[link hpx.manual.parallel.parallel_algorithms](#) Parallel Algorithms] for more details). We also implemented some extensions to `__cpp11_n4104__` allowing to invoke all of the algorithms asynchronously.

This release adds a first implementation of `hpx::vector` which is a distributed data structure closely aligned to the functionality of `std::vector`. The difference is that `hpx::vector` stores the data in partitions where the partitions can be distributed over different localities. We started to work on allowing to use the parallel algorithms with `hpx::vector`. At this point we have implemented only a few of the parallel algorithms to support distributed data structures (like `hpx::vector`) for testing purposes (see [Issue #1338](#)⁵⁷¹⁷ for a documentation of our progress).

Breaking changes

With this release we put a lot of effort into changing the code base to be more compatible to C++11. These changes have caused the following issues for backward compatibility:

- **Move to Variadics**- All of the API now uses variadic templates. However, this change required to modify the argument sequence for some of the exiting API functions (`hpx::async_continue`, `hpx::apply_continue`, `hpx::when_each`, `hpx::wait_each`, synchronous invocation of actions).
- **Changes to Macros**- We also removed the macros `HPX_STD_FUNCTION` and `HPX_STD_TUPLE`. This shouldn't affect any user code as we replaced `HPX_STD_FUNCTION` with `hpx::util::function_nonser` which was the default expansion used for this macro. All `HPX` API functions which expect a `hpx::util::function_nonser` (or a `hpx::util::unique_function_nonser`) can now be transparently called with a compatible `std::function` instead. Similarly, `HPX_STD_TUPLE` was replaced by its default expansion as well: `hpx::util::tuple`.
- **Changes to `hpx::unique_future`**- `hpx::unique_future`, which was deprecated in the previous release for `hpx::future` is now completely removed from `HPX`. This completes the transition to a completely standards conforming implementation of `hpx::future`.
- **Changes to Supported Compilers**. Finally, in order to utilize more C++11 semantics, we have officially dropped support for GCC 4.4 and MSVC 2012. Please see our *Prerequisites* page for more details.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [Issue #1402](#)⁵⁷¹⁸ - Internal `shared_future` serialization copies
- [Issue #1399](#)⁵⁷¹⁹ - Build takes unusually long time...
- [Issue #1398](#)⁵⁷²⁰ - Tests using the scan partitioner are broken on at least gcc 4.7 and intel compiler
- [Issue #1397](#)⁵⁷²¹ - Completely remove `hpx::unique_future`
- [Issue #1396](#)⁵⁷²² - Parallel scan algorithms with different initial values

⁵⁷¹⁶ <https://github.com/TheHPXProject/hpx/issues/839>

⁵⁷¹⁷ <https://github.com/TheHPXProject/hpx/issues/1338>

⁵⁷¹⁸ <https://github.com/TheHPXProject/hpx/issues/1402>

⁵⁷¹⁹ <https://github.com/TheHPXProject/hpx/issues/1399>

⁵⁷²⁰ <https://github.com/TheHPXProject/hpx/issues/1398>

⁵⁷²¹ <https://github.com/TheHPXProject/hpx/issues/1397>

⁵⁷²² <https://github.com/TheHPXProject/hpx/issues/1396>

- Issue #1395⁵⁷²³ - Race Condition - 1d_stencil_8 - SuperMIC
- Issue #1394⁵⁷²⁴ - “suspending thread while at least one lock is being held” - 1d_stencil_8 - SuperMIC
- Issue #1393⁵⁷²⁵ - SEGFAULT in 1d_stencil_8 on SuperMIC
- Issue #1392⁵⁷²⁶ - Fixing #1168
- Issue #1391⁵⁷²⁷ - Parallel Algorithms for scan partitioner for small number of elements
- Issue #1387⁵⁷²⁸ - Failure with more than 4 localities
- Issue #1386⁵⁷²⁹ - Dispatching unhandled exceptions to outer user code
- Issue #1385⁵⁷³⁰ - Adding Copy algorithms, fixing `parallel::copy_if`
- Issue #1384⁵⁷³¹ - Fixing 1325
- Issue #1383⁵⁷³² - Fixed #504: Refactor Dataflow LCO to work with futures, this removes the dataflow component as it is obsolete
- Issue #1382⁵⁷³³ - `is_sorted`, `is_sorted_until` and `is_partitioned` algorithms
- Issue #1381⁵⁷³⁴ - fix for CMake versions prior to 3.1
- Issue #1380⁵⁷³⁵ - resolved warning in CMake 3.1 and newer
- Issue #1379⁵⁷³⁶ - Compilation error with papi
- Issue #1378⁵⁷³⁷ - Towards safer migration
- Issue #1377⁵⁷³⁸ - HPXConfig.cmake should include `TCMALLOC_LIBRARY` and `TCMALLOC_INCLUDE_DIR`
- Issue #1376⁵⁷³⁹ - Warning on uninitialized member
- Issue #1375⁵⁷⁴⁰ - Fixing 1163
- Issue #1374⁵⁷⁴¹ - Fixing the MSVC 12 release builder
- Issue #1373⁵⁷⁴² - Modifying parallel search algorithm for zero length searches
- Issue #1372⁵⁷⁴³ - Modifying parallel search algorithm for zero length searches
- Issue #1371⁵⁷⁴⁴ - Avoid holding a lock during `agas::incf` while doing a credit split
- Issue #1370⁵⁷⁴⁵ - `--hpx:bind` throws unexpected error

⁵⁷²³ <https://github.com/TheHPXProject/hpx/issues/1395>

⁵⁷²⁴ <https://github.com/TheHPXProject/hpx/issues/1394>

⁵⁷²⁵ <https://github.com/TheHPXProject/hpx/issues/1393>

⁵⁷²⁶ <https://github.com/TheHPXProject/hpx/issues/1392>

⁵⁷²⁷ <https://github.com/TheHPXProject/hpx/issues/1391>

⁵⁷²⁸ <https://github.com/TheHPXProject/hpx/issues/1387>

⁵⁷²⁹ <https://github.com/TheHPXProject/hpx/issues/1386>

⁵⁷³⁰ <https://github.com/TheHPXProject/hpx/issues/1385>

⁵⁷³¹ <https://github.com/TheHPXProject/hpx/issues/1384>

⁵⁷³² <https://github.com/TheHPXProject/hpx/issues/1383>

⁵⁷³³ <https://github.com/TheHPXProject/hpx/issues/1382>

⁵⁷³⁴ <https://github.com/TheHPXProject/hpx/issues/1381>

⁵⁷³⁵ <https://github.com/TheHPXProject/hpx/issues/1380>

⁵⁷³⁶ <https://github.com/TheHPXProject/hpx/issues/1379>

⁵⁷³⁷ <https://github.com/TheHPXProject/hpx/issues/1378>

⁵⁷³⁸ <https://github.com/TheHPXProject/hpx/issues/1377>

⁵⁷³⁹ <https://github.com/TheHPXProject/hpx/issues/1376>

⁵⁷⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1375>

⁵⁷⁴¹ <https://github.com/TheHPXProject/hpx/issues/1374>

⁵⁷⁴² <https://github.com/TheHPXProject/hpx/issues/1373>

⁵⁷⁴³ <https://github.com/TheHPXProject/hpx/issues/1372>

⁵⁷⁴⁴ <https://github.com/TheHPXProject/hpx/issues/1371>

⁵⁷⁴⁵ <https://github.com/TheHPXProject/hpx/issues/1370>

- Issue #1369⁵⁷⁴⁶ - Getting rid of (void) in loops
- Issue #1368⁵⁷⁴⁷ - Variadic templates support for tuple
- Issue #1367⁵⁷⁴⁸ - One last batch of variadic templates support
- Issue #1366⁵⁷⁴⁹ - Fixing symbolic namespace hang
- Issue #1365⁵⁷⁵⁰ - More held locks
- Issue #1364⁵⁷⁵¹ - Add counters 1363
- Issue #1363⁵⁷⁵² - Add thread overhead counters
- Issue #1362⁵⁷⁵³ - Std config removal
- Issue #1361⁵⁷⁵⁴ - Parcelport plugins
- Issue #1360⁵⁷⁵⁵ - Detuplify transfer_action
- Issue #1359⁵⁷⁵⁶ - Removed obsolete checks
- Issue #1358⁵⁷⁵⁷ - Fixing 1352
- Issue #1357⁵⁷⁵⁸ - Variadic templates support for runtime_support and components
- Issue #1356⁵⁷⁵⁹ - fixed coordinate test for intel13
- Issue #1355⁵⁷⁶⁰ - fixed coordinate.hpp
- Issue #1354⁵⁷⁶¹ - Lexicographical Compare completed
- Issue #1353⁵⁷⁶² - HPX should set Boost_ADDITIONAL_VERSIONS flags
- Issue #1352⁵⁷⁶³ - Error: Cannot find action “ in type registry: HPX(bad_action_code)
- Issue #1351⁵⁷⁶⁴ - Variadic templates support for appliers
- Issue #1350⁵⁷⁶⁵ - Actions simplification
- Issue #1349⁵⁷⁶⁶ - Variadic when and wait functions
- Issue #1348⁵⁷⁶⁷ - Added hpx_init header to test files
- Issue #1347⁵⁷⁶⁸ - Another batch of variadic templates support

⁵⁷⁴⁶ <https://github.com/TheHPXProject/hpx/issues/1369>

⁵⁷⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1368>

⁵⁷⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1367>

⁵⁷⁴⁹ <https://github.com/TheHPXProject/hpx/issues/1366>

⁵⁷⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1365>

⁵⁷⁵¹ <https://github.com/TheHPXProject/hpx/issues/1364>

⁵⁷⁵² <https://github.com/TheHPXProject/hpx/issues/1363>

⁵⁷⁵³ <https://github.com/TheHPXProject/hpx/issues/1362>

⁵⁷⁵⁴ <https://github.com/TheHPXProject/hpx/issues/1361>

⁵⁷⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1360>

⁵⁷⁵⁶ <https://github.com/TheHPXProject/hpx/issues/1359>

⁵⁷⁵⁷ <https://github.com/TheHPXProject/hpx/issues/1358>

⁵⁷⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1357>

⁵⁷⁵⁹ <https://github.com/TheHPXProject/hpx/issues/1356>

⁵⁷⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1355>

⁵⁷⁶¹ <https://github.com/TheHPXProject/hpx/issues/1354>

⁵⁷⁶² <https://github.com/TheHPXProject/hpx/issues/1353>

⁵⁷⁶³ <https://github.com/TheHPXProject/hpx/issues/1352>

⁵⁷⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1351>

⁵⁷⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1350>

⁵⁷⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1349>

⁵⁷⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1348>

⁵⁷⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1347>

- Issue #1346⁵⁷⁶⁹ - Segmented copy
- Issue #1345⁵⁷⁷⁰ - Attempting to fix hangs during shutdown
- Issue #1344⁵⁷⁷¹ - Std config removal
- Issue #1343⁵⁷⁷² - Removing various distribution policies for `hpx::vector`
- Issue #1342⁵⁷⁷³ - Inclusive scan
- Issue #1341⁵⁷⁷⁴ - Exclusive scan
- Issue #1340⁵⁷⁷⁵ - Adding `parallel::count` for distributed data structures, adding tests
- Issue #1339⁵⁷⁷⁶ - Update argument order for `transform_reduce`
- Issue #1337⁵⁷⁷⁷ - Fix dataflow to handle properly ranges of futures
- Issue #1336⁵⁷⁷⁸ - dataflow needs to hold onto futures passed to it
- Issue #1335⁵⁷⁷⁹ - Fails to compile with `msvc14`
- Issue #1334⁵⁷⁸⁰ - Examples build problem
- Issue #1333⁵⁷⁸¹ - Distributed transform reduce
- Issue #1332⁵⁷⁸² - Variadic templates support for actions
- Issue #1331⁵⁷⁸³ - Some ambiguous calls of `map::erase` have been prevented by adding additional check in locality constructor.
- Issue #1330⁵⁷⁸⁴ - Defining Plain Actions does not work as described in the documentation
- Issue #1329⁵⁷⁸⁵ - Distributed vector cleanup
- Issue #1328⁵⁷⁸⁶ - Sync docs and comments with code in `hello_world` example
- Issue #1327⁵⁷⁸⁷ - Typos in docs
- Issue #1326⁵⁷⁸⁸ - Documentation and code diverged in Fibonacci tutorial
- Issue #1325⁵⁷⁸⁹ - Exceptions thrown during parcel handling are not handled correctly
- Issue #1324⁵⁷⁹⁰ - fixed bandwidth calculation
- Issue #1323⁵⁷⁹¹ - `mmap()` failed to allocate thread stack due to insufficient resources

⁵⁷⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1346>

⁵⁷⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1345>

⁵⁷⁷¹ <https://github.com/TheHPXProject/hpx/issues/1344>

⁵⁷⁷² <https://github.com/TheHPXProject/hpx/issues/1343>

⁵⁷⁷³ <https://github.com/TheHPXProject/hpx/issues/1342>

⁵⁷⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1341>

⁵⁷⁷⁵ <https://github.com/TheHPXProject/hpx/issues/1340>

⁵⁷⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1339>

⁵⁷⁷⁷ <https://github.com/TheHPXProject/hpx/issues/1337>

⁵⁷⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1336>

⁵⁷⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1335>

⁵⁷⁸⁰ <https://github.com/TheHPXProject/hpx/issues/1334>

⁵⁷⁸¹ <https://github.com/TheHPXProject/hpx/issues/1333>

⁵⁷⁸² <https://github.com/TheHPXProject/hpx/issues/1332>

⁵⁷⁸³ <https://github.com/TheHPXProject/hpx/issues/1331>

⁵⁷⁸⁴ <https://github.com/TheHPXProject/hpx/issues/1330>

⁵⁷⁸⁵ <https://github.com/TheHPXProject/hpx/issues/1329>

⁵⁷⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1328>

⁵⁷⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1327>

⁵⁷⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1326>

⁵⁷⁸⁹ <https://github.com/TheHPXProject/hpx/issues/1325>

⁵⁷⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1324>

⁵⁷⁹¹ <https://github.com/TheHPXProject/hpx/issues/1323>

- [Issue #1322⁵⁷⁹²](#) - HPX fails to build aa182cf
- [Issue #1321⁵⁷⁹³](#) - Limiting size of outgoing messages while coalescing parcels
- [Issue #1320⁵⁷⁹⁴](#) - passing a future with `launch::deferred` in remote function call causes hang
- [Issue #1319⁵⁷⁹⁵](#) - An exception when tries to specify number high priority threads with `abp-priority`
- [Issue #1318⁵⁷⁹⁶](#) - Unable to run program with `abp-priority` and `numa-sensitivity` enabled
- [Issue #1317⁵⁷⁹⁷](#) - N4071 `Search/Search_n` finished, minor changes
- [Issue #1316⁵⁷⁹⁸](#) - Add config option to make `-lhp.run_hpx_main!=1` the default
- [Issue #1314⁵⁷⁹⁹](#) - Variadic support for `async` and `apply`
- [Issue #1313⁵⁸⁰⁰](#) - Adjust `when_any/some` to the latest proposed interfaces
- [Issue #1312⁵⁸⁰¹](#) - Fixing #857: `hpx::naming::locality` leaks `parcelport` specific information into the public interface
- [Issue #1311⁵⁸⁰²](#) - Distributed `get'er/set'er_values` for distributed vector
- [Issue #1310⁵⁸⁰³](#) - Crashing in `hpx::parcelset::policies::mpi::connection_handler::handle_messages()` on Super-MIC
- [Issue #1308⁵⁸⁰⁴](#) - Unable to execute an application with `-hpx:threads`
- [Issue #1307⁵⁸⁰⁵](#) - `merge_graph` linking issue
- [Issue #1306⁵⁸⁰⁶](#) - First batch of variadic templates support
- [Issue #1305⁵⁸⁰⁷](#) - Create a compiler wrapper
- [Issue #1304⁵⁸⁰⁸](#) - Provide a compiler wrapper for `hpx`
- [Issue #1303⁵⁸⁰⁹](#) - Drop support for GCC44
- [Issue #1302⁵⁸¹⁰](#) - Fixing #1297
- [Issue #1301⁵⁸¹¹](#) - Compilation error when tried to use `boost range` iterators with `wait_all`
- [Issue #1298⁵⁸¹²](#) - Distributed vector
- [Issue #1297⁵⁸¹³](#) - Unable to invoke component actions recursively

⁵⁷⁹² <https://github.com/TheHPXProject/hpx/issues/1322>

⁵⁷⁹³ <https://github.com/TheHPXProject/hpx/issues/1321>

⁵⁷⁹⁴ <https://github.com/TheHPXProject/hpx/issues/1320>

⁵⁷⁹⁵ <https://github.com/TheHPXProject/hpx/issues/1319>

⁵⁷⁹⁶ <https://github.com/TheHPXProject/hpx/issues/1318>

⁵⁷⁹⁷ <https://github.com/TheHPXProject/hpx/issues/1317>

⁵⁷⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1316>

⁵⁷⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1314>

⁵⁸⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1313>

⁵⁸⁰¹ <https://github.com/TheHPXProject/hpx/issues/1312>

⁵⁸⁰² <https://github.com/TheHPXProject/hpx/issues/1311>

⁵⁸⁰³ <https://github.com/TheHPXProject/hpx/issues/1310>

⁵⁸⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1308>

⁵⁸⁰⁵ <https://github.com/TheHPXProject/hpx/issues/1307>

⁵⁸⁰⁶ <https://github.com/TheHPXProject/hpx/issues/1306>

⁵⁸⁰⁷ <https://github.com/TheHPXProject/hpx/issues/1305>

⁵⁸⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1304>

⁵⁸⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1303>

⁵⁸¹⁰ <https://github.com/TheHPXProject/hpx/issues/1302>

⁵⁸¹¹ <https://github.com/TheHPXProject/hpx/issues/1301>

⁵⁸¹² <https://github.com/TheHPXProject/hpx/issues/1298>

⁵⁸¹³ <https://github.com/TheHPXProject/hpx/issues/1297>

- Issue #1294⁵⁸¹⁴ - HDF5 build error
- Issue #1275⁵⁸¹⁵ - The parcelport implementation is non-optimal
- Issue #1267⁵⁸¹⁶ - Added classes and unit tests for local_file, orangefs_file and pxfs_file
- Issue #1264⁵⁸¹⁷ - Error “assertion ‘!m_fun’ failed” randomly occurs when using TCP
- Issue #1254⁵⁸¹⁸ - thread binding seems to not work properly
- Issue #1220⁵⁸¹⁹ - parallel::copy_if is broken
- Issue #1217⁵⁸²⁰ - Find a better way of fixing the issue patched by #1216
- Issue #1168⁵⁸²¹ - Starting HPX on Cray machines using aprun isn’t working correctly
- Issue #1085⁵⁸²² - Replace startup and shutdown barriers with broadcasts
- Issue #981⁵⁸²³ - With SLURM, -hpx:threads=8 should not be necessary
- Issue #857⁵⁸²⁴ - hpx::naming::locality leaks parcelport specific information into the public interface
- Issue #850⁵⁸²⁵ - “flush” not documented
- Issue #763⁵⁸²⁶ - Create buildbot instance that uses std::bind as HPX_STD_BIND
- Issue #680⁵⁸²⁷ - Convert parcel ports into a plugin system
- Issue #582⁵⁸²⁸ - Make exception thrown from HPX threads available from hpx::init
- Issue #504⁵⁸²⁹ - Refactor Dataflow LCO to work with futures
- Issue #196⁵⁸³⁰ - Don’t store copies of the locality network metadata in the gva table

HPX V0.9.9 (Oct 31, 2014, codename Spooky)

General changes

We have had over 1500 commits since the last release and we have closed over 200 tickets (bugs, feature requests, pull requests, etc.). These are by far the largest numbers of commits and resolved issues for any of the *HPX* releases so far. We are especially happy about the large number of people who contributed for the first time to *HPX*.

- We completed the transition from the older (non-conforming) implementation of `hpx::future` to the new and fully conforming version by removing the old code and by renaming the type `hpx::unique_future` to `hpx::future`. In order to maintain backwards compatibility with existing code which uses the type `hpx::unique_future` we support the configuration variable `HPX_UNIQUE_FUTURE_ALIAS`. If this variable is set to ON while running cmake it will additionally define a template alias for this type.

⁵⁸¹⁴ <https://github.com/TheHPXProject/hpx/issues/1294>

⁵⁸¹⁵ <https://github.com/TheHPXProject/hpx/issues/1275>

⁵⁸¹⁶ <https://github.com/TheHPXProject/hpx/issues/1267>

⁵⁸¹⁷ <https://github.com/TheHPXProject/hpx/issues/1264>

⁵⁸¹⁸ <https://github.com/TheHPXProject/hpx/issues/1254>

⁵⁸¹⁹ <https://github.com/TheHPXProject/hpx/issues/1220>

⁵⁸²⁰ <https://github.com/TheHPXProject/hpx/issues/1217>

⁵⁸²¹ <https://github.com/TheHPXProject/hpx/issues/1168>

⁵⁸²² <https://github.com/TheHPXProject/hpx/issues/1085>

⁵⁸²³ <https://github.com/TheHPXProject/hpx/issues/981>

⁵⁸²⁴ <https://github.com/TheHPXProject/hpx/issues/857>

⁵⁸²⁵ <https://github.com/TheHPXProject/hpx/issues/850>

⁵⁸²⁶ <https://github.com/TheHPXProject/hpx/issues/763>

⁵⁸²⁷ <https://github.com/TheHPXProject/hpx/issues/680>

⁵⁸²⁸ <https://github.com/TheHPXProject/hpx/issues/582>

⁵⁸²⁹ <https://github.com/TheHPXProject/hpx/issues/504>

⁵⁸³⁰ <https://github.com/TheHPXProject/hpx/issues/196>

- We rewrote and significantly changed our build system. Please have a look at the new (now generated) documentation here: *Building HPX*. Please revisit your build scripts to adapt to the changes. The most notable changes are:
 - HPX_NO_INSTALL is no longer necessary.
 - For external builds, you need to set HPX_DIR instead of HPX_ROOT as described here: *Using HPX with CMake-based projects*.
 - IDEs that support multiple configurations (Visual Studio and XCode) can now be used as intended. that means no build dir.
 - Building HPX statically (without dynamic libraries) is now supported (-DHPX_STATIC_LINKING=On).
 - Please note that many variables used to configure the build process have been renamed to unify the naming conventions (see the section *CMake options* for more information).
 - This also fixes a long list of issues, for more information see [Issue #1204](#)⁵⁸³¹.
- We started to implement various proposals to the C++ Standardization committee related to parallelism and concurrency, most notably [N4409](#)⁵⁸³² (Working Draft, Technical Specification for C++ Extensions for Parallelism), [N4411](#)⁵⁸³³ (Task Region Rev. 3), and [N4313](#)⁵⁸³⁴ (Working Draft, Technical Specification for C++ Extensions for Concurrency).
- We completely remodeled our automatic build system to run builds and unit tests on various systems and compilers. This allows us to find most bugs right as they were introduced and helps to maintain a high level of quality and compatibility. The newest build logs can be found at [HPX Buildbot Website](#)⁵⁸³⁵.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [Issue #1296](#)⁵⁸³⁶ - Rename make_error_future to make_exceptional_future, adjust to N4123
- [Issue #1295](#)⁵⁸³⁷ - building issue
- [Issue #1293](#)⁵⁸³⁸ - Transpose example
- [Issue #1292](#)⁵⁸³⁹ - Wrong abs() function used in example
- [Issue #1291](#)⁵⁸⁴⁰ - non-synchronized shift operators have been removed
- [Issue #1290](#)⁵⁸⁴¹ - RDTSCP is defined as true for Xeon Phi build
- [Issue #1289](#)⁵⁸⁴² - Fixing 1288
- [Issue #1288](#)⁵⁸⁴³ - Add new performance counters
- [Issue #1287](#)⁵⁸⁴⁴ - Hierarchy scheduler broken performance counters

⁵⁸³¹ <https://github.com/TheHPXProject/hpx/issues/1204>

⁵⁸³² <http://wg21.link/n4409>

⁵⁸³³ <http://wg21.link/n4411>

⁵⁸³⁴ <http://wg21.link/n4313>

⁵⁸³⁵ <http://roostam.cct.lsu.edu/>

⁵⁸³⁶ <https://github.com/TheHPXProject/hpx/issues/1296>

⁵⁸³⁷ <https://github.com/TheHPXProject/hpx/issues/1295>

⁵⁸³⁸ <https://github.com/TheHPXProject/hpx/issues/1293>

⁵⁸³⁹ <https://github.com/TheHPXProject/hpx/issues/1292>

⁵⁸⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1291>

⁵⁸⁴¹ <https://github.com/TheHPXProject/hpx/issues/1290>

⁵⁸⁴² <https://github.com/TheHPXProject/hpx/issues/1289>

⁵⁸⁴³ <https://github.com/TheHPXProject/hpx/issues/1288>

⁵⁸⁴⁴ <https://github.com/TheHPXProject/hpx/issues/1287>

- Issue #1286⁵⁸⁴⁵ - Algorithm cleanup
- Issue #1285⁵⁸⁴⁶ - Broken Links in Documentation
- Issue #1284⁵⁸⁴⁷ - Uninitialized copy
- Issue #1283⁵⁸⁴⁸ - missing boost::scoped_ptr includes
- Issue #1282⁵⁸⁴⁹ - Update documentation of build options for schedulers
- Issue #1281⁵⁸⁵⁰ - reset idle rate counter
- Issue #1280⁵⁸⁵¹ - Bug when executing on Intel MIC
- Issue #1279⁵⁸⁵² - Add improved when_all/wait_all
- Issue #1278⁵⁸⁵³ - Implement improved when_all/wait_all
- Issue #1277⁵⁸⁵⁴ - feature request: get access to argc argv and variables_map
- Issue #1276⁵⁸⁵⁵ - Remove merging map
- Issue #1274⁵⁸⁵⁶ - Weird (wrong) string code in papi.cpp
- Issue #1273⁵⁸⁵⁷ - Sequential task execution policy
- Issue #1272⁵⁸⁵⁸ - Avoid CMake name clash for Boost.Thread library
- Issue #1271⁵⁸⁵⁹ - Updates on HPX Test Units
- Issue #1270⁵⁸⁶⁰ - hpx/util/safe_lexical_cast.hpp is added
- Issue #1269⁵⁸⁶¹ - Added default value for “LIB” cmake variable
- Issue #1268⁵⁸⁶² - Memory Counters not working
- Issue #1266⁵⁸⁶³ - FindHPX.cmake is not installed
- Issue #1263⁵⁸⁶⁴ - apply_remote test takes too long
- Issue #1262⁵⁸⁶⁵ - Chrono cleanup
- Issue #1261⁵⁸⁶⁶ - Need make install for papi counters and this builds all the examples
- Issue #1260⁵⁸⁶⁷ - Documentation of Stencil example claims

⁵⁸⁴⁵ <https://github.com/TheHPXProject/hpx/issues/1286>

⁵⁸⁴⁶ <https://github.com/TheHPXProject/hpx/issues/1285>

⁵⁸⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1284>

⁵⁸⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1283>

⁵⁸⁴⁹ <https://github.com/TheHPXProject/hpx/issues/1282>

⁵⁸⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1281>

⁵⁸⁵¹ <https://github.com/TheHPXProject/hpx/issues/1280>

⁵⁸⁵² <https://github.com/TheHPXProject/hpx/issues/1279>

⁵⁸⁵³ <https://github.com/TheHPXProject/hpx/issues/1278>

⁵⁸⁵⁴ <https://github.com/TheHPXProject/hpx/issues/1277>

⁵⁸⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1276>

⁵⁸⁵⁶ <https://github.com/TheHPXProject/hpx/issues/1274>

⁵⁸⁵⁷ <https://github.com/TheHPXProject/hpx/issues/1273>

⁵⁸⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1272>

⁵⁸⁵⁹ <https://github.com/TheHPXProject/hpx/issues/1271>

⁵⁸⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1270>

⁵⁸⁶¹ <https://github.com/TheHPXProject/hpx/issues/1269>

⁵⁸⁶² <https://github.com/TheHPXProject/hpx/issues/1268>

⁵⁸⁶³ <https://github.com/TheHPXProject/hpx/issues/1266>

⁵⁸⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1263>

⁵⁸⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1262>

⁵⁸⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1261>

⁵⁸⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1260>

- [Issue #1259⁵⁸⁶⁸](#) - Avoid double-linking Boost on Windows
- [Issue #1257⁵⁸⁶⁹](#) - Adding additional parameter to create_thread
- [Issue #1256⁵⁸⁷⁰](#) - added buildbot changes to release notes
- [Issue #1255⁵⁸⁷¹](#) - Cannot build MiniGhost
- [Issue #1253⁵⁸⁷²](#) - hpx::thread defects
- [Issue #1252⁵⁸⁷³](#) - HPX_PREFIX is too fragile
- [Issue #1250⁵⁸⁷⁴](#) - switch_to_fiber_emulation does not work properly
- [Issue #1249⁵⁸⁷⁵](#) - Documentation is generated under Release folder
- [Issue #1248⁵⁸⁷⁶](#) - Fix usage of hpx_generic_coroutine_context and get tests passing on powerpc
- [Issue #1247⁵⁸⁷⁷](#) - Dynamic linking error
- [Issue #1246⁵⁸⁷⁸](#) - Make cpuid.cpp C++11 compliant
- [Issue #1245⁵⁸⁷⁹](#) - HPX fails on startup (setting thread affinity mask)
- [Issue #1244⁵⁸⁸⁰](#) - HPX_WITH_RDTSC configure test fails, but should succeed
- [Issue #1243⁵⁸⁸¹](#) - CTest dashboard info for CSCS CDash drop location
- [Issue #1242⁵⁸⁸²](#) - Mac fixes
- [Issue #1241⁵⁸⁸³](#) - Failure in Distributed with Boost 1.56
- [Issue #1240⁵⁸⁸⁴](#) - fix a race condition in examples.diskperf
- [Issue #1239⁵⁸⁸⁵](#) - fix wait_each in examples.diskperf
- [Issue #1238⁵⁸⁸⁶](#) - Fixed #1237: hpx::util::portable_binary_iarchive failed
- [Issue #1237⁵⁸⁸⁷](#) - hpx::util::portable_binary_iarchive faileds
- [Issue #1235⁵⁸⁸⁸](#) - Fixing clang warnings and errors
- [Issue #1234⁵⁸⁸⁹](#) - TCP runs fail: Transport endpoint is not connected
- [Issue #1233⁵⁸⁹⁰](#) - Making sure the correct number of threads is registered with AGAS

⁵⁸⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1259>

⁵⁸⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1257>

⁵⁸⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1256>

⁵⁸⁷¹ <https://github.com/TheHPXProject/hpx/issues/1255>

⁵⁸⁷² <https://github.com/TheHPXProject/hpx/issues/1253>

⁵⁸⁷³ <https://github.com/TheHPXProject/hpx/issues/1252>

⁵⁸⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1250>

⁵⁸⁷⁵ <https://github.com/TheHPXProject/hpx/issues/1249>

⁵⁸⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1248>

⁵⁸⁷⁷ <https://github.com/TheHPXProject/hpx/issues/1247>

⁵⁸⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1246>

⁵⁸⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1245>

⁵⁸⁸⁰ <https://github.com/TheHPXProject/hpx/issues/1244>

⁵⁸⁸¹ <https://github.com/TheHPXProject/hpx/issues/1243>

⁵⁸⁸² <https://github.com/TheHPXProject/hpx/issues/1242>

⁵⁸⁸³ <https://github.com/TheHPXProject/hpx/issues/1241>

⁵⁸⁸⁴ <https://github.com/TheHPXProject/hpx/issues/1240>

⁵⁸⁸⁵ <https://github.com/TheHPXProject/hpx/issues/1239>

⁵⁸⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1238>

⁵⁸⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1237>

⁵⁸⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1235>

⁵⁸⁸⁹ <https://github.com/TheHPXProject/hpx/issues/1234>

⁵⁸⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1233>

- Issue #1232⁵⁸⁹¹ - Fixing race in wait_XXX
- Issue #1231⁵⁸⁹² - Parallel minmax
- Issue #1230⁵⁸⁹³ - Distributed run of 1d_stencil_8 uses less threads than spec. & sometimes gives errors
- Issue #1229⁵⁸⁹⁴ - Unstable number of threads
- Issue #1228⁵⁸⁹⁵ - HPX link error (cmake / MPI)
- Issue #1226⁵⁸⁹⁶ - Warning about struct/class thread_counters
- Issue #1225⁵⁸⁹⁷ - Adding parallel::replace etc
- Issue #1224⁵⁸⁹⁸ - Extending dataflow to pass through non-future arguments
- Issue #1223⁵⁸⁹⁹ - Remaining find algorithms implemented, N4071
- Issue #1222⁵⁹⁰⁰ - Merging all the changes
- Issue #1221⁵⁹⁰¹ - No error output when using mpirun with hpx
- Issue #1219⁵⁹⁰² - Adding new AGAS cache performance counters
- Issue #1216⁵⁹⁰³ - Fixing using futures (clients) as arguments to actions
- Issue #1215⁵⁹⁰⁴ - Error compiling simple component
- Issue #1214⁵⁹⁰⁵ - Stencil docs
- Issue #1213⁵⁹⁰⁶ - Using more than a few dozen MPI processes on SuperMike results in a seg fault before getting to hpx_main
- Issue #1212⁵⁹⁰⁷ - Parallel rotate
- Issue #1211⁵⁹⁰⁸ - Direct actions cause the future's shared_state to be leaked
- Issue #1210⁵⁹⁰⁹ - Refactored local::promise to be standard conformant
- Issue #1209⁵⁹¹⁰ - Improve command line handling
- Issue #1208⁵⁹¹¹ - Adding parallel::reverse and parallel::reverse_copy
- Issue #1207⁵⁹¹² - Add copy_backward and move_backward
- Issue #1206⁵⁹¹³ - N4071 additional algorithms implemented

⁵⁸⁹¹ <https://github.com/TheHPXProject/hpx/issues/1232>

⁵⁸⁹² <https://github.com/TheHPXProject/hpx/issues/1231>

⁵⁸⁹³ <https://github.com/TheHPXProject/hpx/issues/1230>

⁵⁸⁹⁴ <https://github.com/TheHPXProject/hpx/issues/1229>

⁵⁸⁹⁵ <https://github.com/TheHPXProject/hpx/issues/1228>

⁵⁸⁹⁶ <https://github.com/TheHPXProject/hpx/issues/1226>

⁵⁸⁹⁷ <https://github.com/TheHPXProject/hpx/issues/1225>

⁵⁸⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1224>

⁵⁸⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1223>

⁵⁹⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1222>

⁵⁹⁰¹ <https://github.com/TheHPXProject/hpx/issues/1221>

⁵⁹⁰² <https://github.com/TheHPXProject/hpx/issues/1219>

⁵⁹⁰³ <https://github.com/TheHPXProject/hpx/issues/1216>

⁵⁹⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1215>

⁵⁹⁰⁵ <https://github.com/TheHPXProject/hpx/issues/1214>

⁵⁹⁰⁶ <https://github.com/TheHPXProject/hpx/issues/1213>

⁵⁹⁰⁷ <https://github.com/TheHPXProject/hpx/issues/1212>

⁵⁹⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1211>

⁵⁹⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1210>

⁵⁹¹⁰ <https://github.com/TheHPXProject/hpx/issues/1209>

⁵⁹¹¹ <https://github.com/TheHPXProject/hpx/issues/1208>

⁵⁹¹² <https://github.com/TheHPXProject/hpx/issues/1207>

⁵⁹¹³ <https://github.com/TheHPXProject/hpx/issues/1206>

- [Issue #1204⁵⁹¹⁴](#) - Cmake simplification and various other minor changes
- [Issue #1203⁵⁹¹⁵](#) - Implementing new launch policy for (local) `async: hpx::launch::fork`.
- [Issue #1202⁵⁹¹⁶](#) - Failed assertion in `connection_cache.hpp`
- [Issue #1201⁵⁹¹⁷](#) - `pkg-config` doesn't add `mpi` link directories
- [Issue #1200⁵⁹¹⁸](#) - Error when querying time performance counters
- [Issue #1199⁵⁹¹⁹](#) - library path is now configurable (again)
- [Issue #1198⁵⁹²⁰](#) - Error when querying performance counters
- [Issue #1197⁵⁹²¹](#) - tests fail with intel compiler
- [Issue #1196⁵⁹²²](#) - Silence several warnings
- [Issue #1195⁵⁹²³](#) - Rephrase initializers to work with VC++ 2012
- [Issue #1194⁵⁹²⁴](#) - Simplify parallel algorithms
- [Issue #1193⁵⁹²⁵](#) - Adding `parallel::equal`
- [Issue #1192⁵⁹²⁶](#) - HPX(out_of_memory) on including `<hpx/hpx.hpp>`
- [Issue #1191⁵⁹²⁷](#) - Fixing #1189
- [Issue #1190⁵⁹²⁸](#) - Chrono cleanup
- [Issue #1189⁵⁹²⁹](#) - Deadlock .. somewhere? (probably serialization)
- [Issue #1188⁵⁹³⁰](#) - Removed `future::get_status()`
- [Issue #1186⁵⁹³¹](#) - Fixed FindOpenCL to find current AMD APP SDK
- [Issue #1184⁵⁹³²](#) - Tweaking future unwrapping
- [Issue #1183⁵⁹³³](#) - Extended `parallel::reduce`
- [Issue #1182⁵⁹³⁴](#) - `future::unwrap` hangs for `launch::deferred`
- [Issue #1181⁵⁹³⁵](#) - Adding `all_of`, `any_of`, and `none_of` and corresponding documentation
- [Issue #1180⁵⁹³⁶](#) - `hpx::cout` defect

⁵⁹¹⁴ <https://github.com/TheHPXProject/hpx/issues/1204>

⁵⁹¹⁵ <https://github.com/TheHPXProject/hpx/issues/1203>

⁵⁹¹⁶ <https://github.com/TheHPXProject/hpx/issues/1202>

⁵⁹¹⁷ <https://github.com/TheHPXProject/hpx/issues/1201>

⁵⁹¹⁸ <https://github.com/TheHPXProject/hpx/issues/1200>

⁵⁹¹⁹ <https://github.com/TheHPXProject/hpx/issues/1199>

⁵⁹²⁰ <https://github.com/TheHPXProject/hpx/issues/1198>

⁵⁹²¹ <https://github.com/TheHPXProject/hpx/issues/1197>

⁵⁹²² <https://github.com/TheHPXProject/hpx/issues/1196>

⁵⁹²³ <https://github.com/TheHPXProject/hpx/issues/1195>

⁵⁹²⁴ <https://github.com/TheHPXProject/hpx/issues/1194>

⁵⁹²⁵ <https://github.com/TheHPXProject/hpx/issues/1193>

⁵⁹²⁶ <https://github.com/TheHPXProject/hpx/issues/1192>

⁵⁹²⁷ <https://github.com/TheHPXProject/hpx/issues/1191>

⁵⁹²⁸ <https://github.com/TheHPXProject/hpx/issues/1190>

⁵⁹²⁹ <https://github.com/TheHPXProject/hpx/issues/1189>

⁵⁹³⁰ <https://github.com/TheHPXProject/hpx/issues/1188>

⁵⁹³¹ <https://github.com/TheHPXProject/hpx/issues/1186>

⁵⁹³² <https://github.com/TheHPXProject/hpx/issues/1184>

⁵⁹³³ <https://github.com/TheHPXProject/hpx/issues/1183>

⁵⁹³⁴ <https://github.com/TheHPXProject/hpx/issues/1182>

⁵⁹³⁵ <https://github.com/TheHPXProject/hpx/issues/1181>

⁵⁹³⁶ <https://github.com/TheHPXProject/hpx/issues/1180>

- Issue #1179⁵⁹³⁷ - `hpx::async` does not work for member function pointers when called on types with self-defined unary operator*
- Issue #1178⁵⁹³⁸ - Implemented variadic `hpx::util::zip_iterator`
- Issue #1177⁵⁹³⁹ - MPI parcelport defect
- Issue #1176⁵⁹⁴⁰ - `HPX_DEFINE_COMPONENT_CONST_ACTION_TPL` does not have a 2-argument version
- Issue #1175⁵⁹⁴¹ - Create `util::zip_iterator` working with `util::tuple<>`
- Issue #1174⁵⁹⁴² - Error Building HPX on linux, `root_certificate_authority.cpp`
- Issue #1173⁵⁹⁴³ - `hpx::cout` output lost
- Issue #1172⁵⁹⁴⁴ - HPX build error with Clang 3.4.2
- Issue #1171⁵⁹⁴⁵ - `CMAKE_INSTALL_PREFIX` ignored
- Issue #1170⁵⁹⁴⁶ - Close `hpx_benchmarks` repository on Github
- Issue #1169⁵⁹⁴⁷ - Buildbot emails have syntax error in url
- Issue #1167⁵⁹⁴⁸ - Merge partial implementation of standards proposal N3960
- Issue #1166⁵⁹⁴⁹ - Fixed several compiler warnings
- Issue #1165⁵⁹⁵⁰ - cmake warns: “tests.regressions.actions” does not exist
- Issue #1164⁵⁹⁵¹ - Want my own serialization of `hpx::future`
- Issue #1162⁵⁹⁵² - Segfault in `hello_world` example
- Issue #1161⁵⁹⁵³ - Use `HPX_ASSERT` to aid the compiler
- Issue #1160⁵⁹⁵⁴ - Do not put `-DNDEBUG` into `hpx_application.pc`
- Issue #1159⁵⁹⁵⁵ - Support Clang 3.4.2
- Issue #1158⁵⁹⁵⁶ - Fixed #1157: Rename `when_n/wait_n`, add `when_xxx_n/wait_xxx_n`
- Issue #1157⁵⁹⁵⁷ - Rename `when_n/wait_n`, add `when_xxx_n/wait_xxx_n`
- Issue #1156⁵⁹⁵⁸ - Force inlining fails
- Issue #1155⁵⁹⁵⁹ - changed header of `printout` to be compatible with python csv module

⁵⁹³⁷ <https://github.com/TheHPXProject/hpx/issues/1179>

⁵⁹³⁸ <https://github.com/TheHPXProject/hpx/issues/1178>

⁵⁹³⁹ <https://github.com/TheHPXProject/hpx/issues/1177>

⁵⁹⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1176>

⁵⁹⁴¹ <https://github.com/TheHPXProject/hpx/issues/1175>

⁵⁹⁴² <https://github.com/TheHPXProject/hpx/issues/1174>

⁵⁹⁴³ <https://github.com/TheHPXProject/hpx/issues/1173>

⁵⁹⁴⁴ <https://github.com/TheHPXProject/hpx/issues/1172>

⁵⁹⁴⁵ <https://github.com/TheHPXProject/hpx/issues/1171>

⁵⁹⁴⁶ <https://github.com/TheHPXProject/hpx/issues/1170>

⁵⁹⁴⁷ <https://github.com/TheHPXProject/hpx/issues/1169>

⁵⁹⁴⁸ <https://github.com/TheHPXProject/hpx/issues/1167>

⁵⁹⁴⁹ <https://github.com/TheHPXProject/hpx/issues/1166>

⁵⁹⁵⁰ <https://github.com/TheHPXProject/hpx/issues/1165>

⁵⁹⁵¹ <https://github.com/TheHPXProject/hpx/issues/1164>

⁵⁹⁵² <https://github.com/TheHPXProject/hpx/issues/1162>

⁵⁹⁵³ <https://github.com/TheHPXProject/hpx/issues/1161>

⁵⁹⁵⁴ <https://github.com/TheHPXProject/hpx/issues/1160>

⁵⁹⁵⁵ <https://github.com/TheHPXProject/hpx/issues/1159>

⁵⁹⁵⁶ <https://github.com/TheHPXProject/hpx/issues/1158>

⁵⁹⁵⁷ <https://github.com/TheHPXProject/hpx/issues/1157>

⁵⁹⁵⁸ <https://github.com/TheHPXProject/hpx/issues/1156>

⁵⁹⁵⁹ <https://github.com/TheHPXProject/hpx/issues/1155>

- Issue #1154⁵⁹⁶⁰ - Fixing iostreams
- Issue #1153⁵⁹⁶¹ - Standard manipulators (like `std::endl`) do not work with `hpx::ostream`
- Issue #1152⁵⁹⁶² - Functions revamp
- Issue #1151⁵⁹⁶³ - Suppressing cmake 3.0 policy warning for CMP0026
- Issue #1150⁵⁹⁶⁴ - Client Serialization error
- Issue #1149⁵⁹⁶⁵ - Segfault on Stampede
- Issue #1148⁵⁹⁶⁶ - Refactoring mini-ghost
- Issue #1147⁵⁹⁶⁷ - N3960 `copy_if` and `copy_n` implemented and tested
- Issue #1146⁵⁹⁶⁸ - Stencil print
- Issue #1145⁵⁹⁶⁹ - N3960 `hpx::parallel::copy` implemented and tested
- Issue #1144⁵⁹⁷⁰ - OpenMP examples `1d_stencil` do not build
- Issue #1143⁵⁹⁷¹ - `1d_stencil` OpenMP examples do not build
- Issue #1142⁵⁹⁷² - Cannot build HPX with gcc 4.6 on OS X
- Issue #1140⁵⁹⁷³ - Fix OpenMP lookup, enable usage of config tests in external CMake projects.
- Issue #1139⁵⁹⁷⁴ - `hpx/hpx/config/compiler_specific.hpp`
- Issue #1138⁵⁹⁷⁵ - clean up pkg-config files
- Issue #1137⁵⁹⁷⁶ - Improvements to create binary packages
- Issue #1136⁵⁹⁷⁷ - `HPX_GCC_VERSION` not defined on all compilers
- Issue #1135⁵⁹⁷⁸ - Avoiding collision between `winsock2.h` and `windows.h`
- Issue #1134⁵⁹⁷⁹ - Making sure, that `hpx::finalize` can be called from any locality
- Issue #1133⁵⁹⁸⁰ - `1d stencil` examples
- Issue #1131⁵⁹⁸¹ - Refactor `unique_function` implementation
- Issue #1130⁵⁹⁸² - Unique function

⁵⁹⁶⁰ <https://github.com/TheHPXProject/hpx/issues/1154>

⁵⁹⁶¹ <https://github.com/TheHPXProject/hpx/issues/1153>

⁵⁹⁶² <https://github.com/TheHPXProject/hpx/issues/1152>

⁵⁹⁶³ <https://github.com/TheHPXProject/hpx/issues/1151>

⁵⁹⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1150>

⁵⁹⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1149>

⁵⁹⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1148>

⁵⁹⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1147>

⁵⁹⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1146>

⁵⁹⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1145>

⁵⁹⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1144>

⁵⁹⁷¹ <https://github.com/TheHPXProject/hpx/issues/1143>

⁵⁹⁷² <https://github.com/TheHPXProject/hpx/issues/1142>

⁵⁹⁷³ <https://github.com/TheHPXProject/hpx/issues/1140>

⁵⁹⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1139>

⁵⁹⁷⁵ <https://github.com/TheHPXProject/hpx/issues/1138>

⁵⁹⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1137>

⁵⁹⁷⁷ <https://github.com/TheHPXProject/hpx/issues/1136>

⁵⁹⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1135>

⁵⁹⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1134>

⁵⁹⁸⁰ <https://github.com/TheHPXProject/hpx/issues/1133>

⁵⁹⁸¹ <https://github.com/TheHPXProject/hpx/issues/1131>

⁵⁹⁸² <https://github.com/TheHPXProject/hpx/issues/1130>

- Issue #1129⁵⁹⁸³ - Some fixes to the Build system on OS X
- Issue #1128⁵⁹⁸⁴ - Action future args
- Issue #1127⁵⁹⁸⁵ - Executor causes segmentation fault
- Issue #1124⁵⁹⁸⁶ - Adding new API functions: `register_id_with_basename`, `unregister_id_with_basename`, `find_ids_from_basename`; adding test
- Issue #1123⁵⁹⁸⁷ - Reduce nesting of try-catch construct in `encode_parcels`?
- Issue #1122⁵⁹⁸⁸ - Client base fixes
- Issue #1121⁵⁹⁸⁹ - Update `hpxrun.py.in`
- Issue #1120⁵⁹⁹⁰ - HTTPS2 tests compile errors on v110 (VS2012)
- Issue #1119⁵⁹⁹¹ - Remove references to `boost::atomic` in accumulator example
- Issue #1118⁵⁹⁹² - Only build test `thread_pool_executor_1114_test` if `HPX_SCHEDULER` is set
- Issue #1117⁵⁹⁹³ - `local_queue_executor` linker error on vc110
- Issue #1116⁵⁹⁹⁴ - Disabled performance counter should give runtime errors, not invalid data
- Issue #1115⁵⁹⁹⁵ - Compile error with Intel C++ 13.1
- Issue #1114⁵⁹⁹⁶ - Default constructed executor is not usable
- Issue #1113⁵⁹⁹⁷ - Fast compilation of logging causes ABI incompatibilities between different `NDEBUG` values
- Issue #1112⁵⁹⁹⁸ - Using `thread_pool_executors` causes segfault
- Issue #1111⁵⁹⁹⁹ - `hpx::threads::get_thread_data` always returns zero
- Issue #1110⁶⁰⁰⁰ - Remove unnecessary null pointer checks
- Issue #1109⁶⁰⁰¹ - More tests adjustments
- Issue #1108⁶⁰⁰² - Clarify build rules for “`libboost_atomic-mt.so`”?
- Issue #1107⁶⁰⁰³ - Remove unnecessary null pointer checks
- Issue #1106⁶⁰⁰⁴ - `network_storage` benchmark improvements, adding legends to plots and tidying layout
- Issue #1105⁶⁰⁰⁵ - Add more plot outputs and improve instructions doc

⁵⁹⁸³ <https://github.com/TheHPXProject/hpx/issues/1129>

⁵⁹⁸⁴ <https://github.com/TheHPXProject/hpx/issues/1128>

⁵⁹⁸⁵ <https://github.com/TheHPXProject/hpx/issues/1127>

⁵⁹⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1124>

⁵⁹⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1123>

⁵⁹⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1122>

⁵⁹⁸⁹ <https://github.com/TheHPXProject/hpx/issues/1121>

⁵⁹⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1120>

⁵⁹⁹¹ <https://github.com/TheHPXProject/hpx/issues/1119>

⁵⁹⁹² <https://github.com/TheHPXProject/hpx/issues/1118>

⁵⁹⁹³ <https://github.com/TheHPXProject/hpx/issues/1117>

⁵⁹⁹⁴ <https://github.com/TheHPXProject/hpx/issues/1116>

⁵⁹⁹⁵ <https://github.com/TheHPXProject/hpx/issues/1115>

⁵⁹⁹⁶ <https://github.com/TheHPXProject/hpx/issues/1114>

⁵⁹⁹⁷ <https://github.com/TheHPXProject/hpx/issues/1113>

⁵⁹⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1112>

⁵⁹⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1111>

⁶⁰⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1110>

⁶⁰⁰¹ <https://github.com/TheHPXProject/hpx/issues/1109>

⁶⁰⁰² <https://github.com/TheHPXProject/hpx/issues/1108>

⁶⁰⁰³ <https://github.com/TheHPXProject/hpx/issues/1107>

⁶⁰⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1106>

⁶⁰⁰⁵ <https://github.com/TheHPXProject/hpx/issues/1105>

- Issue #1104⁶⁰⁰⁶ - Complete quoting for parameters of some CMake commands
- Issue #1103⁶⁰⁰⁷ - Work on test/scripts
- Issue #1102⁶⁰⁰⁸ - Changed minimum requirement of window install to 2012
- Issue #1101⁶⁰⁰⁹ - Changed minimum requirement of window install to 2012
- Issue #1100⁶⁰¹⁰ - Changed readme to no longer specify using MSVC 2010 compiler
- Issue #1099⁶⁰¹¹ - Error returning futures from component actions
- Issue #1098⁶⁰¹² - Improve storage test
- Issue #1097⁶⁰¹³ - data_actions quickstart example calls missing function decorate_action of data_get_action
- Issue #1096⁶⁰¹⁴ - MPI parcelport broken with new zero copy optimization
- Issue #1095⁶⁰¹⁵ - Warning C4005: _WIN32_WINNT: Macro redefinition
- Issue #1094⁶⁰¹⁶ - Syntax error for -DHPX_UNIQUE_FUTURE_ALIAS in master
- Issue #1093⁶⁰¹⁷ - Syntax error for -DHPX_UNIQUE_FUTURE_ALIAS
- Issue #1092⁶⁰¹⁸ - Rename unique_future<> back to future<>
- Issue #1091⁶⁰¹⁹ - Inconsistent error message
- Issue #1090⁶⁰²⁰ - On windows 8.1 the examples crashed if using more than one os thread
- Issue #1089⁶⁰²¹ - Components should be allowed to have their own executor
- Issue #1088⁶⁰²² - Add possibility to select a network interface for the ibverbs parcelport
- Issue #1087⁶⁰²³ - ibverbs and ipc parcelport uses zero copy optimization
- Issue #1083⁶⁰²⁴ - Make shell examples copyable in docs
- Issue #1082⁶⁰²⁵ - Implement proper termination detection during shutdown
- Issue #1081⁶⁰²⁶ - Implement thread_specific_ptr for hpx::threads
- Issue #1072⁶⁰²⁷ - make install not working properly
- Issue #1070⁶⁰²⁸ - Complete quoting for parameters of some CMake commands

⁶⁰⁰⁶ <https://github.com/TheHPXProject/hpx/issues/1104>

⁶⁰⁰⁷ <https://github.com/TheHPXProject/hpx/issues/1103>

⁶⁰⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1102>

⁶⁰⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1101>

⁶⁰¹⁰ <https://github.com/TheHPXProject/hpx/issues/1100>

⁶⁰¹¹ <https://github.com/TheHPXProject/hpx/issues/1099>

⁶⁰¹² <https://github.com/TheHPXProject/hpx/issues/1098>

⁶⁰¹³ <https://github.com/TheHPXProject/hpx/issues/1097>

⁶⁰¹⁴ <https://github.com/TheHPXProject/hpx/issues/1096>

⁶⁰¹⁵ <https://github.com/TheHPXProject/hpx/issues/1095>

⁶⁰¹⁶ <https://github.com/TheHPXProject/hpx/issues/1094>

⁶⁰¹⁷ <https://github.com/TheHPXProject/hpx/issues/1093>

⁶⁰¹⁸ <https://github.com/TheHPXProject/hpx/issues/1092>

⁶⁰¹⁹ <https://github.com/TheHPXProject/hpx/issues/1091>

⁶⁰²⁰ <https://github.com/TheHPXProject/hpx/issues/1090>

⁶⁰²¹ <https://github.com/TheHPXProject/hpx/issues/1089>

⁶⁰²² <https://github.com/TheHPXProject/hpx/issues/1088>

⁶⁰²³ <https://github.com/TheHPXProject/hpx/issues/1087>

⁶⁰²⁴ <https://github.com/TheHPXProject/hpx/issues/1083>

⁶⁰²⁵ <https://github.com/TheHPXProject/hpx/issues/1082>

⁶⁰²⁶ <https://github.com/TheHPXProject/hpx/issues/1081>

⁶⁰²⁷ <https://github.com/TheHPXProject/hpx/issues/1072>

⁶⁰²⁸ <https://github.com/TheHPXProject/hpx/issues/1070>

- Issue #1059⁶⁰²⁹ - Fix more unused variable warnings
- Issue #1051⁶⁰³⁰ - Implement when_each
- Issue #973⁶⁰³¹ - Would like option to report hwloc bindings
- Issue #970⁶⁰³² - Bad flags for Fortran compiler
- Issue #941⁶⁰³³ - Create a proper user level context switching class for BG/Q
- Issue #935⁶⁰³⁴ - Build error with gcc 4.6 and Boost 1.54.0 on hpx trunk and 0.9.6
- Issue #934⁶⁰³⁵ - Want to build HPX without dynamic libraries
- Issue #927⁶⁰³⁶ - Make hpx/lcos/reduce.hpp accept futures of id_type
- Issue #926⁶⁰³⁷ - All unit tests that are run with more than one thread with CTest/hpx_run_test should configure hpx.os_threads
- Issue #925⁶⁰³⁸ - regression_dataflow_791 needs to be brought in line with HPX standards
- Issue #899⁶⁰³⁹ - Fix race conditions in regression tests
- Issue #879⁶⁰⁴⁰ - Hung test leads to cascading test failure; make tests should support the MPI parcelport
- Issue #865⁶⁰⁴¹ - future<T> and friends shall work for movable only Ts
- Issue #847⁶⁰⁴² - Dynamic libraries are not installed on OS X
- Issue #816⁶⁰⁴³ - First Program tutorial pull request
- Issue #799⁶⁰⁴⁴ - Wrap lexical_cast to avoid exceptions
- Issue #720⁶⁰⁴⁵ - broken configuration when using cmake on Ubuntu
- Issue #622⁶⁰⁴⁶ - --hpx:hpx and --hpx:debug-hpx-log is nonsensical
- Issue #525⁶⁰⁴⁷ - Extend barrier LCO test to run in distributed
- Issue #515⁶⁰⁴⁸ - Multi-destination version of hpx::apply is broken
- Issue #509⁶⁰⁴⁹ - Push Boost.Atomic changes upstream
- Issue #503⁶⁰⁵⁰ - Running HPX applications on Windows should not require setting %PATH%
- Issue #461⁶⁰⁵¹ - Add a compilation sanity test

⁶⁰²⁹ <https://github.com/TheHPXProject/hpx/issues/1059>

⁶⁰³⁰ <https://github.com/TheHPXProject/hpx/issues/1051>

⁶⁰³¹ <https://github.com/TheHPXProject/hpx/issues/973>

⁶⁰³² <https://github.com/TheHPXProject/hpx/issues/970>

⁶⁰³³ <https://github.com/TheHPXProject/hpx/issues/941>

⁶⁰³⁴ <https://github.com/TheHPXProject/hpx/issues/935>

⁶⁰³⁵ <https://github.com/TheHPXProject/hpx/issues/934>

⁶⁰³⁶ <https://github.com/TheHPXProject/hpx/issues/927>

⁶⁰³⁷ <https://github.com/TheHPXProject/hpx/issues/926>

⁶⁰³⁸ <https://github.com/TheHPXProject/hpx/issues/925>

⁶⁰³⁹ <https://github.com/TheHPXProject/hpx/issues/899>

⁶⁰⁴⁰ <https://github.com/TheHPXProject/hpx/issues/879>

⁶⁰⁴¹ <https://github.com/TheHPXProject/hpx/issues/865>

⁶⁰⁴² <https://github.com/TheHPXProject/hpx/issues/847>

⁶⁰⁴³ <https://github.com/TheHPXProject/hpx/issues/816>

⁶⁰⁴⁴ <https://github.com/TheHPXProject/hpx/issues/799>

⁶⁰⁴⁵ <https://github.com/TheHPXProject/hpx/issues/720>

⁶⁰⁴⁶ <https://github.com/TheHPXProject/hpx/issues/622>

⁶⁰⁴⁷ <https://github.com/TheHPXProject/hpx/issues/525>

⁶⁰⁴⁸ <https://github.com/TheHPXProject/hpx/issues/515>

⁶⁰⁴⁹ <https://github.com/TheHPXProject/hpx/issues/509>

⁶⁰⁵⁰ <https://github.com/TheHPXProject/hpx/issues/503>

⁶⁰⁵¹ <https://github.com/TheHPXProject/hpx/issues/461>

- Issue #456⁶⁰⁵² - hpx_run_tests.py should log output from tests that timeout
- Issue #454⁶⁰⁵³ - Investigate threadmanager performance
- Issue #345⁶⁰⁵⁴ - Add more versatile environmental/cmake variable support to hpx_find_* CMake macros
- Issue #209⁶⁰⁵⁵ - Support multiple configurations in generated build files
- Issue #190⁶⁰⁵⁶ - hpx::cout should be a std::ostream
- Issue #189⁶⁰⁵⁷ - iostreams component should use startup/shutdown functions
- Issue #183⁶⁰⁵⁸ - Use Boost.ICL for correctness in AGAS
- Issue #44⁶⁰⁵⁹ - Implement real futures

HPX V0.9.8 (Mar 24, 2014)

We have had over 800 commits since the last release and we have closed over 65 tickets (bugs, feature requests, etc.).

With the changes below, *HPX* is once again leading the charge of a whole new era of computation. By intrinsically breaking down and synchronizing the work to be done, *HPX* insures that application developers will no longer have to fret about where a segment of code executes. That allows coders to focus their time and energy to understanding the data dependencies of their algorithms and thereby the core obstacles to an efficient code. Here are some of the advantages of using *HPX*:

- *HPX* is solidly rooted in a sophisticated theoretical execution model – ParalleX
- *HPX* exposes an API fully conforming to the C++11 and the draft C++14 standards, extended and applied to distributed computing. Everything programmers know about the concurrency primitives of the standard C++ library is still valid in the context of *HPX*.
- It provides a competitive, high performance implementation of modern, future-proof ideas which gives an smooth migration path from today's mainstream techniques
- There is no need for the programmer to worry about lower level parallelization paradigms like threads or message passing; no need to understand pthreads, MPI, OpenMP, or Windows threads, etc.
- There is no need to think about different types of parallelism such as tasks, pipelines, or fork-join, task or data parallelism.
- The same source of your program compiles and runs on Linux, BlueGene/Q, Mac OS X, Windows, and Android.
- The same code runs on shared memory multi-core systems and supercomputers, on handheld devices and Intel® Xeon Phi™ accelerators, or a heterogeneous mix of those.

⁶⁰⁵² <https://github.com/TheHPXProject/hpx/issues/456>

⁶⁰⁵³ <https://github.com/TheHPXProject/hpx/issues/454>

⁶⁰⁵⁴ <https://github.com/TheHPXProject/hpx/issues/345>

⁶⁰⁵⁵ <https://github.com/TheHPXProject/hpx/issues/209>

⁶⁰⁵⁶ <https://github.com/TheHPXProject/hpx/issues/190>

⁶⁰⁵⁷ <https://github.com/TheHPXProject/hpx/issues/189>

⁶⁰⁵⁸ <https://github.com/TheHPXProject/hpx/issues/183>

⁶⁰⁵⁹ <https://github.com/TheHPXProject/hpx/issues/44>

General changes

- A major API breaking change for this release was introduced by implementing `hpx::future` and `hpx::shared_future` fully in conformance with the C++11 Standard⁶⁰⁶⁰. While `hpx::shared_future` is new and will not create any compatibility problems, we revised the interface and implementation of the existing `hpx::future`. For more details please see the [mailing list archive](#)⁶⁰⁶¹. To avoid any incompatibilities for existing code we named the type which implements the `std::future` interface as `hpx::unique_future`. For the next release this will be renamed to `hpx::future`, making it full conforming to C++11 Standard⁶⁰⁶².
- A large part of the code base of *HPX* has been refactored and partially re-implemented. The main changes were related to
 - The threading subsystem: these changes significantly reduce the amount of overheads caused by the schedulers, improve the modularity of the code base, and extend the variety of available scheduling algorithms.
 - The parcel subsystem: these changes improve the performance of the *HPX* networking layer, modularize the structure of the parcelports, and simplify the creation of new parcelports for other underlying networking libraries.
 - The API subsystem: these changes improved the conformance of the API to C++11 Standard, extend and unify the available API functionality, and decrease the overheads created by various elements of the API.
 - The robustness of the component loading subsystem has been improved significantly, allowing to more portably and more reliably register the components needed by an application as startup. This additionally speeds up general application initialization.
- We added new API functionality like `hpx::migrate` and `hpx::copy_component` which are the basic building blocks necessary for implementing higher level abstractions for system-wide load balancing, runtime-adaptive resource management, and object-oriented checkpointing and state-management.
- We removed the use of C++11 move emulation (using `Boost.Move`), replacing it with C++11 rvalue references. This is the first step towards using more and more native C++11 facilities which we plan to introduce in the future.
- We improved the reference counting scheme used by *HPX* which helps managing distributed objects and memory. This improves the overall stability of *HPX* and further simplifies writing real world applications.
- The minimal Boost version required to use *HPX* is now V1.49.0.
- This release coincides with the first release of HPXPI (V0.1.0), the first implementation of the [XPI specification](#)⁶⁰⁶³.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [Issue #1086](#)⁶⁰⁶⁴ - Expose internal `boost::shared_array` to allow user management of array lifetime
- [Issue #1083](#)⁶⁰⁶⁵ - Make shell examples copyable in docs
- [Issue #1080](#)⁶⁰⁶⁶ - `/threads{locality#*/total}/count/cumulative` broken
- [Issue #1079](#)⁶⁰⁶⁷ - Build problems on OS X

⁶⁰⁶⁰ <http://www.open-std.org/jtc1/sc22/wg21>

⁶⁰⁶¹ <http://mail.cct.lsu.edu/pipermail/hpx-users/2014-January/000141.html>

⁶⁰⁶² <http://www.open-std.org/jtc1/sc22/wg21>

⁶⁰⁶³ <https://github.com/STELLAR-GROUP/hpxpi/blob/master/spec.pdf?raw=true>

⁶⁰⁶⁴ <https://github.com/TheHPXProject/hpx/issues/1086>

⁶⁰⁶⁵ <https://github.com/TheHPXProject/hpx/issues/1083>

⁶⁰⁶⁶ <https://github.com/TheHPXProject/hpx/issues/1080>

⁶⁰⁶⁷ <https://github.com/TheHPXProject/hpx/issues/1079>

- Issue #1078⁶⁰⁶⁸ - Improve robustness of component loading
- Issue #1077⁶⁰⁶⁹ - Fix a missing enum definition for ‘take’ mode
- Issue #1076⁶⁰⁷⁰ - Merge Jb master
- Issue #1075⁶⁰⁷¹ - Unknown CMake command “add_hpx_pseudo_target”
- Issue #1074⁶⁰⁷² - Implement `apply_continue_callback` and `apply_colocated_callback`
- Issue #1073⁶⁰⁷³ - The new `apply_colocated` and `async_colocated` functions lead to automatic registered functions
- Issue #1071⁶⁰⁷⁴ - Remove `deferred_packaged_task`
- Issue #1069⁶⁰⁷⁵ - `serialize_buffer` with allocator fails at destruction
- Issue #1068⁶⁰⁷⁶ - Coroutine include and forward declarations missing
- Issue #1067⁶⁰⁷⁷ - Add allocator support to `util::serialize_buffer`
- Issue #1066⁶⁰⁷⁸ - Allow for `MPI_Init` being called before HPX launches
- Issue #1065⁶⁰⁷⁹ - AGAS cache isn’t used/populated on worker localities
- Issue #1064⁶⁰⁸⁰ - Reorder includes to ensure `ws2` includes early
- Issue #1063⁶⁰⁸¹ - Add `hpx::runtime::suspend` and `hpx::runtime::resume`
- Issue #1062⁶⁰⁸² - Fix `async_continue` to properly handle return types
- Issue #1061⁶⁰⁸³ - Implement `async_colocated` and `apply_colocated`
- Issue #1060⁶⁰⁸⁴ - Implement minimal component migration
- Issue #1058⁶⁰⁸⁵ - Remove `HPX_UTIL_TUPLE` from code base
- Issue #1057⁶⁰⁸⁶ - Add performance counters for threading subsystem
- Issue #1055⁶⁰⁸⁷ - Thread allocation uses two memory pools
- Issue #1053⁶⁰⁸⁸ - Work stealing flawed
- Issue #1052⁶⁰⁸⁹ - Fix a number of warnings
- Issue #1049⁶⁰⁹⁰ - Fixes for TLS on OSX and more reliable test running

⁶⁰⁶⁸ <https://github.com/TheHPXProject/hpx/issues/1078>

⁶⁰⁶⁹ <https://github.com/TheHPXProject/hpx/issues/1077>

⁶⁰⁷⁰ <https://github.com/TheHPXProject/hpx/issues/1076>

⁶⁰⁷¹ <https://github.com/TheHPXProject/hpx/issues/1075>

⁶⁰⁷² <https://github.com/TheHPXProject/hpx/issues/1074>

⁶⁰⁷³ <https://github.com/TheHPXProject/hpx/issues/1073>

⁶⁰⁷⁴ <https://github.com/TheHPXProject/hpx/issues/1071>

⁶⁰⁷⁵ <https://github.com/TheHPXProject/hpx/issues/1069>

⁶⁰⁷⁶ <https://github.com/TheHPXProject/hpx/issues/1068>

⁶⁰⁷⁷ <https://github.com/TheHPXProject/hpx/issues/1067>

⁶⁰⁷⁸ <https://github.com/TheHPXProject/hpx/issues/1066>

⁶⁰⁷⁹ <https://github.com/TheHPXProject/hpx/issues/1065>

⁶⁰⁸⁰ <https://github.com/TheHPXProject/hpx/issues/1064>

⁶⁰⁸¹ <https://github.com/TheHPXProject/hpx/issues/1063>

⁶⁰⁸² <https://github.com/TheHPXProject/hpx/issues/1062>

⁶⁰⁸³ <https://github.com/TheHPXProject/hpx/issues/1061>

⁶⁰⁸⁴ <https://github.com/TheHPXProject/hpx/issues/1060>

⁶⁰⁸⁵ <https://github.com/TheHPXProject/hpx/issues/1058>

⁶⁰⁸⁶ <https://github.com/TheHPXProject/hpx/issues/1057>

⁶⁰⁸⁷ <https://github.com/TheHPXProject/hpx/issues/1055>

⁶⁰⁸⁸ <https://github.com/TheHPXProject/hpx/issues/1053>

⁶⁰⁸⁹ <https://github.com/TheHPXProject/hpx/issues/1052>

⁶⁰⁹⁰ <https://github.com/TheHPXProject/hpx/issues/1049>

- Issue #1048⁶⁰⁹¹ - Fixing after 588 hang
- Issue #1047⁶⁰⁹² - Use port '0' for networking when using one locality
- Issue #1046⁶⁰⁹³ - `composable_guard` test is broken when having more than one thread
- Issue #1045⁶⁰⁹⁴ - Security missing headers
- Issue #1044⁶⁰⁹⁵ - Native TLS on FreeBSD via `__thread`
- Issue #1043⁶⁰⁹⁶ - `async` et.al. compute the wrong result type
- Issue #1042⁶⁰⁹⁷ - `async` et.al. implicitly unwrap reference_wrappers
- Issue #1041⁶⁰⁹⁸ - Remove redundant costly Kleene stars from regex searches
- Issue #1040⁶⁰⁹⁹ - CMake script regex match patterns has unnecessary kleenes
- Issue #1039⁶¹⁰⁰ - Remove use of `Boost.Move` and replace with `std::move` and real rvalue refs
- Issue #1038⁶¹⁰¹ - Bump minimal required Boost to 1.49.0
- Issue #1037⁶¹⁰² - Implicit unwrapping of futures in `async` broken
- Issue #1036⁶¹⁰³ - Scheduler hangs when user code attempts to “block” OS-threads
- Issue #1035⁶¹⁰⁴ - Idle-rate counter always reports 100% idle rate
- Issue #1034⁶¹⁰⁵ - Symbolic name registration causes application hangs
- Issue #1033⁶¹⁰⁶ - Application options read in from an options file generate an error message
- Issue #1032⁶¹⁰⁷ - `hpx::id_type` local reference counting is wrong
- Issue #1031⁶¹⁰⁸ - Negative entry in reference count table
- Issue #1030⁶¹⁰⁹ - Implement `condition_variable`
- Issue #1029⁶¹¹⁰ - Deadlock in thread scheduling subsystem
- Issue #1028⁶¹¹¹ - HPX-thread cumulative count performance counters report incorrect value
- Issue #1027⁶¹¹² - Expose `hpx::thread_interrupted` error code as a separate exception type
- Issue #1026⁶¹¹³ - Exceptions thrown in asynchronous calls can be lost if the value of the future is never queried

⁶⁰⁹¹ <https://github.com/TheHPXProject/hpx/issues/1048>

⁶⁰⁹² <https://github.com/TheHPXProject/hpx/issues/1047>

⁶⁰⁹³ <https://github.com/TheHPXProject/hpx/issues/1046>

⁶⁰⁹⁴ <https://github.com/TheHPXProject/hpx/issues/1045>

⁶⁰⁹⁵ <https://github.com/TheHPXProject/hpx/issues/1044>

⁶⁰⁹⁶ <https://github.com/TheHPXProject/hpx/issues/1043>

⁶⁰⁹⁷ <https://github.com/TheHPXProject/hpx/issues/1042>

⁶⁰⁹⁸ <https://github.com/TheHPXProject/hpx/issues/1041>

⁶⁰⁹⁹ <https://github.com/TheHPXProject/hpx/issues/1040>

⁶¹⁰⁰ <https://github.com/TheHPXProject/hpx/issues/1039>

⁶¹⁰¹ <https://github.com/TheHPXProject/hpx/issues/1038>

⁶¹⁰² <https://github.com/TheHPXProject/hpx/issues/1037>

⁶¹⁰³ <https://github.com/TheHPXProject/hpx/issues/1036>

⁶¹⁰⁴ <https://github.com/TheHPXProject/hpx/issues/1035>

⁶¹⁰⁵ <https://github.com/TheHPXProject/hpx/issues/1034>

⁶¹⁰⁶ <https://github.com/TheHPXProject/hpx/issues/1033>

⁶¹⁰⁷ <https://github.com/TheHPXProject/hpx/issues/1032>

⁶¹⁰⁸ <https://github.com/TheHPXProject/hpx/issues/1031>

⁶¹⁰⁹ <https://github.com/TheHPXProject/hpx/issues/1030>

⁶¹¹⁰ <https://github.com/TheHPXProject/hpx/issues/1029>

⁶¹¹¹ <https://github.com/TheHPXProject/hpx/issues/1028>

⁶¹¹² <https://github.com/TheHPXProject/hpx/issues/1027>

⁶¹¹³ <https://github.com/TheHPXProject/hpx/issues/1026>

- Issue #1025⁶¹¹⁴ - `future::wait_for/wait_until` do not remove callback
- Issue #1024⁶¹¹⁵ - Remove dependence to boost assert and create hpx assert
- Issue #1023⁶¹¹⁶ - Segfaults with `tcmalloc`
- Issue #1022⁶¹¹⁷ - prerequisites link in readme is broken
- Issue #1020⁶¹¹⁸ - HPX Deadlock on external synchronization
- Issue #1019⁶¹¹⁹ - Convert using `BOOST_ASSERT` to `HPX_ASSERT`
- Issue #1018⁶¹²⁰ - compiling bug with gcc 4.8.1
- Issue #1017⁶¹²¹ - Possible crash in `io_pool` executor
- Issue #1016⁶¹²² - Crash at startup
- Issue #1014⁶¹²³ - Implement Increment/Decrement Merging
- Issue #1013⁶¹²⁴ - Add more logging channels to enable greater control over logging granularity
- Issue #1012⁶¹²⁵ - `--hpx:debug-hpx-log` and `--hpx:debug-agas-log` lead to non-thread safe writes
- Issue #1011⁶¹²⁶ - After installation, running applications from the build/staging directory no longer works
- Issue #1010⁶¹²⁷ - Mergeable decrement requests are not being merged
- Issue #1009⁶¹²⁸ - `--hpx:list-symbolic-names` crashes
- Issue #1007⁶¹²⁹ - Components are not properly destroyed
- Issue #1006⁶¹³⁰ - Segfault/hang in `set_data`
- Issue #1003⁶¹³¹ - Performance counter naming issue
- Issue #982⁶¹³² - Race condition during startup
- Issue #912⁶¹³³ - OS X: component type not found in map
- Issue #663⁶¹³⁴ - Create a buildbot slave based on Clang 3.2/OSX
- Issue #636⁶¹³⁵ - Expose `this_locality::apply<act>(p1, p2);` for local execution
- Issue #197⁶¹³⁶ - Add `--console=address` option for PBS runs

⁶¹¹⁴ <https://github.com/TheHPXProject/hpx/issues/1025>

⁶¹¹⁵ <https://github.com/TheHPXProject/hpx/issues/1024>

⁶¹¹⁶ <https://github.com/TheHPXProject/hpx/issues/1023>

⁶¹¹⁷ <https://github.com/TheHPXProject/hpx/issues/1022>

⁶¹¹⁸ <https://github.com/TheHPXProject/hpx/issues/1020>

⁶¹¹⁹ <https://github.com/TheHPXProject/hpx/issues/1019>

⁶¹²⁰ <https://github.com/TheHPXProject/hpx/issues/1018>

⁶¹²¹ <https://github.com/TheHPXProject/hpx/issues/1017>

⁶¹²² <https://github.com/TheHPXProject/hpx/issues/1016>

⁶¹²³ <https://github.com/TheHPXProject/hpx/issues/1014>

⁶¹²⁴ <https://github.com/TheHPXProject/hpx/issues/1013>

⁶¹²⁵ <https://github.com/TheHPXProject/hpx/issues/1012>

⁶¹²⁶ <https://github.com/TheHPXProject/hpx/issues/1011>

⁶¹²⁷ <https://github.com/TheHPXProject/hpx/issues/1010>

⁶¹²⁸ <https://github.com/TheHPXProject/hpx/issues/1009>

⁶¹²⁹ <https://github.com/TheHPXProject/hpx/issues/1007>

⁶¹³⁰ <https://github.com/TheHPXProject/hpx/issues/1006>

⁶¹³¹ <https://github.com/TheHPXProject/hpx/issues/1003>

⁶¹³² <https://github.com/TheHPXProject/hpx/issues/982>

⁶¹³³ <https://github.com/TheHPXProject/hpx/issues/912>

⁶¹³⁴ <https://github.com/TheHPXProject/hpx/issues/663>

⁶¹³⁵ <https://github.com/TheHPXProject/hpx/issues/636>

⁶¹³⁶ <https://github.com/TheHPXProject/hpx/issues/197>

- [Issue #175](#)⁶¹³⁷ - Asynchronous AGAS API

HPX V0.9.7 (Nov 13, 2013)

We have had over 1000 commits since the last release and we have closed over 180 tickets (bugs, feature requests, etc.).

General changes

- Ported HPX to BlueGene/Q
- Improved HPX support for Xeon/Phi accelerators
- Reimplemented `hpx::bind`, `hpx::tuple`, and `hpx::function` for better performance and better compliance with the C++11 Standard. Added `hpx::mem_fn`.
- Reworked `hpx::when_all` and `hpx::when_any` for better compliance with the ongoing C++ standardization effort, added heterogeneous version for those functions. Added `hpx::when_any_swapped`.
- Added `hpx::copy` as a precursor for a migrate functionality
- Added `hpx::get_ptr` allowing to directly access the memory underlying a given component
- Added the `hpx::lcos::broadcast`, `hpx::lcos::reduce`, and `hpx::lcos::fold` collective operations
- Added `hpx::get_locality_name` allowing to retrieve the name of any of the localities for the application.
- Added support for more flexible thread affinity control from the HPX command line, such as new modes for `--hpx:bind` (balanced, scattered, compact), improved default settings when running multiple localities on the same node.
- Added experimental executors for simpler thread pooling and scheduling. This API may change in the future as it will stay aligned with the ongoing C++ standardization efforts.
- Massively improved the performance of the HPX serialization code. Added partial support for zero copy serialization of array and bitwise-copyable types.
- General performance improvements of the code related to threads and futures.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release.

- [Issue #1005](#)⁶¹³⁸ - Allow one to disable array optimizations and zero copy optimizations for each parcelport
- [Issue #1004](#)⁶¹³⁹ - Generate new HPX logo image for the docs
- [Issue #1002](#)⁶¹⁴⁰ - If MPI parcelport is not available, running HPX under mpirun should fail
- [Issue #1001](#)⁶¹⁴¹ - Zero copy serialization raises assert
- [Issue #1000](#)⁶¹⁴² - Can't connect to a HPX application running with the MPI parcelport from a non MPI parcelport locality
- [Issue #999](#)⁶¹⁴³ - Optimize `hpx::when_n`

⁶¹³⁷ <https://github.com/TheHPXProject/hpx/issues/175>

⁶¹³⁸ <https://github.com/TheHPXProject/hpx/issues/1005>

⁶¹³⁹ <https://github.com/TheHPXProject/hpx/issues/1004>

⁶¹⁴⁰ <https://github.com/TheHPXProject/hpx/issues/1002>

⁶¹⁴¹ <https://github.com/TheHPXProject/hpx/issues/1001>

⁶¹⁴² <https://github.com/TheHPXProject/hpx/issues/1000>

⁶¹⁴³ <https://github.com/TheHPXProject/hpx/issues/999>

- Issue #998⁶¹⁴⁴ - Fixed const-correctness
- Issue #997⁶¹⁴⁵ - Making `serialize_buffer::data()` type save
- Issue #996⁶¹⁴⁶ - Memory leak in `hpx::lcos::promise`
- Issue #995⁶¹⁴⁷ - Race while registering pre-shutdown functions
- Issue #994⁶¹⁴⁸ - `thread_rescheduling` regression test does not compile
- Issue #992⁶¹⁴⁹ - Correct comments and messages
- Issue #991⁶¹⁵⁰ - `setcap cap_sys_rawio=ep` for power profiling causes an HPX application to abort
- Issue #989⁶¹⁵¹ - Jacobi hangs during execution
- Issue #988⁶¹⁵² - `multiple_init` test is failing
- Issue #986⁶¹⁵³ - Can't call a function called "init" from "main" when using `<hpx/hpx_main.hpp>`
- Issue #984⁶¹⁵⁴ - Reference counting tests are failing
- Issue #983⁶¹⁵⁵ - `thread_suspension_executor` test fails
- Issue #980⁶¹⁵⁶ - Terminating HPX threads don't leave stack in virgin state
- Issue #979⁶¹⁵⁷ - Static scheduler not in documents
- Issue #978⁶¹⁵⁸ - Preprocessing limits are broken
- Issue #977⁶¹⁵⁹ - Make `tests.regressions.lcos.future_hang_on_get` shorter
- Issue #976⁶¹⁶⁰ - Wrong library order in `pkgconfig`
- Issue #975⁶¹⁶¹ - Please reopen #963
- Issue #974⁶¹⁶² - Option `pu-offset` ignored in `fixing_588` branch
- Issue #972⁶¹⁶³ - Cannot use MKL with HPX
- Issue #969⁶¹⁶⁴ - Non-existent INI files requested on the command line via `--hpx:config` do not cause warnings or errors.
- Issue #968⁶¹⁶⁵ - Cannot build examples in `fixing_588` branch
- Issue #967⁶¹⁶⁶ - Command line description of `--hpx:queuing` seems wrong

⁶¹⁴⁴ <https://github.com/TheHPXProject/hpx/issues/998>

⁶¹⁴⁵ <https://github.com/TheHPXProject/hpx/issues/997>

⁶¹⁴⁶ <https://github.com/TheHPXProject/hpx/issues/996>

⁶¹⁴⁷ <https://github.com/TheHPXProject/hpx/issues/995>

⁶¹⁴⁸ <https://github.com/TheHPXProject/hpx/issues/994>

⁶¹⁴⁹ <https://github.com/TheHPXProject/hpx/issues/992>

⁶¹⁵⁰ <https://github.com/TheHPXProject/hpx/issues/991>

⁶¹⁵¹ <https://github.com/TheHPXProject/hpx/issues/989>

⁶¹⁵² <https://github.com/TheHPXProject/hpx/issues/988>

⁶¹⁵³ <https://github.com/TheHPXProject/hpx/issues/986>

⁶¹⁵⁴ <https://github.com/TheHPXProject/hpx/issues/984>

⁶¹⁵⁵ <https://github.com/TheHPXProject/hpx/issues/983>

⁶¹⁵⁶ <https://github.com/TheHPXProject/hpx/issues/980>

⁶¹⁵⁷ <https://github.com/TheHPXProject/hpx/issues/979>

⁶¹⁵⁸ <https://github.com/TheHPXProject/hpx/issues/978>

⁶¹⁵⁹ <https://github.com/TheHPXProject/hpx/issues/977>

⁶¹⁶⁰ <https://github.com/TheHPXProject/hpx/issues/976>

⁶¹⁶¹ <https://github.com/TheHPXProject/hpx/issues/975>

⁶¹⁶² <https://github.com/TheHPXProject/hpx/issues/974>

⁶¹⁶³ <https://github.com/TheHPXProject/hpx/issues/972>

⁶¹⁶⁴ <https://github.com/TheHPXProject/hpx/issues/969>

⁶¹⁶⁵ <https://github.com/TheHPXProject/hpx/issues/968>

⁶¹⁶⁶ <https://github.com/TheHPXProject/hpx/issues/967>

- Issue #966⁶¹⁶⁷ - `--hpx:print-bind` physical core numbers are wrong
- Issue #965⁶¹⁶⁸ - Deadlock when building in Release mode
- Issue #963⁶¹⁶⁹ - Not all worker threads are working
- Issue #962⁶¹⁷⁰ - Problem with SLURM integration
- Issue #961⁶¹⁷¹ - `--hpx:print-bind` outputs incorrect information
- Issue #960⁶¹⁷² - Fix cut and paste error in documentation of `get_thread_priority`
- Issue #959⁶¹⁷³ - Change link to `boost.atomic` in documentation to point to `boost.org`
- Issue #958⁶¹⁷⁴ - Undefined reference to `intrusive_ptr_release`
- Issue #957⁶¹⁷⁵ - Make tuple standard compliant
- Issue #956⁶¹⁷⁶ - Segfault with `a3382fb`
- Issue #955⁶¹⁷⁷ - `--hpx:nodes` and `--hpx:nodefiles` do not work with foreign nodes
- Issue #954⁶¹⁷⁸ - Make order of arguments for `hpx::async` and `hpx::broadcast` consistent
- Issue #953⁶¹⁷⁹ - Cannot use MKL with HPX
- Issue #952⁶¹⁸⁰ - `register_[pre_]shutdown_function` never throw
- Issue #951⁶¹⁸¹ - Assert when number of threads is greater than hardware concurrency
- Issue #948⁶¹⁸² - `HPX_HAVE_GENERIC_CONTEXT_COROUTINES` conflicts with `HPX_HAVE_FIBER_BASED_COROUTINES`
- Issue #947⁶¹⁸³ - Need `MPI_THREAD_MULTIPLE` for backward compatibility
- Issue #946⁶¹⁸⁴ - HPX does not call `MPI_Finalize`
- Issue #945⁶¹⁸⁵ - Segfault with `hpx::lcos::broadcast`
- Issue #944⁶¹⁸⁶ - OS X: assertion `pu_offset_ < hardware_concurrency` failed
- Issue #943⁶¹⁸⁷ - `#include <hpx/hpx_main.hpp>` does not work
- Issue #942⁶¹⁸⁸ - Make the BG/Q work with `-O3`
- Issue #940⁶¹⁸⁹ - Use separator when concatenating locality name

⁶¹⁶⁷ <https://github.com/TheHPXProject/hpx/issues/966>

⁶¹⁶⁸ <https://github.com/TheHPXProject/hpx/issues/965>

⁶¹⁶⁹ <https://github.com/TheHPXProject/hpx/issues/963>

⁶¹⁷⁰ <https://github.com/TheHPXProject/hpx/issues/962>

⁶¹⁷¹ <https://github.com/TheHPXProject/hpx/issues/961>

⁶¹⁷² <https://github.com/TheHPXProject/hpx/issues/960>

⁶¹⁷³ <https://github.com/TheHPXProject/hpx/issues/959>

⁶¹⁷⁴ <https://github.com/TheHPXProject/hpx/issues/958>

⁶¹⁷⁵ <https://github.com/TheHPXProject/hpx/issues/957>

⁶¹⁷⁶ <https://github.com/TheHPXProject/hpx/issues/956>

⁶¹⁷⁷ <https://github.com/TheHPXProject/hpx/issues/955>

⁶¹⁷⁸ <https://github.com/TheHPXProject/hpx/issues/954>

⁶¹⁷⁹ <https://github.com/TheHPXProject/hpx/issues/953>

⁶¹⁸⁰ <https://github.com/TheHPXProject/hpx/issues/952>

⁶¹⁸¹ <https://github.com/TheHPXProject/hpx/issues/951>

⁶¹⁸² <https://github.com/TheHPXProject/hpx/issues/948>

⁶¹⁸³ <https://github.com/TheHPXProject/hpx/issues/947>

⁶¹⁸⁴ <https://github.com/TheHPXProject/hpx/issues/946>

⁶¹⁸⁵ <https://github.com/TheHPXProject/hpx/issues/945>

⁶¹⁸⁶ <https://github.com/TheHPXProject/hpx/issues/944>

⁶¹⁸⁷ <https://github.com/TheHPXProject/hpx/issues/943>

⁶¹⁸⁸ <https://github.com/TheHPXProject/hpx/issues/942>

⁶¹⁸⁹ <https://github.com/TheHPXProject/hpx/issues/940>

- [Issue #939](#)⁶¹⁹⁰ - Refactor MPI parcelport to use `MPI_Wait` instead of multiple `MPI_Test` calls
- [Issue #938](#)⁶¹⁹¹ - Want to officially access `client_base::gid_`
- [Issue #937](#)⁶¹⁹² - `client_base::gid_` should be private`
- [Issue #936](#)⁶¹⁹³ - Want doxygen-like source code index
- [Issue #935](#)⁶¹⁹⁴ - Build error with gcc 4.6 and Boost 1.54.0 on hpx trunk and 0.9.6
- [Issue #933](#)⁶¹⁹⁵ - Cannot build HPX with Boost 1.54.0
- [Issue #932](#)⁶¹⁹⁶ - Components are destructed too early
- [Issue #931](#)⁶¹⁹⁷ - Make HPX work on BG/Q
- [Issue #930](#)⁶¹⁹⁸ - make git-docs is broken
- [Issue #929](#)⁶¹⁹⁹ - Generating index in docs broken
- [Issue #928](#)⁶²⁰⁰ - Optimize `hpx::util::static_` for C++11 compilers supporting magic statics
- [Issue #924](#)⁶²⁰¹ - Make `kill_process_tree` (in `process.py`) more robust on Mac OSX
- [Issue #923](#)⁶²⁰² - Correct BLAS and RNPL cmake tests
- [Issue #922](#)⁶²⁰³ - Cannot link against BLAS
- [Issue #921](#)⁶²⁰⁴ - Implement `hpx::mem_fn`
- [Issue #920](#)⁶²⁰⁵ - Output locality with `--hpx:print-bind`
- [Issue #919](#)⁶²⁰⁶ - Correct grammar; simplify boolean expressions
- [Issue #918](#)⁶²⁰⁷ - Link to `hello_world.cpp` is broken
- [Issue #917](#)⁶²⁰⁸ - adapt cmake file to new boostbook version
- [Issue #916](#)⁶²⁰⁹ - fix problem building documentation with `xsltproc` $\geq$ 1.1.27
- [Issue #915](#)⁶²¹⁰ - Add another TBBMalloc library search path
- [Issue #914](#)⁶²¹¹ - Build problem with Intel compiler on Stampede (TACC)
- [Issue #913](#)⁶²¹² - fix error messages in fibonacci examples

⁶¹⁹⁰ <https://github.com/TheHPXProject/hpx/issues/939>

⁶¹⁹¹ <https://github.com/TheHPXProject/hpx/issues/938>

⁶¹⁹² <https://github.com/TheHPXProject/hpx/issues/937>

⁶¹⁹³ <https://github.com/TheHPXProject/hpx/issues/936>

⁶¹⁹⁴ <https://github.com/TheHPXProject/hpx/issues/935>

⁶¹⁹⁵ <https://github.com/TheHPXProject/hpx/issues/933>

⁶¹⁹⁶ <https://github.com/TheHPXProject/hpx/issues/932>

⁶¹⁹⁷ <https://github.com/TheHPXProject/hpx/issues/931>

⁶¹⁹⁸ <https://github.com/TheHPXProject/hpx/issues/930>

⁶¹⁹⁹ <https://github.com/TheHPXProject/hpx/issues/929>

⁶²⁰⁰ <https://github.com/TheHPXProject/hpx/issues/928>

⁶²⁰¹ <https://github.com/TheHPXProject/hpx/issues/924>

⁶²⁰² <https://github.com/TheHPXProject/hpx/issues/923>

⁶²⁰³ <https://github.com/TheHPXProject/hpx/issues/922>

⁶²⁰⁴ <https://github.com/TheHPXProject/hpx/issues/921>

⁶²⁰⁵ <https://github.com/TheHPXProject/hpx/issues/920>

⁶²⁰⁶ <https://github.com/TheHPXProject/hpx/issues/919>

⁶²⁰⁷ <https://github.com/TheHPXProject/hpx/issues/918>

⁶²⁰⁸ <https://github.com/TheHPXProject/hpx/issues/917>

⁶²⁰⁹ <https://github.com/TheHPXProject/hpx/issues/916>

⁶²¹⁰ <https://github.com/TheHPXProject/hpx/issues/915>

⁶²¹¹ <https://github.com/TheHPXProject/hpx/issues/914>

⁶²¹² <https://github.com/TheHPXProject/hpx/issues/913>

- Issue #911⁶²¹³ - Update OS X build instructions
- Issue #910⁶²¹⁴ - Want like to specify MPI_ROOT instead of compiler wrapper script
- Issue #909⁶²¹⁵ - Warning about void* arithmetic
- Issue #908⁶²¹⁶ - Buildbot for MIC is broken
- Issue #906⁶²¹⁷ - Can't use --hpx:bind=balanced with multiple MPI processes
- Issue #905⁶²¹⁸ - --hpx:bind documentation should describe full grammar
- Issue #904⁶²¹⁹ - Add hpx::lcos::fold and hpx::lcos::inverse_fold collective operation
- Issue #903⁶²²⁰ - Add hpx::when_any_swapped()
- Issue #902⁶²²¹ - Add hpx::lcos::reduce collective operation
- Issue #901⁶²²² - Web documentation is not searchable
- Issue #900⁶²²³ - Web documentation for trunk has no index
- Issue #898⁶²²⁴ - Some tests fail with GCC 4.8.1 and MPI parcel port
- Issue #897⁶²²⁵ - HWLOC causes failures on Mac
- Issue #896⁶²²⁶ - pu-offset leads to startup error
- Issue #895⁶²²⁷ - hpx::get_locality_name not defined
- Issue #894⁶²²⁸ - Race condition at shutdown
- Issue #893⁶²²⁹ - --hpx:print-bind switches std::cout to hexadecimal mode
- Issue #892⁶²³⁰ - hwloc_topology_load can be expensive – don't call multiple times
- Issue #891⁶²³¹ - The documentation for get_locality_name is wrong
- Issue #890⁶²³² - --hpx:print-bind should not exit
- Issue #889⁶²³³ - --hpx:debug-hpx-log=FILE does not work
- Issue #888⁶²³⁴ - MPI parcelport does not exit cleanly for --hpx:print-bind
- Issue #887⁶²³⁵ - Choose thread affinities more cleverly

⁶²¹³ <https://github.com/TheHPXProject/hpx/issues/911>

⁶²¹⁴ <https://github.com/TheHPXProject/hpx/issues/910>

⁶²¹⁵ <https://github.com/TheHPXProject/hpx/issues/909>

⁶²¹⁶ <https://github.com/TheHPXProject/hpx/issues/908>

⁶²¹⁷ <https://github.com/TheHPXProject/hpx/issues/906>

⁶²¹⁸ <https://github.com/TheHPXProject/hpx/issues/905>

⁶²¹⁹ <https://github.com/TheHPXProject/hpx/issues/904>

⁶²²⁰ <https://github.com/TheHPXProject/hpx/issues/903>

⁶²²¹ <https://github.com/TheHPXProject/hpx/issues/902>

⁶²²² <https://github.com/TheHPXProject/hpx/issues/901>

⁶²²³ <https://github.com/TheHPXProject/hpx/issues/900>

⁶²²⁴ <https://github.com/TheHPXProject/hpx/issues/898>

⁶²²⁵ <https://github.com/TheHPXProject/hpx/issues/897>

⁶²²⁶ <https://github.com/TheHPXProject/hpx/issues/896>

⁶²²⁷ <https://github.com/TheHPXProject/hpx/issues/895>

⁶²²⁸ <https://github.com/TheHPXProject/hpx/issues/894>

⁶²²⁹ <https://github.com/TheHPXProject/hpx/issues/893>

⁶²³⁰ <https://github.com/TheHPXProject/hpx/issues/892>

⁶²³¹ <https://github.com/TheHPXProject/hpx/issues/891>

⁶²³² <https://github.com/TheHPXProject/hpx/issues/890>

⁶²³³ <https://github.com/TheHPXProject/hpx/issues/889>

⁶²³⁴ <https://github.com/TheHPXProject/hpx/issues/888>

⁶²³⁵ <https://github.com/TheHPXProject/hpx/issues/887>

- Issue #886⁶²³⁶ - Logging documentation is confusing
- Issue #885⁶²³⁷ - Two threads are slower than one
- Issue #884⁶²³⁸ - `is_callable` failing with member pointers in C++11
- Issue #883⁶²³⁹ - Need help with `is_callable_test`
- Issue #882⁶²⁴⁰ - `tests.regressions.lcos.future_hang_on_get` does not terminate
- Issue #881⁶²⁴¹ - `tests.regressions/block_matrix/matrix.hh` won't compile with GCC 4.8.1
- Issue #880⁶²⁴² - HPX does not work on OS X
- Issue #878⁶²⁴³ - `future::unwrap` triggers assertion
- Issue #877⁶²⁴⁴ - “make tests” has build errors on Ubuntu 12.10
- Issue #876⁶²⁴⁵ - `tcmalloc` is used by default, even if it is not present
- Issue #875⁶²⁴⁶ - `global_fixture` is defined in a header file
- Issue #874⁶²⁴⁷ - Some tests take very long
- Issue #873⁶²⁴⁸ - Add block-matrix code as regression test
- Issue #872⁶²⁴⁹ - HPX documentation does not say how to run tests with detailed output
- Issue #871⁶²⁵⁰ - All tests fail with “make test”
- Issue #870⁶²⁵¹ - Please explicitly disable serialization in classes that don't support it
- Issue #868⁶²⁵² - `boost_any` test failing
- Issue #867⁶²⁵³ - Reduce the number of copies of `hpx::function` arguments
- Issue #863⁶²⁵⁴ - Futures should not require a default constructor
- Issue #862⁶²⁵⁵ - `value_or_error` shall not default construct its result
- Issue #861⁶²⁵⁶ - `HPX_UNUSED` macro
- Issue #860⁶²⁵⁷ - Add functionality to copy construct a component
- Issue #859⁶²⁵⁸ - `hpx::endl` should flush

⁶²³⁶ <https://github.com/TheHPXProject/hpx/issues/886>

⁶²³⁷ <https://github.com/TheHPXProject/hpx/issues/885>

⁶²³⁸ <https://github.com/TheHPXProject/hpx/issues/884>

⁶²³⁹ <https://github.com/TheHPXProject/hpx/issues/883>

⁶²⁴⁰ <https://github.com/TheHPXProject/hpx/issues/882>

⁶²⁴¹ <https://github.com/TheHPXProject/hpx/issues/881>

⁶²⁴² <https://github.com/TheHPXProject/hpx/issues/880>

⁶²⁴³ <https://github.com/TheHPXProject/hpx/issues/878>

⁶²⁴⁴ <https://github.com/TheHPXProject/hpx/issues/877>

⁶²⁴⁵ <https://github.com/TheHPXProject/hpx/issues/876>

⁶²⁴⁶ <https://github.com/TheHPXProject/hpx/issues/875>

⁶²⁴⁷ <https://github.com/TheHPXProject/hpx/issues/874>

⁶²⁴⁸ <https://github.com/TheHPXProject/hpx/issues/873>

⁶²⁴⁹ <https://github.com/TheHPXProject/hpx/issues/872>

⁶²⁵⁰ <https://github.com/TheHPXProject/hpx/issues/871>

⁶²⁵¹ <https://github.com/TheHPXProject/hpx/issues/870>

⁶²⁵² <https://github.com/TheHPXProject/hpx/issues/868>

⁶²⁵³ <https://github.com/TheHPXProject/hpx/issues/867>

⁶²⁵⁴ <https://github.com/TheHPXProject/hpx/issues/863>

⁶²⁵⁵ <https://github.com/TheHPXProject/hpx/issues/862>

⁶²⁵⁶ <https://github.com/TheHPXProject/hpx/issues/861>

⁶²⁵⁷ <https://github.com/TheHPXProject/hpx/issues/860>

⁶²⁵⁸ <https://github.com/TheHPXProject/hpx/issues/859>

- Issue #858⁶²⁵⁹ - Create `hpx::get_ptr<>` allowing to access component implementation
- Issue #855⁶²⁶⁰ - Implement `hpx::INVOKE`
- Issue #854⁶²⁶¹ - `hpx/hpx.hpp` does not include `hpx/include/iostreams.hpp`
- Issue #853⁶²⁶² - Feature request: null future
- Issue #852⁶²⁶³ - Feature request: Locality names
- Issue #851⁶²⁶⁴ - `hpx::cout` output does not appear on screen
- Issue #849⁶²⁶⁵ - All tests fail on OS X after installing
- Issue #848⁶²⁶⁶ - Update OS X build instructions
- Issue #846⁶²⁶⁷ - Update `hpx_external_example`
- Issue #845⁶²⁶⁸ - Issues with having both debug and release modules in the same directory
- Issue #844⁶²⁶⁹ - Create configuration header
- Issue #843⁶²⁷⁰ - Tests should use CTest
- Issue #842⁶²⁷¹ - Remove `buffer_pool` from MPI parcelport
- Issue #841⁶²⁷² - Add possibility to broadcast an index with `hpx::lcos::broadcast`
- Issue #838⁶²⁷³ - Simplify `util::tuple`
- Issue #837⁶²⁷⁴ - Adopt `boost::tuple` tests for `util::tuple`
- Issue #836⁶²⁷⁵ - Adopt `boost::function` tests for `util::function`
- Issue #835⁶²⁷⁶ - Tuple interface missing pieces
- Issue #833⁶²⁷⁷ - Partially preprocessing files not working
- Issue #832⁶²⁷⁸ - Native papi counters do not work with wild cards
- Issue #831⁶²⁷⁹ - Arithmetics counter fails if only one parameter is given
- Issue #830⁶²⁸⁰ - Convert `hpx::util::function` to use new scheme for serializing its base pointer
- Issue #829⁶²⁸¹ - Consistently use `decay<T>` instead of `remove_const< remove_reference<T>>`

⁶²⁵⁹ <https://github.com/TheHPXProject/hpx/issues/858>

⁶²⁶⁰ <https://github.com/TheHPXProject/hpx/issues/855>

⁶²⁶¹ <https://github.com/TheHPXProject/hpx/issues/854>

⁶²⁶² <https://github.com/TheHPXProject/hpx/issues/853>

⁶²⁶³ <https://github.com/TheHPXProject/hpx/issues/852>

⁶²⁶⁴ <https://github.com/TheHPXProject/hpx/issues/851>

⁶²⁶⁵ <https://github.com/TheHPXProject/hpx/issues/849>

⁶²⁶⁶ <https://github.com/TheHPXProject/hpx/issues/848>

⁶²⁶⁷ <https://github.com/TheHPXProject/hpx/issues/846>

⁶²⁶⁸ <https://github.com/TheHPXProject/hpx/issues/845>

⁶²⁶⁹ <https://github.com/TheHPXProject/hpx/issues/844>

⁶²⁷⁰ <https://github.com/TheHPXProject/hpx/issues/843>

⁶²⁷¹ <https://github.com/TheHPXProject/hpx/issues/842>

⁶²⁷² <https://github.com/TheHPXProject/hpx/issues/841>

⁶²⁷³ <https://github.com/TheHPXProject/hpx/issues/838>

⁶²⁷⁴ <https://github.com/TheHPXProject/hpx/issues/837>

⁶²⁷⁵ <https://github.com/TheHPXProject/hpx/issues/836>

⁶²⁷⁶ <https://github.com/TheHPXProject/hpx/issues/835>

⁶²⁷⁷ <https://github.com/TheHPXProject/hpx/issues/833>

⁶²⁷⁸ <https://github.com/TheHPXProject/hpx/issues/832>

⁶²⁷⁹ <https://github.com/TheHPXProject/hpx/issues/831>

⁶²⁸⁰ <https://github.com/TheHPXProject/hpx/issues/830>

⁶²⁸¹ <https://github.com/TheHPXProject/hpx/issues/829>

- [Issue #828](#)⁶²⁸² - Update future implementation to N3721 and N3722
- [Issue #827](#)⁶²⁸³ - Enable MPI parcelport for bootstrapping whenever application was started using mpirun
- [Issue #826](#)⁶²⁸⁴ - Support command line option `--hpx:print-bind` even if `--hpx::bind` was not used
- [Issue #825](#)⁶²⁸⁵ - Memory counters give segfault when attempting to use thread wild cards or numbers only total works
- [Issue #824](#)⁶²⁸⁶ - Enable lambda functions to be used with `hpx::async/hpx::apply`
- [Issue #823](#)⁶²⁸⁷ - Using a hashing filter
- [Issue #822](#)⁶²⁸⁸ - Silence unused variable warning
- [Issue #821](#)⁶²⁸⁹ - Detect if a function object is callable with given arguments
- [Issue #820](#)⁶²⁹⁰ - Allow wildcards to be used for performance counter names
- [Issue #819](#)⁶²⁹¹ - Make the AGAS symbolic name registry distributed
- [Issue #818](#)⁶²⁹² - Add `future::then()` overload taking an executor
- [Issue #817](#)⁶²⁹³ - Fixed typo
- [Issue #815](#)⁶²⁹⁴ - Create an lco that is performing an efficient broadcast of actions
- [Issue #814](#)⁶²⁹⁵ - Papi counters cannot specify `thread#*` to get the counts for all threads
- [Issue #813](#)⁶²⁹⁶ - Scoped unlock
- [Issue #811](#)⁶²⁹⁷ - `simple_central_tuplespace_client` run error
- [Issue #810](#)⁶²⁹⁸ - ostream error when `<<` any objects
- [Issue #809](#)⁶²⁹⁹ - Optimize parcel serialization
- [Issue #808](#)⁶³⁰⁰ - HPX applications throw exception when executed from the build directory
- [Issue #807](#)⁶³⁰¹ - Create performance counters exposing overall AGAS statistics
- [Issue #795](#)⁶³⁰² - Create timed `make_ready_future`
- [Issue #794](#)⁶³⁰³ - Create heterogeneous `when_all/when_any/etc.`
- [Issue #721](#)⁶³⁰⁴ - Make HPX usable for Xeon Phi

⁶²⁸² <https://github.com/TheHPXProject/hpx/issues/828>

⁶²⁸³ <https://github.com/TheHPXProject/hpx/issues/827>

⁶²⁸⁴ <https://github.com/TheHPXProject/hpx/issues/826>

⁶²⁸⁵ <https://github.com/TheHPXProject/hpx/issues/825>

⁶²⁸⁶ <https://github.com/TheHPXProject/hpx/issues/824>

⁶²⁸⁷ <https://github.com/TheHPXProject/hpx/issues/823>

⁶²⁸⁸ <https://github.com/TheHPXProject/hpx/issues/822>

⁶²⁸⁹ <https://github.com/TheHPXProject/hpx/issues/821>

⁶²⁹⁰ <https://github.com/TheHPXProject/hpx/issues/820>

⁶²⁹¹ <https://github.com/TheHPXProject/hpx/issues/819>

⁶²⁹² <https://github.com/TheHPXProject/hpx/issues/818>

⁶²⁹³ <https://github.com/TheHPXProject/hpx/issues/817>

⁶²⁹⁴ <https://github.com/TheHPXProject/hpx/issues/815>

⁶²⁹⁵ <https://github.com/TheHPXProject/hpx/issues/814>

⁶²⁹⁶ <https://github.com/TheHPXProject/hpx/issues/813>

⁶²⁹⁷ <https://github.com/TheHPXProject/hpx/issues/811>

⁶²⁹⁸ <https://github.com/TheHPXProject/hpx/issues/810>

⁶²⁹⁹ <https://github.com/TheHPXProject/hpx/issues/809>

⁶³⁰⁰ <https://github.com/TheHPXProject/hpx/issues/808>

⁶³⁰¹ <https://github.com/TheHPXProject/hpx/issues/807>

⁶³⁰² <https://github.com/TheHPXProject/hpx/issues/795>

⁶³⁰³ <https://github.com/TheHPXProject/hpx/issues/794>

⁶³⁰⁴ <https://github.com/TheHPXProject/hpx/issues/721>

- Issue #694⁶³⁰⁵ - CMake should complain if you attempt to build an example without its dependencies
- Issue #692⁶³⁰⁶ - SLURM support broken
- Issue #683⁶³⁰⁷ - python/hpx/process.py imports epoll on all platforms
- Issue #619⁶³⁰⁸ - Automate the doc building process
- Issue #600⁶³⁰⁹ - GTC performance broken
- Issue #577⁶³¹⁰ - Allow for zero copy serialization/networking
- Issue #551⁶³¹¹ - Change executable names to have debug postfix in Debug builds
- Issue #544⁶³¹² - Write a custom .lib file on Windows pulling in hpx_init and hpx.dll, phase out hpx_init
- Issue #534⁶³¹³ - `hpx::init` should take functions by `std::function` and should accept all forms of `hpx_main`
- Issue #508⁶³¹⁴ - FindPackage fails to set FOO_LIBRARY_DIR
- Issue #506⁶³¹⁵ - Add cmake support to generate ini files for external applications
- Issue #470⁶³¹⁶ - Changing build-type after configure does not update boost library names
- Issue #453⁶³¹⁷ - Document `hpx_run_tests.py`
- Issue #445⁶³¹⁸ - Significant performance mismatch between MPI and HPX in SMP for allgather example
- Issue #443⁶³¹⁹ - Make docs viewable from build directory
- Issue #421⁶³²⁰ - Support multiple HPX instances per node in a batch environment like PBS or SLURM
- Issue #316⁶³²¹ - Add message size limitation
- Issue #249⁶³²² - Clean up locking code in big boot barrier
- Issue #136⁶³²³ - Persistent CMake variables need to be marked as cache variables

⁶³⁰⁵ <https://github.com/TheHPXProject/hpx/issues/694>

⁶³⁰⁶ <https://github.com/TheHPXProject/hpx/issues/692>

⁶³⁰⁷ <https://github.com/TheHPXProject/hpx/issues/683>

⁶³⁰⁸ <https://github.com/TheHPXProject/hpx/issues/619>

⁶³⁰⁹ <https://github.com/TheHPXProject/hpx/issues/600>

⁶³¹⁰ <https://github.com/TheHPXProject/hpx/issues/577>

⁶³¹¹ <https://github.com/TheHPXProject/hpx/issues/551>

⁶³¹² <https://github.com/TheHPXProject/hpx/issues/544>

⁶³¹³ <https://github.com/TheHPXProject/hpx/issues/534>

⁶³¹⁴ <https://github.com/TheHPXProject/hpx/issues/508>

⁶³¹⁵ <https://github.com/TheHPXProject/hpx/issues/506>

⁶³¹⁶ <https://github.com/TheHPXProject/hpx/issues/470>

⁶³¹⁷ <https://github.com/TheHPXProject/hpx/issues/453>

⁶³¹⁸ <https://github.com/TheHPXProject/hpx/issues/445>

⁶³¹⁹ <https://github.com/TheHPXProject/hpx/issues/443>

⁶³²⁰ <https://github.com/TheHPXProject/hpx/issues/421>

⁶³²¹ <https://github.com/TheHPXProject/hpx/issues/316>

⁶³²² <https://github.com/TheHPXProject/hpx/issues/249>

⁶³²³ <https://github.com/TheHPXProject/hpx/issues/136>

HPX V0.9.6 (Jul 30, 2013)

We have had over 1200 commits since the last release and we have closed roughly 140 tickets (bugs, feature requests, etc.).

General changes

The major new features in this release are:

- We further consolidated the API exposed by *HPX*. We aligned our APIs as much as possible with the existing C++11 Standard⁶³²⁴ and related proposals to the C++ standardization committee (such as N3632⁶³²⁵ and N3857⁶³²⁶).
- We implemented a first version of a distributed AGAS service which essentially eliminates all explicit AGAS network traffic.
- We created a native *ibverbs* *parcelport* allowing to take advantage of the superior latency and bandwidth characteristics of *Infiniband* networks.
- We successfully ported *HPX* to the Xeon Phi platform.
- Support for the SLURM scheduling system was implemented.
- Major efforts have been dedicated to improving the performance counter framework, numerous new counters were implemented and new APIs were added.
- We added a modular parcel compression system allowing to improve bandwidth utilization (by reducing the overall size of the transferred data).
- We added a modular parcel coalescing system allowing to combine several parcels into larger messages. This reduces latencies introduced by the communication layer.
- Added an experimental executors API allowing to use different scheduling policies for different parts of the code. This API has been modelled after the Standards proposal N3562⁶³²⁷. This API is bound to change in the future, though.
- Added minimal security support for localities which is enforced on the *parcelport* level. This support is preliminary and experimental and might change in the future.
- We created a *parcelport* using low level MPI functions. This is in support of legacy applications which are to be gradually ported and to support platforms where MPI is the only available portable networking layer.
- We added a preliminary and experimental implementation of a tuple-space object which exposes an interface similar to such systems described in the literature (see for instance *The Linda Coordination Language*⁶³²⁸).

⁶³²⁴ <http://www.open-std.org/jtc1/sc22/wg21>

⁶³²⁵ <http://wg21.link/n3632>

⁶³²⁶ <http://wg21.link/n3857>

⁶³²⁷ <http://wg21.link/n3562>

⁶³²⁸ [https://en.wikipedia.org/wiki/Linda_\(coordination_language\)](https://en.wikipedia.org/wiki/Linda_(coordination_language))

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release. This is again a very long list of newly implemented features and fixed issues.

- [Issue #806](#)⁶³²⁹ - make (all) in examples folder does nothing
- [Issue #805](#)⁶³³⁰ - Adding the introduction and fixing DOCTEST dependencies for Windows use
- [Issue #804](#)⁶³³¹ - Add stackless (non-suspendable) thread type
- [Issue #803](#)⁶³³² - Create proper serialization support functions for util::tuple
- [Issue #800](#)⁶³³³ - Add possibility to disable array optimizations during serialization
- [Issue #798](#)⁶³³⁴ - HPX_LIMIT does not work for local dataflow
- [Issue #797](#)⁶³³⁵ - Create a parcelport which uses MPI
- [Issue #796](#)⁶³³⁶ - Problem with Large Numbers of Threads
- [Issue #793](#)⁶³³⁷ - Changing dataflow test case to hang consistently
- [Issue #792](#)⁶³³⁸ - CMake Error
- [Issue #791](#)⁶³³⁹ - Problems with local::dataflow
- [Issue #790](#)⁶³⁴⁰ - wait_for() doesn't compile
- [Issue #789](#)⁶³⁴¹ - HPX with Intel compiler segfaults
- [Issue #788](#)⁶³⁴² - Intel compiler support
- [Issue #787](#)⁶³⁴³ - Fixed SFINAE specializations
- [Issue #786](#)⁶³⁴⁴ - Memory issues during benchmarking.
- [Issue #785](#)⁶³⁴⁵ - Create an API allowing to register external threads with HPX
- [Issue #784](#)⁶³⁴⁶ - util::plugin is throwing an error when a symbol is not found
- [Issue #783](#)⁶³⁴⁷ - How does hpx::bind work?
- [Issue #782](#)⁶³⁴⁸ - Added quotes around STRING REPLACE potentially empty arguments
- [Issue #781](#)⁶³⁴⁹ - Make sure no exceptions propagate into the thread manager

⁶³²⁹ <https://github.com/TheHPXProject/hpx/issues/806>

⁶³³⁰ <https://github.com/TheHPXProject/hpx/issues/805>

⁶³³¹ <https://github.com/TheHPXProject/hpx/issues/804>

⁶³³² <https://github.com/TheHPXProject/hpx/issues/803>

⁶³³³ <https://github.com/TheHPXProject/hpx/issues/800>

⁶³³⁴ <https://github.com/TheHPXProject/hpx/issues/798>

⁶³³⁵ <https://github.com/TheHPXProject/hpx/issues/797>

⁶³³⁶ <https://github.com/TheHPXProject/hpx/issues/796>

⁶³³⁷ <https://github.com/TheHPXProject/hpx/issues/793>

⁶³³⁸ <https://github.com/TheHPXProject/hpx/issues/792>

⁶³³⁹ <https://github.com/TheHPXProject/hpx/issues/791>

⁶³⁴⁰ <https://github.com/TheHPXProject/hpx/issues/790>

⁶³⁴¹ <https://github.com/TheHPXProject/hpx/issues/789>

⁶³⁴² <https://github.com/TheHPXProject/hpx/issues/788>

⁶³⁴³ <https://github.com/TheHPXProject/hpx/issues/787>

⁶³⁴⁴ <https://github.com/TheHPXProject/hpx/issues/786>

⁶³⁴⁵ <https://github.com/TheHPXProject/hpx/issues/785>

⁶³⁴⁶ <https://github.com/TheHPXProject/hpx/issues/784>

⁶³⁴⁷ <https://github.com/TheHPXProject/hpx/issues/783>

⁶³⁴⁸ <https://github.com/TheHPXProject/hpx/issues/782>

⁶³⁴⁹ <https://github.com/TheHPXProject/hpx/issues/781>

- [Issue #780](#)⁶³⁵⁰ - Allow arithmetics performance counters to expand its parameters
- [Issue #779](#)⁶³⁵¹ - Test case for 778
- [Issue #778](#)⁶³⁵² - Swapping futures segfaults
- [Issue #777](#)⁶³⁵³ - `hpx::lcos::details::when_xxx` don't restore completion handlers
- [Issue #776](#)⁶³⁵⁴ - Compiler chokes on dataflow overload with launch policy
- [Issue #775](#)⁶³⁵⁵ - Runtime error with local dataflow (copying futures?)
- [Issue #774](#)⁶³⁵⁶ - Using local dataflow without explicit namespace
- [Issue #773](#)⁶³⁵⁷ - Local dataflow with unwrap: functor operators need to be const
- [Issue #772](#)⁶³⁵⁸ - Allow (remote) actions to return a future
- [Issue #771](#)⁶³⁵⁹ - Setting `HPX_LIMIT` gives huge boost MPL errors
- [Issue #770](#)⁶³⁶⁰ - Add launch policy to (local) dataflow
- [Issue #769](#)⁶³⁶¹ - Make compile time configuration information available
- [Issue #768](#)⁶³⁶² - Const correctness problem in local dataflow
- [Issue #767](#)⁶³⁶³ - Add launch policies to async
- [Issue #766](#)⁶³⁶⁴ - Mark data structures for optimized (array based) serialization
- [Issue #765](#)⁶³⁶⁵ - Align `hpx::any` with N3508: Any Library Proposal (Revision 2)
- [Issue #764](#)⁶³⁶⁶ - Align `hpx::future` with newest N3558: A Standardized Representation of Asynchronous Operations
- [Issue #762](#)⁶³⁶⁷ - added a human readable output for the ping pong example
- [Issue #761](#)⁶³⁶⁸ - Ambiguous typename when constructing derived component
- [Issue #760](#)⁶³⁶⁹ - Simple components can not be derived
- [Issue #759](#)⁶³⁷⁰ - make install doesn't give a complete install
- [Issue #758](#)⁶³⁷¹ - Stack overflow when using `locking_hook<>`
- [Issue #757](#)⁶³⁷² - copy paste error; unsupported function overloading

⁶³⁵⁰ <https://github.com/TheHPXProject/hpx/issues/780>

⁶³⁵¹ <https://github.com/TheHPXProject/hpx/issues/779>

⁶³⁵² <https://github.com/TheHPXProject/hpx/issues/778>

⁶³⁵³ <https://github.com/TheHPXProject/hpx/issues/777>

⁶³⁵⁴ <https://github.com/TheHPXProject/hpx/issues/776>

⁶³⁵⁵ <https://github.com/TheHPXProject/hpx/issues/775>

⁶³⁵⁶ <https://github.com/TheHPXProject/hpx/issues/774>

⁶³⁵⁷ <https://github.com/TheHPXProject/hpx/issues/773>

⁶³⁵⁸ <https://github.com/TheHPXProject/hpx/issues/772>

⁶³⁵⁹ <https://github.com/TheHPXProject/hpx/issues/771>

⁶³⁶⁰ <https://github.com/TheHPXProject/hpx/issues/770>

⁶³⁶¹ <https://github.com/TheHPXProject/hpx/issues/769>

⁶³⁶² <https://github.com/TheHPXProject/hpx/issues/768>

⁶³⁶³ <https://github.com/TheHPXProject/hpx/issues/767>

⁶³⁶⁴ <https://github.com/TheHPXProject/hpx/issues/766>

⁶³⁶⁵ <https://github.com/TheHPXProject/hpx/issues/765>

⁶³⁶⁶ <https://github.com/TheHPXProject/hpx/issues/764>

⁶³⁶⁷ <https://github.com/TheHPXProject/hpx/issues/762>

⁶³⁶⁸ <https://github.com/TheHPXProject/hpx/issues/761>

⁶³⁶⁹ <https://github.com/TheHPXProject/hpx/issues/760>

⁶³⁷⁰ <https://github.com/TheHPXProject/hpx/issues/759>

⁶³⁷¹ <https://github.com/TheHPXProject/hpx/issues/758>

⁶³⁷² <https://github.com/TheHPXProject/hpx/issues/757>

- Issue #756⁶³⁷³ - GTCX runtime issue in Gordon
- Issue #755⁶³⁷⁴ - Papi counters don't work with reset and evaluate API's
- Issue #753⁶³⁷⁵ - cmake bugfix and improved component action docs
- Issue #752⁶³⁷⁶ - hpx simple component docs
- Issue #750⁶³⁷⁷ - Add hpx::util::any
- Issue #749⁶³⁷⁸ - Thread phase counter is not reset
- Issue #748⁶³⁷⁹ - Memory performance counter are not registered
- Issue #747⁶³⁸⁰ - Create performance counters exposing arithmetic operations
- Issue #745⁶³⁸¹ - apply_callback needs to invoke callback when applied locally
- Issue #744⁶³⁸² - CMake fixes
- Issue #743⁶³⁸³ - Problem Building github version of HPX
- Issue #742⁶³⁸⁴ - Remove HPX_STD_BIND
- Issue #741⁶³⁸⁵ - assertion 'px != 0' failed: HPX(assertion_failure) for low numbers of OS threads
- Issue #739⁶³⁸⁶ - Performance counters do not count to the end of the program or evaluation
- Issue #738⁶³⁸⁷ - Dedicated AGAS server runs don't work; console ignores -a option.
- Issue #737⁶³⁸⁸ - Missing bind overloads
- Issue #736⁶³⁸⁹ - Performance counter wildcards do not always work
- Issue #735⁶³⁹⁰ - Create native ibverbs parcelport based on rdma operations
- Issue #734⁶³⁹¹ - Threads stolen performance counter total is incorrect
- Issue #733⁶³⁹² - Test benchmarks need to be checked and fixed
- Issue #732⁶³⁹³ - Build fails with Mac, using mac ports clang-3.3 on latest git branch
- Issue #731⁶³⁹⁴ - Add global start/stop API for performance counters
- Issue #730⁶³⁹⁵ - Performance counter values are apparently incorrect

⁶³⁷³ <https://github.com/TheHPXProject/hpx/issues/756>

⁶³⁷⁴ <https://github.com/TheHPXProject/hpx/issues/755>

⁶³⁷⁵ <https://github.com/TheHPXProject/hpx/issues/753>

⁶³⁷⁶ <https://github.com/TheHPXProject/hpx/issues/752>

⁶³⁷⁷ <https://github.com/TheHPXProject/hpx/issues/750>

⁶³⁷⁸ <https://github.com/TheHPXProject/hpx/issues/749>

⁶³⁷⁹ <https://github.com/TheHPXProject/hpx/issues/748>

⁶³⁸⁰ <https://github.com/TheHPXProject/hpx/issues/747>

⁶³⁸¹ <https://github.com/TheHPXProject/hpx/issues/745>

⁶³⁸² <https://github.com/TheHPXProject/hpx/issues/744>

⁶³⁸³ <https://github.com/TheHPXProject/hpx/issues/743>

⁶³⁸⁴ <https://github.com/TheHPXProject/hpx/issues/742>

⁶³⁸⁵ <https://github.com/TheHPXProject/hpx/issues/741>

⁶³⁸⁶ <https://github.com/TheHPXProject/hpx/issues/739>

⁶³⁸⁷ <https://github.com/TheHPXProject/hpx/issues/738>

⁶³⁸⁸ <https://github.com/TheHPXProject/hpx/issues/737>

⁶³⁸⁹ <https://github.com/TheHPXProject/hpx/issues/736>

⁶³⁹⁰ <https://github.com/TheHPXProject/hpx/issues/735>

⁶³⁹¹ <https://github.com/TheHPXProject/hpx/issues/734>

⁶³⁹² <https://github.com/TheHPXProject/hpx/issues/733>

⁶³⁹³ <https://github.com/TheHPXProject/hpx/issues/732>

⁶³⁹⁴ <https://github.com/TheHPXProject/hpx/issues/731>

⁶³⁹⁵ <https://github.com/TheHPXProject/hpx/issues/730>

- Issue #729⁶³⁹⁶ - Unhandled switch
- Issue #728⁶³⁹⁷ - Serialization of `hpx::util::function` between two localities causes seg faults
- Issue #727⁶³⁹⁸ - Memory counters on Mac OS X
- Issue #725⁶³⁹⁹ - Restore original thread priority on resume
- Issue #724⁶⁴⁰⁰ - Performance benchmarks do not depend on main HPX libraries
- Issue #723⁶⁴⁰¹ - `[teletype]-hpx:nodes=`cat $PBS_NODEFILE`` works; `-hpx:nodefile=$PBS_NODEFILE` does not.`[c++]`
- Issue #722⁶⁴⁰² - Fix binding `const` member functions as actions
- Issue #719⁶⁴⁰³ - Create performance counter exposing compression ratio
- Issue #718⁶⁴⁰⁴ - Add possibility to compress parcel data
- Issue #717⁶⁴⁰⁵ - `strip_credit_from_gid` has misleading semantics
- Issue #716⁶⁴⁰⁶ - Non-option arguments to programs run using `pbsdsh` must be before `--hpx:nodes`, contrary to directions
- Issue #715⁶⁴⁰⁷ - Re-thrown exceptions should retain the original call site
- Issue #714⁶⁴⁰⁸ - failed assertion in debug mode
- Issue #713⁶⁴⁰⁹ - Add performance counters monitoring connection caches
- Issue #712⁶⁴¹⁰ - Adjust parcel related performance counters to be connection type specific
- Issue #711⁶⁴¹¹ - configuration failure
- Issue #710⁶⁴¹² - Error “timed out while trying to find room in the connection cache” when trying to start multiple localities on a single computer
- Issue #709⁶⁴¹³ - Add new thread state ‘staged’ referring to task descriptions
- Issue #708⁶⁴¹⁴ - Detect/mitigate bad non-system installs of GCC on Redhat systems
- Issue #707⁶⁴¹⁵ - Many examples do not link with Git HEAD version
- Issue #706⁶⁴¹⁶ - `hpx::init` removes portions of non-option command line arguments before last = sign
- Issue #705⁶⁴¹⁷ - Create rolling average and median aggregating performance counters

⁶³⁹⁶ <https://github.com/TheHPXProject/hpx/issues/729>

⁶³⁹⁷ <https://github.com/TheHPXProject/hpx/issues/728>

⁶³⁹⁸ <https://github.com/TheHPXProject/hpx/issues/727>

⁶³⁹⁹ <https://github.com/TheHPXProject/hpx/issues/725>

⁶⁴⁰⁰ <https://github.com/TheHPXProject/hpx/issues/724>

⁶⁴⁰¹ <https://github.com/TheHPXProject/hpx/issues/723>

⁶⁴⁰² <https://github.com/TheHPXProject/hpx/issues/722>

⁶⁴⁰³ <https://github.com/TheHPXProject/hpx/issues/719>

⁶⁴⁰⁴ <https://github.com/TheHPXProject/hpx/issues/718>

⁶⁴⁰⁵ <https://github.com/TheHPXProject/hpx/issues/717>

⁶⁴⁰⁶ <https://github.com/TheHPXProject/hpx/issues/716>

⁶⁴⁰⁷ <https://github.com/TheHPXProject/hpx/issues/715>

⁶⁴⁰⁸ <https://github.com/TheHPXProject/hpx/issues/714>

⁶⁴⁰⁹ <https://github.com/TheHPXProject/hpx/issues/713>

⁶⁴¹⁰ <https://github.com/TheHPXProject/hpx/issues/712>

⁶⁴¹¹ <https://github.com/TheHPXProject/hpx/issues/711>

⁶⁴¹² <https://github.com/TheHPXProject/hpx/issues/710>

⁶⁴¹³ <https://github.com/TheHPXProject/hpx/issues/709>

⁶⁴¹⁴ <https://github.com/TheHPXProject/hpx/issues/708>

⁶⁴¹⁵ <https://github.com/TheHPXProject/hpx/issues/707>

⁶⁴¹⁶ <https://github.com/TheHPXProject/hpx/issues/706>

⁶⁴¹⁷ <https://github.com/TheHPXProject/hpx/issues/705>

- Issue #704⁶⁴¹⁸ - Create performance counter to expose thread queue waiting time
- Issue #703⁶⁴¹⁹ - Add support to HPX build system to find libcrtool.a and related headers
- Issue #699⁶⁴²⁰ - Generalize instrumentation support
- Issue #698⁶⁴²¹ - compilation failure with hwloc absent
- Issue #697⁶⁴²² - Performance counter counts should be zero indexed
- Issue #696⁶⁴²³ - Distributed problem
- Issue #695⁶⁴²⁴ - Bad perf counter time printed
- Issue #693⁶⁴²⁵ - --help doesn't print component specific command line options
- Issue #692⁶⁴²⁶ - SLURM support broken
- Issue #691⁶⁴²⁷ - exception while executing any application linked with hwloc
- Issue #690⁶⁴²⁸ - thread_id_test and thread_launcher_test failing
- Issue #689⁶⁴²⁹ - Make the buildbots use hwloc
- Issue #687⁶⁴³⁰ - compilation error fix (hwloc_topology)
- Issue #686⁶⁴³¹ - Linker Error for Applications
- Issue #684⁶⁴³² - Pinning of service thread fails when number of worker threads equals the number of cores
- Issue #682⁶⁴³³ - Add performance counters exposing number of stolen threads
- Issue #681⁶⁴³⁴ - Add apply_continue for asynchronous chaining of actions
- Issue #679⁶⁴³⁵ - Remove obsolete async_callback API functions
- Issue #678⁶⁴³⁶ - Add new API for setting/triggering LCOs
- Issue #677⁶⁴³⁷ - Add async_continue for true continuation style actions
- Issue #676⁶⁴³⁸ - Buildbot for gcc 4.4 broken
- Issue #675⁶⁴³⁹ - Partial preprocessing broken
- Issue #674⁶⁴⁴⁰ - HPX segfaults when built with gcc 4.7

⁶⁴¹⁸ <https://github.com/TheHPXProject/hpx/issues/704>

⁶⁴¹⁹ <https://github.com/TheHPXProject/hpx/issues/703>

⁶⁴²⁰ <https://github.com/TheHPXProject/hpx/issues/699>

⁶⁴²¹ <https://github.com/TheHPXProject/hpx/issues/698>

⁶⁴²² <https://github.com/TheHPXProject/hpx/issues/697>

⁶⁴²³ <https://github.com/TheHPXProject/hpx/issues/696>

⁶⁴²⁴ <https://github.com/TheHPXProject/hpx/issues/695>

⁶⁴²⁵ <https://github.com/TheHPXProject/hpx/issues/693>

⁶⁴²⁶ <https://github.com/TheHPXProject/hpx/issues/692>

⁶⁴²⁷ <https://github.com/TheHPXProject/hpx/issues/691>

⁶⁴²⁸ <https://github.com/TheHPXProject/hpx/issues/690>

⁶⁴²⁹ <https://github.com/TheHPXProject/hpx/issues/689>

⁶⁴³⁰ <https://github.com/TheHPXProject/hpx/issues/687>

⁶⁴³¹ <https://github.com/TheHPXProject/hpx/issues/686>

⁶⁴³² <https://github.com/TheHPXProject/hpx/issues/684>

⁶⁴³³ <https://github.com/TheHPXProject/hpx/issues/682>

⁶⁴³⁴ <https://github.com/TheHPXProject/hpx/issues/681>

⁶⁴³⁵ <https://github.com/TheHPXProject/hpx/issues/679>

⁶⁴³⁶ <https://github.com/TheHPXProject/hpx/issues/678>

⁶⁴³⁷ <https://github.com/TheHPXProject/hpx/issues/677>

⁶⁴³⁸ <https://github.com/TheHPXProject/hpx/issues/676>

⁶⁴³⁹ <https://github.com/TheHPXProject/hpx/issues/675>

⁶⁴⁴⁰ <https://github.com/TheHPXProject/hpx/issues/674>

- Issue #673⁶⁴⁴¹ - `use_guard_pages` has inconsistent preprocessor guards
- Issue #672⁶⁴⁴² - External build breaks if library path has spaces
- Issue #671⁶⁴⁴³ - release tarballs are tarbombs
- Issue #670⁶⁴⁴⁴ - CMake won't find Boost headers in `layout=versioned` install
- Issue #669⁶⁴⁴⁵ - Links in docs to source files broken if not installed
- Issue #667⁶⁴⁴⁶ - Not reading ini file properly
- Issue #664⁶⁴⁴⁷ - Adapt new meanings of 'const' and 'mutable'
- Issue #661⁶⁴⁴⁸ - Implement BTL Parcel port
- Issue #655⁶⁴⁴⁹ - Make HPX work with the "decltype" result_of
- Issue #647⁶⁴⁵⁰ - documentation for specifying the number of high priority threads
--`hpx:high-priority-threads`
- Issue #643⁶⁴⁵¹ - Error parsing host file
- Issue #642⁶⁴⁵² - HWLoc issue with TAU
- Issue #639⁶⁴⁵³ - Logging potentially suspends a running thread
- Issue #634⁶⁴⁵⁴ - Improve error reporting from parcel layer
- Issue #627⁶⁴⁵⁵ - Add tests for async and apply overloads that accept regular C++ functions
- Issue #626⁶⁴⁵⁶ - `hpx/future.hpp` header
- Issue #601⁶⁴⁵⁷ - Intel support
- Issue #557⁶⁴⁵⁸ - Remove action codes
- Issue #531⁶⁴⁵⁹ - AGAS request and response classes should use switch statements
- Issue #529⁶⁴⁶⁰ - Investigate the state of hwloc support
- Issue #526⁶⁴⁶¹ - Make HPX aware of hyper-threading
- Issue #518⁶⁴⁶² - Create facilities allowing to use plain arrays as action arguments
- Issue #473⁶⁴⁶³ - hwloc thread binding is broken on CPUs with hyperthreading

⁶⁴⁴¹ <https://github.com/TheHPXProject/hpx/issues/673>

⁶⁴⁴² <https://github.com/TheHPXProject/hpx/issues/672>

⁶⁴⁴³ <https://github.com/TheHPXProject/hpx/issues/671>

⁶⁴⁴⁴ <https://github.com/TheHPXProject/hpx/issues/670>

⁶⁴⁴⁵ <https://github.com/TheHPXProject/hpx/issues/669>

⁶⁴⁴⁶ <https://github.com/TheHPXProject/hpx/issues/667>

⁶⁴⁴⁷ <https://github.com/TheHPXProject/hpx/issues/664>

⁶⁴⁴⁸ <https://github.com/TheHPXProject/hpx/issues/661>

⁶⁴⁴⁹ <https://github.com/TheHPXProject/hpx/issues/655>

⁶⁴⁵⁰ <https://github.com/TheHPXProject/hpx/issues/647>

⁶⁴⁵¹ <https://github.com/TheHPXProject/hpx/issues/643>

⁶⁴⁵² <https://github.com/TheHPXProject/hpx/issues/642>

⁶⁴⁵³ <https://github.com/TheHPXProject/hpx/issues/639>

⁶⁴⁵⁴ <https://github.com/TheHPXProject/hpx/issues/634>

⁶⁴⁵⁵ <https://github.com/TheHPXProject/hpx/issues/627>

⁶⁴⁵⁶ <https://github.com/TheHPXProject/hpx/issues/626>

⁶⁴⁵⁷ <https://github.com/TheHPXProject/hpx/issues/601>

⁶⁴⁵⁸ <https://github.com/TheHPXProject/hpx/issues/557>

⁶⁴⁵⁹ <https://github.com/TheHPXProject/hpx/issues/531>

⁶⁴⁶⁰ <https://github.com/TheHPXProject/hpx/issues/529>

⁶⁴⁶¹ <https://github.com/TheHPXProject/hpx/issues/526>

⁶⁴⁶² <https://github.com/TheHPXProject/hpx/issues/518>

⁶⁴⁶³ <https://github.com/TheHPXProject/hpx/issues/473>

- [Issue #383](#)⁶⁴⁶⁴ - Change result type detection for `hpx::util::bind` to use `result_of` protocol
- [Issue #341](#)⁶⁴⁶⁵ - Consolidate route code
- [Issue #219](#)⁶⁴⁶⁶ - Only copy arguments into actions once
- [Issue #177](#)⁶⁴⁶⁷ - Implement distributed AGAS
- [Issue #43](#)⁶⁴⁶⁸ - Support for Darwin (Xcode + Clang)

HPX V0.9.5 (Jan 16, 2013)

We have had over 1000 commits since the last release and we have closed roughly 150 tickets (bugs, feature requests, etc.).

General changes

This release is continuing along the lines of code and API consolidation, and overall usability improvements. We dedicated much attention to performance and we were able to significantly improve the threading and networking subsystems.

We successfully ported *HPX* to the Android platform. *HPX* applications now not only can run on mobile devices, but we support heterogeneous applications running across architecture boundaries. At the Supercomputing Conference 2012 we demonstrated connecting Android tablets to simulations running on a Linux cluster. The Android tablet was used to query performance counters from the Linux simulation and to steer its parameters.

We successfully ported *HPX* to Mac OSX (using the Clang compiler). Thanks to Pyry Jähkölä for contributing the corresponding patches. Please see the section `macos_installation` for more details.

We made a special effort to make *HPX* usable in highly concurrent use cases. Many of the *HPX* API functions which possibly take longer than 100 microseconds to execute now can be invoked asynchronously. We added uniform support for composing futures which simplifies to write asynchronous code. *HPX* actions (function objects encapsulating possibly concurrent remote function invocations) are now well integrated with all other API facilities such like `hpx::bind`.

All of the API has been aligned as much as possible with established paradigms. *HPX* now mirrors many of the facilities as defined in the C++11 Standard, such as `hpx::thread`, `hpx::function`, `hpx::future`, etc.

A lot of work has been put into improving the documentation. Many of the API functions are documented now, concepts are explained in detail, and examples are better described than before. The new documentation index enables finding information with lesser effort.

This is the first release of *HPX* we perform after the move to [Github](#)⁶⁴⁶⁹. This step has enabled a wider participation from the community and further encourages us in our decision to release *HPX* as a true open source library (*HPX* is licensed under the very liberal [Boost Software License](#)⁶⁴⁷⁰).

⁶⁴⁶⁴ <https://github.com/TheHPXProject/hpx/issues/383>

⁶⁴⁶⁵ <https://github.com/TheHPXProject/hpx/issues/341>

⁶⁴⁶⁶ <https://github.com/TheHPXProject/hpx/issues/219>

⁶⁴⁶⁷ <https://github.com/TheHPXProject/hpx/issues/177>

⁶⁴⁶⁸ <https://github.com/TheHPXProject/hpx/issues/43>

⁶⁴⁶⁹ <https://github.com/TheHPXProject/hpx/>

⁶⁴⁷⁰ https://www.boost.org/LICENSE_1_0.txt

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release. This is by far the longest list of newly implemented features and fixed issues for any of HPX' releases so far.

- [Issue #666](#)⁶⁴⁷¹ - Segfault on calling `hpx::finalize` twice
- [Issue #665](#)⁶⁴⁷² - Adding declaration `num_of_cores`
- [Issue #662](#)⁶⁴⁷³ - `pkgconfig` is building wrong
- [Issue #660](#)⁶⁴⁷⁴ - Need `uninterrupt` function
- [Issue #659](#)⁶⁴⁷⁵ - Move our logging library into a different namespace
- [Issue #658](#)⁶⁴⁷⁶ - Dynamic performance counter types are broken
- [Issue #657](#)⁶⁴⁷⁷ - HPX v0.9.5 (RC1) `hello_world` example segfaulting
- [Issue #656](#)⁶⁴⁷⁸ - Define the affinity of `parcel-pool`, `io-pool`, and `timer-pool` threads
- [Issue #654](#)⁶⁴⁷⁹ - Integrate the Boost `auto_index` tool with documentation
- [Issue #653](#)⁶⁴⁸⁰ - Make HPX build on OS X + Clang + `libc++`
- [Issue #651](#)⁶⁴⁸¹ - Add fine-grained control for thread pinning
- [Issue #650](#)⁶⁴⁸² - Command line no error message when using `-hpx:(anything)`
- [Issue #645](#)⁶⁴⁸³ - Command line aliases don't work in `[teletype]`@file`[c++]`
- [Issue #644](#)⁶⁴⁸⁴ - Terminated threads are not always properly cleaned up
- [Issue #640](#)⁶⁴⁸⁵ - `future_data<T>::set_on_completed_` used without locks
- [Issue #638](#)⁶⁴⁸⁶ - `hpx` build with intel compilers fails on linux
- [Issue #637](#)⁶⁴⁸⁷ - `--copy-dt-needed-entries` breaks with gold
- [Issue #635](#)⁶⁴⁸⁸ - Boost V1.53 will add `Boost.Lockfree` and `Boost.Atomic`
- [Issue #633](#)⁶⁴⁸⁹ - Re-add examples to final 0.9.5 release
- [Issue #632](#)⁶⁴⁹⁰ - Example `thread_aware_timer` is broken
- [Issue #631](#)⁶⁴⁹¹ - FFT application throws error in `parcellayer`

⁶⁴⁷¹ <https://github.com/TheHPXProject/hpx/issues/666>

⁶⁴⁷² <https://github.com/TheHPXProject/hpx/issues/665>

⁶⁴⁷³ <https://github.com/TheHPXProject/hpx/issues/662>

⁶⁴⁷⁴ <https://github.com/TheHPXProject/hpx/issues/660>

⁶⁴⁷⁵ <https://github.com/TheHPXProject/hpx/issues/659>

⁶⁴⁷⁶ <https://github.com/TheHPXProject/hpx/issues/658>

⁶⁴⁷⁷ <https://github.com/TheHPXProject/hpx/issues/657>

⁶⁴⁷⁸ <https://github.com/TheHPXProject/hpx/issues/656>

⁶⁴⁷⁹ <https://github.com/TheHPXProject/hpx/issues/654>

⁶⁴⁸⁰ <https://github.com/TheHPXProject/hpx/issues/653>

⁶⁴⁸¹ <https://github.com/TheHPXProject/hpx/issues/651>

⁶⁴⁸² <https://github.com/TheHPXProject/hpx/issues/650>

⁶⁴⁸³ <https://github.com/TheHPXProject/hpx/issues/645>

⁶⁴⁸⁴ <https://github.com/TheHPXProject/hpx/issues/644>

⁶⁴⁸⁵ <https://github.com/TheHPXProject/hpx/issues/640>

⁶⁴⁸⁶ <https://github.com/TheHPXProject/hpx/issues/638>

⁶⁴⁸⁷ <https://github.com/TheHPXProject/hpx/issues/637>

⁶⁴⁸⁸ <https://github.com/TheHPXProject/hpx/issues/635>

⁶⁴⁸⁹ <https://github.com/TheHPXProject/hpx/issues/633>

⁶⁴⁹⁰ <https://github.com/TheHPXProject/hpx/issues/632>

⁶⁴⁹¹ <https://github.com/TheHPXProject/hpx/issues/631>

- Issue #630⁶⁴⁹² - Event synchronization example is broken
- Issue #629⁶⁴⁹³ - Waiting on futures hangs
- Issue #628⁶⁴⁹⁴ - Add an HPX_ALWAYS_ASSERT macro
- Issue #625⁶⁴⁹⁵ - Port coroutines context switch benchmark
- Issue #621⁶⁴⁹⁶ - New INI section for stack sizes
- Issue #618⁶⁴⁹⁷ - pkg_config support does not work with a HPX debug build
- Issue #617⁶⁴⁹⁸ - hpx/external/logging/boost/logging/detail/cache_before_init.hpp:139:67: error: 'get_thread_id' was not declared in this scope
- Issue #616⁶⁴⁹⁹ - Change wait_xxx not to use locking
- Issue #615⁶⁵⁰⁰ - Revert visibility 'fix' (fb0b6b8245dad1127b0c25ebafd9386b3945cca9)
- Issue #614⁶⁵⁰¹ - Fix Dataflow linker error
- Issue #613⁶⁵⁰² - find_here should throw an exception on failure
- Issue #612⁶⁵⁰³ - Thread phase doesn't show up in debug mode
- Issue #611⁶⁵⁰⁴ - Make stack guard pages configurable at runtime (initialization time)
- Issue #610⁶⁵⁰⁵ - Co-Locate Components
- Issue #609⁶⁵⁰⁶ - future_overhead
- Issue #608⁶⁵⁰⁷ - --hpx:list-counter-infos problem
- Issue #607⁶⁵⁰⁸ - Update Boost.Context based backend for coroutines
- Issue #606⁶⁵⁰⁹ - 1d_wave_equation is not working
- Issue #605⁶⁵¹⁰ - Any C++ function that has serializable arguments and a serializable return type should be remotable
- Issue #604⁶⁵¹¹ - Connecting localities isn't working anymore
- Issue #603⁶⁵¹² - Do not verify any ini entries read from a file
- Issue #602⁶⁵¹³ - Rename argument_size to type_size/ added implementation to get parcel size

⁶⁴⁹² <https://github.com/TheHPXProject/hpx/issues/630>

⁶⁴⁹³ <https://github.com/TheHPXProject/hpx/issues/629>

⁶⁴⁹⁴ <https://github.com/TheHPXProject/hpx/issues/628>

⁶⁴⁹⁵ <https://github.com/TheHPXProject/hpx/issues/625>

⁶⁴⁹⁶ <https://github.com/TheHPXProject/hpx/issues/621>

⁶⁴⁹⁷ <https://github.com/TheHPXProject/hpx/issues/618>

⁶⁴⁹⁸ <https://github.com/TheHPXProject/hpx/issues/617>

⁶⁴⁹⁹ <https://github.com/TheHPXProject/hpx/issues/616>

⁶⁵⁰⁰ <https://github.com/TheHPXProject/hpx/issues/615>

⁶⁵⁰¹ <https://github.com/TheHPXProject/hpx/issues/614>

⁶⁵⁰² <https://github.com/TheHPXProject/hpx/issues/613>

⁶⁵⁰³ <https://github.com/TheHPXProject/hpx/issues/612>

⁶⁵⁰⁴ <https://github.com/TheHPXProject/hpx/issues/611>

⁶⁵⁰⁵ <https://github.com/TheHPXProject/hpx/issues/610>

⁶⁵⁰⁶ <https://github.com/TheHPXProject/hpx/issues/609>

⁶⁵⁰⁷ <https://github.com/TheHPXProject/hpx/issues/608>

⁶⁵⁰⁸ <https://github.com/TheHPXProject/hpx/issues/607>

⁶⁵⁰⁹ <https://github.com/TheHPXProject/hpx/issues/606>

⁶⁵¹⁰ <https://github.com/TheHPXProject/hpx/issues/605>

⁶⁵¹¹ <https://github.com/TheHPXProject/hpx/issues/604>

⁶⁵¹² <https://github.com/TheHPXProject/hpx/issues/603>

⁶⁵¹³ <https://github.com/TheHPXProject/hpx/issues/602>

- [Issue #599](#)⁶⁵¹⁴ - Enable locality specific command line options
- [Issue #598](#)⁶⁵¹⁵ - Need an API that accesses the performance counter reporting the system uptime
- [Issue #597](#)⁶⁵¹⁶ - compiling on ranger
- [Issue #595](#)⁶⁵¹⁷ - I need a place to store data in a thread self pointer
- [Issue #594](#)⁶⁵¹⁸ - 32/64 interoperability
- [Issue #593](#)⁶⁵¹⁹ - Warn if logging is disabled at compile time but requested at runtime
- [Issue #592](#)⁶⁵²⁰ - Add optional argument value to `--hpx:list-counters` and `--hpx:list-counter-infos`
- [Issue #591](#)⁶⁵²¹ - Allow for wildcards in performance counter names specified with `--hpx:print-counter`
- [Issue #590](#)⁶⁵²² - Local promise semantic differences
- [Issue #589](#)⁶⁵²³ - Create API to query performance counter names
- [Issue #587](#)⁶⁵²⁴ - Add `get_num_localities` and `get_num_threads` to AGAS API
- [Issue #586](#)⁶⁵²⁵ - Adjust local AGAS cache size based on number of localities
- [Issue #585](#)⁶⁵²⁶ - Error while using counters in HPX
- [Issue #584](#)⁶⁵²⁷ - counting argument size of actions, initial pass.
- [Issue #581](#)⁶⁵²⁸ - Remove `RemoteResult` template parameter for `future<>`
- [Issue #580](#)⁶⁵²⁹ - Add possibility to hook into actions
- [Issue #578](#)⁶⁵³⁰ - Use angle brackets in HPX error dumps
- [Issue #576](#)⁶⁵³¹ - Exception incorrectly thrown when `--help` is used
- [Issue #575](#)⁶⁵³² - `HPX(bad_component_type)` with gcc 4.7.2 and boost 1.51
- [Issue #574](#)⁶⁵³³ - `--hpx:connect` command line parameter not working correctly
- [Issue #571](#)⁶⁵³⁴ - `hpx::wait()` (callback version) should pass the future to the callback function
- [Issue #570](#)⁶⁵³⁵ - `hpx::wait` should operate on `boost::arrays` and `std::lists`
- [Issue #569](#)⁶⁵³⁶ - Add a logging sink for Android

⁶⁵¹⁴ <https://github.com/TheHPXProject/hpx/issues/599>

⁶⁵¹⁵ <https://github.com/TheHPXProject/hpx/issues/598>

⁶⁵¹⁶ <https://github.com/TheHPXProject/hpx/issues/597>

⁶⁵¹⁷ <https://github.com/TheHPXProject/hpx/issues/595>

⁶⁵¹⁸ <https://github.com/TheHPXProject/hpx/issues/594>

⁶⁵¹⁹ <https://github.com/TheHPXProject/hpx/issues/593>

⁶⁵²⁰ <https://github.com/TheHPXProject/hpx/issues/592>

⁶⁵²¹ <https://github.com/TheHPXProject/hpx/issues/591>

⁶⁵²² <https://github.com/TheHPXProject/hpx/issues/590>

⁶⁵²³ <https://github.com/TheHPXProject/hpx/issues/589>

⁶⁵²⁴ <https://github.com/TheHPXProject/hpx/issues/587>

⁶⁵²⁵ <https://github.com/TheHPXProject/hpx/issues/586>

⁶⁵²⁶ <https://github.com/TheHPXProject/hpx/issues/585>

⁶⁵²⁷ <https://github.com/TheHPXProject/hpx/issues/584>

⁶⁵²⁸ <https://github.com/TheHPXProject/hpx/issues/581>

⁶⁵²⁹ <https://github.com/TheHPXProject/hpx/issues/580>

⁶⁵³⁰ <https://github.com/TheHPXProject/hpx/issues/578>

⁶⁵³¹ <https://github.com/TheHPXProject/hpx/issues/576>

⁶⁵³² <https://github.com/TheHPXProject/hpx/issues/575>

⁶⁵³³ <https://github.com/TheHPXProject/hpx/issues/574>

⁶⁵³⁴ <https://github.com/TheHPXProject/hpx/issues/571>

⁶⁵³⁵ <https://github.com/TheHPXProject/hpx/issues/570>

⁶⁵³⁶ <https://github.com/TheHPXProject/hpx/issues/569>

- [Issue #568](#)⁶⁵³⁷ - 2-argument version of HPX_DEFINE_COMPONENT_ACTION
- [Issue #567](#)⁶⁵³⁸ - Connecting to a running HPX application works only once
- [Issue #565](#)⁶⁵³⁹ - HPX doesn't shutdown properly
- [Issue #564](#)⁶⁵⁴⁰ - Partial preprocessing of new component creation interface
- [Issue #563](#)⁶⁵⁴¹ - Add `hpx::start/hpx::stop` to avoid blocking main thread
- [Issue #562](#)⁶⁵⁴² - All command line arguments swallowed by `hpx`
- [Issue #561](#)⁶⁵⁴³ - `Boost.Tuple` is not move aware
- [Issue #558](#)⁶⁵⁴⁴ - `boost::shared_ptr<>` style semantics/syntax for client classes
- [Issue #556](#)⁶⁵⁴⁵ - Creation of partially preprocessed headers should be enabled for Boost newer than V1.50
- [Issue #555](#)⁶⁵⁴⁶ - `BOOST_FORCEINLINE` does not name a type
- [Issue #554](#)⁶⁵⁴⁷ - Possible race condition in thread `get_id()`
- [Issue #552](#)⁶⁵⁴⁸ - Move enable `client_base`
- [Issue #550](#)⁶⁵⁴⁹ - Add stack size category 'huge'
- [Issue #549](#)⁶⁵⁵⁰ - ShenEOS run seg-faults on single or distributed runs
- [Issue #545](#)⁶⁵⁵¹ - `AUTOGLOB` broken for `add_hpx_component`
- [Issue #542](#)⁶⁵⁵² - `FindHPX_HDF5` still searches multiple times
- [Issue #541](#)⁶⁵⁵³ - Quotes around application name in `hpx::init`
- [Issue #539](#)⁶⁵⁵⁴ - Race condition occurring with new lightweight threads
- [Issue #535](#)⁶⁵⁵⁵ - `hpx_run_tests.py` exits with no error code when tests are missing
- [Issue #530](#)⁶⁵⁵⁶ - Thread description(<unknown>) in logs
- [Issue #523](#)⁶⁵⁵⁷ - Make thread objects more lightweight
- [Issue #521](#)⁶⁵⁵⁸ - `hpx::error_code` is not usable for lightweight error handling
- [Issue #520](#)⁶⁵⁵⁹ - Add full user environment to HPX logs

⁶⁵³⁷ <https://github.com/TheHPXProject/hpx/issues/568>

⁶⁵³⁸ <https://github.com/TheHPXProject/hpx/issues/567>

⁶⁵³⁹ <https://github.com/TheHPXProject/hpx/issues/565>

⁶⁵⁴⁰ <https://github.com/TheHPXProject/hpx/issues/564>

⁶⁵⁴¹ <https://github.com/TheHPXProject/hpx/issues/563>

⁶⁵⁴² <https://github.com/TheHPXProject/hpx/issues/562>

⁶⁵⁴³ <https://github.com/TheHPXProject/hpx/issues/561>

⁶⁵⁴⁴ <https://github.com/TheHPXProject/hpx/issues/558>

⁶⁵⁴⁵ <https://github.com/TheHPXProject/hpx/issues/556>

⁶⁵⁴⁶ <https://github.com/TheHPXProject/hpx/issues/555>

⁶⁵⁴⁷ <https://github.com/TheHPXProject/hpx/issues/554>

⁶⁵⁴⁸ <https://github.com/TheHPXProject/hpx/issues/552>

⁶⁵⁴⁹ <https://github.com/TheHPXProject/hpx/issues/550>

⁶⁵⁵⁰ <https://github.com/TheHPXProject/hpx/issues/549>

⁶⁵⁵¹ <https://github.com/TheHPXProject/hpx/issues/545>

⁶⁵⁵² <https://github.com/TheHPXProject/hpx/issues/542>

⁶⁵⁵³ <https://github.com/TheHPXProject/hpx/issues/541>

⁶⁵⁵⁴ <https://github.com/TheHPXProject/hpx/issues/539>

⁶⁵⁵⁵ <https://github.com/TheHPXProject/hpx/issues/535>

⁶⁵⁵⁶ <https://github.com/TheHPXProject/hpx/issues/530>

⁶⁵⁵⁷ <https://github.com/TheHPXProject/hpx/issues/523>

⁶⁵⁵⁸ <https://github.com/TheHPXProject/hpx/issues/521>

⁶⁵⁵⁹ <https://github.com/TheHPXProject/hpx/issues/520>

- [Issue #519](#)⁶⁵⁶⁰ - Build succeeds, running fails
- [Issue #517](#)⁶⁵⁶¹ - Add a guard page to linux coroutine stacks
- [Issue #516](#)⁶⁵⁶² - `hpx::thread::detach` suspends while holding locks, leads to hang in debug
- [Issue #514](#)⁶⁵⁶³ - Preprocessed headers for `<hpx/apply.hpp>` don't compile
- [Issue #513](#)⁶⁵⁶⁴ - Buildbot configuration problem
- [Issue #512](#)⁶⁵⁶⁵ - Implement action based stack size customization
- [Issue #511](#)⁶⁵⁶⁶ - Move action priority into a separate type trait
- [Issue #510](#)⁶⁵⁶⁷ - trunk broken
- [Issue #507](#)⁶⁵⁶⁸ - no matching function for call to `boost::scoped_ptr<hpx::threads::topology>::scoped_ptr(hpx::thre`
- [Issue #505](#)⁶⁵⁶⁹ - `undefined_symbol` regression test currently failing
- [Issue #502](#)⁶⁵⁷⁰ - Adding OpenCL and OCLM support to HPX for Windows and Linux
- [Issue #501](#)⁶⁵⁷¹ - `find_package(HPX)` sets cmake output variables
- [Issue #500](#)⁶⁵⁷² - `wait_any/wait_all` are badly named
- [Issue #499](#)⁶⁵⁷³ - Add support for disabling pbs support in pbs runs
- [Issue #498](#)⁶⁵⁷⁴ - Error during no-cache runs
- [Issue #496](#)⁶⁵⁷⁵ - Add partial preprocessing support to cmake
- [Issue #495](#)⁶⁵⁷⁶ - Support HPX modules exporting startup/shutdown functions only
- [Issue #494](#)⁶⁵⁷⁷ - Allow modules to specify when to run startup/shutdown functions
- [Issue #493](#)⁶⁵⁷⁸ - Avoid constructing a string in `make_success_code`
- [Issue #492](#)⁶⁵⁷⁹ - Performance counter creation is no longer synchronized at startup
- [Issue #491](#)⁶⁵⁸⁰ - Performance counter creation is no longer synchronized at startup
- [Issue #490](#)⁶⁵⁸¹ - Sheneos on `_completed_bulk` seg fault in distributed
- [Issue #489](#)⁶⁵⁸² - compiling issue with `g++44`

⁶⁵⁶⁰ <https://github.com/TheHPXProject/hpx/issues/519>

⁶⁵⁶¹ <https://github.com/TheHPXProject/hpx/issues/517>

⁶⁵⁶² <https://github.com/TheHPXProject/hpx/issues/516>

⁶⁵⁶³ <https://github.com/TheHPXProject/hpx/issues/514>

⁶⁵⁶⁴ <https://github.com/TheHPXProject/hpx/issues/513>

⁶⁵⁶⁵ <https://github.com/TheHPXProject/hpx/issues/512>

⁶⁵⁶⁶ <https://github.com/TheHPXProject/hpx/issues/511>

⁶⁵⁶⁷ <https://github.com/TheHPXProject/hpx/issues/510>

⁶⁵⁶⁸ <https://github.com/TheHPXProject/hpx/issues/507>

⁶⁵⁶⁹ <https://github.com/TheHPXProject/hpx/issues/505>

⁶⁵⁷⁰ <https://github.com/TheHPXProject/hpx/issues/502>

⁶⁵⁷¹ <https://github.com/TheHPXProject/hpx/issues/501>

⁶⁵⁷² <https://github.com/TheHPXProject/hpx/issues/500>

⁶⁵⁷³ <https://github.com/TheHPXProject/hpx/issues/499>

⁶⁵⁷⁴ <https://github.com/TheHPXProject/hpx/issues/498>

⁶⁵⁷⁵ <https://github.com/TheHPXProject/hpx/issues/496>

⁶⁵⁷⁶ <https://github.com/TheHPXProject/hpx/issues/495>

⁶⁵⁷⁷ <https://github.com/TheHPXProject/hpx/issues/494>

⁶⁵⁷⁸ <https://github.com/TheHPXProject/hpx/issues/493>

⁶⁵⁷⁹ <https://github.com/TheHPXProject/hpx/issues/492>

⁶⁵⁸⁰ <https://github.com/TheHPXProject/hpx/issues/491>

⁶⁵⁸¹ <https://github.com/TheHPXProject/hpx/issues/490>

⁶⁵⁸² <https://github.com/TheHPXProject/hpx/issues/489>

- Issue #488⁶⁵⁸³ - Adding OpenCL and OCLM support to HPX for the MSVC platform
- Issue #487⁶⁵⁸⁴ - FindHPX.cmake problems
- Issue #485⁶⁵⁸⁵ - Change distributing_factory and binpacking_factory to use bulk creation
- Issue #484⁶⁵⁸⁶ - Change HPX_DONT_USE_PREPROCESSED_FILES to HPX_USE_PREPROCESSED_FILES
- Issue #483⁶⁵⁸⁷ - Memory counter for Windows
- Issue #479⁶⁵⁸⁸ - strange errors appear when requesting performance counters on multiple nodes
- Issue #477⁶⁵⁸⁹ - Create (global) timer for multi-threaded measurements
- Issue #472⁶⁵⁹⁰ - Add partial preprocessing using Wave
- Issue #471⁶⁵⁹¹ - Segfault stack traces don't show up in release
- Issue #468⁶⁵⁹² - External projects need to link with internal components
- Issue #462⁶⁵⁹³ - Startup/shutdown functions are called more than once
- Issue #458⁶⁵⁹⁴ - Consolidate hpx::util::high_resolution_timer and hpx::util::high_resolution_clock
- Issue #457⁶⁵⁹⁵ - index out of bounds in allgather_and_gate on 4 cores or more
- Issue #448⁶⁵⁹⁶ - Make HPX compile with clang
- Issue #447⁶⁵⁹⁷ - 'make tests' should execute tests on local installation
- Issue #446⁶⁵⁹⁸ - Remove SVN-related code from the codebase
- Issue #444⁶⁵⁹⁹ - race condition in smp
- Issue #441⁶⁶⁰⁰ - Patched Boost.Serialization headers should only be installed if needed
- Issue #439⁶⁶⁰¹ - Components using HPX_REGISTER_STARTUP_MODULE fail to compile with MSVC
- Issue #436⁶⁶⁰² - Verify that no locks are being held while threads are suspended
- Issue #435⁶⁶⁰³ - Installing HPX should not clobber existing Boost installation
- Issue #434⁶⁶⁰⁴ - Logging external component failed (Boost 1.50)
- Issue #433⁶⁶⁰⁵ - Runtime crash when building all examples

⁶⁵⁸³ <https://github.com/TheHPXProject/hpx/issues/488>

⁶⁵⁸⁴ <https://github.com/TheHPXProject/hpx/issues/487>

⁶⁵⁸⁵ <https://github.com/TheHPXProject/hpx/issues/485>

⁶⁵⁸⁶ <https://github.com/TheHPXProject/hpx/issues/484>

⁶⁵⁸⁷ <https://github.com/TheHPXProject/hpx/issues/483>

⁶⁵⁸⁸ <https://github.com/TheHPXProject/hpx/issues/479>

⁶⁵⁸⁹ <https://github.com/TheHPXProject/hpx/issues/477>

⁶⁵⁹⁰ <https://github.com/TheHPXProject/hpx/issues/472>

⁶⁵⁹¹ <https://github.com/TheHPXProject/hpx/issues/471>

⁶⁵⁹² <https://github.com/TheHPXProject/hpx/issues/468>

⁶⁵⁹³ <https://github.com/TheHPXProject/hpx/issues/462>

⁶⁵⁹⁴ <https://github.com/TheHPXProject/hpx/issues/458>

⁶⁵⁹⁵ <https://github.com/TheHPXProject/hpx/issues/457>

⁶⁵⁹⁶ <https://github.com/TheHPXProject/hpx/issues/448>

⁶⁵⁹⁷ <https://github.com/TheHPXProject/hpx/issues/447>

⁶⁵⁹⁸ <https://github.com/TheHPXProject/hpx/issues/446>

⁶⁵⁹⁹ <https://github.com/TheHPXProject/hpx/issues/444>

⁶⁶⁰⁰ <https://github.com/TheHPXProject/hpx/issues/441>

⁶⁶⁰¹ <https://github.com/TheHPXProject/hpx/issues/439>

⁶⁶⁰² <https://github.com/TheHPXProject/hpx/issues/436>

⁶⁶⁰³ <https://github.com/TheHPXProject/hpx/issues/435>

⁶⁶⁰⁴ <https://github.com/TheHPXProject/hpx/issues/434>

⁶⁶⁰⁵ <https://github.com/TheHPXProject/hpx/issues/433>

- [Issue #432](#)⁶⁶⁰⁶ - Dataflow hangs on 512 cores/64 nodes
- [Issue #430](#)⁶⁶⁰⁷ - Problem with distributing factory
- [Issue #424](#)⁶⁶⁰⁸ - File paths referring to XSL-files need to be properly escaped
- [Issue #417](#)⁶⁶⁰⁹ - Make dataflow LCOs work out of the box by using partial preprocessing
- [Issue #413](#)⁶⁶¹⁰ - `hpx_svnversion.py` fails on Windows
- [Issue #412](#)⁶⁶¹¹ - Make `hpx::error_code` equivalent to `hpx::exception`
- [Issue #398](#)⁶⁶¹² - HPX clobbers out-of-tree application specific CMake variables (specifically `CMAKE_BUILD_TYPE`)
- [Issue #394](#)⁶⁶¹³ - Remove code generating random port numbers for network
- [Issue #378](#)⁶⁶¹⁴ - ShenEOS scaling issues
- [Issue #354](#)⁶⁶¹⁵ - Create a coroutines wrapper for `Boost.Context`
- [Issue #349](#)⁶⁶¹⁶ - Commandline option `--localities=N/-lN` should be necessary only on AGAS locality
- [Issue #334](#)⁶⁶¹⁷ - Add `auto_index` support to cmake based documentation toolchain
- [Issue #318](#)⁶⁶¹⁸ - Network benchmarks
- [Issue #317](#)⁶⁶¹⁹ - Implement network performance counters
- [Issue #310](#)⁶⁶²⁰ - Duplicate logging entries
- [Issue #230](#)⁶⁶²¹ - Add compile time option to disable thread debugging info
- [Issue #171](#)⁶⁶²² - Add an INI option to turn off deadlock detection independently of logging
- [Issue #170](#)⁶⁶²³ - OSHL internal counters are incorrect
- [Issue #103](#)⁶⁶²⁴ - Better diagnostics for multiple component/action registrations under the same name
- [Issue #48](#)⁶⁶²⁵ - Support for Darwin (Xcode + Clang)
- [Issue #21](#)⁶⁶²⁶ - Build fails with GCC 4.6

⁶⁶⁰⁶ <https://github.com/TheHPXProject/hpx/issues/432>

⁶⁶⁰⁷ <https://github.com/TheHPXProject/hpx/issues/430>

⁶⁶⁰⁸ <https://github.com/TheHPXProject/hpx/issues/424>

⁶⁶⁰⁹ <https://github.com/TheHPXProject/hpx/issues/417>

⁶⁶¹⁰ <https://github.com/TheHPXProject/hpx/issues/413>

⁶⁶¹¹ <https://github.com/TheHPXProject/hpx/issues/412>

⁶⁶¹² <https://github.com/TheHPXProject/hpx/issues/398>

⁶⁶¹³ <https://github.com/TheHPXProject/hpx/issues/394>

⁶⁶¹⁴ <https://github.com/TheHPXProject/hpx/issues/378>

⁶⁶¹⁵ <https://github.com/TheHPXProject/hpx/issues/354>

⁶⁶¹⁶ <https://github.com/TheHPXProject/hpx/issues/349>

⁶⁶¹⁷ <https://github.com/TheHPXProject/hpx/issues/334>

⁶⁶¹⁸ <https://github.com/TheHPXProject/hpx/issues/318>

⁶⁶¹⁹ <https://github.com/TheHPXProject/hpx/issues/317>

⁶⁶²⁰ <https://github.com/TheHPXProject/hpx/issues/310>

⁶⁶²¹ <https://github.com/TheHPXProject/hpx/issues/230>

⁶⁶²² <https://github.com/TheHPXProject/hpx/issues/171>

⁶⁶²³ <https://github.com/TheHPXProject/hpx/issues/170>

⁶⁶²⁴ <https://github.com/TheHPXProject/hpx/issues/103>

⁶⁶²⁵ <https://github.com/TheHPXProject/hpx/issues/48>

⁶⁶²⁶ <https://github.com/TheHPXProject/hpx/issues/21>

HPX V0.9.0 (Jul 5, 2012)

We have had roughly 800 commits since the last release and we have closed approximately 80 tickets (bugs, feature requests, etc.).

General changes

- Significant improvements made to the usability of *HPX* in large-scale, distributed environments.
- Renamed `hpx::lcos::packaged_task` to `hpx::lcos::packaged_action` to reflect the semantic differences to a `packaged_task` as defined by the [C++11 Standard](#)⁶⁶²⁷.
- *HPX* now exposes `hpx::thread` which is compliant to the C++11 `std::thread` type except that it (purely locally) represents an *HPX* thread. This new type does not expose any of the remote capabilities of the underlying *HPX*-thread implementation.
- The type `hpx::lcos::future` is now compliant to the C++11 `std::future<>` type. This type can be used to synchronize both, local and remote operations. In both cases the control flow will ‘return’ to the future in order to trigger any continuation.
- The types `hpx::lcos::local::promise` and `hpx::lcos::local::packaged_task` are now compliant to the C++11 `std::promise<>` and `std::packaged_task<>` types. These can be used to create a future representing local work only. Use the types `hpx::lcos::promise` and `hpx::lcos::packaged_action` to wrap any (possibly remote) action into a future.
- `hpx::thread` and `hpx::lcos::future` are now cancelable.
- Added support for sequential and logic composition of `hpx::lcos::futures`. The member function `hpx::lcos::future::when` permits futures to be sequentially composed. The helper functions `hpx::wait_all`, `hpx::wait_any`, and `hpx::wait_n` can be used to wait for more than one future at a time.
- *HPX* now exposes `hpx::apply` and `hpx::async` as the preferred way of creating (or invoking) any deferred work. These functions are usable with various types of functions, function objects, and actions and provide a uniform way to spawn deferred tasks.
- *HPX* now utilizes `hpx::util::bind` to (partially) bind local functions and function objects, and also actions. Remote bound actions can have placeholders as well.
- *HPX* continuations are now fully polymorphic. The class `hpx::actions::forwarding_continuation` is an example of how the user can write its own types of continuations. It can be used to execute any function as an continuation of a particular action.
- Reworked the action invocation API to be fully conformant to normal functions. Actions can now be invoked using `hpx::apply`, `hpx::async`, or using the `operator()` implemented on actions. Actions themselves can now be cheaply instantiated as they do not have any members anymore.
- Reworked the lazy action invocation API. Actions can now be directly bound using `hpx::util::bind` by passing an action instance as the first argument.
- A minimal *HPX* program now looks like this:

```
#include <hpx/hpx_init.hpp>

int hpx_main()
{
    return hpx::finalize();
}
```

(continues on next page)

⁶⁶²⁷ <http://www.open-std.org/jtc1/sc22/wg21>

(continued from previous page)

```
int main()
{
    return hpx::init();
}
```

This removes the immediate dependency on the `Boost.Program_options`⁶⁶²⁸ library.

Note: This minimal version of an *HPX* program does not support any of the default command line arguments (such as `-help`, or command line options related to PBS). It is suggested to always pass `argc` and `argv` to *HPX* as shown in the example below.

- In order to support those, but still not to depend on `Boost.Program_options`⁶⁶²⁹, the minimal program can be written as:

```
#include <hpx/hpx_init.hpp>

// The arguments for hpx_main can be left off, which very similar to the
// behavior of ``main()`` as defined by C++.
int hpx_main(int argc, char* argv[])
{
    return hpx::finalize();
}

int main(int argc, char* argv[])
{
    return hpx::init(argc, argv);
}
```

- Added performance counters exposing the number of component instances which are alive on a given locality.
- Added performance counters exposing then number of messages sent and received, the number of parcels sent and received, the number of bytes sent and received, the overall time required to send and receive data, and the overall time required to serialize and deserialize the data.
- Added a new component: `hpx::components::binpacking_factory` which is equivalent to the existing `hpx::components::distributing_factory` component, except that it equalizes the overall population of the components to create. It exposes two factory methods, one based on the number of existing instances of the component type to create, and one based on an arbitrary performance counter which will be queried for all relevant localities.
- Added API functions allowing to access elements of the diagnostic information embedded in the given exception: `hpx::get_locality_id`, `hpx::get_host_name`, `hpx::get_process_id`, `hpx::get_function_name`, `hpx::get_file_name`, `hpx::get_line_number`, `hpx::get_os_thread`, `hpx::get_thread_id`, and `hpx::get_thread_description`.

⁶⁶²⁸ https://www.boost.org/doc/html/program_options.html

⁶⁶²⁹ https://www.boost.org/doc/html/program_options.html

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release:

- [Issue #71](#)⁶⁶³⁰ - GIDs that are not serialized via `handle_gid<>` should raise an exception
- [Issue #105](#)⁶⁶³¹ - Allow for `hpx::util::functions` to be registered in the AGAS symbolic namespace
- [Issue #107](#)⁶⁶³² - Nasty threadmanger race condition (reproducible in `sheneos_test`)
- [Issue #108](#)⁶⁶³³ - Add millisecond resolution to *HPX* logs on Linux
- [Issue #110](#)⁶⁶³⁴ - Shutdown hang in distributed with release build
- [Issue #116](#)⁶⁶³⁵ - Don't use TSS for the applier and runtime pointers
- [Issue #162](#)⁶⁶³⁶ - Move local synchronous execution shortcut from `hpx::function` to the applier
- [Issue #172](#)⁶⁶³⁷ - Cache sources in CMake and check if they change manually
- [Issue #178](#)⁶⁶³⁸ - Add an INI option to turn off ranged-based AGAS caching
- [Issue #187](#)⁶⁶³⁹ - Support for disabling performance counter deployment
- [Issue #202](#)⁶⁶⁴⁰ - Support for sending performance counter data to a specific file
- [Issue #218](#)⁶⁶⁴¹ - `boost.coroutines` allows different stack sizes, but stack pool is unaware of this
- [Issue #231](#)⁶⁶⁴² - Implement movable `boost::bind`
- [Issue #232](#)⁶⁶⁴³ - Implement movable `boost::function`
- [Issue #236](#)⁶⁶⁴⁴ - Allow binding `hpx::util::function` to actions
- [Issue #239](#)⁶⁶⁴⁵ - Replace `hpx::function` with `hpx::util::function`
- [Issue #240](#)⁶⁶⁴⁶ - Can't specify `RemoteResult` with `lcos::async`
- [Issue #242](#)⁶⁶⁴⁷ - `REGISTER_TEMPLATE` support for plain actions
- [Issue #243](#)⁶⁶⁴⁸ - `handle_gid<>` support for `hpx::util::function`
- [Issue #245](#)⁶⁶⁴⁹ - `*_c_cache` code throws an exception if the queried GID is not in the local cache
- [Issue #246](#)⁶⁶⁵⁰ - Undefined references in `dataflow/adaptive1d` example

⁶⁶³⁰ <https://github.com/TheHPXProject/hpx/issues/71>

⁶⁶³¹ <https://github.com/TheHPXProject/hpx/issues/105>

⁶⁶³² <https://github.com/TheHPXProject/hpx/issues/107>

⁶⁶³³ <https://github.com/TheHPXProject/hpx/issues/108>

⁶⁶³⁴ <https://github.com/TheHPXProject/hpx/issues/110>

⁶⁶³⁵ <https://github.com/TheHPXProject/hpx/issues/116>

⁶⁶³⁶ <https://github.com/TheHPXProject/hpx/issues/162>

⁶⁶³⁷ <https://github.com/TheHPXProject/hpx/issues/172>

⁶⁶³⁸ <https://github.com/TheHPXProject/hpx/issues/178>

⁶⁶³⁹ <https://github.com/TheHPXProject/hpx/issues/187>

⁶⁶⁴⁰ <https://github.com/TheHPXProject/hpx/issues/202>

⁶⁶⁴¹ <https://github.com/TheHPXProject/hpx/issues/218>

⁶⁶⁴² <https://github.com/TheHPXProject/hpx/issues/231>

⁶⁶⁴³ <https://github.com/TheHPXProject/hpx/issues/232>

⁶⁶⁴⁴ <https://github.com/TheHPXProject/hpx/issues/236>

⁶⁶⁴⁵ <https://github.com/TheHPXProject/hpx/issues/239>

⁶⁶⁴⁶ <https://github.com/TheHPXProject/hpx/issues/240>

⁶⁶⁴⁷ <https://github.com/TheHPXProject/hpx/issues/242>

⁶⁶⁴⁸ <https://github.com/TheHPXProject/hpx/issues/243>

⁶⁶⁴⁹ <https://github.com/TheHPXProject/hpx/issues/245>

⁶⁶⁵⁰ <https://github.com/TheHPXProject/hpx/issues/246>

- Issue #252⁶⁶⁵¹ - Problems configuring sheneos with CMake
- Issue #254⁶⁶⁵² - Lifetime of components doesn't end when client goes out of scope
- Issue #259⁶⁶⁵³ - CMake does not detect that MSVC10 has lambdas
- Issue #260⁶⁶⁵⁴ - io_service_pool segfault
- Issue #261⁶⁶⁵⁵ - Late parcel executed outside of pxtread
- Issue #263⁶⁶⁵⁶ - Cannot select allocator with CMake
- Issue #264⁶⁶⁵⁷ - Fix allocator select
- Issue #267⁶⁶⁵⁸ - Runtime error for hello_world
- Issue #269⁶⁶⁵⁹ - pthread_affinity_np test fails to compile
- Issue #270⁶⁶⁶⁰ - Compiler noise due to -Wcast-qual
- Issue #275⁶⁶⁶¹ - Problem with configuration tests/include paths on Gentoo
- Issue #325⁶⁶⁶² - Sheneos is 200-400 times slower than the fortran equivalent
- Issue #331⁶⁶⁶³ - `hpx::init` and `hpx_main()` should not depend on `program_options`
- Issue #333⁶⁶⁶⁴ - Add doxygen support to CMake for doc toolchain
- Issue #340⁶⁶⁶⁵ - Performance counters for parcels
- Issue #346⁶⁶⁶⁶ - Component loading error when running hello_world in distributed on MSVC2010
- Issue #362⁶⁶⁶⁷ - Missing initializer error
- Issue #363⁶⁶⁶⁸ - Parcel port serialization error
- Issue #366⁶⁶⁶⁹ - Parcel buffering leads to types incompatible exception
- Issue #368⁶⁶⁷⁰ - Scalable alternative to `rand()` needed for *HPX*
- Issue #369⁶⁶⁷¹ - IB over IP is substantially slower than just using standard TCP/IP
- Issue #374⁶⁶⁷² - `hpx::lcos::wait` should work with dataflows and arbitrary classes meeting the future interface
- Issue #375⁶⁶⁷³ - Conflicting/ambiguous overloads of `hpx::lcos::wait`

⁶⁶⁵¹ <https://github.com/TheHPXProject/hpx/issues/252>

⁶⁶⁵² <https://github.com/TheHPXProject/hpx/issues/254>

⁶⁶⁵³ <https://github.com/TheHPXProject/hpx/issues/259>

⁶⁶⁵⁴ <https://github.com/TheHPXProject/hpx/issues/260>

⁶⁶⁵⁵ <https://github.com/TheHPXProject/hpx/issues/261>

⁶⁶⁵⁶ <https://github.com/TheHPXProject/hpx/issues/263>

⁶⁶⁵⁷ <https://github.com/TheHPXProject/hpx/issues/264>

⁶⁶⁵⁸ <https://github.com/TheHPXProject/hpx/issues/267>

⁶⁶⁵⁹ <https://github.com/TheHPXProject/hpx/issues/269>

⁶⁶⁶⁰ <https://github.com/TheHPXProject/hpx/issues/270>

⁶⁶⁶¹ <https://github.com/TheHPXProject/hpx/issues/275>

⁶⁶⁶² <https://github.com/TheHPXProject/hpx/issues/325>

⁶⁶⁶³ <https://github.com/TheHPXProject/hpx/issues/331>

⁶⁶⁶⁴ <https://github.com/TheHPXProject/hpx/issues/333>

⁶⁶⁶⁵ <https://github.com/TheHPXProject/hpx/issues/340>

⁶⁶⁶⁶ <https://github.com/TheHPXProject/hpx/issues/346>

⁶⁶⁶⁷ <https://github.com/TheHPXProject/hpx/issues/362>

⁶⁶⁶⁸ <https://github.com/TheHPXProject/hpx/issues/363>

⁶⁶⁶⁹ <https://github.com/TheHPXProject/hpx/issues/366>

⁶⁶⁷⁰ <https://github.com/TheHPXProject/hpx/issues/368>

⁶⁶⁷¹ <https://github.com/TheHPXProject/hpx/issues/369>

⁶⁶⁷² <https://github.com/TheHPXProject/hpx/issues/374>

⁶⁶⁷³ <https://github.com/TheHPXProject/hpx/issues/375>

- Issue #376⁶⁶⁷⁴ - Find_HPX.cmake should set CMake variable HPX_FOUND for out of tree builds
- Issue #377⁶⁶⁷⁵ - ShenEOS interpolate bulk and interpolate_one_bulk are broken
- Issue #379⁶⁶⁷⁶ - Add support for distributed runs under SLURM
- Issue #382⁶⁶⁷⁷ - _Unwind_Word not declared in boost.backtrace
- Issue #387⁶⁶⁷⁸ - Doxygen should look only at list of specified files
- Issue #388⁶⁶⁷⁹ - Running make install on an out-of-tree application is broken
- Issue #391⁶⁶⁸⁰ - Out-of-tree application segfaults when running in qsub
- Issue #392⁶⁶⁸¹ - Remove HPX_NO_INSTALL option from cmake build system
- Issue #396⁶⁶⁸² - Pragma related warnings when compiling with older gcc versions
- Issue #399⁶⁶⁸³ - Out of tree component build problems
- Issue #400⁶⁶⁸⁴ - Out of source builds on Windows: linker should not receive compiler flags
- Issue #401⁶⁶⁸⁵ - Out of source builds on Windows: components need to be linked with hpx_serialization
- Issue #404⁶⁶⁸⁶ - gfortran fails to link automatically when fortran files are present
- Issue #405⁶⁶⁸⁷ - Inability to specify linking order for external libraries
- Issue #406⁶⁶⁸⁸ - Adapt action limits such that dataflow applications work without additional defines
- Issue #415⁶⁶⁸⁹ - locality_results is not a member of hpx::components::server
- Issue #425⁶⁶⁹⁰ - Breaking changes to traits::*result wrt std::vector<id_type>
- Issue #426⁶⁶⁹¹ - AUTOGLOB needs to be updated to support fortran

HPX V0.8.1 (Apr 21, 2012)

This is a point release including important bug fixes for *HPX V0.8.0 (Mar 23, 2012)*.

⁶⁶⁷⁴ <https://github.com/TheHPXProject/hpx/issues/376>

⁶⁶⁷⁵ <https://github.com/TheHPXProject/hpx/issues/377>

⁶⁶⁷⁶ <https://github.com/TheHPXProject/hpx/issues/379>

⁶⁶⁷⁷ <https://github.com/TheHPXProject/hpx/issues/382>

⁶⁶⁷⁸ <https://github.com/TheHPXProject/hpx/issues/387>

⁶⁶⁷⁹ <https://github.com/TheHPXProject/hpx/issues/388>

⁶⁶⁸⁰ <https://github.com/TheHPXProject/hpx/issues/391>

⁶⁶⁸¹ <https://github.com/TheHPXProject/hpx/issues/392>

⁶⁶⁸² <https://github.com/TheHPXProject/hpx/issues/396>

⁶⁶⁸³ <https://github.com/TheHPXProject/hpx/issues/399>

⁶⁶⁸⁴ <https://github.com/TheHPXProject/hpx/issues/400>

⁶⁶⁸⁵ <https://github.com/TheHPXProject/hpx/issues/401>

⁶⁶⁸⁶ <https://github.com/TheHPXProject/hpx/issues/404>

⁶⁶⁸⁷ <https://github.com/TheHPXProject/hpx/issues/405>

⁶⁶⁸⁸ <https://github.com/TheHPXProject/hpx/issues/406>

⁶⁶⁸⁹ <https://github.com/TheHPXProject/hpx/issues/415>

⁶⁶⁹⁰ <https://github.com/TheHPXProject/hpx/issues/425>

⁶⁶⁹¹ <https://github.com/TheHPXProject/hpx/issues/426>

General changes

- *HPX* does not need to be installed anymore to be functional.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this point release:

- [Issue #295](https://github.com/TheHPXProject/hpx/issues/295)⁶⁶⁹² - Don't require install path to be known at compile time.
- [Issue #371](https://github.com/TheHPXProject/hpx/issues/371)⁶⁶⁹³ - Add `hpx::iostreams` to standard build.
- [Issue #384](https://github.com/TheHPXProject/hpx/issues/384)⁶⁶⁹⁴ - Fix compilation with GCC 4.7.
- [Issue #390](https://github.com/TheHPXProject/hpx/issues/390)⁶⁶⁹⁵ - Remove `keep_factory_alive` startup call from ShenEOS; add shutdown call to `H5close`.
- [Issue #393](https://github.com/TheHPXProject/hpx/issues/393)⁶⁶⁹⁶ - Thread affinity control is broken.

Bug fixes (commits)

Here is a list of the important commits included in this point release:

- `r7642` - External: Fix backtrace memory violation.
- **`r7775` - Components: Fix symbol visibility bug with component startup providers.** This prevents one components providers from overriding another components.
- `r7778` - Components: Fix startup/shutdown provider shadowing issues.

HPX V0.8.0 (Mar 23, 2012)

We have had roughly 1000 commits since the last release and we have closed approximately 70 tickets (bugs, feature requests, etc.).

General changes

- Improved PBS support, allowing for arbitrary naming schemes of node-hostnames.
- Finished verification of the reference counting framework.
- Implemented decrement merging logic to optimize the distributed reference counting system.
- Restructured the LCO framework. Renamed `hpx::lcos::eager_future<>` and `hpx::lcos::lazy_future<>` into `hpx::lcos::packaged_task` and `hpx::lcos::deferred_packaged_task`. Split `hpx::lcos::promise` into `hpx::lcos::packaged_task` and `hpx::lcos::future`. Added 'local' futures (in namespace `hpx::lcos::local`).
- Improved the general performance of local and remote action invocations. This (under certain circumstances) drastically reduces the number of copies created for each of the parameters and return values.

⁶⁶⁹² <https://github.com/TheHPXProject/hpx/issues/295>

⁶⁶⁹³ <https://github.com/TheHPXProject/hpx/issues/371>

⁶⁶⁹⁴ <https://github.com/TheHPXProject/hpx/issues/384>

⁶⁶⁹⁵ <https://github.com/TheHPXProject/hpx/issues/390>

⁶⁶⁹⁶ <https://github.com/TheHPXProject/hpx/issues/393>

- Reworked the performance counter framework. Performance counters are now created only when needed, which reduces the overall resource requirements. The new framework allows for much more flexible creation and management of performance counters. The new sine example application demonstrates some of the capabilities of the new infrastructure.
- Added a buildbot-based continuous build system which gives instant, automated feedback on each commit to SVN.
- Added more automated tests to verify proper functioning of *HPX*.
- Started to create documentation for *HPX* and its API.
- Added documentation toolchain to the build system.
- Added dataflow LCO.
- Changed default *HPX* command line options to have `hpx:` prefix. For instance, the former option `--threads` is now `--hpx:threads`. This has been done to make ambiguities with possible application specific command line options as unlikely as possible. See the section *HPX Command Line Options* for a full list of available options.
- Added the possibility to define command line aliases. The former short (one-letter) command line options have been predefined as aliases for backwards compatibility. See the section *HPX Command Line Options* for a detailed description of command line option aliasing.
- Network connections are now cached based on the connected host. The number of simultaneous connections to a particular host is now limited. Parcels are buffered and bundled if all connections are in use.
- Added more refined thread affinity control. This is based on the external library Portable Hardware Locality (HWLOC).
- Improved support for Windows builds with CMake.
- Added support for components to register their own command line options.
- Added the possibility to register custom startup/shutdown functions for any component. These functions are guaranteed to be executed by an *HPX* thread.
- Added two new experimental thread schedulers: `hierarchy_scheduler` and `periodic_priority_scheduler`. These can be activated by using the command line options `--hpx:queuing=hierarchy` or `--hpx:queuing=periodic`.

Example applications

- [Graph500 performance benchmark](http://www.graph500.org/)⁶⁶⁹⁷ (thanks to Matthew Anderson for contributing this application).
- [GTC \(Gyrokinetic Toroidal Code\)](http://www.nersc.gov/research-and-development/benchmarking-and-workload-characterization/nersc-6-benchmarks/gtc/)⁶⁶⁹⁸: a skeleton for particle in cell type codes.
- Random Memory Access: an example demonstrating random memory accesses in a large array
- [ShenEOS example](http://stellarcollapse.org/equationofstate)⁶⁶⁹⁹, demonstrating partitioning of large read-only data structures and exposing an interpolation API.
- Sine performance counter demo.
- Accumulator examples demonstrating how to write and use *HPX* components.
- Quickstart examples (like `hello_world`, `fibonacci`, `quicksort`, `factorial`, etc.) demonstrating simple *HPX* concepts which introduce some of the concepts in *HPX*.
- Load balancing and work stealing demos.

⁶⁶⁹⁷ <http://www.graph500.org/>

⁶⁶⁹⁸ <http://www.nersc.gov/research-and-development/benchmarking-and-workload-characterization/nersc-6-benchmarks/gtc/>

⁶⁶⁹⁹ <http://stellarcollapse.org/equationofstate>

API changes

- Moved all local LCOs into a separate namespace `hpx::lcos::local` (for instance, `hpx::lcos::local_mutex` is now `hpx::lcos::local::mutex`).
- Replaced `hpx::actions::function` with `hpx::util::function`. Cleaned up related code.
- Removed `hpx::traits::handle_gid` and moved handling of global reference counts into the corresponding serialization code.
- Changed terminology: `prefix` is now called `locality_id`, renamed the corresponding API functions (such as `hpx::get_prefix`, which is now called `hpx::get_locality_id`).
- Adding `hpx::find_remote_localities`, and `hpx::get_num_localities`.
- Changed performance counter naming scheme to make it more bash friendly. The new performance counter naming scheme is now

`/object{parentname#parentindex/instance#index}/counter#parameters`

- Added `hpx::get_worker_thread_num` replacing `hpx::threadmanager_base::get_thread_num`.
- Renamed `hpx::get_num_os_threads` to `hpx::get_os_threads_count`.
- Added `hpx::threads::get_thread_count`.
- Restructured the Futures sub-system, renaming types in accordance with the terminology used by the C++11 ISO standard.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release:

- [Issue #31](#)⁶⁷⁰⁰ - Specialize `handle_gid<>` for examples and tests
- [Issue #72](#)⁶⁷⁰¹ - Fix AGAS reference counting
- [Issue #104](#)⁶⁷⁰² - heartbeat throws an exception when decrefing the performance counter it's watching
- [Issue #111](#)⁶⁷⁰³ - throttle causes an exception on the target application
- [Issue #142](#)⁶⁷⁰⁴ - One failed component loading causes an unrelated component to fail
- [Issue #165](#)⁶⁷⁰⁵ - Remote exception propagation bug in AGAS reference counting test
- [Issue #186](#)⁶⁷⁰⁶ - Test credit exhaustion/splitting (e.g. `prepare_gid` and symbol NS)
- [Issue #188](#)⁶⁷⁰⁷ - Implement remaining AGAS reference counting test cases
- [Issue #258](#)⁶⁷⁰⁸ - No type checking of GIDs in stubs classes
- [Issue #271](#)⁶⁷⁰⁹ - Seg fault/shared pointer assertion in distributed code

⁶⁷⁰⁰ <https://github.com/TheHPXProject/hpx/issues/31>

⁶⁷⁰¹ <https://github.com/TheHPXProject/hpx/issues/72>

⁶⁷⁰² <https://github.com/TheHPXProject/hpx/issues/104>

⁶⁷⁰³ <https://github.com/TheHPXProject/hpx/issues/111>

⁶⁷⁰⁴ <https://github.com/TheHPXProject/hpx/issues/142>

⁶⁷⁰⁵ <https://github.com/TheHPXProject/hpx/issues/165>

⁶⁷⁰⁶ <https://github.com/TheHPXProject/hpx/issues/186>

⁶⁷⁰⁷ <https://github.com/TheHPXProject/hpx/issues/188>

⁶⁷⁰⁸ <https://github.com/TheHPXProject/hpx/issues/258>

⁶⁷⁰⁹ <https://github.com/TheHPXProject/hpx/issues/271>

- Issue #281⁶⁷¹⁰ - CMake options need descriptive text
- Issue #283⁶⁷¹¹ - AGAS caching broken (gva_cache needs to be rewritten with ICL)
- Issue #285⁶⁷¹² - HPX_INSTALL root directory not the same as CMAKE_INSTALL_PREFIX
- Issue #286⁶⁷¹³ - New segfault in dataflow applications
- Issue #289⁶⁷¹⁴ - Exceptions should only be logged if not handled
- Issue #290⁶⁷¹⁵ - c++11 tests failure
- Issue #293⁶⁷¹⁶ - Build target for component libraries
- Issue #296⁶⁷¹⁷ - Compilation error with Boost V1.49rc1
- Issue #298⁶⁷¹⁸ - Illegal instructions on termination
- Issue #299⁶⁷¹⁹ - gravity aborts with multiple threads
- Issue #301⁶⁷²⁰ - Build error with Boost trunk
- Issue #303⁶⁷²¹ - Logging assertion failure in distributed runs
- Issue #304⁶⁷²² - Exception 'what' strings are lost when exceptions from decode_parcel are reported
- Issue #306⁶⁷²³ - Performance counter user interface issues
- Issue #307⁶⁷²⁴ - Logging exception in distributed runs
- Issue #308⁶⁷²⁵ - Logging deadlocks in distributed
- Issue #309⁶⁷²⁶ - Reference counting test failures and exceptions
- Issue #311⁶⁷²⁷ - Merge AGAS remote_interface with the runtime_support object
- Issue #314⁶⁷²⁸ - Object tracking for id_types
- Issue #315⁶⁷²⁹ - Remove handle_gid and handle credit splitting in id_type serialization
- Issue #320⁶⁷³⁰ - applier::get_locality_id() should return an error value (or throw an exception)
- Issue #321⁶⁷³¹ - Optimization for id_types which are never split should be restored
- Issue #322⁶⁷³² - Command line processing ignored with Boost 1.47.0

⁶⁷¹⁰ <https://github.com/TheHPXProject/hpx/issues/281>

⁶⁷¹¹ <https://github.com/TheHPXProject/hpx/issues/283>

⁶⁷¹² <https://github.com/TheHPXProject/hpx/issues/285>

⁶⁷¹³ <https://github.com/TheHPXProject/hpx/issues/286>

⁶⁷¹⁴ <https://github.com/TheHPXProject/hpx/issues/289>

⁶⁷¹⁵ <https://github.com/TheHPXProject/hpx/issues/290>

⁶⁷¹⁶ <https://github.com/TheHPXProject/hpx/issues/293>

⁶⁷¹⁷ <https://github.com/TheHPXProject/hpx/issues/296>

⁶⁷¹⁸ <https://github.com/TheHPXProject/hpx/issues/298>

⁶⁷¹⁹ <https://github.com/TheHPXProject/hpx/issues/299>

⁶⁷²⁰ <https://github.com/TheHPXProject/hpx/issues/301>

⁶⁷²¹ <https://github.com/TheHPXProject/hpx/issues/303>

⁶⁷²² <https://github.com/TheHPXProject/hpx/issues/304>

⁶⁷²³ <https://github.com/TheHPXProject/hpx/issues/306>

⁶⁷²⁴ <https://github.com/TheHPXProject/hpx/issues/307>

⁶⁷²⁵ <https://github.com/TheHPXProject/hpx/issues/308>

⁶⁷²⁶ <https://github.com/TheHPXProject/hpx/issues/309>

⁶⁷²⁷ <https://github.com/TheHPXProject/hpx/issues/311>

⁶⁷²⁸ <https://github.com/TheHPXProject/hpx/issues/314>

⁶⁷²⁹ <https://github.com/TheHPXProject/hpx/issues/315>

⁶⁷³⁰ <https://github.com/TheHPXProject/hpx/issues/320>

⁶⁷³¹ <https://github.com/TheHPXProject/hpx/issues/321>

⁶⁷³² <https://github.com/TheHPXProject/hpx/issues/322>

- Issue #323⁶⁷³³ - Credit exhaustion causes object to stay alive
- Issue #324⁶⁷³⁴ - Duplicate exception messages
- Issue #326⁶⁷³⁵ - Integrate Quickbook with CMake
- Issue #329⁶⁷³⁶ - --help and --version should still work
- Issue #330⁶⁷³⁷ - Create pkg-config files
- Issue #337⁶⁷³⁸ - Improve usability of performance counter timestamps
- Issue #338⁶⁷³⁹ - Non-std exceptions deriving from std::exceptions in tfunc may be sliced
- Issue #339⁶⁷⁴⁰ - Decrease the number of send_pending_parcel threads
- Issue #343⁶⁷⁴¹ - Dynamically setting the stack size doesn't work
- Issue #351⁶⁷⁴² - 'make install' does not update documents
- Issue #353⁶⁷⁴³ - Disable FIXMEs in the docs by default; add a doc developer CMake option to enable FIXMEs
- Issue #355⁶⁷⁴⁴ - 'make' doesn't do anything after correct configuration
- Issue #356⁶⁷⁴⁵ - Don't use `hpx::util::static_` in topology code
- Issue #359⁶⁷⁴⁶ - Infinite recursion in `hpx::tuple` serialization
- Issue #361⁶⁷⁴⁷ - Add compile time option to disable logging completely
- Issue #364⁶⁷⁴⁸ - Installation seriously broken in r7443

HPX V0.7.0 (Dec 12, 2011)

We have had roughly 1000 commits since the last release and we have closed approximately 120 tickets (bugs, feature requests, etc.).

⁶⁷³³ <https://github.com/TheHPXProject/hpx/issues/323>

⁶⁷³⁴ <https://github.com/TheHPXProject/hpx/issues/324>

⁶⁷³⁵ <https://github.com/TheHPXProject/hpx/issues/326>

⁶⁷³⁶ <https://github.com/TheHPXProject/hpx/issues/329>

⁶⁷³⁷ <https://github.com/TheHPXProject/hpx/issues/330>

⁶⁷³⁸ <https://github.com/TheHPXProject/hpx/issues/337>

⁶⁷³⁹ <https://github.com/TheHPXProject/hpx/issues/338>

⁶⁷⁴⁰ <https://github.com/TheHPXProject/hpx/issues/339>

⁶⁷⁴¹ <https://github.com/TheHPXProject/hpx/issues/343>

⁶⁷⁴² <https://github.com/TheHPXProject/hpx/issues/351>

⁶⁷⁴³ <https://github.com/TheHPXProject/hpx/issues/353>

⁶⁷⁴⁴ <https://github.com/TheHPXProject/hpx/issues/355>

⁶⁷⁴⁵ <https://github.com/TheHPXProject/hpx/issues/356>

⁶⁷⁴⁶ <https://github.com/TheHPXProject/hpx/issues/359>

⁶⁷⁴⁷ <https://github.com/TheHPXProject/hpx/issues/361>

⁶⁷⁴⁸ <https://github.com/TheHPXProject/hpx/issues/364>

General changes

- Completely removed code related to deprecated AGAS V1, started to work on AGAS V2.1.
- Started to clean up and streamline the exposed APIs (see ‘API changes’ below for more details).
- Revamped and unified performance counter framework, added a lot of new performance counter instances for monitoring of a diverse set of internal *HPX* parameters (queue lengths, access statistics, etc.).
- Improved general error handling and logging support.
- Fixed several race conditions, improved overall stability, decreased memory footprint, improved overall performance (major optimizations include native TLS support and ranged-based AGAS caching).
- Added support for running *HPX* applications with PBS.
- Many updates to the build system, added support for gcc 4.5.x and 4.6.x, added C++11 support.
- Many updates to default command line options.
- Added many tests, set up buildbot for continuous integration testing.
- Better shutdown handling of distributed applications.

Example applications

- quickstart/factorial and quickstart/fibonacci, future-recursive parallel algorithms.
- quickstart/hello_world, distributed hello world example.
- quickstart/rma, simple remote memory access example
- quickstart/quicksort, parallel quicksort implementation.
- gtc, gyrokinetic torodial code.
- bfs, breadth-first-search, example code for a graph application.
- sheneos, partitioning of large data sets.
- accumulator, simple component example.
- balancing/os_thread_num, balancing/px_thread_phase, examples demonstrating load balancing and work stealing.

API changes

- Added `hpx::find_all_localities`.
- Added `hpx::terminate` for non-graceful termination of applications.
- Added `hpx::lcos::async` functions for simpler asynchronous programming.
- Added new AGAS interface for handling of symbolic namespace (`hpx::agas::*`).
- Renamed `hpx::components::wait` to `hpx::lcos::wait`.
- Renamed `hpx::lcos::future_value` to `hpx::lcos::promise`.
- Renamed `hpx::lcos::recursive_mutex` to `hpx::lcos::local_recursive_mutex`, `hpx::lcos::mutex` to `hpx::lcos::local_mutex`
- Removed support for Boost versions older than V1.38, recommended Boost version is now V1.47 and newer.

- Removed `hpx::process` (this will be replaced by a real process implementation in the future).
- Removed non-functional LCO code (`hpx::lcos::dataflow`, `hpx::lcos::thunk`, `hpx::lcos::dataflow_variable`).
- Removed deprecated `hpx::naming::full_address`.

Bug fixes (closed tickets)

Here is a list of the important tickets we closed for this release:

- [Issue #28⁶⁷⁴⁹](#) - Integrate Windows/Linux CMake code for *HPX* core
- [Issue #32⁶⁷⁵⁰](#) - `hpx::cout()` should be `hpx::cout`
- [Issue #33⁶⁷⁵¹](#) - AGAS V2 legacy client does not properly handle `error_code`
- [Issue #60⁶⁷⁵²](#) - AGAS: allow for `registerid` to optionally take ownership of the `gid`
- [Issue #62⁶⁷⁵³](#) - `adaptive1d` compilation failure in Fusion
- [Issue #64⁶⁷⁵⁴](#) - Parcel subsystem doesn't resolve domain names
- [Issue #83⁶⁷⁵⁵](#) - No error handling if no console is available
- [Issue #84⁶⁷⁵⁶](#) - No error handling if a hosted locality is treated as the bootstrap server
- [Issue #90⁶⁷⁵⁷](#) - Add general commandline option `-N`
- [Issue #91⁶⁷⁵⁸](#) - Add possibility to read command line arguments from file
- [Issue #92⁶⁷⁵⁹](#) - Always log exceptions/errors to the log file
- [Issue #93⁶⁷⁶⁰](#) - Log the command line/program name
- [Issue #95⁶⁷⁶¹](#) - Support for distributed launches
- [Issue #97⁶⁷⁶²](#) - Attempt to create a bad component type in AMR examples
- [Issue #100⁶⁷⁶³](#) - `factorial` and `factorial_get` examples trigger AGAS component type assertions
- [Issue #101⁶⁷⁶⁴](#) - Segfault when `hpx::process::here()` is called in `fibonacci2`
- [Issue #102⁶⁷⁶⁵](#) - `unknown_component_address` in `int_object_semaphore_client`
- [Issue #114⁶⁷⁶⁶](#) - `marduk` raises assertion with default parameters

⁶⁷⁴⁹ <https://github.com/TheHPXProject/hpx/issues/28>

⁶⁷⁵⁰ <https://github.com/TheHPXProject/hpx/issues/32>

⁶⁷⁵¹ <https://github.com/TheHPXProject/hpx/issues/33>

⁶⁷⁵² <https://github.com/TheHPXProject/hpx/issues/60>

⁶⁷⁵³ <https://github.com/TheHPXProject/hpx/issues/62>

⁶⁷⁵⁴ <https://github.com/TheHPXProject/hpx/issues/64>

⁶⁷⁵⁵ <https://github.com/TheHPXProject/hpx/issues/83>

⁶⁷⁵⁶ <https://github.com/TheHPXProject/hpx/issues/84>

⁶⁷⁵⁷ <https://github.com/TheHPXProject/hpx/issues/90>

⁶⁷⁵⁸ <https://github.com/TheHPXProject/hpx/issues/91>

⁶⁷⁵⁹ <https://github.com/TheHPXProject/hpx/issues/92>

⁶⁷⁶⁰ <https://github.com/TheHPXProject/hpx/issues/93>

⁶⁷⁶¹ <https://github.com/TheHPXProject/hpx/issues/95>

⁶⁷⁶² <https://github.com/TheHPXProject/hpx/issues/97>

⁶⁷⁶³ <https://github.com/TheHPXProject/hpx/issues/100>

⁶⁷⁶⁴ <https://github.com/TheHPXProject/hpx/issues/101>

⁶⁷⁶⁵ <https://github.com/TheHPXProject/hpx/issues/102>

⁶⁷⁶⁶ <https://github.com/TheHPXProject/hpx/issues/114>

- [Issue #115](#)⁶⁷⁶⁷ - Logging messages for SMP runs (on the console) shouldn't be buffered
- [Issue #119](#)⁶⁷⁶⁸ - marduk linking strategy breaks other applications
- [Issue #121](#)⁶⁷⁶⁹ - pbsdsh problem
- [Issue #123](#)⁶⁷⁷⁰ - marduk, dataflow and adaptive1d fail to build
- [Issue #124](#)⁶⁷⁷¹ - Lower default preprocessing arity
- [Issue #125](#)⁶⁷⁷² - Move hpx::detail::diagnostic_information out of the detail namespace
- [Issue #126](#)⁶⁷⁷³ - Test definitions for AGAS reference counting
- [Issue #128](#)⁶⁷⁷⁴ - Add averaging performance counter
- [Issue #129](#)⁶⁷⁷⁵ - Error with endian.hpp while building adaptive1d
- [Issue #130](#)⁶⁷⁷⁶ - Bad initialization of performance counters
- [Issue #131](#)⁶⁷⁷⁷ - Add global startup/shutdown functions to component modules
- [Issue #132](#)⁶⁷⁷⁸ - Avoid using auto_ptr
- [Issue #133](#)⁶⁷⁷⁹ - On Windows hpx.dll doesn't get installed
- [Issue #134](#)⁶⁷⁸⁰ - HPX_LIBRARY does not reflect real library name (on Windows)
- [Issue #135](#)⁶⁷⁸¹ - Add detection of unique_ptr to build system
- [Issue #137](#)⁶⁷⁸² - Add command line option allowing to repeatedly evaluate performance counters
- [Issue #139](#)⁶⁷⁸³ - Logging is broken
- [Issue #140](#)⁶⁷⁸⁴ - CMake problem on windows
- [Issue #141](#)⁶⁷⁸⁵ - Move all non-component libraries into \$PREFIX/lib/hpx
- [Issue #143](#)⁶⁷⁸⁶ - adaptive1d throws an exception with the default command line options
- [Issue #146](#)⁶⁷⁸⁷ - Early exception handling is broken
- [Issue #147](#)⁶⁷⁸⁸ - Sheneos doesn't link on Linux
- [Issue #149](#)⁶⁷⁸⁹ - sheneos_test hangs

⁶⁷⁶⁷ <https://github.com/TheHPXProject/hpx/issues/115>

⁶⁷⁶⁸ <https://github.com/TheHPXProject/hpx/issues/119>

⁶⁷⁶⁹ <https://github.com/TheHPXProject/hpx/issues/121>

⁶⁷⁷⁰ <https://github.com/TheHPXProject/hpx/issues/123>

⁶⁷⁷¹ <https://github.com/TheHPXProject/hpx/issues/124>

⁶⁷⁷² <https://github.com/TheHPXProject/hpx/issues/125>

⁶⁷⁷³ <https://github.com/TheHPXProject/hpx/issues/126>

⁶⁷⁷⁴ <https://github.com/TheHPXProject/hpx/issues/128>

⁶⁷⁷⁵ <https://github.com/TheHPXProject/hpx/issues/129>

⁶⁷⁷⁶ <https://github.com/TheHPXProject/hpx/issues/130>

⁶⁷⁷⁷ <https://github.com/TheHPXProject/hpx/issues/131>

⁶⁷⁷⁸ <https://github.com/TheHPXProject/hpx/issues/132>

⁶⁷⁷⁹ <https://github.com/TheHPXProject/hpx/issues/133>

⁶⁷⁸⁰ <https://github.com/TheHPXProject/hpx/issues/134>

⁶⁷⁸¹ <https://github.com/TheHPXProject/hpx/issues/135>

⁶⁷⁸² <https://github.com/TheHPXProject/hpx/issues/137>

⁶⁷⁸³ <https://github.com/TheHPXProject/hpx/issues/139>

⁶⁷⁸⁴ <https://github.com/TheHPXProject/hpx/issues/140>

⁶⁷⁸⁵ <https://github.com/TheHPXProject/hpx/issues/141>

⁶⁷⁸⁶ <https://github.com/TheHPXProject/hpx/issues/143>

⁶⁷⁸⁷ <https://github.com/TheHPXProject/hpx/issues/146>

⁶⁷⁸⁸ <https://github.com/TheHPXProject/hpx/issues/147>

⁶⁷⁸⁹ <https://github.com/TheHPXProject/hpx/issues/149>

- [Issue #154](#)⁶⁷⁹⁰ - Compilation fails for r5661
- [Issue #155](#)⁶⁷⁹¹ - Sine performance counters example chokes on chrono headers
- [Issue #156](#)⁶⁷⁹² - Add build type to `--version`
- [Issue #157](#)⁶⁷⁹³ - Extend AGAS caching to store gid ranges
- [Issue #158](#)⁶⁷⁹⁴ - r5691 doesn't compile
- [Issue #160](#)⁶⁷⁹⁵ - Re-add AGAS function for resolving a locality to its prefix
- [Issue #168](#)⁶⁷⁹⁶ - Managed components should be able to access their own GID
- [Issue #169](#)⁶⁷⁹⁷ - Rewrite AGAS future pool
- [Issue #179](#)⁶⁷⁹⁸ - Complete switch to request class for AGAS server interface
- [Issue #182](#)⁶⁷⁹⁹ - Sine performance counter is loaded by other examples
- [Issue #185](#)⁶⁸⁰⁰ - Write tests for symbol namespace reference counting
- [Issue #191](#)⁶⁸⁰¹ - Assignment of read-only variable in `point_geometry`
- [Issue #200](#)⁶⁸⁰² - Seg faults when querying performance counters
- [Issue #204](#)⁶⁸⁰³ - `--ifnames` and suffix stripping needs to be more generic
- [Issue #205](#)⁶⁸⁰⁴ - `--list-*` and `--print-counter-*` options do not work together and produce no warning
- [Issue #207](#)⁶⁸⁰⁵ - Implement decrement entry merging
- [Issue #208](#)⁶⁸⁰⁶ - Replace the spinlocks in AGAS with `hpx::lcos::local_mutexes`
- [Issue #210](#)⁶⁸⁰⁷ - Add an `--ifprefix` option
- [Issue #214](#)⁶⁸⁰⁸ - Performance test for PX-thread creation
- [Issue #216](#)⁶⁸⁰⁹ - VS2010 compilation
- [Issue #222](#)⁶⁸¹⁰ - r6045 `context_linux_x86.hpp`
- [Issue #223](#)⁶⁸¹¹ - fibonacci hangs when changing the state of an active thread
- [Issue #225](#)⁶⁸¹² - Active threads end up in the FEB wait queue

⁶⁷⁹⁰ <https://github.com/TheHPXProject/hpx/issues/154>

⁶⁷⁹¹ <https://github.com/TheHPXProject/hpx/issues/155>

⁶⁷⁹² <https://github.com/TheHPXProject/hpx/issues/156>

⁶⁷⁹³ <https://github.com/TheHPXProject/hpx/issues/157>

⁶⁷⁹⁴ <https://github.com/TheHPXProject/hpx/issues/158>

⁶⁷⁹⁵ <https://github.com/TheHPXProject/hpx/issues/160>

⁶⁷⁹⁶ <https://github.com/TheHPXProject/hpx/issues/168>

⁶⁷⁹⁷ <https://github.com/TheHPXProject/hpx/issues/169>

⁶⁷⁹⁸ <https://github.com/TheHPXProject/hpx/issues/179>

⁶⁷⁹⁹ <https://github.com/TheHPXProject/hpx/issues/182>

⁶⁸⁰⁰ <https://github.com/TheHPXProject/hpx/issues/185>

⁶⁸⁰¹ <https://github.com/TheHPXProject/hpx/issues/191>

⁶⁸⁰² <https://github.com/TheHPXProject/hpx/issues/200>

⁶⁸⁰³ <https://github.com/TheHPXProject/hpx/issues/204>

⁶⁸⁰⁴ <https://github.com/TheHPXProject/hpx/issues/205>

⁶⁸⁰⁵ <https://github.com/TheHPXProject/hpx/issues/207>

⁶⁸⁰⁶ <https://github.com/TheHPXProject/hpx/issues/208>

⁶⁸⁰⁷ <https://github.com/TheHPXProject/hpx/issues/210>

⁶⁸⁰⁸ <https://github.com/TheHPXProject/hpx/issues/214>

⁶⁸⁰⁹ <https://github.com/TheHPXProject/hpx/issues/216>

⁶⁸¹⁰ <https://github.com/TheHPXProject/hpx/issues/222>

⁶⁸¹¹ <https://github.com/TheHPXProject/hpx/issues/223>

⁶⁸¹² <https://github.com/TheHPXProject/hpx/issues/225>

- [Issue #226](#)⁶⁸¹³ - VS Build Error for Accumulator Client
- [Issue #228](#)⁶⁸¹⁴ - Move all traits into namespace `hpx::traits`
- [Issue #229](#)⁶⁸¹⁵ - Invalid initialization of reference in `thread_init_data`
- [Issue #235](#)⁶⁸¹⁶ - Invalid GID in `iostreams`
- [Issue #238](#)⁶⁸¹⁷ - Demangle type names for the default implementation of `get_action_name`
- [Issue #241](#)⁶⁸¹⁸ - C++11 support breaks GCC 4.5
- [Issue #247](#)⁶⁸¹⁹ - Reference to temporary with GCC 4.4
- [Issue #248](#)⁶⁸²⁰ - Seg fault at shutdown with GCC 4.4
- [Issue #253](#)⁶⁸²¹ - Default component action registration kills compiler
- [Issue #272](#)⁶⁸²² - G++ unrecognized command line option
- [Issue #273](#)⁶⁸²³ - quicksort example doesn't compile
- [Issue #277](#)⁶⁸²⁴ - Invalid CMake logic for Windows

2.11.3 Namespace changes

HPX V1.9.0 Namespace changes

The latest release includes amongst others changes in the namespaces so that *HPX* facilities correspond to the C++ Standard Library. The old namespaces are deprecated. Below is a comprehensive list of the namespace changes.

Table 2.194: Namespace changes in V1.9.0

Old namespace	New namespace
<code>hpx::util::mem_fn</code>	<code>hpx::mem_fn</code>
<code>hpx::util::invoke</code>	<code>hpx::invoke</code>
<code>hpx::util::invoke_r</code>	<code>hpx::invoke_r</code>
<code>hpx::util::invoke_fused</code>	<code>hpx::invoke_fused</code>
<code>hpx::util::invoke_fused_r</code>	<code>hpx::invoke_fused_r</code>
<code>hpx::util::unlock_guard</code>	<code>hpx::unlock_guard</code>
<code>hpx::parallel::v1::reduce_by_key</code>	<code>hpx::experimental::reduce_by_key</code>
<code>hpx::parallel::v1::sort_by_key</code>	<code>hpx::experimental::sort_by_key</code>
<code>hpx::parallel::task_canceled_exception</code>	<code>hpx::experimental::task_canceled_exception</code>
<code>hpx::parallel::task_block</code>	<code>hpx::experimental::task_block</code>
<code>hpx::parallel::define_task_block</code>	<code>hpx::experimental::define_task_block</code>
<code>hpx::parallel::define_task_block_restore_thread</code>	<code>hpx::experimental::define_task_block_restore_thread</code>
<code>hpx::execution::experimental::task_group</code>	<code>hpx::experimental::task_group</code>

⁶⁸¹³ <https://github.com/TheHPXProject/hpx/issues/226>

⁶⁸¹⁴ <https://github.com/TheHPXProject/hpx/issues/228>

⁶⁸¹⁵ <https://github.com/TheHPXProject/hpx/issues/229>

⁶⁸¹⁶ <https://github.com/TheHPXProject/hpx/issues/235>

⁶⁸¹⁷ <https://github.com/TheHPXProject/hpx/issues/238>

⁶⁸¹⁸ <https://github.com/TheHPXProject/hpx/issues/241>

⁶⁸¹⁹ <https://github.com/TheHPXProject/hpx/issues/247>

⁶⁸²⁰ <https://github.com/TheHPXProject/hpx/issues/248>

⁶⁸²¹ <https://github.com/TheHPXProject/hpx/issues/253>

⁶⁸²² <https://github.com/TheHPXProject/hpx/issues/272>

⁶⁸²³ <https://github.com/TheHPXProject/hpx/issues/273>

⁶⁸²⁴ <https://github.com/TheHPXProject/hpx/issues/277>

2.12 Citing *HPX*

Please cite *HPX* whenever you use it for publications. Use our paper in The Journal of Open Source Software as the main citation for *HPX*: ⁶⁸²⁵. Use the Zenodo entry for referring to the latest version of *HPX*: ⁶⁸²⁶. Entries for citing specific versions of *HPX* can also be found at ⁶⁸²⁷.

2.13 *HPX* users

A list of institutions and projects using *HPX* can be found on the *HPX Users*⁶⁸²⁸ page.

2.14 About *HPX*

2.14.1 History

The development of High Performance ParallelX (*HPX*) began in 2007. At that time, Hartmut Kaiser became interested in the work done by the ParallelX group at the [Center for Computation and Technology \(CCT\)](#)⁶⁸²⁹, a multi-disciplinary research institute at [Louisiana State University \(LSU\)](#)⁶⁸³⁰. The ParallelX group was working to develop a new and experimental execution model for future high performance computing architectures. This model was christened ParallelX. The first implementations of ParallelX were crude, and many of those designs had to be discarded entirely. However, over time the team learned quite a bit about how to design a parallel, distributed runtime system which implements the concepts of ParallelX.

From the very beginning, this endeavour has been a group effort. In addition to a handful of interested researchers, there have always been graduate and undergraduate students participating in the discussions, design, and implementation of *HPX*. In 2011 we decided to formalize our collective research efforts by creating the [STE||AR](#)⁶⁸³¹ group (Systems Technology, Emergent Parallelism, and Algorithm Research). Over time, the team grew to include researchers around the country and the world. In 2014, the [STE||AR](#)⁶⁸³² Group was reorganized to become the international community it is today. This consortium of researchers aims to develop stable, sustainable, and scalable tools which will enable application developers to exploit the parallelism latent in the machines of today and tomorrow. Our goal of the *HPX* project is to create a high quality, freely available, open source implementation of ParallelX concepts for conventional and future systems by building a modular and standards conforming runtime system for SMP and distributed application environments. The API exposed by *HPX* is conformant to the interfaces defined by the C++ ISO Standard and adheres to the programming guidelines used by the [Boost](#)⁶⁸³³ collection of C++ libraries. We steer the development of *HPX* with real world applications and aim to provide a smooth migration path for domain scientists.

To learn more about [STE||AR](#)⁶⁸³⁴ and ParallelX, see *People* and *Why HPX?*.

⁶⁸²⁵ <https://joss.theoj.org/papers/022e5917b95517dff20cd3742ab95eca>

⁶⁸²⁶ <https://doi.org/10.5281/zenodo.598202>

⁶⁸²⁷ <https://doi.org/10.5281/zenodo.598202>

⁶⁸²⁸ <https://hpx.stellar-group.org/hpx-users/>

⁶⁸²⁹ <https://www.cct.lsu.edu>

⁶⁸³⁰ <https://www.lsu.edu>

⁶⁸³¹ <https://stellar-group.org>

⁶⁸³² <https://stellar-group.org>

⁶⁸³³ <https://www.boost.org/>

⁶⁸³⁴ <https://stellar-group.org>

2.14.2 People

The [STE||AR](https://stellar-group.org)⁶⁸³⁵ Group (pronounced as stellar) stands for “Systems Technology, Emergent Parallelism, and Algorithm Research”. We are an international group of faculty, researchers, and students working at various institutions around the world. The goal of the [STE||AR](https://stellar-group.org)⁶⁸³⁶ Group is to promote the development of scalable parallel applications by providing a community for ideas, a framework for collaboration, and a platform for communicating these concepts to the broader community.

Our work is focused on building technologies for scalable parallel applications. *HPX*, our general purpose C++ runtime system for parallel and distributed applications, is no exception. We use *HPX* for a broad range of scientific applications, helping scientists and developers to write code which scales better and shows better performance compared to more conventional programming models such as MPI.

HPX is based on *ParalleX* which is a new (and still experimental) parallel execution model aiming to overcome the limitations imposed by the current hardware and the techniques we use to write applications today. Our group focuses on two types of applications - those requiring excellent strong scaling, allowing for a dramatic reduction of execution time for fixed workloads and those needing highest level of sustained performance through massive parallelism. These applications are presently unable (through conventional practices) to effectively exploit a relatively small number of cores in a multi-core system. By extension, these application will not be able to exploit high-end exascale computing systems which are likely to employ hundreds of millions of such cores by the end of this decade.

Critical bottlenecks to the effective use of new generation high performance computing (HPC) systems include:

- *Starvation*: due to lack of usable application parallelism and means of managing it,
- *Overhead*: reduction to permit strong scalability, improve efficiency, and enable dynamic resource management,
- *Latency*: from remote access across system or to local memories,
- *Contention*: due to multicore chip I/O pins, memory banks, and system interconnects.

The *ParalleX* model has been devised to address these challenges by enabling a new computing dynamic through the application of message-driven computation in a global address space context with lightweight synchronization. The work on *HPX* is centered around implementing the concepts as defined by the *ParalleX* model. *HPX* is currently targeted at conventional machines, such as classical Linux based Beowulf clusters and SMP nodes.

We fully understand that the success of *HPX* (and *ParalleX*) is very much the result of the work of many people. To see a list of who is contributing see our tables below.

⁶⁸³⁵ <https://stellar-group.org>

⁶⁸³⁶ <https://stellar-group.org>

HPX contributors

Table 2.195: Contributors

Name	Institution	Email
Hartmut Kaiser	Center for Computation and Technology (CCT) ⁶⁸³⁷ , Louisiana State University (LSU) ⁶⁸³⁸	hkaiser@cct.lsu.edu
Thomas Heller	Department of Computer Science 3 - Computer Architecture ⁶⁸³⁹ , Friedrich-Alexander University Erlangen-Nuremberg (FAU) ⁶⁸⁴⁰	thom.heller@gmail.com
Agustin Berge		agustinberge@gmail.com
Mikael Simberg	Swiss National Supercomputing Centre ⁶⁸⁴¹	simbergm@cscs.ch
John Biddiscombe	Swiss National Supercomputing Centre ⁶⁸⁴²	biddisco@cscs.ch
Anton Bikiineev	Center for Computation and Technology (CCT) ⁶⁸⁴³ , Louisiana State University (LSU) ⁶⁸⁴⁴	ant.bikineev@gmail.com
Martin Stumpf	Department of Computer Science 3 - Computer Architecture ⁶⁸⁴⁵ , Friedrich-Alexander University Erlangen-Nuremberg (FAU) ⁶⁸⁴⁶	martin.h.stumpf@gmail.com
Bryce Adelstein Lelbach		brycelelbach@gmail.com
Shuangyang Yang	Center for Computation and Technology (CCT) ⁶⁸⁴⁷ , Louisiana State University (LSU) ⁶⁸⁴⁸	syang16@cct.lsu.edu
Jeroen Habraken		vexocide@gmail.com
Steven Brandt	Center for Computation and Technology (CCT) ⁶⁸⁴⁹ , Louisiana State University (LSU) ⁶⁸⁵⁰	sbrandt@cct.lsu.edu
Antoine Tran Tan	Paris-Saclay University ⁶⁸⁵¹ ,	antoine.trantant@universite-paris-saclay.fr
Adrian S. Lemoine	AMD ⁶⁸⁵²	Adrian.Lemoine@amd.com
Maciej Brodowicz		maciekab@gmail.com
Giannis Gonidellis	Center for Computation and Technology (CCT) ⁶⁸⁵³ , Louisiana State University (LSU) ⁶⁸⁵⁴	gonidellis@hotmail.com

⁶⁸³⁷ <https://www.cct.lsu.edu>⁶⁸³⁸ <https://www.lsu.edu>⁶⁸³⁹ <https://www3.cs.fau.de>⁶⁸⁴⁰ <https://www.fau.de>⁶⁸⁴¹ <https://www.cscs.ch>⁶⁸⁴² <https://www.cscs.ch>⁶⁸⁴³ <https://www.cct.lsu.edu>⁶⁸⁴⁴ <https://www.lsu.edu>⁶⁸⁴⁵ <https://www3.cs.fau.de>⁶⁸⁴⁶ <https://www.fau.de>⁶⁸⁴⁷ <https://www.cct.lsu.edu>⁶⁸⁴⁸ <https://www.lsu.edu>⁶⁸⁴⁹ <https://www.cct.lsu.edu>⁶⁸⁵⁰ <https://www.lsu.edu>⁶⁸⁵¹ <https://www.universite-paris-saclay.fr/en>⁶⁸⁵² <https://www.amd.com/en>⁶⁸⁵³ <https://www.cct.lsu.edu>⁶⁸⁵⁴ <https://www.lsu.edu>

Contributors to this document

Table 2.196: Documentation authors

Name	Institution	Email
Hartmut Kaiser	Center for Computation and Technology (CCT) ⁶⁸⁵⁵ , Louisiana State University (LSU) ⁶⁸⁵⁶	hkaiser@cct.lsu.edu
Thomas Heller	Department of Computer Science 3 - Computer Architecture ⁶⁸⁵⁷ , Friedrich-Alexander University Erlangen-Nuremberg (FAU) ⁶⁸⁵⁸	thom.heller@gmail.com
Bryce Adelstein Leibach		bryceleibach@gmail.com
Vinay C Amatya	Center for Computation and Technology (CCT) ⁶⁸⁵⁹ , Louisiana State University (LSU) ⁶⁸⁶⁰	vamatya@cct.lsu.edu
Steven Brandt	Center for Computation and Technology (CCT) ⁶⁸⁶¹ , Louisiana State University (LSU) ⁶⁸⁶²	sbrandt@cct.lsu.edu
Maciej Brodowicz		maciekab@gmail.com
Adrian S. Lemoine	AMD ⁶⁸⁶³	Adrian.Lemoine@amd.com
Rebecca Stobaugh		rstobaugh1@gmail.com
Dimitra Karatza	Faculty of Electrical Engineering, Mathematics & Computer Science ⁶⁸⁶⁴ , Delft University of Technology ⁶⁸⁶⁵	dimitra.karatza11@gmail.com
Bhumit Attarde		bhumitattarde2@gmail.com

Acknowledgements

Thanks also to the following people who contributed directly or indirectly to the project through discussions, pull requests, documentation patches, etc.

- Panos Syskakis for benchmarking and optimizing our parallel algorithms.
- Shreyas Atre, for contributing fixes to our implementation of senders/receivers and extending our coroutines integration with senders/receivers.
- Alexander Neumann, for contributing fixes to the cmake build system.
- Dimitra Karatza, for her work on refactoring the documentation and providing a new user-friendly environment during and after Google Season of Docs 2021.

⁶⁸⁵⁵ <https://www.cct.lsu.edu>

⁶⁸⁵⁶ <https://www.lsu.edu>

⁶⁸⁵⁷ <https://www3.cs.fau.de>

⁶⁸⁵⁸ <https://www.fau.de>

⁶⁸⁵⁹ <https://www.cct.lsu.edu>

⁶⁸⁶⁰ <https://www.lsu.edu>

⁶⁸⁶¹ <https://www.cct.lsu.edu>

⁶⁸⁶² <https://www.lsu.edu>

⁶⁸⁶³ <https://www.amd.com/en>

⁶⁸⁶⁴ <https://www.tudelft.nl/en/eemcs>

⁶⁸⁶⁵ <https://www.tudelft.nl/en/>

- Srinivas Yadav, for his work on SIMD support in algorithms before and during Google Summer of Code 2021.
- Akhil Nair, for his work on adapting algorithms to C++20 before and during Google Summer of Code 2021.
- Alexander Toktarev, for updating the parallel algorithm customization points to use `tag_fallback_invoke` for the default implementations.
- Brice Goglin, for reporting and helping fix issues related to the integration of `hwloc` in *HPX*.
- Giannis Gonidelis, for his work on the ranges adaptation during the Google Summer of Code 2020.
- Auriane Reverdell ([Swiss National Supercomputing Centre⁶⁸⁶⁶](https://www.cscs.ch)), for her tireless work on refactoring our CMake setup and modularizing *HPX*.
- Christopher Hinz, for his work on refactoring our CMake setup.
- Weile Wei, for fixing *HPX* builds with CUDA on Summit.
- Severin Strobl, for fixing our CMake setup related to linking and adding new entry points to the *HPX* runtime.
- Rebecca Stobaugh, for her major documentation review and contributions during and after the 2019 Google Season of Documentation.
- Jan Melech, for adding automatic serialization of simple structs.
- Austin McCartney, for adding concept emulation of the Ranges TS bidirectional and random access iterator concepts.
- Marco Diers, reporting and fixing issues related PMIx.
- Maximilian Bremer, for reporting multiple issues and extending the component migration tests.
- Piotr Mikolajczyk, for his improvements and fixes to the set and count algorithms.
- Grant Rostig, for reporting several deficiencies on our web pages.
- Jakub Golinowski, for implementing an *HPX* backend for OpenCV and in the process improving documentation and reporting issues.
- Mikael Simberg ([Swiss National Supercomputing Centre⁶⁸⁶⁷](https://www.cscs.ch)), for his tireless help cleaning up and maintaining *HPX*.
- Tianyi Zhang, for his work on HPXMP.
- Shahrzad Shirzad, for her contributions related to Phylanx.
- Christopher Ogle, for his contributions to the parallel algorithms.
- Surya Priy, for his work with statistic performance counters.
- Anushi Maheshwari, for her work on random number generation.
- Bruno Pitrus, for his work with parallel algorithms.
- Nikunj Gupta, for rewriting the implementation of `hpx_main.hpp` and for his fixes for tests.
- Christopher Taylor, for his interest in *HPX* and the fixes he provided. Chris also contributed support for RISC-V architectures.
- Shoshana Jakobovits, for her work on the resource partitioner.
- Denis Blank, who re-wrote our unwrapped function to accept plain values arbitrary containers, and properly deal with nested futures.
- Ajai V. George, who implemented several of the parallel algorithms.

⁶⁸⁶⁶ <https://www.cscs.ch>

⁶⁸⁶⁷ <https://www.cscs.ch>

- Taeguk Kwon, who worked on implementing parallel algorithms as well as adapting the parallel algorithms to the Ranges TS.
- Zach Byerly ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁸⁶⁸), who in his work developing applications on top of *HPX* opened tickets and contributed to the *HPX* examples.
- Daniel Estermann, for his work porting *HPX* to the Raspberry Pi.
- Alireza Kheirkhahan ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁸⁶⁹), who built and administered our local cluster as well as his work in distributed IO.
- Abhimanyu Rawat, who worked on stack overflow detection.
- David Pfander, who improved signal handling in *HPX*, provided his optimization expertise, and worked on incorporating the Vc vectorization into *HPX*.
- Denis Demidov, who contributed his insights with VexCL.
- Khalid Hasanov, who contributed changes which allowed to run *HPX* on 64Bit power-pc architectures.
- Zahra Khatami ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁸⁷⁰), who contributed the prefetching iterators and the persistent auto chunking executor parameters implementation.
- Marcin Copik, who worked on implementing GPU support for C++AMP and HCC. He also worked on implementing a HCC backend for *HPX.Compute*.
- Minh-Khanh Do, who contributed the implementation of several segmented algorithms.
- Bibek Wagle ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁸⁷¹), who worked on fixing and analyzing the performance of the *parcel* coalescing plugin in *HPX*.
- Lukas Troska, who reported several problems and contributed various test cases allowing to reproduce the corresponding issues.
- Andreas Schaefer, who worked on integrating his library ([LibGeoDecomp](https://www.libgeodecomp.org/)⁶⁸⁷²) with *HPX*. He reported various problems and submitted several patches to fix issues allowing for a better integration with [LibGeoDecomp](https://www.libgeodecomp.org/)⁶⁸⁷³.
- Satyaki Upadhyay, who contributed several examples to *HPX*.
- Brandon Cordes, who contributed several improvements to the inspect tool.
- Harris Brakmic, who contributed an extensive build system description for building *HPX* with Visual Studio.
- Parsa Amini ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁸⁷⁴), who refactored and simplified the implementation of AGAS in *HPX* and who works on its implementation and optimization.
- Luis Martinez de Bartolome who implemented a build system extension for *HPX* integrating it with the [Conan](https://www.conan.io/)⁶⁸⁷⁵ C/C++ package manager.
- Vinay C Amatya ([Louisiana State University \(LSU\)](https://www.lsu.edu)⁶⁸⁷⁶), who contributed to the documentation and provided some of the *HPX* examples.
- Kevin Huck and Nick Chaimov ([University of Oregon](https://uoregon.edu/)⁶⁸⁷⁷), who contributed the integration of APEX (Autonomic Performance Environment for eXascale) with *HPX*.
- Francisco Jose Tapia, who helped with implementing the parallel sort algorithm for *HPX*.

⁶⁸⁶⁸ <https://www.lsu.edu>

⁶⁸⁶⁹ <https://www.lsu.edu>

⁶⁸⁷⁰ <https://www.lsu.edu>

⁶⁸⁷¹ <https://www.lsu.edu>

⁶⁸⁷² <https://www.libgeodecomp.org/>

⁶⁸⁷³ <https://www.libgeodecomp.org/>

⁶⁸⁷⁴ <https://www.lsu.edu>

⁶⁸⁷⁵ <https://www.conan.io/>

⁶⁸⁷⁶ <https://www.lsu.edu>

⁶⁸⁷⁷ <https://uoregon.edu/>

- Patrick Diehl, who worked on implementing CUDA support for our companion library targeting GPGPUs ([HPXCL](#)⁶⁸⁷⁸).
- Eric Lemanissier contributed fixes to allow compilation using the MingW toolchain.
- Nidhi Makhijani who helped cleaning up some enum consistencies in *HPX* and contributed to the resource manager used in the thread scheduling subsystem. She also worked on *HPX* in the context of the Google Summer of Code 2015.
- Larry Xiao, Devang Bacharwar, Marcin Copik, and Konstantin Kronfeldner who worked on *HPX* in the context of the Google Summer of Code program 2015.
- Daniel Bourgeois ([Center for Computation and Technology \(CCT\)](#)⁶⁸⁷⁹) who contributed to *HPX* the implementation of several parallel algorithms (as proposed by [N4313](#)⁶⁸⁸⁰).
- Anuj Sharma and Christopher Bross ([Department of Computer Science 3 - Computer Architecture](#)⁶⁸⁸¹), who worked on *HPX* in the context of the Google Summer of Code⁶⁸⁸² program 2014.
- Martin Stumpf ([Department of Computer Science 3 - Computer Architecture](#)⁶⁸⁸³), who rebuilt our contiguous testing infrastructure (see the [HPX Buildbot Website](#)⁶⁸⁸⁴). Martin is also working on [HPXCL](#)⁶⁸⁸⁵ (mainly all work related to [OpenCL](#)⁶⁸⁸⁶) and implementing an *HPX* backend for [POCL](#)⁶⁸⁸⁷, a portable computing language solution based on [OpenCL](#)⁶⁸⁸⁸.
- Grant Mercer ([University of Nevada, Las Vegas](#)⁶⁸⁸⁹), who helped creating many of the parallel algorithms (as proposed by [N4313](#)⁶⁸⁹⁰).
- Damond Howard ([Louisiana State University \(LSU\)](#)⁶⁸⁹¹), who works on [HPXCL](#)⁶⁸⁹² (mainly all work related to [CUDA](#)⁶⁸⁹³).
- Christoph Junghans (Los Alamos National Lab), who helped making our buildsystem more portable.
- Antoine Tran Tan (Laboratoire de Recherche en Informatique, Paris), who worked on integrating *HPX* as a backend for [NT2](#)⁶⁸⁹⁴. He also contributed an implementation of an API similar to Fortran co-arrays on top of *HPX*.
- John Biddiscombe ([Swiss National Supercomputing Centre](#)⁶⁸⁹⁵), who helped with the BlueGene/Q port of *HPX*, implemented the parallel sort algorithm, and made several other contributions.
- Erik Schnetter (Perimeter Institute for Theoretical Physics), who greatly helped to make *HPX* more robust by submitting a large amount of problem reports, feature requests, and made several direct contributions.
- Mathias Gaunard (Metascale), who contributed several patches to reduce compile time warnings generated while compiling *HPX*.
- Andreas Buhr, who helped with improving our documentation, especially by suggesting some fixes for inconsistencies.

⁶⁸⁷⁸ <https://github.com/STELLAR-GROUP/hpxcl/>

⁶⁸⁷⁹ <https://www.cct.lsu.edu>

⁶⁸⁸⁰ <http://wg21.link/n4313>

⁶⁸⁸¹ <https://www3.cs.fau.de>

⁶⁸⁸² <https://developers.google.com/open-source/soc/>

⁶⁸⁸³ <https://www3.cs.fau.de>

⁶⁸⁸⁴ <http://rosta.cct.lsu.edu/>

⁶⁸⁸⁵ <https://github.com/STELLAR-GROUP/hpxcl/>

⁶⁸⁸⁶ <https://www.khronos.org/opencv/>

⁶⁸⁸⁷ <https://portablecl.org/>

⁶⁸⁸⁸ <https://www.khronos.org/opencv/>

⁶⁸⁸⁹ <https://www.unlv.edu>

⁶⁸⁹⁰ <http://wg21.link/n4313>

⁶⁸⁹¹ <https://www.lsu.edu>

⁶⁸⁹² <https://github.com/STELLAR-GROUP/hpxcl/>

⁶⁸⁹³ https://www.nvidia.com/object/cuda_home_new.html

⁶⁸⁹⁴ <https://www.numscale.com/nt2/>

⁶⁸⁹⁵ <https://www.cscs.ch>

- Patricia Grubel ([New Mexico State University](https://www.nmsu.edu)⁶⁸⁹⁶), who contributed the description of the different *HPX* thread scheduler policies and is working on the performance analysis of our thread scheduling subsystem.
- Lars Viklund, whose wit, passion for testing, and love of odd architectures has been an amazing contribution to our team. He has also contributed platform specific patches for FreeBSD and MSVC12.
- Agustin Berge, who contributed patches fixing some very nasty hidden template meta-programming issues. He rewrote large parts of the API elements ensuring strict conformance with the C++ ISO Standard.
- Anton Bikineev for contributing changes to make using `boost::lexical_cast` safer, he also contributed a thread safety fix to the `iostreams` module. He also contributed a complete rewrite of the serialization infrastructure replacing `Boost.Serialization` inside *HPX*.
- Pyry Jähkölä, who contributed the Mac OS build system and build documentation on how to build *HPX* using Clang and `libc++`.
- Mario Mulansky, who created an *HPX* backend for his `Boost.Odeint` library, and who submitted several test cases allowing us to reproduce and fix problems in *HPX*.
- Rekha Raj, who contributed changes to the description of the Windows build instructions.
- Jeremy Kemp how worked on an *HPX* OpenMP backend and added regression tests.
- Alex Nagelberg for his work on implementing a C wrapper API for *HPX*.
- Chen Guo, helvihartmann, Nicholas Pezolano, and John West who added and improved examples in *HPX*.
- Joseph Kleinhenz, Markus Elfring, Kirill Kropivnyanskiy, Alexander Neundorff, Bryant Lam, and Alex Hirsch who improved our CMake.
- Tapasweni Pathak, Praveen Velliengiri, Jean-Loup Tastet, Michael Levine, Aalekh Nigam, HadrienG2, Prayag Verma, Islada, Alex Myczko, and Avyav Kumar who improved the documentation.
- Jayesh Badwaik, J. F. Bastien, Christoph Garth, Christopher Hinz, Brandon Kohn, Mario Lang, Maikel Nadolski, pierrele, hendrx, Dekken, woodmeister123, xaguilar, Andrew Kemp, Dylan Stark, Matthew Anderson, Jeremy Wilke, Jiazheng Yuan, CyberDrudge, david8dixon, Maxwell Reeser, Raffaele Solca, Marco Ippolito, Jules Penuchot, Weile Wei, Severin Strobl, Kor de Jong, albestro, Jeff Trull, Yuri Victorovich, and Gregor Daiss who contributed to the general improvement of *HPX*.

*HPX Funding Acknowledgements*⁶⁸⁹⁷ lists current and past funding sources for *HPX*. Special thanks to [Google Summer of Code](https://developers.google.com/open-source/soc/)⁶⁸⁹⁸ and [Google Season of Docs](https://developers.google.com/season-of-docs)⁶⁸⁹⁹ for the continuous support they provide which helps us enhance both our code and our documentation.

⁶⁸⁹⁶ <https://www.nmsu.edu>

⁶⁸⁹⁷ <https://hpx.stellar-group.org/funding-acknowledgements/>

⁶⁸⁹⁸ <https://developers.google.com/open-source/soc/>

⁶⁸⁹⁹ <https://developers.google.com/season-of-docs>

INDEX

- genindex